An applied Perspective: Estimating the Differential Identifiability Risk of an Exemplary SOEP Data Set

1 st Allmann, Jonas *Technische Universitat Berlin ¨ j.allmann@campus.tu-berlin.de*

2nd Nuñez von Voigt, Saskia *Technische Universitat Berlin ¨ saskia.nunezvonvoigt@tu-berlin.de*

3 rd Tschorsch, Florian *Technische Universitat Dresden ¨ florian.tschorsch@tu-dresden.de*

Abstract—Using real-world study data usually requires contractual agreements where research results may only be published in anonymized form. Requiring formal privacy guarantees, such as differential privacy, could be helpful for data-driven projects to comply with data protection. However, deploying differential privacy in consumer use cases raises the need to explain its underlying mechanisms and the resulting privacy guarantees. In this paper, we thoroughly review and extend an existing privacy metric. We show how to compute this risk metric efficiently for a set of basic statistical queries. Our empirical analysis based on an extensive, real-world scientific data set expands the knowledge on how to compute risks under realistic conditions, while presenting more challenges than solutions.

1. Introduction

As part of the German Socio-Economic Panel Study (SOEP), tens of thousands of individuals in thousands of households have been and are surveyed each year. The SOEP is the largest and longest-running multidisciplinary long-term study in Germany. The study is conducted annually since 1986 by the German Institute for Economic Research *DIW* [\[1\]](#page-7-0), [\[7\]](#page-7-1). Even under the assumption that the data is handled properly by every single research team and the raw data set is never leaked outside authorized circles, aggregate statistics computed from it are regularly released as part of SOEP-based research publications. However, even precise aggregate statistics can pose a privacy risk [\[4\]](#page-7-2).

Differential privacy [\[4\]](#page-7-2) is a prominent privacy framework to technically and verifiably protect the data from re-identification attacks in published statistics. The main concern with differential privacy is the trade-off between data utility and privacy. It is generally easier to achieve strong privacy guarantees (by choosing a small ε) in combination with high data utility when a data set is large, making the SOEP an interesting candidate for a meaningful implementation of differential privacy.

Even though the optimization of the privacy-utility trade-off is still a major challenge, we focus on how to effectively communicate this notion of privacy protection to participants. There remain risks to privacy even after its implementation, and the guarantees it provides are not trivial to understand, even for trained professionals [\[12\]](#page-7-3). Differential privacy relies on statistical and probabilistic mechanisms and its precise guarantees depend on configurable parameters, as well as on the data being processed and the type of analysis being performed.

While the overall interpretation of the privacy guarantee provided by differential privacy is intuitive, the risk implications of specific values of ε are more challenging to understand. One approach to making the privacy parameter of differential privacy more comprehensible is to translate ε into a corresponding privacy risk, expressed as a risk of individual identifiability [\[9\]](#page-7-4), [\[11\]](#page-7-5). This privacy risk metric depends not only on ε , but also on the data that is processed and the statistical query [\[9\]](#page-7-4). However, it is not clear how such risk metrics perform under real-world conditions, which is a crucial step towards making risk communication formats viable for practical applications.

The major goal of this paper is to look at the concept of the privacy risk metric from an applied perspective. We investigate the interaction of the risk metric of Lee and Clifton [\[9\]](#page-7-4) with an SOEP data set. Our results show that precise risk calculations depend heavily on the actual data involved, on extreme values and, not least, on the number of individuals included in a database and in specific query results. To extend the current knowledge of how practical risk metrics for differential privacy are under real world conditions, it seems necessary to intensify the investigation of these aspects.

The paper's contribution and structure can be summarized as follows: In Section [2,](#page-0-0) we provide essential knowledge about differential privacy and its core concepts, and present an existing risk metric published by Lee and Clifton. In Section [3,](#page-2-0) we extend the risk metric to a wider range of query types and show how to calculate the risk for an SOEP data set. We present the results of our empirical evaluation in Section [4.](#page-3-0) We summarize the challenges that remain by calculating the differential privacy risk for a real world data set in Section [5.](#page-6-0) Lastly, we review related work in Section [6](#page-6-1) and conclude our paper with a brief outlook in Section [7.](#page-7-6)

2. Differential Privacy and Risk Model

Our research is based on the following context: We assume that descriptive statistics of SOEP variables are to be published as part of a data-driven research project. The sensitive nature of the SOEP data calls for guarantees like the ones differential privacy provides. Using the Laplace mechanism, controlled noise is added to the query results (cf. Section [2.1.1\)](#page-1-0). The associated privacy risk is published alongside the results, as we assume a scenario where the data has already been collected anyway. A challenge in this context is calculating this associated privacy risk. To this end, we describe in Section [2.2](#page-1-1) risk metrics relying on an approach of Lee and Clifton [\[9\]](#page-7-4).

2.1. Differential Privacy

Differential privacy is supposed to protect individuals by making any two databases differing in one individual statistically indistinguishable. For potential data subjects, e.g. in the SOEP data set, that means that adding their data to the database, should not affect what can or cannot be learned about them as an individual [\[4\]](#page-7-2). A differentially private mechanism M provides differential privacy for its query result q, for all neighboring database instances X and X' that differ in one single element:

$$
P[M(X) = q] \le e^{\varepsilon} \cdot P[M(X') = q]. \tag{1}
$$

P is the probability operator and ε is the so-called privacy parameter. It balances privacy and utility in any differential privacy implementation.

The parameter ε captures the allowed distance between the probabilistic output distributions of the mechanism M when applied to databases X and X'. If ε is small, the tolerable difference in probability is also small, and the privacy level is high. A larger allowed distance between the output distributions, makes the impact on query results of a single individual more clearly discernible. This diminishes the level of privacy protection. At the same time, utility of the output is increased, as less noise needs to be added to the query result.

2.1.1. Laplace Mechanism. Several mechanisms exist to achieve differential privacy in practice. In the most common case, differences in raw query outputs are masked by a calibrated amount of random noise, added before a query result is released. For example, we add an amount of noise to the average hours spent of paid work querying the SOEP data set. The most commonly used source of noise is the Laplace distribution. It is calibrated to the privacy parameter ε and the global sensitivity $\Delta f()$ of a query function f.

2.1.2. Global Sensitivity. The global sensitivity Δf of a query function f over a data universe U is defined as the largest possible difference in function value between two neighboring inputs taken from U:

$$
\Delta f(U) = \max_{X, X' \subset U, h(X, X') = 1} (|f(X) - f(X')|). \tag{2}
$$

The global sensitivity can usually be computed if the data universe is known, sometimes even without that condition. A simple *count* query, for example, always has a global sensitivity of one, since adding or removing a single entry from a database can only increase or decrease any *count* by one. For many other queries, global sensitivity under a known universe of values can be derived analytically and it can be much larger than one for other queries, especially in the presence of outliers.

2.1.3. Local Sensitivity. A major disadvantage of global sensitivity is, depending on the data universe and the specific query function, it often leads to the addition of much more noise than is actually necessary to make a specific query differentially private. To partially circumvent the disadvantages of global sensitivity, local sensitivity was introduced. The central idea of local sensitivity is to take into account the actual function value of a given data set or a given query result and measure the distance in function value to any possible neighbour data set. Δv will be used as notation for the local sensitivity of a query function f from here on:

$$
\Delta v(U, X) = \max_{X, X' \subset U, h(X, X') = 1} (|f(X) - f(X')|). \tag{3}
$$

Here, additionally to the data universe U , local sensitivity depends on a given subset $X \subset U$. Sensitivity is measured against any possible neighbouring set $X' \subset U$. This approach can lead to drastically reduced amounts of noise needed, since function sensitivity is often much smaller locally than the global worst-case sensitivity [\[13\]](#page-7-7).

In the contruction of the risk metrics presented in the next section, global sensitivity is assumed as the reference parameter to calibrate noise, while local sensitivity represents the potential influence of a data subject on query results in a specific situation.

2.2. Risk Metrics

This section will turn to the question of calculating risks for a given differentially private system. We will rely heavily on an approach by Lee and Clifton [\[9\]](#page-7-4). The risk metric of Lee and Clifton calculates, for the Laplacian noise mechanism, a suitable ε to guarantee that the risk of a successful membership inference attack remains under a given threshold. From here on, this metric will be referred to as ρ_{mw} for many worlds, a name that will become clear later. It is calculated as follows:

$$
\rho_{mw} \le \frac{1}{1 + (n - 1)e^{-\frac{\varepsilon \Delta v}{\Delta f}}}.\tag{4}
$$

Here, n denotes the total number of subjects in the data set at hand, Δv denotes the local sensitivity of the query function and Δf its global sensitivity. Local sensitivity should always be smaller or equal to global sensitivity, and therefore $0 < \frac{\Delta v}{\Delta f} \le 1$ should always hold. The ε , as usual, is the chosen privacy parameter and ρ_{mw} is the risk of being identified as present or absent in the database.

When *n* is large, ρ_{mw} can become much smaller than 0.5. The attacker of Lee and Clifton does not try to decide between presence or absence of one individual. Instead, the number of individuals in a database is known, and the attacker tries to find out, which individuals from a known universe of data subjects are included. Finding the 'true' database becomes a lot harder than just deciding between presence or absence of one individual, and the obtained tracing risk can be dramatically smaller than 0.5. Very broadly, the risk measure ρ_{mw} is small when the number of subjects n is large, because more 'possible worlds' need to be assumed by an attacker. It is small when ε is small, because a smaller ε demands larger amounts of noise. And finally it is small when Δv is much smaller than Δf , because smaller local changes in function value are hidden by the larger amounts of noise demanded by large global sensitivity.

The parameters needed to calculate ρ_{mw} are not necessarily available in every given scenario. Especially local and global sensitivity require knowledge about the data universe and the data set at hand, that might be missing at the point in time when the risk is calculated. In the context of our scenario, it would be impossible to communicate a risk based on this metric to participants before any data is collected. Precise risk computation and communication would only become possible after the participants' decision to share their data has been made. This dilemma is addressed by modified versions of the above metric.

Mehner et al. [\[11\]](#page-7-5) propose a simplified risk metric based on the metric presented above. Their worst-case risk metric requires fewer parameters to be calculated, resulting in reduced precision, but giving more flexibility in practice. Specifically, this approach avoids the assumption of knowing the data universe in advance and being able to calculate precise values for global and local sensitivity. Assuming instead the worst case ratio of these two sensitivities $(\Delta v/\Delta f = 1)$ and number of possible worlds $(n = 2)$ gives the maximum global privacy risk, referred to here as ρ_{al} :

$$
\rho_{gl} = \frac{1}{1 + e^{-\varepsilon}}.\tag{5}
$$

In contrast to the simplified metric proposed by Mehner et al. [\[11\]](#page-7-5), in this paper we suggest a new metric that keeps the fraction between local and global sensitivity as an important factor influencing the risk for a given data set. For the size of the data set it assumes the worst-case parameter $n = 2$, resulting in:

$$
\rho_{tw} \le \frac{1}{1 + e^{-\frac{\varepsilon \Delta v}{\Delta f}}}.\tag{6}
$$

Our newly proposed metric will be called the two-worlds metric from here on, as opposed to the many-worlds metric that was proposed by Lee and Clifton.

3. Procedure for Risk Estimation

It becomes clear that publishing differentially private statistics with precisely bounded risks not only requires an adequate choice of ε , but also detailed knowledge of sensitivities. The difficult task of choosing ε is usually focused on when investigating the privacy-utility tradeoff. Instead, we turn our attention the question of how sensitivities influence risk and help estimating it, which will be the topic of this section. Through a critical review of the presented privacy metrics we highlight and examine the assumptions that such risk estimates are based on.

For clarity, we introduce an example: We intend to publish differentially private statistics for the distancework variable. In Table [1](#page-3-1) we provide an excerpt from that column from the SOEP data set. Note that the index column is only introduced to facilitate referencing.

3.1. Assumptions of Risk Definition

Even with the simple definition of global and local sensitivity, subtleties arise regarding the notion of *neighbouring* databases that are decisive when calculating the sensitivity. In some cases, neighbouring databases means that a single value can be added or removed from a database to obtain a neighbouring database. In other cases, it is assumed that a single value can be altered or replaced, leaving the total number of entries unchanged. These different interpretations are referred to as *unbounded* and *bounded* differential privacy, respectively [\[10\]](#page-7-8).

Lee and Clifton define two databases as neighbours if one can be obtained from the other by adding or removing exactly one individual of the data set. The two databases therefore differ in size by exactly one row and the smaller one is a subset of the larger one.

The model of Lee and Clifton assumes that sensitivities are computed only between non-empty databases. However, it is entirely possible to construct filter queries that return an empty data set. Therefore, it can be argued that global sensitivity formulas should take empty data sets into account. We argued that global sensitivity, as the sole source of noise in our construction, is already likely to be overly large. Only considering data sets with at least one member can be seen as an attempt to limit global sensitivity. While this decision is debatable, it is very unlikely that changing it would have a strong effect on the overall risk patterns and the parameter interactions we will point out in our analysis.

3.2. Sensitivity Calculation

The global sensitivity is not always known before data collection and must therefore often be estimated. Even with a data set as large as the SOEP data set, computing the "true" global sensitivity of a query function remains conceptually impossible. There can be no guarantee that the most extreme values existing in the overall population are present in the SOEP data set. For some variables it is possible to determine extreme values theoretically, for example if a questionnaire item starts with 'How many hours per day...', guaranteeing values between 0 and 24 after implausible survey responses are filtered out. Other variables, like the commuting distance in our example, can vary almost indefinitely and have no specific bounds. To still be able to calculate sensitivities, we treat all values we have as our universe. Distances between 1 and 675 become the practical bounds for commuting distance, and based on these bounds sensitivities are calculated individually per query type.

Mean. Assuming that a valid data set always contains at least one entry, the largest difference in mean between any two neighbouring databases is between one that contains either the largest or the smallest value of the universe U , and one that contains both. As a result, the global sensitivity of the mean query is equal to half the distance between the largest and the smallest value of the universe.

Referring to the example data in Table [1,](#page-3-1) we are talking about the values 1 and 675. Removing any of the two from such a size 2 database increases or decreases the *mean* value by 337. This is the largest possible change between any two databases from the universe Table [1a,](#page-3-1) representing the global sensitivity of the *mean* query.

For both the two-worlds and the many-worlds risk, we also need to calculate local sensitivity for a given data sample taken from the universe. It represents the largest possible local influence any individual from the universe can have on a query result calculated from this sample.

Local sensitivity for a given multiset X from the universe U is obtained by comparing four cases. The *mean* value of X undergoes the largest local change by either adding the largest or the smallest value of the universe, or by removing the largest or the smallest value currently in

TABLE 1: Exemplary data set of *distance-work*.

(b) Neigbouring data set without maximum

the sample. The largest absolute difference between these four cases from the initial *mean* value is equal to the local sensitivity $LS_{mean}(U, X)$.

(a) Complete data set

Again referring to our example and considering Table [1b](#page-3-1) as our sample X, the *mean* value changes from 7.75 to 141.2 by including the value 675. No larger difference in *mean* can be achieved by adding or removing any other value, resulting in a local sensitivity of 133.45 for data set Table [1b](#page-3-1) under universe Table [1a.](#page-3-1)

Median. Similar to the mean, sensitivity of the median query is largest for databases containing only the largest and the smallest value from the universe U. Adding or removing a single value from a database, the largest possible jump in the median function is between $min(U)$ or $max(U)$ and half the distance between $min(U)$ and $max(U)$, in any direction.

Local sensitivity of the median can be determined by shifting the current median of a given multiset X from the universe U one position to the right or to the left. This can be achieved by either adding/removing a value higher than the initial median, e.g. the largest value from the universe, and then determining the median of the resulting set. Local sensitivity is equal to the maximum absolute difference to the initial median between these two cases. Adding or removing the smallest values from the universe or the subset, respectively, would give an equivalent result. With Table [1a](#page-3-1) our initial median is 10. With a sample like Table [1b](#page-3-1) we obtain a median of 6.5 and with Table [1c](#page-3-1) 13.5, resulting in a maximal difference of 3.5.

Min and Max. Assuming that a valid database always contains at least one value, the largest difference in the minimum/maximum value is equal to the distance between the smallest and the largest value from the universe U. Given a database that only contains the smallest value, adding the largest value leads to this largest possible jump.

Given a multiset X from the universe U , the minimum/maximum value can only be influenced by either removing the smallest/largest value from the multiset, or by adding a smaller/larger value from the universe U that is not yet contained. In the latter case, adding the smallest/largest value from the universe will maximize the difference. Comparing the absolute differences of both cases gives the local sensitivity for the max and min query.

Variance. The variance of a distribution is defined as the mean squared difference from the mean over all values of a sample. The largest difference in variance between two neighbouring databases is observed between one that contains two values, the largest and the smallest from the universe U, and one where either of these two is removed. For the first database the variance is at a global maximum

for the given universe. Adding any values in between the extremes or adding uneven amounts of the two extreme values can only decrease the variance. Thus, the global sensitivity is equal to half the squared distance between the largest and smallest value of the universe.

(c) Neigbouring data set without minimum

Working with the example data from Table [1,](#page-3-1) we obtain a sample of maximum variance of 113569 by including only the values 1 and 675. Removing any of the two values gives a variance of 0, leaving us with a global sensitivity of the *variance* query of 113569 under universe Table [1a.](#page-3-1)

To calculate the local sensitivity, we proceed in the same way as for the other queries. The variance should always be influenced the strongest by adding extreme values to or removing them from a database. Given a multiset X from the universe U , we first compute the current variance of X . Then we either add one of the extreme values from the universe or remove one of the extreme values from X . Determining the largest absolute difference from the initial variance between these four cases gives us the local sensitivity. Regarding our example, the variance of Table [1b](#page-3-1) and of Table [1c](#page-3-1) is 1838.75 and 76737, respectively. Thus, the local sensitivity, as the maximum difference to our initial variance, is 111730.25.

4. Empirical Evaluation of Risk Metrics

The goal of our evaluation is to investigate the interaction of the privacy risk of Lee and Clifton [\[9\]](#page-7-4) with the SOEP data set. Thus, we obtain some initial insight into the concrete risk levels that could be communicated to participants of scientific studies similar to the SOEP.

The entire analysis results can be reproduced using the code in this repository $\frac{1}{1}$ $\frac{1}{1}$ $\frac{1}{1}$, This requires access to the SOEP data set, which is not included in the code repository.

4.1. SOEP Data Set and used Variables

For the SOEP study, around 30,000 people in around 15,000 households have been and are continued to be recruited across Germany. Participants in the study are surveyed annually to produce a large longitudinal data set. Individuals in the data set are superficially anonymized, i.e., direct identifiers are removed and replaced with a pseudonym. The data handling contract specifically forbids attempting to re-identify individuals in the data set. This fact and other measures, like the exclusion of precise geolocation data from the regular data set, show a basic awareness of the dangers that re-identification attacks pose for such detailed, superficially anonymized collections of sensitive individual data.

1. [https://git.tu-berlin.de/j](https://git.tu-berlin.de/j_allmann/master_thesis_code)_allmann/master_thesis_code

TABLE 2: Descriptive statistics of the numerical variables

variable (our label)	description		mın	max	mean	median	std
bjp_05_01 (work-hours) bip 82 01 (distance-work) bip 89 01 (monthly-incomeGross)	Average hours spent on paid work / weekday Distance to workplace Gross monthly income	25.238 14.734 16.594		675 2.7 M	5.35 15.07 3.432.00	2.500	4.38 19.90 21,669.00

The SOEP data can be considered highly susceptible to re-identification. It includes precise data about the family status of a person in the past and the present, the size and character of their home, their field of work and salary, including changes over time, some self reported medical diagnoses, and other highly individual and sensitive data.

The SOEP data set is not distributed as a single, unified database. It consists of dozens of individual files, some containing raw survey data and others containing preprocessed variables that are easier to handle than the raw data. For our analysis, we work with a small subset of the variables of the main SOEP questionnaire, limited to the year 2019, being one of the most recent complete years in the SOEP at the time of writing.

The data set has 1159 columns, the vast majority of which represent individual items or sub-items from the survey questionnaire. Around 30 columns contain metadata such as participant and household IDs, biographical information, and information about the interview procedure. Study participants in the SOEP are assigned a random person ID (pseudonym) that allows linkage of data across different tables, for example representing different survey years. The total number of unique person IDs in our chosen data set is 29905 of 19085 households interviewed in the 2019 survey period.

With our analysis, we attempt to include variables spanning different ranges, and statistical characteristics. The chosen variables should be either likely to be known to an attacker or considered sensitive to fit the narrative of an attacker aiming to identify an individual and subsequently learn sensitive facts about them. As a result, we selected the variables listed in Table [2.](#page-4-0) Our selected variables are numerical, since the majority of query types we examine only make sense on numerical variables.

4.2. Procedure

For each variable, listed in Table [2,](#page-4-0) we estimate the two-worlds risk ρ_{tw} and compare it to the many-worlds risk ρ_{mw} and global risk ρ_{ql} . First, negative values representing missing values in the SOEP data set are removed. Obviously, each variable already represents a sample taken from the much larger universe that is the general population. However, for our purpose we treat each variable as its own universe, since for us these are all the values we know can exist. We treat all available positive values as our data universe as explained in Section [3.2.](#page-2-1) Thus we use the maximum value in the data set as the global maximum. The global minimum value is set to 0 if it is a valid answer for the specific variable.

We calculate the risk for all our presented query types with different values of ε . To evaluate the influence of the data characteristics, we iterate over a set of sample sizes that are taken from the universe of each variable. Since each variable contains a different number of valid values,

and they differ substantially in size, the size of the subsets is different for each variable. Due to its randomness, we repeat each experiment 100 times.

Global sensitivity is based on the whole variable representing the universe, local sensitivity is computed from the respective sample and the universe as explained in Section [3.2.](#page-2-1) We compute the many-worlds risk ρ_{mw} , the two-worlds risk ρ_{tw} and the global risk ρ_{gl} that does not factor in the sample size.

4.3. Results

Comparison of Risk Metrics. The differences in risk between the many-worlds metric (ρ_{mw}) and the twoworlds risk (ρ_{tw}) are striking. While the two-worlds risk can never go below 0.5, the risk computed with the many-worlds formula can become arbitrarily small with increasing sample size. Comparing these two metrics is not a question of which one is better, but which one is easier justified under a specific interpretation of the definition of differential privacy.

Small risks resulting from the assumptions underlying the many-worlds metric give a false impression of safety as long as the sample size is large enough. The two-worlds metric captures the assumption that only the presence or absence of a single individual is unknown to an attacker. This fact can always be guessed, and the risk of identification for an individual is always between 0.5 and 1, the latter meaning that an attacker can determine the presence or absence of an individual with absolute certainty.

We can directly compare ρ_{mw} and ρ_{tw} . Comparing these the two metrics in Figure [1](#page-5-0) it becomes clear, how important it is to thoroughly review assumptions and definitions underlying a risk metric to arrive at meaningful and comparable results. While the differences in the construction of the two metrics are subtle, the resulting numbers are worlds apart. Any attempt at successfully educating users about differential privacy will have to deal with these ambiguities. Therefore, we consider the ρ_{tw} to be more accurate.

The worst-case risk (ρ_{gl}) , as already mentioned in [\[11\]](#page-7-5), represents a robust upper bound for the tracing risk of a differentially private system. With $\varepsilon = 1$, the worst-case risk results in $\rho_{ql} = 0.731$. This metric, with its advantage of relying only on ε and not requiring any knowledge of the data universe, can be considered a very useful tool under certain circumstances.

Influence of Query Type. The effects of the query type are also visible in Figure [1b.](#page-5-1) Regardless of the variable, the risks for the query *max* varies more. The *max* query shows a complex pattern of risk values overall spanning the whole range of possible risks. The *min* query, however, stays in average below a risk of $\rho_{tw} = 0.51$ for the variable *work-hours*. For the other two variables the risk

(a) Many-worlds risk. (b) Two-worlds risk.

Figure 1: Comparison of many-worlds risk and two-worlds risk with $\varepsilon = 1$.

is around 0.5. This contrast is especially surprising as *min* and *max* appear to be very similar queries, operating symmetrically on opposite ends of a sample distribution. The reason for this observation then must lie in an interaction with the underlying data. Consulting Table [2,](#page-4-0) the variable *distance-work* captures participant's commuting distance. As can be expected intuitively, it is a rather bottom heavy distribution with outliers at the upper end. Most people tend to live close to their workplace, and only few travel very far. Under these conditions, it is likely that even in small samples at least some very small values are present and local sensitivity of the *min* query is small. At the same time, local sensitivity for the *max* query can frequently be large, when none of the large outlier values is present in a sample. Any of the outliers entering such a database is at high risk of being identified.

Influence of Sample Size. In Figure [2](#page-6-2) we provide the risks for our selected variables with the sample proportion on the x-axis for the *max* query.

The influence of sample size on risk unfolds in two different ways, depending on the risk metric that is observed. For the many-worlds metric, sample size has a direct and drastic effect. Under the assumptions of this metric, the number of possible worlds an attacker has to consider, depends on the number of entries in a database. More possible worlds result in a smaller overall risk for each individual, an effect represented by the factor n in the denominator of the risk Equation [\(4\)](#page-1-2). This is visible in Figure [2a](#page-6-3) for $\varepsilon = 10$. Very small sample sizes, ρ_{mw} approaches the worst case of 1, while large sample sizes keep this risk at values below $\rho_{mw} = 0.01$ even for a large value $\varepsilon = 10$.

In Figure [2b](#page-6-3) we see that ρ_{tw} only decreases slightly, as the influence of sample size is only indirect. As in this case only two possible worlds are considered, the latter does not directly factor into ρ_{tw} . An indirect effect can be observed through a connection between sample size and local sensitivity. Most queries are less locally sensitive on a larger sample, because query functions like *mean*, *variance*, or *median* are intuitively more stable in larger samples if only few individuals change. A similar observation can be made for the *min* and *max* queries. In larger samples, it becomes less likely that the minimum or maximum value in the sample and, respectively, the minimum or maximum value in the universe are far apart, which would result in high local sensitivity.

In summary, sample size has a strong effect on risk under many conditions. It is most striking for the manyworlds risk metric, where it is an explicit component of the formula and leads to risks that are orders of magnitude smaller than even theoretically possible under the twoworlds metric. For the latter, sample size affects risk indirectly through its influence on local sensitivity.

Influence of Epsilon. The privacy parameter ε has the most direct influence on risk in differential privacy. It is the central parameter balancing privacy against utility. Generally, a larger ε allows for larger differences between two neighbouring databases, which reduces the required amount of noise. As a direct result, the risk of being identified increases for each data subject, by allowing an attacker a larger knowledge gain through each noisy query result they obtain. This effect is visible in Figure [2.](#page-6-2) Under certain conditions, epsilon becomes the only parameter influencing risk. In cases where local and global sensitivity are equal, the risk metric is reduced to the global risk metric taking ε as its only parameter.

There is also an interaction with ε and the sample proportion. Sample size only plays a role in a certain region of ε values, while losing its effect at very small and at very large ε , where risk generally approaches the minimum or maximum values of $\rho_{tw} = 0.5$ or $\rho_{tw} = 1$, respectively.

Summary of Findings. The privacy parameter ε has the strongest and most predictable effect on risk. The effects of other parameters are usually most strongly pronounced in this critical window, while they tend to vanish for very large or very small ε .

The magnitude of the sample size effect is harder to specify than it is for ε . In general, this means that reliable risks could only be communicated to the data subjects of a differentially private system if the number of participants can be estimated in advance. Even then, queries filtering out small subsets of users would present greater risks than statistics computed over the entire user base of a system.

A robust risk value can only be computed if sample sizes are guaranteed to be at least of a certain size. While we refrain from quantifying such a lower bound, this requirement for computing reliable risk metrics appears manageable.

(a) Many-worlds risk (b) Two-worlds risk

Figure 2: Risks with varying sample proportion and ε for *max* query and variable *distance work*.

5. Discussion

The overarching goal of our case study is to show how a differential privacy risk metric is under real world conditions. We discuss our results from two angles. Firstly, we reflect on the stability of the risk metric, and secondly, we discuss the general suitability of using the proposed metric to communicate the privacy guarantees.

5.1. Stability of the Risk Metric

Under changing calibrating noise. Local sensitivity often allows adding much smaller amounts of noise, especially for larger numbers of participants [\[13\]](#page-7-7). This directly leads to an increase in query precision and therefore in data utility. However, as Nissim et al. pointed out [\[13\]](#page-7-7), local sensitivity itself leaks information about the values included in the data set. The authors propose a remedy for this problem in the form of smooth sensitivity. Smooth sensitivity attempts to compute a smooth upper bound for local sensitivity, ensuring that the information leaked by the local sensitivity computation itself is limited.

At the centre of the Lee and Clifton risk formula, however, and in turn also of our modified risk formula, lies the assumption that noise is simply calibrated to global sensitivity. The fraction between global and local sensitivity crucially influences the risks computed with both metrics. If noise were to be calibrated to (smooth) local sensitivity, this fraction would approach or become 1, leaving us with the worst-case global privacy risk [5.](#page-2-2) This is very important to note, since it directly connects risk and utility optimization in an opposing manner. It also reinforces the notion that the worst-case metric, however crude it may appear, might be the most viable metric in practical application scenarios.

For composite queries. Data analysis rarely consists in one single, isolated query. The risks depicted in our plots represent risks for single, simple queries against single, isolated variables. In reality, data analysts usually query a data set many times, using composite queries that usually involve more than one variable. One of the very elegant features of differential privacy is the composition theorem, which states, that generally the ε -values of repeated queries add up [\[8\]](#page-7-9). It can be assumed that the risks calculated here behave similarly, and that a risk budget granted to a data analyst is a viable concept. If a certain risk budget was allocated and communicated to end users, it would be important for an analyst to know how strongly different queries and combinations of queries use up this budget. Our results can help inform practical methods to compute such information in realistic scenarios.

5.2. Suitability for Communicating Risks

The effects of the different parameters on risk could be demonstrated and analysed in previously not achieved levels of detail. Detailed risk metrics could prove useful in situations where the necessary parameters are known, while worst case estimates could serve as a fallback whenever this is not the case. How to turn these different metrics into viable information formats to communicate the risk is an open question.

The notion of a 50% privacy risk before even making any decision to participate or not, as implied by the two-worlds metric, is already not very intuitive [\[6\]](#page-7-10). Successfully conveying the fact that subtle differences in the construction of the metric can lead to risks in the order of fractions of a percent, seems unrealistic at best. A road out of this dilemma might lie in using the metrics only for comparing different systems, instead of trying to communicate absolute risks. Being able to state that one system has a less risky parameter set than a competing one appears possible even despite the complex nature of the risk metrics that became apparent in our analysis.

6. Related Work

While there has been research on communicating the mechanisms behind differential privacy [\[2\]](#page-7-11), [\[6\]](#page-7-10), [\[12\]](#page-7-3), [\[14\]](#page-7-12), [\[15\]](#page-7-13), the results are still scarce. Initial findings so far have indicated that the success of these explanations partly depends on prior knowledge and numeracy of participants, indicating the need for adaptive explanation formats [\[6\]](#page-7-10).

Cummings et al. [\[2\]](#page-7-11) have investigated the interaction between users' specific expectations towards a differentially private system and the way differential privacy is described, regarding their willingness to share data with the respective system. Results indicate that a precise description of differential privacy might not be enough to increase users' motivation to share data. Instead, the extent to which their individual privacy concerns can be addressed by differential privacy and the extent to which this is stressed in the description have a major influence on sharing behaviour.

Xiong et al. [\[15\]](#page-7-13) have made initial contributions to studying visual explanation formats. Their approach focuses on visualization of data utility and puts less emphasis on the visualization of remaining privacy risks, the opposite side of the privacy utility trade-off. Additionally, interactive communication designs are pointed out as a promising approach to investigate in the future.

For data subjects, risk can be assumed to be of larger importance than data utility. Unfortunately, quantifying these risks under realistic conditions has not been a research focus so far. Early work on concrete risks was published by Lee and Clifton [\[9\]](#page-7-4), and it was later picked up in the context of risk communication [\[6\]](#page-7-10). The coverage of this topic still appears unsatisfying.

While there are many case studies in which the reidentification risk of a large data set is determined [\[3\]](#page-7-14), in the area of differential privacy, this is rather limited. Example scenarios often consist of very small, artificial databases with few individuals and few variables that suffice to illustrate the mechanisms of differential privacy. These toy scenarios, however, often do not allow reasoning about the performance of a differentially private system under real world conditions.

Theoretical research often avoids discussing concrete parameter choices and points out, that ε , which balances privacy and utility against each other, needs to be chosen depending on the application context and the actual data involved [\[5\]](#page-7-15). Commercial actors, on the other hand, tend to be rather secretive about the exact implementation decisions and parameter choices of their systems. When such information is released, be it in research or in commercial contexts, a huge variance of presumably reasonable parameter choices emerges. This issue has been pointed out by Dwork et al. [\[5\]](#page-7-15), leading to the proposal of a public registry of such parameter choices to guide decisionmaking for future differential privacy applications.

In this context, reasoning about concrete individual risks forms an important part of the overall picture. This is where we pick up the thread in this paper and intend to narrow existing knowledge gaps about risks under differential privacy in realistic scenarios.

7. Conclusion and Outlook

In this paper, we conduct a case study to estimate risk metrics for differential privacy of an SOEP data set. Computing robust, meaningful risk estimates for a differentially private system as a whole is challenging. We discuss an existing differentially identifiability risk metric and highlight the need of some requirements, e.g., that an attacker can always guess the presence or absence of an individual with a probability of 50%. This metric, similar to its predecessors, depends on several factors, including the privacy parameter ε , the data that is handled, and the query that is applied to the data. Especially our evaluation with the SOEP data set shows that the influence of data characteristics and query type make it hard to obtain reliable risk values to communicate the risk beforehand. Falling back to the worst-case risk metric depending only on ε might be the only practical option here.

Our results can help form a more detailed picture of the performance of differentially private systems, both for professionals as for untrained end users. Identifying particularly queries with higher risks and particularly vulnerable attributes should also become easier building on the results and the methodology presented here. This could lead to more fine-grained calibration techniques for complex analyses, possibly increasing data utility while keeping data subjects better informed about how strongly their privacy is affected. Computing risks and situating them in real-world scenarios is hard, but with the results presented here it should have become easier.

References

- [1] D. I. W. Berlin. DIW Berlin: Data Access. Publisher: DIW Berlin.
- [2] Rachel Cummings, Gabriel Kaptchuk, and Elissa M. Redmiles. "I need a better description": An Investigation Into User Expectations For Differential Privacy. In *Proceedings of the 2021 ACM SIGSAC Conference on Computer and Communications Security*, pages 3037–3052, 2021. [arXiv:2110.06452](http://arxiv.org/abs/2110.06452) [cs].
- [3] Fida Kamal Dankar, Khaled El Emam, Angelica Neisa, and Tyson Roffey. Estimating the re-identification risk of clinical data sets. *BMC medical informatics and decision making*, 12(1):1–15, 2012.
- [4] Cynthia Dwork. Differential Privacy. In Michele Bugliesi, Bart Preneel, Vladimiro Sassone, and Ingo Wegener, editors, *Automata, Languages and Programming*, volume 4052 of *Lecture Notes in Computer Science*, pages 1–12, Berlin, Heidelberg, 2006. Springer Berlin Heidelberg.
- [5] Cynthia Dwork, Nitin Kohli, and Deirdre Mulligan. Differential Privacy in Practice: Expose your Epsilons! *Journal of Privacy and Confidentiality*, 9(2), 2019.
- [6] Daniel Franzen, Saskia Nuñez von Voigt, Peter Sörries, Florian Tschorsch, and Claudia Müller-Birn. "Am I Private and If So, how Many?" – Using Risk Communication Formats for Making Differential Privacy Understandable, 2022. [arXiv:2204.04061](http://arxiv.org/abs/2204.04061) [cs].
- [7] Jan Goebel, Markus M. Grabka, Stefan Liebig, Martin Kroh, David Richter, Carsten Schröder, and Jürgen Schupp. The German Socio-Economic Panel (SOEP). *Jahrbücher für Nationalökonomie und Statistik*, 239(2):345–360, April 2019.
- [8] Peter Kairouz, Sewoong Oh, and Pramod Viswanath. The Composition Theorem for Differential Privacy. *IEEE Transactions on Information Theory*, 63(6):4037–4049, 2017.
- Jaewoo Lee and Chris Clifton. How much is enough? choosing ϵ for differential privacy. In Xuejia Lai, Jianying Zhou, and Hui Li, editors, *Information Security, 14th International Conference, ISC 2011, Xi'an, China, October 26-29, 2011. Proceedings*, volume 7001 of *Lecture Notes in Computer Science*, pages 325–340. Springer, 2011.
- [10] Jaewoo Lee and Chris Clifton. Differential identifiability. In *Proceedings of the 18th ACM SIGKDD international conference on Knowledge discovery and data mining*, pages 1041–1049, Beijing China, 2012. ACM.
- [11] Luise Mehner, Saskia Nunez von Voigt, and Florian Tschorsch. Towards Explaining Epsilon: A Worst-Case Study of Differential Privacy Risks. In *2021 IEEE European Symposium on Security and Privacy Workshops (EuroS&PW)*, pages 328–331, Vienna, Austria, 2021. IEEE.
- [12] Priyanka Nanayakkara, Johes Bater, Xi He, Jessica Hullman, and Jennie Rogers. Visualizing Privacy-Utility Trade-Offs in Differentially Private Data Releases, 2022. [arXiv:2201.05964](http://arxiv.org/abs/2201.05964) [cs].
- [13] Kobbi Nissim, Sofya Raskhodnikova, and Adam Smith. Smooth sensitivity and sampling in private data analysis. In *Proceedings of the thirty-ninth annual ACM symposium on Theory of computing - STOC '07*, page 75, San Diego, California, USA, 2007. ACM Press.
- [14] Alexandra Wood, Micah Altman, Aaron Bembenek, Mark Bun, Marco Gaboardi, James Honaker, Kobbi Nissim, David O'Brien, Thomas Steinke, and Salil Vadhan. Differential Privacy: A Primer for a Non-Technical Audience. *SSRN Electronic Journal*, 2018.
- [15] Aiping Xiong, Chuhao Wu, Tianhao Wang, Robert W. Proctor, Jeremiah Blocki, Ninghui Li, and Somesh Jha. Using Illustrations to Communicate Differential Privacy Trust Models: An Investigation of Users' Comprehension, Perception, and Data Sharing Decision, 2022. [arXiv:2202.10014](http://arxiv.org/abs/2202.10014) [cs].