NUMERICAL STABILIZATION METHOD BY SWITCHING TIME-DELAY

KAÏS AMMARI AND STÉPHANE GERBI

ABSTRACT. In this paper, we propose a new numerical strategy for the stabilization of evolution systems. The method is based on the methodology given by Ammari-Nicaise-Pignotti in [10]. This method is then implemented in 1D by suitable numerical approximation techniques. Numerical experiments complete this study to confirm the theoretical announced results.

Contents

1.	Introduc	tion	1				
2.	Well-pos	edness	3				
	2.1.	General case	3				
	2.2.	Bounded case	6				
3.	Asympto	tic behavior	8				
4.	Numerica	al approximation in 1D	11				
	4.1.	Boundary case	12				
	4.2.	Internal case	16				
	4.3.	Pointwise case	19				
5.	Numerica	al experiment and validation of the theoretical results in 1D	28				
	5.1.	The boundary case	28				
	5.2.	The internal case	28				
	5.3.	The pointwise case	29				
6.	Conclusi	on and perspectives	29				
Re	References						

1. INTRODUCTION

Delay effects arise in many applications and practical problems and it is well-known that an arbitrarily small delay may destabilize a system which is uniformly asymptotically stable in absence of delay (see e.g. [14, 16, 15], [24])). Nevertheless recent papers reveal that particular choice of delays may restitute exponential stability property, see [18, 19, 28].

We refer also to [1, 8, 9, 10, 11, 5, 24, 25] for stability results for systems with time delay due to the presence of "good" feedbacks compensating the destabilizing delay effect.

²⁰¹⁰ Mathematics Subject Classification. 35B35, 35B40, 93D15, 65M06, 65M08.

Key words and phrases. numerical stabilization with time-delay, switching control, numerical analysis and numerical study, finite difference method, finite volume method.

In this paper we propose a numerical approach that consists in stabilizing the abstract-wave system by a control law that uses information from the past (by switching or not). This means that the stabilization is obtained by a control method, see [10] for more details, and not by a feedback law. This strategy can provide a guide to the time-delay compensation scheme. For switching control (without delay) we refer to Zuazua [30].

Let H be a Hilbert space equipped with the norm $\||.\|_H$, and let $A : \mathcal{D}(A) \subset H \to H$ be a self-adjoint, positive and invertible operator. We introduce the scale of Hilbert spaces $H_{\alpha}, \alpha \in \mathbb{R}$, as follows: for every $\alpha \geq 0$, $H_{\alpha} = \mathcal{D}(A^{\alpha})$ with the norm $\|z\|_{\alpha} = \|A^{\alpha}z\|_H$. The space $H_{-\alpha}$ is defined by duality with respect to the pivot space H as $H_{-\alpha} = H_{\alpha}^*$ for $\alpha > 0$. The operator Acan be extended (or restricted) to each H_{α} such that it becomes a bounded operator

(1.1)
$$A: H_{\alpha} \to H_{\alpha-1} \text{ for } \alpha \in \mathbb{R}.$$

The second ingredient needed for our construction is a bounded linear operator $B : U \longrightarrow H_{-\frac{1}{2}}$, where U is another Hilbert space identified with its dual. The operator B^* is bounded from $H_{\frac{1}{2}}$ to U.

The system that we considered in this paper is given by the following abstract problem:

(1.2)
$$\ddot{u}(t) + Au(t) = 0, \quad 0 \le t \le T_0,$$

(1.3)
$$\ddot{u}(t) + Au(t) + \mu BB^* \dot{u}(t - T_0) = 0, \quad t \ge T_0,$$

(1.4)
$$u(0) = u_0, \dot{u}(0) = u_1,$$

where $T_0 > 0$ is the time delay, μ is a real number and the initial datum (w_0, w_1) belongs to a suitable space.

For this system we need to assume the closed-loop admissibility of the operator B^* (see for more details [9] and [27]), i.e. that for all T > 0 there exists C(T) > 0 such that

(1.5)
$$\left(\int_{0}^{T} \left\| B^{*} \dot{\phi}(s) \right\|_{U}^{2} ds \right)^{\frac{1}{2}} \leq C(T) \left\| (w_{0}, w_{1}) \right\|_{H_{\frac{1}{2}} \times H}$$

for all $(w_0, w_1) \in H_1 \times H_{\frac{1}{2}}$, $u \in L^2(0, T; U)$ and $\phi \in C([0, T], H_1) \cap C^1([0, T], H_{\frac{1}{2}})$ is the solution of the inhomogeneous evolution equation

(1.6)
$$\ddot{\phi}(t) + A\phi(t) = 0, \quad t \ge 0,$$

 $\phi(0) = w_0, \dot{\phi}(0) = w_1.$

To study the well-posedness of the system (1.2)-(1.4), we write it as an abstract Cauchy problem in a product Banach space, and use the semigroup approach. For this take the Hilbert space $\mathcal{H} := H_{\frac{1}{2}} \times H$ and the unbounded linear operators

(1.7)
$$\mathcal{A}: \mathcal{D}(\mathcal{A}) = H_1 \times H_{\frac{1}{2}} \subset \mathcal{H} \longrightarrow \mathcal{H}, \ \mathcal{A} \begin{pmatrix} u_1 \\ u_2 \end{pmatrix} = \begin{pmatrix} u_2 \\ -Au_1 \end{pmatrix}$$

and

(1.8)
$$\mathcal{A}_{d}: \mathcal{D}(\mathcal{A}_{d}) = \left\{ (u, v) \in \mathcal{H}; v \in H_{\frac{1}{2}}, Au + \mu BB^{*}v \in H \right\} \subset \mathcal{H} \longrightarrow \mathcal{H}$$
$$\mathcal{A}_{d} \begin{pmatrix} u_{1} \\ u_{2} \end{pmatrix} = \begin{pmatrix} u_{2} \\ -Au_{1} - \mu BB^{*}u_{2} \end{pmatrix}.$$

The operators $(\mathcal{A}, \mathcal{D}(\mathcal{A}))$ and $(\mathcal{A}_d, \mathcal{D}(\mathcal{A}_d))$ defined by (1.8) generate group of isometries of \mathcal{H} and strongly continuous semigroup of contractions on \mathcal{H} , respectively, denoted respectively by $(\mathcal{T}(t))_{t\geq 0}$ and $(\mathcal{T}_d(t))_{t\geq 0}$ (as before let $(\mathcal{T}_{-1}(t))_{t\geq 0}$ be the extension of $(\mathcal{T}(t))_{t\geq 0}$ to $H \times H_{-\frac{1}{2}}$). **Proposition 1.1.** Assume that the assumption (1.5) holds, then the system (1.2)–(1.4) is wellposed. More precisely, for every $(u_0, u_1) \in \mathcal{H}$, the solution of (1.2)–(1.4) is given by

(1.9)
$$\begin{pmatrix} u(t) \\ \dot{u}(t) \end{pmatrix} = \begin{cases} \begin{pmatrix} u^{0}(t) \\ \dot{u}^{0}(t) \end{pmatrix} = \mathcal{T}(t) \begin{pmatrix} u_{0} \\ u_{1} \end{pmatrix}, 0 \le t \le T_{0}, \\ \begin{pmatrix} u^{j}(t) \\ \dot{u}^{j}(t) \end{pmatrix} = \mathcal{T}(t - jT_{0}) \begin{pmatrix} u^{j-1}(jT_{0}) \\ \dot{u}^{j-1}(jT_{0}) \end{pmatrix} + \\ \int_{jT_{0}}^{t} \mathcal{T}_{-1}(t - s) \begin{pmatrix} 0 \\ -\mu BB^{*} \dot{u}^{j-1}(s - T_{0}) \end{pmatrix} ds, \\ jT_{0} \le t \le (j+1)T_{0}, j \ge 1 \end{cases}$$

and satisfies $(u^j, \dot{u}^j) \in C([jT_0, (j+1)T_0], \mathcal{H}), j \in \mathbb{N}$. Moreover, there exist two positive constants M and ω such that

(1.10)
$$\|(u(t), \dot{u}(t))\|_{\mathcal{H}}^2 \le M e^{\omega t} \|(u_0, u_1)\|_{\mathcal{H}}^2, \forall t \ge 0.$$

Remark 1.2. The above Proposition suggests that the mapping

$$T_t: \mathcal{H} \to \mathcal{H}: (u_0, u_1) \mapsto (u(t), \dot{u}(t))$$

defines a strongly continuous semigroup but it is not the case since the semigroup property $T_{t+s} = T_t T_s$ is not valid in general.

For any solution of problem (1.2)-(1.4) we define the energy

(1.11)
$$E(t) = \frac{1}{2} \left\| (u(t), \dot{u}(t)) \right\|_{\mathcal{H}}^{2}, t \ge 0.$$

The paper is organized as follows. The second section deals with the well-posedness of the problem while, in section 3, we prove an exponential stability result of the shifted system associated to (1.2)-(1.4) where $B \in \mathcal{L}(U, H)$.

In section 4 we construct suitable numerical schemes to find an approximate solution of the different problems studied in this work: finite difference scheme or finite volume method. For each scheme, we design a discrete energy which must be preserved in the first step of the stabilization method. Finally the section 5 is devoted to present numerical experiments of each studied case in order to confirm the theoretical results.

2. Well-posedness

We study the well-posedness of the problem (1.2)-(1.4) in two cases:

- general case, where $B \in \mathcal{L}(U, H_{-\frac{1}{2}})$
- bounded case, where $B \in \mathcal{L}(U, H)$.

2.1. General case. Consider the evolution problem

(2.1)
$$\ddot{y}^{j}(t) + Ay^{j}(t) = Bv^{j}(t), \text{ in } (jT_{0}, (j+1)T_{0}), j \in \mathbb{N}^{*},$$

(2.2)
$$y^{j}(jT_{0}) = \dot{y}^{j}(jT_{0}) = 0, \ j \in \mathbb{N}^{*}.$$

(2.3)
$$\ddot{\phi}(t) + A\phi(t) = 0, \text{ in } (0, +\infty),$$

(2.4)
$$\phi(0) = \phi_0, \ \dot{\phi}(0) = \phi_1.$$

A natural question is the regularity of y^j when $v^j \in L^2(jT_0, (j+1)T_0; U), j \in \mathbb{N}^*$. By applying standard energy estimates we can easily check that $y^j \in C([jT_0, (j+1)T_0]; H) \cap C^1([jT_0, (j+1)T_0]; H_{-\frac{1}{2}})$. However if B satisfies a certain admissibility condition then y^j is more regular. More precisely the following result, which is a version of the general transposition method (see, for instance, Lions and Magenes [23]) holds true. It is clear that the system (2.3)-(2.4) admits a unique solution ϕ having the regularity

$$\phi \in C([0, T_0]; H_{\frac{1}{2}}) \cap C^1([0, T_0]; H),$$
$$\begin{pmatrix} \phi \\ \dot{\phi} \end{pmatrix}(t) = \mathcal{T}(t) \begin{pmatrix} \phi_0 \\ \phi_1 \end{pmatrix}, \quad 0 \le t \le T_0$$

Moreover, according to assumption (1.5), $B^*\phi(\cdot) \in H^1(0, T_0)$, and for all $T \in (0, T_0)$ there exists a constant C > 0 such that

(2.5) $||B^*\dot{\phi}(\cdot)||_{L^2(0,T;U)} \le C ||(\phi_0,\phi_1)||_{\mathcal{H}}, \quad \forall (\phi_0,\phi_1) \in H_1 \times H_{\frac{1}{2}}.$

Lemma 2.1. Suppose that $v^j \in L^2([jT_0, (j+1)T_0]; U), j \in \mathbb{N}^*$. Then the problem (2.1)–(2.2) admits a unique solution having the regularity

(2.6)
$$y^{j} \in C([jT_{0}, (j+1)T_{0}]; H_{\frac{1}{2}}) \cap C^{1}([jT_{0}, (j+1)T_{0}]; H), \ j \in \mathbb{N}^{*},$$

and

$$\begin{pmatrix} y^{j} \\ \dot{y}^{j} \end{pmatrix}(t) = \int_{jT_{0}}^{t} \mathcal{T}_{-1}(t - jT_{0} - s) \begin{pmatrix} 0 \\ Bv_{j}(s) \end{pmatrix} ds, \quad jT_{0} \le t \le (j+1)T_{0}, \ j \ge 1.$$

Proof. If we set $Z(t) = \begin{pmatrix} y^j(t+jT_0) \\ \dot{y}^j(t+jT_0) \end{pmatrix}$ it is clear that (2.1)–(2.2) can be written as

$$\dot{Z}^{j} + \mathcal{A}Z^{j}(t) = \mathcal{B}v^{j}(t+jT_{0}) \text{ on } (0,T_{0}), Z^{j}(0) = 0,$$

where

$$\mathcal{A} = \begin{pmatrix} 0 & -I \\ A & 0 \end{pmatrix} : \mathcal{H} \to [\mathcal{D}(\mathcal{A})]',$$
$$\mathcal{B} = \begin{pmatrix} 0 \\ B \end{pmatrix} : U \to [\mathcal{D}(\mathcal{A})]'$$

It is well known that \mathcal{A} is a skew adjoint operator so it generates a group of isometries in $[\mathcal{D}(\mathcal{A})]'$, denoted by $\mathcal{S}(t)(=\mathcal{T}_{-1}(t))$.

After simple calculations we get that the operator $\mathcal{B}^* : \mathcal{D}(\mathcal{A}) \to U$ is given by

$$\mathcal{B}^* \left(\begin{array}{c} u^j \\ v^j \end{array} \right) = B^* v^j, \, \forall \, (u^j, v^j) \in \mathcal{D}(\mathcal{A}).$$

This implies that

$$\mathcal{B}^*\mathcal{S}^*(t)\begin{pmatrix}\phi_0\\\phi_1\end{pmatrix} = B^*\dot{\phi}(t), \,\forall\,(\phi_0,\phi_1)\in\mathcal{D}(\mathcal{A})$$

with ϕ satisfying (2.3)–(2.4). From the inequality above and (2.5) we deduce that there exists a constant C > 0 such that for all $T \in (0, 2\ell)$

$$\int_0^T \left\| \mathcal{B}^* \mathcal{S}^*(t) \begin{pmatrix} \phi_0 \\ \phi_1 \end{pmatrix} \right\|_U^2 dt \le C \left\| (\phi_0, \phi_1) \right\|_{\mathcal{H}}^2, \, \forall \, (\phi_0, \phi_1) \in \mathcal{D}(\mathcal{A}).$$

According to Theorem 3.1 in [12, p.187] (see also [27]) the inequality above implies the interior regularity (2.6). \Box

We are now ready to prove the two results of the Proposition 1.1

Proof of Proposition 1.1. First of all, let us prove the equation (1.9). The existence result for problem (1.2)-(1.4) is now made by induction. First on $[0, T_0]$ (case j = 0), we take

$$\begin{pmatrix} u^0(t) \\ \dot{u}^0(t) \end{pmatrix} = \mathcal{T}(t) \begin{pmatrix} u_0 \\ u_1 \end{pmatrix}, \, \forall t \in [0, T_0].$$

That is clearly a solution of (1.2)-(1.4) on $(0, T_0)$ and that has the regularity $(u^0, \dot{u}^0) \in C([0, T_0]; \mathcal{H})$. Now for $j \ge 1$, we take for all $t \in [jT_0, (j+1)T_0]$,

$$\begin{pmatrix} u^{j}(t) \\ \dot{u}^{j}(t) \end{pmatrix} = \begin{pmatrix} \phi(t+jT_{0}) \\ \dot{\phi}(t+jT_{0}) \end{pmatrix} + \begin{pmatrix} y^{j}(t) \\ \dot{y}^{j}(t) \end{pmatrix}$$

$$= \mathcal{T}(t+jT_{0}) \begin{pmatrix} u^{j-1}(jT_{0}) \\ \dot{u}^{j-1}(jT_{0}) \end{pmatrix} + \int_{jT_{0}}^{t} \mathcal{T}_{-1}(t-s) \begin{pmatrix} 0 \\ -\mu BB^{*}\dot{u}^{j-1}(s-T_{0}) \end{pmatrix} ds,$$

where y^j (resp. ϕ) is solution of (2.1)–(2.2) (resp. (2.3)–(2.4)) with $v^j(t) = -\mu B^* \dot{u}^{j-1}(t-T_0)$ (that belongs to $L^2(jT_0, (j+1)T_0; U)$ because the operator B^* is an input admissible operator according to assumption (1.5)) and $\phi_0 = u^{j-1}(jT_0)$, $\phi_1 = \dot{u}^{j-1}(jT_0)$. This solution has the announced regularity due to the above arguments.

Let us now prove the estimation (1.10).

For the system (1.2)–(1.4), the estimate (1.5) is used to prove our existence result by iteration. Namely, for all $j \in \mathbb{N}$, we prove by iteration that (u^j, \dot{u}^j) as defined in the statement belongs to $C([jT_0, (j+1)T_0], \mathcal{H})$, and satisfies

(2.7)
$$\Lambda_{j+1} \le C_2(T_0)(1+|\mu|)\Lambda_j$$

for some positive constant $C_2(T_0)$ and where

$$\Lambda_j = \|(u^j(jT_0), \dot{u}^j(jT_0))\|_{\mathcal{H}} + \left(\int_{(j-1)T_0}^{jT_0} \|B^* \dot{u}^{j-1}(s)\|_U^2 \, ds\right)^{\frac{1}{2}},$$

with the convention $u^{-1} = 0$.

Note that $\begin{pmatrix} u^0(t) \\ \dot{u}^0(t) \end{pmatrix} = \mathcal{T}(t) \begin{pmatrix} u_0 \\ u_1 \end{pmatrix}$ is clearly in $C([0, T_0], \mathcal{H})$, and satisfies (2.7) since $\mathcal{T}(t)$ is a semigroup of contractions.

Now for $j \ge 1$, we assume that the result holds for j-1; then by (1.5), we know that $(u^j, \dot{u}^j) \in C([jT_0, (j+1)T_0], \mathcal{H})$ and that

$$\left(\int_{jT_0}^{(j+1)T_0} \left\| B^* \dot{u}^j(s) \right\|_U^2 ds \right)^{\frac{1}{2}} \leq C(T_0) \left(\| (u^j(jT_0), \dot{u}^j(jT_0)) \|_{\mathcal{H}} + \| \mu \| \left(\int_{jT_0}^{(j+1)T_0} \left\| B^* \dot{u}^{j-1}(s-T_0) \right\|_U^2 ds \right)^{\frac{1}{2}} \right)$$

On the other hand using Theorem 4.4.3 and Proposition 4.2.2 of [27] (see below), we know that there exists $C_1(T_0) > 0$ such that for all $t \in [jT_0, (j+1)T_0]$, (2.8)

$$\|(u^{j}(t), \dot{u}^{j}(t))\|_{\mathcal{H}} \le \|(u^{j}(jT_{0}), \dot{u}^{j}(jT_{0}))\|_{\mathcal{H}} + |\mu|C_{1}(T_{0}) \left(\int_{jT_{0}}^{(j+1)T_{0}} \left\|B^{*}\dot{u}^{j-1}(s-T_{0})\right\|_{U}^{2} ds\right)^{\frac{1}{2}}.$$

This estimate evaluated at $t = (j+1)T_0$ and added to the previous one yields (2.7) with $C_2(T_0) = \max\{1, C_1(T_0), C(T_0)\}$. This proves that the result holds for all j.

By iteration, (2.7) implies that

$$\Lambda_j \le C_2(T_0)^j (1+|\mu|)^j ||(u_0,u_1)||_{\mathcal{H}}, \forall j \in \mathbb{N},$$

This estimate and (2.8) yield (1.10).

2.2. Bounded case. Here we assume that the operator $B \in \mathcal{L}(U, H)$. So we will give a well-posedness result for problem (1.2)–(1.4) by using semigroup theory.

We introduce the auxiliary variable

$$\begin{array}{ll} (2.9) & z(\rho,t) = B^* \dot{u}(t-T_0\rho), \quad \rho \in (0,1), \ t > 0. \\ \\ \text{Then, problem } (1.2)-(1.4) \text{ is equivalent to} \\ (2.10) & \ddot{u}(t) + Au(t) + \mu Bz(1,t) = 0, & \text{in } (0,+\infty), \\ (2.11) & T_0 z_t(\rho,t) + z_\rho(\rho,t) = 0 & \text{in } (0,1) \times (0,+\infty), \\ (2.12) & u(0) = u_0, \quad \dot{u}(0) = u_1, \\ (2.13) & z(\rho,0) = 0, & \text{in } (0,1), \\ (2.14) & z(0,t) = B^* \dot{u}(t), & t > 0. \\ \\ \text{If we denote} \\ & U := (u,\dot{u},z)^\top, \end{array}$$

then

$$\dot{U} := (\dot{u}, \ddot{u}, z_t)^{\top} = (\dot{u}, -Au - \mu Bz(1, \cdot), -T_0^{-1}z_{\rho})^{\top}.$$

Therefore, problem (2.10)-(2.14) can be rewritten as

(2.15)
$$\begin{cases} \dot{U} = \mathcal{A}_g U, \\ U(0) = (u_0, u_1, 0)^\top \end{cases}$$

where the operator \mathcal{A}_g is defined by

$$A_g \begin{pmatrix} u \\ v \\ z \end{pmatrix} := \begin{pmatrix} v \\ -Au - \mu Bz(\cdot, 1) \\ -T_0^{-1} z_\rho \end{pmatrix},$$

with domain

(2.16)
$$\mathcal{D}(\mathcal{A}_g) := \left\{ (u, v, z)^\top \in H_1 \times H_{\frac{1}{2}} \times H^1(0, 1; U) \ B^* v = z(0) \right\},$$

in the Hilbert space

(2.17)
$$\mathcal{H}_g := H_{\frac{1}{2}} \times H \times L^2(0,1;U),$$

equipped with the standard inner product

$$((u, v, z), (u_1, v_1, z_1))_{\mathcal{H}_g} = (A^{\frac{1}{2}}u, A^{\frac{1}{2}}u_1)_H + (v, v_1)_H + \xi \int_0^1 (z, z_1)_U \, d\rho,$$

where $\xi > 0$ is a parameter fixed later on.

We will show that \mathcal{A}_g generates a C_0 semigroup on \mathcal{H}_g by proving that $\mathcal{A}_g - cId$ is maximal dissipative for an appropriate choice of c in function of ξ, T_0, B^* and μ . Namely we prove the next result.

Lemma 2.2. If $\xi \geq |\mu| T_0$, then $\mathcal{A}_g - \left(\frac{|\mu|}{2} + \frac{\xi}{2T_0}\right) \|B^*\|_{\mathcal{L}(H,U)}^2$ Id is maximal dissipative in \mathcal{H}_g .

Proof. Take $U = (u, v, z)^T \in \mathcal{D}(\mathcal{A}_g)$. Then we have

$$(\mathcal{A}_g(u,v,z),(u,v,z))_{\mathcal{H}_g} = -\mu \,(z(1),B^*v)_U - \xi T_0^{-1} \int_0^1 (z_\rho,z)_U \,d\rho$$

Hence, we get

$$(\mathcal{A}_g(u,v,z),(u,v,z))_{\mathcal{H}_g} = -\mu(z(1), B^*v)_U - \frac{\xi}{2T_0} \|z(1)\|_U^2 + \frac{\xi}{2T_0} \|z(0)\|_U^2.$$

Hence reminding that $z(0) = B^*v$ and using Young's inequality we find that

$$\Re(\mathcal{A}_g(u,v,z),(u,v,z))_{\mathcal{H}_g} \le \left(\frac{|\mu|}{2} - \frac{\xi}{2T_0}\right) \|z(1)\|_U^2 + \left(\frac{|\mu|}{2} + \frac{\xi}{2T_0}\right) \|B^*v\|_U^2.$$

We find that

$$\Re(\mathcal{A}_g(u,v,z),(u,v,z))_{\mathcal{H}_g} \le \left(\frac{|\mu|}{2} - \frac{\xi}{2T_0}\right) \|z(1)\|_U^2 + \left(\frac{|\mu|}{2} + \frac{\xi}{2T_0}\right) \|B^*\|_{\mathcal{L}(H,U)}^2 \|v\|_H^2.$$

The choice of ξ is equivalent to $\frac{|\mu|}{2} - \frac{\xi}{2T_0} \leq 0$, and therefore for $c = \left(\frac{|\mu|}{2} + \frac{\xi}{2T_0}\right) \|B^*\|_{\mathcal{L}(H,U)}^2$,

$$(2.18) \quad \Re(\mathcal{A}_g(u,v,z),(u,v,z))_{\mathcal{H}_g} \le \left(\frac{|\mu|}{2} - \frac{\xi}{2T_0}\right) \|z(1)\|_U^2 + \left(\frac{|\mu|}{2} + \frac{\xi}{2T_0}\right) \|B^*\|_{\mathcal{L}(H,U)}^2 \|v\|_H^2$$

As
$$||v||_{H}^{2} \leq ||(u, v, z)||_{\mathcal{H}_{g}}^{2}$$
, we get

(2.19)
$$\Re((\mathcal{A}_g - cId)(u, v, z), (u, v, z))_{\mathcal{H}_g} \le \left(\frac{|\mu|}{2} - \frac{\xi}{2T_0}\right) \|z(1)\|_U^2 \le 0.$$

which directly leads to the dissipativeness of $\mathcal{A}_g^s := \mathcal{A}_g - cId$.

Let us go on with the maximality, namely let us show that $\lambda I - \mathcal{A}_g$ is surjective for a fixed $\lambda > 0$. Given $(f, g, h)^T \in \mathcal{H}_g$, we look for a solution $U = (u, v, z)^T \in \mathcal{D}(\mathcal{A}_g)$ of

(2.20)
$$(\lambda I - \mathcal{A}_g) \begin{pmatrix} u \\ v \\ z \end{pmatrix} = \begin{pmatrix} f \\ g \\ h \end{pmatrix},$$

that is, verifying

(2.21)
$$\begin{cases} \lambda u - v = f, \\ \lambda v + Au + \mu Bz(1) = g, \\ \lambda z + T_0^{-1} z_\rho = h. \end{cases}$$

Suppose that we have found u with the appropriate regularity. Then, (2.22) $v = \lambda u - f$

and we can determine z. Indeed, by (2.16),

(2.23)
$$z(0) = B^* v_{\pm}$$

and, from (2.21),

(2.24)

$$\lambda z(\rho) + T_0^{-1} z_\rho(\rho) = h(\rho) \quad \text{for} \ \rho \in (0,1)$$

Then, by (2.23) and (2.24), we obtain

(2.25)
$$z(\rho) = \lambda B^* u \, e^{-\lambda \rho T_0} - B^* f \, e^{-\lambda \rho T_0} + T_0 e^{-\lambda \rho T_0} \int_0^\rho h(\sigma) e^{\lambda \sigma T_0} d\sigma.$$

In particular, we have

(2.26)
$$z(1) = \lambda B^* u \, e^{-\lambda T_0} - B^* f \, e^{-\lambda T_0} + z_0$$

with $z_0 \in U$ defined by

(2.27)
$$z_0 = T_0 e^{-\lambda T_0} \int_0^1 h(\sigma) e^{\lambda \sigma T_0} d\sigma.$$

This expression in (2.21) shows that the function u verifies formally

$$\lambda^2 u + Au + \lambda \mu BB^* u e^{-\lambda T_0} - \mu BB^* f e^{-\lambda T_0} + \mu Bz_0 = g + \lambda f,$$

that is,

(2.28)
$$\lambda^2 u + Au + \lambda \,\mu \, BB^* u \, e^{-\lambda T_0} = g + \lambda f + \mu \, BB^* f \, e^{-\lambda T_0} - \mu \, Bz_0$$

Problem (2.28) can be reformulated as

(2.29)
$$(\lambda^2 u + Au + \lambda \mu BB^* u e^{-\lambda T_0}, w)_H = (g + \lambda f + \mu BB^* f e^{-\lambda T_0} - \mu Bz_0, w)_H, \quad \forall \ w \in H_{\frac{1}{2}}$$

Using the definition of the adjoint of B , we get

Using the definition of the adjoint of B, we get

(2.30)
$$\lambda^2(u,w)_H + (A^{\frac{1}{2}}u, A^{\frac{1}{2}}w)_{H^{\frac{1}{2}}} + \lambda \,\mu \,e^{-\lambda T_0} \,(B^*u, B^*w)_U =$$

$$(g + \lambda f, w)_H + \mu \left(e^{-\lambda T_0} B^* f - z_0, B^* w \right)_U, \ \forall w \in H_{\frac{1}{2}}.$$

As the left-hand side of (2.30) is coercive on $H_{\frac{1}{2}}$, for λ sufficiently large (for example $\lambda \geq |\mu| \|B^*\|_{\mathcal{L}(H,U)}$), the Lax–Milgram lemma guarantees the existence and uniqueness of a solution $u \in H_{\frac{1}{2}}$ of (2.30). Once u is obtained we define v by (2.22) that belongs to $H_{\frac{1}{2}}$ and z by (2.25) that belongs to $H^1(0,1;U)$. Hence we can set $r = A^{\frac{1}{2}}u$, it belongs to H but owing to (2.30), it fulfils

$$\lambda(v,w)_H + (r, A^{\frac{1}{2}}w)_H = (g - \mu Bz(1), w)_H, \ \forall w \in H_{\frac{1}{2}},$$

or equivalently

$$(r, B^*w)_H = (g - \mu Bz(1) - \lambda v, w)_H, \ \forall w \in H_{\frac{1}{2}}.$$

As $g - Bz(1) - \lambda v \in H$, this implies that r belongs to $H_{\frac{1}{2}}$ with

$$A^{\frac{1}{2}}r = g - Bz(1) - \lambda v.$$

This shows that the triple U = (u, v, z) belongs to $\mathcal{D}(\mathcal{A}_g)$ and satisfies (2.20), hence $\lambda I - \mathcal{A}_g$ is surjective for every $\lambda > 0$.

We have then the following result.

Proposition 2.3. We assume that $\xi \geq |\mu| T_0$. Then, the system (1.2)–(1.4) is well–posed. More precisely, for every $(u_0, u_1, 0) \in \mathcal{H}_g$, there exists a unique solution $(u, v, z) \in C(0, +\infty, \mathcal{H}_g)$ of (2.15). Moreover, if $(u_0, u_1, 0) \in \mathcal{D}(\mathcal{A}_g)$ then $(u, v, z) \in C(0, +\infty, \mathcal{D}(\mathcal{A}_g)) \cap C^1(0, +\infty, \mathcal{H}_g)$ with $v = \dot{u}$ and u is indeed a solution of (1.2)–(1.4).

3. Asymptotic behavior

In this section, we show that the semigroup $e^{t\mathcal{A}_g^s}$, where $(\mathcal{A}_g^s = \mathcal{A}_g - cId, \mathcal{D}(\mathcal{A}_g^s) = \mathcal{D}(\mathcal{A}_g))$, decays to the null steady state with an exponential decay rate. To obtain this, our technique is based on a frequency domain approach and combines a contradiction argument to carry out a special analysis of the resolvent.

Theorem 3.1. We assume that $\xi > |\mu| T_0$. Then, there exist constants $C, \omega > 0$ such that the semigroup $e^{t\mathcal{A}_g^s}$ satisfies the following estimate

(3.1)
$$\left\| e^{t\mathcal{A}_g^s} \right\|_{\mathcal{L}(\mathcal{H}_g)} \le C \, e^{-\omega t}, \, \forall \, t > 0$$

Proof of Theorem 3.1. We will employ the following frequency domain theorem for uniform stability from [20, Thm 8.1.4] of a C_0 semigroup of contractions on a Hilbert space:

Lemma 3.2. A C_0 semigroup of contractions $e^{t\mathcal{L}}$ on a Hilbert space X satisfies

$$|e^{t\mathcal{L}}||_{\mathcal{L}(X)} \leq C e^{-\omega t}$$

for some constant C > 0 and for $\omega > 0$ if and only if

(3.2)
$$\sigma(\mathcal{L}) \cap i\mathbb{R} = \emptyset.$$

and

(3.3)
$$\limsup_{\beta \in \mathbb{R}, |\beta| \to +\infty} \|(i\beta I - \mathcal{L})^{-1}\|_{\mathcal{L}(X)} < \infty.$$

where $\sigma(\mathcal{L})$ denotes the spectrum of the operator \mathcal{L} .

In view of this theorem we need to identify the spectrum of \mathcal{A}_g^s lying on the imaginary axis. Unfortunately, as the embedding of $H^1(0,1;U)$ into $L^2(0,1;U)$ is not compact in general, \mathcal{A}_g^s has not a compact resolvent. Therefore its spectrum $\sigma(\mathcal{A}_g^s)$ does not consist only of eigenvalues of \mathcal{A}_g^s . We have then to show that:

- if β is a real number, then $i\beta Id \mathcal{A}_g^s$ is injective and
- if β is a real number, then $i\beta Id \mathcal{A}_g^s$ is surjective.

It is the objective of the two following lemmas.

First we look at the point spectrum of \mathcal{A}_a^s .

Lemma 3.3. We assume that $\xi > |\mu| T_0$. Then, if β is a real number, then $i\beta$ is not an eigenvalue of \mathcal{A}_g^s .

Proof. We will show that the equation

(3.4)
$$\mathcal{A}_g^s Z = i\beta Z$$

with $Z = (u, v, z)^{\top} \in \mathcal{D}(\mathcal{A}_g)$ and $\beta \in \mathbb{R}$ has only the trivial solution.

Equation (3.4) writes:

$$(3.5) (i\beta + c)u - v = 0,$$

(3.6) $(i\beta + c)v + Au + \mu Bz(1) = 0,$

(3.7)
$$(i\beta + c)z + T_0^{-1} z_\rho = 0.$$

By taking the inner product of (3.4) with Z and using (2.19), we get:

(3.8)
$$\Re\left((\mathcal{A}_g^s Z, Z)_{\mathcal{H}_g}\right) \le \left(\frac{|\mu|}{2} - \frac{\xi}{2T_0}\right) \|z(1)\|_U^2.$$

Thus we firstly obtain that:

$$z(1) = 0, \text{ in } U,$$

and by (3.7) we have that $z(\rho) = z(1) e^{-T_0(i\beta+c)\rho}, \forall \rho \in (0,1)$, so z = 0, in $H^1(0,1;U)$.

Next, according to (3.5), we have $v = (i\beta + c)u$. Moreover, (3.6) implies

$$c(c+i\beta) \|u\|_{H}^{2} + \|A^{\frac{1}{2}}u\|_{H}^{2} = i\beta(c+i\beta) \|u\|_{H}^{2}$$

and then

$$0 \le c^2 \|u\|_H^2 + \left\|A^{\frac{1}{2}}u\right\|_H^2 = -\beta^2 \|u\|_H^2 \le 0.$$

This leads to u = 0 and next v = 0.

Thus the only solution of (3.4) is the trivial one.

Next, we show that \mathcal{A}_g^s has no continuous spectrum on the imaginary axis.

Lemma 3.4. If β is a real number, then $i\beta$ belongs to the resolvent set $\rho(\mathcal{A}_q^s)$ of \mathcal{A}_q^s .

Proof. In view of Lemma 3.3 it is enough to show that $i\beta Id - \mathcal{A}_g^s$ is surjective.

For $F = (f, g, h)^{\top} \in \mathcal{H}_g$, we look for a solution $U = (u, v, z)^{\top} \in \mathcal{D}(\mathcal{A}_g)$ of

(3.9)
$$(\lambda Id - \mathcal{A}_g) \begin{pmatrix} u \\ v \\ z \end{pmatrix} = \begin{pmatrix} f \\ g \\ h \end{pmatrix}$$

that is, verifying

(3.10)
$$\begin{cases} \lambda u - v = f, \\ \lambda v + Au + \mu Bz(1) = g, \\ \lambda z + T_0^{-1} z_\rho = h, \end{cases}$$

where $\lambda = i\beta + c$.

Suppose that we have found u with the appropriate regularity. Then,

$$(3.11) v = \lambda u - f$$

and we can determine z. Indeed, by (2.16),

(3.12)
$$z(0) = B^* v,$$

and, from (3.10),

(3.13)
$$\lambda z(\rho) + T_0^{-1} z_\rho(\rho) = h(\rho) \text{ for } \rho \in (0,1).$$

Then, by (3.12) and (3.13), we obtain

(3.14)
$$z(\rho) = B^* v \, e^{-\lambda \rho T_0} + T_0 e^{-\lambda \rho T_0} \int_0^\rho h(\sigma) e^{\lambda \sigma T_0} d\sigma.$$

In particular, we have

(3.15)
$$z(1) = B^* v \, e^{-\lambda T_0} + z_0,$$

with $z_0 \in U$ defined by

(3.16)
$$z_0 = T_0 e^{-\lambda T_0} \int_0^1 h(\sigma) e^{\lambda \sigma T_0} d\sigma$$

This expression in (3.10) shows that the function u verify formally

(3.17)
$$\lambda^2 u + Au + \lambda \mu BB^* u e^{-\lambda T_0} = g + \lambda f + \mu BB^* f e^{-\lambda T_0} - \mu Bz_0$$

Problem (3.17) can be reformulated as

(3.18)
$$\lambda (u, w)_{H} + \frac{1}{\lambda} (A^{\frac{1}{2}}u, A^{\frac{1}{2}}w)_{H} + \mu e^{-\lambda T_{0}} (B^{*}u, B^{*}w)_{U} = \frac{1}{\lambda} (g + \lambda f, w)_{H} + \frac{1}{\lambda} \mu (e^{-\lambda T_{0}} B^{*}f - z_{0}, B^{*}w)_{U}, \ \forall w \in H_{\frac{1}{2}}.$$

As the left-hand side of (3.18) is coercive sesquilinear form on $H_{\frac{1}{2}}$, the Lax–Milgram lemma guarantees the existence and uniqueness of a solution $u \in H_{\frac{1}{2}}$ of (3.17). Once v and z by (3.14) that belongs to $H^1(0,1;U)$. Hence we can set $r = A^{\frac{1}{2}}u$, it belongs to H but owing to (3.10), it fulfils

$$\lambda(v,w)_H + (r, A^{\frac{1}{2}}w)_H = (g - \mu Bz(1), w)_H, \ \forall w \in H_{\frac{1}{2}},$$

or equivalently

 $(r, B^*w)_H = (g - \mu Bz(1) - \lambda v, w)_H, \ \forall w \in H_{\frac{1}{2}}.$

As $g - \mu Bz(1) - \lambda v \in H$, this implies that r belongs to $H_{\frac{1}{2}}$ with

$$A^{\frac{1}{2}}r = g - \mu Bz(1) - \lambda v.$$

This shows that the triple $U = (u, v, z)^{\top}$ belongs to $\mathcal{D}(\mathcal{A}_g)$ and satisfies (3.9), hence $i\beta Id - \mathcal{A}_g^s$ is surjective.

The following lemma shows that (3.3) holds with $\mathcal{L} = \mathcal{A}_{q}^{s}$.

Lemma 3.5. We assume that $\xi > |\mu| T_0$. Then, the resolvent operator of \mathcal{A}_g^s satisfies condition

(3.19)
$$\lim_{\beta \in \mathbb{R}, |\beta| \to +\infty} \|(i\beta I - \mathcal{A}_g^s)^{-1}\|_{\mathcal{L}(\mathcal{H}_g)} < \infty.$$

Proof. Suppose that condition (3.19) is false. By the Banach-Steinhaus Theorem (see [13]), there exists a sequence of real numbers β_n such that $|\beta_n| \to +\infty$ and a sequence of vectors $Z_n = (u_n, v_n, z_n)^\top \in \mathcal{D}(\mathcal{A}_d)$ with

$$(3.20) ||Z_n||_{\mathcal{H}_q} = 1$$

such that

(3.21)
$$||(\lambda_n Id - \mathcal{A}_g^s) Z_n||_{\mathcal{H}_g} \to 0 \quad \text{as} \quad n \to \infty,$$

i.e.,

(3.22)
$$\lambda_n u_n - v_n \equiv f_n \to 0 \quad \text{in } H_{\frac{1}{2}},$$

(3.23)
$$\lambda_n v_n + A u_n + \mu B z_n(1) \equiv g_n \to 0 \quad \text{in } H,$$

(3.24)
$$\lambda_n z_n + T_0^{-1} \partial_\rho z_n \equiv h_n \to 0 \quad \text{in} \ L^2(0,1;U)$$

where $\lambda_n = c + i\beta_n, n \in \mathbb{N}$.

Our goal is to derive from (3.21) that $||Z_n||_{\mathcal{H}_g}$ converges to zero, that furnishes a contradiction. We notice that from (2.19) and (3.22) we have

$$\left|\left|(\lambda_n Id - \mathcal{A}_g)Z_n\right|\right|_{\mathcal{H}_g} \ge \left|\Re\left((\lambda_n Id - \mathcal{A})Z_n, Z_n\right)_{\mathcal{H}_g}\right| \ge \left(-\frac{|\mu|}{2} + \frac{\xi}{2T_0}\right) \left\|z_n(1)\right\|_U^2.$$

By this estimate, we deduce that

(3.25)
$$z_n(1) \to 0$$
, in U , as $n \to \infty$.

According to (3.22)-(3.23) we have that

$$c\left(\|v_n\|_{H}^{2} + \left\|A^{\frac{1}{2}}u_n\right\|_{H}^{2}\right) = \Re\left(\lambda_n \|v_n\|_{H}^{2} + \overline{\lambda_n} \|A^{\frac{1}{2}}u_n\|_{H}^{2}\right) = \Re\left((g_n - \mu B z_n(1), v_n)_{H} + (A^{\frac{1}{2}}u_n, A^{\frac{1}{2}}f_n)_{H}\right).$$

Which implies that

(3.26)
$$u_n \to 0, \text{ in } H_{\frac{1}{2}}, v_n \to 0, \text{ in } H, \text{ as } n \to \infty.$$

As well as

(3.27)
$$z_n(0) = B^* v_n \to 0, \quad \text{in } U, \text{ as } n \to \infty.$$

By integration of the identity (3.24), we have

(3.28)
$$z_n(\rho) = z_n(0) e^{-T_0 \lambda_n \rho} + \tau \int_0^\rho e^{-T_0 \lambda_n(\rho - \gamma)} h_n(\gamma) d\gamma.$$

Hence recalling that $\Re \lambda_n = c > 0$

$$\int_0^1 \|z_n(\rho)\|_U^2 \, d\rho \le 2\|z_n(0)\|_U^2 + 2T_0^2 \int_0^1 \int_0^\rho \|h_n(\gamma)\|_U^2 \, d\gamma\rho \, d\rho \to 0, \text{ as } n \to \infty.$$

All together we have shown that $||Z_n||_{\mathcal{H}_g}$ converges to zero, that clearly contradicts $||Z_n||_{\mathcal{H}_g} = 1$.

The two hypotheses of Lemma 3.2 are proved, then (3.1) holds. The proof of Theorem 3.1 is then finished. $\hfill \Box$

4. Numerical approximation in 1D

This section is devoted to the construction of a numerical approximation of the considered problem by either a finite difference discretization or a finite volume method. For each studied case, we will firstly construct in detail a discrete problem, present the corresponding algorithm and we will define its corresponding discrete energy which has to be conserved in the first step of the stabilization procedure.

We will consider $\Omega = (0, \ell)$ and set $T = T_0 = 2\ell$.

4.1. Boundary case. Let $\mu \in \mathbb{R}$. We consider the following switching time delay problem:

(4.1)
$$u_{tt}(x,t) - u_{xx}(x,t) = 0 \quad \text{for } (x,t) \in (0,\ell) \times (0,+\infty)$$

(4.2)
$$u(0,t) = 0 \quad \text{for } t > 0$$

(4.3) $u_x(\ell, t) = 0 \quad \text{for } t \in (0, T)$

(4.4)
$$u_x(\ell, t) = \mu u_t(\ell, t - T) \quad \text{for } t \ge T$$

with the following initial data:

(4.5)
$$u(x,0) = u_0(x), \quad x \in (0,\ell)$$

and

(4.6)
$$u_t(x,0) = u_1(x) \quad x \in (0,\ell)$$

Here, $A = -\partial_x^2$ be the unbounded operator in $H = L^2(0, \ell)$ with domain

$$H_1 = \mathcal{D}(A) = \left\{ u \in H^2(0, \ell); \ u(0) = 0, \ u_x(\ell) = 0 \right\},$$
$$H_{\frac{1}{2}} = \mathcal{D}(A^{\frac{1}{2}}) = \left\{ u \in H^1(0, \ell); \ u(0) = 0 \right\}$$

and

$$U=\mathbb{R},\,B\in\mathcal{L}(\mathbb{R},H_{-\frac{1}{2}}),\,Bk=A_{-1}Nk=k\,\delta_{\ell},\forall\,k\in\mathbb{R},\,B^*u=u(\ell),\,\forall\,u\in H_{\frac{1}{2}},$$

where A_{-1} is the extension of A to $H_{-1} = (\mathcal{D}(A))'$ and N is the Neumann map defined by :

$$\partial_x^2(Nk) = 0 \text{ on } (0, \ell)$$
$$Nk(0) = 0$$
$$\partial_x(Nk)(\ell) = k$$

and $H_{-\frac{1}{2}} = H'_{\frac{1}{2}}$ (the duality is in the sense of H).

We have according to [3, 4, Ammari-Chentouf-Smaoui] (which generalize results of Gugat [18] and [19]) the following stability result:

Theorem 4.1. [3, Ammari-Chentouf-Smaoui]

(1) For any $\mu \in (0,1)$ there exist positive constants C_1, C_2 such that for all initial data in \mathcal{H} , the solution of problem (4.1)-(4.6) satisfies

(4.7)
$$E(t) \le C_1 e^{-C_2 t}.$$

The constant C_1 depends on the initial data, on ℓ and on μ , while C_2 depends only on ℓ and on μ .

(2) For $\mu = 1$, if we denote $S_{b,1}(t)$ the propagator of the boundary delayed control problem, we have by definition:

$$\forall t > 0, \mathcal{S}_{b,1}(t) \begin{pmatrix} u_0 \\ u_1 \end{pmatrix} = \begin{pmatrix} u \\ u_t \end{pmatrix}.$$

And we have the following:

$$\forall t > 0, \forall n \in \mathbb{N}^*, \mathcal{S}_{b,1}(t+2nT) \begin{pmatrix} u_0 \\ u_1 \end{pmatrix} = -\mathcal{S}_{b,1}(t) \begin{pmatrix} u_0 \\ u_1 \end{pmatrix}$$

wehere as

$$\forall t > 0, \forall n \in \mathbb{N}, \mathcal{S}_{b,1}(t + (2n+1)T) \begin{pmatrix} u_0 \\ u_1 \end{pmatrix} = \mathcal{S}_{b,1}(t) \begin{pmatrix} u_0 \\ u_1 \end{pmatrix}.$$

In particular, we have that $S_{b,1}$ is 3T-periodic.

We note here that the proof of the second assertion of the above Theorem 4.1 is a simple adaptation of the proof of [3, Theorem 2.3 and Corollary 2.5] for $\mu = 1$.

4.1.1. Construction of the numerical scheme. Let N be a non negative integer. Let $\Delta x = \frac{\ell}{N}$. Consider the uniform subdivision of $[0, \ell]$ given by:

$$0 = x_0 < x_1 < \dots < x_{N-1} < x_N = \ell, \quad i.e. \ x_j = j\Delta x, \ j = 0, \dots, N$$

Set $t^{n+1} - t^n = \Delta t$ for all $n \in \mathbb{N}$. We will suppose that $T = K \times \Delta t$, $K \in \mathbb{N}^*$ to write easily the discretization of the delay term. We will also suppose that $T_f = M\Delta t$, with M > K, be the final time.

First step: for time $t \in [0, T)$.

For interior points $x \in (0, \ell)$ and for time $0 \le t < T$, the explicit finite-difference discretization of equation (4.1) writes for $n = 0, \ldots, K - 1$, and $j = 1, \ldots, N - 1$:

(4.8)
$$\frac{u_j^{n+1} - 2u_j^n + u_j^{n-1}}{\Delta t^2} - \frac{u_{j+1}^n - 2u_j^n + u_{j-1}^n}{\Delta x^2} = 0$$

The Dirichlet boundary condition (4.2) at x = 0 reads: for $n = 0, \ldots, K - 1$,

$$u_0^n = 0$$
.

The Neumann boundary condition (4.3) is commonly written as: $u_N = u_{N-1}$ since the derivative $u_x(x_N, t^n) = 0$ is approximated by the quotient of difference:

$$u_x(x_N, t^n) \approx \frac{u_N^n - u_{N-1}^n}{\Delta x}$$

By proceeding this way, the spatial order of discretization becomes now Δx and it may induce instabilities.

Thus we proceed as follow. The Neumann boundary condition reads: for $n = 0, \ldots, K - 1$,

$$\frac{u_{N+1}^n - u_{N-1}^n}{2\Delta x} = 0$$

where u_{N+1}^n is the value of u in the "ghost" space cell $(\ell, \ell + \Delta x)$. Putting the value of u_{N+1}^n in the numerical discretization (4.8) permits us to write the equation verified by u_N^{n+1} as: for $n = 0, \ldots, K - 1$,

(4.9)
$$\frac{u_N^{n+1} - 2u_N^n + u_N^{n-1}}{\Delta t^2} - 2\frac{u_{N-1}^n - u_N^n}{\Delta x^2} = 0.$$

According to the initial conditions given by equations (4.5), we have firstly: for $j = 1, \ldots, N$,

$$u_j^0 = u_0(x_j)$$

We can use the second initial conditions (4.6) to find the values of u at time $t^1 = \Delta t$, by employing a "ghost" time-boundary *i.e.* $t^{-1} = -\Delta t$ and the second-order central difference formula:

for
$$j = 1, ..., N$$
, $u_1(x_j) = \frac{\partial u}{\partial t}\Big|_{x_j, 0} = \frac{u_j^1 - u_j^{-1}}{2\Delta t} + O(\Delta t^2)$

Thus we have for $j = 1, \ldots, N$:

$$u_j^{-1} = u_j^1 - 2\Delta t \ u_1(x_j) \ .$$

Setting n = 0, in the numerical scheme (4.8), the previous equalities permits to compute $(u_j^1)_{j=0,N}$. Finally, the solution u can be computed at any time t^n .

In order to compute the solution u beyond the time T, we have to compute the quantity $u_t(\ell, t)$ for time $t \in [0, T)$. The centered difference scheme is used and we compute:

$$v^0 = u_1(\ell),$$

for $n = 1, \dots, K - 1, v^n = u_t(\ell, t^n) \approx \frac{u_N^{n+1} - u_N^{n-1}}{2\Delta t}.$

We set $s = \left(\frac{\Delta t}{\Delta x}\right)^2$. Let us now summarize the computation of the solution and the Neumann boundary delay term:

First step: for time $t \in [0, T)$

 $\begin{array}{ll} \mbox{Initialization for } j=0,\ldots,N\,,\,u_{j}^{0}=u_{0}(x_{j}) \quad v^{0}=u_{1}(\ell). \\ \mbox{Solution for } t=\Delta t \\ \mbox{for } j=1,\ldots,N-1\,,\,u_{j}^{1}=\frac{s}{2}\Big(u_{j+1}^{0}+u_{j-1}^{0}\Big)+(1-s)\,u_{i}^{0}+\Delta t\,u_{1}(x_{j}). \\ \mbox{Dirichlet boundary condition} & u_{0}^{1}=0. \\ \mbox{Neumann boundary condition} & u_{N}^{1}=s\,u_{N-1}^{0}+(1-s)\,u_{N}^{0}+\Delta tu_{1}(x_{N}). \\ \mbox{Solution for } t\in(\Delta t,T) \mbox{ i.e. for } n=1,\ldots,K-1 \\ \mbox{ for } j=1,\ldots,N-1\,,\,u_{j}^{n+1}=s\,\Big(u_{j+1}^{n}+u_{j-1}^{n}\Big)+2(1-s)\,u_{i}^{n}-u_{j}^{n-1}. \\ \mbox{Dirichlet boundary condition} & u_{0}^{n+1}=0. \\ \mbox{Neumann boundary condition} & u_{N}^{n+1}=2(1-s)\,u_{N}^{n}+2s\,u_{N-1}^{n}-u_{N}^{n-1}. \\ \mbox{ Delayed boundary equation} & v^{n}=\frac{u_{N}^{n+1}-u_{N}^{n-1}}{2\Delta t}. \end{array}$

Second step: for time $t \in [T, T_f]$

The only novelty comes from the Neumann boundary condition (4.4). As we have set $T = K\Delta t$, the discretization of the Neumann boundary condition (4.4) reads: for $n = K, \ldots, M$,

$$\frac{u_{N+1}^n - u_{N-1}^n}{2\Delta x} = \mu v^{n-K}$$

Thus, this boundary condition leads to: $u_{N+1}^n = u_{N-1}^n + 2\Delta x \mu v^{n-K}$. Inserting this value in the numerical scheme (4.8) permits us to write

$$u_N^{n+1} = 2(1-s)u_N^n + 2su_{N-1}^n - u_N^{n-1} + 2s\Delta x\mu v^{n-K}.$$

Solution for $t \in [T, T_f]$ *i.e.* for $n = K, \ldots, M-1$ for $j = 1, \ldots, N-1$, $u_j^{n+1} = s \left(u_{j+1}^n + u_{j-1}^n \right) + 2(1-s) u_i^n - u_j^{n-1}$ Dirichlet boundary condition $u_0^{n+1} = 0$. Neumann delay boundary condition $u_N^{n+1} = 2(1-s) u_N^n + 2s u_{N-1}^n - u_N^{n-1} + 2s\Delta x \mu v^{n-K}$. Delayed boundary equation $v^n = \frac{u_N^{n+1} - u_N^{n-1}}{2\Delta t}$.

4.1.2. **Discrete energy and CFL condition**. The aim of this section is to design a discrete energy that is preserved in the first step that is the free wave equation with Dirichlet and Neumann boundary condition. To this end, let us define:

• the discrete kinetic energy as:

(4.10)
$$E_k^n = \frac{1}{2} \sum_{j=0}^{N-1} \left(\frac{u_j^{n+1} - u_j^n}{\Delta t} \right)^2 + \frac{1}{4} \left(\frac{u_N^{n+1} - u_N^n}{\Delta t} \right)^2$$

• the discrete potential energy as:

(4.11)
$$E_p^n = \frac{1}{2} \sum_{j=0}^{N-1} \left(\frac{u_{j+1}^n - u_j^n}{\Delta x} \right) \left(\frac{u_{j+1}^{n+1} - u_j^{n+1}}{\Delta x} \right).$$

The total discrete energy is then defined as

(4.12)
$$\mathcal{E}^n = E_k^n + E_p^n.$$

Proposition 4.2. The discrete energy is conserved for all $t = 0, ..., T - \Delta t$, i.e.

$$\forall n = 1, \dots, K-1, \mathcal{E}^{n+1} = \mathcal{E}^n$$

Proof. For this sake, we multiply the equation (4.8) by $(u_j^{n+1}-u_j^{n-1})$, we sum over j = 1, ..., N-1 and we obtain:

(4.13)
$$\sum_{j=1}^{N-1} \frac{u_j^{n+1} - 2u_j^n + u_j^{n-1}}{\Delta t^2} (u_j^{n+1} - u_j^{n-1}) - \sum_{j=1}^{N-1} \frac{u_{j+1}^n - 2u_j^n + u_{j-1}^n}{\Delta x^2} (u_j^{n+1} - u_j^{n-1}) = 0.$$

Estimation of the first term of (4.13) We firstly have:

Estimation of the second term of (4.13). Using the same trick we have:

$$\begin{split} -\sum_{j=1}^{N-1} \frac{u_{j+1}^n - 2u_j^n + u_{j-1}^n}{\Delta x^2} (u_j^{n+1} - u_j^{n-1}) &= -\sum_{j=1}^{N-1} \frac{(u_{j+1}^n - u_j^n) - (u_j^n - u_{j-1}^n)}{\Delta x^2} (u_j^{n+1} - u_j^{n-1}) \\ &= -\sum_{j=1}^{N-1} \frac{(u_{j+1}^n - u_j^n)(u_j^{n+1} - u_j^{n-1})}{\Delta x^2} \\ &+ \sum_{j=1}^{N-1} \frac{(u_j^n - u_{j-1}^n)(u_j^{n+1} - u_j^{n-1})}{\Delta x^2}. \end{split}$$

So, by translation of index in the second term in the previous sum, and since $u_0^{n+1} = u_0^{n-1} = 0$, we will have:

$$\begin{aligned} - \sum_{j=1}^{N-1} \frac{u_{j+1}^n - 2u_j^n + u_{j-1}^n}{\Delta x^2} (u_j^{n+1} - u_j^{n-1}) &= -\sum_{j=0}^{N-1} \frac{(u_{j+1}^n - u_j^n)(u_j^{n+1} - u_j^{n-1})}{\Delta x^2} \\ &+ \sum_{j=0}^{N-2} \frac{(u_{j+1}^n - u_j^n)(u_{j+1}^{n+1} - u_{j+1}^{n-1})}{\Delta x^2}. \end{aligned}$$

Thus we have:

$$-\sum_{j=1}^{N-1} \frac{u_{j+1}^n - 2u_j^n + u_{j-1}^n}{\Delta x^2} (u_j^{n+1} - u_j^{n-1}) = \sum_{j=0}^{N-2} \frac{(u_{j+1}^{n+1} - u_j^{n+1})(u_{j+1}^n - u_j^n)}{\Delta x^2}$$
$$-\sum_{j=0}^{N-2} \frac{(u_{j+1}^{n-1} - u_j^{n-1})(u_{j+1}^n - u_j^n)}{\Delta x^2}$$
$$-\frac{(u_N^n - u_{N-1}^n)(u_{N-1}^{n+1} - u_{N-1}^{n-1})}{\Delta x^2}.$$

To treat the last term of (4.15), we multiply (4.9) by $(u_N^{n+1} - u_N^{n-1})$, to obtain:

$$\left(\frac{u_N^{n+1} - 2u_N^n + u_N^{n-1}}{\Delta t^2} - 2\frac{u_{N-1}^n - u_N^n}{\Delta x^2}\right)(u_N^{n+1} - u_N^{n-1}) = 0.$$

Thus we have:

(4.15)

$$\begin{aligned} -\frac{(u_N^n - u_{N-1}^n)(u_N^{n+1} - u_N^{n-1})}{\Delta x^2} &= \frac{1}{2} \left(\frac{u_N^{n+1} - 2u_N^n + u_N^{n-1}}{\Delta t^2} \right) (u_N^{n+1} - u_N^{n-1}) \\ &= \frac{1}{2} \frac{\left((u_N^{n+1} - u_N^n) - (u_N^n - u_N^{n-1}) \right) \left((u_N^{n+1} - u_N^n) + (u_N^n - u_N^{n-1}) \right)}{\Delta t^2} \\ &= \frac{1}{2} \frac{\left((u_N^{n+1} - u_N^n)^2 - (u_N^n - u_N^{n-1})^2 \right)}{\Delta t^2}. \end{aligned}$$

Thus we obtain:

(4.16)
$$\frac{1}{2} \frac{(u_N^{n+1} - u_N^n)^2 - (u_N^n - u_N^{n-1})^2}{\Delta t^2} + \frac{(u_N^n - u_{N-1}^n)(u_N^{n+1} - u_N^{n-1})}{\Delta x^2} = 0.$$

Adding (4.13) to (4.16) and substituting (4.15) and (4.14) into (4.13), we get:

$$(4.17) \qquad \sum_{j=1}^{N-1} \left(\frac{u_j^{n+1} - u_j^n}{\Delta t} \right)^2 + \frac{1}{2} \frac{(u_N^{n+1} - u_N^n)^2}{\Delta t^2} + \sum_{j=0}^{N-1} \frac{(u_{j+1}^{n+1} - u_j^{n+1})(u_{j+1}^n - u_j^n)}{\Delta x^2} \\ = \sum_{j=1}^{N-1} \left(\frac{u_j^n - u_j^{n-1}}{\Delta t} \right)^2 + \frac{1}{2} \frac{(u_N^n - u_N^{n-1})^2}{\Delta t^2} + \sum_{j=0}^{N-1} \frac{(u_{j+1}^n - u_j^n)(u_{j+1}^{n-1} - u_j^{n-1})}{\Delta x^2}$$

The preceding equation gives:

$$\forall n = 1, \dots, K-1, \mathcal{E}^{n+1} = \mathcal{E}^n.$$

By a standard von Neumann stability analysis (that is a discrete Fourier analysis, see for instance [2]), the numerical scheme is stable if and only if, the following Courant-Friedrichs-Lewy, CFL, condition holds:

 $\Delta t \leq \Delta x$.

The number $\frac{\Delta t}{\Delta x}$ is called the CFL number and is denoted in the following by CFL.

4.2. Internal case. Let $\mu \in \mathbb{R}$. We consider the following switching time delay problem:

(4.18)
$$u_{tt}(x,t) - u_{xx}(x,t) = 0 \quad \text{for } (x,t) \in (0,\ell) \times (0,2\ell)$$

(4.19)
$$u_{tt}(x,t) - u_{xx}(x,t) + \mu d(x) u_t(x,t-2\ell) = 0 \quad \text{in } (0,\ell) \times [2\ell,+\infty),$$

(4.20)
$$u(0,t) = u(\ell,t) = 0 \text{ for } t > 0,$$

where $d \in L^{\infty}(0, \ell)$ is a positive function which satisfies that there exists an nonempty set $I \subset (0, \ell)$ such that $d(x) \ge C > 0$, *a.e.* $x \in I$, and *C* is a constant, with the following initial data:

(4.21)
$$u(x,0) = u_0(x), \quad x \in (0,\ell)$$

and

(4.22)
$$u_t(x,0) = u_1(x) \quad x \in (0,\ell).$$

Here, $A = -\partial_x^2$ be the unbounded operator in $H = L^2(0, \ell)$ with domain:

$$H_1 = \mathcal{D}(A) = H^2(0,\ell) \cap H^1_0(0,\ell), H_{\frac{1}{2}} = \mathcal{D}(A^{\frac{1}{2}}) = H^1_0(0,\ell)$$

and

$$U = H = L^2(0, \ell), B \in \mathcal{L}(H), Bk = B^*k = \sqrt{dk}, \forall k \in H.$$

4.2.1. Construction of the numerical scheme. Let N be a non negative integer. Let $\Delta x = \frac{\ell}{N}$. Consider the uniform subdivision of $[0, \ell]$ given by:

$$0 = x_0 < x_1 < \dots < x_{N-1} < x_N = \ell, \quad i.e. \ x_j = j\Delta x, \ j = 0, \dots, N$$

For the sake of simplicity, we will suppose that the set $I \subset (0, \ell)$ is chosen as $I = [x_{i_0}, x_{i_1}]$, x_{i_0} and x_{i_1} being two mesh points.

Set $t^{n+1} - t^n = \Delta t$ for all $n \in \mathbb{N}$. We will suppose that $T = K \times \Delta t$, $K \in \mathbb{N}^*$ to write easily the discretization of the delay term. We will also suppose that $T_f = M\Delta t$, with M > K, be the final time.

First step: for time $t \in [0, T)$.

16

We proceed exactly the same way as in the previous section, the only novelty is now the Dirichlet boundary condition at $x = \ell$. For interior points $x \in (0, \ell)$ and for time $0 \le t < T$, the explicit finite-difference discretization of equation (4.18) writes for $n = 0, \ldots, K-1$, and $j = 1, \ldots, N-1$:

(4.23)
$$\frac{u_j^{n+1} - 2u_j^n + u_j^{n-1}}{\Delta t^2} - \frac{u_{j+1}^n - 2u_j^n + u_{j-1}^n}{\Delta x^2} = 0.$$

The Dirichlet boundary condition (4.20) at x = 0, $x = \ell$ reads: for $n = 0, \ldots, K - 1$,

(4.24)
$$u_0^n = u_N^n = 0$$

As in the previous section, using the initial condition (4.21)-(4.22), the scheme is defined for $t^1 = \Delta t$. Finally, the solution u can be computed at any time t^n .

In order to compute the solution u beyond the time T, we have to compute the quantity $d(x)u_t(x,t)$ for $x \in [x_{i_0}, x_{i_1}]$ and for time $t \in [0,T)$. The centered difference scheme is used and we compute:

for
$$j = i_0, \ldots, i_1, v_j^0 = d(x_j)u_1(x_j)$$
,
for $n = 1, \ldots, K - 1$, for $j = i_0, \ldots, i_1, v_j^n = d(x_j)\frac{u_j^{n+1} - u_j^{n-1}}{2\Delta t}$.

Second step: for time $t \in [T, T_f]$

The only novelty comes from the internal delay term. As we have set $T = K\Delta t$, the discretization of the wave equation with internal delayed damping and Dirichlet boundary condition reads: for $n = K, \ldots, M$,

$$\begin{aligned} \text{for } j &= 1, \dots, i_0 - 1 \quad \frac{u_j^{n+1} - 2u_j^n + u_j^{n-1}}{\Delta t^2} - \frac{u_{j+1}^n - 2u_j^n + u_{j-1}^n}{\Delta x^2} = 0, \\ \text{for } j &= i_0, \dots, i_1 \quad \frac{u_j^{n+1} - 2u_j^n + u_j^{n-1}}{\Delta t^2} - \frac{u_{j+1}^n - 2u_j^n + u_{j-1}^n}{\Delta x^2} + \mu v_j^{n-K} = 0, \\ \text{for } j &= i_1 + 1, \dots, N - 1 \quad \frac{u_j^{n+1} - 2u_j^n + u_j^{n-1}}{\Delta t^2} - \frac{u_{j+1}^n - 2u_j^n + u_{j-1}^n}{\Delta x^2} = 0, \\ u_0^n &= u_N^n = 0 \end{aligned}$$

whereas the computation of the internal delay damping term reads: for $n = K, \ldots, M$,

for
$$j = i_0, \dots, i_1, v_j^n = d(x_j) \frac{u_j^{n+1} - u_j^{n-1}}{2\Delta t}$$

As in the previous section, we set $s = \left(\frac{\Delta t}{\Delta x}\right)^2$. Let us now summarize the computation of the solution and the internal delay term.

First step: for time $t \in [0, T)$

Second step: for time $t \in [T, T_f]$

Let $M \ge K$. We denote $T_f = M\Delta t$ the final time. The only novelty comes from the internal delay term defined for $x \in [x_{i_0}, x_{i_1}]$. Solution for $t \in [T, T_f]$ *i.e.* for $n = K, \ldots, M - 1$.

$$\begin{aligned} &\text{for } j = 1, \dots, i_0 - 1, \ u_j^{n+1} = s\left(u_{j+1}^n + u_{j-1}^n\right) + 2(1-s) \ u_i^n - u_j^{n-1}, \\ &\text{for } j = i_0, \dots, i_1, \ u_j^{n+1} = s\left(u_{j+1}^n + u_{j-1}^n\right) + 2(1-s) \ u_i^n - u_j^{n-1} - \mu \Delta t^2 v_j^{n-K}, \\ &\text{for } j = i_0 + 1, \dots, N-1, \ , \ u_j^{n+1} = s\left(u_{j+1}^n + u_{j-1}^n\right) + 2(1-s) \ u_i^n - u_j^{n-1} - \mu \Delta t^2 v_j^{n-K}, \\ &\text{Dirichlet boundary condition} \qquad u_0^{n+1} = 0. \\ &\text{Dirichlet boundary condition} \qquad u_N^{n+1} = 0. \\ &\text{Internal delay term} \qquad &\text{for } j = i_0, \dots, i_1, \ v_j^n = d(x_j) \frac{u_j^{n+1} - u_j^{n-1}}{2\Delta t}. \end{aligned}$$

4.2.2. **Discrete energy**. The aim of this section is to design a discrete energy that is preserved in the first step that is the free wave equation with Dirichlet boundary conditions. To this end, let us define:

• the discrete kinetic energy as:

$$E_k^n = \frac{1}{2} \sum_{j=1}^{N-1} \left(\frac{u_j^{n+1} - u_j^n}{\Delta t} \right)^2 ,$$

• the discrete potential energy as:

$$E_p^n = \frac{1}{2} \sum_{j=0}^{N-1} \left(\frac{u_{j+1}^n - u_j^n}{\Delta x} \right) \left(\frac{u_{j+1}^{n+1} - u_j^{n+1}}{\Delta x} \right) \ .$$

The total discrete energy is then defined as

(4.25)
$$\mathcal{E}^n = E_k^n + E_p^n.$$

Proposition 4.3. The discrete energy is conserved for all $t = 0, ..., T - \Delta t$, i.e.

$$\forall n = 1, \dots, K-1, \mathcal{E}^{n+1} = \mathcal{E}^n.$$

Proof. For this sake, we multiply the equation (4.23) by $(u_j^{n+1} - u_j^{n-1})$, we sum over $j = 1, \ldots, N - 1$ and we obtain:

$$(4.26) \qquad \sum_{j=1}^{N-1} \frac{u_j^{n+1} - 2u_j^n + u_j^{n-1}}{\Delta t^2} (u_j^{n+1} - u_j^{n-1}) - \sum_{j=1}^{N-1} \frac{u_{j+1}^n - 2u_j^n + u_{j-1}^n}{\Delta x^2} (u_j^{n+1} - u_j^{n-1}) = 0.$$

Estimation of the first term of (4.26) We firstly have:

Estimation of the second term of (4.26). Using the same trick we have:

$$\begin{split} -\sum_{j=1}^{N-1} \frac{u_{j+1}^n - 2u_j^n + u_{j-1}^n}{\Delta x^2} (u_j^{n+1} - u_j^{n-1}) &= -\sum_{j=1}^{N-1} \frac{(u_{j+1}^n - u_j^n) - (u_j^n - u_{j-1}^n)}{\Delta x^2} (u_j^{n+1} - u_j^{n-1}) \\ &= -\sum_{j=1}^{N-1} \frac{(u_{j+1}^n - u_j^n)(u_j^{n+1} - u_j^{n-1})}{\Delta x^2} \\ &+ \sum_{j=1}^{N-1} \frac{(u_j^n - u_{j-1}^n)(u_j^{n+1} - u_j^{n-1})}{\Delta x^2}. \end{split}$$

So, by translation of index in the second term in the previous sum, and since

$$\begin{split} u_0^{n+1} &= u_0^{n-1} = 0 \ , \\ u_N^{n+1} &= u_N^{n-1} = 0 \ , \end{split}$$

we will have:

$$-\sum_{j=1}^{N-1} \frac{u_{j+1}^n - 2u_j^n + u_{j-1}^n}{\Delta x^2} (u_j^{n+1} - u_j^{n-1}) = -\sum_{j=0}^{N-1} \frac{(u_{j+1}^n - u_j^n)(u_j^{n+1} - u_j^{n-1})}{\Delta x^2} + \sum_{j=0}^{N-1} \frac{(u_{j+1}^n - u_j^n)(u_{j+1}^{n+1} - u_{j+1}^{n-1})}{\Delta x^2}.$$

Thus we have:

(4

$$-\sum_{j=1}^{N-1} \frac{u_{j+1}^n - 2u_j^n + u_{j-1}^n}{\Delta x^2} (u_j^{n+1} - u_j^{n-1}) = \sum_{j=0}^{N-1} \frac{(u_{j+1}^{n+1} - u_j^{n+1})(u_{j+1}^n - u_j^n)}{\Delta x^2} - \sum_{j=0}^{N-1} \frac{(u_{j+1}^{n-1} - u_j^{n-1})(u_{j+1}^n - u_j^n)}{\Delta x^2}.$$
28)

Substituting (4.28) and (4.27) into (4.26), we get

(4.29)
$$\sum_{j=1}^{N-1} \left(\frac{u_j^{n+1} - u_j^n}{\Delta t} \right)^2 + \sum_{j=0}^{N-1} \frac{(u_{j+1}^{n+1} - u_j^{n+1})(u_{j+1}^n - u_j^n)}{\Delta x^2} \\ = \sum_{j=1}^{N-1} \left(\frac{u_j^n - u_j^{n-1}}{\Delta t} \right)^2 + \sum_{j=0}^{N-1} \frac{(u_{j+1}^n - u_j^n)(u_{j+1}^{n-1} - u_j^{n-1})}{\Delta x^2}.$$

The preceding equation gives:

$$\forall n = 1, \dots, K - 1, \, \mathcal{E}^{n+1} = \mathcal{E}^n \,.$$

As in the previous case, in order to obtain a stable numerical scheme, the following Courant-Friedrichs-Lewy, CFL, condition holds:

$$\Delta t \leq \Delta x \; .$$

4.3. **Pointwise case.** Let $\mu \in \mathbb{R}$, $\ell > 0$, $\xi \in (0, \ell)$. We consider the following switching time delay problem:

(4.30) $u_{tt}(x,t) - u_{xx}(x,t) = 0 \quad \text{for } (x,t) \in (0,\ell) \times (0,2\ell)$

$$(4.31) u_{tt}(x,t) - u_{xx}(x,t) + \mu u_t(\xi,t-2\ell) \,\delta_{\xi} = 0 \quad \text{for } (x,t) \in (0,\ell) \times (2\ell,+\infty)$$

- (4.32) $u(0,t) = 0 \quad \text{for } t > 0$
- (4.33) $u_x(\ell, t) = 0 \quad \text{for } t > 0$

with the following initial data:

$$(4.34) u(x,0) = u_0(x), \quad x \in (0,\ell)$$

and

(4.35)
$$u_t(x,0) = u_1(x) \quad x \in (0,\ell)$$

Here, $A = -\partial_x^2$ be the unbounded operator in $H = L^2(0, \ell)$ with domain

$$H_1 = \mathcal{D}(A) = \left\{ u \in H^2(0,\ell); \ u(0) = 0, \ u_x(\ell) = 0 \right\}, \quad H_{\frac{1}{2}} = \mathcal{D}(A^{\frac{1}{2}}) = \left\{ u \in H^1(0,\ell); \ u(0) = 0 \right\}$$
 and

$$U = \mathbb{R}, B \in \mathcal{L}(\mathbb{R}, H_{-\frac{1}{2}}), Bk = k \,\delta_{\xi}, \forall k \in \mathbb{R}, B^*u = u(\xi), \forall u \in H_{\frac{1}{2}}$$

We have according to [10] (see [6, 7] for the case without delay) the following stability result:

Theorem 4.4. [10]

(1) We suppose that $\xi = \frac{\ell}{2}$. Then for any $\mu \in (0,2)$ there exist positive constants C_1, C_2 such that for all initial data in \mathcal{H} , the solution of problem (4.30)-(4.35) satisfies

(4.36)
$$E(t) \le C_1 e^{-C_2 t}$$

The constant C_1 depends on the initial data, on ℓ and on μ , while C_2 depends only on ℓ and on μ .

(2) For $\xi = \frac{\ell}{2}$ and $\mu = 2$, if we denote $S_{p,2}(t)$ the propagator of the pointwise delayed control problem with $\mu = 2$, we have by definition:

$$\forall t > 0, \mathcal{S}_{p,2}(t) \begin{pmatrix} u_0 \\ u_1 \end{pmatrix} = \begin{pmatrix} u \\ u_t \end{pmatrix}.$$

And we have that

$$\forall t > 0, \, \forall n \in \mathbb{N}^*, \, \mathcal{S}_{p,2}(t+2nT) \begin{pmatrix} u_0 \\ u_1 \end{pmatrix} = -\mathcal{S}_{p,2}(t) \begin{pmatrix} u_0 \\ u_1 \end{pmatrix}$$

wehere as

$$\forall t > 0, \forall n \in \mathbb{N}^*, \mathcal{S}_{p,2}(t + (2n+1)T) \begin{pmatrix} u_0 \\ u_1 \end{pmatrix} = \mathcal{S}_{p,2}(t) \begin{pmatrix} u_0 \\ u_1 \end{pmatrix}$$

So in particular, we have that $S_{p,2}$ is 3T-periodic.

We note here that the proof of the second assertion of the above Theorem 4.4 is a simple adaptation of the proof of [8, Theorem 1.2] for $\mu = 2$ and $\xi = \frac{\ell}{2}$.

Remark 4.5. In the sequel we will thus choose $\xi = \frac{\ell}{2}$.

The proof of the preceding result conducted by Ammari, Nicaise and Pignotti in [10] is based on the following equivalent formulation of (4.31)-(4.32)-(4.33) for $t \ge 2\ell$:

(4.37)
$$u_{tt}^{-}(x,t) - u_{xx}^{-}(x,t) = 0 \text{ for } x \in (0,\xi), t \ge 2k$$

(4.38) $u_{tt}^+(x,t) - u_{xx}^+(x,t) = 0 \text{ for } x \in (\xi,\ell), t \ge 2\ell$

(4.39)
$$u^{-}(\xi^{-},t) = u^{+}(\xi^{+},t) \text{ for } t \ge 24$$

(4.40)
$$u_x^-(\xi^-, t) - u_x^+(\xi^+, t) = -\mu u_t^-(\xi^-, t - 2\ell) = -\mu u_t^+(\xi^+, t - 2\ell) \quad \text{for } t \ge 2\ell$$

(4.41)
$$u(0,t) = 0 \quad \text{for } t > 2\ell$$

(4.42)
$$u_x(\ell, t) = 0 \quad \text{for } t \ge 2\ell$$

where we define for ξ^- (for instance):

$$u^{-}(\xi^{-},t) = \lim_{\substack{x \to \xi \\ x < \xi}} u^{-}(x,t) , \ u^{-}_{x}(\xi^{-},t) = \lim_{\substack{x \to \xi \\ x < \xi}} u^{-}_{x}(x,t).$$

A singularity is thus occurring at the point ξ ; so a finite difference discretization is not well adapted to furnish a good approximation. We thus decide to use rather a finite volume scheme well adapted to deal with the case of a point source term [17] 4.3.1. Construction of the numerical scheme: the finite volume discretization. Let N be a non negative even integer. Let $\Delta x = \frac{\ell}{N}$. Following [17], the uniform admissible mesh \mathcal{T} of the interval $(0,\ell)$ is given by the family $\{K_j, j \in \{1, \dots, N\}\}$ of control volumes such that $K_j = (x_{j-\frac{1}{2}}, x_{j+\frac{1}{2}})$ and the family $(x_j)_{j=0,\dots,N+1}$ assumed to be the center of $(K_j)_{j=1,\dots,N}$ such that:

$$0 = x_0 = x_{\frac{1}{2}} < x_1 < x_{\frac{3}{2}} < x_2 < \dots < x_{N-\frac{1}{2}} < x_N < x_{N+\frac{1}{2}} = x_{N+1} = \ell$$

that is $x_{j+\frac{1}{2}} = j\Delta x$, $j = 0, \dots, N$, $x_j = (j - \frac{1}{2})\Delta x$, $j = 1, \dots, N$. For $j = 1, \dots, N$, we denote $h_j = x_{j+1} - x_{j-1} = \Delta x$

$$h_{j} = x_{j+\frac{1}{2}} - x_{j-\frac{1}{2}} - \Delta x$$

$$h_{j}^{-} = x_{j} - x_{j-\frac{1}{2}} = \frac{\Delta x}{2}$$

$$h_{j}^{+} = x_{j+1} - x_{j+\frac{1}{2}} = \frac{\Delta x}{2}$$

$$h_{j+\frac{1}{2}} = x_{j+1} - x_{j-1} = \Delta x$$

$$K_{j} = (x_{j-\frac{1}{2}}, x_{j+\frac{1}{2}})$$

As $0 = x_0 = x_{\frac{1}{2}}$, we have $h_{\frac{1}{2}} = \frac{\Delta x}{2}$ and as $x_{N+\frac{1}{2}} = x_{N+1} = \ell$, we also have $h_{N+\frac{1}{2}} = \frac{\Delta x}{2}$



FIGURE 1. A model representing the admissible one-dimensional mesh

Set $t^{n+1} - t^n = \Delta t$ for all $n \in \mathbb{N}$. We will suppose that $2\ell = T = K \times \Delta t$, $K \in \mathbb{N}^*$ to write easily the discretization of the delay term. Using this uniform discretization, the point $x = \frac{\ell}{2}$ is the point $x_{j_0+\frac{1}{2}} = \frac{\ell}{2}$ where $j_0 = N/2$. For $j = 1, \ldots, N$, and t > 0, we denote

$$u_j(t) = \frac{1}{h_j} \int_{x_{j-\frac{1}{2}}}^{x_{j+\frac{1}{2}}} u(x,t) dx$$

the mean value of u on the cell K_j and for $t = t_n$, we denote $u_j^n = u_j(t_n)$.

As $\forall t \in [0,T]$, u(0,t) = 0, we will denote $\forall n = 1, ..., N$, $u_0^n = 0$. If needed, we also denote $u_{N+1}^n = u(\ell, t^n)$.

First step: for time $t \in [0, T)$.

As originally pointed out by Eymard, Gallouët and Herbin [17], the principle of the finite volume method for conservation laws is to integrate the equation (4.30) on each cell K_j and then approximate the fluxes at the interface. Thus for j = 1, ..., N, and for $t = t^n$, we got:

$$\int_{K_j} u_{tt}(x, t^n) dx - \left(u_x(x_{j+\frac{1}{2}}, t^n) - u_x(x_{j-\frac{1}{2}}, t^n) \right) = 0$$

At this stage, we denote by $F_{j+\frac{1}{2}}^n$ the numerical flux which is an approximation of the flux at the interface $-u_x(x_{j+\frac{1}{2}}, t^n)$.

As $u_x(\ell, t^n) = 0$, we already have $F_{N+\frac{1}{2}}^n = 0$ and we can set $u_{N+1}^n = u_N^n$.

Since u_j^n may also be viewed as an approximation of $u(x_j, t^n)$ and $h_{j+\frac{1}{2}} = x_{j+1} - x_j$, as $u(0, t^n) = 0$, as done in [17], a reasonable choice for the computation of the numerical fluxes $F_{j+\frac{1}{2}}^n$ is given by:

$$F_{j+\frac{1}{2}}^{n} = \begin{cases} -\frac{u_{1}^{n}}{h_{\frac{1}{2}}}, & \text{if } j = 0, \\ -\left(\frac{u_{j+1}^{n} - u_{j}^{n}}{h_{j+\frac{1}{2}}}\right) & j = 1, \dots, N-1 \\ 0 & \text{if } j = N \end{cases} = \begin{cases} -\frac{2u_{1}^{n}}{\Delta x}, & \text{if } j = 0, \\ -\left(\frac{u_{j+1}^{n} - u_{j}^{n}}{\Delta x}\right) & j = 1, \dots, N-1, \\ 0 & \text{if } j = N \end{cases}$$

For the sake of homogeneity, we will denote $\alpha_{j+\frac{1}{2}}$ as

$$\alpha_{j+\frac{1}{2}} = \begin{cases} \frac{1}{h_{\frac{1}{2}}}, & \text{if } j = 0, \\ \frac{1}{h_{j+\frac{1}{2}}}, & j = 1, \dots, N-1 \end{cases} = \begin{cases} \frac{2}{\Delta x}, & \text{if } j = 0, \\ \frac{1}{\Delta x}, & j = 1, \dots, N-1 \\ 0, & \text{if } j = N \end{cases}$$

such that

forall
$$j = 1, ..., N$$
, $F_{j+\frac{1}{2}}^n = -\alpha_{j+\frac{1}{2}} \left(u_{j+1}^n - u_j^n \right)$

$$d^2 \int_{V} u(x,t^n) dx$$

Moreover since $\int_{K_j} u_{tt}(x, t^n) dx = \frac{J_{K_j}}{dt^2}$, the numerical approximation of the equation (4.30) is given by: for $j = 1, \dots, N-1$,

$$h_j u_j(t^n)_{tt} + (F_{j+\frac{1}{2}}^n - F_{j-\frac{1}{2}}^n) = 0$$

The central difference approximation of the second time derivative permits us to finally write: for $n \ge 1$, for $j = 1, \ldots, N$,

$$h_j \frac{u_j^{n+1} - 2u_j^n + u_j^{n-1}}{\Delta t^2} + (F_{j+\frac{1}{2}}^n - F_{j-\frac{1}{2}}^n) = 0$$

or in its homogeneous form: for $n \ge 1$, for $j = 1, \ldots, N$,

(4.43)
$$h_{j} \frac{u_{j}^{n+1} - 2u_{j}^{n} + u_{j}^{n-1}}{\Delta t^{2}} - \left[\alpha_{j+\frac{1}{2}} \left(u_{j+1}^{n} - u_{j}^{n}\right) - \alpha_{j-\frac{1}{2}} \left(u_{j}^{n} - u_{j-1}^{n}\right)\right] = 0.$$

According to the initial conditions given by equations (4.34), we firstly choose: for $j = 1, \ldots, N$,

$$u_j^0 = u_0(x_j)$$

We can use the second initial conditions (4.35) to find the values of u at time $t^1 = \Delta t$, by employing a "ghost" time-boundary *i.e.* $t^{-1} = -\Delta t$ and the second-order central difference formula:

for
$$j = 1, ..., N$$
, $u_1(x_j) = \left. \frac{\partial u}{\partial t} \right|_{x_j, 0} = \left. \frac{u_j^1 - u_j^{-1}}{2\Delta t} + O(\Delta t^2). \right.$

Thus we have for $j = 1, \ldots, N$:

$$u_j^{-1} = u_j^1 - 2\Delta t \ u_1(x_j) \ .$$

Setting n = 0, in the numerical scheme (4.43), the previous equalities permits to compute $(u_i^1)_{j=0,N}$. Finally, the solution u can be computed at any time t^n .

In order to compute the solution u beyond the time T, we have to compute the quantity $u_t(\xi, t)$ for time $t \in [0, T)$. As $\xi = x_{j_0+\frac{1}{2}}$, since the mesh is uniform, we use the mean value of u_{j_0} and u_{j_0+1} as an approximation of $u(x_{j_0+\frac{1}{2}}, t)$. We will see in the next construction of the numerical

fluxes that this formula is well adapted. We use the centered difference scheme in time to finally compute:

$$v^{0} = u_{1}(x_{j_{0}}),$$

for $n = 1, \dots, K - 1$, $u_{t}(\xi, t^{n}) \approx v^{n} = \frac{\frac{\left(u_{j_{0}+1}^{n+1} + u_{j_{0}-1}^{n+1}\right)}{2} - \frac{\left(u_{j_{0}+1}^{n-1} + u_{j_{0}-1}^{n-1}\right)}{2}}{2\Delta t}.$

Second step: for time t > T.

We will use the equivalent formulation (4.37)-(4.42) to construct the numerical scheme recalling that $x_{j_0+\frac{1}{2}} = \xi$. As done before, we integrate the equation (4.37) and (4.38) on each cell K_j and then approximate the fluxes at the interface. Remarking that the cell $K_{j_0-1} = (x_{j_0-\frac{1}{2}}, x_{j_0+\frac{1}{2}})$ and $K_{j_0} = (x_{j_0+\frac{1}{2}}, x_{j_0+\frac{3}{2}})$, we denote

• for $j = 1, ..., j_0$,

• for $j = j_0 + 1, \dots N$,

$$u_{j}^{-,n} = \frac{1}{h_{j}} \int_{x_{j-\frac{1}{2}}}^{x_{j+\frac{1}{2}}} u^{-}(x,t) dx$$
$$u_{j}^{+,n} = \frac{1}{h_{j}} \int_{x_{j-\frac{1}{2}}}^{x_{j+\frac{1}{2}}} u^{+}(x,t) dx.$$

Since the flux $u_x(x_{j_0+\frac{1}{2}},t)$ is not define, we have to treat the two cells K_{j_0} , K_{j_0+1} separately.

As done before, integrating (4.37) on the cell K_j gives:

(4.44) for
$$j = 1, ..., j_0 - 1$$
 $h_j \frac{u_j^{-,n+1} - 2u_j^{-,n} + u_j^{-,n-1}}{\Delta t^2} + (F_{j+\frac{1}{2}}^{-,n} - F_{j-\frac{1}{2}}^{-,n}) = 0$

with

for
$$j = 1, \dots, j_0 - 1$$
, $F_{j+\frac{1}{2}}^{-,n} = \begin{cases} -\frac{u_1^{-,n}}{h_1} & \text{if } j = 0\\ -\left(\frac{u_{j+1}^{-,n} - u_j^{-,n}}{h_{j+\frac{1}{2}}}\right) & = \begin{cases} -\frac{2u_1^{-,n}}{\Delta x} & \text{if } j = 0\\ -\left(\frac{u_{j+1}^{-,n} - u_j^{-,n}}{\Delta x}\right). \end{cases}$

Again, integrating (4.38) on the cell K_j gives:

(4.45) for
$$j = j_0 + 2, N$$
 $h_j \frac{u_j^{+,n+1} - 2u_j^{+,n} + u_j^{+,n-1}}{\Delta t^2} + (F_{j+\frac{1}{2}}^{+,n} - F_{j-\frac{1}{2}}^{+,n}) = 0$

with

for
$$j = j_0 + 2..., N$$
, $F_{j+\frac{1}{2}}^{+,n} = \begin{cases} -\left(\frac{u_{j+1}^{+,n} - u_j^{+,n}}{h_{j+\frac{1}{2}}}\right) \\ 0 & \text{if } j = N \end{cases} = \begin{cases} -\left(\frac{u_{j+1}^{+,n} - u_j^{+,n}}{\Delta x}\right) \\ 0 & \text{if } j = N \end{cases}$

Let us now treat the two cells K_{j_0} and K_{j_0+1} .

We integrate (4.37) on the cell K_{j_0} to obtain:

$$\int_{K_{j_0}} u_{tt}^-(x,t^n) dx - \left(u_x^-(x_{j_0+\frac{1}{2}},t^n) - u_x^-(x_{j_0-\frac{1}{2}},t^n)\right) = 0$$

As $x_{j_0+\frac{1}{2}} = \xi$, we replace $u_x^-(x_{j_0+\frac{1}{2}}, t^n)$ by $u_x^-(\xi^-, t^n)$.

Of course we already have approximated $-u_x^-(x_{j_0-\frac{1}{2}},t^n)$ by the flux $F_{j_0-\frac{1}{2}}^{-,n}$.

We integrate (4.38) on the cell K_{j_0+1} to obtain:

$$\int_{K_{j_0}+1} u_{tt}^+(x,t^n) dx - \left(u_x^+(x_{j_0+\frac{3}{2}},t^n) - u_x^+(x_{j_0+\frac{1}{2}},t^n)\right) = 0$$

As $x_{j_0+\frac{1}{2}} = \xi$, we replace $u_x^+(x_{j_0+\frac{1}{2}}, t^n)$ by $u_x^+(\xi^+, t^n)$.

Of course we already approximated $-u^+_x(x_{j_0+\frac{3}{2}},t^n)$ by the flux $F^{+,n}_{j_0+\frac{3}{2}}$.

Let us now define the auxiliary variable $u_{j_0+\frac{1}{2}}^n$ as an approximation of $u^+(\xi^+, t^n)$. Because of the continuity equation (4.39), we firstly have $u_{j_0+\frac{1}{2}}^n = u^+(\xi^+, t^n) = u^-(\xi^-, t^n)$.

So a good approximation of $u_x^-(\xi^-, t^n)$ and $u_x^+(\xi^+, t^n)$ is respectively:

$$u_x^-(\xi^-, t^n) \approx -F_{j_0+\frac{1}{2}}^{-,n} = \frac{u_{j_0+\frac{1}{2}}^n - u_{j_0}^{-,n}}{h_{j_0}^-}$$
 and $u_x^+(\xi^+, t^n) \approx -F_{j_0+\frac{1}{2}}^{+,n} = \frac{u_{j_0+1}^{+,n} - u_{j_0+\frac{1}{2}}^n}{h_{j_0+1}^+}$.

As the numerical scheme must verify the transmission condition (4.40), to compute $u_{j_0+\frac{1}{2}}^n$, we use the discrete analog of (4.40):

$$-F_{j_0+\frac{1}{2}}^{-,n} + F_{j_0+\frac{1}{2}}^{+,n} = -\mu u_t(\xi, t^n - 2\ell) \; .$$

Replacing the two fluxes by their expression leads to:

$$\frac{u_{j_0+\frac{1}{2}}^n - u_{j_0}^{-,n}}{h_{j_0}^-} - \frac{u_{j_0+1}^{+,n} - u_{j_0+\frac{1}{2}}^n}{h_{j_0+1}^+} = -\mu u_t(\xi, t^n - 2\ell).$$

As we have considered a regular mesh, that is: $h_{j_0}^- = h_{j_0+1}^+ = \Delta x/2$, we obtain finally:

(4.46)
$$u_{j_0+\frac{1}{2}}^n = -\frac{\Delta x}{4}\mu u_t(\xi, t^n - 2\ell) + \frac{u_{j_0+1}^{+,n} + u_{j_0}^{-,n}}{2}.$$

So the two fluxes are computed by:

(4.47)
$$F_{j_0+\frac{1}{2}}^{-,n} = \frac{\mu u_t(\xi, t^n - 2\ell)}{2} - \frac{u_{j_0+1}^{+,n} - u_{j_0}^{-,n}}{\Delta x}$$

(4.48)
$$F_{j_0+\frac{1}{2}}^{+,n} = -\frac{\mu u_t(\xi, t^n - 2\ell)}{2} - \frac{u_{j_0+1}^{+,n} - u_{j_0}^{-,n}}{\Delta x}.$$

On the cell K_{j_0} , we get the fully discrete numerical scheme:

$$h_{j_0} \frac{u_{j_0}^{-,n+1} - 2u_{j_0}^{-,n} + u_{j_0}^{-,n-1}}{\Delta t^2} + (F_{j_0+\frac{1}{2}}^{-,n} - F_{j_0-\frac{1}{2}}^{-,n}) = 0$$

which writes:

$$(4.49) \quad \Delta x \; \frac{u_{j_0}^{-,n+1} - 2u_{j_0}^{-,n} + u_{j_0}^{-,n-1}}{\Delta t^2} - \left(\frac{u_{j_0+1}^{+,n} - u_{j_0}^{-,n}}{\Delta x} - \frac{u_{j_0}^{-,n} - u_{j_0-1}^{-,n}}{\Delta x}\right) = -\frac{\mu u_t(\xi, t^n - 2\ell)}{2}$$

On the cell K_{j_0+1} , we get the fully discrete numerical scheme:

$$h_{j_0+1} \frac{u_{j_0+1}^{+,n+1} - 2u_{j_0+1}^{+,n} + u_{j_0+1}^{+,n-1}}{\Delta t^2} + (F_{j_0+\frac{3}{2}}^{+,n} - F_{j_0+\frac{1}{2}}^{+,n}) = 0$$

which writes:

$$(4.50) \quad \Delta x \ \frac{u_{j_0+1}^{+,n+1} - 2u_{j_0+1}^{+,n} + u_{j_0+1}^{+,n-1}}{\Delta t^2} - \left(\frac{u_{j_0+2}^{+,n} - u_{j_0+1}^{+,n}}{\Delta x} - \frac{u_{j_0+1}^{+,n} - u_{j_0}^{-,n}}{\Delta x}\right) = -\frac{\mu u_t(\xi, t^n - 2\ell)}{2}.$$

So one can remark that the delay pointwise term is equally splitted on the cell K_{j_0} and K_{j_0+1} due to the fact that the mesh is uniform.

At this stage, it remains to compute the value of $u_t(\xi, t^n)$. We first approximate the partial time derivative by the centered difference

$$u_t(\xi, t^n) \approx \frac{u_{j_0+\frac{1}{2}}^{n+1} - u_{j_0+\frac{1}{2}}^{n-1}}{2\Delta t}$$

Then we replace the value of $u_{j_0+\frac{1}{2}}^{n+1}$ and $u_{j_0+\frac{1}{2}}^{n-1}$ using the equation (4.46) and as $T = K\Delta T$ we use the saved value $v^{n+1-K} \approx u_t(\xi, t^{n+1} - 2\ell)$ and $v^{n-1-K} \approx u_t(\xi, t^{n-1} - 2\ell)$ to obtain:

$$u_t(\xi, t^n) \approx v^n = \frac{-\frac{\Delta x}{4}\mu\left(v^{n+1-K} - v^{n-1-K}\right)\right) + \frac{\left(u_{j_0+1}^{+,n+1} + u_{j_0-1}^{-,n+1}\right)}{2} - \frac{\left(u_{j_0+1}^{+,n-1} + u_{j_0-1}^{-,n-1}\right)}{2}}{2\Delta t}.$$

We set $s = \left(\frac{\Delta t}{\Delta x}\right)^2$. Let us now summarize, the computation of the solution and the pointwise delay term in the case of a uniform mesh. Because the definition of the numerical fluxes is not the same for the first cell and the last cell, we have to treat separately these two cells. Let us also remark that contrary to the two preceding cases, there is no need to compute boundary values since the boundary conditions are used to construct the numerical fluxes.

$$\begin{aligned} \text{First step: for time } t \in [0, T) \\ \text{Initialization for } j = 1, \dots, N, \, u_j^0 = u_0(x_j) \quad v^0 = u_1(\ell/2) \\ \text{Solution for } t = \Delta t \\ & \text{for } j = 1, \quad u_1^1 = \frac{s}{2} \left(u_2^0 - 3u_1^0 \right) + u_1^0 + \Delta t \, u_1(x_1) \\ & \text{for } j = 2, \dots, N-1, \quad u_j^1 = \frac{s}{2} \left(u_{j+1}^0 - 2u_j^0 - u_{j-1}^0 \right) + u_j^0 + \Delta t \, u_1(x_j) \\ & \text{for } j = N, \quad u_N^1 = \frac{s}{2} \left(u_{N-1}^0 - u_1^N \right) + u_N^0 + \Delta t \, u_1(x_N) \end{aligned}$$
Solution for $t \in (\Delta t, T)$ i.e. for $n = 1, \dots, K-1$
for $j = 1, \quad u_1^{n+1} = s \left(u_2^n - 3u_1^n \right) + 2u_1^n - u_1^{n-1} \\ & \text{for } j = 2, \dots, N-1, \quad u_j^{n+1} = s \left(u_{j+1}^n - 2u_j^n - u_{j-1}^n \right) + 2u_j^n - u_j^{n-1} \\ & \text{for } j = N, \quad u_N^{n+1} = s \left(u_{N-1}^n - u_N^n \right) + 2u_N^n - u_N^{n-1} \\ & \text{Delayed pointwise term} \quad v^n = \frac{\frac{(u_{j_0+1}^{n+1} + u_{j_0-1}^{n+1})}{2\Delta t} - \frac{(u_{j_0+1}^{n-1} + u_{j_0-1}^{n-1})}{2} \\ \end{array}$

Second step: for time $t \in [T, T_f]$

Solution for $t \in [T, T_f]$ *i.e.* for $n = K, \dots, M - 1$ for j = 1, $u_1^{-,n+1} = s\left(u_2^{-,n} - 3u_1^{-,n}\right) + 2u_1^{-,n} - u_1^{-,n-1}$ for $j = 2, \dots, j_0 - 1$, $u_j^{-,n+1} = s\left(u_{j+1}^{-,n} - 2u_j^{-,n} - u_{j-1}^{-,n}\right) + 2u_j^{-,n} - u_j^{-,n-1}$ for $j = j_0$, $u_{j_0}^{-,n+1} = s\left(u_{j_0+1}^{+,n} - 2u_{j_0}^{-,n} - u_{j_0-1}^{-,n}\right) + 2u_{j_0}^{-,n} - u_{j_0-1}^{-,n-1} - \frac{s\Delta x\mu v^{n-K}}{2}$ for $j = j_0 + 1$, $u_{j_0+1}^{+,n+1} = s\left(u_{j_0+2}^{+,n} - 2u_{j_0+1}^{+,n} - u_{j_0}^{-,n}\right) + 2u_{j_0+1}^{+,n} - u_{j_0+1}^{+,n-1} - \frac{s\Delta x\mu v^{n-K}}{2}$ for $j = j_0 + 2, \dots, N - 1$, $u_j^{+,n+1} = s\left(u_{j+1}^{+,n} - 2u_j^{+,n} - u_{j-1}^{+,n}\right) + 2u_j^{+,n} - u_j^{+,n-1}$ for j = N, $u_N^{+,n+1} = s\left(u_{N-1}^{+,n} - u_N^{+,n}\right) + 2u_N^{+,n} - u_N^{+,n-1}$ Delayed pointwise term $v^n = \frac{-\frac{\Delta x}{4}\mu \left(v^{n+1-K} - v^{n-1-K}\right) + \frac{\left(u_{j_0+1}^{+,n+1} + u_{j_0-1}^{-,n+1}\right)}{2} - \frac{\left(u_{j_0+1}^{+,n-1} + u_{j_0-1}^{-,n-1}\right)}{2}$. 4.3.2. **Discrete energy and CFL condition**. The aim of this section is to design a discrete energy that is preserved in the first step that is the free wave equation with Dirichlet and Neumann boundary condition in the context of a discretization by a finite volume method. To this end, let us define:

• the discrete kinetic energy as:

$$E_{k}^{n} = \frac{1}{2} \sum_{i=1}^{N} h_{i} \left(\frac{u_{i}^{n+1} - u_{i}^{n}}{\Delta t} \right)^{2}$$

• the discrete potential energy as:

$$E_p^n = \frac{1}{2} \sum_{i=0}^N \alpha_{i+\frac{1}{2}} (u_{i+1}^{n+1} - u_i^{n+1}) (u_{i+1}^n - u_i^n).$$

Proposition 4.6. The discrete energy is conserved for all $t = 0, ..., T - \Delta t$ i.e.

$$\forall n = 1, \dots, K - 1, \mathcal{E}^{n+1} = \mathcal{E}^n.$$

Proof. The proof is similar to the continuous case: we multiply the discrete problem by the approximation of u_t . We multiply the left and right and right and right $(u_i^{n+1} - u_i^{n-1})$ and we sum over i = 1, ..., N to obtain:

(4.51)
$$\sum_{i=1}^{N} h_i \left(\frac{u_i^{n+1} - 2u_i^n + u_i^{n-1}}{\Delta t^2} \right) (u_i^{n+1} - u_i^{n-1}) \\ - \sum_{i=1}^{N} \left[\alpha_{i+\frac{1}{2}} (u_{i+1}^n - u_i^n) - \alpha_{i-\frac{1}{2}} (u_i^n - u_{i-1}^n) \right] (u_i^{n+1} - u_i^{n-1}) \\ = 0.$$

Estimation of the first term of (4.51):

$$(4.52) \qquad \sum_{i=1}^{N} h_i \left(\frac{u_i^{n+1} - 2u_i^n + u_i^{n-1}}{\Delta t^2} \right) (u_i^{n+1} - u_i^{n-1}) \\ = \sum_{i=1}^{N} h_i \left[\frac{(u_i^{n+1} - u_i^n) - (u_i^n - u_i^{n-1})}{\Delta t^2} \right] [(u_i^{n+1} - u_i^n) + (u_i^n - u_i^{n-1})] \\ = \sum_{i=1}^{N} h_i \left(\frac{u_i^{n+1} - u_i^n}{\Delta t} \right)^2 - \sum_{i=1}^{N_{max}} h_i \left(\frac{u_i^n - u_i^{n-1}}{\Delta t} \right)^2 \\ = 2(E_k^n - E_k^{n-1}).$$

Estimation of the second term of (4.51):

$$\begin{split} &-\sum_{i=1}^{N} \left[\alpha_{i+\frac{1}{2}}(u_{i+1}^{n}-u_{i}^{n}) - \alpha_{i-\frac{1}{2}}(u_{i}^{n}-u_{i-1}^{n}) \right] (u_{i}^{n+1}-u_{i}^{n-1}) \\ &= -\sum_{i=1}^{N} \alpha_{i+\frac{1}{2}}(u_{i+1}^{n}-u_{i}^{n}) (u_{i}^{n+1}-u_{i}^{n-1}) + \sum_{i=1}^{N} \alpha_{i-\frac{1}{2}}(u_{i}^{n}-u_{i-1}^{n}) (u_{i}^{n+1}-u_{i}^{n-1}). \end{split}$$

By translation of index i of the second term of the right hand side of the above equation, we obtain:

$$\begin{split} &-\sum_{i=1}^{N} \Big[\alpha_{i+\frac{1}{2}}(u_{i+1}^{n}-u_{i}^{n}) - \alpha_{i-\frac{1}{2}}(u_{i}^{n}-u_{i-1}^{n}) \Big] (u_{i}^{n+1}-u_{i}^{n-1}) \\ &= -\sum_{i=1}^{N} \alpha_{i+\frac{1}{2}}(u_{i+1}^{n}-u_{i}^{n}) (u_{i}^{n+1}-u_{i}^{n-1}) + \sum_{i=0}^{N-1} \alpha_{i+\frac{1}{2}}(u_{i+1}^{n}-u_{i}^{n}) (u_{i+1}^{n+1}-u_{i+1}^{n-1}). \end{split}$$

Taking into consideration that $u_0^n = 0$ and $\alpha_{N+\frac{1}{2}} = 0$, we obtain:

$$\begin{split} &-\sum_{i=1}^{N} \left[\alpha_{i+\frac{1}{2}}(u_{i+1}^{n}-u_{i}^{n}) - \alpha_{i-\frac{1}{2}}(u_{i}^{n}-u_{i-1}^{n}) \right] (u_{i}^{n+1}-u_{i}^{n-1}) \\ &= \sum_{i=0}^{N} \alpha_{i+\frac{1}{2}}(u_{i+1}^{n}-u_{i}^{n}) [(u_{i+1}^{n+1}-u_{i}^{n+1}) - (u_{i+1}^{n-1}-u_{i}^{n-1})] \\ &= \sum_{i=0}^{N} \alpha_{i+\frac{1}{2}}(u_{i+1}^{n}-u_{i}^{n}) (u_{i+1}^{n+1}-u_{i}^{n+1}) - \sum_{i=0}^{N} \alpha_{i+\frac{1}{2}}(u_{i+1}^{n}-u_{i}^{n}) (u_{i+1}^{n-1}-u_{i}^{n-1}) \\ &= 2(E_{p}^{n}-E_{p}^{n-1}). \end{split}$$

We finally obtain:

$$\forall n = 1, \dots, K-1, \mathcal{E}^{n+1} = \mathcal{E}^n.$$

As in the two previous cases, in order to obtain a stable numerical scheme, the following Courant-Friedrichs-Lewy, CFL, condition holds:

$$\Delta t \leq \Delta x \; .$$

Remark 4.7 (Implit scheme). We have made the choice to present the three *explicit* numerical schemes for the sake of clarity and conciseness although these schemes generate a CFL condition to ensure the stability.

But let us remark that to avoid the CFL condition, which represents a restriction on the time step, for the three numerical schemes presented above, and to obtain an unconditionally stable numerical scheme, we may construct the equivalent implicit scheme by replacing u_j^n for j = i - 1, i, i + 1 in the approximation of the space derivative by the mean value:

$$\frac{u_j^{n+1} + u_j^{n-1}}{2}$$

The definition of the kinetic energy remains unchanged whereas for the potential energy one has to replace the term:

$$\left(\frac{u_{j+1}^n - u_j^n}{\Delta x}\right) \left(\frac{u_{j+1}^{n+1} - u_j^{n+1}}{\Delta x}\right)$$

by

$$\frac{1}{2} \left(\left(\frac{u_{j+1}^{n+1} - u_j^{n+1}}{\Delta x} \right)^2 + \left(\frac{u_{j+1}^{n-1} - u_j^{n-1}}{\Delta x} \right)^2 \right)$$

for the finite difference approximation and one has to replace the term:

$$\alpha_{i+\frac{1}{2}}(u_{i+1}^{n+1}-u_i^{n+1})(u_{i+1}^{n-1}-u_i^{n-1})$$

by

$$\frac{1}{2} \,\, \alpha_{i+\frac{1}{2}} \Big((u_{i+1}^{n+1} - u_{i}^{n+1})^2 + (u_{i+1}^{n-1} - u_{i}^{n-1})^2 \Big)$$

for the finite volume method. This will guarantee that the total energy remains positive and decreasing in both cases.

The boundedness and the positivity of the discrete energy is used to prove the convergence of the numerical approximation when Δx and Δt tends to 0 towards the strong solution for the finite difference scheme [21] and the convergence towards the weak solution for the finite volume method [17] and [26] for the 2D case.

KAÏS AMMARI AND STÉPHANE GERBI

5. Numerical experiment and validation of the theoretical results in 1D

Without loss of generality (up to a spatial rescaling), for every numerical experiment, we have chosen $\ell = 1$ so that T = 2. We construct these experiments in order to validate the theoretical results.

We have taken N = 100 points and $T_f = 200 \times T = 400$. The *CFL* number is chosen as CFL = 1.

5.1. The boundary case. The initial condition must satisfy Dirichlet boundary condition at the point x = 0 and Neumann boundary condition at the point x = 1. So we have chosen:

$$\forall x \in [0,1], u_0(x) = x^2 - 2x, u_1(x) = -(x^2 - 2x).$$

We present firstly the numerical results for $\mu \in (0, 1)$ for different values of μ on the same graphics to study the influence of this parameter. Figure 2 confirms the decreasing of the energy for any $0 < \mu < 1$ although one cannot conclude on the influence of the damping parameter μ from figures 2A and 2B.

Therefore, we have decide to plot the quantity $-\ln(E(t))$ versus t in figure 3. Figures 3A and 3B show that we obtain almost an increasing straight line whose slope is the exponential decay speed ω that is for large time t, one has $E(t) < Ce^{-\omega t}$. By plotting the quantity $-\frac{\ln(E(t))}{t}$ versus t, in figures 4, we obtain almost an horizontal line so that you may conclude that the quotient $-\frac{\ln(E(t))}{t}$ stays bounded by above and by below by a constant. This constant represents the exponential decay speed. As announced by Ammari, Chentouf and Smaoui, in [3], if we set $\mu_0 = 3 - 2\sqrt{2} \simeq 0.17$, we see in figures 4A and 4B, that this speed is increasing for $\mu \in (0, \mu_0)$ then it decreases for $\mu \in (\mu_0, 0.95)$ but it stays strictly positive. So μ_0 is the optimal parameter to choose to stabilize the system by the boundary delay damping term.

We have then choose $\mu = 1$. This case shows a surprising but predicted behavior, see Theorem 4.1. Indeed figure 5A shows the conservation of the discrete energy for $t \in [0, 20]$. Thus we wanted to know how was the final profile at time T = 20. Figure 5B shows the initial profile and figure 6A shows the profile at time $T_f = 10 \times T = 20$. These two profiles are opposite whereas the final profile at time $T_f = 11 \times T = 22$ are equal as seen in figure 6B. We have then performed several tests for different final time and for different initial condition u_0 , u_1 . The same surprising (but predicted) behavior shows up.

We continue our study by presenting the numerical results for $\mu \in (1,2]$. Figure 7 shows the growth of the energy for any $1 < \mu < 2$. We may conclude that the energy is increasing and the system cannot be stabilized.

We end up this study by presenting the numerical results for $\mu < 0$. Figure 8 shows the growth of the energy for any $\mu < 0$. We may conclude that the energy is increasing and the system cannot be stabilized.

5.2. The internal case. The initial condition must satisfy Dirichlet boundary condition at the point x = 0 and at the point x = 1. So we have chosen:

$$\forall x \in [0,1], u_0(x) = x(x-1), u_1(x) = -x(x-1).$$

The internal acting delay term acts on $[x_{i_0}, x_{i_1}]$ where we have chosen $x_{i_0} = \frac{1}{4}$, $x_{i_1} = \frac{3}{4}$.

We present firstly the numerical results for $\mu \in (0, 2)$ for different values of μ on the same graphics to study the influence of this parameter. Figure 9 shows that there exists $\mu_0 \in (1.7, 1.8)$ such that the energy is decreasing for any $0 < \mu < \mu_0$ while it seems that the energy is increasing for $\mu > \mu_0$. To be convinced by this numerical argument, we plot in figure 10 the quantity $-\ln(E(t))$ versus t. Again for any $0 < \mu < \mu_0$, we obtain almost an increasing straight line whose slope is the exponential decay speed ω that is for large time t, one has $E(t) < Ce^{-\omega t}$, while for any $\mu_0 < \mu$, we obtain almost a decreasing straight line whose slope is the exponential growth

28

speed ω that is for large time t, one has $E(t) > Ce^{\omega t}$. By plotting the quantity $-\frac{\ln(E(t))}{t}$ versus t, in figures 11, we obtain almost an horizontal positive line for $0 < \mu < \mu_0$ so that you may conclude that is for large time t, one has $E(t) < Ce^{-\omega t}$ while we obtain an horizontal negative line for $\mu_0 < \mu$ so that you may conclude that is for large time t, one has $E(t) < Ce^{-\omega t}$ while we obtain an horizontal negative line for $\mu_0 < \mu$ so that you may conclude that is for large time t, one has $E(t) > Ce^{\omega t}$.

We present secondly the numerical results for $\mu < 0$ for different values of μ on the same graphics. Figure 12 shows the growth of the energy for any $\mu < 0$. We may conclude that the energy is increasing and the system cannot be stabilized.

5.3. The pointwise case. The initial condition must satisfy Dirichlet boundary condition at the point x = 0 and Neumann boundary condition at the point x = 1. So we have chosen:

$$\forall x \in [0,1], u_0(x) = x^2 - 2x, u_1(x) = -(x^2 - 2x)$$

We present firstly the numerical results for $\mu \in (0, 2)$ for different values of μ on the same graphics to study the influence of this parameter. Figure 13 confirms the decreasing of the energy for any $0 < \mu < 2$ although one cannot conclude on the influence of the damping parameter μ from figures 13A and 13B.

Therefore, we have decided to plot the quantity $-\ln(E(t))$ versus t in figure 14. Figures 14A and 14B show that we obtain almost an increasing straight line whose slope is the exponential decay speed ω that is for large time t, one has $E(t) < Ce^{-\omega t}$. By plotting the quantity $-\frac{\ln(E(t))}{t}$ versus t, in figures 15, we obtain almost an horizontal line so that you may conclude that the quotient $-\frac{\ln(E(t))}{t}$ stays bounded by above and by below by a constant. This constant represents the exponential decay speed. In figures 15A and 15B, we cannot really conclude about the variations of the exponential decay rate versus the value of the parameter μ .

We have then choose $\mu = 2$. Again this case shows a surprising but predicted behavior, as in Theorem 4.4. Indeed figure 16A shows the conservation of the discrete energy for $t \in [0, 20]$. Thus we wanted to know how was the final profile at time T = 20. Figure 16B shows the initial profile and figure 17A shows the profile at time $T_f = 10 \times T = 20$. These two profiles are equal whereas the final profile at time $T_f = 11 \times T = 22$ are opposite as seen in figure 17B. Again, we have then performed several tests for different final time and for different initial condition u_0 , u_1 . The same surprising (but predicted) behavior shows up.

We continue our study by presenting the numerical results for $\mu > 2$. Figure 18 shows the growth of the energy for any $2 < \mu$. We may conclude that the energy is increasing and the system cannot be stabilized.

We end up this study by presenting the numerical results for $\mu < 0$. Figure 19 shows the growth of the energy for any $\mu < 0$. We may conclude that the energy is increasing and the system cannot be stabilized.

6. Conclusion and perspectives.

Although delay effects arise in many applications and practical problems, we have seen it this work that these effects could be overcame by choosing a control law that uses information from the past (by switching or not).

Moreover by constructing well adapted numerical experiments, one can choose the values of some parameters to optimize the decay rate of the energy.

We think that this type of control laws may also be used for the stabilization of partially damped coupled systems. This will be the future work we plan to investigate.

KAÏS AMMARI AND STÉPHANE GERBI

References

- E. M. AIT BEN HASSI, K. AMMARI, S. BOULITE AND L. MANIAR, Feedback stabilization of a class of evolution equations with delay, J. Evol. Equ., 1 (2009), 103–121.
- W. F. AMES, Numerical methods for partial differential equations. Computer Science and Scientific Computing. Academic Press, Inc., Boston, MA, third edition, 1992.
- [3] K. AMMARI, B. CHENTOUF AND N. SMAOUI, Note on the stabilization of a vibrating string via a switching time-delay boundary control: a theoretical and numerical study, SeMA J., 80 (2023), 647–662.
- [4] K. AMMARI, B. CHENTOUF AND N. SMAOUI, A qualitative and numerical study of the stability of a nonlinear time-delayed dispersive equation, J. Appl. Math. Comput., 66 (2021), 465–491.
- [5] K. AMMARI AND S. GERBI, Interior feedback stabilization of wave equations with dynamic boundary delay, Zeitschrift f
 ür Analysis und Ihre Anwendungen, 36 (2017), 297–327.
- [6] K. AMMARI, A. HENROT AND M. TUCSNAK, Asymptotic behaviour of the solutions and optimal location of the actuator for the pointwise stabilization of a string, Asymptot. Anal., 28 (2001), 215–240.
- [7] K. AMMARI, A. HENROT AND M. TUCSNAK, Optimal location of the actuator for the pointwise stabilization of a string, C. Acad. Sci. Paris, Série I., 330 (2000), 275–280.
- [8] K. AMMARI, S. NICAISE AND C. PIGNOTTI, Feedback boundary stabilization of wave equations with interior delay, Systems Control Lett., 59 (2010), 623–628.
- [9] K. AMMARI AND S. NICAISE, Stabilization of elastic systems by collocated feedback, Lecture Notes in Mathematics, 2124. Springer, Cham, 2015.
- [10] K. AMMARI, S. NICAISE AND C. PIGNOTTI, Stabilization by switching time-delay, Asymptot. Anal., 83 (2013), 263–283.
- [11] K. AMMARI, S. NICAISE AND C. PIGNOTTI, Feedback boundary stabilization of wave equations with interior delay, Systems and Control Letters, 59 (2010), 623–628.
- [12] A. BENSOUSSAN, G. DA PRATO, M. C. DELFOUR AND S. K. MITTER, Representation and control of infinite Dimensional Systems. Vol I, Birkhäuser, 1992.
- [13] H. BREZIS, Analyse Fonctionnelle, Théorie et Applications, Masson, Paris, 1983.
- [14] R. DATKO, Not all feedback stabilized hyperbolic systems are robust with respect to small time delays in their feedbacks, SIAM J. Control Optim., 26 (1988), 697–713.
- [15] R. DATKO, Two examples of ill-posedness with respect to time delays revisited, IEEE Trans. Automatic Control, 42 (1997), 511–515.
- [16] R. DATKO, J. LAGNESE AND P. POLIS, An example on the effect of time delays in boundary feedback stabilization of wave equations, SIAM J. Control Optim., 24 (1985), 152–156.
- [17] R. EYMARD, T. GALLOUËT, AND R. HERBIN, *Finite volume methods*, in Handbook of numerical analysis, Vol. VII, vol. VII of Handb. Numer. Anal., North-Holland, Amsterdam, (2000), 713–1020.
- [18] M. GUGAT, Boundary feedback stabilization by time delay for one-dimensional wave equations, IMA Journal of Mathematical Control and Information, 27 (2010), 189–203.
- [19] M. GUGAT AND M. TUCSNAK, An example for the switching delay feedback stabilization of an infinite dimensional system: The boundary stabilization of a string, System Control Lett., 60 (2011), 226–233.
- [20] B. JACOB AND H. ZWART, Linear Port-Hamiltonian Systems on Infinite-dimensional Spaces, Operator Theory: Advances and Applications, 223, Birkhäuser, 2012.
- [21] P. D. LAX AND R.D. RICHTMYER Survey of the stability of linear finite difference equations, Comm. Pure Appl. Math., 9, (1956), 267–293.
- [22] J. L. LIONS, Contrôlabilité exacte, perturbations et stabilisation de systèmes distribués. Tome 1. Contrôlabilité exacte. With appendices by E. Zuazua, C. Bardos, G. Lebeau and J. Rauch. Recherches en Mathématiques Appliquées, 8. Masson, Paris, 1988.
- [23] J. L. LIONS AND E. MAGENES, Problèmes aux limites non homogénes et applications. Vol 1, Dunod, Paris, 1968.
- [24] S. NICAISE AND C. PIGNOTTI, Stability and instability results of the wave equation with a delay term in the boundary or internal feedbacks, SIAM J. Control Optim., 45 (2006), 1561–1585.
- [25] S. NICAISE AND J. VALEIN, Stabilization of second order evolution equations with unbounded feedback with delay, ESAIM Control Optim. Calc. Var., 16 (2010), 420–456.
- [26] I. RIEČANOVÁ AND A. HANDLOVIČOVÁ, Study of the numerical solution to the wave equation, Acta Math. Univ. Comenian. (N.S.), 87, 2, (2018), 317–332.
- [27] M. TUCSNAK AND G. WEISS, Observation and control for operator semigroups. Birkhäuser Advanced Texts, Birkhäuser Verlag, Basel, 2009.
- [28] J. M. WANG, B. Z. GUO AND M. KRSTIC, Wave equation stabilization by delays equal to even multiplies of the wave propagation time, SIAM J. Control Optim., 49 (2011), 517–554.
- [29] E. ZUAZUA, Exponential decay for the semilinear wave equation with locally distributed damping, Comm. Partial Differential Equations, 15 (1990), 205–235.
- [30] E. ZUAZUA, Switching control, J. Eur. Math. Soc., 13 (2011), 85–117.



(A) Evolution of the discrete energy for $0 < \mu \leq 0.5\,,\,t \in [0,20].$



(B) Evolution of the discrete energy for $0.5<\mu<1$, $t\in[0,20].$ FIGURE 2. Boundary delayed control. Energy when $0<\mu<1$



(B) Evolution of $-\ln(E(t))$ for $0.5 < \mu < 1$.

FIGURE 3. Boundary delayed control. Exponential decay $0 < \mu < 1$



FIGURE 4. Boundary delayed control. Exponential decay rate $0 < \mu < 1$



(B) Initial profile.

FIGURE 5. Boundary delayed control. The surprising case $\mu=1$



(B) Final profile for $T_f = 11 \times T = 22$.

FIGURE 6. Boundary delayed control. Final profiles for $\mu=1$



(A) Evolution of the discrete energy for $1<\mu\leq 1.5\,,\,t\in[0,20].$



(B) Evolution of the discrete energy for $1.5 < \mu \le 2$, $t \in [0, 20]$. FIGURE 7. Boundary delayed control. Energy when $1 < \mu \le 2$



(B) Evolution of the discrete energy for $-1 \le \mu < -0.5$, $t \in [0, 20]$. FIGURE 8. Boundary delayed control. Energy when $-1 \le \mu < 0$



(A) Evolution of the discrete energy for $0<\mu\leq 1\,,\,t\in[0,20].$



(B) Evolution of the discrete energy for $1<\mu<2\,,\,t\in[0,20].$ FIGURE 9. Internal delayed control. Energy when $0<\mu<2$



(B) Evolution of $-\ln(E(t))$ for $1 < \mu < 2$.

FIGURE 10. Internal delayed control. Exponential decay $0 < \mu < \mu_0$ and exponential growth $\mu_0 < \mu$



FIGURE 11. Internal delayed control. Exponential decay rate $0 < \mu < \mu_0$ and exponential growth rate for $\mu_0 < \mu$



(B) Evolution of the discrete energy for $-2 \le \mu < -1$, $t \in [0, 20]$. FIGURE 12. Internal delayed control. Energy when $-2 \le \mu < 0$



(A) Evolution of the discrete energy for $0 < \mu \leq 1, t \in [0, 20]$.



(B) Evolution of the discrete energy for $1 < \mu \le 2$, $t \in [0, 20]$. FIGURE 13. Pointwise delayed control. Energy when $0 < \mu \le 2$



(B) Evolution of $-\ln(E(t))$ for $1 < \mu \leq 2$.

FIGURE 14. Pointwise delayed control. Exponential decay $0 < \mu \leq 2$



FIGURE 15. Pointwise delayed control. Exponential decay rate $0 < \mu \leq 2$



(B) Initial profile.

FIGURE 16. Pointwise delayed control. The surprising case $\mu=2$



(B) Final profile for $T_f = 11 \times T = 22$.

FIGURE 17. Pointwise delayed control. Final profiles for $\mu=2$



(A) Evolution of the discrete energy for $0 < \mu \leq 1, t \in [0, 20]$.



(B) Evolution of the discrete energy for $1 < \mu \le 2$, $t \in [0, 20]$. FIGURE 18. Pointwise delayed control. Energy when $2 < \mu$



(B) Evolution of the discrete energy for $-2 \le \mu < -1$, $t \in [0, 20]$. FIGURE 19. Pointwise delayed control. Energy when $-2 \le \mu < 0$

LR ANALYSIS AND CONTROL OF PDES, LR 22ES03, DEPARTMENT OF MATHEMATICS, FACULTY OF SCIENCES OF MONASTIR, UNIVERSITY OF MONASTIR, 5019 MONASTIR, TUNISIA

Email address: kais.ammari@fsm.rnu.tn

Laboratoire de Mathématiques UMR 5127 CNRS & Université Savoie Mont Blanc, Campus scientifique, 73376 Le Bourget du Lac Cedex, France

 $Email \ address: \verb| stephane.gerbi@univ-smb.fr||$