Faster Machine Unlearning via Natural Gradient Descent

Omri Lev and Ashia Wilson Massachusetts Institute of Technology {omrilev, ashia07}@mit.edu

Abstract

We address the challenge of efficiently and reliably deleting data from machine learning models trained using Empirical Risk Minimization (ERM), a process known as machine unlearning. To avoid retraining models from scratch, we propose a novel algorithm leveraging Natural Gradient Descent (NGD). Our theoretical framework ensures strong privacy guarantees for convex models, while a practical Min/Max optimization algorithm is developed for non-convex models. Comprehensive evaluations show significant improvements in privacy, computational efficiency, and generalization compared to state-of-the-art methods, advancing both the theoretical and practical aspects of machine unlearning. ¹

1 Introduction

The exponential growth in data collection and machine learning applications has intensified concerns about user privacy and data security. Legislative frameworks such as the European Union's General Data Protection Regulation (GDPR), California's Consumer Privacy Act (CCPA), and Canada's proposed Consumer Privacy Protection Act (CPPA) emphasize the right of individuals to have their data deleted upon request. These new requirements have catalyzed the development of "machine unlearning" — the process of modifying a trained model to eliminate the influence of specific data inputs, effectively making the model "forget" this data. The main challenge is making this process efficient without resorting to retraining models from scratch, which is computationally expensive and unsustainable as the scale of models and data grows.

Historically, theoretical approaches to machine unlearning have predominantly focused on convex models, where the problem space allows for the development of algorithms with provable guarantees of privacy and correctness [1, 2]. These methods often rely on operations like the Newton step, which, while effective, are computationally demanding for large-scale applications. In contrast, practical approaches typically address more complex, non-convex models using heuristic methods that lack formal privacy guarantees [3]. These methods often re-optimize the model on a pruned dataset, which is believed not to contain the information intended for unlearning—a computationally expensive process that can inadvertently retain data influence and thus compromise privacy.

This paper proposes a novel algorithm based on Natural Gradient Descent (NGD)—a gradient algorithm that preconditions a gradient descent update with the inverse of the Fisher information matrix of the underlying statistical model. By treating the ERM problem through the lens of maximum-likelihood estimation, we first develop an algorithm for convex models, proving it maintains strong unlearning guarantees and is more computationally efficient than existing methods, which are based on the Newton step. Leveraging NGD's adaptability to large models, we design a practical unlearning algorithm based on a Min/Max optimization procedure for realistic settings. Our new algorithm outperforms state-of-the-art unlearning algorithms in multiple aspects.

¹Code will be available upon publication.

Contributions We make the following key contributions:

- We formalize the unlearning problem from a probabilistic perspective, offering a computationally efficient algorithm for data deletion that scales to large models (c.f. Alg. 1).
- We introduce a theoretical framework that supports our algorithm, ensuring it guarantees privacy for convex models according to unlearning privacy measures (c.f. Lem. 1, Th. 1).
- Next, we extend the theoretical algorithm to real non-convex models, offering a novel unlearning algorithm based on Min/Max training using NGD (c.f. Alg. 2).
- We validate our algorithm's practical advantages through comprehensive simulations, showing significant improvements in privacy and generalization across various non-convex settings (c.f. Sec. 5.1).

2 Related Work

The goal of *exact unlearning*, first proposed by Cao and Yang [4], is to find a model whose predictions match those of a retrained model. This can be achieved through retraining or using other techniques that tend to be computationally or memory-intensive [5, 6, 7]. In contrast, *approximate unlearning* is a less stringent requirement that allows the unlearned model to deviate from the retrained model by a bounded amount. Several works have introduced more efficient methods that satisfy these inexact criteria [1, 2, 8, 9, 10, 11].

We develop a computationally efficient algorithm that satisfies the (ϵ, δ) -approximate unlearning definition from Sekhari et al. [1]. Sekhari et al. [1] also prove that approximate unlearning can be achieved using a Newton step towards the gradient of the points we aim to unlearn in the convex case. This algorithm was later generalized to efficiently remove points online and to delete points in scenarios involving non-differentiable regularizers [2].

In contrast to previous work that utilizes Newton-style updates and requires a full Hessian inversion, we aim to reduce this computational burden by leveraging the NGD [12]. NGD offers a low-cost second-order update by replacing the Hessian with the Fisher Information Matrix (FIM). As we will show, the NGD update is closely related to the Fisher-unlearning methods studied by Golatkar et al. [11, 13] and Wang et al. [14]. Our contributions improve upon these previous algorithms in two key ways. First, we are the first to prove that FIM-based methods satisfy the (ϵ , δ)-unlearning definition, establishing the correctness of our algorithm in the convex case. Second, we demonstrate that FIM-based methods are specific cases of second-order unlearning methods that replace the Hessian with its Positive Semi-Definite (PSD) approximation, given by the Gauss-Newton Matrix [12]. This exploration introduces a more general framework that paves the way for developing advanced unlearning methods.

We end by turning our sights to unlearning in the non-convex regime. While recent works have also introduced unlearning algorithms based on the Min/Max training procedure [9], we extend this theory and show how these methods can be enhanced by incorporating Min/Max training based on NGD.

3 Background

We now discuss the problem of learning and unlearning and review NGD algorithm.

3.1 Machine Learning

In our learning setting, we aim to minimize an objective function comprised of a loss function ℓ , a regularizer π , and a regularization parameter $\lambda \in [0, \infty)$. The goal of learning is to find a parameter $\theta^*(\lambda) \in \Theta$ that minimizes the population risk

$$\theta^*(\lambda) \triangleq \underset{\theta \in \Theta}{\operatorname{argmin}} L(P_{\mathsf{z}}, \theta, \lambda), \quad L(P_{\mathsf{z}}, \theta, \lambda) \triangleq \mathbb{E}_{\mathsf{z} \sim P_{\mathsf{z}}} \left[\ell(\mathsf{z}, \theta) + \lambda \pi(\theta) \right]$$
(1)

where usually z = (x, y) comprised of a covariate x and a label y that distributed according to $P_x(x)P_{y|x}(y|x)$. Our analysis assumes a one-dimensional label, as is common in many typical machine-learning problems (regression, classification, etc). The distribution P_z is often inaccessible,

so given a dataset $\mathcal{S} = (z_1, z_2, \dots z_n)$ with $z_i \stackrel{\text{iid}}{\sim} P_z$ we instead find a model $\hat{\theta}_{\mathcal{S}}(\lambda)$ that minimizes the empirical risk

$$\hat{\theta}_{\mathcal{S}}(\lambda) \triangleq \operatorname*{argmin}_{\theta \in \Theta} L(\mathcal{S}, \theta, \lambda), \quad L(\mathcal{S}, \theta, \lambda) \triangleq \frac{1}{|\mathcal{S}|} \sum_{z \in \mathcal{S}} \ell(z, \theta) + \lambda \pi(\theta).$$
(2)

As we discuss in Sec. 3.3, in many scenarios, $\ell(z, \theta) = -\log (P(y|f(x;\theta)))$; that is, the loss can be interpreted as a likelihood under a probabilistic model induced by a parameterized function $f(x;\theta)$, often taken to be a neural network. Moreover, we study the case where $P(y|f(x;\theta))$ belongs to an *exponential-family* [15] whose natural parameters are the features $f(x;\theta)$. This is satisfied by many common loss functions in machine learning (see App. C). Our formulation assumes that the regularization is convex but not necessarily differentiable, allowing many common convex non-differentiable regularizers (L_1 , elastic-net, etc).

3.2 Machine Unlearning

After using a dataset \mathscr{S} to train and publish a model $\hat{\theta}_{\mathscr{S}}(\lambda)$, a set of m users in the training set $\mathscr{U} \subset \mathscr{S}$ might request that their data points be deleted and that any models produced using their data to be removed. An organization might initially consider re-optimizing the leave- \mathscr{U} -out objective $L(\mathscr{S} \setminus \mathscr{U}, \theta, \lambda)$ to produce $\hat{\theta}_{\mathscr{S} \setminus \mathscr{U}}(\lambda)$ to comply with this request. While re-optimizing from scratch constitutes a baseline for unlearning, the computational cost makes complying with every data deletion request undesirable. Thus, our goal is to derive an efficient method to approximate $\hat{\theta}_{\mathscr{S} \setminus \mathscr{U}}(\lambda)$ without retraining over the entire dataset $\mathscr{S} \setminus \mathscr{U}$ from scratch. Ultimately, our method will only require access to the samples to be deleted \mathscr{U} and possibly additional statistics about the original dataset \mathscr{S} , $B(\mathscr{S})$, obtained during the training process. Moreover, we aim to prevent an external observer from distinguishing between the approximated solution (denoted by $\tilde{\theta}_{\mathscr{S} \setminus \mathscr{U}})$ and the ERM-minimizer $\hat{\theta}_{\mathscr{S} \setminus \mathscr{U}}$. This goal can be defined similarly to the classical definition of Differential Privacy (DP) [1, 2], which can be informally explained as the requirement that, with high-probability, an observer cannot differentiate between the two cases:

- 1. The model is trained on the set S and then a set \mathcal{U} is deleted by the unlearning algorithm.
- 2. The model is trained on the set $S \setminus \mathcal{U}$, and no points are deleted thereafter.

Mathematically, this notion is captured by the next definition by Sekhari et al. [1], which generalizes the privacy notions from the DP literature [16, 17]

Definition 1 ((ϵ, δ)-unlearning). For all \mathscr{S} of size n, delete requests $\mathscr{U} \subset \mathscr{S}$ such that $|\mathscr{U}| \leq m$, and learning algorithm $A : \mathscr{S} \to \theta \in \Theta$, an unlearning algorithm \overline{A} is (ϵ, δ) -unlearning if $\forall \Upsilon \subseteq \Theta$

$$\begin{split} P\left(\bar{A}\left(\mathscr{U}, A(\mathscr{S}), B(\mathscr{S})\right) \in \Upsilon\right) &\leq e^{\epsilon} \cdot P\left(\bar{A}\left(\emptyset, A(\mathscr{S} \backslash \mathscr{U}), B(\mathscr{S} \backslash \mathscr{U})\right) \in \Upsilon\right) + \delta, \\ P\left(\bar{A}\left(\emptyset, A(\mathscr{S} \backslash \mathscr{U}), B(\mathscr{S} \backslash \mathscr{U})\right) \in \Upsilon\right) &\leq e^{\epsilon} \cdot P\left(\bar{A}\left(\mathscr{U}, A(\mathscr{S}), B(\mathscr{S})\right) \in \Upsilon\right) + \delta \end{split}$$

where \emptyset is the empty set, ϵ and δ are some positive constants, and $B(\mathcal{S})$ are some statistics.

Intuitively, this definition asserts that an external observer cannot distinguish between a model trained on $\mathcal{S} \setminus \mathcal{U}$ and a model trained on \mathcal{S} and then unlearning \mathcal{U} .

3.3 Natural Gradient Descent

Natural Gradient Descent (NGD) is considered an efficient method to optimize the sum of likelihood functions from a parametric family [18, 19, 20]. In supervised learning, given a training set S and a loss $\ell(\cdot)$, we aim to minimize the population risk (1) by minimizing the empirical risk (2). This problem is equivalent to the following maximum-likelihood estimation over the model parameters

$$\hat{\theta}_{\mathscr{S}} = \operatorname*{argmax}_{\theta} \sum_{(x,y) \in \mathscr{S}} \log \left(P_{\mathsf{y}|\mathsf{x}}\left(y|x;\theta\right) \right) \triangleq \operatorname*{argmin}_{\theta} L(\mathscr{S},\theta,\lambda=0),$$

given our assumption that the data is distributed according to $P_{y|x}(y|x;\theta)P_x(x)$ and where $\ell(z,\theta) \triangleq -\log(P(y|x;\theta))$. This interpretation comes up naturally in many machine learning problems when

the network predicts a probabilistic distribution over the target alphabet (see [21, Ch. 3.1, Ch. 4.2]). Following this interpretation, the maximization is over probabilistic models $P_{y|x}(y|x;\theta)$, which lies on the probability simplex of the output alphabet \mathcal{Y} and are controlled by the parameters θ . Unlike classical gradient algorithms, which take steps in the steepest direction over the parameter space θ , NGD follows the steepest direction over the probability simplex, where distances are measured via the Kullback Leibler (KL) divergence [20]. The iterative process that defines the NGD algorithm is given by [12, 22]

$$\theta^{(t+1)} = \theta^{(t)} - \alpha \cdot \left(\mathbf{F} \left(\theta^{(t)} \right) \right)^{-1} \nabla_{\theta} L \left(\mathcal{S}, \theta^{(t)} \right),$$

where $\alpha > 0$ is the learning rate and where the matrix $\mathbf{F}(\theta^{(t)})$ is the *Fisher Information Matrix* (FIM), which is given by

$$\mathbf{F}\left(\theta^{(t)}\right) \triangleq \mathbb{E}_{(\mathsf{x},\mathsf{y})\sim P_{\mathsf{x},\mathsf{y};\theta}}\left[\nabla_{\theta}\log\left(P_{\mathsf{y}|\mathsf{x};\theta}\left(\mathsf{y}|\mathsf{x};\theta^{(t)}\right)\right)\nabla_{\theta}^{T}\log\left(P_{\mathsf{y}|\mathsf{x};\theta}\left(\mathsf{y}|\mathsf{x};\theta^{(t)}\right)\right)\right].$$

The FIM represents the local curvature of the KL-divergence, i.e. $D\left(P_{y|x;(\theta+d)} \| P_{y|x;\theta}\right) \cong \frac{1}{2}d^T \mathbf{F} d.^2$ The gradient is typically evaluated over a batch of samples from \mathscr{S} . Since the distribution of the covariates P_x is not accessible, the FIM is approximated using empirical estimates involving averaging over the covariate samples and leveraging the underlying network structure to evaluate the expectation over $P_{y|x;\theta}$ [12, 24]. The approximated matrix is called the *approximated FIM* and is defined as

$$\mathbf{F}\left(\mathcal{S},\theta^{(t)}\right) \triangleq \frac{1}{|\mathcal{S}|} \sum_{x \in \mathcal{S}} \mathbb{E}_{\mathbf{y} \sim P_{\mathbf{y}|\mathbf{x}=x;\theta}} \left[\nabla_{\theta} \log \left(P_{\mathbf{y}|\mathbf{x};\theta}\left(\mathbf{y}|x;\theta^{(t)}\right) \right) \nabla_{\theta}^{T} \log \left(P_{\mathbf{y}|\mathbf{x};\theta}\left(\mathbf{y}|x;\theta^{(t)}\right) \right) \right].$$
(3)

Notably, the approximated FIM averages over the observations of the covariates x while taking the *exact* expectation with respect to $P_{y|x}$. For many common network architectures, (3) is usually simplified by utilizing information about the network architecture. Accordingly, many computationally efficient algorithms are developed in practice to calculate the NGD step [12, 25, 26].

Finally, following classical developments (see, for example, [27] and [12, Sec. 9.2]) whenever the loss function is given by $\ell(z, \theta) = -\log (P(y|f(x; \theta)))$ and the distribution of P(y|f) is out of an exponential family, the approximated FIM can be considered a PSD approximation to the Hessian. Specifically, the Hessian can be written as $\mathbf{H} = \mathbf{F}(\mathcal{S}, \theta) + \mathbf{R}$ where $\mathbf{F}(\mathcal{S}, \theta)$ is guaranteed to be PSD and, in many popular scenarios, \mathbf{R} shrinks to zero (in L_2 sense) as the model's training accuracy improves (see [12, 24]). Thus, the approximated FIM is interpreted as the PSD part of the Hessian.

4 Computationally Efficient Unlearning for Convex Models

Our goal is to develop a *computationally efficient* second-order algorithm for machine unlearning that provably satisfies the (ϵ, δ) -unlearning of Def. 1. To that end, we use the NGD to develop such an algorithm. We start by proposing an algorithm for the convex case, for which we formally prove the unlearning requirement. In Sec. 5, we will extend our algorithm for non-convex cases. Our notations correspond to the ERM framework presented in Sec. 3.1. Our development targets regression and classification tasks.

4.1 Method: Unlearning via the NGD

The aim of our first algorithm is to guarantee fast unlearning in convex models. Building on the existing unlearning techniques, which are based on the Newton step [1, 2], our method shows that the Newton step can be replaced by an NGD step while still maintaining the same unlearning guarantees. However, since the NGD step is computationally cheaper than the Newton step in many models, this algorithm leads to significant savings in terms of computational time. Throughout the analysis, we will make use of the *proximal operator*, defined via

$$\operatorname{prox}_{\lambda\pi}^{\mathbf{H}}(v) = \operatorname{argmin}_{\theta \in \Theta} \left\{ \left(v - \theta \right)^{T} \mathbf{H} \left(v - \theta \right) + 2\lambda \pi(\theta) \right\}$$

for a PSD **H**. Beyond the computational efficiency of the NGD step, the FIM is guaranteed to be PSD, further improving computational stability [10, 26, 27, 28]. The FIM structure also supports many practical approximation algorithms useful in neural network optimization and training [25, 26, 29]. Our NGD-based unlearning algorithm is presented in Alg. 1.

²The KL-divergence between two distributions Q(x) and P(x) defined over alphabet \mathcal{X} is defined by $D(P||Q) = \sum_{x \in \mathcal{X}} P(x) \log\left(\frac{P(x)}{Q(x)}\right)$. The second-order approximation can be derived as in [23, Ch. 2].

Algorithm 1 Unlearning using the NGD

Input: Delete request: $\mathcal{U} = \{z_{i_k}\}_{k=1}^m$, Cost minimizer: $\hat{\theta}_{\mathcal{S}}(\lambda) \triangleq \hat{\theta}_{\mathcal{S}}$, Loss gradient: $\nabla L\left(\mathcal{U}, \hat{\theta}_{\mathcal{S}}, \lambda = 0\right)$, FIM: $\mathbf{F}\left(\mathcal{S}, \hat{\theta}_{\mathcal{S}}\right)$, Cardinality: $|\mathcal{S}| \triangleq n$, either $\lambda \nabla^2 \pi\left(\hat{\theta}_{\mathcal{S}}\right)$ or $\lambda \pi$.

- 1: if $\pi(\cdot)$ is twice differentiable then
- 2: Update parameter estimates

$$\tilde{\theta}_{\mathcal{S}\backslash\mathcal{U}} = \hat{\theta}_{\mathcal{S}} + \left(\mathbf{F} \left(\mathcal{S}, \hat{\theta}_{\mathcal{S}} \right) + \lambda \nabla^2 \pi \left(\hat{\theta}_{\mathcal{S}} \right) \right)^{-1} \nabla \tilde{L} \left(\mathcal{U}, \hat{\theta}_{\mathcal{S}}, \lambda = 0 \right)$$

where $\nabla \tilde{L}\left(\mathcal{U}, \hat{\theta}_{\mathcal{S}}, \lambda\right) \triangleq \frac{n}{n-m} \nabla L\left(\mathcal{U}, \hat{\theta}_{\mathcal{S}}, \lambda\right), m \triangleq |\mathcal{U}|.$

3: **else**

4: Update parameter estimates

$$\tilde{\theta}_{\mathcal{S}\backslash\mathcal{U}} = \operatorname{prox}_{\lambda\pi}^{\mathbf{F}\left(\mathcal{S},\hat{\theta}_{\mathcal{S}}\right)} \left(\hat{\theta}_{\mathcal{S}} + \left(\mathbf{F}\left(\mathcal{S},\hat{\theta}_{\mathcal{S}}\right)\right)^{-1} \nabla \tilde{L}\left(\mathcal{U},\hat{\theta}_{\mathcal{S}},\lambda=0\right)\right)$$
(4)

where $\nabla \tilde{L}\left(\mathcal{U}, \hat{\theta}_{\mathcal{S}}, \lambda\right) \triangleq \frac{n}{n-m} \nabla L\left(\mathcal{U}, \hat{\theta}_{\mathcal{S}}, \lambda\right).$ 5: end if

6: Set $\gamma = \frac{Mm^2C^2}{\mu^3n^2} + \frac{2m^2CQK}{\mu^2n^2} \triangleq \frac{\tilde{\gamma}}{n^2}$ and sample $\nu \sim \mathcal{N}\left(0, \left(\frac{\gamma}{\epsilon}\sqrt{2\log\left(\frac{1.25}{\delta}\right)}\right)^2 \mathbf{I}_d\right)$ 7: Publish $\bar{\theta}_{\delta\backslash\mathcal{U}} = \tilde{\theta}_{\delta\backslash\mathcal{U}} + \nu$

We now prove that Alg. 1 satisfies the (ϵ, δ) -unlearning requirement of Def. 1. To that end, we make the following assumptions:

Assumption 1.a. The loss functions are of the form $\ell(z,\theta) = -\log(P(y|f(x;\theta)))$ where P(y|f) belongs to an exponential family whose natural parameters are $f(x;\theta)$. We further assume that $-\nabla_f^2 \log(P(y|f(x;\theta))) \leq Q \cdot \mathbf{I}_d$ for some Q > 0.

Assumption 1.b. The functions $\ell(z, \theta) + \lambda \pi(\theta)$ are μ -strongly convex and C-Lipschitz. For twicedifferentiable regularizers, we assume that $\ell(z, \theta) + \lambda \pi(\theta)$ is twice differentiable with M-Lipschitz Hessian. Otherwise, we assume these properties only for $\ell(z, \theta)$ and assume that $\pi(\theta)$ is convex. The gradient of the features $f(x; \theta)$ is assumed to be bounded, i.e. $\|\nabla_{\theta} f(x; \theta)\|^2 \leq K$.

In particular, we focus on the case where our loss function is either a cross-entropy loss or a meansquared error loss, which meets our assumptions (see App. C and App. E).

Lemma 1. Suppose our training algorithm returns $\hat{\theta}_{\mathscr{S}}(\lambda)$ that minimizes the training loss exactly: $\ell\left(z, \hat{\theta}_{\mathscr{S}}(\lambda)\right) = 0, \forall z \in \mathscr{S}$. Under Assumptions 1.a and 1.b, Alg. 1 satisfies the (ϵ, δ) -unlearning criterion given in Def. 1.

Lem. 1, whose proof can be found in App. E, follows a similar approach to the proofs of unlearning algorithms based on the Newton step [1, 2]. Specifically, it follows by showing that our algorithm produces an approximate solution with a distance to the ERM-minimizer that scales as $O((m/n)^2)$. Consequently, (ϵ, δ) -unlearning is ensured by employing the Gaussian mechanism for differential privacy [16, App. A]. We now provide guarantees on the population risk.

Theorem 1. Under the same assumptions as Lem. 1 and by using Alg. 1, the population risk satisfies

$$L\left(P_{\mathsf{z}}, \bar{\theta}_{\mathcal{S}\backslash\mathcal{U}}, \lambda\right) - L\left(P_{\mathsf{z}}, \theta^{*}(\lambda), \lambda\right) = O\left(\frac{\sqrt{d\tilde{\gamma}C}}{n^{2}\epsilon}\sqrt{\log\left(\frac{1}{\delta}\right)} + \frac{mC^{2}}{\mu n}\right)$$
(5)

The proof of this theorem is in App. G and broadly follows by a technique similar to that employed in existing unlearning methods [1, 2], by replacing the Hessian with its PSD approximation. Furthermore, (5) ensures that whenever m = o(n), the generalization capabilities of the approximated solution are close to those of the ERM-minimizer.

Finally, We note that the approximation of the Hessian using its PSD part exists beyond our assumed exponential family loss model. Specifically, Schraudolph [27] proved a similar decomposition for

loss functions of the form $a(b(\theta))$ with a convex $a(\cdot)$, where the Gauss-Newton Matrix now provides the PSD part, depending again only on first order gradients of the model (see also [24]). With a proper choice of a function $b(\theta)$, the additional term can be shown to disappear with the training error, allowing the same proof from App. E and App. F. Thus, our technique can be applied to more general loss functions.

4.2 Experiments

We demonstrate the computational efficiency of our method compared to the Newton step through numerical simulations. We applied Alg. 1 to various architectures, measuring the total execution time of the unlearning step. To approximate the Newton and NGD steps, we used the LiSSA algorithm [30] (see also App. I) with T = 1000, $\sigma = 5000$, R = 5 and batches of size 32. Simulations included four architectures: one-layer perceptron (OLP), multi-layer perceptron (MLP), convolutional neural network (CNN), and ResNet18 [31] (A detailed description of the architectures is in App. H.2). Since λ affects the convergence of the LiSSA algorithm, we simulate the performance for two different values of λ . In all experiments, we first train the base network with the entire dataset to obtain the parameters $\theta_{\mathcal{S}}$. All models have been trained until they achieve perfect training accuracy and close to zero training loss. For unlearning, we randomly selected a subset of 1000 examples as the forget set \mathcal{U} . We then applied our algorithm to obtain the modified parameters $\hat{\theta}_{S \setminus \mathcal{U}}$ and recorded the execution time. The graphs report averages over ten runs, with error bars showing standard deviations. We note that when the OLP is trained with L_2 regularization, it is a strongly convex model, which is further Lipschitz and twice differentiable almost everywhere (beyond the single non-linearity point induced by the ReLU) and whose gradient norm is bounded almost everywhere and further is guaranteed to achieve zero training loss whenever it over-parametrized relative to the data dimension [32]. Thus, OLP satisfies the assumptions of Alg. 1 and approximate unlearning is guaranteed. Our experiments suggest that NGD confers significant computational advantage over the Newton step for not only OLP, but all other objectives tried.



Figure 1: Computational time for an NGD and Newton steps, applied to multiple models. Across all unlearning tolerances, the calculation time of the NGD is much lower than that of the Newton step. This trend holds for two different values of the regularization parameter λ .

4.3 Comparison to Previous Results

We compare Alg. 1 to other unlearning algorithms in terms of computational complexity, assumption requirements, theoretical guarantees, and other algorithmic components.

1. Comparison of Assumptions: Our analysis assumes a μ -strongly convex, C-Lipschitz, and M-Hessian Lipschitz loss function, similar to the assumptions in [1, 2]. We further assume that the gradient of the features is bounded and an exponential family loss model, which most common settings satisfy. Our proof assumes zero training loss, which is crucial for good generalization [33]. Since modern machine learning models—both convex [34]

and non-convex [32, 35, 36]—are generally trained to zero training loss, this assumption is practical and generally satisfied.

- 2. Comparison of Computational Complexity: Our algorithm involves inverting the FIM and multiplying the inverse with a gradient vector, whereas the algorithms of Sekhari et al. [1] and Suriyakumar and Wilson [2] require the same operation but with the Hessian. These operations can be efficiently approximated using techniques calculating inverse-Jacobian Vector Products (iJVP) and inverse-Hessian Vector Products (iHVP) [27, 30], respectively. Since JVP computations are less costly than HVP ones [27], our algorithm is more efficient. Our experiments confirm that batch removal using the FIM is faster than using the Hessian.
- 3. Comparison of Unlearning and Generalization Guarantees: The guarantees provided in Lem. 1 and Th. 1 are essentially the same as those of [1] and [2] (up to different constants).
- 4. Algorithmic Comparison: Golatkar et al. [10] suggested using the FIM for unlearning by adding noise whose covariance is the inverse of the FIM, but it relies on approximations and lacks formal unlearning guarantees. Our approach uses NGD, which can be calculated directly without needing direct access to the FIM. Similarly, Golatkar et al. [11] proposed adding a gradient preconditioned with the inverse of the FIM, akin to the NGD step, but it also lacks formal privacy guarantees so we omit this preconditioner.

5 Unlearning Non-Convex Models via NGD-Based Min/Max Training

Using classical theoretical developments established for NGD, we now apply Alg. 1 to real-world models, which usually violate assumptions 1.a and 1.b. Alg. 1 employs a natural gradient *ascent* step towards the data in \mathcal{U} , which amounts to natural gradient *descent* step over the data in $\mathcal{S} \setminus \mathcal{U}$, assuming that $\nabla_{\theta} L(\mathcal{S}, \hat{\theta}_{\mathcal{S}}(\lambda), \lambda) = 0$. Therefore, we propose using a Min/Max optimization algorithm that entails executing both steps iteratively. This formulation amounts to first maximizing the loss on \mathcal{U} and then minimizing it on $\mathcal{S} \setminus \mathcal{U}$ and can be mathematically captured by employing a Min/Max training [37, 38] over the combined loss

$$L^{\operatorname{Min}/\operatorname{Max}} = L(\mathcal{S} \setminus \mathcal{U}, \theta, \lambda) - L(\mathcal{U}, \theta, \lambda) = \frac{1}{|\mathcal{S} \setminus \mathcal{U}|} \sum_{z \in \mathcal{S} \setminus \mathcal{U}} \ell(z, \theta) - \frac{1}{|\mathcal{U}|} \sum_{z \in \mathcal{U}} \ell(z, \theta).$$

As is usually done in Min/Max training, we minimize $L^{Min/Max}$ with an additional smoothing term [38]. Our algorithm is presented in Alg. 2 where we calculate the NGD steps of Alg. 2 using one of the K-FAC schemes proposed for scaling NGD to large models [25, 26].

Comparison of our Alg. 2 to Scrub. Alg. 2 resembles the state-of-the-art Scrub algorithm [9], which has been proposed for unlearning data. While our algorithm directly minimizes a linear combination of loss functions, Scrub optimizes a more complicated linear combination of the loss function and KL-divergences. The combination of losses and KL terms used by Scrub requires careful tuning of the weighting of both factors and scheduling of learning-rate decay. Our algorithm, on the other hand, does not require this weighting and thus requires fewer hyperparameters, making its training process more stable. As demonstrated in Sec. 5.1, our algorithm outperforms Scrub in multiple settings.

5.1 Experiments

We compare our Min/Max NGD algorithm to other unlerning algorithms such as Scrub by examining (1) the amount of information that is left about the removed examples in the new model and (2) test accuracy. The experimental setting is similar to that described in Sec. 4.2. To measure the amount of information that is left about the removed examples, we use a *Membership Inference Attack* (MIA) that assesses if a sample was part of the training set [9, 39, 40]. In particular, we have implemented the MIA that uses logistic regression to classify losses that correspond to both examples from the forget set and from the test set [9]. The success rate of this attack (i.e., the number of correct guesses between the test set and the forget set) is measured on ResNet18 and CNN models trained to classify the CIFAR-10 dataset [41] (a precise description of the models is given in App. H). Baseline unlearning algorithms include a fine-tuning algorithm on the retain set and the *Scrub* algorithm from [9]. Each algorithm ran for six epochs. We measured the test accuracy and the *MIA score* of the

Algorithm 2 Min/Max NGD

Input: Delete request: $\mathscr{U} = \{z_{i_k}\}_{k=1}^m$, Cost minimizer: $\hat{\theta}_{\mathscr{S}}(\lambda) \triangleq \hat{\theta}_{\mathscr{S}}(\lambda)$

- 1: Initialize: $\hat{\theta} \leftarrow \hat{\theta}_{\mathcal{S}}, \ \theta_{\text{smooth}} \leftarrow \hat{\theta}_{\mathcal{S}}$
- 2: for epoch = $1, \ldots, max$ -epochs do
- 3: **for** k_1 -steps **do**
- 4: Sample batch $\mathscr{B}_{\mathscr{U}}$ of size $B_{\mathscr{U}}$ from \mathscr{U} and update $\hat{\theta}$ using natural gradient ascent

$$\hat{\theta} \leftarrow \hat{\theta} + \alpha \left(\mathbf{F} \left(\hat{\theta} \right) \right)^{-1} \left(\sum_{z \in \mathscr{B}_{\mathscr{U}}} \nabla_{\theta} \left(\ell \left(z, \theta \right) + \gamma \left\| \theta - \theta_{\text{smooth}} \right\|^2 \right)_{\theta = \hat{\theta}} \right)$$

5: end for

7:

- 6: for k_2 -steps do
 - Sample batch $\mathscr{B}_{\mathcal{S}\setminus\mathcal{U}}$ of size $B_{\mathcal{S}\setminus\mathcal{U}}$ from $\mathcal{S}\setminus\mathcal{U}$ and update $\hat{\theta}$ using natural gradient descent

$$\hat{\theta} \leftarrow \hat{\theta} - \alpha \left(\mathbf{F} \left(\hat{\theta} \right) \right)^{-1} \left(\sum_{z \in \mathscr{B}_{s \setminus \mathcal{U}}} \nabla_{\theta} \left(\ell\left(z, \theta \right) + \gamma \left\| \theta - \theta_{\text{smooth}} \right\|^2 \right)_{\theta = \hat{\theta}} \right)$$

8: end for

9: Update smoothed parameters

$$\theta_{\text{smooth}} \leftarrow \theta_{\text{smooth}} + \beta \left(\hat{ heta} - \theta_{\text{smooth}} \right)$$

10: end for 11: Release $\tilde{\theta}_{S \setminus \mathcal{U}} = \hat{\theta}$

new models, where the MIA score is defined as the distance between the probability of a correct guess and 0.5. The results are reported in Fig. 2. The Min/Max NGD improves the MIA score while achieving comparable or better test accuracy than the Scrub algorithm. Additionally, NGD significantly enhances the test accuracy of the fine-tuning baseline while maintaining almost the same (in the CNN example) or slightly worse (in the ResNet18 example) MIA score.

6 Discussion

We study the unlearning problem from a probabilistic approach, utilizing NGD as an unlearning algorithm due to its known computational efficiency compared to existing second-order methods.

Theoretically, our study is the first to formally prove that, in a convex setting, NGD-based unlearning satisfies the (ϵ, δ) notion of unlearning. Since NGD is often approximated using Kronecker factors [26], investigating the unlearning capabilities of these approximated NGD algorithms presents another intriguing research direction. Furthermore, in many instances, an explicit NGD step can be directly computed by taking gradients relative to transformed versions of the model parameters [42, 43]. Exploring efficient NGD-based unlearning algorithms using these methods is a promising avenue for future research. Unlike the Scrub algorithm, which lacks theoretical support, our algorithm is proven to meet the (ϵ, δ) -unlearning requirement in convex cases. Extending this theory to more complex scenarios could demonstrate that Min/Max NGD formally satisfies the (ϵ, δ) -unlearning requirement.

On the practical side, we developed a Min/Max training algorithm leveraging NGD to delete samples. Our results show that our algorithm enhances the MIA score while maintaining nearly the same test accuracy as state-of-the-art baselines. Additionally, our algorithm requires fewer hyperparameters than existing algorithms. Given the known instability issues of Min/Max training procedures [9, 44], our approach results in a more stable training process. We encourage future work to explore the applicability of Min/Max NGD in larger models, various architectures, different training objectives, and across diverse domains and modalities. It is important to note that while most unlearning baselines report MIA as a measure of the amount of information the model retains about the unlearned samples, MIA still lacks a meaningful interpretation in terms of the privacy guarantees of the system, specifically regarding the (ϵ, δ) from Def. 1 (see a detailed discussion in [40]). The practical





Figure 2: Test accuracy and MIA score of the Min/Max NGD, Scrub, and the fine-tunning algorithms. The upper and lower dotted lines correspond to the original and retrained model's MIA scores. The details of the experiments are in App. H. Compared to Scrub, Min/Max NGD achieves a better MIA score while maintaining almost the same or slightly better test accuracy.

significance of the MIA score remains unclear. Since this connection is well established in the DP realm (see, for example, [45]), developing similar theorems for the unlearning framework is crucial for effectively deploying unlearning algorithms.

Broader Impact The ability to unlearning at scale is crucial for the practical deployment of artificial intelligence (AI) systems, providing an effective tool for users to manage the amount of sensitive information that machine learning models reveal about their training data. Our proposed technique offers a provable solution for unlearning data in convex cases, significantly enhancing privacy control in such scenarios. However, it is important to recognize that while the Min/Max NGD method shows promise, it lacks a formal privacy proof for non-convex cases. Therefore, any application of this algorithm for data deletion should be approached with caution. Rigorous auditing and validation processes must be in place to ensure that the intended privacy guarantees are met and that the system does not inadvertently retain sensitive information. By highlighting these considerations, we aim to encourage responsible use and further research to extend formal privacy guarantees to non-convex models.

References

- Ayush Sekhari, Jayadev Acharya, Gautam Kamath, and Ananda Theertha Suresh. Remember what you want to forget: Algorithms for machine unlearning. In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 34, pages 18075–18086, 2021.
- [2] Vinith Suriyakumar and Ashia C. Wilson. Algorithms that approximate data removal: New results and limitations. In Advances in Neural Information Processing Systems (NeurIPS), volume 35, pages 18892–18903, 2022.

- [3] Jie Xu, Zihan Wu, Cong Wang, and Xiaohua Jia. Machine unlearning: Solutions and challenges. *IEEE Trans. Emerg. Top. Comput. Intell.*, 2024.
- [4] Yinzhi Cao and Junfeng Yang. Towards making systems forget with machine unlearning. In IEEE Symp. Secur. Privacy., pages 463–480, 2015. doi: 10.1109/SP.2015.35.
- [5] Lucas Bourtoule, Varun Chandrasekaran, Christopher A. Choquette-Choo, Hengrui Jia, Adelin Travers, Baiwu Zhang, David Lie, and Nicolas Papernot. Machine unlearning. In *IEEE Symp. Secur. Privacy.*, pages 141–159, 2021. doi: 10.1109/SP40001.2021.00019.
- [6] Varun Gupta, Christopher Jung, Seth Neel, Aaron Roth, Saeed Sharifi-Malvajerdi, and Chris Waites. Adaptive machine unlearning. In Advances in Neural Information Processing Systems (NeurIPS), volume 34, pages 16319–16330. Curran Associates, Inc., 2021.
- [7] Badih Ghazi, Pritish Kamath, Ravi Kumar, Pasin Manurangsi, Ayush Sekhari, and Chiyuan Zhang. Ticketed learning–unlearning schemes. In *Conference on Learning Theory (COLT)*, volume 195, pages 5110–5139. PMLR, 12–15 Jul 2023.
- [8] Chuan Guo, Tom Goldstein, Awni Hannun, and Laurens Van Der Maaten. Certified data removal from machine learning models. In *Proceedings of the 37th International Conference on Machine Learning (ICML)*. JMLR.org, 2020.
- [9] Meghdad Kurmanji, Peter Triantafillou, Jamie Hayes, and Eleni Triantafillou. Towards unbounded machine unlearning. In Advances in Neural Information Processing Systems (NeurIPS), volume 36, pages 1957–1987, 2023.
- [10] Aditya Golatkar, Alessandro Achille, and Stefano Soatto. Eternal sunshine of the spotless net: Selective forgetting in deep networks. In *Proc. IEEE/CVF Conf. Comput. Vis. Pattern Recognit.*, pages 9304–9312, 2020.
- [11] Aditya Golatkar, Alessandro Achille, Avinash Ravichandran, Marzia Polito, and Stefano Soatto. Mixed-privacy forgetting in deep networks. In Proc. IEEE/CVF Conf. Comput. Vis. Pattern Recognit. (CVPR), pages 792–801, June 2021.
- [12] James Martens. New insights and perspectives on the natural gradient method. The Journal of Machine Learning Research (JMLR), 21(1):5776–5851, 2020.
- [13] Aditya Golatkar, Alessandro Achille, and Stefano Soatto. Forgetting outside the box: Scrubbing deep networks of information accessible from input-output observations. In *Computer Vision– ECCV 2020: 16th European Conference, Glasgow, UK, August 23–28, 2020, Proceedings, Part XXIX 16*, pages 383–398. Springer, 2020.
- [14] Junxiao Wang, Song Guo, Xin Xie, and Heng Qi. Federated unlearning via class-discriminative pruning. In Proc. ACM Web Conf. 2022, pages 622–632, 2022.
- [15] Martin J Wainwright, Michael I Jordan, et al. Graphical models, exponential families, and variational inference. *Foundations and Trends*® *in Machine Learning*, 1(1–2):1–305, 2008.
- [16] Cynthia Dwork, Aaron Roth, et al. The algorithmic foundations of differential privacy. Foundations and Trends® in Theoretical Computer Science, 9(3–4):211–407, 2014.
- [17] Cynthia Dwork. Differential privacy. In *Int. Colloq. Automata Lang. Program.*, pages 1–12. Springer, 2006.
- [18] Shun-ichi Amari. Neural learning in structured parameter spaces-natural riemannian gradient. In Advances in Neural Information Processing Systems (NeurIPS), volume 9, 1996.
- [19] Shun-Ichi Amari and Scott C Douglas. Why natural gradient? In *Proc. IEEE Int. Conf. Acoust. Speech and Sig. Proc. (ICASSP)*, volume 2, pages 1213–1216. IEEE, 1998.
- [20] Shun-ichi Amari. Information geometry and its applications, volume 194. Springer, 2016.
- [21] Christopher M Bishop and Nasser M Nasrabadi. *Pattern recognition and machine learning*, volume 4. Springer, 2006.

- [22] Razvan Pascanu and Yoshua Bengio. Revisiting natural gradient for deep networks. In *International Conference on Learning Representations (ICLR)*, 2014.
- [23] Yury Polyanskiy and Yihong Wu. Information Theory: From Coding to Learning. Cambridge University Press, 2023. URL https://people.lids.mit.edu/yp/homepage/ data/itbook-export.pdf.
- [24] Frederik Kunstner, Philipp Hennig, and Lukas Balles. Limitations of the empirical Fisher approximation for natural gradient descent. In Advances in Neural Information Processing Systems (NeurIPS), volume 32, 2019.
- [25] Roger Grosse and James Martens. A Kronecker-factored approximate fisher matrix for convolution layers. In *International Conference on Machine Learning (ICML)*, pages 573–582. PMLR, 2016.
- [26] James Martens and Roger Grosse. Optimizing neural networks with Kronecker-factored approximate curvature. In *International Conference on Machine Learning (ICML)*, pages 2408–2417. PMLR, 2015.
- [27] Nicol N. Schraudolph. Fast curvature matrix-vector products for second-order gradient descent. *Neural Computation*, 14(7):1723–1738, 2002.
- [28] Juhan Bae, Nathan Ng, Alston Lo, Marzyeh Ghassemi, and Roger B Grosse. If influence functions are the answer, then what is the question? In Advances in Neural Information Processing Systems (NeurIPS), volume 35, pages 17953–17967, 2022.
- [29] Roger Grosse, Juhan Bae, Cem Anil, Nelson Elhage, Alex Tamkin, Amirhossein Tajdini, Benoit Steiner, Dustin Li, Esin Durmus, Ethan Perez, et al. Studying large language model generalization with influence functions. arXiv preprint arXiv:2308.03296, 2023.
- [30] Naman Agarwal, Brian Bullins, and Elad Hazan. Second-order stochastic optimization for machine learning in linear time. *Journal of Machine Learning Research (JMLR)*, 18(116):1–40, 2017.
- [31] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In Proc. IEEE Conf. Comput. Vis. Pattern Recognit., pages 770–778, 2016.
- [32] Daniel Soudry and Yair Carmon. No bad local minima: Data independent training error guarantees for multilayer neural networks. *arXiv preprint arXiv:1605.08361*, 2016.
- [33] Vitaly Feldman. Does learning require memorization? a short tale about a long tail. In *Proc.* 52nd Annu. ACM SIGACT Symp. Theory Comput., pages 954–959, 2020.
- [34] Trevor Hastie, Andrea Montanari, Saharon Rosset, and Ryan J Tibshirani. Surprises in highdimensional ridgeless least squares interpolation. *Annals of statistics*, 50(2):949, 2022.
- [35] Simon Du, Jason Lee, Haochuan Li, Liwei Wang, and Xiyu Zhai. Gradient descent finds global minima of deep neural networks. In *International Conference on Machine Learning (ICML)*, pages 1675–1685. PMLR, 2019.
- [36] Zeyuan Allen-Zhu, Yuanzhi Li, and Zhao Song. A convergence theory for deep learning via over-parameterization. In *International Conference on Machine Learning (ICML)*, pages 242–252. PMLR, 2019.
- [37] Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial nets. In Advances in Neural Information Processing Systems (NeurIPS), volume 27, 2014.
- [38] Jiawei Zhang, Peijun Xiao, Ruoyu Sun, and Zhiquan Luo. A single-loop smoothed gradient descent-ascent algorithm for nonconvex-concave min-max problems. In Advances in Neural Information Processing Systems (NeurIPS), volume 33, pages 7377–7389, 2020.
- [39] Nicholas Carlini, Steve Chien, Milad Nasr, Shuang Song, Andreas Terzis, and Florian Tramer. Membership inference attacks from first principles. In *IEEE Symp. Secur. Privacy.*, pages 1897–1914. IEEE, 2022.

- [40] Jamie Hayes, Ilia Shumailov, Eleni Triantafillou, Amr Khalifa, and Nicolas Papernot. Inexact unlearning needs more careful evaluations to avoid a false sense of privacy. arXiv preprint arXiv:2403.01218, 2024.
- [41] Alex Krizhevsky and Geoffrey Hinton. Learning multiple layers of features from tiny images. Technical report, University of Torontro, ON, Canada, 2009. URL https://www.cs.toronto. edu/~kriz/learning-features-2009-TR.pdf.
- [42] Wu Lin. *Computationally efficient geometric methods for optimization and inference in machine learning*. PhD thesis, University of British Columbia, 2023.
- [43] Wu Lin, Frank Nielsen, Mohammad Emtiyaz Khan, and Mark Schmidt. Structured second-order methods via natural gradient descent. arXiv preprint arXiv:2107.10884, 2021.
- [44] Andrew Brock, Jeff Donahue, and Karen Simonyan. Large scale GAN training for high fidelity natural image synthesis. In *International Conference on Learning Representations (ICLR)*, 2019.
- [45] Peter Kairouz, Sewoong Oh, and Pramod Viswanath. The composition theorem for differential privacy. In *International Conference on Machine Learning (ICML)*, pages 1376–1385. PMLR, 2015.
- [46] Yurii Nesterov. Introductory lectures on convex optimization: A basic course, volume 87. Springer Science & Business Media, 2013.
- [47] Ashia Wilson, Maximilian Kasy, and Lester Mackey. Approximate cross-validation: guarantees for model assessment and selection. In *International Conference on Artificial Intelligence and Statistics (AISTATS)*, pages 4530–4540. PMLR, 2020.
- [48] Shai Shalev-Shwartz, Ohad Shamir, Nathan Srebro, and Karthik Sridharan. Stochastic convex optimization. In *Conference on Learning Theory (COLT)*, volume 2, page 5, 2009.
- [49] Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, et al. Pytorch: an imperative style, high-performance deep learning library. In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 32, 2019.
- [50] Y. LECUN. The MNIST database of handwritten digits. 1998. URL http://yann.lecun. com/exdb/mnist/.
- [51] Daniel Povey, Xiaohui Zhang, and Sanjeev Khudanpur. Parallel training of DNNs with natural gradient and parameter averaging. *arXiv preprint arXiv:1410.7455*, 2015.

A Notation

The notation used in this manuscript is outlined as follows. We denote random variables using sans-serif fonts (x, y, z) and their realizations using regular italic fonts (x, y, z). The Probability Density Function (PDF) of a random variable z is denoted by $P_z(\cdot)$. Groups of values are represented by capital calligraphic letters, such as $\mathcal{S} \triangleq \{z_1, z_2, \ldots, z_n\}$. Real numbers are denoted by \mathbb{R} . Matrices are denoted by bold capital letters, with the symbol \mathbf{I}_d specifically representing the $d \times d$ identity matrix. When it is clear from the context that we are referring to matrices (for example, $\nabla^2 f(\cdot)$), regular notation is used. L_2 norms are denoted by $\|\cdot\|$. We use the usual convention of f(x) = o(g(x)) to denote that $\lim_{x \to \infty} \frac{f(x)}{g(x)} = 0$, and f(x) = O(g(x)) to denote that $\lim_{x \to \infty} \frac{f(x)}{g(x)} = c$ for some finite constant $c \ (c \neq 0)$.

B Definitions

The manuscript uses the next classical definitions from the convex optimization theory [46]. **Definition 2** (Strong convexity). Let $\beta > 0$. A function $f(\cdot)$ is called β -strongly convex if and only if

$$f(y) \ge f(x) + \nabla^T f(x)(y-x) + \beta \|x-y\|^2, \ \forall (x,y) \in \operatorname{dom}(f)$$

Definition 3 (Lipschitzness). A function $f(\cdot)$ is called *C*-Lipschitz if

$$|f(x) - f(y)|| \le C ||x - y||, \ \forall (x, y) \in \text{dom}(f).$$

If $f(\cdot)$ is differentiable, then $f(\cdot)$ is called K-smooth if

$$\left\|\nabla f(x) - \nabla f(y)\right\| \le K \left\|x - y\right\|, \ \forall (x, y) \in \operatorname{dom}(f).$$

Furthermore, if $f(\cdot)$ is further twice differentiable, then $f(\cdot)$ is called M-Hessian Lipschitz if

$$\left\|\nabla^2 f(x) - \nabla^2 f(y)\right\| \le M \left\|x - y\right\|, \ \forall (x, y) \in \operatorname{dom}(f)$$

C Loss Functions With an Exponential Family Structure

In this section, we present a few examples of common loss functions in machine learning of the form $\ell(P(y|f(x;\theta)))$ where $P(y|f(x;\theta))$ belongs to an exponential family. Throughout the paper, we use the following convention to denote an exponential family

$$\log\left(P\left(y|f(x;\theta)\right)\right) = f^{T}(x;\theta)t(y) - \log\left(\sum_{\tilde{y}\in\mathcal{Y}}\exp\left\{f^{T}(x;\theta)t(\tilde{y})\right\}\right) + \beta(y)$$
(6)

and where t(y) are called the *natural statistics* and $f(x; \theta)$ are the *natural parameters*. Using this convention, we provide two popular examples of loss functions whose models fit this exponential family framework (see also [12, Sec. 9.2]).

1. Let

$$\log\left(P\left(y|f(x;\theta)\right)\right) = \left(f(x;\theta)\right)_y - \log\left(\sum_{\tilde{y}=1}^{|\mathcal{Y}|} \exp\left\{\left(f(x;\theta)\right)_{\tilde{y}}\right\}\right)$$

where $f(x; \theta)$ is a vector of size $|\mathcal{Y}|$ and $(f(x; \theta))_y$ denotes it y'th entry. By defining e_y as a vector of zeros with the y'th entry equal to 1, we get that

$$\log\left(P\left(y|f(x;\theta)\right)\right) = f^{T}(x;\theta)e_{y} - \log\left(\sum_{\tilde{y}=1}^{|\mathcal{Y}|} \exp\left\{f^{T}(x;\theta)e_{\tilde{y}}\right\}\right)$$

which corresponds to an exponential family defined over a discrete alphabet of $|\mathcal{Y}|$ letters. Here, the natural statistics are $t(y) = e_y$ and the natural parameters are $f(x; \theta)$. 2. Let

$$\log \left(P\left(y|f(x;\theta)\right) \right) = -\frac{\left(y - f(x;\theta)\right)^2}{2} = f(x;\theta) \cdot y - \frac{y^2}{2} - \frac{\left(f(x;\theta)\right)^2}{2}$$

which corresponds to the squared loss function used in regression problems ³. This corresponds to a Gaussian distribution, which belongs to an exponential family with natural statistics y and natural parameters $f(x; \theta)$.

D Fisher Information Matrix for Exponential Families

Using the fact that the distribution $P(y|f(x;\theta))$ belongs to an exponential family, namely

$$\log\left(P\left(y|f(x;\theta)\right)\right) = f^{T}(x;\theta)t(y) - \log\left(\sum_{\tilde{y}\in\mathcal{Y}}\exp\left\{f^{T}(x;\theta)t(\tilde{y})\right\}\right) + \beta(y),$$

we can directly evaluate the terms $\mathbb{E}_{\mathbf{y} \sim P_{\mathbf{y}|\mathbf{x}=x;\theta}} \left[\nabla_f \log \left(P\left(\mathbf{y} | f(x;\theta) \right) \right) \nabla_f^T \log \left(P\left(\mathbf{y} | f(x;\theta) \right) \right) \right]$ and $\mathbb{E}_{\mathbf{y} \sim P_{\mathbf{y}|\mathbf{x}=x;\theta}} \left[-\nabla_f^2 \log \left(P\left(\mathbf{y} | f(x;\theta) \right) \right) \right]$ to establish the desired equality.

First, we find that:

$$\nabla_{f} \log \left(P\left(y|f(x;\theta)\right) \right) = \nabla_{f} \left(f^{T}(x;\theta)t(y) - \log \left(\sum_{y \in \mathcal{Y}} \exp\left\{ f^{T}(x;\theta)t(y)\right\} \right) \right)$$
$$= t(y) - \mathbb{E}_{\mathsf{y} \sim P_{\mathsf{y}|\mathsf{x}=x;\theta}} \left[t(\mathsf{y}) \right],$$

thus,

$$\begin{split} \mathbb{E}_{\mathbf{y} \sim P_{\mathbf{y}|\mathbf{x}=x;\theta}} \left[\nabla_{f} \log \left(P\left(\mathbf{y}|f(x;\theta)\right) \right) \nabla_{f}^{T} \log \left(P\left(\mathbf{y}|f(x;\theta)\right) \right) \right] \\ &= \mathbb{E}_{\mathbf{y} \sim P_{\mathbf{y}|\mathbf{x}=x;\theta}} \left[\left(t(\mathbf{y}) - \mathbb{E}_{\mathbf{y} \sim P_{\mathbf{y}|\mathbf{x}=x;\theta}} \left[t(\mathbf{y}) \right] \right) \left(t(\mathbf{y}) - \mathbb{E}_{\mathbf{y} \sim P_{\mathbf{y}|\mathbf{x}=x;\theta}} \left[t(\mathbf{y}) \right] \right)^{T} \right] \end{split}$$

Next, we observe that:

$$-\nabla_{f}^{2}\log\left(P\left(y|f(x;\theta)\right)\right) = \nabla_{f}\left(\frac{\sum_{y\in\mathcal{Y}}t(y)\exp\left\{f^{T}(x;\theta)t(y)\right\}}{\sum_{y\in\mathcal{Y}}\exp\left\{f^{T}(x;\theta)t(y)\right\}}\right)$$
$$= \mathbb{E}_{\mathbf{y}\sim P_{\mathbf{y}|\mathbf{x}=x;\theta}}\left[t(\mathbf{y})t^{T}(\mathbf{y})\right] - \left(\mathbb{E}_{\mathbf{y}\sim P_{\mathbf{y}|\mathbf{x}=x;\theta}}\left[t(\mathbf{y})\right]\right)\left(\mathbb{E}_{\mathbf{y}\sim P_{\mathbf{y}|\mathbf{x}=x;\theta}}\left[t(\mathbf{y})\right]\right)^{T}$$
$$= \mathbb{E}_{\mathbf{y}\sim P_{\mathbf{y}|\mathbf{x}=x;\theta}}\left[\left(t(\mathbf{y}) - \mathbb{E}_{\mathbf{y}\sim P_{\mathbf{y}|\mathbf{x}=x;\theta}}\left[t(\mathbf{y})\right]\right)\left(t(\mathbf{y}) - \mathbb{E}_{\mathbf{y}\sim P_{\mathbf{y}|\mathbf{x}=x;\theta}}\left[t(\mathbf{y})\right]\right)^{T}\right].$$

Moreover, we note that this final result holds for any y. This concludes the proof. \Box

E Proof of Th. 1 in the Differentiable Case

We give the proof for the case where $\pi(\cdot)$ is a differentiable function. The proof for the nondifferentiable case is given in App. F.

Proof. Recall that we have defined the loss function as

$$L(\mathcal{S}, \theta, \lambda) \triangleq \frac{1}{|\mathcal{S}|} \sum_{(x, y) \in \mathcal{S}} -\log\left(P\left(y | f(x; \theta)\right)\right) + \lambda \pi(\theta)$$

³In that case, the formulation is similar to (6) where $\mathcal{Y} = \mathbb{R}$ and the summation becomes an integral

and we assume that $P(y|f(x;\theta))$ belongs to an exponential family, whose natural parameters are the features $f(x;\theta)$, namely, $\log (P(y|f(x;\theta))) = f^T(x;\theta)t(y) - \log \left(\sum_{\tilde{y}\in\mathcal{Y}} \exp \left\{f^T(x;\theta)t(\tilde{y})\right\}\right) + \beta(y)$ for some natural statistics t(y). For this model, we have

$$\nabla_{\theta} \log \left(P\left(y | f(x; \theta) \right) \right) = \nabla_{\theta} f(x; \theta) \nabla_{f} \log \left(P\left(y | f(x; \theta) \right) \right)$$

and thus, the approximated FIM is given by

$$\mathbf{F}(\mathcal{S},\theta) = \frac{1}{|\mathcal{S}|} \sum_{x \in \mathcal{S}} \mathbb{E}_{\mathbf{y} \sim P_{\mathbf{y}|\mathbf{x}=x;\theta}} \left[\nabla_{\theta} f(x;\theta) \nabla_{f} \log \left(P\left(\mathbf{y}|f(x;\theta)\right) \right) \nabla_{f}^{T} \log \left(P\left(\mathbf{y}|f(x;\theta)\right) \right) \nabla_{\theta}^{T} f(x;\theta) \right]$$
$$= \frac{1}{|\mathcal{S}|} \sum_{x \in \mathcal{S}} \nabla_{\theta} f(x;\theta) \mathbb{E}_{\mathbf{y} \sim P_{\mathbf{y}|\mathbf{x}=x;\theta}} \left[-\nabla_{f}^{2} \log \left(P\left(\mathbf{y}|f(x;\theta)\right) \right) \right] \nabla_{\theta}^{T} f(x;\theta)$$
(7a)
$$= -\frac{1}{|\mathcal{S}|} \sum_{(x,y) \in \mathcal{S}} \nabla_{\theta} f(x;\theta) \nabla_{f}^{2} \log \left(P\left(y|f(x;\theta)\right) \right) \nabla_{\theta}^{T} f(x;\theta)$$

where (7a) is by using classical properties of the exponential family, and where the last equality is since the Hessian of an exponential family with respect to the natural parameters f is independent of y (see App. D). Moreover, we note that the Hessian of the loss is given by

$$\mathbf{H}(\mathscr{S},\theta,\lambda) = \nabla_{\theta}^{2} L(\mathscr{S},\theta,\lambda) = \frac{1}{|\mathscr{S}|} \sum_{(x,y)\in\mathscr{S}} \nabla_{\theta}^{2} f(x;\theta) \nabla_{f} \log\left(P\left(y|f(x;\theta)\right)\right) + \mathbf{F}(\mathscr{S};\theta) + \lambda \nabla^{2} \pi(\theta)$$

We start by defining the next functions

$$\psi_{1} = \tilde{L}(\mathcal{S} \setminus \mathcal{U}, \theta, \lambda),$$

$$\psi_{2} = \nabla^{T} \tilde{L} \left(\mathcal{S} \setminus \mathcal{U}, \hat{\theta}_{\mathcal{S}}, \lambda \right) \left(\hat{\theta}_{\mathcal{S}} - \theta \right) + \left(\hat{\theta}_{\mathcal{S}} - \theta \right)^{T} \nabla^{2} \tilde{L} \left(\mathcal{S} \setminus \mathcal{U}, \hat{\theta}_{\mathcal{S}}, \lambda \right) \left(\hat{\theta}_{\mathcal{S}} - \theta \right),$$

$$\psi_{3} = \nabla^{T} \tilde{L} \left(\mathcal{S} \setminus \mathcal{U}, \hat{\theta}_{\mathcal{S}}, \lambda \right) \left(\hat{\theta}_{\mathcal{S}} - \theta \right) + \left(\hat{\theta}_{\mathcal{S}} - \theta \right)^{T} \left(\mathbf{F} \left(\mathcal{S}, \hat{\theta}_{\mathcal{S}} \right) + \lambda \nabla^{2} \pi \left(\hat{\theta}_{\mathcal{S}} \right) \right) \left(\hat{\theta}_{\mathcal{S}} - \theta \right),$$
(8)

where $\tilde{L}(\mathcal{S} \setminus \mathcal{U}, \theta, \lambda) \triangleq \frac{|\mathcal{S} \setminus \mathcal{U}|}{|\mathcal{S}|} \cdot L(\mathcal{S} \setminus \mathcal{U}, \theta, \lambda)$ and we note that the minimizer of ψ_1 is $\hat{\theta}_{\mathcal{S} \setminus \mathcal{U}}$. Moreover, we define the approximated solution

$$\check{\theta}_{\mathcal{S}\backslash\mathcal{U}} \triangleq \hat{\theta}_{\mathcal{S}} - \left(\mathbf{F}\left(\mathcal{S}\backslash\mathcal{U}, \hat{\theta}_{\mathcal{S}}\right) + \lambda \nabla^2 \pi\left(\hat{\theta}_{\mathcal{S}}\right)\right)^{-1} \nabla \tilde{L}\left(\mathcal{S}\backslash\mathcal{U}, \hat{\theta}_{\mathcal{S}}, \lambda\right)$$

which we note is further the minimizer of ψ_3 and, upon the regularization term, amounts to an NGD step. We first note that by the convexity and differentiability assumptions on the loss function, $\nabla L\left(\mathcal{S}, \hat{\theta}_{\mathcal{S}}, \lambda\right) = 0$. Thus, using the structure of the loss function, we get that $\nabla L\left(\mathcal{S} \setminus \mathcal{U}, \hat{\theta}_{\mathcal{S}}, \lambda\right) = -\nabla L\left(\mathcal{U}, \hat{\theta}_{\mathcal{S}}, \lambda = 0\right)$ and $\check{\theta}_{\mathcal{S} \setminus \mathcal{U}}$ is $\tilde{\theta}_{\mathcal{S} \setminus \mathcal{U}}$ of Alg. 1. Thus, we will continue with $\tilde{\theta}_{\mathcal{S} \setminus \mathcal{U}}$. We note that Assumption 1.b guarantees that the overall loss, L, is μ -strongly convex. Thus, [2, Lem. 1, (6a)] continue to hold under our assumptions, namely

$$\left\|\hat{\theta}_{\mathcal{S}} - \hat{\theta}_{\mathcal{S}\backslash\mathcal{U}}\right\| \le \frac{|\mathcal{U}| C}{|\mathcal{S}| \mu} = \frac{mC}{n\mu} \tag{9}$$

Using the optimizer comparison lemma [47, Lem. 1] and Cauchy-Schwartz inequality, we get that

$$\frac{\mu}{2} \left\| \hat{\theta}_{\mathcal{S} \setminus \mathcal{U}} - \tilde{\theta}_{\mathcal{S} \setminus \mathcal{U}} \right\|_{2}^{2} \leq \left(\hat{\theta}_{\mathcal{S} \setminus \mathcal{U}} - \tilde{\theta}_{\mathcal{S} \setminus \mathcal{U}} \right)^{T} \left(\nabla(\psi_{3} - \psi_{1}) \left(\hat{\theta}_{\mathcal{S} \setminus \mathcal{U}} \right) \right) \\ \leq \left\| \hat{\theta}_{\mathcal{S} \setminus \mathcal{U}} - \tilde{\theta}_{\mathcal{S} \setminus \mathcal{U}} \right\| \left\| \left(\nabla(\psi_{3} - \psi_{1}) \left(\hat{\theta}_{\mathcal{S} \setminus \mathcal{U}} \right) \right) \right\|$$

We divide both sides by $\left\|\hat{\theta}_{\mathcal{S}\setminus\mathcal{U}} - \tilde{\theta}_{\mathcal{S}\setminus\mathcal{U}}\right\|$, and by using Cauchy-Schwartz again we get

$$\frac{\mu}{2} \left\| \hat{\theta}_{\mathcal{S} \setminus \mathcal{U}} - \tilde{\theta}_{\mathcal{S} \setminus \mathcal{U}} \right\| \leq \left\| \left(\nabla(\psi_{3} - \psi_{1}) \left(\hat{\theta}_{\mathcal{S} \setminus \mathcal{U}} \right) \right) \right\| + \left\| \left(\nabla(\psi_{2} - \psi_{1}) \left(\hat{\theta}_{\mathcal{S} \setminus \mathcal{U}} \right) \right) \right\| \\
\leq \left\| \nabla^{2} \tilde{L} \left(\mathcal{S} \setminus \mathcal{U}, \hat{\theta}_{\mathcal{S}}, \lambda \right) - \mathbf{F} \left(\mathcal{S}, \hat{\theta}_{\mathcal{S}} \right) - \lambda \nabla^{2} \pi \left(\hat{\theta}_{\mathcal{S}} \right) \right\| \left\| \hat{\theta}_{\mathcal{S}} - \hat{\theta}_{\mathcal{S} \setminus \mathcal{U}} \right\| \\
+ \left\| \left(\nabla(\psi_{2} - \psi_{1}) \left(\hat{\theta}_{\mathcal{S} \setminus \mathcal{U}} \right) \right) \right\| \\
\leq \frac{mC}{n\mu} \cdot \left\| \frac{1}{|\mathcal{S}|} \left(\sum_{(x,y) \in \mathcal{U}} \nabla_{\theta} f \left(x; \hat{\theta}_{\mathcal{S}} \right) \nabla_{f}^{2} \log \left(P \left(y \middle| f \left(x; \hat{\theta}_{\mathcal{S}} \right) \right) \right) \right) \nabla_{\theta}^{T} f \left(x; \hat{\theta}_{\mathcal{S}} \right) \\
+ \sum_{(x,y) \in \mathcal{S} \setminus \mathcal{U}} \nabla_{\theta}^{2} f \left(x; \hat{\theta}_{\mathcal{S}} \right) \nabla_{f} \log \left(P \left(y \middle| f \left(x; \hat{\theta}_{\mathcal{S}} \right) \right) \right) \right) \right\| \\
+ \frac{Mm^{2}C^{2}}{2\mu^{2}n^{2}}$$
(10)

where the third term was calculated similarly to the proof in [2, Lem. 1] (implied by the M-smoothness of the gradient of L, see also [46, Lem. 1.2.3]). We further use the triangle inequality to get the next upper bound

$$\begin{split} \frac{\mu}{2} \left\| \hat{\theta}_{\mathcal{S} \setminus \mathcal{U}} - \tilde{\theta}_{\mathcal{S} \setminus \mathcal{U}} \right\| &\leq \frac{mC}{n\mu \left| \mathcal{S} \right|} \sum_{(x,y) \in \mathcal{U}} \left\| \nabla_{\theta} f(x;\theta) \nabla_{f}^{2} \log \left(P\left(y | f(x;\theta) \right) \right) \nabla_{\theta}^{T} f(x;\theta) \right\| \\ &+ \frac{mC}{n\mu \left| \mathcal{S} \right|} \sum_{(x,y) \in \mathcal{S} \setminus \mathcal{U}} \left\| \nabla_{\theta}^{2} f\left(x;\hat{\theta}_{\mathcal{S}}\right) \right\| \left\| \nabla_{f} \log \left(P\left(y | f\left(x;\hat{\theta}_{\mathcal{S}}\right) \right) \right) \right\| \\ &+ \frac{Mm^{2}C^{2}}{2\mu^{2}n^{2}} \end{split}$$

We note that when the loss is minimized exactly, we have $P(y|f(x;\theta)) = 1^4$. Thus, following the notation of App. D we have that $t(y) = \mathbb{E}_{y \sim P_{y|x=x;\theta}} [t(y)]$ and since $\nabla_f \log \left(P\left(y \middle| f\left(x;\hat{\theta}_{\mathcal{S}}\right) \right) \right) = t(y) - \mathbb{E}_{y \sim P_{y|x=x;\theta}} [t(y)]$ we get that the middle term is zero. Thus, by the boundedness assumption on the Hessian, we get that

$$\left\|\hat{\theta}_{\mathcal{S}\backslash\mathcal{U}} - \tilde{\theta}_{\mathcal{S}\backslash\mathcal{U}}\right\| \le \frac{2mCQ}{\mu^2 n^2} \sum_{(x,y)\in\mathcal{U}} \left\|\nabla_{\theta} f\left(x; \hat{\theta}_{\mathcal{S}}\right)\right\|^2 + \frac{Mm^2C^2}{\mu^3 n^2} \tag{11}$$

Using the assumption on the boundedness of the gradient of the features $f(x;\theta)$ and by using the Gaussian mechanism for DP [16, App. A] (see also [2]) the proof is done.

We now demonstrate how the assumptions on the loss minimization and the Hessian boundedness follow in many popular scenarios in machine learning. Specifically, we look at regression tasks (where we aim at minimizing the Mean-Squared Error (MSE) between the label y and the predictor $f(x; \theta)$) and classification tasks (where we try to match $f(x; \theta)$ to the label y), whose probabilistic models were specified in App. C.

Regression: We note that $\nabla_f \log (P(y|f(x;\theta))) = (y - f(x;\theta))$, and thus we get that

$$\sum_{(x,y)\in\mathcal{S}\backslash\mathcal{U}} \left\|\nabla_{\theta}^{2}f(x;\theta)\right\|_{2}^{2} \left\|\nabla_{f}\log\left(P\left(y|f(x;\theta)\right)\right)\right\|_{2}^{2} = \sum_{(x,y)\in\mathcal{S}\backslash\mathcal{U}} \left\|\nabla_{\theta}^{2}f(x;\theta)\right\|_{2}^{2} \left(y-f(x;\theta)\right)^{2}$$

⁴In the continuous case, this amounts to $P(y|f(x;\theta))$ converging to a delta-function, concentrated around the value y

For $\theta = \hat{\theta}_{\mathcal{S}}$, we recognize this term as a weighted version of the training loss over the examples in $\mathcal{S} \setminus \mathcal{U}$. Thus, whenever the training error is zero, this term vanishes. Moreover, we note that in this case $-\nabla_f^2 \log (P(y|f(x;\theta))) = \mathbf{I}_d$ and thus is bounded as desired.

Classification: In this case,

$$\nabla_{f} \log \left(P\left(y|f(x;\theta)\right) \right) = \nabla_{f} \left(\left(f(x;\theta)\right)_{y} - \log \left(\sum_{t \in \mathcal{Y}} \exp\left\{ \left(f(x;\theta)\right)_{t}\right\} \right) \right)$$
$$= e_{y} - \frac{\exp\left\{f(x;\theta)\right\}}{\sum_{t \in \mathcal{Y}} \exp\left\{\left(f(x;\theta)\right)_{t}\right\}}$$
(12)

where $\exp \{f(x; \theta)\}$ refers to applying $\exp \{\cdot\}$ to the vector $f(x; \theta)$ element-wise and e_y denotes a unit vector of size $|\mathcal{Y}|$ whose all entries are 0 except from the entry that corresponds to the letter y, which is 1. However, since for $\theta = \hat{\theta}_s$ the second term of (12) is the vector of probabilities the model assigns to each label, it would be zero whenever the training loss is zero, namely, whenever our model predicts probability 1 to the correct label and zero to the others. Thus, (12) will be zero whenever our model achieves a zero training loss. Moreover, we note that in this case $\nabla_f^2 \log (P(y|f(x;\theta))) = -\nabla_f (\operatorname{softmax}(f(x;\theta)))$. Then, we note that the diagonal elements of this matrix are given by $\operatorname{softmax}(f(x;\theta))_i - (\operatorname{softmax}(f(x;\theta))_i)^2$ and the off-diagonal elements are given by $\operatorname{softmax}(f(x;\theta))_i \cdot \operatorname{softmax}(f(x;\theta))_j$. Thus, since the softmax elements are less than 1, each entry of this matrix is bounded in the range [0, 1], and the overall matrix is bounded as desired.

F Proof of Th. 1 in the Non-Differentiable Case

The proof follows similarly to the proof from App. E (and similarly to [47, Thm. 11]), by changing the definition of the functions ψ_1, ψ_2 and ψ_3 from (8) to

$$\begin{split} \psi_{1} &\triangleq 2\tilde{L}\left(\mathcal{S}\backslash\mathcal{U},\theta,\lambda\right) = 2\tilde{L}\left(\mathcal{S}\backslash\mathcal{U},\theta,\lambda=0\right) + 2\lambda\pi(\theta),\\ \psi_{2} &\triangleq 2\nabla^{T}\tilde{L}\left(\mathcal{S}\backslash\mathcal{U},\hat{\theta}_{\mathcal{S}},\lambda=0\right)\left(\hat{\theta}_{\mathcal{S}}-\theta\right) + \left(\hat{\theta}_{\mathcal{S}}-\theta\right)^{T}\nabla^{2}\tilde{L}\left(\mathcal{S}\backslash\mathcal{U},\hat{\theta}_{\mathcal{S}},\lambda=0\right)\left(\hat{\theta}_{\mathcal{S}}-\theta\right) + 2\lambda\pi(\theta)\\ \psi_{3} &\triangleq 2\nabla^{T}\tilde{L}\left(\mathcal{S}\backslash\mathcal{U},\hat{\theta}_{\mathcal{S}},\lambda=0\right)\left(\hat{\theta}_{\mathcal{S}}-\theta\right) + \left(\hat{\theta}_{\mathcal{S}}-\theta\right)^{T}\mathbf{F}\left(\hat{\theta}_{\mathcal{S}}-\theta\right) + 2\lambda\pi(\theta)\\ &= \left(\theta - \left(\hat{\theta}_{\mathcal{S}}+\mathbf{F}^{-1}\nabla\tilde{L}\left(\mathcal{S}\backslash\mathcal{U},\hat{\theta}_{\mathcal{S}},\lambda=0\right)\right)\right)^{T}\mathbf{F}\left(\theta - \left(\hat{\theta}_{\mathcal{S}}+\mathbf{F}^{-1}\nabla\tilde{L}\left(\mathcal{S}\backslash\mathcal{U},\hat{\theta}_{\mathcal{S}},\lambda=0\right)\right)\right)\\ &+ 2\lambda\pi(\theta) + G \end{split}$$

where G is a constant (which is independent of θ), we use the abbreviated notation **F** for **F** $\left(\mathscr{S} \setminus \mathscr{U}, \hat{\theta}_{\mathscr{S}} \right)$ and where we note that the minimizer of ψ_3 equals to $\tilde{\theta}_{\mathscr{S} \setminus \mathscr{U}}$ from (4). Then, the strong convexity of the overall loss function (implied by the strong convexity of the elements $\ell(z, \theta)$ and the convexity of $\pi(\theta)$) implies that (in a similar way to (10))

$$\frac{\mu}{2} \left\| \hat{\theta}_{\mathcal{S} \setminus \mathcal{U}} - \tilde{\theta}_{\mathcal{S} \setminus \mathcal{U}} \right\|^2 \le \left\| \left(\nabla(\psi_3 - \psi_2) \left(\hat{\theta}_{\mathcal{S} \setminus \mathcal{U}} \right) \right) \right\| + \left\| \left(\nabla(\psi_2 - \psi_1) \left(\hat{\theta}_{\mathcal{S} \setminus \mathcal{U}} \right) \right) \right\|,$$

where the gradient of the difference is defined even if $\pi(\theta)$ is not differentiable, as it canceled out after the subtraction. Then, the proof follows similarly to App. E.

G Proof of Generalization Guarantees

The proof follows similarly to [1, Lem. 9] and [2, Thm. 1]. Let $\hat{\theta}_{\mathcal{S}} \triangleq \hat{\theta}_{\mathcal{S}}(\lambda)$. We first re-write the difference between the population risks as

$$L(P_{z},\theta_{\mathcal{S}\setminus\mathcal{U}},\lambda) - L(P_{z},\theta^{*}(\lambda),\lambda)$$

= $L(P_{z},\bar{\theta}_{\mathcal{S}\setminus\mathcal{U}},\lambda) - L(P_{z},\hat{\theta}_{\mathcal{S}},\lambda) + L(P_{z},\hat{\theta}_{\mathcal{S}},\lambda) - L(P_{z},\theta^{*}(\lambda),\lambda)$

By using the Lipshitzness and strong convexity of the loss function, the second difference can be upper bounded by (see [48, Claim 6.2], [1, Thm. 3])

$$L\left(P_{\mathsf{z}},\hat{\theta}_{\mathscr{S}},\lambda\right) - L\left(P_{\mathsf{z}},\theta^{*}(\lambda),\lambda\right) \leq \frac{4C^{2}}{\mu n}$$

Moreover, by the Lipschitzness of the loss function, we get that

$$L\left(P_{\mathsf{z}},\bar{\theta}_{\mathcal{S}\backslash\mathcal{U}},\lambda\right) - L\left(P_{\mathsf{z}},\hat{\theta}_{\mathcal{S}},\lambda\right) \leq C\mathbb{E}\left[\left\|\bar{\theta}_{\mathcal{S}\backslash\mathcal{U}}-\hat{\theta}_{\mathcal{S}}\right\|\right]$$
$$\leq C\mathbb{E}\left[\left\|\bar{\theta}_{\mathcal{S}\backslash\mathcal{U}}-\hat{\theta}_{\mathcal{S}\backslash\mathcal{U}}\right\|\right] + C\mathbb{E}\left[\left\|\hat{\theta}_{\mathcal{S}\backslash\mathcal{U}}-\hat{\theta}_{\mathcal{S}}\right\|\right] \tag{13a}$$
$$\leq C\left(\mathbb{E}\left[\left\|\tilde{\theta}_{\mathcal{S}\backslash\mathcal{U}}-\hat{\theta}_{\mathcal{S}\backslash\mathcal{U}}\right\|\right] + \mathbb{E}\left[\left\|\hat{\theta}_{\mathcal{S}\backslash\mathcal{U}}-\hat{\theta}_{\mathcal{S}}\right\|\right]$$

$$\leq C\left(\mathbb{E}\left[\left\|\tilde{\theta}_{\mathcal{S}\backslash\mathcal{U}} - \hat{\theta}_{\mathcal{S}\backslash\mathcal{U}}\right\|\right] + \mathbb{E}\left[\left\|v\right\|\right]\right) + \frac{mC^{2}}{\mu n}$$
(13b)

$$\leq \left(\frac{C\tilde{\gamma}}{n^2}\right) \cdot \left(1 + \frac{1}{\epsilon} \cdot \sqrt{2\log\left(\frac{1.25}{\delta}\right) \cdot \frac{\Gamma\left(\frac{d+1}{2}\right)}{\Gamma\left(\frac{d}{2}\right)}}\right) + \frac{mC^2}{\mu n}$$
(13c)

where (13a) is by the triangle inequality, (13b) is by using (9) and using again the triangle inequality, and (13c) is by (11) and since ||v|| is a χ^2 variable with *d*-degrees of freedom, $\tilde{\gamma}$ was defined in Alg. 1 and $\Gamma(x) \triangleq \int_0^\infty t^{x-1} e^{-t} dt$, $x \ge 1$ is the Γ -function. The proof follows by using the fact that m = o(n) and $\frac{\Gamma(\frac{d+1}{2})}{\Gamma(\frac{d}{2})} = O(\sqrt{d})$.

H Experiments Details

All experiments were implemented using the PyTorch [49] framework, and we ran all experiments on NVIDIA Geforce RTX 3090 GPU. The datasets and models used in our experiments are detailed below.

H.1 Datasets

We utilized the MNIST [50] and CIFAR10 [41] datasets, as provided by the torchvision package in PyTorch. During training and for our unlearning simulations, the data was shuffled. We trained the models without data augmentation to stay aligned with previous unlearning works. The CIFAR10 dataset was pre-processed using the next two main steps: first, we converted the images to tensors using the transforms.ToTensor() method. Next, the images were normalized using the transforms.Normalize() method. The normalization process adjusts the image data so that the pixel values have a mean of 0.4914, 0.4822, and 0.4465 and a standard deviation of 0.2023, 0.1994, and 0.2010 for the red, green, and blue channels, respectively. The MNIST dataset was pre-processed using a similar pipeline, where we normalized the mean and the standard deviation to 0.5.

H.2 Neural Networks Architectures

All models were trained using a cross-entropy loss.

One-Layer Perceptron (OLP): We trained a one-layer perceptron to classify the MNIST dataset. The classifier has one hidden layer with 200 neurons and a ReLU activation function. It was trained for 100 epochs using the Adam optimizer, with a learning rate of 0.02, $\beta_1 = 0.9$, $\beta_2 = 0.99$, $\epsilon = 10^{-8}$, a weight decay of 10^{-4} , and a batch size of 256.

Multi-Layer Perceptron (MLP): Similar to the OLP architecture, the MLP was trained to classify the MNIST dataset. This model comprises three fully connected layers with widths of 784×784 , 784×256 , and 256×10 , with ReLU activation between the layers. The classifier was trained using SGD for 100 epochs with a learning rate of 0.01, a weight decay of 10^{-4} , and a batch size of 128. The learning rate was reduced by a factor of 10 at epoch 50.

Convolutional Neural Network (CNN): The CNN architecture was designed to classify the CI-FAR10 dataset. It comprises convolutional layers followed by fully connected layers. The convolutional part includes two convolutional layers with 16 and 32 output channels, respectively, and 3×3 kernels with padding of 1. A 2×2 Max-pooling layer is placed after each convolutional layer. The fully connected part includes two layers with widths of 2048×128 and 128×10 , with a tanh activation between them. The network was trained for 100 epochs using SGD with a learning rate of 0.01, a weight decay of 10^{-4} , and a batch size of 128. We reduced the learning rate by 10 whenever the training loss changes by less than 0.00001 for five consecutive epochs.

ResNet18: We used PyTorch's pre-trained version of ResNet18, initially trained on the ImageNet dataset. A fully connected layer of size 1000×10 was added, and the network was fine-tuned on the CIFAR10 dataset for 50 epochs using SGD with a learning rate of 0.01 and a weight decay of 10^{-4} . The model was trained with a batch size of 128. We reduced the learning rate by 10 whenever the training loss changes by less than 0.00001 for five consecutive epochs.

H.3 Unlearning Algorithms

This section details the implementation of our unlearning algorithms, Fine-Tuning, Scrub, and Min/Max NGD.

Fine-tunning: The fine-tunning algorithm fine-tunes the model on the retain set. In our implementation, we use batches of size 128, weight decay of $5 \cdot 10^{-4}$, momentum of 0.9, and an initial learning rate of 0.05, reduced by a factor of 5 after each epoch. We have used two different optimizers: the first is the vanilla SGD optimizer of Pytorch, and the second aims to approximate an NGD according to the algorithm from [51]. Our implementation is based on the one presented in https://github.com/YiwenShaoStephen/NGD-SGD/tree/master, with the update-period parameter set to 4.

Scrub: Our implementation of the Scrub algorithm follows the procedure detailed in [9], based on the code provided at https://github.com/meghdadk/SCRUB. We set our hyperparameters similarly to those in the original paper [9]: we have used an Adam optimizer with an initial learning rate of 0.0005, reduced by a factor of 10 after each epoch, a weight-decay of 0.1, a smoothing factor of 0.5 and the parameter α of the Scrub algorithm (which weights the KL-term and the loss term) was set to 0.5. We used batches of 64 for the retain-set and of size 16 for the forget set. The rest of the hyperparameters were chosen similarly to those of [9].

Min/Max NGD: The Min/Max NGD algorithm (Alg. 2) is implemented using a Min/Max training procedure similar to that in the Scrub implementation. Smoothing is performed using PyTorch's built-in function torch.optim.swa utils.AveragedModel. The NGD was implemented based on the method from [51], with code from https://github.com/YiwenShaoStephen/NGD-SGD/tree/master. The learning rate is 0.0007 for the CNN example and 0.0005 for the ResNet example. We reduced the learning rate by a factor of 10 after 4 epochs. We set the momentum to 0.9, the weight-decay to 0.1, and the update period of the NGD to 4. The smoothing parameter (β of Alg. 2) was set to 0.4. We used batches of size 128 for the retain-set and 32 for the forget set.

I Computing the Newton and the NGD Steps Using LiSSA

In this section, we review the Linear time Stochastic Second-Order Algorithm (LiSSA) algorithm, used for efficient implementation of second-order optimization methods [30] and which we used to demonstrate the computational efficiency of the NGD relative to a Newton step.

I.1 The LiSSA Algorithm

The LiSSA algorithm approximates the result of a matrix inverse times a vector by using a truncated Neumann series. Following our ERM framework, let $\mathbf{A}(\mathcal{S})$ be a positive-definite matrix of the form $\mathbf{A}(\mathcal{S}) \triangleq \sum_{z \in \mathcal{S}} \mathbf{A}(z)$ for some matrix $\mathbf{A}(z)$ that depends on the training point z. Using Neumann expansion, we can approximate its inverse via the next summation

$$\left(\mathbf{A}\left(\mathcal{S}\right)\right)^{-1} = \sigma^{-1} \cdot \sum_{t=0}^{T} \left(\mathbf{I}_{d} - \sigma^{-1} \cdot \left(\mathbf{A}\left(\mathcal{S}\right)\right)\right)^{t}$$
(14)

where the approximation becomes exact as $T \to \infty$ and where $\sigma > 0$ is a scaling hyperparameter chosen sufficiently large to ensure convergence of the series. We note that (14) can be used to

calculate arguments of the form $(\mathbf{A}(\mathscr{S}))^{-1} x$ for some vector x via the next recursive relations

$$v_0 = x$$

 $v_t = v_{t-1} - \sigma^{-1} \cdot (\mathbf{A}(\mathcal{S})) v_{t-1}, \ t = 1, \dots, T$

where $\hat{v}_T = \sigma^{-1} \cdot v_T$ contains the approximated result, i.e. $\hat{v}_T \cong (\mathbf{A}(\mathcal{S}))^{-1} x$.

In practice, since we can not calculate $\mathbf{A}(\mathcal{S})$ (because we can not evaluate the whole training set), we sample a batch of data points and calculate \mathbf{A} on this batch. Then, the overall calculation is repeated R different times and averaged to yield the next estimate:

$$\left(\mathbf{A}\left(\mathcal{S}\right)\right)^{-1} x \cong \frac{1}{R} \sum_{r=1}^{R} \sigma^{-1} \cdot v_{T}^{(r)}$$

where $v_T^{(r)}$ is generated via the recursion

$$\begin{aligned} v_0^{(r)} &= x, \\ v_t^{(r)} &= v_{t-1}^{(r)} - \sigma^{-1} \cdot \left(\mathbf{A} \left(\mathscr{B}_{t,r} \right) \right) v_{t-1}^{(r)}, \ t = 1, \dots, T \end{aligned}$$

and $\mathscr{B}_{t,r}$ corresponds to a batch of $B \geq 1$ data points that were sampled to calculate **A** in the (t,r) iteration. To calculate the NGD and the Newton steps, we replace the matrix $\mathbf{A}(z)$ with $\mathbb{E}_{\mathbf{y}\sim P_{\mathbf{y}|\mathbf{x}=x;\theta}}\left[\nabla_{\theta}\log\left(P_{\mathbf{y}|\mathbf{x};\theta}\left(\mathbf{y}|x;\theta^{(t)}\right)\right)\nabla_{\theta}^{T}\log\left(P_{\mathbf{y}|\mathbf{x};\theta}\left(\mathbf{y}|x;\theta^{(t)}\right)\right)\right]$ and with $\nabla_{\theta}^{2}\log\left(P_{\mathbf{y}|\mathbf{x};\theta}(y|x;\theta)\right)$, respectively. Moreover, since the LiSSA requires the matrix $\mathbf{A}(\mathscr{S})$ to be positive-definite, we must add a regularization term to ensure this positive definiteness. Thus, usually we replace any $\mathbf{A}(z)$ with $\mathbf{A}(z) + \lambda \mathbf{I}_{d}$.