Towards Building Specialized Generalist AI with System 1 and System 2 Fusion

Kaiyan Zhang¹* Biqing Qi¹* Bowen Zhou^{1,2†} ¹Tsinghua University ²Shanghai AI Laboratory zhoubowen@tsinghua.edu.cn

Abstract

In this perspective paper, we introduce the concept of Specialized Generalist Artificial Intelligence (SGAI or simply SGI) as a crucial milestone toward Artificial General Intelligence (AGI). Compared to directly scaling general abilities, SGI is defined as AI that specializes in at least one task, surpassing human experts, while also retaining general abilities. This fusion path enables SGI to rapidly achieve high-value areas. We categorize SGI into three stages based on the level of mastery over professional skills and generality performance. Additionally, we discuss the necessity of SGI in addressing issues associated with large language models, such as their insufficient generality, specialized capabilities, uncertainty in innovation, and practical applications. Furthermore, we propose a conceptual framework for developing SGI that integrates the strengths of Systems 1 and 2 cognitive processing ³. This framework comprises three layers and four key components, which focus on enhancing individual abilities and facilitating collaborative evolution. We conclude by summarizing the potential challenges and suggesting future directions. We hope that the proposed SGI will provide insights into further research and applications towards achieving AGI.



Figure 1: The role of Specialized Generalist Intelligence (SGI) is a crucial milestone toward Artificial General Intelligence (AGI). The implementation path of AGI encompasses two dimensions: speciality and generality. The development of speciality, as detailed in "Levels of AGI" (Morris et al., 2024), is often compared with human intelligence. The differences in generality lie in the number of skills held, which also depend on distinct learning paradigms. While the "Scaling Law" has led to significant improvements in the generality of LLMs, progress in speciality remains extremely slow. Upon reviewing the development of technology, a high-value area emerges for AGI applications that require models to possess both robust generality and adequate specialty. This optimal balance point is referred to as the "tipping point" for specialized generalists.

^{*}Equal contributions

[†]Corresponding author

³Described by psychologist Daniel Kahneman's book "Thinking, Fast and Slow", System 1 is fast, automatic, and intuitive thinking, while System 2 is slow, deliberate, and analytical thinking.

Contents

1	Intr	Introduction				
2	Wha	What is Specialized Generalist AI?				
	2.1	Three Stages of AI	4			
	2.2	The Current Stage of AI	4			
	2.3	Definition, Capabilities and Stages of SGI	6			
3	Why	Why Specialized Generalist?				
	3.1	Generalists Are Not Sufficiently General	7			
	3.2	Specialists Lack Uncertainty in Innovations	8			
4	Con	Conceptual Framework				
	4.1	Preliminary: History of System 1 and System 2 in AI	8			
	4.2	Layer 1: Foundational Abilities	9			
		4.2.1 Component 1: System 1 Capabilities Enhancement	9			
		4.2.2 Component 2: System 2 Capabilities Enhancement	10			
	4.3	Layer 2: Collaborative Fusion	11			
		4.3.1 Component 3: System 1 and 2 Collaborations	11			
	4.4	Layer 3: Interactive Self-Evolving	12			
		4.4.1 Component 4: Self-Evolving of Dual-System	12			
5	Challenges and Future Directions					
	5.1	Building Models Collaboration Laws.	12			
	5.2	Building Data Mixture Laws	13			
	5.3	New Evaluation and Benchmarks.	13			
	5.4	New Architecture from Scratch.	13			
	5.5	Applications in Multi-modal and Embodied AI	13			
	5.6	Applications in Scientific Discovery	14			
	5.7	Risks and Controllability.	14			
6	Con	Conclusion				
Co	ontrib	outions	15			
Acknowledgements						

1 Introduction

Artificial intelligence (AI) (McCarthy et al., 2006) has a long history, dating back to the Dartmouth Summer Research Project ⁴ in 1956, which aimed to complete intellectual tasks automatically without human intervention. Over the past 60 years, various notable AI applications, such as Deep Blue (Campbell et al., 2002b), Watson (IBM, 2015), AlphaGo (Silver et al., 2017a), and AlphaFold (Jumper et al., 2021a), have surpassed almost all skilled adults in specialized tasks. Recently, the emergence of Large Language Models (LLMs) such as GPT-4 (Achiam et al., 2023), Gemini 1.5 (Reid et al., 2024), Claude (Anthropic, 2024) and Llama 3 (AI@Meta, 2024) has significantly accelerated AI research and applications in general tasks.

According to the "Scaling Law" (Kaplan et al., 2020; Hoffmann et al., 2022), LLMs with massive parameters trained on extremely large corpora exhibit exceptionally high intelligence compared to earlier AIs (Krizhevsky et al., 2012; Sutskever et al., 2014; He et al., 2016; Devlin et al., 2019). LLMs and LLM-based agents demonstrate advanced capabilities in instruction following (Taori et al., 2023; Ding et al., 2023; Xu et al., 2023), programming (Qian et al., 2023; Yang et al., 2024a; Shao et al., 2024b), mathematics (Lightman et al., 2023; Trinh et al., 2024), and various downstream applications. These models have achieved human-level understanding in various academic benchmarks and have even surpassed human experts in specific domains, such as medical (Nori et al., 2023; Saab et al., 2024) and financial (Kim et al., 2024) tasks.

However, LLMs still fail to outperform humans on most tasks, especially those requiring reasoning and deliberation (Huang et al., 2023a; Wan et al., 2024b), which is a characteristic of Artificial General Intelligence (AGI). Broadly defined, AGI refers to machines capable of performing any intellectual task that a human can do (Feng et al., 2024). According to recent definitions of AGI levels (Morris et al., 2024), powerful LLM-based assistants like ChatGPT and Gemini can be regarded as emerging AGI, comparable to or somewhat better than an unskilled human across a wide range of non-physical tasks. Although "sparks" of AGI are already present in the latest LLMs (Bubeck et al., 2023) in terms of general ability, they are still far from achieving real AGI. The next step in the development of AGI from generality is competent AGI (Morris et al., 2024), which should achieve performance at least at the 50th percentile of skilled adults compared to emerging AGI.

In practice, the definition of AGI is challenging to discern in real-world deployments and high-value applications. The applications of the latest LLMs in most real-world scenarios are still experimental and do not yet produce high-value innovations. This raises a critical question:

What should be the next step when optimizing LLMs towards AGI from a practical standpoint?

In contrast to the gradual advancement of scaling general capabilities towards AGI, we aim to prioritize a more expedited approach. This path focuses on achieving a breakthrough in at least one specialized capability while maintaining essential general capabilities, thereby defining the core of Specialized Generalist Intelligence (SGI). Specifically, our goal is to create a self-reinforcing AGI acceleration path by generating high-efficiency data from significant feedback effects. In this position paper, we argue that it is essential to strive for the achievement of SGI at this juncture. From the perspective of intelligence relative to skilled adults, previous AIs specialized in one task, like AlphaGo and AlphaFold, should be regarded as specialists, achieving performance better than 90% of skilled adults (human experts). Meanwhile, AGI is a generalist, possessing higher specialized abilities across various tasks compared to human experts in almost any specific domain. On the other hand, SGI refers to AI systems with intelligence specialized in at least one task, surpassing human experts, while also maintaining general abilities superior to those of an unskilled human across nearly any task. In summary, in the context of SGI system development, we envision that such systems should possess the critical abilities to continuously learn and adapt to new tasks, autonomously uncover novel knowledge, and optimize their objectives in alignment with human values.

In the following sections, we first introduce the concept of specialized generalist AI in § 2, where we define it within the context of AGI levels (Morris et al., 2024). Then, we discuss the necessity of specialized generalists in § 3. Next, we present a conceptual framework from the lens of System 1 and System 2 in § 4, which encompasses four components aimed at enhancing the capabilities of System 1 and System 2 and their interactions. Finally, we discuss challenges and future directions for achieving specialized generalists in § 5.

⁴https://en.wikipedia.org/wiki/Dartmouth_workshop

2 What is Specialized Generalist AI?

Takeaway Message

As significant milestones toward expert-level AGI, Specialized Generalist AI (SGI) possesses specialized abilities in specific tasks, surpassing 90% of human experts, while also maintaining a general capability across a wide range of tasks at least comparable to an unskilled human's abilities.

In this section, we describe what specialized generalist AI is. We first introduce the three stages of AI in § 2.1 and then identify the current state of AI especially LLMs in § 2.2. Finally, we define the position of SGI and outline its five stages in § 2.3.

2.1 Three Stages of AI

Reviewing the development process of AI (Muggleton, 2014; Haenlein & Kaplan, 2019), we can divide it into three main stages based on the scope of intelligence (IBM, 2016):

- Stage 1: Artificial Narrow Intelligence (ANI). ANI primarily relies on supervised learning (Krizhevsky et al., 2012; Russakovsky et al., 2015) with large amounts of manually labeled data. The task scope of ANI is narrow, and new AI models need to be trained for new tasks. During this period, we know exactly what AI can and cannot do, indicating that AIs lack the ability to generalize to new tasks. Generally speaking, efforts on ANI were largely completed by 2016, just before the emergence of transformers and self-supervised pre-training like ELMO (Peters et al., 2018), BERT (Devlin et al., 2019), and GPT (Radford et al., 2018).
- Stage 2: Artificial Broad Intelligence (ABI). The most significant feature of ABI is the selfsupervision learning paradigm, which reduces the need for extensive explicit teaching for specific tasks. The learning method follows an end-to-end approach based on scalable architectures like attention-based (Lin et al., 2017) transformers (Vaswani et al., 2017), enabling AI to decompose and complete multiple tasks independently. Using the next token prediction learning objective (Radford et al., 2019; Brown et al., 2020), there is a paradigm shift from discriminative and classification-based AIs to generative assistants (Zhou & Ding, 2024). This stage encompasses pre-trained models and large language models and is currently ongoing.
- **Stage 3: Artificial General Intelligence (AGI).** The AGI period has not yet arrived. AGI will be smarter than humans and continuously learn to become more proficient in any task. The learning paradigm of AGI should be independent and self-developed, meaning fully autonomous learning without human intervention. At this stage, there will be unexpected risks and uncontrollable factors as AGI's abilities increase. Therefore, governance and regulation are essential, motivating super-alignment research (Burns et al., 2023).

2.2 The Current Stage of AI

Overall, current AI, especially LLMs, still resides between ABI and AGI, making it challenging to pinpoint the exact stage. To quantify AI's abilities and performance on tasks, Morris et al. (2024) proposed levels of AGI to outline different stages of AGI in comparison to human performance. As shown in Table 1, there are six levels, ranging from no AI (Level 0) to superhuman AI (Level 5), which outperforms 100% of humans. The remaining four levels, each skilled in any task, are shown as follows:

- Level 1: Represents an emerging level, somewhat better than an unskilled human.
- Level 2: Competent level, reaching at least the 50th percentile of skilled adults.
- Level 3: Expert level, reaching at least the 90th percentile of skilled adults.
- Level 4: Virtuoso level, reaching at least the 99th percentile of skilled adults.

Based on this categorization, current LLM-based AIs like ChatGPT (OpenAI, 2023), Llama (AI@Meta, 2024) and Gemini (Reid et al., 2024) belong to emerging AGI (i.e., Level 1), which is equal to or somewhat better than an unskilled human across a wide range of non-physical tasks. In addition to performance comparisons with humans, AGI should also encompass preliminary metacognitive tasks (Wang & Zhao, 2023; Didolkar et al., 2024), such as learning new skills (Lake & Baroni, 2023).

Table 1: Based on the "Levels of AGI" proposed by Morris et al. (2024), we introduce a new dimension, "Broad," for SGI, positioned between "Narrow" and "General." SGI encompasses three stages, reflecting the number of skills at the expert level and performance on general tasks. This represents a leveled, matrixed approach to classifying systems on the path to AGI, based on the depth (performance) and breadth (generality) of capabilities. The placement of example systems within this matrix is approximate. The red cells in the table represent stages and levels related to SGI, which also outline the proposed path in this paper toward Expert AGI from Emerging AGI. The blue cells represent the beginning of SGI, respectively. We categorize the status of Levels 1 and 2 within broad AI as **Intermediate State**, which, while valuable (like Siri and Alexa in narrow tasks), struggles to produce high value.

Performance (rows) x Generality (columns)	Narrow clearly scoped task or set of tasks	Broad diverse and complex set of tasks across multiple domains	General wide range of non- physical tasks, including metacognitive tasks like learning new skills
Level 0: No AI	Narrow Non-AI calculator software; com- piler	Broad Non-AI	General Non-AI human-in-the-loop com- puting, e.g., Amazon Me- chanical Turk
Level 1: Emerging equal to or somewhat bet- ter than an unskilled hu- man	Emerging Narrow AI GOFAI (Boden, 2014); simple rule-based systems, e.g., SHRDLU (Winograd, 1971)	Intermediate state	Emerging AGI ChatGPT (OpenAI, 2023), Bard (Anil et al., 2023), Llama 2 (Touvron et al., 2023), Gemini (Pichai & Hassabis, 2023)
Level 2: Competent at least 50th percentile of skilled adults	Competent Narrow AI toxicity detectors such as Jigsaw (Das et al., 2022); Smart Speakers such as Siri (Apple), Alexa (Ama- zon), or Google Assistant (Google); VQA systems such as PaLI (Chen et al., 2023a); Watson (IBM); SOTA LLMs for a subset of tasks (e.g., short essay writing, simple coding)	Intermediate state	Competent AGI not yet achieved
Level 3: Expert at least 90th percentile of skilled adults	Expert Narrow AI spelling & grammar check- ers such as Grammarly (Grammarly, 2023); gener- ative image models such as Imagen (Saharia et al., 2022) or Dall-E 2 (Ramesh et al., 2022)	Specialized Generalists Intelligence (SGI) Stage 1: Emerging SGI e.g., MedPrompt (Nori et al., 2023),MedGem- ini (Saab et al., 2024) Stage 2: Competent SGI not yet achieved Stage 3: Expert SGI not yet achieved	Expert AGI not yet achieved
Level 4: Virtuoso at least 99th percentile of skilled adults	Virtuoso Narrow AI Deep Blue (Campbell et al., 2002a), AlphaGo (Silver et al., 2016, 2017b)	Virtuoso AGI not yet achieved	
Level 5: Superhuman outperforms 100% of hu- mans	Superhuman Narrow AI AlphaFold (Jumper et al., 2021b; Varadi et al., 2021), AlphaZero (Silver et al., 2018), StockFish (Stock- fish, 2023)	Artificial Superintellige	nce (ASI) not yet achieved

2.3 Definition, Capabilities and Stages of SGI

This section defines Specialized Generalist AI (SGI) and delineates its developmental stages, categorized by the number of specialized abilities depicted in Figure 1.

Definition of SGI. SGI builds upon advanced LLMs (i.e., emerging AGI, expectedly endowing it with capabilities that surpass those of over 90% of human experts in specialized domains. Unlike domain-specific ANI, SGI exhibits enhanced general capabilities while retaining deep expertise in specific tasks relative to emerging AGI. The development of SGI spans two dimensions: the acquisition of a broad range of expert-level specialized abilities, and the enhancement of general capabilities across diverse textual tasks. The first dimension involves advancing from Level 3 to Level 5 AGI, leveraging emerging AGI technologies across as many tasks as possible. The second dimension focuses on the continuous improvement of general capabilities in AGI on any task. Through targeted skill optimization, it's expected to surpass the general Scaling Law.

Capabilities of SGI. Specifically, in the development of SGI systems, we anticipate that these systems will exhibit the following three core capabilities:

- Task Streaming Learning Ability: SGI systems should possess cross-domain, long-term, and continuous learning capacities (Lake & Baroni, 2023; Wang et al., 2023b; Qi et al., 2024a). This would enable them to handle an infinite number of tasks, flexibly iterating and generalizing from new task learnings in a task flow context. This capability not only underscores the broad applicability of SGI systems but also their potential for rapid autonomous learning.
- Autonomous Discovery Capability: SGI systems should be able to autonomously uncover new knowledge and identify novel tasks. They should also develop a comprehensive self-assessment and metrics system to ensure the continuous emergence of new knowledge and discoveries, driving sustained progress in science and technology (Volk et al., 2023; Boiko et al., 2023). This capability significantly enhances the innovative and autonomous exploration capacities of SGI systems.
- Value-Aligned Optimization Ability: SGI systems should be capable of establishing a task goal system aligned with human values (Yuan et al., 2022). This alignment would enable them to integrate more closely with the real physical environment and better serve the genuine needs of human society. Cultivating this capability not only improves the practical applicability of SGI systems but also augments their positive contributions to human social development.

Stages of SGI. Drawing from the "Levels of AGI" described by Morris et al. (2024), we delineate the stages of SGI based on the breadth of expert-level specialized tasks and depth of general task capabilities.

- **Stage 1: Emerging SGI.** At this initial stage, SGI achieves at least 90th percentile of skilled adults in one specific domain while maintaining general abilities across a wide range of non-physical tasks, comparable to or slightly better than those of an unskilled human. Recent works (Saab et al., 2024; Yang et al., 2024b) in biomedicine based on LLMs are approaching this stage, although their expert-level abilities still require more comprehensive evaluation.
- **Stage 2: Competent SGI.** Here, SGI demonstrates competency in approximately 20% of typical tasks and domains encountered in everyday life and work. Inspired by the Pareto Principle (80/20 rule) (Dunford et al., 2014), mastering 20% of skills across all domains enables handling nearly 80% of typical scenarios. At this stage, SGI's capabilities are at least on par with the median skill level of skilled adults across a broad spectrum of tasks.
- **Stage 3: Expert SGI.** At this advanced stage, SGI closely approaches the capabilities of Expert AGI, proficiently handling about 90% of tasks worldwide and ranking in the 90th percentile among skilled adults in these areas. Concurrently, SGI's general abilities fall between the 50th and 90th percentiles of skilled adults in a variety of non-physical tasks.
- **Stage 4: Expert AGI.** In this final stage, SGI transitions to Expert AGI, reaching proficiency that matches or exceeds the 90th percentile of skilled adults across a wide range of non-physical tasks.

Relationship between Capabilities and Stages of SGI. As intelligent systems progress from the emerging SGI stage to the expert AGI stage, their three key capabilities exhibit a spiral-like enhancement ⁵: continuous

⁵https://en.wikipedia.org/wiki/Spiral

task learning ability, autonomous knowledge discovery ability, and value alignment optimization capability. In the emerging SGI stage, systems focus on a specific domain and, through continuous task learning, achieve expert-level proficiency while maintaining a basic level of general capability. Upon entering the proficient SGI stage, the system's autonomous discovery ability is enhanced, enabling it to master 20% of the key skills necessary to handle 80% of common tasks, demonstrating a broader capacity for generalization. Progressing to the expert SGI stage, the system's task learning and adaptation capabilities are significantly improved, allowing it to competently handle 90% of tasks. Simultaneously, its autonomous knowledge discovery ability makes substantial progress, enabling it to independently explore and uncover new insights without relying excessively on existing human knowledge supervision. Ultimately, upon reaching the expert AGI stage, the system's key capabilities reach a top-tier level. Not only can it handle over 90% of non-skill-based tasks, but it also exhibits exceptional performance in autonomous discovery and value alignment, aligning closely with human society. In summary, the continuous enhancement of these three key capabilities is a significant hallmark of the intelligent system's evolution from emerging to expert stages, as they mutually reinforce and collectively drive the system towards higher levels of intelligence.

Current specialized LLMs Nori et al. (2023); Saab et al. (2024) are close to Stage 1, although further efforts are still required to fully reach this stage. The subsequent stages have not yet been achieved and require additional exploration, which is also influenced by the enhancement of general abilities. Overall, SGI represents a critical pathway toward AGI, offering more pragmatic objectives of feasibility from the standpoint of practical applications. SGI also serves as a bridge between emerging LLM-based intelligence and AGI. Therefore, LLMs form a crucial backbone for achieving SGI and will be the focus of future research, as detailed in § 4.

3 Why Specialized Generalist?

Takeaway Message

While advanced LLMs excel in specific benchmarks, they often struggle with nuanced reasoning and adaptability in varied contexts. Specialized models may achieve high alignment with human instructions but frequently at the expense of creativity and innovation. Given the same resources, specialized generalists offers a more efficient pathway toward achieving AGI, characterized by lower costs and increased speed compared to traditional "Scaling Laws".

3.1 Generalists Are Not Sufficiently General

Advanced Large Language Models (LLMs) such as GPT-4, Claude-3, and Llama-3 have already surpassed unskilled human performance across various benchmarks. For instance, the latest version of GPT-4 Omni⁶, achieved an average score of 88.7 on the MMLU (Hendrycks et al., 2020), a mixed collection of high school and undergraduate-level questions across various subjects, while the average score of domain experts is 89.7. In the case of GPQA (Rein et al., 2023), a challenging dataset composed of graduate-level questions, Claude 3.5 Sonnet ⁷ scored an average of 67.2, which is higher than the average score of 65 achieved by domain expert PhDs. LLMs perform exceptionally well, often surpassing human experts based on benchmarks.

However, the lack of real reasoning ability in LLMs cannot be overlooked despite their general capabilities (Berglund et al., 2023; Huang et al., 2023a; Valmeekam et al., 2023; Stechly et al., 2023). Despite their capabilities, LLMs still often fail to perform as well as an average unskilled human in many cases, even making unexpected commonsense mistakes (Berglund et al., 2023; Wang et al., 2024c). There is now a debate that the auto-regression learning paradigm offers only a superficial understanding of the world. Recent research also indicates that the neural network responsible for generating and analyzing language in the human brain does not govern formal reasoning, suggesting that reasoning does not necessarily require language as a medium (Fedorenko et al., 2024). Moreover, due to the limited knowledge embedded in language relative to the vast common sense knowledge available in the multimodal real-world (LeCun, 2022; Feng et al., 2024), language models fall short as text-based world simulators (Wang et al., 2024c). Typical LLMs-based emerging AGI possess preliminary generality but are still far from achieving Expert AGI. They are not yet stable enough in their current general state when faced with little disturbed tasks (Chen et al., 2024a; Zhang et al., 2024d; Hong et al., 2024). These issues, likely constrained by current data, algorithms, and even architecture, remains an area of ongoing exploration.

⁶https://openai.com/index/hello-gpt-40/

⁷https://www.anthropic.com/news/claude-3-5-sonnet

Therefore, LLMs are not sufficiently general, as there is quite a gap between LLMs and the human experts. Rather than solely striving for Expert AGI in any task, it is now essential to explore models that specialize in at least one expert-level domain while retaining their generality across multiple domains.

3.2 Specialists Lack Uncertainty in Innovations

Alignment methods such as supervised fine-tuning and preference learning, including techniques like Reinforcement Learning from Human Feedback (RLHF) (Schulman et al., 2017; Ouyang et al., 2022) and Direct Preference Optimization (DPO) (Rafailov et al., 2024), enhance the adherence of base LLMs to human values and improve their responsiveness to instructions. However, high levels of alignment are not always beneficial. Recent studies indicate that diversity and creativity in LLMs diminish following alignment (Franceschelli & Musolesi, 2023; Mohammadi, 2024). For example, self-consistency (Wang et al., 2022) is an effective method to ensemble LLMs' results, where uncertainty in answers is crucial. However, the effectiveness of self-consistency decreases in highly aligned models (Tian et al., 2023; Fierro et al., 2024; Xiong et al., 2023). This suggests that LLMs tend to conform to human intentions present in the instruction datasets, while their ability to generalize to out-of-domain contexts appears to be impaired.

In fact, uncertainty (Gawlikowski et al., 2023; Kong et al., 2023) is crucial for innovations such as scientific discovery (Park et al., 2023), where previous studies have focused on enhancing uncertainty in LLMs' explorations to generate novel hypotheses (Zhang et al., 2021; Qi et al., 2023). High uncertainty in LLMs can foster the production of more diverse candidates (Boiko et al., 2023; Romera-Paredes et al., 2024), among which the ground truth is more likely to be found. From this perspective, fusing generalization in specialists is indispensable, a subject that is gradually being studied in fields such as coding (Zhu et al., 2024), medicine (Zhang et al., 2024g), and chemistry (Zhang et al., 2024c). Yet, there remains a significant gap in achieving a trade-off between specialization and generalization, and in validating the effectiveness of specialized generalists. Furthermore, we must not overlook the importance of generalists while developing specialized LLMs in target domains.

4 Conceptual Framework

In previous sections, we have outlined what Specialized Generalist Intelligence (SGI) is and why it is necessary. As mentioned in § 2.3, we believe SGI should possess three core capabilities. To achieve these capabilities, we propose a conceptual framework based on the dual-process theory of Systems 1 and 2. This framework includes three layers and four key components designed to integrate the abilities of specialists and generalists in applications, summarizing their contributions to the development of specialized generalists. We provide preliminary background on Systems 1 and 2 in § 4.1. Subsequently, we introduce: Layer 1 in § 4.2 to enhance foundational abilities in generality and specialty, including the enhancement of System 2 capabilities in § 4.2.2 and System 1 capabilities in § 4.2.1; Layer 2 in § 4.3 to implement collaborative fusion between Systems 1 and 2; Layer 3 in § 4.4 to achieve interactive self-evolving, including systematic continual task learning.

4.1 Preliminary: History of System 1 and System 2 in AI

When confronted with a problem, the human brain can operate in one of two ways: quickly and intuitively, or slowly and deliberately. These two processing methods are referred to as System 1 and System 2, or, as Nobel Prize-winning psychologist Daniel Kahneman describes them, "Fast and Slow Thinking" (Daniel, 2017). System 1 operates quickly and intuitively, making it well-suited for simple and repetitive tasks. In contrast, System 2 functions in a slow and deliberate manner, tailored for complex problem-solving. There has been a long history of attempts to integrate this dual-process theory into AI systems, as depicted in Figure 2.

Prior to the advent of LLMs, most AI models were characterized by shallow perception and pattern recognition, but lacked capabilities in high-level reasoning, planning, and generalization (Tran et al., 2021; Goyal & Bengio, 2022). Drawing inspiration from the "Fast and Slow Thinking" paradigm, researchers have developed a range of models and frameworks integrating System 1 and 2 abilities tailored to different application scenarios, including reasoning tasks (Hua & Zhang, 2022; Nye et al., 2021), visual question answering (Liu et al., 2022; Ma et al., 2023), lifelong learning (Pham et al., 2021), reinforcement learning (Gulati et al., 2021), among others. With the advancement of deep learning technologies, the integration of System 1 and System 2 continues to evolve. During the initial phase of deep learning, machine learning models (Posner, 2020) and shallow neural networks (Anthony et al., 2017; Ding et al., 2019) were designed primarily for straightforward classification and regression tasks, aligning well with the characteristics of System 1. Concurrently, representation learning,



Figure 2: This image presents the features of Systems 1 and 2 in human cognition, and illustrates their progression from machine learning and deep learning to LLMs in artificial intelligence, emphasizing their evolutionary journey and applications over time.

exemplified by models like BERT and GPT, also serves as a typical embodiment of System 1 within pre-trained language models (Lugosch et al., 2020; Nye et al., 2021). System 2 primarily involves symbolic (Nye et al., 2021; Wu et al., 2023) and logical computation (Chen et al., 2019; Ding et al., 2019; Hua & Zhang, 2022; Ozturkler et al., 2022), wherein search algorithms such as Monte Carlo methods (Anthony et al., 2017; Gulati et al., 2021), Tree Search (Yao et al., 2023) and Graph Neural Networks (Lugosch et al., 2020; Liu et al., 2022) also function as System 2 models. Moreover, by incorporating structural bias via the GFlowNet frameworks (Bengio et al., 2023; Hu et al., 2023), the system can more effectively support the reasoning, design, and optimization processes of System 2, which, in turn, further strengthens the causal properties of System 2.

In the era of large language models, LLMs exhibiting emergent abilities have the potential to handle complex reasoning tasks beyond mere pattern recognition, embodying the characteristics of System 2 (Hagendorff et al., 2023). Recent observations and research indicate that LLMs such as ChatGPT and GPT-4, endowed with robust emergent abilities, possess the capability to be classified as System 2 in specific tasks. Lin et al. (2023) introduced SwiftSage for multi-step reasoning tasks, wherein a fine-tuned T5 model, obtained through imitation learning, is considered as System 1 for simpler steps, and prompting-based GPT-4 is employed as System 2 for more complex steps, as determined by heuristic rules. Some studies also classify LLMs as System 2, while smaller models are categorized as System 1 (Qi et al., 2024a; Zhang et al., 2024e,f). On the other hand, LLMs equipped with specialized reasoning strategies, including Chain-of-Thought (Wei et al., 2022), Tree-of-Thought (Yao et al., 2023), and Algorithm of Thought (Sel et al., 2023), and enhanced with self-reflection (Shinn et al., 2023) or debugging capabilities (Chen et al., 2023b), demonstrate the ability to solve complex tasks. Overall, the shortcomings of LLMs in System 1 and System 2 in LLMs remains an area of ongoing exploration. We will explore this topic further in subsequent sections.

4.2 Layer 1: Foundational Abilities

4.2.1 Component 1: System 1 Capabilities Enhancement

Takeaway Message

System 1, built upon a world knowledge base, should continually be augmented with highly abstracted rules derived from System 2. Through repetitive experiences of System 2 reasoning, these rules can be transformed into intuitive System 1 abilities, which, in turn, can enhance System 2 capabilities.



Figure 3: The three layers and four key components of our proposed theoretical framework for building specialized generalists from a System 1 and System 2 fusion perspective include the development of both systems (① and ②), their collaboration (③), and the self-evolving of dual-system (④). The x-axis represents the two systems, trending more towards System 2 as slow, rational thinking increases. The y-axis represents potential collaborations involving internal representations and external behaviors among the systems, with human readability improving as collaborations shift from representations to behaviors.

A well-developed System 2 can stably produce superior answers for given problems, yet it incurs substantial costs during inference and reasoning (Kahneman, 2003; Evans & Stanovich, 2013). In human cognition, prolonged exercise of System 2 reasoning abilities leads to the abstraction of rules, which then evolve into intuitive responses (Fitts & Posner, 1967; Logan, 1988). This intuitive ability is evident among experts in specific fields and tasks. Therefore, the inherent growth of capabilities in System 1 will naturally arise from the long-term interactive feedback and consolidation provided by System 2.

When we regard LLMs as (weak or approximate) System 2 entities, numerous studies focus on distilling knowledge or rules from larger models into smaller ones (Zhu et al., 2023b; Cai et al., 2023; Zhu et al., 2023a; Fu et al., 2023). This process, known as imitation learning or behavior cloning (Torabi et al., 2018; Shao et al., 2024a), can be optimized through best-of-N (BoN) (Gao et al., 2023) or rejected sampling (Liu et al., 2023a) techniques. Subsequently, the System 1 models derived in this way are closely aligned with System 2 models, thereby enhancing their collaborative and problem-solving capabilities. However, as the capabilities of System 2 models increase, there remains a need for further exploration to stably extract knowledge.

Ultimately, deriving System 1 models from System 2 models is crucial within the fusion paradigm of Systems 1 and 2. Fundamentally, System 1 models are highly specialized derivations of System 2 models, designed for specific skills or tasks. System 1 excels in processing these tasks and exhibit greater stability and efficiency than System 2. Furthermore, this emergence can also enhance the flexibility of cooperation between systems.

4.2.2 Component 2: System 2 Capabilities Enhancement

Takeaway Message

System 2 capability is essential for acquiring expert-level skills in specific domains and is crucial for achieving compositional generalization. The scaling of iterative search, combined with self-feedback in the output space, represents a promising approach to enhance System 2 capabilities.

Current Large Language Models such as ChatGPT and GPT-4 have demonstrated substantial potential in fulfilling System 2 functions, particularly in emergent capabilities such as reasoning and multi-hop planning (Wei et al., 2022; Yao et al., 2023). These models exhibit human-like intuitive behavior and largely eliminate reasoning biases (Hagendorff et al., 2023). However, these models are conditionally categorized as System 2, as their capabilities are not yet stable and require further development.

Let's examine prior Expert ANIs like AlphaGo and AlphaZero (Silver et al., 2017a), where the key factor in their success was scaling search. Scaling search for next token predictions in LLMs represents a highly promising direction for enhancing System 2 abilities, going beyond traditional "Scaling Laws" in parameters (Kaplan et al., 2020) or training data (Sorscher et al., 2022). Previously introduced prompt engineering methods (Sahoo et al., 2024) are relatively superficial approaches to achieving this goal. Moreover, massive sampling and rewarding of next tokens, terminals, or steps can also be used to augment search capabilities. In fact, all these search methods and prompts are designed to enhance the working memory of LLMs (Bubeck et al., 2023; Gong et al., 2024), fostering more deliberate and slow thinking. Recently, there has been a trend (Zhang et al., 2024a; Tian et al., 2024; Brandfonbrener et al., 2024; Zhang et al., 2024b) to augment LLMs with search algorithms like Monte Carlo Tree Search (Świechowski et al., 2023) and Q* (McIntosh et al., 2023). However, these efforts primarily focus on math or coding tasks that possess ground truths. The implementation of scaling search in open-ended generation (Chi et al., 2024) remains largely unexplored. Additionally, researchers are investigating the integration of formal logic, such as neuro-symbolic systems (Trinh et al., 2024), to facilitate more meticulous, logic-based decisions. However, this approach still faces significant challenges in terms of flexibility and universality. Moreover, budget-aware scaling must also be considered (Wang et al., 2024a). Furthermore, GFlowNet (Bengio et al., 2023; Hu et al., 2023) can further reinforce structural priors through implicit search behaviors, effectively boosting diversity. However, these frameworks are still subject to limitations in efficiency and stability.

Overall, enhancing System 2 abilities is crucial for developing specialized generalists capable of achieving expert-level performance in targeted domains. Optimal methods for this enhancement still require further investigation. Among these, scaling search emerges as a practical and promising approach worth exploring.

4.3 Layer 2: Collaborative Fusion

4.3.1 Component 3: System 1 and 2 Collaborations

Takeaway Message

Collaborations between Systems 1 and 2 can strike a balance between effective information processing and high-quality decision-making. These collaborations also exist within each individual system. This balance further enhances adaptation to new environments and improves resource allocations.

Once System 1 and System 2 models are established, the next crucial step involves leveraging their respective strengths to address incoming tasks. Mirroring human cognition, System 1 initially excels at solving given problems, while System 2 corrects biases as needed (Kahneman et al., 1977). These basic collaborations, although fundamental, present challenges in dynamically scheduling System 1 and System 2 interactions in real-world environments (Stanovich & West, 2000; Evans, 2003).

Regarding LLMs, the internal working mechanisms within these models remain largely unknown, particularly the specific functionalities activated in transformer-like circuits (Elhage et al., 2021; Olsson et al., 2022). Therefore, managing or controlling collaborations within these black-box LLMs is challenging. Collaborations at the representation level between models are rarely explored; however, research on relative representations (Moschella et al., 2023) and representation alignment (Sucholutsky et al., 2023) may offer potential methods for enhancing internal collaborations. On the other hand, related research primarily focuses on external collaborations mainly with language behaviors, like model routing (Shnitzer et al., 2023; Ding et al., 2024a), cascade (Dohan et al., 2022; Yue et al., 2023a) or selection (Zhao et al., 2023) based on priors regarding candidates or model uncertainty (Xiong et al., 2023; Shinn et al., 2023), primarily within LLM-based agents (Wang et al., 2023a). More detailed investigations into collaborations involve models' decoding processes like token predictions or step generations (Zhang et al., 2024e) besides of above sample-level. These are explored in techniques such as speculative decoding (Leviathan et al., 2023), contrastive decoding (Li et al., 2022; O'Brien & Lewis, 2023), or proxy tuning (Mitchell et al., 2023; Liu et al., 2024a) within collaborative frameworks between large and small language models. Overall, numerous studies have addressed planning and decoding

in LLMs. However, future research inspired by human cognitive processes or alternative scheduling methods for System 1 and System 2 remains a promising area of exploration. Particularly, the step-level collaborations between the two systems during the generation of free-form responses warrant further investigation.

Broadly speaking, the principle "More is different" applies well in the human brain and complex systems design (Anderson, 1972), which merge collaborative intelligence. Systems 1 and 2 should not be confined to a single model but should be expanded to include multiple and even massive models. Therefore, collaborations occur not only between Systems 1 and 2 but also within the internal models of each system. These represent complex collaborative behaviors that are still under exploration in the era of LLMs.

4.4 Layer 3: Interactive Self-Evolving

4.4.1 Component 4: Self-Evolving of Dual-System

Takeaway Message

Systems 1 and 2 can evolve through dual-system interactions and self-evaluations on dynamic, unseen tasks. Moreover, the dual-system can also achieve evolution through interactions with the physical world by conducting automatic discoveries using virtual simulations and external tools.

The interaction between Systems 1 and 2 is dynamic and continually evolves in response to a changing environment and emerging tasks and challenges. This ongoing adaptation necessitates continuous learning and development of both systems (Stanovich & West, 2000; Buss, 2019).

Unlike previous studies that integrate the concepts of Systems 1 and 2 within continual learning frameworks (Pham et al., 2021; Arani et al., 2022; Wang et al., 2023c), this component focuses on addressing the unique continual learning challenges faced by each model. It aims to perpetually enhance the capabilities of both System 1 and System 2 models, thus improving their combined efficiency and advancing their applications. While Systems 1 and 2 are considered within the context of LLMs, established techniques to combat "catastrophic forgetting" (Kirkpatrick et al., 2017; De Lange et al., 2021) are still relevant for achieving lifelong learning goals. However, a new challenge within the dual-process framework is ensuring consistent alignment for prolonged collaboration between the two systems, including both behavior (Gupta et al., 2024) and representation (Sucholutsky et al., 2023). This alignment is analogous to aligning LLMs with human intentions, values, and the principles of being helpful, honest, and harmless (3H) (Bai et al., 2022; Wang et al., 2023d), aiming for seamless integration between the systems. Recent studies investigate updating knowledge in models through modular approaches that mimic the dynamic memory mechanisms in the brain (Wang et al., 2023b). In terms of Systems 1 and 2, it is crucial to maintain stability in one system while updating the other, ensuring consistency throughout the process (Qi et al., 2024a). One strategy involves modular knowledge storage and management (Qi et al., 2024d). In addition to interactive continual learning from environment, it is also crucial for systems to self-evolve (Jiang et al., 2023; Yuan et al., 2024; Tao et al., 2024) using synthetic data generated by the LLMs themselves within virtual tools (Bauer et al., 2024; Liu et al., 2024b).

In conclusion, defining the alignment between the dual processes is challenging but crucial for continual task learning. For specialized generalists, maintaining the ability to learn continually and process new tasks is essential. During this period, modular knowledge transfer between Systems 1 and 2 is vital to ensure the entire system operates in a closed loop (Stanovich & West, 2000; Floreano & Mattiussi, 2008).

5 Challenges and Future Directions

5.1 Building Models Collaboration Laws.

The performance improvement of current LLMs heavily relies on "Scaling Laws" (Kaplan et al., 2020; Hoffmann et al., 2022), where an increase in parameters and training data generally leads to predictable more powerful performance. However, there is considerable debate regarding the upper limits of Scaling Laws due to the potential for exhausting available web data (Villalobos et al., 2024) and limited computation resource. How can we build upon scaling laws by models or systems interactions? It is crucial to implement the fusion of massive specialized and general models, which may provide new avenues to further enhance the effectiveness of scaling laws at the model level. The "Scaling laws" arising from the coordination among intelligent agents are being explored (Qian et al., 2024; Wang et al., 2024b; Li et al., 2024), demonstrating promising directions for further scaling based on traditional scaling laws. Based on interactive media, these collaborations

can occur during various periods, such as at the parameter level through model merging (Wortsman et al., 2022; Stoica et al., 2023; Goddard et al., 2024; Akiba et al., 2024), at the representation level through representation engineering (Sucholutsky et al., 2023; Zou et al., 2023), at the logit level through inference-time alignment (Huang et al., 2024; Wan et al., 2024a; Ding et al., 2024b; Zhang et al., 2024e), and at the token (Jin et al., 2024) or language level (Guo et al., 2024), which are the most common scenarios in various multi-agent collaborations. Recent work show the collaborations between large and small models seem to be predicatble, further explorations on multiple models collaborations can be studied (Zhang et al., 2024e), which is a potential way to augment current LLMs and to achieve more powerful specialized generalists beyond "Scaling Law".

5.2 Building Data Mixture Laws.

Beyond the development of specialized generalists through model-level collaborations, data plays a crucial role in achieving specialized generalist capabilities. Various data-centric methods (Zha et al., 2023) can be effectively utilized to reach this goal. For instance, high-quality and diverse domain-specific pre-training data (Penedo et al., 2024; Liu et al., 2024b; Longpre et al., 2023) or instructions (Ding et al., 2023; Liu et al., 2023b) are essential for acquiring domain knowledge. Simultaneously, studying the mixture of domain data is important, as it helps balance speciality and generality (Zhang et al., 2024g). While there appear to be underlying principles in data mixture (Xie et al., 2024; Ye et al., 2024), these still require further practical analysis and experimentation. In summary, inspired by data pruning laws (Sorscher et al., 2022), data mixture could also be established as a predictive law to guide our efforts in developing specialized generalist AI.

5.3 New Evaluation and Benchmarks.

As LLM capabilities improve, traditional benchmarks (Hendrycks et al., 2020; Cobbe et al., 2021; Hendrycks et al., 2021; Chen et al., 2021) are nearing saturation, making it increasingly difficult to discern differences between models. In response, researchers are developing more challenging benchmarks that use human experts as the standard, such as GPQA (Rein et al., 2023) and AGIEval (Zhong et al., 2023), or employ real-world use cases for testing, such as SWE (Jimenez et al., 2024) and BigCodeBench (Zhuo et al., 2024). These benchmarks encompass a variety of specific domain problems. However, the diversity and quantity of these problems are still insufficient to fully validate the specialization abilities within domains. Additionally, benchmarks designed to assess the impact of generalization on specialization are under exploration. Such benchmarks are crucial for validating the effectiveness of models and data mixture methods in balancing speciality and generality.

5.4 New Architecture from Scratch.

Recent work has demonstrated that designs inspired by human-like networks can provide superior systematic generalization (Lake & Baroni, 2023). Due to the opaque nature of LLMs, replicating human cognitive processes remains unfeasible. Beyond traditional transformers (including various implementations and linear variants like Mamba (Gu & Dao, 2023)) and autoregressive learning, exploring new architectures is crucial. Such architectures include GFlowNet (Lahlou et al., 2023; Jain et al., 2023; Bengio et al., 2023) and KAN (Liu et al., 2024c; Bozorgasl & Chen, 2024), which hold significant potential for enhanced reasoning and controllability. Recent work has also begun to combine these models to create hybrid architectures (Lieber et al., 2024; Qi et al., 2024c). Additionally, designing new architectures inspired by human cognitive systems like Systems 1 and 2 is a promising avenue. However, further efforts are necessary to determine whether these architectures can scale or surpass LLMs in innovative ways. In addition, some research has explored new architectural designs from the perspective of decoupling memory and reasoning (Chen et al., 2022; Qi et al., 2024a; Qiao et al., 2024). These works have focused on designing externally pluggable memory components (Qi et al., 2024a,b) and modular architectural learning strategies. However, there is limited research on constructing more compositional model designs that can simultaneously enable efficient memory storage and sustainable learning capabilities.

5.5 Applications in Multi-modal and Embodied AI

As indicated in the discussion on enhancing System 2 abilities, increasing the intelligence density of supervised signals is a promising trend. This approach has proven useful in multi-modal pre-training (Chen et al., 2024b; Ma et al., 2022b; Bai et al., 2023), as multi-modal data can provide more fine-grained and diverse information than text alone (Ma et al., 2022a). Moreover, token alignment and pre-training between across-modality information may be the key to improve the intelligence density of supervision signals and further realizing the

emergence of foundational models and AGI. In this regard, it is necessary to extend research and applications of specialized generalists to multi-modal and embodied AI. Embodied intelligence (Gupta et al., 2021) is an another effective means to achieve general and specialized integration, and is also the most likely path to building AGI that understands the physical world. However, embodied intelligence is not just the application of Multi-modal LLMs plus robots, whereas requires the timely self-evolution according to the feedback from the physical world. In a multi-modal physical world, AI systems should possess the potential to learn from the environment and receive feedback that facilitates self-evolution.

5.6 Applications in Scientific Discovery

Scientific discovery in biomedicine (Qi et al., 2023), chemistry (M. Bran et al., 2024), physics (Ma et al., 2024), mathematics (Romera-Paredes et al., 2024), and related domains drives advancements in human societal development. Recent work (Park et al., 2023) indicates that research innovation has slowed due to the emergence of massive literature within specific domains, resulting in an "information cocoon." (Sunstein, 2006) Traditional AI-based scientific tools designed for specific tasks, such as linear classifiers and graph neural networks, lack the generality needed to break out of these information cocoons. LLM-based scientific tools (AI4Science & Quantum, 2023; Zhang et al., 2024h; Liang et al., 2024) introduce new possibilities for navigating vast networks of literature by internalizing all knowledge from the corpus available on the internet. These tools open up a new pathway that simulates real-world researchers (M. Bran et al., 2024), encompassing the uncertainty inherent in exploring unseen fields. However, due to the limited generality of LLMs in specific domains, specializing in particular areas has become a popular method to enhance specificity (Yue et al., 2023b; Zhu et al., 2023a; Bolton et al., 2024). Balancing specificity and generality in scientific research fields is expected to unlock further potential (Zhang et al., 2024c, g). The challenge of building specialized generalists for scientific discovery continues to be a critical area of exploration.

5.7 Risks and Controllability.

Although Specialized Generalist Intelligence is not as advanced as AGI, there are still risks associated with generating harmful content (Weidinger et al., 2022, 2021; Anil et al., 2024). The factuality of generated content must also be monitored, with particular attention to the study of hallucination phenomena (Xu et al., 2024; Huang et al., 2023b; Jiang et al., 2024). For expert-level applications such as clinical surgery (Zhang et al., 2024g) and financial analysis (Kim et al., 2024), it is crucial that the outputs of models are highly controllable (Li et al., 2023; Sun et al., 2024). Relatively speaking, the boundaries of specialized generalists are clearer than those of generalists, which makes them more controllable. This controllability depends on the specialization of System 1 and the fault tolerance of System 2. Compared to solely pursuing performance improvement or security enhancement, we need to adopt a more balanced strategy that comprehensively considers and coordinates their simultaneous development. This approach ensures that performance and security enhancements do not compromise each other. Moreover, it adheres to an AI-45° law, which further drives the sustainable and healthy development of the entire system.

6 Conclusion

In this paper, we formally propose the concept of Specialized Generalist AI (SGI), a pivotal milestone in transitioning from current LLMs to Expert AGI. The purpose of SGI is to effectively enhance specialized capabilities while simultaneously developing general capabilities in a balanced manner. This strategic approach allows for rapid advancement into high-value areas and fosters the creation of an efficient data feedback loop, thereby accelerating the development of AGI. SGI is delineated into three stages, determined by the number of specialized skills and the level of general performance. We introduce a conceptual framework for implementing SGI, viewed through the lens of Systems 1 and 2, and detail the four key components of this framework. Finally, we outline the challenges and potential directions for furthering SGI development.

Contributions

The contributions of this paper are outlined as follows:

- Bowen initially proposed the concept of Specialized Generalist AI (SGI) and the technical roadmap from the perspective of Systems 1 and 2.
- Kaiyan was primarily responsible for leading the discussion, refining the levels of SGI, and writing the initial draft. Together with Biqing, Kaiyan refined the initial concept and framework, which includes the three layers and four components necessary for achieving SGI.
- All authors participated actively in discussions and the polishing of the paper.

Acknowledgements

Professor Bowen Zhou has delivered numerous presentations on Specialized Generalists and Systems 1 and 2 over the past few years at various forums and talks. We thank everyone for their valuable feedback and discussions on these topics with experts and scholars from different domains, including Daniel Kahneman, Andrew Chi-Chih Yao, Thomas J Sargent, and others. We also express our gratitude to Ning Ding, Zhiyuan Ma, Xuekai Zhu, and Ermo Hua in Center for Collaborative & Conversational Intelligence at Tsinghua University for their helpful advice on writing and content. This work is supported by the National Science and Technology Major Project (2023ZD0121403).

References

- Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia Leoni Aleman, Diogo Almeida, Janko Altenschmidt, Sam Altman, Shyamal Anadkat, et al. Gpt-4 technical report. <u>arXiv preprint</u> arXiv:2303.08774, 2023.
- Microsoft Research AI4Science and Microsoft Azure Quantum. The impact of large language models on scientific discovery: a preliminary study using gpt-4. arXiv preprint arXiv:2311.07361, 2023.
- AI@Meta. Llama 3 model card. 2024. URL https://github.com/meta-llama/llama3/blob/ main/MODEL_CARD.md.
- Takuya Akiba, Makoto Shing, Yujin Tang, Qi Sun, and David Ha. Evolutionary optimization of model merging recipes. arXiv preprint arXiv:2403.13187, 2024.
- Amazon. Amazon Alexa. URL https://alexa.amazon.com/. accessed on October 20, 2023.
- Philip W Anderson. More is different: Broken symmetry and the nature of the hierarchical structure of science. Science, 177(4047):393–396, 1972.
- Cem Anil, Esin Durmus, Mrinank Sharma, Joe Benton, Sandipan Kundu, Joshua Batson, Nina Rimsky, Meg Tong, Jesse Mu, Daniel Ford, et al. Many-shot jailbreaking. Anthropic, April, 2024.
- Rohan Anil, Andrew M. Dai, Orhan Firat, and et al. PaLM 2 Technical Report. <u>CoRR</u>, abs/2305.10403, 2023. doi: 10.48550/arXiv.2305.10403. URL https://arxiv.org/abs/2305.10403.
- Thomas Anthony, Zheng Tian, and David Barber. Thinking fast and slow with deep learning and tree search. Advances in neural information processing systems, 30, 2017.
- Anthropic. Claude. 2024. URL https://claude.ai/.
- Apple. Siri. URL https://www.apple.com/siri/. accessed on October 20, 2023.
- Elahe Arani, Fahad Sarfraz, and Bahram Zonooz. Learning fast, learning slow: A general continual learning method based on complementary learning system. arXiv preprint arXiv:2201.12604, 2022.
- Jinze Bai, Shuai Bai, Shusheng Yang, Shijie Wang, Sinan Tan, Peng Wang, Junyang Lin, Chang Zhou, and Jingren Zhou. Qwen-vl: A frontier large vision-language model with versatile abilities. <u>arXiv preprint</u> arXiv:2308.12966, 2023.
- Yuntao Bai, Andy Jones, Kamal Ndousse, Amanda Askell, Anna Chen, Nova DasSarma, Dawn Drain, Stanislav Fort, Deep Ganguli, Tom Henighan, et al. Training a helpful and harmless assistant with reinforcement learning from human feedback. arXiv preprint arXiv:2204.05862, 2022.
- André Bauer, Simon Trapp, Michael Stenger, Robert Leppich, Samuel Kounev, Mark Leznik, Kyle Chard, and Ian Foster. Comprehensive exploration of synthetic data generation: A survey. <u>arXiv preprint</u> arXiv:2401.02524, 2024.
- Yoshua Bengio, Salem Lahlou, Tristan Deleu, Edward J Hu, Mo Tiwari, and Emmanuel Bengio. Gflownet foundations. Journal of Machine Learning Research, 24(210):1–55, 2023.
- Lukas Berglund, Meg Tong, Max Kaufmann, Mikita Balesni, Asa Cooper Stickland, Tomasz Korbak, and Owain Evans. The reversal curse: Llms trained on" a is b" fail to learn" b is a". <u>arXiv preprint</u> arXiv:2309.12288, 2023.
- Margaret A. Boden. GOFAI, pp. 89-107. Cambridge University Press, 2014.
- Daniil A Boiko, Robert MacKnight, Ben Kline, and Gabe Gomes. Autonomous chemical research with large language models. Nature, 624(7992):570–578, 2023.
- Elliot Bolton, Abhinav Venigalla, Michihiro Yasunaga, David Hall, Betty Xiong, Tony Lee, Roxana Daneshjou, Jonathan Frankle, Percy Liang, Michael Carbin, et al. Biomedlm: A 2.7 b parameter language model trained on biomedical text. arXiv preprint arXiv:2403.18421, 2024.
- Zavareh Bozorgasl and Hao Chen. Wav-kan: Wavelet kolmogorov-arnold networks. arXiv preprint arXiv:2405.12832, 2024.

- David Brandfonbrener, Simon Henniger, Sibi Raja, Tarun Prasad, Chloe Loughridge, Federico Cassano, Sabrina Ruixin Hu, Jianang Yang, William E. Byrd, Robert Zinkov, and Nada Amin. Vermcts: Synthesizing multi-step programs using a verifier, a large language model, and tree search, 2024.
- Tom B. Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel M. Ziegler, Jeffrey Wu, Clemens Winter, Christopher Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. Language models are few-shot learners, 2020.
- Sébastien Bubeck, Varun Chandrasekaran, Ronen Eldan, Johannes Gehrke, Eric Horvitz, Ece Kamar, Peter Lee, Yin Tat Lee, Yuanzhi Li, Scott Lundberg, Harsha Nori, Hamid Palangi, Marco Tulio Ribeiro, and Yi Zhang. Sparks of artificial general intelligence: Early experiments with gpt-4, 2023.
- Collin Burns, Pavel Izmailov, Jan Hendrik Kirchner, Bowen Baker, Leo Gao, Leopold Aschenbrenner, Yining Chen, Adrien Ecoffet, Manas Joglekar, Jan Leike, et al. Weak-to-strong generalization: Eliciting strong capabilities with weak supervision. arXiv preprint arXiv:2312.09390, 2023.
- David Buss. Evolutionary psychology: The new science of the mind. Routledge, 2019.
- Tianle Cai, Xuezhi Wang, Tengyu Ma, Xinyun Chen, and Denny Zhou. Large language models as tool makers. arXiv preprint arXiv:2305.17126, 2023.
- Murray Campbell, A. Joseph Hoane, and Feng-hsiung Hsu. Deep Blue. <u>Artif. Intell.</u>, 134(1–2):57–83, jan 2002a. ISSN 0004-3702. doi: 10.1016/S0004-3702(01)00129-1. URL https://doi.org/10.1016/S0004-3702(01)00129-1.
- Murray Campbell, A Joseph Hoane Jr, and Feng-hsiung Hsu. Deep blue. <u>Artificial intelligence</u>, 134(1-2): 57–83, 2002b.
- Di Chen, Yiwei Bai, Wenting Zhao, Sebastian Ament, John M Gregoire, and Carla P Gomes. Deep reasoning networks: Thinking fast and slow. arXiv preprint arXiv:1906.00855, 2019.
- Mark Chen, Jerry Tworek, Heewoo Jun, Qiming Yuan, Henrique Ponde de Oliveira Pinto, Jared Kaplan, Harri Edwards, Yuri Burda, Nicholas Joseph, Greg Brockman, et al. Evaluating large language models trained on code. arXiv preprint arXiv:2107.03374, 2021.
- Xi Chen, Xiao Wang, Soravit Changpinyo, and et al. PaLI: A Jointly-Scaled Multilingual Language-Image Model. <u>CoRR</u>, abs/2209.06794, 2023a. doi: 10.48550/arXiv.2209.06794. URL https://arxiv.org/ abs/2209.06794.
- Xiang Chen, Lei Li, Ningyu Zhang, Xiaozhuan Liang, Shumin Deng, Chuanqi Tan, Fei Huang, Luo Si, and Huajun Chen. Decoupling knowledge from memorization: Retrieval-augmented prompt learning. <u>Advances</u> in Neural Information Processing Systems, 35:23908–23922, 2022.
- Xinyun Chen, Maxwell Lin, Nathanael Schärli, and Denny Zhou. Teaching large language models to self-debug. arXiv preprint arXiv:2304.05128, 2023b.
- Xinyun Chen, Ryan A Chi, Xuezhi Wang, and Denny Zhou. Premise order matters in reasoning with large language models. arXiv preprint arXiv:2402.08939, 2024a.
- Zhe Chen, Jiannan Wu, Wenhai Wang, Weijie Su, Guo Chen, Sen Xing, Muyan Zhong, Qinglong Zhang, Xizhou Zhu, Lewei Lu, Bin Li, Ping Luo, Tong Lu, Yu Qiao, and Jifeng Dai. Internvl: Scaling up vision foundation models and aligning for generic visual-linguistic tasks. In <u>Proceedings of the IEEE/CVF</u> Conference on Computer Vision and Pattern Recognition (CVPR), pp. 24185–24198, June 2024b.
- Yizhou Chi, Kevin Yang, and Dan Klein. Thoughtsculpt: Reasoning with intermediate revision and search. arXiv preprint arXiv:2404.05966, 2024.
- Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, et al. Training verifiers to solve math word problems. arXiv preprint arXiv:2110.14168, 2021.

Kahneman Daniel. Thinking, fast and slow. 2017.

- Millon Madhur Das, Punyajoy Saha, and Mithun Das. Which One is More Toxic? Findings from Jigsaw Rate Severity of Toxic Comments. <u>CoRR</u>, abs/2206.13284, 2022. doi: 10.48550/arXiv.2206.13284. URL https://arxiv.org/abs/2206.13284.
- Matthias De Lange, Rahaf Aljundi, Marc Masana, Sarah Parisot, Xu Jia, Aleš Leonardis, Gregory Slabaugh, and Tinne Tuytelaars. A continual learning survey: Defying forgetting in classification tasks. <u>IEEE</u> transactions on pattern analysis and machine intelligence, 44(7):3366–3385, 2021.
- Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding, 2019.
- Aniket Didolkar, Anirudh Goyal, Nan Rosemary Ke, Siyuan Guo, Michal Valko, Timothy Lillicrap, Danilo Rezende, Yoshua Bengio, Michael Mozer, and Sanjeev Arora. Metacognitive capabilities of llms: An exploration in mathematical problem solving. arXiv preprint arXiv:2405.12205, 2024.
- Dujian Ding, Ankur Mallick, Chi Wang, Robert Sim, Subhabrata Mukherjee, Victor Ruhle, Laks VS Lakshmanan, and Ahmed Hassan Awadallah. Hybrid llm: Cost-efficient and quality-aware query routing. <u>arXiv</u> preprint arXiv:2404.14618, 2024a.
- Ming Ding, Chang Zhou, Qibin Chen, Hongxia Yang, and Jie Tang. Cognitive graph for multi-hop reading comprehension at scale. arXiv preprint arXiv:1905.05460, 2019.
- Ning Ding, Yulin Chen, Bokai Xu, Yujia Qin, Zhi Zheng, Shengding Hu, Zhiyuan Liu, Maosong Sun, and Bowen Zhou. Enhancing chat language models by scaling high-quality instructional conversations. arXiv preprint arXiv:2305.14233, 2023.
- Ning Ding, Yulin Chen, Ganqu Cui, Xingtai Lv, Ruobing Xie, Bowen Zhou, Zhiyuan Liu, and Maosong Sun. Mastering text, code and math simultaneously via fusing highly specialized language models. <u>arXiv</u> preprint arXiv:2403.08281, 2024b.
- David Dohan, Winnie Xu, Aitor Lewkowycz, Jacob Austin, David Bieber, Raphael Gontijo Lopes, Yuhuai Wu, Henryk Michalewski, Rif A Saurous, Jascha Sohl-Dickstein, et al. Language model cascades. <u>arXiv</u> preprint arXiv:2207.10342, 2022.

Rosie Dunford, Quanrong Su, and Ekraj Tamang. The pareto principle. 2014.

- Nelson Elhage, Neel Nanda, Catherine Olsson, Tom Henighan, Nicholas Joseph, Ben Mann, Amanda Askell, Yuntao Bai, Anna Chen, Tom Conerly, et al. A mathematical framework for transformer circuits. <u>Transformer</u> Circuits Thread, 1:1, 2021.
- Jonathan St BT Evans. In two minds: dual-process accounts of reasoning. <u>Trends in cognitive sciences</u>, 7(10): 454–459, 2003.
- Jonathan St BT Evans and Keith E Stanovich. Dual-process theories of higher cognition: Advancing the debate. Perspectives on psychological science, 8(3):223–241, 2013.
- Evelina Fedorenko, Steven T Piantadosi, and Edward AF Gibson. Language is primarily a tool for communication rather than thought. Nature, 630(8017):575–586, 2024.
- Tao Feng, Chuanyang Jin, Jingyu Liu, Kunlun Zhu, Haoqin Tu, Zirui Cheng, Guanyu Lin, and Jiaxuan You. How far are we from agi, 2024.
- Constanza Fierro, Jiaang Li, and Anders Søgaard. Does instruction tuning make llms more consistent? arXiv preprint arXiv:2404.15206, 2024.
- Paul M Fitts and Michael I Posner. Human performance. 1967.
- Dario Floreano and Claudio Mattiussi. <u>Bio-inspired artificial intelligence: theories, methods, and technologies</u>. MIT press, 2008.
- Giorgio Franceschelli and Mirco Musolesi. On the creativity of large language models. <u>arXiv preprint</u> arXiv:2304.00008, 2023.

- Yao Fu, Hao Peng, Litu Ou, Ashish Sabharwal, and Tushar Khot. Specializing smaller language models towards multi-step reasoning. arXiv preprint arXiv:2301.12726, 2023.
- Leo Gao, John Schulman, and Jacob Hilton. Scaling laws for reward model overoptimization. In <u>International</u> Conference on Machine Learning, pp. 10835–10866. PMLR, 2023.
- Jakob Gawlikowski, Cedrique Rovile Njieutcheu Tassi, Mohsin Ali, Jongseok Lee, Matthias Humt, Jianxiang Feng, Anna Kruspe, Rudolph Triebel, Peter Jung, Ribana Roscher, et al. A survey of uncertainty in deep neural networks. Artificial Intelligence Review, 56(Suppl 1):1513–1589, 2023.
- Charles Goddard, Shamane Siriwardhana, Malikeh Ehghaghi, Luke Meyers, Vlad Karpukhin, Brian Benedict, Mark McQuade, and Jacob Solawetz. Arcee's mergekit: A toolkit for merging large language models. <u>arXiv</u> preprint arXiv:2403.13257, 2024.
- Dongyu Gong, Xingchen Wan, and Dingmin Wang. Working memory capacity of chatgpt: An empirical study. In Proceedings of the AAAI Conference on Artificial Intelligence, volume 38, pp. 10048–10056, 2024.
- Google. Google Assistant, your own personal Google. URL https://assistant.google.com/. accessed on October 20, 2023.
- Anirudh Goyal and Yoshua Bengio. Inductive biases for deep learning of higher-level cognition. <u>Proceedings</u> of the Royal Society A, 478(2266):20210068, 2022.
- Grammarly, 2023. URL https://www.grammarly.com/.
- Albert Gu and Tri Dao. Mamba: Linear-time sequence modeling with selective state spaces. <u>arXiv preprint</u> arXiv:2312.00752, 2023.
- Aditya Gulati, Sarthak Soni, and Shrisha Rao. Interleaving fast and slow decision making. In <u>2021 IEEE</u> International Conference on Robotics and Automation (ICRA), pp. 1535–1541. IEEE, 2021.
- Taicheng Guo, Xiuying Chen, Yaqi Wang, Ruidi Chang, Shichao Pei, Nitesh V Chawla, Olaf Wiest, and Xiangliang Zhang. Large language model based multi-agents: A survey of progress and challenges. <u>arXiv</u> preprint arXiv:2402.01680, 2024.
- Agrim Gupta, Silvio Savarese, Surya Ganguli, and Li Fei-Fei. Embodied intelligence via learning and evolution. Nature communications, 12(1):5721, 2021.
- Dhawal Gupta, Yash Chandak, Scott Jordan, Philip S Thomas, and Bruno C da Silva. Behavior alignment via reward function optimization. Advances in Neural Information Processing Systems, 36, 2024.
- Michael Haenlein and Andreas Kaplan. A brief history of artificial intelligence: On the past, present, and future of artificial intelligence. California management review, 61(4):5–14, 2019.
- Thilo Hagendorff, Sarah Fabi, and Michal Kosinski. Human-like intuitive behavior and reasoning biases emerged in large language models but disappeared in chatgpt. <u>Nature Computational Science</u>, pp. 1–6, 2023.
- Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In Proceedings of the IEEE conference on computer vision and pattern recognition, pp. 770–778, 2016.
- Dan Hendrycks, Collin Burns, Steven Basart, Andy Zou, Mantas Mazeika, Dawn Song, and Jacob Steinhardt. Measuring massive multitask language understanding. arXiv preprint arXiv:2009.03300, 2020.
- Dan Hendrycks, Collin Burns, Saurav Kadavath, Akul Arora, Steven Basart, Eric Tang, Dawn Song, and Jacob Steinhardt. Measuring mathematical problem solving with the math dataset. <u>arXiv preprint</u> arXiv:2103.03874, 2021.
- Jordan Hoffmann, Sebastian Borgeaud, Arthur Mensch, Elena Buchatskaya, Trevor Cai, Eliza Rutherford, Diego de Las Casas, Lisa Anne Hendricks, Johannes Welbl, Aidan Clark, et al. Training compute-optimal large language models. arXiv preprint arXiv:2203.15556, 2022.
- Pengfei Hong, Deepanway Ghosal, Navonil Majumder, Somak Aditya, Rada Mihalcea, and Soujanya Poria. Stuck in the quicksand of numeracy, far from agi summit: Evaluating llms' mathematical competency through ontology-guided perturbations. arXiv preprint arXiv:2401.09395, 2024.

- Edward J Hu, Nikolay Malkin, Moksh Jain, Katie Everett, Alexandros Graikos, and Yoshua Bengio. Gflownetem for learning compositional latent variable models. In <u>Proceedings of the 40th International Conference</u> on Machine Learning, pp. 13528–13549, 2023.
- Wenyue Hua and Yongfeng Zhang. System 1+ system 2= better world: Neural-symbolic chain of logic reasoning. In Findings of the Association for Computational Linguistics: EMNLP 2022, pp. 601–612, 2022.
- James Y Huang, Sailik Sengupta, Daniele Bonadiman, Yi-an Lai, Arshit Gupta, Nikolaos Pappas, Saab Mansour, Katrin Kirchoff, and Dan Roth. Deal: Decoding-time alignment for large language models. <u>arXiv</u> preprint arXiv:2402.06147, 2024.
- Jie Huang, Xinyun Chen, Swaroop Mishra, Huaixiu Steven Zheng, Adams Wei Yu, Xinying Song, and Denny Zhou. Large language models cannot self-correct reasoning yet. arXiv preprint arXiv:2310.01798, 2023a.
- Lei Huang, Weijiang Yu, Weitao Ma, Weihong Zhong, Zhangyin Feng, Haotian Wang, Qianglong Chen, Weihua Peng, Xiaocheng Feng, Bing Qin, et al. A survey on hallucination in large language models: Principles, taxonomy, challenges, and open questions. arXiv preprint arXiv:2311.05232, 2023b.
- IBM. IBM Watson. URL https://www.ibm.com/watson. accessed on October 20, 2023.
- IBM. IBM Watson Wikipedia, the free encyclopedia. http://en.wikipedia.org/w/index.php?title=IBM%20Watson&oldid=1230359460, 2015. [Online; accessed 23-June-2024].
- IBM. The path to broad ai, 2016.
- Moksh Jain, Tristan Deleu, Jason Hartford, Cheng-Hao Liu, Alex Hernandez-Garcia, and Yoshua Bengio. Gflownets for ai-driven scientific discovery. Digital Discovery, 2(3):557–577, 2023.
- Che Jiang, Biqing Qi, Xiangyu Hong, Dayuan Fu, Yang Cheng, Fandong Meng, Mo Yu, Bowen Zhou, and Jie Zhou. On large language models' hallucination with regard to known facts. <u>arXiv preprint</u> arXiv:2403.20009, 2024.
- Shuyang Jiang, Yuhao Wang, and Yu Wang. Selfevolve: A code evolution framework via large language models. arXiv preprint arXiv:2306.02907, 2023.
- Carlos E Jimenez, John Yang, Alexander Wettig, Shunyu Yao, Kexin Pei, Ofir Press, and Karthik R Narasimhan. SWE-bench: Can language models resolve real-world github issues? In <u>The Twelfth International</u> <u>Conference on Learning Representations</u>, 2024. URL https://openreview.net/forum?id= VTF8yNQM66.
- Lifeng Jin, Baolin Peng, Linfeng Song, Haitao Mi, Ye Tian, and Dong Yu. Collaborative decoding of critical tokens for boosting factuality of large language models. arXiv preprint arXiv:2402.17982, 2024.
- John Jumper, Richard Evans, Alexander Pritzel, Tim Green, Michael Figurnov, Olaf Ronneberger, Kathryn Tunyasuvunakool, Russ Bates, Augustin Žídek, Anna Potapenko, et al. Highly accurate protein structure prediction with alphafold. Nature, 596(7873):583–589, 2021a.
- John Jumper, Richard Evans, Alexander Pritzel, Tim Green, Michael Figurnov, Olaf Ronneberger, Kathryn Tunyasuvunakool, Russ Bates, Augustin Žídek, Anna Potapenko, Alex Bridgland, Clemens Meyer, Simon A. A. Kohl, Andrew J. Ballard, Andrew Cowie, Bernardino Romera-Paredes, Stanislav Nikolov, Rishub Jain, Jonas Adler, Trevor Back, Stig Petersen, David Reiman, Ellen Clancy, Michal Zielinski, Martin Steinegger, Michalina Pacholska, Tamas Berghammer, Sebastian Bodenstein, David Silver, Oriol Vinyals, Andrew W. Senior, Koray Kavukcuoglu, Pushmeet Kohli, and Demis Hassabis. Highly Accurate Protein Structure Prediction with AlphaFold. Nature, 596:583–589, 2021b. doi: 10.1038/s41586-021-03819-2.
- D Kahneman. A perspective on judgment and choice: mapping bounded rationality. american pychologist, 58 (9), 697, 2003.
- Daniel Kahneman, Amos Tversky, et al. <u>Intuituve Prediction: Biases and Corrective Procedures</u>. Decision Research, Perceptronics, 1977.
- Jared Kaplan, Sam McCandlish, Tom Henighan, Tom B Brown, Benjamin Chess, Rewon Child, Scott Gray, Alec Radford, Jeffrey Wu, and Dario Amodei. Scaling laws for neural language models. <u>arXiv preprint</u> arXiv:2001.08361, 2020.

- Alex Kim, Maximilian Muhn, and Valeri V Nikolaev. Financial statement analysis with large language models. Chicago Booth Research Paper Forthcoming, Fama-Miller Working Paper, 2024.
- James Kirkpatrick, Razvan Pascanu, Neil Rabinowitz, Joel Veness, Guillaume Desjardins, Andrei A Rusu, Kieran Milan, John Quan, Tiago Ramalho, Agnieszka Grabska-Barwinska, et al. Overcoming catastrophic forgetting in neural networks. <u>Proceedings of the national academy of sciences</u>, 114(13):3521–3526, 2017.
- Lingkai Kong, Harshavardhan Kamarthi, Peng Chen, B Aditya Prakash, and Chao Zhang. Uncertainty quantification in deep learning. In Proceedings of the 29th ACM SIGKDD Conference on Knowledge Discovery and Data Mining, pp. 5809–5810, 2023.
- Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. Imagenet classification with deep convolutional neural networks. Advances in neural information processing systems, 25, 2012.
- Salem Lahlou, Tristan Deleu, Pablo Lemos, Dinghuai Zhang, Alexandra Volokhova, Alex Hernández-Garcia, Léna Néhale Ezzine, Yoshua Bengio, and Nikolay Malkin. A theory of continuous generative flow networks. In International Conference on Machine Learning, pp. 18269–18300. PMLR, 2023.
- Brenden M Lake and Marco Baroni. Human-like systematic generalization through a meta-learning neural network. Nature, 623(7985):115–121, 2023.
- Yann LeCun. A path towards autonomous machine intelligence version 0.9. 2, 2022-06-27. Open Review, 62 (1), 2022.
- Yaniv Leviathan, Matan Kalman, and Yossi Matias. Fast inference from transformers via speculative decoding. In International Conference on Machine Learning, pp. 19274–19286. PMLR, 2023.
- Bo Li, Peng Qi, Bo Liu, Shuai Di, Jingen Liu, Jiquan Pei, Jinfeng Yi, and Bowen Zhou. Trustworthy ai: From principles to practices. <u>ACM Comput. Surv.</u>, 55(9), jan 2023. ISSN 0360-0300. doi: 10.1145/3555803. URL https://doi.org/10.1145/3555803.
- Junyou Li, Qin Zhang, Yangbin Yu, Qiang Fu, and Deheng Ye. More agents is all you need. <u>arXiv preprint</u> arXiv:2402.05120, 2024.
- Xiang Lisa Li, Ari Holtzman, Daniel Fried, Percy Liang, Jason Eisner, Tatsunori Hashimoto, Luke Zettlemoyer, and Mike Lewis. Contrastive decoding: Open-ended text generation as optimization. <u>arXiv preprint</u> arXiv:2210.15097, 2022.
- Weixin Liang, Yaohui Zhang, Zhengxuan Wu, Haley Lepp, Wenlong Ji, Xuandong Zhao, Hancheng Cao, Sheng Liu, Siyu He, Zhi Huang, et al. Mapping the increasing use of llms in scientific papers. <u>arXiv</u> preprint arXiv:2404.01268, 2024.
- Opher Lieber, Barak Lenz, Hofit Bata, Gal Cohen, Jhonathan Osin, Itay Dalmedigos, Erez Safahi, Shaked Meirom, Yonatan Belinkov, Shai Shalev-Shwartz, et al. Jamba: A hybrid transformer-mamba language model. arXiv preprint arXiv:2403.19887, 2024.
- Hunter Lightman, Vineet Kosaraju, Yura Burda, Harri Edwards, Bowen Baker, Teddy Lee, Jan Leike, John Schulman, Ilya Sutskever, and Karl Cobbe. Let's verify step by step. <u>arXiv preprint arXiv:2305.20050</u>, 2023.
- Bill Yuchen Lin, Yicheng Fu, Karina Yang, Prithviraj Ammanabrolu, Faeze Brahman, Shiyu Huang, Chandra Bhagavatula, Yejin Choi, and Xiang Ren. Swiftsage: A generative agent with fast and slow thinking for complex interactive tasks. arXiv preprint arXiv:2305.17390, 2023.
- Zhouhan Lin, Minwei Feng, Cicero Nogueira dos Santos, Mo Yu, Bing Xiang, Bowen Zhou, and Yoshua Bengio. A structured self-attentive sentence embedding. arXiv preprint arXiv:1703.03130, 2017.
- Alisa Liu, Xiaochuang Han, Yizhong Wang, Yulia Tsvetkov, Yejin Choi, and Noah A Smith. Tuning language models by proxy. arXiv preprint arXiv:2401.08565, 2024a.
- Luping Liu, Meiling Wang, Xiaohai He, Linbo Qing, and Honggang Chen. Fact-based visual question answering via dual-process system. Knowledge-Based Systems, 237:107650, 2022.

- Ruibo Liu, Jerry Wei, Fangyu Liu, Chenglei Si, Yanzhe Zhang, Jinmeng Rao, Steven Zheng, Daiyi Peng, Diyi Yang, Denny Zhou, et al. Best practices and lessons learned on synthetic data for language models. <u>arXiv</u> preprint arXiv:2404.07503, 2024b.
- Tianqi Liu, Yao Zhao, Rishabh Joshi, Misha Khalman, Mohammad Saleh, Peter J Liu, and Jialu Liu. Statistical rejection sampling improves preference optimization. arXiv preprint arXiv:2309.06657, 2023a.
- Wei Liu, Weihao Zeng, Keqing He, Yong Jiang, and Junxian He. What makes good data for alignment? a comprehensive study of automatic data selection in instruction tuning. <u>arXiv preprint arXiv:2312.15685</u>, 2023b.
- Ziming Liu, Yixuan Wang, Sachin Vaidya, Fabian Ruehle, James Halverson, Marin Soljačić, Thomas Y Hou, and Max Tegmark. Kan: Kolmogorov-arnold networks. arXiv preprint arXiv:2404.19756, 2024c.
- Gordon D Logan. Toward an instance theory of automatization. Psychological review, 95(4):492, 1988.
- Shayne Longpre, Gregory Yauney, Emily Reif, Katherine Lee, Adam Roberts, Barret Zoph, Denny Zhou, Jason Wei, Kevin Robinson, David Mimno, et al. A pretrainer's guide to training data: Measuring the effects of data age, domain coverage, quality, & toxicity. arXiv preprint arXiv:2305.13169, 2023.
- Loren Lugosch, Derek Nowrouzezahrai, and Brett H Meyer. Surprisal-triggered conditional computation with neural networks. arXiv preprint arXiv:2006.01659, 2020.
- Andres M. Bran, Sam Cox, Oliver Schilter, Carlo Baldassari, Andrew D White, and Philippe Schwaller. Augmenting large language models with chemistry tools. Nature Machine Intelligence, pp. 1–11, 2024.
- Pingchuan Ma, Tsun-Hsuan Wang, Minghao Guo, Zhiqing Sun, Joshua B Tenenbaum, Daniela Rus, Chuang Gan, and Wojciech Matusik. Llm and simulation as bilevel optimizers: A new paradigm to advance physical scientific discovery. arXiv preprint arXiv:2405.09783, 2024.
- Zhiyuan Ma, Jianjun Li, Guohui Li, and Yongjing Cheng. Unitranser: A unified transformer semantic representation framework for multimodal task-oriented dialog system. In <u>Proceedings of the 60th Annual</u> Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), pp. 103–114, 2022a.
- Zhiyuan Ma, Jianjun Li, Guohui Li, and Kaiyan Huang. Cmal: A novel cross-modal associative learning framework for vision-language pre-training. In <u>Proceedings of the 30th ACM International Conference on</u> Multimedia, pp. 4515–4524, 2022b.
- Zhiyuan Ma, Zhihuan Yu, Jianjun Li, and Guohui Li. Hybridprompt: bridging language models and human priors in prompt tuning for visual question answering. In <u>Proceedings of the AAAI Conference on Artificial</u> Intelligence, volume 37, pp. 13371–13379, 2023.
- John McCarthy, Marvin L Minsky, Nathaniel Rochester, and Claude E Shannon. A proposal for the dartmouth summer research project on artificial intelligence, august 31, 1955. AI magazine, 27(4):12–12, 2006.
- Timothy R McIntosh, Teo Susnjak, Tong Liu, Paul Watters, and Malka N Halgamuge. From google gemini to openai q*(q-star): A survey of reshaping the generative artificial intelligence (ai) research landscape. <u>arXiv</u> preprint arXiv:2312.10868, 2023.
- Eric Mitchell, Rafael Rafailov, Archit Sharma, Chelsea Finn, and Christopher D Manning. An emulator for fine-tuning large language models using small language models. arXiv preprint arXiv:2310.12962, 2023.
- Behnam Mohammadi. Creativity has left the chat: The price of debiasing language models. <u>arXiv preprint</u> arXiv:2406.05587, 2024.
- Meredith Ringel Morris, Jascha Sohl-Dickstein, Noah Fiedel, Tris Warkentin, Allan Dafoe, Aleksandra Faust, Clement Farabet, and Shane Legg. Position: Levels of AGI for operationalizing progress on the path to AGI. In Forty-first International Conference on Machine Learning, 2024. URL https://openreview.net/forum?id=0ofzEysK2D.
- Luca Moschella, Valentino Maiorca, Marco Fumero, Antonio Norelli, Francesco Locatello, and Emanuele Rodolà. Relative representations enable zero-shot latent space communication, 2023. URL https://arxiv.org/abs/2209.15430.

- Stephen Muggleton. Alan turing and the development of artificial intelligence. <u>AI communications</u>, 27(1): 3–10, 2014.
- Harsha Nori, Yin Tat Lee, Sheng Zhang, Dean Carignan, Richard Edgar, Nicolo Fusi, Nicholas King, Jonathan Larson, Yuanzhi Li, Weishung Liu, et al. Can generalist foundation models outcompete special-purpose tuning? case study in medicine. arXiv preprint arXiv:2311.16452, 2023.
- Maxwell Nye, Michael Tessler, Josh Tenenbaum, and Brenden M Lake. Improving coherence and consistency in neural sequence models with dual-system, neuro-symbolic reasoning. <u>Advances in Neural Information</u> Processing Systems, 34:25192–25204, 2021.
- Sean O'Brien and Mike Lewis. Contrastive decoding improves reasoning in large language models. <u>arXiv</u> preprint arXiv:2309.09117, 2023.
- Catherine Olsson, Nelson Elhage, Neel Nanda, Nicholas Joseph, Nova DasSarma, Tom Henighan, Ben Mann, Amanda Askell, Yuntao Bai, Anna Chen, et al. In-context learning and induction heads. transformer circuits thread, 2022, 2022.
- OpenAI. GPT-4 Technical Report. <u>CoRR</u>, abs/2303.08774, 2023. doi: 10.48550/arXiv.2303.08774. URL https://arxiv.org/abs/2303.08774.
- Long Ouyang, Jeffrey Wu, Xu Jiang, Diogo Almeida, Carroll Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, et al. Training language models to follow instructions with human feedback. Advances in neural information processing systems, 35:27730–27744, 2022.
- Batu Ozturkler, Nikolay Malkin, Zhen Wang, and Nebojsa Jojic. Thinksum: Probabilistic reasoning over sets using large language models. arXiv preprint arXiv:2210.01293, 2022.
- Michael Park, Erin Leahey, and Russell J Funk. Papers and patents are becoming less disruptive over time. Nature, 613(7942):138–144, 2023.
- Guilherme Penedo, Hynek Kydlíček, Leandro von Werra, and Thomas Wolf. Fineweb, 2024. URL https://huggingface.co/datasets/HuggingFaceFW/fineweb.
- Matthew E. Peters, Mark Neumann, Mohit Iyyer, Matt Gardner, Christopher Clark, Kenton Lee, and Luke Zettlemoyer. Deep contextualized word representations, 2018.
- Quang Pham, Chenghao Liu, and Steven Hoi. Dualnet: Continual learning, fast and slow. <u>Advances in Neural</u> Information Processing Systems, 34:16131–16144, 2021.
- Sundar Pichai and Demis Hassabis. Introducing gemini: our largest and most capable ai model, December 2023. URL https://blog.google/technology/ai/google-gemini-ai/.
- H Posner. Robots thinking fast and slow: on dual process theory and metacognition in embodied ai. 2020.
- Biqing Qi, Kaiyan Zhang, Haoxiang Li, Kai Tian, Sihang Zeng, Zhang-Ren Chen, and Bowen Zhou. Large language models are zero shot hypothesis proposers. arXiv preprint arXiv:2311.05965, 2023.
- Biqing Qi, Xinquan Chen, Junqi Gao, Dong Li, Jianxing Liu, Ligang Wu, and Bowen Zhou. Interactive continual learning: Fast and slow thinking. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, pp. 12882–12892, 2024a.
- Biqing Qi, Junqi Gao, Xingquan Chen, Dong Li, Jianxing Liu, Ligang Wu, and Bowen Zhou. Contrastive augmented graph2graph memory interaction for few shot continual learning. <u>arXiv preprint arXiv:2403.04140</u>, 2024b.
- Biqing Qi, Junqi Gao, Kaiyan Zhang, Dong Li, Jianxing Liu, Ligang Wu, and Bowen Zhou. Smr: State memory replay for long sequence modeling. arXiv preprint arXiv:2405.17534, 2024c.
- Biqing Qi, Pengfei Li, Fangyuan Li, Junqi Gao, Kaiyan Zhang, and Bowen Zhou. Online dpo: Online direct preference optimization with fast-slow chasing. arXiv preprint arXiv:2406.05534, 2024d.
- Chen Qian, Xin Cong, Cheng Yang, Weize Chen, Yusheng Su, Juyuan Xu, Zhiyuan Liu, and Maosong Sun. Communicative agents for software development. arXiv preprint arXiv:2307.07924, 2023.

- Chen Qian, Zihao Xie, Yifei Wang, Wei Liu, Yufan Dang, Zhuoyun Du, Weize Chen, Cheng Yang, Zhiyuan Liu, and Maosong Sun. Scaling large-language-model-based multi-agent collaboration. <u>arXiv preprint</u> arXiv:2406.07155, 2024.
- Yuxuan Qiao, Haodong Duan, Xinyu Fang, Junming Yang, Lin Chen, Songyang Zhang, Jiaqi Wang, Dahua Lin, and Kai Chen. Prism: A framework for decoupling and assessing the capabilities of vlms. <u>arXiv</u> preprint arXiv:2406.14544, 2024.
- Alec Radford, Karthik Narasimhan, Tim Salimans, Ilya Sutskever, et al. Improving language understanding by generative pre-training. 2018.
- Alec Radford, Jeff Wu, Rewon Child, David Luan, Dario Amodei, and Ilya Sutskever. Language models are unsupervised multitask learners. 2019. URL https://api.semanticscholar.org/CorpusID: 160025533.
- Rafael Rafailov, Archit Sharma, Eric Mitchell, Christopher D Manning, Stefano Ermon, and Chelsea Finn. Direct preference optimization: Your language model is secretly a reward model. <u>Advances in Neural</u> Information Processing Systems, 36, 2024.
- Aditya Ramesh, Prafulla Dhariwal, Alex Nichol, Casey Chu, and Mark Chen. Hierarchical Text-Conditional Image Generation with CLIP Latents. April 2022. URL https://cdn.openai.com/papers/dall-e-2.pdf.
- Machel Reid, Nikolay Savinov, Denis Teplyashin, Dmitry Lepikhin, Timothy Lillicrap, Jean-baptiste Alayrac, Radu Soricut, Angeliki Lazaridou, Orhan Firat, Julian Schrittwieser, et al. Gemini 1.5: Unlocking multimodal understanding across millions of tokens of context. arXiv preprint arXiv:2403.05530, 2024.
- David Rein, Betty Li Hou, Asa Cooper Stickland, Jackson Petty, Richard Yuanzhe Pang, Julien Dirani, Julian Michael, and Samuel R Bowman. Gpqa: A graduate-level google-proof q&a benchmark. <u>arXiv preprint</u> arXiv:2311.12022, 2023.
- Bernardino Romera-Paredes, Mohammadamin Barekatain, Alexander Novikov, Matej Balog, M Pawan Kumar, Emilien Dupont, Francisco JR Ruiz, Jordan S Ellenberg, Pengming Wang, Omar Fawzi, et al. Mathematical discoveries from program search with large language models. Nature, 625(7995):468–475, 2024.
- Olga Russakovsky, Jia Deng, Hao Su, Jonathan Krause, Sanjeev Satheesh, Sean Ma, Zhiheng Huang, Andrej Karpathy, Aditya Khosla, Michael Bernstein, et al. Imagenet large scale visual recognition challenge. International journal of computer vision, 115:211–252, 2015.
- Khaled Saab, Tao Tu, Wei-Hung Weng, Ryutaro Tanno, David Stutz, Ellery Wulczyn, Fan Zhang, Tim Strother, Chunjong Park, Elahe Vedadi, et al. Capabilities of gemini models in medicine. <u>arXiv preprint</u> arXiv:2404.18416, 2024.
- Chitwan Saharia, William Chan, Saurabh Saxena, Lala Li, Jay Whang, Emily Denton, Seyed Kamyar Seyed Ghasemipour, Burcu Karagol Ayan, S. Sara Mahdavi, Rapha Gontijo Lopes, Tim Salimans, Jonathan Ho, David J Fleet, and Mohammad Norouzi. Photorealistic Text-to-Image Diffusion Models with Deep Language Understanding. <u>CoRR</u>, abs/2205.11487, 2022. doi: 10.48550/arXiv.2205.11487. URL https://arxiv.org/abs/2205.11487.
- Pranab Sahoo, Ayush Kumar Singh, Sriparna Saha, Vinija Jain, Samrat Mondal, and Aman Chadha. A systematic survey of prompt engineering in large language models: Techniques and applications. <u>arXiv</u> preprint arXiv:2402.07927, 2024.
- John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. arXiv preprint arXiv:1707.06347, 2017.
- Bilgehan Sel, Ahmad Al-Tawaha, Vanshaj Khattar, Lu Wang, Ruoxi Jia, and Ming Jin. Algorithm of thoughts: Enhancing exploration of ideas in large language models. arXiv preprint arXiv:2308.10379, 2023.
- Chenyang Shao, Fengli Xu, Bingbing Fan, Jingtao Ding, Yuan Yuan, Meng Wang, and Yong Li. Beyond imitation: Generating human mobility from context-aware reasoning with large language models. <u>arXiv</u> preprint arXiv:2402.09836, 2024a.

- Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junxiao Song, Mingchuan Zhang, YK Li, Y Wu, and Daya Guo. Deepseekmath: Pushing the limits of mathematical reasoning in open language models. <u>arXiv</u> preprint arXiv:2402.03300, 2024b.
- Noah Shinn, Federico Cassano, Ashwin Gopinath, Karthik R Narasimhan, and Shunyu Yao. Reflexion: Language agents with verbal reinforcement learning. In <u>Thirty-seventh Conference on Neural Information</u> Processing Systems, 2023.
- Tal Shnitzer, Anthony Ou, Mírian Silva, Kate Soule, Yuekai Sun, Justin Solomon, Neil Thompson, and Mikhail Yurochkin. Large language model routing with benchmark datasets. <u>arXiv preprint arXiv:2309.15789</u>, 2023.
- David Silver, Aja Huang, Chris J. Maddison, Arthur Guez, Laurent Sifre, George van den Driessche, Julian Schrittwieser, Ioannis Antonoglou, Veda Panneershelvam, Marc Lanctot, Sander Dieleman, Dominik Grewe, John Nham, Nal Kalchbrenner, Ilya Sutskever, Timothy Lillicrap, Madeleine Leach, Koray Kavukcuoglu, Thore Graepel, and Demis Hassabis. Mastering the Game of Go with Deep Neural Networks and Tree Search. Nature, 529:484–489, 2016. doi: 10.1038/nature16961.
- David Silver, Thomas Hubert, Julian Schrittwieser, Ioannis Antonoglou, Matthew Lai, Arthur Guez, Marc Lanctot, Laurent Sifre, Dharshan Kumaran, Thore Graepel, et al. Mastering chess and shogi by self-play with a general reinforcement learning algorithm. arXiv preprint arXiv:1712.01815, 2017a.
- David Silver, Julian Schrittwieser, Karen Simonyan, Ioannis Antonoglou, Aja Huang, Arthur Guez, Thomas Hubert, Lucas Baker, Matthew Lai, Adrian Bolton, Yutian Chen, Timothy Lillicrap, Fan Hui, Laurent Sifre, George van den Driessche, Thore Graepel, and Demis Hassabis. Mastering the Game of Go Without Human Knowledge. Nature, 550:354–359, 2017b. doi: 10.1038/nature24270.
- David Silver, Thomas Hubert, Julian Schrittwieser, Ioannis Antonoglou, Matthew Lai, Arthur Guez, Marc Lanctot, Laurent Sifre, Dharshan Kumaran, Thore Graepel, Timothy Lillicrap, Karen Simonyan, and Demis Hassabis. A General Reinforcement Learning Algorithm that Masters Chess, Shogi, and Go through Self-play. <u>Science</u>, 362(6419):1140–1144, 2018. doi: 10.1126/science.aar6404. URL https://www.science.org/doi/abs/10.1126/science.aar6404.
- Ben Sorscher, Robert Geirhos, Shashank Shekhar, Surya Ganguli, and Ari Morcos. Beyond neural scaling laws: beating power law scaling via data pruning. <u>Advances in Neural Information Processing Systems</u>, 35: 19523–19536, 2022.
- Keith E Stanovich and Richard F West. Advancing the rationality debate. <u>Behavioral and brain sciences</u>, 23 (5):701–717, 2000.
- Kaya Stechly, Matthew Marquez, and Subbarao Kambhampati. Gpt-4 doesn't know it's wrong: An analysis of iterative prompting for reasoning problems. arXiv preprint arXiv:2310.12397, 2023.
- Stockfish. Stockfish Open Source Chess Engine, 2023. URL https://stockfishchess.org/.
- George Stoica, Daniel Bolya, Jakob Bjorner, Pratik Ramesh, Taylor Hearn, and Judy Hoffman. Zipit! merging models from different tasks without training. arXiv preprint arXiv:2305.03053, 2023.
- Ilia Sucholutsky, Lukas Muttenthaler, Adrian Weller, Andi Peng, Andreea Bobu, Been Kim, Bradley C Love, Erin Grant, Jascha Achterberg, Joshua B Tenenbaum, et al. Getting aligned on representational alignment. arXiv preprint arXiv:2310.13018, 2023.
- Lichao Sun, Yue Huang, Haoran Wang, Siyuan Wu, Qihui Zhang, Chujie Gao, Yixin Huang, Wenhan Lyu, Yixuan Zhang, Xiner Li, et al. Trustllm: Trustworthiness in large language models. <u>arXiv preprint</u> arXiv:2401.05561, 2024.
- Cass R Sunstein. Infotopia: How many minds produce knowledge. Oxford University Press, 2006.
- Ilya Sutskever, Oriol Vinyals, and Quoc V Le. Sequence to sequence learning with neural networks. <u>Advances</u> in neural information processing systems, 27, 2014.
- Maciej Świechowski, Konrad Godlewski, Bartosz Sawicki, and Jacek Mańdziuk. Monte carlo tree search: A review of recent modifications and applications. Artificial Intelligence Review, 56(3):2497–2562, 2023.

- Zhengwei Tao, Ting-En Lin, Xiancai Chen, Hangyu Li, Yuchuan Wu, Yongbin Li, Zhi Jin, Fei Huang, Dacheng Tao, and Jingren Zhou. A survey on self-evolution of large language models. <u>arXiv preprint</u> arXiv:2404.14387, 2024.
- Rohan Taori, Ishaan Gulrajani, Tianyi Zhang, Yann Dubois, Xuechen Li, Carlos Guestrin, Percy Liang, and Tatsunori B. Hashimoto. Stanford alpaca: An instruction-following llama model. https://github.com/tatsu-lab/stanford_alpaca, 2023.
- Katherine Tian, Eric Mitchell, Allan Zhou, Archit Sharma, Rafael Rafailov, Huaxiu Yao, Chelsea Finn, and Christopher D Manning. Just ask for calibration: Strategies for eliciting calibrated confidence scores from language models fine-tuned with human feedback. arXiv preprint arXiv:2305.14975, 2023.
- Ye Tian, Baolin Peng, Linfeng Song, Lifeng Jin, Dian Yu, Haitao Mi, and Dong Yu. Toward self-improvement of llms via imagination, searching, and criticizing. arXiv preprint arXiv:2404.12253, 2024.
- Faraz Torabi, Garrett Warnell, and Peter Stone. Behavioral cloning from observation. arXiv preprint arXiv:1805.01954, 2018.
- Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, Dan Bikel, Lukas Blecher, Cristian Canton Ferrer, Moya Chen, Guillem Cucurull, David Esiobu, Jude Fernandes, Jeremy Fu, Wenyin Fu, Brian Fuller, Cynthia Gao, Vedanuj Goswami, Naman Goyal, Anthony Hartshorn, Saghar Hosseini, Rui Hou, Hakan Inan, Marcin Kardas, Viktor Kerkez, Madian Khabsa, Isabel Kloumann, Artem Korenev, Punit Singh Koura, Marie-Anne Lachaux, Thibaut Lavril, Jenya Lee, Diana Liskovich, Yinghai Lu, Yuning Mao, Xavier Martinet, Todor Mihaylov, Pushkar Mishra, Igor Molybog, Yixin Nie, Andrew Poulton, Jeremy Reizenstein, Rashi Rungta, Kalyan Saladi, Alan Schelten, Ruan Silva, Eric Michael Smith, Ranjan Subramanian, Xiaoqing Ellen Tan, Binh Tang, Ross Taylor, Adina Williams, Jian Xiang Kuan, Puxin Xu, Zheng Yan, Iliyan Zarov, Yuchen Zhang, Angela Fan, Melanie Kambadur, Sharan Narang, Aurelien Rodriguez, Robert Stojnic, Sergey Edunov, and Thomas Scialom. Llama 2: Open Foundation and Fine-Tuned Chat Models, 2023.
- Truyen Tran, Vuong Le, Hung Le, and Thao M Le. From deep learning to deep reasoning. In Proceedings of the 27th ACM SIGKDD Conference on Knowledge Discovery & Data Mining, pp. 4076–4077, 2021.
- Trieu H Trinh, Yuhuai Wu, Quoc V Le, He He, and Thang Luong. Solving olympiad geometry without human demonstrations. Nature, 625(7995):476–482, 2024.
- Karthik Valmeekam, Matthew Marquez, and Subbarao Kambhampati. Can large language models really improve by self-critiquing their own plans? arXiv preprint arXiv:2310.08118, 2023.
- Mihaly Varadi, Stephen Anyango, Mandar Deshpande, Sreenath Nair, Cindy Natassia, Galabina Yordanova, David Yuan, Oana Stroe, Gemma Wood, Agata Laydon, Augustin Žídek, Tim Green, Kathryn Tunyasuvunakool, Stig Petersen, John Jumper, Ellen Clancy, Richard Green, Ankur Vora, Mira Lutfi, Michael Figurnov, Andrew Cowie, Nicole Hobbs, Pushmeet Kohli, Gerard Kleywegt, Ewan Birney, Demis Hassabis, and Sameer Velankar. AlphaFold Protein Structure Database: Massively Expanding the Structural Coverage of Protein-Sequence Space with High-Accuracy Models. <u>Nucleic Acids Research</u>, 50:D439–D444, 11 2021. ISSN 0305-1048. doi: 10.1093/nar/gkab1061. URL https://doi.org/10.1093/nar/gkab1061.
- Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. <u>Advances in neural information processing systems</u>, 30, 2017.
- Pablo Villalobos, Anson Ho, Jaime Sevilla, Tamay Besiroglu, Lennart Heim, and Marius Hobbhahn. Position: Will we run out of data? limits of llm scaling based on human-generated data. In <u>Forty-first International</u> Conference on Machine Learning, 2024.
- Amanda A Volk, Robert W Epps, Daniel T Yonemoto, Benjamin S Masters, Felix N Castellano, Kristofer G Reyes, and Milad Abolhasani. Alphaflow: autonomous discovery and optimization of multi-step chemistry using a self-driven fluidic lab guided by reinforcement learning. <u>Nature Communications</u>, 14(1):1403, 2023.
- Fanqi Wan, Xinting Huang, Deng Cai, Xiaojun Quan, Wei Bi, and Shuming Shi. Knowledge fusion of large language models. arXiv preprint arXiv:2401.10491, 2024a.

- Yuxuan Wan, Wenxuan Wang, Yiliu Yang, Youliang Yuan, Jen-tse Huang, Pinjia He, Wenxiang Jiao, and Michael R Lyu. A & b== b & a: Triggering logical reasoning failures in large language models. <u>arXiv</u> preprint arXiv:2401.00757, 2024b.
- Junlin Wang, Siddhartha Jain, Dejiao Zhang, Baishakhi Ray, Varun Kumar, and Ben Athiwaratkun. Reasoning in token economies: Budget-aware evaluation of llm reasoning strategies. <u>arXiv preprint arXiv:2406.06461</u>, 2024a.
- Junlin Wang, Jue Wang, Ben Athiwaratkun, Ce Zhang, and James Zou. Mixture-of-agents enhances large language model capabilities. arXiv preprint arXiv:2406.04692, 2024b.
- Lei Wang, Chen Ma, Xueyang Feng, Zeyu Zhang, Hao Yang, Jingsen Zhang, Zhiyuan Chen, Jiakai Tang, Xu Chen, Yankai Lin, et al. A survey on large language model based autonomous agents. <u>arXiv preprint</u> arXiv:2308.11432, 2023a.
- Liyuan Wang, Xingxing Zhang, Qian Li, Mingtian Zhang, Hang Su, Jun Zhu, and Yi Zhong. Incorporating neuro-inspired adaptability for continual learning in artificial intelligence. <u>Nature Machine Intelligence</u>, 5 (12):1356–1368, 2023b.
- Liyuan Wang, Xingxing Zhang, Hang Su, and Jun Zhu. A comprehensive survey of continual learning: Theory, method and application. arXiv preprint arXiv:2302.00487, 2023c.
- Ruoyao Wang, Graham Todd, Ziang Xiao, Xingdi Yuan, Marc-Alexandre Côté, Peter Clark, and Peter Jansen. Can language models serve as text-based world simulators? arXiv preprint arXiv:2406.06485, 2024c.
- Xuezhi Wang, Jason Wei, Dale Schuurmans, Quoc Le, Ed Chi, Sharan Narang, Aakanksha Chowdhery, and Denny Zhou. Self-consistency improves chain of thought reasoning in language models. <u>arXiv preprint</u> arXiv:2203.11171, 2022.
- Yufei Wang, Wanjun Zhong, Liangyou Li, Fei Mi, Xingshan Zeng, Wenyong Huang, Lifeng Shang, Xin Jiang, and Qun Liu. Aligning large language models with human: A survey. <u>arXiv preprint arXiv:2307.12966</u>, 2023d.
- Yuqing Wang and Yun Zhao. Metacognitive prompting improves understanding in large language models. arXiv preprint arXiv:2308.05342, 2023.
- Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Fei Xia, Ed Chi, Quoc V Le, Denny Zhou, et al. Chain-of-thought prompting elicits reasoning in large language models. <u>Advances in Neural Information</u> Processing Systems, 35:24824–24837, 2022.
- Laura Weidinger, John Mellor, Maribeth Rauh, Conor Griffin, Jonathan Uesato, Po-Sen Huang, Myra Cheng, Mia Glaese, Borja Balle, Atoosa Kasirzadeh, et al. Ethical and social risks of harm from language models. arXiv preprint arXiv:2112.04359, 2021.
- Laura Weidinger, Jonathan Uesato, Maribeth Rauh, Conor Griffin, Po-Sen Huang, John Mellor, Amelia Glaese, Myra Cheng, Borja Balle, Atoosa Kasirzadeh, et al. Taxonomy of risks posed by language models. In <u>Proceedings of the 2022 ACM Conference on Fairness, Accountability, and Transparency</u>, pp. 214–229, 2022.
- Terry Winograd. Procedures as a Representation for Data in a Computer Program for Understanding Natural Language. <u>MIT AI Technical Reports</u>, 1971.
- Mitchell Wortsman, Gabriel Ilharco, Samir Ya Gadre, Rebecca Roelofs, Raphael Gontijo-Lopes, Ari S Morcos, Hongseok Namkoong, Ali Farhadi, Yair Carmon, Simon Kornblith, et al. Model soups: averaging weights of multiple fine-tuned models improves accuracy without increasing inference time. In <u>International</u> conference on machine learning, pp. 23965–23998. PMLR, 2022.
- Xiaoqian Wu, Yong-Lu Li, Jianhua Sun, and Cewu Lu. Symbol-Ilm: Leverage language models for symbolic system in visual human activity reasoning. In <u>Thirty-seventh Conference on Neural Information Processing</u> Systems, 2023.
- Sang Michael Xie, Hieu Pham, Xuanyi Dong, Nan Du, Hanxiao Liu, Yifeng Lu, Percy S Liang, Quoc V Le, Tengyu Ma, and Adams Wei Yu. Doremi: Optimizing data mixtures speeds up language model pretraining. Advances in Neural Information Processing Systems, 36, 2024.

- Miao Xiong, Zhiyuan Hu, Xinyang Lu, Yifei Li, Jie Fu, Junxian He, and Bryan Hooi. Can llms express their uncertainty? an empirical evaluation of confidence elicitation in llms. <u>arXiv preprint arXiv:2306.13063</u>, 2023.
- Can Xu, Qingfeng Sun, Kai Zheng, Xiubo Geng, Pu Zhao, Jiazhan Feng, Chongyang Tao, and Daxin Jiang. Wizardlm: Empowering large language models to follow complex instructions. <u>arXiv preprint</u> arXiv:2304.12244, 2023.
- Ziwei Xu, Sanjay Jain, and Mohan Kankanhalli. Hallucination is inevitable: An innate limitation of large language models. arXiv preprint arXiv:2401.11817, 2024.
- John Yang, Carlos E. Jimenez, Alexander Wettig, Kilian Lieret, Shunyu Yao, Karthik Narasimhan, and Ofir Press. Swe-agent: Agent-computer interfaces enable automated software engineering, 2024a.
- Lin Yang, Shawn Xu, Andrew Sellergren, Timo Kohlberger, Yuchen Zhou, Ira Ktena, Atilla Kiraly, Faruk Ahmed, Farhad Hormozdiari, Tiam Jaroensri, et al. Advancing multimodal medical capabilities of gemini. arXiv preprint arXiv:2405.03162, 2024b.
- Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak Shafran, Karthik Narasimhan, and Yuan Cao. React: Synergizing reasoning and acting in language models. arXiv preprint arXiv:2210.03629, 2022.
- Shunyu Yao, Dian Yu, Jeffrey Zhao, Izhak Shafran, Thomas L Griffiths, Yuan Cao, and Karthik Narasimhan. Tree of thoughts: Deliberate problem solving with large language models. <u>arXiv preprint arXiv:2305.10601</u>, 2023.
- Jiasheng Ye, Peiju Liu, Tianxiang Sun, Yunhua Zhou, Jun Zhan, and Xipeng Qiu. Data mixing laws: Optimizing data mixtures by predicting language modeling performance. <u>arXiv preprint arXiv:2403.16952</u>, 2024.
- Luyao Yuan, Xiaofeng Gao, Zilong Zheng, Mark Edmonds, Ying Nian Wu, Federico Rossano, Hongjing Lu, Yixin Zhu, and Song-Chun Zhu. In situ bidirectional human-robot value alignment. <u>Science robotics</u>, 7(68): eabm4183, 2022.
- Weizhe Yuan, Richard Yuanzhe Pang, Kyunghyun Cho, Sainbayar Sukhbaatar, Jing Xu, and Jason Weston. Self-rewarding language models. arXiv preprint arXiv:2401.10020, 2024.
- Murong Yue, Jie Zhao, Min Zhang, Liang Du, and Ziyu Yao. Large language model cascades with mixture of thoughts representations for cost-efficient reasoning. arXiv preprint arXiv:2310.03094, 2023a.
- Xiang Yue, Xingwei Qu, Ge Zhang, Yao Fu, Wenhao Huang, Huan Sun, Yu Su, and Wenhu Chen. Mammoth: Building math generalist models through hybrid instruction tuning. <u>arXiv preprint arXiv:2309.05653</u>, 2023b.
- Daochen Zha, Zaid Pervaiz Bhat, Kwei-Herng Lai, Fan Yang, Zhimeng Jiang, Shaochen Zhong, and Xia Hu. Data-centric artificial intelligence: A survey. arXiv preprint arXiv:2303.10158, 2023.
- Dan Zhang, Sining Zhoubian, Yisong Yue, Yuxiao Dong, and Jie Tang. Rest-mcts*: Llm self-training via process reward guided tree search. arXiv preprint arXiv:2406.03816, 2024a.
- Di Zhang, Jiatong Li, Xiaoshui Huang, Dongzhan Zhou, Yuqiang Li, and Wanli Ouyang. Accessing gpt-4 level mathematical olympiad solutions via monte carlo tree self-refine with llama-3 8b. <u>arXiv preprint</u> arXiv:2406.07394, 2024b.
- Di Zhang, Wei Liu, Qian Tan, Jingdan Chen, Hang Yan, Yuliang Yan, Jiatong Li, Weiran Huang, Xiangyu Yue, Dongzhan Zhou, et al. Chemllm: A chemical large language model. <u>arXiv preprint arXiv:2402.06852</u>, 2024c.
- Hugh Zhang, Jeff Da, Dean Lee, Vaughn Robinson, Catherine Wu, Will Song, Tiffany Zhao, Pranav Raja, Dylan Slack, Qin Lyu, et al. A careful examination of large language model performance on grade school arithmetic. arXiv preprint arXiv:2405.00332, 2024d.
- Jize Zhang, Bhavya Kailkhura, and T Yong-Jin Han. Leveraging uncertainty from deep learning for trustworthy material discovery workflows. ACS omega, 6(19):12711–12721, 2021.

- Kaiyan Zhang, Jianyu Wang, Ning Ding, Biqing Qi, Ermo Hua, Xingtai Lv, and Bowen Zhou. Fast and slow generating: An empirical study on large and small language models collaborative decoding, 2024e.
- Kaiyan Zhang, Jianyu Wang, Ermo Hua, Biqing Qi, Ning Ding, and Bowen Zhou. Cogenesis: A framework collaborating large and small language models for secure context-aware instruction following. <u>arXiv preprint</u> arXiv:2403.03129, 2024f.
- Kaiyan Zhang, Sihang Zeng, Ermo Hua, Ning Ding, Zhang-Ren Chen, Zhiyuan Ma, Haoxin Li, Ganqu Cui, Biqing Qi, Xuekai Zhu, Xingtai Lv, Jinfang Hu, Zhiyuan Liu, and Bowen Zhou. Ultramedical: Building specialized generalists in biomedicine. 2024g. URL https://api.semanticscholar. org/CorpusID:270286195.
- Qiang Zhang, Keyang Ding, Tianwen Lyv, Xinda Wang, Qingyu Yin, Yiwen Zhang, Jing Yu, Yuhao Wang, Xiaotong Li, Zhuoyi Xiang, et al. Scientific large language models: A survey on biological & chemical domains. arXiv preprint arXiv:2401.14656, 2024h.
- James Xu Zhao, Yuxi Xie, Kenji Kawaguchi, Junxian He, and Michael Qizhe Xie. Automatic model selection with large language models for reasoning. arXiv preprint arXiv:2305.14333, 2023.
- Wanjun Zhong, Ruixiang Cui, Yiduo Guo, Yaobo Liang, Shuai Lu, Yanlin Wang, Amin Saied, Weizhu Chen, and Nan Duan. Agieval: A human-centric benchmark for evaluating foundation models. <u>arXiv preprint</u> arXiv:2304.06364, 2023.
- Bowen Zhou and Ning Ding. Generative ai for complex scenarios: Language models are sequence processors. International Journal of Artificial Intelligence and Robotics Research, 2024.
- Qihao Zhu, Daya Guo, Zhihong Shao, Dejian Yang, Peiyi Wang, Runxin Xu, Y Wu, Yukun Li, Huazuo Gao, Shirong Ma, et al. Deepseek-coder-v2: Breaking the barrier of closed-source models in code intelligence. arXiv preprint arXiv:2406.11931, 2024.
- Xuekai Zhu, Biqing Qi, Kaiyan Zhang, Xingwei Long, and Bowen Zhou. Pad: Program-aided distillation specializes large models in reasoning. arXiv preprint arXiv:2305.13888, 2023a.
- Zhaocheng Zhu, Yuan Xue, Xinyun Chen, Denny Zhou, Jian Tang, Dale Schuurmans, and Hanjun Dai. Large language models can learn rules. arXiv preprint arXiv:2310.07064, 2023b.
- Terry Yue Zhuo, Minh Chien Vu, Jenny Chim, Han Hu, Wenhao Yu, Ratnadira Widyasari, Imam Nur Bani Yusuf, Haolan Zhan, Junda He, Indraneil Paul, Simon Brunner, Chen Gong, Thong Hoang, Armel Randy Zebaze, Xiaoheng Hong, Wen-Ding Li, Jean Kaddour, Ming Xu, Zhihan Zhang, Prateek Yadav, Naman Jain, Alex Gu, Zhoujun Cheng, Jiawei Liu, Qian Liu, Zijian Wang, David Lo, Binyuan Hui, Niklas Muennighoff, Daniel Fried, Xiaoning Du, Harm de Vries, and Leandro Von Werra. Bigcodebench: Benchmarking code generation with diverse function calls and complex instructions, 2024.
- Andy Zou, Long Phan, Sarah Chen, James Campbell, Phillip Guo, Richard Ren, Alexander Pan, Xuwang Yin, Mantas Mazeika, Ann-Kathrin Dombrowski, et al. Representation engineering: A top-down approach to ai transparency. arXiv preprint arXiv:2310.01405, 2023.