# LASPATED: A Library for the Analysis of Spatio-Temporal Discrete Data (User Manual)

V. Guigues EMAp FGV A. J. Kleywegt Industrial and Systems Engineering Georgia Institute of Technology G. Amorim EMAp FGV A. Krauss Department of Informatics PUC-RJ

V. H. Nascimento PESC UFRJ

August 14, 2024

#### Abstract

This is the User Manual of the LASPATED library. This library is available on GitHub (at https://github. com/vguigues/LASPATED)) and provides a set of tools to analyze spatio-temporal data. A video tutorial for this library is available on Youtube. It is made of a Python package for time and space discretizations and of two packages (one in Matlab and one in C++) implementing the calibration of the probabilistic models for stochastic spatio-temporal data proposed in the companion paper Guigues et al. (2023).

## 1 Introduction

LASPATED is a library for the analysis of spatio-temporal data. It has a Python module for space and time discretization and a module for calibration of probabilistic models for such data. LASPATED takes as input a file of events with spatio-temporal information (a .csv file for example) or the corresponding Python DataFrame object. Each event has a location, a timestamp, and possibly a set of features.<sup>1</sup> LASPATED provides three different types of space discretization (in rectangles, hexagons, or customized) and several types of time discretization for such events. LASPATED also allows combining information from two different space discretizations. It computes the areas of intersection of all the subregions from the two discretizations. Given some attribute (for instance, the population) from the first discretization, LASPATED also computes the values of this attribute in the regions of the second discretization.

Time discretizations provide different partitions of time, for instance periodic with time windows of equal duration, periodic with time windows of different durations, or more general partitions, see Section 4.

The calibration module considers a discrete spatio-temporal time series, possibly built by the discretization module. The underlying model assumes the number of arrivals of type c, for zone i, and time window t, is Poisson with some intensity  $\lambda_{c,i,t}$ . Two strategies are implemented for the calibration of these intensities: maximizing a regularized Likelihood with penalizing weights obtained by cross validation and a model with covariates. The corresponding optimization problems are solved using projected gradient with line search along the feasible direction.

The outline of this manual is the following. Sections 3 to 7 describe the discretization tools. In Section 3, we explain how to load data. Time and space discretization functions are respectively discussed in Sections 4 and 5. Additional discretization features are provided in Section 6 while Section 7 explains how to access discretized data and how to write such data in files. Section 8 discusses the Matlab and C++ functions for the calibration of the probabilistic models. Our code is tested using GCC 11.4 and Python 3.10. The projection with covariates was solved using Gurobi 10.0.3.

<sup>&</sup>lt;sup>1</sup>We use the terms events and arrivals with the same meaning in this manual.

## 2 Python installation guide

LASPATED python library can be installed with pip. After downloading the source code, go to laspated directory and run:

\$ pip install .

Throughout this manual, the \$ sign represents the command line interface chosen by the user, whether it is Windows or Linux. The Docker container (see section 11) uses Linux Ubuntu. After running pip, the Python module and all its dependencies will be automatically installed.

## 3 Initializing a data aggregator and adding events

LASPATED library is imported with command **import laspated**. The library uses a *DataAggregator* object of spatial and temporal information.

There are multiple options when using latitude-longitude numbers to represent locations. When initializing the data aggregator object, we should specify the CRS (Coordinates Reference System) used in the data. It is important to note that our data can be passed to different CRS, but LASPATED will use the specified CRS when aggregating information, for instance we can choose app = spated.DataAggregator(crs="epsg:4326"), see Example 1 below.

The observations we are interested in are spatio-temporal observations which have a date and time information, a location information, and possibly additional features. As an example, consider the following 19 first lines of a CSV file reporting emergency calls to Rio de Janeiro emergency health service (a given line of this file available on the GitHub page of the project corresponds to a call and the information we have on the calls are the time of the call, the location given by latitude and longitude, and the priority of the call coded by an integer between 0 and 3):

```
date_time;priority;long;lat
01/01/2016 02:09;3;-43.33366;-22.86939
01/01/2016 02:13;0;-43.67589;-22.87618
01/01/2016 02:17;1;-43.29333;-22.90662
01/01/2016 02:28;0;-43.54172;-23.01242
01/01/2016 02:44;2;-43.35943;-23.01030
01/01/2016 02:51;0;-43.35715;-22.85183
01/01/2016 02:56;3;-43.63401;-23.00212
01/01/2016 02:57;2;-43.25316;-22.99458
01/01/2016 03:00;0;-43.39274;-22.82499
01/01/2016 03:01;1;-43.36692;-22.86628
01/01/2016 03:03;2;-43.51445;-22.87363
01/01/2016 03:05;2;-43.60198;-22.91049
01/01/2016 03:06;3;-43.17507;-22.96576
01/01/2016 03:07;3;-43.29519;-22.83136
01/01/2016 03:11;3;-43.68198;-22.97946
01/01/2016 03:18;3;-43.18982;-22.96926
01/01/2016 03:24;1;-43.46151;-23.02613
01/01/2016 03:26;3;-43.18726;-22.97490
```

This file contains in the first column a date and time information (column **date\_time** with date, hour, and minutes information), in the second column a priority (an integer between 0 and 3), in the third column **long** the longitudes, and in the fourth column **lat** the latitudes. To load this data with LASPATED, we first read the corresponding CSV file events.csv with

events = pandas.read\_csv("events.csv").

Then the columns of the file are passed as specific arguments **datetime\_col**, **lat\_col** and **lon\_col** of LAS-PATED method **add\_events\_data**. Additional information can be added inside a list passed to **feature\_cols** argument. In the example above, the additional information is the priority of the call, provided in column **priority**. Therefore, the data from this file is loaded with LASPATED using

Time-reference data can come in different formats, and the most common ones will be automatically detected and understood by LASPATED. A specific time column format using the **datetime\_format** argument can be used, as shown in the example above. This format should be defined based on the datetime library pattern, see https://docs.python.org/3/library/datetime.html#strftime-and-strptime-behavior for details.

We summarize in Example 1 the commands to load the events given in the file events.csv whose 19 first lines are shown above.

Listing 1: Building a data aggregator and adding events

```
1
        import laspated as spated
2
3
        # The data aggregator constructor receives a string with the coordinate \leftarrow
           reference system
 4
        app = spated.DataAggregator(crs="epsg:4326")
5
6
        # Creating a pandas dataframe with events. It must have columns with the \leftrightarrow
            timestamp, latitude and longitude and it may have other features
7
        events = pandas.read_csv("events.csv")
8
        # The add_events_data method stores the events in the aggregator. The user \leftrightarrow
9
            must provide the names of columns for the timestamps, locations and the \leftrightarrow
            list of columns for the features of interest.
10
        app.add_events_data(events, datetime_col='date_time', lat_col='lat', lon_col=↔
            "long", feature_cols=['priority'],datetime_format='%d/%m/%Y %H:%M:%S')
11
12
        # The data aggregator stores the events added in the events_data dataframe
13
        # Prints the first 19 observations, corresponding to the 19 observations \leftrightarrow
            shown above.
14
        print(app.events_data.head(19))
```

## 4 Time discretization

### 4.1 Periodic with elementary time windows repetition

LASPATED provides multiple types of time discretization via **add\_time\_discretization** method. The simplest discretization is obtained using periodic time windows, where each period is divided into so-called elementary time windows of the same duration. The duration of this elementary time window is specified in the second argument of method add\_time\_discretization while the time unit of this duration is given in the first argument, which is a string with possible values 'Y' for years, 'M' for months, 'W' for weeks, 'D' for day, 'H' for hours, 'm' for minutes, and 'S' for seconds. The duration of a period, in the time unit of the first argument of the method, is specified in the third argument of the method. Therefore, the third argument needs to be a multiple of the second argument: it is the duration of an elementary time window times the number of elementary time windows in a period. In Example 2, we consider two such discretizations. In the first one, we want to count the number of arrivals for every day of the week. Therefore, the first argument of add\_time\_discretization is 'D' (the time unit is a day), the second argument is 1 (an elementary time window lasts 1 day), and the third argument is 7 (the one-week period has 7 days). In the second discretization, we want to count the number of arrivals in time windows of 30 minutes every day. Therefore, the first argument of add\_time\_discretization is 'm' (the time unit is a minute), the second argument is 30 (an elementary time window lasts 30 minutes), and the third argument is 30\*48 (the one-day period has 30\*48 minutes).

Listing 2: Elementary time windows repetition.

```
1 # 7 days in a week
2 app.add_time_discretization('D', 1, 7)
3
4 # 48 30-minutes slots in a day
5 app.add_time_discretization('m', 30, 30*48)
```

### 4.2 Periodic with elementary time windows of different durations

We can modify the previous time discretization keeping periodic observations but with elementary time windows of different durations. The same method add time discretization will be used with the first argument still providing the time unit ('Y', 'M', 'W', 'D', 'H', 'm', or 'S'). The second argument now is a list providing the durations of successive elementary time windows. For instance, in Example 3 which follows, the time unit is 'M' (month) and the second argument is the list [3, 4, 2, 1, 2] providing successive elementary time windows of 3 months, 4 months, 2 months, 1 month, and 2 months. The third argument is the period, which should be a multiple of the sum of the durations specified in the list of the second argument. In Example 3 the period is 12 months meaning that we count the number of observations for January-February-March in a first group, for April-May-June-July in a second group, for August-September in a third group, for October in a fourth group, and for November-December in a fifth group. In this example, if the last argument was 24 instead of 12 we would have 10 groups of time observations: observations for January-February-March of years 1, 3, 5,..., (with the years counted from the first year of historical data) in a first group, for April-May-June-July of years 1, 3, 5,..., in a second group, for August-September of years 1, 3, 5,..., in a third group, for October of years 1, 3, 5,..., in a fourth group, for November-December of years 1, 3, 5,..., in a fifth group, for January-February-March of years 2, 4, 6,..., in a sixth group, for April-May-June-July of years 2, 4, 6,..., in a seventh group, for August-September of years 2, 4, 6,..., in a eighth group, for October of years 2, 4, 6,..., in a ninth group, and for November-December of years 2, 4, 6,..., in a tenth group.

Listing 3: Elementary time windows of different durations.

```
1 # this creates an index that repeats yearly (12 months)
2 # January, February, March => observations indexed by time index 0
3 # April, May, June, July => observations indexed by time index 1
4 # August, September => observations indexed by time index 2
5 # October => observations indexed by time index 3
6 # November, December => observations indexed by time index 4
7 app.add_time_discretization('M', [3,4,2,1,2], 12)
```

### 4.3 Customized time intervals

We can specify more general time windows like holidays or special events defined by the user. LASPATED allows such flexibility by defining a set of customized time indexes for time intervals. The user needs to provide a DataFrame with the following columns:

- 1. start: index start time. When the period for this index starts.
- 2. end: index end time. When the period for this index ends.
- 3. t: index number. The index of the corresponding time period will receive.
- 4. repetition: informs whether the index should be repeated in different years ("yearly").

The customized discretization defined by these parameters will be applied to the data. In Example 4, for data given for years 2016 and 2017, we define a customized discretization that considers additional time windows for holiday January 1 (this holiday is yearly, and the corresponding observations will receive index 1), and for Carnival. For Carnival, the observations will receive index 2 and the **repetition** column is None, since for every year the specific dates of Carnival are given (02-06 to 02-11 for 2016 and 02-24 to 03-06 for 2017). Arrivals that do not belong to a customized time interval receive the index zero. Also note that a yearly defined customized time interval must begin and end the same year.

```
1
  import pandas as pd
2
3
  time_disc_df = pd.DataFrame([
4
       ["2016-01-01", "2016-01-01", 1, "yearly"],
5
       ["2016-02-06", "2016-02-11", 2, None],
       ["2017-02-24", "2017-03-06", 2, None],
6
7
  ], columns=["start", "end", "t", "repetition"])
8
9
  app.add_time_discretization(time_disc_df)
```

## 5 Space discretization

### 5.1 Defining borders

The first step for space discretization is to define the border of a region that contains the arrivals. The border is the region that will next be discretized in space. This can be done with LASPATED either using a custom map or a region automatically built from data (a rectangular region or an approximate convex hull of arrivals).

#### 5.1.1 Custom map

LASPATED method add\_max\_borders adds a max\_border attribute to object app. The parameter data of this method is a GeoDataFrame object<sup>2</sup>. This GeoDataFrame object must have an attribute "geometry" encoding the vertices of the border and this object is obtained by calling the function **gpd.read\_file** which takes as argument a Shapefile (with .shp extension) of the custom map (region under consideration). In Example 5 below, we show how to use add\_max\_borders on two examples, with data lying in Rio de Janeiro for the first example and data in New-York for the second. The respective shape files rj.shp and ny.shp can be found on the internet and also in folders Data/rj and Data/ny of the GitHub project.

Listing 5: Adding borders from a custom map.

```
1
   import geopandas as gpd
2
   import matplotlib as plt
3
4 # GeoDataFrame object read from Rio de janeiro shape file
5 custom_map = gpd.read_file(r'../Data/rj/rj.shp')
6
  # adding as border
  app.add_max_borders(data=custom_map)
7
8
9 # Plotting the border
10 app.max_borders.plot()
11
   plt.show()
12
13 # GeoDataFrame object read from New-York shape file
14 custom_map = gpd.read_file(r'../Data/ny/ny.shp')
15 # adding as border
16 app.add_max_borders(data=custom_map)
17
18 # Plotting the border
19 app.max_borders.plot()
20 plt.show()
```

<sup>&</sup>lt;sup>2</sup>See https://geopandas.org/en/stable/docs/reference/api/geopandas.GeoDataFrame.html

#### 5.1.2 Rectangular border and convex hull

If a customized border is not available, we can use a rectangular border containing all events or an approximate convex hull of the space observations. In the first case, the argument of parameter method of LAS-PATED method add\_max\_borders is "rectangle" while in the second case this parameter method is "convex". The following Example 6 shows how to define these borders. Only one of these two options must be chosen.

#### Listing 6: Automatically defined borders.

```
1 # adding rectangular borders
2 app.add_max_borders(method="rectangle")
3 
4 # adding as border the convex hull of observations
5 app.add_max_borders(method="convex")
6 
7 # plotting borders and a sample of the events
8 app.plot_discretization()
```

Once borders are defined, the space discretization step will split the corresponding region into subregions (depending on the discretization scheme) and link these regions to the arrivals. This step is performed with LASPATED method **add\_geo\_discretization**.

### 5.2 Rectangular discretization

A rectangular discretization of the studied area defined in the previous section is obtained using LASPATED method **add\_geo\_discretization** and specifying the value 'R' for parameter **discr\_type**, and providing parameters **rect\_discr\_param\_x** and **rect\_discr\_param\_y** which respectively define the horizontal and vertical discretization steps. For instance, to generate a discretization into  $10 \times 30=300$  rectangles, we use the parameters' **rect\_discr\_param\_x=**10 and **rect\_discr\_param\_y=**30. The code of two rectangular discretizations for the city of Rio de Janeiro (using the borders of the city given by the corresponding shape file) is given in Example 7: the first discretization is a  $10 \times 10$  discretization in 100 rectangles (resulting in the rectangular discretization given in Figure 1) while the second discretization is a  $10 \times 100$  discretization in 10,000 rectangles (resulting in the rectangular discretization given in Figure 2).

Listing 7: Rectangular discretization.

```
1
   # Discretization in 10x10=100 rectangles
  # The corresponding discretization for Rio de Janeiro city is given in Figure 1
2
3
   app.add_geo_discretization(
 4
       discr_type='R',
5
       rect_discr_param_x=10,
6
       rect_discr_param_y=10
7
   )
8 # Plotting the regions
9 import matplotlib as plt
10 app.geo_discretization.boundary.plot()
11 plt.show()
12
13 # Discretization in 100x100=10 000 rectangles
14 # The corresponding discretization for Rio de Janeiro city is given in Figure 2
15
   app.add_geo_discretization(
16
       discr_type='R',
17
       rect_discr_param_x=100,
18
       rect_discr_param_y=100
19)
20
21 # Plotting the regions
22 app.geo_discretization.boundary.plot()
23
   plt.show()
```



Figure 1: Space discretization of a rectangle containing the city of Rio de Janeiro in  $10 \times 10 = 100$  rectangles, 76 of which have nonempty intersection with the city and are represented in the figure.



Figure 2: Space discretization of a rectangle containing the city of Rio de Janeiro in  $100 \times 100 = 10000$  rectangles, 4916 of which have nonempty intersection with the city and are represented in the figure.

### 5.3 Hexagonal discretization

LASPATED also provides a hexagonal discretization of the studied area (we have used Uber Python package H3 to generate the discretization).

This discretization is again obtained with LASPATED method **add\_geo\_discretization** now specifying 'H' for parameter **discr\_type** and an additional integer parameter textbfhex\_discr\_param taking values between 1 and 16, where the smaller the integer the coarser the discretization. Figures 3 and 4 show two hexagonal discretizations for the city of Rio de Janeiro obtained with Example 8 below: the first discretization uses scale parameter **hex\_discr\_param** equal to 7 while the second sets its scale to 8.

```
Listing 8: Hexagonal discretization.
```

```
1
2
   # Hexagonal discretization with scale parameter 7
З
  # The corresponding discretization for Rio de Janeiro city is given in Figure 3
4
   app.add_geo_discretization(
5
       discr_type='H',
6
       hex_discr_param=7
7
   )
8
9
  import matplotlib as plt
10 app.geo_discretization.boundary.plot()
11
   plt.show()
12
13 # Hexagonal discretization with scale parameter 8
14 # The corresponding discretization for Rio de Janeiro city is given in Figure 4
15 app.add_geo_discretization(
16
       discr_type='H',
17
       hex_discr_param=8
18)
19
20 # Plotting the regions
21
   app.geo_discretization.boundary.plot()
22
   plt.show()
```

### 5.4 Customized discretization

LASPATED also allows discretization with customized subregions. First, a GeoDataFrame object containing the geometries of each subregion needs to be provided. Then the space discretization is obtained again with method **add\_geo\_discretization** specifying 'C' as **discr\_type** parameter and the GeoDataFrame object of the subregions as the additional parameter **custom\_data**. For instance, in Example 9 where the studied area is the city of Rio de Janeiro, we take as subregions the administrative districts. The corresponding GeoDataFrame object, denoted by custom\_map in the example, is obtained from the Shapefile rio\_neighborhoods.shp of the districts of the city (this shape file can be found on the GitHub page of the project). Figure 5 displays the corresponding customized discretization by administrative districts.

Listing 9: Custom discretization.

```
1 import geopandas as gpd
2 custom_map = gpd.read_file(r'../Data/rio_de_janeiro_neighborhoods/↔
        rio_neighborhoods.shp')
3 app.add_geo_discretization('C', custom_data=custom_map)
4 
5 # Plotting the regions
6 app.geo_discretization.boundary.plot()
7 plt.show()
```



Figure 3: Space discretization of a rectangle containing the city of Rio de Janeiro in hexagons using Uber library H3 for space discretization in hexagons with scale parameter equal to 7.



Figure 4: Space discretization of a rectangle containing the city of Rio de Janeiro in hexagons using Uber library H3 for space discretization in hexagons with scale parameter equal to 8.



Figure 5: Space discretization of the city of Rio de Janeiro into 160 administrative districts.

### 5.5 Voronoi discretization

Given a set of locations  $L = \{\ell_1, \ell_2, \dots, \ell_n\}$ , LASPATED allows a discretization based on the Voronoi diagram given by the vertices in L. In our context, a Voronoi diagram is a partition of the border, given by the distances to each location in L. In the diagram, zone  $r_i$  contains all locations that are the closest to location  $\ell_i$  than any other location in L. An application of Voronoi diagrams is to define possible covering regions for facilities (hospitals, schools, etc.).

Example 10 loads a GeoDataFrame object corresponding to the ambulance bases in Rio de Janeiro (we read the corresponding Shapefile bases.shp). Then it obtains the Voronoi discretization using again Laspated method add\_geo\_discretization by setting 'V' as **discr\_type** parameter and providing the bases as a GeoDataFrame object in parameter **custom\_data**. Figure 6 displays the corresponding discretization given by the Voronoi diagram, with the dots corresponding to ambulance base locations.

Listing 10: Voronoi discretization.

```
1 import geopandas as gpd
2 bases = gpd.read_file("bases/bases.shp")
3 app.add_geo_discretization('V', custom_data=bases)
4 
5 # Plotting the regions
6 app.geo_discretization.boundary.plot()
7 plt.show()
```

## 6 Additional discretization features

In the previous section, we have seen how to define a spatial discretization, say discretization  $D_1$ . Let  $\mathcal{I}$  be the index of the regions of this spatial discretization. Assume we have another discretization of the studied area, say discretization  $D_2$ , with regions indexed by  $\mathcal{J}$ . In this context, LASPATED provides the following two functionalities:

• get\_intersection(gpd1, gpd2): it computes the areas  $\mathcal{A}(i, j)$  of the intersections of regions  $i \in \mathcal{I}$  and  $j \in \mathcal{J}$ . Parameters gpd1 and gpd2 are the GeoDataFrames corresponding to discretizations  $D_1$  and



Figure 6: Discretization into 34 regions of the city of Rio de Janeiro given by the Voronoi diagram of ambulance bases in Rio de Janeiro.

 $D_2$ . The method returns the areas  $\mathcal{A}(i, j)$  as a 2-D NumPy array, with the areas measured in square kilometers.

• **app.add\_geo\_variable(gpd2,type\_geo\_variable).** Consider a given attribute, for instance the population and assume that for every region  $j \in \mathcal{J}$  of discretization  $D_2$ , we have a density  $d_j$  of this attribute; the attribute being uniformly distributed in the region. Let  $P_j = d_j \mathcal{A}(j)$  be the value of the attribute in region  $j \in \mathcal{J}$  where  $\mathcal{A}(j)$  is the area of region j. When **type\_geo\_variable** is equal to "feature", LASPATED computes the value of the attribute  $\sum_{j \in \mathcal{J}} d_j \mathcal{A}(i,j) = \sum_{j \in \mathcal{J}} \frac{P_j}{\mathcal{A}(j)} \mathcal{A}(i,j)$  for all regions  $i \in \mathcal{I}$ .

This calculation is simply obtained knowing attributes  $(P_j)$  and once areas  $\mathcal{A}(j)$  and  $\mathcal{A}(i, j)$  (using get\_intersection) have been computed. The corresponding computation is done with LASPATED using method add\_geo\_variable. In Example 11, we consider the attribute population. We first read the corresponding shape file population.shp generating a GeoDataFrame object and filter only the columns "population" and "geometry". This file can be found on the project GitHub page and gives the population in all the districts of the city of Rio de Janeiro. Therefore, for this example, discretization  $D_2$  is given by the districts of Rio de Janeiro (see Figure 5). The GeoDataFrame object filtered as explained above is passed as an argument of method add\_geo\_variable. The object app will contain information about the population of every elementary cell of discretization  $D_1$  (see also the next section).

If we assume the index set  $\mathcal{J}$  for the second discretization  $D_2$  is partitioned into k index sets  $\mathcal{J}_1, \ldots, \mathcal{J}_k$ :  $\mathcal{J} = \sum_{i=1}^k \mathcal{J}_i$ , then LASPATED method add\_geo\_variable can be invoked with **type\_geo\_variable** equal to "area" can also be used to compute  $\mathcal{A}_{i\ell} = \sum_{j \in \mathcal{J}_\ell} \mathcal{A}(i, j)$  for every  $\ell = 1, 2, \ldots, k$ , and  $i \in \mathcal{I}$ . In

Listing 11, we read a shape file soil\_use.shp (available on the GitHub page of the project) providing the different land types (we have 16 of them in this data) for the city of Rio de Janeiro. Each elementary cell of this discretization contains one land type only. We then filter the first two land types. It then suffices to pass the corresponding GeoDataFrame object to method add\_geo\_variable. The object app will contain information about the areas of land types 1 and 2 for every elementary cell of discretization  $D_1$  (see the next section).

Listing 11: Additional discretization features.

```
1 import geopandas as gpd
2 population = gpd.read_file(r'../Data/regressors/population/population.shp')
3 population = population[["population", "geometry"]].copy()
4 app.add_geo_variable(population,type_geo_variable='feature')
5
6 land_use = gpd.read_file(r'../Data/regressors/soil_use/soil_use.shp')
7 land_use = land_use[["type_1", "type_2", "geometry"]].copy()
8 app.add_geo_variable(land_use,type_geo_variable='area')
```

## 7 Retrieving and writing discretization data in files

LASPATED spatio-temporal discretizations are stored in the dataframe **app.events\_data** and in the Geo-DataFrame **app.geo\_discretization**. Dataframe **app.events\_data** has the same columns as the events dataframe loaded in Section 2, plus time and spatial discretization columns. For each event, the time index discretizations are added with the columns named **tdiscr\_i**, i = 0, ..., T - 1, with T being the number of time index discretizations defined. Custom column names may be provided in the **app.add\_time\_discretization** method, with the default **column\_name** parameter. Similarly, the spatial discretization is added with the default name **gdiscr**. For each event, **gdiscr** is the index of the region where the event took place. The regions defined in the spatial discretization are fully detailed in the **app.geo\_discretization** dataframe. For each region, the dataframe stores its index, the list of indexes of neighboring regions, the latitude/longitude of the centroid of the region, and columns with its additional discretization features (for instance population, areas of different land types, see Section 6 and Example 11 for these features).

LASPATED method **get\_events\_aggregated()** returns a NumPy multidimensional array of lists A, where  $A[t_0, t_1, \ldots, t_{T-1}, g, f_0, f_1, \ldots, f_{F-1}]$  is a list containing the number of events observed in app.events\_data for time discretizations  $t_0, \ldots, t_{T-1}$ , spatial discretization g and features  $f_0, \ldots, f_{F-1}$  with T being the number of time discretizations and F the number of features. Example 12 shows how to call the method.

Listing 12: Aggregating events by discretization.

```
app.add_events_data(events, datetime_col='date_time', lat_col='lat', lon_col="
 1
       long", feature_cols=['priority'])
2
3
   app.add_time_discretization('m', 30, 30*48) # tdiscr_0
4
   app.add_time_discretization('D', 1, 7) # tdiscr_1
5
6
   app.add_geo_discretization(
7
       discr_type='R',
8
       rect_discr_param_x=10,
9
       rect_discr_param_y=10
10
   )
11
12 events_agg = app.get_events_aggregated()
13
14 # Axis are respectively: tdiscr_0, tdiscr_1, gdiscr, priority
15 print(events_agg.shape)
```

The method write\_arrivals(path\_arrivals) calls the get\_events\_aggregated() method and saves A in the path given by path\_arrivals. The method write\_regions(path\_regions) saves information about the space discretization in the path given by path\_regions, see Example 13 and the corresponding files on the github page of the project.

Listing 13: Writing the discretized data to a file.

```
1 app.write_arrivals("arrivals.dat")
2 app.write_regions("neighbours.dat")
```

## 8 Model calibration

## 8.1 Matlab LASPATED calibration functions

### 8.1.1 Calibration of the models for fixed penalties

LASPATED function laspated calibrates the models described in Section 2 of the companion paper Guigues et al. (2023). For this function, fixed penalties  $w_{i,j}$  and  $W_G$  are used and the optimization problems to be solved to calibrate the models are solved with the projected gradient method with Armijo line search along the feasible direction. In this section, we focus on laspated function.

A typical call to laspated is

[lambda,obj]=laspated(model, nbObservations, nbArrivals, T, R, C, durations, Groups, whichgroup, sigma, iterMax, epsilon, lambda0, params).

This function has a variable model which is a string which is noreg to calibrate the model without regression and reg to calibrate the model with regression (other values of this string will generate the message Invalid model name).

Function laspated has also the following input variables:

- nbObservations, which gives the number of observations for every possible combinations of arrival types, time steps, and regions. More precisely, if model=noreg then nbObservations is a 3 dimensional array with nbObservations(c,i,t) the number of observations for arrival type with index c, region with index i, and time window with index t (this is parameter  $N_{c,i,t}$  of the model without regressors of Guigues et al. (2023), Section 2.) and if model=reg then nbObservations(c,d,t,i) is the number of observations for arrival type c, day or holiday d, time window with index t, and region with index i (this is parameter  $N_{c,d,t,i}$  of the model with out regressors of Guigues et al. (2023), Section 2.)
- nbArrivals: array providing the number of arrivals. More precisely, if model=noreg then this is a 3 dimensional array with nbArrivals(c,i,t) the total number of arrivals observed for time window t, region i, arrival type c (this is parameter  $M_{c,i,t}$  of the model without regressors of Guigues et al. (2023), Section 2) and if model=reg then nbArrivals(c,d,t,i) is the number of arrivals for arrival type c, day or holiday d, time window with index t, and region with index i (this is parameter  $M_{c,d,t,i}$  of the model with regressors of Guigues et al. (2023), Section 2);
- T: number of discretized time intervals (this is  $|\mathcal{T}|$ );
- R: number of regions (this is  $|\mathcal{I}|$ );
- C: number of arrival types (this is |C|);
- durations: 1-dimensional array with durations(t) the duration of time interval with index t;
- Groups: when model=noreg cell array with Groups{1,i} an array where Groups{1,i}(j) is the index of *j*th time interval which is in time group with index i. Time groups could be added in a future version of the model with regressors but for now set Groups=[] when model=reg.
- whichgroup: 1-dimensional array of size *T* where whichgroup(t) is the index of the time group which contains time interval with index t. Time groups could be added in a future version of the model with regressors but for now set whichgroup=[] when model=reg;
- sigma: this is the value of parameter *σ* in the pseudo-code for projected gradient with Armijo line search along the feasible direction given in Section 2 of the companion paper Guigues et al. (2023);
- iterMax: maximal number of iterations for projected gradient; this is parameter MaxNumberIteration for the pseudo-code in Section 2 of the companion paper Guigues et al. (2023);
- epsilon: parameter ε for the models (reg and noreg) in Section 2 of the companion paper Guigues et al. (2023);

• lambda0: initial value  $\lambda_0$  of  $\lambda$ ; when model=noreg, this is a 3 dimensional array with lambda0(c,i,t) an initial guess for the vector of intensities  $\lambda_{c,i,t}$  for time window with index t, region with index i, arrival type c and lambda0(c,i,t) greater than  $\varepsilon$ . When model=reg this is an initial value for  $\beta = (\beta_{c,d,t})_{c,d,t}$  which needs to be non negative.

Function laspated has also a structure params with parameters that depend on the model. When model=noreg, then params has the following fields:

- params.neighbors: cell array with params.neighbors{1,i} the list of the indexes of the neighbors of region with index i;
- params.weight: 1-dimensional array with params.weight(i) the weight  $W_G$  corresponding to time group G with index i in the loss function; see Section 2 of the companion paper Guigues et al. (2023) for the expression of the loss function;
- params.distance: 2-dimensional array with params.distance(i,j) the distance between the centroids of regions with indexes i and j;
- params.alpha: this is the common value of weights  $w_{ij}$  in the loss function (given in Section 2 of Guigues et al. (2023)) which are equal to params.alpha only when regions with indexes *i* and *j* are neighbors;
- params.delta: parameter  $\delta$  in stopping criterion (15) of LASPATED paper Guigues et al. (2023);
- params.uppx (resp. params.lowx) is an upper bound (resp. a lower bound) on  $\lambda$ .

When model=reg, then params has the following fields:

- · params.D: number of days plus holidays;
- params.indexBeta: a vector of indexes for  $\beta$  such that  $\beta_{c,d,t}(j)$  is given by

lambda(params.indexBeta(c,d,t,j))

(lambda being the optimization variable);

- params.regressor: params.regressor(j,i) is the value of regressor j for region with index i;
- · params.nbRegressors: number of regressors;
- params.sizex: number of entries in vector  $\beta = (\beta_{c,d,t})_{c,d,t}$ .

The outputs are

- lambda: when variable model is noreg lambda is an estimated optimal solution. More precisely, this is a 3 dimensional array with lambda(c,i,t) the optimal intensity  $\lambda_{c,i,t}$  for time window t, region i, arrival type c. When variable model is reg, lambda is a 1 dimensional vector with lambda(params.indexBeta(c,d,t,j)) an optimal value for  $\beta_{c,d,t}(j)$ .
- obj: this is the estimated optimal value along iterations of the optimization method used to solve the optimization problems.

#### 8.1.2 Calibration of penalties

The calibration of parameters  $w_{i,j}$  and  $W_G$  for the loss function of the model without regressors from Section 2 in Guigues et al. (2023)) can be done calling function crossValidation of LASPATED library. This function uses cross validation to estimate a value  $\alpha = w_{i,j} = W_G$  common to all pairs of neighboring regions i, j and all groups G. A call to this function is

```
[cputime,weight,lambda]=crossValidation(model, sample, T, R, C, sigma,
lambda0, iterMax, proportion, epsilon, durations, Groups,
whichgroup, weights, params).
```

The input variables which have the names of the input variables of laspated function have the same meaning as before. Additionally we have the following input variables:

- sample which is the sample of arrivals. More precisely, sample is a 4-dimensional array with sample(t,i,c,j) the *j*th observation for time window *t*, region *i*, and arrival type *c*;
- proportion is a real in the interval (0,1) (typically 0.2) which is the proportion of data used in every estimation block of cross validation while the proportion (1-proportion) is the proportion of data used for validation (in cross validation).
- weights is an array of candidate weights for  $w_{i,j}$  and  $W_G$ .

params is a structure with the fields params.neighbors=neighbors, params.distance=distance, params.alpha=1, which have the same meaning as before.

#### 8.1.3 Matlab examples

**Simulated data, model without regressors.** File laspatedex1noreg.m of the library contains function laspatedex1noreg run with the command

[weight, lambda, obj] = laspatedex1noreg()

which builds the data corresponding to the example of Section 6.1 in Guigues et al. (2023) and runs laspated calibration function for the model without regressors for a set of penalizations. It also runs cross validation. The output weight is the best penalization found by cross validation and lambda is the vector of intensities.

**Simulated data, model with regressors.** File laspatedex1reg.m of the library contains function laspatedex1reg run with the command

[weight, lambda, obj] = laspatedex1reg()

which builds the data corresponding to the example of Section 6.2 in Guigues et al. (2023) and runs laspated calibration function for this example.

### 8.2 C++ LASPATED calibration functions

LASPATED also provides an implementation in  $C_{++}$  of the calibration functions. All code is contained in the header file laspated.h. The user can run the calibration functions by building a model object and a struct with parameters for the projected gradient and cross validation functions. In the following sections we explain how the  $C_{++}$  classes and methods work and show examples of the main functionalities.

#### 8.2.1 Compilation and dependencies

C++ calibration functions use the following libraries:

- Gurobi (https://www.gurobi.com), used only in the model with covariates;
- xtensor and xtl libraries;

When compiling the code, the user need to pass the location of the header files for laspated, xtl, xtensor and gurobi, as well as the location for the Gurobi libraries and their respective flags. xtl and xtensor requires the C++14 standard and its flag must also be passed. The example below compiles an executable called laspated from a main.cpp that includes laspated. The example considers that the Gurobi solver will be used.

```
$ g++ -o laspated main.cpp -std=c++14 -I<gurobi_header_dir> -I<laspated_header_dir>
    -I<xtl_header_dir> -I<xtensor_header_dir> -L<gurobi_libs_dir>
    -lgurobi_c++ -lgurobi100
```

If Gurobi cannot be acquired, calibration functions for the model without covariates can still be used by passing the flag **-DUSE\_GUROBI** equal to zero. The following command can be used to compile:

\$ g++ -o laspated main.cpp -std=c++14 -DUSE\_GUROBI=0 -I<laspated\_header\_dir>
 -I<xtl\_header\_dir> -I<xtensor\_header\_dir>

We provide five test models in the source file test\_problems.cpp and test\_problems.h in the Model\_Calibration directory. They were used for assert the quality of the projected gradient algorithm.

#### 8.2.2 Classes and attributes

The C++ calibration implements a class **RegularizedModel** that represents the model without covariates and class **CovariatesModel** that represents the model with covariates. There is also a **Param** struct, containing all parameters for the projected gradient and cross validation functions. The **Param** struct has the following members:

- · double EPS: tolerance used in comparisons and in the projection algorithm;
- · double sigma: parameter used in the line search of the projected gradient method;
- double accuracy: gap used as stopping criterion for the projected gradient method;
- int max\_iter: maximum number of iterations for the projected gradient method;
- · double lower\_lambda: lower bound for decision variables in the projected gradient method;
- double upper\_lambda: upper bound for decision variables in the projected gradient method;
- · double beta\_bar: initial step size for the projected gradient method;
- double cv\_proportion: proportion of samples used in each sub-iteration of the cross validation.

Class RegularizedModel has the following attributes:

- · param: reference for some parameter object;
- nb\_observations: number of observations for each type-zone-time index;
- nb\_arrivals: number of events for each type-zone-time index;
- durations: duration, in hours, for each time index;
- groups: description of time groups. groups[i][j] is the j-th time index in the i-th group;
- · weights: time regularization weight for each time group;
- alpha: space regularization weight matrix of zones;
- · distance: distance matrix of zones;
- type\_region: space groups. type\_region[r] is the type of subregion r;
- neighbors: neighborhood description. neighbors[i][j] is the j-th neighbor of subregion i;
- which\_group: groups of each time index;
- C: number of event types;
- R: number of zones;
- T: number of periods.

The type of each attribute is defined according to the constructor method:

The CovariatesModel has the following attributes:

- env: Gurobi environment object;
- · param: reference for some parameter object;
- nb\_observations: number of observations for each type-zone-time index;
- · nb\_arrivals: number of events for each type-zone-time index;
- regressors: regressors array. regressor(j,r) is the value of the j-th regressor for zone r;
- C: number of event types;
- · D: number of days;
- T: number of periods;
- R: number of zones;
- nb\_regressors: number of regressors;

with the constructor:

Both model classes have the same methods, with different implementations. The methods are used in the calibration functions and to assess the quality of its solutions:

- double f(xt::xarray<double> &x): returns the value of the objective function at x,
- xt::xarray<double> gradient(xt::xarray<double> &x): returns the gradient of f at x,
- xt::xarray<double> projection(xt::xarray<double> &x): returns the projection of x into the model feasible region,
- bool is\_feasible(xt::xarray<double> &x): returns true if x is in the feasible set,
- double get\_rhs(xt::xarray<double> &grad, xt::xarray<double> &dir): returns the value of the directional derivative given by gradient grad and direction dir.
- double get\_lower\_bound(xt::xarray<double> &x, xt::xarray<double> &grad): returns objective function lower bound given x and gradient grad.
- double average\_rate\_difference(xt::xarray<double> &x1,xt::xarray<double> &x2): returns average absolute difference in rates between x1 and x2.

#### 8.2.3 Calibration of the model without regressors

Given the objects described in the previous section, the function:

Solves the model using the projected gradient method, with parameters given by the param object and with initial solution x. The function uses C++ templates, meaning that Model can be replaced with **Regu-IarizedModel** or **CovariatesModel**. The function returns the best solution found in the projected gradient method.

Example 14 calls the calibration method for the model of section 2.1 from the paper. For simplicity, we ommitted the code that initializes all the model attributes. We begin including laspated header and using the laspated namespace. Next, we build a **RegularizedModel** object m, a **Param** object param and then run the projected gradient method, storing the result in the xarray lambda.

Listing 14: Calibration of the model without regressors in C++

```
1
2
  #include "laspated.h"
3
  // All laspated functions in namespace laspated
   using namespace laspated;
4
5
6
7
   int main(int argc, char* argv[]){
8
       // Load variables nb_observations, nb_arrivals, durations, groups,
9
            weights, alphas, distance, type_region, neighbors.
10
       // Builds param object with default parameters.
11
       Param param;
12
       RegularizedModel m(nb_observations, nb_arrivals, durations, groups, weights, \leftarrow
           alphas, distance, type_region, neighbors, param);
13
14
       // Initial solution
15
       xt::xarray<double> lambda0 = 0.1*xt::ones<double>(nb_observations.shape());
16
       // Runs the solver
17
       xt::xarray<double> lambda = projected_gradient_armijo_feasible<↔
           RegularizedModel>(m, param, lambda0);
18
19
       return 0;
20
   }
```

### 8.2.4 Cross Validation

Cross validation can also be run for the model without regressors. the cross\_validation function has the following signature:

Where CrossValidationResult is the following struct:

```
typedef struct {
    double cpu_time;
    double weight;
    xt::xarray<double> lambda;
} CrossValidationResult;
```

Example 15 shows how to execute the cross validation. The user must set the parameter  $cv\_proportion \in (0, 1]$  in the **Param** object, build a **RegularizedModel** object and provide a vector of  $cv\_weights$ . The cross validation will evaluate how the model performs considering each weight in  $cv\_weights$  as both the space and time regularization penalties. The return struct contains the time spent performing cross validation, the best weight and the solution of the model considering the best weight. Note that the alphas and weights passed when building m are ignored in the cross validation, being replace with each weight in  $cv\_weights$  during the cross validation.

Listing 15: Cross validation in C++

```
1 #include "laspated.h"
2 #include <vector>
3
4 using namespace laspated;
5
   using namespace std;
6
7
   int main(int argc, char* argv[]){
8
       // After loading variables nb_observations, nb_arrivals, durations, groups,
9
            weights, alphas, distance, type_region, neighbors...
10
       // Builds param object with default parameters.
11
       Param param;
12
       // Sets proportion for cross validation
13
       param.cv_proportion = 0.2;
14
       RegularizedModel m(nb_observations, nb_arrivals, durations, groups,
15
            weights, alphas, distance, type_region, neighbors, param);
16
       vector < double > cv_weights {0.1,1,10};
17
       CrossValidationResult result = cross_validation(param, m, cv_weights);
18
19
       return 0;
20
   }
```

#### 8.2.5 Calibration of the model with regressors

Example 16 performs the calibration of the model from section 2 of the LASPATED paper Guigues et al. (2023). The same function projected\_gradient\_armijo\_feasible can be used. We pass both the class **CovariatesModel** and a instance of it to the function. The CovariatesModel objected must be built using the observations, arrivals and covariates (regressors) data. The projected\_gradient\_armijo\_feasible returns the estimated  $\beta$  variables found.

Listing 16: Calibration of the model with regressors in C++

```
1 #include "laspated.h"
   2
           // All laspated functions in namespace laspated
   3
            using namespace laspated;
   4
   5
   6
              int main(int argc, char* argv[]){
   7
                                   // Load variables nb_observations, nb_arrivals, and regressors.
   8
                                   // Builds param object with default parameters.
   9
                                   Param param;
10
                                   //Builds model object
11
                                   Covariates m(nb_observations, nb_arrivals, regressors);
12
13
                                   // Initial solution
14
                                  xt::xarray<double> beta0 = 0.1*xt::ones<double>(nb_observations.shape());
15
                                   // Runs the solver
16
                                   \texttt{xt::xarray} < \texttt{double} > \texttt{beta} = \texttt{projected} \texttt{gradient} \texttt{armijo} \texttt{feasible} < \texttt{Covariates} \texttt{Model} \leftrightarrow \texttt{for the startard start
                                                  >(m, param, beta0);
17
```

#### 8.2.6 Laspated C++ app

To those unfamiliar with C++, we also provide a laspated binary app that allows running the calibration functions. The user must provide a set of files describing the model and a set of configuration options, either via a configuration file or command line. The options describe the algorithmic parameters and model attributes and file locations. The valid options are the following:

- double EPS: tolerance used in comparisons and in the projection algorithm;
- · double sigma: parameter used in the line search of the projected gradient method;
- double accuracy: gap used as stopping criterion for the projected gradient method;
- int max\_iter: maximum number of iterations for the projected gradient method;
- double lower\_lambda: lower bound for decision variables in the projected gradient method;
- double upper\_lambda: upper bound for decision variables in the projected gradient method;
- double beta\_bar: initial step size for the projected gradient method;
- double cv\_proportion: proportion of samples used in each sub-iteration of the cross validation;
- output\_file: path where the laspated app will save the estimated intensities.
- string model\_type: the type of model being solved, must be either "reg" (CovariatesModel) or "no\_reg" (RegularizedModel);
- string method: the type of method being used. For the CovariatesModel, only "calibration" is supported (running the projected gradient algorithm once). For RegularizedModel, can be either "calibration" or "cross\_validation";
- string algorithm: the algorithm used. Can be either "feasible" for projected gradient along the feasible region or "boundary" for the projected gradient along the boundary, however "cross\_validation" only supports the "feasible" algorithm;
- string info\_file: path of file containing general information about the model. See below for a precise description of the format.
- arrivals\_file: path of file containing the samples of arrivals file.
- neighbors\_file: path of file containing description of each zone, including its type, its covariates, and neigborhoods.
- alpha\_regions\_file: path of file containing the space regularizing  $R \times R$  matrix.
- time\_groups\_file: path of file containing a description of period groups and their temporal regularization penalties.
- double duration: The duration of each period.
- cv\_weights\_file: path of file containing the weights to be used in cross validation.

Note that to sue the CovariatesModel, the user only needs to specify the info, arrivals, and neighbors files. Additionally, for the RegularizedModel, the user must specify the alpha\_regions\_file and time\_groups\_file. When performing cross validation, the cv weights file is also needed.

The info\_file must contain two lines. The first line must contain, separated by spaces, the number of periods T per day, the number of week days G, the number of zones R, the number of arrival types C, the number of covariates J and the number of holidays H on each year. The second line contains, for each week

day and holiday, the number of observations  $N_g$  for that day considered on the samples. Values of index g from 0 to 6 are defined as the weekdays while the holidays are defined as  $\{7, 8, ..., 7 + H\}$ .

The arrivals\_file contains the samples observed, where each line describes a sample. Each line contains, separated by spaces, the period  $t \in [0, T)$ , the day  $g \in [0, G)$ , the zone  $r \in [0, R)$ , the arrival type  $c \in [0, C)$ , the sample index  $j \in [0, N_g)$ , the number of arrivals observed, and a flag indicating whether the day is a holiday or not.

The neighbors\_file contains the description of each zone. Each line contains the zone index, two values representing coordinates of the zone centroid, a number indicating the zone's type, J values corresponding to each covariate, followed by a set of pairs of values indicating the index and the distance of each neighbor of the current zone.

The alpha\_regions\_file describe the space regularizations terms. It contains a  $R \times R$  matrix separated by spaces, where entry (i, j) corresponds to the weight included in the objective function of the Regularized-Model if zones *i* and *j* are neighbors.

The time\_groups\_file contains description of groups of periods and their corresponding penalties. The first line must have the number  $\mathcal{G}$  of time groups. Then, the subsequent D \* T lines must have the group index of each period. Then the subsequent  $\mathcal{G}$  lines may contain the weight of each group; if the method is set to "cross validation", the reading of time weights is skipped.

The cv\_weights\_file contains the weights to be used in cross validation, separated by spaces. Each weight must non-negative.

The LASPATED app is only supported in Linux operating systems. The user must have the GCC compiler and the Boost library. Libraries xtl and xtensor are also used and provided with the In order to use the CovariatesModel, the user must have Gurobi installed. The directory Model\_Calibration/Cpp contains a Makefile that is used to compile the app with:

```
$ make GUROBI_LIB_VER=-lgurobi110 GUROBI_HOME=/opt/gurobi1101/linux64
INCLUDE_BOOST=/usr/include/boost
```

The Makefile uses GUROBI\_HOME to find the Gurobi directory, GUROBI\_LIB\_VER to find the Gurobi C library version and INCLUDE\_BOOST to find the Boost directory. The values displayed above are actually the default values set in the Makefile, so if Boost and Gurobi are installed in those locations, then just the make command will compile the code. Once the laspated app is successfully compiled, it can be run with:

```
$ ./laspated -f config
$ ./laspated -f config --option_1=val_1 --option_2=val_1 ...
```

where config is the config text file with options. Note that, in the second example, the options provided in the command line override any options with the same name in the config file.

After running the laspated app, the output is saved in the path provided by option output\_file. If the RegularizedModel was used, the output contains on each line the indexes  $c \in [0, C)$ ,  $r \in [0, R)$ ,  $t \in [0, D * T)$ , and the intensity  $\lambda_{crt}$  estimated by LASPATED. If CovariatesModel is used, then each line correspond to indexes  $c \in [0, C)$ ,  $d \in [0, D)$ ,  $t \in [0, T)$ ,  $j \in [0, J)$ , and the parameter  $\beta_{cdtj}$  estimated by LASPATED.

## 9 Demo scripts

In the LASPATED source code repository, we provide a demo directory, containing examples for the discretization and calibration functions. The demo summarizes all code excerpts provided in the previous sections. The directory contains three Python files:

- demo\_discretization.py: Contains examples of how to generate a discretization;
- demo\_calibration\_regularized.py: Contain an example of running the calibration and cross-validation using the regularized model (without covariates);
- demo\_calibration\_covariates.py: Contain an example of running the calibration model with covariates.

The discretization demo can be run with

\$ python demo\_discretization.py border\_type discretization\_type

where border\_type can be: *rectangle*, *convex* or *custom* and discretization\_type can be: *rectangle*, *hexagon* or *custom*. The border type defines the type of border: rectangular, convex or the border of Rio de Janeiro city (custom). The discretization type can be rectangular, hexagonal or according to Rio de Janeiro's administrative regions (custom). The script considers arrival data from Rio de Janeiro and produces output files considering three time discretizations, and the Rio de Janeiro population as an additional feature.

Before running the calibration demo, the user must compile the laspated executable, following instructions from section 8.2.6. The calibration demo for the model without covariates can be run with

\$ python demo\_calibration\_regularized.py

Additionally, the calibration demo for the model with covariates can be run with:

\$ python demo\_calibration\_covariates.py

The input files for the C++ functions and the output of the functions are saved inside the demo/calib\_data respective subdirectories. The regularized model script runs the calibration function considering an unitary weight time and space regularization, and a cross-validation procedure considering a set of weights.

## 10 Replication script

Along with the LASPATED source code, we also provide a python script that performs all experiments from Guigues et al. (2023). Before running the script, the first step is to compile the C++ code. If you have a GCC compiler installed, this can be done by running the command:

\$ cd LASPATED/Replication
\$ make C ann tosts

\$ make -C cpp\_tests

The cpp\_tests directory contains a Makefile that can be edited by the user that compiles the C++ script. The Makefile inside directory cpp\_tests accesses the user-defined environment variable \$GUROBI\_HOME. If it is set, then the code for the model with Covariates inside laspated.h is accessible. Otherwise, the script will not run the experiments that use covariates.

After the C++ code is successfully compiled, you can run the replication script by simply running:

```
$ python replication_script.py
```

This command will generate the rectangular, hexagonal and district discretizations using the laspated python module, run the experiments with the C++ code and process the results, generating the figures and tables presented in the paper.

All results presented in the paper are saved in the directory replication\_results, with subdirectories plots and tables. If you want access to the raw data generated by C++, check the directory cpp\_tests/results, with subdirectories for each experiment made. Subdirectories ex1 and ex2 contain results for the first and second model without covariates (Examples 1 and 2). Subdirectory ex3 contains results for the model with covariates (Table 2 of the paper) and real\_data contains results for the experiments with real data of Rio de Janeiro. For more details, see Guigues et al. (2023).

### 11 Docker container

We also provide a Docker container. The docker container comes with all dependencies installed and can be built in the project root directory using:

\$ docker build -t laspated-dock .

and run with command:

```
$ docker run -it laspated-dock
```

If the user has a Gurobi WLS license, it can be added using:

```
$ docker run --volume="/absolute/path/to/gurobi.lic:/opt/gurobi/gurobi.lic:ro"
-it laspated-dock
```

This command will download all Python dependencies and install laspated on the \$PYTHONPATH, so you can use it in Python via:

import laspated

See the demo directory for examples on how to run the discretization functions, and how to run the C++ calibration functions from Python.

## References

V. Guigues, A. J. Kleywegt, G. Amorim, A. M. Krauss, and V. H. Nascimento. LASPATED: A Library for the Analysis of SPAtio-TEmporal Discrete Data. arXiv:2401.04156v2 [stat.ME], 2023.