# DisenSemi: Semi-supervised Graph Classification via Disentangled Representation Learning

Yifan Wang, Xiao Luo, Chong Chen, Member, IEEE, Xian-Sheng Hua, Fellow, IEEE, Ming Zhang and Wei Ju, Member, IEEE

Abstract—Graph classification is a critical task in numerous multimedia applications, where graphs are employed to represent diverse types of multimedia data, including images, videos, and social networks. Nevertheless, in real-world scenarios, labeled graph data can be limited or scarce. To address this issue, we focus on the problem of semi-supervised graph classification, which involves both supervised and unsupervised models learning from labeled and unlabeled data. In contrast to recent approaches that transfer the entire knowledge from the unsupervised model to the supervised one, we argue that an effective transfer should only retain the relevant semantics that align well with the supervised task. In this paper, we propose a novel framework named DisenSemi, which learns disentangled representation for semisupervised graph classification. Specifically, a disentangled graph encoder is proposed to generate factor-wise graph representations for both supervised and unsupervised models. Then we train two models via supervised objective and mutual information (MI)-based constraints respectively. To ensure the meaningful transfer of knowledge from the unsupervised encoder to the supervised one, we further define an MI-based disentangled consistency regularization between two models and identify the corresponding rationale that aligns well with the current graph classification task. Experimental results on a range of publicly accessible datasets reveal the effectiveness of our DisenSemi.

Index Terms—Graph Neural Networks, Semi-supervised Graph Classification, Disentangled Representation Learning.

# I. INTRODUCTION

**G** RAPHS are among the most versatile data structures in many real-world multimedia applications across various domains, e.g., biology networks [1], molecule structures [2], citation networks [3], social networks [4] and recommender system [5], etc. For graph-structured data, one fundamental task is graph classification, which endeavors to capture the property of the entire graph and has become an important research hot spot in numerous multimedia tasks, including

Yifan Wang is with School of Information Technology & Management, University of International Business and Economics, Beijing, 100029, China. (yifanwang@uibe.edu.cn)

Xiao Luo is with Department of Computer Science, University of California, Los Angeles, 90095, USA. (xiaoluo@cs.ucla.edu)

Chong Chen and Xian-Sheng Hua are with Terminus Group, Beijing 100027, China. (chenchong.cz@gmail.com, huaxiansheng@gmail.com)

Ming Zhang is with School of Computer Science, National Key Laboratory for Multimedia Information Processing, Peking University-Anker Embodied

AI Lab, Peking University, Beijing, 100871, China. (mzhang\_cs@pku.edu.cn) Wei Ju is with College of Computer Science, Sichuan University, Chengdu, 610064, China. (juwei@pku.edu.cn)

The paper is supported by "the Fundamental Research Funds for the Central Universities" in UIBE (Grant No. 23QN02) and National Natural Science Foundation of China (NSFC Grant Numbers 62306014 and 62276002).

Corresponding author: Wei Ju

Manuscript received April 19, 2021; revised August 16, 2021.



Fig. 1: Illustration of the molecular complicated annotating procedure. It takes around four to five hours to compute the characteristics of the molecule, which fully demonstrates the graph label scarcity in reality.

chemical compound prediction [2], text categorization [6] and social network analysis [4].

To tackle the graph classification problem, many machine learning-based methods are proposed. Graph kernel methods leverage structural patterns such as shortest paths [7], subtrees [8], subgraphs [9] and graphlets [10] to measure the similarity among graphs and pass the similarity matrix to a kernel-based supervised algorithm such as the Support Vector Machine (SVM) to perform classification. Instead of hand-crafted feature extraction in graph kernel methods, more recently, graph neural networks (GNNs) can extract graph structural features in a supervised end-to-end manner. Despite the better performance, GNNs always require a large amount of labeled data, which is highly expensive and time-consuming in the real world [11]. For example, as demonstrated in Fig. 1, the label of a chemical compound is typically produced with a costly Density Functional Theory (DFT) calculation or several complicated experiments.

In practice, there always exist massive unlabeled graph samples. Although labels of these graphs are unavailable, the inherent knowledge of the graph may help to enhance GNNs' encoding more expressive and discriminative. Semi-supervised classification methods combine both supervised and unsupervised models where the unsupervised model learns from unlabeled data and can serve as a regularizer. Indeed, there are a handful of semi-supervised works proposed for graph classification, which can be divided into several categories, i.e., pseudo-labeling [12]-[14], consistency learning [2], [15]-[20]. Especially for consistency learning, methods like Info-Graph [16] and GraphSpa [20] jointly learn supervised and unsupervised models from labeled and unlabeled data. Meanwhile, a popular fashion (i.e., GraphCL [15] and JOAO [17]) has been developed recently which first pre-trains the unsupervised model with unlabeled data and then fine-tunes the model with labeled data.

However, these existing semi-supervised graph classification methods still remain unsatisfactory due to the following limitations. (1) Neglect the entanglement of latent factors. The formation of graphs in the real world typically stems from the highly complex interaction of different latent factors. For example, a molecular graph may consist of various groups of atoms and bonds representing different functional units [21]. Existing works often neglect the entanglement of latent factors and the extracted features are holistic, which harms interpretability and leads to sub-optimal performance for the graph classification task. (2) Mismatch semantics between supervised and unsupervised tasks. Supervised and unsupervised tasks on labeled and unlabeled graph data may capture different information or occupy separate semantic spaces, corresponding to distinct graph factors. Simply combining two tasks may lead to a "negative transfer" [22]. Therefore, we argue that a more efficient way is to disentangle the graph representation learned from unsupervised tasks into distinct latent factors and transfer the corresponding factor-wise information well aligned to semantically enhance the supervised task for semisupervised graph classification.

Recently, disentangled representation learning has gained much attention, aiming at learning factorized representations that are capable of uncovering information about the salient (or explanatory) properties of the data. Moreover, disentangled representations have been demonstrated to be more generalizable and resilient to complex variants, i.e., the learned factors are supposed to be independent and less sensitive to the noises from other factors in the limited observed training data [23]. For graph-structured data, where multiple heterogeneous relations are always mixed and collapsed into one graph, disentangled representation learning tails to decompose underlying relations and is mainly focused on the supervised link prediction tasks (i.e., recommender systems [5], [24]), supervised graph classification tasks [25], [26] and unsupervised graph generation/identification process [27], [28]. However, the semi-supervised method of bridging the supervised and unsupervised tasks remains largely unexplored.

Toward this end, in this paper, we propose DisenSemi, a novel Disentangled graph representation learning framework for **Semi**-supervised graph classification, which is capable of enhancing the supervised prediction task with the unsupervised representation learning tasks semantically. In contrast to existing works that directly utilize an entangled representation learned from a large amount of unlabeled data for prediction, our proposed approach emphasizes regularizing the rationale to explicitly exploit transferable factor information between supervised and unsupervised tasks. In particular, we design a disentangled graph encoder by characterizing the globallevel topological semantics, during which the whole graph is first decomposed into factor graphs. Then the factor-wise interpretable graph representation is produced via the multichannel message-passing layer, where each channel is tailored to propagate features under one factor graph and a separate readout operation in each channel summarizes the specific aspect of the graph. For labeled data, we train the model using a supervised objective function while for unlabeled data,

the model is trained with MI-based constraints for the input factorized graph and its corresponding features to ensure the disentanglement. Next we conduct MI maximization between the supervised and unsupervised models under each latent factor instead of in the whole feature space for disentangled consistency regularization. Compared with the existing works, this novel factor-wise MI estimation strategy can ensure the regularized factor is best pertinent to the aspect bridging supervised and unsupervised models for the current semisupervised graph classification task. More importantly, we demonstrate that our framework can be formalized as a problem of maximizing the log-likelihood solved by Expectation Maximization (EM).

To summarize, in this paper we make the following contributions:

- *Conceptual:* We propose a novel disentangled representation learning framework for semi-supervised graph classification, which explicitly models the rationale factor that fits well between supervised and unsupervised learning tasks. And the proposed mechanism can be potentially generalized to other semi-supervised learning tasks.
- *Methodological:* We propose a graph disentangled encoder that produces factor-wise graph representations under decomposed factor graphs. Moreover, different MI-based constraints and consistency regularization are proposed to capture the characteristic differences and the connections between supervised and unsupervised learning models.
- *Experimental:* We conduct extensive experiments on a variety of public datasets to evaluate the DisenSemi. Experimental results demonstrate the efficiency and outstanding interpretability of our proposed framework for semi-supervised graph classification tasks.

## II. RELATED WORK

# A. Semi-supervised Graph Classification

Semi-supervised learning has received growing attention in recent years. It is associated with a learning paradigm that uses both labeled and unlabeled data and encompasses two prominent techniques. The first line is the consistency regularization methods, which are based on the manifold or smoothness assumption and posit that realistic perturbations of the data points should not change the output of the model. The most common structure is Teacher-Student, consisting of two models called student and teacher and applying a consistency constraint between the two predictions of student and teacher [29]–[31]. The second line is pseudo-labeling methods, which predict the label distribution of unlabeled samples and select confident samples to provide further guidance during the training process [32], [33].

For graph-structured data, there are also attempts using consistency regularization [14]–[16], [18], pseudo-labeling [12], [13], [34], [35] or other approaches [20], [36]–[39] for semisupervised learning. Typically, InfoGraph [16] learns supervised and unsupervised model respectively and estimates the MI between two models. GraphCL [15] and GLA [14] use contrastive learning to get graph representations for semi-supervised graph classification. DualGraph [13] and UGNN [35] jointly learn a prediction and a retrieval module via posterior regularization during the pseudo-labeling process. GraphSpa [20] actively selects informative graphs for subsequent model training using a hybrid selection strategy. However, these approaches fail to disentangle the diverse underlying factors behind the graph data, making it challenging to identify suitable alignments between supervised and unsupervised models.

### B. Disentangled Representation Learning

Disentangled representation learning aims to acquire factorized representations capable of discerning and separating the latent explanatory factors concealed within the observed data [23]. By achieving such a disentangled representation, the model gains a deeper understanding of the intricate dependencies within the data, facilitating more insightful and meaningful analysis or manipulation of the underlying factors. Existing efforts about disentangled representation learning are mainly on computer vision [40], [41], natural language processing [3], [42] and recommendation [24], [43], [44].

Recently, there has been a notable surge of interest in applying disentangled representation learning techniques to graph-structured data [5], [25]-[27]. DisenGCN [25] learns disentangled node representation through a neighborhood routing mechanism to divide the neighborhood of the node into several mutually exclusive parts. DisenHAN [5] learns disentangled representation in Heterogeneous Information Network (HIN) to iteratively identify the major aspect of the relation between node pairs and propagate corresponding information semantically. FactorGCN [26] takes the whole graph as input and produces block-wise interpretable graph-level features for classification. DGCL [27] proposes a self-supervised graph disentangled representation framework via contrastive learning method. UMGRL [28] provides a self-supervised disentangled representation learning method for the multiplex graph to capture common and private graph information. Our work focuses on learning disentangled representation for semi-supervised graph classification. And our primary objective is to design a framework where a supervised model can learn from an unsupervised model through the latent semantic space that aligns well with the current graph classification task.

## III. PROBLEM DEFINITION AND PRELIMINARIES

# A. Problem Definition

**Definition 1** (Graph). A graph is formally defined as G = (V, E, X), where V and  $E \in V \times V$  are the node set and edge set of the graph respectively. We denote the node feature matrix as  $X \in \mathbb{R}^{|V| \times d'}$ , where each row  $x_i \in \mathbb{R}^{d'}$  represents the feature vector of node i and d' is the dimension of node feature. A graph is typically labeled if it is associated with a class label  $y \in \{0, 1\}^C$ , where C is the number of classes. A graph is unlabeled if its class label is unknown.

**Definition 2** (Semi-supervised Graph Classification). Given a set of graphs  $\mathcal{G} = \{\mathcal{G}^L, \mathcal{G}^U\}$ , where  $\mathcal{G}^L = \{G_1, \ldots, G_{|\mathcal{G}^L|}\}$ and  $\mathcal{G}^U = \{G_{|\mathcal{G}^L|+1}, \ldots, G_{|\mathcal{G}^L|+|\mathcal{G}^U|}\}$  represent labeled and unlabeled graphs respectively. Let  $\mathcal{Y}^L = \{y_1, \ldots, y_{|\mathcal{G}^L|}\}$ represents the label corresponding to  $\mathcal{G}^L$ . Semi-supervised graph classification seeks to learn a prediction function that can assign class labels to unlabeled graph data in  $\mathcal{G}^U$  based on the available class labels in  $\mathcal{G}^L$ .

#### B. Preliminaries

**Preliminary 1** (MI Estimation). MI is a fundamental measurement of the dependence between two random variables, which has been applied to a wide range of tasks [41], [45]. However, estimation MI is intractable especially in high dimensional continuous settings. Since earlier non-parametric binning methods perform poor, a neural estimator MINE [46] formates MI between x and y as Kullback-Leibler (KL)-divergence between the joint distribution  $p_{xy}$  and the product of the marginals  $p_x \otimes p_y$ ,

$$I_{KL}(x,y) := D_{KL}(p_{xy}||p_x \otimes p_y), \tag{1}$$

and derive a lower bound of MI with dual representations of KL-divergence. Following previous works [16], [45], we can further rely on non-KL divergence (i.e., Jensen-Shannon divergences) as an alternative for the MI estimator.

$$I_{JS}(x,y) = \mathbb{E}_{p_{xy}}[-T(x,y)] - \mathbb{E}_{p_x \otimes p_y}[\log(1 - T(x,y))],$$
(2)

where  $T(\cdot, \cdot)$  is a critic (or score) function approximated by a neural network. In this way, the loss can be seen as a standard binary cross-entropy (BCE) loss between the samples from the joint (a.k.a. positive examples) and the product of marginals (a.k.a. negative examples).

**Preliminary 2** (MI and Contrastive Learning). More recently, InfoNCE [47] propose a Noise Contrastive Estimation (NCE [48])-based MI lower bound, defined as:

$$I_{NCE}(x,y) := \mathbb{E}\Big[\frac{1}{N}\sum_{i=1}^{N}\log\frac{\exp^{T(x_i,y_i)}}{\frac{1}{N}\sum_{j=1}^{N}\exp^{T(x_j,y_j)}}\Big], \quad (3)$$

where the expectation is over N samples  $\{(x_i, y_i)\}_{i=1}^N$  drawn from the joint distribution  $p_{xy}$ . And contrastive learning encourages learning the model where representations between positive samples are pulled closer (e.g., graph representations corresponding to the same factor bridging supervised and unsupervised tasks) and representations among negative samples are pushed apart.

## IV. THE PROPOSED MODEL

#### A. Overview

For semi-supervised graph learning, the objective is to smooth the label information over graph data with regularization. And a straightforward way for the objective is to combine the purely supervised loss and the unsupervised objective function. Formally, previous semi-supervised learning frameworks try to minimize the following objective function:

$$L_{total} = \sum_{i=1}^{|\mathcal{G}^{L}|} L_{S}(G_{i}, y_{i}) + \lambda \sum_{j=1}^{|\mathcal{G}|} L_{U}(G_{j}), \qquad (4)$$

where  $L_S$  denotes the supervised loss that measures the discrepancy between the supervised model prediction and the real label of the graph data,  $L_U$  denotes the unsupervised loss



Fig. 2: A schematic view of the DisenSemi, which consists of a supervised and an unsupervised model. We extract factorwise graph representations of two models and maximize the agreement under each latent factor.

acting as a regularization term and  $\lambda$  is the relative weight between two losses.

However, we argue that supervised and unsupervised tasks have different optimization targets, which correspond to different semantic spaces of the graph data. Thus, we propose DisenSemi for semi-supervised graph classification. The basic idea is to explicitly infer the latent factors underlying a large amount of unlabeled graph data and transfer the well-aligned knowledge to enhance the supervised task in a factor-wise manner. As shown in Fig. 2, our framework is composed of a supervised model and an unsupervised model, where graph-level representations of both models are learned via the GNN-based encoder. Given the graph data, the GNN-based encoder first factorizes the input graph into several factor graphs, then gets graph representation by propagating and aggregating features on the corresponding factor graph. For the supervised model, we merge all the extracted factor graph representations to predict graph labels. For the unsupervised model, we introduce several MI-based constraints among factorized graphs and their corresponding extracted representations. Finally, a disentangled consistency regularization is conducted to explicitly identify the rationale between the two models and transfer the learned knowledge semantically via factor-wise MI maximization. The process is equivalent to a Variational EM algorithm maximizing the log-likelihood.

# B. GNN-based Encoder

GNNs have recently emerged as effective approaches for learning graph-structured data. Prevailing GNNs for learning graph representations are based on the neural message passing among nodes to update their features and utilize a readout function to get the graph-level representation. However, we argue that these methods are holistic and neglect the hidden factors stemming from different aspects. In fact, multiple heterogeneous relations between nodes are mixed together and collapsed into one single edge, and these relations correspond to multiple aspects of discriminant features of the graph. Thus, given input graph  $G_i$ , we factorize it into K factor graphs  $\{G_{ik}\}_{k=1}^{K}$  to separately encode their features. Specifically, for each edge  $e_m = \{x_u, x_v\}$  in edge set  $E(G_i) = \{e_1, \ldots, e_M\}$ , where M is the total edge of graph  $G_i$ , we project the node feature  $x_v \in \mathbb{R}^{d'}$  with a transformation matrix  $W \in \mathbb{R}^{d \times d'}$ and generate the factor coefficients as follows:

$$E_{uvk}(G_i) = \frac{1}{1 + \exp^{-\Psi_k(Wx_u, Wx_v)}},$$
 (5)

where  $\Psi_k$  is the function that takes the features of node u and v as input to compute the attention score of edge  $e_m$  under factor k, and the function can be implemented via a multilayer perceptron (MLP). Following that, the attention score is normalized to get  $E_{uvk}(G_i)$ , representing the coefficient of edge  $e_m$  contained in the factor graph  $G_{ik}$ .

We represent each factor graph by its own edge coefficient  $E_{uvk}(G_i)$ . By stacking L message passing layers, the node embedding of each node v in  $G_{ik}$  is updated by recursively aggregating and combining its neighborhood features. Formally, the embedding of node v in l-th layer is calculated as follows:

$$h_{N(v)}^{(l)}(G_i) = \mathcal{A}_k^{(l)} \left( \{ h_{uk}^{(l-1)}(G_i), \forall u \in N(v) \}, E_{uvk}(G_i) \right), \\ h_{vk}^{(l)}(G_i) = \mathcal{C}_k^{(l)} \left( h_{vk}^{(l-1)}(G_i), h_{N(v)}^{(l)}(G_i) \right), \\ h_{vk}^{(0)}(G_i) = W_k x_v,$$

$$(6)$$

where N(v) denotes the neighborhood of node v,  $\mathcal{A}_k^{(l)}$  represents the aggregation operation corresponding to the coefficient  $E_{uvk}(G_i)$  as edge weight for factor graph  $G_{ik}$ , and  $\mathcal{C}_k^{(l)}$  represents the combination operations at layer l. In this paper, we adopt GraphConv [49] as our message passing layer due to its powerful expression ability and initialize the node embedding of each factor graph via a factor-specific transformation matrix  $W_K \in \mathbb{R}^{\frac{d}{K} \times d'}$ .

Finally, for each factor graph  $G_{ik}$ , the graph-level representations can be attained by aggregating all node embeddings of the last L layer with a readout function. Formally,

$$z_k(G_i) = \operatorname{READOUT}(\{h_{vk}^{(L)}(G_i)\}_{v \in V(G_i)}), \qquad (7)$$

where  $V(G_i)$  is the node set of  $G_i$ , READOUT can be a simple permutation invariant function such as the mean function. By considering all the hidden factors of graph data, we can get a factor-wise graph representation, namely,  $Z_{G_i} = [z_1(G_i), \ldots, z_K(G_i)].$ 

# C. Supervised Loss

With the GNN-based encoder in the supervised task, a factor-wise representation  $Z_{SG_i} = [z_{S1}(G_i), \ldots, z_{SK}(G_i)]$  is extracted from labeled data, where different factor graphs will result in different features of the graph. Towards this end, we introduce K learnable factor prototypes  $C = \{c_k\}_{k=1}^{K}$  to obtain the attention weight  $\alpha_{G_{ik}}$  over latent factors for the input  $G_i$ :

$$\alpha_k(G_i) = \operatorname{Softmax}(\phi(z_{Sk}(G_i), c_k)), \tag{8}$$

where  $\phi$  is the similarity function, i.e., cosine similarity. After that, we weighted sum all latent factors to get the graph representation and fed it into a label prediction model to get the corresponding output, as shown in Fig. 3(b).

$$Z'_{SG_i} = \sum_{k=1}^{K} \alpha_k(G_i) \cdot z_{Sk}(G_i),$$
  

$$\hat{y}_i = \text{Softmax}(\text{MLP}(Z'_{SG_i})),$$
(9)

5



Fig. 3: Illustration of the supervised and unsupervised training module. We assume that there are three aspects for the input graphs and factorize them into different factor graphs. For the unsupervised module, we maximize the intra-factor, and minimize the inter-factor MI to disentangle the graph representation effectively. Unlike MI-based constraints in the unsupervised module, we merge all extracted factor-wise graph representations to predict graph labels in the supervised module.

where we adopt a two-layer MLP to map the graph representation extracted from different factor graphs to label predictions. For the supervised loss, we adopt cross-entropy, which can be defined as follows:

$$L_S = -\sum_{c=1}^{C} y_{ic} \log \hat{y}_{ic},$$
 (10)

where  $y_i \in \mathbb{R}^C$  is the label with the one-hot encoding of the input graph data  $G_i$ , and C corresponds to the number of graph categories in the dataset.

## D. MI-based Representation Disentanglement

For unsupervised learning, we can also get a factor-wise graph representation  $Z_{UG_i} = [z_{U1}(G_i), \ldots, z_{UK}(G_i)]$  via the GNN-based encoder. Since some of the decomposed factor graphs may contain a similar structure without any other constrain, we propose several MI-based constraints to effectively disentangle the graph representation, as shown in Fig. 3(a).

1) Intra-factor MI: As each factor graph corresponds to an interpretable relation between nodes, we seek to obtain the discriminant representation that captures the global content of the graph. Inspired by the deep InfoMax [45], we maximize the MI between the decomposed factor graph and the corresponding graph-level representation. For factor k, we define the intra-factor MI on global-local pairs, maximizing the estimated MI over all the nodes in factor graph  $G_{ik}$ , which is shown as:

$$L_{intra}^{k} = \frac{1}{|V|} \sum_{v \in V(G_i)} -I(z_{Uk}(G_i), h_{vk}^{(L)}(G_i)), \quad (11)$$

where  $I(z_{Uk}(G_i), h_{vk}^{(L)}(G_i))$  is the MI estimator modeled by discriminator  $D_k$  and parameterized by a neural network. We use the binary cross-entropy (BCE) loss between samples from

the joint (a.k.a., positive example) and product of marginals (a.k.a., negative examples) as the objective:

$$-I(z_{Uk}(G_i), h_{vk}^{(L)}(G_i)) = \log \sigma(D_k(z_{Uk}(G_i), h_{vk}^{(L)}(G_i))) + \mathbb{E}_{p \otimes \tilde{p}} \Big[ \log \big( 1 - \sigma(D_k(z_{Uk}(G_i), h_{vk}^{(L)}(\tilde{G}_i))) \big) \Big],$$
(12)

where  $h_{vk}^{(L)}(\tilde{G}_i)$  is generated by the negative input graph  $\tilde{G}_i$  sampled from a distribution  $\tilde{p} = p$ , which is identical to the empirical probability distribution of the input space. In practice, we could sample negative samples by an explicit (stochastic) corruption function or directly sample negative graph instances in a batch.

2) Inter-factor MI: For graph representations  $Z_{UG_i}$  extracted from different factor graphs, the MI between every two of them reaches its minimum value zero when  $p(z_{Uk}(G_i), z_{Uk'}(G_i)) = p(z_{Uk}(G_i))p(z_{Uk'}(G_i)),$  which means that  $z_{Uk}(G_i)$  and  $z_{Uk'}(G_i)$  are independent to each other. Thus, MI minimization among them encourages the factor-wise graph representation to learn different aspects of information for the graph. Recently, several MI upper bounds [50], [51] have been introduced for MI minimization. However, the estimation MI upper bound among these Kgraph representations requires K(K-1) times estimation, resulting in far more costs especially when K is large. To alleviate this problem, as orthogonality can be seen as a special case of linear independence among representations, we loosen the constraint of minimization MI to orthogonality and the method has also been demonstrated to be effective by many previous studies [52]:

$$L_{inter} = |Z'_{UG_i}^{T} Z'_{UG_i} - I|,$$
  

$$Z'_{UG_i} = z_{U1}(G_i)||\dots||z_{UK}(G_i),$$
(13)

where  $|\cdot|$  is the  $L_1$  norm, I is the identity matrix, || is the concatenation operation.

*Remark:* In our model, we have also tested other MI minimization methods, such as Contrastive Log-ratio Upper Bound (CLUB) [51], which estimates MI by the difference of log-ratio of conditional distribution between positive and negative sample pairs. And these methods do not bring much change to the performance.

We maximize the MI between the factor graph and its corresponding graph representation to characterize each hidden factor while minimizing the MI among different factor graph representations for one input graph to enforce representation disentanglement. Formally, unsupervised loss of DisenSemi can be formulated as:

$$L_U = \sum_{k=1}^{K} L_{intra}^k + L_{inter}.$$
 (14)

## E. Disentangled Consistency Regularization

For transferring the learned disentangled graph representations from the unsupervised encoder to the supervised encoder, we encourage representations extracted from two encoders with high MI when they correspond to the same factor of one graph data bridging supervised and unsupervised tasks. Specifically, we maximize NCE-based MI lower bound [47], which aims at making similar representations closer and different instances far away from each other. We treat each representation of a graph data instance as a distinct class and distinguish it from representations extracted from other graph data instances. Formally, given graph dataset  $\mathcal{G} = \{G_i\}_{i=1}^{|\mathcal{G}^L|+|\mathcal{G}^U|}$ , we assign each graph  $G_i$  with a unique surrogate label  $s_i = i$ . Different from the ground-truth label  $y_i$  of the labeled graph data,  $s_i$  can be seen as the ID of the corresponding graph in the dataset  $\mathcal{G}$ . And in this way, the MI can be defined as:

$$I_{NCE}(Z_{SG_i}, Z_{UG_i}) := \log p(s_i | G_i) = \log \mathbb{E}_{p(k|G_i)}[p(s_i | G_i, k)],$$
(15)

where  $p(s_i|G_i)$  corresponding to the identify discrimination over dataset,  $p(k|G_i)$  is the probability distribution of the *k*-th latent factors reflected in  $G_i$ , namely, can be  $\alpha_k(G_i)$ . And  $p(s_i|G_i, k)$  corresponding to the identify discrimination subtask under *k*-th latent factor defined as:

$$p(s_i|G_i, k) = \frac{\exp \phi(z_{Sk}(G_i), z_{Uk}(G_i))}{\sum_{j=1}^{|\mathcal{G}|} \exp \phi(z_{Sk}(G_i), z_{Uk}(G_j))}, \quad (16)$$

where the subtask is over all graphs in the dataset.  $\phi$  is the similarity function, adopting cosine similarity in our paper.

In effect, it is non-trivial to maximize the log-likelihood over the whole graph dataset due to the latent factors, where we need to calculate the posterior distribution defined with Bayes' theorem as follows:

$$p(k|G_i, s_i) = \frac{p(k|G_i)p(s_i|G_i, k)}{\sum_{k=1}^{K} p(k|G_i)p(s_i|G_i, k)}.$$
 (17)

Compared with prior distribution  $p(k|G_i)$  that inferred only given the graph  $G_i$ ,  $p(k|G_i, s_i)$  is the probability of the kth latent factor effectively aligning both the supervised and unsupervised models when applied to the same graph data. However, it is prohibitive to compute posterior probability due to the term  $p(s_i|G_i, k)$  in Eq. 16, which needs all the instances in the dataset for computing the denominator. Therefore, we alternatively maximize the evidence lower bound (ELBO) of the log-likelihood, which is defined as:

$$\log p(s_i|G_i) \ge L_{ELBO} := \mathbb{E}_{q(k|G_i, s_i)}[\log p(s_i|G_i, k)] - D_{KL}(q(k|G_i, s_i), p(k|G_i)),$$
(18)

where  $q(k|G_i, s_i)$  is a variational distribution to approximate the posterior probability  $p(k|G_i, s_i)$ . Here, we formalize the variational distribution by:

$$q(k|G_i, s_i) = \frac{p(k|G_i)\tilde{p}(s_i|G_i, k)}{\sum_{k=1}^{K} p(k|G_i)\tilde{p}(s_i|G_i, k)},$$
(19)

where  $\tilde{p}(s_i|G_i, k)$  can be defined with NT-Xent loss [53] on a minibatch  $\mathcal{B} \subseteq \mathcal{G}$  of graph data:

$$\tilde{p}(s_i|G_i,k) = \frac{\exp\phi(z_{Sk}(G_i), z_{Uk}(G_i))}{\sum_{j\in\mathcal{B}, j\neq i}^{|\mathcal{B}|} \exp\phi(z_{Sk}(G_i), z_{Uk}(G_j))}.$$
 (20)

Notice that the process is a variation of the Variational EM algorithm, where we infer  $q(k|G_i, s_i)$  at the E-step and optimize the ELBO at the M-step.

#### F. Optimization and Complexity Analysis

1) Optimization: We combine the supervised classification loss  $L_S$ , unsupervised loss  $L_U$  as well as consistency regularization loss  $L_{ELBO}$  together. And the overall objective for our semi-supervised graph classification is defined as:

$$L_{total} = \sum_{i=1}^{|\mathcal{G}^L|} L_S + \lambda \sum_{j=1}^{|\mathcal{G}|} L_U - \gamma \sum_{j=1}^{|\mathcal{G}|} L_{ELBO}, \qquad (21)$$

where  $\lambda$  is the relative weight between losses,  $\gamma$  is a tunable weight for consistency regularization loss.

2) Complexity Analysis: To ensure scalability with largescale datasets, we leverage mini-batch with size  $B = B^L + B^U$ to compute gradients. The computational consumption is mainly composed of three parts: (i) the unsupervised module; (ii) the supervised module; (iii) the disentangled consistency regularization. Given the graph with an average number of nodes |V| and edges |E|, the number of GNN layer and factor graphs is L and K, and the representation dimension is d. For (i) and (ii), the time complexity of the GNNbased encoder O(|E|Ld). For (i), the additional computational complexity of intra-factor and inter-factor MI constraints is O(|V|d) and O((K-1)d/2) respectively. For (ii), the additional computational complexity of the label prediction model is  $O(d + (d/K)^2 + Cd/K)$  with C classes in the task. For (iii), we perform disentangled consistency regularization within minibatch, which takes O(Bd) for each graph. To sum up, we have the overall complexity of DisenSemi,  $O((2|E|L + |V| + (K + 1)/2 + d/K^2 + C/K + B)d),$ which scales linearly in terms of the number of nodes and edges in each graph instance. Moreover, DisenSemi requires K factor graphs, prototypes and coreresponding GNN-based encoder in both supervised and unsupervised module, the space complexity is O((|V| + |E|)Ld + d + K|E|).

# V. EXPERIMENT

We introduce the experimental settings and conduct extensive experiments on ten real-world benchmark datasets to validate the effectiveness of our proposed DisenSemi. We focus on answering the following research questions:

- **RQ1:** How does our proposed model DisenSemi perform compared with other state-of-the-art models for semisupervised graph classification?
- **RQ2:** Is it necessary to keep key components of DisenSemi (i.e. GNN-based encoder, MI-based representation disentanglement and consistency regularization)?
- **RQ3:** How do different hyper-parameters in DisenSemi impact the performance?
- **RQ4:** Can DisenSemi ensure the regularized factor pertinent to the aspect bridging supervised and unsupervised tasks semantically?

#### A. Experimental Settings

1) Datasets and Baselines: We apply our model to ten public accessible graph classification benchmark datasets<sup>1</sup> following the previous works [14], [16], which includes four molecule datasets: MUTAG, PTC-MR, NCI1 and OGB-HIV, one bioinformatic dataset: PROTEINS and five social network datasets: IMDB-BINARY (IMDB-B), IMDB-MULTI (IMDB-M), REDDIT-BINARY (REDDIT-B), REDDIT-MULTI-5K (REDDIT-M5K) and COLLAB. Following recent works [15], [16], we adopt one-hot degree and centrality features instead when node attributes are not available in the datasets. We compare our proposed DisenSemi with sixteen recent proposed baselines including seven traditional graph classification approaches: GK [10], SP [7], WL [8], MLG [9], DGK [54], Sub2Vec [55] and Graph2Vec [56] and nine GNN-based semi-supervised graph classification methods: MVGRL [57], GraphCL [15], JOAO [17], DGCL [27], RGCL [58], Info-Graph [16], GLA [14], TGNN [18], GraphSpa [20].

2) Evaluation Protocol: We evaluate the models with 10fold cross-validation. Following the recent works [14]–[16], we randomly shuffle and split each dataset into 10 parts. Each fold corresponds to one part of data as the test set, another part as the validation set and the rest parts as train set. Then we select 30% graphs from the training set as labeled graphs for each fold and conduct semi-supervised learning. The results are computed by the mean accuracy (%) with standard variation after ten repeated runs.

3) Implementation Details: We implement our DisenSemi model in Pytorch. For all datasets, the embedding size of DisenSemi and other baselines (except GK, SP, WL, MLG) is fixed to 128. Since the ground-truth number of the latent factors is unknown, we search the number of factor graphs K amongst  $\{2^0, 2^1, 2^2, 2^3, 2^4\}$ , corresponding embedding dimensions are  $\{128, 64, 32, 16, 8\}$  per factor graph. We set three message passing layers for our method and the hyperparameters  $\lambda = 0.001, \gamma = 0.001$ . We optimize DisenSemi with Adam optimizer by setting the learning rate to 0.005 and

the number of epochs is set to 200 for all the methods. For all the traditional graph classification approaches, we compute similarities between graphs and feed them into a downstream Support Vector Machines (SVM) classifier to evaluate the classification accuracy. For MVGRL, GraphCL, JOVO, DGCL and RGCL, we pre-train the model with unlabeled graphs first and fine-tune the model with the labeled graphs. For InfoGraph, GLA, TGNN, GraphSpa and our proposed DisenSemi, we integrate the pre-training and fine-tuning phases together. The source code of DisenSemi is available at https: //github.com/jamesyifan/DisenSemi.

#### B. Performance Comparison (RQ1)

1) Overall Comparison: We present the quantitative results of semi-supervised graph classification with 30% label ratio in Table I. According to the results, the following observations can be derived.

- Traditional graph classification approaches, which include graph kernel and unsupervised graph-level representation learning methods, perform worse than GNN-based semisupervised graph classification methods. This indicates that hand-crafted features extracted by traditional methods suffer from poor generalization. Instead, GNN-based methods are more powerful to extract features from graph-structured data for the semi-supervised graph classification task.
- Among GNN-based semi-supervised graph classification methods, DGCL and RGCL, which leverage disentangled representation for graph classification, always achieve better performance than other baselines on most datasets. It shows that explicitly considering the entanglement of factors for a graph helps to learn better representation for semisupervised graph classification.
- Our model DisenSemi achieves the best performance on all ten datasets, which significantly demonstrates the effectiveness of our proposed model. From the results, we deem that the improvement over state-of-the-art methods not only from learning disentangled representation of the graph, but also from explicitly regularizing the rationale that fits well between supervised and unsupervised learning models for semi-supervised graph classification.

2) Performance on Different Labeling Ratio: We vary the labeling ratio of training data to show the performance of different models. Here we omit the traditional methods since they do not have competitive performance. Fig. 4 illustrates the performance w.r.t. different labeling ratios of data on four datasets. We find that:

- The performance of all models generally improves as the number of available labeled data increases. This demonstrates that the labeling ratio of training data is an important factor of the model. Meanwhile, the growth is not linear, which means unsupervised data also plays a key role to boost the model performance.
- Disentangled graph representation model, i.e., DGCL and RGCL, though explicitly considering the entanglement of factors for graph, can not always guarantee the improvement over other baselines among different labeling ratios. This is attributed to the fact that supervised and unsupervised

<sup>&</sup>lt;sup>1</sup>https://ls11-www.cs.tu-dortmund.de/staff/morris/graphkerneldatasets; https://ogb.stanford.edu/docs/graphprop/

TABLE I: Performance comparison on ten benchmark datasets. We present the mean together with the standard deviation of prediction accuracy over ten runs (in %) using different random seeds. The results in bold indicate the best performance.

Methods	MUTAG	PTC-MR	NCI1	PROTEINS	IMDB-B	IMDB-M	REDDIT-B	REDDIT-M5K	COLLAB	OGB-HIV
GK	$82.9\pm2.1$	$56.7\pm2.6$	$64.7\pm0.2$	$67.8 \pm 1.0$	$57.9\pm0.7$	$43.9\pm0.4$	$68.4\pm0.5$	$27.1\pm0.6$	$62.3\pm0.6$	$94.1\pm0.4$
SP	$84.5 \pm 2.5$	$56.4 \pm 2.5$	$69.8\pm0.3$	$72.9 \pm 0.9$	$51.9 \pm 0.6$	$34.7\pm0.7$	$76.0 \pm 1.1$	$41.3 \pm 0.9$	$58.6 \pm 0.3$	$94.6\pm0.5$
WL	$86.8\pm2.1$	$58.2 \pm 2.8$	$76.2 \pm 0.3$	$73.5\pm0.6$	$69.2 \pm 1.0$	$45.3\pm0.8$	$67.7 \pm 1.1$	$44.7\pm0.8$	$74.3 \pm 0.2$	$94.3 \pm 0.6$
MLG	$83.5\pm1.9$	$58.8 \pm 2.2$	$63.0\pm0.6$	$72.3 \pm 1.1$	$49.9\pm0.3$	$38.8\pm0.6$	$72.7 \pm 0.9$	$35.3\pm0.8$	$56.5 \pm 0.1$	$94.8 \pm 0.5$
DGK	$82.9\pm2.6$	$59.3 \pm 2.5$	$78.8\pm0.6$	$73.7\pm0.7$	$69.9\pm0.7$	$46.6 \pm 1.0$	$78.7\pm0.6$	$48.6\pm0.1$	$77.4 \pm 0.2$	$95.0 \pm 0.4$
Sub2Vec	$75.0 \pm 2.7$	$57.6 \pm 2.2$	$58.7 \pm 1.5$	$63.8 \pm 1.2$	$56.1 \pm 0.7$	$35.0 \pm 1.1$	$68.9\pm0.7$	$34.0 \pm 0.6$	$58.3 \pm 0.5$	$94.4 \pm 0.6$
Graph2Vec	$74.9 \pm 1.4$	$59.2\pm2.1$	$70.6\pm0.3$	$70.1\pm0.9$	$63.7 \pm 1.1$	$50.4\pm0.7$	$76.6 \pm 1.0$	-	-	-
MVGRL	$88.8\pm0.7$	$69.5 \pm 1.5$	$72.6\pm0.5$	$73.6\pm0.8$	$74.5\pm0.7$	$50.7\pm0.6$	$90.0 \pm 0.2$	$53.1 \pm 0.4$	$77.8\pm0.2$	$95.6\pm0.4$
GraphCL	$89.4\pm0.8$	$70.0\pm1.6$	$77.4 \pm 0.3$	$76.1\pm0.6$	$74.0\pm0.5$	$50.3 \pm 0.5$	$91.7\pm0.2$	$57.2 \pm 0.6$	$79.1 \pm 0.3$	$95.8\pm0.5$
JOÃO	$91.0\pm0.7$	$70.6 \pm 1.3$	$77.8\pm0.3$	$76.7\pm0.8$	$75.2 \pm 0.8$	$50.8 \pm 0.5$	$91.8\pm0.3$	$57.4 \pm 0.2$	$79.6\pm0.1$	$96.4 \pm 0.3$
DGCL	$90.5\pm0.9$	$71.4 \pm 1.4$	$78.1 \pm 0.4$	$76.8\pm0.7$	$75.7\pm0.6$	$51.7 \pm 0.7$	$91.5\pm0.5$	$\overline{56.1 \pm 0.2}$	$80.3\pm0.4$	$96.4 \pm 0.2$
RGCL	$90.5 \pm 0.5$	$71.2 \pm 1.2$	$78.2 \pm 0.3$	$75.0 \pm 0.6$	$75.9\pm0.6$	$\overline{50.1 \pm 0.4}$	$91.1 \pm 0.4$	$56.4 \pm 0.3$	$79.4 \pm 0.3$	$96.3 \pm 0.4$
InfoGraph	$88.9 \pm 1.1$	$70.6 \pm 1.4$	$75.1 \pm 0.6$	$74.9\pm0.8$	$\overline{74.9\pm0.8}$	$51.5 \pm 0.6$	$92.0 \pm 0.4$	$56.9 \pm 0.5$	$79.8\pm0.5$	$95.6\pm0.3$
GLA	$91.6 \pm 1.0$	$70.6 \pm 1.7$	$77.0 \pm 0.5$	$77.1 \pm 0.6$	$75.8\pm0.6$	$51.1 \pm 0.5$	$92.2 \pm 0.3$	$56.7 \pm 0.2$	$80.2 \pm 0.2$	$96.8 \pm 0.3$
TGNN	$\overline{91.3 \pm 0.6}$	$68.3 \pm 1.4$	$75.2 \pm 0.7$	$76.4 \pm 1.0$	$75.1 \pm 0.7$	$50.9 \pm 0.5$	$\overline{91.5\pm0.5}$	$55.6 \pm 0.6$	$77.6 \pm 0.4$	$96.2 \pm 0.4$
GraphSpa	$91.5\pm0.9$	$70.2\pm1.3$	$77.2\pm0.5$	$76.5\pm0.8$	$75.4\pm0.6$	$51.2\pm0.6$	$91.9\pm0.6$	$56.0\pm0.5$	$78.9\pm0.3$	$95.9\pm0.4$
DisenSemi	$92.6 \pm 0.6$	$72.4 \pm 1.1$	$78.9 \pm 0.4$	$78.4 \pm 0.5$	$76.7 \pm 0.7$	$52.5 \pm 0.5$	$93.2\pm0.3$	$57.6 \pm 0.2$	$81.5 \pm 0.3$	$97.2 \pm 0.2$



Fig. 4: Performance comparison with different labeling ratios (i.e., %10, %30, %50 and %70) on four datasets (i.e., MUTAG, PROTEINS, IMDB-BINARY and REDDIT-BINARY).

TABLE II: Ablation study on GNN-based encoder with different types of message passing layer and \* means randomly removed 15% edges from the original graph to obtain different factor graphs.

Methods	MUTAG	PTC-MR	NCI1	PROTEINS	IMDB-B	IMDB-M	REDDIT-B	REDDIT-M5K	COLLAB	OGB-HIV
SAGEConv*	$89.1\pm0.4$	$68.4 \pm 1.2$	$75.8\pm0.5$	$74.7\pm0.5$	$75.8\pm0.8$	$51.9\pm0.5$	$91.2\pm0.4$	$56.5\pm0.3$	$80.6\pm0.4$	$95.6\pm0.5$
GATConv*	$89.6\pm0.3$	$69.2 \pm 1.3$	$75.2 \pm 0.6$	$74.1 \pm 0.3$	$75.6\pm0.8$	$51.6 \pm 0.6$	$92.1 \pm 0.4$	$56.8 \pm 0.3$	$80.4\pm0.3$	$95.8\pm0.5$
GINConv*	$90.2 \pm 0.5$	$68.9 \pm 1.1$	$75.2 \pm 0.4$	$74.7\pm0.4$	$76.1 \pm 0.9$	$52.2 \pm 0.5$	$92.3 \pm 0.3$	$56.9 \pm 0.2$	$79.3 \pm 0.2$	$96.0\pm0.3$
GraphConv*	$90.1\pm0.4$	$69.1 \pm 1.0$	$75.3\pm0.4$	$74.6\pm0.5$	$76.0\pm0.9$	$51.4 \pm 0.6$	$92.1\pm0.4$	$56.7 \pm 0.3$	$80.9\pm0.3$	$95.8\pm0.4$
GCNConv	$90.6\pm0.5$	$69.2 \pm 1.0$	$75.5\pm0.6$	$75.9\pm0.5$	$76.0\pm0.8$	$52.4 \pm 0.6$	$92.4 \pm 0.2$	$57.1 \pm 0.3$	$81.2\pm0.4$	$96.4 \pm 0.3$
GraphConv	$92.6 \pm 0.6$	$72.4 \pm 1.1$	$78.9 \pm 0.4$	$78.4 \pm 0.5$	$76.7 \pm 0.7$	$52.5 \pm 0.5$	$93.2\pm0.3$	$57.6 \pm 0.2$	$81.5\pm0.3$	$97.2 \pm 0.2$

learning tasks for graph-structured data have different optimization targets.

• DisenSemi consistently outperforms other baselines over the different labeling ratios of data. Especially when the labeled data is scarce (e.g. less than 70%), the superiority of our model indicates that disentangled graph representation with consistency regularization can effectively improve the semi-supervised classification performance.

## C. Ablation Studies (RQ2)

To deeply understand our proposed DisenSemi, we conduct ablation studies over the key components of the model.

1) Effect of GNN-based Encoder: In DisenSemi, we encode each factor graph via the proposed GNN with its own edge coefficient. To explore whether DisenSemi can derive benefits from the proposed GNN-based encoder, we compare five types of well-known GNN operators, namely SAGEConv [59], GATConv [60], GINConv [61], GCNConv [62] and Graph-Conv [49]. Notice that for SAGEConv\*, GATConv\* and GIN-Conv\*, we ignore the edge coefficient and randomly remove 15% edges to obtain different factor graphs. For GraphConv\*, we retain the edge coefficients and randomly remove edges separately. The performance of different GNN operators on all ten datasets is shown in Table II. We make the following observations from the results.

• In most cases, the performance of GCNConv is better than other variants, which ignore the edge coefficient and randomly remove edges to obtain different factor graphs (i.e., SAGEConv\*, GATConv\*, GINConv\*). This indicates that disentangling the graph with heterogeneous relations into different factor graphs can learn more effective and discriminative graph-level representation for the downstream

Methods	MUTAG	PTC-MR	NCI1	PROTEINS	IMDB-B	IMDB-M	REDDIT-B	REDDIT-M5K	COLLAB	OGB-HIV
w/o Intra-MI w/o Inter-MI w/o MI	$\begin{array}{c} 90.8 \pm 0.5 \\ 90.4 \pm 0.5 \\ 89.3 \pm 0.4 \end{array}$	$\begin{array}{c} 68.6 \pm 1.0 \\ 69.2 \pm 1.2 \\ 68.3 \pm 1.5 \end{array}$	$\begin{array}{c} 74.9 \pm 0.8 \\ 74.7 \pm 0.6 \\ 74.1 \pm 0.7 \end{array}$	$75.9 \pm 0.5$ $76.2 \pm 0.4$ $73.9 \pm 0.6$	$\begin{array}{c} 75.8 \pm 0.8 \\ 76.1 \pm 0.7 \\ 75.3 \pm 0.8 \end{array}$	$\begin{array}{c} 51.4 \pm 0.4 \\ 52.3 \pm 0.6 \\ 51.9 \pm 0.5 \end{array}$	$\begin{array}{c} 92.6 \pm 0.2 \\ 92.8 \pm 0.3 \\ 91.6 \pm 0.3 \end{array}$	$56.5 \pm 0.3$ $56.2 \pm 0.4$ $56.1 \pm 0.5$	$\begin{array}{c} 80.8\pm 0.4\\ 80.7\pm 0.5\\ 80.1\pm 0.4\end{array}$	$\begin{array}{c} 95.9 \pm 0.4 \\ 96.2 \pm 0.3 \\ 95.6 \pm 0.5 \end{array}$
Variant 1 Variant 2	$\begin{array}{c} 90.4 \pm 0.4 \\ 91.5 \pm 0.4 \end{array}$	$\begin{array}{c} 69.8 \pm 1.0 \\ 68.6 \pm 0.9 \end{array}$	$75.9 \pm 0.6$ $74.2 \pm 0.5$	$\begin{array}{c} 74.1 \pm 0.5 \\ 74.5 \pm 0.4 \end{array}$	$75.7 \pm 0.8$ $76.6 \pm 0.7$	$51.8 \pm 0.5$ $52.3 \pm 0.7$	$\begin{array}{c} 91.5 \pm 0.2 \\ 92.0 \pm 0.2 \end{array}$	$56.3 \pm 0.5 \\ 56.4 \pm 0.4$	$\begin{array}{c} 80.3 \pm 0.3 \\ 80.8 \pm 0.4 \end{array}$	$\begin{array}{c} 96.2 \pm 0.3 \\ 96.5 \pm 0.2 \end{array}$
DisenSemi	$92.6 \pm 0.6$	$72.4 \pm 1.1$	$78.9 \pm 0.4$	$78.4 \pm 0.5$	$76.7 \pm 0.7$	$52.5 \pm 0.5$	$93.2\pm0.3$	$57.6 \pm 0.2$	$81.5 \pm 0.3$	$97.2 \pm 0.2$

TABLE III: Ablation study on MI-based representation and disentanglement consistency regularization, w/o means remove the module from DisenSemi and Variant means different distribution of latent factors.

classification task.

• GraphConv\* considers the high-order structure of the factor graph but still exhibits poor performance in cases where edges are randomly removed. Instead, GraphConv consistently outperforms other models when considering the edge coefficient. This outcome further validates the effectiveness of the learned edge coefficient within each factor graph for capturing higher-order graph structures.

2) Effect of MI-based Representation Disentanglement: As disentangled graph representation is implemented via MI estimation in our DisenSemi, we investigate its impact on the performance with the following three variants:

- w/o Intra-MI-It removes the intra-factor MI maximization on global-local pairs for unsupervised objective function (i.e.,  $L_U = L_{inter}$ ).
- w/o Inter-MI-It removes the inter-factor MI minimization between every two factor graphs for unsupervised objective function (i.e., L<sub>U</sub> = ∑<sub>k=1</sub><sup>K</sup> L<sub>intra</sub><sup>k</sup>).
   w/o MI-It removes the whole MI-based constraint for
- w/o MI-It removes the whole MI-based constraint for unsupervised objective function (i.e., w/o L<sub>U</sub>).

Table III presents the results of different model variants on all ten datasets and we can observe that the best results have been attained by considering both intra- and inter-MI estimation, which indicates that both intra-factor MI maximization on global-local pairs and inter-factor MI minimization between every two factor graphs play a key role to learn disentangled representation for semi-supervised graph classification.

3) Effect of Consistency Regularization: Disentangled consistency regularization helps to transfer the learned disentangled graph representations from the unsupervised encoder to the supervised encoder. To further investigate how the consistency regularization facilitates the model performance, we compare DisenSemi with the following two variants:

- Variant 1-It set  $p(k|G_i) = 1/K$ , a uniform distribution over K latent factors, which means each k-th latent factors reflected in  $G_i$  is same.
- Variant 2-It set  $p(k|G_i)$  with a random distribution over K latent factors. We implement it by randomly choosing a latent factor reflected in  $G_i$ .

The result of DisenSemi and its variants are shown in Table III and we have the following observations:

• The performance decreases when  $p(k|G_i)$  of the model are set with uniform and random distribution in Variant 1 and Variant 2 respectively, which demonstrates that inferring the latent factor of a graph to explicitly identify and regularize the rationale between supervised and unsupervised learning model is important.

• Variant 1 performs worse than variant 2 in most datasets. This may be that setting  $p(k|G_i)$  with a random distribution can also specify a rationale between supervised and unsupervised learning models. Instead, inferring the latent factor of a graph uniformly might introduce rationale's complement to the representation learning.

## D. Parameter Sensitivity (RQ3)

We also examine the sensitivity of the proposed DisenSemi to various hyper-parameters.

1) Effect of the Number of Factor Graphs: To analyze whether DisenSemi can benefit from disentangled representation, we study the performance of the model with varying numbers of factor graphs. In particular, we search the number of factor graphs in the range of  $\{2^0, 2^1, \ldots, 2^4\}$ . Fig. 5 summarizes the experimental results w.r.t. different numbers of factor graphs on four datasets and we find that:

- When the number of factor graphs K = 1, the model can be degraded into an entangled representation-based semi-supervised graph classification model with poor performance. This indicates that explicitly modeling multiple aspects of discriminant features for the graph can greatly facilitate the model performance.
- Increasing the number of factor graphs can substantially enhance the model performance. DisenSemi achieves the best performance at K = 4 in MUTAG, PROTEINS and REDDIT-B and K = 8 in IMDB-B, which represents the optimal aspects of discriminant features for the graph.
- However, when the number of factor graphs is too large (i.e., K ≥ 16), the model performance will degrade slowly. This might be caused by applying a too complex semantic structure for the graph.

## 2) Effect of the Number of Message Passing Layers:

For each disentangled factor graph, we investigate how the depth of DisenSemi affects the performance. In particular, we stack varying numbers of message passing layers in the range of [0, 5]. Fig. 6 shows the experimental results w.r.t. different number of message passing layers in four datasets (i.e., MUTAG, PROTEINS, IMDB-BINARY and REDDIT-BINARY) and we have the following findings:

• When the number of message passing layers L = 0, the model only takes a linear transformation into consideration and suffers from the degenerating issue. Hence, the result



Fig. 5: Performance w.r.t. different numbers of factor graphs in four datasets (i.e., MUTAG, PROTEINS, IMDB-BINARY and REDDIT-BINARY).



Fig. 6: Performance w.r.t. different numbers of message passing layers in four datasets (i.e., MUTAG, PROTEINS, IMDB-BINARY and REDDIT-BINARY).



Fig. 7: Performance w.r.t. different relative weight between losses in PROTEINS and COLLAB.

verifies the rationality and effectiveness of GNNs for learning graph-level representation.

- More message passing layers will yield influence from highorder neighbors in the graph and increase the depth of the model. Clearly, two layers of a model can achieve better performance than one layer. It illustrates the importance of messages passing between nodes to capture the structure of each factor graph.
- Too many message passing layers may hurt the model performance. When stacking more than three message passing layers, the model may introduce noise and suffer from the over-smoothing issue.

3) Effect of Relative Weight between Losses: We investigate the sensitivity of relative weight between losses, namely  $\lambda$ and  $\gamma$ . In particular, we vary the value of  $\lambda$  and  $\gamma$  from 0 to 1 on PROTEINS and COLLAB. As shown in Fig. 7, unsupervised module and disentangled consistency regularization play an important role in the objective and there is an evident performance drop when  $\lambda, \gamma = 0$ . As  $\lambda$  and  $\gamma$  get larger, the performance is relatively stable, and we can get the best results when  $\lambda, \gamma = 1e - 3$ .

## E. Visualization and Case Study (RQ4)

To further investigate how the disentangled representation facilitates the semi-supervised graph classification task, we conduct two qualitative assessments (visualization and case study) of the proposed DisenSemi and baselines.

1) Visualization of Representation Correlation: Besides the quantitative evaluation, we also plot the absolute values of the correlations between the elements of the 128-dimensional graph representations. Fig. 8 shows the correlations analysis of representation obtained from GraphCL, DGCL and our proposed DisenSemi with four factor graphs in the MUTAG and PROTEINS dataset. We find that:

- Compared with the more highly independent representation of DGCL, the learned representation of GraphCL is entangled and the performance is degraded. This indicates that disentangled representation can achieve high performance in the graph classification task.
- The representation generated from DisenSemi presents a more block-wise correlation pattern, indicating that four factor graphs of DisenSemi are likely capturing mutually exclusive information to provide discriminant learned features for the target task.

2) Case Study: For a more intuitive understanding of the disentanglement, we provide examples of the generated factor graphs in DisenSemi. Fig. 9 presents the original graph and those disentangled factor graphs. The edges of the visualized disentangled factor graphs are highlighted with different colors



Fig. 8: Representation correlation analysis, where representations are obtained from the test split in MUTAG and PROTEINS. We use the fine-tuned model of GraphCL and DGCL and the supervised model of our proposed DisenSemi to get the representation.



Fig. 9: Visualization of disentangled factor graph in MUTAG and PROTEINS. The first column presents the original graph and the second to fifth columns present those factor graphs highlighted with different colors.

after we set the coefficient threshold in the original graph. For example, in the MUTAG dataset, the task is to predict the molecule's mutagenicity on Salmonella typhimurium for a collection of nitroaromatic compounds. We can see different parts of a molecule graph playing different roles in the prediction task. This also justifies the reliability of our generated factor graphs in getting the disentangled graph representation.

#### VI. CONCLUSION

In this paper, we study semi-supervised graph classification, which is a fundamental problem in graph-structured data mining. For transferring suitable knowledge from the unsupervised model to the supervised model, we propose a novel framework termed DisenSemi, which learns disentangled representation to capture multiple graph characteristics stemming from different aspects. Specifically, our DisenSemi consists of a supervised model and an unsupervised model. For both models, we design a disentangled graph encoder to extract factor-wise graph representation and train two models with supervised objective and MI-based constraints, respectively. Then we propose an MI-based disentangled consistency regularization to identify the rationale that aligns well between two models for the current graph classification task and transfer corresponding knowledge semantically. Extensive experiments on ten benchmark graph classification datasets demonstrate the efficacy of

our DisenSemi. However, the number of factor graphs varies among datasets and needs to be searched to find the best value. So in future work, we will apply our DisenSemi to more realistic semi-supervised classification scenarios and automatically select factor graph numbers in a bi-level optimization framework.

## ACKNOWLEDGEMENT

The authors are grateful to the anonymous reviewers for critically reading this article and for giving important suggestions to improve this article.

#### References

- [1] K. M. Borgwardt, C. S. Ong, S. Schönauer, S. Vishwanathan, A. J. Smola, and H.-P. Kriegel, "Protein function prediction via graph kernels," *Bioinformatics*, vol. 21, no. suppl\_1, pp. i47–i56, 2005.
- [2] Z. Hao, C. Lu, Z. Huang, H. Wang, Z. Hu, Q. Liu, E. Chen, and C. Lee, "Asgn: An active semi-supervised graph neural network for molecular property prediction," in *KDD*, 2020, pp. 731–752.
- [3] Y. Wang, Y. Song, S. Li, C. Cheng, W. Ju, M. Zhang, and S. Wang, "Disencite: Graph-based disentangled representation learning for contextspecific citation generation," in AAAI, 2022, pp. 11449–11458.
- [4] L. Backstrom and J. Leskovec, "Supervised random walks: predicting and recommending links in social networks," in WSDM, 2011, pp. 635– 644.
- [5] Y. Wang, S. Tang, Y. Lei, W. Song, S. Wang, and M. Zhang, "Disenhan: Disentangled heterogeneous graph attention network for recommendation," in *CIKM*, 2020, pp. 1605–1614.

- [6] H. Linmei, T. Yang, C. Shi, H. Ji, and X. Li, "Heterogeneous graph attention networks for semi-supervised short text classification," in EMNLP, 2019.
- [7] K. M. Borgwardt and H.-P. Kriegel, "Shortest-path kernels on graphs," in ICDM, 2005, pp. 8-pp.
- [8] N. Shervashidze, P. Schweitzer, E. J. Van Leeuwen, K. Mehlhorn, and K. M. Borgwardt, "Weisfeiler-lehman graph kernels." JMLR, vol. 12, no. 9, 2011.
- [9] R. Kondor and H. Pan, "The multiscale laplacian graph kernel," 2016, pp. 2990-2998.
- [10] N. Shervashidze, S. Vishwanathan, T. Petri, K. Mehlhorn, and K. Borgwardt, "Efficient graphlet kernels for large graph comparison," in AIS-TATS, 2009, pp. 488-495.
- [11] W. Ju, S. Yi, Y. Wang, Q. Long, J. Luo, Z. Xiao, and M. Zhang, "A survey of data-efficient graph learning," arXiv preprint arXiv:2402.00447, 2024
- [12] W. Ju, J. Yang, M. Qu, W. Song, J. Shen, and M. Zhang, "Kgnn: Harnessing kernel-based networks for semi-supervised graph classification," in WSDM, 2022, pp. 421-429.
- [13] X. Luo, W. Ju, M. Qu, C. Chen, M. Deng, X.-S. Hua, and M. Zhang, "Dualgraph: Improving semi-supervised graph classification via dual contrastive learning," in ICDE, 2022, pp. 699-712.
- [14] H. Yue, C. Zhang, C. Zhang, and H. Liu, "Label-invariant augmentation for semi-supervised graph classification," in NeurIPS, 2022, pp. 29350-29 361.
- [15] Y. You, T. Chen, Y. Sui, T. Chen, Z. Wang, and Y. Shen, "Graph contrastive learning with augmentations," in NeurIPS, 2020, pp. 5812-5823
- [16] F.-Y. Sun, J. Hoffmann, V. Verma, and J. Tang, "Infograph: Unsupervised and semi-supervised graph-level representation learning via mutual information maximization," in ICLR, 2020.
- [17] Y. You, T. Chen, Y. Shen, and Z. Wang, "Graph contrastive learning automated," in ICML, 2021, pp. 12121-12132.
- W. Ju, X. Luo, M. Qu, Y. Wang, C. Chen, M. Deng, X.-S. Hua, and [18] M. Zhang, "Tgnn: A joint semi-supervised framework for graph-level classification," in IJCAI, 2022, pp. 2122-2128.
- [19] W. Ju, Z. Mao, S. Yi, Y. Qin, Y. Gu, Z. Xiao, Y. Wang, X. Luo, and M. Zhang, "Hypergraph-enhanced dual semi-supervised graph classification," arXiv preprint arXiv:2405.04773, 2024.
- [20] W. Ju, Z. Mao, Z. Qiao, Y. Qin, S. Yi, Z. Xiao, X. Luo, Y. Fu, and M. Zhang, "Focus on informative graphs! semi-supervised active learning for graph-level classification," Pattern Recognition, p. 110567, 2024
- [21] Z. Ying, J. You, C. Morris, X. Ren, W. Hamilton, and J. Leskovec, "Hierarchical graph representation learning with differentiable pooling," in NeurIPS, 2018, pp. 4805-4815.
- [22] S. J. Pan and Q. Yang, "A survey on transfer learning," TKDE, vol. 22, no. 10, pp. 1345-1359, 2010.
- [23] Y. Bengio, A. Courville, and P. Vincent, "Representation learning: A review and new perspectives," TPAMI, vol. 35, no. 8, pp. 1798-1828, 2013.
- [24] X. Wang, H. Jin, A. Zhang, X. He, T. Xu, and T.-S. Chua, "Disentangled graph collaborative filtering," in *SIGIR*, 2020, pp. 1001–1010. J. Ma, P. Cui, K. Kuang, X. Wang, and W. Zhu, "Disentangled graph
- [25] convolutional networks," in ICML, 2019, pp. 4212-4221.
- Y. Yang, Z. Feng, M. Song, and X. Wang, "Factorizable graph convolutional networks," in *NeurIPS*, 2020, pp. 20286–20296. [26]
- [27] H. Li, X. Wang, Z. Zhang, Z. Yuan, H. Li, and W. Zhu, "Disentangled contrastive learning on graphs," in NeurIPS, 2021, pp. 21872-21884.
- [28] Y. Mo, Y. Lei, J. Shen, X. Shi, H. T. Shen, and X. Zhu, "Disentangled multiplex graph representation learning," in ICML, 2023, pp. 24983-25 005.
- [29] M. Sajjadi, M. Javanmardi, and T. Tasdizen, "Regularization with stochastic transformations and perturbations for deep semi-supervised learning," in NeurIPS, 2016, pp. 1163-1171.
- [30] S. Laine and T. Aila, "Temporal ensembling for semi-supervised learning," in ICLR, 2017.
- [31] A. Tarvainen and H. Valpola, "Mean teachers are better role models: Weight-averaged consistency targets improve semi-supervised deep learning results," in NeurIPS, 2017, pp. 1195-1204.
- [32] K. Sohn, D. Berthelot, N. Carlini, Z. Zhang, H. Zhang, C. A. Raffel, E. D. Cubuk, A. Kurakin, and C.-L. Li, "Fixmatch: Simplifying semisupervised learning with consistency and confidence," in NeurIPS, 2020, pp. 596-608.
- [33] B. Zhang, Y. Wang, W. Hou, H. Wu, J. Wang, M. Okumura, and T. Shinozaki, "Flexmatch: Boosting semi-supervised learning with curriculum pseudo labeling," in NeurIPS, 2021, pp. 18408-18419.

- [34] J. Li, Y. Rong, H. Cheng, H. Meng, W. Huang, and J. Huang, "Semisupervised graph classification: A hierarchical graph perspective," in WWW, 2019, pp. 972-982.
- [35] X. Luo, Y. Zhao, Y. Qin, W. Ju, and M. Zhang, "Towards semisupervised universal graph classification," TKDE, 2023.
- [36] Y. C. Ng, N. Colombo, and R. Silva, "Bayesian semi-supervised learning with graph gaussian processes," in NeurIPS, 2018, pp. 1690-1701.
- [37] B. Xi, J. Li, Y. Li, R. Song, Y. Xiao, Q. Du, and J. Chanussot, "Semisupervised cross-scale graph prototypical network for hyperspectral image classification," TNNLS, vol. 34, no. 11, pp. 9337-9351, 2022.
- [38] R. Yang, W. Dai, C. Li, J. Zou, and H. Xiong, "Ncgnn: Node-level capsule graph neural network for semisupervised classification," TNNLS, vol. 35, no. 1, pp. 1025-1039, 2022.
- [39] J. Wang, J. Liang, J. Liang, and K. Yao, "Guide: Training deep graph neural networks via guided dropout over edges," TNNLS, vol. 35, no. 4, pp. 4465-4477, 2022.
- [40] I. Higgins, L. Matthey, A. Pal, C. Burgess, X. Glorot, M. Botvinick, S. Mohamed, and A. Lerchner, "beta-vae: Learning basic visual concepts with a constrained variational framework," in ICLR, 2016.
- [41] X. Chen, Y. Duan, R. Houthooft, J. Schulman, I. Sutskever, and P. Abbeel, "Infogan: Interpretable representation learning by information maximizing generative adversarial nets," in NeurIPS, 2016, pp. 2172-2180.
- [42] P. Cheng, M. R. Min, D. Shen, C. Malon, Y. Zhang, Y. Li, and L. Carin, "Improving disentangled text representation learning with informationtheoretic guidance," in ACL, 2020, pp. 7530-7541.
- [43] Y. Wang, Y. Qin, F. Sun, B. Zhang, X. Hou, K. Hu, J. Cheng, J. Lei, and M. Zhang, "Disenctr: Dynamic graph-based disentangled representation for click-through rate prediction," in SIGIR, 2022, pp. 2314-2318.
- [44] Y. Qin, Y. Wang, F. Sun, W. Ju, X. Hou, Z. Wang, J. Cheng, J. Lei, and M. Zhang, "Disenpoi: Disentangling sequential and geographical influence for point-of-interest recommendation," in WSDM, 2023, pp. 508-516.
- P. Velickovic, W. Fedus, W. L. Hamilton, P. Liò, Y. Bengio, and R. D. [45] Hjelm, "Deep graph infomax," in ICLR, 2019.
- [46] M. I. Belghazi, A. Baratin, S. Rajeshwar, S. Ozair, Y. Bengio, A. Courville, and D. Hjelm, "Mutual information neural estimation," in ICML, 2018, pp. 531-540.
- [47] A. v. d. Oord, Y. Li, and O. Vinyals, "Representation learning with contrastive predictive coding," arXiv preprint arXiv:1807.03748, 2018.
- [48] M. Gutmann and A. Hvvärinen, "Noise-contrastive estimation: A new estimation principle for unnormalized statistical models," in AISTATS, 2010, pp. 297-304.
- [49] C. Morris, M. Ritzert, M. Fey, W. L. Hamilton, J. E. Lenssen, G. Rattan, and M. Grohe, "Weisfeiler and leman go neural: Higher-order graph neural networks," in AAAI, 2019, pp. 4602-4609.
- [50] B. Poole, S. Ozair, A. Van Den Oord, A. Alemi, and G. Tucker, "On variational bounds of mutual information," in ICML, 2019, pp. 5171-5180.
- [51] P. Cheng, W. Hao, S. Dai, J. Liu, Z. Gan, and L. Carin, "Club: A contrastive log-ratio upper bound of mutual information," in ICML, 2020, pp. 1779-1788.
- [52] X. Liang, D. Li, and A. Madden, "Attributed network embedding based on mutual information estimation," in CIKM, 2020, pp. 835-844.
- [53] T. Chen, S. Kornblith, M. Norouzi, and G. Hinton, "A simple framework for contrastive learning of visual representations," in ICML, 2020, pp. 1597-1607.
- [54] P. Yanardag and S. Vishwanathan, "Deep graph kernels," in KDD, 2015, pp. 1365-1374.
- [55] B. Adhikari, Y. Zhang, N. Ramakrishnan, and B. A. Prakash, "Sub2vec: Feature learning for subgraphs," in PAKDD, 2018, pp. 170-182.
- [56] A. Narayanan, M. Chandramohan, R. Venkatesan, L. Chen, Y. Liu, and S. Jaiswal, "graph2vec: Learning distributed representations of graphs," arXiv preprint arXiv:1707.05005, 2017.
- [57] K. Hassani and A. H. Khasahmadi, "Contrastive multi-view representation learning on graphs," in ICML, 2020, pp. 4116-4126.
- S. Li, X. Wang, A. Zhang, Y. Wu, X. He, and T.-S. Chua, "Let invariant [58] rationale discovery inspire graph contrastive learning," in ICML, 2022, pp. 13052-13065.
- W. Hamilton, Z. Ying, and J. Leskovec, "Inductive representation [59] learning on large graphs," in NeurIPS, 2017, pp. 1025-1035.
- [60] P. Veličković, G. Cucurull, A. Casanova, A. Romero, P. Lio, and Y. Bengio, "Graph attention networks," in ICLR, 2018.
- [61] K. Xu, W. Hu, J. Leskovec, and S. Jegelka, "How powerful are graph neural networks?" in ICLR, 2018.
- T. N. Kipf and M. Welling, "Semi-supervised classification with graph [62] convolutional networks," in ICLR, 2017.



Yifan Wang is currently an assistant professor in the School of Information Technology & Management, University of International Business and Economics. Prior to that, he received his Ph.D. degree in Computer Science from Peking University, Beijing, China, in 2023. He received his M.S. and B.S. degrees in Software Engineering from Northeastern University, Liaoning, China, in 2014 and 2017 respectively. His research interests include graph representation learning, graph neural networks, disentangled representation learning, and corresponding

applications such as drug discovery and recommender systems.



Ming Zhang received her B.S., M.S. and Ph.D. degrees in Computer Science from Peking University respectively. She is a full professor at the School of Computer Science, Peking University. Prof. Zhang is a member of Advisory Committee of Ministry of Education in China and the Chair of ACM SIGCSE China. She is one of the fifteen members of ACM/IEEE CC2020 Steering Committee. She has published more than 200 research papers on Text Mining and Machine Learning in the top journals and conferences. She won the best paper of ICML

2014 and best paper nominee of WWW 2016. Prof. Zhang is the leading author of several textbooks on Data Structures and Algorithms in Chinese, and the corresponding course is awarded as the National Elaborate Course, National Boutique Resource Sharing Course, National Fine-designed Online Course, National First-Class Undergraduate Course by MOE China.



Xiao Luo is a postdoctoral researcher in Department of Computer Science, University of California, Los Angeles, USA. Prior to that, he received the Ph.D. degree in School of Mathematical Sciences from Peking University, Beijing, China and the B.S. degree in Mathematics from Nanjing University, Nanjing, China, in 2017. His research interests include machine learning on graphs, image retrieval, statistical models and bioinformatics.



**Chong Chen** is currently a research scientist in Terminus Group. He received the B.S. degree in Mathematics from Peking University in 2013 and the Ph.D. degree in Statistics from Peking University in 2019 under the supervision of Prof. Ruibin Xi. His research interests include image understanding, self-supervised learning, and data mining.



Wei Ju is currently an associate professor with the College of Computer Science, Sichuan University, Chengdu, China. Prior to that, he worked as a post-doc research fellow and received his Ph.D. degree in the School of Computer Science from Peking University, Beijing, China, in 2022. He received the B.S. degree in Mathematics from Sichuan University, Sichuan, China, in 2017. His current research interests lie primarily in the area of machine learning on graphs including graph representation learning and graph neural networks, and interdisciplinary

applications such as recommender systems, bioinformatics, drug discovery and knowledge graphs. He has published more than 40 papers in top-tier venues and has won the best paper finalist in IEEE ICDM 2022.



Xian-Sheng Hua (Fellow, IEEE) received the B.S. and Ph.D. degrees in applied mathematics from Peking University, Beijing, in 1996 and 2001, respectively. In 2001, he joined Microsoft Research Asia, as a Researcher, and has been a Senior Researcher at Microsoft Research Redmond since 2013. He became a Researcher and the Senior Director of Alibaba Group in 2015. He has authored or coauthored over 250 research articles and has filed over 90 patents. His research interests include multimedia search, advertising, understanding, and

mining, pattern recognition, and machine learning. He was honored as one of the recipients of MIT35. He served as a Program Co-Chair for the IEEE ICME 2013, the ACM Multimedia 2012, and the IEEE ICME 2012, and on the Technical Directions Board for the IEEE Signal Processing Society. He is an ACM Distinguished Scientist.