## Regular language quantum states

Marta Florido-Llinàs,<sup>1,2,\*</sup> Álvaro M. Alhambra,<sup>3,†</sup> David Pérez-García,<sup>4,‡</sup> and J. Ignacio Cirac<sup>1,2,§</sup>

<sup>1</sup>Max-Planck-Institut für Quantenoptik, Hans-Kopfermann-Str. 1, 85748 Garching, Germany

<sup>2</sup>Munich Center for Quantum Science and Technology (MCQST), Schellingstr. 4, 80799 München, Germany

<sup>3</sup>Instituto de Física Teórica UAM/CSIC, C/ Nicolás Cabrera 13-15, Cantoblanco, 28049 Madrid, Spain

<sup>4</sup>Departamento de Análisis Matemático, Universidad Complutense de Madrid, 28040 Madrid, Spain

(Dated: July 26, 2024)

We introduce regular language states, a family of quantum many-body states. They are built from a special class of formal languages, called regular, which has been thoroughly studied in the field of computer science. They can be understood as the superposition of all the words in a regular language and encompass physically relevant states such as the GHZ-, W- or Dicke-states. By leveraging the theory of regular languages, we develop a theoretical framework to describe them. First, we express them in terms of matrix product states, providing efficient criteria to recognize them. We then develop a canonical form which allows us to formulate a fundamental theorem for the equivalence of regular language states, including under local unitary operations. We also exploit the theory of tensor networks to find an efficient criterion to determine when regular languages are shift-invariant.

The identification of physically relevant families of many-body quantum states admitting a concise theoretical description has played a crucial role in the development of quantum science. Prominent examples of such families are stabilizer- [1], graph- [2], Gaussian- [3], or tensor network-states [4], which have turned into fundamental tools across diverse areas such as quantum error correction, measurement-based quantum computation, the classification of phases of matter, and quantum communication [5–9]. These families, among others, have allowed to establish unexpected but tight connections across different fields, ranging from quantum information theory, to condensed matter or quantum gravity [9–12].

In this work, we introduce a family of quantum manybody states that we call regular language states (RLS). This family is inspired by the concept of formal languages. which lie at the heart of theoretical computer science, and consist of collections of strings described by simple mathematical rules [13–15]. A fundamental subset of formal languages is the class of the so-called regular languages [16], which are widely used for efficient pattern manipulation in applications such as text processing, search engines, and compiler design [17-19]. The structural simplicity of regular languages naturally leads us to define sets of quantum states associated to them as the superposition of the words in the language for each given length. It also allows us to study their properties by leveraging the vast range of tools that have been developed for regular languages in the aforementioned contexts. This definition is also motivated by the fact that prominent examples of states appearing in quantum information and condensed matter physics are RLS, such as the GHZ- [20], W- [21], or Dicke-states [22].

Regular languages can be generated by finite automata [15, 23], which are a special type of restricted Turing machines that follow a simple set of rules. As we will see, this connection allows one to express RLS as matrix product states (MPS), the one-dimensional class of tensor

network states. While the theoretical description of MPS is well established by now [9, 24, 25], it turns out that it cannot be applied to general RLS. Indeed, two basic tools, the canonical form and the fundamental theorem, require some technical conditions that are not met by such states. The former one removes the ambiguity in the description in terms of MPS, while the latter allows one to recognize if two MPS are LU-equivalent; that is, if they can be related to each other by local unitary operators. Both play a very relevant role in many applications of MPS, ranging from computational methods [26, 27] to the classification of symmetry-protected topological phases of matter in one dimension [28, 29]. Here we combine and extend some of the tools and techniques devised for regular languages and MPS in order to develop a theory that encompasses RLS. Specifically, we define a canonical form that can be found using RL tools, and a fundamental theorem that allows us to analyze the LU-equivalence of RLS. We also illustrate with examples how, in certain aspects, RLS significantly differ from standard MPS.

Regular language quantum states.— Let us first briefly recall the definition of regular language (RL). Given an alphabet  $\Sigma$ , a word is any finite sequence of letters of  $\Sigma$ , and  $\Sigma^*$  denotes the set of all possible words of arbitrary length. We will take  $\Sigma = \{0, 1, \ldots, d-1\}$ , so that  $\Sigma^*$  is the set of all sequences composed of those numbers. A language, L, is a subset of  $\Sigma^*$ . We focus on regular languages (RL), which are characterized by simple patterns that can be described by regular expressions (regex). Those are sets of words consisting of either a single letter  $a \in \Sigma$ ,  $\varepsilon$ (the "empty string"),  $\emptyset$ , or the result of performing the operations of concatenation  $(R_1R_2)$ , union  $(R_1 \cup R_2)$ , or Kleene star  $(R_1^* := \varepsilon \cup R_1 \cup R_1R_1 \cup \ldots)$  to some regex  $R_1$  and  $R_2$ .

For  $\Sigma = \{0, 1\}$  (d = 2) some examples are  $(a) \ 0^* \cup 1^*$ , including all words composed entirely of 0s or entirely of 1s,  $(b) \ 0^*10^*$ , with all words with exactly one 1 and the rest 0s,  $(c) \ 0^*10^*10^*$ , with all words with exactly two ones in any locations and the rest 0s, or  $(d) \ 0^*12^*$ , with all words of the form  $0^n 12^m$  for any n, m.

We can associate to each RL a family of quantum states consisting of the superposition with weights equal to one of all the words of length N in the language.

**Definition 1.** Given a RL L, the family of regular language states (RLS) associated to L is  $L_q := \{|L_N\rangle\}_{N \in \mathbb{N}}$ , where

$$|L_N\rangle = \sum_{w \in L \cap \Sigma^N} |w\rangle \,. \tag{1}$$

For the examples given above, the corresponding RLS are: (a) GHZ states on qubits [20], (b) W-states [21], (c) Dicke states with two excitations of the same type [22], and (d) the simplified ansatz for a domain-wall excitation with zero momentum [30]. These examples illustrate how RLS contain some familiar states that are found in quantum information theory and quantum many-body physics. Note that, in order to keep a simple notation, we have not normalized the states. Furthermore, we have chosen all the coefficients in front of the states to be identical. One can extend RLS to include complex coefficients, although here we will mainly concentrate on the first case.

MPS representation of RLS.— All the above examples can be written as MPS with a constant bond dimension, independent of N. In order to show that this holds for all RLS, it is convenient to use an equivalent formulation of RL in terms of *non-deterministic finite automata* (NFA). These are structures characterized by  $\mathcal{F} = \langle Q, \Sigma, \delta, I, F \rangle$ , where Q is the set of internal states,  $I, F \subseteq Q$  are the sets of initial and accepting states, respectively, and  $\delta$ :  $Q \times (\Sigma \cup \varepsilon) \to \mathcal{P}(Q)$  is the transition function, where  $\mathcal{P}(Q)$  denotes the power set of Q. A language is said to be accepted by  $\mathcal{F}$  if for any word  $w = x_1 x_2 \dots x_n \in L$ , there is at least one path along the NFA starting at some  $r_0 \in I$  and ending in  $r_n \in F$ , such that  $r_0 \xrightarrow{x_1} r_1 \xrightarrow{x_2}$  $\dots \xrightarrow{x_n} r_n$ , where  $r_{i+1} \in \delta(r_i, x_{i+1})$  [14]. One of the most fundamental results in automata theory, Kleene's theorem [31], asserts that for every RL there exists an NFA that accepts all and only its words.

Given  $\Sigma = \{0, 1\}$ , we can consider as examples the languages  $L_1 := 0^* 10^*$  of all words containing a single 1, and  $L_2 := 1^* (011^*)^*$ , with all words where every 0 is followed by at least one 1. They are accepted by automata  $\mathcal{F}_i = \langle Q_i, \Sigma, \delta_i, I_i, F_i \rangle$  with  $i \in \{1, 2\}$ , depicted below.



The short arrow in each diagram marks the initial state,  $I_1 = I_2 = \{1\}$ . An arrow going from state  $q_i$  to state  $q_j$ , with the symbol x on top, indicates that  $j \in \delta(i, x)$ . For instance, in  $\mathcal{F}_1$ , we have  $\delta_1(1, 1) = \{2\}$ , meaning that if at some step of a computation we are in state  $q_1$ , and emit output symbol 1, then we transition to  $q_2$ . Similarly,  $\delta_1(1,0) = \{1\}, \delta_1(2,0) = \{2\}$  and  $\delta_1(2,1) = \emptyset$ . The double circles indicate the accepting states,  $F_1 = \{2\}$  and  $F_2 = \{1\}$ .

We will be interested in a subset of NFA's called unambiguous finite automata (UFA) [23], for which any word has at most one accepting path. In fact, for any RL there always exists an UFA that accepts all and only its words [32, 33]. With this, we can now establish a connection between RLS and MPS as follows.

**Theorem 1.** Any family of RLS  $L_q = \{|L_N\rangle\}$  admits an MPS description with binary entries and constant bond dimension. In particular, given any UFA  $\mathcal{F} = \langle Q, \Sigma, \delta, I, F \rangle$  that accepts L, then

$$|L_N\rangle := \underbrace{v_1}_{A} \underbrace{A}_{A} \underbrace{I}_{N} \underbrace{I}_{M} \underbrace{I}_{N} \underbrace{I}_{N}$$

where the bond dimension is D = |Q|, and

$$\begin{cases} \underbrace{v_{I}}_{i=1} := \sum_{i \in I} \langle i |, \\ -\underbrace{v_{P}}_{i=1} := \sum_{f \in F} |f\rangle, \quad i = \begin{cases} 1 & if \ j \in \delta(i, x), \\ 0 & otherwise. \end{cases} \end{cases}$$
(3)

The proofs for this theorem and the rest of the results of this work are provided in the Supplemental Material [34]. Note that the resulting MPS is composed of a single tensor A, although it is not necessarily translationally invariant because it has open boundary conditions (OBC).

Given any tensor A and vectors  $v_l, v_r$  with binary entries, is the corresponding MPS a RLS? To answer this, we note that the coefficient in front of each  $|w\rangle$  equals the number of accepting paths for w, which is not necessarily one unless the automaton is unambiguous. Therefore, the MPS is a RLS if and only if the automaton associated to it according to Eq. (3) is an UFA.

Fortunately, RL theory provides a criterion to decide whether an NFA is actually an UFA in time  $O(m^2)$ , where m is the number of transitions in the underlying NFA [23], which scales at worst as  $O(d^2D^4)$  since  $m \leq dD^2$ . By expressing this criterion in terms of the algebra of the MPS, consisting of all finite products of the MPS matrices and any linear combinations thereof [35], we present an alternative characterization of unambiguity in the lemma below, which can be checked in time  $O(dD^3)$ . We denote the algebra of the MPS as  $\mathcal{A} := \operatorname{Alg}(\{A^x\}) \subseteq \mathcal{M}_D(\mathbb{C})$ , and define the sets  $\mathcal{V}_L := \{(a^T | v_l))^{\otimes 2} \mid a \in \mathcal{A}\}$  and  $\mathcal{V}_R := \{(a | v_r \rangle)^{\otimes 2} \mid a \in \mathcal{A}\}$ , where  $a^T$  is the transpose of a.

**Lemma 2.** Given an MPS defined by the binary tensors  $\{A, v_l, v_r\}$  according to Eq. (2), it is a RLS if and only if, for all  $m, n \in \{1, \ldots, D\}$  with  $m \neq n$ ,

$$|m\rangle \otimes |n\rangle \in (\mathcal{V}_L)^{\perp} \cup (\mathcal{V}_R)^{\perp}.$$

This condition can be checked in time  $O(dD^3)$ .

A particularly relevant set of MPS are those that are translationally invariant (TI). Thus, we now address the problem of determining whether a RLS is TI. The first thing to notice is that these states correspond to the socalled shift-invariant languages [36]. A naive algorithm based on automata theory for deciding whether a RL is shift-invariant can scale as  $O(d4^{D^2})$  with the bond dimension D of any MPS representation. However, using the theory of MPS through the lemma below, we can tackle this issue more efficiently.

**Lemma 3.** A family of MPS-X states  $\{|\psi_N(X, A)\rangle\}_N$ ,

$$|\psi_N(X,A)\rangle := \overbrace{X}^{A} \overbrace{A}^{A} \overbrace{A}^{N \text{ times}} \overbrace{A}^{N}, \qquad (4)$$

where  $X, A^i \in \mathcal{M}_D(\mathbb{C})$  is TI for all N, if and only if,

$$\operatorname{Tr}[X[a,b]] = 0, \ \forall a, b \in \operatorname{Alg}(\{A^i\}).$$

As a corollary, we demonstrate that shift-invariant RL's can be identified in time  $O(dD^3)$ . This shows that tensor networks tools can also add a new perspective on the study of certain problems in computer science.

**Corollary 4.** A RL is shift-invariant if and only if, for any MPS representation of the associated RLS with tensors  $\{A, v_l, v_r\}$  of bond dimension D, it holds that  $\langle v_l | [a, b] | v_r \rangle = 0$  for all  $a, b \in \text{Alg}(\{A^i\})$ . This condition can be checked in time  $O(dD^3)$ .

Canonical form of RLS.— Given two RLS and their MPS representations with bond dimensions  $D_1$  and  $D_2$ , how can we determine if they are equivalent? RL theory provides an algorithm to solve this problem in time  $O(d(D_1 + D_2)^3)$  for the case of UFA's [37–39].

But is it possible to find a canonical form that is efficiently computable and uniquely associated with each RLS? Ideally, this canonical form would enable us not only to determine the equivalence between RLS, but also to address physically relevant questions such as the LUequivalence of RLS, which is key to understand the presence of symmetries [28, 29], or to study the entanglement properties of RLS in terms of their interconvertibility [40, 41].

As a first attempt, we might consider using the already existing canonical form of MPS, but this is not generally possible, because many RLS do not fit into the traditional MPS framework. An example of this fact is the RLS consisting of W-states, for which imposing a TI MPS representation with periodic boundary conditions results in a bond dimension scaling with the system size as  $\Omega(N^{1/(3+\delta)})$  for any  $\delta > 0$  [25, 42].

In what follows, we propose an alternative representation that enables us to formulate a fundamental theorem for LU-equivalent RLS. For this purpose, we introduce first a canonical decomposition for regular languages, and use it as the basis to define a canonical form for RLS. Given any RL, L, on alphabet  $\Sigma$ , we will relabel it as  $\Sigma = \Sigma_{\infty} \cup \Sigma_f = \{0, 1, ...\} \cup \{|\Sigma_{\infty}|, |\Sigma_{\infty}| + 1, ..., d - 1\},$ where  $\Sigma_f$  contains the symbols of  $\Sigma$  whose number of appearances in any word of L is upper bounded by a constant. We will also use operation  $S^{(m)} : \mathcal{L}_m \times (\Sigma_f)^m \to \Sigma^*$ , where  $\mathcal{L}_m$  is the set of all RL's in  $(\Sigma_{\infty} \cup \{f\})^*$  with exactly m appearances of the symbol f in any word, such that  $S^{(m)}(L_1, L_2)$  substitutes every occurrence of f in  $L_1$ with the strings indicated by  $L_2$ .

**Theorem 5** (Canonical decomposition of a RL). Any RL, L, can be decomposed in a unique way in terms of the pairs of RL's  $\{(L_i^m, X_i^m)\}_{j,m}$ , where  $m \leq M$ , as

$$L = \bigcup_m \bigcup_j S^{(m)}(L_j^m, X_j^m)$$

in time  $O((d2^{1+2(M+1)D})^{d^M})$ , where  $L_j^m \in \mathcal{L}_m$  and  $X_j^m$  consists of a union of strings of  $(\Sigma_f)^m$ , with the property that  $L_j^m \cap L_k^m = \emptyset$  and  $X_j^m \neq X_k^m$  unless j = k.

For instance,  $L_1 = 0^*10^*$  can be canonically decomposed as  $\{(0^*f0^*, 1)\}$ , so  $L_1 = S^{(1)}(0^*f0^*, 1)$ , and  $L_2 = 0^*10^*20^* \cup 0^*20^*10^*$  can be canonically decomposed as  $\{(0^*f0^*f0^*, 12 \cup 21)\}$ , so  $L_2 = S^{(2)}(0^*f0^*f0^*, 12 \cup 21)$ . We now embed  $L_j^m$  and  $X_j^m$  into quantum states, where  $|L_{j,N}^m\rangle$  is the superposition of all strings of length N in  $L_j^m$ , and similarly  $|X_j^m\rangle$  is the sum of all strings in  $X_j^m$ , which have length m by construction. We also let  $\hat{S}^{(m),N}$  be the linear operator such that  $\hat{S}^{(m),N}|x\rangle|y\rangle$  is the the sum of the words of length N in  $S^{(m)}(x, y)$ . The dependence on N will be omitted for ease of notation.

**Corollary 6.** Given a RLS  $L_q$ , it can be uniquely written in terms of RLS  $\{(|L_i^m\rangle, |X_i^m\rangle)\}_{j,m}$  as

$$L^N \rangle = \sum_m \sum_j \hat{S}^{(m)} |L_j^m\rangle |X_j^m\rangle,$$

where  $L_j^m$  and  $X_j^m$  have the same properties as in Theorem 5, meaning that  $\langle L_j^m | L_k^m \rangle = 0$  and  $|X_j^m \rangle \neq |X_k^m \rangle$  unless j = k.

As the last step towards a canonical form of RLS, we need to look for a canonical choice of the MPS tensors for the RLS  $\{(|L_j^m\rangle, |X_j^m\rangle)\}_{j,m}$  in Corollary 6. A RL can be accepted by many UFA's, each being a valid MPS representation according to Theorem 1. However, we cannot use the traditional canonical form of MPS because it is not generally applicable to RLS, as previously mentioned.

Automata theory provides a solution for this, by showing that any RL admits a canonical deterministic finite automaton (DFA). This canonical DFA is minimal and unique, up to relabelling of the internal states, among all DFA's accepting the language. Given an UFA of bond dimension D, the minimal equivalent DFA can be found in time  $O(dD2^D)$  [15, 33, 43]. Note that there might be UFA's or ansätze as the one of Eq. (4) with rank $(X) \ge 1$ yielding smaller bond dimensions than the minimal DFA [34]. **Definition 2** (Canonical form of RLS). The canonical MPS representation of  $L_q$  thus corresponds to



where the tensors  $l_j^m, x_j^m$  are the canonical DFA tensors of  $L_j^m, X_j^m$ , and the MPO on top is defined as



where  $\mathbb{P}_{\infty} := \sum_{i=0}^{|\Sigma_{\infty}|-1} |i\rangle\langle i|$ .

Therefore, the MPO effectively implements the action of  $\hat{S}^{(m)}$ , by letting the elements in  $\Sigma_{\infty}$  stay the same, and substituting the f symbols by the strings of  $X_i^m$ .

Fundamental theorem of RLS.— Let us now address the equivalence of two RLS under local unitary operations, using the canonical form of RLS. To achieve this, we restrict to the class of sparse regular languages, which have a number of words that scales polynomially with the word length, i.e.  $|||L_N\rangle|| = O(\text{poly}(N))$ . These languages are well-characterized [44] and widely used due to the fact that their reduced complexity can simplify certain problems [44–49]. It can also be efficiently decided whether a language is sparse or not [32, 50].

**Theorem 7** (Fundamental theorem of sparse RLS). Given two sparse RLS  $L_1, L_2$  with canonical forms  $\{(L_{1,j}^m, X_{1,j}^m)\}_{j,m}$  and  $\{(L_{2,j}^m, X_{2,j}^m)\}_{j,m}$ , they are related as

$$\left|L_{2}^{N}\right\rangle = U^{\otimes N}\left|L_{1}^{N}\right\rangle, \ \forall N$$

for some unitary U if and only if there exists a relabelling  $\pi$  of the  $\Sigma_{\infty}$  symbols and a unitary  $U_f \in \mathcal{U}_{|\Sigma_f|}$  such that

$$\begin{cases} L_{2,j}^m = \pi(L_{1,j}^m), & \forall j, m, \\ |X_{2,j}^{(m)}\rangle := U_f^{\otimes m} |X_{1,j}^m\rangle, & \end{cases}$$

upon some reordering of the canonical form elements.

This theorem indicates that LU-equivalence for all N can be tested in terms of a constant number of finite-size sub-problems.

There is a significant difference between the fundamental theorems of TI MPS and RLS. In the standard case of TI MPS, it enables us to translate local unitaries acting at the physical level into invertible matrices at the bond level. Therefore, the bond dimension does not change, which reflects the fact that local changes of basis do not affect the entanglement content of the state. However, this is not necessarily the case for RLS, as illustrated by the following example. Consider the finite languages  $L_1, L_2$  with canonical representations  $\{(ff, 11 \cup 22 \cup 31 \cup 32)\}$ and  $\{(ff, 11 \cup 12 \cup 32 \cup 33)\}$ . Even though they are related as  $|L_2\rangle = U^{\otimes 2} |L_1\rangle$  for a unitary U, their minimal DFA's have bond dimensions 5 and 4, as shown below.



Since the size of the minimal DFA is a fundamental measure that quantifies the descriptional complexity of RL's [51, 52], we see that, even though LU operations do not change the entanglement content of RLS, they can still modify them in a way that is not captured merely by the bond dimension of the TI PBC canonical form.

*Outlook.*— We have delved into the connection between tensor networks and regular languages, exploring a potential cross-fertilization of ideas and tools between them. Indeed, we have seen how RL techniques can aid in studying physically relevant families of states and in answering open questions about MPS. In this regard, we characterized MPS representing RLS and TI RLS, and developed a canonical form for them, since the standard canonical form of MPS is not generally applicable to RLS. Then, we used it to study the LU-equivalence of sparse RLS, thus making a first step towards a generalized understanding of the LU- and SLOCC-equivalence of RLS. Additional examples are provided in [34].

One could also consider RLS with positive or complex coefficients. The resulting states would be linked to the areas of probabilistic graphical models and weighted finite automata, whose connection with tensor networks has been explored in previous works [53-55]. The next natural question that arises is whether there is a generalization of RLS to the two-dimensional setting. Indeed, the concept of *regular pictures* in 2D has been explored in the literature, aiming to retain the properties of 1D regular languages. Among the proposed extensions, the 2Donline tessellation automaton (OTA) stands out for having an equivalent characterization in terms of 2D regular expressions, as well as other desirable properties [56, 57]. OTA, in turn, can be formulated as PEPS with tensors of a special, simple form [34]. However, unlike 1D RLS, there is no efficient characterization of the class of PEPS representing 2D RLS, nor a canonical form, since these problems are undecidable even when restricted to the very special form of the OTA PEPS tensors [56, 58].

Acknowledgements.— MFL thanks Georgios Styliaris for helpful discussions and acknowledges support from the International Max-Planck Research School for Quantum Science and Technology (IMPRS-QST). This research is part of the Munich Quantum Valley (MQV),

which is supported by the Bavarian State Government with funds from the High-tech Agenda Bayern Plus. AMA acknowledges support from the Spanish Agencia Estatal de Investigacion through the grants "IFT Centro de Excelencia Severo Ochoa SEV-2016-0597' and "Ramón v Cajal RvC2021-031610-I", financed by MCIN/AEI/10.13039/501100011033 and the European Union NextGenerationEU/PRTR. DPG acknowledges support from the Spanish Ministry of Science and Innovation MCIN/AEI/10.13039/501100011033 (grants CEX2023-001347-S and PID2020-113523GB-I00). This work has been financially supported by the Ministry for Digital Transformation and of Civil Service of the Spanish Government through the QUANTUM ENIA project call - Quantum Spain project, and by the European Union through the Recovery, Transformation and Resilience Plan NextGenerationEU within the framework of the Digital Spain 2026 Agenda.

- \* marta.florido.llinas@mpq.mpg.de
- <sup>†</sup> alvaro.alhambra@csic.es
- <sup>‡</sup> dperezga@ucm.es
- <sup>§</sup> ignacio.cirac@mpq.mpg.de
- [1] D. Gottesman, Stabilizer codes and quantum error correction (1997), arXiv:quant-ph/9705052 [quant-ph].
- [2] M. Hein, J. Eisert, and H. J. Briegel, Multiparty entanglement in graph states, Phys. Rev. A 69, 062311 (2004).
- [3] C. Weedbrook, S. Pirandola, R. García-Patrón, N. J. Cerf, T. C. Ralph, J. H. Shapiro, and S. Lloyd, Gaussian quantum information, Rev. Mod. Phys. 84, 621 (2012).
- [4] R. Orús, Tensor networks for complex quantum systems, Nature Reviews Physics 1, 538 (2019).
- [5] P. W. Shor, Scheme for reducing decoherence in quantum computer memory, Phys. Rev. A 52, R2493 (1995).
- [6] B. M. Terhal, Quantum error correction for quantum memories, Rev. Mod. Phys. 87, 307 (2015).
- [7] R. Raussendorf and H. J. Briegel, A one-way quantum computer, Phys. Rev. Lett. 86, 5188 (2001).
- [8] H. J. Briegel, D. E. Browne, W. Dür, R. Raussendorf, and M. Van den Nest, Measurement-based quantum computation, Nature Physics 5, 19 (2009).
- [9] J. I. Cirac, D. Pérez-García, N. Schuch, and F. Verstraete, Matrix product states and projected entangled pair states: Concepts, symmetries, theorems, Rev. Mod. Phys. 93, 045003 (2021).
- [10] B. Zeng, X. Chen, D.-L. Zhou, and X.-G. Wen, Quantum Information Meets Quantum Matter: From Quantum Entanglement to Topological Phases of Many-Body Systems, Quantum Science and Technology (Springer, 2019).
- [11] S. Ryu and T. Takayanagi, Holographic derivation of entanglement entropy from the anti-de sitter space/conformal field theory correspondence, Phys. Rev. Lett. 96, 181602 (2006).
- [12] G. Evenbly and G. Vidal, Tensor network states and geometry, Journal of Statistical Physics 145, 891 (2011).
- [13] A. V. Aho and J. D. Ullman, The theory of parsing, translation, and compiling (Prentice-Hall, Inc., USA, 1972).

- [14] M. Sipser, Introduction to the theory of computation (Boston : PWS Pub. Co., 1997).
- [15] J. E. Hopcroft, R. Motwani, and J. D. Ullman, Introduction to automata theory, languages, and computation, Acm Sigact News 32, 60 (2001).
- [16] S. Yu, Regular languages, in *Handbook of Formal Languages: Volume 1 Word, Language, Grammar*, edited by G. Rozenberg and A. Salomaa (Springer Berlin Heidelberg, Berlin, Heidelberg, 1997) pp. 41–110.
- [17] A. V. Aho, Chapter 5 algorithms for finding patterns in strings, in *Algorithms and Complexity*, Handbook of Theoretical Computer Science, edited by J. Van Leeuwen (Elsevier, Amsterdam, 1990) pp. 255–300.
- [18] J. E. Friedl, Mastering regular expressions (O'Reilly Media, Inc., 2006).
- [19] A. V. Aho, M. S. Lam, R. Sethi, and J. D. Ullman, Compilers: principles, techniques, and tools, Always learning (Pearson, 2014).
- [20] D. M. Greenberger, M. A. Horne, and A. Zeilinger, Going beyond bell's theorem, in *Bell's Theorem, Quantum The*ory and Conceptions of the Universe, edited by M. Kafatos (Springer Netherlands, Dordrecht, 1989) pp. 69–72.
- [21] W. Dür, G. Vidal, and J. I. Cirac, Three qubits can be entangled in two inequivalent ways, Phys. Rev. A 62, 062314 (2000).
- [22] R. H. Dicke, Coherence in spontaneous radiation processes, Phys. Rev. 93, 99 (1954).
- [23] J. Sakarovitch, *Elements of automata theory* (Cambridge University Press, 2009).
- [24] M. Fannes, B. Nachtergaele, and R. F. Werner, Finitely correlated states on quantum spin chains, Communications in Mathematical Physics 144, 443 (1992).
- [25] D. Perez-Garcia, F. Verstraete, M. Wolf, and J. Cirac, Matrix product state representations, Quantum Information and Computation 7, 401 (2007).
- [26] U. Schollwöck, The density-matrix renormalization group in the age of matrix product states, Annals of Physics 326, 96 (2011).
- [27] Y. Zhang and E. Solomonik, On stability of tensor networks and canonical forms (2020), arXiv:2001.01191 [math.NA].
- [28] X. Chen, Z.-C. Gu, and X.-G. Wen, Classification of gapped symmetric phases in one-dimensional spin systems, Phys. Rev. B 83, 035107 (2011).
- [29] N. Schuch, D. Pérez-García, and I. Cirac, Classifying quantum phases using matrix product states and projected entangled pair states, Phys. Rev. B 84, 165139 (2011).
- [30] J. Haegeman, B. Pirvu, D. J. Weir, J. I. Cirac, T. J. Osborne, H. Verschelde, and F. Verstraete, Variational matrix product ansatz for dispersion relations, Phys. Rev. B 85, 100408 (2012).
- [31] S. C. Kleene, Representation of events in nerve nets and finite automata, in *Automata Studies. (AM-34), Volume* 34, edited by C. E. Shannon and J. McCarthy (Princeton University Press, Princeton, 1956) pp. 3–42.
- [32] B. Ravikumar and O. H. Ibarra, Relating the type of ambiguity of finite automata to the succinctness of their representation, SIAM Journal on Computing 18, 1263 (1989).
- [33] H. Leung, Descriptional complexity of nfa of different ambiguity, International Journal of Foundations of Computer Science 16, 975 (2005).
- [34] See Supplemental Material at the end of the document.

- [35] D. R. Farenick, Algebras of linear transformations, Universitext (Springer, 2001).
- [36] G. Jirásková and A. Okhotin, State complexity of cyclic shift, RAIRO - Theoretical Informatics and Applications 42, 335–360 (2008).
- [37] M. Schützenberger, On the definition of a family of automata, Information and Control 4, 245 (1961).
- [38] R. E. Stearns and H. B. Hunt III, On the equivalence and containment problems for unambiguous regular expressions, regular grammars and finite automata, SIAM Journal on Computing 14, 598 (1985).
- [39] C. Cortes, M. Mohri, and A. Rastogi, On the computation of some standard distances between probabilistic automata, in *Implementation and Application of Automata*, edited by O. H. Ibarra and H.-C. Yen (Springer Berlin Heidelberg, Berlin, Heidelberg, 2006) pp. 137–149.
- [40] B. Kraus, Local unitary equivalence of multipartite pure states, Phys. Rev. Lett. 104, 020504 (2010).
- [41] D. Sauerwein, A. Molnar, J. I. Cirac, and B. Kraus, Matrix product states: Entanglement, symmetries, and state transformations, Phys. Rev. Lett. **123**, 170504 (2019).
- [42] M. Michałek and Y. Shitov, Quantum version of wielandt's inequality revisited, IEEE Transactions on Information Theory 65, 5239 (2019).
- [43] J. Hopcroft, An n log n algorithm for minimizing states in a finite automaton, in *Theory of Machines and Computations*, edited by Z. Kohavi and A. Paz (Academic Press, 1971) pp. 189–196.
- [44] A. Szilard, S. Yu, K. Zhang, and J. Shallit, Characterizing regular languages with polynomial densities, in *Mathematical Foundations of Computer Science 1992*, edited by I. M. Havel and V. Koubek (Springer Berlin Heidelberg, Berlin, Heidelberg, 1992) pp. 494–503.
- [45] L. Berman and J. Hartmanis, On isomorphisms and density of np and other complete sets, SIAM Journal on Computing 6, 305 (1977).
- [46] J. Hartmanis and S. R. Mahaney, An essay about research on sparse np complete sets, in *Mathematical Foun*dations of Computer Science 1980, edited by P. Dembiński (Springer Berlin Heidelberg, Berlin, Heidelberg, 1980) pp. 40–57.
- [47] F. D'Alessandro, B. Intrigila, and S. Varricchio, On the structure of the counting function of sparse context-free languages, Theoretical Computer Science 356, 104 (2006).
- [48] S. Hoffmann, Computational complexity of synchronization under sparse regular constraints, in *Fundamentals of Computation Theory*, edited by E. Bampis and A. Pagourtzis (Springer International Publishing, Cham, 2021) pp. 272–286.
- [49] H. Fernau, S. Hoffmann, and M. Wehar, Finite automata intersection non-emptiness: Parameterized complexity revisited (2021), arXiv:2108.05244 [cs.FL].
- [50] A. Mandel and I. Simon, On finite semigroups of matrices, Theoretical Computer Science 5, 101 (1977).
- [51] J. A. Brzozowski, Towards a theory of complexity of regular languages (2017), arXiv:1702.05024 [cs.FL].
- [52] S. Yu, Q. Zhuang, and K. Salomaa, The state complexities of some basic operations on regular languages, Theoretical Computer Science 125, 315 (1994).
- [53] G. M. Crosswhite and D. Bacon, Finite automata for caching in matrix product algorithms, Phys. Rev. A 78, 012356 (2008).
- [54] I. Glasser, R. Sweke, N. Pancotti, J. Eisert, and J. I. Cirac, Expressive power of tensor-network factorizations

for probabilistic modeling, in *Proceedings of the 33rd International Conference on Neural Information Processing Systems* (Curran Associates Inc., Red Hook, NY, USA, 2019).

- [55] T. Li, D. Precup, and G. Rabusseau, Connecting weighted automata, tensor networks and recurrent neural networks through spectral learning, Machine Learning **113**, 2619 (2024).
- [56] K. Inoue and A. Nakamura, Some properties of twodimensional on-line tessellation acceptors, Information Sciences 13, 95 (1977).
- [57] D. Giammarresi and A. Restivo, Two-dimensional languages, in *Handbook of Formal Languages: Volume 3 Beyond Words*, edited by G. Rozenberg and A. Salomaa (Springer Berlin Heidelberg, Berlin, Heidelberg, 1997) pp. 215–267.
- [58] Anselmo, Marcella, Giammarresi, Dora, Madonia, Maria, and Restivo, Antonio, Unambiguous recognizable twodimensional languages, RAIRO-Theor. Inf. Appl. 40, 277 (2006).
- [59] C. J. Pappacena, An upper bound for the length of a finite-dimensional algebra, Journal of Algebra 197, 535 (1997).
- [60] S. Kiefer, A. S. Murawski, J. Ouaknine, B. Wachter, and J. Worrell, Language equivalence for probabilistic automata, in *Computer Aided Verification*, edited by G. Gopalakrishnan and S. Qadeer (Springer Berlin Heidelberg, Berlin, Heidelberg, 2011) pp. 526–540.
- [61] M. O. Rabin and D. Scott, Finite automata and their decision problems, IBM Journal of Research and Development 3, 114 (1959).
- [62] J. E. Hopcroft and R. M. Karp, A Linear Algorithm for Testing Equivalence of Finite Automata, Tech. Rep. (University of California, 1971).

#### SUPPLEMENTAL MATERIAL

## Proof of Theorem 1 connecting RLS and MPS

**Theorem 1.** Any family of RLS  $L_q = \{|L_N\rangle\}$  admits an MPS description with binary entries and constant bond dimension. In particular, given any UFA  $\mathcal{F} = \langle Q, \Sigma, \delta, I, F \rangle$  that accepts L, then

$$|L_N\rangle := \underbrace{v_l}_{A} \underbrace{A}_{A} \underbrace{I}_{N \ times} \underbrace{A}_{V} \underbrace{v_r}_{A}, \qquad (2)$$

where the bond dimension is D = |Q|, and

$$\begin{cases} \textcircled{m-} := \sum_{i \in I} \langle i |, & x \\ - \textcircled{m} := \sum_{f \in F} |f \rangle, & i - \overbrace{A-j}^{x} = \begin{cases} 1 & if \ j \in \delta(i, x), \\ 0 & otherwise. \end{cases}$$
(3)

*Proof.* Kleene's theorem asserts that every RL can be equivalently defined either through a regular expression or a finite automaton [31]. Then, given a RL L and a finite automaton that accepts it,  $\mathcal{F} = \langle Q, \Sigma, \delta, I, F \rangle$ , if we define tensor A and vectors  $v_l, v_r$  according to Eq. (3),

then the language L is equal to

and the states  $|L_N\rangle$  defined in Eq. (2) are

$$|L_N\rangle = \sum_{w \in L \cap \Sigma^N} c_w \, |w\rangle$$

where  $c_w$  equals the number of accepting paths for word w through the automaton. Therefore, when  $\mathcal{F}$  is an UFA, all of the coefficients  $c_w$  are one, and thus the family of states  $\{|L_N\rangle\}_N$  is a RLS.

To illustrate this connection, we provide below the explicit MPS representation of the two examples of RLS  $L_1$  and  $L_2$  of the main text. Given  $\Sigma = \{0, 1\}$ , we considered the languages  $L_1 := 0^*10^*$  of all words containing a single 1, and  $L_2 := 1^*(011^*)^*$ , with all words where every 0 is followed by at least one 1. They are accepted by



Using Eq. (3), the MPS associated to the first automaton has the following tensors,

$$A^{0} = \begin{pmatrix} 1 & 0 \\ 0 & 1 \end{pmatrix}, A^{1} = \begin{pmatrix} 0 & 1 \\ 0 & 0 \end{pmatrix}, \langle v_{l} | = (1 \ 0), | v_{r} \rangle = \begin{pmatrix} 0 \\ 1 \end{pmatrix},$$

while the automaton for  $L_2$  corresponds to

$$A^{0} = \begin{pmatrix} 0 & 1 \\ 0 & 0 \end{pmatrix}, \ A^{1} = \begin{pmatrix} 1 & 0 \\ 1 & 0 \end{pmatrix}, \ \langle v_{l} | = (1 \ 0), \ | v_{r} \rangle = \begin{pmatrix} 1 \\ 0 \end{pmatrix}.$$

#### Proof of Lemma 2 to determine which MPS are RLS

**Lemma 2.** Given an MPS defined by the binary tensors  $\{A, v_l, v_r\}$  according to Eq. (2), it is a RLS if and only if, for all  $m, n \in \{1, \ldots, D\}$  with  $m \neq n$ ,

$$|m\rangle \otimes |n\rangle \in (\mathcal{V}_L)^{\perp} \cup (\mathcal{V}_R)^{\perp}$$

This condition can be checked in time  $O(dD^3)$ .

*Proof.* The proof relies on Proposition 1.15 in [23]. First, we need some preliminary definitions.

An automaton  $\mathcal{F}$  is said to be *trim*, if all of its states are *useful*. This means that each state is accessible from at least one of the initial states, and at least one path that reaches one of the accepting states arises from it.

Equivalently, state n is useful if there exist two strings  $v, w \in \Sigma^*$  such that

$$\langle v_l | A^v | n \rangle \neq 0 \text{ and } \langle n | A^w | v_r \rangle \neq 0.$$
 (5)

where tensor A and vectors  $v_l, v_r$  are obtained from  $\mathcal{F}$ according to Theorem 1, and  $A^y := A^{y_1} A^{y_2} \dots A^{y_l}$  for any string  $y := y_1 y_2 \dots y_l \in \Sigma^*$ .

Therefore, n is useless if and only if

$$|n\rangle \in (\mathcal{A}^T |v_l\rangle)^{\perp} \cup (\mathcal{A} |v_r\rangle)^{\perp}, \qquad (6)$$

where  $\mathcal{A} = \text{Alg}(\{A^x\})$ . To assert this, we used the facts that  $\mathcal{A}$  admits a basis  $\{A^{w_1}, \ldots, A^{w_M}\}$  in terms of a set of words  $w_1, \ldots, w_M \in \Sigma^*$  (it is enough to consider  $w_i$  of length upper bounded by  $D^2 - 1$  [59]), and also  $\mathcal{A}^{\dagger} = \mathcal{A}^T$ because there are no complex entries.

On the other hand, the product automaton of  $\mathcal{F}$ , denoted as  $\mathcal{F} = \langle Q \times Q, \Sigma, \delta', I \times I, F \times F \rangle$ , is the Cartesian product of  $\mathcal{F}$  with itself, where

$$(k,l) \in \delta'((i,j),x) \iff k \in \delta(i,x) \text{ and } l \in \delta(j,x).$$

The MPS tensors  $A', v'_l, v'_r$  associated to  $\mathcal{F} \times \mathcal{F}$  are thus  $(A')^x = A^x \otimes A^x, \langle v'_l = \langle v_l | \otimes \langle v_l | \text{ and } | v'_r \rangle = | v_r \rangle \otimes | v_r \rangle$ . The diagonal part of  $\mathcal{F} \times \mathcal{F}$  is the sub-automaton that arises from restricting to the set of internal states  $\{(i,i)\}_{i \in Q}$ .

By defining the vector subspaces  $\mathcal{V}_L := \{(a^T | v_l \rangle)^{\otimes 2} | a \in \mathcal{A}\}$  and  $\mathcal{V}_R := \{(a | v_r \rangle)^{\otimes 2} | a \in \mathcal{A}\}$ , Eq. (6) tells us that state (m, n) in  $\mathcal{F} \times \mathcal{F}$  being useless is equivalent to

$$|m\rangle \otimes |n\rangle \in (\mathcal{V}_L)^{\perp} \cup (\mathcal{V}_R)^{\perp}.$$
 (7)

To prove the first part of the lemma, we can now use Proposition 1.15 in [23], which states that a finite automaton  $\mathcal{F}$  is unambiguous if and only if the trim part of  $\mathcal{F} \times \mathcal{F}$  is equal to its diagonal part, meaning that all states  $(m, n) \in Q \times Q$  with  $m \neq n$  are useless. Therefore, the MPS is a RLS if and only if Eq. (7) is true for all  $m \neq n$ .

Finally, we show that this condition can be checked in time  $O(dD^3)$  in Algorithm 1 box. The procedure we propose scales better than the standard way to check unambiguity according to [23], since it does not require the construction of the product automaton. The latter runs in time  $O(m^2)$ , where *m* is the number of transitions in the NFA, which scales at worst as  $O(d^2D^4)$  since  $m \leq dD^2$ .

### Proof of Lemma 3 and Corollary 4 about translationally invariant RLS

**Lemma 3.** A family of MPS-X states  $\{|\psi_N(X,A)\rangle\}_N$ ,

$$|\psi_N(X,A)\rangle := \overbrace{X + A + A}^{N \text{ times}} \overbrace{A}^{N}, \qquad (4)$$

where  $X, A^i \in \mathcal{M}_D(\mathbb{C})$  is TI for all N, if and only if,

$$\operatorname{Tr}[X[a,b]] = 0, \ \forall a, b \in \operatorname{Alg}(\{A^i\}).$$

## Algorithm 1: Check if an MPS is a RLS

**Data:** NFA  $\mathcal{F} = \langle Q, \Sigma, \delta, I, F \rangle$  with |Q| = D,  $|\Sigma| = d$ . **Result:** Decide if the MPS associated to  $\mathcal{F}$  is a RLS in time  $O(dD^3)$ .

#### begin

```
\{|l_i\rangle\}_i \leftarrow \text{Basis of } \mathcal{A}^T |v_l\rangle ;
      \{|r_i\rangle\}_i \leftarrow \text{Basis of } \mathcal{A} |v_r\rangle ;
      // These bases can be found in time O(dD^3)
            [60].
      foreach i \in \{1, \ldots, D\}, |l_j\rangle, |r_j\rangle do
            L_{ij} \leftarrow \langle i | l_j \rangle ;
            R_{ij} \leftarrow \langle i | r_j \rangle;
      end
      // Runtime of the block above: O(D^3))
      for each m \neq n, m, n \in \{1, \ldots, D\} do
            if L_{mi}L_{ni} = 0, \forall i then |m\rangle \otimes |n\rangle \in (\mathcal{V}_L)^{\perp};
            if R_{mi}R_{ni} = 0, \forall i then |m\rangle \otimes |n\rangle \in (\mathcal{V}_R)^{\perp};
            if |m\rangle \otimes |n\rangle \notin (\mathcal{V}_L)^{\perp} \cup (\mathcal{V}_R)^{\perp} then
                  return The MPS is not a RLS;
            end
      \mathbf{end}
      // Runtime of the block above: O(D^3)
      return The MPS is a RLS;
\mathbf{end}
```

*Proof.* First, let us reformulate the TI condition as follows. Given the state in Eq. (4)

$$|\psi_N(X,A)\rangle = \sum_{i_1,\ldots,i_N} \operatorname{Tr}\left[XA^{i_1}A^{i_2}\ldots A^{i_N}\right] |i_1i_2\ldots i_N\rangle,$$

it is TI for all N, if and only if, for all  $r \leq N - 1$ , and for all values of  $i_1, \ldots, i_N \in \{0, \ldots, d-1\}$ , it holds that

$$\operatorname{Tr}[XA^{i_1}A^{i_2}\dots A^{i_N}] = \operatorname{Tr}[XA^{i_r+1}\dots A^{i_N}A^{i_1}\dots A^{i_r}]$$

Regrouping the terms together, this is equivalent to

$$\operatorname{Tr}[X[A^{i_1}\dots A^{i_r}, A^{i_{r+1}}\dots A^{i_N}]] = 0, \; \forall i_1, \dots, i_N.$$
(8)

On the other hand, the algebra of the MPS matrices,  $\mathcal{A} := \operatorname{Alg}(\{A^i\})$ , admits a basis of the form  $\{A^{w_1} \dots A^{w_M}\}$ , where  $A^{w_i} := A^{w_{i,1}} \dots A^{w_{i,l_i}}$  and we can take  $l_i \leq D^2 - 1$  [59].

Then, for any elements  $a, b \in \mathcal{A}$ , we know that there exist  $\alpha_i, \beta_i \in \mathbb{C}$  such that

$$a = \sum_i \alpha_i A^{w_i}, \ b = \sum_j \beta_j A^{w_j}$$

Therefore,  $|\psi_N(X, A)\rangle$  are TI for all N if and only if

$$\operatorname{Tr}[X[a,b]] = \sum_{i} \sum_{j} \alpha_{i}\beta_{j} \operatorname{Tr}[X[A^{w_{i}}, A^{w_{j}}]]$$
$$= \sum_{i} \sum_{j} \alpha_{i}\beta_{j} \underbrace{\operatorname{Tr}[X[A^{w_{i,1}} \dots A^{w_{i,l_{i}}}, A^{w_{j,1}} \dots A^{w_{j,l_{j}}}]]}_{=0 \text{ by Eq. (8)}}$$
$$= 0, \quad \forall a, b \in \mathcal{A}.$$

**Corollary 4.** A RL is shift-invariant if and only if, for any MPS representation of the associated RLS with tensors  $\{A, v_l, v_r\}$  of bond dimension D, it holds that  $\langle v_l | [a, b] | v_r \rangle = 0$  for all  $a, b \in \text{Alg}(\{A^i\})$ . This condition can be checked in time  $O(dD^3)$ .

*Proof.* The first part of the statement is a direct application of Lemma 3. To prove the runtime, we outline a scheme to check shift invariance in Algorithm 2 box.

Algorithm 2: Decide if a RL is shift-invariant
<b>Data:</b> RL <i>L</i> and any MPS representation $\{A, v_l, v_r\}$ , with bond dimension <i>D</i> and $ \Sigma  = d$ . <b>Result:</b> Decide if <i>L</i> is shift-invariant in time $O(dD^3)$ .
$ \begin{array}{l} \textbf{begin} \\ \mathcal{S} := \{(w_i, \langle l_i  ,  r_i \rangle)\} \leftarrow \text{Set of triples consisting of} \\ \text{strings } w_i \in \Sigma^* \text{ and vectors } \langle l_i   := \langle v_l   A^{w_i}, \\  r_i \rangle := A^{w_i}   v_r \rangle, \text{ which fully span } \langle v_l   \mathcal{A} \text{ and } \mathcal{A}   v_r \rangle, \\ \text{respectively.} \\ \text{// One can compute the set } \mathcal{S} \text{ by finding} \\ \text{bases of } \langle v_l   \mathcal{A} \text{ and } \mathcal{A}   v_r \rangle, \text{ which is} \\ \text{doable in time } O(dD^3) \text{ [60]. Note that} \\ \mathcal{S} \text{ contains at most } 2D \text{ elements.} \end{array} $
foreach $(w_i, \langle l_i  ,  r_i \rangle), (w_j, \langle l_j  ,  r_j \rangle) \in S$ do if $\langle l_i   r_j \rangle \neq \langle l_j   r_i \rangle$ then return L is not shift-invariant; end // Runtime of the block above: $O(D^3)$ . return L is shift-invariant;
end

Note that a naive automata implementation to determine if a RL L is shift-invariant can result in an algorithm scaling much worse with the bond dimension,  $O(dD^24^{D^2})$ . We show this in Algorithm 3 box. The improvement of our scheme relies on the fact that, while the construction of an equivalent DFA leads to an exponential overhead in the naive automata implementation, we can avoid doing so by leveraging Lemma 3.

## Proof of Theorem 5 about the existence and uniqueness of a canonical form for RL's

**Theorem 5** (Canonical decomposition of a RL). Any RL, L, can be decomposed in a unique way in terms of the pairs of RL's  $\{(L_j^m, X_j^m)\}_{j,m}$ , where  $m \leq M$ , as

$$L = \bigcup_m \bigcup_j S^{(m)}(L_j^m, X_j^m)$$

in time  $O((d2^{1+2(M+1)D})^{d^M})$ , where  $L_j^m \in \mathcal{L}_m$  and  $X_j^m$  consists of a union of strings of  $(\Sigma_f)^m$ , with the property that  $L_j^m \cap L_k^m = \emptyset$  and  $X_j^m \neq X_k^m$  unless j = k.

Algorithm 3: Decide if a RL is shift-invariant (naive automata implementation)

**Data:** RL L and any NFA representation with D internal states and  $|\Sigma| = d$ .

**Result:** Decide if *L* is shift-invariant in time  $O(d4^{D^2})$ . begin

```
L' \leftarrow \text{shift}(L) := \{vu \mid uv \in L\}, \text{ through an NFA}
     with at most 2D^2 + 1 internal states [36];
     // Runtime: O(D^2)
    Construct an equivalent DFA accepting L \leftarrow This
     can be done Rabin-Scott powerset construction,
     resulting in a DFA with at most 2^D states [61];
     // Runtime: O(d2^D).
    Construct an equivalent DFA accepting L' \leftarrow
     Results in at most 2^{2D^2+1} states; // Runtime:
     O(d4^{D^2}).
    if \hat{L} = L' then
       return L is shift-invariant ;
    else
       return L is not shift-invariant;
    end
    // Equivalence checking of these DFA's can
       be done in time O(d4^{D^2}) [62].
end
```

*Proof.* To begin with, we see that a decomposition with such properties is unique. Indeed, assume that L admits two such decompositions,  $\{(L_{1,j}^m, X_{1,j}^m)\}_{j,m}$  and  $\{(L_{2,j}^m, X_{2,j}^m)\}_{j,m}$ .

First, we see that  $L_{1,j}^m = L_{2,j}^m$  upon some relabelling of the elements. Suppose that there exist  $v, w \in L_{2,k}^m$  such that  $v \in L_{1,i}^m$  and  $w \in L_{1,j}^m$ , for some  $i \neq j$ . This would imply that  $X_{1,i}^m = X_{2,k}^m = X_{1,j}^m$ , which is not possible unless i = j. Due to the symmetry of the argument under exchange of  $L_1, L_2$ , it follows that  $L_{1,j}^m = L_{2,j}^m$ upon relabelling, and as a consequence,  $X_{1,j}^m = X_{2,j}^m$ .

Now, we show that it is always possible to find the canonical decomposition of L by providing an explicit algorithm to do so. We assume that we are given an NFA representation of L of bond dimension D.

First of all, we find for each m all finite words  $x_1 \dots x_m \in \Sigma_f^m$  such that the languages

$$L_{x_1\dots x_m} := T_{\Sigma_f \to f} (L \cap \Sigma_{\infty}^* x_1 \Sigma_{\infty}^* x_2 \dots \Sigma_{\infty}^* x_m \Sigma_{\infty}^*) \quad (9)$$

are non-empty, where  $T_{\Sigma_f \to f}$  replaces all symbols in  $\Sigma_f$ by the single symbol f. The intersection in Eq. (9) can be obtained through the product automaton construction [23], resulting in a bond dimension of at most (m+1)D, and computable in time  $O(t_1t_2)$ , where  $t_i$  is the number of edges in the NFA. Note that  $t_1 \leq dD^2$  for the NFA accepting L, and  $t_2 = (m+1)|\Sigma_{\infty}| + m$  [23].

Moreover, the substitution  $T_{\Sigma_f \to f}$  can also be done in time  $O(t_1t_2)$ , since we just need to go through the  $t_1t_2$ edges of the product automaton and change the ones with label in  $\Sigma_f$  by the output symbol f. Therefore, the language can be expressed as

$$L = \bigcup_m \bigcup_{x_1...x_m} S^{(m)}(L_{x_1x_2...x_m}, x_1x_2...x_m).$$

However, this decomposition does not satisfy the desired properties yet, since  $\{L_{x_1...x_m}\}$  are not necessarily pairwise disjoint. For example, for the language  $L = 0^* 10^* 20^* \cup 0^* 20^* 10^*$ , we would have that  $L_{12} = L_{21} = 0^* f0^* f0^*$ . We proceed to define a new partition  $\{L_j^m\}$  of pairwise disjoint RL's, with the desirable property that  $L_j^m \cap L_{x_1...x_m} \neq \emptyset \implies L_j^m \subseteq L_{x_1...x_m}$ . For each m, let  $\mathcal{S} := \{S_1, S_2, \ldots\}$  be the power set of

For each m, let  $S := \{S_1, S_2, ...\}$  be the power set of the words  $\{x_1 ... x_m \in \Sigma_f^m \mid L_{x_1...x_m} \neq \emptyset\}$ . Then, the sets defined as

$$L_i^m := \left( \cap_{x_1 \dots x_m \in S_i} L_{x_1 \dots x_m} \right) \cap \left( \cap_{x_1 \dots x_m \notin S_i} L_{x_1 \dots x_m}^c \right),$$
(10)

where  $L^c$  denotes the complement of L, achieve the desired properties, and can be computed again using automata tools [62]. We neglect the  $L_i^m$  that are empty. For clarity, an example of this partition appears in Figure 1.



FIG. 1. Example of how the partition in Eq. (10) looks like in the proof of Theorem 5, given three initial sets  $L_{x_1...x_m}, L_{y_1...y_m}, L_{z_1...z_m}$ .

Then, we can rewrite the language as

$$L = \bigcup_m \bigcup_j S^{(m)}(L_j^m, X_j^m),$$

where  $X_j^m := \bigcup_{x_1...x_m \in S_j} x_1 \dots x_m$ . Note that, by construction,  $X_j^m \neq X_k^m$  unless j = k. Therefore, the desired conditions on  $L_j^m, X_j^m$  are satisfied.

Finally, we show that this scheme to find the canonical decomposition can be implemented in time  $O((d2^{1+2(M+1)D})^{d^M})$  in Algorithm 4 box.

#### Examples of the non-minimality of the canonical DFA

The minimal canonical DFA is not necessarily minimal with respect to all valid MPS representations of RLS, as has been studied in the RL literature [32]. However,

Algorithm 4: Canonical decomposition of a RL

**Data:** RL L and any NFA representation of size D,  $|\Sigma| = d$ , and with at most M appearances of symbols of  $\Sigma_f$  in all words. **Result:** Compute the canonical decomposition  $\{(L_j^m, X_j^m)\}_{j,m}$  of L in time  $O((d2^{1+2(M+1)D})^{d^M}).$ begin forall  $m \leq M$  do foreach  $x_1 x_2 \dots x_m \in (\Sigma_f)^m$  do  $\tilde{L}_{x_1...x_m} \leftarrow L \cap \Sigma_{\infty}^* x_1 \Sigma_{\infty}^* x_2 \dots \Sigma_{\infty}^* x_m \Sigma_{\infty}^* ;$  $L_{x_1...x_m} \leftarrow T_{\Sigma_f \to f}(\tilde{L}_{x_1...x_m});$ if  $L_{x_1...x_m} = \emptyset$  then Discard it; // Runtime:  $O(md^2D^2)$  (Prop. 1.4 and 1.11 in [23])  $L_{x_1...x_m}^c \leftarrow \text{Complement of } L_{x_1...x_m}$  (first, determinize the NFA using Rabin-Scott powerset construction [61], then calculate the complement of the DFA by changing  $F \leftarrow Q \setminus F$  [23]; // Runtime:  $O(d2^{\overline{m}D})$ end // Runtime of the block:  $O(d^m 2^{mD})$  $\mathcal{S} \leftarrow$  Power set of words  $x_1 \dots x_m \in (\Sigma_f)^m$  such that  $L_{x_1...x_m} \neq \emptyset \ (|\mathcal{S}| \le 2^{|\Sigma_f|^m}).$ foreach  $S_i \in \mathcal{S}$  do  $L_i^m \leftarrow \text{Eq.}$  (10) (involves computing the intersection of  $|\Sigma_f|^m$  NFA's of size either  $\leq (m+1)D$  or  $\leq 2^{(m+1)D}$ , and checking emptiness); // Runtime:  $O((d4^{(m+1)D})^{d^m})$ if  $L_{x_1...x_m} \neq \emptyset$  then  $X_i^m \leftarrow \cup_{x_1 \dots x_m \in \mathcal{S}_i} x_1 \dots x_m ;$ // Runtime:  $O(d^m)$ end end // Runtime of the block:  $O((d2^{1+2(m+1)D})^{d^m})$ end return  $\{(L_i^m, X_i^m)\}$ ; // Total runtime:  $O((d2^{1+2(M+1)D})^{d^M})$ end

if we consider a more general ansatz of the form of Eq. (4) motivated by MPS theory, then we can obtain even smaller bond dimensions than the minimal UFA.

The first example illustrating this corresponds to  $L = (0^*21^*3)^* \cup (0^*31^*2)^*$ . While the Schmidt rank imposes a lower bound of 4 on any UFA representation of L, it can also be described by the following MPS-X with D = 2 and rank(X) = 2,

$$X = \begin{pmatrix} 1 \\ 1 \end{pmatrix}, A^0 = \begin{pmatrix} 1 \\ 0 \end{pmatrix}, A^1 = \begin{pmatrix} 0 \\ 1 \end{pmatrix},$$
$$A^2 = \begin{pmatrix} 0 & 1 \\ 0 \end{pmatrix}, A^3 = \begin{pmatrix} 0 \\ 1 & 0 \end{pmatrix}.$$

Diagramatically, this can be seen as the automaton



where X tells us that any path through the automaton can either start at  $q_1$  and accept at  $q_1$ , or start at  $q_2$  and accept at  $q_2$ .

As a second example, we consider  $L = 0^*(10^*20^*3 \cup 20^*30^*1 \cup 30^*10^*2)0^*$ . The Schmidt rank gives a lower bound of 8 for the size of the minimal UFA, which is equal to the minimal DFA in this case,



However, it can also be described by an MPS-X with D = 6 and rank(X) = 3 with

$$\begin{split} X &= |4\rangle\langle 1| + |5\rangle\langle 2| + |6\rangle\langle 3|, \\ A^0 &= \mathbbm{1}_6, \ A^1 &= |1\rangle\langle 2| + |4\rangle\langle 5|, \\ A^2 &= |2\rangle\langle 3| + |5\rangle\langle 6|, \ A^3 &= |3\rangle\langle 4|, \end{split}$$

which can be pictured as the automaton



where X tells us that any path through it can either start at  $q_1$  and accept at  $q_4$ , start at  $q_2$  and accept at  $q_5$ , or start at  $q_3$  and accept at  $q_6$ .

# Proof of Theorem 7 about the LU-equivalence of sparse RLS

A RL L is sparse, with a number of words scaling as  $O(N^k)$  with the system size for some natural number k, if and only if it can be described with a regex of the form

$$L = \bigcup_{i=1}^{Q} z_{i,0}(y_{i,1})^* z_{i,1} \dots (y_{i,t_i})^* z_{i,t_i} , \qquad (11)$$

where Q is a constant,  $t_i \leq k+1$  for all i, and  $y_i, z_i$  are strings in  $\Sigma^*$  [44]. Whether a RL is sparse or not can be decided in polynomial time [32, 50].

Using the canonical representation in Corollary 6, we can characterize RLS that are equivalent under the action of  $U^{\otimes N}$  for some unitary U.

**Theorem 7** (Fundamental theorem of sparse RLS). Given two sparse RLS  $L_1, L_2$  with canonical forms  $\{(L_{1,j}^m, X_{1,j}^m)\}_{j,m}$  and  $\{(L_{2,j}^m, X_{2,j}^m)\}_{j,m}$ , they are related as

$$\left|L_{2}^{N}\right\rangle = U^{\otimes N} \left|L_{1}^{N}\right\rangle, \ \forall N$$

for some unitary U if and only if there exists a relabelling  $\pi$  of the  $\Sigma_{\infty}$  symbols and a unitary  $U_f \in \mathcal{U}_{|\Sigma_f|}$  such that

$$\begin{cases} L_{2,j}^m = \pi(L_{1,j}^m), & \forall j, m, \\ |X_{2,j}^{(m)}\rangle := U_f^{\otimes m} |X_{1,j}^m\rangle, & \end{cases}$$

upon some reordering of the canonical form elements.

*Proof.* First, we assume that  $|L_2^N\rangle = U^{\otimes}|L_1^N\rangle$  for all N. As the initial step, we show that U acts as a permutation when restricted to  $\Sigma_{\infty}$ .

Given  $x \in \Sigma_{\infty}$ , assume first for simplicity that it appears in  $L_2$  in one of the strings  $y_{i,j}$  of Eq. (11) as  $y_{i,j} = x$ . Then, we know that for each  $x \in \Sigma_{\infty}$  there exists a set of words  $\{s_x^N\}_N \in L_2$  of the form  $s_x^N = s_1 x^{N-a} s_2$ , where  $a := |s_1| + |s_2|$ , and  $s_1$ ,  $s_2$  remain the same for all N. Then,

$$1 = \langle s_i^N | U^{\otimes N} | L_1^N \rangle$$
  
= 
$$\sum_{\substack{w_1 w_2 w_3 \in L_1 \cap \Sigma^N \\ |w_2| = N - a}} \langle s_1 | U^{\otimes |w_1|} | w_1 \rangle \langle xx \dots x | U^{\otimes (N-a)} | w_2 \rangle$$
  
$$\langle s_2 | U^{\otimes |w_3|} | w_3 \rangle.$$
(12)

Assume that  $|\langle x|U|y\rangle| \leq \lambda < 1$  for all  $y \in \Sigma_{\infty}$ . Since  $L_1$  contains O(poly(N)) words of length N, Eq. (12) would necessarily imply that  $1 = O(\text{poly}(N)\lambda^N)$ , which leads to a contradiction as  $N \to \infty$ .

Similarly, if  $|y_{i,j}| > 1$  for all strings where  $x \in \Sigma_{\infty}$  appears, the argument above still holds if we just choose  $s_x^N = s_1(y_{i,j})^{N-a}s_2$  in  $L_2$ , for any  $y_{i,j}$  containing x.

Therefore, there is a permutation  $\pi \in \mathcal{S}_{|\Sigma_{\infty}|}$  such that  $U |x\rangle = |\pi(x)\rangle$  for  $x \in \Sigma_{\infty}$ , so  $U = U_{\pi} \oplus U_{f}$ , where  $U_{f} \in \mathcal{U}_{|\Sigma_{f}|}$ . The unitary U thus acts on  $L_{1}$  as

$$\begin{split} U^{\otimes N}|L_1^N\rangle &= \sum_m \sum_j \hat{S}^{(m)} \left( U_\pi^{\otimes N} | L_{1,j}^m \rangle \right) \left( U_f^{\otimes m} | X_{1,j}^m \rangle \right) \\ &= \sum_m \sum_j \hat{S}^{(m)} | \pi(L_{1,j}^m) \rangle \left( U_f^{\otimes m} | X_{1,j}^m \rangle \right) \\ &= \sum_m \sum_j \hat{S}^{(m)} | L_{2,j}^{m,N} \rangle | X_{2,j}^m \rangle = |L_2^N \rangle. \end{split}$$

Due to the uniqueness of the canonical representation, we have that the above is only possible if, for each m, there exists some reordering of the elements in the canonical representation, such that for all j,

$$\begin{cases} |L_{2,j}^{m,N}\rangle = |\pi(L_{1,j}^{m,N})\rangle \\ |X_{2,j}^{m}\rangle := U_f^{\otimes m}|X_{1,j}^{m}\rangle \end{cases}$$
(13)

The forward direction of the claim follows since Eq. (13) holds for all N.

To prove the other direction, we just need to note that, defining  $U := U_{\pi} \oplus U_f$ , we would have  $|L_2^N\rangle = U^{\otimes N} |L_1^N\rangle$  for all N as desired.

#### Examples of LU and SLOCC-equivalent RLS

First, we reproduce the example of LU-equivalent RLS in the main text and provide the explicit unitary relating them for completeness. Consider

$$\begin{cases} L_1 = 11 \cup 22 \cup 31 \cup 32, \\ L_2 = 11 \cup 12 \cup 32 \cup 33, \end{cases}$$

whose minimal DFAs have bond dimensions 5 and 4, respectively, as shown below,



They are related as  $|L_4\rangle = U^{\otimes 3} |L_3\rangle$  by the unitary

$$U = \frac{1}{\sqrt{3}} \begin{pmatrix} \frac{1}{2}(1+\sqrt{3}) & \frac{1}{2}(1-\sqrt{3}) & 1\\ 1 & 1 & -1\\ \frac{1}{2}(1-\sqrt{3}) & \frac{1}{2}(1+\sqrt{3}) & 1 \end{pmatrix}$$

Another example of LU equivalent RLS involving Bell pairs consists of

$$\begin{cases} L_3 = 11 \cup 22, \\ L_4 = 12 \cup 21, \end{cases}$$

whose minimal DFAs have size 2 as shown below, and therefore the bond dimension does not change in this case,



They are related as  $|L_4\rangle = U^{\otimes 2} |L_3\rangle$  by  $U = \frac{1}{\sqrt{2}} \begin{pmatrix} 1 & i \\ 1 & -i \end{pmatrix}$ .

Finally, we give an example involving the GHZ on three particles, where the minimal DFA of a language that is SLOCC-equivalent to it has a different number of internal states,

$$\begin{cases} L_5 = 111 \cup 222, \\ L_6 = 112 \cup 121 \cup 211 \cup 221 \cup 212 \cup 122, \end{cases}$$

related as  $|L_6\rangle = P^{\otimes 3} |L_5\rangle$  where

$$P = -\begin{pmatrix} \frac{i}{3^{1/6}} & \left(-\frac{1}{3}\right)^{1/6} \\ \left(-\frac{1}{3}\right)^{1/6} & \frac{i}{3^{1/6}} \end{pmatrix}.$$

Their minimal DFAs have bond dimensions 6 and 7, respectively, as shown below,



Generalization of RLS to 2D regular pictures

For completeness, we provide here more details on the generalization of RLs to two dimensions following the notation in [57], and their explicit expression in terms of PEPS.

A picture can be defined as a 2D rectangular array of elements of an alphabet  $\Sigma$ . A 2D language is then defined as a subset of  $\Sigma^{**}$ , where  $\Sigma^{**}$  denotes the set of all pictures over  $\Sigma$ . 1D RL's thus correspond to pictures with a single row or column.

**Definition 3** (4.2 in [57]). A (non-deterministic) 2D online tessellation automata (OTA) is defined by  $\mathcal{A} = \langle Q, \Sigma, \delta, q_0, F \rangle$ , where Q is the set of internal states,  $\Sigma$ is the input alphabet,  $q_0$  is the initial state, F is the set of accepting states, and  $\delta : Q \times Q \times \Sigma \to \mathcal{P}(Q)$  is the transition function.

A run of  $\mathcal{A}$  on picture  $p \in \Sigma^{**}$  consists of associating a state from Q to each element (i, j) of p. The state is determined by the transition function  $\delta$  which receives as inputs the states already associated to positions (i - 1, j)and (i, j - 1), and the symbol p(i, j). At time t = 0, the internal states of the first row and the first column are set to the initial state indicated by  $q_0$ .

Then, we say that an OTA  $\mathcal{A}$  recognizes or accepts a picture p of size  $(l_1(p), l_2(p))$  denoting its number of rows

and columns, respectively, if there exists a run of  $\mathcal{A}$  on p such that the state associated to position  $(l_1(p), l_2(p))$  is an accepting state belonging to F.

In fact, we can express the above definition of OTA as a PEPS, with physical dimension equal to  $|\Sigma|$ , bond dimension D = |Q|, and the following tensors:

so that the PEPS evaluated on picture p is



As an example, we provide the explicit representation of a 2D language over  $\Sigma = \{a\}$  consisting of all pictures with an odd number of columns. An OTA that recognizes it is given by (4.3 in [57]):

- $Q = \{0, 1, 2\},\$
- $q_0 = \{0\},\$
- $F = \{1\},\$
- $\delta(0,0,a) = \delta(0,2,a) = \delta(1,0,a) = \delta(1,2,a) = 1;$  $\delta(0,1,a) = \delta(2,1,a) = 2.$

The equivalent PEPS representation has d = 1, D = 3, and tensors