Hybrid Heuristic Algorithms for Adiabatic Quantum Machine Learning Models

Bahram Alidaee, Department of Marketing, School of Business Administration, University of Mississippi, Oxford, MS, USA (e-mail: balidaee@bus.olemiss.edu).

Haibo Wang, Division of International Business and Technology Studies, Texas A&M International University, Laredo, Texas, USA (e-mail: hwang@tamiu.edu).

Lutfu S.Sua, Department of Management and Marketing, Southern University and A&M College, Baton Rouge, LA, USA (e-mail: lutfu.sagbansua@subr.edu).

Wade W. Liu, Department of Computer Science, School of Engineering, University of Mississippi, Oxford, MS, USA (e-mail: wliu6636@yahoo.com).

Abstract— The recent developments of adiabatic quantum machine learning (AQML) methods and applications based on the quadratic unconstrained binary optimization (QUBO) model have received attention from academics and practitioners. Traditional machine learning methods such as support vector machines, balanced k-means clustering, linear regression, Decision Tree Splitting, Restricted Boltzmann Machines, and Deep Belief Networks can be transformed into a QUBO model. The training of adiabatic quantum machine learning models is the bottleneck for computation. Heuristics-based quantum annealing solvers such as Simulated Annealing and Multiple Start Tabu Search (MSTS) are implemented to speed up the training of AQML based on the QUBO model.

The main purpose of this paper is to present a hybrid heuristic embedding an r-flip strategy to solve large-scale QUBO with an improved solution and shorter computing time compared to the state-of-the-art MSTS method. The results of the substantial computational experiments are reported to compare an *r*-flip strategy embedded hybrid heuristic and a multiple start tabu search algorithm on a set of benchmark instances and three large-scale QUBO instances. The *r*-flip strategy embedded algorithm provides very high-quality solutions within the CPU time limits of 60 and 600 seconds.

Index Terms—Machine Learning, Quadratic unconstrained binary optimization, Local optimality, r-flip local optimality

I. INTRODUCTION

The recent developments of adiabatic quantum machine learning (AQML) methods and applications based on the quadratic unconstrained binary optimization (QUBO) model have received attention from academics and practitioners (Biamonte et al., 2017; Date et al., 2021; Guan et al., 2021; Hatakeyama-Sato et al., 2022; Orús et al., 2019; von Lilienfeld, 2018). Traditional machine learning methods such as support vector machines (SVM) (Biamonte et al., 2017; Date et al., 2021), balanced k-means clustering(BKC)(Date et al., 2021), linear regression(LR)(Date & Potok, 2021), Feature subset selection (FSS)(Chakraborty et al., 2020; Mücke et al., 2023; Otgonbaatar & Datcu, 2021), Decision Tree Splitting(DTS)(Yawata et al., 2022), Restricted Boltzmann Machines (RBMs)(Xu & Oates, 2021) and Deep Belief Networks (DBNs)(Date et al., 2021) can be transformed into a QUBO model. AQML methods have been applied to many areas, for example, AQML is used to select candidates in materials development(Guan et al., 2022; H. Wang et al., 2022), to improve the traffic scheduling(Daugherty et al., 2019), to classify remote sensing data(Cavallaro et al., 2022; H. Wang et al., 2021), to detect anomaly(Liu & Rebentrost, 2018), to process sensor data and enable quantum walk-in robotic systems (Petschnigg et al., 2019), and to enhance the prediction in renewable energy development(Ajagekar & You, 2022).

The training process of AQML models is the bottleneck for implementation. Heuristics-based quantum annealing solvers such as Simulated Annealing (SA)(D-Wave Inc, 2021a) and Multiple Start Tabu Search (MSTS)(D-Wave Inc, 2021b) are implemented to speed up the training of AQML based on the QUBO model. However, these quantum annealing solvers have scalability issues for large-scale QUBO instances due to the data structure associated with the Python wrapper implementation. For large-scale instances, the current quantum annealing solvers have to partition the QUBO data into multiple subproblems and compute the subproblems, then assemble the solution to report the best solution found. Computational efficiency suffers from such a divide-and-conquer strategy.

The scalability issues motivate the development of fast local search algorithms to improve the solution quality of the QUBO problem. Before we introduce the hybrid heuristic, we first prove several theoretical results for QUBO, including a necessary and sufficient condition that when a 1-flip search reaches local optimality, the number of candidates for implementation of the *r*-flip moves can be reduced significantly.

The quadratic unconstrained binary optimization (QUBO) can be formulated as,

$$Max f(x) = \sum_{i=1}^{n} q_i x_i + \frac{1}{2} \sum_{i=1}^{n} \sum_{j \neq i}^{n} q_{i,j} x_i x_j, \quad s.t. \ x_i \in \{0,1\}, i = 1, \cdots, n$$
(1)

In (1), $\frac{1}{2}q_{i,j}$ is the *i,j*-th entry of a given *n* by *n* symmetric matrix *Q*. QUBO is often referred to as the x^TQx model, (G. Kochenberger & Glover, 2013). Since $x_i^2 = x_i$, and *Q* may be written as an upper triangular matrix by doubling each entry of the upper triangle part of the matrix and letting $q_{i,i} = q_i$, then we can write (1) as (2).

$$Max f(x) = \sum_{i=1}^{n} \sum_{j\geq i}^{n} q_{i,j} x_i x_j = x^T Q x, s. t. x_i \in \{0,1\}, i = 1, \cdots, n$$
⁽²⁾

The problem has an enormous number of applications and has been used as a unifying approach to many combinatorial optimization problems (Alidaee et al., 1994; Glover et al., 2019; G. Kochenberger et al., 2014; G. A. Kochenberger et al., 2013). QUBO is a classic NP-hard problem. Due to its practicality, as well as theoretical interest, over the years researchers have proposed many theoretical results as well as simple and sophisticated approaches as solution procedures (Alidaee et al., 2010; Boros et al., 1999; Glover et al., 1998; Glover et al., 2018; Palubeckis, 2004). The recent development of quantum machine learning models based on QUBO formulations highlights the importance of designing a heuristic for improving solution quality and computational efficiency.

Local search strategy (LSS) is one of the most fundamental algorithmic concepts that have been successfully applied to a wide range of hard combinatorial optimization problems. The basic ingredient of almost all sophisticated heuristics is some variation of LSS. One LSS that has been used by many researchers as a stand-alone or as a basic component of more sophisticated algorithms is the *r-flip* (also known as *r-Opt*) strategy (Ravindra K. Ahuja et al., 2002; Alidaee et al., 2010; Alidaee et al., 2017; Alidaee & Wang, 2017; Szeider, 2011; Haibo Wang & Alidaee, 2019; M. Yagiura & Ibaraki, 1999, 2001; Mutsunori Yagiura et al., 2006). Let $N = \{1, 2, ..., n\}$. Given a binary solution, $x = (x_1, \dots, x_n)$ of $x^T Qx$, the *r*-flip search chooses a subset, $S \subseteq N$, with $|S| \leq r$, and builds a new solution, x', where $x'_i = 1 - x_i$ for all $i \in S$. If x' improves the objective function, it is called an *improving move* (or improving subset S). The *r*-flip search starts with a solution x, chooses an improving subset S, and flips all elements in S. The process continues until there is no subset S with $|S| \leq r$ that improves the objective function. The result is called *a locally optimal solution concerning the r*-flip *move* (or *r*-Opt).

Often in strategies where variable neighborhood searches, such as *fan-and-filter* (*F&F*) (Alidaee, 2004; Glover, 1998), *variable neighborhood search* (*VNS*)(Ivanov et al., 2019; Mladenović & Hansen, 1997), and *multi-exchange neighborhood search* (*MENS*)(Ravindra K. Ahuja et al., 2002; R. K. Ahuja et al., 2004; Mladenović & Hansen, 1997) are used, the value of *r* dynamically changes as the search progresses. Generally, there are two reasons for a dynamically changing search space strategy.

- a) The execution of an implementation of an *r*-flip local search, for larger values of *r*, can be computationally expensive to execute. This is because the size of the search space is of order *n* chosen *r*, and for fixed values of *n*, it grows quickly in *r* for the value of $r \le \lfloor n/2 \rfloor$. Hence, smaller values of *r*, especially *r* equal to 1 and 2, have shown considerable success.
- b) In practice, an *r*-flip local search process with a small value of r (e.g., r=1) can quickly reach local optimality. Thus, as a way to escape 1-flip local optimality, researchers have tried to dynamically change the value of r as the search progressed. This allows expanding the search to a more diverse solution space.

A clever implementation of (a) and (b) in an algorithm can not only save computational time, since the smaller value of r is less computationally expensive, but it can also possibly reach better solutions because the larger values of r provide an opportunity to search a more diverse part of the solution space.

A. Previous Works

The development of closed-form formulas for *r*-flip moves is desirable for developing heuristics for solving large-scale problem instances because it can reduce computational time consumed by an implementation of an algorithm. Alidaee et al. (2010) introduced several theorems showing closed-form *r*-flip formulas for general Pseudo-Boolean Optimization. In particular, **Theorem 6** in (Alidaee et al., 2010) is specific to the $f(x) = x^T Qx$ problem. To explain the closed-form formula for the *r*-flip rule in $x^T Qx$, we first introduce a few definitions.

Given a solution $x = (x_1, \dots, x_n)$, the *derivative* of f(x) with respect to x_i is defined as:

$$E(x_i) = q_i + \sum_{j < i} q_{j,i} x_j + \sum_{j > i} q_{i,j} x_j, \ i = 1, \cdots, n$$
(3)

Fact 1. Given a solution vector $x = (x_1, \dots, x_i, \dots, x_n)$, and a solution $x' = (x_1, \dots, 1 - x_i, \dots, x_n)$ obtained by flipping the *i*-th element of x, we have:

$$\Delta f = f(x') - f(x) = (x'_i - x_i)E(x_i)$$
(4)

It is well known that any locally optimal solution to an instance of the QUBO problem concerning a 1-flip search satisfies, $Either ((x_i = 0) if E(x_i) \le 0) or (x_i = 1 if E(x_i) \ge 0), for i = 1, \dots, n$ (5)

Furthermore, after changing x to x', the update for $E(x_i)$, j=1,...,n, can be calculated as follows:

$$j < i, E(x_j) \leftarrow E(x_j) + q_{j,i}(x'_i - x_i)$$

$$\forall j > i, E(x_j) \leftarrow E(x_j) + q_{i,j}(x'_i - x_i)$$
(6)

$$j = i, \quad E(x_j) \leftarrow E(x_j)$$

Note that $x'_i - x_i$ may be written as $1 - 2x_i$, which can simplify the implementation process. A simple 1-flip search is provided in Algorithm 1. Note that in line 3 we chose a sequence to implement Fact 1. Using such a strategy has experimentally proven to be very effective in several recent studies (Alidaee et al., 2017; Alidaee & Wang, 2017; Haibo Wang et al., 2020)

Before we present the algorithms in this study for the *r*-flip strategy, the notations used are given as follows:

- *n* The number of variables
- *x* A starting feasible solution
- x^* The best solution found so far by the algorithm
- *K* The largest value of *k* for *r*-flip, $k \le r$
- $\pi(i)$ The *i*-th element of *x* in the order $\pi(1) \cdots \pi(n)$
- $S = \{i:x_i \text{ is tentatively chosen to receive a new value to produce a new solution } x_i'\}$ restricting consideration to |S| = r
- *D* The set of candidates for an improving move
- Tabu_ten The maximum number of iterations for which a variable can remain Tabu
- Tabu(i) A vector representing the Tabu status of x
- $E(x_i)$ Derivative of f(x) concerning x_i

 $E(x) = (E(x_1), \dots, E(x_n))$ The vector of derivatives

- x(.) A vector representing the solution of x
- E(.) A vector representing the value of the derivative $E(x_i)$

Algorithm 1. 1-flip Local Search

Initialize: *n*, *x*, evaluate the vector E(x)Flag=1 1 Do while (Flag=1) 2 Flag=0 3 Randomly choose a sequence $\pi(1), \dots, \pi(n)$ of integers 1,...,*n*. 4 Do $i = \pi(1), \dots, \pi(n)$ 5 If $(E(x_i) < 0$ and $x_i = 1$ or $(E(x_i) > 0$ and $x_i = 0$): $x_i = 1 - x_i$, update the vector E(x) using Equation (6), Flag=1 6 End do 7 End while

The result of Fact 1 has been extended to the *r*-flip search, given below.

(Theorem 6, Alidaee et al. (2010)) Let *x* be a given solution of QUBO and *x*' obtained from *x* by *r*-flip move (for a chosen set *S*) where $S \subseteq N$, |S|=r, the change in the value of the objective function is: $\Delta f = f(x') - f(x) = \sum_{i \in S} (x'_i - x_i) E(x_i) + \sum_{i,j \in S, i < j} (x'_i - x_i) (x'_j - x_j) q_{i,j}$ (7)
Furthermore, after changing *x* to *x*' the update for $E(x_i), j=1, ..., n$, can be calculated as follows:

$$\forall j \in N \setminus S, E(x_j) \leftarrow E(x_j) + \sum_{i \in S} (x'_i - x_i) q_{i,j}$$

$$\forall j \in S, E(x_j) \leftarrow E(x_j) + \sum_{i \in S \setminus \{j\}} (x'_i - x_i) q_{i,j}$$
(8)

As explained in (Alidaee et al., 2010), the evaluation of change in the objective function (7) can be done in $O(r^2)$, i.e., evaluating f(x') from f(x). The update in (8) requires *r* calculations for each *j* in *N**S*, and *r*-1 calculations for each *j* in *S*, Thus, overall, an update for all *n* variables can be performed in O(nr).

Note that for any two elements i,j=1,...,n, and i < j, we can define:

$$E'(x_i) = E(x_i) - q_i - q_{i,j}x_j, E'(x_j) = E(x_j) - q_j - q_{i,j}x_i.$$
(9)

Using (9) is a useful way to express Equation (7) in Equation (10).

$$\Delta f = \sum_{i \in S} \left[(1 - 2x_i) E'(x_i) + \sum_{j \in S, j \le i} (1 - x_i - x_j) q_{i,j} \right]$$
(10)

A simple exhaustive *r*-flip search is provided in Algorithm 2. The complexity of the problem indicates that the use of a larger value of *r* in the *r*-flip local search can make the implementation of the search process more time-consuming. Meanwhile, the larger value of *r* can provide an opportunity to search a more diverse area of search space and thus possibly reach better solutions. To overcome such conflicts, researchers often use r=1 (and occasionally r=2) as the basic components of their more complex

algorithms, such as F&F, VNS, and MENS. Below, in **Theorem 1** and **Proposition 1**, we prove that after reaching the locally optimal solution concerning a 1-flip search, the implementation of an *r*-flip search can significantly be reduced. Further, related results are also provided to allow the efficient implementation of an *r*-flip search within an algorithm.

Algorithm 2. Exhaustive r-flip Local SearchInitialize: n, x, evaluate the vector E(x), value of rFlag=11 Do while (Flag=1)2 Flag=03 For each combination $S \subset N$ and $|S| \leq r$, evaluate Δf , Equation (7):If $\Delta f > 0$: $x_i = 1 - x_1$, for $i \in S$, update E(x) using Equation (8), Flag=14 End While

II. NEW RESULTS ON CLOSED-FORM FORMULAS

We first introduce some notations. For m < n, define (m, n) to be the number of combinations of m elements out of n, and let $\varphi = \max_{i,j \in N} \{|q_{i,j}|\}$, and $M = \varphi * (2, r)$. Furthermore, **Lemma 1** and **Lemma 2**, presented below, help to prove the results. Note

that, Lemma 1 is a direct deduction from previous results (Alidaee et al., 2010; Boros et al., 1999).

Lemma 1. Given a locally optimal solution $x = (x_1, \dots, x_n)$ with respect to a 1-flip search, we have:

$$(x'_{i} - x_{i})E(x_{i}) \le 0$$
, for $i=1,...,n$. (11)

Proof. Condition of local optimality in (5) indicates that: $(E(x_i) \ge 0 \text{ iff } x_i = 1)$, and $(E(x_i) \le 0, \text{ iff } x_i = 0)$. Using this condition, we thus have: $(x'_i - x_i)E(x_i) \le 0$, for $i = 1, \dots, n$.

Lemma 2. Let $x = (x_1, \dots, x_n)$ be any solution to the problem; then, we have:

$$\sum_{i,j\in S} (x'_i - x_i) (x'_j - x_j) q_{i,j} \le M$$
(12)

Proof. For each pair of elements $i, j \in S$, the left-hand-side can be $q_{i,j}$ or $-q_{i,j}$. Since |S|=r, the summation on the left-hand-side is at most equal to M.

Theorem 1: Let φ and M be as defined above and let $x = (x_1, \dots, x_n)$ be a locally optimal solution of $x^T Q x$ with respect to a 1-flip search. A subset $S \subseteq N$, with |S|=r, is an improving *r*-flip move *if and only if* we have:

$$\sum_{i\in\mathcal{S}} |E(x_i)| \le \sum_{i,j\in\mathcal{S}} (x_i' - x_i) \left(x_j' - x_j \right) q_{i,j} \tag{13}$$

Proof: Using (7), a subset $S \subseteq N$ of *r* elements is an improving *r*-flip move if and only if we have: $\Delta f = f(x') - f(x) = \sum_{i \in S} (x'_i - x_i) E(x_i) + \sum_{i,j \in S} (x'_i - x_i) (x'_j - x_j) q_{i,j} > 0$ (14)

Since x is a locally optimal solution with respect to a 1-flip search, it follows from Lemma 1 that inequality (14) is equivalent to (15); which completes the proof.

$$\sum_{i,j\in S} (x'_i - x_i) (x'_j - x_j) q_{i,j} > -\sum_{i\in S} (x'_i - x_i) E(x_i) = \sum_{i\in S} |E(x_i)|$$
(15)

Proposition 1: Let φ and M be as defined above and let $x = (x_1, \dots, x_n)$ be any locally optimal solution of the $x^T Q x$ problem with respect to a 1-flip search. If a subset $S \subseteq N$, with |S|=r, is an improving r-flip move, then we must have: $\sum_{i \in S} |E(x_i)| < M$.

Proof: Since x is a locally optimal solution with respect to a 1-flip search and S is an improving r-flip move, by **Theorem 1**, we have inequality (16):

$$\sum_{i \in S} |E(x_i)| < \sum_{i,j \in S} (x_i' - x_i) (x_j' - x_j) q_{i,j}$$
(16)

Using Lemma 2, we also have (17), which completes the proof.

$$\sum_{i \in S} |E(x_i)| < \sum_{i,j \in S} (x_i' - x_i) (x_j' - x_j) q_{i,j} \le M$$

$$(17)$$

A consequence of *Theorem 1* is as follows. Given a locally optimal solution *x* with respect to a 1-flip search, if there is no subset of *S* with |S|=r that satisfies (13), then *x* is also a locally optimal solution concerning an *r*-flip search. Furthermore, if there is no subset *S* of any size that (13) is satisfied, then *x* is also a locally optimal solution concerning an *r*-flip search for all $r \le n$. Similar statements are also true regarding **Proposition 1**.

The result of **Proposition 1** is significant in the implementation of an *r*-flip search. It illustrates that, after having a 1-flip search implemented, if an *r*-flip search is next served as a locally optimal solution, only those elements with the sum of absolute values

of derivatives less than M are eligible for consideration. Furthermore, when deciding about the elements of an *r*-flip search, we can easily check to see if any element x_i by itself or with a combination of other elements is eligible to be a member of an improving *r*-flip move *S*. Example 1 below illustrates this situation.

Example 1. Consider an $x^T Qx$ problem with *n* variables. Let $x = (x_1, \dots, x_n)$ be a given locally optimal solution concerning a 1-flip search. Consider $S = \{i, j, k, l\}$ for a possible 4-flip move. To have *S* for an improving move, all 15 inequalities, given below in (17), must be satisfied. Of course, if the last inequality in (17) is satisfied, all other inequalities are also satisfied. This means each subset of the *S* is also an improving move. This is important in any dynamic neighborhood search strategies with *k*-flip moves for $k \le r$ in consideration.

Here we have $\varphi = \underset{i,i \in N}{Max}\{|q_{ij}|\}, \text{ and } M = 6 * \varphi$:

$$\begin{split} &| E(x_a) | < M, \text{ for } a = i, j, k, l, \\ &| E(x_a) | + | E(x_b) | < M, \text{ for } (a \neq b), a, b = i, j, k, l, \\ &| E(x_a) | + | E(x_b) | + | E(x_c) | < M, \text{ for } (a \neq b \neq c), a, b, c = i, j, k, l, \\ &| E(x_a) | + | E(x_b) | + | E(x_c) | + | E(x_d) | < M, \text{ for } a = i, b = j, c = k, d = l \end{split}$$

Choosing the appropriate subset *S* to implement a move is critical. There are many ways to check for an improving subset *S*. In addition, a numerical example is given in the Appendix. Below, we explain two such strategies.

A. Strategy 1

We first define a set D(n) where all its subsets are the candidates for an improving move. Given a locally optimal solution x concerning a 1-flip move, let the elements of x be ordered in ascending absolute value of derivatives, as given in (18).

$$E(x_{\pi(1)}) \leq \cdots \leq E(x_{\pi(n)})$$
(18)

Here, $\pi(i)$ means the *i*-th element of x in the order $(\pi(1), \dots, \pi(n))$. Now, one at a time in the given order, check the summation in (19) for $k=1,2,\dots,n$. Let K be the largest value of k where the inequality is satisfied. The set D(n) is now defined by (20).

$$\sum_{i=1}^{k} |E(x_{\pi(i)})| < M, \text{ for } k = 1, 2, 3, \cdots, n$$
(19)

$$D(n) = \{x_{\pi(1)}, \cdots, x_{\pi(K)}\}$$
(20)

Lemma 3. Any subset $S \subseteq D(n)$ satisfies the *necessary conditions* for an improving move. **Proof.** It follows from **Proposition 1**.

There are some advantages to having elements of x in ascending order, i.e., inequalities (18):

a) the smaller the value of $|E(x_i)|$ is, the more likely that x_i is involved in an improving k-flip move for $k \le r$ (this might be because the right-hand-side value M in (19) for given r is constant. Thus, smaller values of $|E(x_i)|$ on the left-hand side might help to satisfy the inequality easier.)

b) because the elements of D(n) are in ascending order of absolute values of derivatives, a straightforward implementable series of alternatives to be considered for improving subsets, *S*, maybe the elements of the set given in (21). Note that, there are a lot more subsets of D(n) compared to the sets in (21) that are the candidates for consideration in possible *k*-flip moves. Here we only gave one possible efficient implementable strategy.

$$S \in \{\{\pi(1), \pi(2)\}, \{\pi(1), \pi(2), \pi(3)\}, ., \{\pi(1), ., \pi(K)\}\}$$
(21)

It is important to note that, if **Proposition 1** is used in the process of implementing an algorithm, given a locally optimal solution x concerning a 1-flip search, after an r-flip implementation for a subset |S|=r with r>1, the locally optimal solution concerning a 1-flip search for the new solution, x', can be destroyed. Thus, if an r-flip search needed to be continued, a 1-flip search might be necessary on solution x' before a new r-flip move can continue. However, there are many practical situations where this problem may be avoided for many subsets, especially when the problem is very large-scale, i.e., the value of n is large, and/or Q is sparse. **Proposition 2** is a weaker condition of **Proposition 1** that can help to overcome up to some point in the aforementioned problem.

In the proof of **Theorem 1** and **Proposition 1**, we only used a condition of optimality for a 1-flip search satisfied for the members of the subset *S*. We now define a condition as follows and call it *'condition of optimality concerning a* 1-flip *search for a set S'*, or simply *'condition of optimality for S'*.

Given a solution *x*, the *condition of optimality* for any subset $S \subseteq N$ is satisfied if and only if we have:

Either
$$(x_i = 0 \text{ iff } E(i) \le 0)$$
 or $(x_i = 1 \text{ iff } E(i) \ge 0)$, for $i \in S$ (22)

Of course, if we have N in (22) instead of S, x is a locally optimal solution as was defined in Fact 1.

For m < n, let (m, n) be the number of combinations of m elements out of n elements, and $\varphi_s = \max_{i,j \in s} \{|q_{i,j}|\}$, and

 $M_s = \varphi_s * (2, r)$. With these definitions now we state **Proposition 2**.

Proposition 2 (weak necessary condition): Let $S \subseteq N$, |S|=r, and φ_S and M_S as defined above. Given any solution $x = (x_1, \dots, x_n)$ of $x^T Q x$, and assume the condition of optimality is satisfied for a subset *S*. If *S* is an *r*-flip improving move, we must have $\sum |E(x_i)| < M_S$.

Proof: Similar to the proof of Proposition 1.

Notice that, the values of φ_s and M_s in **Proposition 2** depends on *S*; however, these values can be updated efficiently as the search progresses. As explained above, in situations where the problem is large-scale and/or *Q* is sparse, for many variables, the values of derivatives are 'unaffected' by the change of values of elements in *S*. This means a large set of variables still satisfies the condition of optimality, and thus the search can continue without applying a 1-flip search each time before finding a new set *S* for *r*-flip implementation.

B. Strategy 2

Another efficient and easily implementable strategy is when instead of (19), we only use an individual element to create a set of candidates for applying an *r*-flip search, set D(1) as defined below. Corollary 1 is a special case of Proposition 1 that suffices such a strategy.

$$D(1) = \{x_i : | E(x_i) | < M\}$$
(23)

Corollary 1: Let φ and M be as defined before, given a solution $x = (x_1, \dots, x_n)$ of $x^T Q x$, if the 1-flip local search cannot further improve the value of f(x), and $i \in S$ with $S \subseteq N$ where an *r*-flip move of elements of *S* improves f(x), then we must have $|E(x_i)| < M$.

To gain insight into the use of **Corollary 1**, we did some experimentation to find the size of the set D(1) for different sizes of instances. The steps of the experiment to find the size of D(1) are given below. Problems considered are taken from the literature (Palubeckis, 2004) and used by many researchers. We only used the larger-scale problems with 2500 to 6000 variables, a total of 38 instances.

Find_D(): Procedure for finding the size of the set *D*(1):

Step 1. Randomly initialize a solution to the problem. For each value of *r* calculate *M*. Apply the algorithm in **Figure 1** and generate a locally optimal solution *x* concerning a 1-flip search. However, in Step 5 of **Figure 1** only consider those derivatives with $|E(x_i)| < M$

Step 2. Find the number of elements in the set D(1) for x.

Step 3. Repeat Steps 1 and 2, 200 times for each problem, and find the average number of elements in the set D(1) for the same size problem, density, and *r* value.

The results of the experiment are shown in **Table 1**. From **Table 1**, in general, we can say that as the density of matrix Q increases, the size of D(1) decreases for all problem sizes and values of r. This is, of course, because the larger density of Q makes the derivative of each element in an x more related to other elements. As the size of a problem increases, the size of D(1) also increases.

An interesting observation in our experiment was that, in most cases, the sizes of D(1) for better locally optimal solutions were smaller than those with the worse locally optimal solutions. This indicates that as the search reaches closer to the globally optimal solutions, the time for an *r*-flip search decreases when we take advantage of **Corollary 1**.

TABLE I
SIZE OF THE SET $D(1)$

					DIZL OI	THE SET E	(1)					
		j	r=2			<u>r</u>	=3			<u>r</u> =	=4	
	Density				Density				Density			
Problem size	0.1	0.3	0.5	0.8	0.1	0.3	0.5	0.8	0.1	0.3	0.5	0.8
2500	<100	<40	<30	<20	<400	<200	<100	<100	<1000	<500	<300	<200
3000	<100	<40	<30	<20	<400	<200	<100	<100	<1100	<500	<400	<250
4000	<100	<30	<30	<20	<500	<200	<100	<100	<1200	<600	<400	<250
5000	<100	<30	<30	<20	<500	<200	<100	<100	<1300	<600	<400	<250
6000	<100	<30	<30	<20	<500	<200	<100	<100	<1400	<600	<400	<250

C. Implementation details

We first implement two strategies in Sections 2.1 and 2.2 via Algorithm 3 for Strategy 1, and Algorithm 4 for Strategy 2, then propose Algorithm 5 for Strategy 2 embedded with a simple tabu search algorithm for the improvement.

Algorithm 3. *r*-flip Local Search: Strategy 1

Initialize: n, x, evaluate vector E(x), value of r, MFlag=1 1 Do while (Flag=1) 2 Flag=0 3 Call 1-flip local search: Algorithm 1 Sort variables according to $|E(x_{\pi(i)})| \le |E(x_{\pi(i+1)})|$, using Inequality (19) to evaluate the value of K 4 5 For $j = \pi(1), \cdots, \pi(K)$: For $S_j = {\pi(1), \dots, \pi(j)}$, evaluate M_{S_j} 6 If $\sum_{i=1}^{j} |E(x_{\pi(i)})| < M_{S_j}$, evaluate Δf using Equation (7). 7 If $\Delta f > 0$: $x_i = 1 - x_i$, for $i \in S_i$, update E(x) using Equation (8), Flag=1, go to Step 1 8 End for 9 End while

Al	gorithm 4. r-flip Local Search: Strategy 2
In	itialize: n, x , evaluate $E(x)$, value of r, M
Fla	ag=1
1	Do while (Flag=1)
2	Flag=0, and $S = \emptyset$
3	Call 1-flip local search: Algorithm 1
4	Randomly choose a sequence $\pi(1), \dots, \pi(n)$ of integers $1, \dots, n$
5	For $j = \pi(1), \dots, \pi(n)$:
6	If $ E(x_i) < M$, and $ S \cup \{j\} \le r$ evaluate Δf for $S \cup \{j\}$ using Equation (7)
7	If $\Delta f > 0$:
	$x_i = 1 - x_i$, for $i \in S \cup \{j\}$, update $E(x)$ using Equation (8), $S = S \cup \{j\}$,
	Flag =1, go to Step 1
8	End for
9	End while

Algorithm 5. Hybrid r-flip/1-flip Local Search embedded with a simple tabu search algorithm

Initialize: <i>n</i> , <i>x</i> , <i>tabu list</i> , evaluate $E(x)$, value of <i>r</i> , <i>M</i> , <i>tabu tenure</i>	
1 Call local search: Algorithm 4	
2 Do while (until some stopping criteria, e.g., CPU time limit, is reached)	
3 Call Destruction()	
4 Call Construction()	
5 Call randChange()	
End while	

In the Destruction() procedure, there are three steps:

Step 3a. Find the variable that is not on the tabu list and lead to the small change to the solution when the variable is flipped.

Step 3b. Change its value, place it on the tabu list to update the tabu list, and update E(x).

Step 3c. Test if there is any variable that is not on the tabu list and can improve the solution. If no, go to Step 3a.

In the Construction() procedure, there are four steps:

- Step 4a. Test all the variables that are not on the tabu list. If a solution better than the current best solution is found, change its value, place it on the tabu list, update E(x), update the tabu list, and go to Step 1.
- Step 4b. Find the index *i* corresponding to the greatest value of $E(x_i)$, change its value of x_i , place it on the tabu list to update the tabu list, and update E(x).

Step 4c. If this is the fifteenth iteration in the Construction() procedure, go to Step 1.

Step 4d. Test if there is any variable that is not on the tabu list and can improve the solution. If no, go to Step 3a. If yes, go to Step 4a.

The randChange() procedure is invoked occasionally and randomly to select an x for the Destruction() using a random number generator. There is less than a 2% probability to invoke after the Construction() procedure. To get the 2% probability, a random number generator is used to create an integer between 1 to 1000. If the value of the integer is smaller than 20, the randChange() is invoked. The variable chosen in the randChange() will lead to the change of E(x) for Destruction().

Any local search algorithm, e.g., Algorithm 3 or 4, can be used in **Step 1** of this simple tabu search heuristic. However, limited preliminary implementation of Algorithms 3 and 4 within Algorithm 5 suggested that due to its simplicity of implementation and computational saving time, **Algorithm 4** with slight modification was quite effective, thus we used it in **Step 1** of **Algorithm 5**. The slight modification was as follows. If the solution found by a 1-flip is worse than the current best-found solution, quit the local search and go to **Step 2**.

To determine whether the hybrid r-flip/1-flip local search algorithms with two strategies (Algorithms 3 and 4) do better than the hybrid r-flip/1-flip local search embedded with a simple tabu search implementation, we compared Algorithms 3 and 4 to Algorithm 5.

The goal of the new strategies is to reach local optimality on large-scale instances with less computing time. We report the comparison of three algorithms of a 2-flip on large-scale QUBO instances in the next section.

III. COMPUTATIONAL RESULTS

In this study, we perform substantial computational experiments to evaluate the proposed strategies for problem size, density, and *r* value. We compare the performance of **Algorithms 3**, **4**, and **5** for r=2 on very large-scale QUBO instances. We also compare the best algorithm among **Algorithms 3**, **4**, and **5** to one of the best algorithms for $x^T Qx$, i.e., According to D-Wave, the wave-tabu solver is based on the multiple start Tabu Search algorithm¹ from Palubeckis's paper (Palubeckis, 2004). The wave-tabu uses a Python wrapper on the MST2 algorithm from (Palubeckis, 2004) and has a limit on the size of the instances. This study uses the original MST2 algorithm from (Palubeckis, 2004) directly to compare the performance of both approaches without the limitation caused by the Python wrapper.

We code hybrid heuristic algorithms in C++ programming language. The source code of Palubeckis' multiple start tabu search algorithms and the instance generator coded in C++ were downloaded². In (Palubeckis, 2004), there are five multiple start tabu search algorithms, and the **MST2** algorithm had the best results reported by the author. We choose the **MST2** algorithm with the default values for the parameters recommended by the author (Palubeckis, 2004). In the **MST2** algorithm, the number of iterations as the stopping criteria for the first tabu search start subroutine is 25000 * the size of the problem, then the **MST2** algorithm reduces the number of iterations to 10000 * the size of the problem as the stopping criteria for the subsequent tabu search starts. Within the tabu search subroutine, if an improved solution is found, then the **MST2** algorithm invokes a local search immediately. The CPU time limit in the **MST2 algorithm** is checked at the end of the tabu search start subroutine. Thus, the computing time might exceed the CPU time limit for large instances when we choose short CPU time limits.

All algorithms in this study are compiled by GNU C++ compiler v4.8.5 and run on a single core of Intel Xeon Quad-core E5420 Harpertown processors, which have a 2.5 GHz CPU with 8 GB memory. All computing jobs were submitted through the Open PBS Job Management System to ensure both methods use the same CPU for memory usage and CPU time limits on the same instance.

Preliminary results indicated that **Algorithms 3, 4**, and **5** perform well on instances with sizes less than 3,000 and low density. All algorithms found the best-known solution with a CPU time limit of 10 seconds. Thus, we only compare the results of large instances with high density and size from 3,000 to 8,000 by the **MST2** algorithm and the best algorithm among **Algorithms 3, 4**, and **5**. These benchmark instances with sizes from 3,000 to 8,000 have been reported by other researchers (Glover et al., 2010; Rosenberg et al., 2016). In addition, we generate some large-scale QUBO instances with a high density and size of 30,000 using the same parameters from the benchmark instances. We use a CPU time limit of 600 seconds and r=2 for **Algorithms 3, 4**, and **5** on the large-scale instances in Table 2. We adopted the following notation for computational results:

OFV The value of the objective function for the best solution found by each algorithm.

BFS Best found solution among algorithms within the CPU time limit.

TB[s] Time to reach the best solution in seconds of each algorithm.

AT[s] Average computing time out of 10 runs to reach OFV.

DT %Deviation of computing time out of 10 runs to reach OFV.

Table 2 shows the results of the comparison for Algorithms 3, 4, and 5 on very-large-scale instances out of 10 runs. Algorithm 5 produces a better solution than Algorithms 3 and 4 with r=2; thus, we use Algorithm 5 with r=1 and r=2 to compare to the **MST2** algorithm. We impose a CPU time limit of 60 seconds and 600 seconds per run with 10 runs per instance on Algorithm 5

¹ https://docs.ocean.dwavesys.com/projects/tabu/en/latest/

² https://www.personalas.ktu.lt/~ginpalu/, access on September 30, 2019

and **MST2** algorithm. We choose a tabu tenure value of 100 for 1-flip and 2-flip. The instance data and solutions files are available at: https://doi.org/10.18738/T8/WDFBR5.

TABLE II									
RESULTS OF ALGORITHMS 3, 4, AND 5 ON P30000 INSTANCES WITH THE CPU TIME LIMIT OF 600 SECONDS AND R=2									
Instance			Algorithm 3		Algorit	hm 4	Algorithm 5		
ID	size	density	OFV	TB[s]	OFV	TB[s]	OFV	TB[s]	
p30000_1	30000	0.5	127239168	591	127292467	591	127336719	592	
p30000_2	30000	0.8	158439036	572	158472098	555	158526518	571	
p30000_3	30000	1	179192241	584	179219781	587	179261723	590	

In our implementation, we choose the CPU time limit as the stopping criteria and check the CPU time limit before invoking the tabu search in **Algorithm 5**. Because the **MST2** algorithm and **Algorithm 5** are not single point-based search methods, the choice of the CPU time limit as the stopping criterion seems to be a fair performance comparison method between algorithms.

Table 3 describes the size and density of each instance and the number of times out of 10 runs to reach the OFV as well as solution deviation within the CPU time limit for the **MST2 algorithm** and **Algorithm 5** with r=1 and r=2. **MST2** algorithm produces a stable performance and reaches the same OFV frequently out of 10 runs. **Algorithm 5** starts from a random initial solution and can search a more diverse solution space in a short CPU time limit. When the CPU time limit is changed to 600 seconds, the **MST2** algorithm and **Algorithm 5** produce a better solution quality in terms of relative standard deviation (Glen, 2014). The relative standard deviation (RSD) in Table 3 inside the parenthesis is measured by: $RSD = 100\frac{\sigma}{\mu}$, $\sigma =$

 $\sqrt{\Sigma(f(x) - \overline{f(x)})^2}/n$, and $\mu = \overline{f(x)}$, where f(x) is the OFV of each run and $\overline{f(x)}$ is the mean value of OFV out of n=10 runs. For some instances, the relative standard deviation (RSD) is less than 5.0*E*-4 even though not all runs found the same OFV. We use 0.000 as the value of RSD when the value is rounded up to three decimal points.

TABLE III

THE SOLUTION QUALITY OF THE MST2 ALGORITHM AND ALGORITHM 5 WITH 60- AND 600-SECOND TIME CPU LIMITS OUT OF 10 RUNS

Instance			MST2	<i>r</i> -flip with 6	iOs	MST2	r-flip with 6	00s
ID	size	density	with 60s	r=1	r=2	with 600s	r=1	<i>r</i> =2
p3000_1	3000	0.5	10(0)	10(0)	10(0)	10(0)	10(0)	10(0)
p3000_2	3000	0.8	10(0)	10(0)	10(0)	10(0)	10(0)	10(0)
p3000_3	3000	0.8	4(0.01)	7(0.007)	10(0)	10(0)	10(0)	10(0)
p3000_4	3000	1	10(0)	10(0)	10(0)	10(0)	10(0)	10(0)
p3000_5	3000	1	10(0)	9(0.003)	7(0.002)	9(0.001)	10(0)	10(0)
p4000_1	4000	0.5	10(0)	10(0)	10(0)	10(0)	10(0)	10(0)
p4000_2	4000	0.8	10(0)	10(0)	10(0)	9(0.004)	10(0)	10(0)
p4000_3	4000	0.8	10(0)	10(0)	10(0)	10(0)	10(0)	10(0)
p4000_4	4000	1	1(0.033)	10(0)	10(0)	10(0)	10(0)	10(0)
p4000_5	4000	1	10(0)	10(0)	10(0)	10(0)	10(0)	10(0)
p5000_1	5000	0.5	6(0.000)	1(0.002)	2(0.002)	10(0)	3(0.002)	2(0.002)
p5000_2	5000	0.8	10(0)	4(0.003)	1(0.002)	6(0.012)	10(0)	10(0)
p5000_3	5000	0.8	10(0)	7(0.001)	3(0.002)	10(0)	10(0)	10(0)
p5000_4	5000	1	10(0)	1(0.002)	1(0.001)	10(0)	3(0.002)	1(0.001)
p5000_5	5000	1	6(0.021)	9(0.003)	4(0.004)	10(0)	10(0)	10(0)
p6000_1	6000	0.5	10(0)	10(0)	4(0.001)	10(0)	10(0)	10(0)
p6000_2	6000	0.8	10(0)	4(0.001)	4(0.001)	1(0.006)	10(0)	9(0)
p6000_3	6000	1	9(0.002)	3(0.002)	1(0.007)	10(0)	10(0)	10(0)
p7000_1	7000	0.5	1(0.002)	1(0.006)	1(0.007)	10(0)	2(0.002)	4(0.002)
p7000_2	7000	0.8	7(0.000)	1(0.008)	1(0.008)	10(0)	1(0.004)	2(0.004)
p7000_3	7000	1	8(0.011)	3(0.021)	5(0.023)	10(0)	10(0)	10(0)
p8000_1	8000	0.5	10(0)	1(0.004)	1(0.005)	9(0.001)	10(0)	1(0.002)
p8000_2	8000	0.8	10(0)	1(0.009)	1(0.008)	10(0)	7(0.003)	10(0)
p8000_3	8000	1	10(0)	1(0.013)	1(0.01)	10(0)	4(0.001)	3(0.002)
p30000_1	30000	0.5	1(0.002)	1(0.023)	1(0.019)	7(0.018)	1(0.017)	1(0.011)
p30000_2	30000	0.8	10(0)	1(0.017)	1(0.016)	6(0.01)	1(0.019)	1(0.013)
p30000_3	30000	1	10(0)	1(0.015)	1(0.019)	2(0.037)	1(0.025)	1(0.019)

Table 4 reports the computational results of a CPU time limit of 60 seconds, and Table 5 reports the computational results of a CPU time limit of 600 seconds. In Table 4, the **MST2** algorithm matches 5 out of 27 best solutions within the CPU time limit. The 1-flip strategy in **Algorithm 5** matches 26 out of 27 best solutions while the 2-flip strategy in **Algorithm 5** matches 18 out of 27 best solutions. For the **MST2** algorithm, the computing time to find the initial solution exceeded the CPU time limit of 60 seconds for two large instances.

When the CPU time limit is increased to 600 seconds, the **MST2** algorithm matches 10 out of 27 best solutions. The 1-flip strategy matches 25 out of 27 best solutions, and the 2-flip strategy matches 23 out of 27 best solutions. The 1-flip and 2-flip strategies in **Algorithm 5** perform well on high-density large instances. There is no clear pattern that the 2-flip strategy uses more time than a 1-flip strategy to find the same OFV. The 1-flip and 2-flip strategies in **Algorithm 5** choose the initial solution randomly and independently. The 1-flip strategy has a better performance when the CPU time limits are 60 and 600 seconds.

TABLE IV

RESULTS OF THE MST2 ALGORITHM AND R-FLIP STRATEGY IN ALGORITHM 5 WITHIN THE CPU TIME LIMIT OF 60 SECONDS

Instance	BFS (60s)	MST2	(60s)	<i>r</i> -flip (60s)				
ID		OFV	TB[s]	OFV(r=1)	TB[s]	OFV(r=2)	TB[s]	
p3000_1	3931583	3931583	10	3931583	3	3931583	8	
p3000_2	5193073	5193073	25	5193073	2	5193073	2	
p3000_3	5111533	5111533	52	5111533	8	5111533	4	
p3000_4	5761822	5761437	10	5761822	2	5761822	2	
p3000_5	5675625	5675430	24	5675625	7	5675625	17	
p4000_1	6181830	6181830	40	6181830	3	6181830	4	
p4000_2	7801355	7797821	12	7801355	13	7801355	4	
p4000_3	7741685	7741685	31	7741685	5	7741685	8	
p4000_4	8711822	8709956	58	8711822	5	8711822	11	
p4000_5	8908979	8905340	27	8908979	4	8908979	13	
p5000_1	8559680	8556675	56	8559680	21	8559680	7	
p5000_2	10836019	10829848	34	10836019	59	10836019	11	
p5000_3	10489137	10477129	28	10489137	20	10489137	16	
p5000_4	12251710	12245282	52	12251710	54	12251520	42	
p5000_5	12731803	12725779	56	12731803	17	12731803	16	
p6000_1	11384976	11377315	42	11384976	12	11384976	5	
p6000_2	14333855	14330032	39	14333855	27	14333767	14	
p6000_3	16132915	16122333	51	16130731	24	16132915	48	
p7000_1	14477949	14467157	56	14477949	41	14476263	21	
p7000_2	18249948	18238729	55	18249948	47	18246895	47	
p7000_3	20446407	20431354	59	20446407	15	20446407	12	
p8000_1	17340538	17326259	47	17340538	26	17340538	35	
p8000_2	22208986	22180465	55	22208986	54	22208683	53	
p8000_3	24670258	24647248	56	24670258	43	24669351	50	
p30000_1	127252438	126732483	60	127252438	58	127219336	60	
p30000_2	158384175	157481366	69	158384175	59	158339497	60	
p30000_3	179103085	178093109	89	179103085	58	179029747	54	

TABLE V

Instance	BFS	MST2	(600s)		<i>r</i> -flip	(600s)	
ID	(600s)	OFV	TB[s]	OFV(r=1)	TB[s]	OFV(r=2)	TB[s]
03000_1	3931583	3931583	11	3931583	5	3931583	5
p3000_2	5193073	5193073	25	5193073	1	5193073	3
p3000_3	5111533	5111533	52	5111533	30	5111533	8
p3000_4	5761822	5761822	269	5761822	1	5761822	2
p3000_5	5675625	5675625	505	5675625	43	5675625	29
p4000_1	6181830	6181830	40	6181830	4	6181830	2
p4000_2	7801355	7800851	530	7801355	8	7801355	8
p4000_3	7741685	7741685	30	7741685	5	7741685	2
p4000_4	8711822	8711822	67	8711822	2	8711822	7
p4000_5	8908979	8906525	65	8908979	4	8908979	13
p5000_1	8559680	8559075	324	8559680	9	8559680	27
p5000_2	10836019	10835437	541	10836019	17	10836019	21
p5000_3	10489137	10488735	400	10489137	29	10489137	38
p5000_4	12252318	12249290	265	12252318	127	12251848	143
p5000_5	12731803	12731803	265	12731803	19	12731803	32
p6000_1	11384976	11384976	406	11384976	8	11384976	39
p6000_2	14333855	14333767	498	14333855	62	14333855	17
p6000_3	16132915	16128609	239	16132915	60	16132915	71
p7000_1	14478676	14477039	344	14478676	92	14478676	397
p7000_2	18249948	18242205	587	18249948	115	18249844	43
p7000_3	20446407	20431833	109	20446407	47	20446407	21
p8000_1	17341350	17337154	546	17340538	45	17341350	141
p8000_2	22208986	22207866	122	22208986	49	22208986	89
p8000_3	24670924	24669797	402	24670924	185	24670924	386
p30000_1	127336719	127323304	568	127332912	598	127336719	592
p30000_2	158561564	158438942	573	158561564	580	158526518	571
p30000 3	179329754	179113916	575	179329754	599	179261723	590

Tables 6 and 7 present the time deviation of each algorithm on reaching the OFV for each instance. The **MST2** algorithm has less variation in computing time when it finds the same OFV while the *r*-flip strategy in **Algorithm 5** has a wider range of computing time. If the algorithm only finds the OFV once out of 10 runs, the time deviation will be zero.

TΑ	BL	Æ	VI

COMPUTING THE TIME DEVIATION OF TH	MST2 ALGORITHM AND R-FLIP STRAT	FEGY IN ALGORITHM 5 WITHIN 60 SEC
COMING THE TIME DEVIATION OF THE	INDIZ ALGORITIMI AND R TEH STRA	

Instance	MST2			1-flip		2-flip		
ID	AT[s]	DT	AT[s]	DT	AT[s]	DT		
p3000_1	12.5	15.663	15.7	84.075	24.1	56.875		
p3000_2	32.5	20.059	4.9	45.583	4.8	68.606		
p3000_3	54.3	5.901	29.3	46.180	12.0	60.477		
p3000_4	13.3	18.434	12.0	107.798	10.0	51.640		
p3000_5	30.4	15.829	33.2	45.470	32.3	48.240		
p4000_1	49.0	10.227	7.7	50.131	9.3	36.570		
p4000_2	14.2	9.848	22.1	62.351	21.1	70.476		
p4000_3	35.4	11.236	15.1	69.699	16.5	75.542		
p4000_4	58.0	0	22.2	65.408	35.4	45.780		
p4000_5	31.1	11.082	18.1	73.038	29.6	40.109		
p5000_1	56.8	2.339	4.0	0	10.0	42.426		
p5000_2	35.0	3.563	28.3	74.329	11.0	0		
p5000_3	30.0	8.607	38.9	33.038	33.0	50.069		
p5000_4	54.0	5.238	54.0	0	42.0	0		
p5000_5	57.2	1.317	38.8	40.504	30.5	63.379		
p6000_1	43.3	5.112	32.9	47.380	21.8	67.507		
p6000_2	39.8	4.238	31.8	51.521	42.3	46.315		
p6000_3	52.1	5.027	32.3	44.640	48.0	0		
p7000_1	56.0	0	41.0	0	21.0	0		
p7000_2	55.3	1.367	47.0	0	47.0	0		
p7000_3	59.0	0	42.0	56.293	35.2	45.958		
p8000_1	48.1	7.232	26.0	0	35.0	0		
p8000_2	55.9	0.566	54.0	0	53.0	0		
p8000_3	57.2	1.806	43.0	0	50.0	0		
p30000_1	60.0	0	58.0	0	60.0	0		
p30000_2	70.0	1.166	59.0	0	60.0	0		
p30000_3	90.3	0.912	58.0	0	54.0	0		

TABLE VII

COMPUTING THE TIME	DEVIATION OF THE MST2 A	LGORITHM AND R-FLIP STRATEGY	IN ALGORITHM 5 WITHIN 600 SEC.
Instance	MST2	1-flip	2-flip

Instance	MST2		1-flip		2-flip	
ID	AT[s]	DT	AT[s]	DT	AT[s]	DT
p3000_1	11.9	16.067	21.3	62.678	37.8	130.045
p3000_2	29.1	18.144	5.5	69.234	7.7	81.231
p3000_3	58.5	16.889	126.4	99.610	143.6	116.812
p3000_4	292.1	11.285	10.8	58.365	13.7	49.512
p3000_5	543.9	6.365	109.1	88.328	164.3	72.144
p4000_1	42.8	7.773	13.5	63.553	15.1	63.861
p4000_2	552.2	2.597	30.7	49.923	37.0	110.712
p4000_3	31.7	7.293	18.8	57.442	22.9	47.545
p4000_4	70.8	4.094	42.2	102.331	48.7	115.376
p4000_5	70.5	8.596	25.3	81.984	43.0	69.595
p5000_1	337.2	4.265	70.7	126.287	48.0	61.872
p5000_2	557.8	4.565	135.4	96.462	210.6	67.670
p5000_3	428.5	7.257	115.8	96.524	115.5	104.238
p5000_4	279.4	5.987	270.3	48.842	143.0	0
p5000_5	287.1	9.234	194.5	94.641	172.7	92.268
p6000_1	424.8	4.555	152.9	95.641	145.9	46.657
p6000_2	498.0	0	142.5	97.375	73.8	122.070
p6000_3	252.3	5.571	248.0	51.129	318.1	61.672
p7000_1	344.5	0.153	272.5	93.675	441.5	12.974
p7000_2	587.0	0	115.0	0	265.1	76.694
p7000_3	109.0	0	84.5	39.472	131.1	55.401
p8000_1	548.6	1.398	251.3	63.346	141.0	0
p8000_2	145.4	11.829	258.3	56.352	300.7	56.001
p8000_3	514.3	11.365	368.8	43.667	417.3	12.797
p30000_1	572.0	1.365	598.0	0	592.0	0
p30000_2	581.5	1.526	580.0	0	571.0	0
p30000_3	586.5	2.773	599.0	0	590.0	0

The r-flip strategy can be embedded in other local search heuristics as an improvement procedure. The clever implementation of the r-flip strategy can reduce the computing time as well as improve the solution quality. We reported the time and solutions out of 10 runs for each instance. The time deviation and solution deviation of 10 runs with the short CPU time limits are computed

due to the available computing resources in this study. Compared to MST2, which is implemented as the key component of a quantum annealing solver, the r-flip strategy can produce high-quality solutions with shorter computing time, and it is easy to implement as the "warm start" local search solution for many quantum annealing solvers.

IV. CONCLUSION

In this paper, we considered the QUBO problem and provided several results including a necessary and sufficient condition for local optimality of an *r*-flip search when a 1-flip search has already reached local optimality. This can help to improve the quantum machine learning models based on QUBO formulation in terms of speed and solution quality. Our computational results show that candidates to be considered for an *r*-flip implementation can be reduced significantly. The results further indicates that the new *r*-flip strategy can solve large-scale QUBO instances within 600 seconds while it uses a fraction of time to reach the best-known solutions on the benchmark instances compared to MST2, which is a key algorithm for a quantum annealing solver. The results are attractive in situations where variable neighborhood strategies are being implemented on large-scale problems or sparse matrices in QUBO formulation of quantum machine learning models such as quantum SVM, quantum equal size k-means, and quantum feature selection.

REFERENCES

- Ahuja, R. K., Ergun, Ö., Orlin, J. B., & Punnen, A. P. (2002). A survey of very large-scale neighborhood search techniques. *Discrete Applied Mathematics*, 123(1), 75-102. <u>https://doi.org/https://doi.org/10.1016/S0166-218X(01)00338-9</u>
- Ahuja, R. K., Orlin, J. B., Pallottino, S., Scaparra, M. P., & Scutellà, M. G. (2004). A Multi-Exchange Heuristic for the Single-Source Capacitated Facility Location Problem. *Management Science*, 50(6), 749-760. <u>https://doi.org/10.1287/mnsc.1030.0193</u>
- Ajagekar, A., & You, F. (2022). Quantum computing and quantum artificial intelligence for renewable and sustainable energy: An emerging prospect towards climate neutrality. *Renewable and Sustainable Energy Reviews*, 165, 112493. <u>https://doi.org/10.1016/j.rser.2022.112493</u>
- Alidaee, B. (2004). Fan-and-Filter Neighborhood Strategy for 3-SAT Optimization, Hearin Center for Enterprise Science. The University of Mississippi
- Alidaee, B., Kochenberger, G., & Wang, H. (2010). Theorems Supporting r-flip Search for Pseudo-Boolean Optimization. Int. J. Appl. Metaheuristic Comput., 1(1), 93-109. <u>https://doi.org/10.4018/jamc.2010102605</u>
- Alidaee, B., Kochenberger, G. A., & Ahmadian, A. (1994). 0-1 Quadratic programming approach for optimum solutions of two scheduling problems. *International Journal of Systems Science*, 25(2), 401-408. <u>https://doi.org/10.1080/00207729408928968</u>
- Alidaee, B., Sloan, H., & Wang, H. (2017). Simple and fast novel diversification approach for the UBQP based on sequential improvement local search. *Computers & Industrial Engineering*, 111, 164-175. https://doi.org/http://dx.doi.org/10.1016/j.cie.2017.07.012
- Alidaee, B., & Wang, H. (2017). A note on heuristic approach based on UBQP formulation of the maximum diversity problem. *Journal of the Operational Research Society*, 68(1), 102-110. https://doi.org/10.1057/s41274-016-0031-4
- Biamonte, J., Wittek, P., Pancotti, N., Rebentrost, P., Wiebe, N., & Lloyd, S. (2017). Quantum machine learning. *Nature*, 549(7671), 195-202. <u>https://doi.org/10.1038/nature23474</u>
- Boros, E., Hammer, P. L., Minoux, M., & Rader, D. J. (1999). Optimal cell flipping to minimize channel density in VLSI design and pseudo-Boolean optimization. *Discrete Applied Mathematics*, 90(1), 69-88. <u>https://doi.org/https://doi.org/10.1016/S0166-218X(98)00114-0</u>
- Cavallaro, G., Willsch, D., Willsch, M., Michielsen, K., & Riedel, M. (2020, 26 Sept.-2 Oct. 2020). Approaching Remote Sensing Image Classification with Ensembles of Support Vector Machines on the D-Wave Quantum Annealer. (Ed.),^(Eds.). IGARSS 2020 - 2020 IEEE International Geoscience and Remote Sensing Symposium.
- Chakraborty, S., Shaikh, S. H., Chakrabarti, A., & Ghosh, R. (2020). A hybrid quantum feature selection algorithm using a quantum-inspired graph theoretic approach. *Applied Intelligence*, *50*(6), 1775-1793. https://doi.org/10.1007/s10489-019-01604-3

- D-Wave Inc. (2021a). *dwave-SA*. Retrieved Nov 10 from <u>https://docs.ocean.dwavesys.com/projects/neal/en/latest/</u>
- D-Wave Inc. (2021b). *dwave-tabu*. Retrieved Nov 10 from <u>https://docs.ocean.dwavesys.com/projects/tabu/en/latest/index.html</u>
- Date, P., Arthur, D., & Pusey-Nazzaro, L. (2021). QUBO formulations for training machine learning models. *Scientific Reports*, 11(1), 10029. <u>https://doi.org/10.1038/s41598-021-89461-4</u>
- Date, P., & Potok, T. (2021). Adiabatic quantum linear regression. *Scientific Reports*, 11(1), 21905. https://doi.org/10.1038/s41598-021-01445-6
- Daugherty, G., Reveliotis, S., & Mohler, G. (2019). Optimized Multiagent Routing for a Class of Guidepath-Based Transport Systems. *IEEE Transactions on Automation Science and Engineering*, 16(1), 363-381. <u>https://doi.org/10.1109/TASE.2018.2798630</u>
- Delilbasic, A., Cavallaro, G., Willsch, M., Melgani, F., Riedel, M., & Michielsen, K. (2021, 11-16 July 2021). Quantum Support Vector Machine Algorithms for Remote Sensing Data Classification. (Ed.),^(Eds.). 2021 IEEE International Geoscience and Remote Sensing Symposium IGARSS.
- Glen, S. (2014). *Relative Standard Deviation: Definition & Formula* https://www.statisticshowto.com/relative-standard-deviation/
- Glover, F. (1998). A template for scatter search and path relinking. In J.-K. Hao, E. Lutton, E. Ronald, M. Schoenauer, & D. Snyers (Ed.),^(Eds.), *Artificial Evolution*. Berlin, Heidelberg.
- Glover, F., Kochenberger, G., & Du, Y. (2019). Quantum Bridge Analytics I: a tutorial on formulating and using QUBO models. *4OR*, *17*(4), 335-371. <u>https://doi.org/10.1007/s10288-019-00424-y</u>
- Glover, F., Kochenberger, G. A., & Alidaee, B. (1998). Adaptive Memory Tabu Search for Binary Quadratic Programs. *Management Science*, 44(3), 336-345. <u>https://doi.org/10.1287/mnsc.44.3.336</u>
- Glover, F., Lewis, M., & Kochenberger, G. (2018). Logical and inequality implications for reducing the size and difficulty of quadratic unconstrained binary optimization problems. *European Journal of Operational Research*, 265(3), 829-842. <u>https://doi.org/https://doi.org/10.1016/j.ejor.2017.08.025</u>
- Glover, F., Lü, Z., & Hao, J.-K. (2010). Diversification-driven tabu search for unconstrained binary quadratic problems. *40R*, *8*(3), 239-253. <u>https://doi.org/10.1007/s10288-009-0115-y</u>
- Grossi, M., Ibrahim, N., Radescu, V., Loredo, R., Voigt, K., Altrock, C. v., & Rudnik, A. (2022). Mixed Quantum–Classical Method for Fraud Detection With Quantum Feature Selection. *IEEE Transactions on Quantum Engineering*, *3*, 1-12. <u>https://doi.org/10.1109/TQE.2022.3213474</u>
- Guan, W., Perdue, G., Pesah, A., Schuld, M., Terashi, K., Vallecorsa, S., & Vlimant, J.-R. (2021). Quantum machine learning in high energy physics. *Machine Learning: Science and Technology*, 2(1), 011003. <u>https://doi.org/10.1088/2632-2153/abc17d</u>
- Hatakeyama-Sato, K., Adachi, H., Umeki, M., Kashikawa, T., Kimura, K., & Oyaizu, K. (2022). Automated Design of Li+-Conducting Polymer by Quantum-Inspired Annealing [https://doi.org/10.1002/marc.202200385]. Macromolecular Rapid Communications, 43(20), 2200385. https://doi.org/https://doi.org/10.1002/marc.202200385
- Ivanov, S. V., Kibzun, A. I., Mladenović, N., & Urošević, D. (2019). Variable neighborhood search for stochastic linear programming problem with quantile criterion. *Journal of Global Optimization*, 74(3), 549-564. <u>https://doi.org/10.1007/s10898-019-00773-2</u>
- Kochenberger, G., & Glover, F. (2013). Introduction to special xQx issue. *Journal of Heuristics*, 19(4), 525-528. <u>https://doi.org/10.1007/s10732-013-9227-9</u>
- Kochenberger, G., Hao, J.-K., Glover, F., Lewis, M., Lü, Z., Wang, H., & Wang, Y. (2014). The unconstrained binary quadratic programming problem: a survey. *Journal of Combinatorial Optimization*, 28(1), 58-81. <u>https://doi.org/10.1007/s10878-014-9734-0</u>
- Kochenberger, G. A., Glover, F., & Wang, H. (2013). Binary Unconstrained Quadratic Optimization Problem. In P. M. Pardalos, D.-Z. Du, & R. L. Graham (Eds.), *Handbook of Combinatorial Optimization* (pp. 533-557). Springer New York. <u>https://doi.org/10.1007/978-1-4419-7997-1_15</u>
- Liu, N., & Rebentrost, P. (2018). Quantum machine learning for quantum anomaly detection. *Physical Review A*, 97(4), 042315. <u>https://doi.org/10.1103/PhysRevA.97.042315</u>

- Mladenović, N., & Hansen, P. (1997). Variable neighborhood search. *Computers & Operations Research*, 24(11), 1097-1100. <u>https://doi.org/10.1016/S0305-0548(97)00031-2</u>
- Mücke, S., Heese, R., Müller, S., Wolter, M., & Piatkowski, N. (2023). Feature selection on quantum computers. *Quantum Machine Intelligence*, 5(1), 11. <u>https://doi.org/10.1007/s42484-023-00099-z</u>
- Orús, R., Mugel, S., & Lizaso, E. (2019). Quantum computing for finance: Overview and prospects. *Reviews* in *Physics*, 4, 100028. <u>https://doi.org/10.1016/j.revip.2019.100028</u>
- Otgonbaatar, S., & Datcu, M. (2021). A Quantum Annealer for Subset Feature Selection and the Classification of Hyperspectral Images. *IEEE Journal of Selected Topics in Applied Earth Observations and Remote Sensing*, 14, 7057-7065. <u>https://doi.org/10.1109/JSTARS.2021.3095377</u>
- Palubeckis, G. (2004). Multistart Tabu Search Strategies for the Unconstrained Binary Quadratic Optimization Problem. *Annals of Operations Research*, 131(1), 259-282. https://doi.org/10.1023/B:ANOR.0000039522.58036.68
- Petschnigg, C., Brandstötter, M., Pichler, H., Hofbaur, M., & Dieber, B. (2019, 20-24 May 2019). Quantum Computation in Robotic Science and Applications. (Ed.),^(Eds.). 2019 International Conference on Robotics and Automation (ICRA).
- Rosenberg, G., Vazifeh, M., Woods, B., & Haber, E. (2016). Building an iterative heuristic solver for a quantum annealer. *Computational Optimization and Applications*, 65(3), 845-869. https://doi.org/10.1007/s10589-016-9844-y
- Szeider, S. (2011). The parameterized complexity of k-flip local search for SAT and MAX SAT. *Discrete Optimization*, 8(1), 139-145. <u>https://doi.org/10.1016/j.disopt.2010.07.003</u>
- von Lilienfeld, O. A. (2018). Quantum Machine Learning in Chemical Compound Space [https://doi.org/10.1002/anie.201709686]. Angewandte Chemie International Edition, 57(16), 4164-4169. https://doi.org/https://doi.org/10.1002/anie.201709686
- Wang, H., & Alidaee, B. (2019). Effective heuristic for large-scale unrelated parallel machines scheduling problems. Omega, 83, 261-274. <u>https://doi.org/https://doi.org/10.1016/j.omega.2018.07.005</u>
- Wang, H., Alidaee, B., Ortiz, J., & Wang, W. (2020). The multi-skilled multi-period workforce assignment problem. *International Journal of Production Research*, 1-18. <u>https://doi.org/10.1080/00207543.2020.1783009</u>
- Wang, H., Wang, W., Liu, Y., & Alidaee, B. (2022). Integrating Machine Learning Algorithms With Quantum Annealing Solvers for Online Fraud Detection. *IEEE Access*, 10, 75908-75917. https://doi.org/10.1109/ACCESS.2022.3190897
- Xu, G., & Oates, W. S. (2021). Adaptive hyperparameter updating for training restricted Boltzmann machines on quantum annealers. *Scientific Reports*, 11(1), 2727. <u>https://doi.org/10.1038/s41598-021-82197-1</u>
- Yagiura, M., & Ibaraki, T. (1999). Analyses on the 2 and 3-Flip Neighborhoods for the MAX-SAT. *Journal* of Combinatorial Optimization, 3(1), 95-114. <u>https://doi.org/10.1023/A:1009873324187</u>
- Yagiura, M., & Ibaraki, T. (2001). Efficient 2 and 3-Flip Neighborhood Search Algorithms for the MAX-SAT: Experimental Evaluation. *Journal of Heuristics*, 7(5), 423-442. <u>https://doi.org/10.1023/A:1011306011437</u>
- Yagiura, M., Kishida, M., & Ibaraki, T. (2006). A 3-flip neighborhood local search for the set covering problem. *European Journal of Operational Research*, 172(2), 472-499. https://doi.org/https://doi.org/10.1016/j.ejor.2004.10.018
- Yawata, K., Osakabe, Y., Okuyama, T., & Asahara, A. (2022, 30 Nov.-1 Dec. 2022). QUBO Decision Tree: Annealing Machine Extends Decision Tree Splitting. (Ed.),^(Eds.). 2022 IEEE International Conference on Knowledge Graph (ICKG).