Fast Algorithms and Implementations for Computing the Minimum Distance of Quantum Codes

Fernando Hernando¹

Gregorio Quintana-Ortí 2

Markus Grassl³

August 21, 2024

Abstract

The distance of a stabilizer quantum code is a very important feature since it determines the number of errors that can be detected and corrected. We present three new fast algorithms and implementations for computing the symplectic distance of the associated classical code. Our new algorithms are based on the Brouwer-Zimmermann algorithm. Our experimental study shows that these new implementations are much faster than current state-of-the-art licensed implementations on single-core processors, multicore processors, and shared-memory multiprocessors. In the most computationally-demanding cases, the performance gain in the computational time can be larger than one order of magnitude. The experimental study also shows a good scalability on shared-memory parallel architectures.

1 Introduction

Quantum computing can be considered as a paradigm shift in computational theory, poised to redefine the boundaries of theory and practice of computing. Departing from the binary system of classical computing, quantum computers leverage the principles of quantum mechanics to operate with quantum bits, or qubits. Unlike classical bits, which can be either 0 or 1, qubits can exist in multiple states simultaneously due to the phenomenon of superposition [11]. Additionally, qubits can be entangled, a property that allows for instantaneous correlation between them, no matter the distance [11].

This fundamental difference enables quantum computers to perform certain calculations exponentially faster, promising groundbreaking advancements across various domains, including cryptography, optimization, and material science. In cryptography, quantum computers have the potential to break widely-used encryption methods, requiring the development of quantum-resistant algorithms [14]. In optimization, they can solve complex problems in logistics, finance, and artificial intelligence more efficiently than classical computers [4]. In material science, quantum simulations could lead to the discovery of new materials and drugs by accurately modeling molecular interactions [10].

Quantum error-correcting codes (QECCs) are a key component to the practical viability of quantum computing, addressing the inherent fragility of quantum systems to noise and decoherence. In essence, quantum error correction addresses the fundamental challenge of preserving quantum coherence in the presence of environmental disturbances. Without error correction, quantum information stored in qubits would quickly degrade, rendering quantum computations unreliable. By leveraging the principles of quantum mechanics, quantum error-correcting codes can detect and correct errors without directly measuring the qubits, thus preserving the delicate quantum superposition, which is essential for quantum computing [5].

The development of fault-tolerant quantum computation, made possible by quantum error correction, is crucial in scaling quantum algorithms to tackle real-world challenges effectively. As

¹Depto. de Matemáticas, Universidad Jaume I, 12.071–Castellón, Spain. carrillf@mat.uji.es

 $^{^2 \}mathrm{Depto.}$ de Ingeniería y Ciencia de Computadores, Universidad Jaume I, 12.071–Castellón, Spain.

gquintan@uji.es

³International Centre for Theory of Quantum Technologies (ICTQT), University of Gdansk, Gdańsk, Poland. markus.grassl@ug.edu.pl

quantum computers continue to evolve, the synergy between quantum computing and quantum error correction underscores the transformative potential of quantum technologies in revolutionizing computation and information processing.

Most of the quantum error-correcting codes discussed in the literature are stabilizer codes, whose minimum distance serves as a critical measure of error detection and correction capabilities. Stabilizer codes, such as those introduced by Daniel Gottesman and the quantum error correction codes over GF(4) pioneered by Calderbank and Shor, encode qubits into highly entangled states, thereby safeguarding quantum information against disruptions. These codes play a vital role in preserving quantum coherence and maintaining the integrity of quantum information during computation [5, 3, 9, 11].

The aim of our work is to accelerate the computation of the minimum distance of a random stabilizer code, a task essential for assessing its error-correcting capabilities. By determining the minimum distance, insights into the code's ability to detect and correct errors is gained, which is key to the practical viability of quantum computing.

This analysis contributes to the ongoing efforts in quantum error correction, paving the way for the development of fault-tolerant quantum computation. Such advancements are fundamental for scaling quantum algorithms to effectively tackle real-world challenges across various domains, showcases the revolutionary impact of quantum technologies on computation and data processing.

Stabilizer codes, essential in quantum coding, emerge when the associated classical stabilizer code is a subset of its symplectic dual, leading to quantum codes with specific properties. Our study focuses on computing the minimum distance of randomly-generated quantum stabilizer codes for qubits by analyzing the symplectic weight of linear combinations of rows of the normalizer matrix. To achieve this, we have developed three new algorithms and implementations. Each one employs unique approaches for matrix manipulation and diagonalization to compute the symplectic minimum distance.

Our experimental analysis assesses these three new implementations and compares them to a state-of-the-art licensed software (MAGMA). The performance assessments encompassed matrices of different sizes and complexities. Our implementations consistently outperformed MAGMA, being faster for most of the codes assessed. Particularly, the speedups were remarkable: Our new implementations were up to 40 times as fast as MAGMA in the most-demanding cases.

The rest of the paper is organized as follows: Section 2 describes the new algorithms and implementations developed in our work. Section 3 contains a comparative analysis of the implementations of our new algorithms. Finally, Section 4 enumerates the conclusions of our work.

2 Algorithms and implementations

The symplectic weight of any vector $(a, b) \in \mathbb{F}_q^{2n}$, with $a, b \in \mathbb{F}_q^n$, is defined as follows:

$$wt_s(a, b) = \#\{i \mid a_i \neq 0 \text{ or } b_i \neq 0\}.$$

For any set $C \subset \mathbb{F}_q^{2n}$, the symplectic weight is defined as the minimum of all such weights within C:

$$\operatorname{wt}_{s}(C) = \min\{\operatorname{wt}_{s}(a,b) \mid (a,b) \in C \setminus \{(0,0)\}\}.$$

Moreover, the symplectic inner product over \mathbb{F}_q^{2n} is defined as:

$$(a,b) \cdot_s (c,d) = a \cdot d - b \cdot c,$$

where $a \cdot d$ and $b \cdot c$ denote the Euclidean inner products.

Given an \mathbb{F}_q -linear subspace $C \subset \mathbb{F}_q^{2n}$, the symplectic dual is defined as:

$$C^{\perp_s} = \{ (a, b) \in \mathbb{F}_q^{2n} \mid (a, b) \cdot_s (c, d) = 0, \quad \forall (c, d) \in C \}.$$

Stabilizer codes are constructed as follows: Given $C \subset \mathbb{F}_q^{2n}$, an \mathbb{F}_q -linear subspace with parameters $[2n, n-k, d]_q$ such that $C \subset C^{\perp_s}$, then there exists a quantum code $Q \subset (\mathbb{C}^q)^{\otimes n}$ with parameters $[n, k, d(Q)]_q$, where $d(Q) = \operatorname{wt}_s(C^{\perp_s} \setminus C)$ for k > 1, and $d(Q) = \operatorname{wt}_s(C)$ for k = 0. The code C is referred to as the *classical stabilizer code* associated to Q, and its symplectic dual C^{\perp_s} is referred to as the *classical normalizer code* associated to Q.

The objective of this study is to compute the minimum distance d(Q) of a randomly generated quantum stabilizer code Q. To achieve this, one must examine a generator matrix of the classicial normalizer code associated to Q, which is an $(n + k) \times 2n$ matrix A over \mathbb{F}_q^{2n} . We refer to A as the *normalizer matrix* of Q. Consequently, the symplectic weight of any \mathbb{F}_q -linear combination of rows of A becomes the focal point of research.

Notice that in MAGMA the normalizer matrix A in so-called *extended form* is obtained from Q as:

A := NormalizerMatrix(Q: ExtendedFormat := true);

We focus on the particular case where q = 2, i.e., so-called qubit codes. Therefore, we study the symplectic weight of the sum over any subset of rows of A, with the restriction that the resulting codeword must be in $C^{\perp_s} \setminus C$ when k > 0.

We have implemented three different algorithms for computing the minimum distance of a random qubit stabilizer code, namely: SAVED_1_ Γ , SAVED_2_ Γ , and SAVED_ISOMETRY. The details of these algorithms and implementations will be described next.

2.1 Modified Brouwer-Zimmerman Algorithm

Determining the minimum weight of a random linear code C requires finding the smallest non-zero Hamming weight among all codewords in C, which can be defined as $\min\{\operatorname{wt}(c) \mid c \in C \setminus \{0\}\}$. When the code operates over \mathbb{F}_q and has a dimension of k, it has q^k codewords. Obviously, computing the minimum of the weight of all those codewords becomes unfeasible even for medium and large values of q and k.

The fastest general algorithm for computing the minimum distance of a random linear code is the so-called Brouwer-Zimmermann algorithm [16], which is described in detail by Grassl [6]. There is an implementation of this algorithm in the closed-source MAGMA [2] over any finite field, whereas there is an open-source implementation in GAP (concretely, in the Guava package) [1, 7] over the fields \mathbb{F}_2 and \mathbb{F}_3 .

To address the challenge of computing the minimum weight, the Brouwer-Zimmerman algorithm introduces an upper bound U and a lower bound L. If $L \ge U$, then the true minimum weight is U. The upper bound U is updated whenever a new codeword c is discovered with a weight wt(c)lower than U. On the other hand, the lower bound L is derived from using possibly more than one systematic generator matrix Γ_i for the code C. Considering linear combinations of w rows, the resulting codeword has weight at least w in each of the information sets. The lower bound L can be increased every time a new enumeration of linear combinations of rows of the generator matrices Γ_i initiates with a different cardinality. This approach streamlines the process, significantly reducing the computational times.

The Modified Brouwer-Zimmerman algorithm additionally checks whether a discovered codeword c with weight lower than U is also in $C^{\perp_s} \setminus C$ before updating U. In the exceptional case where k = 0, the code is self-dual, and the check to see whether it is in $C^{\perp_s} \setminus C$ does not apply. In this situation, we always update U with the new codeword's weight. We denote the case where the algorithm assesses the minimum Hamming distance as MODIFIED_BROUWER_ZIMMERMANN, and the case where it assesses the symplectic minimum distance as MODIFIED_BROUWER_ZIMMERMANN_s.

A fast implementation of the Brouwer-Zimmermann algorithm for both single-core architectures and shared-memory parallel architectures (multicore and multiprocessor architectures) was recently introduced [8]. This work offered performances about two or three times as fast as those of MAGMA and Guava (GAP) over \mathbb{F}_2 by saving and reusing the additions of combinations. A novel implementation for multicomputers and distributed-memory architectures was also recently introduced [12]. It allows the use of thousands of cores for computing the distance, thus notably reducing the total computational time from days to seconds.

We have taken advantage of these algorithms and implementations for single-core architectures and shared-memory parallel architectures, based on the idea of saving and reusing the additions of combinations, to develop new fast implementations for computing the minimum distance of quantum stabilizer codes. Next, we describe our new three algorithms and implementations for computing the minimum distance of quantum stabilizer codes.

2.2 Algorithm Saved_1_ Γ

Given a matrix A of dimension $(n+k) \times 2n$, where $0 \le k \le n$, we must ensure that the n+k rows are linearly independent over \mathbb{F}_2 . Although standard diagonalization algorithms can be applied, an additional constraint is imposed: any column permutation applied within the first half of the columns must be correspondingly applied within the second half (and vice versa). Additionally, one may swap the *i*-th column in the first half with the *i*-th column in the second half. This restriction arises from the symplectic weight's consideration of mirrored coordinates, prohibiting the permutation of one without its corresponding reflection.

This process results in a matrix of the form:

$$B = \begin{pmatrix} I_n & M_1 \\ 0 & M_2 \end{pmatrix}$$

where I_n is the identity matrix of dimension n, M_1 is an $n \times n$ matrix, and M_2 is a $k \times n$ matrix in row-echelon form.

Next, for i = 1, ..., k, determine the column j_i in the matrix M_2 such that the position $(i, j_i) = 1$ and all elements to the left and all elements below are zero. The row j_i of the matrix B is added to the *i*-th row for M_2 , and the sum is appended to B as a new row. Let \tilde{B} be the resulting modified matrix and let this process be denoted as DIAGONALIZATION_OVER_F₂, then $\tilde{B} = \text{DIAGONALIZATION}_\text{OVER}_F_2(A)$.

Afterwards, the MODIFIED_BROUWER_ZIMMERMANN_s is employed, assessing the symplectic weight instead of the Hamming weight.

The rationale for considering the matrix \tilde{B} instead of the matrix A is illustrated with the following example. Assume A is defined as follows:

$$A = \begin{pmatrix} 1 & 0 & 0 & 1 \\ 0 & 1 & 1 & 0 \\ 0 & 0 & 1 & 1 \end{pmatrix}.$$

The matrix A is already in echelon form, so A = B. The matrix B is given by

$$\widetilde{B} = \begin{pmatrix} 1 & 0 & 0 & 1 \\ 0 & 1 & 1 & 0 \\ 0 & 0 & 1 & 1 \\ 1 & 0 & 1 & 0 \end{pmatrix}.$$

When MODIFIED_BROUWER_ZIMMERMANN_s(A) is applied, it first considers the symplectic weight of each row of A and finds the upper bound U = 2. Then, before considering the sum of any two rows, the lower bound L is set to 2. Hence $L \ge U$, and the result is a symplectic minimum distance of 2. In contrast, applying MODIFIED_BROUWER_ZIMMERMANN_s(\tilde{B}) results in the correct symplectic minimum distance of 1. This example demonstrates the importance of considering \tilde{B} to achieve the true symplectic minimum distance.

Algorithm 1 SAVED_1_ Γ

Require: A normalizer matrix A of size $(n + k) \times 2n$ of a quantum stabilizer code Q. Ensure: The minimum weight of Q.

1: Beginning of Algorithm

2: $B := \text{DIAGONALIZATION_OVER}_{\mathbb{F}_2}(A);$

- 3: d := MODIFIED_BROUWER_ZIMMERMANN_s(B);
- 4: return d;
- 5: End of Algorithm

2.3 Algorithm Saved_2_ Γ

This algorithm works on a matrix over \mathbb{F}_4 resulting from a modification of A. Let assume that $\{1, \alpha\}$ forms a basis of \mathbb{F}_4 over \mathbb{F}_2 . Then, a new matrix over \mathbb{F}_4 , denoted as A_4 , is constructed

as follows: The rows of A_4 are formed by $a + \alpha b$, where (a, b) represents a row of A. It is worth noting that the linear code over \mathbb{F}_2 with generator matrix A is isometric to the additive code with generator matrix A_4 . The symplectic weight for the code over \mathbb{F}_2 of length 2n corresponds to the Hamming weight for the code over \mathbb{F}_4 of length n. Here, by "additive," we refer to linearity over \mathbb{F}_2 rather than over \mathbb{F}_4 , therefore only additions between rows are allowed.

Diagonalization over A_4 is computed, noting its linearity over \mathbb{F}_2 . This restricts us to considering row additions exclusively, as multiplications by α or α^2 are prohibited. Thus, one can, for example, nullify α^2 within a given row only by adding another row with α^2 at the same position, or by adding two other rows containing α and 1, respectively, at the same position.

Subsequently, columns and rows are permuted. The current column can be swapped only with one of the next columns. Analogously, the current row can be swapped only with one of the next rows. The current row is also use to "clear" the entries in the same column above and below. Here "clear" refers to making all the other elements either zero or equal to a non-zero element of \mathbb{F}_4 different from the current pivot element.

Columns containing two different non-zero symbols at the desired positions are prioritized, resorting to row permutation if necessary. When there are two different non-zero symbols, all the other entries in the same column can be cleared. However, it is possible that among the remaining columns, a column with two different non-zero symbols cannot be found at the desired positions. Consequently, the last columns may have more than two non-zero entries. Thus, at the conclusion of the diagonalization, for example, a matrix of the following form is obtained:

$$A_4 = \begin{pmatrix} 1 & 0 & 0 & \star & * & * \\ \alpha & 0 & 0 & \star & * & * \\ 0 & 1 & 0 & \star & * & * \\ 0 & \alpha^2 & 0 & \star & * & * \\ 0 & 0 & \alpha & \star & * & * \\ 0 & 0 & \alpha^2 & \star & * & * \\ 0 & 0 & 0 & \alpha & \star & * \end{pmatrix}$$

In the example, the entries marked by \star in the fourth column are either 0 or 1.

Next, the following algorithm is implemented, processing the columns from left to right: Whenever a column contains exactly two non-zero elements that are different, if the corresponding rows have not yet been processed, their sum is appended as a new row to A_4 . The resulting matrix at the end of this process is denoted as B_4 , denoted by $B_4 := \text{DIAGONALIZATION_OVER}_{\mathbb{F}_4}(A_4)$.

Know we explain the reason for these extra rows and why the algorithm works. Whenever we add a new row to A_4 , the corresponding column in the final matrix B_4 will have exactly three nonzero entries 1, α , and α^2 . The corresponding rows form a *package*, corresponding to an element of an information set in the linear case. Rows which have only a single pivot element, like the last row of A_4 in the example, form a package with a single element. For a package with three element, the sum of any pair of rows equals the other row, and hence we do not need to consider sums of different rows from the same package. For packages with a single row, the element in the corresponding column cannot be cancelled by the entries in other rows. Therefore, if we consider the sum of g rows of the final matrix B_4 , we can ensure that the Hamming weight is at least g if each row comes from a different packet. In other words, the weight is higher than or equal to the number of packets involved in the sum. So, after enumerating all the linear combinations of up to g rows of B_4 , where each row comes from a different package, we can obviously guarantee that L > g.

This is illustrated with the following example. Assume A_4 is defined as follows:

$$A_4 = \begin{pmatrix} 1 & 1 & 1 & 1 \\ \alpha & 0 & \alpha & \alpha \\ 0 & \alpha^2 & \alpha^2 & \alpha^2 \end{pmatrix}$$

The matrix B_4 is given by

$$B_4 = \begin{pmatrix} 1 & 1 & 1 & 1 \\ \alpha & 0 & \alpha & \alpha \\ 0 & \alpha^2 & \alpha^2 & \alpha^2 \\ \alpha^2 & 1 & \alpha^2 & \alpha^2 \end{pmatrix}$$

When the modified Brouwer-Zimmermann algorithm is applied to A_4 , we start with L = 1and U = 4. After enumerating one generator codewords we get L = 2 and U = 3, and after enumerating two generators codewords we get L = 3 and U = 3, so the symplectic minimum distance is 3. In contrast, applying the same algorithm to B_4 , we start with L = 1 and U = 4. After enumerating one generator codewords we get L = 2 and U = 3, and after enumerating two generators codewords we get L = 2 and U = 3, and after enumerating two generators codewords we get L = 3 and U = 2, so the symplectic minimum distance is 2.

It is worth mentioning that the last two columns of A_4 are not utilized in the diagonalization process. Generally, this could involve a number of columns of undetermined cardinality, which we refer to as the set of principal columns. Therefore, these columns may be rearranged to the first positions, and a new diagonalization can be performed solely with this set of principal columns.

This new matrix is denoted as C_4 . Similarly, whenever a principal column contains exactly two different non-zero symbols, the addition of the corresponding rows is appended as a new row to C_4 , resulting in a new matrix, D_4 . This process is denoted as $D_4 := \text{DIAGONALIZATION_OVER_F}_4(C_4)$.

For the previous example, these matrices are

$$C_4 = \begin{pmatrix} 1 & 1 & 1 & 1 \\ \alpha & \alpha & \alpha & 0 \\ 0 & 0 & \alpha^2 & \alpha \end{pmatrix}$$

and

$$D_4 = \begin{pmatrix} 1 & 1 & 1 & 1 \\ \alpha & \alpha & \alpha & 0 \\ 0 & 0 & \alpha^2 & \alpha \\ \alpha^2 & \alpha^2 & \alpha^2 & 1 \end{pmatrix}.$$

Then, B_4 and D_4 are transformed back into matrices over \mathbb{F}_2 by reversing the process done previously. Specifically, a row of the form $a + \alpha b \in \mathbb{F}_4^n$ is transformed into the row $(a, b) \in \mathbb{F}_2^{2n}$. The resulting matrices over \mathbb{F}_2 are denoted as B_2 and D_2 .

In the previous example, these matrices are

$$B_{2} = \begin{pmatrix} 1 & 1 & 1 & 1 & | & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & | & 1 & 0 & 1 & 1 \\ 0 & 1 & 1 & 1 & | & 0 & 1 & 1 & 1 \\ 1 & 1 & 1 & 1 & | & 1 & 0 & 1 & 1 \end{pmatrix}$$
$$D_{2} = \begin{pmatrix} 1 & 1 & 1 & 1 & | & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & | & 1 & 1 & 1 & 0 \\ 0 & 0 & 1 & 0 & | & 0 & 0 & 1 & 1 \\ 1 & 1 & 1 & 1 & | & 1 & 1 & 0 \end{pmatrix}.$$

and

Subsequently, the modified Brouwer-Zimmermann algorithm is applied using the two generator matrices B_2 and D_2 , obtaining the symplectic weight instead of the Hamming weight.

During this procedure, the second generator matrix D_2 contributes to adjusting the lower bound of the minimum distance only if a specific technical condition is met. Let us clarify this further. From the previous explanation of the matrices' construction, it is clear that we can analyze either D_2 or D_4 . In this context, we will focus on D_4 .

In our earlier discussion, it was shown how to partition the rows of B_4 into packages, defining $n_p(B_4)$ as the total number of these packages. Applying the same approach to D_4 , $n_p(D_4)$ represents the number of packages of the entire matrix D_4 , and $n_{pp}(D_4)$ is the number of packages of the principal columns of the same matrix.

A key observation is that the diagonalization of B_4 separates it into two independent components: the principal columns, which have already been considered, and the remaining columns. As a result, it is possible that $n_p(B_4)$ might not be equal to $n_p(D_4)$. Note that rows consisting entirely of zeros are excluded from forming any packages.

We have established that any codeword can be generated using at most one row from each package of B_4 , meaning the number of generators g considered in summations is at most $n_p(B_4)$. Similarly, for D_4 , the number of generators g is constrained by $n_p(D_4)$. In conclusion, when the number of generators is greater than or equal to $n_p(D_4) - n_{pp}(D_4)$, the matrix D_2 contributes with $g - n_p(D_4) + n_{pp}(D_4) + 1$ to L, i.e., after fully enumerating all sums of g generators we have

$$L := g + 1 + \max\{0, g + 1 + n_{pp}(D_4) - n_p(D_4)\}.$$

Consequently, based on our experimental results, D_2 will only contribute when k is relatively small. Section 3 includes a specialized dataset, mat_test4, designed for matrices with small values of k. This dataset highlights the increased importance and effectiveness of the algorithm in such scenarios.

Algorithm 2 SAVED_2_ Γ

```
Require: A normalizer matrix A of size (n + k) \times 2n of a quantum stabilizer code Q.
Ensure: The minimum weight of Q.
```

- 1: Beginning of Algorithm
- 2: $A_4 := \text{TRANSFORM}_\text{MATRIX}_{\mathbb{F}_2}\mathbb{F}_4(A)$:
- 3: $B_4 := \text{Diagonalization_over}_{\mathbb{F}_4}(A_4);$
- 4: $D_4 := \text{Diagonalization_over}_{\mathbb{F}_4}(B_4);$
- 5: $B_2 := \text{TRANSFORM}_\text{MATRIX}_\mathbb{F}_4_\mathbb{F}_2(B_4);$
- 6: $D_2 := \text{TRANSFORM}_\text{MATRIX}_\mathbb{F}_4_\mathbb{F}_2(C_4);$
- 7: d := MODIFIED_BROUWER_ZIMMERMANN_s({ B_2, D_2 });
- 8: **return** d;
- 9: End of Algorithm

2.4 Algorithm Saved_isometry

We essentially follow the methodology outlined by White [15]. The modified matrix B is built from A by extending every row of the latter, denoted as $(a, b) \in \mathbb{F}_2^{2n}$, into the new row $(a, b, a + b) \in \mathbb{F}_2^{3n}$. This mapping is denoted as ISOMETRY_TRANSFORMATION, since the Hamming weight of the image (a, b, a + b) equals twice the symplectic weight of (a, b). The new matrix B :=ISOMETRY_TRANSFORMATION(A) indeed serves as the generator matrix of a linear code over \mathbb{F}_2 . Subsequently, the Hamming minimum distance of the linear code with the generator matrix provided by B is computed. To accomplish this task, the Modified Brouwer-Zimmermann algorithm is used for computing the Hamming weight. Finally, the true minimum distance of Q is computed as the Hamming minimum distance of B divided by two.

Algorithm 3 SAVED_ISOMETRY

Require: A normalizer matrix A of size $(n + k) \times 2n$ of a quantum stabilizer code Q. Ensure: The minimum weight of Q.

- 1: Beginning of Algorithm
- 2: $B := ISOMETRY_TRANSFORMATION(A);$
- 3: $d_1 := \text{MODIFIED}_B\text{ROUWER}_Z\text{IMMERMANN}(B);$
- 4: $d := \frac{d_1}{2};$

```
5: return d;
```

6: End of Algorithm

2.5 Availability of the implementations

To achieve high performance, our algorithms have been implemented with the C programming language, which usually offers high speed when compiled to machine language (the native code of the CPU of the target computer).

To increase both the availability and simplicity of using our implementations, we have compiled our C code to WebAssembly code with the Emscripten compiler (release 3.1.61). The WebAssembly [13] language is a portable binary-code format, with a higher level than machine languages. Its main goal is to enable high-performance applications on web pages. Hence, programs written in this language can be executed by the JavaScript interpreter included in most current browsers. However, although the code can be executed in any browser, it is obviously much slower than native code. Nevertheless, since the code can be executed in any browser, it does not require any installation, just opening a web page. This code is available at the following web page:

www3.uji.es/~gquintan/symplectic_distance

This page allows the user to compute the distance of quantum symplectic codes. Since it is executed by the JavaScript interpreter of the browser, it is also executed in the local (user's computer) CPU. Since JavaScript is single-threaded in browsers, one drawback of this approach is that all output messages are only shown when all the computation has finished.

The input matrix A is the normalizer matrix in extended format. If the quantum code is Q, the input matrix can be obtained in MAGMA with the following command:

A := NormalizerMatrix(Q: ExtendedFormat := true);

3 Performance Analysis

In this study we assessed all the implementations on a server with 16 cores (AMD EPYC 7F52 at 2.0 GHz) and a main memory of 512 GB. The operating system is Ubuntu 20.04.6 LTS, and the C compiler is GNU gcc (Ubuntu 9.4.0-1ubuntu1 20.04.2) 9.4.0.

Several other computers were assessed, obtaining similar results with our implementations. The results on these computers are not reported since MAGMA was not installed on them (since it is a licensed software), and therefore no comparison could be performed.

The implementations assessed in this work are the following ones:

- MAGMA [2]: It is a licensed software package designed for computations in algebra, algebraic combinatorics, algebraic geometry, etc. Version V2.26-10 was employed in our experiments. The implementation without AVX vectorization was employed since it was faster than the vectorized versions due to the short length of the vectors being processed.
- SAVED_1_ Γ : This implementation of ours uses one Γ matrix by using a diagonalization over \mathbb{F}_2 . No vectorization was employed for the sake of a fair comparison with MAGMA.
- SAVED_2_Γ: This implementation of ours uses two Γ matrices by using a diagonalization over F₄. No vectorization was employed for the same reason.
- SAVED_ISOMETRY: This implementation of ours uses the isometry method described above. No vectorization was employed for the same reason.

All plots included in this study are of two types: Some plots show the times, and therefore lower is better. On the other hand, other plots show the speedups of the new implementations when compared to MAGMA, and therefore higher is better for the new implementations. The speedup of an implementation is computed as the time of MAGMA divided by the time of that implementation, and therefore it is the number of times that the latter faster than MAGMA.

In order to assess all the implementations, about two thousand normalizer matrices in extended format of dimension $K \times N$ with K = n+k and N = 2n for stabilizer codes $[\![n, k, d]\!]_2$ were processed, all of them generated randomly. These matrices were grouped into the following four different tests or datasets:

• mat_test1: It comprises 286 small matrices generated randomly. The maximum number of elements of the matrices in this dataset was 3552. The minimum, average, and maximum ratio K/N of these matrices (of dimension $K \times N$) was 0.519, 0.673, and 0.958, respectively. This dataset was employed to check that the symplectic distances computed by our new implementations were the same as those of MAGMA. Since the matrices were small, the computational time was very small, and therefore performances are not reported.

- mat_test2: It comprises 1650 small matrices generated randomly. The maximum number of elements of the matrices in this dataset was 3384. The minimum, average, and maximum ratio K/N of these matrices (of dimension $K \times N$) was 0.519, 0.677, and 0.958, respectively. This dataset was employed to check the symplectic distances. Since the matrices were small, performances are not reported.
- mat_test3: It comprises 300 medium and large matrices generated randomly. The maximum number of elements of the matrices in this dataset was 12416. The minimum, average, and maximum ratio K/N of these matrices (of dimension $K \times N$) was 0.586, 0.654, and 0.758, respectively. Because of this, usually only one Γ matrix contributed to the lower bound in the Brouwer-Zimmermann algorithm. As this dataset and the next one contained larger matrices (usually with a larger computational cost), they were employed to assess performances. Nevertheless, symplectic distances were also checked.

Matrices of this dataset in which MAGMA took less than 1 second when using one core were discarded, thus keeping 221 matrices in total with significant computational times. These remaining matrices were classified according to their computational time in MAGMA when using one core into the following subtests or subdatasets:

- Subtest a: It contains those matrices in which MAGMA took [1, 10) seconds.
- Subtest b: It contains those matrices in which MAGMA took [10, 100) seconds.
- Subtest c: It contains those matrices in which MAGMA took [100, 1000) seconds.
- Subtest d: It contains those matrices in which MAGMA took [1 000, 10 000) seconds.
- Subtest e: It contains those matrices in which MAGMA took 10000 seconds or more.
- mat_test4: It comprises 11 medium and large matrices especially designed to benefit algorithms that employ two Γ matrices. The maximum number of elements of the matrices in this dataset was 9100. The minimum, average, and maximum ratio K/N of these matrices (of dimension $K \times N$) was 0.538, 0.542, and 0.545, respectively. As before, symplectic distances were also checked.

3.1 Performances on one core

This subsection reports results on the mat_test3 and mat_test4 datasets, since their computational times are much longer than the first two datasets.

When assessing all implementations for the mat_test3 dataset on one core, our new implementations SAVED_2_ Γ , SAVED_1_ Γ , and SAVED_ISOMETRY outperformed MAGMA in 200 cases out of 221 (90.5 %), 209 cases out of 221 (94.6 %), and 218 cases out of 221 (98.6 %), respectively. The few cases in which MAGMA was faster belonged to the subtests *a* and *b* (and most of them to the first one). Recall that subtest *a* comprises all cases with computational times in [1.0, 10.0) and subtest *b* comprises all cases with computational times in [10.0, 100.0).

Figure 1 shows a comparison of MAGMA and our implementations for all matrices in the mat_test3 dataset. To compare both MAGMA and our new implementations, this figure shows speedups. A circle \circ represent the data point for the speedup for a matrix. For example, if the vertical coordinate of one of our implementations is 10, it means that it is 10 times as fast as MAGMA. To avoid many symbols overlapping in one place, a random small value has been added to the horizontal coordinate. The continuous line and the dashed line represent the median and the mean, respectively, of all the speedups of one implementation.

As this figure shows, the speedups of SAVED_2_F are usually larger than one, thus being faster than MAGMA in most cases. On the other side, the speedups of SAVED_1_F and SAVED_ISOMETRY are indeed remarkable. The median speedups of these two implementations with respect to MAGMA are usually between around 5 and around 45. Therefore, the computational times of our two implementations are between around 5 and around 45 times smaller than MAGMA in median. It is also important to note that the speedups obtained grow as the computational times grow. Recall that each subtest (shown in one plot of that figure) requires a higher (around an order of magnitude) computational time than the previous one.



Figure 1: Speedups of our new implementations with respect to MAGMA for all matrices in the mat_test3 dataset.

To analyze the previous results in more detail, Figures 2, 3, 4, 5, and 6 show a comparison of MAGMA and our implementations for a set of random samples extracted from each subset of the mat_test3 dataset. Each figure shows both the time in seconds (left plots) and the speedups (right plots) for the sample of the corresponding subset. The horizontal axis shows the matrix dimensions $(K \times N)$ and the symplectic distance (sd) in both types of plots.

As can be seen, our SAVED_1_ Γ and SAVED_2_ Γ implementations outperform MAGMA in most cases. It is also important to note how the speedups grow significantly as the computational time of MAGMA grows.

Figure 7 shows a comparison of MAGMA and our implementations on the mat_test4 dataset. This dataset contains matrices specially searched so that two Γ matrices would accelerate the time by contributing to the lower bound in the Brouwer-Zimmermann algorithm. As shown, SAVED_2_ Γ is usually around two times as fast as MAGMA.



Figure 2: Time in seconds (left) and speedups (right) for several matrices. In these plots MAGMA time is [1, 10). The horizontal axis shows the matrices assessed with their dimensions $(K \times N)$ and their symplectic distance (sd).



Figure 3: Time in seconds (left) and speedups (right) for several matrices. In these plots MAGMA time is [10, 100). The horizontal axis shows the matrices assessed with their dimensions $(K \times N)$ and their symplectic distance (sd).



Figure 4: Time in seconds (left) and speedups (right) for several matrices. In these plots MAGMA time is [100, 1000). The horizontal axis shows the matrices assessed with their dimensions $(K \times N)$ and their symplectic distance (sd).

3.2Parallel performances

Table 1 compares the computational times of MAGMA and our implementations with respect to the number of cores being employed. For every subset of mat_test3, the first matrix of the sample employed above was assessed. The MAGMA implementation has only been assessed on 1 and 4



Figure 5: Time in seconds (left) and speedups (right) for several matrices. In these plots MAGMA time is [1000, 10000). The horizontal axis shows the matrices assessed with their dimensions $(K \times N)$ and their symplectic distance (sd).



Figure 6: Time in seconds (left) and speedups (right) for several matrices. In these plots MAGMA time is ≥ 10000 s. The horizontal axis shows the matrices assessed with their dimensions $(K \times N)$ and their symplectic distance (sd).



Figure 7: Time in seconds (left) and speedups (right) for several matrices. The horizontal axis shows the matrices assessed with their dimensions $(K \times N)$ and their symplectic distance (sd).

cores since their performances decrease as the number of cores increases. As said before, the performances on one core of our SAVED_1_T and SAVED_ISOMETRY are remarkable. Moreover, unlike MAGMA (where using more than one core results often in a slow-down), our new implementations significantly accelerate their performances when using several cores, thus taking full advantage of modern shared-memory parallel architectures. For example, a computation (mat30020) that takes

	No.	subtest a	subtest b	subtest c	subtest d	subtest e
Implementation	cores	mat30005	mat30013	mat30015	mat30042	mat30020
Magma	1	1.63	46.55	583.64	1076.66	10012.45
	4	3.15	80.69	1294.61	2756.03	33722.99
Saved_2_ Γ	1	1.32	21.90	300.78	524.16	5769.85
	4	0.88	6.75	78.93	135.90	1450.25
	8	0.79	4.21	44.16	75.40	804.33
Saved_1_ Γ	1	0.28	3.84	38.33	68.16	518.73
	4	0.15	1.07	9.43	17.69	132.88
	8	0.13	0.66	5.28	9.91	70.80
SAVED_ISOMETRY	1	0.22	2.07	17.48	30.98	224.84
	4	0.16	0.73	4.65	8.43	57.98
	8	0.16	0.52	2.64	4.78	30.27

Table 1: Time in seconds of MAGMA and our implementations on one matrix of every subset when using several cores.

more than two hours and a half in MAGMA (when using one core and much more when using four cores) takes around half a minute in one of our new implementations.

Note the good scalability of our new implementations since in our implementations the ratio of the times on 1 core and 4 cores is usually very close to four, and that the ratio of the times on 1 core and 8 cores is usually very close to eight.

4 Conclusions

The symplectic distance of a stabilizer quantum code is a very important feature since it determines the number of errors that can be detected and corrected. This work presents three new fast implementations for computing the symplectic distance. Our new implementations are based on recent fast implementations of the Brouwer-Zimmermann algorithm. Our experimental study included several thousands of matrices. It shows that our new implementations are much faster than current state-of-the-art licensed implementations on single-core processors, multicore processors, and share-memory multiprocessors. In the most computationally-demanding cases, the performance gain in the computational time of our new implementations is usually larger than one order of magnitude. The largest performance gain in the computational time of our new implementations observed in the experimental study was around 45 times as fast. The scalability of our new implementations on shared-memory parallel architectures is also very good.

Contributor role statement

Hernando: Conceptualization, Methodology, Software, Validation, Formal analysis, Investigation, Data Curation, Writing - Original Draft, Visualization. **Quintana-Ortí**: Conceptualization, Methodology, Software, Validation, Formal analysis, Investigation, Data Curation, Writing - Original Draft, Visualization. **Grassl**: Conceptualization, Validation, Writing - Original Draft.

Acknowledgements

F. Hernando was partially funded by MCIN/AEI/10.13039/501100011033, by "ERDF: A way of making Europe" and by "European Union NextGeneration EU/PRTR" Grants PID2022-138906NB-C22 and TED2021-130358B-I00, as well as by Universitat Jaume I, Grants UJI-B2021-02 and GACUJIMB-2023-03.

G. Quintana-Ortí was supported by the Spanish Ministry of Science, Innovation and Universities under Grant RTI2018-098156-B-C54 co-financed with FEDER funds.

M. Grassl would like to thank for the hospitality during his visit of the University Jaume I. The 'International Centre for Theory of Quantum Technologies' project (contract no. 2018/MAB/5) is carried out within the International Research Agendas Programme of the Foundation for Polish Science co-financed by the European Union from the funds of the Smart Growth Operational Programme, axis IV: Increasing the research potential (Measure 4.3).

References

- Reinald Baart, Tom Boothby, Jasper Jasper Cramwinckel, Joe Joe Fields, Robert Joyner, David Miller, Eric Minkes, Erik Roijackers, Lea Ruscio, and Cen Tjhai, GUAVA, a GAP package for computing with error-correcting codes, version 3.12, 2012.
- [2] Wieb Bosma, John Cannon, and Catherine Playoust, The Magma algebra system. I. The user language, J. Symbolic Comput. 24 (1997), no. 3–4, 235–265, Computational algebra and number theory (London, 1993). MR 1484478
- [3] A. Robert Calderbank, Eric M. Rains, Peter W. Shor, and Neil J. A. Sloane, Quantum error correction via codes over GF(4), IEEE Transactions on Information Theory 44 (1998), no. 4, 1369–1387.
- [4] Edward Farhi, Jeffrey Goldstone, Sam Gutmann, Joshua Lapan, Andrew Lundgren, and Daniel Preda, A quantum adiabatic evolution algorithm applied to random instances of an NP-complete problem, Science 292 (2001), no. 5516, 472–475.
- [5] Daniel Gottesman, Stabilizer Codes and Quantum Error Correction, Ph.D. thesis, California Institute of Technology, Pasadena, California, 1997.
- [6] Markus Grassl, Searching for linear codes with large minimum distance, Discovering mathematics with Magma, Algorithms Comput. Math., vol. 19, Springer, Berlin, 2006, pp. 287–313.
- [7] The GAP Group, GAP Groups, Algorithms, and Programming, version 4.7.8, 2015.
- [8] Fernando Hernando, Francisco D. Igual, and Gregorio Quintana-Ortí, Algorithm 994: Fast implementations of the Brouwer-Zimmermann algorithm for the computation of the minimum distance of a random linear code, ACM Trans. Math. Softw. 45 (2019), no. 2.
- [9] Avanti Ketkar, Andreas Klappenecker, Santosh Kumar, and Pradeep Kiran Sarvepalli, Nonbinary stabilizer codes over finite fields, IEEE Transactions on Information Theory 52 (2006), no. 11, 4892–4914.
- [10] Sam McArdle, Suguru Endo, Alán Aspuru-Guzik, Simon Benjamin, and Xiao Yuan, Quantum computational chemistry, Reviews of Modern Physics 92 (2020), no. 1, 015003.
- [11] Michael A. Nielsen and Isaac L. Chuang, Quantum computation and quantum information, Cambridge University Press, Cambridge, UK, 2010.
- [12] Gregorio Quintana-Ortí, Fernando Hernando, and Francisco D. Igual, Algorithm 1033: Parallel implementations for computing the minimum distance of a random linear code on distributed-memory architectures, ACM Trans. Math. Softw. 49 (2023), no. 1.
- [13] Andreas Rossberg, WebAssembly Core Specification, https://www.w3.org/TR/ wasm-core-1/, December 2019.
- [14] Peter W. Shor, Algorithms for quantum computation: discrete logarithms and factoring, Proceedings 35th Annual Symposium on Foundations of Computer Science (1994), 124–134.
- [15] Greg White and Markus Grassl, A new minimum weight algorithm for additive codes, 2006 IEEE International Symposium on Information Theory, 2006, pp. 1119–1123.
- [16] Karl-Heinz Zimmermann, Integral Hecke modules, integral generalized Reed-Muller codes, and linear codes, Berichte des Forschungsschwerpunktes Informations- und Kommunikationstechnik, Techn. Univ. Hamburg-Harburg, 1996.