Supporting Online Discussions: Integrating AI Into the adhocracy+ Participation Platform To Enhance Deliberation

Maike Behrendt Heinrich Heine University maike.behrendt@hhu.de Stefan Sylvius Wagner Heinrich Heine University stefan.wagner@hhu.de Stefan Harmeling Technical University Dortmund stefan.harmeling@tu-dortmund.de

Abstract

Online spaces allow people to discuss important issues and make joint decisions, regardless of their location or time zone. However, without proper support and thoughtful design, these discussions often lack structure and politeness during the exchanges of opinions. Artificial intelligence (AI) represents an opportunity to support both participants and organizers of large-scale online participation processes. In this paper, we present an extension of adhocracy+, a large-scale open source participation platform, that provides two additional debate modules that are supported by AI to enhance the discussion quality and participant interaction.

1 Introduction

Online discussions and participation platforms bring people together to discuss issues that are of high relevance to society. However, it is well known that the written exchanges in online spaces are often characterized by incivility (Anderson et al., 2014) and lack of structure (Arana-Catania et al., 2021). To address these challenges, the concept of deliberation can be particularly useful. Deliberation is defined as the respectful, argumentative exchange of opinions, in order to reach a decision. Deliberation has three main dimensions: rationality, which refers to the argumentative exchange of opinions, civility, being polite and respectful, and finally *reciprocity*, being responsive and listening to each other (Bächtiger et al., 2009; Esau et al., 2021; Graham, 2010).

AI offers a promising opportunity for enhancing deliberation to assist both participants and organizers of online discussions to create a more structured, respectful, and engaging environment for meaningful exchange of opinions. In this work we propose two AI-based solutions for online discussions that we implemented for adhocracy+, an open source participation platform.

Our contributions:

- 1. **Comment Recommendation Module:** To encourage user interaction and confront participants with opposing views, we developed a comment recommendation function that is based on a stance detection model.
- 2. **Deliberative Quality Module:** To improve the engagement of users and the quality of contributed comments, we developed a debate module in which the most deliberative comments are automatically detected and highlighted.

The platform will be made available on GitHub after the review process.

Related work. Previous attempts to apply AI to support discussion platforms have mainly focused on structuring and summarizing discussions: The citizen participation tool Consul gives citizens the opportunity to make proposals to local politicians on how to improve their city. Proposals can be supported and discussed by other participants on the platform. To address the emerging problem of *information overload*, Arana-Catania et al. (2021) extended the platform with several natural language processing (NLP) methods to summarize existing proposals, automatically categorize them, and recommend proposals to participants based on their interests.

In the KOSMO project¹, a moderation dashboard was built for adhocracy+ to support moderators on the platform during an ongoing participation. Two models were trained to detect uncivil and engaging comments, which are proposed to the moderators, who could decide whether to take further action, such as blocking a detected uncivil comment.

Discussions on BCause, developed by Anastasiou et al. (2023), are supported by an automatic

¹https://kosmo-moderation.de/

text summarization tool and an argument recommendation system that suggests arguments from the scientific literature based on the user's opinion on the discussed topic. Other examples of open source discussion tools with AI features are discourse² and Polis (Small et al., 2021) from the Computational Democracy Project.

In our work, we focus on improving the discussion itself by enhancing deliberative features, such as reciprocity and rationality, directly. For this, we provide two new modules for the adhocracy+ platform that are designed to (i) recommend comments based on being *in favor* or *against* the discussed issue, hereby encouraging participants to react to opposing statements, and (ii) automatically highlight the most deliberative user comments, motivating users to write comments of higher quality.

Extending adhocracy+. Our platform extends adhocracy+³, an open source large-scale participation platform, developed by Liquid Democracy e.V. Adhocracy+, which is built with the Django framework⁴, offers a variety of functionalities and modules to set up large-scale citizen participation processes. The debate module on adhocracy+ has a forum-like structure, where a discussion subject is defined and displayed at the top of the discussion, allowing users to comment on the subject or respond to other participants' comments. More information about the platform's functionalities can be found on the adhocracy+ website⁵. In the following section we describe how we extended the debate module with AI functionality to create the new Comment Recommendation Module and the Deliberative Quality Module.

2 Enhancing Reciprocity with the Comment Recommendation Module

One of the biggest issues in online participation processes or even online discussions in general is the low level of participation and engagement of the users. This can be attributed to various reasons, such as lack of motivation or awareness about the process (Davies et al., 2021; Shortall et al., 2022), while some of these reasons are more rooted in the technical aspect of the discussion itself. One important issue is *information overload* (Arana-Catania et al., 2021) due to the large number of comments that are posted in the discussion. This makes it difficult for participants to keep track of the discussion (due to redundancy of posts, see Lago et al., 2019) and to engage with other participants, leading to a lack of reciprocity in the discussion. Another consequence of unorganized content resulting from the large number of comments is dysfunctional argumentation (Klein, 2007). One consequence of dysfunctional argumentation is the emergence of small groups of participants who share the same opinion who avoid interacting with groups holding differing views (Klein, 2015).

To increase reciprocity between participants and improve the quality of discussions, we build a comment recommendation module based on the adhocracy+ debate module. The comment recommendation module suggests a comment to participants that presents an opposing viewpoint to their own stance. For example, if the current user is *against* the debate question a comment from another participant with an *in favor* stance will be proposed.

Stance detection. To detect the stance of a comment, we use a fine-tuned BERT model (Devlin et al., 2019) that has been trained on the X-Stance stance detection dataset (Vamvas and Sennrich, 2020). Our model is a binary classifier which outputs either *in favor* or *against* given a debate question and a specific comment.

Due to the complexity and variety of the debate questions, it is challenging to obtain enough labeled data for stance detection. For that reason we follow Wagner et al. (2024) to generate synthetic data with large language models (LLMs), We use Mistral-7B (Jiang et al., 2023) to generate comments with an *in favor* and *against* stance. The generated comments are then used to further fine-tune the stance detection model. For existing comments the synthetic data can be used to identify the real comments which are most difficult for the model to classify. These comments can then manually labeled and help us to further improve the model, see Wagner et al. (2024) for more details.

Comment recommendation user experience. The main idea of the comment recommendation module is to propose a comment to the current user contrary to their own position or stance regarding the debate question. The first time a user logs into the platform their stance regarding the debate question will be asked. The user's stance which can either be *in favor* or *against* is then stored in the database and is used to determine which comments

²https://meta.discourse.org/

³https://github.com/liqd/adhocracy-plus

⁴https://www.djangoproject.com/

⁵https://adhocracy.plus/info/features/

A state of the	Elisha May 15, 2024, 7:57 p.m.
Folgender Kommentar wurde bereits zur Diskussion beigetragen. Möchten Sie darauf antworten? Kommentar von Pat3@hhu.de:	Ich denke es sollte erlaubt werden, aber eben mit Prüfungen, damit niemand ungewollt durch andere zu Schaden kommt. ∧ 0 ∨ 0 ♀ Reply ▲ Report
Die Regierung muss mehr Debatten führen, um das Thema der aktiven Sterbehilfe. Ich bin dafür wenn kein eigenes Atmen mehr möglich ist.	Payton May 15, 2024, 7:33 p.m.
Your reply	Es ist einfach schwierig finde ich, bei solchem Thema irgendwie auf einen gemeinsamen Nenner zu kommen.
0/4000 characters post	∧ 0 ∨ 0 Ω <u>Reply</u> ▲ Report

Figure 1: We propose two AI tools that we integrate into adhocracy+. (Left) Comment recommendation module: Participants are confronted with a comment that contradicts their own opinion and are asked if they want to respond. The AI tool determines the stance of the comments, which is used to propose opposing comments. Translation: The following comment has already been added to the discussion. Do you want to reply to it? (**Right**) Deliberative quality module: We predict a deliberative quality score (AQuA score) for each comment. Comments with a high AQuA score are sorted to the top of the discussion and highlighted in bright green and marked as "top comment".

to recommend. We then retrieve posted comments in the database that are contrary to the current user's stance. If there is more than one comment, we randomly suggest a comment from the list of contrary stance comments (Figure 1 on the left). Then, a popup window with that comment is displayed to the user and the user can reply. After that, the popup dialog is closed and the screen automatically jumps to the suggested comment in the discussion. By clicking a certain icon, the participant can also reopen the suggestion popup and a new comment with contrary stance (if available) is proposed and can be replied to.

3 Enhancing Debate Quality and Engagement With the Deliberative Quality Module

Besides disorganized content and dysfunctional argumentation (that diminishes reciprocity, see previous section), online discussions face other challenges, including low-quality contributions (Klein, 2007). Addressing this issue is crucial for fostering meaningful and productive conversations. In an observational study, Wang and Diakopoulos (2022) found that manually highlighting high-quality comments in the comment section of the New York Times (referred to as the New York Times Picks) increases the overall discussion quality and the user engagement. The authors suggest that highlighting well-written comments is beneficial to the quality of new comments as the picked comments constitute a social feedback mechanism (Wang and Diakopoulos, 2022). We want to build on these findings and develop a deliberative quality debate module which aims to promote high quality comments by automatically highlighting them. It remains to be investigated whether the human component, i.e., the selection by a New York Times editor, has a significant impact on the participants' perceptions, or whether simply highlighting the comments has the same effect. To measure the deliberativeness of a user comment, we calculate the AQuA score (Behrendt et al., 2024) for each comment and define a threshold for high quality.

AQuA score. The AQuA score, proposed by Behrendt et al. (2024), is a weighted sum of the predictions of individual BERT-based adapter models $f_{\theta_{h}}$, fine-tuned for 20 different deliberative quality indicators. These include, i.a., justification, proposing solutions, referencing other users and the use of sarcasm. Each adapter prediction is weighted with a number $w_k \in \mathbb{R}$ that is estimated from data. Some of the weights are positive, indicating a positive correlation between the respective feature and the overall quality of the comment, and some are negative, indicating a negative correlation. The total score for a comment c is calculated as $s_{AQuA}(c) = \sum_{k=1}^{20} w_k f_{\theta k}(c)$. AQuA scores are normalized to the range between 0 and 5. Note that the individual predictions of AQuA are trained



Figure 2: Overview of the architecture to extend adhocracy+ with our AI tools. (Left) The *debate module* imports both the *stance detection* and *deliberative quality score* AI's as Python modules. (**Right**) The Django database model sends out an event when a new comment is added to the database. The event is handled in signals.py where the new comment is passed either to the stance detection or deliberative quality model. These send a response (either a stance or quality score) back to the database where the corresponding response is stored.

on expert evaluations, which are combined with weights estimated from non-expert assessments, for details see Behrendt et al. (2024). In the deliberative quality debate module, AQuA scores allow us to identify high quality comments.

Deliberative quality user experience. The three comments with the highest quality are automatically identified as top comments and are displayed in the first position and highlighted in light green (see Figure 1 on the right, showing only a single top comment). To ensure that only high quality comments are highlighted, we threshold the scores. The exact threshold depends on the discussion and can be set as a hyperparameter.

4 Implementation Details

We extend adhocracy+ by importing the AI tools into the debate module, as shown in Figure 2 (left). A more detailed view is shown in Figure 2 on the right. When a new comment is added by a user, the Django debate model fires an event, which is handled in the signals.py file. Here, we import the AI tools to pass the comments to the stance detection or the deliberative quality model. Depending on which extension is being used, the AI tools then return a response (either a stance or deliberative quality score), which is stored back to the database for the corresponding comment. This stored response is then presented by the Comment Recommendation Module or the Deliberative Quality Module as shown in Figure 1.

Overall, this architecture is flexible: while we run the AI tools locally on a Linux server, the AI tools could also be run as services where communication is handled via Rest API.

5 Conclusion

In this work we present extensions to the adhocracy+ platform for citizen participation. We implemented two additional modules to support more deliberative online discussions. In the Comment Recommendation Module participants are confronted with opposing views to encourage user interaction, hence improving the reciprocity in the discussion. The Deliberative Quality Module aims to improve the quality of contributed comments by automatically highlighting the most deliberative ones, by this providing feedback to the discussion participants. The platform is released under an open source license and can be deployed and hosted for participation processes.

Future work. Our goal is to evaluate the two presented AI-based online discussion modules in a large-scale experiment. Participants will discuss two topics in small groups, randomly assigned to one of the following conditions: using the comment recommendation debate module, using the deliberative quality debate module, or discussing without any AI support. Participants will be surveyed about their experiences on the platform during and after the discussions. The experiment aims to empirically determine whether the AI-supported modules enhance satisfaction with both the discussion process and its outcomes, and if they influence response behavior in the groups differently compared to discussions without AI support. Note that we kept the two features separate to examine the individual effects. As we gain more insights into their effectiveness, it is conceivable that both features could be integrated into a single debate module.

References

- Lucas Anastasiou, Aldo De Moor, Barbara Brayshay, and Anna De Liddo. 2023. A tale of struggles: an evaluation framework for transitioning from individually usable to community-useful online deliberation tools. In *Proceedings of the 11th International Conference on Communities and Technologies*, C&T '23, page 144–155, New York, NY, USA. Association for Computing Machinery.
- Ashley A Anderson, Dominique Brossard, Dietram A Scheufele, Michael A Xenos, and Peter Ladwig. 2014. The "nasty effect:" online incivility and risk perceptions of emerging technologies. *Journal of computer-mediated communication*, 19(3):373–387.
- Miguel Arana-Catania, Felix-Anselm Van Lier, Rob Procter, Nataliya Tkachenko, Yulan He, Arkaitz Zubiaga, and Maria Liakata. 2021. Citizen participation and machine learning for a better democracy. *Digital Government: Research and Practice*, 2(3):1–22.
- André Bächtiger, Susumu Shikano, Seraina Pedrini, and Mirjam Ryser. 2009. Measuring deliberation 2.0: standards, discourse types, and sequenzialization. In ECPR General Conference, pages 5–12. Potsdam.
- Maike Behrendt, Stefan Sylvius Wagner, Marc Ziegele, Lena Wilms, Anke Stoll, Dominique Heinbach, and Stefan Harmeling. 2024. AQuA – combining experts' and non-experts' views to assess deliberation quality in online discussions using LLMs. In *Proceedings* of the First Workshop on Language-driven Deliberation Technology (DELITE) @ LREC-COLING 2024, pages 1–12, Torino, Italia. ELRA and ICCL.
- Jonathan Davies, Miguel Arana-Catania, Rob Procter, Felix-Anselm van Lier, and Yulan He. 2021. Evaluating the application of nlp tools in mainstream participatory budgeting processes in scotland. In *14th International Conference on Theory and Practice of Electronic Governance*, pages 362–366.
- Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2019. BERT: Pre-training of deep bidirectional transformers for language understanding. In Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers), pages 4171–4186, Minneapolis, Minnesota. Association for Computational Linguistics.
- Katharina Esau, Dannica Fleuß, and Sarah-Michelle Nienhaus. 2021. Different arenas, different deliberative quality? using a systemic framework to evaluate online deliberation on immigration policy in germany. *Policy & Internet*, 13(1):86–112.
- Todd Graham. 2010. The use of expressives in online political talk: Impeding or facilitating the normative goals of deliberation? In *Electronic Participation*, pages 26–41, Berlin, Heidelberg. Springer Berlin Heidelberg.

- Albert Q Jiang, Alexandre Sablayrolles, Arthur Mensch, Chris Bamford, Devendra Singh Chaplot, Diego de las Casas, Florian Bressand, Gianna Lengyel, Guillaume Lample, Lucile Saulnier, et al. 2023. Mistral 7b. arXiv preprint arXiv:2310.06825.
- Mark Klein. 2007. How to harvest collective wisdom for complex problems: An introduction to the mit deliberatorium. *Center for Collective Intelligence working paper*.
- Mark Klein. 2015. A critical review of crowd-scale online deliberation technologies. *Available at SSRN* 2652888.
- Noémie Lago, Marianne Durieux, Jean-Alexandre Pouleur, Chantal Scoubeau, Catherine Elsen, and Clémentine Schelings. 2019. Citizen participation through digital platforms: the challenging question of data processing for cities. In *Proceedings of the Eighth International Conference on Smart Cities, Systems, Devices and Technologies.* DGTRE - Région wallonne. Direction générale des Technologies, de la Recherche et de l'Énergie [BE].
- Ruth Shortall, Anatol Itten, Michiel van der Meer, Pradeep Murukannaiah, and Catholijn Jonker. 2022. Reason against the machine? future directions for mass online deliberation. *Frontiers in Political Science*, 4.
- Christopher Small, Michael Bjorkegren, Timo Erkkilä, Lynette Shaw, and Colin Megill. 2021. Polis: Scaling deliberation by mapping high dimensional opinion spaces. *Recerca: Revista de Pensament i Anàlisi*, 26(2).
- Jannis Vamvas and Rico Sennrich. 2020. X-Stance: A multilingual multi-target dataset for stance detection. In Proceedings of the 5th Swiss Text Analytics Conference (SwissText) & 16th Conference on Natural Language Processing (KONVENS), Zurich, Switzerland.
- Stefan Sylvius Wagner, Maike Behrendt, Marc Ziegele, and Stefan Harmeling. 2024. The Power of LLM-Generated Synthetic Data for Stance Detection in Online Political Discussions. *arXiv e-prints*, arXiv:2406.12480.
- Yixue Wang and Nicholas Diakopoulos. 2022. Highlighting high-quality content as a moderation strategy: The role of new york times picks in comment quality and engagement. *Trans. Soc. Comput.*, 4(4).