MOS-Bench: Benchmarking Generalization Abilities of Subjective Speech Quality Assessment Models

Wen-Chin Huang, Member, IEEE, Erica Cooper, Member, IEEE, and Tomoki Toda, Member, IEEE

Abstract—Subjective speech quality assessment (SSQA) is critical for evaluating speech samples as perceived by human listeners. While model-based SSQA has enjoyed great success thanks to the development of deep neural networks (DNNs), generalization remains a key challenge, especially for unseen, out-of-domain data. To benchmark the generalization abilities of SSQA models, we present MOS-Bench, a diverse collection of datasets. In addition, we also introduce SHEET, an opensource toolkit containing complete recipes to conduct SSQA experiments. We provided benchmark results for MOS-Bench, and we also explored multi-dataset training to enhance generalization. Additionally, we proposed a new performance metric, best score difference/ratio, and used latent space visualizations to explain model behavior, offering valuable insights for future research.

Index Terms—subjective speech quality assessment, mean opinion score, generalization ability, benchmark

I. INTRODUCTION

S PEECH quality assessment (SQA) refers to evaluating the quality of a speech sample. In this work, we are particularly interested in **subjective** speech quality assessment (SSQA). Since most "end-listeners" of speech are human, the most accurate way to assess perceived quality is through subjective listening tests [1]. A common listening test protocol is the mean opinion score (MOS) test, where the quality of a query speech sample is represented as the average of ratings from multiple listeners, usually on a 5-point scale. However, conducting listening tests is inarguably very costly and timeconsuming. Therefore, researchers have dedicated efforts to developing automated *objective* evaluation methods, which can ease the evaluation process and accelerate the development iteration.

Objective measures can be categorized into two types [2], [3]. A *signal-based* metric usually measures the distance or similarity between the query and a reference. However, researchers found that most signal-based methods do not correlate well with human perception [4], which is essential if the goal of the objective metrics is to replace listening tests. Another shortcoming is that signal-based metrics are usually *intrusive* (or *reference-based*, *double-ended*), which means that a reference sample is needed. The choice of the reference is essential to the correctness of the metric, which can be a difficult task. For synthetic speech samples generated by text-to-speech (TTS) or voice conversion (VC) systems, it is often impossible to find the proper reference sample. Therefore A *non-intrusive* (or *reference-free*, *single-ended*) metric would be more convenient to use, thus more attractive.

Another line of work focusing on *model-based* metrics is therefore attractive. These methods directly learn from a *subjective speech rating* dataset that consists of (speech, human rating) pairs, thus they correlate better with human perception compared to signal-based methods. Also, most of the model-based metrics are non-intrusive (with exceptions like SpeechBERTScore [5]), making them easy to use. The development of model-based approaches has been greatly accelerated by deep neural networks (DNNs) in the past decade. In the VoiceMOS Challenge (VMC) 2022 [6], a scientific competition for promoting SSQA, it was shown that the bestperforming system achieved a high correlation (0.959) with human ratings.

However, SSQA models suffer from generalization ability issues, as shown in [7]. In machine learning, generalization ability refers to the model's capacity to make accurate predictions across a wide variety of conditions, beyond the dataset it was trained on. In the context of SSQA, we identify generalization ability in terms of two aspects.

- **Ranking correctness**: the ability to correctly rank samples, either at the utterance-level or system-level.
- **Faithfulness**: the ability to make predictions that are faithful to humans.

Generalization is especially difficult in SSQA due to the nature of how listening tests are conducted. Each listening test represents a unique context, with different contents (text, speakers, etc.), recruited listeners, ranges of systems being evaluated, and even instructions. A test set could be either **in-domain** or **out-of-domain**¹ w.r.t. an SSQA model. The former means the test samples and the ratings come from the same listening test as that of the training set, and the latter means they come from different listening tests. In VMC'23 where participants were asked to make zero-shot predictions on three out-of-domain test sets [8], most teams struggled to excel in all test sets, even if their model did well in one of the sets. This result motivated us to study the generalization ability in a more standard, large-scale setting.

In this work, we present **MOS-Bench**, a collection of datasets for training and benchmarking subjective speech quality predictors. We also introduce **SHEET**, which stands for the Speech Human Evaluation Estimation Toolkit². SHEET is an all-in-one toolkit for SSQA research, with support of several

Wen-Chin Huang is with the Graduate School of Informatics, Nagoya University, Japan (e-mail: wen.chinhuang@g.sp.m.is.nagoya-u.ac.jp). Erica Cooper is with the National Institute of Information and Communications Technology (NICT), Japan. Tomoki Toda is with the Information Technology Center, Nagoya University, Japan.

¹Making predictions for out-of-domain test sets is also referred to as *zero-shot* prediction [8].

²Available at https://github.com/unilight/sheet.

representative DNN-based SSQA models. In our experiments, we provide benchmark results of the twelve test sets in MOS-Bench. We also explored training SSQA models by pooling multiple training datasets, with the motivation to improve the generalization ability.

The main contributions of this work are listed as follows.

- **MOS-Bench** was presented, which contains seven training sets and twelve test sets, covering different sampling frequencies, languages, and speech types, from synthetic speech generated by TTS, VC, speech enhancement (SE) systems, to non-synthetic speech such as transmitted, noisy and reverberant speech.
- **SHEET** was developed for research purposes, providing complete recipes to conduct SSQA experiments, from data processing, training to benchmarking.
- We proposed a new **metric** called *best score difference/ratio*, with the motivation to assess the overall performance of the SSQA models.
- We investigated training SSQA models with **multiple datasets**, and found it could improve the generalization ability, without sacrificing much the performance of indomain test sets.
- We confirmed that the **visualization** of the training and test set samples in the latent space of the SSQA models could be used to explain the generalization ability.

II. RELATED WORKS

In the following subsections, we review three techniques that have been applied to improve the generalization ability of SSQA models.

A. Transfer learning

Transfer learning refers to pre-training models on one task and reusing them on a different task, in order to leverage learned knowledge to improve performance. In speech processing, self-supervised learning (SSL) based transfer learning has been shown to be extremely effective [9]. Essentially, self-supervised pre-training is conducted first on a large-scale unlabeled speech dataset w.r.t. some pretext task, such as contrastive learning [10] or masked prediction [11], [12]. Then, a task-specific prediction head is appended on the pretrained model, and the whole model is fine-tuned with a labeled dataset for the downstream task.

While there have been many attempts to apply SSL in the task of SSQA [13]–[16], perhaps the most representative approach is SSL-MOS [7], where the authors applied a very simple model architecture by attaching a linear head onto SSL models. SSL-MOS was shown to not only improve performance on in-domain datasets but also provide reasonable correlations in the zero-shot setting.

While the above-mentioned methods rely on a labeled dataset during fine-tuning, unsupervised approaches based on pre-trained models have been showing potential in the zero-shot setting recently. By pre-training on natural speech only, the models internally learn a so-called *reference model*, where knowledge of what a natural, high-quality speech sample sounds like is encoded. Given an input speech sample, SpeechLMScore [17] measures the likelihood w.r.t. a generative speech unit language model, and VQScore [18] measures the quantization error w.r.t. a vector quantized autoencoder. Experiments showed that these methods demonstrate superior generalization ability in zero-shot settings, which is possibly because they avoid the risk of overfitting.

B. Ensemble learning

The aim of ensemble learning is to reduce model variance and improve robustness by combining multiple models. For instance, UTMOS [19], which was the top-performing team in VMC'22, performed stacking [20] with a set of strong and weak learners. For strong learners, the authors employed modified SSL-MOS models with additional techniques including contrastive learning, listener modeling [21], and phoneme encodings. For weak learners, they employed regression models including linear regression, decision tree, and kernel methods. The inputs to these weak learners were SSL features. LE-SSL-MOS [22], the top performing team in VMC'23, combined scores from multiple models, including a vanilla SSL-MOS model, an SSL-MOS model with listener modeling, a SpeechLMScore model, and the confidence score of an ASR model. LE-SSL-MOS was the only team in VMC'23 that performed well on all tracks, demonstrating its strong generalization ability.

C. Training with multiple listening test datasets

Perhaps the most straightforward way to increase generalization ability is to simply train with more data. Doing so allows the model to learn a broader and more diverse set of patterns, reducing the risk of overfitting to specific data points and better capturing underlying relationships that generalize well to unseen data. However, as listening tests are costly, it is difficult to rate a large amount of samples in one test. Researchers have therefore been interested in training SSOA models with data from multiple listening test datasets. A naive method is to simply pool several datasets into one large training set. However, some claim that such an approach suffers from a so-called "corpus effect" as defined in [23]. The corpus effect refers to the problem of the same type of speech receiving different scores on different listening tests. For instance, it was reported that the same TTS system received a lower score when systems with higher qualities were present in the listening test [24]. This is because MOS can be affected by listener preferences and the range of conditions included in one listening test. The latter is sometimes called the "rangeequalizing bias" [25].

A traditional approach to deal with this problem is to define a set of common anchors to be included in all listening test datasets. However, if the datasets used different sources, then they often do not contain the same anchors. The biasaware loss was proposed in [26] to assign different weights to different datasets, with the cost of a complicated training process. Listener modeling [21], [27] could solve the listener bias problem, with the requirement of listener labels. Recently, the AlignNet was proposed [28], with a much simpler training process compared to the bias-aware loss but better performance.

Partition	Name	Domain	Language	fs (kHz)	# Samples (train/dev)	Listener label
	BVCC train [29]	TTS, VC, clean speech	English	16000	4944/1066	Yes
Train	SOMOS train [30]	TTS, clean speech	English	24000	14100/3000	Yes
& dev	SingMOS train [31]	SVS, SVC, clean singing voice	Chinese, Japanese	16000	2000/544	No
	NISQA train [32]	simulated distorted speech, real distorted speech, clean speech	English	48000	11020/2700	No
	TMHINT-QI train [33]	simulated noisy speech, enhanced speech, clean speech	Taiwanese Mandarin	16000	11644/1293	Yes
	Tencent train [34]	simulated distorted speech, clean speech	Chinese	16000	10408/1155	No
	PSTN train [35]	PSTN calls, simulated distorted speech	English	8000	52839/5870	No
	BVCC test [29]	TTS, VC, clean speech	English	16000	1066	
' 	SOMOS test [30]	TTS, clean speech	English	24000	3000	
	NISQA TEST FOR [32]	simulated distorted speech, VoIP calls	English	48000	240	
Test	NISQA TEST P501 [32]	simulated distorted speech, VoIP calls	English	48000	240	N/A
1050	NISQA TEST LIVETALK [32]	real noisy speech, VoIP calls	German	48000	232	
	TMHINT-QI test [33]	simulated noisy speech, enhanced speech, clean speech	Taiwanese Mandarin	16000	1978	
	VMC'22 OOD track (BC'19) [6], [36]	TTS, clean speech	Chinese	16000	540	
	VMC'23 track 1a (BC'23 Hub) [8], [37]	TTS, clean speech	French	22050	882	
	VMC'23 track 1a (BC'23 Spoke) [8], [37]	TTS, clean speech	French	22050	578	
	VMC'23 track 2 (SVCC'23) [8], [38]	SVC, clean singing voice	English	24000	4040	
	VMC'23 track 3 (TMHINT-QI(S)) [8], [39]	simulated noisy speech, enhanced speech, clean speech	Taiwanese Mandarin	16000	1960	
	VMC'24 track 2 (SingMOS test) [31], [40]	SVS, SVC, clean singing voice	Chinese, Japanese	16000	645	

TABLE I: Details of MOS-Bench.

III. DESCRIPTION OF MOS-BENCH

original papers.

A. General description

Table I summarizes the MOS-Bench collection presented in this work. It contains the test partition, which consists of twelve datasets, and also the train and dev partition, which consists of seven datasets. All datasets included in MOS-Bench are publicly available and can be easily accessed. The listening test protocol in each dataset was an MOS test with scores ranging from 1 to 5. For datasets with an official train/dev/test split, the test set is included in the test partition, and serves as the datasets in the in-domain experiments. For datasets that only provided a train set, we split it into a train/dev set with a 9:1 ratio. Finally, we also included several datasets that are not seen during training, which are essentially test sets from the past VMCs.

The MOS-Bench demonstrates a diverse collection of datasets with different properties. First, the domains covered in MOS-Bench span from synthetic audio including TTS, VC, SVS, SVC, and enhanced speech, to speech that underwent a variety of distortions, including artificially added and real noise, reverberation, VoIP, transmission, and replay. In terms of languages, MOS-Bench covers six languages in total: English, Chinese, Taiwanese Mandarin, Japanese, French, and German. MOS-Bench also covers a wide range of sampling frequencies, going from 8000 Hz to 48000 Hz. Also, some training datasets provide listener-wise scores, allowing for listener modeling techniques.

In the following subsection, we briefly describe the properties of each dataset. For details, please refer to the respective

B. Brief descriptions of each dataset

1) BVCC: The BVCC dataset [29] is a large-scale listening test covering English samples from 187 different TTS and VC systems, which mainly come from past years of the Blizzard Challenges (BC) and Voice Conversion Challenges (VCC), as well as published samples from ESPnet-TTS [41]. Each sample was rated by 8 distinct listeners, and listener demographics were collected. We used the official partition, where the dev and test sets contain unseen synthesis systems, speakers, texts, and listeners not in the train set while the rating distribution of each set is matched as closely as possible.

2) SOMOS: The SOMOS dataset [30] contains samples from 200 neural TTS systems, which were all trained on LJSpeech [42], a single-speaker English female corpus, with a shared LPCNet vocoder [43]. These TTS systems differ mainly in the acoustic model architecture, as well as input variations, including syntactic, linguistic, and prosody clues. In addition, clean speech samples were also included. Each sample was rated by at least seventeen listeners. We used the official train/dev/test partition within the clean set.

3) SingMOS: The SingMOS dataset [31] focuses on singing voices, and collects samples from a total of 35 modern neural SVS and SVC systems, including natural singing voice samples. These systems are trained on open-source Chinese and Japanese singing voice datasets. Each sample was rated by five listeners. The SingMOS dataset was also used in VMC'24

track 2, and we used the official train/dev/test split in the challenge.

4) NISQA: The NISQA dataset [32] was designed to evaluate speech with distortions occurring in communication networks. In MOS-Bench, the train and dev sets combined the NISQA TRAIN SIM, NISQA TRAIN LIVE and NISQA VAL SIM, NISQA VAL LIVE sets, respectively. The NISQA TRAIN SIM and NISQA VAL SIM sets contained (1) simulated speech distortions, such as packet loss, bandpass filter, different codecs and clipping. (2) artificially added background noises. The NISQA TRAIN LIVE and NISQA VAL LIVE sets contained live Skype and phone recordings, with real distortions created during recording, such as keyboard typing and street noise. Each sample in these four sets was rated by five listeners.

The NISQA TEST P501, NISQA TEST FOR and NISQA TEST LIVETALK sets were used as the test sets in MOS-Bench³. The NISQA TEST P501 and NISQA TEST FOR sets included samples with simulated distortions, as well as live VoIP calls where speech samples were played back directly from the laptop, followed by simulated packet-loss, warping, low-bitrate, etc. Each sample in these two sets was rated by thirty listeners. Finally, NISQA TEST LIVETALK is a German dataset with real phone call recordings, where talkers spoke directly into the terminal device in different backgrounds with different distortions. Talkers called either through the mobile network or via VoIP. Each sample in these two sets was rated by 24 listeners.

5) *TMHINT-QI*: The TMHINT-QI dataset [33] contained Taiwanese Mandarin samples added with four artificial noise types (babble, street, pink, and white) at four signal-to-noise (SNR) ratio levels (-2, 0, 2, and 5), along with their enhanced versions using five speech enhancement systems. We used the official train/dev/test split. It is worthwhile noticing that all noise types, SNR levels, and enhancement systems are the same across the splits.

6) Tencent: The Tencent dataset [34] was a Chinese dataset designed for speech quality assessment in online conference scenarios. First, samples from three publicly available datasets were artificially distorted with either background noise, clipping, or codec compression loss. Then, noise suppression and packet loss concealment were applied to simulate a realistic online conference scenario. In addition, samples with either simulated reverberation or recorded in a reverberant environment were also considered, each with a different room size and reverberation delay. Most samples have a sampling frequency of 16 kHz, while some are in 48 kHz. Each sample was rated by more than twenty listeners. As part of the dataset of the ConferencingSpeech2022 challenge, the organizers only provided the training partition. Therefore, we used a random 9:1 train/dev split.

7) *PSTN:* The PSTN dataset [35] was collected to study the speech quality of the public switched telephone network. Similar to the Tencent dataset, the PSTN dataset was also part of the ConferencingSpeech2022 challenge, so we used the filtered version provided by the organizers and used a random 9:1 train/dev split. The PSTN dataset contains automatically conducted phone calls between a PSTN and a VoIP endpoint. The 500,000 original automated calls were further filtered to maintain a reasonable quality distribution. Then, background noises were artificially added to simulate real-world phone calls.

8) *VMC'22 OOD track (BC'19):* The VMC'22 OOD track [6] adopted the Blizzard Challenge 2019 [36] listening test data. This set contains Chinese TTS samples.

9) VMC'23 track 1a and 1b (BC'23 Hub and Spoke: The VMC'23 tracks 1a and 1b [8] used the Blizzard Challenge 2023 [37] listening test data. The task setting in the Blizzard Challenge 2023 was French TTS, with two subtasks: the main Hub task provided 50 hours of training data from a female speaker, and the Spoke task was a speaker adaptation task where 2 hours of data from a different female speaker was provided. Two different listening tests were conducted separately on the submitted TTS samples for these two tasks.

10) VMC'23 track 2 (SVCC'23): The VMC'23 track 2 [8] adopted the Voice Conversion Challenge (VCC) 2023 [38] listening test data. SVCC'23 focused on singing voice conversion, where there were two tasks: an in-domain task, where the singing voice samples of the target were provided, and a cross-domain task, where the normal voice samples were provided. Each sample was rated by six listeners.

11) VMC'23 track 3 (TMHINT-QI 2: The VMC'23 track 3 [8] used the TMHINT-QI(S) [39] dataset. The base speech samples and the noisy utterance generation process were the same as those in the TMHINT-QI dataset. Two out of five enhancement methods in TMHINT-QI(S) were different from those in TMHINT-QI, resulting in a partially different five enhancement methods. In addition, a separate listening test with non-overlapping listeners was conducted.

IV. SHEET AND SUPPORTED MODELS

In this section, we introduce SHEET, the toolkit we developed towards a complete setup for SSQA benchmarking experiments, including all the experiments conducted in this paper. One important feature of SHEET is to provide *training scripts* of subjective speech quality predictors: while there are many toolkits that provide ready-to-use metrics⁴⁵, few provide the function to train new predictors.

A. Overview

The structure of SHEET follows the design of popular speech processing toolkits like Kaldi [44] and ESPnet [45]. Specifically, in such a design, there are two core parts: a *recipe* is a collection of bash or python scripts that provides easy-tounderstand instructions to complete an experiment, from data preprocessing, model training to evaluation. In practice, each dataset has one recipe, and there are many configuration files to choose from, each representing a set of hyper-parameters of the model and the training procedure. Another core part of the toolkit is the *library* part, where the model architectures and training logic are implemented.

 $^{^{3}\}mbox{The NISQA TEST NSC set was excluded since it was not publicly available anymore.}$

⁴https://github.com/tarepan/SpeechMOS

⁵https://github.com/Takaaki-Saeki/DiscreteSpeechMetrics



Fig. 1: Main models and inference methods supported in SHEET, the open-source toolkit developed.

B. Main model backbone: SSL-MOS

The main model backbone adopted in most experiments in this work is SSL-MOS [7], due to its simplicity compared to other SSL-based models, as described in Section II-A. The top left of Figure 1 is an illustration of SSL-MOS. The original SSL-MOS simply adds a linear output layer on top of a speech SSL model and fine-tunes the whole model on a subjective speech rating dataset with a simple L1 loss. The modified SSL-MOS in SHEET is different from that in the official implementation in the following ways⁶: (1) the frame-wise output representations of the SSL model were first averaged over the time axis before sending to the proceeding layers, while in our implementation the average operation took place at last, (2) we replaced the linear layer with a two-layer feedforward neural network, (3) techniques like range clipping, repetitive padding and clipped MSE loss [27] were used.

C. Naive kNN inference

In a recent work [46], the authors used the term *parametric* inference mode to refer to using a decoder to generate the final score, which is opposed to the *non-parametric* inference modes they promoted in their paper. Inspired by them, in this work, we explore a retrieval-based, non-parametric inference method named *naive kNN*⁷. The naive kNN inference method can be built on any SSQA model with a feature extractor-like module f (for instance, the SSL model in SSL-MOS serves as the feature extractor).

The bottom left of Figure 1 is an illustration of the naive kNN inference method. Here we give the formulation of the naive kNN inference method. We first train an SSQA model with a dataset $\mathcal{D} = \{(x_i, s_i)\}_i$, where s_i is the subjective

rating w.r.t. the training speech sample x_i . After training, we can derive a *datastore* from \mathcal{D} as: $\mathcal{D}_{datastore} = \{(f(x_i), y_i)\}_i$. Then, during inference, given an input speech sample query x_q , we retrieve k nearest neighbors w.r.t. x_q from $\mathcal{D}_{datastore}$, using a pre-defined distance function dis (\cdot, \cdot) . The retrieved k nearest neighbor set can be expressed as follows:

$$\mathcal{N} = \{ (d_i, s_i) \}_{i=1}^k, \tag{1}$$

where d_i is the distance between the representations of the input query and the neighbor: $d_i = \text{dis}(f(x_q), f(x_i))$. Finally, the output score of the naive kNN method can be expressed as:

$$\hat{s}_{kNN} = \sum_{(d_i, s_i) \in \mathcal{N}} \frac{e^{a_i}}{\sum_{j=1}^k e^{d_j}} \cdot s_i,$$
(2)

where the first term in the summation is to normalize the distances with a softmax function.

D. Multiple datasets training with SSL-MOS

For training with multiple datasets, one could employ *naive multiple dataset training*, which is to simply pool all available training datasets into a large one and train an orthodox SSQA model like SSL-MOS with it. As many papers have claimed, in theory, such a method suffers from the corpus effect, possibly resulting in a lower prediction performance.

E. Modified AlignNet

The AlignNet was a model designed to tackle the corpus effect in multiple dataset training [28]. Based on its drawbacks, we made several changes and proposed the modified AlignNet. Despite the changes, they have essentially the same core idea, which is illustrated in the top right of Figure 1.

Both the AlignNet and the modified AlignNet consist of an encoder and a decoder⁸. In the forward pass, the encoder

⁶In our experiments, only with these modifications could we reproduce the same level of results as in the original paper.

⁷Our re-implementation of the complete RAMP model (including k-net and λ -net [46]) did not provide a significant improvement over the naive kNN method but with the cost of an additional training step, thus we do not report those results.

⁸Referred to as the AudioNet and Aligner in the original paper, respectively.

output is fused with a *dataset embedding*, and is then sent to the decoder to output the final score. The core idea is similar to listener modeling [21], [27], which is to have the encoder behave in a dataset-independent fashion, whose output is then mapped to the dataset-specific score by the decoder. Two other implementation details worth mentioning are (1) the output of the encoder is a *score*, which is a scalar, rather than a vector representation, and (2) the encoder was based on MOSNet, a convolutional recurrent neural network structure proposed in [47].

An obvious problem of AlignNet is that a dataset embedding would still be needed during inference. The solution proposed in the original paper is to select a *reference dataset* from all the training datasets beforehand. During training, for all the samples in the reference dataset, the decoder is forced to become the identity function. Then, during inference, the embedding of the reference dataset is used, regardless of the type of the input speech. Such an approach can also ground the encoder to produce meaningful quality scores. However, the behavior of AlignNet will largely depend on the choice of the reference dataset. For instance, the experiments in the original paper used NISQA as the reference dataset, and there would be an obvious mismatch when the input speech is from a TTS system.

We therefore propose the modified AlignNet. First, instead of using a MOSNet-like encoder, we simply use an SSL model, following SSL-MOS. Second, the encoder output is not a scalar but vector representations, to align with the design of SSL-MOS. The biggest modification is a new inference method inspired by retrieval-based methods [46]. We name this method *domain embedding retrieval*, which is illustrated in the bottom right of Figure 1. During inference, we find the nearest neighbor of the input query in the SSL representation space, and send the dataset embedding of that neighbor along with the output of the SSL model to the decoder to get the final score. Since the decoder is used, according to the definition in Section IV-C, the domain embedding retrieval method is also categorized in parametric inference.

F. Multiple dataset fine-tuning (MDF)

SHEET also supports a training technique for multiple dataset training called multi dataset fine-tuning (MDF), which was proposed in [28]. Specifically, the SSQA model is first pre-trained on a single dataset, and then fine-tuned on multiple datasets, including the dataset used for pre-training. The authors claimed that pre-training avoids falling to local minima by learning meaningful representations and balances the misaligned scores from different training datasets. However, they tested MDF on in-domain test sets only. Thus, in Section V-C, we re-examine its effectiveness in the out-of-domain setting.

V. EXPERIMENTS

The experiments in this paper are divided into two parts. First, in Section V-B we examined the out-of-domain generalization ability of SSQA models trained on *one single dataset*. Then, in Section V-C we explored whether training with multiple datasets could improve both in-domain prediction performance and out-of-domain generalization abilities.



(a) Utterance level score distribu-(b) Scatter plot of system level tion score distribution

Fig. 2: Distribution plot of an SSL-MOS model trained on NISQA and tested on VMC'23 track 1a.

A. Experimental settings

1) Datasets: The SSQA models in Section V-B were trained with one of the seven training datasets presented in Table I, and the models in Section V-C were trained by pooling the seven datasets together.

2) Model and training settings: The SSQA models in Section V-B were SSL-MOS. For the experiments in Section V-C', we tried two models: (1) SSL-MOS with naive multiple dataset training, and (2) modified AlignNet. Unless specified, the SSL model in all SSL-MOS and modified AlignNet models was wav2vec 2.0 [10], and the output from the last layer was used. Since the wav2vec 2.0 model only takes 16 kHz waveforms as input, all input speech samples were resampled to 16 kHz.

For all experiments, we report results averaged over three random seed runs. For all experiments, the training batch size was set to 16, and the SGD optimizer with an initial learning rate of 0.001 and a momentum of 0.9 was used. All training runs were allowed to execute for a maximum of 100,000 steps, but we kept track of the 5 best models according to certain criteria on the validation set. If the 5 best checkpoints had not been updated for 2000 steps, the training automatically halts.

3) Conventional evaluation metrics: For datasets that contain mostly synthetic speech, following the VMC series, we mainly reported two evaluation metrics: system-level mean squared error (Sys MSE) and system-level spearman rank correlation coefficient (Sys SRCC). The reason to report system-level metrics is that in scientific challenges like BC or VCC, researchers are more interested in the ranking between systems. On the other hand, for datasets in non-syntheticspeech domains, since it is difficult to define a "system" in such domains, we mainly reported two evaluation metrics: utterance-level mean squared error (Utt MSE) and utterancelevel and system-level linear correlation coefficient (Utt LCC).

Here we would like to emphasize the importance of the MSE metric. MSE is a useful metric to reflect the faithfulness (recall the definition in Section I) of the SSQA model. Figure 2 shows an example. Although the system-level SRCC was not bad (0.684), it could be observed that all predicted scores are skewed to the range of 4.0 to 5.0, which is obviously not faithful. This problem could be fortunately caught by the high MSE value (1.394).

4) Best score difference and best score ratio: Since there are twelve test sets in MOS-Bench, we seek a comprehensive

TABLE II: Breakdown of best score difference/ratio results in the single dataset training experiments with synthetic and non-synthetic test sets.

Training	Syn	thetic	Non-s	ynthetic	Average		
dataset	MSE	LCC/ SRCC	MSE	LCC/ SRCC	MSE	LCC/ SRCC	
BVCC	1.386	80.9%	0.993	84.9%	1.222	82.6%	
SOMOS	1.016	58.6%	0.657	44.4%	0.866	52.6%	
SingMOS	0.499	52.6%	1.440	40.8%	0.891	47.7%	
NISQA	0.548	81.8%	0.379	94.2%	0.478	87.0%	
TMHINT-QI	1.378	47.5%	1.521	82.1%	1.438	61.9%	
PSTN	0.559	86.4%	0.430	93.3%	0.505	89.3%	
Tencent	1.176	69.3%	0.793	84.8%	1.016	75.7%	

metric to assess the overall performance. Therefore, we propose two new metrics: **best score difference** and **best score ratio**. With respect to a specific test set, these two metrics are defined as:

best score difference := MSE of a specific model

- MSE of the best performing model,

best score ratio :=
$$\frac{\text{LCC/SRCC of a specific model}}{\text{LCC/SRCC of the best performing model}}$$

The definition of the "best performing" model can be flexible. In each of the two experiments in Sections V-B and V-C, we will use different definitions. Finally, we can average all best score difference/ratio numbers over the twelve test sets to get an overall metric to assess the generalization ability.

5) Visualization using SSL embeddings: We attempted to explain the generalization ability of the trained SSQA models by visualizing the SSL embeddings, following [13]. Specifically, given an input speech sample from a dataset of interest, the SSL model in the trained SSQA model was used to extract frame-level features, which were then averaged over the time axis to obtain one SSL embedding. After all embeddings were extracted, the t-SNE algorithm [48] was used to visualize the embeddings in 2-dimensional space. When visualizing test sets, to balance out different dataset sizes, we randomly chose 100 samples from each set.

B. Single dataset training experiments

In this subsection, we are interested in the following research question:

RQ1: Does training on certain datasets offer a better generalization ability over the other datasets?

Therefore, using the datasets listed in Table I, we trained SSL-MOS models using the seven training datasets, and examined their generalization ability when tested on the twelve test sets. For synthetic speech datasets (BVCC, SOMOS, SingMOS), the model selection criterion during training was set to the system-level SRCC. For non-synthetic speech datasets (NISQA, TMHINT-QI, PSTN, Tencent), the criterion was set to utterance-level LCC. When calculating the best score difference and ratio numbers, the "best model" was defined as the best model among the seven models trained with the respective training dataset.

1) Best score results: Figure 3 shows the best score results. Table II shows a further breakdown of the scores by synthetic/non-synthetic test sets. For raw metric numbers, please refer to the Supplementary Materials.

First, from Figure 3, for each test set, we first tried to idntify which training dataset yielded the best performance. For BVCC, SOMOS, SingMOS and TMHINT-QI, since their test sets are from the same listening tests of their training sets, the best-scoring models for those test sets are those trained with the respective training sets. On the other hand, we also have some surprising results. For instance, we would expect that for test sets like VMC'22 OOD track, VMC'23 tracks 1a, and VMC'23 track 2 which contained synthetic speech samples, SSQA models trained on synthetic speech datasets like BVCC, SOMOS or SingMOS would yield a better score. Nonetheless, the best-performing models were trained on datasets like NISQA, TMHINT-QI and PSTN.

Next, we looked at the average scores. For best score difference/ratio, the top 2 performing models were trained on PSTN and NISQA. BVCC placed third in best score ratio, although suffering from a high best score difference. This is a surprising result, because PSTN and NISQA do not contain synthetic samples, and it is natural to assume that SSQA models trained on these two datasets would perform poorly on synthetic test sets. Vice versa for BVCC. However, looking at Table II, we confirmed that even on synthetic test sets, models trained on PSTN and NISQA were still the top 2 performing ones. BVCC, although containing only natural and synthetic samples, also yielded a good average best score ratio on non-synthetic sets.

2) Visualization: Following the visualization process described in Section V-A5, for each SSQA model, we visualized the SSL embeddings of the samples in the training set and test sets. Below, we only show a subset of the visualization results. Please refer to the Supplementary Materials for the complete set of figures.

We tried to explain the results in Figure 3 and Table II by visualization. First, Figure 4 shows the visualization of BVCC and NISQA. It could be seen that the training samples (black dots) provided a good coverage over the test sets. On the other hand, Figure 5 shows the visualization of two datasets that did not perform well. For SingMOS, it could be observed that the training samples mostly covered synthetic samples, and as a result, in Table II, the performance on synthetic test sets was better than that on non-synthetic test sets. Tencent demonstrated the opposite behavior.

3) Ablation study by unifying dataset sizes: It seems like we could draw a conclusion that: without collecting an SSQA dataset like BVCC that contains a large variety of synthetic samples, one can simply collect a non-synthetic dataset (like NISQA and PSTN), and achieve great performance on both synthetic and non-synthetic test sets. However, one could argue that the good performance of NISQA and PSTN over BVCC is the dataset size. Therefore, we conducted an ablation study by randomly subsampling subsets of the PSTN and NISQA

Train set Test set		BVCC	SOMOS	SingMOS	NISQA	TMHINT-QI	PSTN	Tencent
DVCC test	sys MSE	0.000	0.258	0.982	0.731	2.713	1.272	2.366
BVCC test	sys SRCC	100.0%	75.9%	34.2%	87.1%	67.6%	84.2%	73.7%
SOMOS test	sys MSE	0.711	0.000	0.847	1.525	1.975	1.308	1.828
	sys SRCC	75.3%	100.0%	-9.4%	71.8%	46.1%	67.5%	51.5%
SingMOS test	sys MSE	4.007	3.356	0.000	0.182	0.298	0.076	0.212
	sys SRCC	68.3%	18.4%	100.0%	39.0%	44.0%	65.9%	62.3%
NISQA FOR	utt MSE	0.221	0.461	2.702	0.000	2.757	0.376	0.853
	utt SRCC	84.9%	55.0%	43.9%	100.0%	77.4%	94.7%	82.8%
NISOA LIVETALK	utt MSE	0.949	0.852	1.694	0.000	1.476	0.005	0.356
NISQALIVETALK	utt SRCC	81.5%	20.8%	44.1%	95.8%	79.5%	100.0%	97.0%
NISQA P501	utt MSE	0.000	0.361	2.238	0.142	3.203	0.916	1.946
	utt SRCC	95.5%	84.1%	31.4%	100.0%	66.4%	89.2%	87.1%
TMUINT OI test	utt MSE	2.415	1.225	0.455	1.305	0.000	0.851	0.765
TMITINT-QLIESI	utt SRCC	73.6%	30.3%	45.6%	80.2%	100.0%	82.6%	78.2%
VMC'22 OOD treats	sys MSE	2.554	1.478	0.727	0.213	0.971	0.000	0.700
VIVIC 22 OOD track	sys SRCC	82.0%	-1.2%	52.5%	98.7%	77.1%	100.0%	75.9%
VMC'23 track1a	sys MSE	0.000	0.689	0.257	1.094	1.558	0.883	1.654
V IVIC 25 trackina	sys SRCC	93.2%	87.6%	31.2%	100.0%	-9.5%	90.0%	56.2%
VMC'23 track1b	sys MSE	1.809	0.715	0.000	0.092	0.967	0.309	0.524
V IVIC 25 LIACKIU	sys SRCC	53.2%	79.8%	66.9%	76.2%	30.9%	100.0%	72.8%
VMC'23 track2	sys MSE	0.618	0.613	0.683	0.000	1.165	0.065	0.947
VIVIC 25 track2	sys SRCC	94.2%	49.3%	93.1%	100.0%	76.5%	97.0%	92.7%
VMC'23 track2	utt MSE	1.382	0.388	0.111	0.446	0.168	0.000	0.046
	utt SRCC	89.2%	31.6%	38.8%	95.1%	87.3%	100.0%	78.7%
AVG	MSE	1.222	0.866	0.891	0.478	1.438	0.505	1.016
AVU	LCC/SRCC	82.6%	52.6%	47.7%	87.0%	61.9%	89.3%	75.7%

Fig. 3: Best score difference and best score ratio result for single dataset training experiments. For best score difference, the more saturated the color, the closer the score to 0. For best score ratio, the more saturated the color, the closer the score to 100%.



Fig. 4: SSL embedding visualization of SSQA models trained on one single dataset. The dots are colored using set labels. Black dots indicate training samples.



Fig. 5: SSL embedding visualization of SSQA models trained on one single dataset. The dots are colored using synthetic(orange)/non-synthetic (yellow) labels. Black dots indicate training samples.

datasets such that they are of the same size of that of BVCC. Furthermore, we also subsampled PSTN such that it has the same size of that of NISQA. We then trained SSL-MOS models on these datasets.

Table III shows the ablation study results. First, when the training samples were around 5000, the best score ratio of BVCC outperformed those of NISQA and PSTN. However, the best score difference of BVCC is still much worse than those of NISQA and PSTN. Then, we observed that when the training samples were around 10000, NISQA outperformed

PSTN in terms of both best score difference and ratio. To conclude, we cannot eliminate the influence of dataset size, although it is not the only important factor. Nonetheless, readers should note that it is much easier to curate large non-synthetic datasets like NISQA and PSTN compared to BVCC, as the latter requires to collect samples from a large number of synthetic systems.

Model		SSL-	MOS		Modified AlignNet				
Multiple Dataset Fine-tuning		wit	hout	with		without		with	
						domain		domain	
Inference met	hod	parametric	naive kNN	parametric	naive kNN	embedding	naive kNN	embedding	naive kNN
						retrieval		retrieval	
BVCC test	sys MSE	0.020	-0.032	0.013	-0.040	-0.037	-0.032	-0.035	-0.032
BVCC test	sys SRCC	98.5%	98.9%	98.5%	99.1%	99.5%	98.5%	98.7%	97.9%
SOMOS test	sys MSE	0.058	-0.017	0.008	-0.014	0.000	-0.016	0.007	-0.016
	sys SRCC	98.4%	98.6%	97.4%	97.5%	97.6%	98.1%	97.8%	97.9%
SingMOS test	sys MSE	0.057	0.009	0.008	0.003	0.051	0.044	0.028	0.049
	sys SRCC	94.0%	96.4%	95.4%	98.1%	88.8%	88.9%	90.0%	89.4%
NISQA FOR	utt MSE	0.019	-0.026	0.017	-0.008	0.075	0.036	0.123	0.045
	utt SRCC	99.2%	98.6%	97.8%	97.3%	94.4%	95.2%	94.0%	95.2%
NISQA LIVETALK	utt MSE	-0.040	-0.046	-0.081	-0.092	0.042	0.017	0.065	0.092
	utt SRCC	100.8%	99.1%	103.4%	102.3%	95.1%	93.7%	89.3%	84.1%
NISQA P501	utt MSE	-0.021	-0.260	-0.048	-0.248	-0.004	-0.125	-0.005	-0.163
	utt SRCC	100.2%	101.2%	99.1%	100.9%	98.5%	98.6%	96.4%	99.0%
TMHINT-QI test	utt MSE	0.072	-0.064	0.008	-0.079	-0.002	-0.063	-0.028	-0.069
	utt SRCC	92.0%	98.3%	95.0%	99.6%	95.5%	98.6%	95.9%	98.9%
VMC'22 OOD track	sys MSE	0.029	0.025	0.078	0.073	0.251	0.322	0.22	0.430
VIVIC 22 OOD track	sys SRCC	105.2%	99.5%	93.0%	92.6%	73.3%	71.4%	92.6%	100.0%
VMC'22 trock10	sys MSE	0.101	-0.234	-0.005	0.068	-0.328	-0.735	-0.511	-0.885
VIVIC 25 udekīd	sys SRCC	62.2%	58.6%	69.4%	69.1%	78.1%	70.0%	76.4%	92.2%
VMC'23 track1h	sys MSE	-0.333	-0.470	-0.248	-0.278	-0.420	-0.448	-0.357	-0.491
VIVIC 25 LIDEKTO	sys SRCC	100.7%	95.7%	100.3%	101.5%	90.2%	83.8%	87.6%	98.1%
VMC'22 track?	sys MSE	-0.103	-0.400	-0.448	-0.504	-0.266	-0.488	-0.074	-0.381
VIVIC 25 track2	sys SRCC	116.0%	117.5%	115.6%	118.0%	120.8%	121.4%	115.1%	114.8%
VMC'22 track2	utt MSE	-0.438	-0.267	-0.490	-0.298	-0.459	-0.267	-0.412	-0.240
	utt SRCC	105.2%	93.7%	108.5%	94.9%	117.9%	107.0%	104.3%	87.0%
AVG	MSE	-0.078	-0.158	-0.129	-0.132	-0.120	-0.156	-0.107	-0.146
AVU	LCC/SRCC	98.3%	96.1%	98.6%	97.4%	97.5%	94.8%	95.6%	95.5%

Fig. 6: Best score difference and best score ratio result for multiple datasets training experiments. Red boxes indicate a best score difference smaller than 0. Green boxes indicate a best score ratio larger than 100%.

TABLE III: Ablation study results on dataset size in single dataset training experiments, broken down with synthetic and non-synthetic tests.

Training	# training	Syn	thetic	Non-s	ynthetic	Average		
dataset	samples	MSE	LCC/ SRCC	MSE	LCC/ SRCC	MSE	LCC/ SRCC	
BVCC NISQA PSTN	4974 4974 4974	1.386 0.431 0.738	80.9% 74.3% 74.0%	0.993 0.387 0.567	84.9% 93.1% 89.1%	1.222 0.413 0.667	82.6% 82.1% 80.3%	
NISQA PSTN	11020 11020	0.548	81.8% 82.3%	0.379 0.454	94.2% 92.1%	0.478 0.513	87.0% 86.4%	
PSTN	52839	0.559	86.4%	0.430	93.3%	0.505	89.3%	

C. Multiple datasets training results

In this subsection, we are interested in the following research question:

RQ2: Does training on multiple datasets improve the generalization ability?

We therefore trained SSQA models by merging the seven training datasets listed in Table I. We trained two types of models, namely SSL-MOS (with naive multiple dataset train-



(a) SSL-MOS without MDF

(b) Modified AlignNet without MDF

Fig. 7: SSL embedding visualization of SSQA models trained on multiple datasets. The dots are colored using set labels. Black dots indicate training samples.

ing) and the modified AlignNet. For SSL-MOS, we reported results of two inference modes: parametric and naive kNN, as described in Section IV-C. For Modified AlignNet, we also reported results of two inference modes: domain embedding retrieval and naive kNN, described in Sections IV-E and IV-C, respectively. We also reported results with and without MDF.

The pre-training dataset was NISQA, following [28].

Since we are interested in "improvements", when calculating best score difference/ratio, the "best model" was defined as *the best-performing model in the single dataset experiments in Figure 3.*

1) Best score results: Figure 6 shows the best score results. For raw metric numbers, please refer to the Supplementary Materials.

First, we examined the results test set-wise. On in-domain test sets (BVCC, SOMOS, SingMOS and TMHINT-QI), while it was difficult to improve upon SRCC, improvements on MSE were observed, except for SingMOS. On SingMOS, it was difficult to get any improvement. We suspected the reason to be that SingMOS train was too small (2000 samples) compared to other training sets. On out-of-domain non-synthetic test sets (NISQA and VMC'23 track 3), we observed mostly improvements, while some were on par. It was worthwhile noting that the modified AlignNet performed worse than SSL-MOS in this category. Finally, on out-of-domain synthetic test sets (VMC'22 OOD track and VMC'23 tracks 1 and 2), we observed mostly improvements, except for VMC'22 OOD track and best score ratio in VMC'23 track 1a.

Next, we checked whether MDF is an effective technique. Looking at the row of average scores in Figure 6, while MDF improved SSL-MOS in both parametric and naive kNN inference modes (except for best score difference in naive kNN inference), and on modified AlignNet, it degraded modified AlignNet in both domain embedding retrieval and naive kNN inference (except for best score ratio in naive kNN inference). Hence, the effectiveness of MDF needs to be further examined.

We then investigated the advantage of naive kNN inference over parametric inference. It could be clearly observed that while the best score ratio numbers were worse, a clear improvement in the best score difference was present in all model variants. This indicates that a non-parametric inference mode like naive kNN offers better faithfulness.

Finally, we identify the best combinations for SSL-MOS and modified AlignNet based on the best score ratio. The best model was SSL-MOS with MDF in parametric inference mode, with an average best score difference/ratio of -0.129/98.6%, and the second best was modified AlignNet without MDF in parametric inference mode, with an average best score difference/ratio of -0.120/97.5%. The high performance of SSL-MOS suggests that, at least in our setting, the corpus effect might not exist, and moreover, the modified AlignNet could not yield better performance. While the highest best score ratio was 98.6%, which was smaller than 100%, we observed that there was only one test set that the model struggled with (VMC'23 track 1a), and for other test sets, especially other tracks in VMC'23 which were out-of-domain, the model offered large improvements. This supports the claim that training with multiple datasets could improve the generalization ability, without sacrificing the performance of in-domain data.

2) Visualization: Figure 7 is the visualization the SSL embeddings of the samples in the training set and the test sets, using the SSL-MOS and modified AlignNet models, both without MDF. We can see that both models provided a good

coverage of the test sets. However, it was difficult to explain set-wise performance differences based on this visualization.

VI. CONCLUSION

In this work, we tried to address the problem of generalization, a key challenge in SSQA, by introducing MOS-Bench, a comprehensive collection of datasets for training and evaluating SSQA models, and SHEET, a toolkit designed to facilitate SSQA research. Additionally, we proposed a novel metric, best score difference/ratio, to better assess model performance across diverse test sets. Through extensive experiments, we demonstrated that training SSQA models on multiple datasets improves generalization without compromising in-domain performance. We further showed that latent space visualization serves as an effective tool for analyzing generalization ability, shedding light on the behavior of SSQA models.

Perhaps the most interesting and important takeaway message is that non-synthetic training datasets like NISQA and PSTN offer a good generalization ability that not only applies to non-synthetic but also synthetic speech samples. While researchers have dedicated a great amount of effort to curating synthetic speech datasets like BVCC and SOMOS with diverse conditions, the findings in this work open up the possibility of eliminating such a need.

ACKNOWLEDGMENT

This work was partly supported by JST CREST under Grant Number JPMJCR19A3. The authors would like to thank Jaden Pieper and Stephen Voran, the authors of the AlignNet paper, for providing references to various datasets used in their work, as well as the fruitful discussions.

REFERENCES

- ITUT Recommendation, "Recommendation p.800: Methods for subjective determination of transmission quality," *International Telecommunications Union—Radiocommunication (ITU-T)*, 1998.
- [2] S. Möller, W.-Y. Chan, N. Côté, T. H. Falk, A. Raake, and M. Wältermann, "Speech Quality Estimation: Models and Trends," *IEEE Signal Processing Magazine*, vol. 28, no. 6, pp. 18–28, 2011.
- [3] E. Cooper, W.-C. Huang, Y. Tsao, H.-M. Wang, T. Toda, and J. Yamagishi, "A review on subjective and objective evaluation of synthetic speech," *Acoustical Science and Technology*, vol. 45, no. 4, pp. 161–183, 2024.
- [4] P. Wagner, J. Beskow, S. Betz, J. Edlund, J. Gustafson, G. Eje Henter, S. Le Maguer, Z. Malisz, Éva Székely, C. Tånnander, and J. Voße, "Speech Synthesis Evaluation — State-of-the-Art Assessment and Suggestion for a Novel Research Program," in *Proc. 10th ISCA Workshop* on Speech Synthesis (SSW 10), 2019, pp. 105–110.
- [5] T. Saeki, S. Maiti, S. Takamichi, S. Watanabe, and H. Saruwatari, "SpeechBERTScore: Reference-aware automatic evaluation of speech generation leveraging nlp evaluation metrics," *arXiv preprint arXiv*:2401.16812, 2024.
- [6] W.-C. Huang, E. Cooper, Y. Tsao, H.-M. Wang, T. Toda, and J. Yamagishi, "The VoiceMOS Challenge 2022," in *Proc. Interspeech*, 2022, pp. 4536–4540.
- [7] E. Cooper, W.-C. Huang, T. Toda, and J. Yamagishi, "Generalization ability of MOS prediction networks," in *Proc. ICASSP*, 2022, pp. 8442– 8446.
- [8] E. Cooper, W.-C. Huang, Y. Tsao, H.-M. Wang, T. Toda, and J. Yamagishi, "The Voicemos Challenge 2023: Zero-Shot Subjective Speech Quality Prediction for Multiple Domains," in *Proc. ASRU*, 2023, pp. 1–7.

- [9] A. Mohamed, H.-y. Lee, L. Borgholt, J. D. Havtorn, J. Edin, C. Igel, K. Kirchhoff, S.-W. Li, K. Livescu, L. Maaløe *et al.*, "Self-supervised speech representation learning: A review," *IEEE Journal of Selected Topics in Signal Processing*, vol. 16, no. 6, pp. 1179–1210, 2022.
- [10] A. Baevski, H. Zhou, A. Mohamed, and M. Auli, "wav2vec 2.0: A framework for self-supervised learning of speech representations," in *Proc. NeruIPS*, 2020.
- [11] W.-N. Hsu, B. Bolte, Y.-H. H. Tsai, K. Lakhotia, R. Salakhutdinov, and A. Mohamed, "Hubert: Self-supervised speech representation learning by masked prediction of hidden units," *IEEE/ACM TASLP*, vol. 29, pp. 3451–3460, 2021.
- [12] S. Chen, C. Wang, Z. Chen, Y. Wu, S. Liu, Z. Chen, J. Li, N. Kanda, T. Yoshioka, X. Xiao *et al.*, "WavLM: Large-scale self-supervised pretraining for full stack speech processing," *IEEE Journal of Selected Topics in Signal Processing*, vol. 16, no. 6, pp. 1505–1518, 2022.
- [13] W.-C. Tseng, C. yu Huang, W.-T. Kao, Y. Y. Lin, and H. yi Lee, "Utilizing self-supervised representations for mos prediction," in *Proc. Interspeech*, 2021, pp. 2781–2785.
- [14] T. Sellam, A. Bapna, J. Camp, D. Mackinnon, A. P. Parikh, and J. Riesa, "Squid: Measuring speech naturalness in many languages," in *ICASSP* 2023-2023 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP). IEEE, 2023, pp. 1–5.
- [15] R. E. Zezario, S.-W. Fu, F. Chen, C.-S. Fuh, H.-M. Wang, and Y. Tsao, "Deep learning-based non-intrusive multi-objective speech assessment model with cross-domain features," *IEEE/ACM TASLP*, vol. 31, pp. 54– 70, 2023.
- [16] K. El Hajal, Z. Wu, N. Scheidwasser-Clow, G. Elbanna, and M. Cernak, "Efficient Speech Quality Assessment Using Self-Supervised Framewise Embeddings," in *Proc. ICASSP*, 2023, pp. 1–5.
- [17] S. Maiti, Y. Peng, T. Saeki, and S. Watanabe, "SpeechLMScore: evaluating speech generation using speech language model," in *Proc. ICASSP*, 2023, pp. 1–5.
- [18] S.-W. Fu, K.-H. Hung, Y. Tsao, and Y.-C. F. Wang, "Self-Supervised Speech Quality Estimation and Enhancement Using Only Clean Speech," in *Proc. ICLR*, 2024. [Online]. Available: https://openreview.net/forum?id=ale56Ya59q
- [19] T. Saeki, D. Xin, W. Nakata, T. Koriyama, S. Takamichi, and H. Saruwatari, "UTMOS: UTokyo-SaruLab System for VoiceMOS Challenge 2022," in *Proc. Interspeech*, 2022, pp. 4521–4525.
- [20] D. H. Wolpert, "Stacked generalization," *Neural networks*, vol. 5, no. 2, pp. 241–259, 1992.
- [21] W.-C. Huang, E. Cooper, J. Yamagishi, and T. Toda, "LDNet: unified listener dependent modeling in MOS prediction for synthetic speech," in *Proc. ICASSP*, 2022, pp. 896–900.
- [22] Z. Qi, X. Hu, W. Zhou, S. Li, H. Wu, J. Lu, and X. Xu, "LE-SSL-MOS: Self-Supervised Learning MOS Prediction with Listener Enhancement," in *Proc. IEEE ASRU*, 2023, pp. 1–6.
- [23] ITUT Recommendation, "Recommendation p.1401: Methods, metrics and procedures for statistical evaluation, qualification and comparison of objective quality prediction models," *International Telecommunications* Union—Radiocommunication (ITU-T), 2001.
- [24] S. Le Maguer, S. King, and N. Harte, "Back to the future: Extending the blizzard challenge 2013," in *Interspeech*, 2022, pp. 2378–2382.
- [25] E. Cooper and J. Yamagishi, "Investigating Range-Equalizing Bias in Mean Opinion Score Ratings of Synthesized Speech," in *Proc. Interspeech*, 2023, pp. 1104–1108.
- [26] G. Mittag, S. Zadtootaghaj, T. Michael, B. Naderi, and S. Möller, "Biasaware loss for training image and speech quality prediction models from multiple datasets," in *International Conference on Quality of Multimedia Experience (QoMEX)*, 2021, pp. 97–102.
- [27] Y. Leng, X. Tan, S. Zhao, F. Soong, X.-Y. Li, and T. Qin, "MBNET: MOS Prediction for Synthesized Speech with Mean-Bias Network," in *Proc. ICASSP*, 2021, pp. 391–395.
- [28] J. Pieper and S. Voran, "Alignnet: Learning dataset score alignment functions to enable better training of speech quality estimators," in *Proc. Interspeech*, 2024, pp. 82–86.
- [29] E. Cooper and J. Yamagishi, "How do voices from past speech synthesis challenges compare today?" in *Proc. 11th ISCA Speech Synthesis Workshop (SSW 11)*, 2021, pp. 183–188.
- [30] G. Maniati, A. Vioni, N. Ellinas, K. Nikitaras, K. Klapsas, J. S. Sung, G. Jho, A. Chalamandaris, and P. Tsiakoulis, "SOMOS: The Samsung Open MOS Dataset for the Evaluation of Neural Text-to-Speech Synthesis," in *Proc. Interspeech*, 2022, pp. 2388–2392.
- [31] Y. Tang, J. Shi, Y. Wu, and Q. Jin, "Singmos: An extensive opensource singing voice dataset for mos prediction," arXiv preprint arXiv:2406.10911, 2024.

- [32] G. Mittag, B. Naderi, A. Chehadi, and S. Möller, "NISQA: A Deep CNN-Self-Attention Model for Multidimensional Speech Quality Prediction with Crowdsourced Datasets," in *Proc. Interspeech*, 2021, pp. 2127–2131.
- [33] Y.-W. Chen and Y. Tsao, "InQSS: a speech intelligibility and quality assessment model using a multi-task learning network," in *Proc. Inter*speech, 2022, pp. 3088–3092.
- [34] G. Yi, W. Xiao, Y. Xiao, B. Naderi, S. Möller, W. Wardah, G. Mittag, R. Culter, Z. Zhang, D. S. Williamson, F. Chen, F. Yang, and S. Shang, "ConferencingSpeech 2022 Challenge: Non-intrusive Objective Speech Quality Assessment (NISQA) Challenge for Online Conferencing Applications," in *Proc. Interspeech*, 2022, pp. 3308–3312.
- [35] G. Mittag, R. Cutler, Y. Hosseinkashi, M. Revow, S. Srinivasan, N. Chande, and R. Aichner, "DNN No-Reference PSTN Speech Quality Prediction," in *Proc. Interspeech*, 2020, pp. 2867–2871.
- [36] Z. Wu, Z. Xie, and S. King, "The Blizzard Challenge 2019," in Proc. Blizzard Challenge Workshop, vol. 2019, 2019.
- [37] O. Perrotin, B. Stephenson, S. Gerber, and G. Bailly, "The Blizzard Challenge 2023," in *Proc. 18th Blizzard Challenge Workshop*, Grenoble, France, August 29 2023.
- [38] W.-C. Huang, L. P. Violeta, S. Liu, J. Shi, and T. Toda, "The Singing Voice Conversion Challenge 2023," in *Proc. ASRU*, 2023, pp. 1–8.
- [39] R. E. Zezario, Y.-W. Chen, S.-W. Fu, Y. Tsao, H.-M. Wang, and C.-S. Fuh, "A study on incorporating Whisper for robust speech assessment," in *Proc. ICME*, 2024.
- [40] W.-C. Huang, S.-W. Fu, E. Cooper, R. Zezario, T. Toda, H.-M. Wang, J. Yamagishi, and Y. Tsao, "The Voicemos Challenge 2024: Beyond Speech Quality Prediction," in *Proc. SLT*, 2024.
- [41] T. Hayashi, R. Yamamoto, K. Inoue, T. Yoshimura, S. Watanabe, T. Toda, K. Takeda, Y. Zhang, and X. Tan, "Espnet-TTS: Unified, Reproducible, and Integratable Open Source End-to-End Text-to-Speech Toolkit," in *Proc. ICASSP*, 2020, pp. 7654–7658.
- [42] K. Ito and L. Johnson, "The LJ Speech Dataset," https://keithito.com/ LJ-Speech-Dataset/, 2017.
- [43] J.-M. Valin and J. Skoglund, "LPCNet: Improving neural speech synthesis through linear prediction," in *Proc. ICASSP*, 2019, pp. 5891–5895.
- [44] D. Povey, A. Ghoshal, G. Boulianne, L. Burget, O. Glembek, N. Goel, M. Hannemann, P. Motlicek, Y. Qian, P. Schwarz *et al.*, "The Kaldi Speech Recognition Toolkit," in *Proc. ASRU*, 2011.
- [45] S. Watanabe, T. Hori, S. Karita, T. Hayashi, J. Nishitoba, Y. Unno, N. E. Y. Soplin, J. Heymann, M. Wiesner, N. Chen, A. Renduchintala, and T. Ochiai, "ESPnet: End-to-End Speech Processing Toolkit," in *Proc. Interspeech*, 2018, pp. 2207–2211.
- [46] H. Wang, S. Zhao, X. Zheng, and Y. Qin, "RAMP: Retrieval-Augmented MOS Prediction via Confidence-based Dynamic Weighting," in *Proc. Interspeech*, 2023, pp. 1095–1099.
- [47] C.-C. Lo, S.-W. Fu, W.-C. Huang, X. Wang, J. Yamagishi, Y. Tsao, and H.-M. Wang, "MOSNet: Deep Learning-Based Objective Assessment for Voice Conversion," in *Proc. Interspeech*, 2019, pp. 1541–1545.
- [48] L. Van der Maaten and G. Hinton, "Visualizing data using t-SNE," Journal of machine learning research, vol. 9, no. 11, 2008.

Supplementary Materials for: MOS-Bench: Benchmarking Generalization Abilities of Subjective Speech Quality Assessment Models

1

Wen-Chin Huang, Member, IEEE, Erica Cooper, Member, IEEE, and Tomoki Toda Member, IEEE

I. ADDITIONAL EXPERIMENTAL RESULTS

Figure 1 shows the raw MSE and LCC/SRCC values of the single training dataset experiments. Figure 2 shows the visualization results of the single dataset training experiments. Figure 3 shows the raw MSE and LCC/SRCC values of the multiple training dataset experiments.

Train set Test set		BVCC	SOMOS	SingMOS	NISQA	TMHINT-QI	PSTN	Tencent
BVCC test	sys MSE	0.156	0.414	1.138	0.887	2.869	1.428	2.522
BVCC test	sys SRCC	0.926	0.703	0.317	0.807	0.626	0.780	0.682
SOMOS test	sys MSE	0.747	0.036	0.883	1.561	2.011	1.344	1.864
SOMOS lest	sys SRCC	0.691	0.918	-0.086	0.659	0.423	0.620	0.473
SingMOS test	sys MSE	4.071	3.420	0.064	0.246	0.362	0.140	0.276
	sys SRCC	0.553	0.149	0.810	0.316	0.356	0.534	0.505
NISQA FOR	utt MSE	0.393	0.633	2.874	0.172	2.929	0.548	1.025
	utt SRCC	0.774	0.502	0.400	0.912	0.706	0.864	0.755
NISQA LIVETALK	utt MSE	1.302	1.205	2.047	0.353	1.829	0.358	0.709
	utt SRCC	0.687	0.175	0.372	0.808	0.670	0.843	0.818
NISQA P501	utt MSE	0.380	0.741	2.618	0.522	3.583	1.296	2.326
	utt SRCC	0.872	0.768	0.287	0.913	0.606	0.814	0.795
TMHINT-QI test	utt MSE	2.883	1.693	0.923	1.773	0.468	1.319	1.233
	utt SRCC	0.576	0.237	0.357	0.628	0.783	0.647	0.612
PC10 test	sys MSE	2.890	1.814	1.063	0.549	1.307	0.336	1.036
BC19 test	sys SRCC	0.618	-0.009	0.396	0.744	0.581	0.754	0.572
VMC'23 track1a	sys MSE	0.286	0.975	0.543	1.380	1.844	1.169	1.940
VIVIC 25 track1a	sys SRCC	0.655	0.616	0.219	0.703	-0.067	0.633	0.395
VMC'23 track1b	sys MSE	2.340	1.246	0.531	0.623	1.498	0.840	1.055
VIVIC 25 trackin	sys SRCC	0.387	0.580	0.486	0.554	0.225	0.727	0.529
VMC'23 track2	sys MSE	1.572	1.567	1.637	0.954	2.119	1.019	1.901
VMC'23 track2	sys SRCC	0.701	0.367	0.693	0.744	0.569	0.722	0.690
VMC'23 track2	utt MSE	2.298	1.304	1.027	1.362	1.084	0.916	0.962
v IVIC 25 tracks	utt SRCC	0.596	0.211	0.259	0.635	0.583	0.668	0.526

Fig. 1: Raw scores of the single dataset training experiments.



(g) PSTN

Fig. 2: SSL embedding visualization of SSQA models trained on one single dataset. For each subfigure, the right-hand side figure colored the dots using set labels, and the left-hand side figure colored the dotes using synthetic/non-synthetic labels. Black dots indicate training samples.

Model		_		SSL-	MOS		Modified			
MDF		Best		-	· ·	V	-		l I	/
Inference method		single dataset result	parametric	naive kNN	parametric	naive kNN	domain embedding retrieval	naive kNN	domain embedding retrieval	naive kNN
BVCC test	sys MSE	0.156	0.176	0.124	0.169	0.116	0.119	0.124	0.121	0.124
	sys SRCC	0.926	0.912	0.916	0.912	0.918	0.921	0.912	0.914	0.907
SOMOS test	sys MSE	0.036	0.094	0.019	0.044	0.022	0.036	0.020	0.043	0.020
SOMOS test	sys SRCC	0.918	0.903	0.905	0.894	0.895	0.896	0.901	0.898	0.899
SingMOS tost	sys MSE	0.064	0.121	0.073	0.072	0.067	0.115	0.108	0.092	0.113
Singwios test	sys SRCC	0.810	0.761	0.781	0.773	0.795	0.719	0.720	0.729	0.724
NISQA FOR	utt MSE	0.172	0.191	0.146	0.189	0.164	0.247	0.208	0.295	0.217
	utt SRCC	0.912	0.905	0.899	0.892	0.887	0.861	0.868	0.857	0.868
NISQA LIVETALK	utt MSE	0.358	0.318	0.312	0.277	0.266	0.400	0.375	0.423	0.450
	utt SRCC	0.843	0.850	0.835	0.872	0.862	0.802	0.790	0.753	0.709
NISQA P501	utt MSE	0.522	0.501	0.262	0.474	0.274	0.518	0.397	0.517	0.359
	utt SRCC	0.913	0.915	0.924	0.905	0.921	0.899	0.900	0.880	0.904
TMHINT-OI test	utt MSE	0.468	0.540	0.404	0.476	0.389	0.466	0.405	0.440	0.399
	utt SRCC	0.783	0.720	0.770	0.744	0.780	0.748	0.772	0.751	0.774
BC19 test	sys MSE	0.336	0.365	0.361	0.414	0.409	0.587	0.658	0.556	0.766
BC17 test	sys SRCC	0.754	0.793	0.750	0.701	0.698	0.553	0.538	0.698	0.754
VMC'23 track1a	sys MSE	1.380	1.481	1.146	1.375	1.448	1.052	0.645	0.869	0.495
	sys SRCC	0.703	0.437	0.412	0.488	0.486	0.549	0.492	0.537	0.648
VMC'23 track1h	sys MSE	0.840	0.507	0.370	0.592	0.562	0.420	0.392	0.483	0.349
VIVIC 25 track10	sys SRCC	0.727	0.732	0.696	0.729	0.738	0.656	0.609	0.637	0.713
VMC'23 track?	sys MSE	0.954	0.851	0.554	0.506	0.450	0.688	0.466	0.880	0.573
VIVIC 25 udok2	sys SRCC	0.744	0.863	0.874	0.860	0.878	0.899	0.903	0.856	0.854
VMC'23 track3	utt MSE	0.916	0.478	0.649	0.426	0.618	0.457	0.649	0.504	0.676
VIVIC 25 LIDEKS	utt SRCC	0.668	0.703	0.626	0.725	0.634	0.708	0.615	0.697	0.581

Fig. 3: Raw scores of the multiple dataset training experiments.