# LARGE LANGUAGE MODELS FOR CONSTRUCTING AND OPTIMIZING MACHINE LEARNING WORKFLOWS: A SURVEY\*

A PREPRINT

Yang Gu<sup>†1</sup>, Hengyu You<sup>1</sup>, Jian Cao<sup>1</sup>, Muran Yu<sup>2</sup>, Haoran Fan<sup>1</sup>, and Shiyou Qian<sup>1</sup> <sup>1</sup>Shanghai Jiao Tong University, Shanghai, China <sup>2</sup>Stanford University, Stanford, California, USA

#### ABSTRACT

Building effective machine learning (ML) workflows to address complex tasks is a primary focus of the Automatic ML (AutoML) community and a critical step toward achieving artificial general intelligence (AGI). Recently, the integration of Large Language Models (LLMs) into ML workflows has shown great potential for automating and enhancing various stages of the ML pipeline. This survey provides a comprehensive and up-to-date review of recent advancements in using LLMs to construct and optimize ML workflows, focusing on key components encompassing data and feature engineering, model selection and hyperparameter optimization, and workflow evaluation. We discuss both the advantages and limitations of LLM-driven approaches, emphasizing their capacity to streamline and enhance ML workflow modeling process through language understanding, reasoning, interaction, and generation. Finally, we highlight open challenges and propose future research directions to advance the effective application of LLMs in ML workflows.

Keywords Machine Learning Workflows · Large Language Models · AutoML

## 1 Introduction

In the era of big data, machine learning (ML) workflows have become essential across various sectors for processing and analyzing large-scale data Xin et al. [2021], Nikitin et al. [2022]. To support the development and sharing of ML workflows, numerous repositories have been established, showcasing diverse paradigms for data analysis. For instance, KNIME offers a repository with over 25,000 workflows and 2,200 components Ordenes and Silipo [2021], providing a comprehensive collection of rigorously tested, practical models complete with detailed specifications. However, despite the availability of these resources, manually constructing and optimizing workflows to meet complex task requirements remains a knowledge-intensive and time-consuming challenge for most people.

The advent of Large Language Models (LLMs) has recently revolutionized artificial intelligence (AI) and ML, delivering advanced capabilities in natural language understanding and generation Hollmann et al. [2024], Wang et al. [2024a]. Models such as OpenAI's GPT-4 Achiam et al. [2023] and Meta AI's LLaMA-3 Touvron et al. [2023] have demonstrated exceptional performance across a wide range of natural language processing (NLP) tasks, thanks to their extensive training on large-scale text datasets. Additionally, multimodal LLMs Hu et al. [2024], Tai et al. [2024], Luo et al. [2024], which incorporate various data types like audio and images, allow for richer interactions by processing and generating non-textual information. Their impressive capabilities have led to widespread adoption across multiple domains Gu et al. [2023], Klievtsova et al. [2023], Zhang et al. [2023a]. As ML tasks and workflows become increasingly complex, often involving diverse modalities and domains, the potential of LLMs to automate and enhance these workflows has

<sup>\*</sup>This paper is under review. © © 20xx IEEE. Personal use of this material is permitted. Permission from IEEE must be obtained for all other uses, in any current or future media, including reprinting/republishing this material for advertising or promotional purposes, creating new collective works, for resale or redistribution to servers or lists, or reuse of any copyrighted component of this work in other works.

<sup>&</sup>lt;sup>†</sup>gu\_yang@sjtu.edu.cn. Corresponding author is Jian Cao (cao-jian@sjtu.edu.cn). For recent work on LLMs for ML workflows, visit our repository: https://github.com/t-harden/LLM4AutoML.

garnered significant attention from the research community Xiao et al. [2024], Hong et al. [2024]. This progress is also viewed as a pivotal step toward achieving artificial general intelligence (AGI).

As illustrated in Fig. 1, an ML workflow, receiving the input of task specification, typically involves a sequence of interconnected steps De Bie et al. [2022], including data and feature engineering, model selection and hyperparameter optimization, and workflow evaluation. Traditionally, these steps demand considerable manual effort and specialized domain expertise, which can limit scalability and adaptability, particularly when working with large, high-dimensional datasets Lazebnik et al. [2022]. This challenge has driven the development of automated machine learning (AutoML), which seeks to streamline the ML workflow by automating essential modeling and optimization processes Hutter et al. [2019].



Figure 1: An overview of the Machine Learning Workflow, where task specification serves as the input, encompassing key stages of data and feature engineering, model selection and hyperparameter optimization, and workflow evaluation.

Despite the significant advancements brought by AutoML Nikitin et al. [2022], An et al. [2023], traditional AutoML frameworks still face notable challenges. First, the iterative nature of the search processes in AutoML—often involving exhaustive model selection and hyperparameter tuning—can be extremely time-consuming and computationally expensive Olson and Moore [2016]. Second, these methods typically struggle to leverage valuable historical and human knowledge from diverse sources effectively. Even with the integration of meta-learning and Bayesian optimization techniques Feurer et al. [2022], Saha et al. [2022], traditional AutoML systems often lack the ability to collaborate seamlessly with human experts, thereby limiting their flexibility and adaptability. Finally, the models generated by AutoML are often criticized for their lack of interpretability, making it difficult for practitioners to understand and trust the decisions made by these systems Shah et al. [2021], Zhang et al. [2023b].

These limitations highlight the need for more advanced solutions, where LLMs demonstrate significant potential by incorporating prior knowledge, facilitating human-AI collaboration, and producing more interpretable outcomes. For instance, in hyperparameter optimization Zhang et al. [2023c], Liu et al. [2024a], LLMs can leverage historical data and domain-specific insights to predict optimal configurations, thereby enhancing model performance and reducing the reliance on exhaustive trial-and-error methods. Furthermore, the sophisticated NLP capabilities of LLMs enable them to act as interactive agents or chatbots, capable of generating and adjusting AutoML code based on contextual information provided by users Arteaga Garcia et al. [2024], Guo et al. [2024], Dakhel et al. [2023]. Crucially, in the process of conversational construction of ML workflows—such as feature engineering Hollmann et al. [2024]—LLMs have shown the ability to generate human-readable and explainable features, offering a level of transparency and guidance that surpasses many traditional black-box AutoML systems Zhang et al. [2024a], Nam et al. [2024].

However, integrating LLMs into ML workflows also presents several challenges. Issues such as reasoning hallucinations, ethical concerns, and the substantial computational demands of deploying large-scale models remain significant barriers to their widespread adoption Bommasani et al. [2021], Hollmann et al. [2024], Yao et al. [2024a]. Additionally, while LLMs have demonstrated impressive results in specific tasks, their effectiveness across the entire spectrum of ML workflow stages Zhang et al. [2023b], Schmidt et al. [2024] still requires thorough investigation and evaluation using some benchmarks like MLE-Bench Chan et al. [2024] and MLAgentBench Huang et al. [2024].

This survey provides a comprehensive overview of the current state of research on the application of LLMs in constructing and optimizing ML workflows. To the best of our knowledge, it is the first survey to systematically address every stage of the ML workflow (Fig. 1), distinguishing it from previous reviews, such as Tornede et al. [2023a], which primarily explore the broader opportunities of an integration of LLMs and AutoML. We organize recent papers based on the specific steps in which LLMs have been utilized, as summarized in Table 1, with entries sorted by publication year (oldest to newest) and the order of workflow steps. Notably, our focus is on capturing the breadth and possibility of research within the specific context of constructing and optimizing ML workflows, rather than providing an exhaustive examination of all LLM-related methods at each individual stage.

Table 1: Comparison of existing methods that utilize LLMs for constructing and optimizing ML workflows in terms of specific workflow components.

Method	Data	Feature	Model	Hyperparameter	Workflow
	Preprocessing	Engineering	Selection	Optimization	Evaluation
LMPriors Choi et al. [2022]		$\checkmark$			
ZAP Öztürk et al. [2022]			$\checkmark$		
VIDS Hassan et al. [2023]	$\checkmark$				
JarviX Liu et al. [2023]	$\checkmark$				
Aliro Choi et al. [2023]	$\checkmark$				
AutoML-GPT Zhang et al. [2023d]	<ul> <li>✓</li> </ul>		$\checkmark$	✓	$\checkmark$
MLCopilot Zhang et al. [2023b]			$\checkmark$		
GENIUS Zheng et al. [2023]			$\checkmark$	$\checkmark$	
GPT-NAS Yu et al. [2023a]			$\checkmark$	$\checkmark$	
AutoMMLab Yang et al. [2024]	$\checkmark$		$\checkmark$	$\checkmark$	
AutoML-Agent Trirat et al. [2024]	$\checkmark$		$\checkmark$	$\checkmark$	
AutoM <sup>3</sup> L Luo et al. [2024]	$\checkmark$	$\checkmark$	$\checkmark$	$\checkmark$	
Text-to-ML Xu et al. [2024]	$\checkmark$	<ul> <li>✓</li> </ul>	$\checkmark$		$\checkmark$
LLM-Select Jeong et al. [2024]		$\checkmark$			
GL-Agent Wei et al. [2024]		$\checkmark$	$\checkmark$		
CAAFE Hollmann et al. [2024]		$\checkmark$			
HuggingGPT Shen et al. [2024]			$\checkmark$		
ModelGPT Tang et al. [2024]			$\checkmark$		
VML Xiao et al. [2024]			$\checkmark$		$\checkmark$
GE Morris et al. [2024]				$\checkmark$	
AgentHPO Liu et al. [2024a]				$\checkmark$	$\checkmark$
LLAMBO Liu et al. [2024b]				$\checkmark$	

\* The symbol  $\sqrt{}$  denotes that LLMs are applied to support a particular component within the method.

The remainder of this paper is structured as follows. We begin with a discussion of the foundational concepts and recent developments in ML workflow and LLMs (Section 2). This is followed by an exploration of the roles LLMs play in key stages of ML workflows, including data and feature engineering (Section 3), model selection and hyperparameter optimization (Section 4), and workflow evaluation (Section 5). In Section 6, we address several open challenges and outline future research directions in this field. Finally, we conclude our survey in Section 7.

# 2 Preliminaries

#### 2.1 Machine Learning Task and Workflow

ML is a subfield of AI that focuses on the development of algorithms and statistical models that enable computers to perform specific tasks Allen [2020]. These tasks range from classification and regression to clustering and reinforcement learning, each designed to identify patterns and make predictions based on data Zhou [2021], LeCun et al. [2015]. The fundamental goal of ML is to create models that generalize well from training data to unseen data, effectively solving the problem at hand Chung et al. [2018]. The ML Workflow, a structured sequence of components Oakes et al. [2024], is designed to systematically and repeatably achieve the task's objective, leading to the development of a robust and effective model.

The input of an ML workflow is typically the task specification, encompassing both the dataset definition and task description. The dataset, consisting of input data (features) and output labels (for supervised tasks), serves as the

foundation for training the model Saha et al. [2022]. For example, the HousingPrice dataset Harrison Jr and Rubinfeld [1978] may contain a CSV table with 14 columns, where the first 13 columns represent predictive features, and the final column indicates the target variable (housing price). The task description further clarifies the model's objective and evaluation metrics Zhang et al. [2023b], specifying goals such as predicting housing prices using the  $R^2$  metric, classifying images with the *F*1-score metric, or identifying clusters within data using the ARI metric. Importantly, datasets and tasks vary widely in structure and type, encompassing diverse data formats such as numerical values, text, images, and time series Huang et al. [2024].

#### 2.2 Background on LLMs

Large Language Models (LLMs) are advanced neural networks, primarily built on Transformer architectures Vaswani [2017], that excel at processing and generating human-like text. Models such as OpenAI's GPT-4 Achiam et al. [2023], Google's PaLM-2 Anil et al. [2023], and Meta AI's LLaMA-3 Touvron et al. [2023] have revolutionized natural language processing (NLP), achieving state-of-the-art performance across a wide array of tasks, including text generation, translation, summarization, and question answering Minaee et al. [2024]. Moreover, LLMs are increasingly being applied to diverse domains beyond NLP, thanks to their ability to model complex language patterns and generalize across various data types Xiao et al. [2024], Liu et al. [2024b], Yu et al. [2023b].

LLMs, which often contain tens to hundreds of billions of parameters Zhao et al. [2023], Wang et al. [2024b], are trained on vast textual datasets, enabling them to capture intricate language patterns and generate coherent, contextually accurate text. One of their most notable features is their ability to perform zero-shot and few-shot learning, where they generalize to new tasks with minimal task-specific data or examples Sahoo et al. [2024]. This flexibility significantly reduces the need for retraining, allowing LLMs to handle a wide range of tasks based on just a few instructions. Additionally, LLMs can break down complex tasks into intermediate reasoning steps, as demonstrated by techniques like Chain-of-Thought (CoT) Wei et al. [2022], Tree-of-Thought (ToT) Yao et al. [2024b], and Graph-of-Thought (GoT) prompting Besta et al. [2024]. LLMs can also be augmented with external knowledge sources and tools Zhuang et al. [2024], Fan et al. [2024], enabling them to interact more effectively with users and their environment Xi et al. [2023]. These models can be deployed as LLM-based agents, artificial entities capable of sensing their environment, making decisions, and taking actions autonomously Zhao et al. [2024]. Furthermore, through mechanisms like reinforcement learning with human feedback (RLHF), LLMs can continually improve their performance by incorporating feedback from interactions Wang et al. [2024c].

While fine-tuning and alignment improves their performance and adds different dimensions to their abilities, there are still some important limitations that come up. Training and deploying LLMs is computationally expensive, requiring significant hardware resources, which restricts their accessibility for many organizations Zhang et al. [2024b], Bai et al. [2024]. Another pressing concern is the phenomenon of reasoning hallucinations, where LLMs, despite generating plausible-sounding text, can produce factually incorrect or unfaithful outputs, potentially leading to unreliable decisions in sensitive applications Li et al. [2024], Leiser et al. [2024]. Furthermore, LLMs inherently operate as probabilistic models, often producing different outputs when presented with the same inputs Wang [2024]. While parameters like temperature can be fine-tuned to control this variability, the stochastic nature of LLM responses presents challenges in ensuring consistency and reliability across use cases Gruver et al. [2024]. Moreover, the vast datasets used to train LLMs often include sensitive information, posing ethical risks around data privacy and security, especially in fields like healthcare or finance where confidentiality is paramount Yao et al. [2024a], Yang et al. [2024]. These limitations are important considerations when evaluating the deployment of LLMs in real-world tasks.

In this survey, we explore the current research landscape on leveraging LLMs to construct and optimize ML workflows, with a focus on each stage of the workflow. Our goal is to provide researchers and practitioners with a comprehensive understanding of the strengths and limitations of LLMs in this context. By examining the key achievements and identifying the existing challenges, we aim for this survey to serve as a foundation for future research, fostering more effective and integrated applications of LLMs in automating ML workflows.

# **3** LLMs for Data and Feature Engineering

Upon receiving the task specification, the first stage in the ML workflow is data and feature engineering, which can be further divided into two key substeps: data preprocessing and feature engineering. Data preprocessing involves cleaning, transforming, and normalizing raw data to ensure consistency and quality for subsequent analysis. Feature engineering focuses on extracting informative and relevant features from the preprocessed data to enhance the performance of learning algorithms. The following subsections will explore how LLMs can support these two crucial processes.

#### 3.1 Data Preprocessing

In many practical scenarios, the qualitative properties of raw data are not often consistent with the requirements of the target application or model Zelaya [2019], Parashar et al. [2023]. Consequently, data preprocessing has become an essential task in the machine learning application development process. Data preprocessing is typically divided into three key aspects: data acquisition, data cleaning, and data augmentation He et al. [2021]. Each aspect plays a crucial role in ensuring the quality and usability of the data before it is fed into machine learning models. The main categorization of LLM-assisted Data Preprocessing methods is illustrated in Fig. 2.

- Data Acquisition involves identifying and gathering suitable datasets.
- Data Cleaning filters noisy or inconsistent data to preserve the integrity of model training.
- Data Augmentation enhances model robustness by artificially increasing the size and diversity of the dataset.



Figure 2: The main categorization of LLM-assisted Data Preprocessing methods.

# 3.1.1 Data Acquisition

Data acquisition forms the foundation of the machine learning workflow by ensuring that the right data is sourced for model training and validation. This stage is critical because the quality and relevance of the collected data directly impact the final model's performance Zhou et al. [2024]. The goal is to identify and gather datasets that align with the task at hand, which can be a time-consuming and labor-intensive process.

LLMs have emerged as powerful tools to streamline the data acquisition process by minimizing the need for extensive manual effort and domain-specific expertise. They are capable of interpreting task requirements, identifying pertinent data sources, and generating comprehensive dataset reports, thereby expediting the workflow. Approaches for LLM-assisted data acquisition generally fall into two main categories: dataset recommendation and dataset summarization.

In the context of **dataset recommendation**, some systems harness LLMs to suggest datasets that align with specific task needs. AutoMMLab Yang et al. [2024] employs LLMs for natural language interaction with users, utilizing a "dataset zoo" to recommend or retrieve relevant datasets based on task descriptions. This automated selection helps tailor custom datasets to the unique requirements of specialized machine learning tasks. Similarly, AutoML-Agent Trirat et al. [2024] employs an LLM-based Data Agent to execute sub-tasks within a decomposed plan generated through retrieval-augmented planning. These sub-tasks include dataset retrieval, pre-processing, augmentation, and analysis, ensuring that the selected datasets align seamlessly with the given task requirements. LLMs are also used for **dataset summarization**, aiding users in understanding data structure and content before further processing. The Virtual Interactive Data Scientist (VIDS) framework Hassan et al. [2023], for example, features ChatGPT-powered agents that extract detailed insights, including dataset structures, column details, and visualization suggestions. Similarly, JarviX Liu et al. [2023] incorporates an "Insight" component to automatically gather structured data information—such as column names, types, and statistics—and generate LLM-driven summary reports, giving users a quick overview of key dataset characteristics.

However, if relevant datasets are unavailable or if the LLM misinterprets task requirements, the data acquisition process can result in irrelevant or poor-quality data, potentially compromising downstream ML tasks Yang et al. [2018, 2024]. Moreover, when integrating data from multiple heterogeneous sources, manual oversight may be necessary to ensure consistency and compatibility Liu et al. [2023]. These limitations highlight the need for continuous refinement of LLM-driven data acquisition methods to enhance reliability and accuracy.

#### 3.1.2 Data Cleaning

Data cleaning is a crucial step in the ML workflow, essential for eliminating noise, inconsistencies, and missing values that can impact model performance Jesmeen et al. [2018], Guha et al. [2024]. Traditionally, AutoML systems have relied heavily on rule-based approaches to handle data cleaning tasks such as error detection, imputation, and normalization Neutatz et al. [2022]. However, the introduction of LLMs into the process offers more dynamic and intelligent solutions by automating these tasks with enhanced flexibility. LLM-assisted data cleaning can be grouped into two primary categories: adaptive data imputation and preparation, and context-enhanced cleaning and transformation.

The **adaptive data imputation and preparation** category leverages LLMs to manage missing data and generate preprocessing modules that are tailored to specific tasks. For example, in the AutoM<sup>3</sup>L framework Luo et al. [2024], the AFE-LLM<sub>imputed</sub> component uses prompts to fill in missing values based on contextual understanding, improving data completeness and ensuring datasets are ready for subsequent processing. Similarly, the Text-to-ML method Xu et al. [2024] employs LLMs to automatically generate data preparation modules, including routines for data loading and cleaning. These modules are refined iteratively through feedback, allowing the system to adapt to the unique needs of each task and continuously enhance preprocessing accuracy.

While adaptive methods focus on imputation and basic preparation, **context-enhanced cleaning and transformation** approaches aim to provide a deeper understanding of the dataset for more accurate cleaning and transformation. In this category, LLMs interpret preliminary data analyses, such as data types, correlations, and statistical summaries, to guide the cleaning process. For instance, in JarviX Liu et al. [2023], LLMs use pre-analyzed data insights stored in a database to inform cleaning recommendations, taking into account both structured and unstructured data characteristics. AutoML-GPT Zhang et al. [2023d] employs a similar strategy by using project-specific descriptions to suggest customized data transformations, recommending operations like image resizing and normalization for computer vision tasks, or tokenization and lowercasing for NLP tasks. Furthermore, the interactive data analysis tool Aliro Choi et al. [2023] enables users to prompt LLMs for preprocessing guidance based on observed data characteristics. For instance, if users identify outliers while exploring a PCA scatterplot, they can engage with Aliro's chat feature to request recommendations for outlier detection methods, along with generated code snippets to effectively manage these outliers.

Despite the advantages of LLMs in identifying data patterns, they can occasionally misinterpret complex data structures, leading to incorrect or suboptimal cleaning suggestions. Moreover, handling domain-specific anomalies often requires specialized knowledge that LLMs may lack, necessitating manual intervention or targeted domain-specific training to ensure high-quality data preparation.

#### 3.1.3 Data Augmentation

Data augmentation refers to techniques used to artificially increase the size of the training dataset by creating enhanced versions of existing data. This step is particularly useful for enhancing model robustness, improving generalization, and avoiding overfitting, especially in scenarios where data is scarce.

LLMs contribute significantly to data augmentation by employing techniques for modifying original data and generating synthetic datasets. In the realm of **original data modification**, LLMs assist in applying diverse transformation techniques to augment data effectively. For instance, the Data Agent in AutoML-Agent Trirat et al. [2024] suggests various image transformation methods, such as random horizontal flipping and zooming, to enhance user-input image datasets, thereby increasing data variability and robustness for model training. For **synthetic data generation**, recent studies underscore the capabilities of pre-trained language models (PLMs) to create synthetic datasets for training target models Gao et al. [2023], Yu et al. [2024]. To address potential biases in synthetic data generated by a single PLM, FuseGen Zou et al. [2024] innovatively combines multiple PLMs to collaboratively produce higher-quality synthetic data generation additional queries to individual models, thereby improving the reliability of synthetic data generation pipelines to produce datasets for diverse applications, including healthcare, retail, and manufacturing. Although the integration of LLMs into data augmentation is still in its early stages, their ability to modify and generate meaningful data based on learned patterns from existing datasets presents a promising avenue. This is particularly valuable in scenarios where data availability is limited, enabling more effective solutions for specific ML tasks Geng et al. [2023].

One challenge in using LLMs for data augmentation is the potential introduction of bias or irrelevant features into the augmented data. Additionally, ensuring that synthetic data accurately reflects real-world tasks without raising privacy or ethical concerns also remains a complex issue Lin et al. [2023], Xie et al. [2024].

#### 3.2 Feature Engineering

While machine learning models built on deep neural architectures can automatically learn useful features Bengio et al. [2013], certain application settings still require explicit feature processing before model training to ensure optimal performance. Feature engineering is the process of extracting and refining relevant features from raw input data, which can significantly enhance predictive accuracy Hollmann et al. [2024]. The process typically involves three key subtopics: feature selection, feature extraction, and feature synthesis Mumuni and Mumuni [2024].

- Feature Selection is the process of choosing the most important features that reduce feature redundancy and improve model performance by focusing on the most relevant data attributes.
- Feature Extraction aims to create more robust, representative and compact features by applying specific mapping functions to the raw data.
- Feature Synthesis involves generating new features from existing ones, creating richer representations that can better capture the underlying patterns in the dataset.

## 3.2.1 Feature Selection

Feature selection involves building a subset of features from the original set by eliminating irrelevant or redundant ones He et al. [2021]. This process simplifies the model, reduces the risk of overfitting, and enhances overall performance Parashar et al. [2023]. The selected features are typically diverse and highly correlated with the target variables, ensuring they contribute meaningfully to the model's predictions.

LLMs are increasingly being employed to automate feature selection by leveraging their ability to understand the semantic context of datasets. In the LMPriors framework Choi et al. [2022], LLMs are prompted to assess whether each candidate feature should be used for predicting the target outcome. Features are selected based on the difference in log probabilities between generating a "Y" (Yes) or "N" (No) token, crossing a predefined threshold. In contrast, LLM-Select Jeong et al. [2024] uses the generated text output directly, rather than token probabilities, to evaluate and select features. In this approach, LLMs analyze textual descriptions of features and their relationship to the target task, helping to identify the most relevant features that are crucial for predictive performance, thus reducing the complexity of the model. Similarly, in AutoM<sup>3</sup>L Luo et al. [2024], the AFE-LLM<sub>filter</sub> component effectively filters out irrelevant or redundant attributes. The LLM integrates contextual information, including attributes from diverse datasets, column names from structured tables, modality inference results from MI-LLM (Modality Inference-LLM), and user instructions or task descriptions, into the prompt to enhance the feature selection process.

However, LLMs may inherit undesirable biases from their pretraining data Gallegos et al. [2024], which could result in biased feature selection and performance disparities across subpopulations within the dataset. This concern may be addressed by using LLM-driven feature selection in a human-in-the-loop setup or combining it with traditional data-driven methods Jeong et al. [2024]. Additionally, there is a risk that features selected based on semantic relevance may be statistically weak, potentially diminishing their contribution to model performance.

# 3.2.2 Feature Extraction

Feature extraction is a dimensionality reduction process that transforms the original features using mapping functions to extract informative and non-redundant features based on specific metrics. Unlike feature selection, which retains the original features, feature extraction modifies them to generate new representations. Common approaches for feature extraction include methods like principal component analysis (PCA) Maćkiewicz and Ratajczak [1993], linear discriminant analysis (LDA) Xanthopoulos et al. [2013], and autoencoders Hinton and Salakhutdinov [2006].

LLMs have demonstrated significant potential in feature extraction, particularly in handling complex, multimodal datasets and generating semantically meaningful features. In the LLM-based Versatile Graph Learning approach Wei et al. [2024], LLMs are employed to select appropriate feature engineering strategies that capture both the structural and semantic properties of graph data, aligning them with the specific learning task and evaluation metric. Similarly, in the Text-to-ML method Xu et al. [2024], LLMs automate the extraction and transformation of raw features for numerical, text, and image data by generating task-specific code. This code is then validated using automatically generated unit tests and synthetic data produced by LLMs, ensuring consistency in the extracted features across all dimensions.

A key challenge with LLM-driven feature extraction is ensuring that the generated features accurately represent the underlying data distribution. In some cases, the complexity of the dataset or domain-specific nuances may lead to suboptimal or incorrect feature extraction, which could adversely affect model performance.

#### 3.2.3 Feature Synthesis

Feature synthesis involves leveraging the statistical distribution of extracted features to generate new, complementary ones. This approach is particularly useful when the existing features are insufficient to provide an adequate representation of the input data Mumuni and Mumuni [2024]. Traditionally, this process has relied heavily on human expertise for tasks like standardization and feature discretization. However, manually exploring all possible feature combinations is infeasible. As a result, automatic feature construction methods, such as tree-based, genetic algorithm-based and reinforcement learning-based approaches Vafaie and De Jong [1998], Zhang et al. [2019], have been developed and have demonstrated performance comparable to or even better than human-designed features.

LLMs have proven highly effective in generating semantically and contextually relevant synthetic features, enhancing the feature synthesis process through an interpretable, human-in-the-loop approach. In the Context-Aware Automated Feature Engineering (CAAFE) framework Hollmann et al. [2024], LLMs iteratively generate additional meaningful features for tabular datasets based on the dataset description, as shown in Fig. 3. This approach not only produces Python code for creating new features but also provides explanations of the utility and relevance of the generated features. CAAFE represents a step forward in semi-automated data science tasks, emphasizing the importance of context-aware solutions that extend AutoML systems into more interpretative and human-centered workflows Lindauer et al. [2024].



Figure 3: An example of feature synthesis by LLMs. Refer to CAAFE Hollmann et al. [2024] for detailed description.

However, processing datasets with a large number of features can result in oversized prompts, which can be challenging for LLMs to handle efficiently. Additionally, LLMs may exhibit hallucinations, generating features and explanations that seem plausible and are logically structured but may not be grounded in the actual data. These issues highlight the need for careful oversight when using LLMs for feature synthesis.

# 4 LLMs for Model Selection and Hyperparameter Optimization

Model Selection (MS) and Hyperparameter Optimization (HPO) play a pivotal role in the ML workflow, directly impacting the performance and generalizability of the model. Model selection involves choosing the most suitable algorithm or model architecture for a given task Yang et al. [2019], while hyperparameter optimization fine-tunes the settings that govern the behavior of the model, such as learning rate, regularization strength, and the number of layers Vincent and Jidesh [2023]. A related task is the Combined Algorithm Selection and Hyper-parameter optimisation (CASH). It jointly address the MS and HPO problems by treating the selection of the ML algorithm as an hyper-parameter itself Thornton et al. [2013].

These two processes are critical for achieving optimal model performance, as they balance the trade-offs between model complexity, training efficiency, and predictive accuracy. Effective MS and HPO ensure that models generalize well to unseen data, mitigating the risks of overfitting or underfitting. Recently, LLMs have shown promise in enhancing

model selection and hyperparameter optimization by leveraging their contextual understanding and data processing capabilities Zhang et al. [2023b], Xiao et al. [2024], Liu et al. [2024a]. In the following subsections, we explore how LLMs are being applied to automate and improve these two crucial aspects of the ML workflow.

#### 4.1 Model Selection

Model selection involves the identification of the most appropriate algorithm or model architecture for a specific task. Selected models can generally be classified into two categories: traditional models, such as decision trees Quinlan [1986] and naive Bayes classifiers Rish et al. [2001], and deep neural networks (DNNs), such as convolutional neural networks (CNNs) LeCun et al. [1998] and recurrent neural networks (RNNs) Hochreiter [1997], which are more frequently used for tasks involving unstructured data like images and sequences. Traditionally, the model selection process relies heavily on trial and error, domain expertise, and substantial computational resources, requiring significant human effort from experts to test and compare various models Lindauer et al. [2015]. The correct choice of model significantly influences predictive performance, interpretability, and scalability.

LLMs are increasingly being leveraged to streamline and automate model selection. By analyzing textual descriptions of tasks and datasets, LLMs can retrieve or generate suitable algorithms based on their pre-trained knowledge and accumulated experience, reducing the need for manual experimentation. Current methods for LLM-assisted model selection can be broadly categorized into two approaches: retrieval-based and generation-based model selection.



Figure 4: The illustration of two distinct approaches for LLM-assisted Model Selection methods.

#### 4.1.1 Retrieval-based Model Selection

The core idea of retrieval-based methods is to first construct a repository of candidate models and then use LLMs to select the most suitable models based on task and model descriptions. In AutoMMLab Yang et al. [2024], the authors construct a comprehensive model zoo, where each model is paired with a detailed model card and pre-trained weights, taking AI safety concerns into account. Each model card includes attributes such as the model's name, structure, parameters, floating point operations per second (FLOPs), inference speed, and performance metrics. An elaborate pipeline is then designed to automatically select the most appropriate model from the zoo, based on model performance and fuzzy matching scores between the model structure and the user's specified requirements.

To address the context length limitations when processing model information, several approaches have been proposed. The multimodal framework AutoM<sup>3</sup>L Luo et al. [2024] catalogues candidate models in a model zoo, utilizing LLM-powered tools like ChatPaper Luo et al. [2023] to automatically generate model cards, eliminating the need for manual documentation. Based on user directives, the system queries the top-5 models that match each input modality by comparing the text-based similarity between the embeddings of user requirements and the model card descriptions. From this refined subset, the Model Selection-LLM (MS-LLM) selects the most appropriate model. Similarly, AutoML-GPT Zhang et al. [2023d] and HuggingGPT Shen et al. [2024] employ an in-context task-model assignment mechanism to dynamically select models. This mechanism first filters models that align with the task type, then selects the top-k models based on the number of downloads, from which LLMs choose the most suitable model based on the user's query and task information provided in the prompt.

Notably, the model repositories in these approaches rely on explicit historical experience, which is critical for solving complex ML tasks but can be challenging due to the heterogeneous nature of the data (e.g., code, configurations,

logs). To address this, MLCopilot Zhang et al. [2023b] introduces a two-stage knowledge-based reasoning approach that leverages LLMs to reason and solve tasks by drawing on knowledge from past experiences. In the offline stage, MLCopilot standardizes historical data into a unified format, creating experience and knowledge pools with the aid of LLMs. In the online stage, it retrieves relevant experiences and knowledge from these pools based on a novel task description, then interacts with LLMs to generate multiple ML solutions tailored to the task.

Additionally, the Model Agent within the AutoML-Agent framework Trirat et al. [2024] performs model retrieval and hyperparameter suggestion, guided by insights provided by an Agent Manager regarding high-performing models and suitable hyperparameters for the specific ML task. Moreover, Öztürk et al. [2022] introduces a zero-shot AutoDL method that meta-learns a large pre-trained model to select the best deep learning model from candidates, conditioned on dataset meta-features.

#### 4.1.2 Generation-based Model Selection

Another class of methods leverages the powerful generative capabilities and vast ML/AI domain knowledge of LLMs. These approaches argue that relying on pre-defined models for a wide range of tasks is often impractical Hollmann et al. [2024], Xu et al. [2024], particularly given the diverse requirements and characteristics of different ML tasks, such as dataset structures, feature types, and desired output formats. To tackle this challenge, Xu et al. [2024] proposes an end-to-end ML program synthesis approach that fully automates the generation and optimization of code across the entire ML workflow. Their Contextual Modular Generation framework breaks down the workflow into smaller modules, including model selection, with each module being generated independently by LLMs. Additionally, unit testing is employed to ensure compatibility between newly generated modules and pre-written, less variable optimization modules.

Other approaches focus specifically on the generation and optimization of model parameters. For instance, Xiao et al. [2024] introduces the Verbalized Machine Learning (VML) framework, where the ML model is described and refined using natural language. In VML, the LLM's input text prompts act as the model parameters to be learned. Meanwhile, an optimizer—also parameterized by LLMs—dynamically updates the model parameters using current values, training data batches, and loss functions. This interaction between the learner and optimizer LLMs enables iterative model refinement, facilitating automatic model selection. In a similar vein, ModelGPT Tang et al. [2024] offers a framework that translates user data and descriptions into model parameters. This workflow consists of two key components: the Requirement Generator and the Model Customizer. The Requirement Generator utilizes LLMs to process user input, summarizing the task, analyzing data patterns, and condensing this information into a concise user requirement. This requirement is then processed by the Model Customizer, which determines the target model's architecture. Finally, the Model Customizer encodes the user requirement into a latent variable, which is decoded into model parameters using LoRA-assisted Hu et al. [2021] Module-Wise hypernetworks, creating a customized model ready for predictive tasks. This represents a significant step towards AGI, enabling the creation of tailored AI models with minimal data, time, and expertise.

In graph learning, GL-Agent Wei et al. [2024] illustrates another generation-based approach, focusing on neural architecture search (NAS). In this framework, LLM-based agents are responsible for configuring both the search space and the search algorithm. These agents leverage their extensive domain knowledge to select appropriate operation modules, matching them to specific learning tasks. By referencing resources like PyG documentation, the agents prepare candidate operations for each module, constructing a search space that aligns with hardware constraints—much like a human expert would. Once the search space is defined, the agent chooses a suitable neural architecture search algorithm based on summarized requirements, effectively guiding the model selection process.

While LLMs offer considerable advantages in automating the model selection process, several challenges and limitations persist. In **retrieval-based** methods, the dependence on pre-built model repositories limits flexibility, especially when addressing novel or highly specialized tasks. These methods are constrained by the models available in the repository, which may not always be suited to the task at hand. Additionally, the effectiveness of these approaches relies heavily on comprehensive, well-maintained model cards and documentation, which can be labor-intensive to curate and difficult to keep up to date. Managing the context length limitations within LLM prompts also presents a challenge, particularly when dealing with large volumes of model information, which can diminish the quality of the recommendations.

In **generation-based** methods, while LLMs offer the flexibility to create customized models, a key challenge arises from the inherent stochasticity of LLM inference. The randomness in the generation process can lead to variability in the models selected, often resulting in inconsistent or suboptimal choices. Although ModelGPT Tang et al. [2024] constrains the candidate model architectures for specific tasks, determining their hyperparameters and parameters still requires a complex and sophisticated process. Additionally, LLMs often struggle with numerical precision Yuan

et al. [2023]. Even when symbolic expressions are correctly interpreted, numerical errors during inference on specific input values can lead to fitting errors, compromising the accuracy of model selection. While LLMs are capable of generating advanced models, ensuring seamless compatibility between newly generated modules and pre-existing workflow components frequently requires manual intervention or extensive testing, diminishing the overall level of automation.

Across **both** approaches, addressing domain-specific constraints and maintaining the interpretability of selected or generated models remain significant hurdles. In addition, all LLM-driven methods face the broader risk of "hallucination," where LLMs generate plausible but incorrect models or configurations. This underscores the need for robust validation mechanisms and human oversight to ensure that the selected or generated models are both reliable and effective for their intended tasks.

## 4.2 Hyperparameter Optimization

Hyperparameter optimization (HPO), or hyperparameter tuning, is the process of selecting the optimal hyperparameters that enhance a machine learning model's performance. Hyperparameters are configuration parameters set prior to training—such as the maximum depth in decision trees or learning rates in neural networks—and are not learned during training itself. The objective of HPO is to automatically identify the hyperparameter values that maximize a model's performance on a given task Bergstra and Bengio [2012]. NAS is a specific instance of HPO, focusing on optimizing both the architecture and hyperparameters of neural networks simultaneously Jawahar et al. [2023], Zheng et al. [2023].

Traditional HPO methods like grid search, random search, and Bayesian optimization have been effective Eggensperger et al. [2021], but they are often computationally intensive and struggle to scale efficiently for large, complex models. Recently, LLMs have emerged as promising tools to enhance the efficiency and effectiveness of hyperparameter optimization by leveraging their contextual understanding and prior knowledge to propose optimized hyperparameter configurations. Based on whether actual training and testing are performed for hyperparameter settings, LLM-assisted HPO methods can be broadly categorized into two types: execution-based and prediction-based HPO.



Figure 5: The overview of two categories of LLM-assisted Hyperparameter Optimization methods.

#### 4.2.1 Execution-based HPO

Execution-based HPO refers to the process where hyperparameter settings recommended by LLMs are tested through actual training and evaluation of models on real machines. In the AutoMMLab system Yang et al. [2024], researchers introduce a "black-box" hyperparameter optimizer, called HPO-LLaMA, which is built by fine-tuning LLaMA-7B Touvron et al. [2023]. HPO-LLaMA begins by receiving a general specification of the HPO problem, alongside request-specific details about the dataset and model. Based on this, it generates an initial hyperparameter configuration tailored to the task. After training the model with this configuration, HPO-LLaMA evaluates its performance on the test data and iteratively recommends refined hyperparameter settings based on the results, thereby optimizing performance. Similarly, GENIUS Zheng et al. [2023] also operates through an iterative refinement process to maximise a given performance objective of a NAS problem by using GPT-4 as a "black box" optimiser.

To address the challenge of the vast search space in neural architecture design, Yu et al. [2023a] introduces GPT-NAS, a novel architecture search algorithm that combines a Generative Pre-Trained (GPT) model with an evolutionary algorithm (EA) as its search strategy. GPT-NAS operates on the assumption that a generative model pre-trained on a large-scale corpus can learn the underlying principles of constructing neural architectures. Leveraging this, GPT-NAS uses the GPT model to propose and reconstruct reasonable architecture components given the basic one and then utilizes EAs to search for the optimal solution. This approach significantly reduces the search space and enhances efficiency by incorporating prior knowledge and rapidly eliminating low-quality architectures during the search process. Likewise, to improve the efficiency and reduce manual intervention in EA-based NAS, Morris et al. [2024] introduces "Guided

Evolution" (GE), a novel framework that combines LLMs' human-like reasoning with the robustness of NAS through genetic algorithms. The key innovation, termed "Evolution of Thought" (EoT), allows LLMs to iteratively refine both model architectures and hyperparameters based on feedback from previous iterations. By leveraging training results, LLMs can make informed adjustments through techniques such as code segment mating and mutation, ultimately enhancing both model accuracy and efficiency.

Moreover, AutoM<sup>3</sup>L Luo et al. [2024] introduces HyperParameter Optimization-LLM (HPO-LLM), which collaborates with external tools like ray.tune to optimize hyperparameters. LLMs, leveraging their vast knowledge of machine learning training processes, first generate comprehensive descriptions for each hyperparameter in the configuration file. These descriptions, along with the original configuration, form the prompt for HPO-LLM, which then recommends optimal hyperparameter settings. The recommended hyperparameters and their corresponding search intervals are incorporated into the ray.tune search space for optimization, reducing the need for manual specification by users.

#### 4.2.2 Prediction-based HPO

Prediction-based HPO refers to methods where LLMs recommend hyperparameter settings based on predicted performance, bypassing the need for actual model training and evaluation Trirat et al. [2024]. This approach allows for faster and more resource-efficient optimization. An example of such a system is AgentHPO Liu et al. [2024a], a two-agent framework consisting of a Creator and Executor agent, which leverages LLM-powered autonomous agents to overcome the complexities of traditional AutoML methods. The Creator agent initiates the optimization process by allowing users to input task-specific details in natural language. It then interprets the input and generates initial hyperparameters, mimicking the expertise of a human specialist. The Executor agent takes the hyperparameters generated by the Creator and handles tasks like training models, recording experimental results, and conducting outcome analysis. The Creator agent further iteratively refines the hyperparameters based on the insights gleaned from the Executor's training history, streamlining the optimization process and making it more intuitive and efficient. Furthermore, AutoML-GPT Zhang et al. [2023d] predicts model performance by generating a training log for a given hyperparameter configuration based on the provided data card and model card. The system then tunes the hyperparameters by analyzing the predicted training log, which includes relevant metrics and information from the simulated training process.

Bayesian optimization (BO) is a widely-used approach for optimizing complex and costly black-box functions, especially in hyperparameter tuning Jones et al. [1998]. However, its success hinges on efficiently balancing exploration and exploitation. To address this challenge, LLAMBO Liu et al. [2024b] frames the BO problem in natural language, allowing LLMs to iteratively propose and evaluate promising solutions based on historical evaluations. LLMs can initiate the BO process via zero-shot warm-starting, sampling candidate points from regions with high potential based on past observations and the problem description, and evaluating these candidate points through a surrogate model, thus enhancing the overall efficiency of the optimization process.

In summary, Execution-based and Prediction-based HPO methods each offer distinct advantages and limitations depending on the machine learning task at hand. **Execution-based** HPO relies on actual training and evaluation, making it highly reliable in assessing the impact of hyperparameter settings on model performance. In this context, LLMs function as intelligent optimizers, utilizing their vast knowledge to propose hyperparameters that align with task requirements and real-time feedback from model training. However, this method is resource-intensive, demanding substantial computational power and time, especially when dealing with large-scale models or datasets. While execution-based approaches ensure precision, their scalability is often constrained by the complexity of the search space and the model architecture.

Conversely, **Prediction-based** HPO leverages LLMs not only to recommend hyperparameters but also to predict model performance without full training cycles for each configuration. Systems like AgentHPO Liu et al. [2024a] accelerate the process by simulating training outcomes and hyperparameter effects using LLM-generated logs or prior task knowledge, making these methods more resource-efficient and faster. However, prediction-based approaches face significant challenges related to accuracy. Relying on LLM-generated predictions can introduce biases or errors, especially for complex tasks or unfamiliar domains. While methods like LLAMBO Liu et al. [2024b] attempt to mitigate these issues by leveraging prior evaluations, predictive uncertainties can still lead to suboptimal configurations, particularly when nuanced interactions between hyperparameters are involved.

# 5 LLMs for Workflow Evaluation

After the ML model is generated, evaluating workflow performance becomes an essential step. The conventional approach is to train the model to convergence and assess its performance on a validation dataset. However, this method

can be time-consuming and computationally expensive, especially for large-scale datasets and complex workflows Lazebnik et al. [2022], Zhang et al. [2023c]. For instance, NASNet required 500 GPUs over four days, consuming 2,000 GPU hours to complete a search for the CIFAR-10 classification task Zoph et al. [2018]. Given these resource demands, LLM-driven methods have emerged as a promising way to expedite workflow evaluation. Notably, evaluation is intrinsically linked to HPO, as hyperparameter tuning frequently relies on performance metrics derived from evaluation. Consequently, there is some overlap between methods applied to both processes.

In systems like AutoML-GPT Zhang et al. [2023d], LLMs are used to predict key metrics like loss and accuracy by generating simulated training logs based on specific hyperparameter settings, data cards, and model cards. However, these predictions are based on the overall dataset, providing a coarse-grained estimation of model performance. More fine-grained evaluation is found in the VML system Xiao et al. [2024], where a learner agent, parameterized by an LLM prompt, predicts the output of individual inputs one-by-one. These predictions are compared with target outputs by an optimizer agent, enabling a more granular comparison of the model's performance across various instances.

Additionally, some approaches utilize large pre-trained models to predict workflow performance. In the optimization phase of Text-to-ML Xu et al. [2024], zero-cost (ZC) proxies Mellor et al. [2021] are incorporated to estimate the performance of candidate ML programs using at most a single forward/backward propagation pass, drastically reducing evaluation costs. Another example is TabPFN Hollmann et al. [2022], a pre-trained Transformer model designed to solve small tabular classification problems in just seconds. TabPFN is trained offline to approximate Bayesian inference on synthetic datasets generated from a prior, enabling it to efficiently process training data and generate predictions in a single forward pass.

LLMs offer several advantages in workflow evaluation. First, they significantly reduce time and computational resources by simulating training processes and predicting performance metrics without the need to run models on physical machines. This is particularly beneficial for large-scale workflows or models that would otherwise require extensive hardware resources. Additionally, LLMs can provide early-stage performance predictions based on hyperparameter settings, improving the efficiency of model selection and optimization processes. Their ability to offer fine-grained evaluation, such as predicting individual output results, further enhances the accuracy of model assessment.

However, LLM-driven workflow evaluation also comes with challenges. The generalizability of LLM predictions may be limited if the pre-training data does not align well with the specific task, leading to inaccurate performance estimates and potentially suboptimal optimization decisions. LLMs may also face difficulties with complex or large-scale workflows, where nuanced interactions between model components are harder to predict. Moreover, LLMs are susceptible to hallucinations, which can result in plausible-sounding but incorrect performance metrics, potentially undermining the reliability of evaluations.

# 6 Open Challenges and Future Directions

In addition to the many promising ways LLMs can be leveraged for constructing and optimizing ML workflows, their integration also presents certain risks. While the earlier sections focused on challenges and limitations unique to each workflow component, this section provides a broader summary of the common challenges faced throughout the entire process and proposes potential solutions to mitigate these issues. Furthermore, we outline key directions for future research aimed at enhancing the effective integration of LLMs into ML workflow construction and optimization.

# 6.1 Open Challenges

#### 6.1.1 Potential Data Leakage

One of the major concerns when integrating LLMs into ML workflows is the risk of data leakage, commonly referred to as data snooping. Since LLMs are pre-trained on vast amounts of publicly available data, including many common ML datasets, this overlap can lead to biased evaluations. LLMs may "memorize" portions of training or test datasets, resulting in inflated performance estimates during evaluation. Additionally, the pre-training data from the internet may embed biases, leading to biased outputs during various components of the ML workflow, such as feature selection Jeong et al. [2024] and feature synthesis Hollmann et al. [2024]. These biases can manifest as gender or racial disparities, potentially impacting model fairness and decision-making across ML tasks Luo et al. [2024].

To mitigate these issues, three primary solutions have been proposed. First, researchers can use datasets that were generated after the LLM's pre-training phase or private datasets that the LLM has not been exposed to Zhang et al. [2023b]. However, this solution raises challenges, such as ensuring access to realistic and publicly available datasets for fair benchmarking across different AutoML systems. Second, fine-tuning the LLM to remove knowledge of specific datasets could reduce the impact of data leakage. However, existing fine-tuning techniques are limited in their ability to

fully erase prior knowledge, and identifying diverse and inclusive fine-tuning data that encompasses various dimensions like gender, race, and culture remains challenging Tornede et al. [2023a], Luo et al. [2024]. Third, implementing robust user-involved evaluation protocols to account for potential data leakage has been proposed as a practical solution. For example, incorporating interactive post-processing steps or rule-based frameworks can help ensure that the generated results are free from harmful biases Luo et al. [2024]. Additionally, refining prompts by including diverse examples or emphasizing fairness criteria can guide the LLM in making unbiased decisions and improve the reliability of workflow outputs Hollmann et al. [2024].

## 6.1.2 Complicated Prompt Engineering

The effectiveness of LLMs heavily depends on the quality and structure of prompts, which must clearly communicate the task, data, and model requirements—a process referred to as prompt engineering Chen et al. [2023]. However, several challenges complicate this process.

First, context length limitations pose a significant challenge in LLM-based workflows. LLMs are constrained by the maximum number of tokens they can process in a single prompt, which restricts their ability to handle large datasets, complex task descriptions, and intricate ML workflows Shen et al. [2024]. For instance, in VML Xiao et al. [2024], the LLM's context window limits the dimensionality of input data and the batch size, preventing the system from processing high-dimensional data or optimizing models efficiently. While advancements in LLMs have extended token limits Islam and Moushi [2024], future work on long-context LLMs equipped with memory mechanisms and positional interpolation may further increase token capacity, enabling the seamless integration of large datasets, multiple models, and task details into a single workflow Ding et al. [2024], Wang et al. [2024].

Second, heterogeneous data and task requirements complicate prompt design. Prompts must encode not only raw data but also model configurations, optimization strategies, and evaluation metrics, which adds layers of complexity Zhang et al. [2023b], Hollmann et al. [2024]. Ensuring that these prompts produce robust and accurate outputs can be difficult, particularly in workflows with varying data types and requirements. Recent research has proposed multi-step refinement frameworks, where LLMs iteratively improve their outputs through user feedback, using techniques like reflection and multi-round dialogues to enhance the reliability of the generated results Wei et al. [2024]. Additionally, users can enhance prompt design by leveraging detailed logging mechanisms that trace LLM decision-making processes, providing transparency and insights into how LLMs select components for the workflow.

#### 6.1.3 Hallucination

Hallucination in LLMs refers to instances where the generated content deviates from either real-world facts or the user's instructions. There are two primary forms of hallucinations: factuality hallucinations and faithfulness hallucinations Huang et al. [2023], both of which pose significant risks to the integrity and reliability of ML workflow construction.

Factuality hallucinations occur when the generated content contradicts real-world facts, resulting in factual inconsistencies or fabrications. In systems like MLCopilot Zhang et al. [2023b], these hallucinations can appear when LLMs recommend incorrect or outdated models and hyperparameters, which may seem plausible but are inappropriate for the task at hand. Similarly, VML Xiao et al. [2024] demonstrates how even correct symbolic interpretations by the LLM can lead to numerical errors Yuan et al. [2023], causing inaccurate predictions during model inference. In CAAFE Hollmann et al. [2024], factuality hallucinations are evident in the feature generation process, where LLMs generate features that appear logically sound but are not grounded in the actual data distribution, resulting in distorted model performance and user misinterpretation.

On the other hand, faithfulness hallucinations occur when the generated content diverges from the user's instructions or input context, or fails to maintain self-consistency. These hallucinations can be further divided into instruction inconsistency, context inconsistency, and logical inconsistency Huang et al. [2023]. For example, in MLAgentBench Huang et al. [2024], LLM-powered agents sometimes modify ML pipelines in ways that contradict the user's original task specifications, leading to instruction inconsistencies. HuggingGPT Shen et al. [2024] probably exhibits both context and logical inconsistencies, where the outputs generated by the LLM fail to align with the task context or maintain internal logical coherence, leading to unreliable and unpredictable results.

To mitigate these hallucinations, future research should focus on integrating knowledge graphs or validated data sources to strengthen the factual grounding of LLM-generated content Pan et al. [2024], thereby reducing the likelihood of factuality hallucinations. Additionally, employing ensemble models that cross-validate LLM outputs before final recommendations can help mitigate the risks of factual fabrications. To address faithfulness hallucinations, incorporating contextual validation mechanisms can ensure that LLM-generated outputs remain consistent with user instructions and input contexts. Finally, RLHF technique could be employed to iteratively fine-tune LLM responses, improving alignment with user expectations and reducing inconsistencies. By implementing these solutions, the reliability and

trustworthiness of LLM-driven ML workflows could be significantly enhanced, especially in critical applications where hallucinations could have serious consequences. Overall, it is crucial to anticipate the possibility of erroneous outputs when integrating LLMs into ML workflow construction and optimization, and to develop probabilistic methods to effectively detect and mitigate these risks.

#### 6.1.4 Interpretability

Interpretability is a vital aspect of ML workflows, especially those involving complex models or automated systems like AutoML Drozdal et al. [2020]. Ensuring that both experts and non-experts can understand how decisions are made by systems is crucial for building trust, improving decision-making, and maintaining accountability. Many current systems address this need by providing transparency through logging and tracing, as seen in Text-to-ML Xu et al. [2024], where prompts and responses are recorded to help users trace decisions. Similarly, AgentHPO Liu et al. [2024a] enhances interpretability by logging experimental results and hyperparameter adjustments, allowing users to track model evolution and performance.

Despite these improvements, significant challenges remain in ensuring interpretability for LLM-driven workflows. Over-reliance on textual explanations, for example, can create a false sense of security among users, particularly those less familiar with ML intricacies. Users might assume the model is fully optimized when, in reality, it may make implicit assumptions or overlook ambiguities in the input data or task description. Additionally, the opaque nature of LLMs, which rely on vast pre-trained knowledge, can make it difficult to fully understand the rationale behind certain model or hyperparameter recommendations, thereby reducing transparency Xu et al. [2024].

To address these challenges, future research should focus on integrating explainable AI (XAI) techniques into LLMdriven workflows. XAI methods Hoffman et al. [2018] could offer deeper insights by complementing textual explanations with visual tools, causal diagrams, or interactive features that highlight how specific features or parameters affect model performance. Furthermore, incorporating human-in-the-loop mechanisms Hollmann et al. [2024], Lindauer et al. [2024] would ensure that users are not merely passive recipients of information but actively engaged in confirming the validity and appropriateness of the system's decisions.

#### 6.1.5 Resource Consumption

While LLM-driven ML workflows offer substantial potential for automation and optimization, they also introduce significant challenges in terms of resource consumption. The computational demands of LLMs, particularly during inference, can be considerably higher than those of traditional machine learning methods. Although some studies suggest that the resource impact during certain workflow phases is minimal Luo et al. [2024], the overall costs in terms of human labor, time, money, and computational power remain considerable.

For example, LLAMBO Liu et al. [2024b] shows that even without fine-tuning, LLM inference incurs a significantly larger computational footprint compared to traditional Bayesian Optimization (BO) algorithms. Similarly, AutoM3L Luo et al. [2024] highlights that while LLMs are primarily utilized during the setup phase of an ML pipeline, the bulk of computational resources are consumed during the actual training phase. Though the cost introduced by LLMs during setup may seem minimal, these costs accumulate across the entire pipeline, particularly due to real-time API calls and the need for scalable infrastructure to support continuous operations.

Addressing these challenges requires future research to focus on improving the computational efficiency of LLM-driven workflows. One potential direction is the development of lightweight LLM architectures specifically tailored for ML tasks, reducing the computational load without sacrificing performance. Additionally, hybrid models that combine the strengths of traditional algorithms with LLMs, as demonstrated by LLAMBO's fusion with more efficient methods, could further enhance resource efficiency. Finally, optimizing the orchestration of LLM interactions, as suggested by HuggingGPT Shen et al. [2024], can reduce redundant steps, cut down on processing time, and improve real-time performance. Embracing these strategies, in line with the principles of Green AutoML Tornede et al. [2023b], will be essential to ensure that the advantages of LLM-driven workflows are realized without imposing excessive resource demands.

#### 6.1.6 Social Impact

The integration of LLM-driven ML workflows offers numerous societal benefits but also raises significant concerns, particularly regarding the displacement of human labor and ethical considerations. On the positive side, LLM-based workflows have the potential to democratize ML by reducing the level of expertise required to develop and deploy models. Tools like Text-to-ML Xu et al. [2024] and AutoMMLab Yang et al. [2024] automate many ML tasks, making the technology accessible to a broader audience. This democratization can empower individuals and organizations

previously excluded from the field due to resource constraints or lack of specialized knowledge, fostering innovation across various domains.

However, this automation also presents challenges. One of the key concerns is the potential displacement of human workers. As systems become more autonomous and capable of managing complex ML tasks, there is a risk that they could diminish or replace roles traditionally held by data scientists, engineers, and researchers. This shift could have significant implications for employment within the field of ML and beyond Huang et al. [2024]. For instance, CAAFE Hollmann et al. [2024] illustrates how automating routine data science tasks could lead to a reduction in the demand for manual labor, potentially displacing workers in data-centric industries. Nevertheless, it also emphasizes that such automation could free up human professionals to focus on more strategic decision-making, enhancing their productivity. Moving forward, developing frameworks where AI augments rather than replaces human labor could mitigate these concerns by encouraging a human-in-the-loop approach to maintain human oversight and creativity Huang et al. [2024].

Ethical considerations are another critical issue. LLMs, especially in highly automated workflows, could generate unethical, biased, or even harmful outputs when exposed to biased training data or malicious user input. For example, MLCopilot Zhang et al. [2023b] warns that while LLMs operate within user-defined boundaries, when applied in more complex or less-constrained scenarios, there is a risk of generating unpredictable or unethical outcomes. AutoMMLab also acknowledges the potential for LLM-generated models to produce toxic or offensive content, particularly when exposed to harmful inputs Yang et al. [2024]. To mitigate these risks, future research should focus on developing mechanisms for continuous monitoring of LLM outputs, ethical auditing frameworks, and incorporating fairness and bias mitigation techniques at every stage of the workflow. Moreover, impact assessments should be conducted before deploying these systems in sensitive applications, ensuring that both ethical standards and societal impacts are properly considered Xu et al. [2024].

#### 6.2 Future Directions

Building on the challenges and opportunities discussed, future research directions present exciting possibilities for advancing LLM-driven ML workflows.

One promising direction is the development of **end-to-end ML workflow construction using LLMs**, where LLMs autonomously handle every stage of the ML pipeline—from data preprocessing to model evaluation—creating fully automated workflows. The goal is to further reduce human intervention, enabling seamless construction, optimization, and deployment of ML models. Some existing agent-based methods, such as AIDE Schmidt et al. [2024], ResearchAgent Huang et al. [2024], CodeActAgent Wang et al. [2024e,f], and DS-Agent Guo et al. [2024], already offer implicit stage-wise solutions for end-to-end ML workflow generation. These approaches leverage the generative capabilities of LLMs to produce solution drafts and iteratively refine them based on performance feedback and interactions with the environment. However, this process often lacks transparency, making it difficult for users to personalize or modify individual workflow components. In contrast, explicit end-to-end ML workflow generation could provide a complete ML solution while allowing users to control and customize each component.

Another promising direction involves **integrating LLMs with specialized models** to enhance workflow generation. Instead of relying solely on LLMs to handle the entire process, hybrid systems can capitalize on the strengths of LLMs for tasks such as data preprocessing and feature selection, while leveraging domain-specific models for more specialized functions like hyperparameter optimization or model evaluation. This hybrid approach combines the flexibility and broad capabilities of general large models with the efficiency and domain expertise of tailored small models, leading to more robust and scalable ML workflows that can adapt to diverse tasks and requirements.

# 7 Conclusion

This paper provides a detailed and systematic review of how LLMs contribute to constructing and optimizing ML workflows across different stages of the ML pipeline (Fig. 1). From data and feature engineering to model selection and hyperparameter optimization, and workflow evaluation, LLMs bring diverse capabilities that can streamline and enhance various steps in the workflow. Despite the significant advancements LLMs have made in automating and improving ML workflows, many challenges remain, and we are still in the early stages of addressing these complexities. This review not only highlights the current achievements but also outlines several open problems and suggests important future research directions.

The potential of LLMs to revolutionize ML workflows is immense, and with continued research and collaboration within the community, the existing challenges can be overcome. We are confident that the innovations and opportunities provided by LLMs will lead to breakthroughs that transform the development and application of ML/AI. By offering

a comprehensive understanding of the role of LLMs in ML workflows, this review will be a valuable resource for researchers and practitioners entering this evolving field, guiding future advancements and fostering continued progress.

#### References

- Doris Xin, Eva Yiwei Wu, Doris Jung-Lin Lee, Niloufar Salehi, and Aditya Parameswaran. Whither automl? understanding the role of automation in machine learning workflows. In *Proceedings of the 2021 CHI Conference on Human Factors in Computing Systems*, pages 1–16, 2021.
- Nikolay O Nikitin, Pavel Vychuzhanin, Mikhail Sarafanov, Iana S Polonskaia, Ilia Revin, Irina V Barabanova, Gleb Maximov, Anna V Kalyuzhnaya, and Alexander Boukhanovsky. Automated evolutionary approach for the design of composite machine learning pipelines. *Future Generation Computer Systems*, 127:109–125, 2022.
- Francisco Villarroel Ordenes and Rosaria Silipo. Machine learning for marketing on the KNIME Hub: The development of a live repository for marketing applications. *Journal of Business Research*, 137:393–410, 2021.
- Noah Hollmann, Samuel Müller, and Frank Hutter. Large language models for automated data science: Introducing caafe for context-aware automated feature engineering. *Advances in Neural Information Processing Systems*, 36, 2024.
- Bailin Wang, Zi Wang, Xuezhi Wang, Yuan Cao, Rif A Saurous, and Yoon Kim. Grammar prompting for domainspecific language generation with large language models. *Advances in Neural Information Processing Systems*, 36, 2024a.
- Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia Leoni Aleman, Diogo Almeida, Janko Altenschmidt, Sam Altman, Shyamal Anadkat, et al. Gpt-4 technical report. arXiv preprint arXiv:2303.08774, 2023.
- Hugo Touvron, Thibaut Lavril, Gautier Izacard, Xavier Martinet, Marie-Anne Lachaux, Timothée Lacroix, Baptiste Rozière, Naman Goyal, Eric Hambro, Faisal Azhar, et al. Llama: Open and efficient foundation language models. *arXiv preprint arXiv:2302.13971*, 2023.
- Wenbo Hu, Yifan Xu, Yi Li, Weiyue Li, Zeyuan Chen, and Zhuowen Tu. Bliva: A simple multimodal llm for better handling of text-rich visual questions. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 38, pages 2256–2264, 2024.
- Yan Tai, Weichen Fan, Zhao Zhang, and Ziwei Liu. Link-context learning for multimodal llms. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, pages 27176–27185, 2024.
- Daqin Luo, Chengjian Feng, Yuxuan Nong, and Yiqing Shen. AutoM3L: An Automated Multimodal Machine Learning Framework with Large Language Models. *arXiv preprint arXiv:2408.00665*, 2024.
- Yang Gu, Jian Cao, Yuan Guo, Shiyou Qian, and Wei Guan. Plan, Generate and Match: Scientific Workflow Recommendation with Large Language Models. In *International Conference on Service-Oriented Computing*, pages 86–102. Springer, 2023.
- Nataliia Klievtsova, Janik-Vasily Benzin, Timotheus Kampik, Juergen Mangler, and Stefanie Rinderle-Ma. Conversational process modelling: state of the art, applications, and implications in practice. In *International Conference on Business Process Management*, pages 319–336. Springer, 2023.
- Zhuosheng Zhang, Aston Zhang, Mu Li, Hai Zhao, George Karypis, and Alex Smola. Multimodal chain-of-thought reasoning in language models. arXiv preprint arXiv:2302.00923, 2023a.
- Tim Z Xiao, Robert Bamler, Bernhard Schölkopf, and Weiyang Liu. Verbalized Machine Learning: Revisiting Machine Learning with Language Models. *arXiv preprint arXiv:2406.04344*, 2024.
- Sirui Hong, Yizhang Lin, Bangbang Liu, Binhao Wu, Danyang Li, Jiaqi Chen, Jiayi Zhang, Jinlin Wang, Lingyao Zhang, Mingchen Zhuge, et al. Data interpreter: An LLM agent for data science. *arXiv preprint arXiv:2402.18679*, 2024.
- Tijl De Bie, Luc De Raedt, José Hernández-Orallo, Holger H Hoos, Padhraic Smyth, and Christopher KI Williams. Automating data science. *Communications of the ACM*, 65(3):76–87, 2022.
- Teddy Lazebnik, Amit Somech, and Abraham Itzhak Weinberg. Substrat: A subset-based optimization strategy for faster automl. *Proceedings of the VLDB Endowment*, 16(4):772–780, 2022.
- Frank Hutter, Lars Kotthoff, and Joaquin Vanschoren. Automated machine learning: methods, systems, challenges. Springer Nature, 2019.

- Sohyun An, Hayeon Lee, Jaehyeong Jo, Seanie Lee, and Sung Ju Hwang. DiffusionNAG: Predictor-guided Neural Architecture Generation with Diffusion Models. In *The Twelfth International Conference on Learning Representations*, 2023.
- Randal S Olson and Jason H Moore. TPOT: A tree-based pipeline optimization tool for automating machine learning. In *Workshop on automatic machine learning*, pages 66–74. PMLR, 2016.
- Matthias Feurer, Katharina Eggensperger, Stefan Falkner, Marius Lindauer, and Frank Hutter. Auto-sklearn 2.0: Hands-free automl via meta-learning. *Journal of Machine Learning Research*, 23(261):1–61, 2022.
- Ripon K Saha, Akira Ura, Sonal Mahajan, Chenguang Zhu, Linyi Li, Yang Hu, Hiroaki Yoshida, Sarfraz Khurshid, and Mukul R Prasad. SapientML: synthesizing machine learning pipelines by learning from human-writen solutions. In *Proceedings of the 44th International Conference on Software Engineering*, pages 1932–1944, 2022.
- Vraj Shah, Jonathan Lacanlale, Premanand Kumar, Kevin Yang, and Arun Kumar. Towards benchmarking feature type inference for automl platforms. In *Proceedings of the 2021 international conference on management of data*, pages 1584–1596, 2021.
- Lei Zhang, Yuge Zhang, Kan Ren, Dongsheng Li, and Yuqing Yang. Mlcopilot: Unleashing the power of large language models in solving machine learning tasks. *arXiv preprint arXiv:2304.14979*, 2023b.
- Michael R Zhang, Nishkrit Desai, Juhan Bae, Jonathan Lorraine, and Jimmy Ba. Using large language models for hyperparameter optimization. In *NeurIPS 2023 Foundation Models for Decision Making Workshop*, 2023c.
- Siyi Liu, Chen Gao, and Yong Li. Large Language Model Agent for Hyper-Parameter Optimization. *arXiv preprint* arXiv:2402.01881, 2024a.
- Emily Judith Arteaga Garcia, João Felipe Nicolaci Pimentel, Zixuan Feng, Marco Gerosa, Igor Steinmacher, and Anita Sarma. How to support ml end-user programmers through a conversational agent. In *Proceedings of the 46th IEEE/ACM International Conference on Software Engineering*, pages 1–12, 2024.
- Siyuan Guo, Cheng Deng, Ying Wen, Hechang Chen, Yi Chang, and Jun Wang. DS-Agent: Automated Data Science by Empowering Large Language Models with Case-Based Reasoning. *arXiv preprint arXiv:2402.17453*, 2024.
- Arghavan Moradi Dakhel, Vahid Majdinasab, Amin Nikanjam, Foutse Khomh, Michel C Desmarais, and Zhen Ming Jack Jiang. Github copilot ai pair programmer: Asset or liability? *Journal of Systems and Software*, 203: 111734, 2023.
- Xinhao Zhang, Jinghan Zhang, Banafsheh Rekabdar, Yuanchun Zhou, Pengfei Wang, and Kunpeng Liu. Dynamic and Adaptive Feature Generation with LLM. *arXiv preprint arXiv:2406.03505*, 2024a.
- Jaehyun Nam, Kyuyoung Kim, Seunghyuk Oh, Jihoon Tack, Jaehyung Kim, and Jinwoo Shin. Optimized Feature Generation for Tabular Data via LLMs with Decision Tree Reasoning. *arXiv preprint arXiv:2406.08527*, 2024.
- Rishi Bommasani, Drew A Hudson, Ehsan Adeli, Russ Altman, Simran Arora, Sydney von Arx, Michael S Bernstein, Jeannette Bohg, Antoine Bosselut, Emma Brunskill, et al. On the opportunities and risks of foundation models. *arXiv* preprint arXiv:2108.07258, 2021.
- Yifan Yao, Jinhao Duan, Kaidi Xu, Yuanfang Cai, Zhibo Sun, and Yue Zhang. A survey on large language model (llm) security and privacy: The good, the bad, and the ugly. *High-Confidence Computing*, page 100211, 2024a.
- Dominik Schmidt, Zhengyao Jiang, and Yuxiang Wu. Introducing Weco AIDE, April 2024. URL https://www.weco.ai/blog/technical-report.
- Jun Shern Chan, Neil Chowdhury, Oliver Jaffe, James Aung, Dane Sherburn, Evan Mays, Giulio Starace, Kevin Liu, Leon Maksin, Tejal Patwardhan, et al. Mle-bench: Evaluating machine learning agents on machine learning engineering. arXiv preprint arXiv:2410.07095, 2024.
- Qian Huang, Jian Vora, Percy Liang, and Jure Leskovec. MLAgentBench: Evaluating Language Agents on Machine Learning Experimentation. In *Forty-first International Conference on Machine Learning*, 2024.
- Alexander Tornede, Difan Deng, Theresa Eimer, Joseph Giovanelli, Aditya Mohan, Tim Ruhkopf, Sarah Segel, Daphne Theodorakopoulos, Tanja Tornede, Henning Wachsmuth, et al. Automl in the age of large language models: Current challenges, future opportunities and risks. arXiv preprint arXiv:2306.08107, 2023a.
- Kristy Choi, Chris Cundy, Sanjari Srivastava, and Stefano Ermon. LMPriors: Pre-Trained Language Models as Task-Specific Priors. In *NeurIPS 2022 Foundation Models for Decision Making Workshop*, 2022.
- Ekrem Öztürk, Fabio Ferreira, Hadi Jomaa, Lars Schmidt-Thieme, Josif Grabocka, and Frank Hutter. Zero-shot AutoML with pretrained models. In *International Conference on Machine Learning*, pages 17138–17155. PMLR, 2022.
- Md Mahadi Hassan, Alex Knipper, and Shubhra Kanti Karmaker Santu. Chatgpt as your personal data scientist. *arXiv* preprint arXiv:2305.13657, 2023.

- Shang-Ching Liu, ShengKun Wang, Tsungyao Chang, Wenqi Lin, Chung-Wei Hsiung, Yi-Chen Hsieh, Yu-Ping Cheng, Sian-Hong Luo, and Jianwei Zhang. JarviX: A LLM no code platform for tabular data analysis and optimization. In Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing: Industry Track, pages 622–630, 2023.
- Hyunjun Choi, Jay Moran, Nicholas Matsumoto, Miguel E Hernandez, and Jason H Moore. Aliro: an automated machine learning tool leveraging large language models. *Bioinformatics*, 39(10):btad606, 2023.
- Shujian Zhang, Chengyue Gong, Lemeng Wu, Xingchao Liu, and Mingyuan Zhou. Automl-gpt: Automatic machine learning with gpt. *arXiv preprint arXiv:2305.02499*, 2023d.
- Mingkai Zheng, Xiu Su, Shan You, Fei Wang, Chen Qian, Chang Xu, and Samuel Albanie. Can gpt-4 perform neural architecture search? *arXiv preprint arXiv:2304.10970*, 2023.
- Caiyang Yu, Xianggen Liu, Wentao Feng, Chenwei Tang, and Jiancheng Lv. GPT-NAS: Evolutionary neural architecture search with the generative pre-trained model. *arXiv preprint arXiv:2305.05351*, 2023a.
- Zekang Yang, Wang Zeng, Sheng Jin, Chen Qian, Ping Luo, and Wentao Liu. AutoMMLab: Automatically Generating Deployable Models from Language Instructions for Computer Vision Tasks. arXiv preprint arXiv:2402.15351, 2024.
- Patara Trirat, Wonyong Jeong, and Sung Ju Hwang. AutoML-Agent: A Multi-Agent LLM Framework for Full-Pipeline AutoML. arXiv preprint arXiv:2410.02958, 2024.
- Jinglue Xu, Zhen Liu, Nagar Anthel Venkatesh Suryanarayanan, and Hitoshi Iba. Large Language Models Synergize with Automated Machine Learning. *arXiv preprint arXiv:2405.03727*, 2024.
- Daniel P Jeong, Zachary C Lipton, and Pradeep Ravikumar. LLM-Select: Feature Selection with Large Language Models. arXiv preprint arXiv:2407.02694, 2024.
- Lanning Wei, Huan Zhao, Xiaohan Zheng, Zhiqiang He, and Quanming Yao. A Versatile Graph Learning Approach through LLM-based Agent, 2024. URL https://arxiv.org/abs/2309.04565.
- Yongliang Shen, Kaitao Song, Xu Tan, Dongsheng Li, Weiming Lu, and Yueting Zhuang. Hugginggpt: Solving ai tasks with chatgpt and its friends in hugging face. *Advances in Neural Information Processing Systems*, 36, 2024.
- Zihao Tang, Zheqi Lv, Shengyu Zhang, Fei Wu, and Kun Kuang. ModelGPT: Unleashing LLM's Capabilities for Tailored Model Generation. *arXiv preprint arXiv:2402.12408*, 2024.
- Clint Morris, Michael Jurado, and Jason Zutty. Llm guided evolution-the automation of models advancing models. In *Proceedings of the Genetic and Evolutionary Computation Conference*, pages 377–384, 2024.
- Tennison Liu, Nicolás Astorga, Nabeel Seedat, and Mihaela van der Schaar. Large Language Models to Enhance Bayesian Optimization, 2024b. URL https://arxiv.org/abs/2402.03921.
- Greg Allen. Understanding AI technology. *Joint Artificial Intelligence Center (JAIC) The Pentagon United States*, 2(1): 24–32, 2020.
- Zhi-Hua Zhou. Machine learning. Springer nature, 2021.
- Yann LeCun, Yoshua Bengio, and Geoffrey Hinton. Deep learning. nature, 521(7553):436-444, 2015.
- Yeounoh Chung, Peter J Haas, Eli Upfal, and Tim Kraska. Unknown examples & machine learning model generalization. arXiv preprint arXiv:1808.08294, 2018.
- Bentley James Oakes, Michalis Famelis, and Houari Sahraoui. Building Domain-Specific Machine Learning Workflows: A Conceptual Framework for the State of the Practice. *ACM Transactions on Software Engineering and Methodology*, 33(4):1–50, 2024.
- David Harrison Jr and Daniel L Rubinfeld. Hedonic housing prices and the demand for clean air. Journal of environmental economics and management, 5(1):81–102, 1978.
- A Vaswani. Attention is all you need. Advances in Neural Information Processing Systems, 2017.
- Rohan Anil, Andrew M Dai, Orhan Firat, Melvin Johnson, Dmitry Lepikhin, Alexandre Passos, Siamak Shakeri, Emanuel Taropa, Paige Bailey, Zhifeng Chen, et al. Palm 2 technical report. arXiv preprint arXiv:2305.10403, 2023.
- Shervin Minaee, Tomas Mikolov, Narjes Nikzad, Meysam Chenaghlu, Richard Socher, Xavier Amatriain, and Jianfeng Gao. Large language models: A survey. *arXiv preprint arXiv:2402.06196*, 2024.
- Shuang Yu, Tao Huang, Mingyi Liu, and Zhongjie Wang. Bear: Revolutionizing service domain knowledge graph construction with llm. In *International Conference on Service-Oriented Computing*, pages 339–346. Springer, 2023b.
- Wayne Xin Zhao, Kun Zhou, Junyi Li, Tianyi Tang, Xiaolei Wang, Yupeng Hou, Yingqian Min, Beichen Zhang, Junjie Zhang, Zican Dong, et al. A survey of large language models. *arXiv preprint arXiv:2303.18223*, 2023.

- Lei Wang, Chen Ma, Xueyang Feng, Zeyu Zhang, Hao Yang, Jingsen Zhang, Zhiyuan Chen, Jiakai Tang, Xu Chen, Yankai Lin, et al. A survey on large language model based autonomous agents. *Frontiers of Computer Science*, 18(6): 186345, 2024b.
- Pranab Sahoo, Ayush Kumar Singh, Sriparna Saha, Vinija Jain, Samrat Mondal, and Aman Chadha. A systematic survey of prompt engineering in large language models: Techniques and applications. *arXiv preprint arXiv:2402.07927*, 2024.
- Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Ed Chi, Quoc Le, and Denny Zhou. Chain of thought prompting elicits reasoning in large language models. *arXiv preprint arXiv:2201.11903*, 2022.
- Shunyu Yao, Dian Yu, Jeffrey Zhao, Izhak Shafran, Tom Griffiths, Yuan Cao, and Karthik Narasimhan. Tree of thoughts: Deliberate problem solving with large language models. *Advances in Neural Information Processing Systems*, 36, 2024b.
- Maciej Besta, Nils Blach, Ales Kubicek, Robert Gerstenberger, Michal Podstawski, Lukas Gianinazzi, Joanna Gajda, Tomasz Lehmann, Hubert Niewiadomski, Piotr Nyczyk, et al. Graph of thoughts: Solving elaborate problems with large language models. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 38, pages 17682–17690, 2024.
- Yuchen Zhuang, Yue Yu, Kuan Wang, Haotian Sun, and Chao Zhang. Toolqa: A dataset for llm question answering with external tools. *Advances in Neural Information Processing Systems*, 36, 2024.
- Wenqi Fan, Yujuan Ding, Liangbo Ning, Shijie Wang, Hengyun Li, Dawei Yin, Tat-Seng Chua, and Qing Li. A Survey on RAG Meeting LLMs: Towards Retrieval-Augmented Large Language Models. In *Proceedings of the 30th ACM* SIGKDD Conference on Knowledge Discovery and Data Mining, pages 6491–6501, 2024.
- Zhiheng Xi, Wenxiang Chen, Xin Guo, Wei He, Yiwen Ding, Boyang Hong, Ming Zhang, Junzhe Wang, Senjie Jin, Enyu Zhou, et al. The rise and potential of large language model based agents: A survey. *arXiv preprint arXiv:2309.07864*, 2023.
- Andrew Zhao, Daniel Huang, Quentin Xu, Matthieu Lin, Yong-Jin Liu, and Gao Huang. Expel: Llm agents are experiential learners. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 38, pages 19632– 19642, 2024.
- Zhichao Wang, Bin Bi, Shiva Kumar Pentyala, Kiran Ramnath, Sougata Chaudhuri, Shubham Mehrotra, Xiang-Bo Mao, Sitaram Asur, et al. A Comprehensive Survey of LLM Alignment Techniques: RLHF, RLAIF, PPO, DPO and More. *arXiv preprint arXiv:2407.16216*, 2024c.
- Hengrui Zhang, August Ning, Rohan Baskar Prabhakar, and David Wentzlaff. LLMCompass: Enabling Efficient Hardware Design for Large Language Model Inference. In 2024 ACM/IEEE 51st Annual International Symposium on Computer Architecture (ISCA), pages 1080–1096. IEEE, 2024b.
- Guangji Bai, Zheng Chai, Chen Ling, Shiyu Wang, Jiaying Lu, Nan Zhang, Tingwei Shi, Ziyang Yu, Mengdan Zhu, Yifei Zhang, et al. Beyond efficiency: A systematic survey of resource-efficient large language models. *arXiv* preprint arXiv:2401.00625, 2024.
- Junyi Li, Jie Chen, Ruiyang Ren, Xiaoxue Cheng, Wayne Xin Zhao, Jian-Yun Nie, and Ji-Rong Wen. The dawn after the dark: An empirical study on factuality hallucination in large language models. *arXiv preprint arXiv:2401.03205*, 2024.
- Florian Leiser, Sven Eckhardt, Valentin Leuthe, Merlin Knaeble, Alexander Maedche, Gerhard Schwabe, and Ali Sunyaev. Hill: A hallucination identifier for large language models. In *Proceedings of the CHI Conference on Human Factors in Computing Systems*, pages 1–13, 2024.
- Jiaye Wang. Guiding Large Language Models to Generate Computer-Parsable Content. CoRR, 2024.
- Nate Gruver, Marc Finzi, Shikai Qiu, and Andrew G Wilson. Large language models are zero-shot time series forecasters. Advances in Neural Information Processing Systems, 36, 2024.
- Carlos Vladimiro González Zelaya. Towards explaining the effects of data preprocessing on machine learning. In 2019 IEEE 35th international conference on data engineering (ICDE), pages 2086–2090. IEEE, 2019.
- Anubha Parashar, Apoorva Parashar, Weiping Ding, Mohammad Shabaz, and Imad Rida. Data preprocessing and feature selection techniques in gait recognition: A comparative study of machine learning and deep learning approaches. *Pattern Recognition Letters*, 172:65–73, 2023.
- Xin He, Kaiyong Zhao, and Xiaowen Chu. AutoML: A survey of the state-of-the-art. *Knowledge-based systems*, 212: 106622, 2021.
- Xuanhe Zhou, Xinyang Zhao, and Guoliang Li. LLM-Enhanced Data Management. *arXiv preprint arXiv:2402.02643*, 2024.

- Jufeng Yang, Xiaoxiao Sun, Yu-Kun Lai, Liang Zheng, and Ming-Ming Cheng. Recognition from web data: A progressive filtering approach. *IEEE Transactions on Image Processing*, 27(11):5303–5315, 2018.
- MZH Jesmeen, J Hossen, S Sayeed, CK Ho, K Tawsif, Armanur Rahman, and E Arif. A survey on cleaning dirty data using machine learning paradigm for big data analytics. *Indones. J. Electr. Eng. Comput. Sci*, 10(3):1234–1243, 2018.
- Shubha Guha, Falaah Arif Khan, Julia Stoyanovich, and Sebastian Schelter. Automated data cleaning can hurt fairness in machine learning-based decision making. *IEEE Transactions on Knowledge and Data Engineering*, 2024.
- Felix Neutatz, Binger Chen, Yazan Alkhatib, Jingwen Ye, and Ziawasch Abedjan. Data Cleaning and AutoML: Would an optimizer choose to clean? *Datenbank-Spektrum*, 22(2):121–130, 2022.
- Jiahui Gao, Renjie Pi, Lin Yong, Hang Xu, Jiacheng Ye, Zhiyong Wu, Weizhong Zhang, Xiaodan Liang, Zhenguo Li, and Lingpeng Kong. Self-Guided Noise-Free Data Generation for Efficient Zero-Shot Learning. In International Conference on Learning Representations (ICLR 2023), 2023.
- Yue Yu, Yuchen Zhuang, Jieyu Zhang, Yu Meng, Alexander J Ratner, Ranjay Krishna, Jiaming Shen, and Chao Zhang. Large language model as attributed training data generator: A tale of diversity and bias. *Advances in Neural Information Processing Systems*, 36, 2024.
- Tianyuan Zou, Yang Liu, Peng Li, Jianqing Zhang, Jingjing Liu, and Ya-Qin Zhang. FuseGen: PLM Fusion for Data-generation based Zero-shot Learning. *arXiv preprint arXiv:2406.12527*, 2024.
- Bo Adler, Niket Agarwal, Ashwath Aithal, Dong H Anh, Pallab Bhattacharya, Annika Brundyn, Jared Casper, Bryan Catanzaro, Sharon Clay, Jonathan Cohen, et al. Nemotron-4 340B Technical Report. *arXiv preprint arXiv:2406.11704*, 2024.
- Zijie Geng, Xijun Li, Jie Wang, Xiao Li, Yongdong Zhang, and Feng Wu. A deep instance generative framework for milp solvers under limited data availability. *Advances in Neural Information Processing Systems*, 36:26025–26047, 2023.
- Zinan Lin, Sivakanth Gopi, Janardhan Kulkarni, Harsha Nori, and Sergey Yekhanin. Differentially private synthetic data via foundation model apis 1: Images. *arXiv preprint arXiv:2305.15560*, 2023.
- Chulin Xie, Zinan Lin, Arturs Backurs, Sivakanth Gopi, Da Yu, Huseyin A Inan, Harsha Nori, Haotian Jiang, Huishuai Zhang, Yin Tat Lee, et al. Differentially private synthetic data via foundation model apis 2: Text. *arXiv preprint arXiv:2403.01749*, 2024.
- Yoshua Bengio, Aaron Courville, and Pascal Vincent. Representation learning: A review and new perspectives. *IEEE transactions on pattern analysis and machine intelligence*, 35(8):1798–1828, 2013.
- Alhassan Mumuni and Fuseini Mumuni. Automated data processing and feature engineering for deep learning and big data applications: a survey. *Journal of Information and Intelligence*, 2024.
- Isabel O Gallegos, Ryan A Rossi, Joe Barrow, Md Mehrab Tanjim, Sungchul Kim, Franck Dernoncourt, Tong Yu, Ruiyi Zhang, and Nesreen K Ahmed. Bias and fairness in large language models: A survey. *Computational Linguistics*, pages 1–79, 2024.
- Andrzej Maćkiewicz and Waldemar Ratajczak. Principal components analysis (PCA). *Computers & Geosciences*, 19 (3):303–342, 1993.
- Petros Xanthopoulos, Panos M Pardalos, Theodore B Trafalis, Petros Xanthopoulos, Panos M Pardalos, and Theodore B Trafalis. Linear discriminant analysis. *Robust data mining*, pages 27–33, 2013.
- Geoffrey E Hinton and Ruslan R Salakhutdinov. Reducing the dimensionality of data with neural networks. *science*, 313(5786):504–507, 2006.
- Haleh Vafaie and Kenneth De Jong. Evolutionary feature space transformation. In *Feature Extraction, Construction and Selection: a data mining perspective*, pages 307–323. Springer, 1998.
- Jianyu Zhang, Jianye Hao, Françoise Fogelman-Soulié, and Zan Wang. Automatic feature engineering by deep reinforcement learning. In *Proceedings of the 18th International Conference on Autonomous Agents and MultiAgent Systems*, pages 2312–2314, 2019.
- Marius Lindauer, Florian Karl, Anne Klier, Julia Moosbauer, Alexander Tornede, Andreas C Mueller, Frank Hutter, Matthias Feurer, and Bernd Bischl. Position: A call to action for a human-centered AutoML paradigm. In Ruslan Salakhutdinov, Zico Kolter, Katherine Heller, Adrian Weller, Nuria Oliver, Jonathan Scarlett, and Felix Berkenkamp, editors, *Proceedings of the 41st International Conference on Machine Learning*, volume 235 of *Proceedings of Machine Learning Research*, pages 30566–30584. PMLR, 21–27 Jul 2024. URL https://proceedings.mlr. press/v235/lindauer24a.html.

- Chengrun Yang, Yuji Akimoto, Dae Won Kim, and Madeleine Udell. OBOE: Collaborative filtering for AutoML model selection. In *Proceedings of the 25th ACM SIGKDD international conference on knowledge discovery & data mining*, pages 1173–1183, 2019.
- Amala Mary Vincent and P Jidesh. An improved hyperparameter optimization framework for AutoML systems using evolutionary algorithms. *Scientific Reports*, 13(1):4737, 2023.
- Chris Thornton, Frank Hutter, Holger H Hoos, and Kevin Leyton-Brown. Auto-WEKA: Combined selection and hyperparameter optimization of classification algorithms. In *Proceedings of the 19th ACM SIGKDD international conference on Knowledge discovery and data mining*, pages 847–855, 2013.
- J. Ross Quinlan. Induction of decision trees. Machine learning, 1:81-106, 1986.
- Irina Rish et al. An empirical study of the naive Bayes classifier. In *IJCAI 2001 workshop on empirical methods in artificial intelligence*, volume 3, pages 41–46. Citeseer, 2001.
- Yann LeCun, Léon Bottou, Yoshua Bengio, and Patrick Haffner. Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, 86(11):2278–2324, 1998.
- S Hochreiter. Long Short-term Memory. Neural Computation MIT-Press, 1997.
- Marius Lindauer, Holger H Hoos, Frank Hutter, and Torsten Schaub. Autofolio: Algorithm configuration for algorithm selection. In Workshops at the Twenty-Ninth AAAI Conference on Artificial Intelligence, 2015.
- Yongle Luo, Rongsheng Wang, Peter Gam, Jiaxi Cui, circlestarzero, Shiwen Ni, Jaseon Quanta, Qingxu Fu, and Siyuan Hou. ChatPaper: Use LLM to summarize papers. https://github.com/kaixindelele/ChatPaper, 2023.
- Edward J Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. Lora: Low-rank adaptation of large language models. *arXiv preprint arXiv:2106.09685*, 2021.
- Zheng Yuan, Hongyi Yuan, Chuanqi Tan, Wei Wang, and Songfang Huang. How well do large language models perform in arithmetic tasks? *arXiv preprint arXiv:2304.02015*, 2023.
- James Bergstra and Yoshua Bengio. Random search for hyper-parameter optimization. *Journal of machine learning research*, 13(2), 2012.
- Ganesh Jawahar, Muhammad Abdul-Mageed, Laks VS Lakshmanan, and Dujian Ding. LLM Performance Predictors are good initializers for Architecture Search. *arXiv preprint arXiv:2310.16712*, 2023.
- Katharina Eggensperger, Philipp Müller, Neeratyoy Mallik, Matthias Feurer, René Sass, Aaron Klein, Noor Awad, Marius Lindauer, and Frank Hutter. HPOBench: A collection of reproducible multi-fidelity benchmark problems for HPO. *arXiv preprint arXiv:2109.06716*, 2021.
- Donald R Jones, Matthias Schonlau, and William J Welch. Efficient global optimization of expensive black-box functions. *Journal of Global optimization*, 13:455–492, 1998.
- Barret Zoph, Vijay Vasudevan, Jonathon Shlens, and Quoc V Le. Learning transferable architectures for scalable image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 8697–8710, 2018.
- Joe Mellor, Jack Turner, Amos Storkey, and Elliot J Crowley. Neural architecture search without training. In *International conference on machine learning*, pages 7588–7598. PMLR, 2021.
- Noah Hollmann, Samuel Müller, Katharina Eggensperger, and Frank Hutter. Tabpfn: A transformer that solves small tabular classification problems in a second. *arXiv preprint arXiv:2207.01848*, 2022.
- Banghao Chen, Zhaofeng Zhang, Nicolas Langrené, and Shengxin Zhu. Unleashing the potential of prompt engineering in Large Language Models: a comprehensive review. *arXiv preprint arXiv:2310.14735*, 2023.
- Raisa Islam and Owana Marzia Moushi. GPT-40: The Cutting-Edge Advancement in Multimodal LLM. Authorea Preprints, 2024.
- Yiran Ding, Li Lyna Zhang, Chengruidong Zhang, Yuanyuan Xu, Ning Shang, Jiahang Xu, Fan Yang, and Mao Yang. Longrope: Extending llm context window beyond 2 million tokens. arXiv preprint arXiv:2402.13753, 2024.
- Xindi Wang, Mahsa Salmani, Parsa Omidi, Xiangyu Ren, Mehdi Rezagholizadeh, and Armaghan Eshaghi. Beyond the limits: A survey of techniques to extend the context length in large language models. *arXiv preprint arXiv:2402.02244*, 2024d.
- Lei Huang, Weijiang Yu, Weitao Ma, Weihong Zhong, Zhangyin Feng, Haotian Wang, Qianglong Chen, Weihua Peng, Xiaocheng Feng, Bing Qin, et al. A survey on hallucination in large language models: Principles, taxonomy, challenges, and open questions. *arXiv preprint arXiv:2311.05232*, 2023.

- Shirui Pan, Linhao Luo, Yufei Wang, Chen Chen, Jiapu Wang, and Xindong Wu. Unifying large language models and knowledge graphs: A roadmap. *IEEE Transactions on Knowledge and Data Engineering*, 2024.
- Jaimie Drozdal, Justin Weisz, Dakuo Wang, Gaurav Dass, Bingsheng Yao, Changruo Zhao, Michael Muller, Lin Ju, and Hui Su. Trust in AutoML: exploring information needs for establishing trust in automated machine learning systems. In *Proceedings of the 25th international conference on intelligent user interfaces*, pages 297–307, 2020.
- Robert R Hoffman, Shane T Mueller, Gary Klein, and Jordan Litman. Metrics for explainable AI: Challenges and prospects. *arXiv preprint arXiv:1812.04608*, 2018.
- Tanja Tornede, Alexander Tornede, Jonas Hanselle, Felix Mohr, Marcel Wever, and Eyke Hüllermeier. Towards green automated machine learning: Status quo and future directions. *Journal of Artificial Intelligence Research*, 77: 427–457, 2023b.
- Xingyao Wang, Yangyi Chen, Lifan Yuan, Yizhe Zhang, Yunzhu Li, Hao Peng, and Heng Ji. Executable code actions elicit better llm agents. *arXiv preprint arXiv:2402.01030*, 2024e.
- Xingyao Wang, Boxuan Li, Yufan Song, Frank F Xu, Xiangru Tang, Mingchen Zhuge, Jiayi Pan, Yueqi Song, Bowen Li, Jaskirat Singh, et al. OpenHands: An Open Platform for AI Software Developers as Generalist Agents. *arXiv* preprint arXiv:2407.16741, 2024f.