

# HJ-Ky-0.1: an Evaluation Dataset for Kyrgyz Word Embeddings

Anton M. Alekseev<sup>1,2,3,4</sup> and Gulnara Kabaeva<sup>4</sup>

<sup>1</sup>Steklov Institute of Mathematics at St. Petersburg,  
St. Petersburg, Russia

<sup>2</sup>St. Petersburg State University, St. Petersburg, Russia

<sup>3</sup>Kazan (Volga Region) Federal University, Kazan, Russia

<sup>4</sup>KSTU named after I. Razzakov, Bishkek, Kyrgyzstan

## Abstract

One of the key tasks in modern applied computational linguistics is constructing word vector representations (word embeddings), which are widely used to address natural language processing tasks such as sentiment analysis, information extraction, and more. To choose an appropriate method for generating these word embeddings, quality assessment techniques are often necessary. A standard approach involves calculating distances between vectors for words with expert-assessed “similarity”. This work introduces the first “silver standard” dataset for such tasks in the Kyrgyz language, alongside training corresponding models and validating the dataset’s suitability through quality evaluation metrics<sup>1</sup>.

**Keywords:** natural language processing, language resources, less-resourced languages, Kyrgyz language, machine learning, distributional semantics.

## 1 Introduction

Natural language processing (NLP) is a multidisciplinary field at the intersection of applied linguistics, artificial intelligence, machine learning, and statistics. Automatic text processing methods play a crucial role in modern data science since valuable information is often presented as unstructured, free-form text rather than in machine-readable formats. Despite the wealth of research in computational linguistics, particularly in morphology (e.g., [32]), there is currently a lack of open datasets and language resources for processing the Kyrgyz language [20]. It is difficult to envision further progress in this area without addressing this gap.<sup>2</sup> Specifically, no datasets are available for evaluating semantic methods, including those designed to assess the quality of word vector representations (word embeddings).

The goal of this work is to begin filling this gap by introducing the first dataset tailored for evaluating word vector quality in Kyrgyz. This dataset was created through manual translation from Russian. We describe the dataset (pairs of words and their estimated “similarity” scores), the translation methodology, and computation of quality metrics for several word embedding models. Furthermore, we validate the dataset’s relevance to the task through these quality evaluation measures. The metrics used include Spearman’s rank correlation and Pearson’s correlation coefficient, comparing the original similarity scores with the similarity scores of trainable vector representations (measured by

<sup>1</sup>This is a translation of the original paper published in 2023, in Russian. In case the reported results or any outcomes of the study find some use in your work, we suggest that you cite it as follows: Alekseev, A., Kabaeva, G.: HJ-Ky-0.1: an Evaluation Dataset for Kyrgyz Word Embeddings. Herald of KSTU 68(4) (2023), or, in bibtex: @article{alekseev2023embeddings, author={Alekseev, Anton and Kabaeva, Gulnara}, title={{HJ-Ky-0.1: an Evaluation Dataset for Kyrgyz Word Embeddings}}, journal={Herald of KSTU}, volume={68}, number={4}, year={2023}, url={https://www.elibrary.ru/item.asp?id=58483453}}.

<sup>2</sup>An incomplete list of open tools and datasets can be found, e.g., at the link <https://github.com/alexeyev/awesome-kyrgyz-nlp>.

cosine similarity). This paper provides a brief overview of non-contextual word vector representation methods, evaluation approaches, and details of both the original and translated datasets, including translation strategies. We report the experimental setups, including hyperparameters and descriptive statistics for the datasets. Finally, we summarize the results and discuss potential shortcomings of the dataset, along with steps for improving it and advancing vector semantic methods for the Kyrgyz language.

## 2 Building vector representations

Word, subword, and text embeddings have become essential components of many modern natural language processing methods. A key property of these embeddings is that the distance (Euclidean, cosine, etc.) between vectors should be smaller for words with closer “senses”. Most of these approaches rely on the principle of distributional semantics: “You shall know a word by the company it keeps!” [9]. In other words, words that appear in similar contexts often share certain properties, not limited to syntax. Zellig Harris [12] illustrated this with the words “oculist” and “eye-doctor”, which, being synonyms, frequently co-occur with terms such as “eye” or “examined”.

Early methods for constructing word vectors were based on term-document matrices and their factorized modifications, such as Latent Semantic Indexing (LSI) [6]. Other methods utilized term-term (or term-context) matrices (e.g., a “vocabulary”  $\times$  “vocabulary” matrix based on word co-occurrence frequencies within a window of consecutive words), often weighted using Pointwise Mutual Information (PMI). These approaches essentially involved calculating and re-weighting large sets of statistics.

A significant breakthrough in vector representation quality was achieved in 2013 with predictive methods introduced in *word2vec* models [17, 18]. These models use shallow neural networks to predict a target word based on its surrounding context (Continuous Bag-of-Words, CBOW) or to predict the context based on a target word (Skip-Gram). The hidden layer values of the trained network are then used as word embeddings. Later, the *fastText* model [4, 11] was developed to address vocabulary dependence and preprocessing challenges, particularly for morphologically rich languages like Kyrgyz, which lack high-quality context-aware lemmatizers. In *fastText*, each word is represented as a combination of character n-grams, summing these to compute the final vector representation. This approach is less sensitive to vocabulary and word normalization. The predictive approach of *word2vec* (specifically the Skip-Gram with Negative Sampling variant) was later shown to implicitly factorize a PMI-based term-context matrix [16]. Other notable non-contextual embeddings include GloVe [21], which incorporates word frequencies, and *dict2vec* [25], which uses dictionary definitions as training data. Additionally, Paragraph2vec (doc2vec) [15], inspired by *word2vec*, was developed for document-level representations, though newer and more efficient methods now exist for representing short texts.

Since 2013, trainable vector representations have been successfully applied to numerous NLP problems across diverse domains [8, 26]. However, since the emergence of contextual embeddings in late 2017, models based on recurrent neural networks [22] or the Transformer architecture [7, 27] have demonstrated superior performance by incorporating contextual information during both training and inference. Despite this, non-contextual models remain crucial for tasks without explicit context or for languages with limited resources, such as Kyrgyz. These models, along with *fastText* and *word2vec*, are also commonly used as baselines for word and short text representations.

## 3 The original dataset

The HJ [34] dataset is a collection of Russian noun pairs derived from translating the well-known English-language WordSim353 [1] dataset, along with the RG [24] and MC [19] datasets, into Russian. Word similarity judgments were newly obtained through crowdsourcing, where annotators rated 15 randomly selected word pairs (out of 398 total pairs) on a scale from 0 (not related at all) to 3 (high similarity) using a specialized interface. Details of the annotation process are described in the original work [34].

In total, 4,200 ratings were gathered from 280 marking sessions. The consistency of the scores was evaluated using Krippendorff’s alpha, which resulted in a value of 0.49. The published dataset

includes each word pair along with the average score from the annotators, normalized to fall within the range [0, 1].

## 4 Translation into the Kyrgyz language

During the process of translating the HJ dataset into Kyrgyz, several challenges arose, necessitating the development of specific rules. These challenges stemmed from the following issues: (1) words in any language can have multiple meanings (senses), and in Kyrgyz, each sense may correspond to a distinct word (e.g., the Russian word «лук» can mean “onion” («пияз») or “bow” («жаа») depending on the context); (2) even when there is no semantic ambiguity, a word may have more than one translation; and (3) for semantic similarity evaluation, it is necessary to translate the original Russian word into a single Kyrgyz word, which is not always feasible. The rules we followed are detailed below.

By default, we used K. K. Yudakhin’s Kyrgyz-Russian dictionary [36] for translation, facilitated by a web interface provided by the creators of `el - sozduk . kg`. If the source word was semantically ambiguous (e.g., «лук»), the translation closest in meaning to the second word in the pair was selected, based on the assumption that annotators likely scored the original dataset intuitively in a similar manner. If a word was not found in Yudakhin’s dictionary, other resources were consulted, with preference given to terminological and spelling dictionaries [29- 31, 33, 35], followed by E. D. Asanov’s dictionary [2], and finally others. Comments in the dataset indicate the sources used for each word pair.

If no single-word translation could be found for one or both words in a pair, the pair was excluded from the dataset. When choosing between a direct lexical borrowing from Russian and an alternative translation, preference was given to the alternative. If Yudakhin’s dictionary [36] only provided a lexical borrowing, but an alternative consistent with other rules was found in terminological dictionaries or Asanov’s dictionary, the latter was used. Proper names not found in dictionaries were translated based on relevant articles from the Kyrgyz Wikipedia (<https://ky.wikipedia.org/>).

As a result, 361 word pairs were created, each paired with similarity scores from the HJ dataset. The dataset and accompanying code will be made publicly available after the publication of this work and potentially after a word embeddings competition<sup>3</sup>. A sample of the data is shown in Table 1.

Word 1	Word 2	Similarity
...		
иерусалим (jerusalem)	ысрайыл (israel)	0.6222
шайман (instrument)	курал (weapon)	0.6222
планета (planet)	жылдыз (star)	0.6191
өлкө (country)	жаран (citizen)	0.6191
жолборс (tiger)	фауна (fauna)	0.6191
студент (student)	профессор (professor)	0.6191
...		
марс (mars)	суу (water)	0.0909
азчылык (minority)	дүйнө (world)	0.0909
кылым (century)	улут (nation)	0.0889
падыша (king)	капуста (cabbage)	0.0889
багуу (care)	архитектура (architecture)	0.0889
...		

Table 1: Pair samples from the constructed HJ-Ky-0.1 dataset.

## 5 Word embeddings

The prepared collection of word pairs is specifically designed to evaluate non-contextual word vector representations. To obtain preliminary results and verify the adequacy of the quality estimates,

<sup>3</sup><https://github.com/alexeyev/kyrgyz-embedding-evaluation>

we utilized pre-trained word embeddings for both Kyrgyz and Russian languages. Additionally, we trained several models using publicly available Kyrgyz text collections, as described below.

**Pre-trained *fastText* and Compressed *fastText* embeddings.** The *fastText* models for 157 languages, including Kyrgyz and Russian, were released online alongside the original publication [11]. These models were trained using the Continuous Bag-of-Words (CBOW) scheme (see Section 2) with a window size of 5, 10 negative samples, and a vector dimension of 300. The models were trained on language-specific segments of the CommonCrawl dataset.

However, the models obtained in this manner are very “heavy” in terms of the number of parameters and overall required memory, and the usage of the software that employs them e. g. on mobile devices and laptop computers is limited due to the high requirements for the computer’s RAM capacity. Specialized compression methods have been developed to solve this problem by reducing the size of the model without significant losses in quality. For example, matrix decomposition via SVD (singular value decomposition), vector quantization [13], “re-design” of the hashing trick used in *fastText*, feature selection, etc.

However, these models are resource-intensive in terms of memory and computational requirements, making them less suitable for use on mobile devices or computers with limited RAM. To address this issue, specialized compression techniques, such as singular value decomposition (SVD), vector quantization [13], and enhanced hashing tricks, have been developed to reduce model size without significant quality loss. These methods, along with options for combining them, are implemented in the `avidale/compress-fasttext` library [5]. Compressed versions of the *fastText* models were published by Liebl Bernhard [3]. For our experiments, we used the relevant compressed models: `fasttext-ky-mini` for Kyrgyz and David Dale’s `geowac_tokens_sg_300_5_2020-100K-20K-100.bin` model<sup>4</sup> for Russian, based on the corresponding model [14].

**Training word embeddings on Leipzig Corpus data.** We also trained embeddings using data from the Leipzig Corpus Collection<sup>5</sup> [10], focusing on the largest available NewsCrawl segment (`kir_newscrawl_2016_1M`, one million sentences) and Wikipedia segment (`kir_wikipedia_2021_300K`<sup>6</sup>, 300,000 sentences). Sentences were tokenized using a tokenizer based on Apertium-Kir [28], which was also used as a stemmer. The stemming process reduced tokens to their first morphological segment as analyzed by Apertium-Kir. While this approach results in some information loss, it was necessary due to the absence of a context-aware lemmatizer for Kyrgyz.

For our first baseline, we used the Skip-Gram Negative Sampling (SGNS) variant of *word2vec*, as implemented in the `gensim-4.2.0` library [23]. We trained vectors of dimensions 100 and 300, with a window size of 5, 5 negative samples per positive example, and 10 training epochs over the corpus.

Next, we trained *fastText* embeddings on the Leipzig Corpus data. The training scheme was also Skip-Gram Negative Sampling, with 10 epochs, vector dimensions of 100 and 300, a window size of 5, and 10 negative samples. Character n-grams of 3 to 6 characters and 2,000,000 hashing buckets were used for the hashing trick.

It is worth noting that we chose SGNS for training because it is considered better suited for relatively small datasets with a large number of rare words compared to CBOW, as suggested by one of the *word2vec* authors<sup>7</sup>. The hyperparameters were chosen based on commonly used values in research and practice to ensure that the results would reflect the HJ-Ky-0.1 dataset’s overall suitability rather than being influenced by specific parameter tuning.

## 6 Results

The results of the data preparation and model training are summarized in Table 2, which presents the quality scores achieved by the models.

<sup>4</sup>[https://github.com/avidale/compress-fasttext/releases/download/gensim-4-draft/geowac\\_tokens\\_sg\\_300\\_5\\_2020-100K-20K-100.bin](https://github.com/avidale/compress-fasttext/releases/download/gensim-4-draft/geowac_tokens_sg_300_5_2020-100K-20K-100.bin)

<sup>5</sup><https://corpora.uni-leipzig.de/>

<sup>6</sup><https://wortschatz.uni-leipzig.de/en/download/Kirghiz>

<sup>7</sup><https://groups.google.com/g/word2vec-toolkit/c/NLvYXU99cAM/m/E5ld8LcDxLAJ>

Model family	Training scheme	Data	Preprocessing	dim	$r_s$	$\rho$
word2vec	SGNS	Leipzig	Apertium tokenization	100	0.513	0.458
word2vec	SGNS	Leipzig	Apertium tokenization	300	0.524	0.472
word2vec	SGNS	Leipzig	Apertium stemming	100	0.440	0.383
word2vec	SGNS	Leipzig	Apertium stemming	300	0.448	0.403
fastText	SGNS	Leipzig	Apertium tokenization	100	<b>0.605</b>	<b>0.572</b>
fastText	SGNS	Leipzig	Apertium tokenization	300	0.601	0.560
fastText	SGNS	Leipzig	Apertium stemming	100	0.583	0.571
fastText	SG	Leipzig	Apertium stemming	300	0.588	0.564
fastText	CBOW	CC-Ky [11]	Europarl tokenization	300	0.557	0.515
C-fastText	CBOW	CC-Ky [11]	Europarl tokenization	100	0.480	0.457
fastText	CBOW	CC-Ru [11]	Europarl tokenization	300	0.245	0.302
C-fastText	CBOW	CC-Ru [11]	Europarl tokenization	100	0.243	0.283

Table 2: Quality estimates achieved with pre-trained models and models trained on Leipzig corpus. Here **dim** is the vector size,  $r_s$  and  $\rho$  are the Spearman’s and Pearson’s correlation coefficients, respectively.. C-fastText are Compressed fastText representations. “Europarl tokenization”: <https://www.statmt.org/europarl/>.

The purpose of this work is not to compare models but to present a new dataset and indirectly validate its suitability for processing Kyrgyz text, as it was constructed through manual translation. Several observations support this validation.

1. *Performance differences by language.* Despite the presence of lexical borrowings from Russian in the Kyrgyz dataset, Russian word embeddings trained on much larger text corpora performed significantly worse, indicating that the dataset is well-aligned with the specific characteristics of the Kyrgyz language.

2. *Impact of stemming.* The “rough” stemming approach resulted in reduced quality scores, which is expected since this method causes significant information loss. For *word2vec*, stemming even led to the absence of representations for some words.

3. *Model comparison.* The fastText models consistently outperformed word2vec, reflecting expectations for morphologically rich languages like Kyrgyz. The performance drop from tokenization to stemming is particularly notable, as certain words are excluded from the dataset after stemming.

4. *Corpus quality.* The fastText model trained on the Leipzig Corpus (fastText, Skip-Gram, Leipzig, 100) outperformed the CommonCrawl-Ky model, even without hyperparameter tuning. This suggests that the Leipzig Corpus is cleaner and more suitable than the automatically collected CommonCrawl dataset, which may include mislabeled or noisy text.

These results indicate that the HJ-Ky-0.1 dataset provides reliable quality metrics for word embeddings. However, further validation on a manually re-annotated dataset is necessary to confirm these findings. We also note that it might be preferable to train models on text data in the Kyrgyz language, since the model published by Facebook (CBOW, CC-Ky, 300,  $r_s = 0.557$ ,  $\rho = 0.515$ ) might not be the best available (which, again, should be confirmed by testing on a manually annotated set of pairs).

## 7 Conclusion

In this work, we introduce the first word vector quality evaluation dataset for the Kyrgyz language, HJ-Ky-0.1, created by translating the HJ dataset from Russian. We provided indirect evidence of the dataset’s adequacy for the task, including:

- superior performance of Kyrgyz word embeddings compared to Russian embeddings on the Kyrgyz dataset;
- a decline in quality when using stemmed text, demonstrating the limitations of rough stemming for morphologically rich languages;
- better results from *fastText* compared to *word2vec*, which aligns with expectations for Kyrgyz text processing.

Our experiments also showed that *fastText* embeddings trained on the Leipzig Corpus outperform those trained on CommonCrawl, highlighting the importance of clean, high-quality text data for training. These findings suggest that the HJ-Ky-0.1 dataset is a valuable resource for selecting word representation methods and fine-tuning model hyperparameters.

Looking ahead, we plan to improve the dataset by manually re-annotating the word pairs with expert ratings provided by native speakers, as translation may have altered the perceived similarity of some pairs. We also aim to expand the dataset with additional pairs, potentially derived from synonym dictionaries. These enhancements will facilitate more reliable evaluations and support the development of high-quality vector semantic methods for the Kyrgyz language.

## Acknowledgments

The authors express their gratitude to S. I. Nikolenko for insightful comments and for proofreading both versions of this paper.

## References

- [1] Eneko Agirre, Enrique Alfonseca, Keith Hall, Jana Kravalova, Marius Pasca, and Aitor Soroa. A study on similarity and relatedness using distributional and wordnet-based approaches. In *Human Language Technologies: The 2009 Annual Conference of the North American Chapter of the Association for Computational Linguistics*, page 19. Citeseer, 2009.
- [2] E. Asanov and N. Suchelenskiy. Русско-киргизский (русско-кыргызский) словарь Э. Асанова. <https://el-sozduk.kg/slovari/rus-kyrgyz-slovar-asanov/>, 2019.
- [3] Liebl Bernhard. Compressed fasttext embeddings. <https://zenodo.org/record/4905385>, June 2021.
- [4] Piotr Bojanowski, Edouard Grave, Armand Joulin, and Tomas Mikolov. Enriching word vectors with subword information. *Transactions of the Association for Computational Linguistics*, 5:135-146, 2017.
- [5] David Dale. Compress-fasttext: Tools for shrinking fasttext models (in gensim format). <https://github.com/avidale/compress-fasttext>, 2023.
- [6] Scott Deerwester, Susan Dumais, Thomas Landauer, George Furnas, and Laura Beck. Improving information-retrieval with latent semantic indexing. In *Proceedings of the ASIS annual meeting*, volume 25, pages 36-40, 1988.
- [7] Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. BERT: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pages 4171-4186, Minneapolis, Minnesota, June 2019. Association for Computational Linguistics.
- [8] Andrey Filchenkov. Morpheme Level Word Embedding. In *Artificial Intelligence and Natural Language: 6th Conference, AINL 2017, St. Petersburg, Russia, September 20-23, 2017, Revised Selected Papers*, volume 789, page 143. Springer, 2017.
- [9] John Firth. A synopsis of linguistic theory, 1930-1955. *Studies in linguistic analysis*, pages 10-32, 1957.
- [10] Dirk Goldhahn, Thomas Eckart, Uwe Quasthoff, et al. Building large monolingual dictionaries at the leipzig corpora collection: From 100 to 200 languages. In *LREC*, volume 29, pages 31-43, 2012.
- [11] Edouard Grave, Piotr Bojanowski, Prakhar Gupta, Armand Joulin, and Tomas Mikolov. Learning word vectors for 157 languages. In *Proceedings of the International Conference on Language Resources and Evaluation (LREC 2018)*, 2018.

- [12] Zellig S Harris. Distributional structure. *Word*, 10(2-3):146-162, 1954.
- [13] Herve Jegou, Matthijs Douze, and Cordelia Schmid. Product quantization for nearest neighbor search. *IEEE transactions on pattern analysis and machine intelligence*, 33(1):117-128, 2010.
- [14] Andrey Kutuzov and Elizaveta Kuzmenko. *WebVectors: A Toolkit for Building Web Interfaces for Vector Semantic Models*, pages 155-161. Springer International Publishing, Cham, 2017.
- [15] Quoc Le and Tomas Mikolov. Distributed representations of sentences and documents. In *International conference on machine learning*, pages 1188-1196. PMLR, 2014.
- [16] Omer Levy and Yoav Goldberg. Neural word embedding as implicit matrix factorization. In Z. Ghahramani, M. Welling, C. Cortes, N. Lawrence, and K.Q. Weinberger, editors, *Advances in Neural Information Processing Systems*, volume 27. Curran Associates, Inc., 2014.
- [17] Tomas Mikolov, Kai Chen, Greg Corrado, and Jeffrey Dean. Efficient estimation of word representations in vector space. *arXiv preprint arXiv:1301.3781*, 2013.
- [18] Tomas Mikolov, Ilya Sutskever, Kai Chen, Greg S Corrado, and Jeff Dean. Distributed representations of words and phrases and their compositionality. *Advances in neural information processing systems*, 26, 2013.
- [19] George A Miller and Walter G Charles. Contextual correlates of semantic similarity. *Language and cognitive processes*, 6(1):1-28, 1991.
- [20] Jamshidbek Mirzakhlov. *Turkic Interlingua: A Case Study of Machine Translation in Low-resource Languages*. PhD thesis, University of South Florida, 2021.
- [21] Jeffrey Pennington, Richard Socher, and Christopher D Manning. Glove: Global vectors for word representation. In *Proceedings of the 2014 conference on empirical methods in natural language processing (EMNLP)*, pages 1532-1543, 2014.
- [22] Matthew E. Peters, Mark Neumann, Mohit Iyyer, Matt Gardner, Christopher Clark, Kenton Lee, and Luke Zettlemoyer. Deep contextualized word representations. In *Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long Papers)*, pages 2227-2237, New Orleans, Louisiana, June 2018. Association for Computational Linguistics.
- [23] Radim Řehůřek and Petr Sojka. Software Framework for Topic Modelling with Large Corpora. In *Proceedings of the LREC 2010 Workshop on New Challenges for NLP Frameworks*, pages 45-50, Valletta, Malta, May 2010. ELRA.
- [24] Herbert Rubenstein and John B Goodenough. Contextual correlates of synonymy. *Communications of the ACM*, 8(10):627-633, 1965.
- [25] Julien Tissier, Christophe Gravier, and Amaury Habrard. Dict2vec: Learning word embeddings using lexical dictionaries. In *Proceedings of the 2017 Conference on Empirical Methods in Natural Language Processing*, pages 254-263, 2017.
- [26] EV Tutubalina, Z Sh Miftahutdinov, RI Nugmanov, TI Madzhidov, SI Nikolenko, IS Alimova, and AE Tropsha. Using semantic analysis of texts for the identification of drugs with similar therapeutic effects. *Russian Chemical Bulletin*, 66:2180-2189, 2017.
- [27] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, L ukasz Kaiser, and Illia Polosukhin. Attention is all you need. In I. Guyon, U. Von Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 30. Curran Associates, Inc., 2017.
- [28] Jonathan North Washington, Mirlan Ipasov, and Francis M Tyers. A finite-state morphological transducer for kyrgyz. In *LREC*, pages 934-940, 2012.
- [29] Абдиев, Т. and Сыдыкова, Л. *Англо-кыргызский словарь // Англисче-кыргызча сөздүк*. Avrasya-Press, Бишкек, 2015.

- [30] Айдарбекова Ч. А. *Русско-киргизский (русско-кыргызский) словарь юридических терминов*. Б.: Учкун, 2005.
- [31] Акматалиев, А. А. and Молдоканов, А. М. *Русско-кыргызский словарь юридических терминов и иных понятий // Юридикалык атоолордун жана башка түшүнүктөрдүн орусча-кыргызча сөздүгү*. Б.: Турар, 2014.
- [32] Бакасова, П. С. and Исраилова, Н. А. Алгоритм образования словоформ для автоматизации процедуры пополнения базы данных словаря. *Известия Кыргызского государственного технического университета им. И. Раззакова*, (2):23-27, 2016.
- [33] Карасаев, Х. К. *Кыргыз тилинин орфографиялык сөздүгү*. Б.: Мамл. тил ж-а энциклопедия борбору, 2009.
- [34] Панченко, А., Лукашевич, Н., Усталов, Д., Паперно, Д., Мейер, К. М., and Константинова, Н. Russe: семинар по оценке семантической близости для русского языка. In *Компьютерная лингвистика и интеллектуальные технологии: По материалам ежегодной Международной конференции «Диалог»(Москва, 27—30 мая 2015 г.)*. М.: Изд-во РГГУ, number 14, page 21, 2015.
- [35] Терминком. *Русско-киргизский (русско-кыргызский) терминологический словарь*. 2007.
- [36] Тил жана адабият институту (Кыргыз ССР илимдер академиясы) and Юдахин, К. К. *Русско-киргизский (русско-кыргызский) словарь*. Гос. изд-во иностранных и национал'ных словарей, 1957.