LIKELIHOODGEOMETRY: MACAULAY2 PACKAGE

DAVID BARNHILL, JOHN COBB, AND MATTHEW FAUST

ABSTRACT. This note introduces the LikelihoodGeometry package for the computer algebra system *Macaulay2*. This package gives tools to construct the likelihood correspondence of a discrete algebraic statistical model, a variety that that ties together data and their maximum likelihood estimators. This includes methods for constructing and combining popular statistical models and calculating their ML-degree.

1. INTRODUCTION AND BACKGROUND

Maximum likelihood estimation (MLE) is a fundamental computational problem in statistics with recent insights stemming from studying the geometry of discrete algebraic statistical models as varieties [CHKS04, Huh13, HS14, AKK19, MRWW22]. The likelihood correspondence of a discrete algebraic statistical model X is the universal family of solutions to all MLE problems on X. This variety, or equivalently its vanishing ideal the *likelihood ideal*, encodes all information about the MLE problem [HKS04, Section 2], such as the *maximum likelihood* (ML) degree of the model. In [BCF23], we presented algorithms to construct the likelihood ideal of toric models and found a Gröbner basis in the case of complete and joint independence models arising from multi-way contingency tables. The *Macaulay2* [GS] package LikelihoodGeometry implements these new algorithms alongside functions which allow the construction of various sorts of models and a calculation of their ML-degree. A more general algorithm [HKS04, Algorithm 6] for non-toric models is also implemented. This package differs from GraphicalModelsMLE [AGPH+22] by constructing MLE estimates for *discrete* algebraic statistical models (rather than Gaussian) by directly constructing the likelihood ideal rather than numerically solving the problem for specified data vectors.

For the rest of this section, we give some background for the models and likelihood correspondence and introduce the main functions of the package with examples. In Section 2, we detail the implementation of the main algorithm computeLC.

1.1. Likelihood Geometry. Fix a system of homogeneous coordinates p_0, p_1, \ldots, p_n of complex projective space \mathbb{P}_p^n representing the space of probabilities. Similarly, we consider u as coordinates of the data space \mathbb{P}_u^n . The likelihood function on \mathbb{P}_p^n is given by

$$\ell_u(p) = \frac{p_0^{u_0} p_1^{u_1} \cdots p_n^{u_n}}{(p_0 + p_1 + \dots + p_n)^{u_0 + u_1 + \dots + u_n}}.$$

We aim to study the MLE problem on the restriction of ℓ_u to a given closed irreducible subvariety $\mathcal{M} \subseteq \mathbb{P}_p^n$. Fixing a data vector u, maximum likelihood estimates are given by the maxima of ℓ_u . These maxima belong to the critical set of the log-likelihood function $\log \ell_u$. This critical set is given by $V(\operatorname{dlog} \ell_u) \subset \mathbb{P}_p^n$, the vanishing set of the gradient of $\log \ell_u$. By varying u, we can collect such critical sets into a universal family $\mathcal{L}_{\mathcal{M}} \subset \mathbb{P}_p^n \times \mathbb{P}_u^n$ called the *likelihood correspondence*. More information can be found in [BCF23, Section 2] or in [HKS04, Section 2]. The main function of the package is computeLC, which can take in an arbitrary ideal representing the vanishing ideal of a statistical model and returns the likelihood ideal. Depending on the input, it automatically implements the fastest algorithms from Section 2.

Example 1.1. Consider the problem of flipping a biased coin two times and recording the number of heads. Let $p = (p_0, p_1, p_2)$ represent the vector of probabilities of getting 0 heads, 1 head, and 2 heads respectively. The possible probabilities for this experiment are defined by the *Hardy–Weinberg curve* $\mathcal{M} = V(4p_0p_2 - p_1^2) \subset \mathbb{P}_p^2$ [Tes07], a statistical model studied in population genetics. The likelihood correspondence is a surface $\mathcal{L}_{\mathcal{M}} \subset \mathbb{P}_p^2 \times \mathbb{P}_u^2$ with ML-degree 1:

```
i1 : R = CC[p_0, p_1, p_2];
i2 : M = ideal(4*p_0*p_2-p_1^2);
o2 : Ideal of R
i3 : L = computeLC(M)
o3 = ideal (4pu - pu + 2pu - 2pu, 2pu - 2pu + pu - 4pu,
           20 11 21 12 10 01 11
                                                        0 2
          2
         p - 4pp)
          1 0 2
o3 : Ideal of CC[p ..p , u ..u ]
               0 2
                     0
                         2
i4 : MLdegree(M)
04 = 1
```

1.1.1. Discrete Random Variables. All of the analyses in this paper applies to discrete algebraic statistical models. This package implements a new data type DiscreteRandomVariable which holds an arity and can be given a custom probability mass function as pmf (default is uniform). There are methods to sample, take the mean, and see the state space with states.

Example 1.2. The following code block demonstrates some of the methods available for DiscreteRandomVariable.

```
i1 : g = new HashTable from {
    1 => 0.5,
    2 => 0.3,
    3 => 0.2
};
i2 : f = x -> if g#?x then g#x else 0;
i3 : Y = discreteRandomVariable(3, f);
o3 = Y
o3 : DiscreteRandomVariable
i4 : {states Y, mean Y, sample(Y,2)}
o4 = {{1, 2, 3}, 1.7, {1, 1}}
o4 : List
```

 \diamond

 \diamond

1.2. Different Types of Models.

1.2.1. Toric Models. A toric model is simply a model which is a toric variety and are among the most thoroughly studied statistical models [GMS06, Tes07, Sul18]. One method to construct a toric model is to pass in a matrix A such that each column is the lattice vertex of the

corresponding polytope to the function toricModel, which returns a NormalToricVariety. The function toricIdeal can take in a toric model given by a NormalToricVariety or the defining matrix and returns the vanishing ideal.

Example 1.3. The rational normal curve of degree d is the image of the map

$$\varphi: \mathbb{P}^1 \longrightarrow \mathbb{P}^d$$
$$[s:t] \mapsto [s^d: s^{d-1}t: \cdots: st^{d-1}: t^d]$$

and is defined as a toric variety by the $2 \times (d+1)$ matrix

$$\begin{bmatrix} 1 & 1 & 1 & \cdots & 1 \\ 1 & 2 & 3 & \cdots & d+1 \end{bmatrix}$$

Taking d = 3 gives the twisted cubic:

Rational normal curves are part of the larger class of rational normal scrolls, and we have implemented the construction of this class via rationalNormalScroll. The family of rational normal scrolls can be parametrized by a list of integers a_0, \ldots, a_k corresponding to $S(a_0, \ldots, a_k) \subseteq \mathbb{P}^N$ where $N = \sum_{i=0}^k (a_i) + k$ [Pet08]. For example, the rational normal curve of degree d can be constructed using rationalNormalCurve({d+1}). Without a toric polytope on hand, one can construct it from a toric ideal using toricPolytope.

Using this package, one can construct the likelihood ideal of toric models much faster than arbitrary ideals using the algorithm detailed in Section 2.

1.2.2. Hierarchical Log-Linear Models. Within the class of toric models is the class of hierarchical log-linear models. Let $\mathcal{X} = [d_1] \times \cdots \times [d_n]$ denote the joint state space of the discrete random variables X_1, \ldots, X_n . A hierarchical log-linear model is defined by a collection $\{G_1, \ldots, G_g\}$ of non-empty subsets of $X = \{X_1, \ldots, X_n\}$ called generators.

Example 1.4. Let $X = \{a, b, c\}$ be a list of binary random variables and the generators be $\{a, b\}$ and $\{b, c\}$. The function makeLogLinearMatrix constructs the defining matrix for the corresponding toric model.

```
i1 : a = discreteRandomVariable 2; b = discreteRandomVariable 2;
    c = discreteRandomVariable 2;
i4 : X = \{a, b, c\};
i5 : G = \{\{a,b\}, \{b,c\}\};\
i6 : makeLogLinearMatrix(G,X)
06 = | 1 1 0 0 0 0 0 0 |
    00110000
    00001100
    | 0 0 0 0 0 0 1 1 |
    0100100
    0010010|
    00010001
           8
                  8
o6 : Matrix ZZ <-- ZZ
```

```
This defines the toric model representing the conditional independence statement a \perp c \mid b, or "a is independent of c given b".
```

1.2.3. Undirected Graphical Models. Within the class of hierarchical log-linear models are the class of undirected graphical models. The undirected graphical model for a graph \mathcal{G} is the log-linear model on X in which the generators are cliques (maximal complete subgraphs) of \mathcal{G} . Many functions described so far can take a graph whose vertices are discrete random variables as input, including toricModel, toricIdeal, and makeLogLinearMatrix.

Example 1.5. The model in Example 1.4 is the undirected graphical model corresponding to the following graph:



The toric model corresponding to a graph can be computed using toricModel, and the ideal using toricIdeal.

2. Constructing the Likelihood Correspondence

Upon running computeLC, there are three possible algorithms that will run. In the case that the input is an ideal, [HKS04, Algorithm 6] utilizing Lagrange multipliers has been implemented. In the case that a toric model is used, then the faster Algorithm 1 is used. Finally, if a undirected graphical model is input, then a check is performed to see if it is a complete or joint independence model in which case we return a Gröbner basis as given in Theorem 3.2 and Corollary 3.5 in [BCF23].

Input : a NormalToricVariety X representing a toric model

Output: the likelihood ideal

if X is a graphical model whose components are complete graphs then

return Gröbner basis as given in [BCF23];

 \mathbf{else}

 $\begin{array}{l} A \coloneqq \text{defining matrix of } X; \\ R \coloneqq \text{LCRing}(X); \\ I_X \coloneqq \texttt{toricIdeal}(A, R); \\ M \coloneqq \texttt{reshape}(R^{\texttt{numcol}}, R^2, \texttt{matrix}(\texttt{gens } R)); \\ \texttt{return saturate}(I_X + \texttt{minors}(2, A * M), (\sum p_i)(\prod p_i)) \end{array}$

 \mathbf{end}

Algorithm 1: Constructing likelihood ideals of toric models

MLdegree is then implemented by taking the fiber of a generic map from the likelihood correspondence down to the model.

Remark 2.1. As noted in [BCF23], it appears to suffice to saturate by only the single hyperplane $V(\sum p_i)$ in the final step, which can be significantly faster. This is how it is implemented and correctness is guaranteed if the output is prime.

Data Availability. All code is available as the *Macaulay2* package, LikelihoodGeometry.¹

Acknowledgement. Part of this research was performed while the authors were visiting the Institute for Mathematical and Statistical Innovation (IMSI), which is supported by the National Science Foundation (Grant No. DMS-1929348). J. Cobb is supported by DMS-2402199. M. Faust is supported by DMS-2052519. The implementation of the functions toricIdeal and toricPolytope are from the packages SlackIdeals [MW20] and Quasidegrees [Bar15], respectively.

References

- [AGPH⁺22] C. Améndola, L. D. García Puente, R. Homs, O. Kuznetsova, and H. J Motwani, Computing maximum likelihood estimates for gaussian graphical models with macaulay2, Journal of Software for Algebra and Geometry 12 (2022), no. 1, 1–10. ↑1
 - [AKK19] C. Améndola, D. Kosta, and K. Kubjas, Maximum likelihood estimation of toric fano varieties, Algebraic Statistics (2019). ↑1
 - [Bar15] R. Barrera, Computing quasidegrees of a-graded modules, Journal of Software for Algebra and Geometry (2015). ↑5
 - [BCF23] D. Barnhill, J. Cobb, and M. Faust, Likelihood correspondence of toric statistical models (2023). arXiv:2312.08501. ↑1, 2, 5

¹https://github.com/johndcobb/LikelihoodGeometry

- [CHKS04] F. Catanese, S. Hoşten, A. Khetan, and B. Sturmfels, The maximum likelihood degree, American Journal of Mathematics 128 (2004), 671 –697. [↑]1
- [GMS06] D. Geiger, C. Meek, and B. Sturmfels, On the toric algebra of graphical models, The Annals of Statistics 34 (2006), no. 3, 1463 –1492. [↑]3
 - [GS] D. R. Grayson and M. E. Stillman, Macaulay2, a software system for research in algebraic geometry. ^{↑1}
- [HKS04] S. Hoşten, A. Khetan, and B. Sturmfels, Solving the likelihood equations, Foundations of Computational Mathematics 5 (2004), 389–407. ↑1, 2, 5
- [HS14] J. Huh and B. Sturmfels, *Likelihood geometry*, Combinatorial algebraic geometry, 2014, pp. 63–117. MR3329087 ↑1
- [Huh13] J. Huh, The maximum likelihood degree of a very affine variety, Compositio Mathematica 149 (2013), no. 8, 1245–1266. ↑1
- [MRWW22] L. G. Maxim, J. I. Rodriguez, B. Wang, and L. Wu, Logarithmic cotangent bundles, chernmather classes, and the huh-sturmfels involution conjecture, Communications on Pure and Applied Mathematics 77 (2022). ↑1
 - [MW20] A. Macchia and A. Wiebe, *Slack ideals in macaulay2*, Mathematical Software ICMS 2020 **12097** (2020), 222 –231. ↑5
 - [Pet08] S. Petrović, On the universal gröbner bases of varieties of minimal degree, Mathematical Research Letters 15 (2008), no. 6. ↑3
 - [Sul18] S. Sullivant, Algebraic Statistics, Graduate Studies in Mathematics, American Mathematical Society, 2018. ↑3
 - [Tes07] G. Tesler, Algebraic Statistics for Computational Biology, Briefings in Bioinformatics 8 (2007), no. 2, 138–139. [↑]2, 3

DEPARTMENT OF MATHEMATICS, UNITED STATES NAVAL ACADEMY, ANNAPOLIS, MD *Email address*: barnhill@usna.edu

DEPARTMENT OF MATHEMATICS, AUBURN UNIVERSITY, AUBURN, AL *Email address*: jdcobb30gmail.com

DEPARTMENT OF MATHEMATICS, MICHIGAN STATE UNIVERSITY, EAST LANSING, MI *Email address*: mfaust@msu.edu