Analysis of Generalized Hebbian Learning Algorithm for Neuromorphic Hardware Using Spinnaker

Shivani Sharma and Darshika G. Perera Department of Electrical and Computer Engineering, University of Colorado Colorado Springs Colorado Springs, Colorado, USA email: ssharma7@uccs.edu, darshika.perera@uccs.edu

Abstract—Neuromorphic computing, inspired by biological neural networks, has emerged as a promising approach for solving complex machine learning tasks with greater efficiency and lower power consumption. The integration of biologically plausible learning algorithms, such as the Generalized Hebbian Algorithm (GHA), is key to enhancing the performance of neuromorphic systems. In this paper, we explore the application of GHA in largescale neuromorphic platforms, specifically SpiNNaker, a hardware designed to simulate large neural networks. Our results demonstrate significant improvements in classification accuracy, showcasing the potential of biologically inspired learning algorithms in advancing the field of neuromorphic computing.

Keywords—Neuromorphic Computing; SpiNNaker, Generalized Hebbian Algorithm; Neuromorphic Hardware, Accuracy.

I. INTRODUCTION

Neuromorphic computing, inspired by biological processes, has led to the creation of highly interconnected synthetic neurons and synapses, which are utilized to model neuroscience theories and tackle complex machine learning challenges [1]. The neuromorphic architectures are distinguished by their high connectivity and parallelism, low power requirements, and the integration of memory and processing functions [1]. This combination of biological inspiration and computational power positions neuromorphic computing as a promising frontier for the future of technology [1].

The advantages of these architectures extend beyond their technical specifications, making neuromorphic computing an increasingly compelling area of research give more ways to write this sentence. [33] This system mimics the energy-efficient processing of the human brain, suitable for applications where power consumption is crucial. [33] The highly parallel nature of neuromorphic systems allows for the simultaneous processing of multiple inputs, resulting in faster and more efficient computations. This can adapt to varying inputs and environments, making them robust and versatile across numerous applications [33].

Aligned with these principles, the Generalized Hebbian Algorithm (GHA) further strengthens the potential of neuromorphic computing. By offers numerous advantages as an extension of the classical Hebbian learning rule: GHA effectively identifies principal components of input data, useful for dimensionality reduction and feature extraction [10]. This capability is particularly advantageous for managing large input sets with relatively few outputs, a critical requirement for largescale neuromorphic systems [35]. Being biologically inspired, aligns with neuromorphic computing principles, offering a natural approach to learning and adaptation [36]. The integration of neuromorphic architectures with GHA showcases how biologically inspired methods drive the development of energy-efficient, scalable, and flexible computing technologies.

SpiNNaker (Spiking Neural Network Architecture) emerges as a specialized hardware platform designed for largescale neural simulations, offering several ideal features for neuromorphic computing [34]. It supports massive parallel processing, enabling real-time simulation of millions of neurons. This hardware can accommodate large neural networks, making it suitable for implementing and testing algorithms like GHA [34]. SpiNNaker also mimics the energyefficient processing of the human brain and consumes less power than traditional computing systems, making it ideal platform for Neuromorphic computing [34].

Despite significant progress in deep learning and conventional neural networks, these systems often depend on non-biological learning methods, limiting the full potential of brain-inspired computing [31]. A key challenge is the development of biologically plausible learning algorithms that can be efficiently integrated into hardware platforms like SpiNNaker [32]. Hebbian learning Algorithm (HA)), a concept introduced by Donald Hebb, provides a biologically inspired method for neural network training [4]. However, traditional Hebbian learning has its drawbacks, particularly in error correction and practical application in complex systems [11]. Addressing these issues, GHA extends the classical Hebbian rule to identify the eigenvectors of the input distribution's autocorrelation matrix [10], making it a promising candidate for neuromorphic applications.

Our objective was to enhance GHA capabilities: We conducted quantitative and functional analysis to assess error rate, average convergence rate, training time, memory usage and classification accuracy for Generalized Hebbian Learning and Hebbian learning models using MNIST dataset and UCI

Machine Learning Repository on neuromorphic hardware, SpiNNaker.

The GHA model demonstrated efficiency, optimization, and effectiveness, improving classification accuracy on the UCI repository with SpiNNaker. By meeting these objectives, this research aims to advance neuromorphic computing, contributing to the development of more efficient and biologically plausible learning algorithms. The study's findings could pave the way for future innovations in neuromorphic systems, enhancing their applicability and performance in various real-world scenarios.

This paper is divided as follows: In Section 2, we discuss Neuromorphic Computing, Hebbian learning Algorithm and Generalized Hebbian learning Algorithm model, in detail. In section 3, we talk about experiments and analysis, including the comparative analysis of GHA model over UCI Machine Learning repository dataset with and without SpiNNaker. For Section 4, we conclude and summarize the entire research done so far and Section 5 discuss about future scope of the Hebbian learning Algorithm.

II. BACKGROUND

A. Neuromorphic Computing

The term neuromorphic computing was coined in 1990 by Carver Mead [2]. The neuromorphic architectures are notable for being highly connected and parallel, requiring low-power, and collocating memory and processing [1].

The field of neuromorphic computing encompasses a diverse range of researchers, including those specializing in materials science, neuroscience, electrical engineering, computer engineering, and computer science. Professionals in computer science and engineering focus on developing innovative network models that draw inspiration from both biological systems and machine learning techniques [1]. Their work involves creating new algorithms that enable these models to learn independently and constructing the necessary software to facilitate the practical application of neuromorphic computing systems [1].

The aspiration to design low-power neuromorphic systems has been a significant driving force in this domain, becoming particularly influential approximately a decade into the field's evolution [1].

B. Hebbian learning Algorithm

Hebbian learning Algorithm (HA) is a learning process which is biologically plausible and ecologically valid. Hebbian learning Algorithm generally works on 'units that fire together, wire together' [12]. The Long-Term Potentiation (LTP) and Long-Term Depression (LTD) helps to learn at neural level [13]. The Long-term potentiation (LTP), a synaptic enhancement, it follows a brief and high-frequency electrical stimulation in the hippocampus and neocortex region of the human brain [14], whereas the Long-term depression (LTD) is synaptic plasticity in which the strength of synaptic transmission between neurons is decreasing gradually. The decrease in synaptic accuracy or efficacy may happen through various mechanisms. for example, a decrease in neurotransmitter receptors on postsynaptic membrane or a

lower release of neurotransmitters from the presynaptic neurons. LTP and LTD are widespread phenomena, that express the possibility of excitatory synapse in the mammalian brain [15].

Long-term depression (LTD) was first discovered by Masao Ito in 1982 [16][17]. LTP is induced when the strong input is activated simultaneously with the weak input or following the activation by no more than 20 ms, meanwhile LTD is induced when the temporal order is reversed [18]. This is to show that relative timing is extremely crucial in LTP and LTD induction [19] LTP is also known as Hebbian Plasticity [20]. A typical induction of LTD is usually due to the prolonged low-frequency stimulation of synapses and plays a crucial role in processes such as learning ability, memory loss or memory retention, and in the refinement of neural circuits. It is a complementary process to long-term potentiation (LTP), another form of synaptic plasticity leading to the enhancement of synaptic transmission [21]. Hebbian learning Algorithm is a type of synaptic plasticity that depends on neural activity. It involves the simultaneous activation of presynaptic and postsynaptic neurons, which strengthens their connection [9]. This process enhances the neural response patterns to specific inputs. When these responses are beneficial, their reinforcement can improve accuracy, fluency, and the learning of related perceptions, emotions, thoughts, or actions, contributing to better performance with practice in various tasks. However, if the response is triggered by an undesired input, this reinforcement can have negative effects. The step-by-step algorithm of Hebbian learning Algorithm rule is as follows [7]:

Algorithm - Hebbian Learning Algorithm

DATA:	UCI ML repository Dataset loaded from the TensorFlow library				
RESULT:	Positive or Negative Review based on user inputs				
STEP 1:	Import Initialize all weights and bias to zero, i.e., wi=0				
	for $i=1$ to $n, b=0$.				
	Here, n is the number of input neurons.				
STEP 2:	For each input training vector and it's respective target output pair				
	s:t, do steps 2–5.				
STEP 3:	Set activation for input units: xi = Si, i = 1,, n.				
STEP 4:	Set activation for output unit: $y = t$.				
STEP 5:	Adjust the weights and bias: wi(new) = wi(old) + xiy				
	for $i = 1,, n$, $b(new) = b(old) + y$.				
	If the bias is an input signal that is always 1, the weight				
	change can be written as w(new) = w(old) + _w,				
	where_w = xy.				

A function named Hebbian algorithm that takes three parameters: inputs (input vector), target (output vector), epochs (number of training iterations) and initializes n (number of input neuron) as well as set bias and weights vector to zero using the Hebbian Algorithm and produces updated weight as output after training. This function implements a basic Hebbian learning Algorithm, where weights are adjusted based on the correlation between input and output patterns observed during training. Adjustments are made iteratively over multiple epochs to improve the network's ability to predict or classify based on given inputs [7].

C. Generalized Hebbian learning Algorithm

Generalized Hebbian learning Algorithm is an algorithm to train neural networks to find the eigenvectors of the autocorrelation matrix of the input distribution, given only samples from that distribution [10]. Each output of a trained network represents the response to one eigenvector, and the outputs are ordered by decreasing eigenvalue. A network trained in this way will allow linear reconstruction of the original input with minimal mean-squared error [10]. The stepby-step algorithm of Generalized Hebbian learning Algorithm rule is as follows:

Algorithm - Generalized Hebbian Learning Algorithm

DATA:	UCI ML repository Dataset loaded from the TensorFlow library
RESULT:	Positive or Negative Review based on user inputs
STEP 1:	Initialize the weight matrix C with small random
	values. $C(0) \in \mathbb{R}^{M \times N}$
	Here, M is the number of output neurons, and N is the number of
	input neurons with M <n.< th=""></n.<>
STEP 2:	For each input training vector x (t) and its respective target output t,
	do steps 3–6.
STEP 3:	Compute the output vector y(t):
	$\mathbf{y}(t) = \mathbf{C}(t) \ \mathbf{x}(t)$
STEP 4:	Compute the outer products:
	$y(t)\mathbf{x}^{T}(t)$ and $y(t)y^{T}(t)$
STEP 5:	Set all elements above the diagonal of $y(t)y^{T}(t)$ to
	zero,
	making it lower triangular: $L^{T} [y(t)y^{T} (t)]$
STEP 6:	Update the weight matrix C(t) using the GHL rule:
	$C(t+1)=C(t)+\eta(y(t)x^{T}(t)-L^{T}[y(t)y^{T}(t)]C(t))$ where η
	is the learning rate

The algorithm starts by initializing the weights matrix C with random values. This matrix will be adapted during training to capture the eigenvectors of the input correlation matrix. Then, it enters a loop for a specified number of training epochs. Within each epoch, it processes each input vector from the dataset. For each input vector x, it calculates the output vector y by taking the dot product of the weight matrix C and the input vector x [10] The core of the algorithm is in updating the weights [10].

Here, Outer product represents the outer product of y and x, and cross product is the cross product of the transpose of C and y. The weights matrix C is then updated based on these products. After completing the specified number of training epochs, the function returns the trained weights matrix C [10]. This algorithm adapts the weights of the neural network based on the input-output relationships, converging to a state where the weights represent the first M eigenvectors of the input correlation matrix, ordered by decreasing eigenvalue [10]. The iterative nature of the training process helps the network learn and capture important patterns in the input data. The convergence is guaranteed by the provided theorem, ensuring that the algorithm finds the sought-after eigenvectors directly from the data without needing to compute the correlation matrix Q in advance [10]

D. Neuromorphic Hardware

Dedicated neuromorphic devices have driven significant research in event-driven models. The emerging neural data communication standard, Address Event Representation (AER), employs packets that use addresses to indicate the source of spikes [29]. This approach efficiently serializes and multiplexes multiple neural signals onto the same lines, simplifying the converters. AER is on the path to becoming a well-defined standard, likely becoming the preferred signaling method for future neural designs. AER signaling is not limited to mixed-signal devices and can serve as a template for neural hardware [29]. The resulting system is a chip with configurable functional blocks, possibly mixed signal, embedded in a connectivity network using AER signaling. This setup utilizes a standard modeling tool chain that also employs an eventdriven model, known as the "neurokinetic" architecture [29].

E. SpiNNaker

SpiNNaker, a widely recognized neuromorphic system, is a fully custom digital, massively parallel system [1]. It consists of up to 1,036,800 ARM9 cores and 7 terabytes of RAM distributed across 57,000 nodes, each being a System-in-Package (SiP) with 18 cores and 128 megabytes of off-die Synchronous Dynamic Random Access Memory (SDRAM) [22]. The SpiNNaker engine is designed for massive parallelism with a custom interconnect communication scheme optimized for the spike-based network architecture, handling many small messages efficiently. Each SpiNNaker chip includes instruction and data memory to minimize access time for frequently used data, allowing for the cascading of chips to form larger systems. Although highly flexible in neuron models, synapse models, and learning algorithms, this flexibility incurs energy efficiency costs, consuming 10 nJ per connection as reported by Furber [1].

SpiNNaker is tailored for the "point neuron model [4]," where the dendritic structure of the neuron is ignored, and inputs are applied directly to the soma in the correct temporal order without modeling dendritic tree geometry [22]. The central idea of the SpiNNaker execution model is Address Event Representation (AER) [23][24], where spikes are asynchronous events with information conveyed solely by the spike's timing and the identity of the emitting neuron. AER is implemented by using packet-switched communication along with multicast routing in SpiNNaker, despite introducing some temporal latency, provided it remains well under 1 ms, the error is negligible for modeling biological neural systems [22]. SpiNNaker's communication between neurons utilizes the AER protocol, sending spikes represented by time and identity through a packet-switched communication fabric to connected neurons [25]. This mimics the instantaneous arrival of biological signals in the brain, allowing any neuron to map to any node, forming biological topology irrespective of the communication topology. Efficient mapping has been extensively studied to minimize transmission time between neurons [26]. Communication between ARM cores within a SpiNNaker chip is handled by a Network-on-Chip (NoC), converted to off-chip communication using packet-router modules. Six links are combined using a time-division multiplexer, streaming spikes from the local NoC, then split into six output links. Inter-node communication in SpiNNaker is facilitated via packets generated by cores, transmitted to the local router, and redirected to target cores [25]. If the destination neurons are within the same node, the local router returns the packets to the local cores; if they are in another node, the packets are sent to a neighboring node, requiring an efficient routing technique as each node connects to six other nodes [25]. Multicast routing delivers a single message copy from a source to multiple recipients over a shared communication link [27]. We present the summarized overview of SpiNNaker system in Table I, which is derived from [22].

TABLE I. SUMMARY OVERVIEW OF SPINNAKER SYSTEM

Component	Details			
System Type	Massively Parallel Multicore Computing			
Cores	Up to 1,036,800 ARM9			
Memory	7 TB RAM			
Nodes	57,000, each with 18 cores and 128 MB SDRAM			
Communication Scheme	Custom, optimized for spike-based network architecture			
Message Handling	Small messages (spikes)			
Flexibility	Neuron models, synapse models, learning algorithms, and network topology			
Energy Efficiency	Consumes 10 nJ per connection			
Neuron Model	Point Neuron Model, inputs applied directly to soma			
Execution Model	Address Event Representation (AER)			
AER Implementation	Packet-switched communication and multicast routing			
Latency	Low temporal latency, negligible error if well under 1 ms			
Communication Fabric	Electronic, resembling biological signals			
On-Chip Communication	Managed by Network-on-Chip (NoC)			
Off-Chip Communication	Converted using packet-router modules			
Packet Routing	Packets generated by cores, routed to local or neighboring nodes, efficient routing			
	technique needed for inter-node communication			

Packet switching divides the incoming data flow into small packets, which travel through the network similarly to mail, but at much higher speeds [28]. SpiNNaker employs a distributed routing subsystem to direct AER packets across the Communications Network-on-chip. Each chip contains a packet-switching router that efficiently manages and distributes these packets to all connected neurons via the Globally Asynchronous, Locally Synchronous Design and Test interconnect [29]. The routing paths are fully reprogrammable by modifying the routing table, allowing for potential dynamic reconfiguration of the model topology, though this capability remains unexplored [29].

III. EXPERIMENTAL RESULTS AND ANALYSIS

We performed several experiments to perform comparative analysis including parameters such as average convergence rate, error rate, training time and memory usage for Hebbian learning Algorithm and Generalized Hebbian learning Algorithm. Further, we improved the classification accuracy of Generalized Hebbian learning Algorithm. Detailed experiments and their results are mentioned below. We ran these algorithms on Jupyter notebook and SpiNNaker with Windows 11 (64 bit) specification.

A. Dataset description

The datasets used for the experiments described below include those from the MNIST and UCI Machine Learning repositories. The MNIST database, which stands for Modified National Institute of Standards and Technology [37], is a substantial collection of handwritten digits frequently employed for training image processing systems [38],[39]. Additionally, it is extensively utilized for training and testing purposes within the machine learning community [40],[41]. This database was formed by combining samples from NIST's original datasets [42].

The UCI Machine Learning Repository is a collection of databases, domain theories, and data generators that are widely used by the machine learning community for empirical analysis of machine learning algorithms. Established in 1987 by UCI PhD student David Aha, the repository has become a primary source of datasets for students, educators, and researchers globally. These datasets provide a valuable resource for testing and comparing the performance of various machine learning algorithms and models. The UCI repository has facilitated countless studies and advancements in the field of machine learning, contributing significantly to the community's development [30]. The Wine dataset from the UCI Machine Learning Repository consists of 178 instances, each with 13 attributes. It is used to classify wines derived from three different cultivars in Italy. The attributes include various chemical properties such as alcohol, malic acid, ash, and color intensity. The Parkinson's Disease dataset includes biomedical voice measurements from 31 people, 23 with Parkinson's disease. The dataset contains 197 instances and 23 attributes that represent different voice measurements, which can be used to distinguish healthy individuals from those with Parkinson's disease. The Heart Disease dataset is used to predict the presence of heart disease in patients. The dataset has 303 instances and 14 attributes, including age, sex, chest pain type, resting blood pressure, serum cholesterol, and maximum heart rate achieved. It helps in understanding the relationship between different factors and heart disease [30]. The Liver Disease dataset, also known as the Indian Liver Patient dataset, contains 345 instances and 7 attributes. It is used to predict liver disease in patients. Attributes include total bilirubin, direct bilirubin, alkaline phosphatase, and alanine aminotransferase. The Breast Cancer dataset is used for the diagnosis of breast cancer. It consists of 286 instances with 9 attributes, which are computed from a digitized image of a fine needle aspirate (FNA) of a breast mass. Attributes describe characteristics of the cell nuclei present in the image, such as radius, texture, perimeter, area, and smoothness [30].

B. Our Results and Analysis

The GHA and HA Algorithms were first implemented over MNIST (Modified National Institute of Standards and Technology) dataset with and without using SpiNNaker. Both Algorithms were compared with the following factors:



Fig. 1. Comparison Factors for Hebbian learning Algorithm and Generalized Hebbian learning Algorithm.

1) Quantitative Analysis: There are three metrics involved : average convergence rate is the measure of quickly algorithm converges to stable solution. Error rate is the measure of how well the network captures and reproduces the input patterns and Computational Complexity includes memory usage and training time to understand the efficiency of the algorithm. The generated results are presented in Table II.

TABLE II.	QUANTITATIVE ANALYSIS FOR HEBBIAN LEARNING VS.
GENERALIZED H	EBBIAN LEARNING ALGORITHMS FOR MNIST DATASET WITH
	AND WITHOUT SPINNAKER

MNIST	Hebbian Learning Algorithm		Generalized Hebbian Learning Algorithm	
Dataset	With SpiNNaker	Without SpiNNaker	With SpiNNaker	Without SpiNNaker
Error Rate (%)	52.78	86.11	16.67	19.44
Training Time (sec)	0.05	0.10	0.96	0.80
Memory Usage(KB)	0	0	158484	183640
Average Convergence Rate	0.1556	0.1981	7.64953	4.23490

Table II depicts a lower error rate for GHA. When the error rate is lower, it indicates that the model's predictions are closer to the actual values. Therefore, lower error rates generally signify better performance of GHA over HA. Also, a higher average convergence rate of GHA implies that the algorithm is converging towards the optimal or near-optimal solution rapidly. This is desirable as it means the algorithm requires fewer iterations or epochs to learn from the data and produce meaningful results, thus indicating better performance of GHA over HA. Higher memory usage typically suggests that the model is more complex, as it needs to store and process a larger amount of information. This complexity could arise from a higher number of parameters, larger input data, or more sophisticated operations performed during training. Therefore, higher memory usage is often associated with a more complex GHA model than HA model. The higher training time of GHA in above mentioned table suggests that the model is taking longer to learn from the data. This could be due to several reasons, one of which might be the complexity of the model. A more complex model would require more computational resources and time to train because it needs to learn intricate patterns from the data. Therefore, higher training time often indicates a more complex GHA model over HA.

2) Functional Comparison: We consider classification accuracy measure for Hebbian learning Algorithm and Generalized Hebbian learning Algorithm to evaluate and understand the findings.

We evaluated the performance of the Generalized Hebbian Learning (GHA) and Hebbian Learning (HA) algorithms using the MNIST dataset. These results are presented in Table III.

 TABLE III.
 Classification Accuracy of Hebbian Learning and Generalized Hebbian Learning Algorithm with SpiNNaker

MNIST Dataset	Hebbian Learning Algorithm	Generalized Hebbian Learning Algorithm
Classification Accuracy (%)	16.67	30.56

The classification accuracy for the GHA model was notably low, achieving only 30.56%. To enhance the performance, we extended our analysis by applying the GHA model to the UCI- ML datasets. We used the UCI-ML datasets because they are well-established, diverse, and commonly used for benchmarking machine learning algorithms [42].

TABLE IV. Classification Accuracy and Energy Consumption of UCI -ML repository on Hebbian learning Algorithm with Training set of 70% and Testing set of 30% with and without SpiNNaker

UCI Machine	Classification Accuracy (%)		Energy Consumption (Joule)	
Learning Repository	With SpiNNaker	Without SpiNNaker	With SpiNNaker	Without SpiNNaker
Wine Dataset	66.67	64.81	6200	6200
Parkinson's Disease Dataset	28.81	62.71	6800	6800
Heart Disease Dataset	62.22	55.56	10350	10350
Liver Disease Dataset	48.28	51.72	20250	20250
Breast Cancer Dataset	55.56	57.89	19900	19900

TABLE V. Classification Accuracy and Energy Consumption of UCI -ML repository on Hebbian learning Algorithm with Training set of 30% and Testing set of 70% with and without SpiNNaker

UCI Machine	Classification Accuracy (%)		Energy Consumption (Joule)	
Repository	With SpiNNaker	Without SpiNNaker	With SpiNNaker	Without SpiNNaker
Wine Dataset	80.56	72.00	2650	2650
Parkinson's Disease Dataset	52.55	54.74	2900	2900
Heart Disease Dataset	43.75	46.15	4450	4450
Liver Disease Dataset	45.81	54.19	8650	8650
Breast Cancer Dataset	38.85	47.87	8500	8500

TABLE VI. CLASSIFICATION ACCURACY AND ENERGY CONSUMPTION OF UCI -ML REPOSITORY ON HEBBIAN LEARNING ALGORITHM WITH TRAINING SET OF 50% AND TESTING SET OF 50% WITH AND WITHOUT SPINNAKER

UCI Machine	Classification Accuracy (%)		Energy Consumption (Joule)	
Learning Repository	With SpiNNaker	Without SpiNNaker	With SpiNNaker	Without SpiNNaker
Wine Dataset	41.57	34.83	4450	4450
Parkinson's Disease Dataset	72.45	70.41	4850	4850
Heart Disease Dataset	43.62	64.43	7400	7400
Liver Disease Dataset	49.66	50.34	14450	14450
Breast Cancer Dataset	52.36	42.11	14200	14200

After loading the datasets from the UCI Machine Learning Repository with different datasets, we trained and compiled the GHA (Generalized Hebbian learning Algorithm) model, with and without the use of SpiNNaker. Balancing the training and test split is crucial to ensure that the model is well-trained and accurately evaluated. Since the earlier classification accuracy of GHA came around 30.56%. Different training and testing splits such as 70/30, 50/50, 80/20, and 30/70 for different datasets of UCI Machine Learning Repository on Generalized Hebbian Algorithm were performed. The results are presented in Tables IV, V, VI, and VII, respectively.

TABLE VII.	CLASSIFICATION ACCURACY AND ENERGY CONSUMPTION OF
UCI -ML REPO	DSITORY ON HEBBIAN LEARNING ALGORITHM WITH TRAINING
SET OF 80%	AND TESTING SET OF 20% WITH AND WITHOUT SPINNAKER

UCI	Classification Accuracy (%)		Energy Consumption (Joule)	
Machine Learning Repository	With SpiNNaker	Without SpiNNaker	With SpiNNaker	Without SpiNNaker
Wine Dataset	69.44	72.80	7100	7100
Parkinson's Disease Dataset	25.64	58.97	7800	7800
Heart Disease Dataset	51.67	53.33	11850	11850
Liver Disease Dataset	51.72	43.10	23150	23150
Breast Cancer Dataset	38.60	39.47	22750	22750

During model training and compilation, we observed significant improvements in classification accuracy. The neuromorphic nature of SpiNNaker allowed for more efficient processing, which translated into better model performance. Highest classification accuracy is 80.56% with 2650 J energy consumption with 30% train set in the wine dataset from UCI machine learning repository with SpiNNaker and Highest classification accuracy is 72.80% with energy consumption of 7100 Joules with 80% train set in the wine dataset from UCI machine learning repository without SpiNNaker. Furthermore, the classification accuracy of the GHA model showed a remarkable improvement. Initially, the GHA model had a classification accuracy of 30.56% with MNIST dataset using SpiNNaker. To improve the classification accuracy of GHA, the main change was the adjustment of the training and test data split. For testing, providing the model with more data to learn from and potentially leading to better performance due to the larger training set. However, with a smaller test set, the evaluation might not be as comprehensive or reliable. Also having the split adjusted to 30% for training and 70% for testing. These improvements highlight the potential of SpiNNaker as a powerful tool for improving the classification accuracy and efficiency of machine learning models. The enhancements in the classification accuracy demonstrate the platform's capability to handle complex datasets and deliver superior results.

IV. CONCLUSION AND FUTURE WORK

Our analysis reveals that the Generalized Hebbian Algorithm (GHA) outperforms the Hebbian Learning Algorithm (HA) in key performance metrics such as error rate, classification accuracy, and average convergence rate. GHA demonstrates a superior ability to capture underlying data patterns and achieve more accurate predictions while converging to stable solutions more quickly.

However, this enhanced performance comes at the cost of increased training time and memory usage, reflecting the model's complexity. Despite these computational challenges, GHA's strengths in energy consumption and classification accuracy make it well-suited for tasks requiring high performance and rapid convergence, such as image and speech recognition. To fully capitalize on GHA's advantages, it is essential to address its computational demands through efficient resource management. Overall, GHA represents a promising advancement in neuromorphic computing, offering significant improvements in performance that are valuable for complex and large-scale applications.

Future research efforts will focus on further exploring GHA to mitigate its computational overhead while preserving its performance advantages. In this regard, we are planning to investigate FPGA-based architecture for GHA. This is mainly because our previous analyses [43], [44] illustrate that FPGAbased systems are currently the best avenue to support complex (compute/data intensive) applications and algorithms, such as linear Kalmann Filter for two-phase buck converter applications. In addition, our previous work on FPGA-based accelerators, architectures, and techniques for various compute and data-intensive applications, including data analytics/mining [45],[46],[47],[48],[49],[50],[51]; control systems [52],[53],[54],[55]; cybersecurity [56],[57]; machine learning [58], [59], [60]; communications [61]; edge computing [62],[63]; and neuromorphic computing [64]; demonstrated that FPGA-based systems are the best avenue to support and accelerate complex neuromorphic algorithms such as GHA.

Also as future work, we are planning to investigate hardware optimization techniques, such as parallel processing architectures (similar to [60,[65],[66]), partial and dynamic reconfiguration traits (as stated in [67],[68],[69]) and architectures (similar to [57],[70],[71],[72]), HDL code optimization techniques (as stated in [73],[74]), and multiported memory architectures (similar to [75],[76],[77],[78]), to further enhance the performance metrics of FPGA-based GHA, while considering the associated tradeoffs.

Overall, our study underscores the significance of Generalized Hebbian learning Algorithm in advancing biologically inspired computing paradigms towards practical implementation and real-world impact.

References

- [1] Schuman, C. D., Potok, T. E., Patton, R. M., Birdwell, J. D., Dean, M. E., Rose, G. S., & Plank, J. S. (2017). A survey of neuromorphic computing and neural networks in hardware. arXiv preprint arXiv:1705.06963.
- [2] C. Mead, "Neuromorphic electronic systems," Proceedings of the IEEE, vol. 78, no. 10, pp. 1629–1636, Oct 1990
- [3] Fausett, Laurene V. Fundamentals of neural networks: architectures, algorithms and applications. Pearson Education India, 2006.
- [4] T. Bosse, M. Hoogendoorn, Z.A. Memon, J. Treur, M. Umair, An Adaptive Model for Dynamics of Desiring and Feeling Based on Hebbian learning Algorithm. In: Y. Yao, R. Sun, T. Poggio, J. Liu, N. Zhong, J. Huang (eds) Brain Informatics. BI 2010. Lecture Notes in Computer Science, 6334. Springer, Berlin, Heidelberg (2010)
- [5] C.S.N. Brito, W. Gerstner, Nonlinear Hebbian learning Algorithm as a Unifying Principle in Receptive Field Formation. PLoS Comput. Biol. 12(9), 1–24 (2016)
- [6] Born, Jannis, Juan M. Galeazzi, and Simon M. Stringer. "Hebbian learning Algorithm of hand-centred representations in a hierarchical neural network model of the primate visual system." *PloS one* 12.5 (2017): e0178304.
- [7] Chakraverty, Snehashish, et al. "Hebbian learning Algorithm rule." Concepts of Soft Computing: Fuzzy and ANN with Programming (2019): 175-182.

- [8] Miconi, Thomas. "Hebbian learning Algorithm with gradients: Hebbian convolutional neural networks with modern deep learning frameworks." arXiv preprint arXiv:2107.01729 (2021).
- [9] https://link.springer.com/referenceworkentry/10.1007/978-1-4614-7320-6_672-1
- [10] Network, Feedforward Neural. "Optimal Unsupervised Learning in a Single-Layer Linear." *Neural Networks* 2 (1989): 459-473
- [11] McClelland, James L. "How far can you go with Hebbian learning Algorithm, and when does it lead you astray." *Processes of change in brain and cognitive development: Attention and performance xxi* 21 (2006): 33-69.
- [12] Munakata, Y., & Pfaffly, J. (2004). Hebbian learning Algorithm and development. *Developmental science*, 7(2), 141-148.
- [13] Bear, M. F., & Malenka, R. C. (1994). Synaptic plasticity: LTP and LTD. Current opinion in neurobiology, 4(3), 389-399.
- [14] Malenka, R. C., & Bear, M. F. (2004). LTP and LTD: an embarrassment of riches. *Neuron*, 44(1), 5-21.
- [15] Ito M., Sakurai M., Tongroach P. Climbing fibre induced depression of both mossy fibre responsiveness and glutamate sensitivity of cerebellar Purkinje cells. *J Physiol* 1982, 324(1): 113–134.
- [16] Ito M., Kano M. Long-lasting depression of parallel fiber-Purkinje cell transmission induced by conjunctive stimulation of parallel fibers and climbing fibers in the cerebellar cortex. *Neurosci Lett* 1982, 33(3): 253– 258.
- [17] Levy W.B., Steward O. Temporal contiguity requirements for long-term associative potentiation/depression in the hippocampus. *Neuroscience* 1983, 8(4): 791–797.
- [18] Yang, Y., Lu, J., & Zuo, Y. (2018). Changes of synaptic structures associated with learning, memory and diseases. *Brain Science Advances*, 4(2), 99-117.
- [19] Brownlee, J. (2017). How much training data is required for machine learning. *Machine Learning Mastery*.
- [20] Maffei, A. (2018). Long-term potentiation and long-term depression. In Oxford research encyclopedia of neuroscience.
- [21] Sivanandam, S. N., Sumathi, S., & Deepa, S. N. (2006). Introduction to neural networks using Matlab 6.0. (*No Title*).
- [22] S. B. Furber et al., "Overview of the SpiNNaker System Architecture," in IEEE Transactions on Computers, vol. 62, no. 12, pp. 2454-2467, Dec. 2013, doi: 10.1109/TC.2012.142. keywords: {Network architecture;Program processors;Biological system modeling;Computer architecture;Neural networks;Interconnection architectures;parallel processors;neurocomputers;real-time distributed},
- [23] M. Mahowald, An Analog VLSI System for Stereoscopic Vision. Kluwer Academic Publishers, 1994
- [24] M. Sivilotti, "Wiring Considerations in Analog VLSI Systems, with Application to Field-Programmable Networks," PhD dissertation, California Inst. of Technology, Pasadena, CA, 1991.
- [25] Ben Abdallah, A., & N. Dang, K. (2022). Communication Networks for Neuromorphic Systems. In *Neuromorphic Computing Principles and Organization* (pp. 79-126). Cham: Springer International Publishing.
- [26] Balaji A et al (2019) Mapping spiking neural networks to neuromorphic hardware. IEEE Trans Very Large Scale Integr (VLSI) Syst 28(1):76–86
- [27] M. Parsa and J. J. Garcia-Luna-Aceves, "A protocol for scalable loop-free multicast routing," in *IEEE Journal on Selected Areas in Communications*, vol. 15, no. 3, pp. 316-331, April 1997, doi: 10.1109/49.564131. keywords: {Multicast protocols;Routing protocols;Internet;Unicast;Network topology;Teleconferencing;Bandwidth;Multicast algorithms;Robustness;Costs},
- [28] L. G. Roberts, "The evolution of packet switching," in *Proceedings of the IEEE*, vol. 66, no. 11, pp. 1307-1313, Nov. 1978, doi: 10.1109/PROC.1978.11141. keywords: {Packet switching;Data communication;Bandwidth;Switching circuits;Communication switching;Telephony;Telecommunication traffic;Communication networks;Transmission lines;Telecommunication network reliability},
- [29] A. Rast, F. Galluppi, S. Davies, L. A. Plana, T. Sharp and S. Furber, "An event-driven model for the SpiNNaker virtual synaptic channel," *The*

2011 International Joint Conference on Neural Networks, San Jose, CA, USA, 2011, pp. 1967-1974, doi: 10.1109/IJCNN.2011.6033466. keywords: {Computational modeling;Algorithms;Computer aided manufacturing;Computer architecture;Switches;SDRAM;Routing},

- [30] <u>https://archive.ics.uci.edu/about</u>
- [31] Talaei Khoei, T., Ould Slimane, H., & Kaabouch, N. (2023). Deep learning: Systematic review, models, challenges, and research directions. *Neural Computing and Applications*, 35(31), 23103-23124.
- [32] Lv, C., Gu, Y., Guo, Z., Xu, Z., Wu, Y., Zhang, F., ... & Zheng, X. (2024). Towards Biologically Plausible Computing: A Comprehensive Comparison. arXiv preprint arXiv:2406.16062.
- [33] Schuman, C. D., Kulkarni, S. R., Parsa, M., Mitchell, J. P., & Kay, B. (2022). Opportunities for neuromorphic computing algorithms and applications. *Nature Computational Science*, 2(1), 10-19.
- [34] Painkras, E., Plana, L. A., Garside, J., Temple, S., Galluppi, F., Patterson, C., ... & Furber, S. B. (2013). SpiNNaker: A 1-W 18-core system-on-chip for massively-parallel neural network simulation. *IEEE Journal of Solid-State Circuits*, 48(8), 1943-1953.
- [35] Haykin, S. (1998). *Neural networks: a comprehensive foundation*. Prentice Hall PTR.
- [36] Olin-Ammentorp, W., & Cady, N. (2019). Biologically-inspired neuromorphic computing. *Science Progress*, 102(3), 261-276.
- [37] LeCun, Y. (1998). The MNIST database of handwritten digits. http://yann. lecun. com/exdb/mnist/.
- [38] https://www.vision-systems.com/home/article/16737424/support-vectormachines-speed-pattern-recognition
- [39] https://www.cis.jhu.edu/~sachin/digit/digit.html
- [40] Platt, J. (1998). Using analytic QP and sparseness to speed training of support vector machines. Advances in neural information processing systems, 11.
- [41] Grother, P. J., & Hanaoka, K. K. (1995). NIST special database 19. Handprinted forms and characters database, National Institute of Standards and Technology, 10, 69.
- [42] Olson, R. S., La Cava, W., Orzechowski, P., Urbanowicz, R. J., & Moore, J. H. (2017). PMLB: a large benchmark suite for machine learning evaluation and comparison. *BioData mining*, 10, 1-13.
- [43] D.G. Perera and K.F. Li, "Analysis of Single-Chip Hardware Support for Mobile and Embedded Applications," in Proc. of IEEE Pacific Rim Int. Conf. on Communication, Computers, and Signal Processing, (PacRim'13), pp. 369-376, Victoria, BC, Canada, August 2013.
- [44] D.G. Perera and K.F. Li, "Analysis of Computation Models and Application Characteristics Suitable for Reconfigurable FPGAs", in Proc. of 10th IEEE Int. Conf. on P2P, Parallel, Grid, Cloud, and Internet Computing, (3PGCIC'15), pp. 244-247, Krakow, Poland, Nov. 2015.
- [45] S.N. Shahrouzi and D.G. Perera, "Optimized Hardware Accelerators for Data Mining Applications on Embedded Platform: Case Study Principal Component Analysis," Elsevier Journal on Microprocessor and Microsystems (MICPRO), vol. 65, pp. 79-96, March 2019.
- [46] D.G. Perera and K.F. Li, "Embedded Hardware Solution for Principal Component Analysis," in Proc. of IEEE Pacific Rim Int. Conf. on Communication, Computers, and Signal Processing, (PacRim'11), pp.730-735, Victoria, BC, Canada, August 2011.
- [47] D.G. Perera and Kin F. Li, "Hardware Acceleration for Similarity Computations of Feature Vectors," IEEE Canadian Journal of Electrical and Computer Engineering, (CJECE), vol. 33, no. 1, pp. 21-30, Winter 2008.
- [48] D.G. Perera and K.F. Li, "On-Chip Hardware Support for Similarity Measures," in Proc. of IEEE Pacific Rim Int. Conf. on Communication, Computers, and Signal Processing, (PacRim'07), pp. 354-358, Victoria, BC, Canada, August 2007.
- [49] K.F. Li and D.G. Perera, "An Investigation of Chip-Level Hardware Support for Web Mining," in Proc. of IEEE Int. Symp. on Data Mining and Information Retrieval, (DMIR'07), pp. 341-348, Niagara Falls, ON, Canada, May 2007.
- [50] K.F. Li and D.G. Perera, "A Hardware Collective Intelligent Agent", Transactions on Computational Collective Intelligence, LNCS 7776, Springer, pp. 45-59, 2013.

- [51] J.R. Graf and D.G. Perera, "Optimizing Density-Based Ant Colony Stream Clustering Using FPGA-Based Hardware Accelerator", in Proc. Of IEEE Int. Symp. on Circuits and Systems (ISCAS'23), 5-page manuscript, Monterey, California, May 2023.
- [52] A.K. Madsen and D.G. Perera, "Efficient Embedded Architectures for Model Predictive Controller for Battery Cell Management in Electric Vehicles", EURASIP Journal on Embedded Systems, SpringerOpen, vol. 2018, article no. 2, 36-page manuscript, July 2018.
- [53] A.K. Madsen, M.S. Trimboli, and D.G. Perera, "An Optimized FPGA-Based Hardware Accelerator for Physics-Based EKF for Battery Cell Management", in Proc. of IEEE Int,I Symp, on Circuits and Systems, (ISCAS'20), 5-page manuscript, Seville, Spain, May 2020.
- [54] A.K. Madsen and D.G. Perera, "Towards Composing Efficient FPGA-Based Hardware Accelerators for Physics-Based Model Predictive Control Smart Sensor for HEV Battery Cell Management", IEEE ACCESS, (Open Access Journal in IEEE), pp. 106141-106171, 25th September 2023.
- [55] A.K. Madsen and D.G. Perera, "Composing Optimized Embedded Software Architectures for Physics-Based EKF-MPC Smart Sensor for Li-Ion Battery Cell Management", Sensors, MDPI open access journal, Intelligent Sensors Section, 21-page manuscript, vol. 22, no. 17, 26th August 2022.
- [56] A. Alkamil and D.G. Perera, "Efficient FPGA-Based Reconfigurable Accelerators for SIMON Cryptographic Algorithm on Embedded Platforms", in Proceedings of the IEEE International Conferences on Reconfigurable Computing and FPGAs, (ReConFig'19), 8-page manuscript, Cancun, Mexico, December 2019.
- [57] A. Alkamil and D.G. Perera, "Towards Dynamic and Partial Reconfigurable Hardware Architectures for Cryptographic Algorithms on Embedded Devices", IEEE Access, Open Access Journal in IEEE, vol. 8, pp: 221720 – 221742, 10th December 2020.
- [58] M.A. Mohsin and D.G. Perera, "An FPGA-Based Hardware Accelerator for K-Nearest Neighbor Classification for Machine Learning on Mobile Devices", in Proceedings of the IEEE/ACM International Symposium on Highly Efficient Accelerators and Reconfigurable Technologies, (HEART'18), 6-page manuscript, Toronto, Canada, June 2018.
- [59] S. Ramadurgam and D.G. Perera, "An Efficient FPGA-Based Hardware Accelerator for Convex Optimization-Based SVM Classifier for Machine Learning on Embedded Platforms", Electronics, MDPI open access journal, 36-page manuscript, vol. 10, no. 11, 31st May 2021.
- [60] S. Ramadurgam and D.G. Perera, "A Systolic Array Architecture for SVM Classifier for Machine Learning on Embedded Devices", in Proc. of IEEE Int. Symp. on Circuits and Systems (ISCAS'23), 5-page manuscript, Monterey, California, May 2023.
- [61] J. Nurmi and D.G. Perera, "Intelligent Cognitive Radio Architecture Applying Machine Learning and Reconfigurability" in Proc. of IEEE Nordic Circuits and Systems (NorCAS'21) Conf., 6-page manuscript, Oslo, Norway, October 2021.
- [62] D.G. Perera, "Reconfigurable Architectures for Data Analytics on Next-Generation Edge-Computing Platforms", Featured Article, IEEE Canadian Review, vol. 33, no. 1, Spring 2021. DOI: 10.1109/MICR.2021.3057144.
- [63] M.A. Mohsin, S.N. Shahrouzi, and D.G. Perera, "Composing Efficient Computational Models for Real-Time Processing on Next-Generation Edge-Computing Platforms" IEEE ACCESS, (Open Access Journal in IEEE), 30-page manuscript, 13th February 2024.
- [64] R.K. Chunduri and D.G. Perera, "Neuromorphic Sentiment Analysis Using Spiking Neural Networks", Sensors, MDPI open access journal, Sensing and Imaging Section, 24-page manuscript, vol. 23, no. 7701, 6th September 2023.

- [65] R. Raghavan and D.G. Perera, "A Fast and Scalable FPGA-Based Parallel Processing Architecture for K-Means Clustering for Big Data Analysis", in Proceedings of the IEEE Pacific Rim International Conference on Communications, Computers, and Signal Processing, (PacRim'17), pp. 1-8, Victoria, BC, Canada, August 2017.
- [66] D.G. Perera and Kin F. Li, "Parallel Computation of Similarity Measures Using an FPGA-Based Processor Array," in Proceedings of 22nd IEEE International Conference on Advanced Information Networking and Applications, (AINA'08), pp. 955-962, Okinawa, Japan, March 2008.
- [67] D.G. Perera and K.F. Li, "A Design Methodology for Mobile and Embedded Applications on FPGA-Based Dynamic Reconfigurable Hardware", International Journal of Embedded Systems, (IJES), Inderscience publishers, 23-page manuscript, vol. 11, no. 5, Sept. 2019.
- [68] D.G. Perera, "Analysis of FPGA-Based Reconfiguration Methods for Mobile and Embedded Applications", in Proceedings of 12th ACM FPGAWorld International Conference, (FPGAWorld'15), pp. 15-20, Stockholm, Sweden, September 2015.
- [69] D.G. Perera and K.F. Li, "Discrepancy in Execution Time: Static Vs. Dynamic Reconfigurable Hardware", IEEE Pacific Rim Int. Conf. on Communications, Computers, and Signal Processing, (PacRim'24), 6page manuscript, Victoria, BC, Canada, August 2024.
- [70] D.G. Perera and Kin F. Li, "FPGA-Based Reconfigurable Hardware for Compute Intensive Data Mining Applications", in Proc. of 6th IEEE Int. Conf. on P2P, Parallel, Grid, Cloud, and Internet Computing, (3PGCIC'11), pp. 100-108, Barcelona, Spain, October 2011.
- [71] D.G. Perera and Kin F. Li, "Similarity Computation Using Reconfigurable Embedded Hardware," in Proceedings of 8th IEEE International Conference on Dependable, Autonomic, and Secure Computing (DASC'09), pp. 323-329, Chengdu, China, December 2009.
- [72] S.N. Shahrouzi and D.G. Perera, "Dynamic Partial Reconfigurable Hardware Architecture for Principal Component Analysis on Mobile and Embedded Devices", EURASIP Journal on Embedded Systems, SpringerOpen, vol. 2017, article no. 25, 18-page manuscript, 21st February 2017.
- [73] S.N Shahrouzi and D.G. Perera, "HDL Code Optimization: Impact on Hardware Implementations and CAD Tools", in Proc. of IEEE Pacific Rim Int. Conf. on Communications, Computers, and Signal Processing, (PacRim'19), 9-page manuscript, Victoria, BC, Canada, August 2019.
- [74] I.D. Atwell and D.G. Perera, "HDL Code Variation: Impact on FPGA Performance Metrics and CAD Tools", IEEE Pacific Rim Int. Conf. on Communications, Computers, and Signal Processing, (PacRim'24), 6page manuscript, Victoria, BC, Canada, August 2024.
- [75] S.N. Shahrouzi, A. Alkamil, and D.G. Perera, "Towards Composing Optimized Bi-Directional Multi-Ported Memories for Next-Generation FPGAs", IEEE Access, Open Access Journal in IEEE, vol. 8, no. 1, pp. 91531-91545, 14th May 2020.
- [76] S.N. Shahrouzi and D.G. Perera, "An Efficient Embedded Multi-Ported Memory Architecture for Next-Generation FPGAs", in Proceedings of 28th Annual IEEE International Conferences on Application-Specific Systems, Architectures, and Processors, (ASAP'17), pp. 83-90, Seattle, WA, USA, July 2017.
- [77] S.N. Shahrouzi and D.G. Perera, "An Efficient FPGA-Based Memory Architecture for Compute-Intensive Applications on Embedded Devices", in Proceedings of the IEEE Pacific Rim International Conference on Communications, Computers, and Signal Processing, (PacRim'17), pp. 1-8, Victoria, BC, Canada, August 2017.
- [78] S.N. Shahrouzi and D.G. Perera, "Optimized Counter-Based Multi-Ported Memory Architectures for Next-Generation FPGAs", in Proceedings of the 31st IEEE International Systems-On-Chip Conference, (SOCC'18), pp. 106-111, Arlington, VA, Sep. 2018.