Matrix-Scheduling of QSR-Dissipative Systems

Sepehr Moalemi, and James Richard Forbes

Abstract—This paper considers gain-scheduling of QSR-dissipative subsystems using scheduling matrices. The corresponding QSR-dissipative properties of the overall matrix-gain-scheduled system, which depends on the QSR properties of the subsystems scheduled, are explicitly derived. The use of scheduling matrices is a generalization of the scalar scheduling signals used in the literature, and allows for greater design freedom when scheduling systems, such as in the case of gain-scheduled control. Furthermore, this work extends the existing gain-scheduling results to a broader class of QSR-dissipative systems. The matrix-scheduling of important special cases, such as passive, input strictly passive, output strictly passive, finite \mathcal{L}_2 gain, very strictly passive, and conic systems are presented. The proposed gain-scheduling architecture is used in the context of controlling a planar three-link robot subject to model uncertainty. A novel control synthesis technique is used to design QSR-dissipative subcontrollers that are gain-scheduled using scheduling matrices. Numerical simulation results highlight the greater design freedom of scheduling matrices, leading to improved performance.

Index Terms— Gain-scheduling, nonlinear control, QSRdissipativity.

I. INTRODUCTION

ISSIPATIVE systems theory [1] is a general and broadly applicable systems theoretic framework that characterize a dynamical system by its input-output behavior, and it strongly relates to Lyapunov and \mathcal{L}_2 stability theories [2]. As discussed in [3], the input-output dissipativity theory in [4, 5] is an extension of classical Lyapunov based dissipativity theory in [1, 6], where *a priori* information between input and output variables is not distinguished. Through the introduction of a storage function, these two approaches were unified in [7]. One such class of storage functions are quadratic supply rate (OSR) functions, which are used to analyze the stability of interconnected systems [6, 8]. A special case of QSRdissipativity for square systems, whose inputs and outputs have the same dimension, is passivity. Over the years, passivity and dissipativity have seen a wide range of applications, including exponential stabilization of dynamical systems [9], analysis of event-triggered networked control systems [10], synchronization of neural networks [11], and control of Euler-Lagrange systems [12], flexible multi-link manipulators [13], and delayed teleoperations [14].

When controlling a nonlinear system, it is possible to design linear controllers using the linearized model of a system about



(b) Gain-scheduling using scheduling matrices $\Phi_{u,i}(t)$ and $\Phi_{u,i}(t)$.

Fig. 1. Gain-scheduling of N subsystems using two different gainscheduling architectures. The scalar scheduling signals $s_i(t)$ and the scheduling matrices $\Phi_{u,i}(t)$ and $\Phi_{y,i}(t)$ are designed to interpolate between the subsystems to achieve acceptable performance.

an operating point. However, the linearized model of the plant may not adequately capture the behavior of the nonlinear system over a wide range of operating conditions. Therefore, a single linear controller designed using a single linearized plant may not realize adequate closed-loop performance, or even closed-loop stability, across a wide range of operating conditions. Gain-scheduled control is a nonlinear control technique where a set of linear subcontrollers are designed about multiple linearization points across the operating range of a nonlinear system to be controlled. The linear subcontrollers are then interpolated or scheduled to form a gain-scheduled controller that realizes acceptable performance, ideally with closed-loop stability guarantees as well.

Recently, the stability of gain-scheduled controllers has been studied through the lens of passivity [15–17], conicity [18, 19], and dissipativity [20]. The gain-scheduling architecture in Figure 1a was first introduced in [15] where it was shown that the gain-scheduling of input strictly passive (ISP) subcontrollers, as per Figure 1a, results in an overall ISP gain-scheduled controller. Using the same gain-scheduling architecture, the results of [15] were further extended to very strictly passive (VSP), finite \mathcal{L}_2 gain, and conic systems in [16–19].

Sepehr Moalemi sepehr.moalemi@mail.mcgill.ca and James Richard Forbes james.richard.forbes@mcgill.ca are with the Department of Mechanical Engineering, McGill University, 817 Sherbrooke St. W., Montreal, QC H3A 0C3, Canada.

By leveraging the passivity and conic sector theorems, respectively, the gain-scheduling results of [15–19] are used to guarantee \mathcal{L}_2 stability of robotic and aerospace systems. More recently, the gain-scheduling of QSR-dissipative subcontrollers, as per Figure 1a, was considered in [20]. The results of [20] are of particular interest, as subsystems to be gainscheduled are not required to have identical QSR-dissipative properties, nor be square. Alternate scalar-gain-scheduling architectures, accounting for actuator saturation [21] and affine parameter dependence [22], have also been studied within the context of passivity-based control.

The gain-scheduling architectures presented in [15-22] all involve scalar scheduling signals. As shown in Figure 1a, scalar scheduling signals, denoted s_i , scale the entire inputoutput map of the subsystems based on the same scheduling signal and its parameters. When controlling multiple-input multiple-output (MIMO) systems, each control variable may require a different scheduling profile to switch between subcontrollers. In [23], a row of scalar scheduling signals is used to introduce a notion of extended passive systems. However, the scheduling of special classes of passive systems, such as ISP, output strictly passive (OSP), finite \mathcal{L}_2 gain, VSP, and conic systems is not considered in [23]. More recently in [24], the gain-scheduling of VSP subcontrollers using scheduling matrices was shown to result in an overall gain-scheduled VSP controller. The extension of scheduling rows to scheduling matrices allows for coupling between the scheduling signals of different control variables through off-diagonal terms. Nevertheless, the gain-scheduling architecture presented in [24] is limited to VSP systems and cannot be used for the scheduling of a broader class of QSR-dissipative systems. This paper presents the generalized matrix-gain-scheduling architecture in Figure 1b that can be used to schedule a broader class of QSR-dissipative systems. Specifically, the contributions of this paper are as follows:

- 1) Presenting a generalized matrix-gain-scheduling architecture along with a detailed discussion on the *design* and *construction* of scheduling matrices.
- 2) Extending the gain-scheduling results of [20, 24] by considering the scheduling of a broader class of QSR-dissipative systems using the proposed matrix-gain-scheduling architecture. The scheduling of important special cases of QSR-dissipativity, such as passive, ISP, OSP, finite \mathcal{L}_2 gain, VSP, and conic systems are shown to result in an overall gain-scheduled system of the same special case.
- 3) Presenting a linear matrix inequality (LMI)-based QSRdissipative control synthesis technique that renders the feedback system asymptotically stable. This proposed technique is inspired by the LMI-based QSR-dissipative control synthesis technique in [20] and the linearquadratic-Gaussian (LQG) design in [25].

The remainder of this paper is as follows. Notation and preliminaries are presented in Section II. The gain-scheduling architecture, including properties and construction of scheduling matrices, is introduced in Section III. Two theorems classifying the QSR-dissipativity of a matrix-scheduled system composed of N QSR-dissipative subsystems are discussed in Section IV. In Section V, the special cases of QSR-dissipativity are used to compare the results of the proposed theorems to existing results in the literature. An application of the proposed gainscheduling architecture, complete with the proposed LMIbased QSR-dissipative control synthesis technique is presented in Section VI, followed by closing remarks in Section VII.

II. PRELIMINARIES

A. Notation

Scalars are denoted $\alpha \in \mathbb{R}$, matrices are denoted $\mathbf{A} \in \mathbb{R}^{m \times n}$, and column matrices are denoted $\mathbf{v} \in \mathbb{R}^n$. The identity and zero matrices are 1 and 0, respectively. The set \mathbb{S}^n denotes the set of real symmetric matrices of size $n \times n$. The set of symmetric negative semidefinite matrices is denoted as \mathbb{S}^n_- , the set of symmetric negative definite matrices is denoted as \mathbb{S}^n_- , the set of symmetric positive semidefinite matrices is denoted as \mathbb{S}^n_+ , and the set of symmetric positive definite matrices is denoted as \mathbb{S}^n_+ , and the set of symmetric positive definite matrices is denoted as \mathbb{S}^n_{++} [26]. The maximum eigenvalue and singular value of \mathbf{A} are denoted as $\lambda_{\max}(\mathbf{A})$ and $\sigma_{\max}(\mathbf{A})$, respectively. The notation diag(\cdot) denotes a block diagonal matrix of its arguments. Operators are denoted by \mathcal{G} , and index sets are denoted by \mathcal{N} .

B. Definitions

Definition 1 (Induced Matrix Norm [27]): Let $\mathbf{A} \in \mathbb{R}^{m \times n}$, then the matrix norm induced by a vector *p*-norm is defined as $\|\mathbf{A}\|_p = \sup_{\mathbf{x} \neq \mathbf{0}} \|\mathbf{A}\mathbf{x}\|_p / \|\mathbf{x}\|_p$. The special case of p = 2 can be written as $\|\mathbf{A}\|_2 = \sqrt{\lambda_{\max}(\mathbf{A}^{\mathsf{T}}\mathbf{A})} = \sigma_{\max}(\mathbf{A})$.

Definition 2 (Truncated Signal [28]): Given a signal \mathbf{u} : $\mathbb{R}_{\geq 0} \to \mathbb{R}^n$, the truncated signal, \mathbf{u}_T , is defined as $\mathbf{u}_T(t) = \mathbf{u}(t)$ for $0 \leq t \leq T$ and $\mathbf{u}_T(t) = \mathbf{0}$ for $t > T \in \mathbb{R}_{\geq 0}$.

Definition 3 (Truncated Inner Product [28]): Given signals $\mathbf{u}, \mathbf{y} : \mathbb{R}_{\geq 0} \to \mathbb{R}^n$, the truncated inner product is defined as $\langle \mathbf{u}, \mathbf{y} \rangle_T = \langle \mathbf{u}_T, \mathbf{y}_T \rangle = \int_0^T \mathbf{u}^{\mathsf{T}}(t) \mathbf{y}(t) \, \mathrm{d}t, \forall T \in \mathbb{R}_{\geq 0}$.

Definition 4 (\mathcal{L}_p Signal Spaces [28]): Given a piecewise continuous signal $\mathbf{u} : \mathbb{R}_{\geq 0} \to \mathbb{R}^n$, $\mathbf{u} \in \mathcal{L}_{2e}$ if $\|\mathbf{u}\|_{2T}^2 = \langle \mathbf{u}, \mathbf{u} \rangle_T < \infty$, $\forall T \in \mathbb{R}_{\geq 0}$. Additionally, $\mathbf{u} \in \mathcal{L}_{\infty}$ if $\|\mathbf{u}\|_{\infty}^2 = \sup_{t \in \mathbb{R}_{\geq 0}} \max_{i=1,...,n} |u_i(t)| < \infty$.

Definition 5 (QSR-Dissipativity [6, 20]): Consider a causal continuous-time system, $\mathcal{G} : \mathcal{L}_{2e} \to \mathcal{L}_{2e}$, defined by

$$\dot{\mathbf{x}}(t) = \mathbf{f}(\mathbf{x}(t), \mathbf{u}(t)), \qquad \mathbf{y}(t) = \mathbf{h}(\mathbf{x}(t), \mathbf{u}(t)),$$

where $\mathbf{x} \in \mathbb{R}^{n_x}$, $\mathbf{y} \in \mathbb{R}^{n_y}$, and $\mathbf{u} \in \mathbb{R}^{n_u}$. The system \mathcal{G} is QSR-dissipative with matrices $\mathbf{Q} \in \mathbb{S}^{n_y}$, $\mathbf{S} \in \mathbb{R}^{n_y \times n_u}$, and $\mathbf{R} \in \mathbb{S}^{n_u}$ if for all $\mathbf{u} \in \mathcal{L}_{2e}$ and $T \in \mathbb{R}_{\geq 0}$ there exists a storage function $V : \mathbb{R}^{n_x} \to \mathbb{R}_{>0}$ such that

$$\langle \mathbf{y}, \mathbf{Q}\mathbf{y} \rangle_T + 2 \langle \mathbf{y}, \mathbf{S}\mathbf{u} \rangle_T + \langle \mathbf{u}, \mathbf{R}\mathbf{u} \rangle_T \ge V(\mathbf{x}(T)) - V(\mathbf{x}(0)).$$



Fig. 2. Gain-scheduled system \overline{g} , composed of N parallel QSRdissipative subsystems. The input and output of each subsystem are scheduled as per (1) via the matrix multiplication between the scheduling matrices $\Phi_{u,i}(t)$ and $\Phi_{y,i}(t)$, and their corresponding signals $\mathbf{u}(t)$ and $\mathbf{y}_i(t)$, respectively.

The special cases of QSR-dissipativity are

- passive if $\mathbf{Q} = \mathbf{0}$, $\mathbf{S} = \frac{1}{2}\mathbf{1}$, and $\mathbf{R} = \mathbf{0}$,
- *input strictly passive (ISP)* if $\mathbf{Q} = \mathbf{0}$, $\mathbf{S} = \frac{1}{2}\mathbf{1}$, and $\mathbf{R} = -\delta \mathbf{1}$, where $\delta \in \mathbb{R}_{>0}$,
- *output strictly passive (OSP)* if $\mathbf{Q} = -\varepsilon \mathbf{1}$, $\mathbf{S} = \frac{1}{2}\mathbf{1}$, and $\mathbf{R} = \mathbf{0}$, where $\varepsilon \in \mathbb{R}_{>0}$,
- finite \mathcal{L}_2 gain if $\mathbf{Q} = -1$, $\mathbf{S} = \mathbf{0}$, and $\mathbf{R} = \gamma^2 \mathbf{1}$, where $\gamma \in \mathbb{R}_{>0}$,
- very strictly passive (VSP) if $\mathbf{Q} = -\varepsilon \mathbf{1}$, $\mathbf{S} = \frac{1}{2}\mathbf{1}$, and $\mathbf{R} = -\delta \mathbf{1}$, where $\delta, \varepsilon \in \mathbb{R}_{>0}$, and
- conic if $\mathbf{Q} = -\mathbf{1}$, $\mathbf{S} = \frac{a+b}{2}\mathbf{1} = c\mathbf{1}$, and $\mathbf{R} = -ab\mathbf{1} = (r^2 c^2)\mathbf{1}$, where $a, b \in \mathbb{R}$ represent lower and upper conic bounds, while $c \in \mathbb{R}$ and $r \in \mathbb{R}_{>0}$ represent the center and radius of the conic sector, respectively.

III. MATRIX-GAIN-SCHEDULING ARCHITECTURE

This section presents the matrix-gain-scheduling architecture in Figure 2. The scheduling functions to be designed take the form of scheduling matrices, allowing for greater design freedom compared to the scalar scheduling signals in [15–22].

Consider the gain-scheduled system, \mathcal{G} , in Figure 2, composed of N parallel QSR-dissipative subsystems, $\mathcal{G}_1, \ldots, \mathcal{G}_N$. The subsystems could be linear or nonlinear, and their input-output maps are given by $\mathbf{y}_i(t) = \mathcal{G}_i(\mathbf{u}_i(t))$ for $i \in \mathcal{N} = \{1, \ldots, N\}$. The input and output of each subsystem are scheduled in a multiplicative manner such that

$$\mathbf{u}_i(t) = \mathbf{\Phi}_{u,i}(t)\mathbf{u}(t),\tag{1a}$$

$$\bar{\mathbf{y}}_i(t) = \mathbf{\Phi}_{y,i}(t)\mathbf{y}_i(t), \tag{1b}$$

where $\Phi_{u,i} \in \mathbb{R}^{n_u \times n_u}$ and $\Phi_{y,i} \in \mathbb{R}^{n_y \times n_y}$ are the scheduling matrices, $\mathbf{u}_i, \mathbf{u} \in \mathbb{R}^{n_u}$, and $\mathbf{y}_i, \mathbf{y} \in \mathbb{R}^{n_y}$, for all $i \in \mathcal{N}$. The gain-scheduled system, $\bar{\boldsymbol{\mathcal{G}}}$, input-output map can be written in terms of the individual subsystems inputs, outputs, and scheduling matrices as

$$\mathbf{y}(t) = \sum_{i \in \mathcal{N}} \bar{\mathbf{y}}_i(t) = \sum_{i \in \mathcal{N}} \mathbf{\Phi}_{y,i}(t) \mathbf{y}_i(t)$$
$$= \sum_{i \in \mathcal{N}} \mathbf{\Phi}_{y,i}(t) \mathcal{G}_i(\mathbf{u}_i(t))$$
$$= \sum_{i \in \mathcal{N}} \mathbf{\Phi}_{y,i}(t) \mathcal{G}_i(\mathbf{\Phi}_{u,i}(t) \mathbf{u}(t)). \quad (2)$$

Based on the QSR-dissipativity property in Definition 5, the input and output of each subsystem must satisfy

$$\langle \mathbf{y}_i, \mathbf{Q}_i \mathbf{y}_i \rangle_T + 2 \langle \mathbf{y}_i, \mathbf{S}_i \mathbf{u}_i \rangle_T + \langle \mathbf{u}_i, \mathbf{R}_i \mathbf{u}_i \rangle_T \ge V_i, \ \forall T \in \mathbb{R}_{\ge 0}, \ (3)$$

with $V_i = V_i(\mathbf{x}(T)) - V_i(\mathbf{x}(0))$, $\mathbf{Q} \in \mathbb{S}^{n_y}$, $\mathbf{S} \in \mathbb{R}^{n_y \times n_u}$, and $\mathbf{R} \in \mathbb{S}^{n_u}$ for all $i \in \mathcal{N}$ and $\mathbf{u}_i \in \mathcal{L}_{2e}$.

The objective is to *design* the scheduling matrices $\Phi_{u,i}(t)$ and $\Phi_{y,i}(t)$ for $i \in \mathcal{N}$, such that the gain-scheduling of the *N* QSR-dissipative subsystems results in an overall gainscheduled QSR-dissipative system. Furthermore, if all subsystems belong to the same special case of QSR-dissipativity as defined in Definition 5, the scheduling matrix design should result in the overall gain-scheduled system belonging to that same special case.

A. Scheduling Matrix Properties

Consider the set of scheduling matrices $\Phi_{j,i}(t) \in \mathbb{R}^{n_j \times n_j}$ for $j \in \{u, y\}$ and $i \in \mathcal{N}$. With abuse of set notation, denote the time dependent set, $\mathcal{F}_j(t)$, as the index set of all the respective full rank scheduling matrices at time $t \in \mathbb{R}_{\geq 0}$. That is, for $t \in \mathbb{R}_{\geq 0}$ and $j \in \{u, y\}$,

$$\mathcal{F}_{j}(t) = \left\{ i \in \mathcal{N} \mid \operatorname{rank}\left(\boldsymbol{\Phi}_{j,i}(t)\right) = n_{j} \right\}.$$
(4)

Definition 6 (Active Scheduling Matrices): Given a gainscheduled system of the type shown in Figure 2 with scheduling matrices $\Phi_{j,i}(t) \in \mathbb{R}^{n_j \times n_j}$ for $j \in \{u, y\}$ and $i \in \mathcal{N}$, the scheduling matrices are said to be

- *active* if at all times, there exists at least one nonzero scheduling matrix, meaning $\forall t \in \mathbb{R}_{\geq 0}$, $\exists i \in \mathcal{N}$ such that $\Phi_{j,i}(t) \neq \mathbf{0}$ and
- strongly active if at all times, there exists at least one full rank scheduling matrix, meaning ∀t ∈ ℝ_{≥0}, ∃i ∈ N such that rank(Φ_{j,i}(t)) = n_j. Using set notation, this can be written as ∀t ∈ ℝ_{>0}, F_j(t) ≠ Ø.

When considering the special cases of QSR-dissipativity in Section V, the active and strongly active cases of scheduling matrices are invoked to correctly quantify the overall QSRdissipativity of the gain-scheduled system.

For the remainder of this paper the input and output scheduling matrices are assumed to be bounded in the sense that

$$\sup_{t\in\mathbb{R}_{\geq 0}}\left\|\boldsymbol{\Phi}_{j,i}(t)\right\|_{2} = \sup_{t\in\mathbb{R}_{\geq 0}}\sigma_{j,i}(t) = \left\|\sigma_{j,i}\right\|_{\infty} < \infty, \quad (5)$$

for all $j \in \{u, y\}$ and $i \in \mathcal{N}$, where $\sigma_{j,i}(t)$ is the largest singular value of $\Phi_{j,i}(t)$. This can be thought of as an extension of the \mathcal{L}_{∞} space in Definition 4 for piecewise continuous matrix functions $\Phi_{j,i} : \mathbb{R}_{\geq 0} \to \mathbb{R}^{n_j \times n_j}$, for $j \in \{u, y\}$ and $i \in \mathcal{N}$. Finally, for simplicity, the scheduling matrices are assumed to be explicitly time-dependent, though a similar analysis can be used to account for dependence on other signals or parameters.

B. Scheduling Matrix Construction

This subsection presents the construction of the scheduling matrices such that they satisfy the following pseudocommutativity condition. Definition 7 (Pseudo-Commuting Scheduling Matrices): Consider a gain-scheduled system of type shown in Figure 2 with scheduling matrices $\Phi_{u,i}(t) \in \mathbb{R}^{n_u \times n_u}$ and $\Phi_{y,i}(t) \in \mathbb{R}^{n_y \times n_y}$ for $i \in \mathcal{N}$. Given a series of matrices $\mathbf{S}_i \in \mathbb{R}^{n_y \times n_u}$ for $i \in \mathcal{N}$, the scheduling matrices are said to pseudo-commute with \mathbf{S}_i , if they satisfy

$$\boldsymbol{\Phi}_{y,i}^{\mathsf{T}}(t)\mathbf{S}_{i} = \mathbf{S}_{i}\boldsymbol{\Phi}_{u,i}(t), \quad \forall t \in \mathbb{R}_{\geq 0}, \forall i \in \mathcal{N}.$$
(6)

In Section IV, for each QSR-dissipative subsystem \mathcal{G}_i satisfying (3) with \mathbf{Q}_i , \mathbf{S}_i , and \mathbf{R}_i , this pseudo-commutativity condition is invoked by assuming the corresponding scheduling matrices of \mathcal{G}_i pseudo-commute with \mathbf{S}_i . It will now be shown that the scheduling matrices can be constructed to satisfy the pseudo-commutativity condition in (6) for any matrix $\mathbf{S}_i \in \mathbb{R}^{n_y \times n_u}$.

Consider an arbitrary matrix $\mathbf{S}_i \in \mathbb{R}^{n_y \times n_u}$ and the corresponding input scheduling matrix $\mathbf{\Phi}_{u,i}(t) \in \mathbb{R}^{n_u \times n_u}$ and output scheduling matrix $\mathbf{\Phi}_{y,i}(t) \in \mathbb{R}^{n_y \times n_y}$. For the trivial case of $\mathbf{S}_i = \mathbf{0}$, the $n_u^2 + n_y^2$ entries of the input and output scheduling matrices can be independently designed to pseudo-commute with $\mathbf{S}_i = \mathbf{0}$. Now, consider an arbitrary nonzero matrix $\mathbf{S}_i \in \mathbb{R}^{n_y \times n_u}$ and its singular value decomposition (SVD) given by

$$\mathbf{S}_{i} = \mathbf{U}_{i} \begin{bmatrix} \boldsymbol{\Sigma}_{1,i} & \mathbf{0} \\ \mathbf{0} & \mathbf{0} \end{bmatrix} \mathbf{V}_{i}^{\mathsf{T}},\tag{7}$$

where $\mathbf{U}_i \in \mathbb{R}^{n_y \times n_y}$, $\mathbf{\Sigma}_{1,i} \in \mathbb{S}^{\varrho_i}$, $\mathbf{V}_i \in \mathbb{R}^{n_u \times n_u}$, and $\varrho_i = \operatorname{rank}(\mathbf{S}_i) \geq 1$. As shown in Lemma 4 found in the Appendix, the scheduling matrices $\Phi_{u,i}(t) \in \mathbb{R}^{n_u \times n_u}$ and $\Phi_{y,i}(t) \in \mathbb{R}^{n_y \times n_y}$ satisfy the pseudo-commutativity condition in (6) if and only if there exists $\mathbf{Z}_{11,i}(t)$, $\mathbf{Z}_{21,i}(t)$, $\mathbf{Z}_{22,i}(t)$, $\mathbf{W}_{21,i}(t)$, and $\mathbf{W}_{22,i}(t)$, with appropriate dimensions, such that

$$\boldsymbol{\Phi}_{u,i}(t) = \mathbf{V}_i \begin{bmatrix} \mathbf{Z}_{11,i}(t) & \mathbf{0} \\ \mathbf{Z}_{21,i}(t) & \mathbf{Z}_{22,i}(t) \end{bmatrix} \mathbf{V}_i^{\mathsf{T}}, \tag{8a}$$

$$\boldsymbol{\Phi}_{y,i}(t) = \mathbf{U}_{i} \begin{bmatrix} \boldsymbol{\Sigma}_{1,i}^{-1} \mathbf{Z}_{11,i}^{\mathsf{T}}(t) \boldsymbol{\Sigma}_{1,i} & \mathbf{0} \\ \mathbf{W}_{21,i}(t) & \mathbf{W}_{22,i}(t) \end{bmatrix} \mathbf{U}_{i}^{\mathsf{T}}.$$
 (8b)

Therefore, for any arbitrary matrix $\mathbf{S}_i \in \mathbb{R}^{n_y \times n_u}$ with $\varrho_i = \operatorname{rank}(\mathbf{S}_i) \geq 1$, the scheduling matrices can be designed using the $n_u^2 + n_y^2 + \varrho_i^2 - \varrho_i(n_u + n_y)$ entries of the independent design variables $\mathbf{Z}_{11,i}(t)$, $\mathbf{Z}_{21,i}(t)$, $\mathbf{Z}_{22,i}(t)$, $\mathbf{W}_{21,i}(t)$, and $\mathbf{W}_{22,i}(t)$ to satisfy the pseudo-commutativity condition in (6).

It is also useful to consider the implications of the pseudocommutativity condition in (6) for the special case of a square matrix $\mathbf{S}_i \in \mathbb{R}^{n \times n}$. If \mathbf{S}_i is square and full rank, the scheduling matrices can be designed using the similarity transformation

$$\mathbf{\Phi}_{u,i}(t) = \mathbf{S}_i^{-1} \mathbf{\Phi}_{y,i}^{\mathsf{T}}(t) \mathbf{S}_i, \quad \forall t \in \mathbb{R}_{\geq 0}, \forall i \in \mathcal{N},$$
(9)

where $\Phi_{y,i}(t) \in \mathbb{R}^{n \times n}$ are free design variables. Additionally, since similarity transformations preserve eigenvalues, the input scheduling matrix can be made full rank by requiring the output scheduling matrix to be full rank. For the case of $\mathbf{S}_i = c_i \mathbf{1}$ with $c_i \in \mathbb{R} \setminus \{0\}$, the pseudo-commutativity in (6) simplifies to $\Phi_{u,i}(t) = \Phi_{y,i}^{\mathsf{T}}(t)$, which is exactly the scheduling-matrix architecture presented in [24].



Fig. 3. Gain-scheduling of the i^{th} subsystem, \mathcal{G}_i . The input and output of \mathcal{G}_i are scheduled as per (1) via the matrix multiplication between the scheduling matrices $\Phi_{u,i}(t)$ and $\Phi_{y,i}(t)$, and their corresponding signals $\mathbf{u}(t)$ and $\mathbf{y}_i(t)$, respectively.

IV. MAIN CONTRIBUTION

This section presents the QSR-dissipativity of the matrixgain-scheduled system in Figure 2 for two cases.

- Case 1: All N subsystems are QSR-dissipative with Q_i ∈ S^{ny}₋₋.
- Case 2: All N subsystems are QSR-dissipative with $\mathbf{Q}_i \in \mathbb{S}_{-}^{n_y}$ and share a common $\mathbf{S}_i = \mathbf{S} \in \mathbb{R}^{n_y \times n_u}$.

Doing so extends the cases discussed in [20] while generalizing the scheduling approach by allowing the scheduling signals to be scheduling matrices.

A. Case 1: All N Subsystems are QSR-Dissipative with $\mathbf{Q}_i \in \mathbb{S}_{--}^{n_y}$

Lemma 1: Consider the subsystem \mathcal{G}_i in Figure 3 being QSR-dissipative with $\mathbf{Q}_i \in \mathbb{S}_{--}^{n_y}$, $\mathbf{S}_i \in \mathbb{R}^{n_y \times n_u}$, and $\mathbf{R}_i \in \mathbb{S}^{n_u}$. The gain-scheduled subsystem $\bar{\mathcal{G}}_i$ is QSR-dissipative, provided its corresponding scheduling matrices pseudo-commute with \mathbf{S}_i .

Proof: Applying the Rayleigh inequality to the QSRdissipativity property in (3) yields

$$\tilde{V}_i \le \lambda_{\max}(\mathbf{Q}_i) \|\mathbf{y}_i\|_{2T}^2 + 2 \langle \mathbf{y}_i, \mathbf{S}_i \mathbf{u}_i \rangle_T + \lambda_{\max}(\mathbf{R}_i) \|\mathbf{u}_i\|_{2T}^2,$$
(10)

where $\lambda_{\max}(\mathbf{Q}_i) \in \mathbb{R}_{<0}$ and $\lambda_{\max}(\mathbf{R}_i) \in \mathbb{R}$ since $\mathbf{Q}_i \in \mathbb{S}_{--}^{n_y}$ and $\mathbf{R}_i \in \mathbb{S}^{n_y}$, respectively. Moreover, based on the pseudocommutativity condition in Definition 7, it follows that $\mathbf{\Phi}_{y,i}^{\mathsf{T}}(t)\mathbf{S}_i = \mathbf{S}_i\mathbf{\Phi}_{u,i}(t)$ for all $t \in \mathbb{R}_{\geq 0}$. Consider the term $\langle \mathbf{y}_i, \mathbf{S}_i \mathbf{u}_i \rangle_T$ in (10). Using the relation in (1), it follows that

Additionally, define $\sigma_{y,i}(t)$ as the largest singular value of $\Phi_{y,i}(t)$. From (1b), it follows that

$$\begin{aligned} \|\bar{\mathbf{y}}_{i}\|_{2T}^{2} &= \left\|\mathbf{\Phi}_{y,i}\mathbf{y}_{i}\right\|_{2T}^{2} \leq \int_{0}^{T} \sigma_{y,i}^{2}(t) \|\mathbf{y}_{i}(t)\|_{2}^{2} \,\mathrm{d}t \\ &\leq \bar{\sigma}_{y,i}^{2} \|\mathbf{y}_{i}\|_{2T}^{2}, \end{aligned} \tag{12}$$

where

$$\bar{\sigma}_{y,i} = \sup_{t \in \mathbb{R}_{\ge 0}} \sigma_{y,i}(t). \tag{13}$$

Furthermore, $\bar{\sigma}_{y,i} \in \mathbb{R}_{>0}$, provided there exists a $t \in \mathbb{R}_{\geq 0}$ such that $\Phi_{y,i}(t) \neq 0$. This condition is satisfied by design, since if this subsystem is being included in the parallel interconnection, it means at some point in time, its output must be nonzero, and therefore, its output scheduling matrix cannot be zero for all time. Additionally, $\bar{\sigma}_{y,i} < \infty$, since as

per (5), the scheduling matrices are assumed to be bounded. Consequently, rearranging (12) yields

$$\frac{1}{\bar{\sigma}_{y,i}^2} \|\bar{\mathbf{y}}_i\|_{2T}^2 \le \|\mathbf{y}_i\|_{2T}^2.$$
(14)

Since $\lambda_{\max}(\mathbf{Q}_i) \in \mathbb{R}_{<0}$, substituting (11) and (14) into (10) leads to

$$\tilde{V}_{i} \leq \frac{\lambda_{\max}(\mathbf{Q}_{i})}{\bar{\sigma}_{y,i}^{2}} \|\bar{\mathbf{y}}_{i}\|_{2T}^{2} + 2\langle \bar{\mathbf{y}}_{i}, \mathbf{S}_{i}\mathbf{u} \rangle_{T} + \lambda_{\max}(\mathbf{R}_{i}) \|\mathbf{u}_{i}\|_{2T}^{2}.$$
(15)

Given that $\bar{\sigma}_{y,i}^2 \in \mathbb{R}_{>0}$, (15) can be written as

$$\begin{aligned} \bar{\sigma}_{y,i}^2 \tilde{V}_i &\leq -\varepsilon_i \|\bar{\mathbf{y}}_i\|_{2T}^2 + 2\bar{\sigma}_{y,i}^2 \langle \bar{\mathbf{y}}_i, \mathbf{S}_i \mathbf{u} \rangle_T \\ &+ \lambda_{\max}(\mathbf{R}_i) \bar{\sigma}_{y,i}^2 \|\mathbf{u}_i\|_{2T}^2, \end{aligned} \tag{16}$$

where

$$\varepsilon_i = |\lambda_{\max}(\mathbf{Q}_i)| = -\lambda_{\max}(\mathbf{Q}_i) > 0.$$
 (17)

Since other than symmetry, there are no restrictions on \mathbf{R}_i , the sign of its maximum eigenvalue is unknown. Denoting $\sigma_{u,i}(t)$ and $\nu_{u,i}(t)$ as the largest and smallest singular values of $\Phi_{u,i}(t)$, respectively, define

$$\delta_{i} = \begin{cases} \lambda_{\max}(\mathbf{R}_{i})\bar{\sigma}_{y,i}^{2}\bar{\sigma}_{u,i}^{2}, & \text{if } \lambda_{\max}(\mathbf{R}_{i}) > 0, \\ \lambda_{\max}(\mathbf{R}_{i})\bar{\sigma}_{y,i}^{2}\bar{\nu}_{u,i}^{2}, & \text{if } \lambda_{\max}(\mathbf{R}_{i}) \le 0, \end{cases}$$
(18)

where

$$\bar{\sigma}_{u,i} = \sup_{t \in \mathbb{R}_{\ge 0}} \sigma_{u,i}(t), \qquad \bar{\nu}_{u,i} = \inf_{t \in \mathbb{R}_{\ge 0}} \nu_{u,i}(t). \tag{19}$$

If \mathbf{S}_i is full rank and $n_u \leq n_y$, the pseudo-commutativity property suggests $\bar{\sigma}_{u,i} \in \mathbb{R}_{>0}$, since $\bar{\sigma}_{y,i} \in \mathbb{R}_{>0}$. If \mathbf{S}_i is rank deficient or $n_y < n_u$, it is possible to have $\bar{\sigma}_{u,i} \in \mathbb{R}_{\geq 0}$, since the output scheduling matrices can be designed with $\Phi_{u,i}(t) = \mathbf{0}$ for all $t \in \mathbb{R}_{\geq 0}$. Additionally, $\bar{\nu}_{u,i} \in \mathbb{R}_{\geq 0}$, since the scheduling matrix $\Phi_{u,i}(t)$ may note full rank at all times. Consider the term $\lambda_{\max}(\mathbf{R}_i)\bar{\sigma}_{y,i}^2 ||\mathbf{u}_i||_{2T}^2$ in (16). Using (1a) and the definition of δ_i in (18), it follows that

$$\lambda_{\max}(\mathbf{R}_i)\bar{\sigma}_{y,i}^2 \|\mathbf{u}_i\|_{2T}^2 = \lambda_{\max}(\mathbf{R}_i)\bar{\sigma}_{y,i}^2 \|\mathbf{\Phi}_{u,i}\mathbf{u}\|_{2T}^2$$
$$\leq \delta_i \|\mathbf{u}\|_{2T}^2.$$
(20)

Substituting (20) into (16) yields

$$\hat{V}_{i} \leq -\varepsilon_{i} \|\bar{\mathbf{y}}_{i}\|_{2T}^{2} + 2\bar{\sigma}_{y,i}^{2} \langle \bar{\mathbf{y}}_{i}, \mathbf{S}_{i}\mathbf{u} \rangle_{T} + \delta_{i} \|\mathbf{u}\|_{2T}^{2} \qquad (21)$$

$$= \langle \bar{\mathbf{y}}_{i}, \bar{\mathbf{Q}}_{i}\bar{\mathbf{y}}_{i} \rangle_{T} + 2 \langle \bar{\mathbf{y}}_{i}, \bar{\mathbf{S}}_{i}\mathbf{u} \rangle_{T} + \langle \mathbf{u}, \bar{\mathbf{R}}_{i}\mathbf{u} \rangle_{T},$$

where $\hat{V}_i = \bar{\sigma}_{y,i}^2 \tilde{V}_i$, and

$$\bar{\mathbf{Q}}_i = -\varepsilon_i \mathbf{1}, \qquad \bar{\mathbf{S}}_i = \bar{\sigma}_{y,i}^2 \mathbf{S}_i, \qquad \bar{\mathbf{R}}_i = \delta_i \mathbf{1}.$$
 (22)

Consequently, the gain-scheduled subsystem \mathcal{G}_i is QSRdissipative with $\bar{\mathbf{Q}}_i \in \mathbb{S}_{--}^{n_y}$, $\bar{\mathbf{S}}_i \in \mathbb{R}^{n_y \times n_u}$, and $\bar{\mathbf{R}}_i \in \mathbb{S}^{n_u}$ as defined in (22).

Theorem 1: Given that each subsystem \mathcal{G}_i for $i \in \mathcal{N}$ is QSR-dissipative with $\mathbf{Q}_i \in \mathbb{S}_{--}^{n_y}$, $\mathbf{S}_i \in \mathbb{R}^{n_y \times n_u}$, and $\mathbf{R}_i \in \mathbb{S}^{n_u}$, the gain-scheduled system $\overline{\mathcal{G}}$ in Figure 2 is QSR-dissipative, provided the scheduling matrices $\Phi_{u,i}(t)$ and $\Phi_{y,i}(t)$ pseudo-commute with \mathbf{S}_i .

Proof: Following Lemma 1, each scheduled subsystem $\bar{\boldsymbol{\mathcal{G}}}_i$ is QSR-dissipative with $\bar{\mathbf{Q}}_i \in \mathbb{S}_{--}^{n_y}$, $\bar{\mathbf{S}}_i \in \mathbb{R}^{n_y \times n_u}$, and $\bar{\mathbf{R}}_i \in$

 \mathbb{S}^{n_u} defined in (22). Furthermore, $\bar{\sigma}_{y,i}$, ε_i , and δ_i are given by (13), (17), and (18), respectively. Adding and subtracting $\bar{\sigma}_{y,i}^4/\varepsilon_i \|\mathbf{S}_i \mathbf{u}\|_{2T}^2$ from (21) and factoring leads to

$$\hat{V}_{i} \leq -\varepsilon_{i} \left\| \bar{\mathbf{y}}_{i} - \frac{\bar{\sigma}_{y,i}^{2}}{\varepsilon_{i}} \mathbf{S}_{i} \mathbf{u} \right\|_{2T}^{2} + \delta_{i} \|\mathbf{u}\|_{2T}^{2} + \frac{\bar{\sigma}_{y,i}^{4}}{\varepsilon_{i}} \|\mathbf{S}_{i} \mathbf{u}\|_{2T}^{2}.$$
(23)

To simplify further analysis, let

$$\tilde{\mathbf{y}}_{i}(t) = \bar{\mathbf{y}}_{i}(t) - \frac{\bar{\sigma}_{y,i}^{2}}{\varepsilon_{i}} \mathbf{S}_{i} \mathbf{u}(t), \qquad (24)$$

for $i \in \mathcal{N}$ and denote $\sigma_{\mathbf{S}_i}$ as the largest singular value of \mathbf{S}_i . Substituting (24) into (23) and using the Rayleigh inequality results in

$$\hat{V}_{i} \leq -\varepsilon_{i} \|\tilde{\mathbf{y}}_{i}\|_{2T}^{2} + \left(\delta_{i} + \frac{\bar{\sigma}_{y,i}^{4} \sigma_{\mathbf{S}_{i}}^{2}}{\varepsilon_{i}}\right) \|\mathbf{u}\|_{2T}^{2}.$$
 (25)

Summing (25) over all $i \in \mathcal{N}$, it follows that

$$\sum_{i\in\mathcal{N}} \hat{V}_{i} \leq -\sum_{i\in\mathcal{N}} \varepsilon_{i} \|\tilde{\mathbf{y}}_{i}\|_{2T}^{2} + \sum_{i\in\mathcal{N}} \left(\delta_{i} + \frac{\bar{\sigma}_{y,i}^{4}\sigma_{\mathbf{S}_{i}}^{2}}{\varepsilon_{i}}\right) \|\mathbf{u}\|_{2T}^{2}$$
$$\leq -\varepsilon_{\min} \sum_{i\in\mathcal{N}} \|\tilde{\mathbf{y}}_{i}\|_{2T}^{2} + \bar{\delta} \|\mathbf{u}\|_{2T}^{2}, \tag{26}$$

where

$$\varepsilon_{\min} = \min_{i \in \mathcal{N}} \varepsilon_i > 0, \quad \bar{\delta} = \sum_{i \in \mathcal{N}} \left(\delta_i + \frac{\bar{\sigma}_{y,i}^4 \sigma_{\mathbf{S}_i}^2}{\varepsilon_i} \right).$$
(27)

Rewriting the summation in (26) as a vector norm yields

$$\sum_{i \in \mathcal{N}} \hat{V}_i \leq -\varepsilon_{\min} \left\| \begin{bmatrix} \|\tilde{\mathbf{y}}_1\|_{2T} \\ \vdots \\ \|\tilde{\mathbf{y}}_N\|_{2T} \end{bmatrix} \right\|_2^2 + \bar{\delta} \|\mathbf{u}\|_{2T}^2.$$
(28)

Applying the inequality in Lemma 5, which is a special case of the Cauchy–Schwartz inequality, to (28) results in

$$\sum_{i \in \mathcal{N}} \hat{V}_{i} \leq -\frac{\varepsilon_{\min}}{N} \left\langle \begin{bmatrix} 1\\ \vdots\\ 1 \end{bmatrix}, \begin{bmatrix} \|\tilde{\mathbf{y}}_{1}\|_{2T}\\ \vdots\\ \|\tilde{\mathbf{y}}_{N}\|_{2T} \end{bmatrix} \right\rangle^{2} + \bar{\delta} \|\mathbf{u}\|_{2T}^{2}$$
$$= -\frac{\varepsilon_{\min}}{N} \left(\sum_{i \in \mathcal{N}} \|\tilde{\mathbf{y}}_{i}\|_{2T} \right)^{2} + \bar{\delta} \|\mathbf{u}\|_{2T}^{2}.$$
(29)

Multiplying both sides of (29) by N and applying the triangle inequality yields

$$N\sum_{i\in\mathcal{N}}\hat{V}_{i}\leq -\varepsilon_{\min}\left\|\sum_{i\in\mathcal{N}}\tilde{\mathbf{y}}_{i}\right\|_{2T}^{2}+N\bar{\delta}\|\mathbf{u}\|_{2T}^{2}.$$
 (30)

Substituting back (24) into (30) and defining $\tilde{V} = N \sum_{i \in \mathcal{N}} \hat{V}_i$ results in

$$\tilde{V} \le -\varepsilon_{\min} \left\| \sum_{i \in \mathcal{N}} \left(\bar{\mathbf{y}}_i - \frac{\bar{\sigma}_{y,i}^2}{\varepsilon_i} \mathbf{S}_i \mathbf{u} \right) \right\|_{2T}^2 + N \bar{\delta} \|\mathbf{u}\|_{2T}^2.$$
(31)

Defining $\bar{\mathbf{S}} = \sum_{i \in \mathcal{N}} (\bar{\sigma}_{y,i}^2 / \varepsilon_i) \mathbf{S}_i$ and using (2), it follows from (31) that

$$\begin{split} \tilde{V} &\leq -\varepsilon_{\min} \left\| \mathbf{y} - \bar{\mathbf{S}} \mathbf{u} \right\|_{2T}^{2} + N \bar{\delta} \| \mathbf{u} \|_{2T}^{2} \\ &= -\varepsilon_{\min} \left(\left\| \mathbf{y} \right\|_{2T}^{2} - 2 \left\langle \mathbf{y}, \bar{\mathbf{S}} \mathbf{u} \right\rangle_{T} + \left\| \bar{\mathbf{S}} \mathbf{u} \right\|_{2T}^{2} \right) + N \bar{\delta} \| \mathbf{u} \|_{2T}^{2}. \end{split}$$
(32)

Applying the Rayleigh inequality to (32) and defining $\nu_{\bar{s}}$ as the smallest singular value of \bar{s} , it follows that

$$\tilde{V} \leq -\varepsilon_{\min} \|\mathbf{y}\|_{2T}^{2} + 2\varepsilon_{\min} \left\langle \mathbf{y}, \bar{\mathbf{S}}\mathbf{u} \right\rangle_{T} + \left(N\bar{\delta} - \varepsilon_{\min}\nu_{\bar{\mathbf{S}}}^{2} \right) \|\mathbf{u}\|_{2T}^{2}$$
$$= -\varepsilon_{\min} \|\mathbf{y}\|_{2T}^{2} + 2\varepsilon_{\min} \left\langle \mathbf{y}, \bar{\mathbf{S}}\mathbf{u} \right\rangle_{T} + \hat{\delta} \|\mathbf{u}\|_{2T}^{2}, \qquad (33)$$

where $\hat{\delta} = N\bar{\delta} - \varepsilon_{\min}\nu_{\bar{\mathbf{S}}}^2$. Alternatively, (33) can be written as

$$V \leq \langle \mathbf{y}, \mathbf{Q}\mathbf{y} \rangle_T + 2 \langle \mathbf{y}, \mathbf{S}\mathbf{u} \rangle_T + \langle \mathbf{u}, \mathbf{R}\mathbf{u} \rangle_T,$$

where

$$\mathbf{Q} = -\varepsilon_{\min} \mathbf{1}, \qquad \mathbf{S} = \varepsilon_{\min} \bar{\mathbf{S}}, \qquad \mathbf{R} = \hat{\delta} \mathbf{1}.$$
 (34)

Additionally, (34) can be written in terms of $\bar{\sigma}_{y,i}$, ε_i , and δ_i , given by (13), (17), and (18), respectively, as follows:

$$\mathbf{Q} = -\min_{i \in \mathcal{N}} (\varepsilon_i) \mathbf{1},\tag{35a}$$

$$\mathbf{S} = \min_{i \in \mathcal{N}} (\varepsilon_i) \sum_{i \in \mathcal{N}} \frac{\bar{\sigma}_{y,i}^2}{\varepsilon_i} \mathbf{S}_i,$$
(35b)

$$\mathbf{R} = \left(N \sum_{i \in \mathcal{N}} \left(\delta_i + \frac{\bar{\sigma}_{y,i}^4 \sigma_{\mathbf{S}_i}^2}{\varepsilon_i} \right) - \min_{i \in \mathcal{N}} (\varepsilon_i) \nu_{\mathbf{S}}^2 \right) \mathbf{1}, \quad (35c)$$

where $\sigma_{\mathbf{S}_i}$ is the largest singular value of \mathbf{S}_i and $\nu_{\bar{\mathbf{S}}}$ is the smallest singular value of $\bar{\mathbf{S}} = \sum_{i \in \mathcal{N}} (\bar{\sigma}_{y,i}^2 / \varepsilon_i) \mathbf{S}_i$. Therefore, the gain-scheduled system $\bar{\boldsymbol{\mathcal{G}}}$ is QSR-dissipative with $\mathbf{Q} \in \mathbb{S}_{-}^{n_y}$, $\mathbf{S} \in \mathbb{R}^{n_y \times n_u}$, and $\mathbf{R} \in \mathbb{S}^{n_u}$ as defined in (35).

B. Case 2: All N Subsystems are QSR-Dissipative with $\mathbf{Q}_i \in \mathbb{S}_{-}^{n_y}$ and Share a Common $\mathbf{S}_i = \mathbf{S} \in \mathbb{R}^{n_y \times n_u}$

Lemma 2: Given each subsystem \mathcal{G}_i for $i \in \mathcal{N}$ is QSRdissipative with $\mathbf{Q}_i \in \mathbb{S}_{-}^{n_y}$, there exists a $\mathbf{Q} = -\varepsilon \mathbf{1}$ with $\varepsilon \in \mathbb{R}_{\geq 0}$ such that the gain-scheduled system $\overline{\mathcal{G}}$ in Figure 2 satisfies $\sum_{i \in \mathcal{N}} \langle \mathbf{y}_i, \mathbf{Q}_i \mathbf{y}_i \rangle_T \leq \langle \mathbf{y}, \mathbf{Q} \mathbf{y} \rangle_T$, provided the output scheduling matrices are active.

Proof: Using the Rayleigh inequality, it follows that

$$\sum_{i \in \mathcal{N}} \langle \mathbf{y}_i, \mathbf{Q}_i \mathbf{y}_i \rangle_T \leq -\sum_{i \in \mathcal{N}} \varepsilon_i \|\mathbf{y}_i\|_{2T}^2$$
$$\leq -\varepsilon_{\min} \sum_{i \in \mathcal{N}} \|\mathbf{y}_i\|_{2T}^2, \qquad (36)$$

where $\varepsilon_i = -\lambda_{\max}(\mathbf{Q}_i) \ge 0$ and $\varepsilon_{\min} = \min_{i \in \mathcal{N}} \varepsilon_i \ge 0$. Additionally, the summation in (2) can be rewritten as the matrix-vector multiplication $\mathbf{y}(t) = \mathbf{\Psi}(t)\mathbf{v}(t)$, where

$$\boldsymbol{\Psi}(t) = \begin{bmatrix} \boldsymbol{\Phi}_{y,1}(t) & \cdots & \boldsymbol{\Phi}_{y,N}(t) \end{bmatrix}, \quad \boldsymbol{\upsilon}(t) = \begin{bmatrix} \mathbf{y}_1(t) \\ \vdots \\ \mathbf{y}_N(t) \end{bmatrix}. \quad (37)$$

Consequently, by defining $\sigma_{\Psi}(t)$ as the largest singular value of $\Psi(t)$ and applying the Rayleigh inequality to $\|\Psi(t)\upsilon(t)\|_2^2$, it follows that

$$\|\mathbf{y}(t)\|_{2}^{2} = \|\mathbf{\Psi}(t)\boldsymbol{\upsilon}(t)\|_{2}^{2} \le \sigma_{\mathbf{\Psi}}^{2}(t)\|\boldsymbol{\upsilon}(t)\|_{2}^{2}.$$
 (38)

Moreover, $\sigma_{\Psi}(t) \in \mathbb{R}_{>0}$, provided the output scheduling matrices are active, that is, $\forall t \in \mathbb{R}_{\geq 0}$, $\exists i \in \mathcal{N}$ such that $\Phi_{y,i}(t) \neq \mathbf{0}$, and therefore, $\Psi^{\mathsf{T}}(t)\Psi(t) \in \mathbb{S}^{N \times n_y}_+$ is nonzero. Additionally,

$$\begin{split} \sigma_{\Psi}^2(t) &\leq \operatorname{tr} \Big(\Psi^{\mathsf{T}}(t) \Psi(t) \Big) = \sum_{i \in \mathcal{N}} \operatorname{tr} \Big(\Phi_{y,i}^{\mathsf{T}}(t) \Phi_{y,i}(t) \Big) \\ &\leq n_y \sum_{i \in \mathcal{N}} \lambda_{\max} \Big(\Phi_{y,i}^{\mathsf{T}}(t) \Phi_{y,i}(t) \Big) \\ &= n_y \sum_{i \in \mathcal{N}} \sigma_{y,i}^2(t). \end{split}$$

Therefore, $\sup_{t \in \mathbb{R}_{\geq 0}} \sigma_{\Psi}^2(t) < \infty$ since the output scheduling matrices are assumed to be bounded as per (5). Consequently, rearranging (38) yields

$$\frac{1}{\sigma_{\Psi}^{2}(t)} \|\mathbf{y}(t)\|_{2}^{2} \leq \|\boldsymbol{v}(t)\|_{2}^{2} = \sum_{i \in \mathcal{N}} \|\mathbf{y}_{i}(t)\|_{2}^{2}.$$
 (39)

Since $\lambda_{\max}(\mathbf{Q}_i) \in \mathbb{R}_{\leq 0}$, substituting (39) into (36), it follows that

$$\begin{split} \sum_{i \in \mathcal{N}} \langle \mathbf{y}_i, \mathbf{Q}_i \mathbf{y}_i \rangle_T &\leq -\varepsilon_{\min} \int_0^T \frac{1}{\sigma_{\mathbf{\Psi}}^2(t)} \|\mathbf{y}(t)\|_2^2 \,\mathrm{d}t \\ &\leq -\frac{\varepsilon_{\min}}{\bar{\sigma}_{\mathbf{\Psi}}^2} \int_0^T \|\mathbf{y}(t)\|_2^2 \,\mathrm{d}t \\ &= -\varepsilon \|\mathbf{y}\|_{2T}^2 = \langle \mathbf{y}, \mathbf{Q}\mathbf{y} \rangle_T \,, \end{split}$$

where

$$\bar{\sigma}_{\Psi} = \sup_{t \in \mathbb{R}_{\geq 0}} \sigma_{\Psi}(t) > 0, \qquad \varepsilon = \frac{\varepsilon_{\min}}{\bar{\sigma}_{\Psi}^2} \ge 0, \qquad (40)$$

and $\mathbf{Q} = -\varepsilon \mathbf{1} \in \mathbb{S}_{-}^{n_y}$.

Lemma 3: Given each subsystem \mathcal{G}_i for $i \in \mathcal{N}$ is QSRdissipative with $\mathbf{R}_i \in \mathbb{S}^{n_u}$, there exists an $\mathbf{R} = \delta \mathbf{1}$ with $\delta \in \mathbb{R}$ such that the gain-scheduled system, $\overline{\mathcal{G}}$, in Figure 2 satisfies $\sum_{i \in \mathcal{N}} \langle \mathbf{u}_i, \mathbf{R}_i \mathbf{u}_i \rangle_T \leq \langle \mathbf{u}, \mathbf{R} \mathbf{u} \rangle_T$.

Proof: Using the Rayleigh inequality, it follows that

$$\sum_{i \in \mathcal{N}} \langle \mathbf{u}_i, \mathbf{R}_i \mathbf{u}_i \rangle_T \le \sum_{i \in \mathcal{N}} \lambda_{\max}(\mathbf{R}_i) \| \mathbf{u}_i \|_{2T}^2.$$
(41)

Defining the index sets

$$\mathcal{R}_{>0} = \{ i \in \mathcal{N} \mid \lambda_{\max}(\mathbf{R}_i) > 0 \}, \tag{42a}$$

$$\mathcal{R}_{<0} = \{ i \in \mathcal{N} \mid \lambda_{\max}(\mathbf{R}_i) < 0 \}, \tag{42b}$$

$$\mathcal{R}_0 = \{ i \in \mathcal{N} \mid \lambda_{\max}(\mathbf{R}_i) = 0 \}, \qquad (42c)$$

it follows that

$$\sum_{i \in \mathcal{N}} \lambda_{\max}(\mathbf{R}_i) = \sum_{i \in \mathcal{R}_{>0}} \lambda_{\max}(\mathbf{R}_i) + \sum_{i \in \mathcal{R}_{<0}} \lambda_{\max}(\mathbf{R}_i).$$
(43)

Expanding (41) using (43) results in

$$\sum_{i \in \mathcal{N}} \langle \mathbf{u}_{i}, \mathbf{R}_{i} \mathbf{u}_{i} \rangle_{T} \leq \sum_{i \in \mathcal{R}_{>0}} \lambda_{\max}(\mathbf{R}_{i}) \|\mathbf{u}_{i}\|_{2T}^{2} + \sum_{i \in \mathcal{R}_{<0}} \lambda_{\max}(\mathbf{R}_{i}) \|\mathbf{u}_{i}\|_{2T}^{2}.$$
(44)

Substituting the relation in (1a) into (44), it follows that

$$\sum_{i \in \mathcal{N}} \langle \mathbf{u}_{i}, \mathbf{R}_{i} \mathbf{u}_{i} \rangle_{T} \leq \delta_{\max} \sum_{i \in \mathcal{R}_{>0}} \left\| \mathbf{\Phi}_{u,i} \mathbf{u} \right\|_{2T}^{2} - \delta_{\min} \sum_{i \in \mathcal{R}_{<0}} \left\| \mathbf{\Phi}_{u,i} \mathbf{u} \right\|_{2T}^{2},$$
(45)

where

$$\delta_i = |\lambda_{\max}(\mathbf{R}_i)|, \quad \delta_{\max} = \max_{i \in \mathcal{R}_{>0}} \delta_i, \quad \delta_{\min} = \min_{i \in \mathcal{R}_{<0}} \delta_i.$$

Expanding (45) and using the Rayleigh inequality yields

$$\begin{split} \sum_{i \in \mathcal{N}} \langle \mathbf{u}_i, \mathbf{R}_i \mathbf{u}_i \rangle_T &\leq \delta_{\max} \sum_{i \in \mathcal{R}_{>0}} \int_0^T \sigma_{u,i}^2(t) \|\mathbf{u}(t)\|_2^2 \,\mathrm{d}t \\ &- \delta_{\min} \sum_{i \in \mathcal{R}_{<0}} \int_0^T \nu_{u,i}^2(t) \|\mathbf{u}(t)\|_2^2 \,\mathrm{d}t \\ &\leq \delta_{\max} \bar{\sigma}_u \int_0^T \|\mathbf{u}(t)\|_2^2 \,\mathrm{d}t \\ &- \delta_{\min} \bar{\nu}_u \int_0^T \|\mathbf{u}(t)\|_2^2 \,\mathrm{d}t \\ &= \delta \|\mathbf{u}\|_{2T}^2 = \langle \mathbf{u}, \mathbf{R}\mathbf{u} \rangle_T \,, \end{split}$$

where

$$\bar{\sigma}_u = \sup_{t \in \mathbb{R}_{\geq 0}} \sum_{i \in \mathcal{R}_{> 0}} \sigma_{u,i}^2(t) \geq 0, \tag{46a}$$

$$\bar{\nu}_u = \inf_{t \in \mathbb{R}_{\ge 0}} \sum_{i \in \mathcal{R}_{< 0}} \nu_{u,i}^2(t) \ge 0, \tag{46b}$$

$$\delta = \delta_{\max} \bar{\sigma}_u - \delta_{\min} \bar{\nu}_u, \qquad (46c)$$

and $\mathbf{R} = \delta \mathbf{1}$.

Since Lemma 3 considers the most general case of subsystems being QSR-dissipative with $\mathbf{R}_i \in \mathbb{S}^{n_u}$ and imposes no further restriction on the eigenvalues of \mathbf{R}_i , the sign of δ in (46c) cannot be determined without additional information.

Corollary 1: Consider the gain-scheduled system, $\overline{\mathcal{G}}$, in Figure 2 where each subsystem \mathcal{G}_i for $i \in \mathcal{N}$ is QSR-dissipative. Given the sets $\mathcal{R}_{>0}$, $\mathcal{R}_{<0}$, and \mathcal{R}_0 defined in (42), the special cases of Lemma 3 are as follows:

- 1) $\delta \in \mathbb{R}_{>0}$ provided $\mathcal{R}_{>0} \neq \emptyset$ and $\mathcal{R}_{<0} = \emptyset$.
 - 1.1) $\delta \in \mathbb{R}_{>0}$, provided further $\exists t \in \mathbb{R}_{\geq 0}$ and an $i \in \mathcal{R}_{>0}$ such that $\Phi_{u,i}(t) \neq \mathbf{0}$.
- 2) $\delta \in \mathbb{R}_{<0}$ provided $\mathcal{R}_{>0} = \emptyset$ and $\mathcal{R}_{<0} \neq \emptyset$.
- 2.1) $\delta \in \mathbb{R}_{<0}$, provided further $\mathcal{R}_{<0} \cap \mathcal{F}_u(t) \neq \emptyset$, $\forall t \in \mathbb{R}_{\geq 0}$, meaning for $i \in \mathcal{R}_{<0}$, the nonempty subset of input scheduling matrices, $\Phi_{u,i}(t)$, is strongly active.

3) $\delta = 0$ provided $\mathcal{R}_{>0} = \emptyset$ and $\mathcal{R}_{<0} = \emptyset$.

Proof: The proof for each case follows from the definition of δ in (46c) and the sets $\mathcal{R}_{>0}$, $\mathcal{R}_{<0}$, and \mathcal{R}_0 in (42). The strictly positive case follows from the fact that $\bar{\sigma}_u \in \mathbb{R}_{>0}$, provided there exists a $t \in \mathbb{R}_{\geq 0}$ and an $i \in \mathcal{R}_{>0}$ such that $\Phi_{u,i}(t) \neq \mathbf{0}$. The strictly negative case follows from

$$\bar{\nu}_u = \inf_{t \in \mathbb{R}_{\geq 0}} \sum_{i \in \mathcal{R}_{<0}} \nu_{u,i}^2(t) = \inf_{t \in \mathbb{R}_{\geq 0}} \sum_{i \in \mathcal{R}_{<0} \cap \mathcal{F}_u(t)} \nu_{u,i}^2(t) > 0,$$

provided that $\mathcal{R}_{<0} \cap \mathcal{F}_u(t) \neq \emptyset$ for all $t \in \mathbb{R}_{>0}$.

Theorem 2: Given each subsystem \mathcal{G}_i for $i \in \mathcal{N}$ is QSRdissipative with $\mathbf{Q}_i \in \mathbb{S}_{-}^{n_y}$, $\mathbf{S}_i = \mathbf{S} \in \mathbb{R}^{n_y \times n_u}$, and $\mathbf{R}_i \in \mathbb{S}^{n_u}$, the gain-scheduled system, $\overline{\mathcal{G}}$, in Figure 2 is QSR-dissipative, provided the output scheduling matrices are active, and the scheduling matrices pseudo-commute with \mathbf{S} .

Proof: Summing (3) over all N subsystems yields

$$\sum_{i \in \mathcal{N}} \tilde{V}_{i} \leq \sum_{i \in \mathcal{N}} \langle \mathbf{y}_{i}, \mathbf{Q}_{i} \mathbf{y}_{i} \rangle_{T} + 2 \sum_{i \in \mathcal{N}} \langle \mathbf{y}_{i}, \mathbf{S} \mathbf{u}_{i} \rangle_{T} + \sum_{i \in \mathcal{N}} \langle \mathbf{u}_{i}, \mathbf{R}_{i} \mathbf{u}_{i} \rangle_{T}.$$
(47)

Consider the term $\sum_{i \in \mathcal{N}} \langle \mathbf{y}_i, \mathbf{S}\mathbf{u}_i \rangle_T$. Given the scheduling matrices pseudo-commute with respect to **S** such that $\Phi_{y,i}^{\mathsf{T}}(t)\mathbf{S} = \mathbf{S}\Phi_{u,i}(t)$, and using (1) and (2), it follows that

$$\sum_{i \in \mathcal{N}} \langle \mathbf{y}_i, \mathbf{S} \mathbf{u}_i \rangle_T = \sum_{i \in \mathcal{N}} \left\langle \mathbf{y}_i, \mathbf{S} \mathbf{\Phi}_{u,i} \mathbf{u} \right\rangle_T$$
$$= \sum_{i \in \mathcal{N}} \left\langle \mathbf{y}_i, \mathbf{\Phi}_{y,i}^\mathsf{T} \mathbf{S} \mathbf{u} \right\rangle_T$$
$$= \sum_{i \in \mathcal{N}} \left\langle \mathbf{\Phi}_{y,i} \mathbf{y}_i, \mathbf{S} \mathbf{u} \right\rangle_T = \left\langle \mathbf{y}, \mathbf{S} \mathbf{u} \right\rangle_T. \quad (48)$$

Consequently, using Lemmas 2 and 3 and substituting (48) into (47) yields

$$\tilde{V} = \sum_{i \in \mathcal{N}} \tilde{V}_i \leq \left< \mathbf{y}, \mathbf{Q} \mathbf{y} \right>_T + 2 \left< \mathbf{y}, \mathbf{S} \mathbf{u} \right>_T + \left< \mathbf{u}, \mathbf{R} \mathbf{u} \right>_T,$$

where $\mathbf{Q} = -\varepsilon \mathbf{1}$ and $\mathbf{R} = \delta \mathbf{1}$, with ε and δ defined as per (40) and (46), respectively. Therefore, the gain-scheduled system, $\overline{\mathbf{G}}$, is QSR-dissipative with $\mathbf{Q} \in \mathbb{S}_{-}^{n_y}$, $\mathbf{S} \in \mathbb{R}^{n_y \times n_u}$, and $\mathbf{R} \in \mathbb{S}^{n_u}$.

V. DISCUSSION

In this section, the special cases of QSR-dissipativity, as defined in Definition 5, are discussed for the gain-scheduled system $\bar{\boldsymbol{\mathcal{G}}}$ in Figure 2. For each case, to compare the scheduling matrix results presented in Theorems 1 and 2 with the existing literature on scalar scheduling signals, the special case of $\Phi_{u,i}(t) = s_i(t)\mathbf{1}$ and $\Phi_{y,i}(t) = s_i(t)\mathbf{1}$ for all $i \in \mathcal{N}$ is considered and referred to as the *base case*.

Moreover, the matrix-scheduling architecture in [24] includes additional constant scaling parameters, $\alpha_i \in \mathbb{R}_{>0}$, for each subsystem \mathcal{G}_i . These scaling parameters are not considered in this work to maintain focus on the proposed generalized matrix-gain-scheduling architecture. However, they can easily be incorporated into the results presented in Theorems 1 and 2. Therefore, when comparing the results of this work with [24], the scaling parameters are assumed to be $\alpha_i = 1$ for all $i \in \mathcal{N}$.

A. Subsystems are Passive

Consider the case where each subsystem \mathcal{G}_i for $i \in \mathcal{N}$ is passive with $\mathbf{Q}_i = \mathbf{0}$, $\mathbf{S}_i = \frac{1}{2}\mathbf{1}$, and $\mathbf{R}_i = \mathbf{0}$. Theorem 2 suggests $\overline{\mathcal{G}}$ is QSR-dissipative with $\mathbf{Q} = \mathbf{0}$, $\mathbf{S} = \frac{1}{2}\mathbf{1}$, and $\mathbf{R} = \mathbf{0}$, and therefore is passive, provided the scheduling matrices pseudo-commute with \mathbf{S} . Note, Theorem 2 further requires the output scheduling matrices to be active. However,

this condition can be relaxed for the passive case since $\mathbf{Q}_i = \mathbf{0}$, for all $i \in \mathcal{N}$. As discussed in Section III-B, for this choice of \mathbf{S} , the pseudo-commutativity condition leads to $\Phi_{u,i}(t) = \Phi_{y,i}^{\mathsf{T}}(t)$ for all $i \in \mathcal{N}$ and $t \in \mathbb{R}_{\geq 0}$. Therefore, the gain-scheduling of passive subsystems using scheduling matrices results in an overall passive gain-scheduled system. For the base case, this result is consistent with the results shown in [28, Theorem 8.2], which is again shown in [20, Theorem 2] and [18, Corollary 6.1.2].

B. Subsystems are ISP

Consider the case where each subsystem \mathcal{G}_i for $i \in \mathcal{N}$ is ISP with $\mathbf{Q}_i = \mathbf{0}$, $\mathbf{S}_i = \frac{1}{2}\mathbf{1}$, and $\mathbf{R}_i = -\delta_i\mathbf{1}$, where $\delta_i \in \mathbb{R}_{>0}$. Theorem 2 suggests $\overline{\mathcal{G}}$ is QSR-dissipative with

$$\mathbf{Q} = \mathbf{0}, \qquad \mathbf{S} = \frac{1}{2}\mathbf{1}, \qquad \mathbf{R} = -\delta\mathbf{1},$$

where

$$\delta = \min_{i \in \mathcal{N}} (\delta_i) \inf_{t \in \mathbb{R}_{\ge 0}} \sum_{i \in \mathcal{N}} \nu_{u,i}^2(t) \ge 0,$$
(49)

provided the scheduling matrices pseudo-commute with $\mathbf{S} = \frac{1}{2}\mathbf{1}$. Furthermore, if the scheduling matrices are designed to be strongly active, Corollary 1 with $\mathcal{R}_{<0} = \mathcal{N}$ suggests $\bar{\boldsymbol{\mathcal{G}}}$ is ISP with

$$\delta = \delta_{\min} \inf_{t \in \mathbb{R}_{\geq 0}} \sum_{i \in \mathcal{F}_u(t)} \nu_{u,i}^2(t) > 0, \tag{50}$$

where $\delta_{\min} = \min_{i \in \mathcal{N}} \delta_i$. Note, as per the definition of $\mathcal{F}_u(t)$ in (4), $s_i(t) = 0$ for $i \in \mathcal{N} \setminus \mathcal{F}_u(t)$. The ISP coefficient in (50), exactly recovers the matrix scheduling of ISP subsystems result shown in [24, Theorem 1]. For the base case, the ISP coefficient δ in (50) simplifies to

$$\delta = \delta_{\min} \inf_{t \in \mathbb{R}_{\ge 0}} \sum_{i \in \mathcal{F}_u(t)} |s_i(t)|^2, \tag{51}$$

matching the results in [15, Theorem 1]. In [20, Theorem 2] a slightly different bound on δ is provided as

$$\delta = \sum_{i \in \mathcal{N}} \delta_i \nu_i^2, \tag{52}$$

where $\nu_i = \inf_{t \in \mathbb{R}_{\geq 0}} |s_i(t)| \geq 0$ for all $i \in \mathcal{N}$. The authors of [20] argue that (52) is a less conservative bound on δ compared to [15, Theorem 1], since it involves the summation of δ_i across all subsystems instead of the minimum value of δ_i . However, (52) also involves the summation of infima, which is more conservative than the infimum of the summation in (51). Therefore, it is not guaranteed that (52) is less conservative than (51). Additionally, to maintain the ISP property of the subsystems, [20, Theorem 2] requires the existence of at least one $i \in \mathcal{N}$ such that $\nu_i > 0$. This means that there exists at least one scheduled subsystem $\bar{\boldsymbol{\mathcal{G}}}_i$ with $i \in \mathcal{N}$ that is always active in the sense that $s_i(t) \neq 0$ for all $t \in \mathbb{R}_{>0}$. Depending on the application, one may need to freely switch between the scheduled subsystems, which may not be possible if at least one subsystem is always active. In practice, it can be argued that by setting the scheduling signal to an arbitrary small value, the scheduled subsystem can be made inactive while still retaining the ISP property of the gain-scheduled system.

Contrary to [20], at any time, [15, Theorem 1] requires at least one scheduling signal to be nonzero. This ensures that for all time $t \in \mathbb{R}_{\geq 0}$, there exists at least one $i \in \mathcal{N}$ such that $\mathbf{u}_i(t)$ and $\bar{\mathbf{y}}_i(t)$ are nonzero, provided that $\mathbf{u}(t)$ and $\mathbf{y}_i(t)$ are nonzero. Here, the scheduling matrices are required to pseudo-commute with **S** and be strongly active to ensure for all time $t \in \mathbb{R}_{\geq 0}$, there exists at least one $i \in \mathcal{N}$ such that $\Phi_{u,i}(t) = \Phi_{y,i}^{\mathsf{T}}(t)$ is full rank. The existence of a full rank scheduling matrix at each time ensures that there exists at least one $i \in \mathcal{N}$ such that $\mathbf{u}_i(t)$ and $\bar{\mathbf{y}}_i(t)$ are nonzero, provided that $\mathbf{u}(t)$ and $\mathbf{y}_i(t)$ are nonzero, which can be thought of as direct extension of the aforementioned condition in [15, Theorem 1].

C. Subsystems are OSP

Consider the case where each subsystem \mathcal{G}_i for $i \in \mathcal{N}$ is OSP with $\mathbf{Q}_i = -\varepsilon_i \mathbf{1}$, $\mathbf{S}_i = \frac{1}{2}\mathbf{1}$, and $\mathbf{R}_i = \mathbf{0}$, where $\varepsilon_i \in \mathbb{R}_{>0}$. Theorem 1 suggests $\overline{\mathcal{G}}$ is QSR-dissipative with

$$\mathbf{Q} = -\varepsilon_{\min} \mathbf{1}, \qquad \mathbf{S} = \varepsilon_{\min} \sum_{i \in \mathcal{N}} \frac{\bar{\sigma}_{y,i}^2}{2\varepsilon_i} \mathbf{1},$$
$$\mathbf{R} = \left(N \sum_{i \in \mathcal{N}} \left(\frac{\bar{\sigma}_{y,i}^4}{4\varepsilon_i} \right) - \varepsilon_{\min} \left(\sum_{i \in \mathcal{N}} \frac{\bar{\sigma}_{y,i}^2}{2\varepsilon_i} \right)^2 \right) \mathbf{1},$$

provided the scheduling matrices pseudo-commute with $\mathbf{S} = \frac{1}{2}\mathbf{1}$. Notice $\mathbf{R} \in \mathbb{S}^{n_u}_+$ as a consequence of Lemma 5, since

$$N\sum_{i\in\mathcal{N}}\frac{\bar{\sigma}_{y,i}^4}{4\varepsilon_i} = N\sum_{i\in\mathcal{N}}\varepsilon_i\frac{\bar{\sigma}_{y,i}^4}{4\varepsilon_i^2} \ge \left(\sum_{i\in\mathcal{N}}\sqrt{\varepsilon_i}\frac{\bar{\sigma}_{y,i}^2}{2\varepsilon_i}\right)^2$$
$$\ge \left(\min_{i\in\mathcal{N}}\left(\sqrt{\varepsilon_i}\right)\sum_{i\in\mathcal{N}}\frac{\bar{\sigma}_{y,i}^2}{2\varepsilon_i}\right)^2 = \varepsilon_{\min}\left(\sum_{i\in\mathcal{N}}\frac{\bar{\sigma}_{y,i}^2}{2\varepsilon_i}\right)^2,$$

with $\mathbf{R} = \mathbf{0}$ if and only if $\overline{\sigma}_{y,i}^2/\sqrt{\varepsilon_i} = k$, for some positive constant $k \in \mathbb{R}_{>0}$ and for all $i \in \mathcal{N}$. Therefore, Theorem 1 does not provide a tight bound on \mathbf{R} for the OSP case. Similarly, for the base case, [20, Theorem 1] also leads to $\mathbf{R} \in \mathbb{S}_+^{n_u}$, with $\mathbf{R} = \mathbf{0}$ if and only if $\sup_{t \in \mathbb{R}_{\geq 0}} |s_i(t)|^2/\varepsilon_i = k$, for some positive constant $k \in \mathbb{R}_{>0}$, for all $i \in \mathcal{N}$. However, Theorem 2 suggests $\overline{\mathcal{G}}$ is QSR-dissipative with

$$\mathbf{Q} = -\varepsilon \mathbf{1}, \qquad \mathbf{S} = \frac{1}{2}\mathbf{1}, \qquad \mathbf{R} = \mathbf{0},$$

and therefore is OSP with

$$\varepsilon = \frac{\varepsilon_{\min}}{\bar{\sigma}_{\Psi}^2} > 0, \tag{53}$$

provided the output scheduling matrices are active and the scheduling matrices pseudo-commute with $\mathbf{S} = \frac{1}{2}\mathbf{1}$. Additionally, for the base case, the augmented matrix, $\Psi(t)$, defined in (37), can be written as

$$\boldsymbol{\Psi}(t) = \begin{bmatrix} s_1(t) & \cdots & s_N(t) \end{bmatrix} \otimes \boldsymbol{1} = \boldsymbol{s}^{\mathsf{T}}(t) \otimes \boldsymbol{1},$$

where \otimes denotes the Kronecker product. Since the output scheduling matrices are assumed to be active, then $\mathbf{s}(t) \neq \mathbf{0}$ for all $t \in \mathbb{R}_{>0}$. Therefore, the nonzero singular values of $\Psi(t)$

are the positive numbers $\{\sigma(\mathbf{s}(t))\sigma_i(\mathbf{1}) \mid i \in \mathcal{N}_y\}$, where $\mathcal{N}_y = \{1, 2, \dots, n_y\}$ [29, Theorem 4.2.15]. Consequently,

$$\sigma_{\Psi}(t) = \max_{i \in \mathcal{N}_y} \sigma(\mathbf{s}(t)) \sigma_i(\mathbf{1}) = \sqrt{\sum_{i \in \mathcal{N}} |s_i(t)|^2} > 0.$$

From (40), it follows that

$$\bar{\sigma}_{\Psi}^2 = \sup_{t \in \mathbb{R}_{\ge 0}} \sum_{i \in \mathcal{N}} |s_i(t)|^2 > 0.$$
(54)

Similar to the ISP case, the OSP coefficient, ε , in (53) exactly matches matrix scheduling of OSP subsystems shown in [24, Theorem 2]. For the base case, (54) further expands on the relationship between the scheduling signals and the OSP coefficient

$$\varepsilon = \frac{\varepsilon_{\min}}{\sup_{t \in \mathbb{R}_{>0}} \sum_{i \in \mathcal{N}} |s_i(t)|^2} > 0.$$
(55)

Using the Cauchy–Schwartz inequality, it can be shown that if a system is OSP with $\mathbf{Q} = -\varepsilon \mathbf{1}$, it also possesses finite \mathcal{L}_2 gain such that $\varepsilon = 1/\gamma$. Here, by defining $\varepsilon_i = 1/\gamma_i$ with $\gamma_i \in \mathbb{R}_{>0}$, (55) can be rewritten as $\varepsilon = 1/\gamma$, where

$$\gamma = \max_{i \in \mathcal{N}} (\gamma_i) \sup_{t \in \mathbb{R}_{\ge 0}} \sum_{i \in \mathcal{N}} |s_i(t)|^2 > 0.$$
 (56)

Therefore, the gain-scheduled system $\overline{\mathcal{G}}$ possess finite \mathcal{L}_2 gain with γ defined as per (56).

D. Subsystems possess Finite \mathcal{L}_2 Gain

Consider the case where each subsystem \mathcal{G}_i for $i \in \mathcal{N}$ has finite \mathcal{L}_2 gain with $\mathbf{Q}_i = -1$, $\mathbf{S}_i = \mathbf{0}$, and $\mathbf{R}_i = \gamma_i^2 \mathbf{1}$, where $\gamma_i \in \mathbb{R}_{>0}$. Theorem 2 suggests $\overline{\mathcal{G}}$ is QSR-dissipative with

$$\mathbf{Q} = -\frac{1}{\bar{\sigma}_{\Psi}^2} \mathbf{1}, \qquad \mathbf{S} = \mathbf{0}, \qquad \mathbf{R} = \bar{\sigma}_u \max_{i \in \mathcal{N}} \gamma_i^2 \mathbf{1}, \qquad (57)$$

provided the output scheduling matrices are active. Since $\mathbf{S} = \mathbf{0}$, the pseudo-commutativity condition is trivially satisfied, effectively decoupling the input and output scheduling matrices. To get a more familiar form, (57) can be scaled by $\bar{\sigma}_{\Psi}^2 > 0$ to obtain

$$\mathbf{Q} = -\mathbf{1}, \qquad \mathbf{S} = \mathbf{0}, \qquad \mathbf{R} = \bar{\sigma}_{\Psi}^2 \bar{\sigma}_u \max_{i \in \mathcal{N}} \gamma_i^2 \mathbf{1}.$$
(58)

Considering the base case and Corollary 1 with $\mathcal{R}_{>0} = \mathcal{N}$, substituting (46a) and (54) into (58) leads to

$$\mathbf{Q} = -\mathbf{1}, \qquad \mathbf{S} = \mathbf{0}, \qquad \mathbf{R} = \gamma^2 \mathbf{1},$$

where \mathcal{G} possess finite \mathcal{L}_2 gain with the exact same γ derived in (56), where the subsystems were assumed to be OSP. Moreover, the gain in (56) is similar to that of [16, Theorem 5.2]. It is unclear which gain is more conservative since here, the maximum γ_i over all subsystems is used, whereas in [16, Theorem 5.2], the γ_i terms remain in the summation. On the other hand, (56) uses the supremum of sums of scheduling signals, $s_i(t)$, whereas [16, Theorem 5.2] uses sum of suprema of scheduling signals. Alternatively, Theorem 1 suggests $\overline{\mathcal{G}}$ is QSR-dissipative with $\mathbf{Q} = -1$, $\mathbf{S} = \mathbf{0}$, and

$$\mathbf{R} = \left(N \sum_{i \in \mathcal{N}} \gamma_i^2 \bar{\sigma}_{y,i}^2 \bar{\sigma}_{u,i}^2 \right) \mathbf{1}.$$
 (59)

Again, for the base case, (59) simplifies to

$$\mathbf{R} = \left(N \sum_{i \in \mathcal{N}} \gamma_i^2 \| s_i \|_{\infty}^4 \right) \mathbf{1},\tag{60}$$

where $||s_i||_{\infty} = \sup_{t \in \mathbb{R}_{\geq 0}} |s_i(t)|$. Furthermore, applying [20, Theorem 1] to the finite \mathcal{L}_2 gain case recovers (60). Using the inequality in Lemma 5, it can be shown that

$$N\sum_{i\in\mathcal{N}}\gamma_i^2\|s_i\|_{\infty}^4 \ge \left(\sum_{i\in\mathcal{N}}\gamma_i\|s_i\|_{\infty}^2\right)^2,$$

meaning, [16, Theorem 5.2] is less conservative than Theorem 1 and [20, Theorem 1] for the finite \mathcal{L}_2 gain case.

E. Subsystems are VSP

Consider the case where each subsystem \mathcal{G}_i for $i \in \mathcal{N}$ is VSP with $\mathbf{Q}_i = -\varepsilon_i \mathbf{1}$, $\mathbf{S}_i = \frac{1}{2}\mathbf{1}$, and $\mathbf{R}_i = -\delta_i \mathbf{1}$, where $\varepsilon_i, \delta_i \in \mathbb{R}_{>0}$. Theorem 2 suggests $\overline{\mathcal{G}}$ is QSR-dissipative with

$$\mathbf{Q} = -\varepsilon \mathbf{1}, \qquad \mathbf{S} = \frac{1}{2}\mathbf{1}, \qquad \mathbf{R} = -\delta \mathbf{1},$$

with $\varepsilon \in \mathbb{R}_{>0}$ and $\delta \in \mathbb{R}_{\geq 0}$ given by (53) and (49), respectively, provided the output scheduling matrices are active and the scheduling matrices pseudo-commute with $\mathbf{S} = \frac{1}{2}\mathbf{1}$. Furthermore, if the scheduling matrices are strongly active, Corollary 1 with $\mathcal{R}_{<0} = \mathcal{N}$ suggests $\bar{\boldsymbol{\mathcal{G}}}$ is VSP with $\delta \in \mathbb{R}_{>0}$ given in (50). In [16], the authors combine the ISP and finite \mathcal{L}_2 gain results to show that the gain-scheduled system is VSP, while in [24], the ISP and OSP results are combined to achieve the same. Similar to the OSP case, Theorem 1 and [20, Theorem 1] can still be used to show the overall gain-scheduled system $\bar{\boldsymbol{\mathcal{G}}}$ is QSR-dissipative. However, they cannot ensure $\bar{\boldsymbol{\mathcal{G}}}$ is VSP as they lead to $\delta \in \mathbb{R}$ without the further guarantee of $\delta > 0$.

F. Subsystems are Conic

Consider the case where each subsystem \mathcal{G}_i for $i \in \mathcal{N}$ is conic with $\mathbf{Q}_i = -1$, $\mathbf{S}_i = c_i \mathbf{1}$, and $\mathbf{R}_i = (r_i^2 - c_i^2)\mathbf{1}$, where $c_i \in \mathbb{R}$ and $r_i \in \mathbb{R}_{>0}$, provided the scheduling matrices pseudo-commute with \mathbf{S}_i . Theorem 1 suggests $\overline{\mathcal{G}}$ is QSR-dissipative with

$$\mathbf{Q} = -\mathbf{1}, \qquad \mathbf{S} = c\mathbf{1}, \qquad \mathbf{R} = \left(r^2 - c^2\right)\mathbf{1}, \qquad (61)$$

where

$$c = \sum_{i \in \mathcal{N}} \left(c_i \bar{\sigma}_{y,i}^2 \right), \tag{62a}$$

$$r = \sqrt{N \sum_{i \in \mathcal{N}} \left(\delta_i + \bar{\sigma}_{y,i}^4 c_i^2\right)} = \sqrt{N \sum_{i \in \mathcal{N}} \bar{r}_i^2}, \qquad (62b)$$

are the conic center and radius, respectively, and $\bar{r}_i^2 = \delta_i + \bar{\sigma}_{u,i}^4 c_i^2$. Following the definition of δ_i in (18),

$$\bar{r}_{i} = \begin{cases} \bar{\sigma}_{y,i} \sqrt{\bar{\sigma}_{u,i}^{2}(r_{i}^{2} - c_{i}^{2}) + \bar{\sigma}_{y,i}^{2}c_{i}^{2}}, & \text{if } r_{i} > |c_{i}|, \\ \bar{\sigma}_{y,i} \sqrt{\bar{\nu}_{u,i}^{2}(r_{i}^{2} - c_{i}^{2}) + \bar{\sigma}_{y,i}^{2}c_{i}^{2}}, & \text{if } r_{i} \le |c_{i}|. \end{cases}$$
(63)



Fig. 4. Planar rigid three-link robotic manipulator with a fixed base, damped joints, no forces acting on the end-effector, and no potential energy due to gravity

Additionally, the scheduling matrices pseudo-commute with $\mathbf{S}_i = c_i \mathbf{1}$, meaning $\mathbf{\Phi}_{y,i}^{\mathsf{T}}(t) \mathbf{S}_i = \mathbf{S}_i \mathbf{\Phi}_{u,i}(t)$, for all $t \in \mathbb{R}_{\geq 0}$ and $i \in \mathcal{N}$. It follows that

$$\boldsymbol{\Phi}_{y,i}^{\mathsf{T}}(t) = \mathbf{S}_i \boldsymbol{\Phi}_{u,i}(t) \mathbf{S}_i^{-1} = \boldsymbol{\Phi}_{u,i}(t),$$

for all $t \in \mathbb{R}_{\geq 0}$ and $i \in \mathcal{N}$, such that $c_i \neq 0$. Therefore, the scheduling matrices corresponding to the i^{th} subsystem must share the same eigenvalues and singular values, provided $c_i \neq 0$. Consequently, (63) can be simplified as

$$\bar{r}_{i} = \begin{cases} \bar{\sigma}_{y,i} \bar{\sigma}_{u,i} r_{i}, & \text{if } r_{i} > |c_{i}| = 0, \\ \bar{\sigma}_{i}^{2} r_{i}, & \text{if } r_{i} > |c_{i}| \neq 0, \\ \bar{\sigma}_{i} \sqrt{\bar{\nu}_{i}^{2} r_{i}^{2} + (\bar{\sigma}_{i}^{2} - \bar{\nu}_{i}^{2}) c_{i}^{2}}, & \text{if } r_{i} \leq |c_{i}|, \end{cases}$$
(64)

where $\bar{\sigma}_i = \bar{\sigma}_{u,i} = \bar{\sigma}_{y,i}$ and $\bar{\nu}_i = \bar{\nu}_{u,i} = \bar{\nu}_{y,i}$ for all $i \in \mathcal{N}$ such that $c_i \neq 0$. For the base case, the conic center defined per (62a) simplifies to $c = \sum_{i \in \mathcal{N}} c_i ||s_i||_{\infty}^2$, matching the results in [20, Theorem 1] and [18, Theorem 6.2.1]. Moreover, for the base case, \bar{r}_i in (64) simplifies to the results in [20, Theorem 1] as

$$\bar{r}_i = \begin{cases} \sigma_i^2 r_i, & \text{if } r_i > |c_i|, \\ \sigma_i \sqrt{\nu_i^2 r_i^2 + (\sigma_i^2 - \nu_i^2) c_i^2}, & \text{if } r_i \leq |c_i|, \end{cases}$$

with $\sigma_i = ||s_i||_{\infty} < \infty$ and $\nu_i = \inf_{t \in \mathbb{R}_{\geq 0}} |s_i(t)| \geq 0$, for all $i \in \mathcal{N}$. As discussed in [20], when $r_i > |c_i|$, [18, Theorem 6.2.1] provides a less conservative bound on the conic radius of the gain-scheduled system compared to Theorem 1. This is again as a direct result of the special case of Cauchy–Schwartz inequality used in the proof of Theorem 1. Alternatively, since $\nu_i \leq \sigma_i$ for all $i \in \mathcal{N}$, Theorem 1 provides a tighter bound on the conic radius of the gain-scheduled system when $r_i \leq |c_i|$ compared to [18, Theorem 6.2.1].

VI. APPLICATION EXAMPLE

A. QSR-Dissipative Properties of the Plant

Consider a planar rigid three-link robotic manipulator, shown in Figure 4, with a fixed base, damped joints, no forces acting on the end-effector, and no potential energy due to gravity. The equations of motion of the robot are given by

$$\mathbf{M}(\mathbf{q}(t))\ddot{\mathbf{q}}(t) + \mathbf{D}\dot{\mathbf{q}}(t) = \mathbf{f}_{\text{non}}(\mathbf{q}(t), \dot{\mathbf{q}}(t)) + \boldsymbol{\tau}(t), \qquad (65)$$

where $\mathbf{M}(\mathbf{q}(t)) = \mathbf{M}^{\mathsf{T}}(\mathbf{q}(t)) \in \mathbb{S}^{3}_{++}$ is the mass matrix, $\mathbf{D} = \operatorname{diag}(d_1, d_2, d_3) \in \mathbb{S}^{3}_{++}$ is the damping matrix, $\mathbf{f}_{\operatorname{non}}(\mathbf{q}(t), \dot{\mathbf{q}}(t))$ captures the nonlinear inertial and Coriolis forces, $\boldsymbol{\tau}(t) = \begin{bmatrix} \tau_1(t) & \tau_2(t) & \tau_3(t) \end{bmatrix}^{\mathsf{T}}$ are the joint torques,



Fig. 5. Gain-scheduled feedback control of the plant to be controlled. The input and output of each subcontroller are scheduled as per (1) via the matrix multiplication between the scheduling matrices $\Phi_{u,i}(t)$ and $\Phi_{y,i}(t)$, and their corresponding signals $\mathbf{u}(t)$ and $\mathbf{y}_i(t)$, for $i \in \{1, 2, 3\}$.

and $\mathbf{q}(t) = \begin{bmatrix} \theta_1(t) & \theta_2(t) & \theta_3(t) \end{bmatrix}^{\mathsf{T}}$ are the generalized coordinates. The mass matrix and nonlinear forces can be obtained using the general Lagrangian dynamics formulation in [30, Section 8.1.2] as shown in [31]. A proportional control prewrap is added in negative feedback with the plant, \mathcal{G}_0 , as per Figure 5, where $\mathbf{K}_{\mathrm{p}} = \mathrm{diag}(k_{\mathrm{p},1}, k_{\mathrm{p},2}, k_{\mathrm{p},3}) \in \mathbb{S}^3_{++}$ and $\theta_{\mathrm{d}}(t) = \begin{bmatrix} \theta_{\mathrm{d},1}(t) & \theta_{\mathrm{d},2}(t) & \theta_{\mathrm{d},3}(t) \end{bmatrix}^{\mathsf{T}}$ is the desired trajectory. The resulting inner-loop, $\overline{\mathcal{G}}_0$, controls the displacement of the system. Dropping the time dependency for brevity, the nonlinear dynamics of the prewrapped system can be written as

$$\mathbf{M}\ddot{\mathbf{q}} = \mathbf{f}_{\text{non}} - \mathbf{D}\dot{\mathbf{q}} + \hat{\mathbf{B}}\bar{\mathbf{u}} - \mathbf{K}_{\text{p}}\mathbf{e}$$
(66)

where $\hat{\mathbf{B}} = \begin{bmatrix} 0 & 1 & 0 \\ 0 & 0 & 1 \end{bmatrix}^{\mathsf{T}}$, $\bar{\mathbf{u}} = \begin{bmatrix} \bar{u}_1(t) & \bar{u}_2(t) \end{bmatrix}^{\mathsf{T}}$ is from the output of the gain-scheduled controller $\bar{\boldsymbol{\mathcal{G}}}$, and $\mathbf{e}(t) = \mathbf{q}(t) - \boldsymbol{\theta}_{\mathsf{d}}(t)$ is the tracking error. The zero row in $\hat{\mathbf{B}}$ is purposely chosen to allow for gain-scheduling of non-square controllers. To analyze the dissipative property of the inner-loop, define the storage function $V = \frac{1}{2}\dot{\mathbf{q}}^{\mathsf{T}}\mathbf{M}\dot{\mathbf{q}} + \frac{1}{2}\mathbf{e}^{\mathsf{T}}\mathbf{K}_{\mathsf{p}}\mathbf{e}$. It follows that

$$\dot{V} = \dot{\mathbf{q}}^{\mathsf{T}} \left(\mathbf{M} \ddot{\mathbf{q}} + \frac{1}{2} \dot{\mathbf{M}} \dot{\mathbf{q}} \right) + \dot{\mathbf{e}}^{\mathsf{T}} \mathbf{K}_{\mathsf{p}} \mathbf{e}.$$
(67)

For a constant tracking trajectory, it follows that $\dot{\mathbf{e}} = \dot{\mathbf{q}}$. Substituting (66) into (67) and simplifying yields

$$\dot{V} = \dot{\mathbf{q}}^{\mathsf{T}} \left(\mathbf{f}_{\text{non}} + \frac{1}{2} \dot{\mathbf{M}} \dot{\mathbf{q}} \right) - \dot{\mathbf{q}}^{\mathsf{T}} \mathbf{D} \dot{\mathbf{q}} + \dot{\mathbf{q}}^{\mathsf{T}} \hat{\mathbf{B}} \bar{\mathbf{u}}.$$
(68)

From the Lagrangian dynamics formulation of the system, it can be verified that $\dot{\mathbf{q}}^{\mathsf{T}}(\mathbf{f}_{\mathsf{non}} + \frac{1}{2}\dot{\mathbf{M}}\dot{\mathbf{q}}) = 0$. Therefore, (68) simplifies to $\dot{V} = -\dot{\mathbf{q}}^{\mathsf{T}}\mathbf{D}\dot{\mathbf{q}} + \dot{\mathbf{q}}^{\mathsf{T}}\hat{\mathbf{B}}\bar{\mathbf{u}}$. Integrating both sides with $t \in [0, T]$ yields

$$V(T) - V(0) = \int_0^T -\dot{\mathbf{q}}^\mathsf{T}(t)\mathbf{D}\dot{\mathbf{q}}(t) + \dot{\mathbf{q}}^\mathsf{T}(t)\hat{\mathbf{B}}\bar{\mathbf{u}}(t)\,\mathrm{d}t$$
$$= \langle \mathbf{y}, -\mathbf{D}\mathbf{y} \rangle_T + \left\langle \mathbf{y}, \hat{\mathbf{B}}\bar{\mathbf{u}} \right\rangle_T, \quad \forall T \in \mathbb{R}_{\geq 0}, \quad (69)$$

Disonere doint Andees for These for deneration				
Discrete Time Point t_k [s]	Desired Joint Angle $\boldsymbol{\theta}_{d}(t_k)$ [deg]			
$t_{0} = 0$ $t_{1} = 2$ $t_{2} = 3$ $t_{3} = 7$ $t_{4} = 9$	$\begin{bmatrix} 0^{\circ} & 160^{\circ} & -90^{\circ} \end{bmatrix}^{T} \\ \begin{bmatrix} 0^{\circ} & 160^{\circ} & -90^{\circ} \end{bmatrix}^{T} \\ \begin{bmatrix} 0^{\circ} & 45^{\circ} & 45^{\circ} \end{bmatrix}^{T} \\ \begin{bmatrix} 0^{\circ} & 45^{\circ} & 45^{\circ} \end{bmatrix}^{T} \\ \begin{bmatrix} 0^{\circ} & -90^{\circ} & 160^{\circ} \end{bmatrix}^{T} \end{bmatrix}$			

TABLE II THREE-LINK MANIPULATOR PROPERTIES

Link Parameters	Link 1	Link 2	Link 3
Length [m]	$L_1 = 1.10$	$L_2 = 0.60$	$L_3 = 0.50$
Measured Length [m]	$\bar{L}_1 = 1.21$	$\bar{L}_2 = 0.54$	$\bar{L}_3 = 0.55$
Mass [kg]	$m_1 = 2.00$	$m_2 = 0.90$	$m_3 = 0.30$
Measured Mass [kg]	$\bar{m}_1 = 2.40$	$\bar{m}_2 = 0.72$	$\bar{m}_3 = 0.36$
Damping Coefficient [N·m·s/rad]	$d_1 = 5.00$	$d_2 = 2.50$	$d_3 = 2.50$

where $\mathbf{y}(t) = \dot{\mathbf{q}}(t) = \begin{bmatrix} \dot{\theta}_1(t) & \dot{\theta}_2(t) & \dot{\theta}_3(t) \end{bmatrix}^{\mathsf{T}}$ is the measurement. Consequently, the prewrapped system $\bar{\mathbf{\mathcal{G}}}_0$, in Figure 5, with input $\bar{\mathbf{u}}(t)$ and output $\mathbf{y}(t)$ is QSR-dissipative with $\mathbf{Q}_{\mathrm{P}} = -\mathbf{D}$, $\mathbf{S}_{\mathrm{P}} = \frac{1}{2}\hat{\mathbf{B}}$, and $\mathbf{R}_{\mathrm{P}} = \mathbf{0}$. More precisely, as per [3, Definition 3.1.2], the prewrapped system is conservative with respect to the quadratic storage function constructed using \mathbf{Q}_{P} , \mathbf{S}_{P} , and \mathbf{R}_{P} .

B. Trajectory Generation

The control objective is to have the three-link robot track a position, $\theta_d(t)$, and rate, $\dot{\theta}_d(t)$, trajectory. This is achieved by choosing discrete joint angles $\theta_d(t_k)$ and $\theta_d(t_{k+1})$ at times t_k and t_{k+1} , and interpolating between them as such

$$\eta(t) = \frac{t - t_k}{t_{k+1} - t_k}, \quad p_5(t) = 6\eta^5 - 15\eta^4 + 10\eta^3, \quad (70a)$$

$$\boldsymbol{\theta}_{\mathrm{d}}(t) = p_{5}(t) \left(\boldsymbol{\theta}_{\mathrm{d}}(t_{k+1}) - \boldsymbol{\theta}_{\mathrm{d}}(t_{k}) \right) + \boldsymbol{\theta}_{\mathrm{d}}(t_{k}). \tag{70b}$$

As shown in Table I, the desired discrete joint angles are chosen such that the base remains fixed at 0° while the second and third joint angles operate within $[-90^{\circ}, 160^{\circ}]$.

C. QSR-Dissipative Control Synthesis

The subcontrollers to be gain-scheduled will be linear non-square QSR-dissipative controllers, synthesized using the linearized model of the system. In [20], similar to \mathcal{H}_2 -conic synthesis in [32], \mathcal{H}_2 -optimal controllers are first designed using the linearized model of the system. These controllers are then rendered QSR-dissipative by solving a semidefinite program (SDP) involving a modified version of the linear matrix inequality (LMI) found in Lemma 6. Finally, the asymptotic stability of the closed-loop system is guaranteed using Theorem 3. Herein, a similar synthesis approach to [15, 20, 25, 33] is taken, where QSR-dissipative controllers are synthesized using the solution to the linear-quadratic regulator (LQR) problem in conjunction with Lemma 6 and Theorem 3.

First, the LQR problem requires a linearized state-space representation of (65). As shown in [31], $\mathbf{M}(\mathbf{q}(t))$ is nonlinear with respect to the second and third joint angles, $\theta_2(t)$ and $\theta_3(t)$. Therefore, to cover the range of possible

TABLE III CONTROLLER DESIGN PARAMETERS

Properties	Symbol	Value
Proportional Gain	Kp	diag(5, 35, 35)
LQR Weights	Q _{LQR} R _{LQR}	$\frac{\text{diag}(15, 15, 15, 10, 10, 10)^{-2}}{\text{diag}(25, 25)^{-2}}$

joint angles during the desired trajectory in Table I, three linearization points are chosen as $\bar{\mathbf{q}}_1 = \boldsymbol{\theta}_d(t_0)$, $\bar{\mathbf{q}}_2 = \boldsymbol{\theta}_d(t_2)$, and $\bar{\mathbf{q}}_3 = \boldsymbol{\theta}_d(t_3)$. The linearization of the prewrapped model, $\bar{\boldsymbol{\mathcal{G}}}_0$ in Figure 5, about $\bar{\mathbf{q}}_i$, for $i \in \mathcal{N} = \{1, 2, 3\}$, is given by

$$\delta \dot{\mathbf{x}}(t) = \mathbf{A}_i \delta \mathbf{x}(t) + \mathbf{B}_i \delta \mathbf{u}(t), \qquad \delta \mathbf{y}(t) = \mathbf{C}_i \delta \mathbf{x}(t), \tag{71}$$

with

$$\mathbf{A}_{i} = \begin{bmatrix} \mathbf{0} & \mathbf{1} \\ -\bar{\mathbf{M}}^{-1}(\bar{\mathbf{q}}_{i})\mathbf{K}_{p} & -\bar{\mathbf{M}}^{-1}(\bar{\mathbf{q}}_{i})\mathbf{D} \end{bmatrix},$$
(72a)

$$\mathbf{B}_{i} = \begin{bmatrix} \mathbf{0} \\ \bar{\mathbf{M}}^{-1}(\bar{\mathbf{q}}_{i}) \end{bmatrix}, \qquad \mathbf{C}_{i} = \begin{bmatrix} \mathbf{0} & \mathbf{1} \end{bmatrix}, \qquad (72b)$$

where $\bar{\mathbf{M}}(\bar{\mathbf{q}}_i)$ is the measured mass matrix obtained using the measured link lengths and masses in Table II, \mathbf{K}_p is the proportional gain matrix in Table III, and $\delta \mathbf{x}(t) = [\delta \mathbf{q}^{\mathsf{T}}(t) \ \delta \dot{\mathbf{q}}^{\mathsf{T}}(t)]^{\mathsf{T}}$. Furthermore, the LQR problem's state and input weight matrices, \mathbf{Q}_{LQR} and \mathbf{R}_{LQR} , are chosen following Bryson's rule [34], and are provided in Table III. Using the linearization of the prewrapped model in (71) with the LQR state and input weight matrices, the gain matrix \mathbf{K}_i is computed for each linearization point by solving the algebraic Riccati equation (ARE) [34]. Inspired by the LQG controller design in [25], the three subcontrollers to be gain-scheduled are designed to have the state-space form

$$\dot{\mathbf{x}}_{i}(t) = (\mathbf{A}_{i} - \mathbf{B}_{i}\mathbf{K}_{i} - \mathbf{B}_{c,i}\mathbf{C}_{i})\mathbf{x}_{i}(t) + \mathbf{B}_{c,i}\mathbf{y}_{i}(t), \quad (73a)$$
$$\mathbf{u}_{i}(t) = \mathbf{K}_{i}\mathbf{x}_{i}(t), \quad (73b)$$

for $i \in \mathcal{N}$, with $\mathbf{A}_i, \mathbf{B}_i$, and \mathbf{C}_i in (72), and $\mathbf{B}_{c,i}$ is to be constructed such that the subcontrollers are QSR-dissipative. To synthesize QSR-dissipative subcontrollers, an SDP is constructed using a modified version of the LMI in Lemma 6 through a change of variable, $\mathbf{F}_i = \mathbf{P}_i \mathbf{B}_{c,i}$, and solved using \mathbb{CVX} [35, 36], and \mathbb{MOSEK} [37]. This involves solving for $\mathbf{P}_i \in \mathbb{S}_{++}^6$, $\mathbf{Q}_{c,i} \in \mathbb{S}^2$, $\mathbf{R}_{c,i} \in \mathbb{S}^3$, $\mathbf{F}_i \in \mathbb{R}^{6\times 3}$, and $\rho_i \in \mathbb{R}_{>0}$ subject to

$$\begin{bmatrix} \mathbf{P}_{i}\hat{\mathbf{A}}_{i} + \hat{\mathbf{A}}_{i}^{\mathsf{T}}\mathbf{P}_{i} - \mathbf{F}_{i}\mathbf{C}_{i} - \mathbf{C}_{i}^{\mathsf{T}}\mathbf{F}_{i}^{\mathsf{T}} - \hat{\mathbf{Q}}_{i} & \mathbf{F}_{i} - \hat{\mathbf{S}}_{i} \\ \mathbf{F}_{i}^{\mathsf{T}} - \hat{\mathbf{S}}_{i}^{\mathsf{T}} & -\mathbf{R}_{c,i} \end{bmatrix} \leq 0, \quad (74a)$$

$$\begin{bmatrix} \rho_{i}\mathbf{Q}_{P} + \mathbf{R}_{c,i} & -\rho_{i}\mathbf{S}_{P} + \mathbf{S}_{c,i}^{\mathsf{T}} \\ -\rho_{i}\mathbf{S}_{P}^{\mathsf{T}} + \mathbf{S}_{c,i} & \mathbf{Q}_{c,i} \end{bmatrix} \prec 0, \quad (74b)$$

where

$$\hat{\mathbf{A}}_i = \mathbf{A}_i - \mathbf{B}_i \mathbf{K}_i, \quad \hat{\mathbf{Q}}_i = \mathbf{K}_i^{\mathsf{T}} \mathbf{Q}_{\mathrm{c},i} \mathbf{K}_i, \quad \hat{\mathbf{S}}_i = \mathbf{K}_i^{\mathsf{T}} \mathbf{S}_{\mathrm{c},i}, \quad (75)$$

and $\mathbf{S}_{c,i} = \mathbf{S}_{P}^{\mathsf{T}}$ for $i \in \mathcal{N}$. Additionally, $\mathbf{B}_{c,i}$ is obtained from \mathbf{F}_{i} as $\mathbf{B}_{c,i} = \mathbf{P}_{i}^{-1}\mathbf{F}_{i}$.

The LMI in (74a) is obtained from Lemma 6 and ensures the subcontrollers are QSR-dissipative. Additionally, in the absence of gain-scheduling, the LMI in (74b) guarantees the asymptotic stability of the negative feedback interconnection of any individual subcontroller with the prewrapped plant \mathcal{G}_0 as per Theorem 3. Therefore, the LMI in (74) is a sufficient condition for the synthesis of QSR-dissipative subcontrollers that render the closed-loop system asymptotically stable when connected in negative feedback with the prewrapped plant.

Similar to the control synthesis techniques in [20, 32], a cost function can be used in tandem with the LMI in (74) to impose certain design constraints. Here, from (74), it can be shown using the Schur complement lemma that $\mathbf{R}_{c,i} \in \mathbb{S}^3_+$ and $\mathbf{Q}_{c,i} \in \mathbb{S}^2_-$. Therefore, minimizing the cost function $\mathcal{J}(\mathbf{R}_{c,i}) = \operatorname{tr}(\mathbf{R}_{c,i})$ results in $\mathbf{R}_{c,i} = \mathbf{0}$ and subsequently $\mathbf{F}_i = \hat{\mathbf{S}}_i$. This choice of cost function is motivated by the fact that solving the SDP in (74) subject to $\mathbf{R}_{c,i} = \mathbf{0}$ and $\rho_i = 1$ is equivalent to solving for $\mathbf{P}_i \in \mathbb{S}^6_{++}$ and $\mathbf{Q}_{c,i} \in \mathbb{S}^2_{--}$, subject to

$$\mathbf{P}_{i}\hat{\mathbf{A}}_{i} + \hat{\mathbf{A}}_{i}^{\mathsf{T}}\mathbf{P}_{i} - \hat{\mathbf{S}}_{i}\mathbf{C}_{i} - \mathbf{C}_{i}^{\mathsf{T}}\hat{\mathbf{S}}_{i}^{\mathsf{T}} - \hat{\mathbf{Q}}_{i} \leq 0,$$
(76)

with $\hat{\mathbf{A}}_i$, $\hat{\mathbf{Q}}_i$, and $\hat{\mathbf{S}}_i$ found in (75). Again, $\mathbf{B}_{c,i}$ can be obtained from $\mathbf{F}_i = \hat{\mathbf{S}}_i = \mathbf{P}_i \mathbf{B}_{c,i}$ as $\mathbf{B}_{c,i} = \mathbf{P}_i^{-1} \hat{\mathbf{S}}_i$. Compared to (74), the SDP involved in solving (76) is computationally less expensive and results in a subcontroller \mathcal{G}_i that is QSR-dissipative with $\mathbf{Q}_{\mathrm{c},i} \in \mathbb{S}^2_{--}, \ \mathbf{S}_{\mathrm{c},i} = \frac{1}{2}\hat{\mathbf{B}}^\mathsf{T}, \ \mathrm{and} \ \mathbf{R}_{\mathrm{c},i} = \mathbf{0}.$ Three QSRdissipative subcontrollers, \mathcal{G}_i for $i \in \mathcal{N}$, are synthesized using the linearization of the prewrapped model in (71) about the linearization points $\bar{\mathbf{q}}_i$ and the LQR weights in Table III. The subcontrollers are then gain-scheduled to form the overall gain-scheduled controller $\bar{\mathcal{G}}$ in Figure 5. Since $\mathbf{Q}_{c,i} \in \mathbb{S}^2_{--}$ and the subcontrollers share a common $\mathbf{S}_{c,i}$ for $i \in \mathcal{N}$, Theorem 2 suggest the overall gain-scheduled controller $\overline{\mathcal{G}}$, in Figure 5, is QSR-dissipative, with $\mathbf{Q}_{c} = -\varepsilon \mathbf{1} \in \mathbb{S}_{--}^{2}$, $\mathbf{S}_{c} = \mathbf{S}_{c}^{\mathsf{T}} = \frac{1}{2}\mathbf{\hat{B}}^{\mathsf{T}}$, and $\mathbf{R}_{c} = \mathbf{0}$ with ε defined in (40), provided the output scheduling matrices are active, and the scheduling matrices pseudo-commute with $\hat{\mathbf{B}}^{\mathsf{T}}$. Finally, the closed-loop system in Figure 5 is guaranteed to be asymptotically stable, since the LMI in (85) can be trivially satisfied with $\rho = 1$.

D. Scheduling Function Construction

Similar to [24], fourth degree scalar polynomials are used as scheduling signals in the construction of scheduling matrices. For the linearization points $\bar{\mathbf{q}}_i$, the scheduling signals in Figure 6 are defined as

$$s_1(t) = \begin{cases} 1 & 0.0 \le t < 1.0, \\ 1 - \left(\frac{t-1}{3}\right)^4 & 1.0 \le t \le 4.0, \\ 0 & 4.0 < t, \end{cases}$$
(77a)

$$s_2(t) = \begin{cases} 1 - \left(\frac{t-5}{4}\right)^4 & 1.0 \le t \le 9.0, \\ 0 & \text{otherwise,} \end{cases}$$
(77b)

$$s_{3}(t) = \begin{cases} 0 & 0.0 \le t < 7.0, \\ 1 - \left(\frac{t-9}{2}\right)^{4} & 7.0 \le t \le 9.0, \\ 1 & 9.0 < t, \end{cases}$$
(77c)

where for 9 < t, $s_3(t) = 1$, while the other signals are zero. Additionally, at all times, all scheduling signals are bounded and for each time $t \in \mathbb{R}_{\geq 0}$, at least one scheduling signal is active, meaning $\forall t \in \mathbb{R}_{\geq 0}, \exists i \in \mathcal{N}$ such that $s_i(t) \neq 0$. Contrary to [20], the scheduling signals in (77)



Fig. 6. Scheduling signals $s_1(t)$, $s_2(t)$, and $s_3(t)$ defined in (77).

are "turned off", in the sense that $0 = \nu_i \leq |s_i(t)| \leq 1$ for $i \in \mathcal{N}$ and $\forall t \in \mathbb{R}_{>0}$.

As discussed in Section VI-C, to guarantee the gainscheduled controller \bar{g} is QSR-dissipative, the scheduling matrices need to pseudo-commute with $\mathbf{S}_c = \mathbf{S}_P^T = \frac{1}{2}\hat{\mathbf{B}}^T$, while the output scheduling matrices need to be active. Furthermore, as discussed in Section III-B, the scheduling matrices can be design using \mathbf{S}_c to satisfy this pseudo-commutativity condition. Consider the SVD of $\mathbf{S}_c = \frac{1}{2} \begin{bmatrix} \mathbf{0} & \mathbf{1} \end{bmatrix}$ given by

$$\mathbf{U} = \begin{bmatrix} 1 & 0 \\ 0 & 1 \end{bmatrix}, \quad \mathbf{\Sigma}_1 = \frac{1}{2} \begin{bmatrix} 1 & 0 \\ 0 & 1 \end{bmatrix}, \quad \mathbf{V} = \begin{bmatrix} 0 & 0 & 1 \\ 1 & 0 & 0 \\ 0 & 1 & 0 \end{bmatrix}$$

such that $\mathbf{S}_{c} = \mathbf{U} \begin{bmatrix} \boldsymbol{\Sigma}_{1} & \mathbf{0} \end{bmatrix} \mathbf{V}^{\mathsf{T}}$. As per Lemma 4, to satisfy the pseudo-commutativity condition, $\boldsymbol{\Phi}_{y,i}^{\mathsf{T}}(t)\mathbf{S}_{c} = \mathbf{S}_{c}\boldsymbol{\Phi}_{u,i}(t)$, the scheduling matrices need to satisfy

$$\boldsymbol{\Phi}_{u,i}(t) = \mathbf{V} \begin{bmatrix} \mathbf{Z}_{11,i}(t) & \mathbf{0} \\ \mathbf{\bar{z}}_{21,i}(t) & \bar{z}_i(t) \end{bmatrix} \mathbf{V}^{\mathsf{T}} = \mathbf{V} \mathbf{\bar{Z}}_i(t) \mathbf{V}^{\mathsf{T}}, \quad (78a)$$

$$\boldsymbol{\Phi}_{y,i}(t) = \mathbf{U}\bar{\mathbf{Z}}_{11,i}^{\mathsf{T}}(t)\mathbf{U}^{\mathsf{T}} = \bar{\mathbf{Z}}_{11,i}^{\mathsf{T}}(t), \tag{78b}$$

for all $t \in \mathbb{R}_{\geq 0}$, where $\bar{\mathbf{Z}}_{11,i}(t) \in \mathbb{R}^{2\times 2}$, $\bar{\mathbf{z}}_{21,i}(t) \in \mathbb{R}^{1\times 2}$, and $\bar{z}_i(t) \in \mathbb{R}$, for $i \in \mathcal{N}$, are design variables. Therefore, scheduling of each subcontroller \mathcal{G}_i in Figure 5 requires seven hyperparameters. Herein, $\bar{\mathbf{Z}}_i(t)$ for each subcontroller is chosen as

$$\bar{\mathbf{Z}}_{1}(t) = \begin{bmatrix} s_{1}(t) & -0.5s_{1}(t) & 0\\ 0 & 0 & 0\\ s_{3}(t) & s_{2}(t) & s_{1}(t) \end{bmatrix},$$
(79a)

$$\bar{\mathbf{Z}}_{2}(t) = \begin{bmatrix} s_{1}(t) + s_{2}(t) & 0 & 0\\ 0 & s_{2}(t) + s_{3}(t) & 0\\ 0 & 0 & s_{2}(t) \end{bmatrix}, \quad (79b)$$

$$\bar{\mathbf{Z}}_{3}(t) = \begin{bmatrix} s_{3}(t) & 0 & 0\\ s_{1}(t) & s_{3}(t) & 0\\ 0 & 0 & s_{2}(t) + s_{3}(t) \end{bmatrix}, \quad (79c)$$

for all $t \in \mathbb{R}_{\geq 0}$, where $s_1(t)$, $s_2(t)$, and $s_3(t)$ are defined in (77). The scheduling matrices constructed as per (78) with $\bar{\mathbf{Z}}_i(t)$ in (79) are chosen to demonstrate the various possible structures. For instance, $\bar{\mathbf{Z}}_1(t)$ is rank deficient for all $t \in \mathbb{R}_{\geq 0}$, $\bar{\mathbf{Z}}_2(t)$ is diagonal, and $\bar{\mathbf{Z}}_3(t)$ is lower-triangular. Finally, as required by Theorem 2, the output scheduling matrices in (78) are active, that is, $\forall t \in \mathbb{R}_{\geq 0}, \exists i \in \mathcal{N} = \{1, 2, 3\}$ such that $\Phi_{u,i}(t) = \bar{\mathbf{Z}}_{11,i}^T(t) \neq \mathbf{0}$.

E. Comparison

A closed-loop simulation is performed using three different control approaches to have the three-link planar manipulator in Figure 4 track the trajectory given by (70). As a baseline, the controller \mathcal{G}_3 , a QSR-dissipative controller synthesized using the SDP in Section VI-C, is used and will be referred to as the unscheduled controller henceforth. The second approach, referred to as the scalar gain-scheduled (GS) controller, uses the scalar scheduling signals in (77) to gain-schedule the three subcontrollers, \mathcal{G}_1 , \mathcal{G}_2 , and \mathcal{G}_3 , designed about the linearization points $\bar{\mathbf{q}}_1$, $\bar{\mathbf{q}}_2$, and $\bar{\mathbf{q}}_3$, respectively. This approach is inspired by the VSP gain-scheduling architecture in [16] but with non-square subcontrollers gain-scheduled as per Figure 5, where $\Phi_{u,i}(t) = s_i(t)\mathbf{1}$ and $\Phi_{y,i}(t) = s_i(t)\mathbf{1}$ for all $i \in \mathcal{N}$. The third approach, referred to as the matrix GS controller, uses the scheduling matrices constructed as per (78) and (79) instead. Finally, since the controllers designed in Section VI-C are meant to control the second and third joint angles, the comparison will only focus on these joints. The desired trajectory generated using (70) with the discrete points in Table I is shown in Figure 7 where the close tracking performance of the three control approaches is shown. The joint angle error, $\mathbf{e}(t) = \begin{bmatrix} e_1(t) & e_2(t) & e_3(t) \end{bmatrix}^{\mathsf{T}} = \mathbf{q}(t) - \boldsymbol{\theta}_{\mathsf{d}}(t)$, is shown in Figure 8, where the matrix GS controller has noticeably less error, magnitude wise, than the scalar GS controller when the three-link manipulator transitions between desired positions. The root-mean-square (RMS) joint angle error, and joint angle error rates are tabulated in Table IV. Again, the matrix GS controller realizes lower RMS angle error and RMS angle rate error. The code used to generate the figures presented in this section can be found in the GitHub repository at https: //github.com/decargroup/matrix_scheduling_ gsr_dissipative_systems.

VII. CLOSING REMARKS

The gain-scheduling of QSR-dissipative subsystems using scheduling matrices is considered in this paper. The proposed gain-scheduling architecture is shown to result in an overall OSR-dissipative gain-scheduled system, provided the scheduling matrices are bounded and possess certain pseudocommutative properties. A detailed discussion is provided regarding the design and construction of scheduling matrices that satisfy the introduced pseudo-commutative property. Furthermore, the gain-scheduling of a broader class of QSRdissipative systems is considered than that found in prior work. For the various passive cases of QSR-dissipativity, the conditions on the scheduling matrices reduce to the same conditions on the scheduling signals reported in [15, 16], while for the conic case, the results of [20] were recovered when the scheduling matrices are chosen to be a scalar times the identity matrix. The proposed gain-scheduling architecture, along with the LMI-based QSR-dissipative control synthesis technique, is applied to the control of a planar three-link robotic manipulator subject to model uncertainty. Numerical simulation results highlight the added benefits of using scheduling matrices compared to scheduling signals.



Fig. 7. Comparison of joint angles and joint rates.



Fig. 8. Comparison of joint angles errors and error rates.



Fig. 9. Comparison of joint torques.

TABLE IV RMS ERROR OF JOINT ANGLE AND JOINT ANGLE RATE

	RMS an [de	RMS angle error [deg]		RMS angle rate error [deg/s]	
Control method	e_2	e_3	\dot{e}_2	\dot{e}_3	
Unscheduled	1.8239	1.7892	2.1111	2.1191	
Scalar scheduling	1.5226	1.4358	1.6073	1.5442	
Matrix scheduling	1.1304	1.2015	1.3669	1.1356	

VIII. ACKNOWLEDGMENT

The authors would like to thank Prof. Xiao-Wen Chang for their helpful input with regard to Lemma 4.

APPENDIX

Lemma 4: Consider a real nonzero matrix $\mathbf{S} \in \mathbb{R}^{m \times n}$ such that $\mathbf{S} \neq \mathbf{0}$. The arbitrary matrices $\mathbf{A} \in \mathbb{R}^{m \times m}$ and $\mathbf{B} \in \mathbb{R}^{n \times n}$ satisfy $\mathbf{AS} = \mathbf{SB}$ if and only if

$$\mathbf{A} = \mathbf{U} \begin{bmatrix} \boldsymbol{\Sigma}_1 \bar{\mathbf{B}}_{11} \boldsymbol{\Sigma}_1^{-1} & \bar{\mathbf{A}}_{12} \\ \mathbf{0} & \bar{\mathbf{A}}_{22} \end{bmatrix} \mathbf{U}^\mathsf{T}, \quad \mathbf{B} = \mathbf{V} \begin{bmatrix} \bar{\mathbf{B}}_{11} & \mathbf{0} \\ \bar{\mathbf{B}}_{21} & \bar{\mathbf{B}}_{22} \end{bmatrix} \mathbf{V}^\mathsf{T},$$

where $\mathbf{U} \in \mathbb{R}^{m \times m}$, $\Sigma_1 \in \mathbb{S}^{\varrho}$, and $\mathbf{V} \in \mathbb{R}^{n \times n}$ are given by the singular value decomposition (SVD) of **S** such that

$$\mathbf{S} = \mathbf{U} \begin{bmatrix} \mathbf{\Sigma}_1 & \mathbf{0} \\ \mathbf{0} & \mathbf{0} \end{bmatrix} \mathbf{V}^{\mathsf{T}}$$

with $\rho = \operatorname{rank}(\mathbf{S}) \geq 1$, and $\mathbf{A}_{12}, \mathbf{A}_{22}, \mathbf{B}_{11}, \mathbf{B}_{21}$, and \mathbf{B}_{22} are arbitrary real matrices of appropriate dimensions.

Proof: Assume $\mathbf{A} \in \mathbb{R}^{m \times m}$ and $\mathbf{B} \in \mathbb{R}^{n \times n}$ satisfy $\mathbf{AS} = \mathbf{SB}$. Using the SVD of **S**, it follows that

$$\mathbf{A}\mathbf{U}\begin{bmatrix}\boldsymbol{\Sigma}_1 & \mathbf{0}\\ \mathbf{0} & \mathbf{0}\end{bmatrix}\mathbf{V}^{\mathsf{T}} = \mathbf{U}\begin{bmatrix}\boldsymbol{\Sigma}_1 & \mathbf{0}\\ \mathbf{0} & \mathbf{0}\end{bmatrix}\mathbf{V}^{\mathsf{T}}\mathbf{B}.$$
 (80)

Since U and V are orthogonal matrices, left and right multiplying (80) by U^{T} and V, respectively, yields

$$\mathbf{U}^{\mathsf{T}}\mathbf{A}\mathbf{U}\begin{bmatrix}\boldsymbol{\Sigma}_{1} & \mathbf{0}\\ \mathbf{0} & \mathbf{0}\end{bmatrix} = \begin{bmatrix}\boldsymbol{\Sigma}_{1} & \mathbf{0}\\ \mathbf{0} & \mathbf{0}\end{bmatrix}\mathbf{V}^{\mathsf{T}}\mathbf{B}\mathbf{V}.$$
 (81)

Define

$$\mathbf{U}^{\mathsf{T}}\mathbf{A}\mathbf{U} = \begin{bmatrix} \bar{\mathbf{A}}_{11} & \bar{\mathbf{A}}_{12} \\ \bar{\mathbf{A}}_{21} & \bar{\mathbf{A}}_{22} \end{bmatrix}, \quad \mathbf{V}^{\mathsf{T}}\mathbf{B}\mathbf{V} = \begin{bmatrix} \bar{\mathbf{B}}_{11} & \bar{\mathbf{B}}_{12} \\ \bar{\mathbf{B}}_{21} & \bar{\mathbf{B}}_{22} \end{bmatrix}.$$
(82)

Substituting (82) into (81) results in

$$\begin{bmatrix} \mathbf{A}_{11}\boldsymbol{\Sigma}_1 & \mathbf{0} \\ \bar{\mathbf{A}}_{21}\boldsymbol{\Sigma}_1 & \mathbf{0} \end{bmatrix} = \begin{bmatrix} \boldsymbol{\Sigma}_1 \mathbf{B}_{11} & \boldsymbol{\Sigma}_1 \mathbf{B}_{12} \\ \mathbf{0} & \mathbf{0} \end{bmatrix}.$$
 (83)

Equating similar terms in (83) yields $\bar{\mathbf{A}}_{11} \Sigma_1 = \Sigma_1 \bar{\mathbf{B}}_{11}$, $\bar{\mathbf{A}}_{21} \Sigma_1 = \mathbf{0}$, and $\Sigma_1 \bar{\mathbf{B}}_{12} = \mathbf{0}$. Since Σ_1 is full rank, it follows that

$$\bar{\mathbf{A}}_{11} = \boldsymbol{\Sigma}_1 \bar{\mathbf{B}}_{11} \boldsymbol{\Sigma}_1^{-1}, \quad \bar{\mathbf{A}}_{21} = \mathbf{0}, \quad \bar{\mathbf{B}}_{12} = \mathbf{0}.$$
 (84)

Substituting (84) into (82) and rearranging recovers the desired result.

Lemma 5: Suppose that u_1, \ldots, u_N are real numbers. The arithmetic mean-quadratic mean (AM-QM) inequality, given as part of the mean inequalities in [38, Theorem 2.16], states that

$$\left(\sum_{i=1}^N u_i\right)^2 \le N \sum_{i=1}^N u_i^2.$$

Proof: The Cauchy–Schwartz inequality for $\mathbf{u} = [u_1, \ldots, u_N]^\mathsf{T} \in \mathbb{R}^N$ and $\mathbf{v} = [1, \ldots, 1]^\mathsf{T} \in \mathbb{R}^N$ states that

$$\left(\sum_{i=1}^{N} u_i\right)^2 = \left|\langle \mathbf{u}, \mathbf{v} \rangle\right|^2 \le \|\mathbf{u}\|_2^2 \|\mathbf{v}\|_2^2 = N \sum_{i=1}^{N} u_i^2.$$

Lemma 6 ([39, Lemma 2]): The continuous-time linear time-invariant system described by the state-space realization $(\mathbf{A}, \mathbf{B}, \mathbf{C}, \mathbf{D})$ is QSR-dissipative with matrices $\mathbf{Q} = \mathbf{Q}^{\mathsf{T}}$, \mathbf{S} , and $\mathbf{R} = \mathbf{R}^{\mathsf{T}}$ if and only if there exists $\mathbf{P} = \mathbf{P}^{\mathsf{T}} \succ 0$ such that

$$\begin{bmatrix} \mathbf{P}\mathbf{A} + \mathbf{A}^{\mathsf{T}}\mathbf{P} - \hat{\mathbf{Q}} & \mathbf{P}\mathbf{B} - \hat{\mathbf{S}} \\ \left(\mathbf{P}\mathbf{B} - \hat{\mathbf{S}}\right)^{\mathsf{T}} & -\hat{\mathbf{R}} \end{bmatrix} \preceq \mathbf{0},$$

where

$$\begin{aligned} \mathbf{Q} &= \mathbf{C}^{\mathsf{T}} \mathbf{Q} \mathbf{C}, \\ \hat{\mathbf{S}} &= \mathbf{C}^{\mathsf{T}} \mathbf{S} + \mathbf{C}^{\mathsf{T}} \mathbf{Q} \mathbf{D}, \\ \hat{\mathbf{R}} &= \mathbf{D}^{\mathsf{T}} \mathbf{Q} \mathbf{D} + \left(\mathbf{D}^{\mathsf{T}} \mathbf{S} + \mathbf{S}^{\mathsf{T}} \mathbf{D} \right) + \mathbf{R} \end{aligned}$$

Theorem 3 ([8, Theorem 2]): Consider two continuoustime systems \mathcal{H}_1 and \mathcal{H}_2 that are QSR-dissipative with matrices $\mathbf{Q}_1 = \mathbf{Q}_1^{\mathsf{T}}$, \mathbf{S}_1 , $\mathbf{R}_1 = \mathbf{R}_1^{\mathsf{T}}$, and $\mathbf{Q}_2 = \mathbf{Q}_2^{\mathsf{T}}$, \mathbf{S}_2 , $\mathbf{R}_2 = \mathbf{R}_2^{\mathsf{T}}$, respectively. Provided \mathcal{H}_1 is connected in a negative feedback loop with \mathcal{H}_2 , the feedback system is asymptotically stable if there exists a $\rho \in \mathbb{R}_{>0}$ such that

$$\begin{bmatrix} \rho \mathbf{Q}_1 + \mathbf{R}_2 & -\rho \mathbf{S}_1 + \mathbf{S}_2^\mathsf{T} \\ -\rho \mathbf{S}_1^\mathsf{T} + \mathbf{S}_2 & \rho \mathbf{R}_1 + \mathbf{Q}_2 \end{bmatrix} \prec 0.$$
(85)

REFERENCES

- J. C. Willems, "Dissipative Dynamical Systems Part I: General Theory," *Archive for Rational Mechanics and Analysis*, vol. 45, pp. 321– 351, 1972.
- [2] H. K. Khalil, *Nonlinear Systems*. United Kingdom: Prentice Hall, 1996.
 [3] A. van der Schaft, *L*₂-Gain and Passivity Techniques in Nonlinear
- Control. Germany: Springer International Publishing, 2018.
- [4] B. Brogliato, R. Lozano, B. Maschke, and O. Egeland, *Dissipative Systems Analysis and Control: Theory and Applications*. Germany: Springer London, 2013.
- [5] G. Zames, "On the Input-Output Stability of Time-Varying Nonlinear Feedback Systems Part I: Conditions Derived Using Concepts of Loop Gain, Conicity, and Positivity," *IEEE Transactions on Automatic Control*, vol. 11, no. 2, pp. 228–238, 1966.
- [6] D. Hill and P. Moylan, "The Stability of Nonlinear Dissipative Systems," *IEEE Transactions on Automatic Control*, vol. 21, no. 5, pp. 708–711, Nov. 1976.
- [7] J. L. Willems, "A System Theory Approach to Unified Electrical Machine Analysis," *International Journal of Control*, vol. 15, no. 3, pp. 401–418, 1972.
- [8] D. Hill and P. Moylan, "Stability Results for Nonlinear Feedback Systems," *Automatica*, vol. 13, no. 4, pp. 377–382, 1977.
- [9] A. L. Fradkov and D. J. Hill, "Exponential Feedback Passivity and Stabilizability of Nonlinear Systems," *Automatica*, vol. 34, no. 6, pp. 697–703, 1998.
- [10] A. Rahnama, M. Xia, and P. J. Antsaklis, "A QSR-Dissipativity and Passivity Based Analysis of Event-Triggered Networked Control Systems," *IEEE Conference on Decision and Control*, pp. 3072–3077, 2016.
- [11] X. Zhang, Y. Liu, H. Qiu, and H. Liu, "Dissipativity and Synchronization of Fractional-Order Output-Coupled Neural Networks with Multiple Adaptive Coupling Weights," *Mathematics and Computers in Simulation*, vol. 215, pp. 306–322, 2024.
- [12] R. Ortega, A. Loría, P. J. Nicklasson, and H. Sira-Ramírez, Passivitybased Control of Euler-Lagrange Systems: Mechanical, Electrical and Electromechanical Applications. Germany: Springer London, 2013.
- [13] C. J. Damaren, "Passivity Analysis for Flexible Multilink Space Manipulators," *Journal of Guidance Control and Dynamics*, vol. 18, no. 2, pp. 272–279, 1995.
- [14] M. Panzirsch, J. Artigas, J.-H. Ryu, and M. Ferre, "Multilateral control for delayed teleoperation," *International Conference on Advanced Robotics*, Nov. 2013.
- [15] C. J. Damaren, "Gain-Scheduled SPR Controllers for Nonlinear Flexible Systems," *Journal of Dynamic Systems, Measurement, and Control*, vol. 118, no. 4, pp. 698–703, 1996.

- [16] J. R. Forbes and C. J. Damaren, "Design of Gain-Scheduled Strictly Positive Real Controllers Using Numerical Optimization for Flexible Robotic Systems," *Journal of Dynamic Systems, Measurement, and Control*, vol. 132, no. 3, 2010.
- [17] J. R. Forbes and C. J. Damaren, "Overcoming Passivity Violations: Closed-Loop Stability, Controller Design and Controller Scheduling," *IET Control Theory & Applications*, vol. 7, no. 6, pp. 785–795, 2013.
- [18] J. R. Forbes, "Extensions of Input-Output Stability Theory and the Control of Aerospace Systems," Ph.D. dissertation, University of Toronto, Canada, 2011.
- [19] J. J. Brown and R. Caverly, "Conic Gain-Scheduled Control of an Aeroelastic Airfoil," p. 1562, 2021.
- [20] L. Anderson, R. J. Caverly, and A. Lamperski, "Gain-Scheduled QSR-Dissipative Systems: An Input-Output Approach," *American Control Conference*, pp. 2417–2423, 2023.
- [21] A. Walsh and J. R. Forbes, "A Very Strictly Passive Gain-Scheduled Controller: Theory and Experiments," *IEEE/ASME Transactions on Mechatronics*, vol. 21, no. 6, pp. 2817–2826, 2016.
- [22] A. Walsh and J. R. Forbes, "Very Strictly Passive Controller Synthesis With Affine Parameter Dependence," *IEEE Transactions on Automatic Control*, vol. 63, no. 5, pp. 1531–1537, 2018.
- [23] X. Lang and C. J. Damaren, "Gain-Scheduled Control for an Antenna with Multiple Collocated Sensors and Actuators," AIAA Guidance, Navigation, and Control Conference, 2018.
- [24] S. Moalemi and J. R. Forbes, "Passivity-Based Gain-Scheduled Control with Scheduling Matrices," *IEEE Conference on Control Technology* and Applications, pp. 7–13, 2024.
- [25] R. J. Benhabib, R. P. Iwens, and R. L. Jackson, "Stability of Large Space Structure Control Systems Using Positivity Concepts," *Journal* of Guidance and Control, vol. 4, no. 5, pp. 487–494, 1981.
- [26] S. P. Boyd and L. Vandenberghe, *Convex Optimization*. United States: Cambridge University Press, 2004.
- [27] K. Zhou, J. C. Doyle, and K. Glover, *Robust and Optimal Control*. United Kingdom: Prentice Hall, 1996.
- [28] H. J. Márquez, Nonlinear Control Systems: Analysis and Design. United Kingdom: Wiley, 2003.
- [29] R. A. Horn and C. R. Johnson, *Topics in Matrix Analysis*. United Kingdom: Cambridge University Press, 1994.
- [30] K. M. Lynch and F. C. Park, *Modern Robotics: Mechanics, Planning, and Control.* Singapore: Cambridge University Press, 2017.
- [31] M. I. Azeez, A. M. M. Abdelhaleem, S. Elnaggar, K. A. F. Moustafa, and K. R. Atia, "Optimization of PID Trajectory Tracking Controller for a 3-DOF Robotic Manipulator using Enhanced Artificial Bee Colony Algorithm," *Scientific Reports*, vol. 13, no. 1, p. 11 164, 2023.
- [32] L. J. Bridgeman, R. J. Caverly, and J. R. Forbes, "Conic-Sector-Based Controller Synthesis: Theory and Experiments," *American Control Conference*, pp. 4292–4297, 2014.
- [33] A. Walsh and J. R. Forbes, "Analysis and Synthesis of Input Strictly Passive Gain-Scheduled Controllers," *Journal of the Franklin Institute*, vol. 354, no. 3, pp. 1285–1301, 2017.
- [34] G. F. Franklin, J. D. Powell, and A. Emami-Naeini, *Feedback Control of Dynamic Systems*. United States: Pearson Education, 2011.
- [35] S. Diamond and S. Boyd, "CVXPY: A Python-Embedded Modeling Language for Convex Optimization," *Journal of Machine Learning Research*, vol. 17, no. 83, pp. 1–5, 2016.
- [36] A. Agrawal, R. Verschueren, S. Diamond, and S. Boyd, "A Rewriting System for Convex Optimization Problems," *Journal of Control and Decision*, vol. 5, no. 1, pp. 42–60, 2018.
- [37] M. ApS, The MOSEK Optimizer API for Python 10.1.28, 2024. [Online]. Available: https://docs.mosek.com/latest/ pythonapi/index.html.
- [38] D. Djukić, V. Janković, I. Matić, and N. Petrović, *The IMO Compendium: A Collection of Problems Suggested for The International Mathematical Olympiads: 1959-2009*, 2nd ed. Netherlands: Springer New York, 2011.
- [39] N. Kottenstette, M. McCourt, M. Xia, V. Gupta, and P. Antsaklis, "On Relationships Among Passivity, Positive realness, and Dissipativity in Linear Systems," *Automatica*, vol. 50, no. 4, 2014.