Transformers with Sparse Attention for Granger Causality

Riya Mahesh ee21b112@smail.iitm.ac.in Indian Institute of Technology Madras Chennai, Tamil Nadu, India Rahul Vashisht cs18d006@cse.iitm.ac.in Indian Institute of Technology Madras Chennai, Tamil Nadu, India Chandrashekar Lakshminarayanan chandrashekar@cse.iitm.ac.in Indian Institute of Technology Madras Chennai, Tamil Nadu, India

ABSTRACT

Temporal causal analysis means understanding the underlying causes behind observed variables over time. Deep learning based methods such as transformers are increasingly used to capture temporal dynamics and causal relationships beyond mere correlations. Recent works suggest self-attention weights of transformers as a useful indicator of causal links. We leverage this to propose a novel modification to the self-attention module to establish causal links between the variables of multivariate time-series data with varying lag dependencies. Our Sparse Attention Transformer captures causal relationships using a two-fold approach - performing temporal attention first followed by attention between the variables across the time steps masking them individually to compute Granger Causality indices. The key novelty in our approach is the ability of the model to assert importance and pick the most significant past time instances for its prediction task against manually feeding a fixed time lag value. We demonstrate the effectiveness of our approach via extensive experimentation on several synthetic benchmark datasets. Furthermore, we compare the performance of our model with the traditional Vector Autoregression based Granger Causality method that assumes fixed lag length.

CCS CONCEPTS

• Computing methodologies \rightarrow Supervised learning; Machine learning;

KEYWORDS

Multi-variate time series, Granger Causality, Stationarity, Self-attention, Sparse Attention, Transformers

ACM Reference Format:

Riya Mahesh, Rahul Vashisht, and Chandrashekar Lakshminarayanan. 2024. Transformers with Sparse Attention for Granger Causality. In 8th International Confernce on Data Science and Management of Data (12th ACM IKDD CODS and 30th COMAD) (CODS-COMAD Dec '24), December 18–21, 2024, Jodhpur, India. ACM, New York, NY, USA, 5 pages. https://doi.org/10.1145/ 3703323.3703335

1 INTRODUCTION

Establishing causal links is vital to analyze cause-effect relationships between different natural processes. Causality analysis finds

CODS-COMAD Dec '24, December 18–21, 2024, Jodhpur, India © 2024 Copyright held by the owner/author(s). ACM ISBN 979-8-4007-1124-4/24/12.

https://doi.org/10.1145/3703323.3703335

its application in various domains, spanning from climate discovery [13],[9] to economics[2]. The underlying motivation is to understand the patterns and analyze how a change in a particular process can influence another. By identifying causal links, we can potentially mitigate the risks (if any) associated with the ill effects of such changes.

Identifying potential causal relations from observational time-series data is a challenging task due to the lack of sufficient information on the underlying distribution of the causal model and highly interdependent nature of the that exhibit time lags, auto-correlation, non-linearities and non-stationary characteristics[4]. Several methods using classical machine learning (ML) techniques based on regression [15],[18] have been employed to explain causality. These, however, do not disambiguate clearly between correlation and causality. Granger Causality[3] has been instrumental as a pioneering method for identifying causal dependencies in multivariate time series data. The popular framework uses vector autoregressive models to compare the prediction accuracy of the effect variable in the presence and absence of the cause variable[12].

Most traditional approaches consider fixed time lags. Our method, however, explicitly tackles the cases of stationary data with longrange dependencies that show random delayed effects due to small, varying lags. We investigate a more realistic setting where the knowledge about the exact time lag with which the past events affect the present is unknown due to such delays. In a real-world scenario, consider a dataset that records crop yield annually over several years along with factors like temperature and precipitation during the monsoon. However, it is very typical that the onset of the monsoon has random delays every year. Traditional models which need a fixed a lag to be specified will fail in this scenario because the lag differs from year to year. On the other hand, using the entire year as the time window has the danger of overfitting, in that, models could use all the time points thereby making it hard to determine causal links. Motivated by this we propose a novel Sparse Attention Transformer (SAT). Our specific contributions are listed below.

- i. Our sparse attention transformer (SAT) uses a novel sparse attention mechanism which at time t selects the top 'k' important past time instance within a given window. In SAT, we don't explicitly specify the lag which enables the model to use the power in the hidden features to learn to select the appropriately lagged time points in a contextual manner.
- ii. We experimentally verify performance of SAT on datasets with random delays.

2 PROBLEM SETTING

Let $X_t = (X_t^1, X_t^2, ..., X_t^D)$ be a set of D variables observed at a time instance t. Consider a time-series data observed across T time steps,

Permission to make digital or hard copies of part or all of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for third-party components of this work must be honored. For all other uses, contact the owner/author(s).

 $X \in \mathbb{R}^{T \times D}$ such that $X = \{X_1, X_2, ..., X_T\}$ is generated using a single causal model with arbitrary small lags. Such a dataset can be modeled as $X_t = f(X_{t-1-l_1}, X_{t-2-l_2}, ..., X_{t-k-l_k}) \forall t$ where $l_1, l_2, ..., l_k$ are small, variable lags associated with the past time steps. The task is to generate a causation matrix $\hat{A} \in \mathbb{R}^{D \times D}$ such that every entry $\hat{A}_{ij} \in [0, 1]$; with 0 indicating the absence and 1 indicating the strong presence of a causal link between $X_{i'}^{i}$ and $X_{i}^{j} \forall t' < t$.

3 BACKGROUND

3.1 Causality analysis

Multi-variate time series data is characterised by multiple observations or features recorded at equal intervals of time. The method proposed involves time-series dataset that shows a combination of the following properties:

- Autocorrelaion is the degree of correlation of a variable at the present instance with its own value in the past.
- **Time homogenous** system is where the underlying causal graph remains constant with time.
- **Delayed** behavior is demonstrated when the variable is observed at a time much later than its scheduled occurrence.

3.2 Self-Attention in Transformers

The self-attention layer in a transformer captures the importance weights of every token in a sequence while encoding another token. The attention layer can be visualized as a mapping from queries and key-value pairs to an output[14].

Each token in the input sequence is embedded into a vector. Let the number of words in the sequence be *n*, and each word be represented as a *d*-dimensional embedding. Input is a vector $X \in \mathbb{R}^{n \times d}$. The queries, keys and values are obtained by linear transformation of the input sequence as below:

 $Q = XW_Q$ where $W_Q \in \mathbb{R}^{d \times d_k}$, d_k = dimension of queries

 $K = X W_K$ where $W_K \in R^{d \times d_k}, d_k$ = dimension of keys

 $V = XW_V$ where $W_V \in \mathbb{R}^{d \times d_k}$, d_k = dimension of values

The scaled dot product attention output is given as

Attention(Q, K, V) = softmax(
$$\frac{QK^T}{\sqrt{d_k}}$$
)V

Here, the term obtained after softmax operation before multiplying with V is an $n \times n$ attention weight matrix.

3.3 Attention for Temporal Causality

The weights of an attention matrix can be viewed as a measure of the influence one variable has on another and, hence, can be interpreted as an indicator of causal links[8]. Recent discoveries on causal transformers[6],[7],[11], Self-Attentive Hawkes Process[16] and improved Granger Causality approaches [19], [1] provide impetus to explore methods based on these mechanisms for causality analysis.

Previous works involving transformer based mechanisms for causality analysis are on fixed lag datasets. The paper on Causal-Transformer[22] performs independent spatial and temporal causal analysis and then concatenates them to output the final causal analysis results. This method however does not use sparse-attention while training. Sparse attention based transformers are less memory intensive as we calculate lesser number of dot products while computing causal attention between the variables and hence our method is computationally more efficient. Several methods like Informer[21] and Sparse Transformers[20] have been developed, but they majorly focus on time-series forecasting and have not been employed for causal analysis. CausalFormer[17], uses the Prob-Sparse attention architecture of an Informer[21] in its time encoder. It separately calculates another attention using causal encoder and feeds it to the decoder to predict the time-series. The informer architecture used here calculates KL divergence between the querykey probability distribution against a uniform distribution. Our mechanism, on the other hand, picks the top-K time-instances contextually by using the column sums of the attention scores without assuming any underlying distribution.

3.4 Granger Causality

For stationary, linear time-series data Granger Causality test determines whether a variable X causes another variable Y[12].

Consider a D-dimensional vector, spread across T time instances: $X_t = (X_t^1, X_t^2, ..., X_t^D) \forall t \in [1, T]$

To check if a variable X_i causes a variable X_j , we consider two models for a chosen lag *l*:

Unrestricted model(U) is regressing present value of X_j with every variable's past values including itself

$$X_{t}^{j} = \sum_{k=1}^{D} (a_{jk,1}X_{t-1}^{k} + \dots + a_{jk,l}X_{t-l}^{k}) + u_{t}^{j}$$

Restricted model(R) is regressing the present value of X_j with every variable's past value excluding X_i

$$X_{t}^{j} = \sum_{k=1,k\neq i}^{D} (b_{jk,1}X_{t-1}^{k} + \dots + b_{jk,l}X_{t-l}^{k}) + e_{t}^{j}$$

The Conditional Granger Causality Index is given as

$$\mathbf{CGCI}_{X_i \to X_j} = \ln \frac{\sigma_R^2}{\sigma_U^2}$$

where σ_R^2 and σ_U^2 are variances of restricted and unrestricted models post regression, with a higher index implying stronger link.

4 OUR METHOD

Using the previously established methods as a basis, the concepts of self-attention and Granger Causality are combined to devise a novel algorithm to establish causal relationships. The attention module is modified to select and train on a subset of the original dataset that holds the most important time instances. We introduce Sparse Attention Transformer as shown in [Figure 1].

Temporal attention: The time-series data $X \in \mathbb{R}^{T \times D}$ can be split into samples of input vectors $X' = \{X_{t-1}, X_{t-2}, ..., X_{t-k}\}$ and the output vector $X_t \forall t > k$ when it demonstrates no delays. The presence of small, random delays can be visualized by modeling X_t as a function of $\{X_{t-1-l_1}, ..., X_{t-k-l_k}\}$ such that $0 \le l_i \le k \forall$ $i \in [1, k]$. As the data exhibits long-range dependencies in the past, these small delays can be approximated to be upper bounded by the lag value k. Hence, the following inequalities can be deduced:

$$t - 1 - k \le t - 1 - l_1 \le t - 1$$

Transformers with Sparse Attention for Granger Causality



Figure 1: Sparse Attention Transformer Model Architecture

$$\dots$$
$$t - 2k \le t - k - l_1 \le t - k$$

Thus, $t - 2k \leq t - i - l_i \leq t - 1 \forall i \in [1, k]$, which indicates the length of the sliding window to be 2k to establish the influence of past 2k time steps on the present values and pick the k most important time instances. This is analogous to finding the k unknown lags that determine the exact time steps causing the current vector. The above task is achieved by using a temporal attention module. The time-series data $X \in R^{T \times D}$ can be split into a sequence of T - 2k input vectors $\{\{X_1, X_2, ..., X_{2k}\}, \{X_2, X_3, ..., X_{2k+1}\}, ..., \{X_{T-2k}, X_{T-2k+1}, ..., X_{T-1}\}\}$ and their corresponding output vectors $\{X_{2k+1}, X_{2k+2}, ..., X_T\}$. Consider an input-output pair at a current time instance t. The input vector $X' \in R^{2k \times D}$ is modeled as an input sequence with 2k tokens, each having an embedding dimension D. The vector X' is then linearly transformed into queries, keys and values as follows:

$$\begin{array}{l} Q_1 = X' W_{Q_1}, W_{Q_1} \in R^{D \times d_{k_1}} \\ K_1 = X' W_{K_1}, W_{K_1} \in R^{D \times d_{k_1}} \\ V_1 = X' W_{V_1}, W_{V_1} \in R^{D \times d_{k_1}} \end{array}$$

A temporal mask is further applied to prevent the future tokens from being attended. This *mask* is of dimensions $2k \times 2k$ and has its lower triangular and diagonal elements 0 and the remaining as $-\infty$. The temporal attention matrix $A_t \in \mathbb{R}^{2k \times 2k}$ is obtained as

$$A_t = softmax(\frac{Q_1K_1^T}{\sqrt{d_{k_1}}} + mask)$$

Every entry A_{ij} indicates the importance weight $\in [0,1]$ with which token (time instance in this case) j is influencing i. The matrix A is a lower triangular matrix with entries in each row summing to 1. This is in accordance with the usual attention weights interpretation, as for a given row, the sum of weights of all the tokens influencing it is 1.

We now analyze the physical significance of the column sums of this matrix. The mean of a column j indicates the average influence that time-instance j has on all other time-instances. It is evident that comparing column sums is equivalent to comparing column means as they only differ through a scaling factor of 2k. Thus, a column with the largest sum corresponds to the time-instance that is most important in predicting the output vector.

Let $S = \{s_1, s_2, ..., s_{2k}\}$ be the column sum vector of the temporal attention matrix. We pick *k* indices with the largest column sums which essentially represent the *k* most important time instances in predicting X_t . Let us denote this index set as I_k . We proceed by modifying the input vector $X' = \{X_1, X_2, ..., X_{2k}\}$ as $X'' \in \mathbb{R}^{k \times D}$ such that $X'' = \{X_i | i \in I_k\}$.

Inter-variable Attention: To compute attention between the variables, we start by reformulating the structure of the input. We now transpose X'' and model it as an input sequence with D tokens, each having an embedding dimension k. This modified input vector

 $X''' = (X'')^T \in \mathbb{R}^{D \times k}$ is linearly transformed into queries, keys and values as follows:

$$\begin{array}{l} Q_2 = X''' W_{Q_2}, W_{Q_2} \in R^{k \times d_{k_2}} \\ K_2 = X''' W_{K_2}, W_{K_2} \in R^{k \times d_{k_2}} \\ V_2 = X''' W_{V_2}, W_{V_2} \in R^{k \times 1} \end{array}$$

On performing self-attention between queries and keys of this input in a similar way, we obtain the attention matrix $A_d \in \mathbb{R}^{D \times D}$ capturing the dependencies of the D variables over each other as:

$$A_d = softmax(\frac{Q_2 K_2^T}{\sqrt{d_{k_2}}})$$

The matrix A_d is multiplied with V_2 to generate the output vector $Y \in \mathbb{R}^{D \times 1}$ that is backpropagated with respect to X_t to minimize the loss function.

Granger Causality using Attention: The transformer model trained using the above method is now deployed at the inference stage on the given dataset, masking the effect of every variable one at a time. This is achieved by using a mask before applying softmax while computing scaled dot-product attention matrix A_d . We apply a $D \times D$ mask with entries of the i^{th} column as $-\infty$ and others as 0 to mask the effect of the i^{th} variable. Hence, new predictions for X_t are obtained with each column being masked individually, keeping the parameters of the model learned during training constant. We now compute the standard deviation of errors for the unrestricted model (predictions obtained during the training phase) and restricted model (predictions obtained during the inference stage by masking variables one by one) and calculate the Granger Causality Index of every variable with past instances of every other variable. We normalize the obtained Granger Causality matrix by dividing each entry with the maximum value in the matrix, producing a final causation matrix as shown in Algorithm 1.

5 EXPERIMENTAL SETUP

5.1 Dataset

We modelled our data generation process based on the framework presented in the Causality 4 Climate (C4C) challenge as part of the NeurIPS 2019 competitions track[10]. The data is generated by a function that given the number of variables and maximum lag, creates a graph with probabilistic edges, where weights (linear coefficients) and delays are uniformly sampled, and the data is iteratively accumulated over time steps. The performance of the model is evaluated on such time-homogenous linear datasets with endogenous variables. We generate 20 different datasets each with 150 time-steps for every group. We also alter the number of variables, to obtain a total of 80 datasets across 4 groups. The maximum CODS-COMAD Dec '24, December 18-21, 2024, Jodhpur, India

Riya Mahesh, Rahul Vashisht, and Chandrashekar Lakshminarayanan

Algorithm 1: Sparse Attention Transformers for Granger Causality **Input:** Data *X* with *T* time samples $X(1), \ldots, X(T)$ over *D* variables **Output:** Causation matrix \hat{A} of dimension $D \times D$ $Y \leftarrow (X(2k+1), \dots, X(T))$ $X_{past} \leftarrow X(1) \cdots X(2k)$ $X(T-2k)\cdots X(T-1)$ $Y' = \phi$ ▶ List of output vectors of unrestricted model $Y_l' = \phi \ \forall \ l \in [1, D]$ ▶ List of output vectors on masking l^{th} variable for $i \in [0, T - 2k - 1]$ do $(x,y) = X_{past}[i], Y[i]$ **Temporal Attention:** ► $x \in R^{2k \times D}, W_{Q_1} \in R^{D \times d_{k_1}}$ ► $x \in R^{2k \times D}, W_{K_1} \in R^{D \times d_{k_1}}$ $Q_1 = x W_{O_1}$ $K_1 = x W_{K_1}$ mask $M \in \mathbb{R}^{2k \times 2k}$ $M_{ii} = -\infty \forall i < j$ 0 otherwise $A_t = softmax(\frac{Q_1K_1^T}{\sqrt{d_{k_1}}} + M)$ $\triangleright A_t \in R^{2k \times 2k}$ for $l \in [1, 2k]$ do $s_l = \sum_{j=1}^{2k} A_{jl}$ end I_k = Set of k indices with largest s_k values $x' = \{x(p) \mid p \in I_k\}$ ▶ $x'' \in R^{D \times k}$ $x^{\prime\prime} = (x^{\prime})^T$ Attention between variables: Unrestricted model (Training Phase) $\triangleright W_{Q_2} \in R^{k \times d_{k_2}}$ $Q_2 = x^{\prime\prime} W_{O_2}$ $\triangleright W_{K_2} \in \mathbb{R}^{k \times d_{k_2}}$ $K_2 = x^{\prime\prime} W_{K_2}$ $V_2 = x^{\prime\prime} W_{V_2}$ $\triangleright W_{V_2} \in \mathbb{R}^{k \times 1}$ $A_d = softmax(\frac{Q_2 K_2^T}{\sqrt{du}})$ $\triangleright A_d \in R^{D \times D}$ ▷ $y' \in R^{D \times 1}$ $y' = A_d V_2$ Backpropagate y' w.r.t y using MSE loss $Y' \leftarrow Y' \cup \{y'\}$ Restricted model (Evaluation phase) for $l \in [1, D]$ do Mask $x_l'' \forall k$ time steps Pass through the trained model $\rightarrow y'_{l}$ $Y'_l \leftarrow Y'_l \cup \{y'_l\}$ end end for $l \in [1, D]$ do Find σ_1^2 using Y' and Y $\triangleright \sigma_l^2$ is variance in l^{th} variable in unrestricted model Find $\sigma_{l_1}^2, \dots, \sigma_{l_D}^2$ using Y'_l and $Y \ge \sigma_{l_m}^2$ is variance in m^{th} variable when l^{th} is masked $\hat{A}_{lm} = \ln \left(\frac{\sigma_{lm}^2}{\sigma_m^2} \right) \quad \forall m \in [1, D]$ end $\hat{A} = \frac{\hat{A}}{\max \hat{A}_{i,j}}$

lag dependency in the synthetically generated data is 10. Hence, we use a window size of 20 (2k) and pick the top 10 (k) elements in our transformer model.

5.2 Training Details

Two single-head self-attention layers are used for capturing time instance dependencies and relations between the variables respectively. The input vector is passed through the positional embedding layer to preserve the temporal order of the observed variables. Adam optimizer[5] with Mean Squared Error Loss function is used to train SAT.

| No. of variables | Our method | | VAR Granger Causality | |
|------------------|------------|----------|-----------------------|----------|
| | AUC-ROC | F1 score | AUC-ROC | F1 score |
| 4 | 0.77 | 0.72 | 0.47 | 0.63 |
| 5 | 0.71 | 0.69 | 0.49 | 0.51 |
| 6 | 0.70 | 0.63 | 0.67 | 0.66 |
| 10 | 0.78 | 0.65 | 0.63 | 0.62 |

| Table 1: Comparison of mean AUC-ROC and F1 scores across the |
|--|
| three groups of data samples with $D=4, 5, 6$ |



Figure 2: ROC plots across four groups of data samples- D=4, 5, 6, 10; D indicating the number of variables in the time-series

6 RESULTS AND DISCUSSION

We choose the AUC-ROC measure and F1 scores between the causation matrix and ground truth causality matrix as metrics to evaluate performance across various datasets, grouped into sets based on the number of variables in Table 1. The ROC plots generated using our method for each of the cases is reported in Figure 2. Vector Autoregression (VAR) based Granger Causality[12] with the same window size of 20 is used as a baseline algorithm for our analysis. For the chosen evaluation metrics, mean scores across all the 20 datasets for each group obtained using our method and the baseline are compared. We show that Sparse Attention Transformer performs significantly better than the baseline method.

7 CONCLUSION

In this work, we introduce Sparse Attention Transformer model for Granger Causality. We address the problem of the presence of random delayed effects in time series data and our model successfully identifies the importance weights associated with every variable in predicting the others. Our method outperforms the traditional Granger Causality approach for the synthetic datasets considered. Future work includes extending the method to non-linear as well as non-stationary datasets and explaining the exact mathematical relation of multi-head attention weights with causality coefficients. Transformers with Sparse Attention for Granger Causality

CODS-COMAD Dec '24, December 18-21, 2024, Jodhpur, India

REFERENCES

- Chainarong Amornbunchornvej, Elena Zheleva, and Tanya Y Berger-Wolf. 2019. Variable-lag granger causality for time series analysis. In 2019 IEEE International Conference on Data Science and Advanced Analytics (DSAA). IEEE, 21–30.
- John Geweke. 1984. Inference and causality in economic time series models. Handbook of econometrics 2 (1984), 1101–1144.
- [3] Clive WJ Granger. 1969. Investigating causal relations by econometric models and cross-spectral methods. *Econometrica: journal of the Econometric Society* (1969), 424–438.
- [4] Uzma Hasan, Emam Hossain, and Md Osman Gani. 2023. A survey on causal discovery methods for iid and time series data. arXiv preprint arXiv:2303.15027 (2023).
- [5] Diederik P Kingma and Jimmy Ba. 2014. Adam: A method for stochastic optimization. arXiv preprint arXiv:1412.6980 (2014).
- [6] Valentyn Melnychuk, Dennis Frauen, and Stefan Feuerriegel. 2022. Causal transformer for estimating counterfactual outcomes. In International Conference on Machine Learning. PMLR, 15293–15329.
- [7] Eshaan Nichani, Alex Damian, and Jason D Lee. 2024. How transformers learn causal structure with gradient descent. arXiv preprint arXiv:2402.14735 (2024).
- [8] Raanan Y Rohekar, Yaniv Gurwicz, and Shami Nisimov. 2024. Causal Interpretation of Self-Attention in Pre-Trained Transformers. Advances in Neural Information Processing Systems 36 (2024).
- [9] Jakob Runge, Sebastian Bathiany, Erik Bollt, Gustau Camps-Valls, Dim Coumou, Ethan Deyle, Clark Glymour, Marlene Kretschmer, Miguel D Mahecha, Jordi Muñoz-Marí, et al. 2019. Inferring causation from time series in Earth system sciences. *Nature communications* 10, 1 (2019), 2553.
- [10] Jakob Runge, Xavier-Andoni Tibau, Matthias Bruhns, Jordi Muñoz-Marí, and Gustau Camps-Valls. 2020. The causality for climate competition. In *NeurIPS* 2019 Competition and Demonstration Track. PMLR, 110-120.
- [11] Xiao Shou, Debarun Bhattacharjya, Tian Gao, Dharmashankar Subramanian, Oktie Hassanzadeh, and Kristin P Bennett. 2024. Pairwise causality guided transformers for event sequences. Advances in Neural Information Processing Systems 36 (2024).
- [12] Elsa Siggiridou and Dimitris Kugiumtzis. 2015. Granger causality in multivariate time series using a time-ordered restricted vector autoregressive model. *IEEE*

Transactions on Signal Processing 64, 7 (2015), 1759–1773.

- [13] Dmitry A Smirnov and Igor I Mokhov. 2009. From Granger causality to long-term causality: Application to climatic data. *Physical Review E—Statistical, Nonlinear,* and Soft Matter Physics 80, 1 (2009), 016208.
- [14] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. 2017. Attention is all you need. Advances in neural information processing systems 30 (2017).
- [15] Sebastian Weichwald, Martin E Jakobsen, Phillip B Mogensen, Lasse Petersen, Nikolaj Thams, and Gherardo Varando. 2020. Causal structure learning from time series: Large regression coefficients may predict causal links better in practice than small p-values. In *NeurIPS 2019 Competition and Demonstration Track*. PMLR, 27–36.
- [16] Dongxia Wu, Tsuyoshi Idé, Georgios Kollias, Jiri Navratil, Aurelie Lozano, Naoki Abe, Yian Ma, and Rose Yu. 2024. Learning Granger Causality from Instancewise Self-attentive Hawkes Processes. In International Conference on Artificial Intelligence and Statistics. PMLR, 415–423.
- [17] Chonghao Zhang, Linlin Zhao, Zhefeng Yin, and Zhenguo Zhang. 2023. Causalformer: Causal Discovery-based Transformer for Multivariate Time Series Forecasting. 1–6. https://doi.org/10.1109/CISP-BMEI60920.2023.10373365
- [18] Cheng Zhang, Xiong Zou, and Chuan Lin. 2022. Fusing XGBoost and SHAP models for maritime accident prediction and causality interpretability analysis. *Journal of Marine Science and Engineering* 10, 8 (2022), 1154.
- [19] Wei Zhang, Thomas Panum, Somesh Jha, Prasad Chalasani, and David Page. 2020. Cause: Learning granger causality from event sequences using attribution methods. In *International Conference on Machine Learning*. PMLR, 11235–11245.
- [20] Yifan Zhang, Rui Wu, Sergiu M Dascalu, and Frederick C Harris Jr. 2024. Sparse transformer with local and seasonal adaptation for multivariate time series forecasting. *Scientific Reports* 14, 1 (2024), 15909.
- [21] Haoyi Zhou, Shanghang Zhang, Jieqi Peng, Shuai Zhang, Jianxin Li, Hui Xiong, and Wancai Zhang. 2021. Informer: Beyond efficient transformer for long sequence time-series forecasting. In Proceedings of the AAAI conference on artificial intelligence, Vol. 35. 11106–11115.
- [22] Yaqi Zhu, Fan Yang, and Andrei Torgashov. 2024. Causal-Transformer: Spatialtemporal causal attention-based transformer for time series prediction. IFAC-PapersOnLine 58, 14 (2024), 79–84.