Enhancing Medical Image Segmentation with Deep Learning and Diffusion Models

Houze Liu New York University New York, USA Tong Zhou Rice University Houston, USA Yanlin Xiang University of Houston Houston, USA

Aoran Shen University of Michigan Ann Arbor, USA Jiacheng Hu Tulane University New Orleans, USA Junliang Du* Shanghai Jiao Tong University Shanghai, China

Abstract—Medical image segmentation is crucial for accurate clinical diagnoses, yet it faces challenges such as low contrast between lesions and normal tissues, unclear boundaries, and high variability across patients. Deep learning has improved segmentation accuracy and efficiency, but it still relies heavily on expert annotations and struggles with the complexities of medical images. The small size of medical image datasets and the high cost of data acquisition further limit the performance of segmentation networks. Diffusion models, with their iterative denoising process. offer a promising alternative for better detail capture in segmentation. However, they face difficulties in accurately segmenting small targets and maintaining the precision of boundary details. This article discusses the importance of medical image segmentation, the limitations of current deep learning approaches, and the potential of diffusion models to address these challenges.

Keywords-component; Medical Image Segmentation, Diffusion Models, Boundary Accuracy.

I. INTRODUCTION

Disease information contained in medical images is particularly important when doctors make clinical diagnoses. The purpose of medical image segmentation is to train a machine learning model to learn the characteristics of target objects from expert annotations and apply them to test images [1]. Good medical image segmentation results can maximize the utility of medical images, while inaccurate segmentation results can lead to very serious problems. Over-segmentation may damage tissue surrounding the lesion, while undersegmentation may affect the patient's condition. However, in many cases, the contrast between the lesion area and normal tissue is low, the boundaries of the lesion area are sometimes unclear, the differences between the target and the background are not obvious, and for the same disease, images from different patients may vary. Therefore, continuously improving the accuracy of medical image segmentation can help doctors analyze and judge lesion tissues more accurately, thereby improving treatment effectiveness.

With the development of deep learning technology, relatively mature systems have been established in many

research fields, such as natural language processing and graph networks[2]. It has also been applied in areas like risk management [3] and generative language [4-5]. Automatic learning of segmentation results has become an important direction in the field of medical image segmentation, improving segmentation accuracy to some extent while saving doctors' time and alleviating pressure. Although people hope that deep learning algorithms can further assist experts in diagnosing diseases and improve segmentation efficiency, the annotation of medical images still heavily relies on the judgment of medical experts. Due to blurred target boundaries in medical images, errors in human judgment, and disagreements between different experts, using deep learning for segmentation of regions of interest inevitably introduces certain errors. The complexities in the segmentation process mean that deep learning methods still have room for improvement. At the same time, segmentation networks require a large amount of data for training to better adjust parameters and improve network performance. However, the process of acquiring medical images is quite difficult, and the cost of obtaining data and annotations is high [6]. Therefore, medical image datasets are usually small, making it challenging to use these data to train a segmentation network with good performance. Currently, some classic image segmentation networks do not perform well when segmenting medical images, especially when facing the various complexities of medical images, resulting in large errors.

Recently, diffusion models, as a class of powerful generative models, have been rising due to their good generative capabilities [7]. Diffusion models consist of two phases: forward diffusion and reverse diffusion. In the forward diffusion process, clean images are gradually disturbed by Gaussian noise until they approximate a Gaussian distribution; in the reverse diffusion process, Gaussian noise is sampled, and a trained denoising deep neural network is used to iteratively denoise the data to obtain clean images [8]. Diffusion models perform iterative denoising and gradual learning, unlike deep learning segmentation methods that segment directly in one step, thus allowing them to better account for target details in

medical image segmentation, making the network more robust and producing better performance. However, since the accuracy of target boundaries is very important in medical image segmentation, previous diffusion probabilistic models often struggle to meet the need for segmentation boundary accuracy when performing medical image segmentation. At the same time, regions of interest in medical images often vary in size, and diffusion models often struggle to effectively segment small target areas during segmentation. Although U-shaped denoising networks use skip connections to supplement shallow information, there is a semantic gap between shallow and deep information, so the effect on small target segmentation is limited.

We propose a Boundary-information-enhanced Diffusion Segmentation Network (BIEDSNet), mainly targeting the problems of unclear boundaries of regions of interest in medical images and indistinct contrast differences with surrounding tissues. In the conditional feature encoder, we utilize average pooling to design a Boundary Feature Fusion Module (BFFM) to effectively mine boundary information and fuse it into conditional features. The fused conditional features are concatenated with the encoder layer features of the denoising network, thereby incorporating boundary features into every step of the diffusion model's denoising process, improving the segmentation accuracy of target boundaries.

II. BACKGROUND

Advances in deep learning and diffusion models have paved the way for more precise and reliable medical image segmentation, which is critical in clinical decision-making. This section highlights key contributions relevant to our work, focusing on techniques that enhance segmentation performance, boundary detection, and iterative refinement.

Numerous studies have proposed improvements in segmentation accuracy and model robustness, particularly for challenging images. For instance, D. Sun et al. [9] explored a segmentation approach integrating bilateral spatial attention with transfer learning, emphasizing the role of attention mechanisms in refining feature extraction and enhancing accuracy—a technique that informs the boundary-sensitive aspects of our work. Similarly, Y. Zi et al. [10] applied deep learning for complex image analysis, demonstrating the capability of deep networks to adapt to high-dimensional data and extract intricate features, an essential element in our boundary-focused diffusion model.

Diffusion models, known for their iterative denoising process, have shown potential in capturing fine details and maintaining feature integrity in image segmentation tasks. This characteristic aligns with the needs of medical segmentation, where precision in boundaries and small regions is crucial. Additionally, J. Wei et al. [11] presented self-supervised learning techniques within graph neural networks, highlighting a method for enhancing feature extraction without extensive labeled data, which is particularly useful given the typically small datasets in medical imaging.

Several studies have further investigated how neural networks can be adapted to capture complex structural details

in segmented regions, contributing insights into efficient feature fusion and data representation. For example, Y. Cang et al. [12] leveraged neural networks for extracting and enhancing deep feature representations, showcasing the potential of layered architectures to capture diverse and nuanced features—a key concept in designing boundary-enhanced modules. Moreover, neural networks have also been employed to achieve adaptable and high-accuracy predictions across varied data conditions, as demonstrated by X. Yan et al. [13], supporting our objective to refine boundary representation in variable imaging contexts.

Additionally, generative models such as GANs have been effective in capturing diverse feature representations across complex datasets. Z. Wu et al. [14] introduced a lightweight generative approach to fuse complementary information, a method that aligns with our use of iterative refinement in boundary features. This work emphasizes how generative models can maintain data fidelity across transformations, informing our approach to detail preservation in diffusion-based segmentation.

Lastly, the challenges of handling sensitive medical data have led to privacy-preserving mechanisms, as discussed by X. Fei et al. [15], which underscore the importance of efficient data handling and secure model deployment in medical imaging applications.

The process of solving image segmentation problems based on deep learning mainly consists of three parts: neural network models, image preprocessing, and loss functions. Currently, the U-shaped structure based on convolutional neural networks (CNNs) is the most commonly used deep learning network model structure for image segmentation tasks. Its origin can be traced back to 2015, when researchers proposed a fully convolutional network with an encoder-decoder structure, which discarded fully connected layers, used convolutional layers and deconvolution operations for upsampling, and combined skip connections to merge high and low-level feature maps, achieving pixel-level classification prediction.

With the success of Transformer neural networks in the field of natural language processing [16-18]and other image processing domains, to address the shortcomings of convolutional neural networks in establishing long-distance dependency relationships, TransUNet [19], while maintaining the U-Net encoder-decoder structure, introduced Transformers and convolutional neural networks to form a hybrid encoder for the first time, achieving segmentation performance beyond models that use only convolutional neural networks.

Subsequently, the U-shaped encoder-decoder model based on Swin Transformer, SwinUnet [20], has achieved even better medical image segmentation performance than TransUNet. From U-Net to the current SwinUnet, the success of a series of network models has proven that the U-shaped encoder-decoder architecture can effectively capture semantic information in medical images, making the model more accurate and comprehensive in learning and understanding the structure of medical images. Therefore, the encoder-decoder architecture has also become the most widely used model architecture in the

field of medical image segmentation, promoting the development of medical image segmentation technology.

III. METHOD

Accurate segmentation of regions of interest in medical

accuracy and mitigate its sensitivity to outliers, we use SmoothL1 loss instead of the commonly used Mean Squared Error (MSE) loss in diffusion models, forming the final joint diffusion segmentation loss. Based on this, we explore a Boundary-information-enhanced Diffusion Segmentation




Figure 1: BIEDSNet




Figure 2: Boundary Feature Fusion Module (BFFM)

images can help doctors better diagnose and treat conditions. Both under-segmentation and over-segmentation can significantly impact disease assessment, making the segmentation of boundaries in regions of interest in medical images crucial. Medical images themselves are complex, with regions of interest such as lesions or organs often adhering to surrounding tissues and having blurred target boundaries. These factors affect the accuracy of network segmentation of boundaries in regions of interest. Therefore, improvements to diffusion models are made to enhance the accuracy of boundary segmentation in regions of interest.

To generate segmentation masks for specific images, feature information from the original image is incorporated into the encoding phase of the denoising network. Inspired by Wang et al. [21], when conditioning on the original image, we design a Boundary Feature Fusion Module (BFFM) to extract and fuse boundary features, incorporating boundary information into each step of the denoising process. Additionally, to focus the denoising network's attention on more important features, we design an Attention-denoising Residual Block (ADRB) that combines channel attention and spatial attention, further improving the network's denoising capability and enhancing its ability to learn image features. To more effectively constrain the denoised image, the denoising network directly predicts the segmentation mask rather than noise, and a segmentation loss is added. Furthermore, to improve the network's segmentation

Network (BIEDSNet).

A. BIEDSNet

BIEDSNet is designed based on the diffusion model and consists of two main parts: a conditional feature encoder and a denoising network. The conditional feature encoder is constructed using Boundary Feature Fusion Modules, with each layer of the conditional feature encoder containing one BFFM. The denoising network is built with Attention-denoising Residual Blocks, with each encoder and decoder layer containing three ADRBs, as shown in Figure 1.

B. Boundary Feature Fusion Module

As a generative model, diffusion models often generate different images, so before each denoising step, the original image is concatenated with the current denoised image to induce the diffusion model to generate a segmentation map for a specific image. To better utilize the information from the original image, a conditional feature encoder is added, with each layer of features from the conditional feature encoder concatenated to the features of each layer of the denoising network encoder.

The average pooling process typically takes the average value of a rectangular region, which to some extent preserves background information in the feature map and enhances overall features. The boundaries of lesion areas in medical images often provide important information, but these boundaries are usually unclear, and regions of interest adhere to surrounding tissues. To better supplement boundary features during the denoising process, we design a simple and effective Boundary Feature Fusion Module (BFFM) using average pooling layers. This module extracts boundary features at various layers of the conditional feature encoder, incorporates a channel attention mechanism for better fusion, and uses depthwise separable convolution to change the number of feature channels and reduce parameters, as shown in Figure 2.

The input features go through two convolution blocks to obtain the original features, which can be expressed by equation (1):

$$F_1 = CBR\left(CBR(F_{\text{input}})\right),\tag{1}$$

where CBR represents the combination of a convolution layer, batch normalization layer, and ReLU activation function.

The original features pass through three average pooling layers of different sizes to obtain global features. Then, using a residual-like form, edge features are obtained by subtracting the global features from the original feature maps, specifically calculated as shown in equation (2):

$$F_{\text{edge 1}} = F_1 - \text{AvgPool 3}(F1),$$

$$F_{\text{edge 2}} = F_1 - \text{AvgPool 5}(F1),$$

$$F_{\text{edge 3}} = F_1 - \text{AvgPool 7}(F1).$$
(2)

The edge features of multiple granularities are concatenated with the original features, as shown in equation (3):

$$F_{\text{edge}} = \text{Concat}(F_1, F_{\text{edge 1}}, F_{\text{edge 2}}, F_{\text{edge 3}}).$$
 (3)

Then, after average pooling, convolution is used to compress and restore the number of channels to obtain channel attention weights, which are then allocated. Finally, a depthwise separable convolution changes the number of input feature channels to obtain the output of this encoder layer.

The specific calculation process is shown in equation (4): F_{output}

=
$$DConv(F_{concat})$$

 $\cdot Sig(Conv(ReLU(Conv(AvgPool(F_{edge}))))),$ (4)

where DConv represents depthwise separable convolution, $F_{\rm concat}$ represents the concatenation operation, Sig represents the Sigmoid activation function, Conv represents the convolution operation, and AvgPool represents the average pooling layer.

C. Attention-denoising Residual Block

As convolutional blocks increase, convolutional networks typically lose some image information, such as image details. To focus the network's attention on more important features, an attention mechanism is added to the denoising residual block, designing an Attention-denoising Residual Block (ADRB). The U-shaped denoising network is built using attention denoising residual blocks, with each layer of the denoising network encoder and decoder containing three ADRBs. ADRB

enhances important features while alleviating the vanishing gradient problem and improving the network's ability to learn features.

ADRB is built based on convolution, batch normalization, and activation functions. The input features are processed in two paths: one path directly goes through convolution layer, batch normalization layer, and activation function. The other path goes through convolution layer, batch normalization layer, activation function, and is then added with step information that has gone through activation function and linear layer, followed by another set of convolution layer, batch normalization layer, and activation function. The features from both paths are summed to obtain the final residual features. The specific calculation method is shown in equation (5):

$$F_{\text{residual}} = \text{CGR}(F_{\text{input}}) + CGR(RL(Emb) + CGR(F_{\text{input}}))$$
 (5)

IV. EXPERIMENT

A. Dataset

The COVID-19 image dataset was collected by the Italian Society of Medical and Interventional Radiology, consisting of CT images from 20 cases. The data used in this paper selected 1490 images from this dataset, and according to the principle of case exclusivity, it was divided into training, validation, and testing sets in the ratio of 8:1:1, namely 1192 training set images, 149 validation set images, and 149 testing set images. The images in this dataset vary in size, with two sizes of 512×512 and 630×630 . To ensure the consistency of the input image size for the network, the images were scaled to a size of 256×256 .

Table 1. Comparative Experiment Results

Method	Dice↑	HD↓	IoU↑	Acc↑	Rec↑	Pre↑
UNet	0.7037	2.9616	0.5917	0.9769	0.6284	0.8005
UNet++	0.7291	2.7829	0.6121	0.9772	0.6255	0.8255
AttentionUNe t	0.7113	2.8352	0.5955	0.9770	0.6441	0.7923
UNeXt	0.6653	2.8358	0.5589	0.9775	0.6577	0.7265
SwinUNet	0.5698	2.9158	0.4616	0.9771	0.5882	0.6153
MedSegDiff	0.7424	2.7798	0.6182	0.9767	0.5670	0.8745
BIEDSNet	0.7578	2.7090	0.6322	0.9764	0.5440	0.8924

B. Comparative Experiment

To better validate the segmentation effect of BIEDSNet, it was compared with classic and cutting-edge image segmentation networks under the same experimental settings. Classic segmentation networks include UNet, UNet++, AttentionUNet [22], and cutting-edge segmentation networks include UNeXt, SwinUNet, MedSegDiff [23]. The segmentation results of each algorithm are as follows.

According to Table 1, BIEDSNet outperformed the other networks in most metrics for COVID-19 image segmentation, achieving the highest Dice (0.7578) and IoU (0.6322) scores. BIEDSNet also showed competitive HD (2.7090) and Precision

(0.8924) values, although its Recall (0.5440) was slightly lower. These results demonstrate the effectiveness of BIEDSNet's boundary feature fusion and attentional denoising mechanisms in enhancing segmentation performance.

C. Ablation Experiment

Table 2. Ablation Experiment Results

BFFM	ADRB	Dice↑	HD↓	IoU↑	Acc↑	Rec↑	Pre↑
×	×	0.7233	2.9764	0.6045	0.9748	0.5037	0.9155
\checkmark	×	0.7308	2.8655	0.6104	0.9760	0.5433	0.8745
\checkmark	\checkmark	0.7444	2.8032	0.6252	0.9760	0.5288	0.8978
$\sqrt{}$	\checkmark	0.7512	2.7390	0.6264	0.9765	0.5619	0.8778
\checkmark	\checkmark	0.7578	2.7090	0.6322	0.9764	0.5440	0.8924

Ablation experiments on the COVID-19 image dataset assessed each module's impact on segmentation performance. Without the joint diffusion segmentation loss, the network used mean squared error loss. Results in Table 2 show that each module—the boundary feature fusion, attentional denoising residual block, joint diffusion segmentation loss, and multilayer supervision—contributed to performance gains. The boundary feature fusion module notably reduced Hausdorff distance, improving boundary precision. The attentional denoising block enhanced Dice and IoU metrics by highlighting essential COVID-19 features. The joint diffusion loss reduced outlier sensitivity, improving accuracy, while the multi-layer supervision boosted feature extraction, collectively enhancing BIEDSNet's performance.

V. CONCLUSION

This study's introduction of BIEDSNet in the context of medical image segmentation contributes a valuable advancement in AI-driven healthcare and demonstrates a broader influence across AI research fields. By effectively addressing issues like boundary precision and target contrast in medical imaging, BIEDSNet exemplifies how diffusion models can be tailored to overcome challenges in high-stakes, complex image segmentation tasks. The proposed integration of a Boundary Feature Fusion Module and iterative denoising within a diffusion framework not only raises the standard for segmentation accuracy but also inspires new possibilities for enhancing model architectures in areas such as autonomous driving, remote sensing, and geospatial analysis, where precise delineation of objects in varying contrasts and sizes is crucial. This work suggests a path forward for the integration of boundary-sensitive enhancements in diffusion models, encouraging further research into adaptable segmentation techniques that could broadly improve performance and reliability across diverse AI applications reliant on fine-grained image analysis.

REFERENCES

- S. He, Y. Feng, P. E. Grant, Y. Liang, and Y. Xie, "Segmentation ability map: Interpret deep features for medical image segmentation," *Medical Image Analysis*, vol. 84, p. 102726, 2023.
- [2] Y. Dong, S. Wang, H. Zheng, J. Chen, Z. Zhang, and C. Wang, "Advanced RAG

- models with graph structures: Optimizing complex knowledge reasoning and text generation," arXiv preprint arXiv:2411.03572, 2024.
- [3] J. Yao, J. Wang, B. Wang, B. Liu, and M. Jiang, "A hybrid CNN-LSTM model for enhancing bond default risk prediction," Journal of Computer Technology and Software, vol. 3, no. 6, 2024.
- [4] J. Chen, R. Bao, H. Zheng, Z. Qi, J. Wei, and J. Hu, "Optimizing retrieval-augmented generation with Elasticsearch for enhanced question-answering systems," arXiv preprint arXiv:2410.14167, 2024.
- [5] C. Wang, Y. Dong, Z. Zhang, R. Wang, S. Wang, and J. Chen, "Automated genre-aware article scoring and feedback using large language models," arXiv preprint arXiv:2410.14165, 2024.
- [6] N. Tajbakhsh, L. Jeyaseelan, Q. Li, J. Chiang, Z. Wu, and X. Yu, "Embracing imperfect datasets: A review of deep learning solutions for medical image segmentation," *Medical Image Analysis*, vol. 63, p. 101693, 2020.
- [7] H. Cao, C. Tan, Z. Gao, and Q. Zheng, "A survey on generative diffusion models," IEEE Transactions on Knowledge and Data Engineering, 2024.
- [8] X. Yan, Y. Jiang, W. Liu, D. Yi, and J. Wei, "Transforming multidimensional time series into interpretable event sequences for advanced data mining," arXiv preprint arXiv:2409.14327, 2024.
- [9] D. Sun, M. Sui, Y. Liang, J. Hu, and J. Du, "Medical image segmentation with bilateral spatial attention and transfer learning," Journal of Computer Science and Software Applications, vol. 4, no. 6, pp. 19-27, 2024.
- [10] Y. Zi, X. Cheng, T. Mei, Q. Wang, Z. Gao, and H. Yang, "Research on intelligent system of medical image recognition and disease diagnosis based on big data," Proceedings of the 2024 IEEE 2nd International Conference on Image Processing and Computer Applications (ICIPCA), pp. 825-830, June 2024.
- [11] J. Wei, Y. Liu, X. Huang, X. Zhang, W. Liu, and X. Yan, "Self-supervised graph neural networks for enhanced feature extraction in heterogeneous information networks," arXiv preprint arXiv:2410.17617, 2024.
- [12] Y. Cang, Y. Zhong, R. Ji, Y. Liang, Y. Lei, and J. Wang, "Leveraging deep learning techniques for enhanced analysis of medical textual data," Proceedings of the 2024 IEEE 2nd International Conference on Sensors, Electronics and Computer Engineering (ICSECE), pp. 1259-1263, Aug. 2024.
- [13] X. Yan, W. Wang, M. Xiao, Y. Li, and M. Gao, "Survival prediction across diverse cancer types using neural networks," Proceedings of the 2024 7th International Conference on Machine Vision and Applications, pp. 134-138, 2024
- [14] Z. Wu, J. Chen, L. Tan, H. Gong, Y. Zhou, and G. Shi, "A lightweight GAN-based image fusion algorithm for visible and infrared images," Proceedings of the 2024 4th International Conference on Computer Science and Blockchain (CCSB), pp. 466-470, Sept. 2024.
- [15] X. Fei, S. Chai, W. He, L. Dai, R. Xu, and L. Cai, "A systematic study on the privacy protection mechanism of natural language processing in medical health records," Proceedings of the 2024 IEEE 2nd International Conference on Sensors, Electronics and Computer Engineering (ICSECE), pp. 1819-1824, Aug. 2024
- [16] B. Liu, J. Chen, R. Wang, J. Huang, Y. Luo, and J. Wei, "Optimizing news text classification with Bi-LSTM and attention mechanism for efficient data processing," arXiv preprint arXiv:2409.15576, 2024.
- [17] W. Liu, R. Wang, Y. Luo, J. Wei, Z. Zhao, and J. Huang, "A recommendation model utilizing separation embedding and self-attention for feature mining," arXiv preprint arXiv:2410.15026, 2024.
- [18] Y. Cang, W. Yang, D. Sun, Z. Ye, and Z. Zheng, "ALBERT-driven ensemble learning for medical text classification," Journal of Computer Technology and Software, vol. 3, no. 6, 2024.
- [19] J. Chen, Y. Lu, Q. Yu, H. Xie, and D. Zhou, "Transunet: Transformers make strong encoders for medical image segmentation," arXiv preprint arXiv:2102.04306, 2021.
- [20] H. Cao, Y. Wang, J. Chen, and X. Lu, "Swin-unet: Unet-like pure transformer for medical image segmentation," *European Conference on Computer Vision*, Cham: Springer Nature Switzerland, pp. 205-218, 2022.
- [21] W. Wang, M. Gao, M. Xiao, X. Yan, and Y. Li, "Breast cancer image classification method based on deep transfer learning," arXiv preprint arXiv:2404.09226, 2024.
- [22] Y. Sun, F. Bi, Y. Gao, and J. Hu, "A multi-attention UNet for semantic segmentation in remote sensing images," Symmetry, vol. 14, no. 5, p. 906, 2022.
- [23] J. Wu, R. Fu, H. Fang, and T. Lin, "Medsegdiff: Medical image segmentation with diffusion probabilistic model," *Medical Imaging with Deep Learning*, PMLR, pp. 1623-1639, 2024.