Quantum Algorithm for the Multiple String Matching Problem

Kamil Khadiev^{1[0000-0002-5151-9908]} and Danil Serov¹

Kazan Federal University, Kazan, Russia kamilhadi@gmail.com

Abstract. Let us consider the Multiple String Matching Problem. In this problem, we consider a long string, denoted by t, of length n. This string is referred to as a text. We also consider a sequence of m strings, denoted by S, which we refer to as a dictionary. The total length of all strings from the dictionary is represented by the variable L. The objective is to identify all instances of strings from the dictionary within the text. The standard classical solution to this problem is Aho-Corasick Algorithm that has O(n+L) query and time complexity. At the same time, the classical lower bound for the problem is the same $\Omega(n+L)$. We propose a quantum algorithm with $O(n + \sqrt{mL\log n} + m\log n)$ query complexity and $O(n + \sqrt{mL \log n} \log b + m \log n) = O^*(n + \sqrt{mL})$ time complexity, where b is the maximal length of strings from the dictionary. This improvement is particularly significant in the case of dictionaries comprising long words. Our algorithm's complexity is equal to the quantum lower bound $O(n + \sqrt{mL})$, up to a log factor. In some sense, our algorithm can be viewed as a quantum analogue of the Aho-Corasick algorithm.

Keywords: Aho–Corasick Algorithm \cdot strings \cdot quantum algorithms-query complexity \cdot search in strings \cdot string matching \cdot multiple string matching

1 Introduction

Let us consider the Multiple String Matching Problem. In this problem, we have a long string t of a length n that we call a text; and a sequence of m strings S that we call a dictionary. The total length of all strings from the dictionary is L, and the maximal length of the dictionary's strings is b. Our goal is to find all positions of strings from the dictionary in the text. The standard classical solution to this problem is Aho–Corasick Algorithm [3] that has O(n + L) time and query complexity.

We are interested in a quantum algorithm for this problem. There are many examples of quantum algorithms [40,6,21,1] that are faster than classical counterparts [42,17]. Particularly, we can find such examples among problems for strings processing [2,4,18,20,22,23,24,25,26,27,28,29,34,35,39,30]. One such problem is the String matching problem. That is checking whether a string s is

2 K. Khadiev and D. Serov

a substring of a string t. It is very similar to the Multiple String Matching Problem but with only one string in the dictionary. Additionally, in the String matching problem, we should find any position of s not all of them. The last difference can be significant for quantum algorithms. For this problem, we can use, for example, Knuth–Morris–Pratt algorithm [13,31] in the classical case with O(n + k) time and query complexity, where n is the length of t and k is the length of s. Other possible algorithms can be Backward Oracle Matching [5], Wu-Manber [43]. In the quantum case, we can use Ramesh-Vinay algorithm [41] with $O\left(\sqrt{n}\log\sqrt{\frac{n}{k}}\log n + \sqrt{k}(\log k)^2\right) =$ query complexity. We can say that query and time complexity of the Ramesh-Vinay algorithm is $O^*(\sqrt{n} + \sqrt{k})$, where O^* notation hides log factors. If we naively apply these algorithms to the Multiple String Matching Problem, then we obtain O(mn + L) complexity in the classical case, and $O\left(mn\log\sqrt{\frac{n}{b}}\log n + m^{1.5}\sqrt{L}(\log b)^2\right) = O^*(mn + m^{1.5}\sqrt{L})$ in the quantum case.

In the classical case, Aho–Corasick Algorithm [3] has better complexity that is O(n + L). Another possible algorithm that can work better in average is the Commentz-Walter algorithm [12]. In the quantum case, we suggest a new algorithm for the Multiple String Matching Problem with $O(n + \sqrt{mL \log n} + m \log n)$ query complexity and $O(n + \sqrt{mL \log n} \log b + m \log n)$ time complexity. So, we can say that both are $O^*(n + \sqrt{mL})$. At the same time, we show that the lower bound for classical complexity is $\Omega(n + l)$, and for quantum complexity, it is $\Omega(n + \sqrt{mL})$. It means, that the Aho–Corasick Algorithm reaches the lower bound, and our algorithm reaches the lower bound up to a log factor. At the same time, if O(m) strings of the dictionary have at least $\omega(\log n)$ length, then our quantum algorithm shows speed-up.

The structure of this paper is as follows: Section 2 contains preliminaries, used data structures and algorithms. Section 3 provides a quantum algorithm for the Multiple String Matching Problem. The final Section 4 concludes the paper and contains open questions.

2 Preliminaries and Tools

For a string $u = (u_1, \ldots, u_M)$, let |u| = M be a length of the string. Let $u[i : j] = (u_i, \ldots, u_j)$ be a substring of u from *i*-th to *j*-th symbol. Let $u[i] = u_i$ be *i*-th symbol of u. In the paper, we say that a string u is less than a string v if u precedes v in the lexicographical order.

2.1 The Multiple String Matching Problem

Suppose, we have a string t and a sequence of strings $S = (s^1, \ldots, s^m)$. We call the set S a dictionary, and the the string t a text. Let $L = |s^1| + \cdots + |s^m|$ be the total length of the dictionary, and $b = \max\{|s^1|, \ldots, |s^m|\}$ be the maximal length of dictionary's strings. Let an integer n = |t| be the length of t. The problem is to find positions in t for all strings from S. Formally, we want to find a sequence of indexes $\mathcal{I} = (I_1, \ldots, I_m)$, where $I_j = (i_{j,1}, \ldots, i_{j,k_j})$ such that $t[i_{j,x}: i_{j,x} + |s^j| - 1] = s^j$ for each $x \in \{1, \ldots, k_j\}, j \in \{1, \ldots, m\}$. Here k_j is the number of occurrences of s^j in the string t.

2.2 Suffix Array

A suffix array [38] is an array $suf = (suf_1, \ldots, suf_l)$ for a string u where l = |u| is the length of the string. The suffix array is the lexicographical order for all suffixes of u. Formally, $u[suf_i : l] < u[suf_{i+1} : l]$ for any $i \in \{1, \ldots, l-1\}$. Let CONSTRUCTSUFFIXARRAY(u) be a procedure that constructs the suffix array for the string u. The query and time complexity of the procedure are as follows:

Lemma 1 ([36]). A suffix array for a string u can be constructed with O(|u|) query and time complexity.

Let longest common prefix (LCP) of two strings u and s or LCP(u, s) be an index i such that $u_j = s_j$ for each $j \in \{1, \ldots, i\}$, and $u_{i+1} \neq s_{i+1}$.

For a suffix array suf we can define an array of longest common prefixes (LCP array). Let call it $lcp = (lcp_1, \ldots, lcp_{l-1})$, where $lcp_i = LCP(u[suf_i : l], u[suf_{i+1} : l])$ is the longest common prefix of two suffixes $u[suf_i : l]$ and $u[suf_{i+1} : l]$. The array can be constructed with linear complexity:

Lemma 2 ([33,19]). An array of longest common prefixes (LCP array) for a string u can be constructed with O(|u|) query and time complexity.

Using the lcp array, we can compute the LCP of any two suffixes $LCP(u[suf_i : l], u[suf_i : l])$ in constant time due to the algorithm from [9].

Lemma 3 ([9]). For $i, j \in \{1, ..., |u|\}$, there is an algorithm that computes the longest common prefix for suffixes $u[suf_i : l]$ and $u[suf_j : l]$ of the string u with O(1) query and time complexity with preprocessing with O(|u|) query and time complexity.

For $i, j \in \{1, ..., |u|\}$, let LCPSUF(u, i, j) be the procedure that returns $LCP(u[suf_i : l], u[suf_j : l])$, and PREPROCESSINGFORLCP(u) be the preprocessing procedure for this algorithm and constructing the lcp array.

2.3 Quantum Query Model

One of the most popular computation models for quantum algorithms is the query model. We use the standard form of the quantum query model. Let $f : D \to \{0,1\}, D \subseteq \{0,1\}^M$ be an M variable function. Our goal is to compute it on an input $x \in D$. We are given oracle access to the input x, i.e. it is implemented by a specific unitary transformation usually defined as $|i\rangle |z\rangle |w\rangle \mapsto |i\rangle |z + x_i \pmod{2} |w\rangle$, where the $|i\rangle$ register indicates the index of the variable we are querying, $|z\rangle$ is the output register, and $|w\rangle$ is some auxiliary workspace. An algorithm in the query model consists of alternating applications of

arbitrary unitaries which are independent of the input and the query unitary, and a measurement at the end. The smallest number of queries for an algorithm that outputs f(x) with probability $\geq \frac{2}{3}$ on all x is called the quantum query complexity of the function f and is denoted by Q(f). We refer the readers to [40,6,1,21] for more details on quantum computing.

In this paper, we are interested in the query complexity of the quantum algorithms. We use modifications of Grover's search algorithm [15,11] as quantum subroutines. For these subroutines, time complexity can be obtained from query complexity by multiplication to $O(\log D)$, where D is the size of a search space [7,16].

3 Quantum Algorithm for the Multiple String Matching Problem

Let us present a quantum algorithm for the Multiple String Matching Problem. A typical solution for the problem is the Aho–Corasick Algorithm that works with O(n + L) query and time complexity. Here we present an algorithm that works with $O(n + \sqrt{mL \log n} + m \log n)$ query complexity. The algorithm uses ideas from the paper of Manber and Myers [38] and uses quantum strings comparing algorithm [8,20,24].

Firstly, let us construct a suffix array, LCP array, and invoke preprocessing for LCPSUF function for the string t (see Section 2 for details). Note that n = |t|.

Let us consider a string s^j for $j \in \{1, \ldots, m\}$. If s^j is a substring of t starting from an index i, then s^j is a prefix of the suffix $t[suf_i : n]$, i.e. $t[suf_i : suf_i + |s^j| - 1] = s^j$. Since $t[suf_i : n]$ strings are in a lexicographical order according to suf order, all suffixes that have s^j as prefixes are situated sequentially. Our goal is to find two indexes $left_j$ and $right_j$ such that all suffixes $t[suf_i : n]$ has s^j as a prefix for each $i \in \{suf_{left_j}, \ldots, suf_{right_j}\}$. So, we can say that $I_j = (suf_{left_j}, \ldots, suf_{right_j})$.

There is a quantum algorithm for computing LCP of u and v. Let QLCP(u, v) be the corresponding function. Its complexity is presented in the next lemma.

Lemma 4 ([18]). There is a quantum algorithm that implements QLCP(u, v) procedure, and has query complexity $O(\sqrt{d})$ and time complexity $O(\sqrt{d}\log d)$, where d is the minimal index of an unequal symbol of u and v. The error probability is at most 0.1.

The algorithm is an application of the First-One Search algorithm [14,32,37,18] that finds a minimal argument of a Boolean-valued function (predicate) that has the 1-result. The First-One Search algorithm algorithm has an error probability 0.1 that is why we have the same error probability for QLCP procedure. The First-One Search is an algorithm that is based on the Grover Search algorithm [15,11]. So, the difference between query and time complexity is a log factor due to [7,16]. The QLCP(u, v) procedure is similar to the quantum algorithm that compares two strings u and v in lexicographical order that was independently developed in [8] and in [20,24].

For $i \in \{1, \ldots, min(|u|, |v|)\}$, let QLCP(u, v, i) be a similar function that computes LCP starting from the *i*-th symbol. Formally, QLCP(u, v, i) = QLCP(u[i : |u|], v[i : |v|]). Due to Lemma 4, complexity of QLCP(u, v, i) is following

Corollary 1. There is a quantum algorithm that implements QLCP(u, v, i) procedure, and has $O(\sqrt{d-i})$ query complexity and $O(\sqrt{d-i}\log(d-i))$ time complexity, where d is the minimal index of an unequal symbol of u and v such that d > i. The error probability is at most 0.1.

Let us present the algorithm that finds $left_j$. Let us call it LEFTBORDERSEARCH(J). The algorithm is based on the Binary search algorithm [13]. Let Le be the left border of the search segment, and Ri be the right border of the search segment. Let $St_i = t[suf_i : n]$ be *i*-th suffix for $i \in \{1, ..., n\}$.

Step 1. We assign $Le \leftarrow 1$ and $Ri \leftarrow n$. Let $Llcp \leftarrow QLCP(St_{Le}, s^j)$ be the LCP of the first suffix and the searching string. Let $Rlcp \leftarrow QLCP(St_{Ri}, s^j)$ be the LCP of the last suffix and the searching string.

Step 2. If $Llcp < |s^j|$ and $s^j < St_1$, i.e. $Llcp < |s^j|$ and $s^j[Llcp + 1] < St_1[Llcp + 1]$, then we can say that s^j is less than any suffix of t and is not a prefix of any suffix of t. So, we can say that I_j is empty. In that case, we stop the algorithm, otherwise, we continue with Step 3.

Step 3. If $Rlcp < |s^j|$ and $s^j > St_n$, i.e. $Rlcp < |s^j|$ and $s^j[Rlcp + 1] > St_n[Rlcp + 1]$, then we can say that s^j greats any suffix of t and is not a prefix of any suffix of t. So, we can say that I_j is empty also. In that case, we stop the algorithm, otherwise, we continue with Step 4.

Step 4. We repeat the next steps while Ri - Le > 1, otherwise we go to Step 9.

Step 5. Let $M \leftarrow \lfloor (Le + Ri)/2 \rfloor$.

Step 6. If $Llcp \geq Rlcp$, then we go to Step 7, and to Step 8 otherwise. **Step 7.** Here we compare $LCP(St_L, St_M)$ and Llcp. Note that $LCP(St_{Le}, St_M)$ can be computed as LCPSUF(t, Le, M) in O(1) query and time complexity. We have one of three options:

- If $LCP(St_{Le}, St_M) > Llcp$, then all suffixes from St_{Le} to St_M are such that $St_M[Llcp+1] = \cdots = St_{Le}[Llcp+1] \neq s^j[Llcp+1]$, and they cannot have s^j as a prefix. So, we can assign $Le \leftarrow M$ and not change Llcp.
- If $LCP(St_{Le}, St_M) = Llcp$, then all suffixes from St_{Le} to St_M has at least Llcp common symbols with s^j . Let us compute $Mlcp = LCP(St_M, s^j)$ using $QLCP(St_M, s^j, Llcp + 1)$. If $Mlcp = |s^j|$, then we can move the right border to M and update Rlcp because we search the leftmost occurrence of s^j . So, $Ri \leftarrow M$ and $Rlcp \leftarrow Mlcp$. A similar update of R and Rlcp we do if $St_M[Mlcp + 1] > s^j[Mlcp + 1]$. If $St_M[Mlcp + 1] < s^j[Mlcp + 1]$, then $Le \leftarrow M$ and $Llcp \leftarrow Mlcp$.
- If $LCP(St_{Le}, St_M) < Llcp$, then all suffixes from St_M to St_R cannot have s^j as a prefix. Therefore, we update $Ri \leftarrow M$, and $Rlcp \leftarrow LCP(St_{Le}, St_M)$.

After that, we go back to Step 4.

Step 8. The step is similar to Step 7, but we compare $LCP(St_M, St_{Ri})$ with *Rlcp*. We have one of three options:

- 6 K. Khadiev and D. Serov
 - If $LCP(St_M, St_{Ri}) > Rlcp$, then $Ri \leftarrow M$ and we do not change Rlcp.
 - If $LCP(St_M, St_{Ri}) = Rlcp$, then we compute $Mlcp = LCP(St_M, s^j)$ using $QLCP(St_M, s^j, Rlcp + 1)$. Then, we update variables exactly by the same rule as in the second case of Step 7.
 - If $LCP(St_M, St_{Ri}) < Rlcp$, then we update $L \leftarrow M$, and $Llcp \leftarrow LCP(St_M, St_{Ri})$.

After that, we go back to Step 4.

Step 9. The result of the search is Ri. So, we assign $left_j \leftarrow Ri$.

Similarly, we can compute $right_j$ in a procedure RIGHTBORDERSEARCH(j).

The implementation for LEFTBORDERSEARCH(j) is presented in Algorithm 1, and the complexity is presented in Lemma 5.

Algorithm 1 Quantum algorithm for LEFTBORDERSEARCH(j) that searches $left_j$.

```
Llcp \leftarrow QLCP(St_1, s^j), Rlcp \leftarrow QLCP(St_n, s^j)
if Llcp = |s^j| then
    answer \gets 0
else if s^{j}[Llcp+1] < St_{1}[Llcp+1] then
    answer \leftarrow -1
else if s^{j}[Rlcp+1] > St_{n}[Rlcp+1] then
    answer \gets -1
else
    Le \leftarrow 1, Ri \leftarrow n
    while Ri - Le > 1 do
        M \leftarrow \lfloor (Le + Ri)/2 \rfloor
        if Llcp \geq Rlcp then
           if LCPSUF(Le, M) > Llcp then
               Le \gets M
            end if
           if LCPSUF(Le, M) = Llcp then
               Mlcp = QLCP(St_M, s^j, Llcp + 1)
               if Mlcp = |s^j| or St_M[Mlcp + 1] > s^j[Mlcp + 1] then
                   Ri \leftarrow M, Rlcp \leftarrow Mlcp
               else
                   Le \leftarrow M, Llcp \leftarrow Mlcp
               end if
           end if
            if LCPSUF(Le, M) < Llcp then
                Ri \leftarrow M, Rlcp \leftarrow LCPSUF(Le, M)
            end if
        else
           if LCPSUF(M, Ri) > Rlcp then
                Ri \leftarrow M
           end if
           if LCPSUF(M, Ri) = Rlcp then
               Mlcp = QLCP(St_M, s^j, Rlcp + 1)
               if Mlcp = |s^j| or St_M[Mlcp + 1] > s^j[Mlcp + 1] then
                   Ri \leftarrow M, Rlcp \leftarrow Mlcp
               else
                   Le \leftarrow M, Llcp \leftarrow Mlcp
               end if
           end if
           if LCPSUF(M, Ri) < Rlcp then
                Le \leftarrow M, Llcp \leftarrow LCPSUF(M, Ri)
            end if
        end if
    end while
    answer \leftarrow Ri
end if
{\bf return} \ answer
```

Lemma 5. Algorithm 1 implements LEFTBORDERSEARCH(j), searches $left_j$ and works with $O(\sqrt{|s^j|\log n} + \log n)$ query complexity, $O(\sqrt{|s^j|\log n}\log |s^j| + \log n)$ time complexity, and at most 0.1 error probability.

Proof. Let us consider Llcp. It is always increased and never decreased. Assume that during the algorithm, it has values $Llcp_1, \ldots, Llcp_d$. We can say that $Llcp_1 < \cdots < Llcp_d$, and $d \leq \log_2 n$ because Binary search do at most $\log_2 n$ steps. Additionally, we can say that $Llcp_d \leq |s^j|$. The function QLCP increases Llcp. Query complexity of changing Llcp from $Llcp_i$ to $Llcp_{i+1}$ is $O(\sqrt{Llcp_{i+1} - Llcp_i})$ due to Corollary 1. The time complexity is

$$O(\sqrt{Llcp_{i+1} - Llcp_i}\log(Llcp_{i+1} - Llcp_i)) = O(\sqrt{Llcp_{i+1} - Llcp_i}\log(|s^j|)).$$

So, the total query complexity is

$$\sqrt{Llcp_1} + \sum_{i=1}^{d-1} O(\sqrt{Llcp_{i+1} - Llcp_i}) = O\left(\sqrt{d(Llcp_1 + \sum_{i=1}^{d-1} (Llcp_{i+1} - Llcp_i))}\right)$$

due to Cauchy–Bunyakovsky–Schwarz inequality. At the same time, $Llcp_1 + \sum_{i=1}^{d-1} (Llcp_{i+1} - Llcp_i) = Llcp_d \leq |s^i|$. Finally, the complexity of all changing of Llcp is $O(\sqrt{d|s^j|}) = O(\sqrt{|s^j|\log n})$. Using the same technique, we can show that the time complexity is $O(\sqrt{|s^j|\log n}\log |s^j|)$ Similarly, we can see that the complexity of all changing of Rlcp is $O(\sqrt{d|s^j|}) = O(\sqrt{|s^j|\log n})$. All other parts of the step of Binary search work with O(1) query and time complexity, including LCPSUF due to Lemma 3. They give us additional $O(\log n)$ complexity.

Note that each invocation of QLCP has an error probability 0.1. Therefore, $O(\log n)$ invocations of the procedure have an error probability that is close to 1. At the same time, the whole Algorithm 1 is a sequence of First-One Search procedures such that next invocation of the First-One Search uses results of the previous invocations. Due to [32], such sequence can be converted to an algorithm with the same total complexity and error probability 0.1.

The whole algorithm is presented in Algorithm 2, and complexity is discussed in Theorem 1

Quantum Algorithm for the Multiple String Matching Problem

Algorithm 2 Quantum algorithm for the Multiple String Matching Problem.

CONSTRUCTSUFFIXARRAY(t) PREPROCESSINGFORLCP(t) for $j \in \{1, ..., m\}$ do $left_j \leftarrow \text{LEFTBORDERSEARCH}(j)$ $right_j \leftarrow \text{RIGHTBORDERSEARCH}(j)$ if $left_j = -1$ or $right_j = -1$ then $I_j \leftarrow ()$ else $I_j \leftarrow (suf_{left_j}, ..., suf_{right_j})$ end if end for return $(I_1, ..., I_m)$

Theorem 1. Algorithm 2 solves the Multiple String Matching Problem and works with $O(n + \sqrt{mL \log n} + m \log n)$ query complexity, $O(n + \sqrt{mL \log n} \log b + m \log n)$ time complexity and at most 0.1 error probability.

Proof. Firstly, complexity of CONSTRUCTSUFFIXARRAY(t) and PREPROCESSINGFORLCP(t) is O(n) due to Lemmas 1, 2, and 3.

Query complexity of LEFTBORDERSEARCH(j) and RIGHTBORDERSEARCH(j) is $O(\sqrt{|s^j| \log n} + \log n)$, and time complexity is $O(\sqrt{|s^j| \log n} \log |s^j| + \log n)$. So, the total query complexity of these procedures for all $j \in \{1, \ldots, m\}$ is

$$O\left(m\log n + \sum_{j=1}^{m} \sqrt{|s^j|\log n}\right) = O\left(m\log n + \sqrt{\log n} \sum_{j=1}^{m} \sqrt{|s^j|}\right) = O\left(m\log n + \sqrt{\log n} + \sqrt{\log n} + \sqrt{\log n}\right)$$
$$O\left(m\log n + \sqrt{\log n} + \sqrt{\log n} + \sqrt{\log n}\right)$$

We get such a result because of Cauchy–Bunyakovsky–Schwarz inequality. Similarly, time complexity is $O(m \log n + \sqrt{mL \log n} \log b)$ since $b = max\{|s^1|, \ldots, |s^m|\}$.

The total query complexity is $O(n + \sqrt{mL \log n} + m \log n)$, and time complexity is $O(n + \sqrt{mL \log n} \log d + m \log b)$.

Note that, each invocation of LEFTBORDERSEARCH(j) and RIGHTBORDERSEARCH(j) has error probability 0.1. Therefore, O(m) invocations of the procedure have an error probability that is close to 1. At the same time, the algorithm is a sequence of First-One Search procedures. Due to [32], such sequence can be converted to an algorithm with the same total complexity and error probability 0.1.

Let us present the lower bound for the problem.

Theorem 2. The lower bound for query complexity of the Multiple String Matching Problem is $\Omega(n + L)$ in the classical case, and $\Omega(n + \sqrt{mL})$ in the quantum case.

10 K. Khadiev and D. Serov

Proof. Let us consider a binary alphabet for simplicity. Let $s^1 = "1"$. Then, the complexity of searching positions of s^1 in t is at least as hard as an unstructured search of all positions of 1 among n bits. Due to [10], classical query complexity of this problem is $\Omega(n)$ and quantum query complexity is $\Omega(\sqrt{nt})$, where t is the number of occurrences 1 among n bits. In the worst case, it is also $\Omega(n)$.

Let us consider t as a string of 0s. In that case, if we have any symbol 1 in a dictionary string, then this string does not occur in t. We should find all such strings for forming results for these strings. Number of such strings is at most m. The size of the search space is L. Then, the complexity of searching the answer is at least as hard as an unstructured search of at least m positions of 1 among L bits. Due to [10], classical query complexity of this problem is $\Omega(n)$ and quantum query complexity is $\Omega(\sqrt{mL})$

So, the total lower bound is $\Omega(max(n, L)) = \Omega(n + L)$ in the classical case and $\Omega(max(\sqrt{n}, \sqrt{mL})) = \Omega(\sqrt{n} + \sqrt{mL})$ in the quantum case.

4 Conclusion

In the paper, we present a quantum algorithm for the Multiple String Matching Problem that works with $O(n + \sqrt{mL} + m \log n)$ query complexity and error probability 0.1. It is better than the classical counterparts if O(m) strings of the dictionary have at least $\omega(\log n)$ length. In that case, $\sqrt{mL \log n} = o(L)$ and $m \log n = o(L)$. Similar situation for time complexity. We obtain speed up if $m \log n(\log b)^2 = o(L)$, or at lest O(m) strings have length $\omega(\log n \log \log n)$.

In the quantum case the lower bound is $\Omega(n + \sqrt{mL})$ and upper bound is $O^*(n + \sqrt{mL})$. They are equal up to a log factor. The open question is to develop a quantum algorithm with complexity that is equal to the lower bound.

References

- Ablayev, F., Ablayev, M., Huang, J.Z., Khadiev, K., Salikhova, N., Wu, D.: On quantum methods for machine learning problems part i: Quantum tools. Big Data Mining and Analytics 3(1), 41–55 (2019)
- Ablayev, F., Ablayev, M., Khadiev, K., Salihova, N., Vasiliev, A.: Quantum algorithms for string processing. In: Mesh Methods for Boundary-Value Problems and Applications. Lecture Notes in Computational Science and Engineering, vol. 141 (2022)
- string 3. Aho, A.V., Corasick, M.J.: Efficient matching: an aid to bibliographic search. Commun. ACM 18(6),333 - 340(1975).https://doi.org/10.1145/360825.360855
- Akmal, S., Jin, C.: Near-optimal quantum algorithms for string problems. In: Proceedings of the 2022 Annual ACM-SIAM Symposium on Discrete Algorithms (SODA). pp. 2791–2832. SIAM (2022)
- Allauzen, C., Crochemore, M., Raffinot, M.: Factor oracle: A new structure for pattern matching. In: SOFSEM'99: Theory and Practice of Informatics: 26th Conference on Current Trends in Theory and Practice of Informatics Milovy, Czech

Republic, November 27—December 4, 1999 Proceedings 26. pp. 295–310. Springer (1999)

- Ambainis, A.: Understanding quantum algorithms via query complexity. In: Proc. Int. Conf. of Math. 2018. vol. 4, pp. 3283–3304 (2018)
- Arunachalam, S., de Wolf, R.: Optimizing the number of gates in quantum search. Quantum Information and Computation 17(3&4), 251–261 (2017)
- Babu, H.M.H., Jamal, L., Dibbo, S.V., Biswas, A.K.: Area and delay efficient design of a quantum bit string comparator. In: 2017 IEEE Computer Society Annual Symposium on VLSI (ISVLSI). pp. 51–56. IEEE (2017)
- 9. Bender, M.A., Farach-Colton, M.: The lca problem revisited. In: Latin American Symposium on Theoretical Informatics. pp. 88–94. Springer (2000)
- Bennett, C.H., Bernstein, E., Brassard, G., Vazirani, U.: Strengths and weaknesses of quantum computing. SIAM journal on Computing 26(5), 1510–1523 (1997)
- Boyer, M., Brassard, G., Høyer, P., Tapp, A.: Tight bounds on quantum searching. Fortschritte der Physik 46(4-5), 493–505 (1998)
- Commentz-Walter, B.: A string matching algorithm fast on the average. In: International colloquium on automata, languages, and programming. pp. 118–132. Springer (1979)
- Cormen, T.H., Leiserson, C.E., Rivest, R.L., Stein, C.: Introduction to Algorithms. McGraw-Hill (2001)
- Dürr, C., Heiligman, M., Høyer, P., Mhalla, M.: Quantum query complexity of some graph problems. SIAM Journal on Computing 35(6), 1310–1328 (2006)
- Grover, L.K.: A fast quantum mechanical algorithm for database search. In: Proceedings of the twenty-eighth annual ACM symposium on Theory of computing. pp. 212–219. ACM (1996)
- 16. Grover, L.K.: Trade-offs in the quantum search algorithm. Physical Review A **66**(5), 052314 (2002)
- 17. Jordan, S.: Quantum algorithms zoo (2023), http://quantumalgorithmzoo.org/
- Kapralov, R., Khadiev, K., Mokut, J., Shen, Y., Yagafarov, M.: Fast classical and quantum algorithms for online k-server problem on trees. CEUR Workshop Proceedings 3072, 287–301 (2022)
- Kasai, T., Lee, G., Arimura, H., Arikawa, S., Park, K.: Linear-time longestcommon-prefix computation in suffix arrays and its applications. Lecture Notes in Computer Science, volume=2089, pages=0181–0181, year=2001, publisher=Springer-Verlag GmbH
- Khadiev, K., Ilikaev, A.: Quantum algorithms for the most frequently string search, intersection of two string sequences and sorting of strings problems. In: International Conference on Theory and Practice of Natural Computing. pp. 234–245 (2019)
- 21. Khadiev, K.: Lecture notes on quantum algorithms. arXiv preprint arXiv:2212.14205 (2022)
- Khadiev, K., Bosch-Machado, C.M., Chen, Z., Wu, J.: Quantum algorithms for the shortest common superstring and text assembling problems. Quantum Information and Computation 24(3-4), 267–294 (2024)
- Khadiev, K., Enikeeva, S.: Quantum version of self-balanced binary search tree with strings as keys and applications. In: International Conference on Micro- and Nano-Electronics 2021. vol. 12157, pp. 587 – 594. International Society for Optics and Photonics, SPIE (2022). https://doi.org/10.1117/12.2624619
- 24. Khadiev, K., Ilikaev, A., Vihrovs, J.: Quantum algorithms for some strings problems based on quantum string comparator. Mathematics **10**(3), 377 (2022)

- 12 K. Khadiev and D. Serov
- Khadiev, K., Kravchenko, D.: Quantum algorithm for dyck language with multiple types of brackets. In: Unconventional Computation and Natural Computation. pp. 68–83 (2021)
- Khadiev, K., Machado, C.M.B.: Quantum algorithm for the shortest superstring problem. In: International Conference on Micro- and Nano-Electronics 2021. vol. 12157, pp. 579 – 586. International Society for Optics and Photonics, SPIE (2022). https://doi.org/10.1117/12.2624618
- Khadiev, K., Remidovskii, V.: Classical and quantum algorithms for assembling a text from a dictionary. NONLINEAR PHENOMENA IN COMPLEX SYSTEMS 24(3), 207–221 (2021)
- Khadiev, K., Remidovskii, V.: Classical and quantum algorithms for constructing text from dictionary problem. Natural Computing 20(4), 713–724 (2021)
- Khadiev, K., Savelyev, N., Ziatdinov, M., Melnikov, D.: Noisy tree data structures and quantum applications. Mathematics 11(22), 4707 (2023)
- Khadiev, K., Serov, D.: Quantum property testing algorithm for the concatenation of two palindromes language. In: International Conference on Unconventional Computation and Natural Computation. pp. 134–147. Springer (2024)
- Knuth, D.E., Morris, Jr, J.H., Pratt, V.R.: Fast pattern matching in strings. SIAM journal on computing 6(2), 323–350 (1977)
- Kothari, R.: An optimal quantum algorithm for the oracle identification problem. In: 31st International Symposium on Theoretical Aspects of Computer Science. pp. 482–493 (2014)
- 33. Landau, G.M., Kasai, T., Lee, G., Arimura, H., Arikawa, S., Park, K.: Lineartime longest-common-prefix computation in suffix arrays and its applications. In: Combinatorial Pattern Matching: 12th Annual Symposium, CPM 2001 Jerusalem, Israel, July 1–4, 2001 Proceedings 12. pp. 181–192. Springer (2001)
- Le Gall, F., Seddighin, S.: Quantum meets fine-grained complexity: Sublinear time quantum algorithms for string problems. Algorithmica pp. 1–36 (2022)
- Le Gall, F., Seddighin, S.: Quantum meets fine-grained complexity: Sublinear time quantum algorithms for string problems. In: 13th Innovations in Theoretical Computer Science Conference (ITCS 2022). Schloss Dagstuhl-Leibniz-Zentrum für Informatik (2022)
- Li, Z., Li, J., Huo, H.: Optimal in-place suffix sorting. In: String Processing and Information Retrieval. pp. 268–284. Springer International Publishing, Cham (2018)
- Lin, C.Y.Y., Lin, H.H.: Upper bounds on quantum query complexity inspired by the elitzur-vaidman bomb tester. Theory of Computing 12(18), 1–35 (2016)
- Manber, U., Myers, G.: Suffix arrays: A new method for on-line string searches. In: Proceedings of the First Annual ACM-SIAM Symposium on Discrete Algorithms. p. 319–327. SODA '90, Society for Industrial and Applied Mathematics (1990)
- Montanaro, A.: Quantum pattern matching fast on average. Algorithmica 77(1), 16–39 (2017)
- Nielsen, M.A., Chuang, I.L.: Quantum computation and quantum information. Cambridge univ. press (2010)
- 41. Ramesh, H., Vinay, V.: String matching in $O(\sqrt{n} + \sqrt{m})$ quantum time. Journal of Discrete Algorithms 1(1), 103–110 (2003)
- 42. de Wolf, R.: Quantum computing and communication complexity. University of Amsterdam (2001)
- Wu, S., Manber, U.: A fast algorithm for multi-pattern searching. Tech. Rep. TR-94-17, Department of Computer Science, University of Arizona, Tucson, AZ (1994)