On Multi-Agent Inverse Reinforcement Learning

Till Freihaut¹ and Giorgia Ramponi¹

¹University of Zürich[∗]

November 25, 2024

Abstract

In multi-agent systems, the agent behavior is highly influenced by its utility function, as these utilities shape both individual goals as well as interactions with the other agents. Inverse Reinforcement Learning (IRL) is a well-established approach to inferring the utility function by observing an expert behavior within a given environment. In this paper, we extend the IRL framework to the multi-agent setting, assuming to observe agents who are following Nash Equilibrium (NE) policies. We theoretically investigate the set of utilities that explain the behavior of NE experts. Specifically, we provide an explicit characterization of the feasible reward set and analyze how errors in estimating the transition dynamics and expert behavior impact the recovered rewards. Building on these findings, we provide the first sample complexity analysis for the multi-agent IRL problem. Finally, we provide a numerical evaluation of our theoretical results.

1 Introduction

Multi-agent Reinforcement Learning has gathered significant interest in recent years due to its ability to model scenarios involving interacting agents. Notable successes have been achieved in domains such as autonomous driving [\(Shalev-Shwartz et al., 2016;](#page-13-0) [Zhou et al., 2020\)](#page-13-1), internet marketing [\(Jin](#page-11-0) [et al., 2018\)](#page-11-0), multi-robot control [\(Dawood et al., 2023\)](#page-11-1), traffic control [\(Wang et al., 2019\)](#page-13-2), and multi-player games [\(Baker et al., 2019;](#page-11-2) [Samvelyan et al., 2019\)](#page-13-3). All these applications require carefully designed reward functions, which is challenging even in single-agent settings [\(Amodei et al., 2016;](#page-10-0) [Hadfield-Menell et al., 2017\)](#page-11-3) and becomes more complex in multi-agent environments where each agent's reward function must be tailored to their specific, potentially different, goals.

In many scenarios, it is possible to observe an expert demonstrating optimal behavior, yet the underlying reward function guiding this behavior remains unknown. This is where IRL [\(Ng and](#page-12-0) [Russell, 2000\)](#page-12-0) becomes crucial. IRL aims to recover feasible reward functions that can rationalize the observed behavior as optimal. However, the initial work in IRL revealed a fundamental challenge: the problem is ill-posed because multiple reward functions can potentially explain the same behavior. To address this, subsequent research has focused on reformulating the IRL problem to make it more practical and applicable in real-world settings [\(Abbeel and Ng, 2004;](#page-10-1) [Ziebart et al., 2008;](#page-14-0) [Ramachandran and Amir, 2007;](#page-12-1) [Ratliff et al., 2006;](#page-13-4) [Levine et al., 2011\)](#page-12-2).

Translating IRL to the multi-agent setting introduces new challenges, particularly regarding the concept of optimality, as each agent's strategy depends on the strategies of all other agents. This necessitates game-theoretic solution concepts, particularly equilibrium solutions. The most common of these is the Nash equilibrium [\(Goktas et al., 2024;](#page-11-4) [Song et al., 2018;](#page-13-5) [Ramponi et al., 2023;](#page-13-6) [Song](#page-13-7) [et al., 2022;](#page-13-7) [Fu et al., 2021;](#page-11-5) [Reddy et al., 2012\)](#page-13-8).

[∗]Correspondence to: tillfreihaut@gmail.com

In the single-agent IRL domain, there has been significant progress in understanding theoretical properties. [Metelli et al.](#page-12-3) [\(2021\)](#page-12-3) introduced explicit conditions for feasible reward functions and efficient algorithms for unknown transition models and expert policies with access to a generative model. This work was extended to settings without a generative model [\(Lindner et al., 2023\)](#page-12-4) and stricter optimality metrics [\(Zhao et al., 2024;](#page-13-9) [Metelli et al., 2023\)](#page-12-5). However, these studies are limited to single-agent settings and compare performance based on criteria that are not directly applicable to general-sum competitive Markov games.

This paper seeks to bridge the gap between the theoretical understanding of IRL in single-agent settings and its application to multi-agent systems. We extend the characterization of feasible reward sets to multi-agent settings by introducing explicit conditions for n-person general-sum Markov games. Additionally, we provide a comprehensive sample complexity analysis in the presence of a generative model of the transition model and the Nash experts policy.

Our contributions are as follows:

- Extending the implicit conditions for feasible reward functions from two-person to n -person general-sum Markov games, building on [Lin et al.](#page-12-6) [\(2018\)](#page-12-6).
- Deriving an explicit characterization of the reward function feasible under a Nash-expert strategy, inspired by [Metelli et al.](#page-12-3) [\(2021\)](#page-12-3).
- Introducing the Nash Gap as an optimality criterion in Inverse Learning for general-sum Markov Games, extending its use beyond standard MARL.
- Considering the problem of recovering the feasible set of reward functions in Markov Games, we proved an upper bound on the sample complexity having access to the generative model and accounting for errors in transition probabilities and expert policy estimation.

2 Related Work

This work intersects with several fields of research, particularly Inverse Reinforcement Learning, Multi-Agent Inverse Reinforcement Learning , and Inverse (Algorithmic) Game Theory.

Inverse Reinforcement Learning The concept of IRL was first introduced by [Ng and Russell](#page-12-0) [\(2000\)](#page-12-0), highlighting the ill-posed nature of the problem. Subsequent research focused on reformulating the problem to identify a single good reward function [\(Abbeel and Ng, 2004;](#page-10-1) [Ziebart et al., 2008;](#page-14-0) [Ramachandran and Amir, 2007;](#page-12-1) [Ratliff et al., 2006;](#page-13-4) [Levine et al., 2011\)](#page-12-2).

Multi-Agent Inverse Reinforcement Learning The first extension of IRL to the multi-agent setting was presented by [Natarajan et al.](#page-12-7) [\(2010\)](#page-12-7). This work considered a centralized controller and an average reward RL setting, deriving the initial implicit conditions for a feasible reward function for the observed expert. However, it did not address competitive settings where game-theoretic equilibrium solutions are essential. [Lin et al.](#page-12-8) [\(2014\)](#page-12-8) extended this to Zero-Sum Markov Games, introducing a Bayesian framework for MAIRL based on observed Nash equilibrium behaviors. This Bayesian framework was further developed by [Lin et al.](#page-12-6) [\(2018\)](#page-12-6), deriving implicit conditions for various solution concepts within a Bayesian framework. Despite these advancements, these works focused on selecting a single reward function and lacked sample complexity bounds. Another work [Fu et al.](#page-11-5) [\(2021\)](#page-11-5) tries to break the Multi-agent approach into single agent problems by considering the induced single-agent MDP from the Markov Game. The authors state restrictive conditions when to get guarantees of the original Markov Game. The conditions are restrictive as they require that the transition dynamics of one agent are not influenced by the others. This barely holds true, one example are Normal-form games. A recent promising approach by [Goktas et al.](#page-11-4) [\(2024\)](#page-11-4) addresses the MAIRL problem as a minimax problem between a stabilizer and destabilizer, deriving polynomial sample bounds for parameters describing an ε -Nash equilibrium of an observed Nash-expert. However, their method selects only one set of parameters and relies on several assumptions, such as the representation of the NE in terms of parameters, access to reward function samples and smooth gradients.

Theoretical Understanding of IRL Techniques for deriving explicit conditions for feasible reward functions and actively exploring the environment with a generative model in the single-agent IRL setting were pioneered by [Metelli et al.](#page-12-3) [\(2021\)](#page-12-3). These ideas were extended to finite horizon settings and environments without a generative model by [Lindner et al.](#page-12-4) [\(2023\)](#page-12-4). Further, [Metelli](#page-12-5) [et al.](#page-12-5) [\(2023\)](#page-12-5) established the first lower bounds for IRL and introduced stronger metrics for describing feasible reward sets, leading to new concentration inequalities and sample complexity bounds. More recently, [Zhao et al.](#page-13-9) [\(2024\)](#page-13-9) introduced even stronger metrics and the first offline learning scenarios combined with a sample complexity analysis. All these works and their introduced metrics consider a distance to the value function with the highest value and an expert policy maximizing this value function, making direct translation to competitive Markov games challenging as they do not consider equilibrium concepts, necessary in the presence of multiple agents.

Inverse (Algorithmic) Game Theory There is significant overlap between *Multi-Agent Inverse* Reinforcement Learning and inverse algorithmic game theory. Many works in this area apply gametheoretic solution concepts to rationalize the behavior of observed players in specific types of games [\(Kalyanaraman and Umans](#page-11-6) [\(2008\)](#page-11-6), [Kalyanaraman and Umans](#page-11-7) [\(2009\)](#page-11-7)). A related work is by [Kuleshov](#page-12-9) [and Schrijvers](#page-12-9) [\(2015\)](#page-12-9), who developed polynomial-time algorithms for coarse correlated equilibria in succinct games, where the structure of the game is known and noted that in cases where the game structure is unknown, the problem is NP-hard. Their theorems indicate that without additional assumptions or more specific settings, polynomial-time algorithms cannot be expected for inversely solving Nash equilibria.

3 Preliminaries

We present the essential background and notation used throughout this paper.

Mathematical background. Let X be a finite set, then we denote by $\mathbb{R}^{\mathcal{X}}$ all functions mapping from X to R. Additionally, we denote by $\Delta^{\mathcal{X}}$ the set of probability measures over X. For $n \in \mathbb{N}$ we use $[n] := \{1, \ldots, n\}$. We introduce for a (pre)metric space (\mathcal{X}, d) with $\mathcal{Y}, \mathcal{Y}' \subseteq \mathcal{X}$ two non-empty sets the Hausdorff (pre)metric $\mathcal{H}_d: 2^{\mathcal{X}} \times 2^{\mathcal{X}} \to [0, +\infty]$ as

$$
\mathcal{H}_d(\mathcal{Y},\mathcal{Y}'):=\max\left\{\sup_{y\in\mathcal{Y}}\inf_{\sup_{y'\in\mathcal{Y}'}d(y,y'),\sup_{y'\in\mathcal{Y}'}\sup_{y\in\mathcal{Y}}d(y,y')\right\}
$$

Markov Games. An infinite time, discounted n-person general-sum Markov Game without reward function $(MG \setminus R)$ is characterized by a tuple $\mathcal{G} = (n, \mathcal{S}, \mathcal{A}, P, \gamma, \mu)$, where $n \in \mathbb{N}$ denotes the finite number of players; S is the finite state space; $A := A^1 \times \ldots \times A^n$ is the joint action space of the individual action spaces \mathcal{A}^i ; $P : \mathcal{S} \times \mathcal{A} \to \Delta^{\mathcal{S}}$ is the joint transition model; γ is the discount factor and μ is the initial state distribution. Therefore G is simply a *n*-person general-sum Markov Game [\(Shapley, 1953;](#page-13-10) [Takahashi, 1964;](#page-13-11) [Fink, 1964\)](#page-11-8) without the reward function. We will make use of the words persons, agents and players interchangeably. The strategy of a single agent, also called the policy, we denote by $\pi^i : S \to \Delta^{\mathcal{A}^i}$. A joint strategy is given by $\pi = (\pi^i, \ldots, \pi^i) = (\pi^i, \pi^{-i}),$ where π^{-i} refers to the policy of all players except i. In the following we will use the notation $a = (a^1, \ldots, a^n) \in A$ to denote a joint action of all agents. Therefore, the probability of a joint strategy is given by $\pi(\mathbf{a} | s) := \prod_{j=1}^n \pi^j(a^j | s)$. By Π^i we denote the set of all policies for agent *i*.

Reward function. The reward function for an agent, R^i : $S \times A \rightarrow [0, R^i_{\text{max}}]$, takes a state and a joint action as inputs, mapping them to a bounded real number. The joint reward is represented as $R = (R^1, \ldots, R^n)$. The uniform reward bound across all agents is defined by $R_{\text{max}} := \max_{i \in [n]} R_{\text{max}}^i$. It is crucial to recognize that the reward value is influenced by the actions of other agents. A $\mathcal{G} \setminus R$ combined with a joint reward results in a Markov game $\mathcal{G} \cup \mathcal{R}$.

Value functions and equilibrium concepts. For a Markov game $\mathcal{G} \cup R$ with a policy π we define the Q-function and the value-function for a given state and action as $Q_{\mathcal{G}\cup R}^{i,\pi}(s, \mathbf{a})$ and $V_{\mathcal{G}\cup R}^{i,\pi}(s)$. Additionally, we define the advantage function $A_{\mathcal{G}\cup R}^{i,\pi}$ for a given state and joint policy as $A_{\mathcal{G}\cup R}^{i,\boldsymbol{\pi}}(s,\boldsymbol{\pi}') = \sum_{\mathbf{a}} \boldsymbol{\pi}'(\mathbf{a} \mid s) Q_{\mathcal{G}\cup R}^{i,\boldsymbol{\pi}}(s,\mathbf{a}) - V_{\mathcal{G}\cup R}^{i,\boldsymbol{\pi}}(s,\mathbf{a})$ and if agent i is playing action a^i deterministically we have $A_{\mathcal{G}\cup R}^{i,\pi}(s,a^{-i}\pi-i')=\sum_{\mathbf{a}}\pi^{-i'}(a^{-i}\mid s)(\mathbf{a}\mid s)Q_{\mathcal{G}\cup R}^{i,\pi}(s,\mathbf{a})-V_{\mathcal{G}\cup R}^{i,\pi}(s,\mathbf{a})$. It is important to note, that the advantage is written in terms of switching distributions and not only a single action. Since the reward depends on the actions of other agents, the optimal strategy must consider this interdependence. This situation is common in game-theoretic problems.

Nash Equilibrium. Various types of equilibrium solutions have been proposed to model optimal strategies in Markov Games. In this work, we focus on the NE similarly to previous works on MARL [\(Goktas et al., 2024;](#page-11-4) [Song et al., 2018;](#page-13-5) [Fu et al., 2021\)](#page-11-5). A Nash strategy is one where no agent can improve their outcome by independently deviating from their strategy, assuming the strategies of the other agents remain unchanged. Formally, a policy π^{Nash} is a Nash equilibrium strategy, if for every state s and every agent i

$$
V_{\mathcal{G}\cup R}^{i,(\pi^{i,\operatorname{Nash}},\pi^{-i,\operatorname{Nash}})}(s)\geq V_{\mathcal{G}\cup R}^{i,(\pi^i,\pi^{-i,\operatorname{Nash}})}(s)\quad \forall \pi^i\in \Pi^i.
$$

To simplify the notation used in the remainder of this work, we will denote this as $V(\pi^{\text{Nash}}) \geq$ $V(\pi^i, \pi^{-i, \text{Nash}}).$

State-action Visitation Probability. The discounted probability of visiting a state-(joint-)action pair, given that the starting state is drawn from μ , is defined as $\overline{w}_{s,\mathbf{a}}^{\boldsymbol{\pi},\mu} = \sum_{t=0}^{\infty} \gamma^t \mathbb{P}(s, \mathbf{a}, \mu)$, where \mathbb{P} denotes a probability measure. If the starting distribution is deterministic for a state s, we will omit the dependence on μ and simply write $\overline{w}_{s,\mathbf{a}}^{\boldsymbol{\pi}}$.

4 Inverse Multi-agent Reinforcement Learning

This section discusses the differences between Multi-agent Inverse Reinforcement Learning (MAIRL) and Single-agent Inverse Reinforcement Learning (IRL). We then present a characterization of the feasible reward set under an NE expert. Building on this initial characterization, we extend a condition that the reward function must satisfy for n-person general-sum Markov Games. Similar to works in IRL [\(Lindner et al., 2023;](#page-12-4) [Metelli et al., 2021\)](#page-12-3), we state an implicit condition for the feasibility of reward functions, from which we derive an explicit condition. Afterward, we introduce the Nash Imitation Gap for MAIRL as an extension of Definition 7 in [Ramponi et al.](#page-13-6) [\(2023\)](#page-13-6). To conclude this section, we state an error propagation theorem and the optimality criterion for MAIRL.

4.1 Problem Definition

IRL problems generally involve observing an expert policy that performs optimally in an environment and attempting to recover a reward function under which this policy is optimal, where a policy is considered optimal if it maximizes the value function. However, this problem itself is ill-posed, as multiple solutions are admissible [\(Ng and Russell, 2000\)](#page-12-0). For this reason, it was defined a feasible set that explains the optimal behavior as the objective of IRL [\(Ng and Russell, 2000;](#page-12-0) [Metelli et al.,](#page-12-5) [2023,](#page-12-5) [2021;](#page-12-3) [Lindner et al., 2023\)](#page-12-4).

Transferring the IRL framework to the multi-agent setting is not straightforward, as the *optimality of* multiple agents is not univocal. In [3,](#page-2-0) we introduced the *optimality* in terms of equilibrium solutions, specifically introducing the NE strategy following recent literature [\(Goktas et al., 2024;](#page-11-4) [Song et al.,](#page-13-5) [2018\)](#page-13-5). For this reason, we assume that the experts we observe are playing an NE solution. Our goal is to reconstruct the set of reward functions by designing simple exploration strategies to generate a dataset of demonstrations D , from which any MAIRL algorithm can recover a good reward function. Formally, we introduce the (Nash-)MAIRL problem as $(\mathcal{G}, \pi^{\text{Nash}})$, where \mathcal{G} is a Markov Game without a Reward function and π^{Nash} is a NE policy. It is important to remind ourselves, that π^{Nash} is the joint policy of the n agents.

Definition 4.1 (Feasible Reward Set). Let (G, π^{Nash}) be a MAIRL problem. For any agent $i \in [n]$, a reward function R is feasible if and only if π^{Nash} is an NE strategy in the Markov Game $\mathcal{G} \cup R$. The set of all feasible rewards $\mathcal{R}_{G\cup R}$ is called the feasible reward set. When we only have access to a dataset of demonstrations D and estimate the MAIRL problem using samples from D , we denote the set as $\mathcal{R}_{\hat{G}\cup\hat{R}}$ and refer to it as the recovered feasible reward set. For simplicity, we will use \mathcal{R}_B and $\mathcal{R}_{\hat{\mathcal{B}}}$ respectively.

4.2 Feasible Reward Sets in MAIRL with Nash experts

Similar to the implicit conditions derived for IRL in [Metelli et al.](#page-12-3) [\(2021\)](#page-12-3) and [Lindner et al.](#page-12-4) [\(2023\)](#page-12-4), we now state an implicit condition in terms of the advantage function for the MAIRL setting. Subsequently, we will use this implicit condition to derive an explicit condition. Additional details can be found in the Appendix [C.](#page-17-0)

Lemma 4.1 (Feasible Reward Set Implicit). A reward function $R = (R^1, \ldots, R^n)$ is feasible if and only if for a Nash policy π^{Nash} , for every agent $i \in [n]$ and all $(s, a^i) \in S \times A^i$, it holds true that:

$$
\mathbf{A} = 0, if \pi^{i, Nash}(a^i \mid s) > 0, a^{-i} \in supp(\pi^{-i, Nash}(\cdot \mid s)).
$$
\n
$$
\mathbf{A} \le 0, if \pi^{i, Nash}(a^i \mid s) = 0, a^{-i} \in supp(\pi^{-i, Nash}(\cdot \mid s)),
$$
\nwhere
$$
\mathbf{A} := \sum_{a^{-i} \in \mathcal{A}^{-i}} \pi^{-i}(a^{-i} \mid s) A_{\mathcal{G} \cup R}^{i, \pi^{Nash}}(s, a^i, a^{-i})
$$

Compared to the IRL case, it is important to emphasize that we have a weaker condition here, as we require the additional condition that the actions of the other agents must have positive probability under the NE strategy. We cannot make any statements about the advantage if the joint action has a non-positive probability under the (Nash-)expert. This requirement is necessary because we only need to ensure that an agent does not deviate from an action, given the strategies of the others. Additionally, this condition differs from the single-agent setting, as the statement is not based on individual actions but on the other agents' policy distribution directly. This distinction arises because the expert may be using a mixed strategy. Assuming that the other agents have a deterministic policy and adapt the transition probability accordingly, we would recover the single-agent condition.

The next lemma derives an explicit form on the structure of a feasible reward function in the multi-agent setting.

Lemma 4.2 (Feasible Reward Set Explicit). A reward function $R = (R^1, \ldots, R^n)$ is feasible if and only if, for each agent $i \in [n]$, there exist a function $A^i \in \mathbb{R}_{\geq 0}^{S \times A}$ and a function $V^i \in \mathbb{R}^S$ such that for all $(s, a) \in S \times A$, the following holds:

$$
R^{i}(s, \mathbf{a}) = -A^{i}(s, \mathbf{a})\mathbb{1}_{E} + V^{i}(s) - \gamma \sum_{s'} P(s' \mid s, \mathbf{a})V^{i}(s'),
$$

where $E := \{ \{ \pi^{i, Nash}(a^i \mid s) = 0 \} \cap \{ \pi^{-i, Nash}(a^{-i} \mid s) > 0 \} \}.$

Similar to the single-agent IRL case [Metelli et al.](#page-12-3) [\(2021\)](#page-12-3); [Lindner et al.](#page-12-4) [\(2023\)](#page-12-4), the first term in the equation serves to ensure that deviating from the expert strategy is suboptimal. However, in contrast to the single-agent scenario, where any deviation is discouraged, the presence of multiple agents introduces a key distinction: only unilateral deviations are penalized, provided that the other agents execute the Nash strategy. This reflects the strategic interdependence inherent in multi-agent settings. The second term, much like in the single-agent case, captures the reward shaping through the value function, but it now operates over the joint action space, accounting for the interactions between all agents.

4.3 Nash Imitation Gap in MARL

In IRL, the primary goal often involves reconstructing an approximation of a reward function that leads to a policy that maximizes the value function under the actual (unknown) reward function. However, this objective differs in the MAIRL setting as we do not know if the NE played by the expert is the one with the highest value function, as different NEs may induce different values and we do not assume to have a unique NE nor the social optimal one. Therefore, we want to measure the performance of a policy induced by a recovered reward function in terms of being an NE under the true (unknown) reward function and dynamics. A common objective used to measure the performance of algorithms in MARL is the Nash Gap (see e.g. [\(Song et al., 2022\)](#page-13-7)). In [Ramponi et al.](#page-13-6) [\(2023\)](#page-13-6) they introduce the Nash imitation gap for Mean-field systems, We propose to use the objective also in the MAIRL setting.

Definition 4.2 (Nash Imitation Gap for MAIRL). Let $\mathcal{G} \cup \mathcal{R}$ be the underlying n-person general-sum Markov Game. Furthermore, let $\hat{\pi}$ be the policy recovered from the corresponding MAIRL problem. Then we define the Nash Imitation Gap of $\hat{\pi}$ as

$$
\mathcal{E}(\hat{\boldsymbol{\pi}}) := \max_{i \in [n]} \max_{\pi^i \in \Pi^i} V^i(\pi^i, \hat{\pi}^{-i}) - V^i(\hat{\boldsymbol{\pi}}).
$$

The definition possesses the desirable property that it equals 0 if $\hat{\pi}$ is a NE. In this case, the difference is zero for every player i , thereby making the maximum difference also zero. Furthermore, it is greater than zero if $\hat{\pi}$ is not an NE in the underlying Markov Game.

4.4 Error Propagation and Optimality Criterion

As already pointed out, we do not expect to recover the true problem perfectly. Instead, we are interested in how an estimation of the true problem can be transferred to the actual problem. In [4.2,](#page-4-0) we observed that a feasible reward function consists of a part depending on the expert's policy and another part on the transition probability. Therefore, we now aim to investigate how an error in estimating these two properties results in an error in the recovered reward function. To conclude this section, we then derive the optimality criterion for the MAIRL setting and state an upper bound on this criterion.

Theorem 4.1 (Error Propagation). Let (G, π^{Nash}) and $(\hat{G}, \hat{\pi}^{Nash})$ be the true and the recovered MAIRL problem. Then, for every agent $i \in [n]$ and any $R_i \in \mathcal{R}_{\mathcal{B}}$ there exists $\hat{R}_i \in \mathcal{R}_{\hat{\mathcal{B}}}$ such that:

$$
|R^{i}(s, a) - \hat{R}^{i}(s, a)| \leq A^{i}(s, a)|1\mathbf{1}_{E} - 1_{\hat{E}}| + \gamma \sum_{s'} V^{i}(s')|P(s' | s, a) - \hat{P}(s' | s, a)|,
$$

where $E := \{ \{\pi^{i, Nash}(a^i \mid s) = 0 \} \cap \{\pi^{-i, Nash}(a^{-i} \mid s) > 0 \} \}$ and $\hat{E} := \{ \{\hat{\pi}^{i, Nash}(a^i \mid s) = 0 \} \}$ $0\} \cap {\hat{\pi}}^{-i, Nash}(a^{-i} | s) > 0\}$.

Some comments on the theorem are necessary, particularly regarding the differences from the singleagent case. Both the policy estimation (first part) and transition model estimation (second part) introduce added complexity. In the multi-agent setting, policy errors not only arise when agent i misidentifies an expert's action but also when other agents fail to correctly identify Nash equilibrium actions. Furthermore, the transition model now depends on joint actions, increasing the exploration needed across the action space.

Finally, we can formally introduce an optimality criterion for algorithms to recover the feasible set in MAIRL.

Definition 4.3 (Optimality Criterion). Let $\mathcal{R}_{\mathcal{G}\cup R}$ be the exact feasible set and $\mathcal{R}_{\hat{G}\cup R}$ the recovered feasible set after observing $N \geq 0$ samples from the underlying true problem $(\mathcal{G}, \boldsymbol{\pi}^{Nash})$. We consider an algorithm to be (ε, δ, N) -correct after observing N samples if it holds with a probability of at least $1 - \delta$:

$$
\sup_{R \in \mathcal{R}_{\mathcal{G} \cup R}} \inf_{\hat{R}^i \in \mathcal{R}_{\hat{\mathcal{G}} \cup \hat{R}}} \mathcal{E}(\hat{\boldsymbol{\pi}}) \leq \varepsilon
$$
\n
$$
\sup_{\hat{R} \in \mathcal{R}_{\mathcal{G} \cup R}} \inf_{R \in \mathcal{R}_{\hat{\mathcal{G}} \cup \hat{R}}} \mathcal{E}(\hat{\boldsymbol{\pi}}) \leq \varepsilon
$$

The optimality criterion is in the Hausdorff metric style, see [3.](#page-2-0) The first condition ensures that the recovered feasible set captures a reward function that makes sure that the recovered policy is at most an ε -NE in the true Markov Game. However, this would support choosing a set that captures all possible reward functions $\mathbb{R}^{\mathcal{S}\times\mathcal{A}}$. Consequently, the second condition ensures that this is not possible by requiring every recovered reward to also have a true reward function that captures the desired behavior.

In [Zhao et al.](#page-13-9) [\(2024\)](#page-13-9), an in-depth discussion is provided on the appropriate selection of metrics for various IRL settings (see Appendix D of [Zhao et al.](#page-13-9) [\(2024\)](#page-13-9)). The authors emphasize that when a generative model is accessible, metrics that uniformly account for errors across the entire state-action space, as applied in this work, are most suitable. However, in other contexts, such as the offline setting, their proposed metrics may offer superior performance. We recognize the relevance of these cases and leave them open for exploration in future work.

The error propagation theorem has already shown how an error in the reward function is related to estimating the NE policy of the experts and the transition probability. We want to analyze how this is connected to the just-derived optimality criterion. To do so, the next lemma is of great importance. The lemma uses twice the simulation lemma (see e.g. [\(Zanette et al., 2019\)](#page-13-12) Lemma 3, also [E.1\)](#page-25-0) to the multi-agent setting and could be of independent interest, whenever the Nash Gap is the objective in MARL.

Lemma 4.3. Let $\mathcal{G} \cup R$ be a n-person general-sum Markov Game, P, \hat{P} two transition probabilities and R, \hat{R} two reward functions, such that $\hat{\pi}$ is a Nash equilibrium strategy in $\hat{G} \cup \hat{R}$. Then, it holds true that:

$$
V^{i}(\pi^{i}, \hat{\pi}^{-i}) - V^{i}(\hat{\pi}_{i}, \hat{\pi}^{-i})
$$

\n
$$
\leq \sum_{s,a} \overline{w}^{\hat{\pi}}_{s,a} (R^{i}(s, a) - \hat{R}^{i}(s, a)
$$

\n
$$
+ \gamma \sum_{s'} (\hat{P}(s' \mid s, a) - P(s' \mid s, a)) V^{i, \hat{\pi}}(s'))
$$

\n
$$
+ \sum_{s,a} \overline{w}^{\tilde{\pi}}_{s,a} (R^{i}(s, a) - \hat{R}^{i}(s, a)
$$

\n
$$
+ \gamma \sum_{s'} (\hat{P}(s' \mid s, a) - P(s' \mid s, a)) V^{i, \tilde{\pi}}(s')),
$$

where $\tilde{\boldsymbol{\pi}} = (\pi^i, \hat{\pi}^{-i}).$

5 Recovering Feasible Reward Sets in MAIRL with a Generative Model

Algorithm 1 MAIRL Uniform Sampling Algorithm with Generative Model

Require: Significance $\delta \in (0,1)$, target accuracy ε 1: Initialize $k \leftarrow 0, \varepsilon_0 \leftarrow +\infty$ 2: while $\varepsilon_k > \varepsilon$ do 3: Generate one sample for each $(s, \mathbf{a}) \in \mathcal{S} \times \mathcal{A}$ 4: Update $\hat{\pi}_k^{\text{Nash}}$ for each agent $i = 1, ..., n$ as described in [\(2\)](#page-7-0) 5: Update \hat{P}_k as described in [\(1\)](#page-7-1) 6: Update accuracy $\varepsilon_k \leftarrow \frac{1}{1-\gamma} \max_{(s,\mathbf{a})} \hat{C}_k(s,\mathbf{a})$ 7: end while

In this section, we consider the scenario where observed experts are executing an NE policy and we assume access to a generative model [\(Metelli et al., 2021\)](#page-12-3). Additionally, we provide a detailed analysis of the sample complexity. Unfortunately, our results reveal that the sample complexity for the inverse setting is comparable to that of directly learning Nash equilibria (up to a factor of $(1 - \gamma)$, indicating an exponential dependency on the size of the action spaces across the n players.

Before presenting our estimators for the transition probability \hat{P} and the (Nash-)expert policy $\hat{\pi}^{\text{Nash}}$, we first outline the sample collection procedure.

Samples are collected iteratively, with a maximum of n_{max} samples obtained during each iteration. The samples are generated by querying the generative model. The sampling process is terminated after τ iterations, where τ is a random stopping time determined by the satisfaction of a specified optimality criterion.

5.1 Transition Model and Policy Estimation

In this section, we elaborate on our approach to estimating the transition model and the expert's policy. After introducing the estimators, we will present a theorem for the confidence intervals.

For both estimation tasks, we employ empirical estimators. For each iteration $k \in [K]$, let $n_k(s, \mathbf{a}, s') =$ $\sum_{t=1}^k 1\!\!1_{(s_t,\mathbf{a}_t,s'_t)=(s,\mathbf{a},s')}$ denote the count of visits to the triplet $(s,\mathbf{a},s')\in\mathcal{S}\times\mathcal{A}\times\mathcal{S}$, and let $n_k(s, \mathbf{a}) = \sum_{s' \in \mathcal{S}} n_k(s, \mathbf{a}, s')$ denote the count of visits to the state-action pair (s, \mathbf{a}) . Additionally, we introduce $n_{k_i}(s, a^i) = \sum_{t=1}^k \mathbb{1}_{(s_t, a^i_t) = (s, a^i)}$ as the count of times action a^i was sampled in state $s \in \mathcal{S}$ for each agent i, and $n_k(s) = \sum_{a^i \in \mathcal{A}^i} n_{k_i}(s, a^i)$ as the count of visits to state s for any agent i.

It is important to note the distinction here: the count of actions must be done separately for each agent, whereas the count of state visits needs to be done for any one of the agents. The cumulative count over all iterations $k \in [K]$ can then be written as: $N_k(s, \mathbf{a}, s') = \sum_{j \in [k]} n_j(s, \mathbf{a}, s')$, $N_k(s, \mathbf{a}) =$ $\sum_{j \in [k]} n_j(s, \mathbf{a}).$

The cumulative count of actions for each agent and the cumulative state visit count are given by: $N_k^i(s, a^i) = \sum_{j \in [k]} n_j^i(s, a^i)$ $\forall i \in [n]$ $N(s) = \sum_{j \in [k]} n_j(s)$. After introducing the empirical counts, we can now state the empirical estimators for the transition model and the expert's policy:

$$
\hat{P}_k(s' \mid s, \mathbf{a}) = \begin{cases} \frac{N_k(s, \mathbf{a}, s')}{N_k(s, \mathbf{a})} & \text{if } N_k(s, \mathbf{a}) > 0\\ \frac{1}{S} & \text{otherwise} \end{cases}
$$
(1)

$$
\hat{\pi}_k^i(a^i \mid s) = \begin{cases} \frac{N_k^i(s, a^i)}{N_k(s)} & \text{if } N_k(s) > 0\\ \frac{1}{|\mathcal{A}^i|} & \text{otherwise.} \end{cases}
$$
 (2)

To state useful confidence bounds we extend a common assumption made in other works to the

Figure 1: Nash Gap in Grid Games for different transition probabilities.

Multi-agent setting (compare Assumption D.1 in [Metelli et al.](#page-12-5) [\(2023\)](#page-12-5)).

Assumption 5.1. For every agent $i \in [n]$, there exists a known constant $\pi^{i, Nash}_{min} \in (0,1]$, meaning that every agent plays every action with at least probability $\pi_{min}^{i, Nash}$.

 $\forall i \in [n] \, \forall (s,a^i) \in \mathcal{S} \times \mathcal{A}^i : \pi^{i, Nash}(a^i \mid s) \in \{0\} \cup [\pi^{i, Nash}_{min}, 1).$

To denote the minimum over all agents we introduce $\boldsymbol{\pi}_{min}^{Nash} := \min_{i \in [n]} \pi_{min}^{i, Nash}$.

We now state, with the help of Hoeffding's confidence intervals, that with high probability, we can bound the error in the estimation of the transition probabilities and the (Nash-)expert policy.

Theorem 5.1 (Good Event). Let k be the number of iterations and π^{Nash} be the stochastic expert policy. Let \hat{P} and $\hat{\pi}^{Nash}$ be the empirical estimates of the Nash expert and the transition probability after k iterations as defined in [\(1\)](#page-7-1) and [\(2\)](#page-7-0) respectively. Then for $\delta \in (0,1)$, define the good event $\mathcal E$ as the event such that the following inequalities hold simultaneously for all $(s, a) \in S \times A$ and $k \ge 1$:

$$
\left|1_{E} - 1_{\hat{E}} A^{i}(s, a)\right| \leq \frac{R_{\max}}{1 - \gamma} 1_{\{N_{k}(s) \leq \max\{1, \xi(N_{k}(s), \delta/2)\}\}},
$$
\n
$$
\left|1_{E} - 1_{\hat{E}} \hat{A}^{i}(s, a)\right| \leq \frac{R_{\max}}{1 - \gamma} 1_{\{N_{k}(s) \leq \max\{1, \xi(N_{k}(s), \delta/2)\}\}},
$$
\n
$$
\sum_{s'} \left| (P(s' \mid s, a) - \hat{P}_{k}(s' \mid s, a)) V^{i}(s') \right| \leq \frac{R_{\max}}{1 - \gamma} \sqrt{\frac{2l_{k}(s, a)}{N_{k}^{+}(s, a)}}
$$
\n
$$
\sum_{s'} \left| (P(s' \mid s, a) - \hat{P}_{k}(s' \mid s, a)) \hat{V}^{i}(s') \right| \leq \frac{R_{\max}}{1 - \gamma} \sqrt{\frac{2l_{k}(s, a)}{N_{k}^{+}(s, a)}}
$$

,

.

where we introduced $l_k(s, a) := \log \left(\frac{12S \prod_i |A^i| (N_k^+(s,a))^2}{\delta} \right)$ $\left(\frac{\left(N_k^+(s,a)\right)^2}{\delta}\right)$ for the last two equations, $\xi(N_k(s),\delta/2) :=$ $2S\prod_{i=1}^{n}|\mathcal{A}^{i}|(n-1)N_{k}(s)^{2}/\delta$ $\frac{d^n_{i=1} |A^*|(n-1)N_k(s)^2}{\log((1/(1-\pi_{min}^{Nash}))}$ and $|A^i|$ is the cardinality of the action space of agent i.

5.2 Sample Complexity for the Uniform Sampling algorithm

In the last section, we derived confidence intervals using the construction of the estimator and Hoeffding's inequality. By combining these results with the error propagation theorem (see [4.1\)](#page-5-0), we can compute the uncertainty estimate used as a stopping criterion for the uniform sampling algorithm. We define the uncertainty estimate as follows:

$$
C_k(s, \mathbf{a}) = \frac{2R_{\max}}{1-\gamma} \left(\mathbb{1}_{\{N_k(s) \leq \tilde{\xi}\}} + \gamma \sqrt{\frac{8l_k(s, \mathbf{a})}{N_k^+(s, \mathbf{a})}} \right),
$$

where we used $\tilde{\xi} := \max\{1, \xi(N_k(s), \delta/2)\}\.$ The resulting stopping criterion is then given by $\tau :=$ ${k \in \mathbb{N} : \frac{1}{1-\gamma} \max_{(s,a)} C_k(s,a) \leq \frac{\varepsilon}{2}}$. The uniform sampling algorithm is given in [1.](#page-7-2)

We can now state the main result regarding the sample complexity of the Uniform Sampling algorithm for MAIRL.

Theorem 5.2 (Sample Complexity of Uniform Sampling MAIRL). The Uniform Sampling algorithm [\(1\)](#page-7-2) stops with a probability of at least $1 - \delta$ after iteration τ and satisfies the optimality criterion (see [4.3\)](#page-6-0), where the sample complexity is of order $\tilde{\mathcal{O}}\left(\max\left(\frac{\gamma^2 R_{\max}^2 S \prod_{i=1}^n |\mathcal{A}^i|}{(1-\gamma)^4 \varepsilon^2}\right)\right)$ $\frac{\max\limits_{\max}S\prod_{i=1}^{n}|\mathcal{A}^{i}|}{(1-\gamma)^{4}\varepsilon^{2}},nS+\frac{nS}{\log(1/(1-\boldsymbol{\pi}^{Nash}_{min}))}\bigg)\bigg)$

Some remarks are in order for this complexity bound. We observe that the sample complexity bound is exponential in the number of players. Although this might seem unfavorable, it is generally known that learning an NE in the worst case has an exponential bound. Therefore, the derived bound for the MAIRL setting aligns with the bounds derived for learning NE in the MARL setting. An extensive discussion on the bounds derived in the literature can be found in Appendix [B.](#page-16-0)

Another point to notice is that for $n = 2$, we can compare the result with the model-based RL zero-sum bounds derived in [Zhang et al.](#page-13-13) [\(2020\)](#page-13-13) (compare Theorem 5). We observe that our bound includes an additional $(1 - \gamma)^{-1}$ factor. Initially, one might think this is due to the assumption of a zero-sum game in [Zhang et al.](#page-13-13) [\(2020\)](#page-13-13). However, this is not the case. If we closely examine Lemma 13 in [Zhang et al.](#page-13-13) [\(2020\)](#page-13-13), we see that the zero-sum structure is not required for the proof. Instead, the key point stated by the authors below the proof of Lemma 13 is that a tighter Bernstein bound is only applicable if the value function, and particularly the policy, is not dependent on the transition model of the empirical game \ddot{P} . Since this dependency exists in our problem setting, we must apply the looser Hoeffding bound and therefore get the additional factor of $(1 - \gamma)^{-1}$.

Last, we can see that the second part of the sample complexity bound is related to estimating the expert policy. In general, this can be a mixed strategy. However, if the (Nash-) expert is a pure strategy, meaning for all the agents the strategy is deterministic, we only need nS many samples. This is the case, since after one sample, we can immediately observe the true policy.

6 Experimental Evaluation

In this section, we aim to demonstrate the advantages of IRL in the multi-agent setting compared to Behavior Cloning.

It is important to emphasize that the primary goal of this paper is to address the IRL problem from a theoretical perspective by defining a new objective and presenting the first algorithm to characterize the feasible set of rewards when observing a Nash expert. Since we assume the observation of a Nash expert, it is necessary to either know or compute the NE before applying the Uniform Sampling algorithm. Given that calculating the NE is PPAD-hard, our focus will be on environments where it remains feasible. The idea is to emphasize the need for MAIRL framework and motivate future research on computationally more feasible equilibrium solutions.

MAIRL vs. Behavior Cloning In this paragraph, we empirically evaluate the benefits of MAIRL compared to BC. One of the advantages of IRL over BC lies in its ability to transfer the recovered reward function to new environments with different transition probabilities. This is particularly significant in a multi-agent setting, where even minor changes in transition probabilities can alter not only the individual behavior of agents but also the interactions between them.

For our experiments, we utilize the 3×3 Gridworld example, also considered in [Hu and Wellman](#page-11-9) [\(2003\)](#page-11-9). To recover the feasible reward set and learn the expert policy with BC, we consider a scenario where the transition probabilities are deterministic. The Nash experts are learned via NashQ-Learning as proposed in [Hu and Wellman](#page-11-9) [\(2003\)](#page-11-9). The resulting Nash Experts and more details on the environments can be found in [F.1.1.](#page-27-0)

Using the Uniform Sampling algorithm to recover the entire feasible set, we then apply a Random Max Gap MAIRL algorithm to extract a reward function from the feasible set, similar to the approach introduced in Appendix C of [Metelli et al.](#page-12-3) [\(2021\)](#page-12-3). A detailed description can be found in Appendix [F.2.](#page-27-1) To test the transferability of the recovered reward function, we alter the transition probabilities so that in states (0, any) and (any, 2), taking action "up" is only successful with a probability of 0.5; otherwise, the agent remains in the same state (as in Grid Game 2 in [Hu and](#page-11-9) [Wellman](#page-11-9) [\(2003\)](#page-11-9)). In a second scenario, we introduce an obstacle into the environment, that prohibits the agent from passing through. While in the first scenario, the BC strategy still performs reasonably, the second altered environment leads to a failure to reach the goal state for agent 1, resulting in the maximal Nash Gap.

We observe that while BC may perform better in the original environment, for the first iterations, the Uniform Sampling Algorithm proves superior when transferring the reward function, especially as the number of samples increases and the environment changes.

7 Conclusion and future work

In this work, we have provided the formalization of the Inverse Reinforcement Learning problem in the multi-agent setting. Specifically, we derived implicit and explicit conditions that characterize the feasible reward set by observing Nash experts. These conditions define for which reward function the observed behaviors are in an NE. Since in practice, we do not have access to the true transition model and experts' policies, we studied the consequences of estimating these quantities. We extended bounds from the single-agent IRL setting [Metelli et al.](#page-12-3) [\(2021\)](#page-12-3), showing how errors in estimating the transition model and expert policy affect the recovered reward set. Then, to assess an agent's performance on the recovered reward, we formalized the Nash Imitation Gap [\(Ramponi et al., 2023;](#page-13-6) [Song et al., 2022\)](#page-13-7). As part of this, we provided a new simulation lemma that accounts for the fact that Nash policies may not always maximize the value function. Building on these theoretical insights, we derived a sample complexity bound for a Uniform Sampling algorithm and empirically demonstrated the advantages of IRL over BC. This work lays the foundation for a more rigorous theoretical understanding of MAIRL. We hope that with this work researchers in the field, will use the Nash Imitation Gap as performance metrics for the MAIRL algorithms. Potential avenues for future research include deriving sample complexity bounds for alternative solution concepts and relaxing assumptions like the availability of a generative model. Exploring these directions will help further bridge the gap between theory and practical multi-agent learning applications.

Bibliography

- Pieter Abbeel and Andrew Y. Ng. Apprenticeship learning via inverse reinforcement learning. In Proceedings of the Twenty-First International Conference on Machine Learning, ICML '04, page 1, New York, NY, USA, 2004. Association for Computing Machinery. ISBN 1581138385. doi: 10.1145/1015330.1015430. URL <https://doi.org/10.1145/1015330.1015430>.
- Dario Amodei, Chris Olah, Jacob Steinhardt, Paul F. Christiano, John Schulman, and Dan Mané. Concrete problems in AI safety. $CoRR$, abs/1606.06565, 2016. URL [http://arxiv.org/abs/](http://arxiv.org/abs/1606.06565) [1606.06565](http://arxiv.org/abs/1606.06565).
- Mohammad Gheshlaghi Azar, Ian Osband, and Rémi Munos. Minimax regret bounds for reinforcement learning, 2017. URL <https://arxiv.org/abs/1703.05449>.
- Yu Bai, Chi Jin, and Tiancheng Yu. Near-optimal reinforcement learning with self-play. CoRR, abs/2006.12007, 2020. URL <https://arxiv.org/abs/2006.12007>.
- Bowen Baker, Ingmar Kanitscheider, Todor M. Markov, Yi Wu, Glenn Powell, Bob McGrew, and Igor Mordatch. Emergent tool use from multi-agent autocurricula. CoRR, abs/1909.07528, 2019. URL <http://arxiv.org/abs/1909.07528>.
- Xi Chen, Xiaotie Deng, and Shang-Hua Teng. Settling the complexity of computing two-player nash equilibria. $CoRR$, abs/0704.1678, 2007. URL <http://arxiv.org/abs/0704.1678>.
- Constantinos Daskalakis, Paul W. Goldberg, and Christos H. Papadimitriou. The complexity of computing a nash equilibrium. SIAM Journal on Computing, 39(1):195–259, 2009. doi: 10.1137/070699652. URL <https://doi.org/10.1137/070699652>.
- Murad Dawood, Sicong Pan, Nils Dengler, Siqi Zhou, Angela P. Schoellig, and Maren Bennewitz. Safe multi-agent reinforcement learning for formation control without individual reference targets, 2023. URL <https://arxiv.org/abs/2312.12861>.
- A. M. Fink. Equilibrium in a stochastic \$n\$-person game. Journal of Science of the Hiroshima University, 28:89–93, 1964. URL <https://api.semanticscholar.org/CorpusID:120600263>.
- Justin Fu, Andrea Tacchetti, Julien Perolat, and Yoram Bachrach. Evaluating strategic structures in multi-agent inverse reinforcement learning. J. Artif. Int. Res., 71:925–951, September 2021. ISSN 1076-9757. doi: 10.1613/jair.1.12594. URL <https://doi.org/10.1613/jair.1.12594>.
- Denizalp Goktas, Amy Greenwald, Sadie Zhao, Alec Koppel, and Sumitra Ganesh. Efficient inverse multiagent learning. In The Twelfth International Conference on Learning Representations, 2024. URL <https://openreview.net/forum?id=JzvIWvC9MG>.
- Dylan Hadfield-Menell, Smitha Milli, Pieter Abbeel, Stuart Russell, and Anca D. Dragan. Inverse reward design. CoRR, abs/1711.02827, 2017. URL <http://arxiv.org/abs/1711.02827>.
- Junling Hu and Michael P. Wellman. Nash q-learning for general-sum stochastic games. J. Mach. Learn. Res., 4(null):1039–1069, dec 2003. ISSN 1532-4435.
- Chi Jin, Qinghua Liu, Yuanhao Wang, and Tiancheng Yu. V-learning - A simple, efficient, decentralized algorithm for multiagent RL. CoRR, abs/2110.14555, 2021. URL [https://arxiv.org/abs/2110.](https://arxiv.org/abs/2110.14555) [14555](https://arxiv.org/abs/2110.14555).
- Junqi Jin, Chengru Song, Han Li, Kun Gai, Jun Wang, and Weinan Zhang. Real-time bidding with multi-agent reinforcement learning in display advertising. In Proceedings of the 27th ACM International Conference on Information and Knowledge Management, CIKM '18. ACM, October 2018. doi: 10.1145/3269206.3272021. URL <http://dx.doi.org/10.1145/3269206.3272021>.
- Shankar Kalyanaraman and Christopher Umans. The complexity of rationalizing matchings. In Proceedings of the 19th International Symposium on Algorithms and Computation, ISAAC '08, page 171–182, Berlin, Heidelberg, 2008. Springer-Verlag. ISBN 9783540921813. doi: 10.1007/ 978-3-540-92182-0_18. URL https://doi.org/10.1007/978-3-540-92182-0_18.
- Shankar Kalyanaraman and Christopher Umans. The complexity of rationalizing network formation. In 2009 50th Annual IEEE Symposium on Foundations of Computer Science, pages 485–494, 2009. doi: 10.1109/FOCS.2009.48.
- Emilie Kaufmann, Pierre Ménard, Omar Darwiche Domingues, Anders Jonsson, Edouard Leurent, and Michal Valko. Adaptive reward-free exploration. CoRR, abs/2006.06294, 2020. URL [https:](https://arxiv.org/abs/2006.06294) [//arxiv.org/abs/2006.06294](https://arxiv.org/abs/2006.06294).
- Volodymyr Kuleshov and Okke Schrijvers. Inverse game theory: Learning utilities in succinct games. In Workshop on Internet and Network Economics, 2015. URL [https://api.semanticscholar.](https://api.semanticscholar.org/CorpusID:2405324) [org/CorpusID:2405324](https://api.semanticscholar.org/CorpusID:2405324).
- Sergey Levine, Zoran Popovic, and Vladlen Koltun. Nonlinear inverse reinforcement learning with gaussian processes. In J. Shawe-Taylor, R. Zemel, P. Bartlett, F. Pereira, and K.Q. Weinberger, editors, Advances in Neural Information Processing Systems, volume 24. Curran Associates, Inc., 2011. URL [https://proceedings.neurips.cc/paper_files/paper/2011/file/](https://proceedings.neurips.cc/paper_files/paper/2011/file/c51ce410c124a10e0db5e4b97fc2af39-Paper.pdf) [c51ce410c124a10e0db5e4b97fc2af39-Paper.pdf](https://proceedings.neurips.cc/paper_files/paper/2011/file/c51ce410c124a10e0db5e4b97fc2af39-Paper.pdf).
- Xiaomin Lin, Peter A. Beling, and Randy Cogill. Multi-agent inverse reinforcement learning for zero-sum games. $CoRR$, abs/1403.6508, 2014. URL <http://arxiv.org/abs/1403.6508>.
- Xiaomin Lin, Stephen C. Adams, and Peter A. Beling. Multi-agent inverse reinforcement learning for general-sum stochastic games. CoRR, abs/1806.09795, 2018. URL [http://arxiv.org/abs/1806.](http://arxiv.org/abs/1806.09795) [09795](http://arxiv.org/abs/1806.09795).
- David Lindner, Andreas Krause, and Giorgia Ramponi. Active exploration for inverse reinforcement learning, 2023.
- Qinghua Liu, Tiancheng Yu, Yu Bai, and Chi Jin. A sharp analysis of model-based reinforcement learning with self-play. CoRR, abs/2010.01604, 2020. URL <https://arxiv.org/abs/2010.01604>.
- Weichao Mao and Tamer Basar. Provably efficient reinforcement learning in decentralized general-sum markov games. CoRR, abs/2110.05682, 2021. URL <https://arxiv.org/abs/2110.05682>.
- Weichao Mao, Tamer Basar, Lin F. Yang, and Kaiqing Zhang. Decentralized cooperative multi-agent reinforcement learning with exploration. CoRR, abs/2110.05707, 2021. URL [https://arxiv.org/](https://arxiv.org/abs/2110.05707) [abs/2110.05707](https://arxiv.org/abs/2110.05707).
- Alberto Maria Metelli, Giorgia Ramponi, Alessandro Concetti, and Marcello Restelli. Provably efficient learning of transferable rewards. In Marina Meila and Tong Zhang, editors, Proceedings of the 38th International Conference on Machine Learning, volume 139 of Proceedings of Machine Learning Research, pages 7665-7676. PMLR, 7 2021. URL [https://proceedings.mlr.press/](https://proceedings.mlr.press/v139/metelli21a.html) [v139/metelli21a.html](https://proceedings.mlr.press/v139/metelli21a.html).
- Alberto Maria Metelli, Filippo Lazzati, and Marcello Restelli. Towards theoretical understanding of inverse reinforcement learning, 2023.
- Sriraam Natarajan, Gautam Kunapuli, Kshitij Judah, Prasad Tadepalli, Kristian Kersting, and Jude W. Shavlik. Multi-agent inverse reinforcement learning. 2010 Ninth International Conference on Machine Learning and Applications, pages 395–400, 2010. URL [https://api.semanticscholar.](https://api.semanticscholar.org/CorpusID:3440496) [org/CorpusID:3440496](https://api.semanticscholar.org/CorpusID:3440496).
- Andrew Y. Ng and Stuart J. Russell. Algorithms for inverse reinforcement learning. In Proceedings of the Seventeenth International Conference on Machine Learning, ICML '00, page 663–670, San Francisco, CA, USA, 2000. Morgan Kaufmann Publishers Inc. ISBN 1558607072.
- Christos H. Papadimitriou and Tim Roughgarden. Computing correlated equilibria in multi-player games. J. ACM, 55(3), aug 2008. ISSN 0004-5411. doi: 10.1145/1379759.1379762. URL <https://doi.org/10.1145/1379759.1379762>.
- Deepak Ramachandran and Eyal Amir. Bayesian inverse reinforcement learning. In Proceedings of the 20th International Joint Conference on Artifical Intelligence, IJCAI'07, page 2586–2591, San Francisco, CA, USA, 2007. Morgan Kaufmann Publishers Inc.
- Giorgia Ramponi, Pavel Kolev, Olivier Pietquin, Niao He, Mathieu Laurière, and Matthieu Geist. On imitation in mean-field games, 2023.
- Nathan D. Ratliff, David M. Bradley, J. Andrew Bagnell, and Joel E. Chestnutt. Boosting structured prediction for imitation learning. In Neural Information Processing Systems, 2006. URL [https:](https://api.semanticscholar.org/CorpusID:1528918) [//api.semanticscholar.org/CorpusID:1528918](https://api.semanticscholar.org/CorpusID:1528918).
- Tummalapalli Sudhamsh Reddy, Vamsikrishna Gopikrishna, Gergely Zaruba, and Manfred Huber. Inverse reinforcement learning for decentralized non-cooperative multiagent systems. In 2012 IEEE International Conference on Systems, Man, and Cybernetics (SMC), pages 1930–1935, 2012. doi: 10.1109/ICSMC.2012.6378020.
- Mikayel Samvelyan, Tabish Rashid, Christian Schroeder de Witt, Gregory Farquhar, Nantas Nardelli, Tim G. J. Rudner, Chia-Man Hung, Philip H. S. Torr, Jakob Foerster, and Shimon Whiteson. The starcraft multi-agent challenge, 2019. URL <https://arxiv.org/abs/1902.04043>.
- Shai Shalev-Shwartz, Shaked Shammah, and Amnon Shashua. Safe, multi-agent, reinforcement learning for autonomous driving. CoRR, abs/1610.03295, 2016. URL [http://arxiv.org/abs/](http://arxiv.org/abs/1610.03295) [1610.03295](http://arxiv.org/abs/1610.03295).
- Lloyd S. Shapley. Stochastic games^{*}. Proceedings of the National Academy of Sciences, 39:1095 1100, 1953. URL <https://api.semanticscholar.org/CorpusID:263414073>.
- Jiaming Song, Hongyu Ren, Dorsa Sadigh, and Stefano Ermon. Multi-agent generative adversarial imitation learning. CoRR, abs/1807.09936, 2018. URL <http://arxiv.org/abs/1807.09936>.
- Ziang Song, Song Mei, and Yu Bai. When can we learn general-sum markov games with a large number of players sample-efficiently?, 2022. URL <https://arxiv.org/abs/2110.04184>.
- Masayuki Takahashi. Equilibrium points of stochastic non-cooperative \$n\$-person games. Journal of Science of the Hiroshima University, 28:95–99, 1964. URL [https://api.semanticscholar.org/](https://api.semanticscholar.org/CorpusID:118906641) [CorpusID:118906641](https://api.semanticscholar.org/CorpusID:118906641).
- Xiaoqiang Wang, Liangjun Ke, Zhimin Qiao, and Xinghua Chai. Large-scale traffic signal control using a novel multi-agent reinforcement learning. $CoRR$, abs/1908.03761, 2019. URL [http:](http://arxiv.org/abs/1908.03761) [//arxiv.org/abs/1908.03761](http://arxiv.org/abs/1908.03761).
- Andrea Zanette, Mykel J Kochenderfer, and Emma Brunskill. Almost horizon-free structure-aware best policy identification with a generative model. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett, editors, Advances in Neural Information Processing Systems, volume 32. Curran Associates, Inc., 2019. URL [https://proceedings.neurips.cc/](https://proceedings.neurips.cc/paper_files/paper/2019/file/a724b9124acc7b5058ed75a31a9c2919-Paper.pdf) [paper_files/paper/2019/file/a724b9124acc7b5058ed75a31a9c2919-Paper.pdf](https://proceedings.neurips.cc/paper_files/paper/2019/file/a724b9124acc7b5058ed75a31a9c2919-Paper.pdf).
- Kaiqing Zhang, Sham M. Kakade, Tamer Basar, and Lin F. Yang. Model-based multi-agent RL in zero-sum markov games with near-optimal sample complexity. CoRR, abs/2007.07461, 2020. URL <https://arxiv.org/abs/2007.07461>.
- Lei Zhao, Mengdi Wang, and Yu Bai. Is inverse reinforcement learning harder than standard reinforcement learning? a theoretical perspective, 2024.
- Ming Zhou, Jun Luo, Julian Villela, Yaodong Yang, David Rusu, Jiayu Miao, Weinan Zhang, Montgomery Alban, Iman Fadakar, Zheng Chen, Aurora Chongxi Huang, Ying Wen, Kimia Hassanzadeh, Daniel Graves, Dong Chen, Zhengbang Zhu, Nhat M. Nguyen, Mohamed Elsayed, Kun Shao, Sanjeevan Ahilan, Baokuan Zhang, Jiannan Wu, Zhengang Fu, Kasra Rezaee, Peyman Yadmellat, Mohsen Rohani, Nicolas Perez Nieves, Yihan Ni, Seyedershad Banijamali, Alexander I. Cowen-Rivers, Zheng Tian, Daniel Palenicek, Haitham Bou-Ammar, Hongbo Zhang, Wulong Liu,

Jianye Hao, and Jun Wang. SMARTS: scalable multi-agent reinforcement learning training school for autonomous driving. $CoRR$, $abs/2010.09776$, 2020. URL <https://arxiv.org/abs/2010.09776>.

Brian D. Ziebart, Andrew Maas, J. Andrew Bagnell, and Anind K. Dey. Maximum entropy inverse reinforcement learning. In Proceedings of the 23rd National Conference on Artificial Intelligence - Volume 3, AAAI'08, page 1433–1438. AAAI Press, 2008. ISBN 9781577353683.

Part

Appendix

Table of Contents

A Notation and Symbols

In this part of the appendix, we include notation used in the main paper and some additional notation used for the proofs in the appendix.

In this section, we introduce the additional notation needed for the matrix expression of the Qfunction, the value function, and in particular, for an additional implicit condition for the feasible reward function (Theorem [C.1\)](#page-17-1) similar to the one derived in [Lin et al.](#page-12-6) [\(2018\)](#page-12-6). To achieve this we use a similar notation from [Lin et al.](#page-12-6) [\(2018\)](#page-12-6), adjusted to this work. First, we introduce for every agent $i \in [n]$ the stacked reward \mathbb{R}^i . For every state $s \in \mathcal{S}$ the reward can be seen as a matrix of dimension $|\mathcal{A}^i| \times |\prod_{j \neq i}^n |\mathcal{A}^j|$. Doing this for every state and stacking them, results in a vector $\mathbf{R}^i \in \mathbb{R}^{|\mathcal{S}||\mathcal{A}|}, |\mathcal{A}|$ is the dimension of the joint action space. We additionally introduce the operator π , which can be written as a $|\mathcal{S}| \times |\mathcal{S}||\mathcal{A}|$ matrix, structured in the following way. First, we need to fix an arbitrary order on the joint action space $\|\mathcal{A}\|$ in the same way as already done for stacking the Reward for every agent. Given the order, we have that for $k \in |S|$, the k-th row is given by

$$
\Phi_1^{\pi}(k),\ldots,\Phi_{|\mathcal{A}|}^{\pi}(k),
$$

where for $j \in [A]$ we have

$$
\Phi_j^{\pi}(k) = \left[\underbrace{0, \ldots, 0}_{k-1}, \prod_{i=1}^n \pi^i(a_j^i \mid k), \underbrace{0, \ldots, 0}_{|S| - k} \right].
$$

Therefore, the resulting matrix has in its first $|S|$ columns a diagonal matrix of size $|S| \times |S|$ with the corresponding probabilities of playing the first joint action in all possible states.

$$
\begin{pmatrix}\n\prod_{i=1}^{n} \pi^{i}(a_{1} \mid 1) & 0 & 0 & \cdots & 0 & \cdots \\
0 & \prod_{i=1}^{n} \pi^{i}(a_{1} \mid 2) & 0 & \cdots & 0 & \cdots \\
0 & 0 & \prod_{i=1}^{n} \pi^{i}(a_{1} \mid 3) & \cdots & 0 & \cdots \\
\vdots & \vdots & \vdots & \ddots & \vdots & \ddots \\
0 & 0 & 0 & \cdots & \prod_{i=1}^{n} \pi^{i}(a_{1} \mid S) & \cdots\n\end{pmatrix}
$$

The transition matrix P of a Markov Game also depends on the joint actions, making the resulting transition matrix of dimension $|\mathcal{S}||\mathcal{A}| \times \mathcal{S}$. This allows us to write the value function as a column vector of dimension $\mathbb{R}^{|S|}$ and the Q-value function as a vector, identically as the reward vector, of dimension $|\mathcal{S}||\mathcal{A}| \times 1$. Therefore, we can write:

$$
\boldsymbol{Q}^{i,\boldsymbol{\pi}}=\boldsymbol{R}^i+\gamma \boldsymbol{P} \boldsymbol{V}^{i,\boldsymbol{\pi}},\quad \boldsymbol{V}^{i,\boldsymbol{\pi}}=\boldsymbol{\pi}\boldsymbol{Q}^{i,\boldsymbol{\pi}}.
$$

B Extensive Discussion on theoretical works of MARL

In this section, we review the limited but rapidly growing body of theoretical work on MARL and compare existing sample complexity bounds with those derived in our study.

In a seminal work, [Daskalakis et al.](#page-11-10) [\(2009\)](#page-11-10) established that the problem of learning Nash equilibria in 3-player zero-sum Markov games is PPAD-complete (Polynomial Parity Arguments on Directed graphs). Subsequently, [Chen et al.](#page-11-11) [\(2007\)](#page-11-11) extended this result to two-player general-sum games, showing that computing Nash equilibria remains PPAD-complete in this setting. Among the early algorithms for n-player general-sum Markov games in the MARL context is the Nash Q-learning algorithm introduced by [Hu and Wellman](#page-11-9) [\(2003\)](#page-11-9). Their analysis demonstrated that the computational complexity of the algorithm is linear in the number of states, polynomial in the number of actions, but exponential in the number of agents. These results align with our derived sample complexity bounds, as we similarly show that it grows exponentially with the number of agents.

More recent works additionally highlight that the exponential dependence on the number of agents regarding Nash equilibria is unavoidable. Consequently, many existing sample complexity analyses are restricted to more computationally tractable settings. A notable starting point for this line of work is [Bai et al.](#page-11-12) [\(2020\)](#page-11-12), which introduces computationally feasible algorithms with theoretical guarantees in the MARL setting. The authors focus on the finite-horizon, two-player, zero-sum Markov Games and propose the *V*-learning algorithm, deriving a sample complexity of $\tilde{\mathcal{O}}(H^6S(A+B)/\varepsilon^2)$, where A and B represent the action space sizes for the two players, H is the time horizon, and S is the number of states. This result matches the minimax lower bound up to a $poly(H)$ factor. The key innovation is the use of both upper and lower estimates for the V -value, alongside techniques from bandit literature, such as Follow the Regularized Leader, integrated with standard Q-learning ideas.

Building on these model-free results, which outperform existing model-based approaches, [Liu et al.](#page-12-10) [\(2020\)](#page-12-10) propose the *Optimistic Nash Value Iteration* algorithm. This algorithm achieves an ε -NE with a sample complexity of $\tilde{\mathcal{O}}(H^3SAB/\varepsilon^2)$, matching the information-theoretic lower bound

 $\Omega(H^3S(A+B)/\varepsilon^2)$ up to a min $\{A, B\}$ factor. Furthermore, they extend their analysis to *n*-player games, proposing an algorithm that outputs policies constituting either a NE, correlated equilibrium (CE), or coarse correlated equilibrium (CCE), with a sample complexity of $\tilde{\mathcal{O}}(H^4S^2 \prod_{i \in [n]} \mathcal{A}^i/\varepsilon^2)$. This again underscores the inherent exponential dependence on the number of players, driven by the extensive exploration requirements in the joint action space.

To address the curse of multi-agency in the general-sum setting, three concurrent works [\(Mao and](#page-12-11) [Basar, 2021;](#page-12-11) [Song et al., 2022;](#page-13-7) [Jin et al., 2021\)](#page-11-13) explore decentralized algorithms, achieving sample complexity bounds that depend only on the largest action space $(\max_{i\in[n]}A_i)$. However, their algorithms are restricted to computing CE and CCE, which are known to be solvable in polynomial time–[\(Papadimitriou and Roughgarden, 2008\)](#page-12-12). In [Mao and Basar](#page-12-11) [\(2021\)](#page-12-11), the authors extend the V-learning algorithm and prove sample complexities of $\tilde{\mathcal{O}}(H^5SA_{\max}/\varepsilon^2)$ (also derived in [\(Song et al.,](#page-13-7) [2022\)](#page-13-7)) for CCE and $\tilde{\mathcal{O}}(H^5SA_{\max}^2\varepsilon^{-2})$ for CE, outperforming other algorithms by a factor of H. Similar results are achieved by a stage-based version of V-learning introduced in [Mao et al.](#page-12-13) [\(2021\)](#page-12-13).

Additionally, [Song et al.](#page-13-7) [\(2022\)](#page-13-7) investigate the conditions under which NE can be learned efficiently. They consider Markov Potential Games, a subclass of Markov Games in which the change in the value function resulting from a unilateral policy change by agent i can be expressed as the difference in a real-valued potential function, Φ . In this setting, NE can be learned with a sample complexity that is linear in the number of players: $\tilde{\mathcal{O}}(\Phi_{\max}H^3S\sum_{i\in[n]}\mathcal{A}^i/\varepsilon^2)$, where $\Phi_{\max}\leq nH$ represents the natural bound on the potential function. This result shows that NE can be efficiently learned in this specific setting, offering a significant improvement over general-sum Markov games.

As all of the aforementioned works focus on finite-horizon Markov Games, while our work addresses the infinite-horizon setting, a recent study by [Zhang et al.](#page-13-13) [\(2020\)](#page-13-13) is of particular relevance. They propose a model-based approach for finding NE in two-player zero-sum Markov Games, matching the single-agent model-based sample complexity bounds from [Azar et al.](#page-10-2) [\(2017\)](#page-10-2), with the adjusted action space size. The authors demonstrate that, when the reward is unknown to the agent, a NE value can be computed with a sample complexity of $\tilde{\mathcal{O}}(SAB(1-\gamma)^{-3}\varepsilon^{-2})$. Given that our bound for $n = 2$ includes an additional factor of $(1 - \gamma)^{-1}$, it raises the natural question of why this discrepancy exists.

A potential explanation lies in the use of the tighter Bernstein concentration bounds in [Azar et al.](#page-10-2) [\(2017\)](#page-10-2). However, these bounds cannot be directly applied to our setting because they require the independence of the value function and the transition probability (see Discussion below Lemma 13 in [Zhang et al.](#page-13-13) [\(2020\)](#page-13-13)). A similar issue arises in the single-agent setting (see Discussion 6.2 in [Metelli](#page-12-3) [et al.](#page-12-3) [\(2021\)](#page-12-3)). Furthermore, it is important to note that in zero-sum games, the value of a NE is identical across different equilibria, whereas in general-sum Markov Games, different Nash equilibria can lead to completely different values.

We have extended the Related Work section on Forward MARL works and their sample complexity bounds to better understand what constitutes a good sample complexity in the MARL setting.To the best of our knowledge, only two works address sample complexity analysis in the inverse setting and have already been discussed in detail in Section [2.](#page-1-0)

C Proofs of Chapter 4

The first theorem serves as an extension of the two player version theorem of [Lin et al.](#page-12-6) [\(2018\)](#page-12-6) (see section 4.6 in [Lin et al.](#page-12-6) [\(2018\)](#page-12-6)) to *n*-person games and general Nash equilibria. It makes use of the notation introduced in Appendix [A.](#page-15-0)

Theorem C.1. Let $\mathcal{G} \cup R$ be a n-person general-sum Markov Game. A policy π is an NE strategy if

and only if

$$
(\boldsymbol{\pi}^{Nash} - \tilde{\boldsymbol{\pi}})(I - \gamma \boldsymbol{P} \boldsymbol{\pi}^{Nash})^{-1} \boldsymbol{R}^{i} \geq 0.
$$

with the meaning that without (s, a) symbols a matrix notation and $\tilde{\pi}$ is the policy with $\pi^{-i} = \pi^{-i, Nash}$ and π^i plays action a with probability 1.

Proof. In the first step of the proof we state the theorem for the case where $n = 2$ with the use of the definition of an NE. We only write the condition for agent 1 to understand the structure. For every action $a^1 \in \mathcal{A}^1$ and every state $s \in \mathcal{S}$ it must hold true that:

$$
\sum_{a^2 \in \mathcal{A}^2} \pi^{2,\text{Nash}}(a^2 \mid s) R^1(s, a^1 a^2) + \gamma \sum_{a^2 \in \mathcal{A}^2} \pi^{2,\text{Nash}}(a^2 \mid s) \sum_{s'} P(s' \mid s, a^1 a^2) V^{\pi^{\text{Nash}}}(s) \leq V^{\pi^{\text{Nash}}}(s)
$$

If we now want to generalize this to a n-person Markov Game, we get that for every player $i \in [n]$, every action a^i and every state $s \in \mathcal{S}$ it must hold true that:

$$
\sum_{a^{-i} \in \mathcal{A}^{-i}} \pi^{-i, \text{Nash}}(a^{-i} \mid s) R^{1}(s, a^{i} a^{-i}) + \gamma \sum_{a^{-i} \in \mathcal{A}^{-i}} \pi^{-i, \text{Nash}}(a^{-i} \mid s) \sum_{s'} P(s' \mid s, a^{i} a^{-i}) V^{\pi^{\text{Nash}}}(s) \leq V^{\pi^{\text{Nash}}}(s)
$$

We can rewrite this equation in terms of the Q-function and get

$$
\sum_{a^{-i} \in \mathcal{A}^{-i}} \pi^{-i} (a^{-i} \mid s) Q^{\pi^{\text{Nash}}}(s, \mathbf{a}) \leq V^{\pi^{\text{Nash}}}(s).
$$
\n(3)

Now we want to rewrite the equation for all states simultaneously. Therefore we recall the notation introduced in Appendix [A.](#page-15-0) We have that

$$
Q^{i,\boldsymbol{\pi}} = R^i + \gamma P V^{i,\boldsymbol{\pi}}, \quad V^{i,\boldsymbol{\pi}} = \boldsymbol{\pi} Q^{i,\boldsymbol{\pi}}.
$$

Rewriting this equation for the Nash Policy π^{Nash} gives us

$$
\boldsymbol{Q}^{i,\boldsymbol{\pi}^{\mathrm{Nash}}} = (I - \gamma \boldsymbol{P} \boldsymbol{\pi}^{\mathrm{Nash}})^{-1} \boldsymbol{R}^i.
$$

Plugging in the derived equations in [\(3\)](#page-18-0) using matrix notation for all states $s \in \mathcal{S}$ simultaneously and additionally denote the joint policy, where agent i plays action a^i with probability 1 and the other agents execute their Nash strategy $\pi^{-i, Nash}$ as $\tilde{\pi}$, we get

$$
(\tilde{\boldsymbol{\pi}} - \boldsymbol{\pi}^{\text{Nash}})(I - \gamma \boldsymbol{P} \boldsymbol{\pi}^{\text{Nash}})^{-1} \boldsymbol{R}^{i} \leq 0.
$$

The next lemma restates the condition by directly using the expectation of the advantage function with respect to the policy.

Lemma C.1 (Feasible Reward Set Implicit). A reward function $R = (R^1, \ldots, R^n)$ is feasible if and only if for a Nash policy π^{Nash} , for every agent $i \in [n]$ and all $(s, a^i) \in S \times A^i$, it holds true that:

$$
\sum_{a^{-i} \in \mathcal{A}^{-i}} \pi^{-i} (a^{-i} \mid s) A_{\mathcal{G} \cup R}^{i, \pi^{Nash}}(s, a^i, a^{-i}) = 0, \text{ if } \pi^{i, Nash}(a^i \mid s) > 0, a^{-i} \in \text{supp}(\pi^{-i, Nash}(\cdot \mid s)).
$$

$$
\sum_{a^{-i} \in \mathcal{A}^{-i}} \pi^{-i} (a^{-i} \mid s) A_{\mathcal{G} \cup R}^{i, \pi^{Nash}}(s, a^i, a^{-i}) \le 0, \text{ if } \pi^{i, Nash}(a^i \mid s) = 0, a^{-i} \in \text{supp}(\pi^{-i, Nash}(\cdot \mid s)).
$$

Proof. As we know that $a^{-i} \in \text{supp}(\pi^{-i, \text{Nash}}(\cdot | s))$ for both cases, we get for all agents $i \in [n]$ and all actions $a^{i, Nash} \in A^i$ that fulfill $\pi^{i, Nash}(a^{i, Nash} \mid s) > 0$, that $\sum_{a^{-i} \in A^{-i}} Q^{i, \pi^{Nash}}(s, a^{i, Nash} a^{-i}) > 0$ $\sum_{a^{-i} \in \mathcal{A}^{-i}} Q^{i, \pi^{\text{Nash}}}(s, a^{i, \text{Nash}} a^{-i})$. Additionally, we have that for all $a^{i, \text{Nash}}$ with $\pi^{i, \text{Nash}}(a^{i, \text{Nash}} \mid s)$ 0 that $Q^{i,\boldsymbol{\pi}^{\text{Nash}}}(s, a^{i,\text{Nash}}a^{-i}) = V^{i,\boldsymbol{\pi}^{\text{Nash}}}(s)$.

Before we are able to state the explicit form of the feasible reward set, we have to introduce the next lemma, which will be required for the proof of the explicit form.

Lemma C.2. Let $i \in [n]$ be an arbitrary agent. Then the Q-function of player i satisfies the optimality conditions of [4.1](#page-4-1) if and only if for every $(s, a) \in S \times A$ there exists a function $A^i \in \mathbb{R}_{\geq 0}^{S \times A}$ and $V^i \in \mathbb{R}^S$ such that:

$$
Q_{\mathcal{G}\cup R}^{i,\pi^{Nash}}(s,\bm{a})=-A^{i}(s,\bm{a})\mathbb{1}_{\{\pi^{i,Nash}(a_{i}|s)=0\}}\mathbb{1}_{\{\pi^{-i,Nash}(a_{-i}|s)>0\}}+V^{i}(s)
$$

Proof. First we assume that the Q-function can be expressed as

 \overline{N}

$$
Q_{\mathcal{G}\cup R}^{i,\pi^{\text{Nash}}}(s,\mathbf{a})=-A^{i}(s,\mathbf{a})1_{\{\pi^{i,\text{Nash}}(a_{i}|s)=0\}}1_{\{\pi^{-i,\text{Nash}}(a_{-i}|s)>0\}}+V^{i}(s).
$$

We note that

$$
V_{\mathcal{G}\cup R}^{i,\pi^{\mathrm{Nash}}}(s) = \sum_{\mathbf{a}\in\mathcal{A}} \pi^{\mathrm{Nash}}(\mathbf{a} \mid s) Q_{\mathcal{G}\cup R}^{i,\pi^{\mathrm{Nash}}}
$$

=
$$
\sum_{\mathbf{a}\in\mathcal{A}} \pi^{\mathrm{Nash}}(\mathbf{a} \mid s) (-A^{i}(s, \mathbf{a}) \mathbb{1}_{\{\pi^{i,\mathrm{Nash}}(a_{i}|s)=0\}} \mathbb{1}_{\{\pi^{-i,\mathrm{Nash}}(a_{-i}|s)>0\}} + V^{i}(s))
$$

=
$$
V^{i}(s),
$$

where the last equality follows from the fact, that if $\pi^{\text{Nash}}(\mathbf{a} \mid s) > 0$, then $\mathbb{1}_{\{\pi^{i,\text{Nash}}(a_i|s)=0\}} = 0$ and vice versa. Additionally, $V^i(s)$ is independent of **a** and as the sum is over the joint action space it holds true that $\sum_{\mathbf{a}\in\mathcal{A}} \pi^{\text{Nash}}(\mathbf{a} \mid s) = 1$. We now have to consider two cases. The first one is if $\mathbb{1}_{\{\pi^{i,\text{Nash}}(a_i|s)=0\}}=0$ and $\mathbb{1}_{\{\pi^{-i,\text{Nash}}(a_{-i}|s)>0\}}=1$ for every $a \in \text{supp}(\pi^{\text{Nash}})$. Then it holds true that

$$
\sum_{\mathbf{a}\in\mathcal{A}}\boldsymbol{\pi}^{\mathrm{Nash}}(\mathbf{a} \mid s)Q_{\mathcal{G}\cup R}^{i,\boldsymbol{\pi}^{\mathrm{Nash}}}(s,\mathbf{a})=V^{i}(s)=V_{\mathcal{G}\cup R}^{i,\boldsymbol{\pi}^{\mathrm{Nash}}}.
$$

The second case is if $\mathbb{1}_{\{\pi^{i,\text{Nash}}(a_i|s)=0\}}=1$ and $\mathbb{1}_{\{\pi^{-i,\text{Nash}}(a_{-i}|s)>0\}}=1$ for any $\mathbf{a}\in \text{supp}(\pi^{\text{Nash}})$. Then it holds true that

$$
\sum_{\mathbf{a}\in\mathcal{A}} \pi^{-i, \text{Nash}}(a^{-i} \mid s) Q_{\mathcal{G}\cup R}^{i, \pi^{\text{Nash}}}(s, a^{i} a^{-i})
$$
\n
$$
= \sum_{\mathbf{a}\in\mathcal{A}} \pi^{-i, \text{Nash}}(a^{-i} \mid s) \left(-A^{i}(s, \mathbf{a}) \mathbbm{1}_{\{\pi^{i, \text{Nash}}(a_{i}|s)=0\}} \mathbbm{1}_{\{\pi^{-i, \text{Nash}}(a_{-i}|s)>0\}} + V^{i}(s) \right)
$$
\n
$$
\leq V^{i}(s) = V_{\mathcal{G}\cup R}^{i, \pi^{\text{Nash}}},
$$

where we used the fact that $-A^{i}(s, \mathbf{a}) \leq 0$.

If we now assume that the conditions of [4.1](#page-4-1) hold, we can set for every $(s, a) \in S \times A$ $V^i(s) = V^{i, \pi^{\text{Nash}}}_{G \cup B}$ G∪R and $A^{i}(s, \mathbf{a}) = V_{\mathcal{G} \cup R}^{i, \pi^{\text{Nash}}}(s) - Q_{\mathcal{G} \cup R}^{i, \pi^{\text{Nash}}}(s, \mathbf{a}).$

Lemma C.3 (Feasible Reward Set Explicit). A reward function R is feasible if and only if, for each agent $i \in [n]$, there exist a function $A^i \in \mathbb{R}_{\geq 0}^{S \times A}$ and a function $V^i \in \mathbb{R}^S$ such that for all $(s, a) \in S \times A$, the following holds:

$$
R^{i}(s, a) = -A^{i}(s, a) 1_{\{\pi^{i, Nash}(a^{i}|s)=0\}} 1_{\{\pi^{-i, Nash}(a^{-i}|s)>0\}} + V^{i}(s) - \gamma \sum_{s'} P(s' \mid s, a) V^{i}(s').
$$

Proof. Remembering that we can express the Q-function as $Q_{\mathcal{G}\cup R}^{i,\pi^{\text{Nash}}}(s, \mathbf{a}) = R^{i}(s, \mathbf{a}) + \gamma \sum_{s'} P(s' \mid s')$ $(s, a)V_{G\cup R}^{i, \pi^{\text{Nash}}}(s')$ and applying Lemma [C.2](#page-19-0) to express the Q-function for an NE policy, we can conclude

$$
R^{i}(s, \mathbf{a}) = Q_{\mathcal{G} \cup R}^{i, \pi^{\text{Nash}}}(s, \mathbf{a}) - \gamma \sum_{s'} P(s' \mid s, a) V_{\mathcal{G} \cup R}^{i, \pi^{\text{Nash}}}(s')
$$

= $-A^{i}(s, \mathbf{a}) \mathbb{1}_{\{\pi^{i, \text{Nash}}(a_{i}|s)=0\}} \mathbb{1}_{\{\pi^{-i, \text{Nash}}(a_{-i}|s)>0\}} + V^{i}(s) - \gamma \sum_{s'} P(s' \mid s, \mathbf{a}) V^{i}(s').$

Theorem C.2 (Error Propagation). Let (G, π^{Nash}) and $(\hat{G}, \hat{\pi}^{Nash})$ be the true and the recovered MAIRL problem. Then, for every agent $i \in [n]$ and any $R_i \in \mathcal{R}_{\mathcal{B}}$ there exists $\hat{R}_i \in \mathcal{R}_{\hat{\mathcal{B}}}$ such that:

$$
|R_i(s, \mathbf{a}) - \hat{R}_i(s, \mathbf{a})| \leq A^i(s, \mathbf{a}) |\mathbb{1}_E - \mathbb{1}_{\hat{E}}| + \gamma \sum_{s'} V^i(s')|P(s' \mid s, \mathbf{a}) - \hat{P}(s' \mid s, \mathbf{a})|,
$$

where $E := \{ \{\pi^{i, Nash}(a^i \mid s) = 0\} \cap \{\pi^{-i, Nash}(a^{-i} \mid s) > 0\} \}$ and $\hat{D} := \{ \{\hat{\pi}^{i, Nash}(a^i \mid s) = 0\} \}$ $0\} \cap {\hat{\pi}}^{-i, Nash}(a^{-i} | s) > 0\}$.

Proof. From the explicit expression of a feasible reward [4.2,](#page-4-0) we know that we can write the reward function of any agent $i \in [n]$ as

$$
R^{i}(s, \mathbf{a}) = -A^{i}(s, \mathbf{a}) \mathbb{1}_{\{\pi^{i, \text{Nash}}(a^{i}|s)=0\}} \mathbb{1}_{\{\pi^{-i, \text{Nash}}(a^{-i}|s)>0\}} + V^{i}(s) - \gamma \sum_{s'} P(s' | s, \mathbf{a}) V^{i}(s')
$$
(4)

$$
\hat{R}^{i}(s, \mathbf{a}) = -\hat{A}^{i}(s, \mathbf{a}) \mathbb{1}_{\{\hat{\pi}^{i, \text{Nash}}(a^{i}|s) = 0\}} \mathbb{1}_{\{\hat{\pi}^{-i, \text{Nash}}(a^{-i}|s) > 0\}} + \hat{V}^{i}(s) - \gamma \sum_{s'} \hat{P}(s' | s, \mathbf{a}) \hat{V}^{i}(s')
$$
(5)

As we proof the existence of such reward function, we can choose $\hat{V}^i(s) = V^i(s)$ for every $s \in \mathcal{S}$ and $\hat{A}^i(s, \mathbf{a}) = A^i(s, \mathbf{a})$ for every $(s, \mathbf{a}) \in \mathcal{S} \times \mathcal{A}$. It then follows that:

$$
R^{i}(s, \mathbf{a}) - \hat{R}^{i}(s, \mathbf{a}) = -A^{i}(s, \mathbf{a}) \mathbb{1}_{\{\pi^{i, \text{Nash}}(a^{i}|s)=0\}} \mathbb{1}_{\{\pi^{-i, \text{Nash}}(a^{-i}|s)>0\}} + V^{i}(s) - \gamma \sum_{s'} P(s' | s, \mathbf{a}) V^{i}(s')
$$

+ $A^{i}(s, \mathbf{a}) \mathbb{1}_{\{\hat{\pi}^{i, \text{Nash}}(a^{i}|s)=0\}} \mathbb{1}_{\{\hat{\pi}^{-i, \text{Nash}}(a^{-i}|s)>0\}} - V^{i}(s) + \gamma \sum_{s'} \hat{P}(s' | s, \mathbf{a}) V^{i}(s')$
= $-A^{i}(s, \mathbf{a}) (\mathbb{1}_{E} - \mathbb{1}_{\hat{E}}) - \gamma \sum_{s'} (P(s' | s, \mathbf{a}) - \hat{P}(s' | s, \mathbf{a})) V^{i}(s')$

Taking the absolute value and applying the triangle inequality completes the proof.

 \Box

Lemma C.4. Let $\mathcal{G} \cup \mathcal{R}$ be a n-person general-sum Markov Game, P, \hat{P} two transition probabilities and R, \hat{R} two reward functions, such that $\hat{\pi}$ is a Nash equilibrium strategy in $\hat{G} \cup \hat{R}$. Then, it holds true that:

$$
V^{i}(\pi^{i}, \hat{\pi}^{-i}) - V^{i}(\hat{\pi}_{i}, \hat{\pi}^{-i})
$$

\n
$$
\leq \sum_{s,a} \overline{w}^{\hat{\pi}}_{s,a} (R^{i}(s, a) - \hat{R}^{i}(s, a) + \gamma \sum_{s'} (\hat{P}(s' \mid s, a) - P(s' \mid s, a)V^{i, \hat{\pi}}(s')))
$$

\n
$$
+ \sum_{s,a} \overline{w}^{\tilde{\pi}}_{s,a} (R^{i}(s, a) - \hat{R}^{i}(s, a) + \gamma \sum_{s'} (\hat{P}(s' \mid s, a) - P(s' \mid s, a)V^{i, \hat{\pi}}(s'))),
$$

where $\tilde{\boldsymbol{\pi}} = (\pi^i, \hat{\pi}^{-i}).$

Proof.

$$
V^{i}(\pi^{i}, \hat{\pi}^{-i}) - V^{i}(\hat{\pi}^{i}, \hat{\pi}^{-i})
$$

\n
$$
= V^{i}(\pi^{i}, \hat{\pi}^{-i}) - \hat{V}^{i}(\pi^{i}, \hat{\pi}^{-i}) + \hat{V}^{i}(\hat{\pi}^{i}, \hat{\pi}^{-i}) - V^{i}(\hat{\pi}^{i}, \hat{\pi}^{-i}) + \hat{V}^{i}(\pi^{i}, \hat{\pi}^{-i}) - \hat{V}^{i}(\hat{\pi}^{i}, \hat{\pi}^{-i})
$$

\n
$$
\leq V^{i}(\pi^{i}, \hat{\pi}^{-i}) - \hat{V}^{i}(\pi^{i}, \hat{\pi}^{-i}) + \hat{V}^{i}(\hat{\pi}^{i}, \hat{\pi}^{-i}) - V^{i}(\hat{\pi}^{i}, \hat{\pi}^{-i})
$$

\n
$$
= \sum_{s, \mathbf{a}} \overline{w}_{s, a}^{\hat{\pi}}(R^{i}(s, \mathbf{a}) - \hat{R}^{i}(s, \mathbf{a}) + \gamma \sum_{s'} (\hat{P}(s' \mid s, \mathbf{a}) - P(s' \mid s, a)) V^{i, \hat{\pi}}(s'))
$$

\n
$$
+ \sum_{s, \mathbf{a}} \overline{w}_{s, \mathbf{a}}^{\hat{\pi}}(R^{i}(s, \mathbf{a}) - \hat{R}^{i}(s, \mathbf{a}) + \gamma \sum_{s'} (\hat{P}(s' \mid s, \mathbf{a}) - P(s' \mid s, \mathbf{a})) V^{i, \hat{\pi}}(s')),
$$

where we used that $\hat{V}^i(\hat{\pi}^i, \hat{\pi}^{-i}) - V^i(\hat{\pi}^i, \hat{\pi}^{-i}) \leq 0$ as $\hat{\pi}$ is a NE policy and in the last equation we applied [E.1.](#page-25-0) П

D Sample Complexity analysis of the Uniform Sampling algorithm

In this section we give the proofs of the theorems and lemmas derived in Section [4](#page-3-0) and Section [5.](#page-6-1) The structure is as follows:

- 1. We begin by stating the optimality criterion based on the Nash Imitation Gap.
- 2. Next, we present the Good Event Lemma bounds, using Hoeffding's inequality.
- 3. We define the reward uncertainty.
- 4. Then, we state a theorem that provides conditions—dependent on the derived confidence bounds—under which the optimality criterion holds.
- 5. Finally, we consolidate all results to prove the sample complexity bound for the uniform sampling algorithm.

Definition D.1 (Optimality Criterion). Let $\mathcal{R}_{\mathcal{G}\cup R}$ be the exact feasible set and $\mathcal{R}_{\hat{G}\cup\hat{R}}$ the recovered feasible set after sampling $N \geq 0$ from $(\mathcal{G}, \pi^{Nash})$. We consider an algorithm to be (ε, δ, N) -correct after observing N samples if it holds with a probability of at least $1 - \delta$:

$$
\sup_{R \in \mathcal{R}_{\mathcal{G} \cup R}} \inf_{\hat{R}^i \in \mathcal{R}_{\hat{\mathcal{G}} \cup \hat{R}}} \max_{i \in [n]} \max_{\pi^i \in \pi^i} V^i_{\mathcal{G} \cup R}(\pi^i, \hat{\pi}^{-i}) - V^i_{\mathcal{G} \cup R}(\hat{\pi}^i, \hat{\pi}^{-i}) \le \varepsilon
$$
\n
$$
\sup_{\hat{R} \in \mathcal{R}_{\mathcal{G} \cup \hat{R}}} \inf_{R \in \mathcal{R}_{\hat{\mathcal{G}} \cup \hat{R}}} \max_{i \in [n]} \max_{\pi^i \in \pi^i} V^i_{\mathcal{G} \cup R}(\pi^i, \hat{\pi}^{-i}) - V^i_{\mathcal{G} \cup R}(\hat{\pi}^i, \hat{\pi}^{-i}) \le \varepsilon
$$

Next, we state the lemma that derives the good event by applying Hoeffding's bound.

Theorem D.1 (Good Event). Let k be the number of iterations and π^{Nash} be the stochastic expert policy. Furthermore let $\hat{\pi}^{Nash}$ and \hat{P} be the empirical estimates of the Nash expert and the transition probability after k iterations as defined in [\(1\)](#page-7-1) and [\(2\)](#page-7-0) respectively. Then for $\delta \in (0,1)$, define the good event E as the event such that the following inequalities hold simultaneously for all $(s, a) \in S \times A$ and $k \geq 1$:

$$
\left|1_{E} - 1_{\hat{E}} A^{i}(s, a)\right| \leq \frac{R_{\max}}{1 - \gamma} 1_{\{N_{k}(s) \geq \max\{1, \xi(N_{k}(s), \delta/2)\}\}},
$$
\n
$$
\left|1_{E} - 1_{\hat{E}} \hat{A}^{i}(s, a)\right| \leq \frac{R_{\max}}{1 - \gamma} 1_{\{N_{k}(s) \geq \max\{1, \xi(N_{k}(s), \delta/2)\}\}},
$$
\n
$$
\sum_{s'} \left| (P(s' \mid s, a) - \hat{P}_{k}(s' \mid s, a)) V^{i}(s') \right| \leq \frac{R_{\max}}{1 - \gamma} \sqrt{\frac{2l_{k}(s, a)}{N_{k}^{+}(s, a)}},
$$
\n
$$
\sum_{s'} \left| (P(s' \mid s, a) - \hat{P}_{k}(s' \mid s, a)) \hat{V}^{i}(s') \right| \leq \frac{R_{\max}}{1 - \gamma} \sqrt{\frac{2l_{k}(s, a)}{N_{k}^{+}(s, a)}}.
$$

where we introduced $l_k(s, a) := \log \left(\frac{12S \prod_i |\mathcal{A}^i| (N_k^+(s, a))^2}{\delta} \right)$ $\frac{\left|\left(N_k^+(s,a)\right)^2}{\delta}\right)$ for the last two equations, $\xi(N_k(s),\delta/2):=$ $\log(2S\prod_{i=1}^{n}|\mathcal{A}^{i}|(n-1)N_{k}(s)^{2}/\delta)$ $\frac{\prod_{i=1}^{n}|\mathcal{A}^{(n-1)}(n-1)N_k(s)^2/\delta)}{\log((1/(1-\pi_{min}^{N_{\text{can}}}))}$ and $|\mathcal{A}^i|$ is the cardinality of the action space of agent i.

Proof. We start with bound the two last equations. Therefore we define $l_k(s, \mathbf{a}) = \log \left(\frac{12S \prod_i |\mathcal{A}^i| (N_k^+(s, \mathbf{a}))^2}{\delta} \right)$ $\frac{|(N_k^+(s,\mathbf{a}))^2}{\delta}\bigg)$ and additionally we denote $\beta_{N_k(s,\mathbf{a})} = \frac{R_{\text{max}}}{1-\gamma}$ $\sqrt{2l_k(s,\mathbf{a})}$ $\frac{2l_k(s,\mathbf{a})}{N_k^+(s,\mathbf{a})}$. Now we define the set

$$
\mathcal{E}^{\text{trans}} := \left\{ \forall k \in \mathbb{N}, \, \forall (s, \mathbf{a}) \in \mathcal{S} \times \mathcal{A} : \sum_{s' \in \mathcal{S}} |(P(s' \mid s, \mathbf{a}) - \hat{P}(s' \mid s, \mathbf{a}))V^{i}(s')| \leq \beta_{N_{k}(s, \mathbf{a})} \right\}.
$$

Then we get for V^i with probability of $1 - \delta$:

$$
\mathbb{P}\left((\mathcal{E}^{\text{trans}})^{C}\right) = \mathbb{P}\left(\exists k \geq 1, \exists (s, \mathbf{a}) \in \mathcal{S} \times \mathcal{A} : \sum_{s'} \left| \left(P(s' \mid s, \mathbf{a}) - \hat{P}_k(s' \mid s, \mathbf{a})\right)V^i(s')\right| > \beta_{N_k(s, \mathbf{a})}(s, \mathbf{a})\right)
$$
\n
$$
\stackrel{(a)}{\leq} \sum_{(s, \mathbf{a}) \in \mathcal{S} \times \mathcal{A}} \mathbb{P}\left(\exists k \geq 1 : \sum_{s'} \left| \left(P(s' \mid s, \mathbf{a}) - \hat{P}_k(s' \mid s, \mathbf{a})\right)V^i(s')\right| > \beta_{N_k(s, \mathbf{a})}(s, \mathbf{a})\right)
$$
\n
$$
\stackrel{(b)}{\leq} \sum_{(s, \mathbf{a}) \in \mathcal{S} \times \mathcal{A}} \mathbb{P}\left(\exists m \geq 0 : \sum_{s'} \left| \left(P(s' \mid s, \mathbf{a}) - \hat{P}_k(s' \mid s, \mathbf{a})\right)V^i(s')\right| > \beta_{N_k(s, \mathbf{a})}(s, \mathbf{a})\right)
$$
\n
$$
\stackrel{(c)}{\leq} \sum_{(s, \mathbf{a}) \in \mathcal{S} \times \mathcal{A}} \sum_{m \geq 0} 2 \exp\left(\frac{\beta_{N_k(s, \mathbf{a})}^2 m^2 (1 - \gamma)^2}{4m\gamma^2 R_{\text{max}}^2}\right)
$$
\n
$$
\leq \sum_{(s, \mathbf{a}) \in \mathcal{S} \times \mathcal{A}} \sum_{m \geq 0} \frac{\delta}{6S(\prod_{i=1}^n |\mathcal{A}^i|)(m^+)^2}
$$
\n
$$
\leq \frac{\delta}{6} \left(1 + \frac{\pi^2}{6}\right) \leq \frac{\delta}{2},
$$

where (a) uses a union bound over the state and joint-action space, (b) uses that we only consider the m-times, where we updated the estimated transition model and (c) uses an union bound over the update times m and an application of Hoeffding's inequality combined with the fact that we can bound the value function, i.e. $V^i(s') \leq \frac{R_{\text{max}}}{1-\gamma}$ for every $s' \in \mathcal{S}$. Next, we will consider the first two equations regarding the estimation of the Nash policy of the expert. In a first step we define the following set

$$
\mathcal{E}^{\pi}:=\left\{\forall k\in\mathbb{N},\,\forall (s,\mathbf{a})\in\mathcal{S}\times\mathcal{A}:\left|\mathbbm{1}_{E}-\mathbbm{1}_{\hat{E}}\right|\leq\mathbbm{1}_{\{N_{k}(s)\leq\max\{1,\xi(N_{k}(s),\delta/2)\}\}}\right\}.
$$

We will the bound the probability of the complement of this event by δ and can then take the intersection of both events to get the total result.

$$
\mathbb{P}((\mathcal{E}^{\pi})^{C}) = \mathbb{P}(\exists k \in \mathbb{N}, \exists (s, \mathbf{a}) \in \mathcal{S} \times \mathcal{A} : |\mathbb{1}_{E} - \mathbb{1}_{\hat{E}}| > \mathbb{1}_{\{N_{k}(s) \leq \max\{1, \xi(N_{k}(s), \delta/2)\}\}})
$$
\n
$$
\stackrel{(a')}{\leq} \mathbb{P}\left(\exists m \in \mathbb{N}, \exists (s, \mathbf{a}) \in \mathcal{S} \times \mathcal{A} : |\mathbb{1}_{E} - \mathbb{1}_{\hat{D}_{m}}| > \mathbb{1}_{\{N_{k}(s) \leq \max\{1, \xi(N_{k}(s), \delta/2)\}\}}\right)
$$
\n
$$
\stackrel{(b')}{\leq} \sum_{(s, \mathbf{a}) \in \mathcal{S} \times \mathcal{A}} \sum_{m \geq 0} \mathbb{P}\left(|\mathbb{1}_{E} - \mathbb{1}_{\hat{D}_{m}}| > \mathbb{1}_{\{N_{k}(s) \leq \max\{1, \xi(m, \delta/2)\}\}}\right)
$$
\n
$$
\leq \sum_{(s, \mathbf{a}) \in \mathcal{S} \times \mathcal{A}} \sum_{m \geq 1} \mathbb{P}\left(|\mathbb{1}_{E} - \mathbb{1}_{\hat{D}_{m}}| > \mathbb{1}_{\{N_{k}(s) \leq \max\{1, \xi(m, \delta/2)\}\}}\right)
$$
\n
$$
\stackrel{(c')}{\leq} \sum_{(s, \mathbf{a}) \in \mathcal{S} \times \mathcal{A}} \sum_{m \geq 1} \frac{\delta}{6S \prod_{i=1}^{n} |\mathcal{A}^{i}| m^{2}} = \frac{\pi^{2}}{12} \frac{\delta}{2} \leq \frac{\delta}{2},
$$

where (a') again uses the fact to only consider the m-times, where the policy estimation is updated, (b') uses an union bound over (s, a) and m. (c') is an application of [E.2.](#page-26-0)

If we now define $\mathcal{E} := \mathcal{E}^{\text{trans}} \cap \mathcal{E}^{\pi}$, we can conclude the proof since both events of the good event hold with probability $1 - \delta/2$ and therefore $\mathcal E$ holds with probability $1 - \delta$.

 \Box

.

Following, we present the reward uncertainty metric, which allows us to demonstrate that the difference between the recovered reward function and the true reward function is bounded.

Definition D.2 (Reward Uncertainty). Let k be the number of iterations. Then the reward uncertainty after k iterations for any $(s, a) \in S \times A$ is defined as

$$
C_k(s, \mathbf{a}) := \frac{R_{\max}}{1 - \gamma} \left(\mathbb{1}_{\{N_k(s) \leq \max\{1, \xi(N_k(s), \delta/2)\}\}} + \gamma \sqrt{\frac{8l_k(s, \mathbf{a})}{N_k^+(s, \mathbf{a})}} \right)
$$

Theorem [D.2.](#page-23-0) Let the reward uncertainty be defined as in D.2. Under the good event it holds for any $(s, a) \in S \times A$ that:

$$
|R^i(s, a) - \hat{R}^i(s, a)| \leq C_k(s, a).
$$

Proof. The theorem is an application of the error propagation [4.1,](#page-5-0) followed by [5.1.](#page-8-0)

$$
|R^{i}(s, \mathbf{a}) - \hat{R}^{i}(s, \mathbf{a})| \leq A^{i}(s, \mathbf{a})|\mathbb{1}_{E} - \mathbb{1}_{\hat{E}}| + \gamma \sum_{s'} |(P(s' \mid s, \mathbf{a}) - \hat{P}(s' \mid s, \mathbf{a}))V^{i}(s')|
$$

$$
\leq \frac{R_{\max}}{1 - \gamma} \left(\mathbb{1}_{\{N_{k}(s) \leq \max\{1, \xi(N_{k}(s), \delta/2)\}\}} + \gamma \sqrt{\frac{2l_{k}(s, \mathbf{a})}{N_{k}^{+}(s, \mathbf{a})}} \right)
$$

$$
\leq \frac{R_{\max}}{1 - \gamma} \left(\mathbb{1}_{\{N_{k}(s) \leq \max\{1, \xi(N_{k}(s), \delta/2)\}\}} + \gamma \sqrt{\frac{8l_{k}(s, \mathbf{a})}{N_{k}^{+}(s, \mathbf{a})}} \right)
$$

$$
= C_{k}(s, \mathbf{a}).
$$

 \Box

Corollary D.1. Let k be the number of iterations for any allocation of the samples over the stateaction space $S \times A$. Furthermore, let $\mathcal{R}_{\mathcal{G} \cup R}$ be the true feasible set and $\mathcal{R}_{\hat{G} \cup \hat{R}}$ the recovered one. Then the optimality criterion [4.3](#page-6-0) holds true, if

$$
\frac{1}{1-\gamma}\max_{(s,\mathbf{a})}C_k(s,\mathbf{a})\leq \frac{\varepsilon}{2}.
$$

Proof. We complete the proof for the first case of the optimality criterion, the second one follows analogously.

$$
\sup_{R \in \mathcal{R}_{\mathcal{G} \cup R}} \inf_{\hat{R}^i \in \mathcal{R}_{\mathcal{G} \cup \hat{R}}} \max_{i \in [n]} \max_{\pi^i \in \Pi^i} V_{\mathcal{G} \cup R}^i(\pi^i, \hat{\pi}^{-i}) - V_{\mathcal{G} \cup R}^i(\hat{\pi}^i, \hat{\pi}^{-i})
$$
\n
$$
\leq \sup_{R \in \mathcal{R}_{\mathcal{G} \cup R}} \inf_{\hat{R}^i \in \mathcal{R}_{\mathcal{G} \cup \hat{R}}} \max_{i \in [n]} \max_{\pi^i \in \Pi^i} \sum_{s, \mathbf{a}} \overline{w}_{s,a}^{\hat{\pi}} \left(R^i(s, \mathbf{a}) - \hat{R}^i(s, \mathbf{a}) + \gamma \sum_{s'} \left(\hat{P}(s' \mid s, \mathbf{a}) - P(s' \mid s, a) \right) V^{i, \hat{\pi}}(s') \right)
$$
\n
$$
+ \sum_{s, \mathbf{a}} \overline{w}_{s, \mathbf{a}}^{\pi} (R^i(s, \mathbf{a}) - \hat{R}^i(s, \mathbf{a}) + \gamma \sum_{s'} \left(\hat{P}(s' \mid s, \mathbf{a}) - P(s' \mid s, \mathbf{a}) \right) V^{i, \tilde{\pi}}(s') \right)
$$
\n
$$
\leq \sup_{R \in \mathcal{R}_{\mathcal{G} \cup R}} \inf_{\hat{R}^i \in \mathcal{R}_{\mathcal{G} \cup \hat{R}}} \max_{i \in [n]} \max_{\pi^i \in \Pi^i} 2 \sum_{s, \mathbf{a}} \overline{w}_{s, \mathbf{a}}^{\pi} \left(R^i(s, \mathbf{a}) - \hat{R}^i(s, \mathbf{a}) + \gamma \sum_{s'} \left(\hat{P}(s' \mid s, \mathbf{a}) - P(s' \mid s, \mathbf{a}) \right) V^{i, \pi}(s') \right)
$$
\n
$$
\leq \sup_{R \in \mathcal{R}_{\mathcal{G} \cup R}} \inf_{\hat{R}^i \in \mathcal{R}_{\mathcal{G} \cup \hat{R}}} \max_{i \in [n]} \max_{\pi^i \in \Pi^i} 2 \sum_{s
$$

where in (a) we applied [4.3;](#page-6-2) in (b) we used the fact that $a + b \leq 2 \max\{a, b\}$ and denoted the corresponding policy as π ; in (c) we used the error propagation [4.1](#page-5-0) and in (d) we used [D.2.](#page-23-1) \Box

We can combine the derived results to now state the main theorem regarding the sample complexity of the Uniform Sampling [1.](#page-7-2)

Theorem D.3 (Sample Complexity of Uniform Sampling MAIRL). The Uniform Sampling algorithm [\(1\)](#page-7-2) stops with a probability of at least $1 - \delta$ after iteration τ and satisfies the optimality criterion (see [4.3\)](#page-6-0), where the sample complexity is of order

$$
\tilde{\mathcal{O}}\left(\max\left(\frac{\gamma^2 R_{\max}^2 S\prod_{i=1}^n |\mathcal{A}^i|}{(1-\gamma)^4\varepsilon^2},nS+\frac{nS}{\log(1/(1-\boldsymbol{\pi}^{Nash}_{min}))}\right)\right)
$$

Proof. We know from [D.1,](#page-23-2) that we need

$$
\frac{1}{1-\gamma} \max_{(s,\mathbf{a})} C_k(s,\mathbf{a}) \le \frac{\varepsilon_k}{2}
$$

$$
\Leftrightarrow \frac{R_{\max}}{(1-\gamma)^2} \max_{(s,\mathbf{a})} \left(\mathbb{1}_{\{N_k(s) \le \max\{1,\xi(N_k(s),\delta/2)\}\}} + \gamma \sqrt{\frac{8l_k(s,\mathbf{a})}{N_k^+(s,\mathbf{a})}} \right) \le \frac{\varepsilon_k}{2}
$$

This is satisfied if

$$
\frac{\gamma R_{\max}}{(1-\gamma)^2} \sqrt{\frac{8l_k(s,\mathbf{a})}{N_k^+(s,\mathbf{a})}} \le \frac{\varepsilon_k}{2}
$$

$$
\frac{R_{\max}}{(1-\gamma)^2} \mathbb{1}_{\{N_k(s) \le \max\{1,\xi(N_k(s),\delta/2)\}\}} = 0.
$$

To achieve the first condition, we get

$$
N_k(s, \mathbf{a}) \ge \frac{R_{\text{max}}^2}{(1 - \gamma)^4} \gamma^2 8l_k(s, \mathbf{a}) \frac{4}{\varepsilon_k^2} = \frac{\gamma^2 32 R_{\text{max}}^2}{(1 - \gamma)^4 \varepsilon_k^2} \log \left(\frac{12S \prod_i |\mathcal{A}^i| (N_k^+(s, \mathbf{a}))^2}{\delta} \right)
$$

Applying Lemma B.8 by [Metelli et al.](#page-12-3) [\(2021\)](#page-12-3) we get that

$$
N_k(s, \mathbf{a}) \le \frac{128\gamma^2 R_{\max}^2}{(1-\gamma)^4 \varepsilon_k^2} \log \left(\frac{64\gamma^2 R_{\max}^2}{(1-\gamma)^4 \varepsilon_k^2} \sqrt{\frac{12S \prod_i |\mathcal{A}^i|}{\delta}} \right)
$$

.

At each iteration we are allocating the samples uniformly over $S \times A$ and recalling that $\tau_{s,a} =$ $S \prod_i |\mathcal{A}^i| N_k(s, \mathbf{a})$ therefore we get

$$
\tau \le \frac{128S \prod_i |\mathcal{A}^i| \gamma^2 R_{\text{max}}^2}{(1-\gamma)^4 \varepsilon_k^2} \log \left(\frac{64a \gamma^2 R_{\text{max}}^2}{(1-\gamma)^4 \varepsilon_k^2} \sqrt{\frac{12S \prod_i |\mathcal{A}^i|}{\delta}} \right)
$$

Now we only have to achieve the second condition, we have to satisfy that the indicator function needs to be equal to 0 and therefore

$$
N_k(s) \geq \frac{\log(2S\prod_{i=1}^n|\mathcal{A}^i|(n-1)N_k(s)^2/\delta)}{\log((1/(1-\pi_{\min}^{\text{Nash}}))} = \frac{\log(2S\prod_{i=1}^n|\mathcal{A}^i|(n-1)/\delta)}{\log((1/(1-\pi_{\min}^{\text{Nash}}))} + \frac{2\log(N_k(s))}{\log((1/(1-\pi_{\min}^{\text{Nash}}))}
$$

If we additionally force that $N_k(s) \ge 1$ and apply Lemma 15 of [Kaufmann et al.](#page-11-14) [\(2020\)](#page-11-14) we get that

$$
N_k(s) \le 1 + \frac{1}{\log((1/(1 - \pi_{\min}^{\text{Nash}}))} \left(\log(2S) \prod_{i=1}^n |\mathcal{A}^i| (n-1)/\delta) + 2 \frac{\log(2S) \prod_{i=1}^n |\mathcal{A}^i| (n-1)/\delta) + 2}{\log((1/(1 - \pi_{\min}^{\text{Nash}}))} \right)
$$

As we here need to allocate samples uniformly over the state space only but for every agent separately and recalling that $\tau_s = SN_k(s)$, we get

$$
\tau_s \leq nS + \frac{nS}{\log((1/(1-\pi_{\min}^{\text{Nash}}))} \left(\log(2S) \prod_{i=1}^n |\mathcal{A}^i|(n-1)/\delta) + 2 \frac{\log(2S) \prod_{i=1}^n |\mathcal{A}^i|(n-1)/\delta) + 2}{\log((1/(1-\pi_{\min}^{\text{Nash}}))} \right).
$$

With $\tau = \tau_{s,a} + \tau_s$ we get in total

$$
\tau \leq \frac{128S \prod_{i} |\mathcal{A}^{i}| \gamma^{2} R_{\max}^{2}}{(1-\gamma)^{4} \varepsilon_{k}^{2}} \log \left(\frac{64a \gamma^{2} R_{\max}^{2}}{(1-\gamma)^{4} \varepsilon_{k}^{2}} \sqrt{\frac{12S \prod_{i} |\mathcal{A}^{i}|}{\delta}} \right) + nS + \frac{nS}{\log((1/(1-\pi_{\min}^{\text{Nash}}))} \left(\log(2S \prod_{i=1}^{n} |\mathcal{A}^{i}|(n-1)/\delta) + 2 \frac{\log(2S \prod_{i=1}^{n} |\mathcal{A}^{i}|(n-1)/\delta) + 2}{\log((1/(1-\pi_{\min}^{\text{Nash}}))} \right).
$$

This is exactly of order

$$
\tilde{\mathcal{O}}\left(\max\left(\frac{\gamma^2 R_{\max}^2 S\prod_{i=1}^n |\mathcal{A}^i|}{(1-\gamma)^4 \varepsilon^2}, nS + \frac{nS}{\log(1/(1-\pi_{\min}^{\text{Nash}}))}\right)\right)
$$

E Technical Lemmas

The next lemma is an extension of Lemma 3 from [Zanette et al.](#page-13-12) [\(2019\)](#page-13-12) for the multi-agent setting, accounting that different Nash equilibria can have different values.

Lemma E.1 (Simulation Lemma). Let $i \in [n]$ be any agent. Then it holds true that

$$
\hat{V}^{i,\pi}(s) - V^{i,\pi}(s) = \sum_{s,\mathbf{a}} \overline{w}_{s,\mathbf{a}}^{\pi} \left(\hat{R}^i(s,\mathbf{a}) - R^i(s,\mathbf{a}) + \gamma \left(\sum_{s'} \left(\hat{P}(s' \mid s,\mathbf{a}) - P(s' \mid s,\mathbf{a}) \right) V^{i,\pi}(s') \right) \right)
$$

Proof. Let the starting distribution be a dirac measure on some $s \in \mathcal{S}$. It then holds that

$$
\hat{V}^{i,\pi}(s) - V^{i,\pi}(s) = \hat{R}^i(s, \mathbf{a}) - R^i(s, \mathbf{a}) + \gamma \left(\sum_{s'} \hat{P}(s' \mid s, \mathbf{a}) \hat{V}^{i,\pi}(s') - P(s' \mid s, \mathbf{a}) V^{i,\pi} \right) (s')
$$
\n
$$
= \hat{R}^i(s, \mathbf{a}) - R^i(s, \mathbf{a}) + \gamma \left(\hat{P}(s' \mid s, \mathbf{a}) - P(s' \mid s, \mathbf{a}) \right) V^{i,\pi}(s')
$$
\n
$$
+ \gamma \sum_{s'} \hat{P}(s' \mid s, \mathbf{a}) (\hat{V}^{i,\pi}(s') - V^{i,\pi}(s'))
$$

The proof follows by induction.

 \Box

The next lemma is crucial for bounding the error on the policy estimation problem. It is an extension of Lemma E.5 in [Metelli et al.](#page-12-5) [\(2023\)](#page-12-5) to n independent categorical distributions and the additional indicator.

Lemma E.2. Let $\mathbb{P}_j = (p_{1_j}, \ldots, p_{D_j})$ be a categorical probability measure with support on the number of events D_j for all $j \in \{1, \ldots, n\}$ with $n \geq 2$ denoting the total number of probability measures. Furthermore, let $\mathbb{P}_{n_j} = (\hat{p}_1, \ldots, \hat{p}_{D_j})$ be the maximum likelihood estimate of \mathbb{P}_j obtained with $N \geq 1$ independent samples. Then if $p_{i_j} \in \{0\} \cup [p_{min_j}, 1]$ for some $p_{min_j} \in (0, 1]$ for all $j \in \{1, ..., n\}$. Then for every joint event l in the joint probability measure $\mathbb P$ individually, it holds with probability greater than 1- δ , with $\delta \in (0,1)$:

$$
|\mathbbm{1}_{\{p_{\textbf{I}_i}=0\}}\mathbbm{1}_{\{p_{\textbf{I}_{-i}}>0\}}-\mathbbm{1}_{\{\hat{p}_{\textbf{I}_i}=0\}}\mathbbm{1}_{\{\hat{p}_{\textbf{I}_{-i}}>0\}}|\ \leq\mathbbm{1}_{\left\{N\leq\max\left\{1,\frac{\log\left(\frac{1}{\delta}\right)+\log\left(n-1\right)}{\log\left(\frac{1}{1-P_{\min}}\right)}\right\}\right\}},
$$

where $p_{\min} := \min_{j \in [n]} p_{\min_j}$ and $p_{l_{-i}}$ refers to any index l_j for all $j \in \{1, \dots n\} \setminus \{i\}.$

Proof. As the appearing term is the difference of the product of indicator functions, it is equal to 0 or 1. We want to bound the difference with high probability, therefore we will derive the amounts of sample we need, such that the difference is equal to 0 with high probability. To do so, we investigate the different cases of the difference to be zero. We start with the two trivial cases and then give the last case, that yields the resulting high probability bound.

- 1. $p_{l_i} > 0$ and for at least one $j \neq i$ $p_{l_j} = 0$. In this case it is enough to investigate the estimation of any one of the agents $j \neq i$ that has zero probability on that event. As after the first sample the maximum likelihood estimation of the categorical distribution almost surely equals 0.
- 2. $p_{i} = 0$ and for at least one $j \neq i$ $p_{i} = 0$. The same arguments hold true for this case.

The next case is if $p_{l_i} > 0$ and for all $l_j \neq i \, p_{l_j} > 0$. In this case the difference is zero as long as we haven't seen all the events of the categorical distribution of \mathbb{P}_j for all $j \neq i$ or once we see the event of categorical distribution \mathbb{P}_i . Therefore the case that yields to the result is $p_{l_i} = 0$ and $p_{l_{-i}} > 0$. Since after one sample of the categorical probability measure \mathbb{P}_i we have $\hat{p}_{i_i} = 0$ almost surely, we focus on the latter case. $\hat{p}_{l_{-i}} = 0$ holds true if for any $j \in [n] \setminus \{i\}$ we haven't seen a sample yet. Let $X_{1_j}, \ldots X_{N_j}$ denote a sequence of random variables for drawing the event l_j from the categorical

distribution \mathbb{P}_j and N the total number of samples. Then we can denote the probability of $\hat{p}_{l_{-i}} = 0$ as

$$
\mathbb{P}\left(\bigcup_{j\neq i}\bigcap_{k_j\in[N]} X_{k_j} \neq l_j\right) \stackrel{(1)}{\leq} \sum_{j\neq i} \mathbb{P}\left(\bigcap_{k_j\in[N]} X_{k_j} \neq l_j\right)
$$

$$
\stackrel{(2)}{=} \sum_{j\neq i} \prod_{k_j\in[N]} \mathbb{P}(X_{k_j} \neq l_j)
$$

$$
\stackrel{(3)}{=} \sum_{j\neq i} \mathbb{P}(X_{1j} \neq l_j)^N
$$

$$
\stackrel{(4)}{\leq} \sum_{j\neq i} (1 - p_{\min_j})^N
$$

$$
\stackrel{(5)}{\leq} \sum_{j\neq i} (1 - p_{\min_j})^N \leq (n - 1)(1 - p_{\min})^N,
$$

where (1) follows by a union bound over $[n] \setminus \{i\}$, (2) by the independent drawing of the samples, (3) uses the identical distributions of the j-th samples and (4) , (5) the assumption on the probability lower bounds. Rewriting this in terms of the samples N yields

$$
(n-1)(1 - p_{\min})^N \le \delta
$$

\n
$$
\Leftrightarrow \log(n-1) + N \log(1 - p_{\min}) \le \log(\delta)
$$

\n
$$
\Leftrightarrow N \ge \frac{\log(\delta) - \log(n-1)}{\log(1 - p_{\min})}
$$

\n
$$
\Leftrightarrow N \ge \frac{\log(\frac{1}{\delta}) + \log(n-1)}{\log(\frac{1}{1 - p_{\min}})}.
$$

F Experimental Evaluation

F.1 Environments

In this section, we describe in detail the environment of the Multi-agent Gridworld.

F.1.1 Multi-agent Gridworld

In this section, we describe the environments used for the experiments. The environments are similar to the ones used in [Hu and Wellman](#page-11-9) [\(2003\)](#page-11-9). We adjust them in such that for the random transition probabilities in the states (0, any) and (2, any) the environment still has different goals for each agent. Additionally, we introduce the scenario, where an obstacle is added in the middle of the environment, that bounces the agent back with probability 1. This results in a failure of reaching the goal for agent 1 in the BC case.

In the left column, we draw the learned Nash path for both agents in the deterministic environment, when applying the NashQ Learning algorithm to retrieve an expert policy.

F.2 Max Gap MAIRL

In this section, we describe the Max Gap MAIRL algorithm, an extension of the approach presented by [Metelli et al.](#page-12-3) [\(2021\)](#page-12-3) (see Appendix C in [Metelli et al.](#page-12-3) [\(2021\)](#page-12-3)) to the multi-agent setting. This

Figure 2: Multi-agent grid world environments with different transition probabilities and learned NE path

algorithm is chosen due to the limited number of existing works that address the selection of feasible reward functions in general-sum Markov games with a Nash expert, particularly without imposing additional assumptions on the reward structure. Given the simplicity of the chosen environments, the Max Gap MAIRL procedure is a suitable choice.

The algorithm operates as follows: for each agent $i \in [n]$, a random reward function \tilde{R}^i is selected such that $\|\tilde{R}^i\| \le R_{\text{max}}$. The next step involves finding a reward function R^i that minimizes the squared 2-norm distance to the randomly chosen reward \tilde{R}^i , subject to two constraints: (1) R^i must belong to the recovered feasible set, and (2) it must maximize the maximal reward gap, thereby enforcing the feasible reward condition as introduced in [4.2.](#page-4-0) This results in the following constrained quadratic optimization problem:

$$
\max_{R^i \in \mathbb{R}^S, A^{i, \pi}} A^{i, \pi}
$$
\ns.t.
$$
(\pi^{\text{Nash}} - \tilde{\pi})(I - \gamma \mathbf{P} \pi^{\text{Nash}})^{-1} \mathbf{R}^i \geq A^{i, \pi} \mathbb{1}_{\{\pi^{i, \text{Nash}} = 0\}} \mathbb{1}_{\{\pi^{-i, \text{Nash}} > 0\}} \mathbb{1}_{\mathcal{S} \times \mathcal{A}},
$$
\n
$$
\|R^i\|_{\infty} \leq R_{\text{max}}.
$$

F.3 Empirical Evaluation of the Theoretical Bound

In this subsection, we empirically evaluate the sample complexity bound in the introduced Gridworld environment with altered transition probabilities for the "up" action in the starting states. We observe that the theoretical bound is higher than the empirically observed one. A potential reason for this discrepancy is the simplicity of the chosen environment. Specifically, the expert explores only a few of the 72 possible states, while the introduced theory is designed for the most general case. The uniform sampling algorithm does not explore efficiently in these cases, and problem-dependent algorithms, similar to those introduced in [Metelli et al.](#page-12-3) [\(2021\)](#page-12-3), should be investigated. We leave this for future work. As the Nash Gap can not be smaller than 0, we clip the lower confidence interval.

Figure 3: Theoretical Bound vs Empirical Nash Gap evaluation.