

Stain-invariant representation for tissue classification in histology images

Author

Manahil Raza, Saad Bashir, Talha Qaiser, Nasir Rajpoot – Tissue Image Analytics Centre, Department of Computer Science, University of Warwick, Coventry CV4 7AL, U.K.

Citation

Raza, M., Bashir, S., Qaiser, T., Rajpoot, N., Stain-invariant representation for tissue classification in histology images.

Abstract

The process of digitizing histology slides involves multiple factors that can affect a whole slide image's (WSI) final appearance, including the staining protocol, scanner, and tissue type. This variability constitutes a domain shift and results in significant problems when training and testing deep learning (DL) algorithms in multi-cohort settings. As such, developing robust and generalizable DL models in computational pathology (CPath) remains an open challenge. In this regard, we propose a framework that generates stain-augmented versions of the training images using stain matrix perturbation. Thereafter, we employed a stain regularization loss to enforce consistency between the feature representations of the source and augmented images. Doing so encourages the model to learn stain-invariant and consequently, domain-invariant feature representations. We evaluated the performance of the proposed model on cross-domain multi-class tissue type classification of colorectal cancer images and have achieved improved performance compared to other state-of-the-art methods.



Introduction

The advent of Deep Learning (DL) has revolutionised the field of Computational Pathology (CPath) and has enabled the automated and guantitative analysis of histology images [1,2]. Despite the success of DL methods, they are vulnerable to domain-specific variations [3]. Some major sources of variations include staining and scanning processes, where distinct institutions may employ different staining protocols and use various scanners, resulting in differences in the visual appearance of whole slide images (WSIs). This variability poses a significant challenge known as domain shift for training robust DL models and encumbers their ability to generalise well across diverse histology datasets. Addressing the domain shift problem has been a focal point for CPath researchers, leading to several efforts in stain normalisation [4-6], augmentation and adaptation. Stain augmentation (SA) aims to mitigate the effects of domain shift by generating augmented variations of the source images to mimic the stain variations present in the target domain for improving the model's generalisability on unseen data [7-9]. Tellez et al. [24] has stressed upon the importance of using stain augmentations for histopathology images for a more robust classification performance. Abbet et al. [11] proposed a novel domain adaptation (DA) method, Self-Rule to Multi-Adapt (SRMA), for single-source and muti-source tissue classification with multiple datasets by using in-domain and crossdomain losses. Unlike in DA, domain generalisation (DG) methods cannot leverage unlabelled data from the target domain [10]. To this effect, Vuong et al. [12] adopted a self-supervised contrastive learning approach using a combination of encoders and momentum encoders for colorectal cancer classification using patch shuffling augmentations. Our proposed method, inspired by [14] uses stain augmentations to help extract domain-invariant feature representations for colorectal cancer tissue images, thus ensuring that the class labels assigned to an image remain consistent in the face of staining variability.

Methodology

The proposed framework comprises of two modules, one for classification and the other for stain augmentation, as shown in Fig. 1. Each image x





with label y is passed through ResNet-18 based feature extractor f_{e} for extracting the feature representation as $f_e(x) = r$. This feature representation is then passed onto an MLP-based classifier f_c for a classification decision, \hat{y} as $f_c(f_e(x)) = \hat{y}$ During the training process, we also employ the stain augmentation network, which generates stain-altered version(s) of the source image as $x' = \{x'_1 \dots x'_N\}$. For this purpose, we use the Vahadane [18] method for extracting the stain matrix. The stain concentrations are perturbed to create the stain-altered images using [15]. These images are then passed onto the same feature extractor $f_e(x') = r' = \{r'_1 \dots r'_N\}$ to extract feature representations of the stain-altered images. Two loss functions are employed in the proposed workflow. We use the cross-entropy loss as the primary classification loss L_c between the predicted label \hat{y} and the groundtruth label y. Additionally, we employed a mean squared error (MSE) loss as a stain regularisation loss, $L_s = ||r - r'||_{2,1}^2$, which measures the distance between the extracted feature representations of the source and augmented images. The MSE loss acts as a strong penalisation factor, enforcing



consistency in the face of stain augmentations. The overall loss function combines the two loss functions, $L = L_c + L_s$.

Results and Discussions

We have employed two datasets to validate the proposed framework 1). Kather-19 (K19) [16], which contains 100,000 images (224×224 pixels) from 9 tissue classes and 2). Kather-16 (K16) [17], which consists of 5,000 images (150×150 pixels) from 8 classes. Since there are discrepancies between the class labels of the two datasets, we followed the strategy for relabelling [11] and grouped the data into seven classes, namely adipose, background, debris, lymphocytes, normal colon mucosa, stroma and colorectal adenocarcinoma epithelium. Sample images from K16 are shown in Fig.1. The results of the experiments are reported in Table 1, where ImageNet Upper Bound denotes an experiment where both the training and testing are performed with the same dataset (K16). The degradation in performance in ImageNet Lower bound is due to the presence of a domain shift when the model is trained and tested on different source (K19) and target domains (K16). We observe that the proposed method which generated 6 augmented images for each input image, outperforms the ImageNet baseline by 22% in terms of accuracy. Whereas it performed 20% and 12% better as compared to MocoV2 [22] and InfoMin [23]. IMPaSh [12] is a combination of InfoMin [23] and PatchShuffling augmentations, and our methods still outperform it by 1% while being less computationally expensive. To summarise, the proposed workflow leveraged stain augmentations to encourage the DL model to learn stain and domain-invariant feature representations and outperformed other state-of-the-art methods which begs the guestion "Is Stain Augmentation really all you need for Domain Generalisation?" Our future work will include automating the selection of the optimal number of augmentations.



Method	Training Dataset	Accura- cy	Recall	Precision	F1- Score
ImageNet - Upper Bound	K16 (Target)	0.942	0.942	0.941	0.941
ImageNet - Lower Bound	К19	0.654	0.654	0.741	0.626
SN Macenko [19]	К19	0.660	0.660	0.683	0.645
SN Vahadane [18]	К19	0.683	0.683	0.696	0.656
InsDis [20]	К19	0.694	0.694	0.766	0.659
PIRL [21]	К19	0.818	0.818	0.853	0.812
MocoV2 [22]	К19	0.675	0.675	0.816	0.642
InfoMin [23]	К19	0.750	0.750	0.824	0.752
IMPaSh [12]	К19	0.868	0.868	0.887	0.865
Proposed Method	K19	0.878	0.878	0.887	0.877

TABLE 1: Experimental Results between source (K19) and target (K16) domains

References

[1] Wu, Y., Cheng, M., Huang, S., Pei, Z., Zuo, Y., Liu, J., Yang, K., Zhu, Q., Zhang, J., Hong, H. and Zhang, D., 2022. Recent advances of deep learning for computational histopathology: Principles and applications. Cancers, 14(5), p.1199.

[2] Echle, A., Rindtorff, N.T., Brinker, T.J., Luedde, T., Pearson, A.T. and Kather, J.N., 2021. Deep learning in cancer pathology: a new generation of clinical biomarkers. British journal of cancer, 124(4), pp.686-696.

[3] Stacke, K., Eilertsen, G., Unger, J. and Lundström, C., 2020. Measuring domain shift for deep learning in histopathology. IEEE journal of biomedical and health informatics, 25(2), pp.325-336.



frontiers

[4] Shaban, M.T., Baur, C., Navab, N. and Albarqouni, S., 2019, April. Staingan: Stain style transfer for digital histological images. In 2019 leee 16th international symposium on biomedical imaging (Isbi 2019) (pp. 953-956). IEEE.

[5] Jia, Q., Guo, J., Du, F., Yang, P. and Yang, Y., 2022, December. A Fast Texture-to-Stain Adversarial Stain Normalization Network for Histopathological Images. In 2022 IEEE International Conference on Bioinformatics and Biomedicine (BIBM) (pp. 2294-2301). IEEE.

[6] Zhao, B., Han, C., Pan, X., Lin, J., Yi, Z., Liang, C., Chen, X., Li, B., Qiu, W., Li, D. and Liang, L., 2022. RestainNet: a self-supervised digital re-stainer for stain normalization. Computers and Electrical Engineering, 103, p.108304.

[7] Jahanifar, M., Shepard, A., Zamanitajeddin, N., Bashir, R.S., Bilal, M., Khurram, S.A., Minhas, F. and Rajpoot, N., 2022. Stain-robust mitotic figure detection for the mitosis domain generalization challenge. In Biomedical Image Registration, Domain Generalisation and Out-of-Distribution Analysis: MICCAI 2021 Challenges: MIDOG 2021, MOOD 2021, and Learn2Reg 2021, Held in Conjunction with MICCAI 2021, Strasbourg, France, September 27–October 1, 2021, Proceedings (pp. 48-52). Cham: Springer International Publishing.

[8] Yamashita, R., Long, J., Banda, S., Shen, J. and Rubin, D.L., 2021. Learning domain-agnostic visual representation for computational pathology using medically-irrelevant style transfer augmentation. IEEE Transactions on Medical Imaging, 40(12), pp.3945-3954.

[9] Chang, J.R., Wu, M.S., Yu, W.H., Chen, C.C., Yang, C.K., Lin, Y.Y. and Yeh, C.Y., 2021. Stain mix-up: Unsupervised domain generalization for histopathology images. In Medical Image Computing and Computer Assisted Intervention–MICCAI 2021: 24th International Conference, Strasbourg, France, September 27–October 1, 2021, Proceedings, Part III 24 (pp. 117-126). Springer International Publishing. 27th Conference on Medical Image Understanding and Analysis 2023



[10] Ghifary, M., Balduzzi, D., Kleijn, W.B. and Zhang, M., 2016. Scatter component analysis: A unified framework for domain adaptation and domain generalization. IEEE transactions on pattern analysis and machine intelligence, 39(7), pp.1414-1430.

[11] Abbet, C., Studer, L., Fischer, A., Dawson, H., Zlobec, I., Bozorgtabar, B. and Thiran, J.P., 2022. Self-rule to multi-adapt: Generalized multi-source feature learning using unsupervised domain adaptation for colorectal cancer tissue detection. Medical image analysis, 79, p.102473.

[12] Vuong, T.T.L., Vu, Q.D., Jahanifar, M., Graham, S., Kwak, J.T. and Rajpoot, N., 2023, February. IMPaSh: A Novel Domain-Shift Resistant Representation for Colorectal Cancer Tissue Classification. In Computer Vision–ECCV 2022 Workshops: Tel Aviv, Israel, October 23–27, 2022, Proceedings, Part III (pp. 543-555). Cham: Springer Nature Switzerland.

[13] Raipuria, G., Shrivastava, A. and Singhal, N., 2022, September. Stain-AgLr: Stain Agnostic Learning for Computational Histopathology Using Domain Consistency and Stain Regeneration Loss. In Domain Adaptation and Representation Transfer: 4th MICCAI Workshop, DART 2022, Held in Conjunction with MICCAI 2022, Singapore, September 22, 2022, Proceedings (pp. 33-44). Cham: Springer Nature Switzerland

[14] Pakzad, A., Abhishek, K. and Hamarneh, G., 2023, February. CIRCLe: Color Invariant Representation Learning for Unbiased Classification of Skin Lesions. In Computer Vision–ECCV 2022 Workshops: Tel Aviv, Israel, October 23–27, 2022, Proceedings, Part IV (pp. 203-219). Cham: Springer Nature Switzerland.

[15] Pocock, J., Graham, S., Vu, Q.D., Jahanifar, M., Deshpande, S., Hadjigeorghiou, G., Shephard, A., Saad Bashir, R.M., Bilal, M., Lu, W. and Epstein, D., 2021. TIAToolbox: an end-to-end toolbox for advanced tissue image analytics. bioRxiv, pp.2021-12



[16] Kather, J.N., Krisam, J., Charoentong, P., Luedde, T., Herpel, E., Weis, C.A., Gaiser, T., Marx, A., Valous, N.A., Ferber, D. and Jansen, L., 2019. Predicting survival from colorectal cancer histology slides using deep learning: A retrospective multicenter study. PLoS medicine, 16(1), p.e1002730.

[17] Kather, J.N., Weis, C.A., Bianconi, F., Melchers, S.M., Schad, L.R., Gaiser, T., Marx, A. and Zöllner, F.G., 2016. Multi-class texture analysis in colorectal cancer histology. Scientific reports, 6(1), pp.1-11.

[18] Vahadane, A., Peng, T., Sethi, A., Albarqouni, S., Wang, L., Baust, M., Steiger, K., Schlitter, A.M., Esposito, I. and Navab, N., 2016. Structure-preserving color normalization and sparse stain separation for histological images. IEEE transactions on medical imaging, 35(8), pp.1962-1971.

[19] Macenko, M., Niethammer, M., Marron, J.S., Borland, D., Woosley, J.T., Guan, X., Schmitt, C. and Thomas, N.E., 2009, June. A method for normalizing histology slides for quantitative analysis. In 2009 IEEE international symposium on biomedical imaging: from nano to macro (pp. 1107-1110). IEEE.

[20] Wu, Z., Xiong, Y., Yu, S.X. and Lin, D., 2018. Unsupervised feature learning via non-parametric instance discrimination. In Proceedings of the IEEE conference on computer vision and pattern recognition (pp. 3733-3742).

[21] Misra, I. and Maaten, L.V.D., 2020. Self-supervised learning of pretextinvariant representations. In Proceedings of the IEEE/CVF conference on computer vision and pattern recognition (pp. 6707-6717).

[22] Chen, X., Fan, H., Girshick, R. and He, K., 2020. Improved baselines with momentum contrastive learning. arXiv preprint arXiv:2003.04297.

[23] Tian, Y., Sun, C., Poole, B., Krishnan, D., Schmid, C. and Isola, P., 2020. What makes for good views for contrastive learning?. Advances in neural information processing systems, 33, pp.6827-6839.



[24] Tellez, D., Litjens, G., Bándi, P., Bulten, W., Bokhorst, J.M., Ciompi, F. and Van Der Laak, J., 2019. Quantifying the effects of data augmentation and stain color normalization in convolutional neural networks for computational pathology. Medical image analysis, 58, p.101544.