Aligning Generalisation Between Humans and Machines

Filip Ilievski^{1*}, Barbara Hammer², Frank van Harmelen¹, Benjamin Paassen², Sascha Saralajew³, Ute Schmid⁴, Michael Biehl⁵, Marianna Bolognesi⁶, Xin Luna Dong⁷, Kiril Gashteovski^{3,8}, Pascal Hitzler⁹, Giuseppe Marra¹⁰, Pasquale Minervini^{11,12}, Martin Mundt^{13,14}, Axel-Cyrille Ngonga Ngomo¹⁵, Alessandro Oltramari¹⁶, Gabriella Pasi¹⁷, Zeynep G. Saribatur¹⁸, Luciano Serafini¹⁹, John Shawe-Taylor²⁰, Vered Shwartz^{21,22}, Gabriella Skitalinskaya²³, Clemens Stachl^{24,25}, Gido M. van de Ven¹⁰, Thomas Villmann^{26,27}
¹Vrije Universiteit Amsterdam. ²University of Bielefeld. ³NEC Laboratories Europe. ⁴University of Groningen. ⁶Università di Bologna. ⁷Meta Reality Labs. ⁸CAIR, Ss. Cyril and Methodius University of Skopje. ⁹Kansas State University. ¹⁰KU Leuven. ¹¹University of Edinburgh. ¹²Miniml.AI.
¹³Technical University of Darmstadt.

*Corresponding author(s). E-mail(s): f.ilievski@vu.nl;

Abstract

Recent advances in AI-including generative approaches-have resulted in technology that can support humans in scientific discovery and decision support but may also disrupt democracies and target individuals. The responsible use of AI increasingly shows the need for human-AI teaming, necessitating effective interaction between humans and machines. A crucial yet often overlooked aspect of these interactions is the different ways in which humans and machines generalise. In cognitive science, human generalisation commonly involves abstraction and concept learning. In contrast, AI generalisation encompasses out-of-domain generalisation in machine learning, rule-based reasoning in symbolic AI, and abstraction in neuro-symbolic AI. In this perspective paper, we combine insights from AI and cognitive science to identify key commonalities and differences across three dimensions: notions of generalisation, methods for generalisation, and evaluation of generalisation. We map the different conceptualisations of generalisation in AI and cognitive science Along these three dimensions and consider their role in human-AI teaming. This results in interdisciplinary challenges across AI and cognitive science that must be tackled to provide a foundation for effective and cognitively supported alignment in human-AI teaming scenarios.

Keywords: generalisation, human-AI teaming, alignment

Contents

1	Introduction	4			
2	2 Parallels in the Generalisation by Humans and Machines				
3	Notions of Generalisation 3.1 Generalisation as a process 3.2 Generalisation as a product	8 9 9			
4	 3.3 Generalisation as an operator	10 10 11 12 14			
5	Evaluation of Generalisation5.1Measuring distributional shifts5.2Determining under- and over-generalisation5.3Distinguishing memorisation, generalisation, and abstraction5.4Evaluating human-AI teaming	14 15 15 16 17			
6	Emerging Directions	18			

1 Introduction

Recent advances in AI—including generative approaches—have resulted in technology that can support humans in decision-making and scientific discovery, as exemplified by its recent use for predicting protein structures (Jumper et al., 2021). Conversely, AI also has the potential to disrupt democracies and target individuals (Ferrara, 2024), as shown by the deepfake audio of President Biden in the New Hampshire primary. The responsible use of AI increasingly highlights the need for advances in human-AI teaming, especially in complex application scenarios, such as automotive driver assistance or decision-making in medicine. However, effective human-AI teaming requires *alignment* of their interaction properties. Alignment implies at least that humans must be able to assess the AI's responses and to access rationales (called "explanations", Doran et al., 2017) that underpin these responses.

A crucial yet often overlooked aspect of these interactions is the complementary ways in which humans and machines generalise (Figure 1). Generalisation is typically defined as a transfer of what has been learned in one context to a new, potentially similar one (Goldstein, 2015). In cognitive science, human generalisation commonly involves concept learning and the abstraction of general characteristics to a collection of entities (Harnad, 2017, Medin et al., 2005). Humans excel at generalising from a few examples, handling out-of-distribution (OOD) data, reasoning about causal implications, and filling gaps in experience using abstraction, common sense, and structured knowledge, even within limited information and time constraints (Holzinger et al., 2023). This contrasts sharply with data-driven AI systems, which struggle to generalise beyond their training distribution and abstract effectively despite processing vast amounts of data. Statistical learning systems are driven by correlations rather than causal inference. Statistical learning, in turn, excels in data faithfulness (finding regularities in complex data), scale, and high complexity.

The goal of human-machine teaming (Vats et al., 2024) is that each side addresses the limitations of the other. For example, some generalisation capabilities of large language models (LLMs), like the quick production of rhetorically polished texts on any topic, are beyond those of most humans. Yet, their over-generalisation errors ("hallucinations", Ji et al., 2023b), like replacing specific facts with non-factual information, can be easily caught by a knowledgeable human. The complementarity of humans and AI has also shed new light on traditional analytical and case-to-case (or instancebased) AI paradigms, resulting in emerging research directions under the umbrella of neuro-symbolic AI (Besold et al., 2021, Hitzler et al., 2023). Neuro-symbolic AI aims to preserve the strengths of currently dominant (neural) statistical models, such as scaling and capturing complexity, while enhancing their ability for abstraction and justification by leveraging symbolic approaches, ultimately enabling more effective human-AI teaming.

This perspective paper draws on insights about the generalisation of humans and machines from AI and cognitive science. We identify key commonalities and differences across three dimensions critical for human-AI teaming: *notions* of generalisation, *methods* for generalisation, and *evaluation* of generalisation. Along these three dimensions, we map the different conceptualizations of generalisation in AI and cognitive



Fig. 1: Comparison of generalisation mechanisms in humans and machines. Humans excel at compositionality, common sense, abstraction from a few examples, and robustness to variations. Machines excel at data faithfulness, scale, memorization, and model extension. Bias and over-generalisation remain challenging for both humans and machines. Collaborative and explainable mechanisms are key to human-AI teaming.

science while focusing on the following questions: What are the known notions of generalisation in humans and AI? What are the generalisation strengths and weaknesses of various families of AI methods? What is the state-of-the-art of evaluating the generalisation properties of AI? And finally, what are the capabilities and limitations of human-AI teams regarding generalisation? Addressing these questions reveals interdisciplinary generalisation challenges across AI and cognitive science that must be tackled to provide a foundation for effective and cognitively supported alignment in human-AI teaming scenarios.

2 Parallels in the Generalisation by Humans and Machines

Approaches to generalisation have been proposed in the context of machine learning (ML) as well as in cognitive psychology and often mutually inspired each other. This mutual inspiration holds for all types of approaches, be it symbolic and knowledge-informed approaches to rule learning, case-based and analogy-based approaches, as well as neural and statistical approaches (we will describe how the capability of generalisation is approached in such methods in Section 4). In the current section, this observation will be illustrated by selected historical milestones, summarized in Figure 2.

In the early days of cognitive psychology, Bruner et al. (1956) presented a series of empirical studies and experiments investigating human concept learning (Figure 2a). These studies focused on learning conjunctive and disjunctive rules from examples. The reported findings inspired the first decision tree learning algorithms (Hunt et al.,



(a) Learning conjunctive rules (Bruner et al., 1956), the relational rule 'grandparent' using a background theory 'parent' (Muggleton and De Raedt, 1994), and names of alien objects modelled as Bayesian inference over a tree-structured domain representation (Tenenbaum et al., 2011).



(b) Example-based prototypical representations (cf. Rosch and Mervis, 1975, and Medin et al., 1987), context-effects (Labov, 1973), and analogy (Falkenhainer et al., 1989).



(c) Statistical generalisation: neural network model of semantic memory (Rumelhart et al., 1986).

Fig. 2: Illustrative examples of human generalisation and its inspiration of rule-based (top), example-based (middle), and statistical machine learning approaches (bottom).

1966, Quinlan, 1987). Observations on human learning of relational concepts—such as family relations or compound objects such as arches— inspired early machine learning approaches for learning from structural representations (Muggleton and De Raedt, 1994, Winston, 1970) and for recursive concepts (Schmid and Kitzelmann, 2011). This class of approaches is often referred to as inductive programming, and allows learning from a few examples and taking into account background knowledge for model induction (Gulwani et al., 2015). Rule learning approaches have been extended to statistical relational learning (De Raedt and Kersting, 2008) to overcome the brittleness of purely symbolic learning. Bayesian approaches to rule learning have been introduced in cognitive science as a plausible framework to model human learning in complex domains such as language acquisition (Lake et al., 2015, Tenenbaum et al., 2011).

Although there is substantial empirical evidence for human concept learning as learning of rules (Bruner et al., 1956, Lafond et al., 2009), this learning approach is typically evident only in specific settings. Rule learning as an explicit approach (system 2, Kahneman, 2011) is apparent for domains of high-level cognition where relevant features and possibly relations can be verbalised. For many other domains where knowledge is not (entirely) available in explicit, symbolic, or declarative representations, other theories have been proposed in cognitive psychology, and other machine learning approaches than rule learning are more suitable and effective. For instance, prototype theory was proposed as a similarity-based approach where entities are grouped into concepts or categories where similarity within category borders is maximized and between categories minimized (Rosch and Mervis, 1975), see Figure 2b. This approach is reflected in similarity-based methods to machine learning, especially k-nearest neighbours (Cover and Hart, 1967). While cognitive theories address the grouping of objects into basic, super-, and subcategories—for example, empirically demonstrated by Rosch (1978), chair as a basic category, furniture as a super-category, and office chair as a sub-category—similarity-based machine learning typically does not address the hierarchical structure of categories. Another similarity-based approach proposed in cognitive research is exemplar theories (Nosofsky, 1988), which were proposed to address the flexibility of human categorization. For instance, these theories were used to show that the context-dependence of the classification of visual objects by humans empirically: Labov (1973) presented evidence that a cup might be classified alternatively as bowl or vase when different contexts, i.e., soup or flower, are induced.

Research in analogical reasoning addresses knowledge transfer from one situation to another, often from a different domain (Falkenhainer et al., 1989, Gentner, 1983). Analogical reasoning is also a similarity-based approach. In contrast to other methods based on similarity, it is not based on feature-similarity but on structural similarity (Gentner and Markman, 1997, Wiese et al., 2008). Computational models of analogical transfer and learning have been proposed in cognitive science and AI research (Gentner and Forbus, 2011) and have demonstrated the suitability of approaches to analogical generalisation to address transfer and learning in highly complex cognitive domains. In cognitive artificial intelligence, analogy-based approaches have been, for instance, proposed for problem-solving in physics (Forbus and Gentner, 1983, Gust et al., 2006) and for challenging abstract reasoning problems (Clark et al., 2018, Lovett et al., 2007).

Neural network approaches, especially multilayer perceptrons, were proposed by cognitive scientists (Rumelhart et al., 1986) as an approach to generalisation learning that overcomes the brittleness of symbolic approaches, see Figure 2c. Despite strong arguments from researchers in symbolic AI (Fodor and Pylyshyn, 1988), neural networks and other statistical approaches became the most dominant branch of machine learning due to their superior performance in increasingly large datasets. However, some core arguments of the critiques from Fodor and Pylyshyn (1988) concerning the relation of statistical machine learning to human cognition remain. First, data is separated from a semantic model. While humans who have learned a concept robustly recognize out-of-distribution inputs, machine learning has only addressed this problem more recently (Yang et al., 2024a). Second, in many domains, even if knowledge is primarily implicit, humans can verbally describe at least part of what constitutes a concept. This observation has been recently reflected in research on explainable AI where novel approaches to explain black-box models have been proposed focusing on explanations based on concepts and relations (Achtibat et al., 2023, Dalal et al., 2024, Finzel et al., 2024). Third, human explanations typically are based on the causal history of an event and a causal explanation for the generalisation itself (Miller, 2019). Substantial empirical evidence has been given, demonstrating that humans do not focus on the superficial level of event covariations but reason and learn based on deeper causal representations (Lombrozo, 2007, Waldmann et al., 2006). In machine learning, discovering high-level causal variables from low-level observations remains a significant challenge (Schölkopf et al., 2021).

Combining implicit, neural learning and explicit, symbolic approaches is addressed in research in neuro-symbolic AI (Demir and Ngonga Ngomo, 2023, Hitzler et al., 2023, Marra et al., 2024). Here, different architectures have been proposed, such as transforming symbolic structures into neural network models for more efficient learning (graph neural networks, Lamb et al., 2020; deep Q learning over embeddings, Demir and Ngonga Ngomo, 2023) or using concepts learned with deep neural networks as input for rule learning systems (Manhaeve et al., 2021). Combining strong generalisation and explainability would make neuro-symbolic systems adequate for effective human-AI teaming in many tasks, including skill acquisition and problemsolving. However, today's neuro-symbolic methods sometimes report lower accuracy and scalability, limiting their practical significance and requiring further research.

3 Notions of Generalisation

There are three different notions of generalisation in the broader context of cognitive science and AI research. First, generalisation refers to a *process* by which general concepts and rules are constructed from example data. Second, generalisation refers to the *product* of such a process, meaning the general concepts and rules themselves in their diverse representations. Third, generalisation refers to an *operation* of applying this product to new data. Next, we elaborate on these three notions and their categories, drawing on research in cognitive science, symbolic AI, and machine learning.

3.1 Generalisation as a process

In cognitive science, generalisation is related to the process of abstraction. Colunga and Smith (2003) propose that conceptual categories, i.e., products of abstraction processes, emerge from associative learning and generalisation by similarity. Campell and Piaget (2014) distinguish between abstraction through associative learning and abstraction through the transformation of schemas from the lower to the higher stages of cognitive development. More broadly, French (1995) distinguishes three types of conceptual changes: (1) generalisation of concrete instances into an abstract schema, which we call *abstraction*, (2) generalisation through the application or extension of the schema to various situations, which we call *extension*, and (3) generalisation involving the transformation/adaptation of the schema to fit a new context, which we call analoqy. These three subtypes of generalisation processes are also recognizable in symbolic AI and machine learning. Abstraction (type 1) relates to classic forms of constructing a model from example data, such as concept learning or rule mining in symbolic AI, as well as clustering/classification (for discrete classes) and regression/dimension reduction (for functional relationships) in machine learning (Biehl, 2023). Model extension (type 2) relates to methods that (slightly) adapt machine learning models to make them applicable to new data similar to the original training data. Examples are online learning, multi-task learning, few-shot learning, and continual learning (Lu et al., 2018, Verwimp et al., 2024, Zhang and Yang, 2021). Analogy (type 3) refers to the model transfer to a new domain or task. Techniques for this constitute transfer learning (Zhuang et al., 2020) and reasoning by analogy in symbolic AI. Importantly, generalisation does not always start from example data, resulting in a (general) model. Instead, we may start from a pre-existing model and abstract, extend, or transfer it further by analogy, thereby generalising it beyond its original scope. The result of this generalisation process (of either type 1, 2, or 3) is a product, which we discuss next.

3.2 Generalisation as a product

Products of generalisation formalise an abstraction that goes beyond specific instances and can thus be applied to new cases (for a cognitive science perspective, refer to Reilly et al., 2003). For example, the concept of a 'cup' can be generalised from experiences with exemplars of cups. Typical products are categories, concepts, rules, and models. Generalisations of *categories and concepts* may be represented in different ways, for instance, as a symbolic definition via a list of attributes, via bounds in attributes (refer to Jackendoff, 1985, for the cognitive science perspective and Bertsimas and Dunn, 2017, for decision trees in machine learning perspective), as a prototype (refer to Mervis et al., 1981, for a cognitive science perspective and to Bien and Tibshirani, 2011, for machine learning perspective), or as a set of exemplars of the category (as in k-nearest neighbour classification in machine learning Peterson, 2009; for cognitive science see Nosofsky, 2011). In probabilistic models, categories or concepts are represented as a probability distribution from which examples of this category can be drawn, which is also the notion implicitly used by generative AI models (Bengesi et al., 2024). Beyond categories or concepts, products may also be rules or relations. For example, from observed instances of dogs, we may generalise the rule that bigger dogs also tend to have more weight. Analogous to concepts, such rules or relations may have parametric or non-parametric representations depending on the method to construct them. In summary, the products of generalisation are *categories*, *concepts*, *rules*, *or models*, represented in either *parametric or non-parametric* form.

3.3 Generalisation as an operator

The whole purpose of generalisation (as a *process*) that produces a generalisation (as a product) is to apply the generalisation (as an operator) to new data. The ability of a model to generate accurate predictions on new data is at the core of generalisation in machine learning (Adams et al., 2022, Shaley-Shwartz and Ben-David, 2014). Different proposals have been put forward on how to formalise the generalisation operator in mathematical terms, as this is a prerequisite to developing algorithms for generalisation (see Section 4) and to evaluate the generalisation capability of digital artefacts (see Section 5). Three mathematical theories of generalisation have emerged in the literature: (1) The Probably Approximately Correct (PAC) framework analyses whether a model (i.e., a product) derived from a machine learning algorithm (i.e., a generalisation process) from a random sample of data can be expected to achieve a low prediction error on new data from the same distribution in most cases (Shaley-Shwartz and Ben-David, 2014). (2) The statistical physics of learning aims to understand the typical properties of learning algorithms (i.e., processes) with many adaptive parameters (Decelle, 2022, Engel and Broeck, 2001, Seung et al., 1992). (3) Vapnik–Chervonenkis (VC) dimension theory focuses on the storage capacity of model classes and their subsequent ability to make accurate predictions on new data (Vapnik and Chervonenkis, 2015). One of the key insights in this context is that generalisation begins where memorisation ends, paraphrasing Cover (1965). In other words, only if the capacity of a system to memorise is limited or restricted can it generalise to novel data.

Importantly, all three theories have been applied mainly to machine learning algorithms of the abstraction kind (subtype 1 above). For model extension or analogy, the mathematical theory is less well-established. For example, for out-of-distribution generalisation, which refers to the application of a model on data drawn from another distribution than the training data (Liu et al., 2021), Straat et al. (2022) provide statistical physics analysis for drift and Tripuraneni et al. (2020) analyse the generalisation risk in transfer learning. Moreover, almost all formalisations resort to probabilistic guarantees rather than uniform guarantees for arbitrary input. Alternative notions of generalisation have been proposed in language learning by the idea of learning in the limit (Gold, 1967). Although learning in the limit can capture the generalisability in compositional objects, such as language, algorithmic solutions are limited by the undecidability or high complexity of their inference (Zeugmann, 2003).

4 Machine Methods for Generalisation

Humans' ability to generalise from past experiences to previously unconceived scenarios constitutes a necessary principle for navigating daily life. As elaborated in Section 2, human generalisation relates to the abstraction of rules or patterns of characteristics from previous experiences with similar stimuli (Gluck et al., 2020). Humans

Category	Attributes
Training signal	supervised, unsupervised, reinforcement, semi-supervised, self-supervised
Data type	tabular data, data structures (e.g. text, graph), prior knowledge
Model representation	parametric/non-parametric, symbolic/sub-symbolic, black-/white-/grey-box
Training objective	Bayesian inference, maximum likelihood principle, rule learning, mean squared error minimization

Table 1: Common categories to structure AI methods algorithmically centred. These categories are not uniquely related to their type of generalisation.

display astonishing capabilities of systematic generalisation across representations, contexts, and tasks based on only a few observations. Which computational methods can achieve such generalisation capabilities? *Mathematical models of human generalisation* have been based on mechanisms induced by similarities in psychological concept space (Shepard, 1987) or statistical models such as Bayesian inference (Tenenbaum and Griffiths, 2001), among others (see also Section 2). Yet, although recent work has demonstrated remarkable results of specially trained artificial neural networks in solving compositional tasks (Lake and Baroni, 2023), the underlying mechanisms of human generalisation are not understood sufficiently to mimic them in artificial systems.

Generalisation methods constitute fundamental principles of formal qualitative and quantitative processes to build insights from observations (Firestone, 1993). Although generalisation is at the heart of AI technologies, it is common practice to structure AI methods according to algorithmic aspects rather than their generalisation ability. Common algorithmic categories are enumerated in Table 1. These algorithmic choices impact the generalisation behaviour. For instance, symbolic methods often implement compositionality. Yet, there is no simple mapping from these algorithmic categories to the form of generalisation that an AI model can achieve. Therefore, in the following, we discuss AI methods according to the interplay of observational data and models, as this correlates to their form of generalisation and paves the way to evaluate them (section 5). Based on this interplay of observational data (i.e., single instances) and models (i.e., principles that apply to a whole population), three categories of methods can be distinguished: (1) The transfer of individual observations to a population is the basis for statistical generalisation methods. (2) The search for observational evidence of an explicit model or theory is done in analytical or knowledge-informed methods. (3) Generalisation methods focusing on individual instances as both generalisation sources and targets include *instance-based methods* such as case-based reasoning or nearest neighbour inference.

4.1 Statistical generalisation methods in AI

Many modern ML methods, including deep learning, aim for statistical generalisation: observational data (i.e., training patterns) serve as input to an inference mechanism that extracts a model for the whole population (i.e., the entire underlying distribution). Generalisation refers to the property that the inferred patterns can be successfully applied to new data (cf. Section 3.3). Commonly, algorithmic methods are

11

expressed as optimisation methods of a model loss function, such as the model prediction error. As the loss cannot be evaluated on the whole population, it is typically approximated by the empirical loss on a given training set, referred to as *empiri*cal risk minimization (Vapnik, 1995). While the empirical error on an independent test set can evaluate the model generalisation ability (cf. Section 5), the empirical loss on the training set underestimates the actual model loss. Therefore, generalisation needs to be accounted for explicitly, which means that additional incentives are necessary to ensure patterns derived from specific instances transfer to the whole population. Popular strategies include regularization terms that favour models with better generalisation behaviour: specific instances are margin maximization, optimization of stability, or restriction to simple functions (Bousquet and Elisseeff, 2002, Schneider et al., 2009). Interestingly, heavily overparameterized deep learning models can lead to surprising generalisation capabilities due to intrinsic regularization, which is not yet fully understood (Grohs and Kutyniok, 2022). Empirical risk minimization has a fundamental limitation compared to human generalisation: generalisation can only be expected in areas covered by observations. That means generalisation to out-of-sample events, novel contexts, or distributional changes cannot be expected (Ye et al., 2021).

Statistical generalisation methods are often based on model families with universal approximation capability to account for the lack of domain-specific knowledge. This allows modelling complex mechanisms such as those in computer vision or natural language processing (Chai et al., 2021, Otter et al., 2018). The product is typically a black box: since model parameters do not have a semantic meaning, the mere functional form does not provide insight into the model's generalisation behaviour. Recently developed post-hoc explanation methods allow a closer inspection of the underlying rationale and its impact on the model generalisation behaviour (Dalal et al., 2024, Molnar, 2020).

Another surprising observation has become popular in recent years: many vital settings, including generative models or LLMs, do not allow a simple analytic loss function that fully describes human intentions. Thus, surrogate losses such as next token prediction or masked prediction tasks are used as a proxy. Together with a massive amount of training data and tasks used for instruction tuning, impressive generalisability arises (Brown et al., 2020a, Zhang et al., 2023). The emerging generalisation abilities are only partially understood and do not necessarily align with human expectation, necessitating downstream evaluation (Section 5) (Bommasani et al., 2022).

4.2 Analytical and knowledge-informed generalisation methods in AI

Analytical generalisation methods aim for empirical evidence of a theory. The resulting product is an explicit semantically meaningful representation inferred from and confirmed by data. Depending on its specific representation, different methods exist, such as mechanistic models (Baker et al., 2018), causal inference (Yao et al., 2021), Bayesian networks (Puga et al., 2015), knowledge graphs (Hogan et al., 2022, Ji et al., 2022), functional programming (Kitzelmann and Schmid, 2006), and inductive logic programming (Cropper et al., 2022). As the inherent model semantics is directly accessible to humans, humans can inspect how these models generalise to previously not

Pros	Cons			
Statistical: generalisation from observations to a population				
universal approximation, surprising generalisation of deep models	black boxes, generalisation only within observed distribution			
Knowledge-informed: confirm/adapt hypothesis based on observations				
meaningful models, identifiable parameters, generalisation in the limit, compositionality	restriction to simple scenarios, optimization/structure identification usually			
Case-to-case: translation from previous observations to a new observation				
flexible to change/distributional shift	rely on suitable representation			

Table 2: Characterization of AI generalisation methods.

encountered scenarios. Since the parameters of these analytic models have a semantic meaning, they require semantic grounding, which is challenging to realise with sub-symbolic, low-level sensor data. Such limitations can be partially overcome by neuro-symbolic integration: Deep-Problog, as an example, combines deep neural networks that transfer sub-symbolic signals to semantic concepts that can be used in symbolic inference (Manhaeve et al., 2021).

Choosing the optimal model structure is challenging, facing numerically complex problems and limitations caused by the non-identifiability of structural components (Koller and Friedman, 2009). Hence, many methods are restricted to simple schemes, such as description logic, rather than universal approximators. Learning methods are diverse as they mirror the specific representation, ranging from semantic clustering over probabilistic rule mining to subsumption and analogies. Besides a valid generalisation, noise robustness and inference efficiency constitute significant challenges, which render hybrid approaches such as embedding mechanisms appealing (Cao et al., 2024).

Systematic compositionality refers to the ability to generalise and produce novel combinations from known components. It has been fundamental in the design of traditional logic-based systems and, more generally, analytics methods. Statistical methods, particularly neural networks, have struggled with compositional generalisation (Fodor and Pylyshyn, 1988), as they do not inherently possess the structure needed for compositional reasoning. In the last few years, significant progress has been made in enhancing compositional generalisation in deep learning, typically by adding analytical components that mirror the compositional structure of the domain. Examples include compositional processing of structured objects such as recursive models or graph neural networks (Hammer, 2000, Wu et al., 2021), object-centric representation learning (Locatello et al., 2020), or meta-learning for compositional generalisation (Lake and Baroni, 2023). While these efforts provide a pathway for neural networks to generalise systematically, most results are empirical, making achieving predictable and systematic generalisation challenging (Wiedemer et al., 2024). There remains a significant gap between the systematic generalisation capabilities of analytical models and the representation learning techniques of deep models, with new approaches, specifically neuro-symbolic AI, promising as a viable bridge (Sehgal et al., 2024).

4.3 Instance-based translation in AI

Lazy-learning methods refer to non-parametric techniques such as nearest-neighbours methods, case-based reasoning, or local regression (Aha, 2013). They rely on local inference, computed when needed based on similar cases encountered previously. Nearest neighbour methods are among the oldest and most popular ML methods, displaying immense flexibility when combined with complex representations (Khandelwal et al., 2020). As they rely on local inference, human inspection of single decisions—albeit not the entire model—is usually possible.

Because of their local representation and controlled inference, instance-based models have shown great promise for incremental learning in the context of possible distributional shift or drift (Losing et al., 2016). One reason is the explicit memory in nearest-neighbours models, which comes with a natural forget mechanism. However, since they rely on the notion of similarity or neighbourhood, a suitable choice of representation and similarity metrics is crucial to support generalisation (Kulis, 2013); more generally, the representation directly influences the ability of models to capture and generalise cases effectively and evolve patterns across diverse datasets and tasks. Interestingly, there has been research on representations to support specific generalisations, including generalisations across tasks or domains (He et al., 2022).

Context has a unique role as generalisation requires adapting knowledge learnt in one setting to fit a novel, unseen one. Humans can make such generalisations, addressing two main aspects: acquiring and formally representing context knowledge and assessing the similarity of two contextual representations (e.g., domain- and taskrelated knowledge) (Shepard, 1987). Different ML techniques can be applied to mimic this process, including transfer learning and, in generative approaches, techniques such as prompting and retrieval augmented generation (Gao et al., 2024). Indeed, LLMs have demonstrated remarkable capabilities as few-shot learners provided sufficient scaling (Brown et al., 2020c); this is even surpassed by their capabilities for in-context learning (Dong et al., 2024). These techniques aim to adapt a learnt model to contextual information, albeit implicitly. A suitable explicit representation of contextual knowledge, e.g., through neuro-symbolic AI, is the subject of ongoing research.

5 Evaluation of Generalisation

From a statistical learning perspective, evaluating the generalisation of supervised approaches estimates how well they perform on unseen data samples. When testing generalisation as applicability to new data (Section 3.3), the training and test data samples are assumed to be independently generated by the same data distribution. This formalization of train-test generalisation is theoretically grounded and thus remains relevant when assessing and certifying systems. However, as tasks become more complex and potentially increase system opaqueness, special care must be taken to ensure that respective assumptions remain in practice. In particular, we need to consider the data distribution, how we can draw *representative* samples for the train and test set, and ensure that they are independent. As an illustration, Li and Flanigan (2024) show that ChatGPT performs surprisingly well on all benchmarks published before its release and much worse on all benchmarks published later. In this case,

the independence assumption is not fulfilled as test set information has been leaked into the model, such that the estimation of the generalisation performance on benchmarks published before the release of ChatGPT is inaccurate. It is often unclear which data pre-trained LLMs have been trained on, so it is challenging to define test data samples unseen during training. Consequently, the estimation of the generalisation performance might be inaccurate, so the models might fail surprisingly on simple tasks (Shin and Kaneko, 2024). Further investigations are necessary to understand the theoretical limits of such models by deriving provable guarantees and properties such as generalisation bounds and provable robustness guarantees so that a model assessment beyond empirical evaluations is possible. In the following, we discuss several areas related to evaluation of generalisation and its role in recent AI applications.

5.1 Measuring distributional shifts

Assessing whether empirically gathered data stem from the same distribution is nontrivial. To measure the extent to which existing datasets are OOD, statistical distance measures such as the Kullback-Leibler divergence or Wasserstein distance can quantify the divergence between the feature distributions of the training and test sets. Generative models offer an explicit likelihood estimation p(x) that can be used to assess how typical a given instance is to the training distribution. Because discriminative models do not offer this possibility, proxy techniques include calculating cosine similarity between embedding vectors and using nearest-neighbour distances in a suitably transformed feature space. In the case of LLMs, a common approach is to measure perplexity as a proxy for familiarity. When the model's internal representations cannot be directly accessed, probing its sensitivity to changes is informative. For example, the layers of non-linear abstractions formed in most modern (deep) machine learning models allow for gauging relations through intermittent embeddings.

Data samples with distributional shifts can also be deliberately identified or generated to understand the model's robustness. Such adversarial techniques alter key data features such as syntax, semantics, or context while preserving the underlying task and the original label. In contrast, counterfactual techniques create data samples that alter the target prediction with minimal input changes.

5.2 Determining under- and over-generalisation

The performance of models is known to degrade for a wide range of potential natural changes, such as frequent camera and environment perturbations in computer vision (Hendrycks and Dietterich, 2019), because the model is not invariant to these changes. Such examples reveal *under-generalisation* because they introduce an imperceptible shift in input that results in a considerable modification within a model. For foundation models, even the prompt choice can substantially affect performance (Gonen et al., 2023). In contrast, models typically overconfidently make false predictions for completely unknown concepts (Boult et al., 2019) precisely because critical differences are ignored in prediction. One such *over-generalisation* phenomenon is hallucination in LLMs. This term originally referred to models deviating from the source, such as the input document in summarization. In LLMs, the source covers pre-training data in a

more general way (Ji et al., 2023a), extending the definition of hallucination to include factually incorrect statements. Other examples of inappropriate over-generalisation are biased predictions, e.g., when a model predicts a property of an individual from the statistical properties of a demographic group to which they belong (Hovy and Spruit, 2016), and logical fallacies (Sourati et al., 2023).

Characterising the model's under- and over-generalisation requires choosing an appropriate metric, defining its point of use, and setting a mechanism to interpret the metric's value regarding its ability to generalise beyond the particular test examples. The procedure is also susceptible to two caveats. First, the choice between discriminative and generative model, in the mathematical sense of modelling p(y|x) and p(y|x)p(x), determines what representational basis is used to infer similarity (Mundt et al., 2023). Second, deep models are prone to learn various decision shortcuts (Lapuschkin et al., 2019) and to fall victim to simplicity bias in their prediction by ignoring meaningful features altogether (Shah et al., 2020) (e.g., a visual classification model that learns to distinguish oranges from avocados may learn to only rely on colour features). To guard against these caveats, evaluating across different levels of abstraction (from surface forms, through semantic similarity, to higher-level conceptual analogies) and explicitly considering application context and limits is critical.

In the era of foundation models trained on large data sets, the appropriateness of evaluations on test sets is questionable. Foundation models show impressive performance on many tasks without being specifically trained to perform them (Brown et al., 2020b); that is, trained models on task A perform surprisingly well on task B. This is a positive shift from the fine-tuning paradigm, in which models had to be trained on each task, often learning spurious correlations. However, measuring the extent to which models generalise is still challenging. Modern models are frequently updated, partially based on user interactions through reinforcement learning, increasing their exposure to datasets and hindering reproducibility. The lack of transparency is also induced by the fact that many large models are proprietary and not openly published.

5.3 Distinguishing memorisation, generalisation, and abstraction

In AI, *memorisation* refers to learning details from the training data, including noise and facts, that do not generalise to new data. Memorisation is often seen as a challenge for the evaluation of foundational models because models may have been trained on a data sample that may also be used for testing, invalidating the findings (so-called data contamination, Dodge et al., 2021). A more fundamental question is: in which cases should the models generalise, and when should they memorise? And how can this be evaluated convincingly? Factual knowledge should often be memorised; for instance, Paris is the capital of France, and mosquitoes fly. When learning from experience, generalisation is crucial, e.g., to recognise a new manifestation of a maze object (Hsu et al., 2024). In practice, the expectation of whether the models should generalise or memorise is a priori. Tasks that involve recall from memory, such as factual question answering and legal reasoning over precedents, require models to have provably correct reasoning over explicit background information. Generalisation task setups include cross-domain validation, robustness testing, adversarial testing, and counterfactual

reasoning. A special category of generalisation tasks evaluates the ability of models to provide a useful *abstraction* over limited information. Abstraction tasks focus on visual reasoning (Małkiński and Mańdziuk, 2023), common sense reasoning (Davis, 2023), analogies (Sourati et al., 2024), and concept induction (Nie et al., 2020).

5.4 Evaluating human-AI teaming

Effective human-machine collaboration can be based on a unifying theoretical framework for both forms of intelligence or focus on their complementary strengths and weaknesses. The first approach, reflected in cognitive architecture research (cf. Gonzalez et al., 2023), aims to replicate human cognition at a computational level to facilitate collaboration. The second approach designs AI systems to maximise accuracy and minimise human effort, as seen in reinforcement learning from human feedback (Christiano et al., 2017). A third approach, inspired by the concept of "ultra-strong machine learning" (Michie, 1988, Muggleton et al., 2018), proposes integrating both perspectives to enhance collaboration. Michie (1988) emphasised predictive performance and the comprehensibility of learnt knowledge, advocating for AI to support human learning by making its knowledge interpretable and teachable. The sophistication of the necessary alignment will depend on the complexity of the underlying task tackled by the human-AI team, such as automotive driver assistance or decision-making in medicine. This implicit hierarchy of complexity suggests we can develop challenges that appropriately stretch the state-of-the-art without overreaching to unrealistic scenarios. Such challenges include focusing on interactive representation alignment, contextual inference, theory of mind, real-world grounding, and communication levels.

A nuanced approach that considers the interplay between human and AI capabilities (Akata et al., 2020) is paramount to evaluating the efficacy of human-AI teams. This requires a meticulous evaluation of the objective task-related outcomes, subjective process-related experiences, and the long-term ramifications of the collaboration. Furthermore, the success metrics for human-AI teaming are contingent upon each party's relative contributions and responsibilities. For instance, if the cooperation is characterised by humans augmenting the AI's capabilities (e.g., manual data labelling, reinforcement learning), the success of the collaboration could be objectively quantified in terms of the model's post-interaction performance on suitable benchmarks. In contrast, subjective evaluation metrics may be more suitable if a collaborative task is characterised by an AI assisting humans (e.g., question answering in a conversational interface). These metrics encompass but are not limited to, trust in the veracity of provided answers, the enjoyment of interaction, or a user's perceived self-efficacy (Li et al., 2024, Sharma et al., 2023, Yang et al., 2024b). In balanced collaborations, where both AI and humans contribute equally, a blend of objective measures (errors made, task completion time) and subjective measures (user satisfaction) is required (Braun et al., 2023). Notably, while metrics for human-AI teaming are being developed, there is little research into the possibility of evaluating the generalisation of such teams.

Duran antar	Method			
Property	S	С	А	Evaluation
accuracy	+	_	_	train-test splits
robustness to shifts/OOD	-	+	-	novel distributions
robustness to over-generalisation	-	+	+	hallucination detection
explainability	-	$+^*$	+	human studies
efficiency/scale	+	+	_	large/complex datasets
compositionality	—	_	+	human studies
common sense	-	—	-	implicit task
learning from a few samples	—	+	+	infrequent samples
analogical transfer	+	$+^{*}$	-	analogy tasks, new domains
complexity	+	+	-	complex datasets

Table 3: Desired properties of generalisation enabled by statistical (S), case-to-case (C), and analytical (A) AI methods. Asterisk means partially achieved.

6 Emerging Directions

The prior sections highlight the challenges in aligning human and machine intelligence, highlighting AI's potential to augment human generalisation capabilities. A summary of the different properties, methods, and evaluation practices for generalisation in humans and AI is shown in Table 3. The table shows the complementarity of statistical, case-to-case, and analytical generalisation approaches to satisfying desirable properties such as accuracy, shift robustness, and compositionality. The evaluation column indicates that developing adequate evaluation procedures remains challenging, especially for explainability, compositionality, and learning from a few samples. We discuss research directions toward novel theories, methods, and evaluation practices.

Generalisation theory in the era of foundation models

Recent approaches of zero-shot and in-context learning in LLMs try to generalise to tasks that may be entirely disconnected from the ones the LLMs were trained for, without any explicit similarity having been established (Bubeck et al., 2023, Kojima et al., 2022). In other words, the model builders assume that LLMs have implicitly generalised (process, Section 3.1) to generalisations (product, Section 3.2) that permit generalisation (application, Section 3.3) to entirely new tasks and domains. Based on the prior work outlined in Section 3, such an assumption appears unsubstantiated, motivating further research to make generalisations in that form realistic. First, new processes and products of generalisation are required to provide guarantees or reasons to believe that (zero-shot) application to new tasks and domains is viable. Explicitly encoding invariances/equivariances in models or cognitively-inspired representations, such as prototypes, may be helpful. Second, a new *theory* is required to understand the conditions under which few- or zero-shot applications to new tasks and domains can be expected. This theory will likely need to join established notions of ML theory (be it statistical machine learning theory, statistical physics, or VC dimension) with notions of invariances or analogies between domains that must be mathematically precise.

Generalisable neuro-symbolic methods

Neuro-symbolic AI carries great promises, as it can combine aspects of statistical methods and analytic models, thus leading to a possible combination of statistically robust and data-driven models for complex sub-symbolic parts and explicit compositional modelling for overarching schemes. Yet many challenges remain. First, defining provable generalisation properties, including worst-case bounds, is essential. How can we derive formal properties for (neuro-symbolic) AI generalisation based only on compositionality rather than (weaker) statistical guarantees? Can we identify reasonable and relevant situations with formal guarantees for continual learning and learning under drift? Which surrogate cost functions are provably compatible with the underlying learning objective? Second, how to handle *context* remains a question. What measures the distance between contexts? What is a reasonable projection operator for applying a generalisation from one context to another? How do we know that a context is too novel to support generalisation? When do we overgeneralise? Third, neuro-symbolic methods should *represent* information efficiently and facilitate *compositionality*. How can we choose a suitable representation and similarity measure(s) to enable generalisation? How do we combine multiple representations for generalisation? How do we compose two generalisations into a new one? Can we exploit compositional embeddings for compositional generalisation?

Evaluation of generalisation in foundation models

Several directions have emerged in response to concerns about data contamination, spurious correlations, and overfitting state-of-the-art models. Generalization benchmarks for abstract visual reasoning (Chollet, 2019, Jiang et al., 2024) and analogy (Bitton et al., 2023, Sourati et al., 2024) are gaining popularity. Such test sets can be created regularly and scaled more easily using crowd-sourcing platforms. However, crowd-sourcing can introduce cognitive and sociopolitical biases by annotators (Draws et al., 2021), a poorly understood issue. Evaluation servers and public leaderboards that apply safety measures, such as hidden test labels, can prevent overfitting and memorisation but lack standardisation and are expensive and labour-intensive to set up and maintain. Another form of community benchmarking is early materials with an informal evaluation of models' success and failure cases (cf. Arkoudas (2023)). Yet, it remains unclear how to facilitate the inclusion of such examples in benchmarks to ensure reproducibility and prevent model memorisation. Ultimately, the path forward may be to move away from static test sets and toward simulation environments and synthetic data generators (Duan et al., 2022). However, data generators and simulated environments are challenging to develop and are often too artificial, restricting their resemblance to real-world situations (sim-to-real gap). Addressing reproducibility concerns, researchers have proposed concepts such as model cards (Mitchell et al., 2019) or data cards (Pushkarna et al., 2022) to report critical information for reproducing experiments, such as training parameters and evaluation metrics. Orthogonal efforts introduce reproducibility checklists based on a broad consensus (Kapoor et al., 2024); however, their coverage of generalisability remains limited.

Generalisation mechanisms in human-AI teams

Human-AI teaming requires well-understood collaboration and explanation workflows (Akata et al., 2020). Explanations bridge the gap between human reasoning and AI's internal workings. A critical challenge is reconciling fundamentally different reasoning paradigms, such as human causal models versus AI's deep learning associations. Can these approaches be unified into a common explanatory language? Efforts like concept-based explanations (Widmer et al., 2023) and those considering concepts and relationships (Finzel et al., 2024) suggest promising avenues for achieving intertranslatability, a potential cornerstone for truly explainable AI. Furthermore, fostering successful human-AI teams necessitates AI's ability to learn and potentially retain feedback indefinitely. Robust feedback mechanisms are crucial for AI to understand effective communication and align with human cognition, fostering seamless collaboration. Future research should also prioritize investigating human generalisation and abstraction processes and contrast those with AI-based approaches. Interdisciplinary collaboration between computer and social scientists will be essential to integrate this understanding into AI design, enhancing explainability and mitigating biases in ML generalisation. Finally, while human-centred AI promises personalized experiences, navigating data privacy regulations and ensuring transparency, accountability, and user choice are paramount legal challenges.

Acknowledgements. The manuscript resulted from the Dagstuhl seminar 24192: Generalization by People and Machines, held in May 2024.

References

- Reduan Achtibat, Maximilian Dreyer, Ilona Eisenbraun, Sebastian Bosse, Thomas Wiegand, Wojciech Samek, and Sebastian Lapuschkin. From attribution maps to human-understandable explanations through concept relevance propagation. *Nature Machine Intelligence*, 5(9):1006–1019, 2023.
- Reuben Adams, John Shawe-Taylor, and Benjamin Guedj. Controlling multiple errors simultaneously with a pac-bayes bound. arXiv preprint arXiv:2202.05560, 2022.
- D.W. Aha. *Lazy Learning*. Springer Netherlands, 2013. ISBN 9789401720533. URL https://books.google.de/books?id=b1CqCAAAQBAJ.
- Zeynep Akata, Dan Balliet, Maarten De Rijke, Frank Dignum, Virginia Dignum, Guszti Eiben, Antske Fokkens, Davide Grossi, Koen Hindriks, Holger Hoos, et al. A research agenda for hybrid intelligence: augmenting human intellect with collaborative, adaptive, responsible, and explainable artificial intelligence. *Computer*, 53 (8):18–28, 2020.
- Konstantine Arkoudas. Gpt-4 can't reason. arXiv preprint arXiv:2308.03762, 2023.
- Ruth E Baker, Jose-Maria Peña, Jayaratnam Jayamohan, and Antoine Jérusalem. Mechanistic models versus machine learning, a fight worth fighting for the biological community? *Biol Lett*, 14(5), May 2018.

- Staphord Bengesi, Hoda El-Sayed, Md Kamruzzaman Sarker, Yao Houkpati, John Irungu, and Timothy Oladunni. Advancements in generative ai: A comprehensive review of gans, gpt, autoencoders, diffusion model, and transformers. *IEEE Access*, 2024.
- Dimitris Bertsimas and Jack Dunn. Optimal classification trees. *Machine Learning*, 106:1039–1082, 2017.
- Tarek R Besold, Artur d'Avila Garcez, Sebastian Bader, Howard Bowman, Pedro Domingos, Pascal Hitzler, Kai-Uwe Kühnberger, Luis C Lamb, Priscila Machado Vieira Lima, Leo de Penning, et al. Neural-symbolic learning and reasoning: A survey and interpretation 1. In *Neuro-Symbolic Artificial Intelligence: The State of the Art*, pages 1–51. IOS press, Amsterdam, 2021.
- Michael Biehl. The Shallow and the Deep: A biased introduction to neural networks and old school machine learning. University of Groningen Press, 2023. URL https: //doi.org/10.21827/648c59c1a467e.
- Jacob Bien and Robert Tibshirani. Prototype selection for interpretable classification. The Annals of Applied Statistics, 5(4):2403–2424, 2011.
- Yonatan Bitton, Ron Yosef, Eliyahu Strugo, Dafna Shahaf, Roy Schwartz, and Gabriel Stanovsky. Vasr: Visual analogies of situation recognition. In *Proceedings of the* AAAI Conference on Artificial Intelligence, volume 37, pages 241–249, 2023.
- Rishi Bommasani, Drew A. Hudson, Ehsan Adeli, Russ Altman, Simran Arora, Sydney von Arx, Michael S. Bernstein, Jeannette Bohg, Antoine Bosselut, Emma Brunskill, Erik Brynjolfsson, Shyamal Buch, Dallas Card, Rodrigo Castellon, Niladri Chatterji, Annie Chen, Kathleen Creel, Jared Quincy Davis, Dora Demszky, Chris Donahue, Moussa Doumbouya, Esin Durmus, Stefano Ermon, John Etchemendy, Kawin Ethayarajh, Li Fei-Fei, Chelsea Finn, Trevor Gale, Lauren Gillespie, Karan Goel, Noah Goodman, Shelby Grossman, Neel Guha, Tatsunori Hashimoto, Peter Henderson, John Hewitt, Daniel E. Ho, Jenny Hong, Kyle Hsu, Jing Huang, Thomas Icard, Saahil Jain, Dan Jurafsky, Pratyusha Kalluri, Siddharth Karamcheti, Geoff Keeling, Fereshte Khani, Omar Khattab, Pang Wei Koh, Mark Krass, Ranjay Krishna, Rohith Kuditipudi, Ananya Kumar, Faisal Ladhak, Mina Lee, Tony Lee, Jure Leskovec, Isabelle Levent, Xiang Lisa Li, Xuechen Li, Tengyu Ma, Ali Malik, Christopher D. Manning, Suvir Mirchandani, Eric Mitchell, Zanele Munyikwa, Suraj Nair, Avanika Narayan, Deepak Narayanan, Ben Newman, Allen Nie, Juan Carlos Niebles, Hamed Nilforoshan, Julian Nyarko, Giray Ogut, Laurel Orr, Isabel Papadimitriou, Joon Sung Park, Chris Piech, Eva Portelance, Christopher Potts, Aditi Raghunathan, Rob Reich, Hongyu Ren, Frieda Rong, Yusuf Roohani, Camilo Ruiz, Jack Ryan, Christopher Ré, Dorsa Sadigh, Shiori Sagawa, Keshav Santhanam, Andy Shih, Krishnan Srinivasan, Alex Tamkin, Rohan Taori, Armin W. Thomas, Florian Tramèr, Rose E. Wang, William Wang, Bohan Wu, Jiajun Wu, Yuhuai Wu, Sang Michael Xie, Michihiro Yasunaga, Jiaxuan You, Matei Zaharia, Michael
 - 21

Zhang, Tianyi Zhang, Xikun Zhang, Yuhui Zhang, Lucia Zheng, Kaitlyn Zhou, and Percy Liang. On the opportunities and risks of foundation models, 2022. URL https://arxiv.org/abs/2108.07258.

- Terrance E. Boult, Steve Cruz, Akshay R. Dhamija, Manuel Gunther, James Henrydoss, and Walter J. Scheirer. Learning and the Unknown : Surveying Steps Toward Open World Recognition. AAAI Conference on Artificial Intelligence (AAAI), 2019.
- Olivier Bousquet and André Elisseeff. Stability and generalization. J. Mach. Learn. Res., 2:499–526, 2002. URL http://dblp.uni-trier.de/db/journals/jmlr/jmlr2.html# BousquetE02.
- Marvin Braun, Maike Greve, and Ulrich Gnewuch. The new dream team? a review of human-ai collaboration research from a human teamwork perspective. 2023.
- Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel Ziegler, Jeffrey Wu, Clemens Winter, Chris Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. Language models are few-shot learners. In H. Larochelle, M. Ranzato, R. Hadsell, M.F. Balcan, and H. Lin, editors, Advances in Neural Information Processing Systems, volume 33, pages 1877–1901. Curran Associates, Inc., 2020a. URL https://proceedings.neurips.cc/paper_files/paper/2020/ file/1457c0d6bfcb4967418bfb8ac142f64a-Paper.pdf.
- Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. Language models are few-shot learners. Advances in neural information processing systems, 33:1877–1901, 2020b.
- Tom B. Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel M. Ziegler, Jeffrey Wu, Clemens Winter, Christopher Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. Language models are few-shot learners. In *Proceedings of the* 34th International Conference on Neural Information Processing Systems, NIPS '20, Red Hook, NY, USA, 2020c. Curran Associates Inc. ISBN 9781713829546.
- Jerome Bruner, Jacqueline J. Goodnow, and George A. Austin. A Study of Thinking. Wiley, New York, 1956.
- Sébastien Bubeck, Varun Chandrasekaran, Ronen Eldan, Johannes Gehrke, Eric Horvitz, Ece Kamar, Peter Lee, Yin Tat Lee, Yuanzhi Li, Scott Lundberg, et al.
 - 22

Sparks of artificial general intelligence: Early experiments with gpt-4. arXiv preprint arXiv:2303.12712, 2023.

- Robert L Campell and Jean Piaget. *Studies in reflecting abstraction*. Psychology Press, London, 2014.
- Jiahang Cao, Jinyuan Fang, Zaiqiao Meng, and Shangsong Liang. Knowledge graph embedding: A survey from the perspective of representation spaces. ACM Comput. Surv., 56(6), mar 2024. ISSN 0360-0300. doi: 10.1145/3643806. URL https://doi. org/10.1145/3643806.
- Junyi Chai, Hao Zeng, Anming Li, and Eric W.T. Ngai. Deep learning in computer vision: A critical review of emerging techniques and application scenarios. *Machine Learning with Applications*, 6:100134, 2021. ISSN 2666-8270. doi: https://doi.org/ 10.1016/j.mlwa.2021.100134. URL https://www.sciencedirect.com/science/article/ pii/S2666827021000670.
- François Chollet. On the measure of intelligence. arXiv preprint arXiv:1911.01547, 2019.
- Paul F Christiano, Jan Leike, Tom Brown, Miljan Martic, Shane Legg, and Dario Amodei. Deep reinforcement learning from human preferences. Advances in neural information processing systems, 30, 2017.
- Peter Clark, Isaac Cowhey, Oren Etzioni, Tushar Khot, Ashish Sabharwal, Carissa Schoenick, and Oyvind Tafjord. Think you have solved question answering? try arc, the ai2 reasoning challenge. arXiv preprint arXiv:1803.05457, 2018.
- Eliana Colunga and Linda B Smith. The emergence of abstract ideas: Evidence from networks and babies. *Philosophical Transactions of the Royal Society of London.* Series B: Biological Sciences, 358(1435):1205–1214, 2003.
- Thomas Cover and Peter Hart. Nearest neighbor pattern classification. *IEEE Transactions on information theory*, 13(1):21–27, 1967.
- Thomas M Cover. Geometrical and statistical properties of systems of linear inequalities with applications in pattern recognition. *IEEE transactions on electronic computers*, (3):326–334, 1965.
- Andrew Cropper, Sebastijan Dumančić, Richard Evans, and Stephen H. Muggleton. Inductive logic programming at 30. Machine Learning, 111(1):147–172, Jan 2022. ISSN 1573-0565. doi: 10.1007/s10994-021-06089-1. URL https://doi.org/10.1007/ s10994-021-06089-1.
- Abhilekha Dalal, Rushrukh Rayan, Adrita Barua, Eugene Y. Vasserman, Md. Kamruzzaman Sarker, and Pascal Hitzler. On the value of labeled data and symbolic methods for hidden neuron activation analysis. In Tarek R. Besold, Artur d'Avila

Garcez, Ernesto Jiménez-Ruiz, Roberto Confalonieri, Pranava Madhyastha, and Benedikt Wagner, editors, Neural-Symbolic Learning and Reasoning – 18th International Conference, NeSy 2024, Barcelona, Spain, September 9-12, 2024, Proceedings, Part II, volume 14980 of Lecture Notes in Computer Science, pages 109–131, Heidelberg, 2024. Springer. doi: 10.1007/978-3-031-71170-1_12.

- Ernest Davis. Benchmarks for automated commonsense reasoning: A survey. ACM Computing Surveys, 56(4):1–41, 2023.
- Luc De Raedt and Kristian Kersting. Probabilistic inductive logic programming. In *Probabilistic inductive logic programming: theory and applications*, pages 1–27. Springer, New York, 2008.
- Aurélien Decelle. An introduction to machine learning: a perspective from statistical physics. *Physica A: Statistical Mechanics and its Applications*, page 128154, 2022.
- Caglar Demir and Axel-Cyrille Ngonga Ngomo. Neuro-symbolic class expression learning. In Proceedings of the Thirty-Second International Joint Conference on Artificial Intelligence, IJCAI 2023, 19th-25th August 2023, Macao, SAR, China, pages 3624–3632. ijcai.org, 2023. doi: 10.24963/IJCAI.2023/403. URL https: //doi.org/10.24963/ijcai.2023/403.
- Jesse Dodge, Maarten Sap, Ana Marasović, William Agnew, Gabriel Ilharco, Dirk Groeneveld, Margaret Mitchell, and Matt Gardner. Documenting large webtext corpora: A case study on the colossal clean crawled corpus. In Marie-Francine Moens, Xuanjing Huang, Lucia Specia, and Scott Wen-tau Yih, editors, Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing, pages 1286–1305, Online and Punta Cana, Dominican Republic, November 2021. Association for Computational Linguistics. doi: 10.18653/v1/2021.emnlp-main.98. URL https://aclanthology.org/2021.emnlp-main.98.
- Qingxiu Dong, Lei Li, Damai Dai, Ce Zheng, Jingyuan Ma, Rui Li, Heming Xia, Jingjing Xu, Zhiyong Wu, Baobao Chang, Xu Sun, Lei Li, and Zhifang Sui. A survey on in-context learning. In Yaser Al-Onaizan, Mohit Bansal, and Yun-Nung Chen, editors, *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 1107–1128, Miami, Florida, USA, November 2024. Association for Computational Linguistics. URL https://aclanthology.org/2024. emnlp-main.64.
- Derek Doran, Sarah Schulz, and Tarek R. Besold. What does explainable AI really mean? A new conceptualization of perspectives. In Tarek R. Besold and Oliver Kutz, editors, Proceedings of the First International Workshop on Comprehensibility and Explanation in AI and ML 2017 co-located with 16th International Conference of the Italian Association for Artificial Intelligence (AI*IA 2017), Bari, Italy, November 16th and 17th, 2017, volume 2071 of CEUR Workshop Proceedings. CEUR-WS.org, 2017. URL https://ceur-ws.org/Vol-2071/CExAIIA_2017_paper_2.pdf.

- Tim Draws, Alisa Rieger, Oana Inel, Ujwal Gadiraju, and Nava Tintarev. A checklist to combat cognitive biases in crowdsourcing. In *Proceedings of the AAAI conference* on human computation and crowdsourcing, volume 9, pages 48–59, 2021.
- Jiafei Duan, Samson Yu, Hui Li Tan, Hongyuan Zhu, and Cheston Tan. A survey of embodied ai: From simulators to research tasks. *IEEE Transactions on Emerging Topics in Computational Intelligence*, 6(2):230–244, 2022.
- A. Engel and C. van den Broeck. The Statistical Mechanics of Learning. Cambridge University Press, Cambridge, UK, 2001.
- Brian Falkenhainer, Kenneth D Forbus, and Dedre Gentner. The structure-mapping engine: Algorithm and examples. *Artificial intelligence*, 41(1):1–63, 1989.
- Emilio Ferrara. Genai against humanity: Nefarious applications of generative artificial intelligence and large language models. *Journal of Computational Social Science*, pages 1–21, 2024.
- Bettina Finzel, Patrick Hilme, Johannes Rabold, and Ute Schmid. When a relation tells more than a concept: Exploring and evaluating classifier decisions with corex. arXiv preprint arXiv:2405.01661, 2024.
- William A. Firestone. Alternative arguments for generalizing from data as applied to qualitative research. *Educational Researcher*, 22(4):16–23, 1993. doi: 10.3102/ 0013189X022004016. URL https://doi.org/10.3102/0013189X022004016.
- Jerry A Fodor and Zenon W Pylyshyn. Connectionism and cognitive architecture: A critical analysis. *Cognition*, 28(1-2):3–71, 1988.
- Kenneth D Forbus and Dedre Gentner. Learning physical domains. Machine Learning: An Artificial Intelligence Approach, Volume II, 2:311, 1983.
- Robert Matthew French. The subtlety of sameness: A theory and computer model of analogy-making. MIT press, 1995.
- Yunfan Gao, Yun Xiong, Xinyu Gao, Kangxiang Jia, Jinliu Pan, Yuxi Bi, Yi Dai, Jiawei Sun, Meng Wang, and Haofen Wang. Retrieval-augmented generation for large language models: A survey, 2024. URL https://arxiv.org/abs/2312.10997.
- Dedre Gentner. Structure-mapping: A theoretical framework for analogy. Cognitive Science, 7(2):155–170, 1983.
- Dedre Gentner and Kenneth D Forbus. Computational models of analogy. Wiley interdisciplinary reviews: cognitive science, 2(3):266–276, 2011.
- Dedre Gentner and Arthur B Markman. Structure mapping in analogy and similarity. American psychologist, 52(1):45, 1997.

- M.A. Gluck, E. Mercado, and C.E. Myers. *Learning and Memory: From Brain to Behavior*. Worth Publishers, 4 edition, 2020. ISBN 9781429240147. URL https://books.google.de/books?id=CDdUkgEACAAJ.
- E Mark Gold. Language identification in the limit. Information and Control, 10(5):447–474, 1967. ISSN 0019-9958. doi: https://doi.org/10.1016/ S0019-9958(67)91165-5. URL https://www.sciencedirect.com/science/article/pii/ S0019995867911655.
- E Bruce Goldstein. Cognitive psychology: Connecting mind, research and everyday experience. Wadsworth, Cengage Learning, Belmont, CA, 2015.
- Hila Gonen, Srini Iyer, Terra Blevins, Noah Smith, and Luke Zettlemoyer. Demystifying prompts in language models via perplexity estimation. In Houda Bouamor, Juan Pino, and Kalika Bali, editors, *Findings of the Association for Computational Linguistics: EMNLP 2023*, pages 10136–10148, Singapore, December 2023. Association for Computational Linguistics. doi: 10.18653/v1/2023.findings-emnlp.679. URL https://aclanthology.org/2023.findings-emnlp.679.
- Cleotilde Gonzalez, Henny Admoni, Scott Brown, and Anita Williams Woolley. Cohumain: Building the socio-cognitive architecture of collective human–machine intelligence, 2023.
- P. Grohs and G. Kutyniok, editors. *Mathematical Aspects of Deep Learning*. Cambridge University Press, 2022.
- Sumit Gulwani, José Hernández-Orallo, Emanuel Kitzelmann, Stephen H Muggleton, Ute Schmid, and Benjamin Zorn. Inductive programming meets the real world. *Communications of the ACM*, 58(11):90–99, 2015.
- Helmar Gust, Kai-Uwe Kühnberger, and Ute Schmid. Metaphors and heuristic-driven theory projection (hdtp). Theoretical Computer Science, 354(1):98–117, 2006.
- Barbara Hammer. Learning with Recurrent Neural Networks. Springer-Verlag, Berlin, Heidelberg, 2000. ISBN 185233343X.
- S. Harnad. To cognize is to categorize: Cognition is categorization. In H. Cohen and C. Lefebvre, editors, *Handbook of Categorization in Cognitive Science (2nd edition)*, pages 21–54. Elsevier Academic Press, Amsterdam, 2017.
- Jerry Zhi-Yang He, Zackory Erickson, Daniel S. Brown, Aditi Raghunathan, and Anca Dragan. Learning representations that enable generalization in assistive tasks. In 6th Annual Conference on Robot Learning, 2022. URL https://openreview.net/ forum?id=b88HF4vd_ej.
- Dan Hendrycks and Thomas Dietterich. Benchmarking neural network robustness to common corruptions and perturbations. *International Conference on Learning*

Representations (ICLR), 2019.

- Pascal Hitzler, Md. Kamruzzaman Sarker, and Aaron Eberhart, editors. Compendium of Neurosymbolic Artificial Intelligence, volume 369 of Frontiers in Artificial Intelligence and Applications. IOS Press, Amsterdam, 2023. ISBN 978-1-64368-406-2. doi: 10.3233/FAIA369.
- Aidan Hogan, Eva Blomqvist, Michael Cochez, Claudia d'Amato, Gerard de Melo, Claudio Gutierrez, Sabrina Kirrane, José Emilio Labra Gayo, Roberto Navigli, Sebastian Neumaier, Axel-Cyrille Ngonga Ngomo, Axel Polleres, Sabbir M. Rashid, Anisa Rula, Lukas Schmelzeisen, Juan F. Sequeda, Steffen Staab, and Antoine Zimmermann. Knowledge graphs. ACM Comput. Surv., 54(4):71:1–71:37, 2022. doi: 10.1145/3447772. URL https://doi.org/10.1145/3447772.
- Andreas Holzinger, Anna Saranti, Alessa Angerschmid, Bettina Finzel, Ute Schmid, and Heimo Mueller. Toward human-level concept learning: Pattern benchmarking for AI algorithms. *Patterns*, 4:100788, 2023.
- Dirk Hovy and Shannon L. Spruit. The social impact of natural language processing. In Katrin Erk and Noah A. Smith, editors, *Proceedings of the 54th Annual Meeting* of the Association for Computational Linguistics (Volume 2: Short Papers), pages 591–598, Berlin, Germany, August 2016. Association for Computational Linguistics. doi: 10.18653/v1/P16-2096. URL https://aclanthology.org/P16-2096.
- Joy Hsu, Jiayuan Mao, Joshua B Tenenbaum, Noah D Goodman, and Jiajun Wu. What makes a maze look like a maze? *arXiv preprint arXiv:2409.08202*, 2024.
- Earl B Hunt, Janet Marin, and Philip J Stone. Experiments in Induction. Academic Press, New York, 1966.
- Ray S Jackendoff. Semantics and cognition, volume 8. MIT press, 1985.
- Shaoxiong Ji, Shirui Pan, Erik Cambria, Pekka Marttinen, and Philip S. Yu. A survey on knowledge graphs: Representation, acquisition, and applications. *IEEE Transactions on Neural Networks and Learning Systems*, 33(2):494–514, 2022. doi: 10.1109/TNNLS.2021.3070843.
- Ziwei Ji, Nayeon Lee, Rita Frieske, Tiezheng Yu, Dan Su, Yan Xu, Etsuko Ishii, Ye Jin Bang, Andrea Madotto, and Pascale Fung. Survey of hallucination in natural language generation. ACM Comput. Surv., 55(12), mar 2023a. ISSN 0360-0300. doi: 10.1145/3571730. URL https://doi.org/10.1145/3571730.
- Ziwei Ji, Nayeon Lee, Rita Frieske, Tiezheng Yu, Dan Su, Yan Xu, Etsuko Ishii, Ye Jin Bang, Andrea Madotto, and Pascale Fung. Survey of hallucination in natural language generation. ACM Computing Surveys, 55(12):1–38, 2023b.

- Yifan Jiang, Jiarui Zhang, Kexuan Sun, Zhivar Sourati, Kian Ahrabian, Kaixin Ma, Filip Ilievski, and Jay Pujara. Marvel: Multidimensional abstraction and reasoning through visual evaluation and learning. *NeurIPS Datasets & Benchmarks*, 2024.
- John Jumper, Richard Evans, Alexander Pritzel, Tim Green, Michael Figurnov, Olaf Ronneberger, Kathryn Tunyasuvunakool, Russ Bates, Augustin Žídek, Anna Potapenko, et al. Highly accurate protein structure prediction with alphafold. *nature*, 596(7873):583–589, 2021.

Daniel Kahneman. Thinking, fast and slow. Macmillan, New York, 2011.

- Sayash Kapoor, Emily M Cantrell, Kenny Peng, Thanh Hien Pham, Christopher A Bail, Odd Erik Gundersen, Jake M Hofman, Jessica Hullman, Michael A Lones, Momin M Malik, et al. Reforms: Consensus-based recommendations for machinelearning-based science. *Science Advances*, 10(18):eadk3452, 2024.
- Urvashi Khandelwal, Omer Levy, Dan Jurafsky, Luke Zettlemoyer, and Mike Lewis. Generalization through memorization: Nearest neighbor language models. In *International Conference on Learning Representations*, 2020. URL https://openreview. net/forum?id=HklBjCEKvH.
- Emanuel Kitzelmann and Ute Schmid. Inductive synthesis of functional programs: An explanation based generalization approach. J. Mach. Learn. Res., 7:429–454, dec 2006. ISSN 1532-4435.
- Takeshi Kojima, Shixiang Shane Gu, Machel Reid, Yutaka Matsuo, and Yusuke Iwasawa. Large language models are zero-shot reasoners. Advances in neural information processing systems, 35:22199–22213, 2022.
- D. Koller and N. Friedman. Probabilistic Graphical Models: Principles and Techniques. Adaptive computation and machine learning. MIT Press, 2009. ISBN 9780262013192. URL https://books.google.co.in/books?id=7dzpHCHzNQ4C.
- Brian Kulis. Metric learning: A survey. Foundations and Trends® in Machine Learning, 5(4):287–364, 2013. ISSN 1935-8237. doi: 10.1561/2200000019. URL http://dx.doi.org/10.1561/2200000019.
- William Labov. The boundaries of words and their meanings. In C.-J. N. Bailey and R. W. Shuy, editors, New Ways of Analyzing Variation in English, pages 67–90. Georgetown University Press, Washington, 1973.
- Daniel Lafond, Yves Lacouture, and Andrew L Cohen. Decision-tree models of categorization response times, choice proportions, and typicality judgments. *Psychological Review*, 116(4):833, 2009.
- Brenden M. Lake and Marco Baroni. Human-like systematic generalization through a meta-learning neural network. *Nature*, 623(7985):115–121, Nov 2023. ISSN

1476-4687. doi: 10.1038/s41586-023-06668-3. URL https://doi.org/10.1038/s41586-023-06668-3.

- Brenden M Lake, Ruslan Salakhutdinov, and Joshua B Tenenbaum. Human-level concept learning through probabilistic program induction. *Science*, 350(6266):1332–1338, 2015.
- Luís C Lamb, Artur Garcez, Marco Gori, Marcelo Prates, Pedro Avelar, and Moshe Vardi. Graph neural networks meet neural-symbolic computing: A survey and perspective. arXiv preprint arXiv:2003.00330, 2020.
- Sebastian Lapuschkin, Stephan Wäldchen, Alexander Binder, Grégoire Montavon, Wojciech Samek, and Klaus-Robert Müller. Unmasking clever hans predictors and assessing what machines really learn. *Nature Communications*, 10, 2019.
- Changmao Li and Jeffrey Flanigan. Task contamination: Language models may not be few-shot anymore. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 38, pages 18471–18480, 2024.
- Zhuoyan Li, Chen Liang, Jing Peng, and Ming Yin. The value, benefits, and concerns of generative ai-powered assistance in writing. In *Proceedings of the CHI Conference* on Human Factors in Computing Systems, pages 1–25, 2024.
- Jiashuo Liu, Zheyan Shen, Yue He, Xingxuan Zhang, Renzhe Xu, Han Yu, and Peng Cui. Towards out-of-distribution generalization: A survey. *arXiv preprint arXiv:2108.13624*, 2021.
- Francesco Locatello, Dirk Weissenborn, Thomas Unterthiner, Aravindh Mahendran, Georg Heigold, Jakob Uszkoreit, Alexey Dosovitskiy, and Thomas Kipf. Object-centric learning with slot attention. In H. Larochelle, M. Ranzato, R. Hadsell, M.F. Balcan, and H. Lin, editors, Advances in Neural Information Processing Systems, volume 33, pages 11525–11538. Curran Associates, Inc., 2020. URL https://proceedings.neurips.cc/paper_files/paper/2020/file/ 8511df98c02ab60aea1b2356c013bc0f-Paper.pdf.
- Tania Lombrozo. Simplicity and probability in causal explanation. Cognitive Psychology, 55(3):232–257, 2007.
- Viktor Losing, Barbara Hammer, and Heiko Wersing. Knn classifier with self adjusting memory for heterogeneous concept drift. In 2016 IEEE 16th International Conference on Data Mining (ICDM), pages 291–300, 2016. doi: 10.1109/ICDM.2016. 0040.
- Andrew Lovett, Kenneth Forbus, and Jeffrey Usher. Analogy with qualitative spatial representations can simulate solving raven's progressive matrices. In *Proceedings of the Annual Meeting of the Cognitive Science Society*, volume 29, 2007.
 - 29

- Jie Lu, Anjin Liu, Fan Dong, Feng Gu, Joao Gama, and Guangquan Zhang. Learning under concept drift: A review. *IEEE transactions on knowledge and data* engineering, 31(12):2346–2363, 2018.
- Mikołaj Małkiński and Jacek Mańdziuk. A review of emerging research directions in abstract visual reasoning. *Information Fusion*, 91:713–736, 2023.
- Robin Manhaeve, Sebastijan Dumančić, Angelika Kimmig, Thomas Demeester, and Luc De Raedt. Neural probabilistic logic programming in deepproblog. Artificial Intelligence, 298:103504, 2021. ISSN 0004-3702. doi: https://doi.org/10. 1016/j.artint.2021.103504. URL https://www.sciencedirect.com/science/article/ pii/S0004370221000552.
- Giuseppe Marra, Sebastijan Dumančić, Robin Manhaeve, and Luc De Raedt. From statistical relational to neurosymbolic artificial intelligence: A survey. *Artificial Intelligence*, page 104062, 2024.
- Douglas L Medin, William D Wattenmaker, and Sarah E Hampson. Family resemblance, conceptual cohesiveness, and category construction. Cognitive Psychology, 19(2):242–279, 1987. ISSN 0010-0285. doi: https://doi.org/10.1016/ 0010-0285(87)90012-0. URL https://www.sciencedirect.com/science/article/pii/ 0010028587900120.
- Douglas L Medin, Brian H Ross, and Arthur B Markman. Cognitive Psychology. Wiley, Hoboken, NJ, 4th edition, 2005. ISBN 0471458201.
- Carolyn B Mervis, Eleanor Rosch, et al. Categorization of natural objects. Annual review of psychology, 32(1):89–115, 1981.
- Donald Michie. Machine learning in the next five years. In Proceedings of the 3rd European conference on European working session on learning, pages 107–122, 1988.
- Tim Miller. Explanation in artificial intelligence: Insights from the social sciences. *Artificial Intelligence*, 267:1–38, 2019.
- Margaret Mitchell, Simone Wu, Andrew Zaldivar, Parker Barnes, Lucy Vasserman, Ben Hutchinson, Elena Spitzer, Inioluwa Deborah Raji, and Timnit Gebru. Model cards for model reporting. In *Proceedings of the conference on fairness*, accountability, and transparency, pages 220–229, 2019.
- C. Molnar. Interpretable Machine Learning. Leanpub, 2020. ISBN 9780244768522. URL https://books.google.de/books?id=jBm3DwAAQBAJ.
- Stephen Muggleton and Luc De Raedt. Inductive logic programming: Theory and methods. The Journal of Logic Programming, 19:629–679, 1994.

- Stephen H Muggleton, Ute Schmid, Christina Zeller, Alireza Tamaddoni-Nezhad, and Tarek Besold. Ultra-strong machine learning: comprehensibility of programs learned with ilp. *Machine Learning*, 107:1119–1140, 2018.
- Martin Mundt, Yongwon Hong, Iuliia Pliushch, and Visvanathan Ramesh. A wholistic view of continual learning with deep neural networks: Forgotten lessons and the bridge to active and open world learning. *Neural Networks*, 160:306–336, 2023.
- Weili Nie, Zhiding Yu, Lei Mao, Ankit B Patel, Yuke Zhu, and Anima Anandkumar. Bongard-logo: A new benchmark for human-level concept learning and reasoning. Advances in Neural Information Processing Systems, 33:16468–16480, 2020.
- Robert M Nosofsky. Exemplar-based accounts of relations between classification, recognition, and typicality. Journal of Experimental Psychology: Learning, Memory, and Cognition, 14(4):700, 1988.
- Robert M Nosofsky. The generalized context model: An exemplar model of classification. *Formal approaches in categorization*, pages 18–39, 2011.
- Daniel W. Otter, Julian R. Medina, and Jugal K. Kalita. A survey of the usages of deep learning in natural language processing. *CoRR*, abs/1807.10854, 2018. URL http://arxiv.org/abs/1807.10854.
- Leif E Peterson. K-nearest neighbor. Scholarpedia, 4(2):1883, 2009.
- Jorge López Puga, Martin Krzywinski, and Naomi Altman. Bayesian networks. *Nature Methods*, 12(9):799–800, Sep 2015. ISSN 1548-7105. doi: 10.1038/nmeth.3550. URL https://doi.org/10.1038/nmeth.3550.
- Mahima Pushkarna, Andrew Zaldivar, and Oddur Kjartansson. Data Cards: Purposeful and Transparent Dataset Documentation for Responsible AI. In *Proceedings* of the 2022 ACM Conference on Fairness, Accountability, and Transparency, pages 1776–1826, 2022.
- J. Ross Quinlan. Simplifying decision trees. International Journal of Man-Machine Studies, 27(3):221–234, 1987.
- Jamie Reilly, M Diaz, L Pylkkänen, E Jefferies, D Poeppel, G Zubicaray, L Connell, D Mirman, C Sandberg, Marc Brysbaert, et al. What we mean when we say semantic: A consensus statement on the nomenclature of semantic memory. *PsyArXiv* preprint: https://osf. io/pre prints/psyarxiv/xrnb2, 2003.
- Eleanor Rosch. Principles of categorization. In Cognition and Categorization, pages 27–48. Routledge, Milton Park, UK, 1978.
- Eleanor Rosch and Carolyn B Mervis. Family resemblances: Studies in the internal structure of categories. *Cognitive psychology*, 7(4):573–605, 1975.

- David E Rumelhart, James L McClelland, PDP Research Group, et al. Parallel distributed processing, volume 1: Explorations in the microstructure of cognition: Foundations. The MIT press, Cambridge, MA, 1986.
- Ute Schmid and Emanuel Kitzelmann. Inductive rule learning on the knowledge level. Cognitive Systems Research, 12(3-4):237–248, 2011.
- Petra Schneider, Michael Biehl, and Barbara Hammer. Adaptive relevance matrices in Learning Vector Quantization. *Neural Comput.*, 21(12):3532–3561, 2009. doi: 10. 1162/NECO.2009.11-08-908. URL https://doi.org/10.1162/neco.2009.11-08-908.
- Bernhard Schölkopf, Francesco Locatello, Stefan Bauer, Nan Rosemary Ke, Nal Kalchbrenner, Anirudh Goyal, and Yoshua Bengio. Toward causal representation learning. *Proceedings of the IEEE*, 109(5):612–634, 2021.
- Atharva Sehgal, Arya Grayeli, Jennifer J. Sun, and Swarat Chaudhuri. Neurosymbolic grounding for compositional world models. In *The Twelfth International Confer*ence on Learning Representations, ICLR 2024, Vienna, Austria, May 7-11, 2024. OpenReview.net, 2024. URL https://openreview.net/forum?id=4KZpDGD4Nh.
- H. S. Seung, H. Sompolinsky, and N. Tishby. Statistical mechanics of learning from examples. *Phys. Rev. A*, 45:6056–6091, Apr 1992. doi: 10.1103/PhysRevA.45.6056. URL https://link.aps.org/doi/10.1103/PhysRevA.45.6056.
- Harshay Shah, Kaustav Tamuly, Aditi Raghunathan, Prateek Jain, and Praneeth Netrapalli. The pitfalls of simplicity bias in neural networks. *Neural Information Processing Systems*, 2020.
- Shai Shalev-Shwartz and Shai Ben-David. Understanding machine learning: From theory to algorithms. Cambridge university press, 2014.
- Ashish Sharma, Sudha Rao, Chris Brockett, Akanksha Malhotra, Nebojsa Jojic, and Bill Dolan. Investigating agency of llms in human-ai collaboration tasks. arXiv preprint arXiv:2305.12815, 2023.
- Roger N. Shepard. Toward a universal law of generalization for psychological science. *Science*, 237(4820):1317–1323, 1987. doi: 10.1126/science.3629243. URL https://www.science.org/doi/abs/10.1126/science.3629243.
- Andrew Shin and Kunitake Kaneko. Large language models lack understanding of character composition of words, 2024.
- Zhivar Sourati, Vishnu Priya Prasanna Venkatesh, Darshan Deshpande, Himanshu Rawlani, Filip Ilievski, Hông-Ân Sandlin, and Alain Mermoud. Robust and explainable identification of logical fallacies in natural language arguments. *Knowledge-Based Systems*, 266:110418, 2023.

- Zhivar Sourati, Filip Ilievski, Pia Sommerauer, and Yifan Jiang. Arn: Analogical reasoning on narratives. Transactions of the Association for Computational Linguistics, 12:1063–1086, 2024.
- Michiel Straat, Fthi Abadi, Zhuoyun Kan, Christina Göpfert, Barbara Hammer, and Michael Biehl. Supervised learning in the presence of concept drift: a modelling framework. *Neural Computing and Applications*, 34(1):101–118, 2022.
- Joshua B. Tenenbaum and Thomas L. Griffiths. Generalization, similarity, and bayesian inference. *Behavioral and Brain Sciences*, 24(4):629–640, 2001. doi: 10.1017/S0140525X01000061.
- Joshua B Tenenbaum, Charles Kemp, Thomas L Griffiths, and Noah D Goodman. How to grow a mind: Statistics, structure, and abstraction. *Science*, 331(6022): 1279–1285, 2011.
- Nilesh Tripuraneni, Michael Jordan, and Chi Jin. On the theory of transfer learning: The importance of task diversity. Advances in neural information processing systems, 33:7852–7862, 2020.
- Vladimir N. Vapnik. The nature of statistical learning theory. Springer-Verlag New York, Inc., 1995. ISBN 0-387-94559-8.
- Vladimir N Vapnik and A Ya Chervonenkis. On the uniform convergence of relative frequencies of events to their probabilities. In *Measures of complexity: festschrift* for alexey chervonenkis, pages 11–30. Springer, 2015.
- Vanshika Vats, Marzia Binta Nizam, Minghao Liu, Ziyuan Wang, Richard Ho, Mohnish Sai Prasad, Vincent Titterton, Sai Venkat Malreddy, Riya Aggarwal, Yanwen Xu, et al. A survey on human-ai teaming with large pre-trained models. arXiv preprint arXiv:2403.04931, 2024.
- Eli Verwimp, Rahaf Aljundi, Shai Ben-David, Matthias Bethge, Andrea Cossu, Alexander Gepperth, Tyler L Hayes, Eyke Hüllermeier, Christopher Kanan, Dhireesha Kudithipudi, et al. Continual learning: Applications and the road forward. *Transactions on Machine Learning Research*, 2024. ISSN 2835-8856. URL https://openreview.net/forum?id=axBIMcGZn9.
- Michael R Waldmann, York Hagmayer, and Aaron P Blaisdell. Beyond the information given: Causal models in learning and reasoning. *Current Directions in Psychological Science*, 15(6):307–311, 2006.
- Cara Leigh Widmer, Md Kamruzzaman Sarker, Srikanth Nadella, Joshua Fiechter, Ion Juvina, Brandon Minnery, Pascal Hitzler, Joshua Schwartz, and Michael Raymer. Towards human-compatible xai: Explaining data differentials with concept induction over background knowledge. *Journal of Web Semantics*, 79:100807, 2023.

- Thaddäus Wiedemer, Jack Brady, Alexander Panfilov, Attila Juhos, Matthias Bethge, and Wieland Brendel. Provable compositional generalization for object-centric learning. In *The Twelfth International Conference on Learning Representations*, 2024. URL https://openreview.net/forum?id=7VPTUWkiDQ.
- Eva Wiese, Uwe Konderding, and Ute Schmid. Mapping and inference in analogical problem solving—as much as needed or as much as possible? In *Proceedings of the Annual Meeting of the Cognitive Science Society*, volume 30, pages 927–932, 2008.
- Patrick H Winston. Learning structural descriptions from examples. Technical report, MIT, AI Technical Reports, 1970.
- Zonghan Wu, Shirui Pan, Fengwen Chen, Guodong Long, Chengqi Zhang, and Philip S. Yu. A comprehensive survey on graph neural networks. *IEEE Transac*tions on Neural Networks and Learning Systems, 32(1):4–24, 2021. doi: 10.1109/ TNNLS.2020.2978386.
- Jingkang Yang, Kaiyang Zhou, Yixuan Li, and Ziwei Liu. Generalized out-ofdistribution detection: A survey. International Journal of Computer Vision, pages 1–28, 2024a.
- Mingzhe Yang, Hiromi Arai, Naomi Yamashita, and Yukino Baba. Fair machine guidance to enhance fair decision making in biased people. In *Proceedings of the CHI Conference on Human Factors in Computing Systems*, pages 1–18, 2024b.
- Liuyi Yao, Zhixuan Chu, Sheng Li, Yaliang Li, Jing Gao, and Aidong Zhang. A survey on causal inference. ACM Trans. Knowl. Discov. Data, 15(5), may 2021. ISSN 1556-4681. doi: 10.1145/3444944. URL https://doi.org/10.1145/3444944.
- Haotian Ye, Chuanlong Xie, Tianle Cai, Ruichen Li, Zhenguo Li, and Liwei Wang. Towards a theoretical framework of out-of-distribution generalization. In A. Beygelzimer, Y. Dauphin, P. Liang, and J. Wortman Vaughan, editors, Advances in Neural Information Processing Systems, 2021. URL https://openreview.net/forum?id= kFJoj7zuDVi.
- Thomas Zeugmann. Can learning in the limit be done efficiently? In Ricard Gavaldá, Klaus P. Jantke, and Eiji Takimoto, editors, *Algorithmic Learning Theory*, pages 17– 38, Berlin, Heidelberg, 2003. Springer Berlin Heidelberg. ISBN 978-3-540-39624-6.
- Shengyu Zhang, Linfeng Dong, Xiaoya Li, Sen Zhang, Xiaofei Sun, Shuhe Wang, Jiwei Li, Runyi Hu, Tianwei Zhang, Fei Wu, et al. Instruction tuning for large language models: A survey. arXiv preprint arXiv:2308.10792, 2023.
- Yu Zhang and Qiang Yang. A survey on multi-task learning. IEEE transactions on knowledge and data engineering, 34(12):5586–5609, 2021.

Fuzhen Zhuang, Zhiyuan Qi, Keyu Duan, Dongbo Xi, Yongchun Zhu, Hengshu Zhu, Hui Xiong, and Qing He. A comprehensive survey on transfer learning. *Proceedings* of the IEEE, 109(1):43–76, 2020.