Distributed Online Optimization with Stochastic Agent Availability

Juliette Achdou CRIStAL, Université de Lille, Inria, Università degli Studi di Milano CNRS, Centrale Lille Lille, France

Nicolò Cesa-Bianchi and Politecnico di Milano Milan, Italy

Hao Qiu Università degli Studi di Milano, Milan, Italy

Abstract

Motivated by practical federated learning settings where clients may not be always available, we investigate a variant of distributed online optimization where agents are active with a known probability p at each time step, and communication between neighboring agents can only take place if they are both active. We introduce a distributed variant of the FTRL algorithm and analyze its network regret, defined through the average of the instantaneous regret of the active agents. Our analysis shows that, for any connected communication graph G over Nagents, the expected network regret of our FTRL variant after T steps is at most of order (κ/p^2) min $\{\sqrt{N}, N^{1/4}/\sqrt{p}\}\sqrt{T}$, where κ is the condition number of the Laplacian of G. We then show that similar regret bounds also hold with high probability. Moreover, we show that our notion of regret (averagecase over the agents) is essentially equivalent to the standard notion of regret (worst-case over agents), implying that our bounds are not significantly improvable when p = 1. Our theoretical results are supported by experiments on synthetic datasets.

INTRODUCTION 1

Distributed convex optimization (Nedic and Ozdaglar, 2009; Duchi et al., 2011) is an algorithmic framework widely used in federated learning settings—see, e.g., Yang et al. (2019) for a survey of applications. In distributed convex optimization the goal is to optimize a global convex objective by means of a decentralized algorithm run by multiple agents who can exchange messages only with their neighbors in a given communication network. The global objective is expressed as a sum of local functions associated with the agents, where each agent has only oracle access to its local function (typically, via a first-order oracle).

In this work we focus on distributed online optimization (DOO), an online learning variant of distributed convex optimization in which each agent is facing an adversarial sequence of convex loss functions (Hosseini et al., 2013). The goal of an agent is to minimize its regret with respect to a sequence of global loss functions, each obtained by summing the corresponding local losses for each agent. In both batch and online distributed optimization settings, the presence of the communication network, which limits the exchange of information to adjacent nodes, implies that agents must use some information-propagation technique to collect information about the global loss function.

Our main contribution in this work is the analysis of a variant of DOO in which agents may not be available in every time step. When inactive, an agent neither contributes to the regret nor can it communicate with its neighbors. In practice, this scenario may arise due to machine failures, disconnections, or devices (e.g., mobile phones) being turned off. While the problem of intermittent agents availability has been investigated before in distributed convex optimization (Gu et al., 2021; Wang and Ji, 2022; Yan et al., 2024), we are not aware of any such study in the DOO framework. More specifically, we consider random agent activations where, in each round, each agent v becomes independently active with some unknown probability p_{v} . As a consequence, the active communication network at time t becomes stochastic, as it is induced by the random subset of active agents at time t. Because the number of active agents is a random variable, to ensure a uniform scaling of losses across times steps we define the global loss function as an average (as opposed to a sum) over the active agents. Likewise, we define the instantaneous regret as an average over the active agents. We call network regret the sum of these instantaneous regrets. Although network regret may seem weaker than the notion of regret commonly used in DOO settings where agents are always active, we show that the two notions are essentially equivalent, see Remark 1.

Hosseini et al. (2016); Lei et al. (2020) investigated DOO on random communication networks. However, these previous studies only consider stochastic edge availability. Our analysis of networks with random node availability provides a set of results that can be applied to both edge and node availability. In particular, we recover the bounds of (Lei et al., 2020) for the full information setting as a special case of ours.

To propagate information, we use standard gossiping techniques (Xiao and Boyd, 2004; Boyd et al., 2006), that average gradient information from neighboring agents. Alternatively, one can propagate information about local losses by message passing. This approach has two main drawbacks. When the network is dense or the activation probabilities are high, the number of messages becomes too big. Conversely, when the network is sparse or the activation probabilities are small, the time it takes for an agent to collect all gradient information for a given round becomes too long.

Main contributions. The main contributions of this work can be summarized as follows.

• We design and analyze Gossip-FTRL, a distributed variant of the FTRL algorithm for online convex optimization, and prove a general network regret bound for arbitrary connected communication networks *G* and arbitrary activation probabilities.

• In the *p*-uniform case (activation probabilities equal to some known $p \geq 1/N$), the expected regret of our algorithm is bounded by $\frac{1}{1-\rho} \min\left(\sqrt{N}, \frac{N^{1/4}}{\sqrt{p}}\right)\sqrt{T}$, where *T* is the known time horizon, *N* is the known number of agents, and $1-\rho$ is the unknown spectral gap of the gossip matrix supported on *G*. For the same algorithm, we also prove a regret bound of order $\frac{N}{1-\rho^2}\sqrt{T}$ that holds with high probability for any arbitrary activation probabilities.

• For a standard choice of the gossip matrix, we show that $\frac{1}{1-\rho}$ is of order κ/p^2 in the *p*-uniform case, where κ is the condition number of the Laplacian matrix of *G*. If the spectral radius of *G* is known, then the network regret is bounded by $\frac{\kappa(G)}{p} \min\left(\sqrt{N}, \frac{N^{1/4}}{\sqrt{p}}\right)\sqrt{T}$.

• For p = 1 (all agents are always active), we prove a lower bound showing that any distributed online algorithm must suffer, on some G, a network regret at least of order $\left(\frac{\rho}{1-\rho}\right)^{\alpha/4} N^{(1-\alpha)/2} \sqrt{T}$ for any $0 \le \alpha \le 1$. By comparison, when tuned for ρ , our regret bound is of order $\left(\frac{1}{1-\rho}\right)^{1/2} N^{1/4} \sqrt{T}$.

• Finally, we run experiments on synthetic data com-

paring Gossip-FTRL with DOGD by Lei et al. (2020) for different choices of the relevant parameters.

Our most general bounds (Theorem 1) hold when agents only know p, N and T. In particular, agents need not know the structure of G and Gossip-FTRL is run with the same initialization for all agents. The more refined bounds in Corollary 1 and Corollary 2 need also the preliminary knowledge of the spectral radius of G (or of a suitable bound on it).

Technical challenges. The fact that our global loss at time t is averaged over the random subset of active agents requires some substantial modifications to previous analyses of DOO. Unlike previous works, which use Online Gradient Descent and Dual Averaging as base algorithms, we prove our results using the general FTRL algorithm with arbitrary regularizers.

To prove our main result (Theorem 1), we introduce an omniscient agent, who runs FTRL knowing the past loss gradients of all active agents. We then decompose the regret in two terms: one measuring the regret of the omniscient agent, which we can bound using singleagent FTRL analysis, and one accounting for the deviations between the predictions of the omniscient agent and of the individual agents. To analyze the latter term, we first apply convex analysis to bound the norm of the difference between the prediction \overline{x}_t of the omniscient agent and the prediction $x_t(v)$ of each individual agent v in terms of the dual norm of the cumulative gradients of the corresponding global losses, \overline{z}_t and $z_t(v)$, where $z_t(v)$ is the gossiping-based local estimate of \overline{z}_t . We then relate the expected value of these dual norms, averaged over the random set of active agents, with terms of the form $\mathbb{E} \| \prod_s W_s - \frac{\mathbf{1}\mathbf{1}^\top}{N} \|_2$, which appear in the analysis of gossip algorithms. Here W_s are doubly stochastic gossip matrices and $\mathbf{1} = (1, \dots, 1)$. A technical hurdle, missing in previous analyses, is to account for the random number of active agents when relating the two quantities above and also when bounding the regret of the omniscient agent. This is due to the fact that a direct application of single-agent FTRL analysis only bounds the sum of active agents' losses rather than their average.

2 SETTING AND NOTATION

In multi-agent online convex optimization, agents are nodes of a communication network represented by a connected and an undirected graph G = (V, E), where $V = \{1, \ldots, N\} = [N]$ indexes the agents and the edge set E defines the communication structure among agents. We use $\mathcal{N}_v = \{u \in V : (u, v) \in E\}$ to denote the neighborhood of $v \in V$. Let $\mathcal{X} \subset \mathbb{R}^d$ be the agents' common decision space, which we assume to be convex and closed. A arbitrary and unknown sequence $\ell_1(v,\cdot), \ell_2(v,\cdot), \ldots$ of local losses $\ell_t(v,\cdot) : \mathcal{X} \to \mathbb{R}$ is associated with each agent $v \in V$. For all t > 1we assume $\ell_t(v, \cdot)$ is convex and L-Lipschitz with respect to an arbitrary norm $\|\cdot\|$. At every round $t = 1, 2, \ldots$, each agent $v \in V$ becomes independently active with fixed probability p_v . Without loss of generality, we assume $p_{\min} = \min_v p_v > 0$ and, for simplicity, $\sum_{v} p_{v} \geq 1$ (otherwise less than one active agent would be active per round on average). Note that this implies $p_{\max} = \max_v p_v \ge \frac{1}{N}$. We call *p*-uniform the special case when $p_v = p$ for all $v \in V$. We assume that active agents v know which of their neighbors in \mathcal{N}_v are active. Let S_t be the set of active agents at time t and $E_t = E \cap \{(u, v) : u, v \in S_t\}$ be the set of active edges at time t, i.e., edges in E whose both endpoints are active in that round. We say that a doubly stochastic matrix W_t is a gossip matrix for the set S_t of active agents at time t if $W_t(v, v') = 0$ for all distinct $v, v' \in V$ such that $(v, v') \notin E_t$. Let W be a random gossip matrix (with respect to a graph Gand activation probabilities p_v for $v \in V$) and define $\rho = \sqrt{\lambda_2(\mathbb{E}[WW^{\top}])}, \text{ for i.i.d gossip matrices } W_t,$ where we denote by $\lambda_i(\cdot)$ the *i*-th highest eigenvalue of a matrix (keeping track of multiplicity). Clearly, $0 < \rho < 1$. In what follows, we often write ρ leaving G and $\{p_v\}_{v \in V}$ implicitly understood from the context.

Next, we define the distributed online optimization protocol used in this work.

At each round $t = 1, 2, \ldots, T$,

- 1. Each active agent $v \in S_t$ chooses an action $x = x_t(v) \in \mathcal{X}$ and observes the gradient $\nabla \ell_t(v, x)$ of the local loss $\ell_t(v, \cdot)$.
- 2. Each active agent $v \in S_t$ sends a message $z_t(v)$ to their active neighbors and uses the messages received from the active neighbors to compute a new message $z_{t+1}(v)$.

Note that this protocol implicitly defines an active communication graph $G_t = (S_t, E_t)$ for round t. As the number of agents that incur loss in a step is a random variable, we define the *network loss* at step t as the average over the active agents of the local losses in that round,

$$\ell^{\text{net}}_t(S_t,\cdot) = \frac{1}{|S_t|} \sum_{v \in S_t} \ell_t(v,\cdot)$$

and let $\ell_t^{\text{net}}(\emptyset, \cdot) = 0$. Hence, unlike the standard DOO model where ℓ_t^{net} scales linearly with N, in our model ℓ_t^{net} is independent of N.

The agents' performance is measured by the *network* regret R_T^{net} defined by

$$\sum_{t=1}^{T} \frac{1}{|S_t|} \sum_{v \in S_t} \ell_t^{\text{net}} (S_t, x_t(v)) - \min_{x \in \mathcal{X}} \sum_{t=1}^{T} \ell_t^{\text{net}} (S_t, x)$$

where the steps t when $S_t = \emptyset$ are omitted from the sum. In this work, we provide bounds in high probability and in expectation for the network regret.

Remark 1. When p = 1, we recover the standard DOO setting and our network regret R_T^{net} becomes

$$\frac{1}{N} \sum_{v \in V} \sum_{t=1}^{T} \ell_t^{\text{net}} (V, x_t(v)) - \min_{x \in \mathcal{X}} \sum_{t=1}^{T} \ell_t^{\text{net}} (V, x) . \quad (1)$$

In standard DOO, ℓ_t^{net} is a sum over the N local losses, and $\frac{1}{N} \sum_{v \in V}$ is replaced by $\max_{v \in V}$. The resulting regret R_T is then defined by

$$\max_{v \in V} \sum_{t=1}^{T} \sum_{v' \in V} \ell_t(v', x_t(v)) - \min_{x \in \mathcal{X}} \sum_{t=1}^{T} \sum_{v' \in V} \ell_t(v', x) \ . \ (2)$$

Hence, when p = 1, $R_T^{\text{net}} \leq R_T/N$. Recently, Wan et al. (2024) proved that $R_T = \tilde{\Theta}(N(1-\rho)^{-1/4}\sqrt{T})$ where the upper bound relies on accelerated gossiping and $\tilde{\Theta}$ hides factors logarithmic in N. Hence, using the same algorithm, we get $R_T^{\text{net}} = \tilde{O}((1-\rho)^{-1/4}\sqrt{T})$. In Theorem 3 we prove that $R_T^{\text{net}} = \Omega((1-\rho)^{-1/4}\sqrt{T})$ for any distributed online algorithm, thus proving that $R_T^{\text{net}} = \tilde{\Theta}(R_T)/N$ in the special case p = 1.

Remark 2. In the multi-agent single-task setting of Cesa-Bianchi et al. (2020), local losses are the same for each agent, $\ell_t(v, \cdot) = \ell_t(\cdot)$ for all $v \in V$. The network regret then takes the form

$$R_t^{\text{net}} = \sum_{t=1}^T \frac{1}{|S_t|} \sum_{v \in S_t} \ell_t (x_t(v)) - \min_{x \in \mathcal{X}} \sum_{t=1}^T \ell_t(x) \; .$$

This setting is not comparable with DOO. Indeed, in the single-task setting agents can achieve an expected network regret of order $\mathcal{O}(\sqrt{T})$ even without communicating. In DOO, instead, ignoring communication leads to a linear expected network regret.

3 THE Gossip-FTRL ALGORITHM

We assume each agent runs an instance of **Gossip-FTRL** (Algorithm 1), a gossiping variant of FTRL with a regularizer $\psi : \mathcal{X} \mapsto \mathbb{R}$ that is μ -strongly convex with respect to the same norm $\|\cdot\|$ with respect to which the Lipschitzness of the losses is defined. Our analysis depends on the choice of ψ only through μ and the diameter $D^2 = \max_{x \in \mathcal{X}} \psi(x) - \min_{x' \in \mathcal{X}} \psi(x')$. At any time step t, the instance of **Gossip-FTRL** run by an active agent v computes a weight vector $W_t(v, \cdot)$ over the set $\mathcal{N}_v \cap S_t$ of active neighbors. In Section 6, we introduce a simple way of choosing these weights so

Algorithm 1: Gossip-FTRL. An instance of this algorithm is run by each agent $v \in V$

that the gossip matrix $W_t(\cdot, \cdot)$ is a doubly stochastic matrix, which is a requirement for our analysis.

The instance of Gossip-FTRL run by agent v has two local variables: $g_t(v)$, corresponding to the local loss gradient for the prediction $x_t(v)$ of v at time t, and $z_t(v)$, corresponding to the estimate of the network loss gradient computed by agent v.

Let $\Gamma_t \in \mathbb{R}^{N \times d}$ be the matrix whose v-th row is

$$g_t(v) = \begin{cases} 0 & \text{if } v \notin S_t, \\ \nabla \ell_t \big(v, x_t(v) \big) & \text{if } v \in S_t. \end{cases}$$
(3)

Correspondingly, we define Z_t , the matrix whose v-th row is $z_t(v)$ for all $v \in V$. Let e_v be the canonical basis vector for coordinate $v \in [N]$. Let the weights $W_t(v, \cdot)$ computed by the instance of Algorithm 1 run by each $v \in S_t$ form a $N \times N$ gossip matrix W_t for S_t such that $W_t(v, \cdot) = e_v$ for all $v \in V \setminus S_t$. We may write the updates performed by the instance as $Z_{t+1} = W_t Z_t + \Gamma_t$. Note that the definitions of W_t and Γ_t imply that $z_{t+1}(v) = z_t(v)$ for all agents $v \in V \setminus S_t$ that are inactive at time t. Moreover, any active agent $v \in S_t$ can compute $z_{t+1}(v)$ using the most recent value $z_s(j)$ (for some s < t) received by agents $j \in$ $\mathcal{N}_v \setminus S_t$ (i.e., neighbors inactive at time t).

The algorithm considered here is a natural extension to arbitrary regularizers and random activations of the algorithms traditionally used for DOO, e.g., (Hosseini et al., 2013; Lei et al., 2020). The optimal choice for the learning rate is however different, as it depends on the activation probabilities.

4 UPPER BOUNDS

Recall that at each round t, each agent $v \in V$ is independently active with probability $p_v > 0$. Let \overline{p} the average of these probabilities and $\sigma_p^2 = \frac{1}{N} \sum_{v \in V} p_v^2 - \overline{p}^2$ their variance.

The next result establishes an upper bound on the expected network regret of Algorithm 1 (all missing proofs are in the supplementary material).

Theorem 1. Assume each agent runs an instance of Gossip-FTRL with learning rate $\eta > 0$ and i.i.d gossip matrices W_t . Then, the expected network regret can be bounded by

$$\mathbb{E}\left[R_T^{\text{net}}\right] \le \frac{ND^2}{\eta} + \frac{L^2}{\mu} \eta \left(\bar{p}N + \bar{p}(1-\bar{p}) - \sigma_p^2 + 6 + 3\min\left(\bar{p}N,\sqrt{N}\right)\frac{\rho}{1-\rho}\right) T, \qquad (4)$$

where $\rho = \sqrt{\lambda_2(\mathbb{E}[W_1W_1^{\top}])}$. In the p-uniform case, we have

$$\mathbb{E}[R_T^{\text{net}}] \le \frac{D^2}{p\eta} + \frac{L^2}{\mu} \eta \left(8 + 3\min\left(pN,\sqrt{N}\right)\frac{\rho}{1-\rho}\right) T .$$
(5)

If, in addition,
$$\eta = \frac{(D/L)\sqrt{\mu}}{2\sqrt{2p\min(pN,\sqrt{N})T}}$$
, then

$$\mathbb{E}\left[R_T^{\text{net}}\right] \le 2\sqrt{2} \frac{DL}{\sqrt{\mu}} \frac{1}{1-\rho} \sqrt{T} \\ \times \begin{cases} \sqrt{N} & \text{if } p \in [1/N, 1/\sqrt{N}] \\ N^{1/4}/\sqrt{p} & \text{otherwise} \end{cases}$$
(6)

Bound (6) reveals two different regimes based on the value of p in the p-uniform case. Regardless of the regime, the factor inside the brackets in bound (6) is less than \sqrt{N} and becomes at most $N^{1/4}$ when $p \to 1$. Note also that, lacking any knowledge on p, one can can set $\eta = (D/L)N^{1/4}\sqrt{\mu/T}$ and get the suboptimal bound $\mathbb{E}[R_T^{\text{net}}] \leq 8DLN^{\frac{3}{4}} \frac{1}{1-\rho}\sqrt{T}$.

The bounds of Theorem 1 capture the structure of G through the reciprocal of the spectral gap, $\frac{1}{1-\rho}$. In Section 6, we give upper bounds on $\frac{1}{1-\rho}$ for an appropriately chosen gossip matrix W_1 . Specifically, combining (4) with Theorem 4 and choosing an appropriate η which only requires knowing p_{\min} , N, and the spectral radius of G we get, under mild conditions on $\{p_v\}_{v \in V}$ (see the appendix),

$$\mathbb{E}[R_T^{\text{net}}] \le 12DL \frac{\kappa(G)}{p_{\min}} N^{3/4} \sqrt{\frac{T}{\mu}} .$$
 (7)

Concerning the dependence of the network regret on N, there is a discrepancy between bound (7) for arbitrary activation probabilities and bound (6) for the p-uniform case. In the appendix, we show that the factor $N^{3/4}$ in (7) can be brought down to \sqrt{N} provided active agents know $|S_t|$ in each round t.

Comparison with previous bounds. As mentioned in Section 1, lower bounds on the standard notion of regret in DOO apply (up to constant factors) to our network regret. Hence, it is fair to compare our bound in Theorem 1 to the bounds previously shown in the DOO literature. To compare with previous results, we restrict our analysis to the special case when $p_v = 1$ for all $v \in V$. In this case, our bound (6) is of order of $N^{1/4} \frac{\rho}{1-\rho} \sqrt{T}$. This matches the upper bounds of (Hosseini et al., 2013; Yan et al., 2013)recall that our global loss is divided by the number of active agents, so the upper bounds for the standard DO setting must be divided by N. If the active graph G_t is an Erdős-Rényi random graph with parameter q, our setting reduces to that of Lei et al. (2020) for convex losses and full feedback. As shown in Section 7, our analysis recovers the upper bound of order $\frac{N^{1/4}}{q} \frac{\rho}{1-\rho} \sqrt{T}$ in (Lei et al., 2020, Theorem 1) when η is tuned based on N. In Corollary 2, we also prove a general bound that holds for all p and q and where ρ is expressed in terms of simple graph-theoretic quantities. When p = 1 and q = 1, Wan et al. (2024) recently show that using accelerated gossip one can achieve a bound of order $\sqrt{\frac{\rho}{1-\rho}T \ln N}$ when η is tuned based on both N and ρ . Under the same tuning assumptions, our bound (6) is instead of order $N^{1/4} \sqrt{\frac{\rho}{1-\rho}T}$.

Lower bound on activation probabilities. Our analysis assumes $\sum_{v} p_v \geq 1$ ensuring that the fraction of rounds with zero active agents is vanishingly small with high probability. If this assumption is dropped, the time horizon T in our bounds is replaced by the expected number $\tilde{T} = (1 - \prod_{v \in \mathcal{V}} (1 - p_v))T$ of time steps when there is at least one active agent (if no agents are active in a give step, then that step does not contribute to the regret). However, optimizing the learning rate with respect to \tilde{T} is problematic because this quantity depends on the activation probabilities. On the other hand, note that $\tilde{T} \leq (1 - (1 - p_{\max})^N)T \leq p_{\max}NT$. Hence, when p_{\max} is known and smaller than $\frac{1}{N}$ (which, in turn, implies that $\sum_{v} p_v < 1$), we can tune the learning rate using $p_{\max}NT < T$.

Non stationary activation distributions. If the activation probabilities change over time within known bounds p^{\min} and p^{\max} , we can still recover the main bound as long as the activations events are inde-

pendent. In particular, by tuning η as a function of T, p_{\min}, p_{\max} , the expected network regret of Gossip-FTRL is bounded by (7).

We complement the result of Theorem 1 with a high probability bound on the network regret.

Theorem 2. Assume each agent runs an instance of Gossip-FTRL with learning rate $\eta > 0$. Then, with probability $1 - \delta$, the network regret is bounded by

$$R_T^{\text{net}} \le N\left(\frac{D^2}{\eta} + \frac{L^2}{\mu}\eta T\right) + 3\eta T N \frac{L^2}{\mu} \left(\frac{3}{1-\rho^2}\log\frac{NT^2}{\delta} + 3\right)$$

There are two notable differences between the bound in expectation provided by Theorem 1 and this one. First, the high-probability bound has a $1/(1-\rho^2)$ factor instead of $\rho/(1-\rho)$, where the former is smaller than the latter when $\rho < (\sqrt{5}-1)/2$. This difference in the dependence on ρ is caused by Markov's inequality, which is used here to bound the deviation probabilities between $\prod W_s$ and $\mathbf{11}^T/N$ in the gossiping analysis. Second, the dependence on N is worse by a factor of \sqrt{N} (however, when $|S_t|$ is known, this extra \sqrt{N} factor disappears).

5 LOWER BOUND

Although our notion of network regret is weaker than the one considered in DOO settings with a constant number of agents, the next result shows that when all agents are active with probability 1, then instances that are hard for any given agent are also hard for most agents.

Theorem 3. Pick any \mathcal{X} with diameter D with respect to the Euclidean norm. Pick any $N \ge 4$ multiple of 4, and let $p_v = 1$ for all $v \in V = [N]$. For any DOO algorithm and for any horizon T, there exists a connected graph G = (V, E) and L-Lipschitz, convex local losses $\ell_t(v, \cdot)$ for $v \in V$ and $t \in [T]$ such that

$$R_T^{\text{net}} \ge \frac{3DL}{16} \left(\frac{8\rho}{1-\rho}\right)^{\frac{\alpha}{4}} N^{\frac{1-\alpha}{2}} \sqrt{T},$$

for all $0 \leq \alpha \leq 1$, where $\rho = \sqrt{\lambda_2(\mathbb{E}[W^2])}$ and $W = I_N - \frac{\operatorname{Lap}(G)}{\lambda_1(G)}$.

For $\alpha = 1$, the lower bound of Theorem 3 becomes of order $\left(\frac{\rho}{1-\rho}\right)^{1/4}\sqrt{T}$, showing $R_T^{\text{net}} = \widetilde{\Omega}(R_T)/N$ because of (Wan et al., 2024, Theorem 3).

6 THE GOSSIP MATRIX

Following the literature on gossip algorithms, we set

$$W_t = I_N - b \operatorname{Lap}(G_t), \qquad (8)$$

where $G_t = (V, E_t)$ and b > 0 is a parameter set so that $b \leq 1/\lambda_1(G_t)$. One can easily verify that this a gossip matrix for S_t . Indeed, it is a symmetric and doubly-stochastic matrix, whose off-diagonal elements $W_t(i, j)$ are zero whenever either *i* or *j* are not in S_t . In particular, W_t is nonnegative because $\lambda_1(G_t) \leq \lambda_1(G)$, since G_t is obtained by removing edges from *G*. Note also that by knowing *b* and its active neighborhood, an agent *v* can compute $W_t(v, \cdot)$, as required by **Gossip-FTRL**. Finally, since the sets S_1, S_2, \ldots of active agents are drawn i.i.d., the matrices W_1, W_2, \ldots are also i.i.d.

A general bound on ρ . The following result provides a general upper bound that, when applied to the bounds of Theorem 1, characterizes the dependence of the regret both on the probabilities p_v and on the graph structure (through the Fiedler value $\lambda_{N-1}(G)$ or the condition number $\kappa(G)$).

Theorem 4. If W_1 is set according to (8), then

$$\rho^2 \le 1 - bp_{\min}^2 \lambda_{N-1}(G) . \tag{9}$$

Moreover, for $b = 1/\lambda_1(G)$ we have

$$\rho^2 \le 1 - \frac{p_{\min}^2}{\kappa(G)} .$$
(10)

Proof. Recall $\rho^2 = \lambda_2(\mathbb{E}[W_1 W_1^{\top}])$. We have

$$\lambda_{2}(\mathbb{E}[W_{1}W_{1}^{\top}]) \leq \lambda_{2}(\mathbb{E}[W_{1}])$$

$$\leq \lambda_{2} \left(I - b \mathbb{E}[\operatorname{Lap}(G_{1})] \right)$$

$$\leq \lambda_{2} \left(I - b P \operatorname{Lap}(G) P \right)$$

$$\leq \lambda_{2} \left(I - b p_{\min}^{2} \operatorname{Lap}(G) \right)$$

$$\leq 1 - b p_{\min}^{2} \lambda_{N-1}(G) ,$$

$$(13)$$

where P is the diagonal matrix such that $P(v, v) = p_v$. Now, (11) holds because W_1 is symmetric and $W_1^2 \preceq W_1$. Moreover, $P \operatorname{Lap}(G) P$ is also symmetric and, clearly, $P \operatorname{Lap}(G) P \succeq p_{\min}^2 \operatorname{Lap}(G)$, implying (12). Finally, (13) holds because $\lambda_{N-1}(G)$ is the smallest non-zero eigenvalue of $\operatorname{Lap}(G)$.

This choice of b, which is the best possible under the constraint that the gossip matrix is nonnegative, reveals that the regret is naturally controlled by the condition number of Lap(G).

The *p*-uniform case. We now derive a closed-form expression for ρ in the *p*-uniform case.

Theorem 5. If W_t is set according to (8), $b = 1/\lambda_1(G)$, then in the *p*-uniform case we have

$$\rho^{2} = 1 - \frac{2p^{2}}{\kappa(G)} \left(1 - \frac{1-p}{\lambda_{1}(G)} - \frac{p}{2\kappa(G)} \right)$$

From Theorem 1, we know that the expected network regret scales with $\frac{\rho}{1-\rho}$. Using Theorem 5 and some simple calculations (see appendix), we get

$$\frac{\rho}{1-\rho} \leq \frac{2\kappa(G)}{p^2}$$

Combining this with (5), we immediately get the following result.

Corollary 1. Assume each agent runs an instance of Gossip-FTRL with learning rate $\eta > 0$. If the gossip matrix W_t is chosen as in (8) with $b = 1/\lambda_1(G)$ and η is tuned with respect to p and N, the expected network regret can be bounded by

$$\mathbb{E}\left[R_T^{\text{net}}\right] = \mathcal{O}\left(\frac{\kappa(G)}{p}\min\left(\sqrt{N}, \frac{N^{1/4}}{\sqrt{p}}\right)\sqrt{T}\right) \quad (14)$$

for all $p \leq 1$.

This bound captures the intuition that bottlenecks in G (causing a small Fiedler value or a high condition number) negatively impact the regret due to a slower propagation of the information in the network.

To better visualize the dependence on the graph structure, we study specific graphs of particular practical importance. Specifically, we give results in the puniform case for cliques, strongly regular graphs, and grids (see Figure 1).

Clique. We have $\lambda_1(G) = \lambda_{N-1}(G) = N$ and

$$\rho^{2} = 1 - 2p^{2} + p^{2} \left(\frac{2(1-p)}{N} + p\right)$$

Strongly regular. Let *G* be strongly regular with parameters *k* (the degree of any node), *m* (the number of common neighbors for any two adjacent nodes), and *n* (the number of common neighbors for any two nonadjacent nodes). Then $\lambda_1(G) = k - s$, $\lambda_{N-1}(G) = k - r$, and

$$\rho^{2} \leq 1 - \frac{k - r}{k - s} p^{2},$$
where
$$\begin{cases} r = \frac{m - n + \sqrt{(m - n)^{2} + 4(k - n)}}{2}, \\ s = \frac{m - n - \sqrt{(m - n)^{2} + 4(k - n)}}{2}, \end{cases}$$

In particular, when G is the lattice graph, i.e. the graph with vertices $[M]^2$ and an edge between any two vertices in the same rows or columns (yielding k = 2M - 2, m = M - 2 and n = 2), $\rho \leq 1 - \frac{1}{2}p^2$.

2-dim grid. We have $\lambda_1(G) = 4 - 4\cos(\pi(M-1)/M)$ and $\lambda_{N-1}(G) = 2 - 2\cos(\pi/M)$, where $M = \sqrt{N}$ is the grid side length. Then

$$\rho^2 \le 1 - \frac{1 - \cos(\pi/M)}{2 - 2\cos(\pi(M-1)/M)}p^2$$



Figure 1: Empirical estimate $\hat{\rho}$ compared to ρ and the upper bound $\hat{\rho}_{up}$ (10) for $b = 1/\lambda_1(G)$ plotted as a function of $p \in [0, 1]$.

Note that $\frac{1-\cos(\pi/M)}{2-2\cos(\pi(M-1)/M)} \sim \frac{\pi^2}{4M^2}$, which goes to zero when $M \to \infty$.

Figure 1 shows the empirical behavior of ρ^2 for $b = 1/\lambda_1(G)$. The quantity $\hat{\rho}^2$ is the second eigenvalue of W_1^2 averaged over 1000 different draws of active agents, where each agent is activated with probability p ranging from 0 to 1. We also plot the exact value ρ^2 (Theorem 5) and its upper bound $\rho_{\rm up}^2$ (10).

Figure 1 reveals that for dense graphs (e.g., clique and lattice), ρ^2 decreases quickly as $p \to 1$, implying a better regret rate. For the clique we have $\rho = 0$, implying an expected regret rate of order \sqrt{T} , which is independent of N—see (5). On the other hand, in sparse graphs ρ may remain high. For example, in the grid $\rho > 0.9$ for all p. Note also that $\rho_{\rm up}^2$ approximates ρ^2 well, especially when p is small.

7 RANDOM EDGES

We now study a setting where, after agents are activated, edges between pairs of active agents are independently deleted with probability 1-q. More specification

ically, given a graph G = (V, E), the active graph $G_t = (S_t, E_t)$ at time t is defined by $\mathbb{P}((i, j) \in E_t) = q \mathbb{P}(i, j \in S_t) \mathbb{I}\{(i, j) \in E\}$. When $\mathbb{P}(i, j \in S_t) = 1$ for all distinct $i, j \in V$ we recover the model of Lei et al. (2020). In the p-uniform case, we write $G_t \sim \mathcal{G}(G, p, q)$. Note that G_1, G_2, \ldots is i.i.d. because S_1, S_2, \ldots is i.i.d.; moreover, if W_t is chosen as in (8), then W_1, W_2, \ldots is also an i.i.d. sequence. Using (5), we can prove the following result.

Corollary 2. Assume each agent runs an instance of Gossip-FTRL with learning rate $\eta > 0$. If the gossip matrix W_t is chosen as in (8) with $b = 1/\lambda_1(G)$, then

$$\rho^2 = 1 - \frac{2p^2q}{\kappa(G)} \left(1 - \frac{1 - pq}{\lambda_1(G)} - \frac{pq}{2\kappa(G)} \right)$$

By tuning η with respect to p and N, the expected network regret on G_1, G_2, \ldots drawn i.i.d. from $\mathcal{G}(G, p, q)$ can be bounded by

$$\mathbb{E}\left[R_T^{\text{net}}\right] = \mathcal{O}\left(\frac{\kappa(G)}{pq}\min\left(\sqrt{N}, \frac{N^{1/4}}{\sqrt{p}}\right)\sqrt{T}\right) \quad (15)$$

8 EXPERIMENTS

We empirically evaluate Gossip-FTRL on synthetic data and compare it with DOGD (Lei et al., 2020). While Gossip-FTRL can deal with arbitrary values of p and q, DOGD is designed for settings with p = 1 (agents are always active) and $0 < q \leq 1$ (edges of G are active with probability q). To run DOGD when p < 1 we feed a zero gradient vector to instances run by agents that are inactive on that round.

Our synthetic data are generated based on the distributed linear regression setting of Yuan et al. (2020). In particular, the agents' decision space \mathcal{X} is the 10dimensional Euclidean ball of radius 2 centered in the origin. The local loss functions are $\ell_t(v, \boldsymbol{x}) = \frac{1}{2} (\langle \boldsymbol{w}_t(v), \boldsymbol{x} \rangle - y_t(v) \rangle^2$ for all $v \in V$ and $\boldsymbol{x} \in \mathcal{X}$. The feature vectors $\boldsymbol{w}_t(v)$ are generated independently, by picking each coordinate independently and uniformly at random in [-1, 1]. The labels $y_t(v)$ are generated according to $y_t(v) = \varepsilon_t(v)$ for $1 \leq v < \lceil N/2 \rceil$ and $y_t(v) = \langle \boldsymbol{w}_t(v), \mathbf{1} \rangle + \varepsilon_t(v)$ for the remaining agents, where $\varepsilon_t(v)$ is independent Gaussian noise (zero mean and unit variance). Hence, the local losses of half of the agents are random noise.

Each of the following experiments is run with |V| = N = 36 and T = 1000. Plots are averages over 20 repetitions, where repetitions use the same labels and feature vectors and only agent (and possibly edge) activations are drawn afresh in each repetition. Both algorithms are tuned according to the theoretical specifications (ignoring constant factors):



Figure 2: Growth over T = 1000 steps of the network regret of Gossip-FTRL and DOGD on a clique and on a grid for N = 36 and for different choices of p, q.

we set $\eta = (p\min(pN,\sqrt{N})T)^{-1/2}$ for Gossip-FTRL (see Theorem 1) and $\eta = N^{-1/4}T^{-1/2}$ for DOGD.

Our experiments show that Gossip-FTRL performs consistently better than DOGD, although the difference is not huge. Both algorithms are surprisingly robust to sparsity induced by low values of q when G is dense (Figure 2a and Figure 2c). When G is sparse though, the regret goes up much quickly as q becomes smaller (Figure 2b and Figure 2d). Figure 3 shows the behavior of Gossip-FTRL and DOGD on a grid for pairs (p,q) in the set $\{0.4, 0.6, 0.8\}^2$. Figure 4 shows that, for Gossip-FTRL, R_T^{net} scales approximately with $\frac{1}{n^2}$ as predicted by (6)—at least for sufficiently small values of p—and DOGD exhibits a similar behavior. Finally, Figure 5 shows the impact of $\lambda_{N-1}(G)$ on the network regret of Gossip-FTRL. The regret decreases as $\lambda_{N-1}(G)$ is increased by adding more edges to the bottleneck between the two cliques.

9 OPEN PROBLEMS

There is a gap between our upper bounds and the lower bound of Theorem 3. When p = 1, a distributed algorithm using accelerated gossiping techniques matches the lower bound (Wan et al., 2024). It is unclear if the same techniques could be applied in our more general setting, where 1/N , to improve on our results.Finally, our bounds require tuning based on preliminary knowledge of <math>p in the p-uniform case, or p_{\min}, \overline{p} in the general case. It is unclear whether we could get similar results when this information is unavailable.



Figure 3: Network regret of Gossip-FTRL and DOGD after T = 1000 steps on a grid with N = 36.



Figure 4: Plot of $(R_T^{\text{net}})^{-1/2}$ for Gossip-FTRL on a clique for $p \in [0, 1]$ and T = 1000.



Figure 5: Network regret of Gossip-FTRL after T = 1000 steps when p = 0.5, q = 1, and G is made up by two cliques joined by a varying number of random edges.

Acknowledgements

This work was done when JA was research assistant at Università degli Studi di Milano, Italy. All the authors acknowledge the financial support from the FAIR (Future Artificial Intelligence Research) project, funded by the NextGenerationEU program within the PNRR-PE-AI scheme (M4C2, investment 1.3, line on Artificial Intelligence) and the One Health Action Hub (1H-Hub) within the PSR-LINEA6 (MUR, DM 737/2021). JA and NCB also acknowledge the financial support from the EU Horizon CL4-2021-HUMAN-01 research and innovation action under grant agreement 101070617, project ELSA (European Lighthouse on Secure and Safe AI).

References

- Amiri, M. M., Gündüz, D., Kulkarni, S. R., and Poor, H. V. (2021). Convergence of update aware device scheduling for federated learning at the wireless edge. *IEEE Transactions on Wireless Communications*, 20(6):3643–3658.
- Barik, S., Bapat, R. B., and Pati, S. (2015). On the laplacian spectra of product graphs. *Applicable Analysis and Discrete Mathematics*, pages 39–58.
- Bertsekas, D. P. and Tsitsiklis, J. N. (1991). Some aspects of parallel and distributed iterative algorithms—a survey. *Automatica*, 27(1):3–21.
- Boyd, S., Ghosh, A., Prabhakar, B., and Shah, D. (2005). Gossip algorithms: Design, analysis and applications. In *Proceedings IEEE 24th Annual Joint Conference of the IEEE Computer and Communications Societies.*, volume 3, pages 1653–1664. IEEE.
- Boyd, S., Ghosh, A., Prabhakar, B., and Shah, D. (2006). Randomized gossip algorithms. *IEEE trans*actions on information theory, 52(6):2508–2530.
- Cesa-Bianchi, N., Cesari, T., and Monteleoni, C. (2020). Cooperative online learning: Keeping your neighbors updated. In *Algorithmic learning theory*, pages 234–250. PMLR.
- Duchi, J. C., Agarwal, A., and Wainwright, M. J. (2011). Dual averaging for distributed optimization: Convergence analysis and network scaling. *IEEE Transactions on Automatic control*, 57(3):592–606.
- Eichner, H., Koren, T., McMahan, B., Srebro, N., and Talwar, K. (2019). Semi-cyclic stochastic gradient descent. In *International Conference on Machine Learning*, pages 1764–1773. PMLR.
- Gu, X., Huang, K., Zhang, J., and Huang, L. (2021). Fast federated learning in the presence of arbitrary device unavailability. Advances in Neural Information Processing Systems, 34:12052–12064.

- Hosseini, S., Chapman, A., and Mesbahi, M. (2013). Online distributed optimization via dual averaging. In 52nd IEEE Conference on Decision and Control, pages 1484–1489. IEEE.
- Hosseini, S., Chapman, A., and Mesbahi, M. (2016). Online distributed convex optimization on dynamic networks. *IEEE Transactions on Automatic Control*, 61(11):3545–3550.
- Lei, J., Yi, P., Hong, Y., Chen, J., and Shi, G. (2020). Online convex optimization over Erdos-Rényi random networks. Advances in neural information processing systems, 33:15591–15601.
- Mateos-Núnez, D. and Cortés, J. (2014). Distributed online convex optimization over jointly connected digraphs. *IEEE Transactions on Network Science* and Engineering, 1(1):23–37.
- Nedić, A. and Olshevsky, A. (2014). Distributed optimization over time-varying directed graphs. *IEEE Transactions on Automatic Control*, 60(3):601–615.
- Nedic, A. and Ozdaglar, A. (2009). Distributed subgradient methods for multi-agent optimization. *IEEE Transactions on Automatic Control*, 54(1):48–61.
- Nedic, A., Ozdaglar, A., and Parrilo, P. A. (2010). Constrained consensus and optimization in multiagent networks. *IEEE Transactions on Automatic Control*, 55(4):922–938.
- Orabona, F. (2019). A modern introduction to online learning. arXiv preprint arXiv:1912.13213.
- Raginsky, M., Kiarashi, N., and Willett, R. (2011). Decentralized online convex programming with local information. In *Proceedings of the 2011 American Control Conference*, pages 5363–5369. IEEE.
- Shi, C. and Shen, C. (2021). Federated multi-armed bandits. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 35, pages 9603–9611.
- Spielman, D. (2019). Spectral and algebraic graph theory. Yale lecture notes, draft of December, 4:47.
- Wan, Y., Wei, T., Song, M., and Zhang, L. (2024). Nearly optimal regret for decentralized online convex optimization. In *Proceedings of Thirty Seventh Conference on Learning Theory*, volume 247 of *Proceedings of Machine Learning Research*, pages 4862– 4888. PMLR.
- Wang, S. and Ji, M. (2022). A unified analysis of federated learning with arbitrary client participation. Advances in Neural Information Processing Systems, 35:19124–19137.
- Xiao, L. and Boyd, S. P. (2004). Fast linear iterations for distributed averaging. Syst. Control. Lett., 53(1):65–78.

- Yan, F., Sundaram, S., Vishwanathan, S., and Qi, Y. (2013). Distributed autonomous online learning: Regrets and intrinsic privacy-preserving properties. *IEEE Transactions on Knowledge and Data Engineering*, 25(11):2483–2493.
- Yan, Y., Niu, C., Ding, Y., Zheng, Z., Tang, S., Li, Q., Wu, F., Lyu, C., Feng, Y., and Chen, G. (2024). Federated optimization under intermittent client availability. *INFORMS Journal on Computing*, 36(1):185–202.
- Yang, T., Yi, X., Wu, J., Yuan, Y., Wu, D., Meng, Z., Hong, Y., Wang, H., Lin, Z., and Johansson, K. H. (2019). A survey of distributed optimization. *Annual Reviews in Control*, 47:278–305.
- Yuan, D., Proutiere, A., and Shi, G. (2020). Distributed online linear regressions. *IEEE Transac*tions on Information Theory, 67(1):616–639.
- Yuan, D., Proutiere, A., and Shi, G. (2021). Distributed online optimization with long-term constraints. *IEEE Transactions on Automatic Control*, 67(3):1089–1104.

A Additional related works

Distributed optimization (DO), now central to federated learning, dates back to the work of Bertsekas and Tsitsiklis (1991), originally applied to parallel computation. Much of the research in DO focuses on gossip algorithms, introduced by Boyd et al. (2005, 2006) to address the distributed averaging problem, especially in scenarios where communication is expensive. These algorithms involve randomly selecting a neighbor for information exchange, or *gossiping*. The concept later expanded to include weighted averaging of information from all neighbors using weights collected in a gossip matrix. Nedic et al. (2010) extended gossip methods to distributed optimization, combining projected gradient descent with gossip-based averaging of iterates. Typically, the convergence rate of gossip algorithms is inversely related to the spectral gap of the gossip matrix.

A key constraint frequently considered in distributed optimization is that the algorithm should be robust to random network topologies. This can arise not only from unstable communication channels (Nedić and Olshevsky, 2014), but randomization can also be leveraged to reduce communication costs while preserving performance (Lei et al., 2020). Other constraints, considered in the literature but less relevant to this work, include event-related communication and time delays (Yang et al., 2019). Recent advances in DO also concern accelerated gossip algorithms that allow for accelerated rates with respect to the number of agents (Wan et al., 2024).

In the online DOO setting, Yan et al. (2013) proposed a (sub)gradient descent algorithm with regret bounds of $\mathcal{O}(\sqrt{T})$ for the convex and $\mathcal{O}(\log T)$ for the strongly convex case. Hosseini et al. (2013) later introduced an online dual-averaging algorithm, also achieving $\mathcal{O}(\sqrt{T})$ regret for convex losses. Yuan et al. (2021) extended this to long-term constraints. Time varying graph networks were considered by Hosseini et al. (2016); Mateos-Núnez and Cortés (2014), who proved regret rates under the assumption that the union of communication networks over any m time steps is strongly connected. Lei et al. (2020) studied the special case where communication networks are Erdös-Rényi graphs, in which each edge has a probability q of existing at each round. They proposed a gradient descent algorithm and proved regret upper bounds for the convex and strongly convex case, also extending their result to the bandit feedback framework—see also (Shi and Shen, 2021).

In this work, we address the problem of device unavailability, a topic explored in federated learning from various angles. For example, availability patterns, such as diurnal cycles, can violate the assumption of data independence, as active agents may disproportionately represent certain populations (e.g., by geographic location) (Eichner et al., 2019; Amiri et al., 2021). Device unavailability has not been addressed in the context of DOO, except indirectly in (Hosseini et al., 2016), which focuses on time-varying graphs, thus tackling the case in which isolated devices are unavailable for communication. Our approach differs in that inactive agents do not have an associated loss function and do not contribute to the global loss. Raginsky et al. (2011) consider a notion of information structure replacing the communication network. However, their results are based on a specific linear structure and a horizon-dependent communication radius within which agents can freely exchange information.

B Preliminary results

Lemma 1 (Regret decomposition). The network regret

$$R_T^{\text{net}} = \sum_{t=1}^T \frac{1}{|S_t|} \sum_{v \in S_t} \ell_t^{\text{net}} \big(S_t, x_t(v) \big) - \min_{x \in \mathcal{X}} \sum_{t=1}^T \ell_t^{\text{net}}(S_t, x)$$

can be decomposed in the following way

$$R_T^{\text{net}} \leq \underbrace{3\sum_{t=1}^T \sum_{u \in V} \frac{\mathbb{I}\left\{u \in S_t\right\}}{|S_t|} L \left\|x_t(u) - y_t\right\|}_{(A)} + \underbrace{\sum_{t=1}^T \sum_{v \in V} \frac{\mathbb{I}\left\{v \in S_t\right\}}{|S_t|} \left\langle \nabla \ell_t(x_t(v), v), y_t - x^* \right\rangle}_{(B)},$$

for any $y_t \in \mathcal{X}$, with the convention that 0/0 = 0 when $|S_t| = 0$.

This will be particularly useful when setting y_t as the prediction of a omniscient agent knowing the gradients of all incurred losses up to time t - 1. In this case, Term (B) is the part of the regret related to the loss incurred by the prediction of the omniscient agent, and Term (A) is the part of the regret related to the deviations with respect to these predictions.

Proof. By definition of the regret,

$$\begin{split} R_T^{\text{net}} &= \sum_t^T \sum_{u \in V} \sum_{v \in V} \frac{1}{|S_t|^2} \left(\ell_t(x_t(u), v) - \ell_t(x^*, v) \right) \mathbb{I} \Big\{ u \in S_t \Big\} \mathbb{I} \Big\{ v \in S_t \Big\} \\ &= \sum_{t=1}^T \sum_{u \in V} \sum_{v \in V} \frac{1}{|S_t|^2} \left(\ell_t(x_t(u), v) - \ell_t(y_t, v) + \ell_t(y_t, v) - \ell_t(x^*, v) \right) \times \mathbb{I} \Big\{ u \in S_t \Big\} \mathbb{I} \Big\{ v \in S_t \Big\} \\ &\leq \sum_{t=1}^T \sum_{u \in V} \sum_{v \in V} \frac{1}{|S_t|^2} \left(L \left\| x_t(u) - y_t \right\| + \ell_t(y_t, v) - \ell_t(x^*, v) \right) \times \mathbb{I} \Big\{ u \in S_t \Big\} \mathbb{I} \Big\{ v \in S_t \Big\} \,, \end{split}$$

because $\ell_t(\cdot, v)$ is *L*-Lipschitz over the set \mathcal{X} w.r.t the norm $\|\cdot\|$, i.e. $|\ell_t(x, v) - \ell_t(y, v)| \leq L \|x - y\|, \forall x, y \in X$. Next, because we need to introduce individual gradients, we add and remove each $\ell_t(x_t, v)$:

$$\begin{split} R_T^{\text{net}} &\leq \sum_{t=1}^T \sum_{u \in V} \sum_{v \in V} \left(L \left\| x_t(u) - y_t \right\| + \ell_t(y_t, v) - \ell_t(x_t(v), v) + \ell_t(x_t(v), v) - \ell_t(x^*, v) \right) \times \frac{1}{|S_t|^2} \mathbb{I} \left\{ u \in S_t \right\} \mathbb{I} \left\{ v \in S_t \right\} \\ &\leq \sum_{t=1}^T \sum_{u \in V} \sum_{v \in V} \left(L \left\| x_t(u) - y_t \right\| + L \left\| x_t(v) - y_t \right\| + \ell_t(x_t(v), v) - \ell_t(x^*, v) \right) \times \frac{1}{|S_t|^2} \mathbb{I} \left\{ u \in S_t \right\} \mathbb{I} \left\{ v \in S_t \right\}, \end{split}$$

where we used again the Lipschitzness of the loss functions. Then by convexity of $\ell_t(\cdot, v)$,

$$R_T^{\text{net}} \leq \sum_{t=1}^T \sum_{u \in V} \sum_{v \in V} \frac{1}{|S_t|^2} \left(L \, \|x_t(u) - y_t\| + L \, \|x_t(v) - y_t\| + \langle \nabla \ell_t(x_t(v), v), x_t(v) - x^* \rangle \right) \\ \times \mathbb{I} \Big\{ u \in S_t \Big\} \mathbb{I} \Big\{ v \in S_t \Big\},$$

which can be rewritten as

$$\begin{split} R_T^{\text{net}} &\leq \sum_{t=1}^T \sum_{u \in V} \frac{\mathbb{I}\left\{u \in S_t\right\}}{|S_t|} L \left\|x_t(u) - y_t\right\| + \sum_{t=1}^T \sum_{v \in V} \frac{\mathbb{I}\left\{v \in S_t\right\}}{|S_t|} L \left\|x_t(v) - y_t\right\| \\ &+ \sum_{t=1}^T \sum_{v \in V} \frac{\mathbb{I}\left\{v \in S_t\right\}}{|S_t|} \left\langle \nabla \ell_t(x_t(v), v), x_t(v) - x^* \right\rangle \\ &= 2 \sum_{t=1}^T \sum_{u \in V} \frac{\mathbb{I}\left\{u \in S_t\right\}}{|S_t|} L \left\|x_t(u) - y_t\right\| + \sum_{t=1}^T \sum_{v \in V} \frac{\mathbb{I}\left\{v \in S_t\right\}}{|S_t|} \left\langle \nabla \ell_t(x_t(v), v), x_t(v) - y_t + y_t - x^* \right\rangle \\ &\leq 2 \sum_{t=1}^T \sum_{u \in V} \frac{\mathbb{I}\left\{u \in S_t\right\}}{|S_t|} L \left\|x_t(u) - y_t\right\| + \sum_{t=1}^T \sum_{v \in V} \frac{\mathbb{I}\left\{v \in S_t\right\}}{|S_t|} L \left\|x_t(v) - y_t\right\| \\ &+ \sum_{t=1}^T \sum_{v \in V} \frac{\mathbb{I}\left\{v \in S_t\right\}}{|S_t|} \left\langle \nabla \ell_t(x_t(v), v), y_t - x^* \right\rangle, \end{split}$$

again by the Lipschitzness of the losses. Finally,

$$R_{T}^{\text{net}} \leq \underbrace{3\sum_{t=1}^{T}\sum_{u \in V} \frac{\mathbb{I}\left\{u \in S_{t}\right\}}{|S_{t}|} L \|x_{t}(u) - y_{t}\|}_{(A)} + \underbrace{\sum_{t=1}^{T}\sum_{v \in V} \frac{\mathbb{I}\left\{v \in S_{t}\right\}}{|S_{t}|} \left\langle \nabla \ell_{t}(x_{t}(v), v), y_{t} - x^{*} \right\rangle}_{(B)}$$
(16)

concluding the proof.

ce

Lemma 2. Assuming that for k = 1...T, W_k are doubly stochastic matrices and i.i.d., we have, $\forall v \in V$, $\forall s, t \in [T]$ such that t > s,

$$\mathbb{E}\left[\left(W_{t}\cdots W_{s+1}e_{v}-\frac{1}{N}\right)^{T}\left(W_{t}\cdots W_{s+1}e_{v}-\frac{1}{N}\right)\right] \leq e_{v}^{T}e_{v}\left\|\mathbb{E}[W_{1}W_{1}^{\top}]-\frac{1}{N}\mathbf{1}\mathbf{1}^{\top}\right\|_{\mathrm{op}}^{t-s} \leq \lambda_{2}(\mathbb{E}[W_{1}W_{1}^{\top}])^{t-s}.$$
(17)

This can be derived exactly as in the proof of (Lei et al., 2020, Lemma 2). For completeness, we provide a quick justification.

Proof. Let $\widetilde{W}_k = W_k - \frac{1}{N} \mathbf{1} \mathbf{1}^\top$ and assume

$$\mathbb{E}\left[\left\|W_{k-1}\cdots W_{s+1}e_v - \frac{\mathbf{1}}{N}\right\|_2^2\right] \le e_v^T e_v \left\|\mathbb{E}[W_1 W_1^\top] - \frac{1}{N} \mathbf{1} \mathbf{1}^\top\right\|_{\mathrm{op}}^{k-s-1} \qquad \text{for some } k-1 > s$$

Let \mathcal{F}_{k-1} be the σ -algebra generated by all random events up to time k-1. We have that

$$\begin{split} \mathbb{E}\left[\left\|W_{k}^{\top}\cdots W_{s+1}^{\top}e_{v}-\frac{1}{N}\right\|_{2}^{2}\right] &= \mathbb{E}\left[e_{v}^{T}\widetilde{W}_{s+1}^{\top}\cdots \widetilde{W}_{k-1}^{\top}\widetilde{W}_{k}^{\top}\widetilde{W}_{k}\widetilde{W}_{k-1}\cdots \widetilde{W}_{s+1}e_{v}\right] \\ &= \mathbb{E}\left[e_{v}^{T}\widetilde{W}_{s+1}^{\top}\cdots \widetilde{W}_{k-1}^{\top}\mathbb{E}[\widetilde{W}_{k}^{\top}\widetilde{W}_{k}\mid\mathcal{F}_{k-1}]\widetilde{W}_{k-1}\cdots \widetilde{W}_{s+1}e_{v}\right] \\ &= \mathbb{E}\left[e_{v}^{T}\widetilde{W}_{s+1}^{\top}\cdots \widetilde{W}_{k-1}^{\top}\mathbb{E}[\widetilde{W}_{1}^{\top}\widetilde{W}_{1}]\widetilde{W}_{k-1}\cdots \widetilde{W}_{s+1}e_{v}\right] \quad (by independence of W_{k}) \\ &\leq \left\|\mathbb{E}[W_{1}W_{1}^{\top}]-\frac{1}{N}\mathbf{1}\mathbf{1}^{\top}\right\|_{op}e_{v}^{T}e_{v}\left\|\mathbb{E}[W_{1}W_{1}^{\top}]-\frac{1}{N}\mathbf{1}\mathbf{1}^{\top}\right\|_{op}^{k-s-1} \\ &\leq \lambda_{2}(\mathbb{E}[W_{1}W_{1}^{\top}])e_{v}^{T}e_{v}\left\|\mathbb{E}[W_{1}W_{1}^{\top}]-\frac{1}{N}\mathbf{1}\mathbf{1}^{\top}\right\|_{op}^{k-s-1} \end{split}$$

which by induction, suffices to prove Equation (17).

C Proof of Theorem 1

Theorem 1. Assume each agent runs an instance of Gossip-FTRL with learning rate $\eta > 0$ and i.i.d gossip matrices W_t . Then, the expected network regret can be bounded by

$$\mathbb{E}\left[R_T^{\text{net}}\right] \le \frac{ND^2}{\eta} + \frac{L^2}{\mu} \eta \left(\bar{p}N + \bar{p}(1-\bar{p}) - \sigma_p^2 + 6 + 3\min\left(\bar{p}N,\sqrt{N}\right)\frac{\rho}{1-\rho}\right) T,$$
(4)

where $\rho = \sqrt{\lambda_2(\mathbb{E}[W_1W_1^{\top}])}$. In the p-uniform case, we have

$$\mathbb{E}[R_T^{\text{net}}] \le \frac{D^2}{p\eta} + \frac{L^2}{\mu} \eta \left(8 + 3\min\left(pN,\sqrt{N}\right)\frac{\rho}{1-\rho}\right) T .$$
(5)

If, in addition,
$$\eta = \frac{(D/L)\sqrt{\mu}}{2\sqrt{2p\min(pN,\sqrt{N})T}}$$
, then

$$\mathbb{E}[R_T^{\text{net}}] \leq 2\sqrt{2}\frac{DL}{\sqrt{\mu}}\frac{1}{1-\rho}\sqrt{T}$$

$$\times \begin{cases} \sqrt{N} & \text{if } p \in [1/N, 1/\sqrt{N}] \\ N^{1/4}/\sqrt{p} & \text{otherwise} \end{cases}$$
(6)

Proof. The proof relies on the use of an omniscient agent knowing the gradients of all incurred losses up to time t-1.

Let us define the quantities \bar{z}_t and \bar{g}_t

$$\bar{g}_t = \frac{1}{N} \sum_{v \in V} g_t(x_t(v), v) = \sum_{v \in V} \frac{\mathbb{1}(v \in S_t)}{N} \nabla \ell_t(x_t(v), v)$$
$$\bar{z}_t = \frac{1}{N} \sum_{v \in V} z_t(v).$$

 -	-	-	

Then the decision of the omniscient agent is defined as

$$\bar{x}_t = \operatorname{argmin}_{x \in X} \left\{ \langle \bar{z}_t, x \rangle + \frac{1}{\eta} \psi(x) \right\}.$$

Note that

$$\bar{z}_{t+1} = \bar{z}_t + \bar{g}_t. \tag{18}$$

The proof of the theorem relies on Lemma 1, where y_t is set to \bar{x}_t .

$$R_T^{\text{net}} \le \underbrace{3\sum_{t=1}^T \sum_{u \in V} \frac{\mathbb{I}\{u \in S_t\}}{|S_t|} L \|x_t(u) - \bar{x}_t\|}_{(A)} + \underbrace{\sum_{t=1}^T \sum_{v \in V} \frac{\mathbb{I}\{v \in S_t\}}{|S_t|} \langle \nabla \ell_t(x_t(v), v), \bar{x}_t - x^* \rangle}_{(B)}.$$
(19)

We start by analyzing the general case. Let us focus on Term (B) first.

$$\begin{split} \mathbb{E}\left[\sum_{t=1}^{T}\sum_{v\in V}\frac{\mathbb{I}\left\{v\in S_{t}\right\}}{|S_{t}|}\left\langle\nabla\ell_{t}(x_{t}(v),v),\bar{x}_{t}-x^{*}\right\rangle\right] &=\sum_{t=1}^{T}\sum_{v\in V}\mathbb{E}\left(\frac{\mathbb{I}\left\{v\in S_{t}\right\}}{1+\sum_{u\in\mathcal{V}\setminus v}\mathbb{I}\left\{u\in S_{t}\right\}}\right)\mathbb{E}\left[\left\langle\nabla\ell_{t}(x_{t}(v),v),\bar{x}_{t}-x^{*}\right\rangle\right] \\ &=\sum_{t=1}^{T}\sum_{v\in V}p_{v}c_{v}\mathbb{E}\left[\left\langle\nabla\ell_{t}(x_{t}(v),v),\bar{x}_{t}-x^{*}\right\rangle\right] \\ &\leq \max_{v\in\mathcal{V}}c_{v}\sum_{t=1}^{T}\sum_{v\in V}p_{v}\mathbb{E}\left[\left\langle\nabla\ell_{t}(x_{t}(v),v),\bar{x}_{t}-x^{*}\right\rangle\right], \end{split}$$

where $c_v = \mathbb{E}\left(\frac{1}{1+\sum_{u\in\mathcal{V}\setminus v}\mathbb{I}\left\{u\in S_t\right\}}\right) \leq 1$. Recall that $\widetilde{T} = (1 - \prod_{v\in\mathcal{V}}(1-p_v))T$ denotes the expected number of time steps when there is at least one active agent.

In the *p*-uniform case for example, $c_v = \frac{\tilde{T}}{T_p N} \leq 1$. This holds because, on the one hand,

$$\sum_{v \in V} \mathbb{E}\left[\frac{\mathbb{I}\left\{v \in S_t\right\}}{|S_t|}\right] = \sum_{v \in V} pc_v = Npc_v$$

due to all c_v being equal. On the other hand,

$$\sum_{v \in V} \mathbb{E}\left[\frac{\mathbb{I}\left\{v \in S_t\right\}}{|S_t|}\right] = \mathbb{P}\left(S_t \neq \emptyset\right) = \frac{\widetilde{T}}{T}$$

Since \bar{x}_t are the predictions of FTRL on linear losses $\langle \bar{g}_t, \cdot \rangle$, we know from standard FTRL analysis (Orabona, 2019, Corollary 7.9),

$$\frac{1}{N}\sum_{t=1}^{T}\sum_{v\in V} \langle \nabla \ell_t(x_t(v), v), \bar{x}_t - x^* \rangle \, \mathbb{I}\big\{v \in S_t\big\} \le \frac{\psi(x^*)}{\eta} + \frac{L^2}{\mu} \sum_{t=1}^{T} \eta \frac{|S_t|^2}{N^2} \tag{20}$$

which by taking expectation and using the independence of S_t and $x_t(v)$ leads to

$$\mathbb{E}\left[\sum_{t=1}^{T}\sum_{v\in V}p_{v}\left\langle\nabla\ell_{t}(x_{t}(v),v),\bar{x}_{t}-x^{*}\right\rangle\right] \leq \frac{\psi(x^{*})N}{\eta} + \frac{L^{2}}{\mu}\eta\sum_{t=1}^{T}\left(N\bar{p}+\bar{p}(1-\bar{p})-\sigma_{p}^{2}\right)$$

where $\bar{p} = \frac{1}{N} \sum_{v \in \mathcal{V}} p_v$ and $\sigma_p^2 = \frac{1}{N} \sum_{v \in \mathcal{V}} p_v^2 - \bar{p}^2$.

This holds because $\mathbb{E}[|S_t|^2] = \mathbb{E}[|S_t|]^2 + \operatorname{Var}(|S_t|)$, and $|S_t|$ is the sum of independent Bernoulli of parameter p_v , so that $\operatorname{Var}(|S_t|) = \sum_{v \in \mathcal{V}} p_v(1-p_v)$, which can also be written as $N\bar{p}(1-\bar{p}) - N\sigma_p^2$. Hence

$$\mathbb{E}\left[\sum_{t=1}^{T}\sum_{v\in V}\frac{\mathbb{I}\left\{v\in S_{t}\right\}}{|S_{t}|}\left\langle\nabla\ell_{t}(x_{t}(v),v),\bar{x}_{t}-x^{*}\right\rangle\right] \leq \max c_{v}\left(\frac{\psi(x^{*})N}{\eta}+\frac{L^{2}}{\mu}\sum_{t=1}^{T}\eta(N\bar{p}+\bar{p}(1-\bar{p})-\sigma_{p}^{2})\right)$$
$$\leq \left(\frac{\psi(x^{*})N}{\eta}+\frac{L^{2}}{\mu}\sum_{t=1}^{T}\eta(N\bar{p}+\bar{p}(1-\bar{p})-\sigma_{p}^{2})\right).$$

Regarding Term (A), since

$$\bar{x}_t = \operatorname{argmin}_{x \in X} \left\{ \langle \bar{z}_t, x \rangle + \frac{1}{\eta} \psi(x) \right\}$$

and

$$x_t(v) = \operatorname{argmin}_{x \in X} \left\{ \langle z_t(v), x \rangle + \frac{1}{\eta} \psi(x) \right\}$$

we have

$$\|x_t(v) - \bar{x}_t\| \le \eta/\mu \, \|z_t(v) - \bar{z}_t\|_* , \qquad (21)$$

,

thanks to the duality between strong convexity and smoothness (Orabona, 2019, Theorem 6.11). For any $t \in [T]$ and any $v \in [N]$, we have

$$Z_{t+1} = W_t Z_t + \Gamma_t = W_t W_{t-1} Z_{t-1} + W_t \Gamma_{t-1} + \Gamma_t = \sum_{s=1}^{t-1} W_t \cdots W_{s+1} \Gamma_s + \Gamma_t .$$

Simultaneously, we have

$$\bar{z}_{t+1} = \frac{1}{N} \sum_{s=1}^{t} \mathbf{1}^\top \Gamma_s,$$

so that

$$Z_{t+1} - \mathbf{1}\bar{z}_{t+1} = \sum_{s=1}^{t} W_t \cdots W_{s+1}\Gamma_s + \Gamma_t - \frac{1}{N}\mathbf{1}\mathbf{1}^{\top}\Gamma_s$$
$$= \sum_{s=1}^{t-1} \left[W_t \cdots W_{s+1} - \frac{1}{N}\mathbf{1}\mathbf{1}^{\top} \right]\Gamma_s + \Gamma_t - \frac{1}{N}\mathbf{1}\mathbf{1}^{\top}\Gamma_t$$

In turn,

$$z_{t+1}(v) - \bar{z}_{t+1} = (Z_{t+1} - \mathbf{1}\bar{z}_{t+1})^T e_v$$

= $\sum_{s=1}^{t-1} \Gamma_s^T \left[W_t \cdots W_{s+1} - \frac{1}{N} \mathbf{1} \mathbf{1}^\top \right]^T e_v + \Gamma_t^\top (I - \frac{1}{N} \mathbf{1} \mathbf{1}^\top) e_v,$

so that we can compute :

$$\begin{aligned} \|z_{t+1}(v) - \bar{z}_{t+1}\|_{*} &= \left\| \sum_{s=0}^{t-1} \left(\sum_{u=1}^{N} \left([W_{t} \cdots W_{s+1}]_{u,v} - \frac{1}{N} \right) g_{s}(x_{s}(u), u) \right) + g_{t}(x_{t}(v), v) - \bar{g}_{t} \right\|_{*} \\ &\leq \left\| \sum_{s=0}^{t-1} \left(\sum_{u=1}^{N} \left([W_{t} \cdots W_{s+1}]_{u,v} - \frac{1}{N} \right) g_{s}(x_{s}(u), u) \right) \right\|_{*} + \|g_{t}(x_{t}(v), v) - \bar{g}_{t}\|_{*} \\ &\leq \left\| \sum_{s=0}^{t-1} \left(\sum_{u=1}^{N} \left([W_{t} \cdots W_{s+1}]_{u,v} - \frac{1}{N} \right) g_{s}(x_{s}(u), u) \right) \right\|_{*} + \|g_{t}(x_{t}(v), v) - \bar{g}_{t}\|_{*} \\ &\leq \sum_{s=0}^{t-1} \sum_{u=1}^{N} \left\| [W_{t} \cdots W_{s+1}]_{u,v} - \frac{1}{N} \right\| \|g_{s}(x_{s}(u), u)\|_{*} + \|g_{t}(x_{t}(v), v) - \bar{g}_{t}\|_{*} \\ &\leq \sum_{s=0}^{t-1} \sum_{u=1}^{N} \max_{u \in V} \left| [W_{t} \cdots W_{s+1}]_{u,v} - \frac{1}{N} \right\| \|g_{s}(x_{s}(u), u)\|_{*} + \|g_{t}(x_{t}(v), v) - \bar{g}_{t}\|_{*} \end{aligned}$$

which yields

$$\|z_{t+1}(v) - \bar{z}_{t+1}\|_* \le \sum_{s=0}^{t-1} |S_s| L \left\| W_t \cdots W_{s+1} e_v - \frac{1}{N} \mathbf{1} \right\|_{\infty} + 2L$$
(22)

Because $\|g_s(x_s(u), u)\|_* \leq \mathbb{I}\{u \in S_t\}L$ and $\sum_{u \in V}^N \mathbb{I}\{u \in S_t\} = |S_t|$. By taking the expectation on each side,

$$\mathbb{E}[\|z_{t+1}(v) - \bar{z}_{t+1}\|_*] \le \sum_{s=0}^{t-1} \bar{p}NL\mathbb{E}\left[\left\|W_t \cdots W_{s+1}e_v - \frac{1}{N}\mathbf{1}\right\|_{\infty}\right] + 2L$$
$$\le \sum_{s=0}^{t-1} \bar{p}NL\mathbb{E}\left[\left\|W_t \cdots W_{s+1}e_v - \frac{1}{N}\mathbf{1}\right\|_2\right] + 2L.$$

At the same time, we also have

$$\mathbb{E}[\|z_{t+1}(v) - \bar{z}_{t+1}\|_*] \le \sum_{s=1}^{t-1} \sqrt{N} L \mathbb{E}\left[\left\|W_t \cdots W_{s+1} e_v - \frac{1}{N} \mathbf{1}\right\|_2\right] + 2L,$$

because

$$\|z_{t+1}(v) - \bar{z}_{t+1}\|_{*} \leq \left\|\sum_{s=0}^{t-1} \sum_{u=1}^{N} \left([W_{t} \cdots W_{s+1}]_{u,v} - \frac{1}{N} \right) g_{s}(x_{s}(u), u) \right\|_{*} + \|g_{t}(x_{t}(v), v) - \bar{g}_{t}\|_{*}$$

$$\leq \sum_{s=0}^{t-1} \sum_{u=1}^{N} \left\| [W_{t} \cdots W_{s+1}]_{u,v} - \frac{1}{N} \right\| \max_{u \in V} \|g_{s}(x_{s}(u), u)\|_{*} + 2L$$

$$= \sum_{s=0}^{t-1} \left\| W_{t} \cdots W_{s+1}e_{v} - \frac{1}{N}\mathbf{1} \right\|_{1} \max_{u \in V} \|g_{s}(x_{s}(u), u)\|_{*} + 2L$$

$$\leq \sum_{s=0}^{t-1} \sqrt{N} \left\| W_{t} \cdots W_{s+1}e_{v} - \frac{1}{N}\mathbf{1} \right\|_{2} \max_{u \in V} \|g_{s}(x_{s}(u), u)\|_{*} + 2L$$

$$(23)$$

Hence, combing the above two inequalities on $||z_{t+1}(v) - \bar{z}_{t+1}||_*$ with Equation (21),

$$\mathbb{E}\left[\sum_{t=1}^{T}\sum_{u\in\mathcal{V}}\frac{1}{|\mathcal{S}_t|}\mathbb{1}(u\in\mathcal{S}_t)L\|x_t(u)-\bar{x}_t\|\right] \le \eta \frac{L^2}{\mu} \left(2+\min(\bar{p}N,\sqrt{N})\frac{\rho}{1-\rho}\right)\widetilde{T}.$$
(24)

In turn,

$$\mathbb{E}[R_T^{\text{net}}] \le \frac{D^2 N}{\eta} + \frac{L^2}{\mu} \eta \sum_{t=1}^T \left(6 + (N\bar{p} + \bar{p}(1-\bar{p}) + \sigma_p^2)T/\tilde{T} + 3\min(\bar{p}N,\sqrt{N})\frac{\rho}{1-\rho} \right) \tilde{T}.$$

Consequently

$$\mathbb{E}[R_T^{\text{net}}] \le \frac{D^2 N}{\eta} + \frac{L^2}{\mu} \eta \sum_{t=1}^T \left(6 + \frac{\bar{p}N + \bar{p}(1-\bar{p}) - \sigma_p^2}{p_{\min}} + 3\min(\bar{p}N,\sqrt{N})\frac{\rho}{1-\rho} \right) \widetilde{T}.$$

We also have

$$\mathbb{E}\left[R_T^{\text{net}}\right] \le \frac{D^2 N}{\eta} + \frac{L^2}{\mu} \eta \sum_{t=1}^T \left(6 + (N\bar{p} + \bar{p}(1-\bar{p}) + \sigma_p^2) + 3\min(\bar{p}N, \sqrt{N})\frac{\rho}{1-\rho}\right) T,$$

which is less tight in general but sufficient with the assumption that $\sum_{v \in V} p_v \ge 1$. This directly yields Equation (4)

We now turn to the *p*-uniform case. The refinement in this case is due to the fact that we can compute c_v . This makes it possible to refine our bound of Term (*B*). Specifically, we are interested in the expectation of Term (*B*),

$$\begin{split} \mathbb{E}\left[\sum_{t=1}^{T}\sum_{v\in V}\frac{\mathbb{I}\left\{v\in S_{t}\right\}}{|S_{t}|}\left\langle\nabla\ell_{t}(x_{t}(v),v),\bar{x}_{t}-x^{*}\right\rangle\right] &=\sum_{t=1}^{T}\sum_{v\in V}\mathbb{E}\left[\frac{\mathbb{I}\left\{v\in S_{t}\right\}}{|S_{t}|}\right]\mathbb{E}\left[\left\langle\nabla\ell_{t}(x_{t}(v),v),\bar{x}_{t}-x^{*}\right\rangle\right] \\ &=\sum_{t=1}^{T}\sum_{v\in V}\frac{1-(1-p)^{N}}{N}\mathbb{E}\left[\left\langle\nabla\ell_{t}(x_{t}(v),v),\bar{x}_{t}-x^{*}\right\rangle\right] \\ &=\frac{1-(1-p)^{N}}{N}\mathbb{E}\left[\sum_{t=1}^{T}\sum_{v\in V}\left\langle\nabla\ell_{t}(x_{t}(v),v),\bar{x}_{t}-x^{*}\right\rangle\right] \\ &\leq \frac{\widetilde{T}}{TN}\mathbb{E}\left[\sum_{t=1}^{T}\sum_{v\in V}\left\langle\nabla\ell_{t}(x_{t}(v),v),\bar{x}_{t}-x^{*}\right\rangle\right], \end{split}$$

where the second inequality comes from the independence of S_t and \bar{x}_t (whose update only depends on the history) and $x_t(v)$.

Since \bar{x}_t are the predictions of FTRL on linear losses $\langle \bar{g}_t, \cdot \rangle$, we know

$$\frac{1}{N} \sum_{t=1}^{T} \sum_{v \in V} \langle \nabla \ell_t(x_t(v), v), \bar{x}_t - x^* \rangle \, \mathbb{I} \big\{ v \in S_t \big\} \le \frac{\psi(x^*)}{\eta} + \frac{L^2}{\mu} \sum_{t=1}^{T} \eta |S_t|^2 / N^2$$

which by similar arguments yields

$$p\mathbb{E}\left[\sum_{t=1}^{T}\sum_{v\in V} \left\langle \nabla \ell_t(x_t(v), v), \bar{x}_t - x^* \right\rangle \right] \le \frac{\psi(x^*)N}{\eta} + \frac{L^2}{\mu} \sum_{t=1}^{T} \eta Np + p(1-p).$$

Hence

$$\mathbb{E}\left[\sum_{t=1}^{T}\sum_{v\in V}\frac{\mathbb{I}\left\{v\in S_{t}\right\}}{|S_{t}|}\left\langle\nabla\ell_{t}(x_{t}(v),v),\bar{x}_{t}-x^{*}\right\rangle\right] \leq \frac{\widetilde{T}}{T}\left(\frac{\psi(x^{*})}{\eta p}+\frac{L^{2}}{\mu}\sum_{t=1}^{T}\eta(1+(1-p)/N)\right),$$
(25)

which concludes our bound of the expectation of Term (B).

The analysis of Term (A) is unchanged for the case of uniform p_v , and yields:

$$\mathbb{E}\left[\sum_{t=1}^{T}\sum_{u\in\mathcal{V}}\frac{1}{|\mathcal{S}_t|}\mathbb{1}(u\in\mathcal{S}_t)L\|x_t(u)-\bar{x}_t\|\right] \le \eta \frac{L^2}{\mu}\min(Np,\sqrt{N})\frac{\rho}{1-\rho}\widetilde{T}.$$
(26)

Combining with Equation (25), we have

$$\begin{split} \mathbb{E}\big[R_T^{\text{net}}\big] &\leq \frac{\widetilde{T}}{T} \left(\frac{\psi(x^*)}{\eta p}\right) + \frac{L^2}{\mu} \eta \left(6 + 1 + (1-p)/N + 3\min(Np,\sqrt{N})\frac{\rho}{1-\rho}\right) \widetilde{T} \\ &\leq \left(1 - (1-p)^N\right) \left(\frac{\psi(x^*)}{\eta p}\right) + \frac{L^2}{\mu} \eta \left(8 + 3\min(Np,\sqrt{N})\frac{\rho}{1-\rho}\right) \widetilde{T} \\ &\leq \frac{D^2\min(1,Np)}{\eta p} + \frac{L^2}{\mu} \eta \left(8 + 3\min(Np,\sqrt{N})\frac{\rho}{1-\rho}\right) \widetilde{T} \,. \end{split}$$

With the assumption that $\sum_{v \in V} p_v \ge 1$, this easily yields Equation (5):

$$\mathbb{E}[R_T^{\text{net}}] \le \frac{D^2}{\eta p} + \frac{L^2}{\mu} \eta \left(8 + 3\min(Np, \sqrt{N})\frac{\rho}{1-\rho}\right) T.$$

Finally, Equation (6) follows from simple computations.

D Proof of Theorem 2

D.1 Preliminary result

The main difference between the proof of the bound in expectation and that of the high probability bound is the use of the following Lemma to bound the deviation between $W_t \cdots W_{s+1}$ and $\frac{1}{N} \mathbf{1} \mathbf{1}^\top$.

Lemma 3. Assuming that for k = 1...T, W_k are doubly stochastic matrices and i.i.d., we have, $\forall v \in V$, $\forall s, t \in [T]$ such that t > s,

$$\mathbb{P}\left(\left\|W_t \cdots W_{s+1}e_v - \frac{1}{N}\mathbf{1}\right\|_2 \ge \epsilon\right) \le \frac{\lambda_2(\mathbb{E}[W^2])^{t-s}}{\epsilon^2}.$$

When $t-s \geq \frac{3\log \epsilon^{-1}}{\log \lambda_2 [W^2]^{-1}} = t^*$, we have

$$\mathbb{P}\left(\left\|W_t \cdots W_{s+1}e_v - \frac{1}{N}\mathbf{1}\right\|_2 \ge \epsilon\right) \le \epsilon$$

This lemma is from Boyd et al. (2006). We provide a proof for completeness.

Proof. By applying Markov's inequality we have

$$\mathbb{P}\left(\left\|W_t \cdots W_{s+1}e_v - \frac{1}{N}\mathbf{1}\right\|_2 \ge \epsilon\right) \le \frac{\mathbb{E}\left(\left\|W_t \cdots W_{s+1}e_v - \frac{1}{N}\mathbf{1}\right\|_2^2\right)}{\epsilon^2}$$

Denoting by $\widetilde{W}_k = W_k - \frac{1}{N} \mathbf{1} \mathbf{1}^\top$, we need to prove that $\mathbb{E}\left(\left\|W_t \cdots W_{s+1} e_v - \frac{1}{N} \mathbf{1}\right\|_2^2\right)$ is bounded by $\lambda_2(\mathbb{E}[W^2])^{t-s}$. This is done by using Lemma 2.

D.2 Proof of Theorem 2

Theorem 2. Assume each agent runs an instance of Gossip-FTRL with learning rate $\eta > 0$. Then, with probability $1 - \delta$, the network regret is bounded by

$$\begin{aligned} R_T^{\text{net}} &\leq N\left(\frac{D^2}{\eta} + \frac{L^2}{\mu}\eta T\right) \\ &+ 3\eta T N \frac{L^2}{\mu} \left(\frac{3}{1-\rho^2}\log\frac{NT^2}{\delta} + 3\right) \;. \end{aligned}$$

Proof. We have

$$R_T^{\text{net}} \le \underbrace{3\sum_{t=1}^T \sum_{u \in V} \frac{\mathbb{I}\{u \in S_t\}}{|S_t|} L \, \|x_t(u) - \bar{x}_t\|}_{(A)} + \underbrace{\sum_{t=1}^T \sum_{v \in V} \frac{\mathbb{I}\{v \in S_t\}}{|S_t|} \left< \nabla \ell_t(x_t(v), v), \bar{x}_t - x^* \right>}_{(B)}$$

thanks to Lemma 1. Let us start by bounding Term (B).

$$\begin{split} \sum_{t=1}^{T} \sum_{v \in V} \frac{\mathbb{I}\left\{v \in S_{t}\right\}}{|S_{t}|} \left\langle \nabla \ell_{t}(x_{t}(v), v), \bar{x}_{t} - x^{*} \right\rangle &\leq N \left(\frac{1}{N} \sum_{t=1}^{T} \sum_{v \in V} \mathbb{I}\left\{v \in S_{t}\right\} \left\langle \nabla \ell_{t}(x_{t}(v), v), \bar{x}_{t} - x^{*} \right\rangle \mathbb{P}\left(S_{t} \neq \emptyset\right) \right). \\ &\leq N \left(\frac{\psi(x^{*})}{\eta} + \frac{L^{2}}{\mu} \sum_{t=1}^{T} \eta\right) \end{split}$$

We then proceed by bounding Term (A), by observing

$$3\sum_{t=1}^{T}\sum_{u\in V}\frac{\mathbb{I}\{u\in S_t\}}{|S_t|}L \, \|x_t(u) - \bar{x}_t\| \le 3\eta \sum_{t=1}^{T}\sum_{u\in V}\max_{u\in V}L \, \|z_t(u) - \bar{z}_t\|$$

Now, we focus on $||z_{t+1}(v) - \bar{z}_{t+1}||_*$. Starting from Equation (23) and applying Lemma 3, we obtain

$$||z_{t+1}(v) - \bar{z}_{t+1}||_* \le \sum_{s=1}^{t-1} \sqrt{NL} \left| ||W_t \cdots W_{s+1} e_v - \frac{1}{N} \mathbf{1} ||_2 + 2L$$

$$\le \sqrt{NL} (t - t^*) \epsilon + \sqrt{NL} t^* + 2NL$$

$$\le \sqrt{NLT} \epsilon + \sqrt{NL} t^* + 2NL$$
(27)

with probability at least $1 - \epsilon T$. Hence,

$$R_T^{\text{net}} \le 3\eta \sqrt{N} \frac{L^2}{\mu} T(t^* + \epsilon T + 2) + N\left(\frac{D^2}{\eta} + \frac{L^2}{\mu} \sum_{t=1}^T \eta\right) \le N \frac{D^2}{\eta} + \eta N \frac{L^2}{\mu} T(3t^* + \epsilon T + 3)$$

with probability at least $1 - \epsilon NT^2$. Setting $\epsilon = \frac{\delta}{NT^2}$ and $t^* = \frac{3 \log(\frac{NT^2}{\delta})}{1 - \rho^2}$, we have

$$R_T^{\text{net}} \le N \frac{D^2}{\eta} + 3\eta T N \frac{L^2}{\mu} \left(\frac{3\log\left(\frac{NT^2}{\delta}\right)}{1 - \rho^2} + 3 + \frac{\delta}{NT} \right) \le N \frac{D^2}{\eta} + 3\eta T N \frac{L^2}{\mu} \left(\frac{3\log\left(\frac{NT^2}{\delta}\right)}{1 - \rho^2} + 4 \right)$$
(28)

with probability at least $1 - \delta$.

E Proof of Theorem 3

Theorem 3. Pick any \mathcal{X} with diameter D with respect to the Euclidean norm. Pick any $N \ge 4$ multiple of 4, and let $p_v = 1$ for all $v \in V = [N]$. For any DOO algorithm and for any horizon T, there exists a connected graph G = (V, E) and L-Lipschitz, convex local losses $\ell_t(v, \cdot)$ for $v \in V$ and $t \in [T]$ such that

$$R_T^{\text{net}} \ge \frac{3DL}{16} \left(\frac{8\rho}{1-\rho}\right)^{\frac{\alpha}{4}} N^{\frac{1-\alpha}{2}} \sqrt{T},$$

for all $0 \le \alpha \le 1$, where $\rho = \sqrt{\lambda_2(\mathbb{E}[W^2])}$ and $W = I_N - \frac{\operatorname{Lap}(G)}{\lambda_1(G)}$.

Proof. The proof is an adaptation of (Wang and Ji, 2022, Theorem 3). Let G be the cycle with N = 4M nodes. Suppose that for 3M nodes, the local loss functions are set to 0 for all $t \in [T]$,

$$\ell_t(1,\cdot) = \cdots = \ell_t(3M,\cdot) = 0$$

The local loss functions of the remaining nodes are reset every M steps, in such a way that for each $k = 0, \ldots, \lceil T/M \rceil - 1$,

$$\ell_t(3M+1, \cdot) = \dots = \ell_t(4M, \cdot) = (N-M+1)H_k(\cdot) \qquad t \in [Mk+1, M(k+1)]$$

where $H_0, \ldots, H_{\lceil T/M \rceil - 1}$ are random functions such that $H_k(x) = \varepsilon_k L \langle w, x \rangle$ and ε_k are independent Rademacher random variables (equal to 1 with probability 1/2 and to -1 with probability 1/2). The value w is chosen as follows: pick $x_1, x_2 \in \mathcal{X}$ such that $||x_1 - x_2||_2 = D$ and let $w = (x_1 - x_2)/||x_1 - x_2||_2$. The network loss at time t is thus

$$\ell_t^{\text{net}}(V, x) = \frac{(N - M + 1)M}{N} H_{\lceil t/M \rceil}(x) \; .$$

Observe that there is a delay introduced by communication over a cycle, such that agents $M + 1 \dots 2M$ have no access to information about the loss of any agent in $\{3M + 1, \dots, 4M\}$ before at least M time steps have elapsed. Specifically, for any $v \in \{M + 1, \dots, 2M\}$, predictions $x_{kt+1}(v), \dots, x_{kt+M}(v)$ are computed without vknowing H_k . Hence, using the standard lower bound for online learning (Orabona, 2019, Theorem 5.1), we have that in expectation with respect to $\varepsilon_0, \ldots, \varepsilon_{\lceil T/M \rceil - 1}$, for all $v \in \{M + 1, \ldots, 2M\}$,

$$\begin{split} \mathbb{E} \left[\sum_{t=1}^{T} \ell_t^{\text{net}} (V, x_t(v)) - \min_{x \in \mathcal{X}} \sum_{t=1}^{T} \ell_t^{\text{net}} (V, x) \right] \\ &= \mathbb{E} \left[\sum_{k=0}^{[T/M]^{-1}} \sum_{t=kM+1}^{(k+1)M} \frac{(N-M+1)}{N} H_k(x_t(v)) - \min_{x \in \mathcal{X}} \sum_{k=0}^{[T/M]^{-1}} \sum_{t=kM+1}^{(k+1)M} \frac{(N-M+1)}{N} H_k(x) \right] \\ &= \frac{(N-M+1)}{N} \mathbb{E} \left[\sum_{k=0}^{[T/M]^{-1}} \sum_{t=kM+1}^{(k+1)M} H_k(x_t(v)) - \min_{x \in \mathcal{X}} M \sum_{k=0}^{[T/M]^{-1}} H_k(x) \right] \\ &= \frac{(N-M+1)M}{N} \mathbb{E} \left[-\min_{x \in \mathcal{X}} \sum_{k=0}^{[T/M]^{-1}} \varepsilon_k \langle w, x \rangle \right] \\ &\geq \frac{(N-M+1)ML}{N} \mathbb{E} \left[\max_{x \in \mathcal{X}} \sum_{k=0}^{[T/M]^{-1}} \varepsilon_k \langle w, x_1 - x_2 \rangle \right] \\ &= \frac{(N-M+1)ML}{2N} \mathbb{E} \left[\left| \sum_{k=0}^{[T/M]^{-1}} \varepsilon_k \right| \right] \\ &= \frac{(N-M+1)ML}{2N} \mathbb{E} \left[\left\| \sum_{k=0}^{[T/M]^{-1}} \varepsilon_k \langle w, x_1 - x_2 \rangle \right\| \right] \\ &= \frac{(N-M+1)MLD}{2N} \mathbb{E} \left[\left\| \sum_{k=0}^{[T/M]^{-1}} \varepsilon_k \right\| \right] \\ &= \frac{(N-M+1)MLD}{2N} \mathbb{E} \left[\left\| \sum_{k=0}^{[T/M]^{-1}} \varepsilon_k \right\| \right] \\ &\qquad (\text{using } \max\{a, b\} = \frac{1}{2}(a+b) + |a-b|) \\ &= \frac{(N-M+1)MLD}{2N} \mathbb{E} \left[\left\| \sum_{k=0}^{[T/M]^{-1}} \varepsilon_k \right\| \right] \\ &\geq \frac{(N-M+1)MLD}{2N} \sqrt{\frac{T}{M}} \\ &\leq \frac{(N-M+1)MLD}{2N} \sqrt{MT} . \end{aligned}$$

Now, let $U = \{M + 1, \dots, 2M\} \subset V$. We have

$$\mathbb{E}[R_T^{\text{net}}] = \frac{1}{N} \sum_{v \in V} \left(\sum_{t=1}^T \ell_t^{\text{net}} (V, x_t(v)) - \min_{x \in \mathcal{X}} \sum_{t=1}^T \ell_t^{\text{net}} (V, x) \right)$$
$$\geq \frac{1}{N} \sum_{v \in U} \left(\sum_{t=1}^T \ell_t^{\text{net}} (V, x_t(v)) - \min_{x \in \mathcal{X}} \sum_{t=1}^T \ell_t^{\text{net}} (V, x) \right)$$
$$\geq \frac{(N - M + 1)DL}{2N} \sqrt{MT}$$

Hence there exists a choice of $\varepsilon_1, \ldots, \varepsilon_{\lceil T/M \rceil - 1}$ such that

$$R_T^{\text{net}} \ge \frac{(N - M + 1)DL}{2N} \sqrt{MT}$$

Note that, on the N-cycle, the highest and smallest non-zero eigenvalues of the Laplacian are, respectively, $\lambda_1(G) = 1$ and $\lambda_{N-1}(G) = 2 - 2\cos(2\pi/N)$ (Spielman, 2019, Chapter 6.5). Using the inequality $1 - \cos(x) \ge x^2/5$, $\forall x \in [0, \pi]$ (recall that $N \ge 4$ implying $2\pi/N \le \pi$), we have $\lambda_{N-1}(G) \ge \frac{8\pi^2}{5N^2}$ and so $\kappa(G) \le \frac{5N^2}{8\pi^2} \le \frac{N^2}{8}$. Then, using Theorem 5, we have that $\rho/(1-\rho) = \kappa(G) - 1 \le \frac{N^2}{8} - 1 \le \frac{N^2}{8}$. This in turn implies that, for all $0 \le \alpha \le 1$,

$$R_T^{\text{net}} \ge \frac{(N-M+1)DL}{2N}\sqrt{MT} \ge \frac{3DL}{16}\sqrt{N}\sqrt{T} \ge \frac{3DL}{16}\left(\frac{8\rho}{1-\rho}\right)^{\frac{\alpha}{4}}N^{\frac{1-\alpha}{2}}\sqrt{T}$$

concluding the proof.

F Spectral properties of the gossip matrix in the *p*-uniform case

F.1 Arbitrary graph.

Theorem 5. If W_t is set according to (8), $b = 1/\lambda_1(G)$, then in the p-uniform case we have

$$\rho^2 = 1 - \frac{2p^2}{\kappa(G)} \left(1 - \frac{1-p}{\lambda_1(G)} - \frac{p}{2\kappa(G)} \right) \ .$$

Proof. Denoting by $L_1 = \text{Lap}(G_1)$, one has:

$$\mathbb{E}[W_1^2] = \mathbb{E}[I - 2bL_1 + b^2L_1^2] = I - 2b\mathbb{E}[L_1] + b^2\mathbb{E}(L_1^2)$$
$$\mathbb{E}[L_1] = p^2D_G - p^2A_G = p^2L_G$$

We compute:

$$\mathbb{E}[L_1^2] = \mathbb{E}[D_1^2 - 2D_1A_1 + A_1^2]$$

where D_1 and A_1 denote the diagonal matrix of degrees and the adjacency matrix of G_1 .

$$\mathbb{E}[(D_1^2)_{ii}] = \mathbb{E}\left[\left(\sum_{j\in\mathcal{N}_i}\mathbbm{1}(j\in S_1)\right)^2\mathbbm{1}(i\in S_1)\right]$$
$$= p\mathbb{E}\left[\sum_{j\in\mathcal{N}_i}\mathbbm{1}(j\in S_1)\sum_{k\in\mathcal{N}_i}\mathbbm{1}(k\in S_1)\right]$$
$$= p\mathbb{E}\left[\sum_{j\in\mathcal{N}_i}\mathbbm{1}(j\in S_1)\left(\sum_{k\in\mathcal{N}_i,k\neq j}\mathbbm{1}(k\in S_1) + \mathbbm{1}(j\in S_1)\right)\right]$$
$$= p\left(p^2D_G(D_G - I) + D_Gp\right)_i,$$

where D_G denotes the matrix of degrees of the graph G. Finally,

$$\mathbb{E}[(D_1^2)] = p^2(pD_G(D_G - I) + D_G).$$

where A_G denotes the adjacency matrix of the graph G. Regarding A_1^2

$$\mathbb{E}[(A_1^2)_{ij}] = \mathbb{E}\left[\sum_{k \in \mathcal{N}_i, k \in \mathcal{N}_j} \mathbb{1}(k \in S_1) \mathbb{1}(i \in S_1) \mathbb{1}(j \in S_1)\right]$$
$$= \begin{cases} p^3 \left| \mathcal{N}_i \cap \mathcal{N}_j \right| = p^3 (A_G^2)_{ij} & \text{if } i \neq j \\ \mathbb{E}\left[\sum_{k \in \mathcal{N}_i} \mathbb{1}(k \in S_1) \mathbb{1}(i \in S_1)\right] = p^2 (D_G)_i & \text{if } i = j \end{cases}$$

Hence, finally,

$$\mathbb{E}[A_1^2] = p^3 A_G^2 - p^3 D_G + p^2 D_G \,.$$

Now, regarding D_1A_1 ,

$$\mathbb{E}[(D_1A_1)_{ij}] = \mathbb{E}\left[(D_1)_{ii}(A_1)_{ij}\right] \\ = \mathbb{E}\left[\mathbbm{1}\{i \in S_1\} \mathbbm{1}\{j \in S_1\} \mathbbm{1}\{(i,j) \in E\} \sum_{k \in \mathcal{N}_i} \mathbbm{1}\{k \in S_1\}\right] \\ = \begin{cases} p^3(D_GA_G)_{ij} - p^3[A_G]_{ij} + p^2(A_G)_{ij} & \text{if } i \neq j \\ 0 & \text{if } i = j \end{cases}$$

Finally,

$$\mathbb{E}[D_1A_1] = p^3(D_G - I)A_G + p^2A_G$$

Putting everything together,

$$\mathbb{E}[L_1^2] = p^2(pD_G(D_G - I) + D_G) + p^3A_G^2 - p^3D_G + p^2D_G - 2p^3(D_G - I)A_G - 2p^2A_G$$

= $p^3D_G^2 - 2p^3D_G + 2p^2D_G - 2p^3D_GA_G + 2p^3A_G - 2p^2A_G + p^3A_G^2$.

So in the end we have

$$\mathbb{E}[W_1^2] = I - 2bp^2(D_G - A_G) + b^2 \left(p^3(D_G^2 - 2D_G - 2D_G A_G + 2A_G) + p^3 A_G^2 + p^2(2D_G - 2A_G) \right)$$

= $I - 2bp^2(D_G - A_G) + b^2[p^3((D_G - A_G)^2 + 2(A_G - D_G)) + 2p^2(D_G - A_G)]$
$$\mathbb{E}[W_1^2] = I - 2bp^2L_G + b^2[p^3(L_G^2 - 2L_G) + 2p^2L_G].$$

So if x is an eigenvector of L_G with eigenvalue $\lambda_i(L_G)$, then

$$\mathbb{E}[W_1^2]x = x - 2bp^2\lambda_i(L_G)x + b^2[p^3(\lambda_i(L_G)^2 - 2\lambda_i(L_G)) + 2p^2\lambda_i(L_G)]x = (1 - 2bp^2\lambda_i(L_G) + b^2[p^3(\lambda_i(L_G)^2 - 2\lambda_i(L_G)) + 2p^2\lambda_i(L_G)])x = (1 + (-2bp^2 + 2b^2p^2 - 2p^3b^2)\lambda_i(L_G) + b^2p^3(\lambda_i(L_G)^2)x$$

So that the eigenvalues of $\mathbb{E}[W_1^2]$ can easily be expressed as eigenvalues of L_G . It is easy to check that $f_{b,p}: x \mapsto 1 + (-2bp^2 + 2b^2p^2 - 2p^3b^2)x + b^2p^3x^2$ is a quadratic function decreasing on $] - \infty, 1 + (1 - b)/(bp)]$.

It is clear that

$$1 + (1-b)/(bp) = 1 + (1/b - 1)/p \ge 1/bp \ge 1/b \ge 2\Delta(G) \ge \lambda_1(L_G)$$

So that $f_{b,p}$ is decreasing on an interval containing all eigenvalues of the Laplacian L_G and that

$$\lambda_2(\mathbb{E}[W_1^2]) = f_{b,p}(\lambda_{N-1}(L_G)).$$

Hence

$$\lambda_2(\mathbb{E}[W_1^2]) = 1 + (-2bp^2 + 2b^2p^2 - 2p^3b^2)\lambda_{N-1}(L_G) + b^2p^3(\lambda_{N-1}(L_G))^2.$$

Setting $b = 1/\lambda_1(G)$ and rewriting yields

$$\rho^{2} = \lambda_{2}(\mathbb{E}[W_{1}^{2}]) = 1 - \frac{2p^{2}}{\kappa(G)} \left(1 - \frac{1-p}{\lambda_{1}(G)} - \frac{p}{2\kappa(G)}\right)$$

F.2 Special cases

Clique. When G is the clique, and b = 1/(N), since $\lambda_{N-1}(G) = N$

$$\lambda_2(\mathbb{E}[W_1^2]) = 1 - p^2 - \frac{1}{N}((N-2)p^3 + 2p^2),$$

using Theorem 5.

Strongly Regular graphs. Strongly Regular graphs are such that

- they are k-regular, for some integer k
- there exists an integer m such that for every pair of vertices u and v that are neighbors in G, there are m vertices that are neighbors of both u and v
- there exists an integer n such that for every pair of vertices u and v that are not neighbors in G, there are n vertices that are neighbors of both u and v.

Such graphs' adjacency matrices have eigenvalues k with multiplicity 1 and r and s defined as follows:

$$r = \frac{m - n + \sqrt{(m - n)^2 + 4(k - n)}}{2}$$
 and
$$s = \frac{m - n - \sqrt{(m - n)^2 + 4(k - n)}}{2}.$$

Hence, their Laplacian have eigenvalues 0 with multiplicity 1 and and k-r and k-s. This yields $\lambda_1(\text{Lap}(G)) = k-s$ and $\lambda_{N-1}(G) = k-r$.

Using Theorem 4, we have that if $b = 1/\lambda_1(\text{Lap}(G))$, then

$$\rho^2 = \lambda_2(\mathbb{E}[W_1^2]) \le 1 - p^2 \frac{k-r}{k-s}$$

In particular, when G is the lattice graph, with $N = M^2$ vertices

$$\rho^2 = \lambda_2(\mathbb{E}[W_1^2]) \le 1 - \frac{1}{2}p^2.$$

replacing k by 2M - 2, m by M - 2 and n by 2.

Grid. Consider G a grid of dimension 2, with $N = M^2$. G is the product of two paths graphs of length M. Then if $\mu_1 \dots \mu_M$ are the eigenvalues of the path graph of length M, then all eigenvalues of Lap(G) can be rewritten as $\mu_i + \mu_j$ for some i and j—see (Barik et al., 2015, Theorem 3). Furthermore we know that $\mu_i = 2(1 - \cos(\pi(M - i)/M))$ —see, e.g., (Spielman, 2019, Theorem 6.6)—so that $\lambda_1(\text{Lap}(G)) = 2\mu_1 = 4 - 4\cos(\pi(M - 1)/M)$ and $\lambda_{N-1}(G) = \mu_N + \mu_{N-1} = 2 - 2\cos(\pi/M)$.

Hence setting $b = 1/\lambda_1(\operatorname{Lap}(G))$

$$\rho^2 = \lambda_2(\mathbb{E}[W_1^2]) \le 1 - p^2 \frac{2 - 2\cos(\pi/M)}{4 - 4\cos(\pi(M-1)/M)}$$

by using Theorem 4.

G Proof of Corollary 2

Corollary 2. Assume each agent runs an instance of Gossip-FTRL with learning rate $\eta > 0$. If the gossip matrix W_t is chosen as in (8) with $b = 1/\lambda_1(G)$, then

$$\rho^{2} = 1 - \frac{2p^{2}q}{\kappa(G)} \left(1 - \frac{1 - pq}{\lambda_{1}(G)} - \frac{pq}{2\kappa(G)} \right) \; .$$

By tuning η with respect to p and N, the expected network regret on G_1, G_2, \ldots drawn i.i.d. from $\mathcal{G}(G, p, q)$ can be bounded by

$$\mathbb{E}[R_T^{\text{net}}] = \mathcal{O}\left(\frac{\kappa(G)}{pq}\min\left(\sqrt{N}, \frac{N^{1/4}}{\sqrt{p}}\right)\sqrt{T}\right) .$$
(15)

Proof. As bound (5) in Theorem 1 applies, we just have to compute the spectral gap.

Regarding the expression of $\rho^2 = \lambda_2(\mathbb{E}[W_1^2])$, we take the same steps as for the proof of Theorem 5. We observe that

$$\mathbb{E}[W_1^2] = \mathbb{E}[I - 2bL_1 + b^2 L_1^2] = I - 2b\mathbb{E}[L_1] + b^2\mathbb{E}(L_1^2)$$

We compute

$$\mathbb{E}[L_1] = p^2 D_G - p^2 A_G = p^2 L_G$$

and

$$\mathbb{E}[L_1^2] = \mathbb{E}[D_1^2 - 2D_1A_1 + A_1^2].$$

Mutatis mutandis in the computations of the proof of Theorem 5, we get the following equalities for the first term,

$$\begin{split} \mathbb{E}[(D_1^2)_{ii}] &= \mathbb{E}\left[\left(\sum_{j\in\mathcal{N}_i} \mathbb{1}((i,j)\in E_1)\right)^2\right] \\ &= \mathbb{E}\left[\sum_{j\in\mathcal{N}_i} \mathbb{1}((i,j)\in E_1)\left(\sum_{k\in\mathcal{N}_i,k\neq j} \mathbb{1}((i,k)\in E_1) + \mathbb{1}((i,j)\in E_1)\right)\right] \\ &= \mathbb{E}\left[\mathbb{E}\left[\sum_{j\in\mathcal{N}_i} \mathbb{1}((i,j)\in E_1)\left(\sum_{k\in\mathcal{N}_i,k\neq j} \mathbb{E}\left[\mathbb{1}((i,k)\in E_1) + \mathbb{1}((i,j)\in E_1)\Big|(i,k)\in S_1\right]\right)\Big|(i,j)\in S_1\right]\right] \\ &= p^2q\left(pqD_G(D_G-I) + D_G\right)_i\,, \end{split}$$

the second term,

$$\mathbb{E}[(A_1^2)_{ij}] = \mathbb{E}\left[\sum_{k \in \mathcal{N}_i, k \in \mathcal{N}_j} \mathbb{1}((k, i) \in E_1) \mathbb{1}((k, j) \in E_1)\right] \\ = \begin{cases} p^3 |\mathcal{N}_i \cap \mathcal{N}_j| = p^3 q^2 (A_G^2)_{ij} & \text{if } i \neq j \\ p^2 \sum_{k \in \mathcal{N}_i} \mathbb{E}\left[\mathbb{1}((i, k) \in E_1) \middle| \mathbb{1}((i, k) \in S_1)\right] = p^2 q(D_G)_i & \text{if } i = j \end{cases}$$

and the third term.

$$\mathbb{E}[(D_1A_1)_{ij}] = \mathbb{E}\left[(D_1)_{ii}(A_1)_{ij}\right] \\ = \mathbb{E}\left[\mathbb{1}((i,j) \in E_t) \sum_{k \in \mathcal{N}_i} \mathbb{1}((i,k) \in E_1)\right] \\ = \begin{cases} p^3 q^2 (D_G A_G)_{ij} - p^3 q^2 [A_G]_{ij} + p^2 q (A_G)_{ij} & \text{if } i \neq j \\ 0 & \text{if } i = j \end{cases}$$

Finally, by adding these three inequalities and rearranging,

$$\mathbb{E}[W_1^2] = I - 2bp^2qL_G + b^2\left(p^3q^2(L_G^2 - 2L_G) + 2p^2qL_G\right) \,.$$

It is easy to check that $f_{b,p,q}: x \mapsto 1 + (-2bp^2q + 2b^2p^2q - 2p^3b^2q^2)x + b^2p^3q^2x^2$ is a quadratic function decreasing on $(-\infty, 1 + (1-b)/(bpq)]$.

Again,

$$1 + (1-b)/(bpq) = 1 + (1/b-1)/pq \ge 1/bpq \ge 1/b \ge 2\Delta(G) \ge \lambda_1(L_G).$$

so that $f_{b,p,q}$ is decreasing on an interval containing all eigenvalues of the Laplacian L_G and that

$$\rho^2 = \lambda_2(\mathbb{E}[W_1^2]) = f_{b,p,q}(\lambda_{N-1}(L_G))$$

concluding the proof.

H Some results mentioned in the discussions

H.1 Tuning the learning rate in the general case (Proof of Equation (7))

Corollary 3. Assume $N \ge 2$. Assume each agent runs an instance of Gossip-FTRL with learning rate $\eta = \frac{D\sqrt{\mu p_{\min}}}{L\sqrt{T}}$ and gossip matrices set according to (8). Then, the expected network regret can be bounded by

$$\mathbb{E}\left[R_T^{\text{net}}\right] \le 12DL \frac{\kappa(G)}{p_{\min}} N \sqrt{\frac{T}{\mu}} .$$
⁽²⁹⁾

If $p_{\min}^2 \overline{p} \leq \frac{1}{\sqrt{N}}$, and each agent runs an instance of Gossip-FTRL with learning rate $\eta = \frac{D\sqrt{\mu}p_{\min}}{L\sqrt{T}}$, which only requires knowing p_{\min} , and gossip matrices set according to (8) then

$$\mathbb{E}\left[R_T^{\text{net}}\right] \le 12DL \frac{\kappa(G)}{p_{\min}} N \sqrt{\frac{T}{\mu}} . \tag{30}$$

Proof. Thanks to Theorem 1, we have

$$\mathbb{E}\left[R_T^{\text{net}}\right] \le \frac{ND^2}{\eta} + \frac{L^2}{\mu} \eta \left(\bar{p}N + \bar{p}(1-\bar{p}) - \sigma_p^2 + 6 + 3\bar{p}N\frac{\rho}{1-\rho}\right) T.$$

We note that $\bar{p}N + \bar{p}(1-\bar{p}) - \sigma_p^2 \leq \bar{2}pN$ and

$$\frac{\rho}{1-\rho} \leq \frac{1}{1-\rho} \leq \frac{1}{1-\sqrt{1-\frac{p_{\min}^2}{\kappa}}} \leq 2\frac{\kappa}{p_{\min}^2}$$

where the second inequality follows from Theorem 4, and the last one follows from the concavity of $\sqrt{\cdot}$. Consequently, we can prove

$$\mathbb{E}\left[R_T^{\text{net}}\right] \le \frac{ND^2}{\eta} + \left(6 + 8\bar{p}N\frac{\kappa}{p_{\min}^2}\right)T \le \frac{ND^2}{\eta} + \left(11\bar{p}N\frac{\kappa}{p_{\min}^2}\right)T$$

Setting $\eta = \frac{D\sqrt{\mu}p_{\min}}{L\sqrt{T}}$, which only requires knowing p_{\min} , suffices to obtain the bound

$$\mathbb{E}\left[R_T^{\text{net}}\right] \le 12DL \frac{\kappa(G)}{p_{\min}} N \sqrt{\frac{T}{\mu}} .$$
(31)

If additionally $p_{\min}^2 \overline{p} \leq \frac{1}{\sqrt{N}}$, we have $\overline{p}N \leq \sqrt{N} \frac{\kappa}{p_{\min}^2}$, so that using Theorem 1 along with $\frac{\rho}{1-\rho} \leq 2\frac{\kappa}{p_{\min}^2}$ yields

$$\mathbb{E}\left[R_T^{\text{net}}\right] \le \frac{ND^2}{\eta} + 2\sqrt{N}\frac{\kappa}{p_{\min}^2} + 6 + 3\sqrt{N}\frac{\kappa}{p_{\min}^2} \le \frac{ND^2}{\eta} + 11\sqrt{N}\frac{\kappa}{p_{\min}^2} \,.$$

In turn, setting $\eta = \frac{N^{1/4} D \sqrt{\mu} p_{\min}}{L \sqrt{T}}$ yields

$$\mathbb{E}[R_T^{\text{net}}] \le 12DL \frac{\kappa(G)}{p_{\min}} N^{3/4} \sqrt{\frac{T}{\mu}} \ .$$

H.2 Regret bounds with known $|S_t|$

We study the variant of the algorithm where $\nabla \ell_t(v)$ in Equation (3) is replaced by $\frac{N}{|S_t|} \nabla \ell_t(v)$. Using this variant of the algorithm yields the bound given by the following theorem.

Theorem 6. With any $\eta > 0$, the network regret can be bounded by

$$\mathbb{E}\left[R_T^{\text{net}}\right] \le \frac{D^2}{\eta} + \frac{L^2}{\mu} T\eta + 3\eta N \frac{L^2}{\mu} \frac{1}{1-\rho} T,$$

Setting $\eta = D\sqrt{\mu}/(L\sqrt{N}\sqrt{T})$,

$$\mathbb{E}\left[R_T^{\text{net}}\right] \le 4\frac{LD}{\sqrt{\mu}}\sqrt{N}\frac{1}{1-\rho}\sqrt{T}\,.$$

Proof. Like for Theorem 1, the proof relies on the use of an omniscient agent knowing the gradients of all losses incurred up to time t - 1.

Let us define these quantities \bar{z}_t and \bar{g}_t

$$\bar{g}_t = \frac{1}{N} \sum_{v \in V} g_t(x_t(v), v) = \sum_{v \in V} \frac{\mathbb{1}(v \in S_t)}{|S_t|} \nabla \ell_t(x_t(v), v)$$
$$\bar{z}_t = \frac{1}{N} \sum_{v \in V} z_t(v).$$

The decision of the omniscient agent is defined as

$$\bar{x}_t = \operatorname{argmin}_{x \in X} \left\{ \langle \bar{z}_t, x \rangle + \frac{1}{\eta} \psi(x) \right\},\$$

as in the proof of Theorem 1. We still have

$$\bar{z}_{t+1} = \bar{z}_t + \bar{g}_t.$$

Still like for Theorem 1, the proof of the theorem relies on the use of Lemma 1, where y_t is set to \bar{x}_t .

$$R_T^{\text{net}} \le \underbrace{3\sum_{t=1}^T \sum_{u \in V} \frac{\mathbb{I}\{u \in S_t\}}{|S_t|} L \|x_t(u) - \bar{x}_t\|}_{(A)} + \underbrace{\sum_{t=1}^T \sum_{v \in V} \frac{\mathbb{I}\{v \in S_t\}}{|S_t|} \langle \nabla \ell_t(x_t(v), v), \bar{x}_t - x^* \rangle}_{(B)} .$$
(32)

Let us focus on Term (B) first. According to the usual analysis of FTRL, we have

$$\sum_{t=1}^{T} \sum_{v \in V} \frac{\mathbb{I}\left\{v \in S_t\right\}}{|S_t|} \left\langle \nabla \ell_t(x_t(v), v), \bar{x}_t - x^* \right\rangle \le \frac{\psi(x^*)}{\eta} + \frac{L^2}{\mu} \sum_{t=1}^{T} \eta \mathbb{1} \left(S_t \neq \emptyset\right) \,. \tag{33}$$

since the omniscient agent's updates correspond to FTRL on linear losses equal to $\langle \tilde{L}_1, x \rangle$ where $\tilde{l}_t = \sum_v \nabla \ell_1(x_t(v), v) \frac{\mathbb{1}(v \in S_t)}{|S_t|}$.

Regarding Term (A), s we still have (like in Equation (21))

$$\|x_t(v) - \bar{x}_t\| \le \eta/\mu \, \|z_t(v) - \bar{z}_t\|_* \,. \tag{34}$$

For any $t \in [T]$ and any $v \in [N]$, it also still holds that

$$Z_{t+1} = \sum_{s=1}^{t-1} W_t \cdots W_{s+1} \Gamma_s + \Gamma_t$$

and that

$$\bar{z}_{t+1} = \frac{1}{N} \sum_{s=1}^{t} \mathbf{1}^\top \Gamma_s$$

Consequently, we can still prove

$$z_{t+1}(v) - \bar{z}_{t+1} = \sum_{s=1}^{t-1} \Gamma_s^T \left[W_t \cdots W_{s+1} - \frac{1}{N} \mathbf{1} \mathbf{1}^\top \right]^T e_v + \Gamma_t^\top (I - \frac{1}{N} \mathbf{1} \mathbf{1}^\top) e_v,$$

and compute :

$$\begin{aligned} \|z_{t+1}(v) - \bar{z}_{t+1}\|_{*} &\leq \left\| \sum_{s=0}^{t-1} \left(\sum_{u=1}^{N} \left([W_{t} \cdots W_{s+1}]_{u,v} - \frac{1}{N} \right) g_{s}(x_{s}(u), u) \right) \right\|_{*} + \|g_{t}(x_{t}(v), v) - \bar{g}_{t}\|_{*} \\ &\leq \sum_{s=0}^{t-1} \sum_{u=1}^{N} \left\| [W_{t} \cdots W_{s+1}]_{u,v} - \frac{1}{N} \right\| \|g_{s}(x_{s}(u), u)\|_{*} + \|g_{t}(x_{t}(v), v) - \bar{g}_{t}\|_{*} \\ &\leq \sum_{s=0}^{t-1} \sum_{u=1}^{N} \left\| W_{t} \cdots W_{s+1} e_{v} - \frac{1}{N} \right\|_{\infty} \|g_{s}(x_{s}(u), u)\|_{*} + \sum_{u=1}^{N} \left\| Ie_{v} - \frac{1}{N} \right\|_{\infty} \|g_{s}(x_{s}(u), u)\|_{*} \end{aligned}$$

Since $\|\nabla \ell_1(\cdot, v)\|_* \leq L$ for all v,

$$\|z_{t+1}(v) - \bar{z}_{t+1}\|_{*} \leq \sum_{s=1}^{t-1} |S_{s}| \left(\frac{N}{|S_{s}|}L\right) \|W_{t} \cdots W_{s+1}e_{v} - \frac{1}{N}\mathbf{1}\|_{\infty} + NL$$
$$\leq \sum_{s=1}^{t-1} NL \|W_{t} \cdots W_{s+1}e_{v} - \frac{1}{N}\mathbf{1}\|_{\infty} + NL$$
$$\leq \sum_{s=1}^{t-1} NL \|W_{t} \cdots W_{s+1}e_{v} - \frac{1}{N}\mathbf{1}\|_{2} + NL, \qquad (35)$$

considering $\|\cdot\|_{\infty} \leq \|\cdot\|_2$. By using Jensen's inequality,

$$\mathbb{E}\left[\left\|W_t \cdots W_{s+1}e_v - \frac{\mathbf{1}}{N}\right\|_2\right] \le \sqrt{\mathbb{E}\left[(W_t \cdots W_{s+1}e_v - \frac{\mathbf{1}}{N})^T (W_t \cdots W_{s+1}e_v - \frac{1}{N})\right]}$$

By using Lemma 2, we obtain

$$\mathbb{E}[\|z_{t+1}(v) - \bar{z}_{t+1}\|_*] \le \sum_{s=1}^t NL\lambda_2(\mathbb{E}[W_1W_1^\top])^{\frac{t-s}{2}} \le NL\frac{1}{1-\rho}$$

Hence, coming back to the expression of Term (A), and following Equation (21)

$$\sum_{t=1}^{T} \sum_{u \in \mathcal{V}} \frac{1}{|\mathcal{S}_t|} \mathbb{1}(u \in \mathcal{S}_t) L \| x_t(u) - \bar{x}_t \| \le \sum_{u \in \mathcal{V}} \sum_{t=1}^{T} \frac{1}{|\mathcal{S}_t|} \eta / \mu L \| z_t(u) - \bar{z}_t \| \mathbb{1}(u \in \mathcal{S}_t)$$

and combining with the following,

$$\mathbb{E}\left[\sum_{u\in\mathcal{V}}\sum_{t=1}^{T}\frac{1}{|\mathcal{S}_{t}|}\|z_{t}(u)-\bar{z}_{t}\|_{*}\mathbf{1}(u\in\mathcal{S}_{t})\right]$$
$$=\sum_{u\in\mathcal{V}}\sum_{t=1}^{T}\mathbb{E}\left[\frac{\mathbf{1}(u\in\mathcal{S}_{t})}{|\mathcal{S}_{t}|}\right]\mathbb{E}\left[\|z_{t}(u)-\bar{z}_{t}\|_{*}\right]$$
$$\leq\sum_{u\in\mathcal{V}}\sum_{t=1}^{T}\mathbb{E}\left[\frac{\mathbf{1}(u\in\mathcal{S}_{t})}{|\mathcal{S}_{t}|}\right]\times NL\frac{1}{1-\rho}$$
$$\leq\sum_{t=1}^{T}\left(1-\Pi_{v\in\mathcal{V}}\left(1-p_{v}\right)\right)NL\frac{1}{1-\rho},$$

we have

$$\mathbb{E}\left[\sum_{t=1}^{T}\sum_{u\in\mathcal{V}}\frac{1}{|\mathcal{S}_t|}\mathbb{1}(u\in\mathcal{S}_t)L\|x_t(u)-\bar{x}_t\|\right] \le \eta \frac{L^2}{\mu}N\frac{1}{1-\rho}\widetilde{T}$$
(36)

where $\widetilde{T} = (1 - \prod_{v \in \mathcal{V}} (1 - p_v)) T$ is the expected number of times where there is at least one active agent. Recalling Equation (32) and combining Equation (36) and Equation (33), we obtain

$$\mathbb{E}(R_T^{\text{net}}) \le \frac{D^2}{\eta} + \frac{L^2}{\mu} \widetilde{T}\eta + 3\eta N \frac{L^2}{\mu} \frac{1}{1-\rho} \widetilde{T}.$$

This directly yields

$$\mathbb{E}(R_T^{\text{net}}) \le \frac{D^2}{\eta} + \frac{L^2}{\mu}T\eta + 3\eta N \frac{L^2}{\mu} \frac{1}{1-\rho}T,$$

and the computation with the appropriate η follows.

Theorem 7. (Known $|S_t|$) For any $\eta > 0$, with probability $1 - \delta$, the network regret can be bounded by

$$R_T^{\text{net}} \le \frac{D^2}{\eta} + \frac{L^2}{\mu} T\eta + 3\eta TN \frac{L^2}{\mu} \left(\frac{9 \log \frac{NT^2}{\delta}}{1 - \lambda_2(\mathbb{E}[W_1 W_1^\top])} + 2 + \frac{1}{T^2} \right)$$

We have

$$R_T^{\text{net}} \le \underbrace{3\sum_{t=1}^T \sum_{u \in V} \frac{\mathbb{I}\{u \in S_t\}}{|S_t|} L \, \|x_t(u) - \bar{x}_t\|}_{(A)} + \underbrace{\sum_{t=1}^T \sum_{v \in V} \frac{\mathbb{I}\{v \in S_t\}}{|S_t|} \left< \nabla \ell_t(x_t(v), v), \bar{x}_t - x^* \right>}_{(B)}$$

thanks to Lemma 1. Thanks to Equation (35), we can bound Term (B) in the following way

$$\sum_{v \in V} \frac{\mathbb{I}\left\{v \in S_t\right\}}{|S_t|} \left\langle \nabla \ell_t(x_t(v), v), \bar{x}_t - x^* \right\rangle \frac{\psi(x^*)}{\eta} + \frac{L^2}{\mu} \sum_{t=1}^T \eta$$

We then proceed by bounding Term (A), by observing

$$3\sum_{t=1}^{T}\sum_{u\in V}\frac{\mathbb{I}\left\{u\in S_{t}\right\}}{|S_{t}|}L \left\|x_{t}(u)-\bar{x}_{t}\right\| \leq 3\eta\sum_{t=1}^{T}\sum_{u\in V}\max_{u\in V}L\left\|z_{t}(u)-\bar{z}_{t}\right\|$$

Now, we focus on $||z_{t+1}(v) - \bar{z}_{t+1}||_*$. Starting from Equation (35) and applying Lemma 3, we obtain

$$\|z_{t+1}(v) - \bar{z}_{t+1}\|_{*} \leq \sum_{s=1}^{t-1} NL \left\| W_{t} \cdots W_{s+1} e_{v} - \frac{1}{N} \mathbf{1} \right\|_{2} + 2NL$$

$$\leq NL(t-t^{*})\epsilon + NLt^{*} + 2NL$$

$$\leq NLT\epsilon + NLt^{*} + 2NL$$
(37)

with probability at least $1 - \epsilon T$. Hence,

$$R_T^{\text{net}} \le 3\eta N \frac{L^2}{\mu} T(t^* + \epsilon T + 2) + \frac{\psi(x^*)}{\eta} + \frac{L^2}{\mu} \sum_{t=1}^T \eta$$

with probability at least $1 - \epsilon NT^2$. Set $\epsilon = \frac{\delta}{NT^2}$ and $t^* = \frac{3 \log(\frac{NT^2}{\delta})}{1 - \lambda_2(\mathbb{E}[W^\top W])}$, we have

$$R_T^{\text{net}} \le \frac{D^2}{\eta} + \frac{L^2}{\mu} T\eta + 3\eta T N \frac{L^2}{\mu} \left(\frac{3\log\left(\frac{NT^2}{\delta}\right)}{1 - \lambda_2(\mathbb{E}[W^\top W])} + 2 + \frac{\delta}{NT} \right),$$

with probability at least $1 - \delta$.

H.3 Nonstationary case

Corollary 4. Suppose that the activation probabilities change over time within known bounds p_{\min} and p_{\max} , and the activations events are independent. Assume each agent runs an instance of Gossip-FTRL with learning rate $\eta > 0$ and gossip matrices set according to Equation (8). Then, the expected network regret can be bounded by

$$\mathbb{E}\left[R_T^{\text{net}}\right] \le \frac{ND^2}{\eta} + \frac{L^2}{\mu} \eta \left(\bar{p}N + \bar{p}(1-\bar{p}) - \sigma_p^2 + 6 + 3\min\left(\bar{p}N,\sqrt{N}\right)\frac{\sqrt{B_\lambda}}{1-\sqrt{B_\lambda}}\right) T$$

where we denote by $B_{\lambda} = 1 - \frac{(p^{\min})^2}{\kappa}$.

Proof. The proof works exactly like that of Theorem 1, with the difference that Equation (17) does not hold anymore. Instead, we replace it by

$$\mathbb{E}\left[\left\|W_t \cdots W_{s+1}e_v - \frac{\mathbf{1}}{N}\right\|_2\right] \le B_{\lambda}^{\frac{t-s}{2}}.$$

In fact, thanks to Theorem 4, we know that $\lambda_2(\mathbb{E}[W_k^2]) \leq B_{\lambda}$ for all $k \in [T]$. To prove the above, we then proceed by induction.

$$\mathbb{E}\left[\left\|W_{k}\cdots W_{s+1}e_{v}-\frac{\mathbf{1}}{N}\right\|_{2}^{2}\right] = \mathbb{E}\left[e_{v}^{T}\widetilde{W}_{s+1}\cdots\widetilde{W}_{k-1}\widetilde{W}_{k}^{2}\widetilde{W}_{k-1}\cdots\widetilde{W}_{s+1}e_{v}\right]$$
$$= \mathbb{E}\left[e_{v}^{T}\widetilde{W}_{s+1}\cdots\widetilde{W}_{k-1}\mathbb{E}[\widetilde{W}_{k}^{2}|\mathcal{F}_{k-1}]\widetilde{W}_{k-1}\cdots\widetilde{W}_{s+1}e_{v}\right]$$
$$\leq \left\|\mathbb{E}[W_{k}^{2}]-\frac{1}{N}\mathbf{1}\mathbf{1}^{\top}\right\|_{\mathrm{op}}B_{\lambda}^{k-1-s}$$
$$\leq \sqrt{\lambda_{2}(\mathbb{E}[W_{k}^{2}])}B_{\lambda}^{k-1-s}$$
$$\leq B_{\lambda}^{k-s},$$

where \widetilde{W}_s is $W_s - \frac{1}{N} \mathbf{1} \mathbf{1}^T$. Hence,

$$\mathbb{E}\left[\left\|W_k\cdots W_{s+1}e_v - \frac{\mathbf{1}}{N}\right\|_2\right] \le B_{\lambda}^{\frac{k-s}{2}}$$

The rest of the proof is identical to that of Theorem 1.

H.4 Bound on $\rho/(1-\rho)$

Lemma 4. In the p-uniform case, if the gossip matrices are set according to Equation (8), then

$$\frac{\rho}{1-\rho} \le \frac{2\kappa(G)}{p^2}$$

for all $0 \le p \le 1$.

Proof. We have

$$\frac{\rho}{1-\rho} \leq \frac{1}{1-\rho} \leq \frac{1}{1-\sqrt{1-\frac{p^2}{\kappa(G)}}}$$

thanks to Theorem 4. We also have $1 - \sqrt{1-y} \ge \frac{1}{2}y$ for all $y \le 1$ by concavity of $\sqrt{\cdot}$. Hence,

$$\frac{\rho}{1-\rho} \le \frac{2\kappa(G)}{p^2}$$

Since $\frac{\lambda_1(G)}{\lambda_1(G)-1} \ge 1$, this also yields $\frac{\rho}{1-\rho} \le \frac{2\kappa(G)}{p^2} \frac{\lambda_1(G)}{\lambda_1(G)-1}$.

I Experimental details

The code is available at https://anonymous.4
open.science/r/DistOLR-6085/.