What can LLM tell us about cities?

Zhuoheng Li¹, Yaochen Wang¹, Zhixue Song¹, Yuqi Huang¹, Rui Bao¹, Guanjie Zheng², Zhenhui Jessie Li¹

¹Yunqi Academy of Engineering, Hangzhou, Zhejiang, China ²Shanghai Jiaotong University, Shanghai, Shanghai, China zhlii@umich.edu, misakiwang74@gmail.com, kmno4.zhixue@gmail.com, hhhuangq@sjtu.edu.cn, 851756936@sjtu.edu.cn, gjzheng@sjtu.edu.cn, jessielzh@gmail.com

Abstract

This study explores the capabilities of large language models (LLMs) in providing knowledge about cities and regions on a global scale. We employ two methods: directly querying the LLM for target variable values and extracting explicit and implicit features from the LLM correlated with the target variable. Our experiments reveal that LLMs embed a broad but varying degree of knowledge across global cities, with ML models trained on LLM-derived features consistently leading to improved predictive accuracy. Additionally, we observe that LLMs demonstrate a certain level of knowledge across global cities on all continents, but it is evident when they lack knowledge, as they tend to generate generic or random outputs for unfamiliar tasks. These findings suggest that LLMs can offer new opportunities for data-driven decision-making in the study of cities.

Introduction

Cities are of significant importance, as more than half of the world's population now resides in cities. With the availability of rich city data, LLMs inherently encode extensive information about various aspects of our cities. LLMs could open new possibilities for city research, as illustrated in the following examples.

Example 1. Region-level knowledge inside cities. Using NYC open data (New York City Taxi &Limousine Commission 2024), Figure 1 shows the 24-hour taxi pick-up and drop-off count for two zones in New York City (NYC). Since the 24-hour data are aggregated from raw pick-up and dropoff records, LLMs naturally do not have access to this specific information. When directly asked to generate a 24-hour curve, an LLM will either acknowledge that it lacks this data or produce random numbers. However, LLMs can provide insights into the functions of these zones within NYC, and the semantics of these functions often align well with our understanding of traffic patterns. For example, the LLM identifies the Garment District primarily as a commercial zone, exhibiting a drop-off peak in the morning and a pick-up peak in the evening. In contrast, the LLM classifies Arden Heights as a predominantly residential area, showing the opposite pattern. These functional characteristics can be leveraged as features to model traffic.




Figure 1: Taxi pick-up and drop-off patterns in NYC: the commercial Garment District (left) shows morning drop-off and evening pick-up peaks, while the residential Arden Heights (right) shows opposite trends.

This example demonstrates that although LLMs may not have direct access to the target variable, they can identify features that could be used to model it. This implication is significant. If an LLM can estimate features for *all* cities and the correlation between these features and traffic patterns can be generalized, we could potentially derive traffic patterns for any city, even those that do not release traffic data as comprehensively as NYC does.

Example 2. City-level knowledge across the globe. Public transportation is a core topic in city research. However, since different cities around the world release data in various formats, collecting public transportation data is a tremendous effort. For instance, a recent study (Verbavatz and Barthelemy 2020) compiles public transportation data from 85 cities in OECD (Organization for Economic Cooperation and Development) countries, spanning across 25 nations. Figure 2 shows a snippet of the data sources. As seen, these countries use different languages, and some data sources include terms that may be well-known locally but unfamiliar to outsiders (e.g., SNCF, which stands for Société nationale des chemins de fer français, is France's national state-owned railway company). Even within the same country, data sources can come from different agencies (e.g., PTV of Melbourne and TransLink of Brisbane, both in Australia). This example illustrates the significant challenges involved in collecting city data across global cities.

Meanwhile, LLMs possess a broad understanding of cities

Copyright © 2025, Association for the Advancement of Artificial Intelligence (www.aaai.org). All rights reserved.

City	Country	Agency
Athens	Greece	Οργανισμός Αστικών Συγκοινωνιών ΟΑΣΑ
Bilbao	Spain	Euskotren, Metro Bilbao, Renfe
Brisbane	Australia	TransLink
Helsinki	Finland	Helsingin seudun liikenne
Lyon	France	SNCF, TCL SYTRAL
Melbourne	Australia	PTV

Figure 2: Public transportation data are collected from various agencies. Source: (Verbavatz and Barthelemy 2020).

across the globe. As shown in Figure 3, when asked to score public transportation for these 85 cities, the LLM's responses strongly correlate with the public transportation metric, People Near Transit (PNT), calculated in the dataset (Verbavatz and Barthelemy 2020). We do not intend to suggest that the effort of collecting raw data should be replaced by LLMs. However, we want to emphasize that LLMs can easily scale up studies to include global cities with minimal effort. In situations where no data is available, having some insight from an LLM is better than having none, especially when attempting to generalize a scientific study to a global scale. While we do not believe that data from LLMs should be directly trusted to derive rigorous scientific findings, we do think that this data can be valuable in helping to test some hypotheses.



Figure 3: A strong correlation between public transportation scores retrieved from LLM and the public transportation metric computed from raw transportation data (Verbavatz and Barthelemy 2020).

Motivated by the examples above, we conduct extensive experiments to explore what LLMs know about cities. Our experiments cover more than 40 tasks, each involving hundreds of cities on average. These tasks encompass various aspects of cities, including the environment, transportation, energy, crime, industry, and more. We also experiment with different ways to prompt the LLM and test various models. Through these experiments, we discover many interesting findings, with our key insight being that LLMs know something about everywhere.

In summary, our contributions are as follows:

- We systematically investigate the knowledge in LLMs about cities, providing a comprehensive analysis across a broad range of city-related tasks.
- We demonstrate that LLMs can effectively identify and leverage latent features within both cities and regions, even in the absence of direct data, offering a novel approach to modeling urban and regional phenomena and generalizing insights across different areas. This suggests a scalable method for extending research to locations with limited or no data availability.
- We provide valuable experimental results that pave the way for future studies on the application of LLMs in city research, opening new possibilities for understanding global cities.

Related Work

LLM as a Knowledge Base

By pre-training large language models on vast amounts of data, they acquire a significant amount of knowledge. Since the advent of pre-trained language models, numerous studies have sought to quantify the extent of knowledge contained within these models (Roberts, Raffel, and Shazeer 2020). A common focus has been on evaluating how well these models respond to factual knowledge (Petroni et al. 2019; Jiang et al. 2020). Other areas of investigation include commonsense knowledge (Davison, Feldman, and Rush 2019), time-sensitive knowledge (Dhingra et al. 2022), biomedical knowledge (Sung et al. 2021), geospatial knowledge (Manvi et al. 2023), among others. Our work draws inspiration from GeoLLM (Manvi et al. 2023), which explores using LLMs to infer global geospatial knowledge such as population and education. However, we specifically focus on cities, examining how to extract city knowledge and exploring how this knowledge correlates with open city data.

Extracting Knowledge from LLM

LLMs are known to embed extensive knowledge, yet the challenge lies in effectively extracting this knowledge in a desired way. A common approach involves fine-tuning the LLM by adapting its pre-trained weights to a new data domain, thereby enabling its prediction capabilities in that area (Radford et al. 2018). Recent years have seen the development of efficient fine-tuning frameworks like LoRA (Hu et al. 2021), which optimizes the process by using lowrank matrices to approximate necessary adjustments instead of modifying entire weight matrices. Another group of research focuses on prompt tuning (Zhong, Friedman, and Chen 2021), which seeks to design prompts that effectively leverage the pre-trained model's knowledge in new domains. Crafting effective prompts is notoriously challenging (Qin and Eisner 2021); thus, strategies like chain-of-thought reasoning (Wei et al. 2022) and instruction templates (Longpre et al. 2023) have demonstrated more effective in guiding LLMs toward accurate responses. Rather than adapting the pre-trained model to a specific new field, we propose to investigate the extent of city knowledge that LLMs can reveal across various aspects. Our goal is to demonstrate that LLMs can achieve comparable accuracy to traditional feature engineering approaches but with significantly less effort.

LLM for City Tasks

Recent studies have been utilizing the large language model (LLM) to better tackle traffic-related tasks (Jin et al. 2024; Minaee et al. 2024). Generally, the utilization of LLM can be divided into three categories. (1) LLM as prediction model. Most of the current methods aim to use LLM as a predictor. Hence, the critical step is to convert the time series data into the space of LLM, by quantizing the time series into discrete tokens (Ansari et al. 2024) through methods like VQ-VAE or training a separate encoder to align the time series to LLM semantic space (Zhou et al. 2023). Thus, LLM can be used to make time series predictions (Gruver et al. 2024) like traffic prediction. (2) Fine-tuned LLM as a prediction model. Recent studies further explored utilizing the traffic time series data to fine-tune the pre-trained LLM model (Jin et al. 2023; Cao et al. 2023; Chang, Peng, and Chen 2023) to achieve better prediction results. Extra background information like date and hour can be extracted from the time series to help LLM better fine-tune (Guo et al. 2024). (3) LLM to enhance feature. Researchers also try to use LLM as a feature extractor (Xue and Salim 2023) to reveal more information from the time series data and use this information to further make predictions. (4) LLM to interpret instructions to run traffic models. Some studies also use the power of LLM to facilitate a front-end chatbot in which people can call several traffic analysis tools (Zhang et al. 2024a). In contrast, we are working on a completely different problem, in which we aim to use LLM to extract external long-tail knowledge and verify its effectiveness on various tasks, instead of one specific prediction task.

Problem and Method

Given a set of cities (or regions in a city) $C = \{c_1, c_2, \ldots, c_n\}$, we are interested in obtaining the target variable values for all cities (or regions) in C. Let the target variable be denoted by y. The goal is to determine the values $y(c_i)$ for each city c_i in the set C. Cities or regions in the cities are treated the same in the method. We will use cities for simplicity in the description of the method.

We conduct experiments in two categories:

- Directly asking LLM. This method is to directly ask LLM about the values of the target value for the city of interest.
- Extract features and train an ML model. This line of methods is to ask LLM about the features that potentially correlate with the target variable for the city of interest. Using these features retrieved for each city, we then train a machine learning model to predict the target variables across the set of cities.

We will describe the methods in detail in the rest of the section.

Directly Asking LLM

When directly asking LLM, the prompt includes both the city name and the target variable. The following is a template applicable to all tasks.

```
Your task is to provide target information about {Place}.
Organize your answer in a JSON object containing the
following keys:
- zone: The name of the city, {Place}
- pred: {Target} {Unit} in {Place}
```

If the city or the target variable changes, we simply adjust the "Target", "Place", and "Unit" accordingly.

Implicit Feature Extraction

To extract the features for the target variable, we obtain the last hidden states from the LLM and then treat them as features. These features may not be human-understandable but they encapsulate knowledge relevant to the city and the target variable.

We use the same prompt as the one used in directly asking LLM. The last hidden layer is used to extract features. However, directly using the last layer is problematic due to its size. For example, the last hidden layer of Llama3.1-8B is the size of 37×4096 . Since our data samples are usually in the scale of hundreds, the high dimensionality will cause the under-fitting of the machine learning models. It is necessary to conduct dimension reduction for the raw features from the last hidden layer.




Figure 4: Features of a specific task are extracted from the last hidden state using Llama3.1-8B.

As shown in Figure 4, to conduct dimension reduction, we first use a concatenated mean-max pooling technique, followed by a linear transformation, inspired by common practices in NLP (Lin et al. 2017) and computer vision (Kipf and Welling 2016). The dimension of features is 32 by default in experiments. A machine learning model is further trained on the extracted features and the target variable.

We could only conduct this experiment on the opensource LLMs. LLMs such as chatGPT only provide API access, limiting the access of the hidden layers. In the experiments, we use Llama3.1-8B-Instruct by default. We also conduct experiments using Llama3.1-70B-Instruct. The difference between these two models is marginal in our tasks.

Explicit Feature Extraction

Another method to extract features is to explicitly include the feature names in the prompt. Different from implicit feature extraction, such an explicit approach can extract features that are human-understandable. The following example is a template applicable to all tasks.

```
Your task is to provide feature information about {Place}.

Please provide information about <{feature1>,

<{feature2}, and <{feature3} in {Place}:

{feature2}: {description1}

{feature3}: {description2}

{feature3}: {description3}


Please organize your answer in a JSON object containing


the following keys:

"{feature1}" (scale from 0.0 to 10.0),

"{feature3}" (scale from 0.0 to 10.0)
```

Though explicit features are good for human understanding, it is tricky to design what features to be asked. Especially for the unfamiliar target variable, we may have little knowledge of which features might be relevant. Even for the target variable that we are familiar with, we may not be sure which wording we should use for features.





Step2: Feature extraction

Figure 5: Extract relevant features impacting city-level energy consumption and provide their scaled values for a specific location (e.g. New York City in 2024) to better understand the factors influencing energy usage.

We find that instead of handcrafting features by humans, it is more effective to ask LLM about the features to use. LLM not only serves as feature extraction but also feature identification in this method. We design an interactive feature extraction framework as shown in Figure 5. In feature identification step, LLM provides the general knowledge related to the target variable. In feature extraction step, LLM provides specific knowledge about certain features for the city of interest. In this framework, the feature extraction is more coherent using the knowledge and the wording that LLM inherently encodes. The correlation with the target variable is often more significant for LLM-extracted features, leading to better model performance compared to manually selected features.

Experiment

Experiment Settings

We conduct experiments about 41 various tasks in 8 domains on two levels of data, region-level (each data point represents a census block, community area, or district) and city-level (each data point represents a city). For evaluation, we use the Root Mean Square Error (RMSE) as the primary metric.

The compared methods are listed below.

- **Exp-Feature**: Given a task, explicitly ask LLM for related feature names and then ask LLM for feature values.
- **Imp-Feature**: Ask LLM about the target variable and implicitly obtain the last hidden layer vector to represent the city/region.
- **Direct-Ask**: Directly ask LLM for predictions on the target variable.
- **No-Feature**: Use the average value of the target as the predicted value.

Note that, the Exp-Feature and Imp-Feature are further fed into an ML model. A set of frequently used ML models are tried including Decision Tree, Random Forest, Gradient Boosting, XGBoost, AdaBoost, and Linear Regressor. The best results are reported. We use 5-fold cross-validation in the ML setting.

Regarding computational resources, we use machines equipped with either four NVIDIA A30 GPUs or eight NVIDIA A100 GPUs. For the model, note that all references to Llama 3.1-8B in this paper refer specifically to Llama 3.1-8B-Instruct. Llama3.1-8B is locally deployed on A30 GPUs, while GPT-40 is accessed via API. Due to the limitations of the GPT-40 API, which does not allow access to hidden layers, the Imp-Feature method was implemented solely using the locally deployed Llama3.1-8B to extract the necessary hidden layers.

To illustrate, on the Carbon emission dataset (Nangini et al. 2019), which includes 343 global cities, the Exp-Feature and Direct-Ask experiments on GPT-40 each take approximately 50 minutes. Similarly, on Llama3.1-8B, these experiments also take around 50 minutes, while the Imp-Feature experiment requires only about 1 minute. The No-Feature experiment, which does not involve GPU computation, takes only a very short amount of time.

Overall Results

Table 1 shows the comprehensive results of 41 tasks. The key findings are as follows:

• LLMs generally provide meaningful responses, enabling us to predict target values effectively, whether through Direct-Ask or feature-based methods. For popular datasets (i.e., datasets that might be public and easy-to-be-browsed online), Direct-Ask yields the smallest error. This means *LLM directly knows the answer* (like the $PM_{2.5}$, PM_{10} , COVID-19, and Home value cases).

					GP	Т-4о	I	Jama3.1-8B	5	
Cate	egory	Task Data		Coverage	Explicit Direct		Explicit	Explicit Implicit Direct		No
		ID			Feature	Ask	Feature	Feature	Ask	Feature
		1	NO_2	749 cities, Europe	3.35	4.53	4.21	4.37	6.10	4.55
		2	<i>O</i> ₃	749 cities, Europe	1187.05	3995.10	1507.91	1468.87	4011.17	1606.76
	Ħ	3	PM_{10}	749 cities, Europe	4.20	3.87	5.00	4.64	7.70	5.55
	mer	4	$PM_{2.5}$	749 cities, Europe	3.59	2.16	3.80	3.51	4.58	4.13
	Environment	5	Methane	347 cities, China	24654.91	45339.00	34225.74	28534.40	err	35258.76
	linvi	6	Carbon emission	343 global cities	10.26	13.37	14.66	13.41	353.46	12.51
		7	Household CO ₂	52 cities, Japan	139.98	853.42	164.29	181.92	4192.01	170.19
		8	Total CO_2	82 entities, Russia	23.67	23.96	25.24	28.64	24.55	25.61
		9	Water withdrawal	391 cities, China	13.40	17.38	14.89	15.57	err	15.78
Ē	NS.	10	Total energy	331 cities, China	886.75	1208.01	1414.11	1400.86	err	1250.45
	Energy	11	Traditional energy	331 cities, China	851.10	2250.13	1202.83	1293.12	err	1154.61
	Ē	12	Renewable energy	331 cities, China	110.72	2934.21	133.37	135.49	err	143.64
िष		13	Dengue	1541 global cities	1858.82	3309.80	1945.33	1896.27	err	1947.40
City-Level	Health	14	COVID-19	415 counties, USA	2234.81	2159.20	2508.96	2367.35	2782.53	2784.65
ity-	Hei	15	Life expectancy	29 cities, England	2.59	13.10	2.81	2.61	10.70	2.90
ບ		16	Health access	374 districts, UK	5.38	16.39	7.33	7.02	20.21	6.19
F		17	Avg travel time	387 global cities	205.52	370.43	246.01	228.39	1089.14	269.47
	ort	18	Avg speed	387 global cities	7.05	10.44	8.75	8.10	16.42	10.02
	Transport	19	PNT (500m)	85 global cities	10.54	14.27	13.49	11.09	26.83	14.16
	Tra	20	PNT (1000m)	85 global cities	13.22	19.41	18.77	15.53	23.76	20.19
		21	PNT (1500m)	85 global cities	13.98	19.92	20.06	17.94	28.34	22.55
F	•	22	Total industry	245 cities, China	3357.65	3508.40	3914.05	5040.15	err	5296.17
	Industry	23	Mining	245 cities, China	314.64	329.82	324.00	344.96	err	324.14
	npu	24	Manufacture	245 cities, China	3224.63	3383.90	3805.45	4735.16	err	5010.07
	Π	25	Utilities	245 cities, China	309.55	372.22	295.15	314.23	err	378.27
ſ	do	26	Patent	487 global cities	2490.46	3305.90	2793.08	2851.43	err	2826.34
	Develop	27	Avg home value	200 cities, USA	184.32	23.96	202.87	223.66	292.84	238.02
	Ď	28	Material stocks	337 cities, China	33.71	106.68	34.68	34.24	err	36.60
		29	NYC pick-up	256 regions	1.47	3.11	1.45	1.61	3.23	1.65
	t	30	NYC drop-off	256 regions	1.69	3.95	1.72	1.78	3.61	1.79
	Transport	31	Chicago pick-up	167 regions	1.82	3.19	1.91	1.96	3.17	1.96
	ran	32	Chicago drop-off	167 regions	1.75	3.45	2.07	1.96	3.48	2.02
	L	33	DC pick-up	129 regions	1.89	3.02	1.91	1.95	4.48	1.97
Region-Level		34	DC drop-off	129 regions	1.85	3.20	1.87	1.90	4.83	1.89
on-]		35	NYC crime	177 regions	1.85	3.47	2.35	2.16	2.87	1.90
kegi	Crime	36	Chicago crime	77 regions	1.30	3.15	1.99	2.26	3.03	2.27
¥	Cri	37	DC crime	41 regions	1.90	5.19	2.87	1.90	4.01	2.35
		38	Cincinnati crime	67 regions	1.60	4.70	1.92	1.79	3.57	1.74
F		39	NYC 311	177 regions	1.84	4.43	2.15	1.85	3.59	2.19
	311	40	Austin 311	69 regions	1.75	4.19	2.72	1.67	3.33	2.57
		41	Cincinnati 311	47 regions	2.09	5.03	3.22	2.16	3.25	2.78

Table 1: Results on City-level and Region-level tasks for cities all over the world. The values represent RMSE (Root Mean Square Error) compared to ground truth. "err" indicates the return of answers may be entirely unrelated to the question. Units and notations are detailed in the supplementary material.

- For most of the cases, extracting features improves the performance over Direct-Ask and No-Feature. This means that even for target values that LLM does not directly know, *LLM can help to extract useful features to assist the prediction*.
- In terms of different LLM models, *GPT-40 performs better in general*. This selection of various LLMs will be further illustrated later in the experiment.
- It is interesting to see that Exp-Feature and Imp-Feature using Llama3.1-8B show a tie in their performance, indicating that *explicitly extracting features is recommended in practice* because not all LLMs provide the hidden layers as Llama does.

Q1: Can we determine when LLM knows or does not know the answer?

Although it can be fairly difficult to prove what LLM says is correct (without knowing the ground truth), there are some obvious flags when LLM does not know.

Detecting consistent generic values. If the LLM frequently produces the same rounded number, such as 50, across various contexts, it suggests that the model may lack specific knowledge about the data in question. This behavior indicates a tendency to default to a generic or placeholder value rather than providing a contextually informed estimate. As shown in Figure 6, for the queries on values of Industry Output of Mining for 245 cities in China (Zhang et al. 2024b), LLM outputs certain placeholder values for most of the time ('5' for 54 times, and '50' for 176 times out of the 245 city queries). This is clearly suggesting suspicious generic outputs.




Figure 6: Query results on Mining for 245 cities. 93.9% queried values are '5' and '50'. This indicates LLM frequently defaults to placeholder values for unknown tasks.

Detecting inconsistent values among different rounds of generations. If the outputs of the LLM regarding the same query exhibit large variance, this suggests that the model may be uncertain about the information and is generating responses based on random guesses rather than a solid knowledge of the data. Such inconsistency indicates that the LLM may not be reliably estimating the information, instead oscillating between generic or uncertain predictions. As shown

in Figure 7, we plot the re-scaled deviation of each sample in 100 queries for two datasets, COVID-19 (CDC 2023) and Mining. For a dataset that LLM has high confidence, COVID-19, its output is very stable. While for a dataset that LLM has no clear answer, Mining, its output has a much larger deviation. This aligns with the fact that LLM does a good job in the COVID-19 prediction while a poor job in the Mining prediction.




Figure 7: Re-scaled deviation of each sample in 100 queries for two cities in two datasets: COVID-19 (Los Angeles, California) and Mining (Tianjin, China). The responses show much more certainty for COVID-19 compared to Mining, indicating that the LLM is more confident in its knowledge of COVID-19 data but lacks certainty regarding Mining data.

Q2: Can LLM tell the precise value of the features?

When asking LLM for feature values, it is observed that LLM may generate data with some randomness. Here, we ask LLM to generate features for PNT on a scale of 0.0-10.0 and 0.0-100.0. The extracted feature values on a scale of 0.0-10.0 are shown in Figure 8. A pattern emerges where the generated features tend to cluster around specific intervals (e.g., 5.0, 5.5, 6.0). When changing the feature scale to 0.0-100.0, the original feature values are basically amplified by 10 times. Averaging results across scales of 0.0-10.0 and 0.0-100.0 reveals that over 60% of standard deviations are less than 1.0, indicating consistent feature extraction by the LLM across different scales, with minor variation added.




Figure 8: Count statistics of the public transportation score extracted from LLM using the 0.0-10.0 scale in the PNT dataset. The extracted scores occur at a certain fixed gap value (0.5).

Thus, it is easy to conclude that LLM is not outputting the precise value. Since LLM-generated features do help the prediction (as in Table 1), it can be inferred that LLMgenerated features keep the relative order of samples compared with the ground truth samples. Here, we plot the ground truth nightlife POI data (Wang et al. 2016) and LLMgenerated nightlife POI data for Chicago in Figure 9. We can observe that although the exact values in the two feature sets are different, the relative order among different regions is close.




Figure 9: Similarity is being observed on Chicago Nightlife Feature (left: POI data processed from (Wang et al. 2016); right: explicit feature extracted by GPT-40). Darker colors indicate more active nightlife in the regions.

Q3: Which LLM model performs the best?

While we have compared GPT-40 and Llama3.1-8B in Table 1, here we further compare several frequently-used LLM via API queries. These LLMs are asked to generate the Methane data (Du et al. 2024) of 347 cities in China using the Exp-Feature manner. It is obvious that GPT-40 achieves the best performance and all other three models hold an 8% - 19% larger error.

Model	Methane	+Error
GPT-40	24654.910	/
Claude3.5-sonnet	26610.090	+7.9%
Deepseek-chat	28310.989	+14.8%
Qwen2-72B-Instruct	29364.221	+19.1%

Table 2: Comparison of RMSE across different LLMs on the Methane dataset. The "+Error" column shows the relative percentage increase compared to GPT-40.

We further investigate the impact of model size by implicit feature Llama3.1-8B and Llama3.1-70B for the NYC 311 data (nyc opendata 2023) three times. The results in Table 3 show that the model size does not make too much difference.

Q4: Which language should be used to formulate the prompt?

We formulate the prompts in Chinese and English respectively and test the Direct-Ask performance on two datasets,

Model	Llama3.1-8B		Model Llama3.1-8B Llama3.1		ma3.1-7	70B
Run	1	2	3	1	2	3
RMSE	1.81	1.89	1.97	1.89	1.98	1.91

Table 3: Comparison of RMSE results from three runs using Llama3.1 (8B and 70B) on the NYC 311 dataset with Imp-Feature. The findings indicate that a larger model size did not lead to better performance.

Material stocks (Li et al. 2023) and PNT(1500m). Since Material stocks focus on Chinese cities while PNT(1500m) covers worldwide cities, we expect prompts in different languages to exhibit different performances. The results are shown in Table 4. For global cities, using English brings a better performance, while for Chinese cities, using Chinese can bring a similar performance as using English.

Material s	tocks (China)	PNT(1500m) (Global)		
English	Chinese	English	Chinese	
33.706	33.216	13.976	15.522	

Table 4: The impact of Language on Direct-Ask performance across Material Stocks and PNT(1500m), which shows that English performs better for global cities, while Chinese and English are close in performance for Chinese cities.

Conclusion

Our paper conducts extensive experiments to explore what LLM knows about cities. From experiments, there are three key takeaways. (1) LLM knows something about everywhere. Our experiments include global cities on all continents. All the experiments consistently show that LLM either directly knows the answer or contains related features that could be used to train ML models with 18% improvements over the No-Feature method. (2) It is obvious to know when LLM does not know. Most of our tasks are not common knowledge and LLM may have not seen such data before. In these cases, we commonly see that LLM generates generic or random answers. (3) Explicit feature extraction is often more effective and versatile, offering a structured approach to capturing information across both open-source and closed-source models. Though Exp-Feature and Imp-Feature with Llama 3.1-8B perform similarly, Exp-Feature is recommended since not all LLMs provide accessible hidden layers. Additionally, our method could offer valuable insights into how different models perform in city contexts. In conclusion, our work paves the way for future studies on the application of LLMs in city research, opening new possibilities for understanding global cities.

References

Ansari, A. F.; Stella, L.; Turkmen, C.; Zhang, X.; Mercado, P.; Shen, H.; Shchur, O.; Rangapuram, S. S.; Arango, S. P.; Kapoor, S.; et al. 2024. Chronos: Learning the language of time series. *arXiv preprint arXiv:2403.07815*.

Cao, D.; Jia, F.; Arik, S. O.; Pfister, T.; Zheng, Y.; Ye, W.; and Liu, Y. 2023. Tempo: Prompt-based generative pre-trained transformer for time series forecasting. *arXiv* preprint arXiv:2310.04948.

CDC. 2023. Provisional COVID-19 Death Counts in the United States by County. Data retrieved from CDC data catalog. Effective June 28, 2023, this dataset will no longer be updated. Similar data are accessible from CDC WONDER (https://wonder.cdc.gov/mcd-icd10-provisional.html).

Chang, C.; Peng, W.-C.; and Chen, T.-F. 2023. Llm4ts: Twostage fine-tuning for time-series forecasting with pre-trained llms. *arXiv preprint arXiv:2308.08469*.

Chicago Police Department. 2024. Chicago Crimes - 2014. Chicago Data Portal. Accessed: 2024-07-31.

Cincinnati Police Department. 2024. PDI (Police Data Initiative) Crime Incidents. City of Cincinnati Open Data Portal. Accessed: 2024-08-01.

City of Chicago. 2024. Transportation Network Providers - Trips (2023-). Accessed: 2024-7-25.

Clarke, J.; Lim, A.; Gupte, P.; et al. 2024. A global dataset of publicly available dengue case count data. *Scientific Data*, 11: 296.

Daras, K.; Green, M. A.; Davies, A.; Barr, B.; and Singleton, A. 2019. Open data on health-related neighbourhood features in Great Britain. *Sci Data*, 6.

Davison, J.; Feldman, J.; and Rush, A. M. 2019. Commonsense knowledge mining from pretrained models. In *Proceedings of the 2019 conference on empirical methods in natural language processing and the 9th international joint conference on natural language processing (EMNLP-IJCNLP)*, 1173–1178.

Department of For Hire Vehicles. 2022. Taxi Trips in 2017. Accessed: 2024-7-25.

Dhingra, B.; Cole, J. R.; Eisenschlos, J. M.; Gillick, D.; Eisenstein, J.; and Cohen, W. W. 2022. Time-aware language models as temporal knowledge bases. *Transactions of the Association for Computational Linguistics*, 10: 257–273.

Du, M.; Kang, X.; Liu, Q.; et al. 2024. City-level livestock methane emissions in China from 2010 to 2020. *Scientific Data*, 11: 251.

European Environment Agency. 2021. Air Quality Health Risk Assessments for cities and urban centres. Accessed: 2024-7-30.

Gruver, N.; Finzi, M.; Qiu, S.; and Wilson, A. G. 2024. Large language models are zero-shot time series forecasters. *Advances in Neural Information Processing Systems*, 36.

Guo, X.; Zhang, Q.; Jiang, J.; Peng, M.; Yang, H. F.; and Zhu, M. 2024. Towards Responsible and Reliable Traffic

Flow Prediction with Large Language Models. Available at SSRN 4805901.

Han, Z.; Xia, T.; Xi, Y.; et al. 2023. Healthy Cities, A comprehensive dataset for environmental determinants of health in England cities. *Scientific Data*, 10.

Hu, E. J.; Wallis, P.; Allen-Zhu, Z.; Li, Y.; Wang, S.; Wang, L.; Chen, W.; et al. 2021. LoRA: Low-Rank Adaptation of Large Language Models. In *International Conference on Learning Representations*.

Jiang, Z.; Xu, F. F.; Araki, J.; and Neubig, G. 2020. How can we know what language models know? *Transactions of the Association for Computational Linguistics*, 8: 423–438.

Jin, M.; Wang, S.; Ma, L.; Chu, Z.; Zhang, J. Y.; Shi, X.; Chen, P.-Y.; Liang, Y.; Li, Y.-F.; Pan, S.; et al. 2023. Time-LLM: Time Series Forecasting by Reprogramming Large Language Models. In *The Twelfth International Conference on Learning Representations*.

Jin, M.; Zhang, Y.; Chen, W.; Zhang, K.; Liang, Y.; Yang, B.; Wang, J.; Pan, S.; and Wen, Q. 2024. Position: What Can Large Language Models Tell Us about Time Series Analysis. In *Forty-first International Conference on Machine Learning*.

Kipf, T. N.; and Welling, M. 2016. Semi-Supervised Classification with Graph Convolutional Networks. *CoRR*, abs/1609.02907.

Li, X.; Song, L.; Liu, Q.; Ouyang, X.; Mao, T.; Lu, H.; Liu, L.; Liu, X.; Chen, W.; and Liu, G. 2023. Product, building, and infrastructure material stocks dataset for 337 Chinese cities between 1978 and 2020. *Scientific Data*, 10(1): 228.

Lin, Z.; Feng, M.; dos Santos, C. N.; Yu, M.; Xiang, B.; Zhou, B.; and Bengio, Y. 2017. A Structured Self-attentive Sentence Embedding. *CoRR*, abs/1703.03130.

Long, Y.; Jiang, Y.; Chen, P.; Sharifi, A.; Gasparatos, A.; Wu, Y.; Kenichiro, K.; guan, D.; Yoshida, Y.; and Shigetomi, Y. 2021. Monthly direct and indirect greenhouse gases emissions from household consumption in the major Japanese cities. *Scientific Data*.

Longpre, S.; Hou, L.; Vu, T.; Webson, A.; Chung, H. W.; Tay, Y.; Zhou, D.; Le, Q. V.; Zoph, B.; Wei, J.; et al. 2023. The flan collection: Designing data and methods for effective instruction tuning. In *International Conference on Machine Learning*, 22631–22648. PMLR.

Manvi, R.; Khanna, S.; Mai, G.; Burke, M.; Lobell, D.; and Ermon, S. 2023. Geollm: Extracting geospatial knowledge from large language models. *arXiv preprint arXiv:2310.06213*.

Minaee, S.; Mikolov, T.; Nikzad, N.; Chenaghlu, M.; Socher, R.; Amatriain, X.; and Gao, J. 2024. Large language models: A survey. *arXiv preprint arXiv:2402.06196*.

Nangini, C.; Peregon, A.; Ciais, P.; Weddige, U.; Vogel, F.; Wang, J.; Bréon, F.-M.; Bachra, S.; Wang, Y.; Gurney, K.; Yamagata, Y.; Appleby, K.; Telahoun, S.; Canadell, J. G.; Grübler, A.; Dhakal, S.; and Creutzig, F. 2019. A global dataset of CO2 emissions and ancillary data related to emissions for 343 cities. *Sci Data*, 6: 180280. New York City Taxi & Limousine Commission. 2024. TLC Trip Record Data. Accessed: 2024-6-22.

NHIT Data Fusion Center. 2024. Washington D.C. Crime Incidents - 2020. NHIT Data Fusion Center. Accessed: 2024-07-18.

nyc opendata. 2023. 311 Service Requests from 2010 to Present. https://data.cityofnewyork.us/Social-Services/311-Service-Requests-from-2010-to-Present/erm2-nwe9/ data_preview.

of Austin Open Data Portal, C. 2024. Austin 311 Service Requests. https://datahub.austintexas.gov/Utilities-and-City-Services/Austin-311-Public-Data/xwdj-i9he/about_data.

of Cincinnati Open Data Portal, C. 2024. Cincinnati 311 Non-Emergency Service Requests. https://data.cincinnatioh.gov/Thriving-Neighborhoods/Cincinnati-311-Non-Emergency-Service-Requests/4cjh-bm8b/about_data.

Petroni, F.; Rocktäschel, T.; Lewis, P.; Bakhtin, A.; Wu, Y.; Miller, A. H.; and Riedel, S. 2019. Language models as knowledge bases? *arXiv preprint arXiv:1909.01066*.

Police Department (NYPD). 2024. NYPD Arrests Data (Historic). NYC OpenData. Accessed: 2024-04-24.

Qin, G.; and Eisner, J. 2021. Learning how to ask: Querying LMs with mixtures of soft prompts. *arXiv preprint arXiv:2104.06599*.

Radford, A.; Narasimhan, K.; Salimans, T.; Sutskever, I.; et al. 2018. Improving language understanding by generative pre-training. *OpenAI*.

Roberts, A.; Raffel, C.; and Shazeer, N. 2020. How much knowledge can you pack into the parameters of a language model? *arXiv preprint arXiv:2002.08910*.

Sung, M.; Lee, J.; Yi, S.; Jeon, M.; Kim, S.; and Kang, J. 2021. Can language models be biomedical knowledge bases? *arXiv preprint arXiv:2109.07154*.

TomTom International BV . 2023. TomTom Traffic Index. Accessed: 2024-7-31.

Verbavatz, V.; and Barthelemy, M. 2020. Access to mass rapid transit in OECD urban areas. *Scientific Data*, 7(1): 301.

Wang, H.; Kifer, D.; Graif, C.; and Li, Z. 2016. Crime rate inference with big data. In *Proceedings of the 22nd ACM SIGKDD international conference on knowledge discovery and data mining*, 635–644.

Wei, J.; Wang, X.; Schuurmans, D.; Bosma, M.; Xia, F.; Chi, E.; Le, Q. V.; Zhou, D.; et al. 2022. Chain-of-thought prompting elicits reasoning in large language models. *Advances in neural information processing systems*, 35: 24824–24837.

Xiao, H.; Zhao, W.; Shan, Y.; and Guan, D. 2020. CO2 emission accounts of Russia's constituent entities 2005-2019. *Scientific Data*.

Xue, H.; and Salim, F. D. 2023. Promptcast: A new promptbased learning paradigm for time series forecasting. *IEEE Transactions on Knowledge and Data Engineering*. Yang, G.; Zhang, G.; Cao, D.; Gao, X.; Wang, X.; Yang, S.; Jiang, P.; Zha, D.; and Shan, Y. 2024. A comprehensive citylevel final energy consumption dataset including renewable energy for China, 2005–2021. *Scientific Data*, 11: 738.

Zhang, S.; Fu, D.; Liang, W.; Zhang, Z.; Yu, B.; Cai, P.; and Yao, B. 2024a. Trafficgpt: Viewing, processing and interacting with traffic foundation models. *Transport Policy*, 150: 95–105.

Zhang, Z.; Shan, Y.; Zhao, D.; Cai, B.; Li, X.; Guan, D.; et al. 2024b. City-level water withdrawal and scarcity accounts of China. figshare. Collection. Accessed: 2024-7-30.

Zhong, Z.; Friedman, D.; and Chen, D. 2021. Factual Probing Is [MASK]: Learning vs. Learning to Recall. In 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, NAACL-HLT 2021, 5017–5033. Association for Computational Linguistics (ACL).

Zhou, T.; Niu, P.; Sun, L.; Jin, R.; et al. 2023. One fits all: Power general time series analysis by pretrained lm. *Advances in neural information processing systems*, 36: 43322–43355.

Zillow, I. 2024. Zillow Research Data.

Task Descriptions

[1-4] NO₂, O₃, PM₁₀, PM_{2.5}

Data Description This study utilizes Air Quality Health Risk Assessments for cities and urban centers in 2021 (European Environment Agency 2021), employing the ESTAT Urban Audit Cities (LAU) as the City Boundary Specification, focusing on cities within European countries. It aggregates and analyzes the Air Pollution Population Weighted Average statistics for four key air pollutants: NO₂, O₃, PM₁₀, and PM_{2.5}.

Data Preprocess We first filter the rows where the "Air Pollutant" is "NO₂". Then, we merge the "City" column and the "Country Or Territory" column into a new target column and select the "Air Pollution Population Weighted Average $[\mu g/m^3]$ " as the target column.

Feature

- Population Density: How densely populated the area is? (0.0: very low, 10.0: very high)
- Traffic Volume: How heavy the traffic is? (0.0: very low, 10.0: very high)
- Industrial Activity: How much industrial activity is there, including factories and other industrial facilities? (0.0: very low, 10.0: very high)
- Sunlight Exposure: How much sunlight the area receives? (0.0: very low, 10.0: very high)
- Green Spaces: How extensive the green spaces are? (0.0: very poor, 10.0: very extensive)
- Regulatory Measures: How strict and effective the regulatory measures for controlling NO2 emission are? (0.0: very poor, 10.0: very strict)

Table 1: Correlation and p-value of NO₂ features.

Features	Correlation	p-value
population_density	0.4759	0.0000
traffic_volume	0.5284	0.0000
industrial_activity	0.3636	0.0000
sunlight_exposure	0.1033	0.0047
green_spaces	-0.3116	0.0000
regulatory_measures	-0.1861	0.0000

Table 2: Correlation and p-value of O₃ features.

Features	Correlation	p-value
population_density	0.1316	0.0003
traffic_volume	0.1164	0.0014
industrial_activity	-0.0040	0.9136
sunlight_exposure	0.6217	0.0000
green_spaces	-0.3334	0.0000
regulatory_measures	-0.2210	0.0000

Table 3: Correlation and p-value of PM_{10} features.

Features	Correlation	p-value
population_density	0.1532	0.0000
traffic_volume	0.1650	0.0000
industrial_activity	0.2149	0.0000
sunlight_exposure	0.2798	0.0000
green_spaces	-0.4429	0.0000
regulatory_measures	-0.4731	0.0000

Table 4: Correlation and p-value of $PM_{2.5}$ features.

Features	Correlation	p-value
population_density	0.0415	0.2561
traffic_volume	0.1015	0.0054
industrial_activity	0.2222	0.0000
sunlight_exposure	-0.0114	0.7555
green_spaces	-0.2834	0.0000
regulatory_measures	-0.3841	0.0000

[5] Methane

Data Description This dataset (Du et al. 2024) presents a comprehensive city-level inventory of livestock methane emission in China from 2010 to 2020, incorporating biological, management, and environmental variables. The data is measured in tonnes.

Data Preprocess The methane emission from livestock, measured in tons per year, are analyzed using data from 2020, encompassing 347 cities across China.

Feature

- Livestock Density: Measures the density of livestock in the area (0.0: very low density, 10.0: very high density). Based on the number of livestock per square mile.
- Feeding Practices: Reflects the type of feeding practices in the area (0.0: very poor, 10.0: very good). Based on the composition of livestock feed.
- Manure Management: Measures the effectiveness of manure management practices in the area (0.0: very poor, 10.0: excellent). Includes methods of handling and processing livestock manure.
- Climate Conditions: Reflects the climate conditions of the area (0.0: very low, 10.0: very high). Based on temperature and humidity.
- Policy and Technology: Measures the implementation of policies and technologies aimed at reducing methane emission (0.0: very poor, 10.0: excellent). Includes the use of methane inhibitors, feed additives, and government regulations.

[6] Carbon emission

Data Description This dataset (Nangini et al. 2019) provides a comprehensive compilation of anthropogenic CO_2 emission data for 343 cities worldwide. It integrates data

Table 5: Correlation and p-value of Methane features.

Features	Correlation	p-value
livestock_density	0.2377	0.0000
feeding_practices	-0.0517	0.3368
manure_management	-0.0383	0.4765
climate_conditions	-0.0896	0.0956
policy_and_technology	-0.3129	0.0000

from three major sources: the Carbon Disclosure Project (CDP), the Bonn Center for Local Climate Action and Reporting (Carbonn), and Peking University. The dataset includes both self-reported and systematically collected data, with additional quality control measures and corrections applied to ensure accuracy and consistency. The data is measured in million tonnes of CO_2 (MtCO₂-eq).

Data Preprocess Total emission (CDP) [MtCO₂-eq] is chosen as the target value. Then Cities with zero Carbon emission values are removed from thes dataset.

Feature

- Population: The population of the city. (0.0: very low, 10.0: very high)
- GDP: The Gross Domestic Product of the city. (0.0: very low, 10.0: very high)
- Average Annual Temperature: The average annual temperature of the city. (0.0: very low, 10.0: very high)
- Built-up Area: The built-up area of the city. (0.0: very low, 10.0: very high)

Table 6: Correlation and p-value of Carbon emission features.

Features	Correlation	p-value
population	0.5605	0.0000
gdp	0.4387	0.0000
average_annual_temperature	0.1725	0.0186
built-up_area	0.5119	0.0000

[7] Household CO₂

Data Description The dataset utilized in this study (Long et al. 2021) comprises an emission inventory of urban house-hold CO_2 -equivalent emissions for 52 major cities in Japan. It includes fossil fuels related to direct household emissions such as gasoline, kerosene, liquefied petroleum gas, and city gas. These emissions are calculated by converting the monthly household expenditures on these fuels, as reported in the (?), into grams of CO_2 -equivalent per capita (g- CO_2 eq/capita).

Data Preprocess For the purpose of this study, the direct emission $[g-CO_2$ equivalent per capita] for the year 2015 across the 52 Japanese cities are selected as the target variable.

Feature

- Use of Fossil Fuels: Household use of gasoline, kerosene, LPG, and city gas. (0.0: very low, 10.0: very high)
- Consumption of Goods and Services: consumed goods and services, including food, electricity, durable goods, and entertainment. (0.0: very low, 10.0: very high)
- City Size and Population Density: The size and population density of the city. (0.0: very low, 10.0: very high)
- Population: The population of the city. (0.0: very low, 10.0: very high)
- Household Economic Level: The economic level of the households in the city. (0.0: very low, 10.0: very high)
- Average Annual Temperature: The average annual temperature of the city. (0.0: very low, 10.0: very high)
- Public Transport and Infrastructure: The development of public transport systems and infrastructure. (0.0: very low, 10.0: very high)

Table 7: Correlation and p-value of Household CO₂ features.

Features	Correlation	p-value
use_of_fossil_fuels	-0.2566	0.0663
consumption	-0.2688	0.0540
city_size	-0.2262	0.1069
population	-0.1786	0.2052
household_economy	-0.1455	0.3033
average_annual_temperatures	-0.7210	0.0000
public_transport_and_infrastructure	-0.2193	0.1183

[8] Total CO₂

Data Description The dataset (Xiao et al. 2020) provides CO_2 emissions data for Russia's 82 constituent entities from 2005 to 2019. For this experiment, the total CO_2 emissions of each entity in 2019 are selected, with emissions measured in million tonnes.

Data Preprocess The target variable is calculated by summing the energy-related and process-related emissions for each entity in 2019.

- Agriculture Forestry and Fishing: How significant are agriculture, forestry, and fishing activities in the region? (0.0: very low, 10.0: very high)
- Mining and Quarrying: How significant are mining and quarrying activities in the region? (0.0: very low, 10.0: very high)
- Manufacturing: How significant are manufacturing activities in the region? (0.0: very low, 10.0: very high)
- Electricity, Gas, Steam: How significant are these utilities in the region? (0.0: very low, 10.0: very high)
- Water Supply: How significant are these activities in the region? (0.0: very low, 10.0: very high)
- Construction: How significant are construction activities in the region? (0.0: very low, 10.0: very high)

- Wholesale and Retail Trade: How significant are wholesale and retail trade activities in the region? (0.0: very low, 10.0: very high)
- Transportation and Storage: How significant are transportation and storage activities in the region? (0.0: very low, 10.0: very high)
- Human Health and Social Work: How significant are human health and social work activities in the region? (0.0: very low, 10.0: very high)

Table 8: Correlation and p-value of Total CO₂ features.

Features	Correlation	p-value
agriculture_forestry_fishing	-0.2925	0.0077
mining_and_quarrying	0.3091	0.0047
manufacturing	0.4546	0.0000
electricity_gas_steam	0.3130	0.0042
water_supply	0.3830	0.0004
construction	0.3451	0.0015
wholesale_and_retail_trade	0.3082	0.0048
transportation_and_storage	0.4165	0.0001
human_health_and_social_work	0.1907	0.0862

[9] Water withdrawal

Data Description The City-level water withdrawal and scarcity accounts of China dataset (Zhang et al. 2024b) is used for this experiment. The data is measured in 100 million cubic meters (100 million m^3).

Data Preprocess The dataset provides information on water withdrawal, availability, and criticality for different cities in China. For this task, only the water withdrawal data is considered. The zero-value entries are removed to ensure the dataset accurately reflects cities with active water usage.

Feature

- Population: How densely populated the area is? (0.0: very low, 10.0: very high)
- Climate: The general climate of the area. (0.0: very harsh, 10.0: very mild)
- Economy: The economic activity and development level. (0.0: very poor, 10.0: very strong)
- Agriculture: The extent of agricultural activity and land use. (0.0: very low, 10.0: very high)
- Industry: How much industrial activity is there, including factories and other industrial facilities? (0.0: very low, 10.0: very high)

[10-12] Energy (Total, Traditional and Renewable)

Data Description The dataset (Yang et al. 2024) provides an extensive inventory of final energy consumption across 331 Chinese cities from 2005 to 2021. The data is measured in 10,000 tonnes of coal equivalent (10Kt-coal-eq). Table 9: Correlation and p-value of Water withdrawal features.

Features	Correlation	p-value
population	0.3919	0.0000
climate	0.0162	0.7488
economy	0.3374	0.0000
agriculture	0.1117	0.0264
industry	0.2700	0.0000

Data Preprocess Cities with zero energy consumption values are removed from the dataset. The Total, Traditional, and Renewable Energy consumption data are each selected as target variables for separate analyses.

- Population: The population of the city. (0.0: very low, 10.0: very high)
- GDP: The Gross Domestic Product of the city. (0.0: very low, 10.0: very high)
- Average Annual Temperature: The average annual temperature of the city. (0.0: very low, 10.0: very high)
- Built-up Area: The built-up area of the city. (0.0: very low, 10.0: very high)

Features	Correlation	p-value
population	0.6026	0.0000
gdp	0.6467	0.0000
average_annual_temperature	-0.0573	0.2983
built-up_area	0.5679	0.0000

Table 11: Correlation and p-value of Traditional energy features.

Features	Correlation	p-value
population	0.5938	0.0000
gdp	0.6026	0.0000
average_annual_temperature	-0.0617	0.1762
built-up_area	0.5464	0.0000

Table 12: Correlation and p-value of Renewable energy features.

Features	Correlation	p-value
population	0.6315	0.0000
gdp	0.6058	0.0000
average_annual_temperature	0.2058	0.0000
built-up_area	0.5914	0.0000

[13] Dengue

Data Description This paper introduces the OpenDengue dataset(Clarke et al. 2024), a global collection of publicly available dengue case counts from 1924 to 2023, covering 102 countries. The dataset integrates data from 843 sources, emphasizing its high temporal (weekly/monthly) and spatial resolution. This resource aims to support research on dengue dynamics, enhance disease surveillance, and inform public health interventions. The data is measured in counts.

Data Preprocess The total number of dengue fever cases in 2020 across 1,541 cities worldwide is chosen as the target variable. Cities with missing data are excluded from the analysis to ensure data completeness and consistency.

Feature

- Population Density: Measures the population density of the area (0.0: very low, 10.0: very high). Based on the number of residents per square mile.
- Temperature: Reflects the average temperature of the area (0.0: very low, 10.0: very high). Based on the annual average temperature.
- Rainfall: Reflects the annual rainfall level in the area (0.0: very low, 10.0: very high). Based on the annual average rainfall.
- Public Health Measures: Measures the effectiveness of public health measures in the area (0.0: very low, 10.0: very high). Includes mosquito control, public education, and healthcare infrastructure.
- Urbanization Level: Measures the level of urbanization in the area (0.0: very low, 10.0: very high). Based on the presence of urban infrastructure, services, and population concentration.

Table 13: Correlation and p-value of Dengue features.

Features	Correlation	p-value
population_density	0.2867	0.0000
temperature	0.0259	0.3105
rainfall	0.0701	0.0059
public_health_measures	0.1451	0.0000
urbanization_level	0.2908	0.0000

[14] COVID-19

Data Description This dataset (CDC 2023) presents a provisional count of deaths involving COVID-19 by county of occurrence in the United States from 2020 to 2023. The data is measured in counts.

Data Preprocess Among the six urban-rural codes (Noncore, Medium metro, Small metro, Micropolitan, Large fringe metro, Large central metro), only Large fringe metro and large central metro are reserved and zero values are dropped.

Feature

- Population Density: How densely populated the county is? (0.0: very low, 10.0: very high)
- Age Distribution: What percentage of the county's population is elderly (65+ years old)? (0.0: very low, 10.0: very high)
- Healthcare Capacity: How well-equipped is the county's healthcare system? (0.0: very poor, 10.0: excellent)
- Prevalence of Pre-existing Conditions: What percentage of the population has chronic illnesses? (0.0: very low, 10.0: very high)
- Socioeconomic Factors: How favorable are the socioeconomic conditions in the county? (0.0: very unfavorable, 10.0: very favorable)

Features	Correlation	p-value
population	0.4238	0.0000
age	-0.0728	0.0679
healthcare	0.2558	0.0000
existing	0.1927	0.0000
social	0.0999	0.0122

Table 14: Correlation and p-value of COVID-19 features.

[15] Life expectancy

Data Description This dataset (Han et al. 2023) is used to study the impact of environmental factors on health in English cities. It includes a variety of variables related to the environment and health, which can be used to analyze the relationship between health conditions in different cities and environmental factors. The data is measured in years.

Data Preprocess We have chosen healthy life expectancy at birth as the primary target variable for our research, as it provides a comprehensive measure of population health. To ensure the accuracy and reliability of our analysis, we meticulously cleaned the dataset by removing all instances of missing or NaN values.

- Healthcare Quality: Reflects the overall quality and accessibility of healthcare services in the area (0.0: very poor, 10.0: excellent).
- Economic Status: Measures the economic development and average income levels of residents (0.0: very low, 10.0: very high).
- Public Health Infrastructure: Reflects the availability and quality of public health facilities and services (0.0: very poor, 10.0: excellent).
- Education Level: Measures the average educational attainment and quality of education services in the area (0.0: very low, 10.0: very high).
- Environmental Conditions: Reflects the overall environmental quality, including air and water quality (0.0: very poor, 10.0: excellent).

Table 15: Correlation and p-value of Life expectancy features.

Features	Correlation	p-value
healthcare_quality	0.6480	0.0001
economic_status	0.6381	0.0002
public_health_infrastructure	0.5385	0.0026
education_level	0.7215	0.0000
environmental_conditions	0.6200	0.0003

[16] Health access

Data Description This dataset (Daras et al. 2019) provides a comprehensive series of national open source low-level geographical measures of accessibility to various health-related features across Great Britain. It includes 14 measures categorized into three domains: retail environment, health services, and physical environment. The dataset is created using network analysis to calculate postcode accessibility to these features, resulting in a valuable resource for researchers and policymakers interested in the spatial determinants of health.

Data Preprocess We select "Access to Healthy Assets and Hazards" (AHAH) as our target variable. Outliers and missing values are removed from the dataset.

Feature

- Retail Environment: The availability and type of retail establishments, such as fast food outlets and pubs, can significantly influence the dietary and social health of a community. (0.0: very low, 10.0: very high)
- Physical Environment: The presence of green spaces, pollution levels, and other physical factors can affect the overall health and well-being of residents. (0.0: very low, 10.0: very high)
- population: The population of the city. (0.0: very low, 10.0: very high)
- GDP: The Gross Domestic Product of the city. (0.0: very low, 10.0: very high)
- average annual temperature: The average annual temperature of the city. (0.0: very low, 10.0: very high)
- built-up area: The built-up area of the city. (0.0: very low, 10.0: very high)

Table 16: Correlation and p-value of Health access features.

Features	Correlation	p-value
retail_environment	0.3120	0.0000
physical_environment	-0.3968	0.0000
population	0.4070	0.0000
gdp	0.2713	0.0000
average_annual_temperature	0.0789	0.1278
built-up_area	0.4439	0.0000

[17-18] Avg travel time, Avg speed

Data Description The TomTom Traffic Index website (TomTom International BV 2023) provides rankings and analysis of traffic information in 387 cities worldwide. Key data metrics include:

- Average travel time per 10 km: The average time to travel 10 kilometers, shown in minutes and seconds. (0.0: very low, 10.0: very high)
- Change from 2022: The difference in travel time compared to 2022. (0.0: very low, 10.0: very high)
- Congestion level: The percentage of extra travel time due to congestion during peak hours. (0.0: very low, 10.0: very high)
- Time lost per year at rush hours: The total hours lost annually in rush hour traffic. (0.0: very low, 10.0: very high)
- Average speed in rush hour: The average speed during peak hours, in kilometers per hour. (0.0: very low, 10.0: very high)

This study selects the average travel time per 10 km and average speed in rush hour for analysis. The data is measured in seconds.

Data Preprocess We convert the data in the "Average travel time per 10 km" column, such as "37 min 20s," into seconds for the target column. Additionally, we remove the "km/h" unit from the "Average speed in rush hour" column and use the modified values as the target column. The "City" column is used as the zone column.

Feature

- Traffic Volume: How heavy the traffic is? (0.0: very low, 10.0: very high)
- Road Network Quality: How good the road infrastructure is, including the number and condition of roads, highways, and bridges? (0.0: very poor, 10.0: excellent)
- Traffic Signal Efficiency: How well-optimized and efficient the traffic signal system is, including signal timing and coordination? (0.0: very poor, 10.0: very efficient)
- Public Transportation: How extensive and efficient the public transportation system is, including buses, trains, and subways? (0.0: very poor, 10.0: very extensive and efficient)
- Urban Planning: How well the city is planned, including the distribution of residential, commercial, and industrial areas, as well as zoning and land use? (0.0: very poor, 10.0: very well planned)

[19-21] PNT (500m, 1000m and 1500m)

Data Description The People Near Transit (PNT) levels are defined as the share of urban population living at geometric distances of 500m, 1,000m, and 1,500m from any MRT (mass rapid transit) station in the agglomeration. This paper (Verbavatz and Barthelemy 2020) introduces the largest global dataset of PNT. In their definition, mass rapid transit encompasses:

• Tram, streetcar, or light rail services.

Features Correlation p-value traffic_volume 0.3224 0.0000 road_network_quality -0.0200 0.6953 traffic_signal_efficiency 0.0483 0.3436 public_transportation 0.5529 0.0000 urban_planning 0.1008 0.0476

Table 17: Correlation and p-value of Avg travel time fea-

Table 18: Correlation and p-value of Avg speed features.

Features	Correlation	p-value
traffic_volume	-0.2805	0.0000
road_network_quality	-0.0339	0.5063
traffic_signal_efficiency	-0.0956	0.0601
public_transportation	-0.6363	0.0000
urban_planning	-0.1725	0.0007

- Subway, Metro, or any underground service.
- Suburban rail services.

The data is measured in percentage (%).

Data Preprocess We merge the "City" column and the "Country" column into a new target column, and select the "500m", "1000m" and "1500m" as the target columns.

Feature

tures.

- Urban Planning: How well the city is planned, including the distribution of residential, commercial, and industrial areas, as well as zoning and land use? (0.0: very poor, 10.0: very well planned)
- Road Network Quality: How good the road infrastructure is, including the number and condition of roads, highways, and bridges? (0.0: very poor, 10.0: excellent)
- Public Transportation: How extensive and efficient the public transportation system is, including buses, trains, and subways? (0.0: very poor, 10.0: very extensive and efficient)
- Government Policy: How is the government's investment and development strategy for public transportation? (0.0: very poor, 10.0: very good)

Table 19: Correlation and p-value of PNT(500m) features.

Features	Correlation	p-value
urban_planning	0.5208	0.0000
road_network_quality	0.3495	0.0010
public_transportation	0.6791	0.0000
government_policy	0.5000	0.0000

Table 20: Correlation and p-value of PNT(1000m) features.

Features	Correlation	p-value
urban_planning	0.6005	0.0000
road_network_quality	0.4185	0.0001
public_transportation	0.7611	0.0000
government_policy	0.5862	0.0000

Table 21: Correlation and p-value of PNT(1500m) features.

Features	Correlation	p-value
urban_planning road_network_quality public_transportation government_policy	0.6327 0.4408 0.7895 0.6192	$\begin{array}{c} 0.0000\\ 0.0000\\ 0.0000\\ 0.0000\\ 0.0000 \end{array}$

[22-25] Industry (Total, Mining, Manufacture, Utilities)

Data Description This dataset (Zhang et al. 2024b) contains data including various types of industry output from 245 cities in China in 2015. The data is measured in 100 million Yuan.

Data Preprocess The industry categorization is divided into three sectors: Mining (e.g., coal, metal ores, petroleum extraction), Manufacture (including food processing, textiles, machinery, electronics, and more specialized manufacturing), and Utilities (comprising electricity, gas, and water supply services).

Feature

_

- Population: How densely populated the area is? (0.0: very low, 10.0: very high)
- Resource: The amount of resources of the area (0.0: very scarce, 10.0: very rich)
- Economy: The economic activity and development level (0.0: very poor, 10.0: very strong)
- Infrastructure: The level of infrastructure, including factories and industrial facilities (0.0: very low, 10.0: very high)
- Technology: The level of technology (0.0: very low, 10.0: very high)

Table 22: Correlation and p-value of Total industry features.

Features	Correlation	p-value
population	0.6394	0.0000
resource	-0.1225	0.0556
economy	0.7632	0.0000
infrastructure	0.6840	0.0000
technology	0.7245	0.0000

Table 23: Correlation and p-value of Mining features.

Features	Correlation	p-value
population	-0.0031	0.9611
resource	0.3724	0.0000
economy	0.1105	0.0843
infrastructure	0.1096	0.0869
technology	0.0821	0.2004

Table 24: Correlation and p-value of Manufacture features.

Features	Correlation	p-value
population	0.6361	0.0000
resource	-0.1448	0.0234
economy	0.7505	0.0000
infrastructure	0.6750	0.0000
technology	0.7138	0.0000

Table 25: Correlation and p-value of Utilities features.

Features	Correlation	p-value
population	0.5008	0.0000
resource	-0.1034	0.1063
economy	0.6244	0.0000
infrastructure	0.5233	0.0000
technology	0.5925	0.0000

[26] Patent

Data Description This dataset (?) provides geographic coordinates for inventor and applicant locations in 18.8 million patent documents spanning more than 30 years. The geocoded data is further allocated to the corresponding countries, regions, and cities. The data is measured in counts.

Data Preprocess Data from 2014 is selected, focusing on the top 500 cities. Due to errors in the names of 13 cities, the final dataset includes 487 cities.

Feature

- Population: How densely populated the city is? (0.0: very low, 10.0: very high)
- Education: The amount of educational resource in this city. (0.0: very scarce, 10.0: very rich)
- Economy: The economic activity and development level. (0.0: very poor, 10.0: very strong)
- Policy: Government Incentives and Intellectual Property Laws. (0.0: very low, 10.0: very high)
- Technology: The level of technology. (0.0: very low, 10.0: very high)

[27] Avg home value

Data Description This dataset (Zillow 2024) includes housing data with home value information derived from

Table 26: Correlation and p-value of Patent features.

Features	Correlation	p-value
population	0.0645	0.1556
education	0.1497	0.0009
economy	0.1814	0.0001
policy	0.1235	0.0064
technology	0.1875	0.0000

more than 374 million public records and assessor data for approximately 200 million parcels across over 3,100 counties in the United States. The values are measured in thousands of U.S. dollars.

Data Preprocess The top 200 largest U.S. cities, ranked by size in the dataset, are selected for this study. The average monthly urban housing prices for each city in 2023 are averaged to represent the annual average housing price, which is used as the target variable.

Feature

- Regional Economic Strength: How strong is the overall economy of the city, including major industries and employment opportunities? (0.0: very low, 10.0: very high).
- Population Growth and Density: How significant is the population growth and density in the city? (0.0: very low, 10.0: very high).
- Cost of living and quality of life: How does the cost of living and quality of life (including climate, healthcare, and education) in the city impact home values? (0.0: very low, 10.0: very high).
- Infrastructure and public services: How well-developed are the infrastructure and public services (transportation, healthcare, education) in the city? (0.0: very low, 10.0: very high).
- local_housing_market_dynamics: How strong are the local housing market trends and housing supply dynamics in the city? (0.0: very low, 10.0: very high).

Table 27: Correlation and p-value of Avg home value features.

Features	Correlation	p-value
regional_economic_strength	0.4283	0.0000
population_growth_and_density	0.4689	0.0000
cost_of_living_and_quality_of_life	0.3987	0.0000
infrastructure_and_public_services	0.3792	0.0000
local_housing_market_dynamics	0.5770	0.0000

[28] Material stocks

Data Description This paper (Li et al. 2023) introduces a dataset that contains the stock of 24 materials contained in 10 types of products, buildings, and infrastructure in all 332 prefecture-level cities in China from 1978 to 2020. We select the per capita material stocks as our research target for

this part. The data is measured in tonnes per capita (tonnes/-capita).

Data Preprocess We select the data from the "2020" column in the "Material stock and population 1978-2020" table, add "China" to the "City" column to create the zone column and use the "2020" column as the target column.

Feature

- Economic Activity: How high is the level of economic activity, including industrial output, commercial activity, and service sector strength? (0.0: very low, 10.0: very high)
- Infrastructure Quality: How good is the city's infrastructure, including transportation, utilities, and communication systems? (0.0: very poor, 10.0: excellent)
- Housing Development: How well-developed is the housing sector, including the availability and quality of residential buildings? (0.0: very poor, 10.0: very well-developed)
- Land Use Policy: How effective are the city's land use policies, including zoning regulations, green space allocation, and land management practices? (0.0: very poor, 10.0: very effective)

Table 28: Correlation and p-value of Material stocks features.

Features	Correlation	p-value
economic_activity	-0.3082	0.0000
infrastructure_quality	-0.2871	0.0000
housing_development	-0.2862	0.0000
land_use_policy	-0.1278	0.0198

[29-34] Transport

Data Description For this experiment, we use trip record data from New York City, Chicago, and Washington D.C., normalizing the data across all cities to a count scale ranging from 0 to 10. The New York City data comes from the Taxi and Limousine Commission (TLC) trip record data collected in 2024 (New York City Taxi & Limousine Commission 2024). For the Chicago analysis, we utilize the Transportation Network Providers (TNP) Trips dataset, which is provided by the City of Chicago and last updated on July 26, 2024 (City of Chicago 2024). In Washington D.C., the experiment utilizes data from the Taxi Trips in 2017 dataset, which is provided by the Department of For-Hire Vehicles and last updated on September 27, 2022 (Department of For Hire Vehicles 2022).

Data Preprocess The study processes for-hire vehicle data from New York City, Chicago, and Washington D.C., focusing on hourly weekday trip patterns. The data is filtered to retain only weekday trips and is grouped by hour, pick-up zone, and drop-off zone to calculate counts, which are normalized on a scale of 0.0 to 10.0. The processed

dataset includes hourly pick-up and drop-off counts, normalized within each zone, with missing values filled in as zeros. The final dataset provides a comprehensive view of hourly traffic flow in each zone for weekdays, facilitating further analysis.

Feature

_

- Residential: How residential the area is? (0.0: least residential zone, 10.0: most residential zone)
- Commercial: How commercial the area is? (0.0: least commercial zone, 10.0: most commercial zone)
- Recreation: How people would come here for recreation? (0.0: least recreational zone, 10.0: most recreational zone)
- Tourism: How much tourism is there? (0.0: least tourists zone, 10.0: most tourists zone)
- Transportation: How good is the transportation in the area? (0.0: worst transportation zone, 10.0: best transportation zone)

Table 29: Correlation and p-value of NYC pick-up features.

Features	Correlation	p-value
hour	0.5003	0.0000
residential	0.0245	0.0544
commercial	0.0442	0.0005
recreation	0.0074	0.5609
tourism	0.0275	0.0310
transportation	0.0547	0.0000

Table 30: Correlation and p-value of NYC drop-off features.

Features	Correlation	p-value
hour	0.5700	0.0000
residential	0.0623	0.0000
commercial	0.0114	0.3720
recreation	-0.0346	0.0066
tourism	-0.0359	0.0049
transportation	0.0082	0.5190

Table 31: Correlation and p-value of Chicago pick-up features.

Features	Correlation	p-value
hour	0.2225	0.0000
residential	0.0081	0.6955
commercial	-0.0053	0.7996
recreation	-0.0032	0.8786
tourism	0.0198	0.3380
transportation	-0.0026	0.9015

Table 32: Correlation and p-value of Chicago drop-off features.

Features	Correlation	p-value
hour	0.4371	0.0000
residential	0.0180	0.3845
commercial	-0.0518	0.0124
recreation	-0.0311	0.1332
tourism	-0.0302	0.1451
transportation	-0.0507	0.0142

Table 33: Correlation and p-value of DC pick-up features.

Features	Correlation	p-value
hour	0.2870	0.0000
residential	-0.0325	0.0707
commercial	0.0645	0.0003
recreation	0.0269	0.1351
tourism	0.0688	0.0001
transportation	0.0613	0.0006

Table 34: Correlation and p-value of DC drop-off features.

Features	Correlation	p-value
hour residential commercial recreation tourism	0.6585 0.0099 -0.0218 -0.0435 -0.0406	0.0000 0.5827 0.2243 0.0156 0.0238
transportation	-0.0125	0.4876

[35-38] Crime

For this experiment, we utilize crime data from New York City, Chicago, Washington D.C., and Cincinnati, with all datasets normalized to a scale ranging from 0.0 to 10.0. The New York City data comes from the NYPD Arrests Data (Historic) for 2021 (Police Department (NYPD) 2024). For Chicago, we use the Chicago Crimes-2014 dataset (Chicago Police Department 2024). The Washington D.C. data is derived from the Washington D.C. Crime Incidents - 2020 dataset (NHIT Data Fusion Center 2024). Finally, for Cincinnati, we rely on the PDI (Police Data Initiative) Crime Incidents in 2023 dataset (Cincinnati Police Department 2024).

Data Preprocess The crime counts are aggregated by "zone" and "year" for each city to obtain the total "crime count" for each zone in the specified year. The zone could be either community or zip code. The crime rate is then calculated by normalizing the crime count to a scale of 0.0 to 10.0, which is used as the target variable for evaluation.

Feature Unlike other tasks where features are selected by the LLM, crime features in this task are derived from demographic and POI factors as identified in (Wang et al. 2016), which analyzed crime factors in Chicago. Note that the last

feature "Nightlife" is only used in Chicago to compare with previous work (Wang et al. 2016), while the other 3 cities use the first 6 features.

- Total Population: What is the total population of the area? (0: very low, 10: very high)
- Population Density: How densely populated is the area? (0: very sparsely populated, 10: very densely populated)
- Poverty Index: What is the level of poverty in the area? (0: no poverty, 10: extreme poverty)
- Disadvantage Index: How disadvantaged is the area compared to others? (0: not disadvantaged, 10: extremely disadvantaged)
- Residential Stability: How stable is the residential population in the area? (0: very unstable, 10: very stable)
- Ethnic Diversity: How ethnically diverse is the area? (0: not diverse at all, 10: very diverse)
- Nightlife: How active is the nightlife in the area? (0: very quiet, 10: very active)

Table 35: Correlation and p-value of NYC crime features.

Features	Correlation	p-value
total_population	0.4405	0.0000
population_density	0.3299	0.0000
poverty_index	0.5564	0.0000
disadvantage_index	0.5523	0.0000
residential_stability	-0.4562	0.0000
ethnic_diversity	0.3668	0.0000

Table 36: Correlation and p-value of Chicago crime features.

Features	Correlation	p-value
total_population	0.0023	0.9840
population_density	0.0771	0.5050
poverty_index	0.6395	0.0000
disadvantage_index	0.7095	0.0000
residential_stability	-0.5687	0.0000
ethnic_diversity	-0.2503	0.0281
nightlife	-0.2891	0.0108

Table 37: Correlation and p-value of Washington DC crime features.

Features	Correlation	p-value
total_population	0.0196	0.9034
population_density	0.1218	0.4480
poverty_index	0.0614	0.7030
disadvantage_index	0.0840	0.6016
residential_stability	-0.1581	0.3236
ethnic_diversity	0.2294	0.1491

Table 38: Correlation and p-value of Cincinnati crime features.

Features	Correlation	p-value
total_population	0.4192	0.0004
population_density	0.3295	0.0065
poverty_index	0.0584	0.6388
disadvantage_index	0.0637	0.6088
residential_stability	-0.1091	0.3794
ethnic_diversity	0.3036	0.0125

[39-41] 311

Data Description For this experiment, we use 311 service request data from New York City, Austin, and Cincinnati, with all datasets normalized to a count scale ranging from 0.0 to 10.0. The New York City data is sourced from the 311 Service Requests dataset, collected in 2023 and hosted on the NYC Open Data portal (nyc opendata 2023). For Austin, the experiment uses the Austin 311 Service Requests dataset, collected in 2024 and hosted on Austin's Open Data portal (of Austin Open Data Portal 2024). The Cincinnati data comes from the Cincinnati 311 Non-Emergency Service Requests dataset, collected in 2024 and hosted on Cincinnati's Open Data portal (of Cincinnati Open Data Portal 2024).

Data Preprocess We calculate the total number of 311 service requests made in 2022 to serve as the target variable for our model's predictions. Initially, we remove samples with nonexistent or incorrect zip codes and excluded entries where the creation time did not fall within 2022. Subsequently, we compute the count of 311 service requests for each zip code area and normalized these counts to a scale of 0.0 to 10.0 to be used as the target column.

- Population Density: Measures the population density of the area (0.0: very low density, 10.0: very high density). Based on the number of residents per square mile.
- Unemployment Rate: Reflects the unemployment rate in the area (0.0: very low unemployment, 10.0: very high unemployment). Based on the proportion of unemployed individuals in the total labor force.
- Annual Income: Reflects the annual income level of residents (0.0: very low income, 10.0: very high income). Based on median household income.
- Crime Rate: Measures the crime rate in the area (0.0: very low, 10.0: very high).
- Infrastructure: Measures the quality and availability of infrastructure (0.0: very poor, 10.0: excellent). Includes transportation, utilities, and public services.

Table 39: Correlation and p-value of New York 311 features.

Features	Correlation	p-value
population_density	0.2887	0.0001
unemployment_rate	0.3369	0.0000
annual_income	-0.4603	0.0000
infrastructure	-0.3043	0.0000
crime_rate	0.4141	0.0000

Table 40: Correlation and p-value of Austin 311 features.

Features	Correlation	p-value
population_density	0.5582	0.0000
unemployment_rate	0.3436	0.0038
annual_income	-0.1830	0.1323
infrastructure	0.2195	0.0700
crime_rate	0.6544	0.0000

Table 41: Correlation and p-value of Cincinnati 311 features.

Features	Correlation	p-value
population_density	0.4067	0.0046
unemployment_rate	0.4282	0.0027
annual_income	-0.5347	0.0001
infrastructure	-0.4306	0.0025
crime_rate	0.7024	0.0000