

# Optimized 2-Approximation of Treewidth

Mahdi Belbasi<sup>1</sup>, Martin Fürer<sup>1</sup>, and Medha Kumar<sup>1</sup>

Pennsylvania State University

**Abstract.** This paper presents a linear FPT algorithm to find a tree decomposition with a 2-approximation of the treewidth with a significantly smaller exponential dependence on the treewidth in the running time than previously known.

**Keywords:** FPT Algorithms · Treewidth · Tree Decomposition · Approximation Algorithms.

## 1 Introduction

Since its introduction by Robertson and Seymour [9,10], the treewidth – a measure of how ‘tree-like’ a graph is – has played a significant role in computer science. When a near-optimal tree decomposition is known, many hard problems can be solved efficiently for graphs with a small treewidth. Unfortunately, computing an optimal tree decomposition and finding the treewidth of a graph are both NP-hard problems [1].

A problem is said to be fixed parameter tractable (FPT) if there exists an algorithm solving the problem in time  $f(k)\ell^{\mathcal{O}(1)}$ , where  $\ell$  is the input size,  $k$  is the parameter, and  $f(\cdot)$  is a computable function. For graphs with bounded treewidth, many NP-complete graph problems obtain FPT algorithms using dynamic programming, where the parameter is the treewidth. In order to design an FPT dynamic programming algorithm however, we need to have access to a reasonable tree decomposition of the input graph.

Finding an optimal tree decomposition and the exact treewidth was proven to be in FPT [4,8]. Bodlaender gave the first exact FPT algorithm running in time  $2^{\mathcal{O}(k^3)}n$  [4] (where  $k$  denotes the optimal treewidth, and  $n$  is the number of vertices), however the prohibitive running time shifted focus back to approximate solutions. Over time, the primary emphasis shifted from optimizing the dependence on  $n$ , to reducing the exponential coefficients of  $k$  [2,3,6]. Both known linear-time algorithms with single-exponential dependence on  $k$  [5,6], suffer from very large coefficients of  $k$  in the exponent.

In this paper, we achieve a significant reduction in the exponential coefficient for the algorithm proposed in [6].

### 1.1 Main Result

Many ideas of our algorithm are motivated by Korhonen’s algorithm [6,7] which also achieves a 2-approximation of the treewidth in time linear in  $n$ , but with a

much larger exponential dependence on  $k$ . The algorithm in [6] attains a decrease in the width of a tree decomposition  $\mathcal{T}$  by *splitting* a root node  $r$  with a bag (denoted by  $B_r$ ) of maximum size. To maintain the tree decomposition, the split is propagated through an unbounded number of nodes in the tree decomposition.

Every split operation results in either a decrease in the number of nodes with maximum size bags, or a decrease in the width of the current tree decomposition. Throughout, the algorithm in [6] maintains a maximum tree degree  $\leq 3$ . By repeatedly splitting nodes with maximum size bags, [6] arrives at a tree decomposition with a 2-approximation of the treewidth. Each split in [6] however, creates 2 or 3 copies of all edited nodes. This sometimes creates a large number of nodes in the tree decomposition, which slows down the algorithm.

Our algorithm avoids this by *merging* redundant nodes, and relaxing the maximum degree constraint to allow merging. To avoid any corresponding increase in running time, we impose a specific structure on the tree decompositions – a grouped tree decomposition – which allows us to obtain the following result.

**Theorem 1.** *Given a graph  $G$ , a tree decomposition  $\mathcal{T}$  of  $G$  with width  $\leq 4k + 3$  for some integer  $k$ , in time  $\mathcal{O}^*(81^k)n^1$ , one can either construct a tree decomposition of  $G$  with width  $\leq 2k + 1$ , or conclude that  $tw(G) > k$ .*

Using Bodlaender’s [4] reduction method, as in [6], one can omit the assumption at a cost of only a factor polynomial in  $k$ .

**Corollary 1.** *In time  $\mathcal{O}^*(81^k)n$ , one can either construct a tree decomposition of  $G$  with width  $\leq 2k + 1$ , or conclude that  $tw(G) > k$ .*

## 2 Preliminaries

A tree decomposition  $\mathcal{T} = (V_{\mathcal{T}}, E_{\mathcal{T}})$  of a graph  $G = (V, E)$ , is a tree where each  $y \in V_{\mathcal{T}}$  is associated with a set  $B_y \subseteq V$ , such that for every edge  $(u, v) \in E$  there exists  $x \in V_{\mathcal{T}}$  with  $\{u, v\} \subseteq B_x$ , all vertices in  $V$  appear in some  $B_x$ , and for all  $x, y \in V_{\mathcal{T}}$  with  $z \in V_{\mathcal{T}}$  appearing on the unique path between  $x$  and  $y$  in  $\mathcal{T}$ ,  $B_x \cap B_y \subseteq B_z$ . We refer to  $x \in V_{\mathcal{T}}$  as *node  $x$* , and  $B_x$  as the *bag* of node  $x$ . The width of  $\mathcal{T}$  is one less than the size of the maximum bag  $B_x$  of any  $x \in V_{\mathcal{T}}$ .

Assume  $\mathcal{T}$  is rooted (arbitrarily). For a node  $x \in V_{\mathcal{T}}$ , the parent of  $x$  is denoted by  $p(x)$ . The tree decomposition rooted at some node  $x$  in  $\mathcal{T}$  is denoted by  $\mathcal{T}_x = (V_{\mathcal{T}_x}, E_{\mathcal{T}_x})$ . The graph induced by  $\mathcal{T}_x$  is denoted by  $G_x = (V_x, E_x)$ .

**Definition 1.** *Given a rooted tree decomposition  $\mathcal{T}$ , a node  $x \in V_{\mathcal{T}}$  is the home of a vertex  $v$ , i.e.,  $x = h(v)$  if  $v \in B_x$  and  $v \notin B_{p(x)}$ .*

**Definition 2.** *A unique home tree decomposition  $\mathcal{T}$  is a rooted tree decomposition where every non-root node  $x$  is the home of exactly one vertex  $v \in V$ , and the root node  $r$  is the home of at least one vertex  $v \in V$ .*

<sup>1</sup> We use the notation  $\mathcal{O}^*$  to describe the running time of an algorithm while ignoring the polynomial factors of  $k$

**Definition 3.** A grouped tree decomposition  $\mathcal{T}$  is a rooted tree decomposition such that:

1. All nodes in  $V_{\mathcal{T}}$  are either main nodes ( $V_{\mathcal{T}^M}$ ) or intersection nodes ( $V_{\mathcal{T}^I}$ )
2. All leaves of  $\mathcal{T}$  are main nodes.
3. For all  $x \in V_{\mathcal{T}}^M$  and  $y \in V_{\mathcal{T}}^I$ ,  $p(x) \in V_{\mathcal{T}}^I$  and  $p(y) \in V_{\mathcal{T}}^M$
4. For all  $x, y \in V_{\mathcal{T}}^M$  with  $x = p(p(y))$ ,  $|B_y \setminus B_x| = 1$  and  $B_{p(y)} = B_x \cap B_y$  with all  $B_x \neq \emptyset$ , i.e.,  $y = h(v)$  for exactly one  $v \in V$
5. For all  $x, y \in V_{\mathcal{T}}^I$ ,  $B_x \subseteq B_{p(x)}$  and if  $p(x) = p(y)$  then  $B_x \neq B_y$ .

For all main nodes  $x$ , the set of nodes  $y$  such that  $x = p(y)$  are referred to as the *children* or *intersection children* of  $x$ . The set of main nodes  $y$  such that  $y = p(p(x))$  are referred to as the *grandchildren* of  $x$ . Note that for a connected graph,  $x$  can have at most  $2^{|B_x|} - 1$  children, but may have an unbounded number of grandchildren.

Furthermore, the main nodes in a grouped tree decomposition  $\mathcal{T}$  clearly form a unique home tree decomposition, that we shall refer to as the *corresponding unique home tree decomposition*  $\mathcal{T}^M$  of  $\mathcal{T}$ .

**Lemma 1.** Given a tree decomposition  $\mathcal{T} = (V_{\mathcal{T}}, E_{\mathcal{T}})$  of a graph  $G$ , with width  $k$ , one can construct a unique home tree decomposition  $\mathcal{T}' = (V_{\mathcal{T}'}, E_{\mathcal{T}'})$  of  $G$  of the same width  $k$  in  $\mathcal{O}(k^2|V_{\mathcal{T}}|)$  time.

*Proof.* For  $\mathcal{T}$  to be transformed into a unique home tree decomposition, we need to ensure that each node in  $\mathcal{T}$  is the home of exactly one vertex. We can create the unique home tree decomposition  $\mathcal{T}'$  by traversing  $\mathcal{T}$  and handling each pair  $x, y$  of nodes of  $\mathcal{T}$ , where  $x$  is the parent of  $y$ , as follows:

- If  $B_y \subseteq B_x$ , we add the child nodes of  $y$  as child nodes of  $x$  and delete node  $y$ .
- If  $B_y \setminus B_x = \{v_1, \dots, v_j\}$  for some  $j > 1$ , we add a string of forget nodes between  $x$  and  $y$  such that the bag of each node is exactly 1 vertex smaller than the bag of its child. Let these forget nodes be  $\{y_1, \dots, y_{j-1}\}$  then  $B_{y_1} = B_y \setminus \{v_1\}$ ,  $B_{y_i} = B_{y_{i+1}} \setminus \{v_i\}$  and  $B_{y_{j-1}} = B_x \cup B_y$ .
- Else if  $B_y \setminus B_x = \{v_1\}$ , then the unique home property is satisfied and we do nothing.

We can traverse  $\mathcal{T}$  in time linear in the number of nodes. Comparing bags of each pair of nodes takes time linear in the size of their bags. At each instance of the second case, we create at most  $k$  nodes. Creating  $k$  nodes with bags of size  $\mathcal{O}(k)$  can be done in time  $\mathcal{O}(k^2)$  resulting in an overall time of  $\mathcal{O}(k^2|V_{\mathcal{T}}|)$  to construct a unique home tree decomposition  $\mathcal{T}'$  from  $\mathcal{T}$ .  $\square$

**Lemma 2.** Given a tree decomposition of a graph  $G = (V, E)$  with width  $k$ , one can construct a grouped tree decomposition of  $G$  with width  $k$ , in time  $\mathcal{O}(k^2n)$ , where  $n = |V|$ .<sup>2</sup>

<sup>2</sup> omitted proofs in appendix

*Proof.* Using Lemma 1, we first convert  $\mathcal{T}^*$  into a unique home tree decomposition  $\mathcal{T}$ , in time  $\mathcal{O}(k^2 n)$ . Since the unique home property is satisfied in the tree decomposition  $\mathcal{T}$ , to construct a grouped tree decomposition  $\mathcal{T}'$ , we must ensure that the additional structural properties of intersection nodes are satisfied. Given main nodes  $x$  and  $y$  in  $\mathcal{T}$ , where  $x$  is the parent of  $y$ , we proceed as follows.

- If there exists an intersection child node  $z$  of  $x$ , such that  $B_z = B_x \cap B_y$ , we add  $y$  as a child of  $z$ .
- Else create an intersection child node  $z$  of  $x$  such that  $B_z = B_x \cap B_y$  and  $y$  is the child of  $z$ .

Searching for an intersection child node  $z$  such that  $B_z = B_x \cap B_y$  can take time  $\mathcal{O}(2^k)$ . However, since we keep a global order over all vertices in  $V$ , we might as well construct a temporary binary tree of intermediate nodes – which each layer representing a vertex (according to the global order) in  $B_x$  that is either included (right child) or excluded (left child) in the intersection children below. We add nodes to this binary tree only when we need to add a path to a newly created intersection node below  $x$ . Using this temporary tree we can check for existing intersection nodes in  $\mathcal{O}(k)$  time, since  $|B_x| = \mathcal{O}(k)$  means that the length of the longest path in the tree is at most  $\mathcal{O}(k)$ . Once all children of  $x$  have been added below intersection children of  $x$ , we delete the temporary binary tree and proceed to the As a unique home tree,  $\mathcal{T}$  has at most  $n = |V|$  nodes. The time spent on each node  $y$  is  $\mathcal{O}(k^2)$ , as an intersection node with bag size at most  $k+1$  is visited, or constructed with an additional  $\mathcal{O}(k)$  temporary nodes leading to it, resulting in a total time of  $\mathcal{O}(k^2 n)$ .  $\square$

## 2.1 Partitions

A crucial step in our algorithm is the finding of good partitions of vertex sets  $V' \subseteq V$ . We allow some parts in a partition to be empty. Partitions of sets  $V_1$  and  $V_2$  are said to be *compatible* if they agree on the assignment of the elements in  $V_1 \cap V_2$ . Given  $V_1 \subseteq V_2$ , the unique partition  $P_1$  of  $V_1$ , compatible with a partition  $P_2$  of  $V_2$ , is said to be the partition *induced* by  $P_2$ .

**Definition 4.** A partition  $P = (W_1, W_2, W_3, X)$  of  $V' \subseteq V$  is a legal partition if there are no edges between  $W_i$  and  $W_j$  for  $i \neq j$ , and  $\exists i, j, i \neq j$  such that  $W_i, W_j \neq \emptyset$ .

If  $P_x$  is a legal partition of  $B_x$  for some node  $x \in V_{\mathcal{T}}$ , then there exists at least one legal partition  $P^x = (C_1^x, C_2^x, C_3^x, S^x)$  of  $V_x$  compatible with  $P_x$ .  $S^x$  is called a separator of  $G_x$ .

**Definition 5.** For a given tree decomposition  $\mathcal{T}$  the size of a partition  $P^x = (C_1^x, C_2^x, C_3^x, S^x)$  of  $V_x$  is the size of the separator  $S^x$ , and the size of a legal partition  $P_x = (W_1^x, W_2^x, W_3^x, X^x)$  of  $B_x$  is the minimal size of a compatible legal partition  $P^x$  of  $V_x$ .

**Definition 6.** For a given tree decomposition  $\mathcal{T}$  with  $x = p(y)$  for nodes  $x$  and  $y$  of  $\mathcal{T}$ , a legal partition  $P_y = (W_1^y, W_2^y, W_3^y, X^y)$  of  $B_y$  is good with respect to a partition  $P_x = (W_1^x, W_2^x, W_3^x, X^x)$  of  $B_x$  if  $P_y$  is compatible with  $P_x$ ,  $\text{size}(P_y) = \text{size}(P_x) - |X^x \setminus X^y|$ , and  $|X^y|$  is maximized among the partitions satisfying the two previous conditions. For the root  $r$ ,  $P_r$  is good if  $|W_i^r| + \text{size}(P_r) < |B_r|$  and  $\text{size}(P_r) \leq k + 1$ .

A legal partition  $P = (C_1, C_2, C_3, S)$  of  $V$  is good if  $P$  induces a good partition of  $B_r$  and for all nodes  $x$  and  $y$  of  $\mathcal{T}$  with  $x = p(y)$ , the partition of  $B_y$  induced by  $P$  is good with respect to the partition of  $B_x$  induced by  $P$ .

A *split* is a special good partition  $P = (C_1, C_2, C_3, S)$  of  $V$ . For  $P$  to be a split, it is not allowed for any node  $y$  with partition  $P_y$  induced by  $P$  to assign  $v \in B_y$  to some component  $C_i$ , unless  $p(y)$  also assigns some  $v' \in B_{p(y)}$  to  $C_i$ .

**Definition 7.** A split of a tree decomposition  $\mathcal{T}$  is a partition  $P = (C_1, C_2, C_3, S)$  of  $V$  and a function  $a : V_{\mathcal{T}} \rightarrow \{1, 2, 3\}$  with the following properties:

- $P$  is good for  $\mathcal{T}$
- For every node  $x$ , and  $P_x = (W_1^x, W_2^x, W_3^x, X^x)$  induced by  $P$ ,  $P_x$  satisfies:
  1.  $a(x) \subseteq a(p(x))$
  2.  $a(x) = \begin{cases} \{i \mid W_i^x \neq \emptyset\}, & \text{if } \exists i \text{ such that } W_i^x \neq \emptyset \\ \{i\} & \text{for one } i \text{ such that } W_i^{P(x)} \neq \emptyset, \text{ else} \end{cases}$

Notice that with our definition, each  $C_i^r$  is of size at most  $\frac{1}{2}|B_r|$  in any split.

**Lemma 3.** For a graph  $G$  with  $\text{tw}(G) \leq k$ , and a tree decomposition  $\mathcal{T}$  of  $G$  with a root  $r$  such that  $|B_r| > 2(k + 1)$ , there exists a split of  $\mathcal{T}$ .

*Proof.* Assume the size of the root bag  $B_r$  is more than  $2(k + 1)$ . By Lemma II.2 of [10], there is a separator  $S$  of  $B_r$  of size  $|S| \leq k + 1$  such that every connected component of  $G[V \setminus S]$  contains at most  $|B_r|/2$  vertices of  $B_r$ . These connected components can easily be grouped into 3 sets to produce a legal partition  $P = (C_1, C_2, C_3, S)$  of  $V$  such that  $C_i$  is the set of vertices belonging to the connected components in the  $i$ th set and  $|C_i \cap B_r| \leq |B_r|/2$  for all  $i$ . As a consequence, for the induced partition  $P_r = (W_1^r, W_2^r, W_3^r, X^r)$  of  $B_r$ , we have  $|W_i^r| + |S| \leq \frac{|B_r|}{2} + k + 1 < |B_r|$  for all  $i$ , implying that  $P$  is good at  $r$ .

Now, we show how to modify  $P$  to obtain a split. Let  $\mathcal{T}' = (V_{\mathcal{T}'}, E_{\mathcal{T}'})$  be a maximal subtree of  $\mathcal{T}$  such that there is a pair  $(P, a)$  with

- $P$  is a legal partition of  $V$ , and
- $P$  and  $a$  fulfill properties (a) and (b) of Definition 7 for the nodes in  $V_{\mathcal{T}'}$ .

It is straightforward to see that the root  $r$  belongs to  $V_{\mathcal{T}'}$ . We claim that  $V_{\mathcal{T}'} = V_{\mathcal{T}}$ . Otherwise, there would be a node  $y$  with parent  $x$  such that (a) and (b) are satisfied in  $x$  but not in  $y$ .

Let  $(W_1^y, W_2^y, W_3^y, X^y)$  be the partition of  $B_y$  induced by  $P$ . First, assume that (b) is violated in  $y$ . Then, for all  $i$  with  $W_i^x = \emptyset$ , but  $W_i^y \neq \emptyset$ ,  $P$  can be

modified by moving all vertices of  $C_i \cap V_y$  from  $C_i$  to a  $C_j$  with  $j \in a(x)$  and removing  $i$  from  $a(y)$  to satisfy (b) in  $y$ .

If (a) is violated in  $y$ , it just means that there is a better partition  $P'$  which differs from  $P$  only in  $V_y$ , is of the same minimal size, and has a larger intersection with  $B_y$ . After at most  $k + 1$  such improvement steps, (a) is satisfied. We have obtained a partition  $\mathcal{T}''$  that satisfies (a) and (b) in the vertices of  $\mathcal{T}'$  and also in  $y$ , contradicting the optimality of  $\mathcal{T}'$ . Thus  $V_{\mathcal{T}'} = V_{\mathcal{T}}$ , and we have obtained a split.  $\square$

**Definition 8.** *Given a tree decomposition  $\mathcal{T}$ , a node  $x \in V_{\mathcal{T}}$  is *editable* with respect to a split  $P$  of  $V$ , if the induced partition  $P_x$  of  $B_x$  has at least two non-empty components  $W_i^x, W_j^x$  ( $i \neq j$ ).*

By the definition of a split, this implies that the parent of an editable node is also editable.

**Lemma 4.** *For a tree decomposition  $\mathcal{T}$  and a split  $P^x = (C_1^x, C_2^x, C_3^x, S^x)$  of  $\mathcal{T}_x$  that induces partition  $P_x = (W_1^x, W_2^x, W_3^x, X^x)$  on  $B_x$ , we have  $|S^x \setminus B_x| < |B_x \cap (C_i \cup C_j)|$  for  $i \neq j$ .*

*Proof.* Recall that  $S^x \setminus B_x$  is the set of all separator vertices with their home in a descendant of node  $x$ . Define  $C_i^x = C_i \cap B_x$  for all  $i \in \{1, 2, 3\}$  and let  $X^x = S \cap B_x$ .

We prove this lemma by contradiction. Let  $|S^x \setminus B_x| \geq |C_i^x \cup C_j^x|$  for a given  $i, j$ , where  $S^x \setminus B_x$  is non-empty. Then, there exists a smaller separator  $S'$  such that  $S' = (S \setminus S^x) \cup X^x \cup (C_i^x \cup C_j^x)$ . Additionally,  $|B_x \cap S| < |B_x \cap S'|$  since  $B_x \cap S = X^x \subsetneq X^x \cup C_i^x \cup C_j^x \subseteq (S \setminus S^x) \cup X^x \cup C_i^x \cup C_j^x = B_x \cap S'$ . Following a similar argument as in [6], we note that  $B_x$  separates  $S^x \setminus B_x$  from  $B_r$ . Now,  $|S^x| \geq |S' \cap B_x|$ ,  $B_r \cap S \subseteq B_r \cap S'$ . Now let us assume that there exists a path between  $B_r \cap C_i \setminus S'$  to  $B_r \cap C_j \setminus S'$  for  $i \neq j$ . This path must intersect  $S^x \setminus B_x$  since we know that  $S' \cup S^x \setminus B_x$  separates  $C_i$  from the rest of the graph. However, since  $B_x$  separates  $B_r$  from  $S^x \setminus B_x$ , this path must also intersect  $B_x$ . Thus some vertex from  $B_x \cap C_i$  must be in the path, since  $B_x \cap S^x \setminus B_x = \phi$ . However, all such vertices are included in the new separator  $S'$ . Thus,  $S'$  is a smaller separator with a larger intersection with  $B_x$  than  $S$ . This contradicts our original assumption of  $S$  being a good separator in  $\mathcal{T}$ , so the lemma holds.  $\square$

## 2.2 Data Structure

Given a grouped tree decomposition  $\mathcal{T}$  of a graph  $G$ , we use dynamic programming to find a good partition and a good separator of  $G$ . We build a data structure consisting of dynamic programming tables (DP-Tables)  $A_x$  stored at every node  $x \in V_{\mathcal{T}}$ , to help us find a good separator. Each  $A_x$  is of size  $4^{|B_x|}$  and stores an entry for every possible 4-partition of  $B_x$ .

**Definition 9.** *Given a partition  $P_x = (W_1^x, W_2^x, W_3^x, X^x)$  of  $B_x$  for node  $x$ , the DP-table entry  $A_x[P_x]$  stores the entry  $(s, cl)$ :*

1.  $s$  : Size of  $P_x$ . If  $P_x$  is not legal, or has size  $> k + 1 + |X^x|$ , then  $s = \perp$ .
2.  $cl = [(pointer_1, P_1) \dots (pointer_t, P_t)]$  such that
  - (a)  $pointer_i$  stores a pointer to the start of the table  $A_{y_i}$
  - (b) Partition  $P_i$  that contributes to the separator at  $A_x[P_x]$

We use  $s(A_x[.])$  and  $cl(A_x[.])$  to refer to the two elements of each entry. Entries in  $cl(A_x[.])$  are indexed as  $cl(A_x[.][0])$  and  $cl(A_x[.][1])$ .

**Lemma 5.** *Given graph  $G = (V, E)$  such that  $tw(G) = k$  and a partition  $P_x$  of  $B_x$ , no good partition of  $V$  requires more than  $k + 1$  entries in  $cl(A_x[P])$ .*

*Proof.* Notice that  $s(A_x[P]) = |cl(A_x[P])| + |X^x|$ . This is because the size of a minimum separator of  $V_x$  compatible with  $P$  must be the sum of the size of the separator of  $B_x$ , i.e.,  $X^x$ , and the minimum number of separator vertices added from the children of  $x$ , i.e.,  $|cl(A_x[P])|$ . Since every element of  $cl(A_x[P])$  contributes at least 1 vertex, if  $|cl(A_x[P])| > k + 1$ , then  $s(A_x[P]) > k + 1 + |X^x|$ . This implies that this entry is no longer meaningful because any partition compatible with  $(W_1^x, W_2^x, W_3^x, \emptyset)$  has size greater than  $k + 1$ , while all good partitions have size at most  $k + 1$  (Def 6). Therefore, no good partition requires more than  $k + 1$  entries in  $cl(A_x[P])$ . Should some  $cl(A_x[P])$  have more than  $k + 1$  entries, we redefine  $s(A_x[P]) = cl(A_x[P]) = \perp$ .  $\square$

### 2.3 Node Operations

Four main operations – Initialization, Addition, Subtraction, and Update – are performed on nodes in a grouped tree decomposition over the course of Algorithm 1. They are described along with their corresponding DP-table updates in this section.

**Addition** Given grouped tree decompositions  $\mathcal{T}_1$  with root  $x$ , and  $\mathcal{T}_2$  with root  $y$ , an Addition creates a new tree decomposition where  $\mathcal{T}_2$  is a sub-tree of  $\mathcal{T}_1$  and  $x = p(y)$ . To ensure that this new tree decomposition  $\mathcal{T}$  is a grouped tree decomposition, we allow either  $x$  or  $y$  to be an intersection node, while the other is a main node. This creates the following cases:

- **Case 1:** Main node  $y$  and Intersection node  $x$
- **Case 2:** Intersection node  $y$  and Main node  $x$

*Case 1:* Addition is only done when  $B_y = B_x \cup \{v\}$  for some  $v \notin B_x$ . For each  $P_x = (W_1^x, W_2^x, W_3^x, X^x)$  of  $B_x$ , there exists four compatible partitions of  $B_y$  corresponding to  $v$ 's assignment to any one of the four parts. Let  $P_y = (W_1^y, W_2^y, W_3^y, X^y)$  be a compatible partition such that  $s(A_y[P_y])$  is minimal. We update  $A_x[P_x]$  as follows:

$$s(A_x[P_x]) = s(A_x[P_x]) + s(A_y[P_y]) - |X^x|$$

$$cl(A_x[P_x]) = cl(A_x[P_x]), (y, pointer^*)$$

where  $pointer^*$  is a pointer to  $A_y[P_y]$ .

*Case 2:* Clearly  $B_y \subseteq B_x$ . Notice that every partition  $P_x = (W_1^x, W_2^x, W_3^x, X^x)$  of  $B_x$  can be written as  $P_x = (W_1^y \cup W_1^{x \setminus y}, W_2^y \cup W_2^{x \setminus y}, W_3^y \cup W_3^{x \setminus y}, X^y \cup X^{x \setminus y})$ , using  $P_y = (W_1^y, W_2^y, W_3^y, X^y)$  of  $B_y$ , and  $P_{x \setminus y} = (W_1^{x \setminus y}, W_2^{x \setminus y}, W_3^{x \setminus y}, X^{x \setminus y})$  of  $B_x \setminus B_y$ . Thus  $A_x[P_x]$  is updated using  $A_y[P_y]$ . If  $P_x$  is not a legal partition, then  $s(A_x[P_x]) = cl(A_x[P_x]) = \perp$ . Else:

$$s(A_x[P_x]) = s(A_x[P_x]) + s(A_y[P_y]) - |X^y|$$

$$cl(A_x[P_x]) = cl(A_x[P_x]), (y, \text{pointer}^*)$$

where  $\text{pointer}^*$  is a pointer to  $A_y[P_y]$ . If  $s(A_x[P_x]) > k + 1 + |X^x|$  then, according to Definition 9,  $s(A_x[P_x]) = cl(A_x[P_x]) = \perp$ .

At the end of an Addition, all DP-tables in descendants of  $x$  are correct, while those in ancestors of  $x$  must still be updated.

Clearly an Addition can be done in  $O^*(|A_x|)$  which, for a tree decomposition with width  $w$  is a function of  $w$ .

**Subtraction** Given grouped tree decompositions  $\mathcal{T}$  with root  $x$  and its sub-tree  $\mathcal{T}_1$  with root  $y$  such that  $x = p(y)$ , a Subtraction removes the sub-tree rooted at  $y$  from  $x$ . Clearly this is just a reverse addition and does not require further explanation.

**Initialization** For a one-node grouped tree decomposition  $\mathcal{T} = (\{x\}, \phi)$ , the DP-table  $A_x$  can be Initialized for each legal partition  $P_x = (W_1^x, W_2^x, W_3^x, X^x)$  of  $B_x$  as  $s(A_x[P_x]) = |X^x|$ ,  $cl(A_x[P_x]) = \phi$ . If  $P_x$  is illegal then  $s(A_x[P_x]) = cl(A_x[P_x]) = \perp$ . For node  $x$  with children  $y_1, \dots, y_l$  in  $\mathcal{T} = (V_{\mathcal{T}}, E_{\mathcal{T}})$ , an Initialization is performed by initializing  $x$  in a one-node tree decomposition, followed by an Addition of  $y_i$  to  $x$  for all  $i \in [l]$ .

Given a grouped tree decomposition of  $O(n)$  nodes and width  $b$ , an initialization takes time at most  $O^*(4^b)n$ .

**Update** Given grouped tree decomposition  $\mathcal{T}$  with nodes  $x, y$  such that  $p(y) = x$ , an Update of  $A_x$  is performed when  $A_y$  is modified. This can be done efficiently by subtracting  $y$  with its previous table from  $x$ , and then adding  $y$  with the modified table to  $x$ . Clearly, this takes time  $O^*(4^b)$  for a grouped tree decomposition with width  $\leq b$ .

### 3 Our Algorithm

Algorithm 1 describes the pseudo-code of the algorithm which works in rounds. Each round splits all nodes with bags of maximum size  $w + 1$  (constant for that round) until all nodes have bags of size strictly smaller than  $w + 1$ . When the width of the tree decomposition falls to below  $2k + 1$ , a split may not be found, and the 2-approximation is returned. If no split is found for some width  $> 2k + 1$ , then the treewidth is known to be greater than  $k$ .

---

**Algorithm 1** 2-ApproximationOfTreewidth( $G, \mathcal{T}, w, k$ )
 

---

**Input:**  $k \in \mathbb{N}$ ,  $G = (V, E)$ , and tree decomposition  $\mathcal{T}$  with width  $w \leq 4k + 3$ 
**Output:** A tree decomposition with width  $\leq 2k + 1$  OR FALSE if treewidth of  $G > k$ 

- 1: Construct grouped tree decomposition  $\mathcal{T}$  from  $\mathcal{T}'$  following Lemma 2
  - 2: **for**  $w = 4k + 3$  down to  $2k + 2$  with step size:  $-1$  **do**
  - 3:     Initialize DFS instance on  $\mathcal{T}$
  - 4:     **while**  $\exists$  unvisited node  $x$  in a DFS instance on  $\mathcal{T}$  **do**
  - 5:         **if**  $B_x$  is of maximum bag size  $w + 1$  **then**
  - 6:             MOVE  $x$  to root
  - 7:             Perform SPLIT at root  $r$  by finding a split  $(C_1, C_2, C_3, S)$  of  $V$ , s.t.  $S$   
               separates  $C_1, \dots, C_3$ ,  $|S| \leq k + 1$ , and for all  $i$   $|C_i \cap B_i| \leq (w + 1)/2$ .
  - 8:             **if** no split exists **then**
  - 9:                 **return** FALSE
  - 10:             Propagate SPLIT through the tree by editing all editable nodes  $x$   
               i.e., for all  $i \in a(x)$  (Def 7) replace  $x$  with nodes  $x_i$  s.t.  
                $B_{x_i} = (C_i \cap B_x) \cup S^x$ .
  - 11:             MERGE main nodes that are not the home of any vertex.
  - 12:             Mark all newly created nodes as unvisited
  - 13:             Create a new root node  $r'$  s.t.  $B_{r'} = S$  and the  $r_i$  are the children of  $r'$
  - 14: **return**  $\mathcal{T}$
- 

**Analysis** The bottleneck in the algorithm is recomputing the large DP-table stored at each node after an operation is performed on the grouped tree decomposition  $\mathcal{T}$  with root node  $r$ .

The potential function  $\phi(\mathcal{T})$  is defined to upper bound the number of DP-Table recomputations per round of Algorithm 1. Consider the function  $\phi(\mathcal{T}) = \alpha(\mathcal{T}) + \beta(\mathcal{T}) + \gamma(\mathcal{T}) + \delta(\mathcal{T})$ , where:

$$\begin{aligned}
 - \alpha(\mathcal{T}) &= c_\alpha \sum_{x \in V_{\mathcal{T}^*}} |B_x| f(x), \text{ where } c_\alpha > 0 \text{ and } f(x) = \begin{cases} |B_x \setminus B_{p(x)}| & \text{if } x \neq r \\ (|B_x + 1|)/2 & \text{if } x = r \end{cases}, \\
 - \beta(\mathcal{T}) &= c_\beta \sum_{x \in V_{\mathcal{T}^*}} \text{DFS-Status}(x), \text{ where } c_\beta > 0 \text{ and DFS-Status}(x) \text{ is its} \\
 &\quad \text{visited status (2/1/0) in the DFS instance initialized in Alg 1} \\
 - \gamma(\mathcal{T}) &= c_\gamma |V_{\mathcal{T}}|, \text{ where } c_\gamma > 0 \\
 - \delta(\mathcal{T}) &= h(k) |V_{\mathcal{T}}^{\max}|, \text{ and } h(k) = \mathcal{O}(k^2).
 \end{aligned}$$

where,  $V^M$  denotes the main nodes of  $\mathcal{T}$ . We prove that this potential function is sufficient.

**Theorem 2.** *The Potential Function  $\phi(\mathcal{T})$  bounds the number of DP-table recomputations performed in each round of the algorithm.*

*Proof.* Thm 4 proves that the number of DP-table updates performed during all Split operations in a round is bounded by  $\alpha(\mathcal{T}) + \delta(\mathcal{T})$ .

From Lemma 6 we know that the  $\alpha$ -potential does not change during a Move operation. Lemma 8 and Lemma 7 show that the number of rotation operations

performed on a tree  $\mathcal{T}$  can be counted using the  $\beta$ -potential. Furthermore, Thm 4 proves that any increase in the  $\beta$ -potential is paid for by the  $\alpha$  and  $\delta$  potentials.

A Merge operation reduces the number of nodes in  $\mathcal{T}$ . Lemma 9 shows that  $\gamma(\mathcal{T})$  bounds the number of merge operations that may be performed per round. Thm 4 proves that any increase in the  $\gamma$ -potential is also covered by the  $\alpha$  and  $\delta$  potentials.

Lastly, since we only initialize a Split at a node with a maximum size bag, the number of SPLIT operations initiated in a round is equal to the number of nodes with maximum size bags in  $\mathcal{T}$ . Furthermore, splitting a maximum size bag also requires the creation of a new root node whose bag contains the  $\mathcal{O}(k)$  separator vertices.

The  $h(k) = \mathcal{O}(k^2)$  factor – required to give  $\mathcal{O}(k)$  potential for each of the additional  $\mathcal{O}(k)$  vertices whose home is the new root – accounts for the potential given to the new root node and the construction time of the root node. This gives us the last term of the potential function  $\delta(\mathcal{T}) = h(k)|V_{\mathcal{T}}^{max}|$ .

Thus,  $\phi(\mathcal{T})$  bounds the number of DP-table updates done in each round of the algorithm.  $\square$

The algorithm begins with a tree decomposition  $\mathcal{T}$  that has a 4-approximation of the treewidth  $k$ . Let the size of the maximum size bag in  $\mathcal{T}$  be  $b$ , such that  $b \leq 4k + 4$ . While choosing a split for  $\mathcal{T}$ , two factors are considered: 1) the value of  $b$ , and 2) the size of the DP-table created. When  $b \in [3k + 4, 4k + 4]$ , a 4-partition split, i.e.,  $(C_1, C_2, C_3, S)$ , creates DP-tables of size  $\mathcal{O}(4^{4k}) = \mathcal{O}(256^k)$ . However, note that it suffices to simply create a 3-partition split, i.e.,  $(C_1, C_2, S)$ , and let each  $W_i^r$  to be of size at most  $\frac{2}{3}|B_r|$  in any split. This needs a DP-table of size  $\mathcal{O}(3^{4k}) = \mathcal{O}(81^k)$  to successfully split maximum size bags. When  $b \in [2k + 3, 3k + 3]$ , creating a 4-partition split, i.e.,  $(C_1, C_2, C_3, S)$ , creates DP-tables of size  $\mathcal{O}(4^{3k}) = \mathcal{O}(64^k)$ . Since this is smaller than the tables in the  $b \in [3k + 4, 4k + 4]$  case with a 3-partition split, the former case determines the running time of our algorithm.

Thus, 3-partition splits are created when the size of the maximum size bag is  $\geq 3k + 4$ , and 4-partition splits are used when the size of the maximum size bag is in the  $[2k + 3, 3k + 3]$  range.

**Theorem 3.** *Algorithm 1 has a running time of  $\mathcal{O}^*(81^k)n$ .*

*Proof.* The running time of the algorithm is bounded by the most expensive operations performed, i.e., the number of times we recompute a DP-table.  $\phi(\mathcal{T})$  bounds the number of such DP-table recomputations that occur in a single round of the algorithm [Thm 2].

Furthermore  $\phi(\mathcal{T}) = \mathcal{O}(k^2 n)$ . When the width of  $\mathcal{T}$ , say  $w$ , is in the range  $[2k + 2, 3k + 2]$ , the size of the DP-table is  $\mathcal{O}(4^{3k})$ . Locating an entry in the DP-table takes time linear in  $k$ . Correspondingly, the amount of work done per round is  $\mathcal{O}(k^2 4^{3k} n) = \mathcal{O}(64^k k^2 n)$ , and the algorithm runs for at most  $\mathcal{O}(k)$  rounds.

This gives us a running time of  $\mathcal{O}(k^3 64^k n)$ , which is  $\mathcal{O}^*(64^k)n$ . When  $w \in [3k + 3, 4k + 3]$ , the size of the DP-table should be  $3^{4k}$ , which gives us a running

time of  $\mathcal{O}(k^3 81^k n)$ , which is  $\mathcal{O}^*(81^k)n$ . Thus, Algorithm 1 has a running time of  $\mathcal{O}^*(81^k)n$ .  $\square$

Crucial to the running of the algorithm are the Merge, Split and Move operations. These are described and analyzed in the following sections, thus completing the analysis of Algorithm 1.

### 3.1 DFS Instance

Each round of Algorithm 1 proceeds with a single DFS instance over the main nodes in  $\mathcal{T}$ . Notice that the intersection nodes in  $\mathcal{T}$  can at most scale the DFS time by a factor of 2 and can thus be ignored. As with all DFS instances, every main node in  $\mathcal{T}$  is either unvisited, pre-visited, or post-visited. We define a function DFS-Status over  $V_{\mathcal{T}}^M \rightarrow \{0, 1, 2\}$  that maps all main nodes that are unvisited, pre-visited or post-visited to 2, 1 or 0 respectively. When the round begins, all main nodes are marked unvisited.

However, contrary to a straightforward DFS implementation, Algorithm 1 interrupts the DFS traversal whenever it encounters a node  $x$  with a bag of size  $w + 1$ , i.e., a maximum-size bag, during its traversal. Node  $x$  is then Split before the DFS resumes. All the new nodes created during a Split operation are marked unvisited, and the decrease in the  $\alpha$ -potential caused by the Split pays for their  $\beta$ -potential. The DFS instance then resumes from the last visited main node that was *not* split.

Every step of the DFS decreases the  $\beta$ -potential by one. Thus the  $\beta$ -potential at the start of each round bounds the total time taken for the DFS. Since the input to Algorithm 1 is assumed to be a 4-approximation of the tree decomposition, Alg 1 runs  $O(k)$  many rounds.

### 3.2 Move

Alg 1 decreases the size of a maximum-size bag of a node  $r$  (with size  $w + 1$ ) by finding a split of a tree decomposition rooted at  $r$ . Once  $r$  has been split, the DFS instance on  $\mathcal{T}$  resumes until it finds a node  $x$  such that  $|B_x| = w + 1$ . Node  $x$  must then be moved to the root of  $\mathcal{T}$ , and DP-tables of all nodes on the path  $P$  between  $r$  and  $x$  in  $\mathcal{T}$  updated to reflect the new root. This Move, described in Alg 3, is performed as a series of edge rotations (Alg 2) between consecutive nodes  $y_i, y_{i+1}$  in  $P$ .

Notice that whenever the bag of the main node is  $j > 1$  vertices larger than the intersection node it is being added to in Alg 2, up to  $O(k)$  nodes may be created. However the node sizes decrease by 1, which decreases the corresponding DP-table size by a factor of 4. The cost of creating and updating the tables of these  $r_i$  is at most  $4/3$  times the cost of updating  $A_r$ . Thus each rotation takes time within a constant factor of the time taken to update a single DP-table, i.e.  $4^{|B_r|}$ . Furthermore, the number of rotations performed during a round is bounded by the number of steps taken by the DFS-instance (Lemma 8). Consider:

**Algorithm 2** Rotate( $\mathcal{T}, r, y, A_{\mathcal{T}}$ )**Note:**  $r, y \in V_{\mathcal{T}}^M$  and  $r = p(p(y))$ .**Output:** Grouped Tree Decomposition  $\mathcal{T}$  with root  $y$  such that  $y = p(r)$ Let  $z = p(y)$   $\triangleright$  Thus  $z \in V_{\mathcal{T}}^I$  and  $r = p(z)$ Subtract  $y$  from  $z$  and Update the table  $A_r$ **if** there are no nodes  $y'$  such that  $z = p(y')$  **then**Subtract  $z$  from  $r$ .**if**  $\exists z_y \in V_{\mathcal{T}}^I$  such that  $y = p(z_y)$  AND  $B_{z_y} = B_y \cap B_r$  **then****if**  $|B_r \setminus B_{z_y}| = j > 1$  **then**Add  $j - 1$  main nodes  $r_1, \dots, r_{j-1}$  between  $r$  and  $z_y$  such that  $|B_{r_1} \setminus B_r| = 1$ ,  
 $|B_{r_{i+1}} \setminus B_{r_i}| = 1$  and  $|B_{z_y} \setminus B_{r_{j-1}}| = 1$ .Add corresponding intersection nodes  $z_{r_i}$  for  $i \in [j - 1]$  for each node  
 $r_1, \dots, r_{j-1}$ Add  $r$  to  $z_{r_1}$ Update all nodes up to  $z_y$ **else if**  $|B_r \setminus B_{z_y}| == 1$  **then**Add  $r$  to  $z_y$ .**else**Initialize  $z_y$  such that  $y = p(z_y)$  and  $z_y \in V_{\mathcal{T}}^I$  and  $B_{z_y} = B_y \cap B_r$ **if**  $|B_r \setminus B_{z_y}| = j > 1$  **then**Add  $j - 1$  main nodes  $r_1, \dots, r_{j-1}$  between  $r$  and  $z_y$  such that  $|B_{r_1} \setminus B_r| = 1$ ,  
 $|B_{r_{i+1}} \setminus B_{r_i}| = 1$  and  $|B_{z_y} \setminus B_{r_{j-1}}| = 1$ .Add corresponding intersection nodes  $z_{r_i}$  for  $i \in [j - 1]$  for each node  
 $r_1, \dots, r_{j-1}$ Add  $r$  to  $z_{r_1}$ Update all nodes up to  $z_y$ **else if**  $|B_r \setminus B_{z_y}| == 1$  **then**Add  $r$  to  $z_y$ .Update  $A_y$  to reflect the change in  $z_y$ .**if**  $|B_r \setminus B_y| = 0$  **then**Merge  $r$  into  $y$ **return**  $\mathcal{T}$ **Algorithm 3** Move( $\mathcal{T}, r, x, P, A_{\mathcal{T}}$ )**Note:**  $r, x \in V_{\mathcal{T}}^M$  and  $P$  is the path from the root  $r$  to  $x$ .**Output:** Grouped Tree Decomposition  $\mathcal{T}$  with new root  $x$ **for**  $y$  in  $P$  from below  $r$  to  $x$  **do** $\mathcal{T} \leftarrow \text{Rotate}(\mathcal{T}, r, y, A_{\mathcal{T}})$  $r \leftarrow y$ **return**  $\mathcal{T}$ 

$$\begin{aligned}
- \alpha(\mathcal{T}) &= c_{\alpha} \sum_{x \in V_{\mathcal{T}}^M} |B_x| f(x), \text{ where } c_{\alpha} > 0 \text{ and } f(x) = \begin{cases} |B_x \setminus B_{p(p(x))}| & \text{if } x \neq r \\ (|B_x| + 1)/2 & \text{if } x = r \end{cases}, \\
- \beta(\mathcal{T}) &= c_{\beta} \sum_{x \in V_{\mathcal{T}}^M} \text{DFS-Status}(x), \text{ where } c_{\beta} > 0
\end{aligned}$$

When  $x \neq r$ ,  $f(x) = 1$  because of the unique home property of the grouped tree decomposition. However, during intermediate steps when this property is not maintained (eg. during a Split) the value of  $f(x) = 0$  for main nodes that must be merged.

**Lemma 6.** *Given a grouped tree decomposition  $\mathcal{T}$ ,  $\alpha(\mathcal{T})$  does not change while Moving a node with a maximum size bag to the root.*

*Proof.* Let the  $\alpha$  potential of  $\mathcal{T}$  refer to the first term of  $\phi(\mathcal{T})$ , i.e.  $\alpha(\mathcal{T})$ .

Consider a grouped tree decomposition  $\mathcal{T}$  rooted at a node  $r$ . Let  $\mathcal{T}^M$  be the corresponding unique home tree decomposition of  $\mathcal{T}$ . To make the analysis simpler, the Move operation is analyzed over  $\mathcal{T}^M$ . Notice that the  $\alpha$  potential is defined over all main nodes of  $\mathcal{T}$ , and analyzing it over  $\mathcal{T}^M$  is sufficient.

Assume that  $B_r$  is the home of  $\ell + 1$  vertices  $v_1, \dots, v_{\ell+1}$ . To maintain the unique home property of  $\mathcal{T}^M$ , assume that the existing  $\alpha$  potential of the root node ( $|B_r| \frac{(|B_r|+1)}{2} = \sum_{j=1}^{|B_r|} j$ ) is distributed over a chain of main nodes  $r_1, \dots, r_\ell$  above  $r$ , such that  $r_\ell$  is the parent of  $r$  with  $B_{r_\ell} = B_r \setminus \{v_{\ell+1}\}$ . Also, for all  $i \in \{1, \dots, \ell - 1\}$ ,  $B_{r_i} = B_{r_{i+1}} \setminus \{v_{i+1}\}$ . The Move operation is performed on  $\mathcal{T}^M$  to change the current root  $r$  to some new node  $r'$  with a bag of maximum size. This operation is done step-wise by rotating the edges on the path  $P$  between  $r$  and  $r'$ . During the move, the chain  $\{r_1, \dots, r_\ell\}$  is maintained according to the current (temporary) root of the tree. Given nodes  $x, y$  that occur successively on  $P$  such that  $x = p(y)$  in  $\mathcal{T}^M$ , when the edge between  $x$  and  $y$  is rotated, one of the following must occur:

- $|B_x| < |B_y|$ : Since  $\mathcal{T}^M$  is a unique home tree decomposition,  $B_x \subset B_y$  and  $|B_y \setminus B_x| = 1$ . To maintain the unique home property, node  $x$  must be merged into node  $y$ . Since the new root  $y$  is now home to one additional vertex, an additional  $r_{\ell+1}$  node must be added to the chain of nodes above the root. The  $\alpha$  potential given to node  $r_{\ell+1}$  is the same as that of  $x$ , which means the  $\alpha$  potential of  $\mathcal{T}^M$  remains unchanged.
- $|B_x| > |B_y|$ : Let  $|B_x \setminus B_y| = t$  for  $t > 1$ , and  $B_y = \{u_0, u_1, \dots, u_s\}$ , and  $B_x = \{u_1, \dots, u_{s+t}\}$ . Let  $x$  be the home of vertices  $u_{s+1}, \dots, u_{s+t}$ . A chain of main nodes, namely  $x_1, \dots, x_t$  are added between  $y$  and  $x$ , where  $B_{x_i} = B_x \setminus \{u_{s+t}\}$  and  $B_{x_i} = B_{x_{i+1}} \setminus \{u_{(s+i)}\}$  for  $i \in \{1, \dots, t\}$ . Notice that since  $|B_y| < |B_x|$  the chain of nodes above  $y$  is exactly  $t$  nodes shorter than the chain above  $x$  when  $x$  was the root of  $\mathcal{T}$ . These additional nodes  $r_1, \dots, r_t$  have exactly the same potential as the main nodes that will now be added between root  $y$  and node  $x$  to maintain the unique home property. Thus, the  $\alpha$  potential remains unchanged.
- $|B_x| = |B_y|$ :  $\mathcal{T}^M$  is a unique home tree decomposition and so  $|B_y \setminus B_x| = 1$ . Since  $|B_x| = |B_y|$  are equal, it follows that  $|B_x \setminus B_y| = 1$ , and nothing more must be changed in  $\mathcal{T}^M$ , i.e., the  $\alpha$  potential remains unchanged. □

**Lemma 7.** *The  $\beta$ -potential decreases by 1 per step in the DFS-Instance.*

*Proof.* In each step of the DFS-Instance, the DFS moves to a different node. The label of the node it moves to then changes from unvisited to pre-visited, or pre-visited to post-visited. Both these changes mark a decrease in the DFS-Status of the node it moves to – thus decreasing the  $\beta$ -potential of  $\mathcal{T}$ .  $\square$

**Lemma 8.** *The number of rotations performed in a round is bound by the number of steps in the DFS-Instance.*

*Proof.* All nodes with maximum-size bags are found in a round using the DFS-Instance. The maximum number of rotations that can occur are then, at most, a constant factor times the number of steps in the DFS-Instance.  $\square$

### 3.3 Merge

The unique home property is essential for Algorithm 1. To maintain this property, *main nodes* are merged if they aren't the home of any vertex, i.e., given  $x, y \in V_{\mathcal{T}}^M$  such that  $x = p(p(y))$  and  $B_y \subseteq B_x$ ,  $y$  is merged into  $x$ . A Merge operation is performed bottom-up as described in Algorithm 4.

The running time of Alg 4 is determined by the number of complete DP-table updates required. Notice that a full DP-table is only updated when intersection nodes overlap between  $x$  and  $y$ , i.e.  $I_x \cap I_y$ , or when the contribution lists of  $x$  must be fixed.

Consider a function  $\gamma(\mathcal{T}) = c_\gamma |V_{\mathcal{T}}|$ , for some  $c_\gamma > 0$ . The number of DP-table recomputations performed during the Merge can be counted using  $\gamma(\mathcal{T})$ .

**Lemma 9.** *Given a grouped tree decomposition  $\mathcal{T}$  that is transformed into a grouped tree decomposition  $\mathcal{T}'$  by a Merge,  $\gamma(\mathcal{T}) - \gamma(\mathcal{T}')$  bounds the number of DP-tables recomputed during the Merge.*

*Proof.* A main node  $y$  is merged into its grandparent  $x$  if  $B_y \subseteq B_x$ . As described in Alg 4, a DP-table is recomputed at every node  $i \in I_x$  such that there exists a node  $j \in I_y$  (where  $I_z$  denotes the intersection node children of a node  $z$ ) that satisfies  $B_i = B_j$ . Furthermore  $A_x$  is also updated when the contribution lists in  $A_x$  must be updated using  $A_y$ . In both cases, observe that a node is deleted for each update during the merge, i.e.,  $j \in I_y$  for each  $A_i$  updated, and  $y$  for  $A_x$ . These decrease the  $\gamma$  function. Thus  $\gamma(\mathcal{T}) - \gamma(\mathcal{T}')$  bounds the number of complete DP-table updates that occur during a Merge.  $\square$

### 3.4 Split

A Split operation involves finding a *split* (Def 7) of  $\mathcal{T}$  where root  $r$  has a bag of maximum size  $w + 1$ , and using it to decrease the size of  $B_r$ . We describe the procedure in Algorithm 6, but the operation comprises the following three stages:

---

<sup>3</sup> Note that all intersection nodes of a node are ordered according to an imposed global order over all vertices in  $V$ . Thus this does not take significant time

---

**Algorithm 4** Merge( $\mathcal{T}$ ,  $x$ ,  $y$ ,  $A_{\mathcal{T}}$ )
 

---

**Output:** Updated grouped tree decomposition  $\mathcal{T}$  and  $A_{\mathcal{T}}$  with node  $y$  merged into node  $x$

```

1: Let  $I_x = \{i \mid i \in V_{\mathcal{T}}^I, x = p(i)\}$  and  $I_y = \{i \mid i \in V_{\mathcal{T}}^I, y = p(i)\}$ .
2: Let node  $z \in I_x$  such that  $z = p(y)$ .
3: if  $\exists y' \neq y$  such that  $z = p(y')$  then
4:     Subtract  $y$  from  $z$ 
5: else
6:     Delete  $z$  from  $I_x$ 
7: for  $z_y \in I_y$  do
8:     if  $\exists z_x \in I_x$  such that  $B_{z_x} = B_{z_y}$  then3
9:         Append the list of children of  $z_y$  to the list of children of  $z_x$ 
10:        for Partition  $P = (W_1, W_2, W_3, X)$  of  $B_{z_x}$  and  $B_{z_y}$  do
11:            if  $P$  not legal then
12:                 $s(A_{z_x}[P]) = cl(A_{z_x}[P]) = \perp$ 
13:            else
14:                 $s(A_{z_x}[P]) = s(A_{z_x}[P]) + s(A_{z_y}[P]) - |X|$ 
15:                 $cl(A_{z_x}[P]) = cl(A_{z_x}[P]), cl(A_{z_y}[P])$ 
16:                if  $s(A_{z_x}[P]) > k + 1 + |X|$  OR  $|cl(A_{z_x}[P])| > k + 1$  then
17:                     $s(A_{z_x}[P]) = cl(A_{z_x}[P]) = \perp$ 
18:                    Store pointer to start of  $A_{z_x}$  at start of  $A_{z_y}$ 
19:            else
20:                Add  $z_y$  as a child of  $x$ 
21:        for Partition  $P$  of  $B_x$  do
22:            for  $\exists$  entry  $a \in cl(A_x[P])$  that points to  $z$  do
23:                for Entry  $b \in cl(A_z[a[2]])$  that points to  $y$  do
24:                    for  $x \in cl(A_y[b[2]])$  that points to  $z'_y$  do
25:                        if  $*$ (( $x[1]$ )) points to the start of some table  $A_{z_x}$ ,  $x = p(z_x)$  then
26:                            Update  $a[1] = * (x[1])$ 
27: Delete  $y$  and any intersection nodes of  $y$ 
28: Return  $\mathcal{T}$ 
    
```

---

1. Finding a split  $P = (C_1, C_2, C_3, S)$  of  $\mathcal{T}$  : This is done top-down in  $\mathcal{T}$
2. Using  $P$  to create up to three copies  $(x_1, x_2, x_3)$  of all editable nodes (Def 8)  $x$  in  $\mathcal{T}$ , with each  $B_{x_i}$  containing only vertices in  $C_i \cup S$
3. Preserving the unique home property of grouped tree decompositions and creating a new root node  $r'$  such that  $B_{r'} = S$ .

It is important to note that the tree traversal stops further exploration when it reaches a (intersection) node that is not editable, i.e., it only explores the editable tree. This is crucial for maintaining the linear running time. Yet again, the running time of the Split operation is bounded by the number of table updates performed, which we bound using the potential functions  $\alpha(\mathcal{T}) = c_\alpha \sum_{x \in V^M} |B_x| f(x)$  where  $c_\alpha > 0$  and  $f(x) = \begin{cases} |B_x \setminus B_{p(x)}| & \text{if } x \neq r \\ \frac{|B_x| + 1}{2} & \text{if } x = r \end{cases}$  and  $\delta(\mathcal{T}) = h(k) |V_{\mathcal{T}}^{\max}|$ , for  $h(k) = \mathcal{O}(k^2)$ .

**Algorithm 5** UpdateTables( $x, x_i, P^g, \mathcal{T}, \mathcal{T}_i$ )

---

```

if  $x$  is an intersection node then
  Let  $M_x^E$  be the (editable) children of  $x$  and  $M_{x_i}^E$  be the (editable) children of  $x_i$ 
  for  $y \in M_x^E$  do
    Subtract  $y$  from  $x$ 
  for  $y \in M_{x_i}^E$  do
    Add  $y$  to  $x_i$ 
  Return
  Let  $I_x^E$  be the editable children of  $x$  and  $I_x^N$  be the non-editable children of  $x$ 
  Let  $I_{x_i}^E$  be the editable children of  $x_i$  and  $I_{x_i}^N$  be the non-editable children of  $x_i$ 
  for  $y \in I_x^E$  do ▷ Remove the contribution of editable children
    Subtract  $y$  from  $x$ 
  for Every  $P_i = (W_1^i, W_2^i, W_3^i, X^i)$  of every  $B_{x_i}$  do ▷ Efficient Update  $x_i$  using  $x$ 
    Let  $Q = B_x \cap (W_j \cup W_k)$  for chosen good partition  $P^g = (W_1, W_2, W_3, X)$  of  $B_x$ 
    Let  $P$  be the partition  $(W_1^i, W_2^i, W_3^i, X^i \cup Q)$  of  $B_x$ 
     $s(A_{x_i}[P_i]) = s(A_x[P]) - |Q|$ 
     $cl(A_{x_i}[P_i]) = cl(A_{x_i}[P_i]) \cap I_{x_i}^N$ 
  for  $y \in I_{x_i}^N$  do ▷ Add any separator vertices present in  $\mathcal{T}^{x_i}$  that are not in  $x_i$ 
    Let  $X^y$  be the separator of  $\mathcal{T}_y$  at  $y$ 
    for  $v \in X^y, v \notin B_{x_i}$  do
      Add  $v$  to  $B_{x_i}$ 
  for  $y \in I_{x_i}^E$  do ▷ Add editable children and their separator vertices to  $x_i$ 
    Add  $y$  to  $x_i$ 
    Let  $X^y$  be the separator of  $\mathcal{T}_y$  at  $y$ 
    for  $v \in X^y, v \notin B_{x_i}$  do
      Add  $v$  to  $B_{x_i}$ 
    for  $P = (W_1^i, W_2^i, W_3^i, X^i)$  of  $B_{x_i} \setminus \{v\}$  do
      Set  $P'_j = P$  with  $\{v\}$  added to  $W_j^i$ 
      for  $P'_j, j \in [3]$  do
        if  $P'_j$  is a legal partition then
           $A_{x_i}[P'_j] = A_{x_i}[P]$ 
        else
           $A_{x_i}[P'] = \perp$ 
        Set  $P' = P$  with  $\{v\}$  added to  $X^i$ 
         $s(A_{x_i}[P']) = s(A_{x_i}[P]) + 1$ 

```

---

Algorithm 5 is a crucial sub-routine of Algorithm 6. After all editable nodes  $x$  are edited during a Split, Alg 5 updates the tables at each copy  $x_i$  of an edited node  $x$ , while avoiding any expensive recomputations. Consider the work done to update the tables at each  $x_i$ . Node  $x$  could have both editable children and non-editable children. The values in  $A_{x_i}$  would have to represent the separator created by the non-editable child nodes of  $x$  that are assigned to  $C_i$ , and the editable child nodes of  $x$  that have a subset of the vertices in their bags assigned to  $C_i$ .

While the update each editable child node of  $x_i$  causes at  $x_i$  is bound by the  $\alpha$  potential of  $\mathcal{T}$  (Thm 4), the non-editable nodes represent a cost of computation

that is not covered by  $\phi(\mathcal{T})$ . However this costly computation can be avoided by utilizing the table at  $x$ , after subtracting all editable nodes from  $x$ , i.e., when  $A_x$  only has the contribution of all non-editable children of  $x$ .

Let  $B_x = B_{x_i} \cup Q$ , where  $Q = \bigcup_{j \in a(x), j \neq i} W_j^x$ . Let  $P' = W'_1, W'_2, W'_3, X'$  be a partition of  $B_{x_i}$  and  $P$  be a partition of  $B_x$ , such that  $P = W'_1, W'_2, W'_3, X' \cup Q$ . Notice, that since  $A_x$  is indexed by all possible partitions of  $B_x$ , it must have an entry corresponding to  $P$ . By setting  $s(A_{x_i}[P']) = s(A_x[P]) - |Q|$  and  $cl(A_{x_i}[P'])$  equal to all pointers in  $cl(A_x[P])$  that point to a non-editable child of  $x_i$ , we retrieve the table at  $x_i$  in time proportional to the table size times the maximum length of  $cl(A_x[.])$ , i.e.,  $k$ . This is significantly faster than having to add an unbounded number non-editable nodes to  $x_i$ , and is done at most thrice for each editable node  $x$  – a constant cost for each editable node. Finally, all the editable children of  $x_i$  are added to  $x_i$ . While this is an expensive operation, it is covered by the  $\alpha$  potential of  $\mathcal{T}$  (Thm 4).

The separator vertices present in the child nodes of  $x_i$ , that are not in  $x_i$  are added to the bag of  $x_i$  – to ensure that all vertices in the separator  $S$  of the chosen split have their home in the root node. As Lemma 4 proves, this still ensures that  $|B_{x_i}| < |B_x|$ . This is done twice, once while updating  $A_{x_i}$  to reflect the contribution of its non-editable children, and once after the editable children have been added to  $x_i$ . Every time a separator vertex  $v_s$  is added to  $B_{x_i}$ ,  $A_{x_i}$  expands to include  $v_s$  in each index. Given a partition  $P$  of  $B_{x_i}$ ,  $v_s$  can either be assigned to a component ( $W_j^{x_i}$ ) or to the separator  $X^{x_i}$ . If  $v_s$  is added to a component  $W_j^{x_i}$ , the entries in  $A_{x_i}[P']$  remain unchanged if  $P'$  is a legal partition (where  $P'$  is a new partition of  $B_{x_i}$  with  $v_s$ ). Else we set both  $s(A_{x_i}[P'])$  and  $cl(A_{x_i}[P'])$  to  $\perp$ . If  $v_s$  is added to  $X^{x_i}$ , then  $s(A_{x_i}[P'])$  is increased by one, and  $cl(A_{x_i}[P'])$  adds the child node that contains  $v_s$ .

**Theorem 4.** *The  $\alpha$  and  $\delta$  potential of a grouped tree decomposition  $\mathcal{T}$  bounds the number of table updates performed during Split operations in a round of Algorithm 1 and the increase in the  $\beta$  and  $\gamma$ -potential during a Split.*

*Proof.* Consider a grouped tree decomposition  $\mathcal{T}$ . First we show that  $\alpha(\mathcal{T})$  before a Split operation is strictly greater than  $\alpha(\mathcal{T}')$ , where  $\mathcal{T}'$  is the tree decomposition obtained after all editable nodes in  $\mathcal{T}$  are edited.

Let  $x$  be a non-root editable main node in  $\mathcal{T}$ , that is home to some vertex  $\{v\}$ , and is edited into  $x_i$  for all  $i \in a(x)$ . The  $\alpha$  potential of  $x$  is  $c_\alpha |B_x|$ . Let  $\{v\}$  be assigned to some component  $W_j^x$  for  $j \in a(x)$ . Then,  $x_j$  is the only copy of  $x$  that has  $\alpha$  potential, since for all  $i \neq j, i \in a(x)$ ,  $x_i$  is not the home of any vertex. By Def 7,  $|B_{x_j}| < |B_x|$ , i.e., the  $\alpha$  potential of  $x_j$  is strictly less than that of  $x$  – for all non-root main nodes  $x$  in  $\mathcal{T}$ . Now let  $\{v\}$  be assigned to  $X^x$ . At the end of a Split, all separator vertices have their home in the root node. Thus no  $x_i$  for  $i \in a(x)$  has any  $\alpha$  potential.

Let  $r$  be the root of  $\mathcal{T}$ , with maximum size bag  $B_r$ , that is home to  $|B_r|$  vertices.  $r$  is split into  $r_i$  for all  $i \in a(r)$ . If the unique home property was preserved at the root as well, there would exist a series of forget nodes above  $r$  until the root of  $\mathcal{T}$  had a bag of size one. As seen above, the  $\alpha$  potential of

**Algorithm 6** Split( $r, \mathcal{T}$ )

---

Begin a tree walk of  $\mathcal{T}$  at root  $r$   
**while** At an editable  $x \in V_{\mathcal{T}}$  **do**  
  **if**  $x$  is unvisited **then**  
    Pick a good partition  $P^x = (W_1^x, W_2^x, W_3^x, X^x)$  of  $B_x$   
    **if**  $x$  is editable **then**  
      Create copies  $x_i$  of  $x$  s.t.  $B_{x_i} = W_i^x \cup X^x$  for all  $i \in a(x)$   
      Link  $x_i$  to  $p(x)_i$  in  $\mathcal{T}_i$   
    **else**  
      Move  $x$  and  $\mathcal{T}^x$  to  $C_i$  such that  $W_i \neq \emptyset$  by linking it to  $p(x)_i$   
      Mark  $x$  as post-visited and return  
    **else if**  $x$  is pre-visited **then**  
      **for**  $i \in a(x)$  **do**  
        UpdateTables( $x, x_i, P^x, \mathcal{T}, \mathcal{T}_i$ )  
      Create new node  $r'$  such that  $B_{r'} = \bigcup_{x \in V_{\mathcal{T}}} X^x$ .  
      Add all  $r_i$  for  $i \in a(r)$  as grandchildren of  $r'$ , and create corresponding intersection nodes of  $r'$ .  
      Begin a new tree traversal of the new tree  $\mathcal{T}'$  from  $r'$   
      **while**  $\exists x \in V_{\mathcal{T}'}$  that is not post-visited **do**  
        Merge  $x$  into  $p(x)$  if it violates the unique home property

---

these forget nodes and  $r$  would also decrease in their copies in  $\mathcal{T}'$ . Since the unique home property is not preserved at the root, we give  $r$  enough  $\alpha$  potential to cover the  $|B_r|$  forget nodes that would be required to preserve the property. This is covered by the additional factor in  $f(x)$ .

Thus the  $\alpha$  potential of  $\mathcal{T}$  is strictly greater than the  $\alpha$  potential of  $\mathcal{T}'$ . This decrease, multiplied by the constant factors in  $c_\alpha$ , pays for updating the tables of all the copies of an editable node and its intersection node parent.

Each editable main node in  $\mathcal{T}$  creates up to 6 nodes in  $\mathcal{T}'$  when it is edited – i.e., its copies and their intersection node parents. These added nodes increase both the  $\beta$  and  $\gamma$  potential. The increase in  $\gamma$  potential is  $6c_\gamma$ , while the increase in  $\beta$  potential is  $12c_\beta$  – to account for the DFS-Status of the unvisited nodes. Since this is always a constant increase, it can be accounted for in  $c_\alpha$ . Thus the decrease in the  $\alpha$  potential, covers the increase in the  $\beta$  and  $\gamma$  potentials during a round as well.

The last step in a Split is to create the new root  $r'$  with  $B_{r'} = S$ . Each copy  $r_i$  of the original root  $r$  is home to  $|B_{r_i}|$  vertices. To maintain the unique home property, if  $|B_{r_i} \setminus S| > 1$ , we would have to create a chain of forget nodes and their corresponding intersection nodes between  $r_i$  and  $r'$ . Each of these nodes would be decreasing in size, with the largest being of size  $O(k)$ , and we could have at most  $O(k)$  many such nodes. Furthermore, the new root  $r'$  would need to be give enough potential to be home to  $|S|$  vertices. The  $\delta$  potential with  $h(k) = O(k^2)$  given to all maximum size bags, including  $r$ , covers the potential of the new root, as well as that of the chain of nodes between  $r_i$  and  $r'$ .

Thus, the  $\alpha$  and  $\delta$  potentials bound the work done during a Split operation. The merge performed at the end of a Split, to maintain the unique home property, is paid for by the  $\gamma$  potential. As we have already described above, the increase in  $\gamma$  potential is covered by the decrease in  $\alpha$  potential.  $\square$

## 4 Conclusion

There have been quite a few FPT algorithms with running time linear in  $n$  ([4, 6, 8]), and the focus has been shifting towards improving both the dependency on  $k$  and the approximation ratio. In this paper, we present an  $\mathcal{O}^*(81^k)n$ -time 2-approximation of treewidth, which is a significant improvement on Korhonen's  $\mathcal{O}^*(1728^k)n$ -time 2-approximation algorithm [6]. While our algorithm cannot guarantee a tighter upper bound on the running time, it is highly unlikely that any tree decomposition would require nearly this much time to output a 2-approximation of the treewidth. Not all main nodes with bags of size  $w$  will have  $\mathcal{O}(2^w)$  intersection node children, and fewer still will need to be edited.

There are still many open questions to be answered. Unlike [6], our running time bottleneck occurs when the width is in the range  $[3k + 3, 4k + 3]$ , i.e. when we create a 3-partition. It would be interesting to see if that case could be further optimized. In light of the recent work by Korhonen and Lokshtanov [8] it would be interesting to see if we can achieve the  $(1 + \epsilon)$  approximation in time  $\mathcal{O}(c^k n)$  for some constant  $c$ .

## References

1. Arnborg, S., Corneil, D.G., Proskurowski, A.: Complexity of finding embeddings in a  $k$ -tree. *SIAM Journal on Algebraic Discrete Methods* **8**(2), 277–284 (1987)
2. Belbasi, M., Fürer, M.: Finding all leftmost separators of size  $\leq k$ . In: *Combinatorial Optimization and Applications - 15th International Conference, COCOA 2021*. pp. 273–287. LNCS 13135, Springer (2021). [https://doi.org/10.1007/978-3-030-92681-6\\_23](https://doi.org/10.1007/978-3-030-92681-6_23), [https://doi.org/10.1007/978-3-030-92681-6\\_23](https://doi.org/10.1007/978-3-030-92681-6_23)
3. Belbasi, M., Fürer, M.: An improvement of Reed’s treewidth approximation. *J. Graph Algorithms Appl.* **26**(2), 257–282 (2022). <https://doi.org/10.7155/jgaa.00593>, <https://doi.org/10.7155/jgaa.00593>
4. Bodlaender, H.L.: A linear-time algorithm for finding tree-decompositions of small treewidth. *SIAM Journal on computing* **25**(6), 1305–1317 (1996)
5. Bodlaender, H.L., Drange, P.G., Dregi, M.S., Fomin, F.V., Lokshtanov, D., Pilipczuk, M.: A  $c^k n$  5-approximation algorithm for treewidth. *SIAM Journal on Computing* **45**(2), 317–378 (2016)
6. Korhonen, T.: A single-exponential time 2-approximation algorithm for treewidth. In: *62nd IEEE Annual Symposium on Foundations of Computer Science, FOCS*. pp. 184–192 (2021). <https://doi.org/10.1109/FOCS52979.2021.00026>, <https://doi.org/10.1109/FOCS52979.2021.00026>
7. Korhonen, T.: A single-exponential time 2-approximation algorithm for treewidth (2023)
8. Korhonen, T., Lokshtanov, D.: An improved parameterized algorithm for treewidth. In: *Proceedings of the 55th Annual ACM Symposium on Theory of Computing*. p. 528–541. *STOC 2023*, Association for Computing Machinery, New York, NY, USA (2023). <https://doi.org/10.1145/3564246.3585245>, <https://doi.org/10.1145/3564246.3585245>
9. Robertson, N., Seymour, P.D.: Graph minors. III. Planar tree-width. *Journal of Combinatorial Theory, Series B* **36**(1), 49–64 (1984)
10. Robertson, N., Seymour, P.D.: Graph minors II. Algorithmic aspects of tree-width. *J. Algorithms* **7**(3), 309–322 (1986). [https://doi.org/10.1016/0196-6774\(86\)90023-4](https://doi.org/10.1016/0196-6774(86)90023-4), [http://dx.doi.org/10.1016/0196-6774\(86\)90023-4](http://dx.doi.org/10.1016/0196-6774(86)90023-4)