THE RQR ALGORITHM*

DAAN CAMPS[‡], THOMAS MACH[§], RAF VANDEBRIL[¶], AND DAVID S. WATKINS^{||}

Abstract. Pole-swapping algorithms, generalizations of bulge-chasing algorithms, have been shown to be a viable alternative to the bulge-chasing QZ algorithm for solving the generalized eigenvalue problem for a matrix pencil $A - \lambda B$. It is natural to try to devise a pole-swapping algorithm that solves the standard eigenvalue problem for a single matrix A. This paper introduces such an algorithm and shows that it is competitive with Francis's bulge-chasing QR algorithm.

Key words. eigenvalue, QZ algorithm, QR algorithm, bulge chasing, pole swapping

AMS subject classifications. 65F15, 15A18

1. Introduction. The standard algorithm for computing the eigenvalues of a small to medium-sized non-Hermitian matrix $A \in \mathbb{C}^{n \times n}$ is still Francis's implicitly-shifted QR algorithm [11,18]. In many applications, eigenvalue problems arise naturally as generalized eigenvalue problems for a pencil $A-\lambda B$, and for these problems the Moler-Stewart variant of Francis's algorithm [14], commonly called the QZ algorithm, can be used. These are bulge-chasing algorithms [17]: they introduce a non-zero matrix element (or bulge) in an upper Hessenberg matrix (resp. upper Hessenberg-triangular pencil), and chase it downwards along the subdiagonal.

In recent years a generalization of QZ called RQZ was introduced by Camps, Meerbergen, and Vandebril [8,10]. See also Steel et al. [15] and Camps et al. [9]. This uses a generalization of bulge chasing called pole swapping and is a viable competitor of QZ for the generalized eigenvalue problem. It is natural to ask whether the pole-swapping idea can be adapted to the standard eigenvalue problem for a single matrix A, which would provide an alternative to Francis's algorithm. The RQR algorithm introduced in this paper is such an alternative.

In Sections 2 and 3 we will explain the modifications to RQZ that are needed to make an efficient and numerically stable RQR algorithm, and in Section 4 we will present some numerical results that demonstrate that RQR is competitive with QR. In fact, the RQR code is slightly faster and a bit more accurate, in the sense that the backward error is smaller.

2. Modifying RQZ to make RQR. We assume that the reader is familiar with the papers about pole swapping cited above, especially the original RQZ paper [10], and perhaps also [9]. We will also need to use some core-chasing terminology, for which we refer to [1] or [3], for example.

^{*}This research was partially supported by the Research Council KU Leuven (Belgium), project C16/21/002 (Manifactor: Factor Analysis for Maps into Manifolds) and by the Fund for Scientific Research – Flanders (Belgium), projects G0A9923N (Low rank tensor approximation techniques for up- and downdating of massive online time series clustering) and G0B0123N (Short recurrence relations for rational Krylov and orthogonal rational functions inspired by modified moments).

[‡]National Energy Research Scientific Computing Center, Lawrence Berkeley National Laboratory, USA (dcamps@lbl.gov).

[§]University of Potsdam, Institute of Mathematics, Karl-Liebknecht-Str. 24–25, 14476 Potsdam, Germany; (thomas.mach@uni-potsdam.de).

[¶]Department of Computer Science, KU Leuven, Belgium (raf.vandebril@cs.kuleuven.be).

Department of Mathematics, Washington State University (watkins@math.wsu.edu)

¹LAPACK, the most widely used library for linear algebra computation, uses Francis's algorithm in https://github.com/Reference-LAPACK/lapack/blob/master/SRC/zhseqr.f.

The RQZ algorithm acts on Hessenberg pencils $A - \lambda B$, that is, pencils for which both A and B are upper-Hessenberg matrices. Let's suppose throughout that the matrices have dimension n. The poles of the Hessenberg pencil $A - \lambda B$ are $\sigma_1 = a_{21}/b_{21}$, $\sigma_2 = a_{32}/b_{32}$, ..., $\sigma_{n-1} = a_{n,n-1}/b_{n,n-1}$, i.e., the ratios of the subdiagonal elements. Associated with this pencil is a pole pencil $A_{\pi} - \lambda B_{\pi}$ obtained by deleting the first row and last column from $A - \lambda B$. The pole pencil is clearly $(n-1) \times (n-1)$ and upper triangular, and its eigenvalues are exactly the poles of $A - \lambda B$. Therefore the task of swapping two adjacent poles in $A - \lambda B$ is exactly the same as that of interchanging two adjacent eigenvalues of the pole pencil.

If we wish to find the eigenvalues of a single upper-Hessenberg matrix A, we can do this by applying the RQZ algorithm to the pencil $A-\lambda I$, which is a Hessenberg pencil. However RQZ applies unitary equivalence transformations that are not similarities, so the form $A-\lambda I$ is not preserved. Once we begin the iterations, the form of the pencil will become $A-\lambda U$, where $U\neq I$. However U will be upper Hessenberg, and it will also be unitary because I is unitary and so are all of the transformations performed by the RQZ algorithm. Our task is just to show how to do the operations efficiently in this special case.²

It is well known, see [1, 3, 4, 12] for example, that a unitary Hessenberg matrix U can be stored very compactly as a product of a descending sequence of n-1 core transformations: $U = U_1U_2\cdots U_{n-1}$. We remind the reader that a core transformation is just a unitary matrix whose active part is 2×2 , acting on two successive rows and columns as indicated by its subscript. For example, Givens rotations are core transformations. Here U_1 acts on rows 1 and 2, U_2 acts on rows 2 and 3, and so on. We represent this pictorially by a double arrow pointing at the active rows. For example,

$$U = \bigcap_{\zeta} \zeta \qquad (2.1)$$

Here we have depicted the case n = 6. Since each core transformation is determined by two numbers, the total storage required for U is just 2n - 2 numbers.

The main operation in RQZ is the swap of two adjacent poles, which we call a move of type II. The interchange of poles j-1 and j is accomplished by a transformation,

$$A \to Q_j^* A Z_{j-1} \qquad U \to Q_j^* U Z_{j-1},$$
 (2.2)

where Q_j and Z_{j-1} are core transformations, Q_j acting on rows j and j+1 of A and U, and Z_{j-1} acting on columns j-1 and j. We need to show how to carry out the transformation efficiently and accurately on U, which is stored as in (2.1). There are several ways to generate Q_j and Z_{j-1} , and it's important how we do it here, but let's not worry about that initially.

²We also investigated whether there is an efficient way of obtaining $A - \lambda U$ with A upper Hessenberg and U unitary upper Hessenberg from a general matrix C. However, we have so far not being able to find a better way than using the traditional reduction of B to its Hessenberg form A combined with U = I.

In the case j = 3 we have for the update of U in (2.2) that,

The result must again be upper Hessenberg, so there must be a way of reorganizing the core transformations into a single descending sequence, as pictured in (2.1). One possibility is to move the blue core from the right to the left by a shift-through operation (one turnover) [1], resulting in,

$$Q_j^*UZ_{j-1} = \bigcap_{i=1}^{n} \bigcap_{j=1}^{n} \bigcap_{j=1}^{n} \bigcap_{i=1}^{n} \bigcap_{j=1}^{n} \bigcap_{j=1}^{n} \bigcap_{i=1}^{n} \bigcap_{j=1}^{n} \bigcap_{i=1}^{n} \bigcap_{j=1}^{n} \bigcap_{i=1}^{n} \bigcap_{j=1}^{n} \bigcap_{i=1}^{n} \bigcap_{j=1}^{n} \bigcap_{i=1}^{n} \bigcap_{j=1}^{n} \bigcap_{i=1}^{n} \bigcap_{j=1}^{n} \bigcap_{j=1}^{n} \bigcap_{i=1}^{n} \bigcap_{j=1}^{n} \bigcap_{j=1}^{n} \bigcap_{i=1}^{n} \bigcap_{j=1}^{n} \bigcap_{j=1}^{n}$$

Because the matrix is upper Hessenberg, the resulting blue core must be the inverse of the red core, so that they cancel each other out. Another possibility is to move the red core from the left to the right, resulting in,

$$Q_j^*UZ_{j-1} = \bigcap_{i=1}^{r} \bigcap_{j=1}^{r} \bigcap_{j=1}^{r} \bigcap_{i=1}^{r} \bigcap_{j=1}^{r} \bigcap_{j=1}^{r} \bigcap_{i=1}^{r} \bigcap_{j=1}^{r} \bigcap_{i=1}^{r} \bigcap_{j=1}^{r} \bigcap_{i=1}^{r} \bigcap_{j=1}^{r} \bigcap_{i=1}^{r} \bigcap_{j=1}^{r} \bigcap_{i=1}^{r} \bigcap_{j=1}^{r} \bigcap_{i=1}^{r} \bigcap_{j=1}^{r} \bigcap_{j=1}^{r} \bigcap_{i=1}^{r} \bigcap_{j=1}^{r} \bigcap_{j=1}^{r} \bigcap_{i=1}^{r} \bigcap_{j=1}^{r} \bigcap_{j=1}^{r} \bigcap_{j=1}^{r} \bigcap_{i=1}^{r} \bigcap_{j=1}^{r} \bigcap_{j=1}^{r}$$

Again, the resulting red core must be the inverse of the blue core, and they must cancel out. Neither of these procedures works in practice because of problems with roundoff errors, so we need to be a bit more careful.

We have to go back to the details of the computation of Q_j and Z_{j-1} , which must swap the eigenvalues of the subpencil,

$$\left[\begin{array}{cc} a_{j,j-1} & a_{jj} \\ & a_{j+1,j} \end{array}\right] - \lambda \left[\begin{array}{cc} u_{j,j-1} & u_{jj} \\ & u_{j+1,j} \end{array}\right].$$

For this we need to figure out the values of a few entries of U, which is, fortunately, easy. If the active part of the jth core transformation U_j is $\begin{bmatrix} c_j & -s_j \\ s_j & \overline{c}_j \end{bmatrix}$, then $u_{j,j-1} = s_{j-1}$ and $u_{jj} = \overline{c}_{j-1}c_j$, as the reader can easily check. Thus our pencil is,

$$\begin{bmatrix} a_{j,j-1} & a_{jj} \\ & a_{j+1,j} \end{bmatrix} - \lambda \begin{bmatrix} s_{j-1} & \overline{c}_{j-1}c_j \\ & s_j \end{bmatrix}.$$
 (2.3)

Its two eigenvalues are $\lambda_1 = a_{j,j-1}/s_{j-1}$ and $\lambda_2 = a_{j+1,j}/s_j$, and we need to swap them. The basic procedure that we follow is due to Van Dooren [16], as modified by Camps et al. [9]. There are several variants, and our choice of variant will depend on the relative magnitudes of the eigenvalues.

The case $|\lambda_1| \ge |\lambda_2|$. For this case we will use a variant that computes Z_{j-1} first and then Q_j . Substituting λ_2 for λ in (2.3), we get,

$$\begin{split} H &= s_j \left[\begin{array}{cc} a_{j,j-1} & a_{jj} \\ & a_{j+1,j} \end{array} \right] - a_{j+1,j} \left[\begin{array}{cc} s_{j-1} & \overline{c}_{j-1}c_j \\ & s_j \end{array} \right], \\ &= \left[\begin{array}{cc} s_j a_{j,j-1} - a_{j+1,j}s_{j-1} & s_j a_{jj} - a_{j+1,j}\overline{c}_{j-1}c_j \\ 0 & 0 \end{array} \right] = \left[\begin{array}{cc} * & * \\ 0 & 0 \end{array} \right]. \end{split}$$

Let Z be a core transformation such that,

$$HZ = \left[\begin{array}{cc} 0 & * \\ 0 & 0 \end{array} \right].$$

This is (the active part of) our transformation Z_{j-1} in (2.2). If we now compute Q_j as prescribed in [16] or [9], we get a backward-stable swap that never fails, but since we are storing U in the special form (2.1), we have to proceed differently.

Instead of computing Q_j , we immediately apply Z_{j-1} to the pencil $A - \lambda U$. In the case j = 3, the picture looks like this:

When we apply the core Z_{j-1} to A on the right, it recombines columns 2 and 3, creating a bulge in the (4,2) position. In U, let's do a turnover to move the extra core from the right to the left:

Now we need to apply Q_j^* on the left to return the matrices to upper Hessenberg form. How do we compute Q_j ? The picture tells the story. The remaining red core must be Q_j , as the way to return U to Hessenberg form is to get rid of the red core by multiplying by its inverse, which we show in blue here:

This returns U to upper Hessenberg form, and it also knocks out the bulge in A,

returning it to Hessenberg form:

This completes the swap.

This procedure is guaranteed to keep U perfectly in Hessenberg form. The entry in the (j+1,j-1) position of A will be slightly nonzero due to roundoff, but the error analysis in [9] guarantees that it is small enough to be ignored.

The case $|\lambda_1| < |\lambda_2|$. In this case we compute Q_j first. Substituting λ_1 for λ in (2.3), we get,

$$\begin{split} H &= s_{j-1} \left[\begin{array}{c} a_{j,j-1} & a_{jj} \\ a_{j+1,j} \end{array} \right] - a_{j,j-1} \left[\begin{array}{c} s_{j-1} & \overline{c}_{j-1}c_j \\ & s_j \overline{c}_{j-1}c_j \end{array} \right], \\ &= \left[\begin{array}{cc} 0 & s_{j-1}a_{jj} - a_{j-1}\overline{c}_{j-1}c_j \\ 0 & s_{j-1}a_{j+1,j} - a_{j,j-1}s_j \end{array} \right] = \left[\begin{array}{cc} 0 & * \\ 0 & * \end{array} \right]. \end{split}$$

Now compute a core transformation Q such that

$$Q^*H = \left[\begin{array}{cc} 0 & * \\ 0 & 0 \end{array} \right].$$

This Q is (the active part of) our desired Q_j in (2.2). Now we apply Q_j^* to the pencil $A - \lambda U$ immediately. In the case j = 3 it looks like this:

When we apply Q_j^* to A, it recombines rows 3 and 4, making a bulge in the (4,2) position. We pass Q_j^* through U by a turnover:

We now return U to upper Hessenberg form by multiplying by the inverse of the extra core, which we mark in blue. This must be Z_{j-1} .

When we apply Z_{j-1} to A on the right, it recombines columns 2 and 3, cancelling out the bulge.

This completes the swap.

Again the (j+1, j-1) entry of A will be slightly nonzero due to roundoff, but it is guaranteed to be small enough to ignore. The analysis in [9] does not mention this case explicitly, but this is dual to the "Z-first" method shown above and has the same numerical properties.

Moves of type I. Each iteration of the RQR algorithm begins and ends with a move of type I. A type I move at the top of the pencil inserts an arbitrary pole ρ , replacing σ_1 , at the top of the pencil. Let $x = (A - \rho B)e_1$, and let Q_1 be a core transformation such that $Q_1^*x = \alpha e_1$ for some $\alpha \neq 0$. This is possible because only the first two entries of x are nonzero: $\begin{bmatrix} x_1 \\ x_2 \end{bmatrix} = \begin{bmatrix} a_{11} - \rho u_{11} \\ a_{21} - \rho u_{21} \end{bmatrix}$. Since U is stored in the form (2.1), we need to extract the values of u_{11} and u_{21} , but this is easy: if $\begin{bmatrix} c_1 & -s_1 \\ s_1 & \overline{c_1} \end{bmatrix}$ is the active part of the first core transformation in U, then $u_{11} = c_1$ and $u_{21} = s_1$.

Once we have Q_1^* , we apply it to $A - \lambda U$ to obtain $Q_1^*A - \lambda Q_1^*U$:

The core Q_1^* recombines the first two rows of A, and it can be absorbed into U by a fusion operation. The resulting $Q_1^*A - \lambda Q_1^*U$ remains in Hessenberg form. This completes the move of type I. The reader can easily check that the first pole is now ρ . The other poles are unchanged.

A move of type I at the bottom replaces the bottom pole by an arbitrary pole τ . The details of this routine are analogous and are left to the reader.

3. The RQR algorithm. The RQR algorithm applied to $A - \lambda U$ is the same as the RQZ algorithm, with the modifications described in the previous section. Each iteration of the basic algorithm begins with the choice of a shift ρ . Any shifting strategy that is commonly used by the Francis or Moler-Stewart algorithm can be used. For example, the simplest choice is the Rayleigh-quotient shift $\rho = a_{nn}/u_{nn}$. A better choice is the Wilkinson shift, which computes the eigenvalues of the 2×2 subpencil in the lower right-hand corner and takes ρ to be the eigenvalue that is closer to a_{nn}/u_{nn} .

Once ρ has been chosen, it is inserted as a pole at the top of the pencil by a move of type I. Then, by a sequence of moves of type II, ρ is swapped with poles σ_2 , σ_3 , and so on, until ρ reaches the bottom of the pencil. Then it is replaced by a new pole τ by a move of type I. The simplest pole choice is the *Rayleigh-quotient pole* $\tau = a_{11}/u_{11}$. A better choice is the *Wilkinson pole*: Compute the eigenvalues of the

 2×2 submatrix in the upper left-hand corner and take τ to be the eigenvalue that is closer to a_{11}/u_{11} .

This completes the iteration.

Repeated iterations will generally cause the pencil to converge to triangular form, revealing the eigenvalues on the main diagonal. Convergence is not equally rapid up and down the pencil. Good shifts ρ inserted at the top will cause rapid convergence at the bottom. If $a_{n,n-1} \to 0$ and $u_{n,n-1} \to 0$ rapidly, they can be declared to be zero after just a few iterations, and a_{nn}/u_{nn} can be declared to be an eigenvalue. This is known as a deflation and it reduces the problem to size n-1. After deflating, we can go after the next eigenvalue. At the same time, the poles τ that are inserted at the bottom will gradually move to the top and improve the rate of convergence to zero of elements at the top, such as a_{21} and a_{21} . This generally decreases the total number of iterations required compared to a similar bulge chasing approach.

The algorithm can be enhanced in several ways. For one thing, there is no need to wait until one iteration is complete before initiating the next one; many iterations can proceed at once. Suppose we want to do m iterations simultaneously, where $1 \ll m \ll n$. We pick m shift ρ_1, \ldots, ρ_m at once. For example, we can compute the eigenvalues of the $m \times m$ subpencil in the lower right-hand corner of $A - \lambda B$ and use them as shifts. Then, by moves of types I and II, we insert ρ_1, \ldots, ρ_m as the first m poles in the pencil. Then we chase them all down to the bottom simultaneously. This improves performance substantially by enabling the use of level-3 BLAS and decreasing cache misses. This was proposed in the context of bulge chasing by Braman et al. [6] and Lang [13], and discussed in the context of pole swapping in [9, 15].

Another very important enhancement is the use of aggressive early deflation, introduced by Braman et al. [7] and discussed in the context of pole swapping in [15].

For real matrices it is desirable to introduce a double-shift algorithm that allows for the use of complex-conjugate shifts and poles while staying in real arithmetic.

We have not implemented any of these enhancements so far.

4. Numerical Results. We wrote a Fortran implementation of the RQR algorithm with Wilkinson shifts and Wilkinson poles. We compared the performance of our RQR code (ZLAHPS) with that of ZLAHQR, the QR kernel from LAPACK version 3.12.0. ZLAHPS was built by modifying ZLAHQR.³ On the test problems that we considered, RQR was, on average, faster and more accurate than QR.

For the numerical experiments reported below we used the gfortran compiler from gcc 9.4.0 with optimization flag -O2 on a computer with Ubuntu 20.04.2, an Intel Core i7-10700K CPU with 12 MiB of L3 cache, and 32 GiB of RAM. Experiments on other computers showed similar results.

We considered two kinds of matrices: (1) randomly-generated matrices reduced to upper Hessenberg form, and (2) upper Hessenberg matrices with entries $a_{ij} = i + j$ (i < j + 2). Matrices of dimension 10×10 up to 1297×1297 were tested. For the random matrices we did 100 trials at each dimension. The results are shown in Figure 4.1.

The RQR algorithm (red) is consistently faster than QR (blue). The typical speedup is around 17% for matrices of size less than 75 and 29% for larger matrices. At the same time, the backward errors are smaller by a factor of 1.5 to 2. The results for smaller matrices are particularly relevant since LAPACK's main eigenvalue routine

 $^{^3}$ We also modified routines for manipulating rotations, for instance the turnover, from the eiscorproject [2].




FIG. 4.1. Comparison of the RQR pole swapping algorithm (in red) with the QR bulge chasing algorithm (in blue) in terms of backward error (left) and runtime (right) for random matrices reduced to upper Hessenberg form (square markers) and i + j upper Hessenberg matrices (dashed line).

ZHSEQR uses ZLAHQR only for matrices of dimension up to 75.4

The results for the randomly-generated matrices are also given in tabular form in Table 4.1. This lists execution times, backward errors (BWE), and total iterations divided by n (It/n). The iteration counts are significantly less for RQR, which explains why RQR is faster, and may also explain why it is more accurate, as fewer iterations imply fewer roundoff errors.

We also tested both codes on 35 matrices of size less than 1000 from matrix market [5]. Both codes performed well. With a small number of exceptions, RQR was faster and more accurate than QR. See Table 4.2.

These results show that pole swapping is a viable alternative to bulge chasing for the standard eigenvalue problem. The code and the experiments we presented only use a single shift in each iteration. This is the natural and the fastest choice for small matrices of dimension up to about 75. For larger matrices multishift/multibulge variants with aggressive early deflation are preferred. We do not yet have pole swapping code with these features. Hence, a fair comparison with LAPACK's routines including these features is not possible at this time. Nevertheless, the experiments that we have presented here are a preliminary indication that pole swapping has the potential to be faster and more accurate than the QR codes that are currently in use.

REFERENCES

- J. L. AURENTZ, T. MACH, L. ROBOL, R. VANDEBRIL, AND D. S. WATKINS, Core-Chasing Algorithms for the Eigenvalue Problem, SIAM, Philadelphia, 2018.
- [2] J. L. AURENTZ, T. MACH, R. VANDEBRIL, AND D. S. WATKINS, eiscor eigensolvers based on core transformations. https://github.com/eiscor/eiscor, 2014–2018.
- [3] J. L. AURENTZ, T. MACH, R. VANDEBRIL, AND D. S. WATKINS, Fast and backward stable computation of roots of polynomials, SIAM J. Matrix Anal. Appl., 36 (2015), pp. 942–973.

 $^{^4}$ The LAPACK installation used for the experiment uses $n_{\min}=75$ for deciding when to use ZLAHQR. This parameter is machine- and installation-dependent, thus your mileage may vary.

RQR				QR			
n	Time [s]	BWE	It/n	n	Time [s]	BWE	It/n
10	3.88e-05	1.30e-15	2.58	10	4.41e-05	1.93e-15	3.10
15	8.74 e-05	1.61e-15	2.67	15	1.02e-04	2.42e-15	3.27
23	2.14e-04	2.00e-15	2.70	23	2.57e-04	3.03 e-15	3.35
34	5.15 e-04	2.42e-15	2.74	34	6.25 e-04	3.70 e-15	3.38
51	1.35e-03	2.97e-15	2.74	51	1.67e-03	4.55e-15	3.37
76	3.54 e-03	3.59 e-15	2.74	76	4.52e-03	5.54 e-15	3.35
114	1.01e-02	4.36e-15	2.74	114	1.32e-02	6.75 e-15	3.32
171	3.30e-02	5.31e-15	2.73	171	4.57e-02	8.41e-15	3.28
256	1.63e-01	$6.45\mathrm{e}\text{-}15$	2.72	256	2.25 e-01	1.06e-14	3.25
384	5.03e-01	7.78e-15	2.70	384	6.83 e-01	1.25 e-14	3.22
577	1.09	9.44e - 15	2.68	577	1.61	1.53e-14	3.19
865	3.59	1.15e-14	2.67	865	5.41	1.93e-14	3.16
1297	15.51	1.40e-14	2.66	1297	22.30	2.54e-14	3.13

Table 4.1

Comparison of RQR vs. QR on random matrices with normally-distributed entries. In a preprocessing step the matrices have been reduced to upper Hessenberg form.

- [4] J. L. AURENTZ, T. MACH, R. VANDEBRIL, AND D. S. WATKINS, Fast and stable unitary QR algorithm, Electron. Trans. Numer. Anal., 44 (2015), pp. 327–341.
- [5] R. F. Boisvert, R. Pozo, K. Remington, R. F. Barrett, and J. J. Dongarra, Matrix Market: a web resource for test matrix collections, Quality of Numerical Software: Assessment and Enhancement, (1997), pp. 125–137.
- [6] K. Braman, R. Byers, and R. Matthias, The multishift QR algorithm, part I: Maintaining well focused shifts and level 3 performance, SIAM J. Matrix Anal. Appl., 23 (2001), pp. 929–947.
- [7] ——, The multishift QR algorithm, part II: Aggressive early deflation, SIAM J. Matrix Anal. Appl., 23 (2001), pp. 948–973.
- [8] D. CAMPS, Pole swapping methods for the eigenvalue problem: Rational QR algorithms, PhD thesis, KU Leuven, 2019.
- [9] D. CAMPS, T. MACH, R. VANDEBRIL, AND D. S. WATKINS, On pole-swapping algorithms for the eigenvalue problem, Electron. Trans. Numer. Anal., 52 (2020), pp. 480–508.
- [10] D. CAMPS, K. MEERBERGEN, AND R. VANDEBRIL, A rational QZ method, SIAM J. Matrix Anal. Appl., 40 (2019), pp. 943–972.
- [11] J. G. F. Francis, The QR transformation, part II, Computer J., 4 (1961), pp. 332–345.
- [12] W. B. GRAGG, The QR algorithm for unitary Hessenberg matrices, J. Comput. Appl. Math., 16 (1986), pp. 1–8.
- [13] B. Lang, Using level 3 BLAS in rotation-based algorithms, SIAM J. Sci. Comput., 19 (1998), pp. 626-634.
- [14] C. B. Moler and G. W. Stewart, An algorithm for generalized matrix eigenvalue problems, SIAM J. Numer. Anal., 10 (1973), pp. 241–256.
- [15] T. STEEL, D. CAMPS, K. MEERBERGEN, AND R. VANDEBRIL, A multishift, multipole rational QZ method with aggressive early deflation, SIAM J. Sci. Comput., 42 (2021), pp. 753-774.
- [16] P. VAN DOOREN, A generalized eigenvalue approach for solving Riccati equations, SIAM J. Sci. Stat. Comput., 2 (1981), pp. 121–135.
- [17] D. S. WATKINS, The Matrix Eigenvalue Problem: GR and Krylov Subspace Methods, SIAM, Philadelphia, 2007.
- [18] ——, Francis's algorithm, Amer. Math. Monthly, 118 (2011), pp. 387–403.

		RQR			QR		
n	Name	Time [s]	BWE	$\mathrm{It/n}$	Time [s]	BWE	It/n
200	bwm200	0.031	1.19e-14	1.81	0.037	6.27e-15	2.04
961	cdde1	3.460	8.17e-15	1.89	3.779	1.18e-14	2.02
961	cdde2	4.791	9.88e-15	2.53	6.706	1.61e-14	3.07
961	cdde3	3.345	7.71e-15	1.90	3.787	1.18e-14	2.03
961	cdde4	4.962	1.00e-14	2.53	6.879	1.61e-14	3.08
961	cdde5	3.335	1.31e-14	1.91	3.769	1.25e-14	2.01
961	cdde6	4.909	1.01e-14	2.52	6.753	1.58e-14	3.09
104	ck104	0.005	2.25 e-15	2.06	0.005	3.80e-15	2.03
400	ck400	0.233	8.61e-15	1.82	0.320	7.91e-15	1.89
656	ck656	1.037	9.14e-15	2.81	1.339	1.06e-14	2.00
512	dwa512	0.647	1.05e-14	1.89	0.795	1.21e-14	1.91
512	dwb512	0.618	5.06e-15	1.88	0.779	7.00e-15	1.93
163	lop163	0.024	4.10e-15	2.37	0.029	7.83e-15	2.59
100	olm100	0.003	2.72e-15	1.70	0.004	4.62e-15	2.02
500	olm500	0.243	8.21e-15	1.63	0.262	7.53e-15	1.85
225	pde225	0.068	4.83e-15	2.77	0.086	7.70e-15	3.04
900	pde900	3.575	9.62e-15	2.49	4.900	1.48e-14	2.70
362	plat362	0.202	6.93 e-15	2.14	0.235	1.20e-14	2.38
362	plskz362	0.255	7.42e-15	2.75	0.333	1.22e-14	3.25
324	qc324	0.163	5.77e-15	2.22	0.220	9.72e-15	2.39
768	qh768	1.216	3.63e-15	2.93	1.427	3.04e-15	2.11
882	qh882	1.127	4.68e-15	3.70	1.214	5.56e-15	2.08
480	rbs480a	0.666	8.73e-15	2.62	0.853	1.35e-14	3.01
480	rbs480b	0.656	8.81e-15	2.70	1.066	1.58e-14	3.06
200	rdb200	0.025	3.85e-15	2.21	0.028	6.26e-15	1.68
200	rdb200l	0.025	4.02e-15	2.78	0.026	5.66e-15	1.74
450	rdb450	0.270	9.19e-15	2.40	0.309	1.14e-14	1.61
450	rdb450l	0.273	6.44e - 15	2.52	0.303	9.64e-15	1.66
800	rdb800l	1.904	9.69e-15	2.38	2.164	1.40e-14	1.63
968	rdb968	3.034	9.46e-15	1.95	3.657	1.81e-14	1.72
136	rw136	0.021	4.64e-15	2.76	0.024	8.28e-15	3.15
496	rw496	0.718	8.39e-15	2.72	1.248	1.72e-14	3.06
340	tols340	0.109	4.81e-15	8.43	0.078	6.61e-15	1.95
90	tols 90	0.003	3.10e-15	2.01	0.003	4.10e-15	2.24
100	tub100	0.005	3.50e-15	2.34	0.006	5.15e-15	2.82

Table 4.2

 $Results\ special\ matrices\ from\ matrix\ market.\ Green\ entries\ are\ better\ than\ {\it red}\ entries.$