# DiagramQG: A Dataset for Generating Concept-Focused Questions from Diagrams

Xinyu Zhang<sup>1</sup>, Lingling Zhang<sup>1</sup><sup>†</sup>, Yanrui Wu<sup>1</sup>, Muye Huang<sup>1</sup>, Wenjun Wu<sup>1</sup>, Bo Li<sup>1</sup>, Shaowei Wang<sup>1</sup>, Basura Fernando <sup>3</sup>, Mike Zheng Shou <sup>2</sup>, Jun Liu<sup>1</sup>

<sup>1</sup>Xi'an Jiaotong University <sup>2</sup>Show Lab, National University of Singapore <sup>3</sup>Institute of High-Performance Computing, A\*STAR <sub>zhang1393869716@stu.xjtu.edu.cn</sub>

# Abstract

Visual Question Generation (VQG) has gained significant attention due to its potential in educational applications. However, VQG researches mainly focus on natural images, largely neglecting diagrams in educational materials used to assess students' conceptual understanding. To address this gap, we construct DiagramQG, a dataset containing 8,372 diagrams and 19,475 questions across various subjects. DiagramQG introduces concept and target text constraints, guiding the model to generate concept-focused questions for educational purposes. Meanwhile, we present the Hierarchical Knowledge Integration framework for Diagram Question Generation (HKI-DQG) as a strong baseline. This framework obtains multi-scale patches of diagrams and acquires knowledge using a visual language model with frozen parameters. It then integrates knowledge, text constraints and patches to generate concept-focused questions. We evaluate the performance of existing VOG models, open-source and closed-source vision-language models, and HKI-DQG on the DiagramQG dataset. Our novel HKI-DQG consistently outperforms existing methods, demonstrating that it serves as a strong baseline. Furthermore, we apply HKI-DOG to four other VOG datasets of natural images, namely VQG-COCO, K-VQG, OK-VQA and A-OKVQA, achieving state-of-the-art performance.

# **1. Introduction**

Visual Question Generation (VQG), a crucial research area in computer vision and natural language processing, aims to automatically generate meaningful questions from input images. The evolution of VQG approaches has witnessed a significant shift from traditional rule-based and templatebased methodologies to sophisticated neural network archi-



Figure 1. Comparison of different types of text constraints in visual question generation on natural images (a) and on the DiagramQG dataset (b).

tectures, encompassing both unconstrained [27] and constrained [11, 14, 34, 35] paradigms. While early VQG research focused primarily on generating questions using only image inputs [27], contemporary research has expanded to incorporate various guiding information to enhance question generation specificity, including answers [14, 16], answer types [11, 36], image region [35], question types [7], and knowledge triple [34], thereby significantly improving the quality and relevance of generated questions. We demonstrate various existing text constraints as inputs for visual question generation, as shown in (a) of Figure 1.

However, current VQG research focuses on natural images, neglecting diagrams commonly popular in educational materials. This fails to meet educational requirements for assessment. Diagrams play a vital role in education by presenting information in a structured engaging manner, enabling students to understand complex concepts more effectively [4]. Moreover, these concept-focused questions based on diagrams assess students' ability to explain, analyze, and apply the information presented in diagrams using concepts [12] on diverse subjects. Therefore, generating questions based on diagrams is crucial for assessing students' ability to apply the learned concepts in a practical context.

To bridge the gap between current research and educational requirements, we have constructed DiagramQG, the first dataset containing 8,372 diagrams and 19,475 questions, covering 4 subjects, 15 courses, and 169 concepts, by integrating existing diagram question-answering datasets [10, 23, 40, 49] with secondary school curriculum materials. These questions provide a more comprehensive evaluation of students' understanding of the concepts across different subjects. Meanwhile, the DiagramQG dataset introduces concept and target text constraints, guiding the model to generate questions that meet educational requirements and include the target text, as shown in (b) of Figure 1. The target text serves as guidance to control question diversity, as each diagram can generate multiple concept-focused questions. Related research shows that answer-based constraints tend to generate contextindependent questions [18]. Question-type constraints often deviate from the intended assessment objectives [34]. Moreover, knowledge triple-based constraints frequently result in mere triple expansions rather than meaningful questions [25]. This demonstrates the importance of our proposed text constraint for diagram question generation.

Compared to natural images, diagrams require a significant amount of subject-specific background knowledge for understanding [41], and they typically contain a higher number of objects [9]. Thus, tackling the Diagram Question Generation (DQG) task requires a framework that can incorporate subject-specific knowledge, comprehend object relationships within diagrams, and generate meaningful questions accordingly. We propose a novel Hierarchical Knowledge Integration framework for Diagram Question Generation (HKI-DQG). The framework leverages CLIP to identify relevant multi-scale diagram patches, from which vision-language models like BLIP and Qwen2-VL extract knowledge. After T5 filters the extracted knowledge to ensure relevance to text constraints, the framework integrates these filtered insights with text constraints and multi-scale diagram patches to generate questions. Notably, this approach doesn't require training the vision-language model, which improves scalability and reduces costs. We evaluate HKI-DQG against current VQG and vision-language models on our DiagramQG dataset. Additionally, we conduct experiments with HKI-DQG on four natural image VQG datasets, validating HKI-DQG's generalizability and effectiveness. Our contributions are summarized as follows:

• We introduce the comprehensive DiagramQG dataset, the first question generation dataset specifically designed for diagrams, and develop a novel text constraint that guides

the model in generating concept-focused questions.

- We propose an adaptable framework based on different frozen-parameter vision-language models, addressing DQG tasks at a lower cost, and conduct experiments on both DiagramQG and four natural image VQG datasets.
- We thoroughly evaluate the performance of current mainstream VQG models, various open-source and closedsource vision-language models, and our proposed framework on the newly constructed DiagramQG dataset.

# 2. Related Work

#### 2.1. Visual Question Generation

VQG task has progressed from rule-based and templatebased methods to advanced neural network architectures, including both unconstrained and constrained approaches. The unconstrained approach, while implement, often produces generic questions with insufficient image specificity, restricting the development of constrained VQG methods [1, 27]. Researchers have explored various text constraints to improve question generation quality, including answerguided methods [11, 20, 43, 46], question types [7], answer categories [38], and knowledge-enhanced approaches [2, 44]. Recent works have proposed cross-topic VOG models [19] and dual contrastive learning approaches [25] to address unseen topics and improve visual-textual alignment. However, current methods face challenges in balancing question diversity and effective utilization of visual information, emphasizing the need for innovative text constraints and methods that ensure constraint validity, question naturalness, and diversity the use of visual information.

#### 2.2. Diagram Question Answering

Diagram Question Answering (DQA) requires higher reasoning ability and background knowledge compared to Visual Question Answering (VQA). Previous research has focused on enhancing diagram understanding through pretraining approaches [8, 24, 45]. Additionally, studies investigate the use of prompting methods with Large Language Models to harness their extensive prior knowledge for DQA [23, 41, 47, 50]. Aligning the information in the diagram with background knowledge is crucial for understanding the diagram and achieving effective DQA performance.

# 3. The DiagramQG Dataset

The DiagramQG is a dataset of questions covering 4 subjects, 15 courses, and 169 concepts, consisting of 19,475 unique questions and 8,372 diagrams. These components form 44,472 combinations of tuples (target & concept text constraint, diagram, question). We provide examples from four subjects in the DiagramQG dataset, as shown in Figure 2. The diagram list annotates objects appearing in the diagram, which will be used in later evaluation metrics.



Biology	Physics	Astronomy	Computer Science	Human Physiology	Engineering
Adaptations	Acceleration	Astronomy	Array list	Excretion	Designing experiments
Adaptations and natural selection	Changes of state	Eclipses $\{\bigcup_{i=1}^{n}\}$	Binary tree 💋 💼	First two lines of defense	Electric circuits
Animals 00	Earth as a magnet XOX	Introduction to the solar system	Deadlock	Immune system defenses	Engineering practices
Cell biology	Force and motion	Revolutions of earth	Directed graph	Male reproductive system	Simple machines
Cell division	Inside the atom	Rotation of earth	Flowchart	The digestive system a C	The electromagnetic spectrum
Cell structures BIOLOGY	Law of reflection	The sun	Linked list	The muscular system	Using electromagnetism
Cells	Magnets	The sun and the earth moon system	Logic circuit	The nervous system	Oceanography
Classification	Materials	World History	Network topology	The respiratory system	Introduction to the oceans
Classification and scientific names	Measuring waves	20th century american history	Nonbinary tree	The senses	Ocean movements
Conservation	Nuclear energy	Age of exploration	Queue	The skeletal system	Seafloor spreading
Echinoderms and invertebrate	Optics	Ancient egypt and kush	Stack	Vision and the eye	Surface ocean currents
Ecological interactions	Particle motion and energy	Ancient mesopotamia	Undirected graph	Climate Science	The ocean floor
Ecosystems	Solids liquids gases and plasmas	Ancient south asia	Environmental Science	Climate and its causes	Geology
Evolution and classification of plants	States of matter	Colonial america	Air pollution	Climate zones and biomes	Continental drift
Fish	Thermal energy	Early 10th century american history	Effects of air pollution	Clouds	Earth's features
Flatworms and roundworms	Transfer of thermal energy	Early 19th century american history	Water cycle	Greenhouse effect	Erosion and deposition by water
Flow of energy	Velocity, acceleration, and forces	Early americas	Geography	Layers of the atmosphere 0,0	Erosion and deposition by glaciers
Fungi Conos to troita	Wave interference	English colonies in north america	Cities 2	Seasons	Fossils
Insects and other arthropods	Chemistry	Greece	Earth events	Weather and climate	Groundwater
Introduction to plants	Atoms and molecules	Islamic empires	Geography	Economics =:	History of life on earth
Nucleic acid classification	Biochemical reactions . H -	Medieval asia	Maps	Asia society	Inside earth
Overview of the cardiovascular system	Chemical reactions	Reconstruction	Natural resources and human	Economic principles	Plate tectonics
Photosynthesis		Rome and the byzantine empire	impacts	Government	Radioactive decay
Plant reproduction		Social studies skills	Oceania geography	Language Science	Relative ages of rocks
Plants	Cycles of matter	The american revolution	Oceans and continents	Context clues	Rocks and minerals
Protists	How elements are organized	The antebellum period	Physical geography	Descriptive details	Soils
Reproduction and life stages	Hydrocarbons	The civil war and reconstruction	States	Reading comprehension	Stress in earth crust
Scientific names	Introduction to chemical bonds	The early republic	State Capitals	Informational texts level 1	Theory of plate tectonics
The integumentary system	Ionic bonds	The silk road	The americas geography	Persuasive strategies	Types of rocks
The microscope	Solutions	World religions	Topographic maps	Visual elements	Types of volcanoes

Figure 2. Four different examples of different subjects in DiagramQG dataset.

Figure 3. Domain diversity in DiagramQG. Each color corresponds to one subject: Natural Science (blue), Earth Science (yellow), Applied Science (green), and Social Science (orange).

# 3.1. Data Collection

The data collection process is divided into four distinct phases. This process begins by gathering content from well-established datasets [10, 23, 40, 49], supplemented by searching for relevant images on Hugging Face, GitHub, and Roboflow, with all data following CC BY-SA 4.0, CC BY-NC-SA, and MIT licenses. This initial phase yields a substantial raw dataset containing over 20,000 diagrams and 40,000 questions spanning multiple subjects.

Subsequently, the collected materials are organized into four primary subjects and further categorized into 15 specific courses. This structuring process involves mapping questions to their corresponding concepts, resulting in the identification of 169 distinct concepts.

The third phase involves comprehensive annotation work conducted by trained crowd workers, who annotate target text constraints for each diagram-question pair. This annotation effort produces more than 70,000 unique combinations, as some questions are associated with different target & concept text constraints, such as the same concept but different targets. Additionally, they annotate diagram elements and texts to evaluate models' diagram understanding.

The final phase employs crowd workers to evaluate combinations using a 100-point scale for educational utility, with a passing threshold of 60 points. The resulting DiagramQG dataset contains 8,372 diagrams, 19,475 questions, and 44,472 complete combinations, sourced from ScienceQA (34.1%), TQA (24.3%), CSDQA (10.8%), ADE (9.2%), and our collection (21.6%).

#### 3.2. Data Analyse

#### 3.2.1. Domain & Question diversity.

The DiagramQG dataset encompasses a broad spectrum of academic domains, categorized into four primary subjects: Natural Science (blue), Earth Science (yellow), Applied

	Num. of Q	Num. of I	Object on I	Images	Text Constraint	Knowledge types
VQAv2.0	1.1M	20k	3.5	natural	answer	N/A
FVQA	5,826	2k	2.9	natural	answer	common-sense
VQG-COCO	25,000	5k	3.3	natural	image, caption	common-sense
K-VQG	16,098	13K	2.7	natural	knowledge triple	common-sense
DiagramQG	19,475	8,372	11.2	diagram	target, concept	subject knowledge

Table 1. Comparing core characteristics of major VQG Datasets and DiagramQG



Figure 4. Question distribution in DiagramQG.



Figure 5. Distribution of diagrams, questions, and questions per diagram ratios across different concepts in DiagramQG.

Science (green), and Social Science (orange), as shown in Figure 3. The dataset is structured hierarchically, with samples first classified by subject, then further divided into specific courses (e.g., Biology), and ultimately categorized into detailed concepts (e.g., Ecological interactions). Figure 3 presents a treemap visualization illustrating the dataset's breadth and depth, encompassing 4 subjects, 15 courses, and 169 concepts across several academic domains.

The DiagramQG dataset is distinguished by its diverse range of scientific questions, which exhibit significant variation in both question formulation and complexity. As depicted in Figure 4, an analysis of the first four words in question texts reveals a wide array of question types and structures. The diversity is further exemplified by the variation in question length, ranging from 4 to 50 words, with an average length of 9.52 words, underscoring the comprehensive nature of the dataset.

An in-depth analysis of the distribution of diagrams and questions across different concepts reveals a distinct longtail distribution pattern. As shown in Figure 5, the ratio of questions per diagram for each concept also exhibits a pronounced long-tail phenomenon. This skewed distribution indicates that while certain concepts are well-represented, a considerable number of concepts have limited coverage—a common challenge in educational datasets, representative of a typical occurrence in educational environments.

# **3.2.2.** Comparisons to Other Datasets.

Table 1 presents a comprehensive comparison between the DiagramQG dataset and existing visual question generation datasets. The comparative analysis reveals that DiagramQG distinguishes itself by focusing on specialized concepts across multiple subjects, in contrast to other datasets that primarily emphasize general diagram descriptions and common sense reasoning. Moreover, DiagramQG stands out as the first large-scale multimodal scientific question generation dataset that incorporates non-answer words or phrases and concepts across different subjects as text constraints. A notable aspect of our analysis involves the examination of object density per diagram across the five datasets. This is particularly significant considering that diagrams inherently contain more complex and information-rich content compared to natural images.

#### 3.2.3. Challenges in DiagramQG dataset

Based on our comparative analysis, DiagramQG presents three unique challenges that differentiate it from existing visual question generation datasets:

- **Domain-specific knowledge requirement:** Unlike other existing VQG datasets that rely on general common sense, DiagramQG encourages models to possess and apply different concepts across various subjects to generate meaningful and practical questions.
- Long-tail distribution phenomenon: The inherent longtail distribution in DiagramQG, where concept coverage ranges from abundant to limited, challenges models to generalize and optimize performance across both wellrepresented and underrepresented concepts.
- High object information density: The high density of object information in the diagrams complicates content

interpretation and risks overlooking critical details, demanding models to possess capabilities in capturing and processing complex visual information.

# 4. Baseline

# 4.1. Problem Definition

The Diagram Question Generation (DQG) task aims to generate a reasonable question q given a diagram d, a target text t, and a concept text c. The generated question should contain the target text t and effectively assess students' understanding of the specified concept c. This task can be formulated as a conditional generation problem, represented as p(q|d, t, c), where a multimodal model maps visual and textual information into a joint embedding space before decoding questions that satisfy both the text constraint and the conceptual assessment requirement.

#### 4.2. Architecture

We propose the Hierarchical Knowledge Integration (HKI-DQG) framework as a baseline for the DQG task. This framework is designed to be compatible with any visionlanguage foundation model and implements a threestage pipeline for question generation: **HierKnowExtract**, **KnowSelect**, and **KnowFusionQG**, as shown in Figure 6. The **HierKnowExtract** stage extracts knowledge  $K_s$  from multi-scale diagram patches  $P_s$  using vision-language models with frozen parameters. The **KnowSelect** stage selects the *m* most relevant knowledge sentences  $K_{(t,c)}$  based on text *t* and concept *c*. The **KnowFusionQG** stage integrates *t*, *c*,  $P_d$ , and  $K_{(t,c)}$  to generate the final question  $\hat{q}$ .

#### 4.2.1. HierKnowExtract

The **HierKnowExtract** stage obtains diagram patches  $P_s$ of different scales related to the target & concept text constraints and uses vision-language models to extract the knowledge  $K_s$  contained in all patches. This process begins with a hierarchical decomposition of diagram d into ordered patches  $P_d$  across an n-layered pyramid structure, followed by visual encoding using the CLIP Image Encoder [32] to get  $F^l$ , as formulated in Equation 1.

$$\begin{cases} F_{d} = \{F^{l}\}_{l=1}^{n} \\ P_{d} = \{p_{i,j}^{l} \mid l \in [1,n], i, j \in [1,l]\} \\ F^{l} = \{f_{i,j}^{l} = \text{CLIP}(p_{i,j}^{l}) \mid p_{i,j}^{l} \in P_{d}\} \\ p_{i,j}^{l} = d\left[\frac{i-1}{l}H : \frac{i}{l}H, \frac{j-1}{l}W : \frac{j}{l}W\right] \end{cases}$$
(1)

where H and W denote the height and width of the input diagram, respectively.

For textual components, the T5 Encoder [33] is employed to process both the target text t and concept text c

independently. We introduce a learnable linear transformation  $W_h$  to ensure compatibility between the CLIP Image Encoder [32] and T5 Encoder [33] feature spaces. This facilitates unified similarity computation and subsequent operations in the **KnowFusionQG** phase. The process culminates in the selection of the most semantically relevant patch from each hierarchical layer to form the set  $P_s$ , as shown in Equation 2.

$$\begin{cases} e_t = \mathsf{T5}_{enc}(t), & e_c = \mathsf{T5}_{enc}(c) \\ s_{i,j}^l = \sin(W_h f_{i,j}^l, e_t) + \sin(W_h f_{i,j}^l, e_c) \\ P_s = \{ p_{i^*,j^*}^l \mid (i^*,j^*) = \operatorname*{argmax}_{i,j} s_{i,j}^l, l \in [1,n] \} \end{cases}$$
(2)

Selected patches  $P_s$ , target text t, and concept text c are fed into a large-scale vision-language model (VLM) like Qwen-VL or BLIP to obtain diverse patch-specific knowledge. The resulting knowledge set  $K_s$  is generated according to Equation 3.

$$\begin{cases} K_s = \{k^l \mid l \in [1, n]\} \\ k^l = \text{VLM}(p_{i^*, j^*}^l, t, c), \quad \forall p_{i^*, j^*}^l \in P_s \end{cases}$$
(3)

where  $k^l$  is the text paragraph retrieved by the VLM, containing several knowledge sentences. To optimize the learning process, the CLIP Image Encoder [32], T5 Encoder [33], and the linear transformation  $W_h$  employed in this phase share parameters with their counterparts in the third phase, where gradient updates are effectively propagated.

#### 4.2.2. KnowSelect

The **KnowSelect** stage selects the *n* most relevant knowledge sentences  $K_{(t,c)}$  from the extensive knowledge set  $K_s$ based on target text *t* and concept text *c*. The process begins with encoding the knowledge set  $K_s$  and the text constraints using the T5 Encoder [33], as formulated in Equation 4.

$$\begin{cases} H_K = \mathsf{T5}_{\mathsf{enc}}(K_s) \\ H_{t,c} = \mathsf{T5}_{\mathsf{enc}}(\mathsf{Prompt}(t,c)) \end{cases}$$
(4)

where Prompt(t, c) synthesizes t and c into a coherent prompt following the template: Given the target text t, identify key knowledge related to the concept c.

To quantify the semantic relevance between the knowledge set  $(K_{(t,c)})$  and text constraints (t and c), we employ a scaled dot-product attention mechanism. This process computes attention scores between the knowledge tokens and the text constraint, followed by knowledge selection, as formulated in Equation 5:

$$\begin{cases} A = \operatorname{softmax} \left( \frac{H_K H_{t,c}^T}{\sqrt{d_k}} \right) \\ K_{(t,c)} = \operatorname{top-m}(AH_K) \end{cases}$$
(5)



Figure 6. (a) Process the diagram into a pyramid structure of patches. (b) Our DiagramQA baseline, HKI-DQG, consists of three distinct stages: HierKnowExtract, KnowSelect, and KnowFusionQG. In this framework, orange modules indicate trainable parameters, blue modules represent fixed parameters, and gray modules denote components without learnable parameters.

where  $d_k$  denotes the dimensionality of the hidden representations. The top-m operator selects the m most semantically relevant knowledge sentences based on attention scores, creating a knowledge set  $K_{(t,c)}$  that best matches the text constraints.

#### 4.2.3. KnowFusionQG

The **KnowFusionQG** stage integrates the selected diagram patches  $P_s$ , target text t, concept text c, and knowledge set  $K_{(t,c)}$  to generate the concept-focused question through a multimodal fusion mechanism. The process begins with encoding inputs into language and vision representations, as shown in Equation 6.

$$\begin{cases} H_t = \text{T5}_{\text{enc}}(\text{Prompt}[t;c;K_{(t,c)}]) \\ H_v = W_h \cdot \text{CLIP}(P_s) \end{cases}$$
(6)

where  $W_h$  is also used in **HierKnowExtract** phase. This Prompt[ $t; c; K_{(t,c)}$ ] synthesizes t, c and  $K_{(t,c)}$  into a coherent prompt following the template: Generate the question including Target: t to assess Concept: c with the knowledge:  $K_{(t,c)}$ . To capture the intricate relationships between textual and visual representations, a cross-modal attention mechanism followed by a gated fusion network is employed, as formulated in Equation 7.

$$\begin{cases} H_v^{attn} = \text{Softmax}(\frac{H_t H_v^T}{\sqrt{d_k}})H_v \\ \lambda = W_t H_t + W_v H_v^{attn} \\ H_{fuse} = H_t + \tanh(\lambda) \cdot H_v^{attn} \end{cases}$$
(7)

Finally, the fused output  $H_{fuse}$  is fed into the T5 decoder [33] to predict the target question  $\hat{q}$ . This integration of visual and textual information through cross-modal attention and gated fusion enables the model to generate questions that are both contextually relevant and conceptually focused.

# 5. Experiments

#### 5.1. Implementation Details

The experimental framework uses T5 Base and Large architectures along with the CLIP (ViT-B/32) model. Optimization is performed with the AdamW optimizer, applying a learning rate of 1e-5 for CLIP and 5e-5 for other components, running through 20 epochs of fine-tuning. Key parameters include a maximum input sequence length of 256, an output sequence length of 32, and a batch size of 32, with experiments conducted on one NVIDIA A800 80G GPU.

#### **5.2. Split**

The DiagramQG dataset is split into training, validation, and testing sets with a ratio of 70:5:25, ensuring no overlap of diagrams and questions across these sets. Additionally, each concept is represented in both validation and testing sets, despite some concepts having relatively few samples.

#### 5.3. Baselines

VQG approaches can be classified into two main categories: *Fine-tuned* and *In-Context Learning* methods. *Fine-tuned* methods use models like BERT [6], T5 [33], or GPT-2 [31] for question generation, with examples including K-VQG [34], Patch-TRM [22], ConVQG [25], and KC-VQG [18]. *In-Context Learning* methods utilize large vision-language models to extract relevant information from diagrams and generate questions using three reference questions. This includes open-source models like Qwen2-VL [39], MiniCPM-V [48], DeepSeek-VL [21], and InternVL2 [3], as well as closed-source models such as GLM4-V pro, Claude-3.5 Sonnect, and GPT-40. Models such as BLIP2 [13], Llava 1.5 [17], and CogVLM [42] do not perform satisfactorily on the DiagramQG dataset, likely caused by limited exposure to diagram datasets.

#### **5.4. Evaluation metrics**

We evaluate our model using established language generation metrics, including BLEU [28], Bert Score, METEOR [5], CIDEr [37], and ROUGE [15]. We evaluate model performance using the pycocoevalcap package to measure alignment between generated and ground truth questions. In addition to traditional question metrics, we propose the Diagram Element Hit Number (DEHN) to measure the utilization of diagram elements in the generated questions. Due to the uneven distribution of elements across diagrams, with

Method	BLEU-1	BLEU-2	BLEU-3	BLEU-4	Bert-Score	METEOR	CIDEr	ROUGE-L	DEHN
In-Context Learning									
InternVL2 (8B) [3]	25.57	14.48	8.76	4.54	75.18	12.78	0.25	22.12	0.37
InternVL2 (26B) [3]	27.84	16.54	10.76	7.64	78.72	15.56	0.37	24.12	0.45
InternVL2 (40B) [3]	28.40	17.78	11.85	8.63	79.72	16.91	0.39	25.35	0.46
MiniCPM-V2(8B) [48]	24.25	12.51	7.86	4.89	74.64	11.49	0.28	21.96	0.45
DeepSeek-VL(7B) [21]	23.96	14.14	8.53	5.51	76.12	14.96	0.30	23.42	0.47
Qwen2-VL(2B) [39]	26.87	15.53	9.35	5.59	75.16	12.76	0.29	23.21	0.34
Qwen2-VL(7B) [39]	28.64	17.71	11.51	8.59	76.68	15.18	0.45	24.79	0.36
Qwen2-VL(72B) [39]	35.82	25.17	18.94	15.21	82.19	19.84	0.71	31.76	0.42
GLM4-V pro	31.89	20.05	13.87	10.68	81.16	16.52	0.62	27.41	0.37
Claude-3.5-Sonnet (T)	22.76	13.01	8.05	5.16	78.77	13.26	0.45	20.51	0.02
GPT-4o (T)	19.31	10.22	6.17	3.65	80.54	11.02	0.36	20.7	0.02
Claude-3.5-Sonnet	41.86	35.15	30.14	26.20	83.54	30.39	1.78	39.67	0.20
GPT-40	43.72	37.22	32.26	28.13	84.16	31.50	1.91	43.39	0.23
Fine-tuned									
K-VQG [34]	22.37	16.97	13.51	11.05	73.88	27.48	0.45	28.55	0.25
Patch-TRM [22]	23.02	17.63	14.08	11.67	74.68	28.74	0.47	30.50	0.28
ConVQG (BLIP) [25]	31.21	23.42	18.47	15.06	74.71	29.89	0.56	31.24	0.43
KC-VQG (BLIP) [18]	33.13	26.56	21.75	17.52	79.84	31.59	1.03	34.26	0.45
KC-VQG (Q-2B) [18]	36.11	28.74	23.59	19.72	83.54	33.93	1.32	37.54	0.54
Ours									
HKI-DQG(BLIP, T5-B)	47.98	40.25	35.31	31.87	84.27	41.68	2.91	46.31	0.29
HKI-DQG(Q-2B, T5-B)	58.76	52.64	48.52	46.94	88.74	52.44	4.15	58.21	0.51
HKI-DQG(Q-7B, T5-B)	60.62	54.68	50.54	47.48	89.52	53.09	4.19	59.97	0.57
HKI-DQG(BLIP, T5-L)	50.63	43.61	38.94	35.69	85.44	43.84	3.11	49.75	0.31
HKI-DQG(Q-2B, T5-L)	60.03	54.14	50.07	47.05	89.28	53.21	4.21	59.62	0.54
HKI-DQG(Q-7B, T5-L)	61.63	55.62	51.46	48.41	89.81	54.26	4.32	60.69	0.59

Table 2. Results on DiagramQG, where GPT-40 (T) and Claude-3.5-Sonnet (T) are meant to generate questions using only text constraints, where, Q-2B, Q-7B, T5-B, T5-L mean, Qwen2-VL-2B, Qwen2-VL-7B, T5-Base and T5-Large.

Dataset	Model	BLEU-4	CIDEr	METEOR
	IM-VQG [11]	11.44	17.07	0.26
	K-VQG [34]	18.84	22.79	1.31
K-VQG	ConVQG [25]	20.01	22.66	1.53
	HKI-DQG <sub>B</sub>	55.49	48.89	4.81
	HKI-DQG <sub><math>Q</math></sub>	62.69	52.42	5.48





Figure 7. The solid line represents concept-wise BLEU scores, while the dotted line indicates the mean performance.

some containing over 30 elements, a single question cannot cover all elements. Thus, we define DEHN as the count of diagram elements present in the generated question, providing a complementary metric to assess the model's ability to incorporate relevant diagram information. The DEHN is calculated as follows: DEHN =  $\frac{1}{|Q|} \sum_{q \in Q} \sum_{i=1} \mathbb{W}(e_i \in q)$  where |Q| represents the total number of generated questions, q is a single question from the set of generated questions Q, and  $\mathbb{W}(e_i \in q)$  is an indicator function that equals 1 if the diagram element  $e_i$  is present in the question q and 0 otherwise. This metric quantitatively measures how well the model incorporates relevant diagram elements into the generated questions, complementing traditional metrics.

#### 5.5. Results

We evaluate various models on our DiagramQG dataset, as shown in Table 2. Among the in-context learning methods that utilize Vision-Language Models (VLMs), models with larger parameter counts generally perform better, indicating their abundant knowledge across different specialized scientific domains. Interestingly, Qwen2-VL 2B achieves impressive and competitive results despite having fewer parameters, making it a suitable base model for further comprehensive experiments. Tests conducted with GPT-40 and Claude-3.5 Sonnet using only text inputs result in both lower DEHN scores and reduced generation perfor-

Dataset	Model	BLEU-1	CIDEr	METEOR
	MDN [30]	36.0	23.4	0.51
	MC-BMN [29]	40.7	22.6	0.50
VQG-COCO	ConVQG [25]	50.2	26.4	0.56
	HKI-DQG $_B$	55.6	43.4	0.74
	HKI-DQG $_Q$	58.1	46.3	1.06
	IM-VQG [11]	36.47	30.25	0.15
	KVQG [34]	27.18	55.38	0.13
OK-VQA	LV2-Net [20]	29.90	92.17	0.15
	HKI-DQG $_B$	31.51	112.61	0.20
	HKI-DQG $_Q$	33.24	126.42	0.23
	IM-VQG [11]	39.30	22.11	0.12
A-OKVQA	KVQG [34]	30.56	40.97	0.13
	LV2-Net [20]	32.11	60.06	0.14
	HKI-DQG $_B$	33.21	78.42	0.18
	HKI-DQG <sub>O</sub>	34.57	92.36	0.20

Table 4. Evaluation results on VQG-COCO, OK-VQA and A-OKVQA datasets.

mance, highlighting the critical importance of incorporating diagrams in the question generation process. Among the fine-tuned methods, KVQG and Patch-TRM do not leverage VLMs for additional knowledge, while ConVQG and KC-VQG do. The latter models demonstrate superior performance, with KC-VQG showing improved results as VLM parameters scale up. HKI-DQG framework achieves the best performance across all quantitative evaluation metrics, regardless of whether it is based on T5-base or T5-large, particularly when using the larger-scale Qwen2-VL model. These impressive results validate HKI-DQG as an effective baseline for future research by demonstrating the value of incorporating subject knowledge in the DQG task. We further analyze the performance of HKI-DOG across different concepts, as illustrated in Figure 7. The results exhibit a long-tail distribution, where concepts with more training samples consistently and significantly perform better.

# 5.6. Results on Other Dataset

We thoroughly evaluate HKI-DQG's generalizability on four VQG datasets of natural images, namely VQG-COCO, OK-VQA, A-OKVQA, and K-VQG. Our proposed HKI-DQG model consistently outperforms previous state-of-theart methods on both VQG-COCO and K-VQG datasets, as shown in Table 4 and 3. According to the results, HKI-DQG achieves the best performance on most metrics, particularly on CIDEr and METEOR, indicating that the model can better grasp the semantic content of questions and generate more contextually appropriate questions.

#### 5.7. Parameter Sensitive Study

Our comprehensive laboratory experiments carefully involve two manually set key parameters: dividing the diagram into an n-layer pyramid of patches and selecting m sentences of background knowledge for question generation. Based on our analysis, Table 5 clearly shows the de-

Setting	BLEU-4	METEOR	CIDEr	DEHN
n=1,m=4	40.69	45.93	3.31	0.35
n=2,m=4	43.76	50.68	3.64	0.43
n=4,m=4	46.12	51.95	4.02	0.53
n=3,m=0	42.82	49.14	3.72	0.42
n=3,m=1	43.63	49.81	3.82	0.46
n=3,m=2	44.59	50.26	3.88	0.49
n=3,m=3	45.65	51.70	4.05	0.51
n=3,m=5	46.69	52.28	4.12	0.52
n=3,m=4	46.94	52.44	4.15	0.51

Table 5. Results on DiagramQG under different settings. We employ HKI-DQG (Qwen2-VL 2B & T5-Base) to obtain the results.

	Chosepeake say wereford Food web	
1		V U
:	and the second s	
		X
Input	Target: Bivalves; Concept: Ecological interaction	s Input Target: Filter; Concept: Echinoderms and invertebrate chordates
GT	If the number of Bivalves suddenly decreases, wh will happen to the number of Geese and Mute Sw	ant GT Which represents the part that is used to filter food out of water?
Our	If Bivalves suddenly decline in numbers, what would happen to the populations of Sea Ducks?	Our Which represents the part used to filte food from the water?
GPT-40	What kinds of organisms do bivalves eat?	GPT-40 What is the function of the filter?

Figure 8. Two different cases in DiagramQG dataset.

tailed results with n ranging from 1 to 4, with the model performance consistently peaking at n = 3, strongly suggesting that overly fine diagram division leads to noisy knowledge extraction by VLM, significantly affecting model performance. Regarding the second important parameter, Table 5 systematically shows experimental results for m ranging from 1 to 5, definitively peaking at m = 4. While excessive background knowledge notably affects the performance of HKI-DQG, the relatively minor overall impact clearly demonstrates the framework's impressive resilience to redundant input information.

## 5.8. Case Study

The comprehensive evaluation of the HKI-DQG framework on the DiagramQG dataset (Figure 8) reveals good overall capability in question generation. While advanced models like GPT-40 can generate coherent and fluent question texts, those questions often fail to effectively test students' deeper understanding of concepts. Compared to GPT-40, HKI-DQG consistently demonstrates significant advantages in generating questions with stronger concept relevance. For a more detailed case study analysis and results, please refer to the supplementary materials.

# 6. Conclusion

This study introduces DiagramQG dataset, the first dataset for diagram question generation. We propose Hierarchical Knowledge Integration for Diagram Question Generation (HKI-DQG) framework to generate concept-focused questions, supporting interactive and personalized learning [26].

# References

- Chao Bi, Shuhui Wang, Zhe Xue, Shengbo Chen, and Qingming Huang. Inferential visual question generation. In *Proceedings of the 30th ACM International Conference on Multimedia*, pages 4164–4174, 2022. 2
- [2] Jiali Chen, Zhenjun Guo, Jiayuan Xie, Yi Cai, and Qing Li. Deconfounded visual question generation with causal inference. In *Proceedings of the 31st ACM International Conference on Multimedia*, pages 5132–5142, 2023. 2
- [3] Zhe Chen, Jiannan Wu, Wenhai Wang, Weijie Su, Guo Chen, Sen Xing, Muyan Zhong, Qinglong Zhang, Xizhou Zhu, Lewei Lu, et al. Internvl: Scaling up vision foundation models and aligning for generic visual-linguistic tasks. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, pages 24185–24198, 2024. 6, 7, 2
- [4] Michelle Patrick Cook. Visual representations in science education: The influence of prior knowledge and cognitive load theory on instructional design principles. *Science education*, 90(6):1073–1091, 2006. 1
- [5] Michael Denkowski and Alon Lavie. Meteor universal: Language specific translation evaluation for any target language. In *Proceedings of the ninth workshop on statistical machine translation*, pages 376–380, 2014. 6
- [6] Jacob Devlin. Bert: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805*, 2018. 6
- [7] Zhihao Fan, Zhongyu Wei, Piji Li, Yanyan Lan, and Xuanjing Huang. A question type driven framework to diversify visual question generation. In *IJCAI*, pages 4048–4054, 2018. 1, 2
- [8] José Manuel Gómez-Pérez and Raúl Ortega. Isaaqmastering textbook questions with pre-trained transformers and bottom-up and top-down attention. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 5469–5479, 2020. 2
- [9] Xin Hu, Lingling Zhang, Jun Liu, Xinyu Zhang, Wenjun Wu, and Qianying Wang. Diagram visual grounding: Learning to see with gestalt-perceptual attention. In *IJCAI*, pages 837– 845, 2023. 2
- [10] Aniruddha Kembhavi, Minjoon Seo, Dustin Schwenk, Jonghyun Choi, Ali Farhadi, and Hannaneh Hajishirzi. Are you smarter than a sixth grader? textbook question answering for multimodal machine comprehension. In *Proceedings of the IEEE Conference on Computer Vision and Pattern recognition*, pages 4999–5007, 2017. 2, 3
- [11] Ranjay Krishna, Michael Bernstein, and Li Fei-Fei. Information maximizing visual question generation. In *Proceedings* of the IEEE/CVF conference on computer vision and pattern recognition, pages 2008–2018, 2019. 1, 2, 7, 8, 3
- [12] Amanda Jane Lambertus et al. Students' understanding of the function concept: Concept images and concept definitions. 2008. 2

- [13] Junnan Li, Dongxu Li, Silvio Savarese, and Steven Hoi. Blip-2: Bootstrapping language-image pre-training with frozen image encoders and large language models. In *International conference on machine learning*, pages 19730– 19742. PMLR, 2023. 6, 2
- [14] Yikang Li, Nan Duan, Bolei Zhou, Xiao Chu, Wanli Ouyang, Xiaogang Wang, and Ming Zhou. Visual question generation as dual task of visual question answering. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 6116–6124, 2018. 1
- [15] Chin-Yew Lin. Rouge: A package for automatic evaluation of summaries. In *Text summarization branches out*, pages 74–81, 2004. 6
- [16] Feng Liu, Tao Xiang, Timothy M Hospedales, Wankou Yang, and Changyin Sun. ivqa: Inverse visual question answering. In Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition, pages 8611–8619, 2018. 1
- [17] Haotian Liu, Chunyuan Li, Qingyang Wu, and Yong Jae Lee. Visual instruction tuning. Advances in neural information processing systems, 36, 2024. 6, 2
- [18] Hongfei Liu, Guohua Wang, Jiayuan Xie, Jiali Chen, Wenhao Fang, and Yi Cai. Knowledge-guided cross-topic visual question generation. In *Proceedings of the 2024 Joint International Conference on Computational Linguistics, Language Resources and Evaluation (LREC-COLING 2024)*, pages 9854–9864, Torino, Italia, 2024. ELRA and ICCL. 2, 6, 7, 1
- [19] Hongfei Liu, Guohua Wang, Jiayuan Xie, Jiali Chen, Wenhao Fang, and Yi Cai. Knowledge-guided cross-topic visual question generation. In *Proceedings of the 2024 Joint International Conference on Computational Linguistics, Language Resources and Evaluation (LREC-COLING 2024)*, pages 9854–9864, 2024. 2
- [20] Xumeng Liu, Wenya Guo, Ying Zhang, Xubo Liu, Yu Zhao, Shenglong Yu, and Xiaojie Yuan. Look before you leap: Dual logical verification for knowledge-based visual question generation. In Proceedings of the 2024 Joint International Conference on Computational Linguistics, Language Resources and Evaluation (LREC-COLING 2024), pages 10802–10812, Torino, Italia, 2024. ELRA and ICCL. 2, 8
- [21] Haoyu Lu, Wen Liu, Bo Zhang, Bingxuan Wang, Kai Dong, Bo Liu, Jingxiang Sun, Tongzheng Ren, Zhuoshu Li, Yaofeng Sun, et al. Deepseek-vl: towards real-world visionlanguage understanding. arXiv preprint arXiv:2403.05525, 2024. 6, 7, 2
- [22] Pan Lu, Liang Qiu, Jiaqi Chen, Tony Xia, Yizhou Zhao, Wei Zhang, Zhou Yu, Xiaodan Liang, and Song-Chun Zhu. Iconqa: A new benchmark for abstract diagram understanding and visual language reasoning. arXiv preprint arXiv:2110.13214, 2021. 6, 7, 1
- [23] Pan Lu, Swaroop Mishra, Tanglin Xia, Liang Qiu, Kai-Wei Chang, Song-Chun Zhu, Oyvind Tafjord, Peter Clark, and Ashwin Kalyan. Learn to explain: Multimodal reasoning via thought chains for science question answering. *Advances in Neural Information Processing Systems*, 35:2507–2521, 2022. 2, 3

- [24] Jie Ma, Qi Chai, Jingyue Huang, Jun Liu, Yang You, and Qinghua Zheng. Weakly supervised learning for textbook question answering. *IEEE Transactions on Image Processing*, 31:7378–7388, 2022. 2
- [25] Li Mi, Syrielle Montariol, Javiera Castillo Navarro, Xianjie Dai, Antoine Bosselut, and Devis Tuia. Convqg: Contrastive visual question generation with multimodal guidance. In *Proceedings of the AAAI Conference on Artificial Intelligence*, pages 4207–4215, 2024. 2, 6, 7, 8, 1, 3
- [26] Ishan Misra, Ross Girshick, Rob Fergus, Martial Hebert, Abhinav Gupta, and Laurens Van Der Maaten. Learning by asking questions. In *Proceedings of the IEEE Conference* on Computer Vision and Pattern Recognition, pages 11–20, 2018. 9
- [27] Nasrin Mostafazadeh, Ishan Misra, Jacob Devlin, Margaret Mitchell, Xiaodong He, and Lucy Vanderwende. Generating natural questions about an image. *arXiv preprint arXiv:1603.06059*, 2016. 1, 2
- [28] Kishore Papineni, Salim Roukos, Todd Ward, and Wei-Jing Zhu. Bleu: a method for automatic evaluation of machine translation. In *Proceedings of the 40th annual meeting of the Association for Computational Linguistics*, pages 311–318, 2002. 6
- [29] Badri Patro, Vinod Kurmi, Sandeep Kumar, and Vinay Namboodiri. Deep bayesian network for visual question generation. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision*, pages 1566–1576, 2020. 8, 3
- [30] Badri N Patro, Sandeep Kumar, Vinod K Kurmi, and Vinay P Namboodiri. Multimodal differential network for visual question generation. arXiv preprint arXiv:1808.03986, 2018. 8, 3
- [31] Alec Radford, Jeffrey Wu, Rewon Child, David Luan, Dario Amodei, Ilya Sutskever, et al. Language models are unsupervised multitask learners. *OpenAI blog*, 1(8):9, 2019. 6
- [32] Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, et al. Learning transferable visual models from natural language supervision. In *International conference on machine learning*, pages 8748–8763. PMLR, 2021. 5
- [33] Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J Liu. Exploring the limits of transfer learning with a unified text-to-text transformer. *Journal of machine learning research*, 21(140):1–67, 2020. 5, 6
- [34] Kohei Uehara and Tatsuya Harada. K-vqg: Knowledgeaware visual question generation for common-sense acquisition. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision*, pages 4401–4409, 2023. 1, 2, 6, 7, 8, 3
- [35] Kohei Uehara, Antonio Tejero-De-Pablos, Yoshitaka Ushiku, and Tatsuya Harada. Visual question generation for class acquisition of unknown objects. In *Proceedings of the European conference on computer vision (ECCV)*, pages 481–496, 2018. 1
- [36] Shagun Uppal, Anish Madan, Sarthak Bhagat, Yi Yu, and Rajiv Ratn Shah. C3vqg: Category consistent cyclic visual

question generation. In *Proceedings of the 2nd ACM International Conference on Multimedia in Asia*, pages 1–7, 2021.

- [37] Ramakrishna Vedantam, C Lawrence Zitnick, and Devi Parikh. Cider: Consensus-based image description evaluation. In *Proceedings of the IEEE conference on computer* vision and pattern recognition, pages 4566–4575, 2015. 6
- [38] Nihir Vedd, Zixu Wang, Marek Rei, Yishu Miao, and Lucia Specia. Guiding visual question generation. In Proceedings of the 2022 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, pages 1640–1654, 2022. 2
- [39] Peng Wang, Shuai Bai, Sinan Tan, Shijie Wang, Zhihao Fan, Jinze Bai, Keqin Chen, Xuejing Liu, Jialin Wang, Wenbin Ge, et al. Qwen2-vl: Enhancing vision-language model's perception of the world at any resolution. *arXiv preprint arXiv:2409.12191*, 2024. 6, 7, 1
- [40] Shaowei Wang, Lingling Zhang, Xuan Luo, Yi Yang, Xin Hu, Tao Qin, and Jun Liu. Computer science diagram understanding with topology parsing. ACM Transactions on Knowledge Discovery from Data (TKDD), 16(6):1–20, 2022. 2, 3
- [41] Shaowei Wang, Lingling Zhang, Longji Zhu, Tao Qin, Kim-Hui Yap, Xinyu Zhang, and Jun Liu. Cog-dqa: Chain-ofguiding learning with large language models for diagram question answering. In *Proceedings of the IEEE Conference* on Computer Vision and Pattern Recognition (CVPR), 2024. 2
- [42] Weihan Wang, Qingsong Lv, Wenmeng Yu, Wenyi Hong, Ji Qi, Yan Wang, Junhui Ji, Zhuoyi Yang, Lei Zhao, Song XiXuan, et al. Cogvlm: Visual expert for large language models. 2023. 6, 2
- [43] Jiayuan Xie, Yi Cai, Qingbao Huang, and Tao Wang. Multiple objects-aware visual question generation. In *Proceedings* of the 29th ACM International Conference on Multimedia, pages 4546–4554, 2021. 2
- [44] Jiayuan Xie, Wenhao Fang, Yi Cai, Qingbao Huang, and Qing Li. Knowledge-based visual question generation. *IEEE Transactions on Circuits and Systems for Video Technology*, 32(11):7547–7558, 2022. 2
- [45] Fangzhi Xu, Qika Lin, Jun Liu, Lingling Zhang, Tianzhe Zhao, Qi Chai, Yudai Pan, Yi Huang, and Qianying Wang. Moca: Incorporating domain pretraining and cross attention for textbook question answering. *Pattern Recognition*, 140: 109588, 2023. 2
- [46] Xing Xu, Tan Wang, Yang Yang, Alan Hanjalic, and Heng Tao Shen. Radial graph convolutional network for visual question generation. *IEEE transactions on neural networks and learning systems*, 32(4):1654–1667, 2020. 2
- [47] Shunyu Yao, Dian Yu, Jeffrey Zhao, Izhak Shafran, Tom Griffiths, Yuan Cao, and Karthik Narasimhan. Tree of thoughts: Deliberate problem solving with large language models. Advances in Neural Information Processing Systems, 36, 2024. 2
- [48] Yuan Yao, Tianyu Yu, Ao Zhang, Chongyi Wang, Junbo Cui, Hongji Zhu, Tianchi Cai, Haoyu Li, Weilin Zhao, Zhihui He, et al. Minicpm-v: A gpt-4v level mllm on your phone. arXiv preprint arXiv:2408.01800, 2024. 6, 7, 1

- [49] Xinyu Zhang, Lingling Zhang, Xin Hu, Jun Liu, Shaowei Wang, and Qianying Wang. Alignment relation is what you need for diagram parsing. *IEEE Transactions on Image Processing*, 2024. 2, 3
- [50] Zhuosheng Zhang, Aston Zhang, Mu Li, George Karypis, Alex Smola, et al. Multimodal chain-of-thought reasoning in language models. *Transactions on Machine Learning Research*, 2024. 2

# DiagramQG: A Dataset for Generating Concept-Focused Questions from Diagrams

# Supplementary Material

In this supplementary material, we provide more details on our implementation and experiments as follows:

- Section A: More details on implementation;
- Section B: More details on baselines;
- Section C: More details on DiagramQG;
- Section D: More experiments on other VQG datasets;
- Section E: More case studies on Diagram.

#### A. More details on implementation

In our experimental setup, we developed a framework based on the T5 architecture, utilizing both its Base and Large variants with 220M and 770M parameters respectively, alongside CLIP (ViT-B/32) for visual understanding capabilities. The framework's trainable parameters, excluding pre-trained components, were initialized following a normal distribution ( $\mu = 0, \sigma = 0.02$ ). For optimization, we implemented the AdamW optimizer with a dual learning rate strategy: a conservative 1e - 5 for CLIP components to maintain visual feature integrity, and a higher 5e-5 for remaining components. The training process spanned 20 epochs, incorporating linear learning rate warmup during the initial 2 epochs followed by cosine decay. Our implementation featured specific configurations including 256 tokens for maximum input sequence length, 32 tokens for output sequence length, a batch size of 32, 4 gradient accumulation steps, 0.01 weight decay, and 0.1 dropout rate, with FP16 mixed precision training enabled. All experimental procedures were executed on a hardware setup consisting of two NVIDIA Tesla A100 80G GPUs, utilizing CUDA 11.8 and PyTorch 1.13.1.

#### **B.** More details on baselines

Visual Question Generation (VQG) approaches can be classified into two main categories: fine-tuning-based methods and large vision-language models.

For **Fine-tuning-based methods**, using the same data split approach as our method, the dataset is divided into training, validation, and test sets in a ratio of 7:1:2. Models are trained on the training set, validated on the validation set, and final results are reported on the test set.

K-VQG [34] integrates UNITER, a multi-modal transformer, to encode both visual features (extracted via Faster R-CNN) and masked knowledge triplets. The model processes visual region features with positional information and combines them with tokenized knowledge triplets through a BART-based decoder, generating questions

Patch-TRM [22] employs a hierarchical patch-based

transformer that processes diagrams by decomposing them into meaningful patches through a pyramid layout. The model combines ResNet and vision Transformer for visual processing, using attention mechanisms to fuse visual and textual features, enabling effective capture of both local details and global relationships for diagram-focused question generation.

ConVQG [25] introduces a contrastive learning framework with dual modality-specific objectives for visual question generation. By contrasting image-specific and textguided features, the model generates diverse questions that are both image-specific and controllable through flexible textual constraints such as answers, captions, or knowledge triplets, enabling precise control over question content while maintaining visual grounding.

KC-VQG [18] presents a knowledge-guided framework that combines topic-aware visual attention and Large Language Model (LLM) generated knowledge for question generation. The model integrates three components: a topicaware visual feature extractor, a knowledge extractor with discriminative filtering, and a GPT-2 based decoder, enabling it to generate questions that incorporate both explicit visual information and implicit commonsense knowledge about specified topics.

For **large vision-language models** (VLMs), whether open-source or closed-source, we selected three reference questions for each concept. These reference questions, along with target and concept textual constraints, are incorporated into the prompt during the VLM's question generation process to obtain final outputs.

#### **Open-Source Large vision-language models:**

Qwen2-VL [39] introduces two key architectural innovations in vision-language modeling: a Naive Dynamic Resolution mechanism that processes arbitrary image resolutions by mapping them to dynamic visual tokens, and a Multimodal Rotary Position Embedding (M-ROPE) that decomposes positional information to capture 1D textual, 2D visual, and 3D video dimensions. Available in 2B, 7B, and 72B parameter versions, it employs a streaming architecture that enables efficient processing of varying input formats while maintaining strong performance on diagram-related tasks.

MiniCPM-V [48] presents a compact yet effective vision-language model that combines SigLip-400M visual encoder with Qwen2-7B language model, totaling 8B parameters. The model offers efficient multi-image and video understanding capabilities while maintaining competitive

Statistic	Number
Total unique diagrams	8,372
Total unique questions	19,475
Total combinations	44,472
Total Subject	4
Total Course	15
Total Concept	169
Train unique diagrams	5,610
Train unique questions	13,271
Train combinations	30,531
Val unique diagrams	922
Val unique questions	2,015
Val combinations	4,350
Test unique diagrams	1,839
Test unique questions	4,189
Test combinations	9,591

Table 6. Main statistics in DiagramQG

performance on vision-language tasks through its streamlined architecture and parameter-efficient design.

DeepSeek-VL [21] introduces a balanced approach to vision-language modeling that builds upon the DeepSeek language model series. The model emphasizes maintaining strong language capabilities while developing visual understanding, featuring high-resolution processing capabilities and a carefully curated training strategy. Through its systematic scaling methodology from 1B to 7B parameters, it achieves competitive performance in practical applications while maintaining efficiency in multi-modal processing.

InternVL2 [3] introduces a progressive alignment training strategy that scales efficiently from small to large language models while supporting diverse input modalities (text, images, video, and medical data). Built upon InternVL 1.5, the model incorporates an expanded training dataset covering multiple tasks (captioning, VQA, detection, grounding, and OCR) and employs VisionLLMv2 technology to enable various output formats including images, bounding boxes, and masks. This comprehensive approach allows the model to handle hundreds of visionlanguage tasks while maintaining expert-level performance.

# **Closed-Source Large vision-language models:**

GLM4-V is a large-scale multimodal language model developed by ZhiPu, featuring outstanding visual understanding and language generation capabilities. It employs a unified pre-training framework, capable of handling multiple modalities such as text, images, and audio. GLM4-V demonstrates strong performance in tasks like visual question answering, image description, and cross-modal reasoning, and can quickly adapt to new scenarios through fewshot learning. The model supports both Chinese and English, excelling in multilingual understanding and generation.

Claude 3.5 Sonnect is a next-generation multimodal assistant developed by Anthropic, exhibiting exceptional performance in both visual and language understanding. It utilizes an innovative neural network architecture that allows for deep comprehension of image content and complex reasoning. The model has strict controls in terms of safety and ethics, capable of identifying and filtering inappropriate content. A notable feature is its strong contextual understanding and coherent conversational abilities.

GPT-4 is the latest large language model developed by OpenAI, possessing powerful multimodal understanding and generation capabilities. It can process image and text inputs and perform complex reasoning and knowledge integration. This model showcases remarkable few-shot learning abilities, quickly mastering new tasks with only a few examples. GPT-4 also excels in creativity, generating highquality text, code, and other creative content.

#### Other Large vision-language models:

BLIP2 [13], Llava 1.5 [17], and CogVLM [42], despite their strong performance in general vision-language tasks, showed limitations in diagram-specific question generation, possibly due to insufficient training on diagram-focused datasets.

#### C. More details on DiagramQG

The DiagramQG dataset is a comprehensive collection of questions covering 4 subjects, 15 courses, and 169 concepts, consisting of 19,077 unique questions and 8,372 diagrams. These components form 44,074 combinations of (target & concept text constraint, diagram, question). This dataset aims to encourage models to generate questions that assess students' conceptual understanding by leveraging the provided target & concept text constraints and diagrams, as shown in Figure 2. Accomplishing this task requires two key capabilities from computational models. First, they must demonstrate sophisticated visual comprehension abilities. Second, they need comprehensive domain knowledge across multiple academic disciplines. Following established methodological practices in machine learning, we implemented a stratified partitioning of the dataset, allocating 70% for training, 10% for validation, and 20% for testing purposes. The comprehensive statistical distribution across these partitions, along with the aggregate dataset metrics, is presented in Table 6.

# D. More experimental details on other VQG datasets

We evaluated our baseline model's generalizability in visual question generation on two datasets of natural images, namely VQG-COCO and K-VQG.

VQG-COCO contains 2,500 training images and 1,250







Figure 10. Three different cases (Diagram Interpretation Bias) in DiagramQG dataset.

Method	BLEU-1	METEOR	CIDEr
MDN [30]	36.0	23.4	0.51
MC-BMN [29]	40.7	22.6	0.50
ConVQG [25]	50.2	26.4	0.56
HKI-DQG $_B$	55.3	43.4	0.74
HKI-DQG $_{O}^{-}$	58.1	46.3	1.06

Table 7. Results on VQG-COCO, using captions as text constraint. We report BLEU-1 instead of BLEU-4 to be consistent with the comparison methods.

Method	BLEU-4	METEOR	CIDEr
IM-VQG [11]	11.44	17.07	0.26
K-VQG [34]	18.84	22.79	1.31
ConVQG [25]	20.01	22.66	1.53
HKI-DQG <sub>B</sub>	55.49	48.89	4.81
HKI-DQG <sub><math>Q</math></sub>	62.69	52.42	5.48

Table 8. Results on the K-VQG dataset. The results of IM-VQG are reproduced based on the official code.

validation and test images each, designed for generating natural image-based questions. Each image is accompanied by five natural questions and five ground truth captions. Unlike other datasets, answers are not always provided.

K-VQG is a knowledge-aware VQG dataset that

uniquely combines visual content with structured knowledge triplets. It is a large-scale, human-annotated dataset containing around 13,000 images, 16,000 question-answer pairs, and 6,000 knowledge triplets. Each sample consists of an image, a question, an answer, and a knowledge triplet. K-VQG allows the use of both answers or knowledge triplets as text constraints.

Our proposed HKI-DQG consistently achieves substantial improvements over previous state-of-the-art methods across both VQG-COCO and K-VQG datasets, as shown in Table 7 and 8. These results demonstrate the strong generalization capability of our approach and prove that using a more advanced vision-language model as a foundation can significantly enhance performance in visual question generation tasks.

#### E. More case studies on Diagram

Addressing the three bottlenecks in DQG task previously mentioned, **Text Constraint Lost**, **Diagram Interpretation Bias**, and **Concept Ambiguity**, we present additional reference cases in Figures 9, 10, and 11.

In the first case (Text Constraint Lost), as shown in Figure 9, the generated questions fail to incorporate the target text, leading to inconsistent question generation. Regarding



Figure 11. Three different cases (Concept Ambiguity) in DiagramQG dataset.



bladder.

Figure 12. Three different cases in DiagramQG dataset.

the cause of this issue, we hypothesize that the model's in-

struction processing capabilities are not fully refined, result-

In the second case (Diagram Interpretation Bias), as

ing in the loss of target text during the generation process.

shown in Figure 10, while the generated questions assess students' concept comprehension to some extent, they show simplified concept application compared to ground truth questions, indicating room for improvement. In response to this issue, we visualize the selected relevant background knowledge during the question generation process, as shown in Figure 10. It can be observed that these background knowledge entries do not contain any content related to the text "filter blood," making it difficult for the model to generate questions related to this concept.

In the third case (Concept Ambiguity), as shown in Figure 11, the generated questions fail to reflect concept-related content, merely providing simple extensions of the target text. Similarly, for this issue, we visualize the selected relevant background knowledge during the question generation process, as shown in Figure 13. The questions generated in this case demonstrate basic concept awareness but fail to interact with the specific details presented in the background knowledge. This indicates that the model tends to adopt generic question patterns, lacking sufficient in-depth analysis of the specific content within the diagram, which may be related to the long-tail phenomenon present in the training samples.