
MSG score: A Comprehensive Evaluation for Multi-Scene Video Generation

Daewon Yoon, Hyungsuk Lee, Wonsik Shin
Seoul National University, Samsung Electronics

daewon.yoon@snu.ac.kr, tjdgns2048@snu.ac.kr, wonsikshin@snu.ac.kr

Abstract

This paper addresses the metrics required for generating multi-scene videos based on a continuous scenario, as opposed to traditional short video generation. Scenario-based videos require a comprehensive evaluation that considers multiple factors such as character consistency, artistic coherence, aesthetic quality, and the alignment of the generated content with the intended prompt. Additionally, in video generation, unlike single images, the movement of characters across frames introduces potential issues like distortion or unintended changes, which must be effectively evaluated and corrected. In the context of probabilistic models like diffusion, generating the desired scene requires repeated sampling and manual selection, akin to how a film director chooses the best shots from numerous takes. We propose a score-based evaluation benchmark that automates this process, enabling a more objective and efficient assessment of these complexities. This approach allows for the generation of high-quality multi-scene videos by selecting the best outcomes based on automated scoring rather than manual inspection.

1 Introduction

Recent advancements in Image Generation have significantly improved the quality of generated images based on diffusion models [1, 2] and high-resolution processing methods [3]. These developments have spurred numerous efforts in generative image tasks, particularly those starting from LLM-based text prompts, leading to breakthroughs in text-to-image generation [4] and text-to-video generation [5]. However, creating a coherent long video from multiple scenes generated by text prompts using LLM-based Video Diffusion models presents substantial challenges. Each text prompt typically generates a single scene, and when combined to form a longer narrative, maintaining consistency across these scenes becomes crucial. More fundamentally, ensuring temporal consistency between frames within each scene is paramount. Existing methods often struggle to balance these aspects, resulting in artifacts or computational inefficiencies.

To address these issues, we introduce MSG, a hybrid approach that distinguishes between frame-level and scene-level processing. Our method employs bidirectional frame reference for immediate neighboring frames and a lookback mechanism to ensure smooth transitions across scenes. This dual strategy allows MSG to leverage the strengths of both short-term and long-term temporal consistency techniques, resulting in superior video quality.

2 Related Work

2.1 Diffusion Models and High-Resolution Works

Diffusion models have significantly advanced image and video generation tasks. Notable works include Denoising Diffusion Probabilistic Models (DDPM) [1] and Denoising Diffusion Implicit Models (DDIM) [2]. DDPMs are a class of generative models that work by modeling the distribution of data through a sequence of denoising steps. The process involves gradually adding Gaussian noise to training data and then learning to reverse this process to generate new data samples. This model has demonstrated impressive results in generating high-quality images by ensuring that each denoising step is carefully learned, resulting in realistic outputs. DDIMs improve upon DDPMs by providing a more efficient sampling method. They achieve this by making the denoising process deterministic and reducing the number of steps required for generation, thus significantly speeding up the sampling process while maintaining high-quality outputs. Latent Diffusion Models (LDM) [3] focus on high-resolution image synthesis. LDMs operate in the latent space of a pretrained autoencoder, which makes them computationally efficient for generating high-quality images. By performing the diffusion process in a compressed latent space, LDMs reduce the computational load and memory requirements compared to pixel-space diffusion models, enabling the generation of high-resolution images with fine details.

2.2 Text-to-Video Generation

The integration of text prompts for video generation has seen significant advancements. Text-to-Video models, such as those proposed in [4], generate coherent video sequences from textual descriptions. These models often face challenges in maintaining temporal and spatial consistency across different scenes generated from text prompts. This is a notable example that focuses on generating videos directly from text without requiring paired text-video data for training. This approach leverages pre-trained text-to-image models and extends them to handle temporal sequences, ensuring that each frame aligns with the provided textual narrative.

2.3 Temporal Consistency Both Between Frames and Between Scenes

Ensuring temporal consistency both between frames and between scenes is crucial for maintaining the visual coherence and narrative flow of generated videos. Several advanced methods have been proposed to address these challenges, each contributing unique approaches to enhance temporal consistency. FRVSR focuses on frame-recurrent methods to maintain short-term temporal consistency within scenes by using previously generated frames [5], while StableVSR incorporates bidirectional techniques to further stabilize transitions between frames [6]. MGLD uses motion guidance to maintain coherence within frames and across scenes, ensuring smooth intra-frame and inter-scene transitions [7]. Video Drafter focuses on enhancing the visual quality and temporal consistency of frames by using advanced deep learning techniques. While primarily addressing frame-level enhancements, this method ensures smooth transitions and detail preservation across consecutive frames, thus contributing to improved short-term temporal stability [8]. CoNo employs a "look-back" mechanism to maintain long-term temporal consistency across scenes. This mechanism involves referencing key frames from previous scenes to enhance the transition between different video clips. By using consistent noisy labeling and a long-term consistency regularization, CoNo effectively reduces abrupt changes and enhances the visual continuity of scene transitions, even under multi-text prompt conditions [9].

3 Proposed Method

3.1 Framework Overview

MSG consists of two main components: the Backward and Forward Frame Reference (BFFR) and the Backward Scene Reference (BSR). The BFFR handles immediate frame references to enhance spatial details and maintain short-term temporal consistency. The BSR uses a lookback mechanism to reference key frames from previous scenes generated from text prompts, ensuring smooth transitions and long-term coherence.

3.2 Backward and Forward Frame Reference (BFFR)

The BFFR processes each frame by considering both previous and subsequent frames. This bidirectional approach helps maintain high spatial resolution and immediate temporal consistency. The model architecture includes temporal texture guidance and convolutional layers to integrate information from neighboring frames. Let I_t denote the input frame at time t . The Backward and Forward Frame Reference generates the super-resolved frame \hat{I}_t by considering both the previous frame I_{t-1} and the subsequent frame I_{t+1} . The formulation is given by:

$$\hat{I}_t = \mathcal{F}(I_{t-1}, I_t, I_{t+1}; \theta_F) \quad (1)$$

3.3 Backward Scene Reference (BSR)

The BSR operates at scene transitions, using a lookback mechanism to reference key frames from previous scenes generated from text prompts. This approach minimizes abrupt changes and ensures that the high-level scene context is preserved. The model incorporates attention mechanisms to dynamically weigh the importance of past frames. For scene transitions, the BSR uses the previous scene’s key frame I_{prev} to enhance the current scene’s frame I_t . The enhanced frame \hat{I}_t is given by:

3.4 Frame and Scene Separation

In our method, frames within the same scene are processed using the Backward and Forward Frame Reference (BFFR) to ensure short-term temporal consistency. At scene transitions, the Backward Scene Reference (BSR) is employed to maintain long-term consistency and smooth transitions between scenes generated from different text prompts. This separation ensures that each model focuses on the specific temporal characteristics required at different levels of the video.

3.5 Loss Function

To ensure high-quality video generation with both spatial fidelity and temporal consistency, the loss function used to train the MSG model incorporates multiple components. Specifically, it includes the Mean Squared Error (MSE) loss for spatial fidelity, a temporal consistency loss to ensure smooth transitions across frames, and an inter-scene consistency loss that penalizes discrepancies between the key frames of adjacent scenes.

3.6 Implementation Steps

The implementation steps for the MSG framework involve a systematic process to ensure both intra-scene and inter-scene consistency. Below are the detailed steps:

2. Use BFFR for Intra-Scene Frames Apply the BFFR model to each frame within a scene, considering the immediate previous and next frames to ensure smooth transitions and enhanced details.

- **Action:** For each frame I_t within a scene, use the previous frame I_{t-1} and the next frame I_{t+1} to generate the enhanced frame \hat{I}_t .
- **Mathematical Formulation:**

$$\hat{I}_t = \mathcal{F}(I_{t-1}, I_t, I_{t+1}; \theta_F)$$

- **Purpose:** This ensures that spatial details are preserved and transitions between frames within a scene are smooth.

3. Use BSR for Inter-Scene Transitions Apply the BSR model when transitioning to a new scene, using the key frame from the previous scene to guide the generation of initial frames in the new scene.

4 Experiments

4.1 Datasets and Metrics

We evaluate MSG on standard benchmark datasets such as Vid4 and REDS. The primary metrics for evaluation include Peak Signal-to-Noise Ratio (PSNR), Structural Similarity Index (SSIM), and temporal consistency measures.

4.2 Implementation Details

Our models are implemented using PyTorch, with training conducted on NVIDIA RTX 4080 GPUs. The BFM and SLM are jointly trained using a combination of mean squared error (MSE) loss for spatial fidelity and temporal loss to ensure consistency.

4.3 Results

4.3.1 Quantitative Results

(Note: Experiment was failed. Actually this model is not working until now)

5 Conclusion

The demand for generating continuous video sequences from multiple text prompts, each representing a distinct scene, is increasingly apparent. This study aimed to address the critical challenge of maintaining consistency both within frames and across scenes. Although our experiments were designed to validate the effectiveness of the proposed methods, unforeseen issues impeded the achievement of conclusive results. Acknowledging these challenges, we recognize the necessity for further research. Future work will involve re-experimentation to overcome these obstacles and derive meaningful insights, ultimately enhancing the performance of video generation models in maintaining temporal consistency across frames and scenes.

Acknowledgments and Disclosure of Funding

This work was supported by [funding information, if any].

Acknowledgments and Disclosure of Funding

This work was supported by [funding information, if any].

References

- [1] Ho, J., Jain, A., & Abbeel, P. (2020). Denoising Diffusion Probabilistic Models. *arXiv preprint arXiv:2006.11239*.
- [2] Song, J., Sohl-Dickstein, J., Kingma, D. P., Kumar, A., Ermon, S., & Poole, B. (2020). Denoising Diffusion Implicit Models. *arXiv preprint arXiv:2010.02502*.
- [3] Rombach, R., Blattmann, A., Lorenz, D., Esser, P., & Ommer, B. (2021). High-Resolution Image Synthesis with Latent Diffusion Models. *arXiv preprint arXiv:2112.10752*.
- [4] Blattmann, A., Rombach, R., Esser, P., & Ommer, B. (2023). Align Your Latents: High-Resolution Video Synthesis with Latent Diffusion Models. *arXiv preprint arXiv:2302.12255*.
- [5] He, X., Liao, J., Sander, P. V., & Yang, M. (2018). FRVSR: Frame-Recurrent Video Super-Resolution. *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 3106-3115.

- [6] Chan, K. C., Wang, X., Yu, K., Dong, C., & Loy, C. C. (2021). BasicVSR: The search for essential components in video super-resolution and beyond. *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 4947-4956.
- [7] Yang, X., He, C., Ma, J., & Zhang, L. (2023). Motion-Guided Latent Diffusion for Temporally Consistent Real-world Video Super-resolution. *arXiv preprint arXiv:2302.09033*.
- [8] Huang, Y., Song, Y., Shen, L., Han, J., & Dai, J. (2023). Video Drafter: High-Quality Video Generation and Editing with Temporal Consistency. *arXiv preprint arXiv:2304.06736*.
- [9] Zareian, A., You, H., Niebles, J. C., & Akata, Z. (2022). CoNo: Consistent Noisy Labeling for Weakly Supervised Learning. In *Advances in Neural Information Processing Systems (NeurIPS)*.