Online Experimental Design With Estimation-Regret Trade-off Under Network Interference

Zhiheng Zhang[∗]

zhiheng-20@mails.tsinghua.edu.cn

Institute for Interdisciplinary Information Sciences, Tsinghua University

Zichen Wang[∗]

zichenw6@illinois.edu

Coordinate Science Laboratory & Computer Engineering, University of Illinois Urbana-Champaign

Abstract

Network interference has garnered significant interest in the field of causal inference. It reflects diverse sociological behaviors, wherein the treatment assigned to one individual within a network may influence the outcome of other individuals, such as their neighbors. To estimate the causal effect, one classical way is to randomly assign experimental candidates into different groups and compare their differences. However, in the context of sequential experiments, such treatment assignment may result in a large regret. In this paper, we develop a unified interference-based online experimental design framework. Compared to existing literature, we expand the definition of arm space by leveraging the statistical concept of exposure mapping. Importantly, we establish the Pareto-optimal trade-off between the estimation accuracy and regret with respect to both time period and arm space, which remains superior to the baseline even in the absence of network interference. We further propose an algorithmic implementation and model generalization.

Keywords: Multi-armed bandit; Causal inference; Network interference; Experimental design; Pareto trade-off; Exposure mapping

1. Introduction

Network interference has received significant attention in both the fields of causal inference [\(Leung,](#page-14-0) [2022a](#page-14-0)[,b,](#page-14-1) [2023\)](#page-14-2) and statistical learning theory [\(Agarwal et al.,](#page-12-0) [2024;](#page-12-0) [Jia et al.,](#page-14-3) [2024\)](#page-14-3). Unlike the SUTVA assumption [\(Imbens,](#page-14-4) [2024\)](#page-14-4), network interference considers a more general scenario where the treatment received by one individual may influence the outcomes of others. Network interference model has been widely used in economics [\(Arpino](#page-12-1) [and Mattei,](#page-12-1) [2016;](#page-12-1) [Munro et al.,](#page-15-0) [2021\)](#page-15-0) social sciences [\(Bandiera et al.,](#page-12-2) [2009;](#page-12-2) [Bond et al.,](#page-12-3) [2012;](#page-12-3) [Paluck et al.,](#page-15-1) [2016;](#page-15-1) [Imbens,](#page-14-4) [2024\)](#page-14-4).

To successfully identify causal effect under network interference, one straightforward way is to conduct randomized experiments and use difference in means type estimators to estimate causal effect based on the experimental data [\(Leung,](#page-14-0) [2022a,](#page-14-0) [b,](#page-14-1) [2023;](#page-14-2) [Gao and](#page-13-0) [Ding,](#page-13-0) [2023\)](#page-13-0). Such design is related to many applications [\(Ciotti et al.,](#page-13-1) [2020;](#page-13-1) [Cai et al.,](#page-12-4) [2015\)](#page-12-4). For instance, [Ciotti et al.](#page-13-1) [\(2020\)](#page-13-1) suggested the randomized experiment on a group of volunteering patients to investigate the therapeutic average treatment effects of various

^{*.} These authors contributed equally to this work. This is the first version of this preliminary draft submitted by Zhiheng Zhang (correspondence email: zhiheng-20@mails.tsinghua.edu.cn). We sincerely welcome all kinds of suggestions.

Zhang∗ Wang∗

drugs for influenza, e.g., Covid-19, where each individual's status of cure is influenced by the treatment assignment of their neighboring individuals. In practice, an experiment may consist of multiple rounds, and researchers may wish to use the experimental data from the previous rounds to enhance the social welfare of the experimental participants by minimizing the regret of the future rounds [\(Mok et al.,](#page-15-2) [2021\)](#page-15-2). This requires us to consider the tradeoff between the estimation accuracy of the causal effect and the cumulative regret of the experiment. Apparently, such an online experiment represents a more complex design than offline. For example, if experimental designers directly borrow the Bernoulli sampling in offline design [\(Leung,](#page-14-0) $2022a$), they may result in a large regret. This motivates us to design a sequential policy that theoretically guarantees the optimal trade-off between the two objectives under interference. Besides, such sequential policy is also relevant to interferencebased Multi-Armed Bandit (MAB) literature [\(Jia et al.,](#page-14-3) [2024;](#page-14-3) [Agarwal et al.,](#page-12-0) [2024\)](#page-12-0), which focuses primarily on minimizing regret rather than improving estimation accuracy.

It is important to note that the estimation efficiency and regret cannot be optimized simultaneously, which is why we need to consider the "trade-off" between the two objectives. Specifically, the optimal estimation efficiency typically requires the sampling probability of each arm to be strictly greater than zero, which may result in a large regret; on the contrary, optimal algorithms (e.g., Upper Confidence Bound (UCB) [\(Auer et al.,](#page-12-5) [2002\)](#page-12-5) and its variants) that implement the probability-vanishing exploration strategy for sub-optimal arms might violate the overlap assumption in causal inference $(D'Amountet al., 2021)$ $(D'Amountet al., 2021)$, thereby compromising the precision of the estimator.

Existing works that consider estimation-regret trade-off typically assume the interference does not exist, or equivalently that there is only one individual throughout the experiment. Examples include empirical algorithm design [\(Liang and Bojinov,](#page-15-3) [2023\)](#page-15-3), theoretical biobjective optimization [\(Simchi-Levi and Wang,](#page-15-4) [2024\)](#page-15-4), and the relationship between tradeoff and exogenous model assumptions [\(Duan et al.,](#page-13-3) [2024\)](#page-13-3). In this paper, we further consider such trade-off in the context of network interference. In particular, we are interested in a unified online interference-based experimental design setting, which we refer to as MAB under Network interference (MAB-N). This setting generalizes the definition of arm space in MAB literature via taking advantage of a statistical concept called exposure mapping [\(Le](#page-14-0)[ung,](#page-14-0) [2022a;](#page-14-0) [Aronow and Samii,](#page-12-6) [2017\)](#page-12-6). We derive the theoretical optimal estimation-regret trade-off under this setting and provide an algorithmic implementation that can achieve this optimal trade-off. Our contributions are summarized as follows:

- We establish a unified setting for online experimental design with network interference called MAB-N take advantage of exposure mapping in statistics.
- We bridge the multi-objective minimax trade-off, so-called Pareto-optimal, between the treatment effect estimation and the regret efficiency under network interference. We also propose the criteria for an MAB algorithm to be Pareto-optimal.
- We propose the UCB-Two Stage-Network (UCB-TSN) algorithm to match the above Pareto trade-off via constructing the upper bound both for the ATE estimation error and regret. Our UCB-TSN outperforms [Simchi-Levi and Wang](#page-15-4) [\(2024\)](#page-15-4) in (i) degenerated single-unit case without interference; and (ii) extended adversarial bandit setting.

Our paper is organized as follows. Section [2](#page-2-0) introduces our general MAB-N setting and introduce the Pareto-optimality to illustrate the estimation-regret trade-off. Section [3](#page-6-0) provides a general lower bound when we simultaneously consider the joint performance of regret and estimation, and then extract the if and only if condition for any algorithm to satisfy the above Pareto-optimality. Section [4](#page-8-0) propose the Pareto-optimal algorithmic implementation and comparison with the baseline. Section [5](#page-9-0) extend MAB-N to the adversarial cases. Finally, Section [6](#page-11-0) concludes the paper with further discussion.

2. Framework

2.1. Basic MAB setting under network interference

We introduce our setting following [Agarwal et al.](#page-12-0) [\(2024\)](#page-12-0), which is generalized from [Auer](#page-12-5) [et al.](#page-12-5) [\(2002\)](#page-12-5); [Simchi-Levi and Wang](#page-15-4) [\(2024\)](#page-15-4) to the network interference. We focus on a multi-arm stochastic bandit problem involving a K-armed set $\mathcal{K} = \{k\}_{k \in [K]}$, an N-unit set $\mathcal{U} = \{i\}_{i \in [N]}$, and the time period $t \in [T]$. The adjacent matrix among these units is defined as $\mathbb{H} := \{h_{ij}\}_{i,j\in[N]}^{-1}$ $\mathbb{H} := \{h_{ij}\}_{i,j\in[N]}^{-1}$ $\mathbb{H} := \{h_{ij}\}_{i,j\in[N]}^{-1}$. K, N, H are pre-fixed. In each round, we consider the interference among units. The *original super arm* is an N-dimension vector $A_t := (a_{1,t},...,a_{N,t}) \in \mathcal{K}^{\mathcal{U}}$. To bridge it to the domain of causal inference, we start by notating the so-called potential outcome in statistics [\(Rubin,](#page-15-5) [2005\)](#page-15-5) as $\{Y_i(A_t)\}_{i\in[N]} = \{Y_i(a_{1,t}, a_{2,t}, ... a_{N,t})\}_{i\in[N]}$ for unit i in time t^2 t^2 . Without loss of generalization, we set $\forall i \in \mathcal{U}, A \in \mathcal{K}^{\mathcal{U}}, Y_i(A) \in [0,1]$. In this sense, the *single-unit reward* of unit i upon time t is given by $r_{i,t}(A_t) = Y_i(A_t) + \eta_{i,t}$, where $r_{i,t}(.)$ represents the reward function of unit $i \in [N]$, and $\eta_{i,t}$ is zero-mean i.i.d. 1sub Gaussian noise for each unit. Finally, we define instance ν as any legitimate choice of ${D(Y_i(A))}_{i\in\mathcal{U},A\in\mathcal{K}^U}$, where $D(Y_i(A))$ denotes the reward distribution of unit i if super arm A is pulled; and then set \mathcal{E}_0 as the set of all kinds of feasible ν .

Our primary interest is designing a learning policy $\pi := (\pi_1, ..., \pi_T)$. In round t, we observe the history $\mathcal{H}_{t-1} = \{A_1, \{r_{i,1}(A_1)\}_{i \in [N]}, ..., A_{t-1}, \{r_{i,t-1}(A_{t-1})\}_{i \in [N]}\},\$ where each term is an N-dimensional vector. π_t is a probabilistic map from \mathcal{H}_{t-1} to the next action A_t. We denote it as $\pi_t(A) = \mathbb{P}_{\pi}(A_t = A | \mathcal{H}_{t-1})$ indicating the probability that a super arm Z is selected in round t .

Additional notation We introduce simplified notation for ease of exposition. We write $[Q] := \{1, 2, \ldots Q\}$ for any $Q \in \mathbb{N}^+$. We define $a \vee b := \max\{a, b\}$ and $a \wedge b := \min\{a, b\}$. For sequences of all positive numbers $\{a_n\}_{n\in\mathbb{N}^+}$ and $\{b_n\}_{n\in\mathbb{N}^+}$, we denote $a_n = O(b_n)$ if $\exists C > 0$, such that $\forall n, a_n \leq C b_n$; to the contrary, we denote $a_n = \Omega(b_n)$ if $\exists C > 0$, such that $\forall n, a_n \geq Cb_n$. Moreover, we denote $a_n = \Theta(b_n)$ if $a_n = O(b_n)$ and $a_n = \Omega(b_n)$ both hold. We also denote $a_n = \tilde{O}(b_n)$ if $\exists C > 0, k \in \mathbb{N}^+ \cup \{0\}$, such that $a_n \leq C b_n (log(b_n))^k$.

^{1.} It does not mean we must get all information about H; instead, it depends on our detailed design.

^{2.} Unit i's potential outcome is only related to the treatments of the total population via a fixed function. It is a commonly adopted notation in interference-based causality [\(Leung,](#page-14-0) [2022a,](#page-14-0)[b,](#page-14-1) [2023\)](#page-14-2) where the traditional "Stable Unit Treatment Values Assumption (SUTVA)" assumption [\(Rubin,](#page-15-6) [1980\)](#page-15-6) (one unit's outcome should not be affected by treatments upon other units) is violated.

2.2. The hardness of MAB under interference

Referring to the concept of cumulative regret in traditional MAB problems [\(Lattimore and](#page-14-5) Szepesvári, [2020\)](#page-14-5), the performance metric of policy π could be identified as

$$
\mathcal{R}_{\nu}^{naive}(T,\pi) := \frac{T}{N} \sum_{i \in \mathcal{U}} Y_i(A^*) - \mathbb{E}_{\pi} \left[\frac{1}{N} \sum_{t \in [T]} \sum_{i \in \mathcal{U}} r_{i,t}(A_t) \right], \ A^* := \arg \max_{A \in \mathcal{K}^{\mathcal{U}}} \frac{1}{N} \sum_{i \in \mathcal{U}} Y_i(A). \tag{1}
$$

Foreseeably, a severe unavoidable challenge is the exponential action space of the original super arm (K^N) . In this sense, we first construct a negative result to illustrate that directly pursue the optimal π adopting the original super arm is "impractical".

Proposition 1 Given a priori N, K, \mathbb{H} . For any policy π , there exists a hard instance $\nu \in \mathcal{E}_0$ such that $\mathcal{R}_{\nu}^{naive}(T,\pi) = \Omega\left(\frac{1}{\sqrt{\lambda}}\right)$ $\frac{1}{\overline{N}}(T\wedge\sqrt{K^NT})\big).$

Proposition [1](#page-3-0) indicates that the regret convergence rate is dominated by the relative size between time period and arm space, and thus exhibits as a two-piece function: when $T \leq$ K^N under interference, regret $\mathcal{R}_{\nu}^{naive}(T,\pi)$ grows linearly with T; to the contrary, when $T \geq K^N$, although it degenerates to a square root rate with respect to T, unfortunately, it is additionally harmed by an exponentially large parameter $\sqrt{K^N/N}$. Further, this also verifies why [Agarwal et al.](#page-12-0) [\(2024\)](#page-12-0) should additionally consider the interference only from first-order neighbors and introduce sparsity assumptions, otherwise it would not be possible to obtain a meaningful regret.

It manifests more insights upon the triple of concepts {time, regret, arm space} than traditional lower bound analysis in MAB (Lattimore and Szepesvári, [2020\)](#page-14-5). It is because researchers tends to preemptively judge that "time period \gg arm numbers", e.g., force $N = 1$ in the single-unit setting and then $T \gg K$ holds by default. However, this oversimplification consideration of arm space can be detrimental under the interference scenario. For instance, even we just choose $K = 2, N = 50$, any algorithm under interference-based MAB setting would potentially be cursed by an impractical regret. It motivates us to introduce new statistical tool to reduce the K^N action space to the low-dimensional space, which is the so-called *exposure mapping*, which will be illustrated as follows.

2.3. Our MAB-N

We introduce the concept of exposure mapping developed by [Leung](#page-14-0) [\(2022a\)](#page-14-0); [Aronow and](#page-12-6) [Samii](#page-12-6) [\(2017\)](#page-12-6). We define the pre-specified function mapping from original super arm space (K^N) to a d_s -cardinality discrete values $(d_s \ll K^N)$ taking advantage of the network structure. For clarity, we consider the discrete function case:

$$
s_{i,t} \equiv \mathbf{S}(i, A_t, \mathbb{H}), \text{ where } \mathbf{S}: \mathcal{U} \times \mathcal{K}^{\mathcal{U}} \times \mathbb{H} \to \mathcal{U}_s, |\mathcal{U}_s| = d_s.
$$
 (2)

Here \mathcal{U}_s is called as exposure arm set. We set $S_t = \{ \mathbf{S}(i, A_t, \mathbb{H}) \}_{i \in [N]} \equiv (s_{1,t}, ..., s_{N,t})$ as the exposure super arm, and then we can decompose the policy $\pi_t(\cdot)$ and define the exposurebased reward:

$$
\pi_t(A) \equiv \mathbb{P}(A_t = A | \mathcal{H}_{t-1}) = \mathbb{P}(A_t = A | S_t) \mathbb{P}(S_t | \mathcal{H}_{t-1}),
$$

\n
$$
[\tilde{Y}_i(S_t), \tilde{r}_i(S_t)]^\top := \sum_{A \in \mathcal{K}^U} [Y_i(A), r_i(A)]^\top \mathbb{P}(A_t = A | S_t),
$$
\n(3)

	Interference-based MAB Exposure mapping $(S(i, A_t, \mathbb{H}))$ Action space $(\mathcal{U}_{\mathcal{E}})$ Clusters		
Jia et al. (2024) Agarwal et al. (2024)	$\{0,1\} \subseteq \{\sum_i \frac{a_{i,t}}{N}\}\$ $a_{i,t}$	K^N	N
MAB-N	General $\mathbf{S}(i, A_t, \mathbb{H})$	$O(d_s ^C)$	C

Table 1: MAB-N surrogates the previous bandit under interference as special cases.

The second line of [\(3\)](#page-3-1) is a generalized notation of [Leung](#page-14-0) [\(2022a\)](#page-14-0). Noteworthy, here $\mathbb{P}(A_t =$ $A | S_t$ could be manually controlled, e.g., uniformly sampling^{[3](#page-4-0)}. In this sense, $\tilde{Y}_i(S_t)$ in Eq (3) is only correlated to the network topology $\mathbb H$. Analogously, we also define the exposure reward $\tilde{r}_i(S_t)^4$ $\tilde{r}_i(S_t)^4$. Then we could define the regret based on the exposure mapping.

Regret based on exposure mapping According to the action space reduction in Eq (3) , we provide a more general and realistic regret compared to [Jia et al.](#page-14-3) [\(2024\)](#page-14-3); [Simchi-Levi](#page-15-4) [and Wang](#page-15-4) [\(2024\)](#page-15-4); [Agarwal et al.](#page-12-0) [\(2024\)](#page-12-0) (refer to Example 1-4). We define the clustering set $\mathcal{C} := {\mathcal{C}_q}_{q \in [C]}, C = |\mathcal{C}|$ where $\forall i \neq j, i, j \in [C], \mathcal{C}_i \cap \mathcal{C}_j = \emptyset, \cup \{\mathcal{C}_q\}_{q \in [C]} = [N]$. For brevity, we denote $\mathcal{C}^{-1}(i)$ as the cluster of node i. We define the exposure-based regret:

$$
\mathcal{R}_{\nu}(T,\pi) = \frac{T}{N} \sum_{i \in \mathcal{U}} \tilde{Y}_i(S^*) - \frac{1}{N} \mathbb{E}_{\pi} \bigg[\sum_{t \in [T]} \sum_{i \in \mathcal{U}} \tilde{r}_i(S_t) \bigg], \ S^* = \underset{S \in \mathcal{U}_{\mathcal{E}}}{\arg \max} \sum_{i \in \mathcal{U}} \tilde{Y}_i(S), \tag{4}
$$

where $\mathcal{U}_{\mathcal{E}} := \mathcal{U}_{\mathcal{C}} \cap \mathcal{U}_{\mathcal{O}}$ with $\mathcal{U}_{\mathcal{C}} := \{ S_t : \forall i, j \in [N], \mathcal{C}^{-1}(i) = \mathcal{C}^{-1}(j) \text{ implies } S_t e_i = S_t e_j \}$ and $\mathcal{U}_{\mathcal{O}} := \big\{ \{\mathbf{S}(i, A, \mathbb{H})\}_{i \in \mathcal{U}} : A \in \mathcal{K}^{\mathcal{U}} \big\}.$ Here, $\mathcal{U}_{\mathcal{C}}$ denotes all kinds of cluster-wise switchback exposure super arm. For instance, if $\mathcal{U}_s \in \{0,1\}$, $N = 4$, $\mathcal{C}_1 = \{1,2\}$, $\mathcal{C}_2 = \{3,4\}$, then $\mathcal{U}_{\mathcal{C}} =$ $\{(k_1, k_1, k_2, k_2) : k_1, k_2 \in \{0, 1\}\}\.$ Moreover, $\mathcal{U}_{\mathcal{O}}$ is to make sure the S_t is compatible with the original arm set A_t . Hence, the exposure super arm space's cardinality is $|\mathcal{U}_{\mathcal{E}}| = O(|d_s|^C)$, serving as a trade-off between [Jia et al.](#page-14-3) [\(2024\)](#page-14-3) and [Agarwal et al.](#page-12-0) [\(2024\)](#page-12-0)(Table [1\)](#page-4-2). Regret in [\(4\)](#page-4-3) is generic and flexible^{[5](#page-4-4)}, since the choice of any pre-fixed C and exposure mapping $\mathbf{S}(\cdot)$ depends on practitioner's interests, which will be shown in Examples 1-4.

Remark 2 We treat the exposure action space $\mathcal{U}_{\mathcal{E}}$ induced by $\{S(i, Z, \mathbb{H})\}_{i \in \mathcal{U}}$ as pre-fixed. In the following text, our regret analysis mainly focuses on the individual arm space K and the time horizon T, and then omits the pre-fixed N. Here K is included in $\mathcal{U}_{\mathcal{E}}$.

We consider the case where T is relatively large with pre-specified $\mathcal{U}_{\mathcal{E}}$. We formalize it in Condition [1,](#page-4-5) which is satisfied in previous literature [\(Simchi-Levi and Wang,](#page-15-4) [2024;](#page-15-4) [Jia](#page-14-3) [et al.,](#page-14-3) [2024;](#page-14-3) [Agarwal et al.,](#page-12-0) [2024\)](#page-12-0).

3. $\mathbb{P}_{\pi}(A_t = Z \mid S_t) = \sum_{Z} \delta\{Z : \{S(i, Z, \mathbb{H})\}_{i \in [N]} = S_t\}/[\{Z : \{S(i, Z, \mathbb{H})\}_{i \in [N]} = S_t\}],$ where $\delta(\cdot)$ is an indicator function.

^{4.} It should be mentioned that the difference between the $\tilde{Y}_i(S_t)$ and the reward of S_t which practitioners actually collect are accommodated with two kinds of noise: (i) sampling noise, where practitioners sample legitimate $r_i(A_t)$ to approximate $\tilde{r}_i(S_t)$ via Eq [\(3\)](#page-3-1), and (ii) endogenous noise, inheriting from the original noise in the original arm $r_i(A_t)$, i.e., $\eta_{i,t}$.

^{5.} Since the curse of oversized action space in the interference-based online learning is unavoidable, we could arbitrarily manually control $|\mathcal{U}_{\mathcal{E}}|$ to balance the sacrifice of original arm information, and the bless of regret efficiency improvement.

Condition 1 $2 \leq |\mathcal{U}_{\mathcal{E}}| \leq T$.

Condition [1](#page-4-5) is inherently verifiable and adjustable. Regardless of any pre-fixed \mathbb{H} , we could manually design legitimate [\(2\)](#page-3-2) to fit Condition [1.](#page-4-5) It is the weakest condition to date, as compared to the above previous work as follows. For better comprehension, we present Examples 1-4.

Example 1 Traditional MAB literature [\(Auer et al.,](#page-12-5) [2002\)](#page-12-5) considered the case $N = 1$, *i.e.*, single unit without network, and $S(1, A, \mathbb{H}) := A$ with action space K.

Moreover, current interference-based MAB literature [\(Agarwal et al.,](#page-12-0) [2024;](#page-12-0) [Jia et al.,](#page-14-3) [2024\)](#page-14-3) are both included as our special instances:

Example 2 [Agarwal et al.](#page-12-0) [\(2024\)](#page-12-0) chooses $S(i, A_t, \mathbb{H}) := a_{i,t}$. On the other hand, [Jia et al.](#page-14-3) [\(2024\)](#page-14-3) chooses $K = 2, a_{i,t} \in \{0,1\}, \forall i \in [N], S(i, A_t, \mathbb{H}) := \sum_{i \in \mathcal{U}} a_{i,t}/N$, which denotes the global proportion of treatment in each time t. They only consider the fixed best arm $S_t \in \{0,1\} \subseteq \{0,1/N,2/N,...1\}$. They both satisfy $S^* \in \mathcal{U}_{\mathcal{C}} \subseteq \mathcal{U}_{\mathcal{O}}$.

Additionally, we mention that the general exposure mapping is derived from the offline setting and illustrate its extension to the online setting is essential.

Example 3 Suppose $\forall j \in \mathcal{U}, \sum_j h_{ij} > 0, \mathcal{K} \in \{0,1\}.$ We can choose $S(i, A_t, \mathbb{H}) :=$ $\mathbf{1}(\sum_j h_{ij}a_{j,t}/\sum_j h_{ij}\in [0,\frac{1}{2}$ $\frac{1}{2})$) inspired from the literature of offline estimation [\(Leung,](#page-14-0) [2022a;](#page-14-0) [Gao and Ding,](#page-13-0) [2023\)](#page-13-0) . Its objective is to explore the influence of the treatment assignment proportion among all neighborhoods of each unit, which is still under-explored in the online learning scenario.

For a supplement, we point out that the clustering strategy could also be traced back to the offline setting [\(Viviano et al.,](#page-16-0) [2023\)](#page-16-0), which is also our special case:

Example 4 [Viviano et al.](#page-16-0) [\(2023\)](#page-16-0); [Zhang and Imai](#page-16-1) [\(2023\)](#page-16-1) considered the clustering-based setting $S(i, A_t, \mathbb{H}) := \sum_{j \in \mathcal{C}^{-1}(i)} a_{j,t} / |\mathcal{C}^{-1}(i)|$, in which only considers the subset case of the super arm $\{0,1\}^{\mathcal{C}}$. Specifically, [Viviano et al.](#page-16-0) [\(2023\)](#page-16-0) restricts the policy that each cluster selects a simultaneous arm under the same Bernoulli design, while [Zhang and Imai](#page-16-1) [\(2023\)](#page-16-1) further assumes that the interference only occurs within clusters instead of across clusters. They both have $S^* \in \mathcal{U}_{\mathcal{C}} = \mathcal{U}_{\mathcal{O}}$.

After preparation, we establish the trade-off formulation.

2.4. Trade-off goal

We introduce the goal of the trade-off between the regret efficiency and statistical power of reward gap estimation. Average treatment effect (ATE) between exposure super arm S_i and S_i is defined as the reward gap:

$$
\Delta^{(i,j)} := \frac{1}{N} \sum_{i' \in \mathcal{U}} \left(\tilde{Y}_{i'}(S_i) - \tilde{Y}_{i'}(S_j) \right), \text{where } S_i, S_j \in \mathcal{U}_{\mathcal{E}}.
$$
\n
$$
(5)
$$

It is a generalized definition compared with the most relevant literature [\(Jia et al.,](#page-14-3) [2024;](#page-14-3) [Agarwal et al.,](#page-12-0) [2024;](#page-12-0) [Simchi-Levi and Wang,](#page-15-4) [2024\)](#page-15-4) when considering ATE^{[6](#page-6-1)}. We use $\hat{\Delta}^{(i,j)}$:= $\{\hat{\Delta}_{t}^{(i,j)}% (\hat{\Delta}_{t}^{(i,j)}(\hat{\alpha},j))\}_{i=1}^{N_{\text{max}}(\hat{\alpha},j)}$ $\{\hat{t}^{(i,j)}_t\}_{t\geq 1}, \hat{\Delta} := {\{\hat{\Delta}^{(i,j)}\}_{S_i,S_j\in\mathcal{U}_{\mathcal{E}}}}$ to identify a sequence of adaptive admissible estimates of $\Delta^{(i,j)}$. The total design of an MAB experiment could be represented by the vector $\{\pi, \hat{\Delta}\}.$ Our final goal is to explore the trade-off:

$$
\min_{\{\pi,\hat{\Delta}\}} \max_{\nu \in \mathcal{E}_0} \left(\mathcal{R}_{\nu}(T,\pi), e_{\nu}(T,\hat{\Delta}) \right), \text{ where } e_{\nu}(T,\hat{\Delta}) := \max_{S_i, S_j \in \mathcal{U}_{\mathcal{E}}} \mathbb{E}[|\Delta^{(i,j)} - \hat{\Delta}_T^{(i,j)}|]. \tag{6}
$$

Given any feasible ν , $\mathcal{R}_{\nu}(T,\pi)$ is associated with π , while $e_{\nu}(T,\hat{\Delta})$ is associated with $\hat{\Delta}$. Due to the complicated relation between π and $\hat{\Delta}$ w.r.t. the history \mathcal{H}_t , $t \in [T]$, especially in the network interference setting, this multi-objective optimization is quite challenging. To portray the best solution $\{\pi, \tilde{\Delta}\}\$ in [\(6\)](#page-6-2), we first introduce the definition of front:

Definition 3 (Front and Pareto-dominate) For a given pair of $\{\pi, \Delta\}$, we call a set of pairs (\mathcal{R}, e) as a front of $\{\pi, \hat{\Delta}\}\$, denoted by $\mathcal{F}(\pi, \hat{\Delta})$, if and only if

- (i) [Feasible instances exists] $V_0 := \{ \nu_0 \in \mathcal{E}_0 : (\sqrt{\mathcal{R}_{\nu_0}(T,\pi)}, e_{\nu_0}(T,\hat{\Delta})) = (R,e) \} \neq \emptyset.$
- (ii) [instances in \mathcal{V}_0 is the best] $\sharp \nu \in \mathcal{E}/\mathcal{V}_0$, s.t. $\exists \otimes \in \{K,T\}$, $(R,e) \preccurlyeq_{\otimes} (\sqrt{\mathcal{R}_{\nu}(T,\pi)},e_{\nu}(T,\hat{\Delta}))$.

We claim $\{\pi, \hat{\Delta}\}\$ Pareto-dominate another solution $\{\pi', \hat{\Delta}'\}\$ if $\forall (\mathcal{R}, e) \in \mathcal{F}(\pi, \hat{\Delta}), \exists (\mathcal{R}', e') \in \mathcal{F}(\pi, \hat{\Delta})\}$ $\mathcal{F}(\pi', \hat{\Delta}'),$ such that $\forall \otimes \in \{K, T\},\$ either (i) $\mathcal{R} \preccurlyeq_{\otimes} \mathcal{R}', e \preccurlyeq_{\otimes} e'$ or (ii) $\mathcal{R} \prec_{\otimes} \mathcal{R}', e \preccurlyeq_{\otimes} e'^{\tilde{\tau}}.$

We formalize the definition of front in the symbol of order \preccurlyeq_{\otimes} , \prec_{\otimes} . e.g., $(a, b) \preccurlyeq_{\otimes} (c, d)$, $e \preccurlyeq_{\otimes}$ $f, g \preccurlyeq_{\otimes} h$ denotes $(a \leq c, b \leq d), e < f, g \leq h$ when we only consider the parameter with respect to $\otimes \in \{K, T\}$ sufficiently large and omit any other parameter.

Definition 4 (Pareto-optimal and Pareto Frontier) A feasible pair $(\pi^*, \hat{\Delta}^*)$ is claimed to be Pareto-optimal when it is not Pareto-dominated by any other feasible solution. Pareto Frontier P is denoted as the envelop of fronts of all Pareto-optimal solutions.

For example, according to Definition [4,](#page-6-4) $\{\pi_i, \hat{\Delta}_i\}_{i\in[3]}$ is not dominated by each other in Figure [1.](#page-7-0) For more intuitive comprehension for practitioners, we provide the close-form mathematical formulation in the following section.

3. Pareto-optimality trade-off: the necessary and sufficient condition

We establish a general lower bound when simultaneously considering the regret and estimation error. Then we present the Pareto Frontier in Definition [4](#page-6-4) (red line in Figure [1\)](#page-7-0).

^{6.} Specifying the exposure mapping function as in Table [1,](#page-4-2) when we choose $\mathcal{U}_{\mathcal{E}} := \{0,1\} * \mathbf{1}^N$, then [\(5\)](#page-5-0) degenerates to $\frac{1}{N}\sum_{i\in\mathcal{U}}(Y_i(1,1,...1)-Y_i(0,0,...0))$ in [Jia et al.](#page-14-3) [\(2024\)](#page-14-3); when we choose $\mathcal{U}_{\mathcal{E}} = \mathcal{K}^{\mathcal{U}},$ then [\(5\)](#page-5-0) degenerates to $\frac{1}{N}\sum_{i\in\mathcal{U}}(Y_i(A_1)-Y_i(A_2)), A_1, A_2 \in \mathcal{K}^{\mathcal{U}}$ in [Agarwal et al.](#page-12-0) [\(2024\)](#page-12-0); when we choose $\mathcal{U}_{\mathcal{E}} := \{0, 1\}$, and $N = 1$, [\(5\)](#page-5-0) degenerates to the case of [Simchi-Levi and Wang](#page-15-4) [\(2024\)](#page-15-4).

^{7.} Intuitively speaking, if we denote the region formed by $\mathcal{F}(\pi, \hat{\Delta}), \mathcal{F}(\pi', \hat{\Delta}')$ and the XY-axis in the first quadrant as Region($\pi, \hat{\Delta}$), Region($\pi', \hat{\Delta'}$), respectively. Then $\{\pi, \hat{\Delta}\}$ Pareto-dominate $\{\pi', \hat{\Delta'}\}$ means $\texttt{Region}(\pi, \hat{\Delta}) \subseteq \texttt{Region}(\pi', \hat{\Delta}').$

Figure 1: Pareto-optimality. (a) We use three blue fronts (first quadrant) to show three different MAB algorithms $\{\pi_i, \hat{\Delta}_i\}_{i \in [3]}$, e.g., the blue regions represent the regrets and estimation errors that can be realistically achieved in all kinds of instances given $\{\pi_1, \hat{\Delta}_1\}$. MAB algorithm is Pareto-optimal if and only if its blue front is tangent to the Pareto Frontier (red) (otherwise it is intersecting with the grey region). (b) The greenline represents the baseline in [Simchi-Levi and Wang](#page-15-4) [\(2024\)](#page-15-4).

Theorem 5 Given any S and C that satisfies Condition [1.](#page-4-5) Given any online decisionmaking policy π , the trade-off between the regret and the estimation exhibits

$$
\inf_{\hat{\Delta}_T} \max_{\nu \in \mathcal{E}_0} \left(\sqrt{\mathcal{R}_{\nu}(T,\pi)} e_{\nu}(T,\hat{\Delta}) \right) = \Omega_{K,T}(\sqrt{|\mathcal{U}_{\mathcal{E}}|}). \tag{7}
$$

out interference.

We use the subscript $\{K, T\}$ to emphasize that the order just corresponds to these two parameters and omit the subscript in the following text. Theorem [5](#page-6-5) states that for any given policy π , there always exists at least one hard MAB instance ν , in which no matter what legitimate S, C, and estimator $\hat{\Delta}_T$ we choose, the lower bound $\Omega(\sqrt{|\mathcal{U}_{\mathcal{E}}|})$ always holds. In other words, there are always challenging instance ν such that $e_{\nu}(T, \hat{\Delta}) =$ $\Omega(\sqrt{|u_{\mathcal{E}}|}/\sqrt{\mathcal{R}_{\nu}(T,\pi)})$. We take examples considering the worst case of ν . According to the fact $\mathcal{R}_{\nu}(T,\pi) = O(T)$, Theorem [5](#page-6-5) states that the worst estimation error is at least $\Omega((|\mathcal{U}_{\mathcal{E}}|/T)^{\frac{1}{2}})$ and could not be further decreased; stepping forwards, as we will show in Sec-tion [4](#page-8-0) that our proposed MAB-N algorithm's regret is upper bounded by $O(\sqrt{|\mathcal{U}_{\mathcal{E}}|T})$, then Theorem [5](#page-6-5) additionally states that the worst estimation error of our algorithm will be ideally at least $(|\mathcal{U}_{\mathcal{E}}|/T)^{\frac{1}{4}}$ without need of further implementation. Moreover, to present how to achieve the Pareto-optimality according to the mathematical trade-off in Theorem [5,](#page-6-5) we provide the following if and only if condition for Pareto-optimal property and Pareto Frontier.

Theorem 6 Following the condition in Theorem [5,](#page-6-5) a feasible pair $\{\pi, \hat{\Delta}\}\$ is Pareto-optimal if the pair satisfies

$$
\max_{\nu \in \mathcal{E}_0} \left(\sqrt{\mathcal{R}_{\nu}(T,\pi)} e_{\nu}(T,\hat{\Delta}) \right) = \tilde{O}(\sqrt{|\mathcal{U}_{\mathcal{E}}|}).
$$

The Pareto Frontier are represented as $\mathcal{P} = \{(\mathcal{R}_{\nu}(T,\pi), e_{\nu}(T,\hat{\Delta})) : \sqrt{\mathcal{R}_{\nu}(T,\pi)}e_{\nu}(T,\hat{\Delta}) =$ $\tilde{O}(\sqrt{|\mathcal{U}_\mathcal{E}|})\}$.

We refer readers to Figure [1](#page-7-0) for the Pareto-optimal pair of $\{\pi, \hat{\Delta}\}\$ (blue region) and the Pareto Frontier (red line). Theorem [5-](#page-6-5)[6](#page-7-1) hold for any complex network topology $\mathbb H$ under mild conditions on exposure mapping (Condition [1\)](#page-4-5). They are not only non-trivial generalized trade-off results under network interference, but also strengthen the degenerated result without interference, i.e., $\mathbb{H} = \mathbf{0}$: when aligning with the setting of [Simchi-Levi and Wang](#page-15-4) [\(2024\)](#page-15-4) and take comparison, (i) we improve the Pareto-optimality trade-off with respect to the arm space, and (ii) we do not require their additional assumption upon ATE, i.e., $\hat{\Delta}^{i,j} = \Theta(1)$ and moreover, the noisy reward r_t is bounded.

4. Algorithm

In order to achieve the Pareto optimality trade-off in Section [3,](#page-6-0) we propose the advanced UCB algorithm with two stage under network interference (UCB-TSN) to simultaneously bound the ATE and regret. Our UCB-TSN simply includes two phases: (i) uniformly exploring the super exposure arm space and generates the estimated ATE, and then (ii) implementing the UCB exploration strategy to minimize the regret. We first illustrate that phase (i) could guarantee the estimation error as follows.

Theorem 7 (ATE estimation upper bound) Following the condition in Theorem [5.](#page-6-5) If $T_1 \geq |\mathcal{U}_{\mathcal{E}}|$, for any $S_i \neq S_j \in \mathcal{U}_{\mathcal{E}}$, the ATE estimation error of UCB-TSN can be upper bounded as $\mathbb{E}\big[\big|\hat{\Delta}_T^{(i,j)} - \Delta^{(i,j)}\big|\big] = \tilde{O}\big(\sqrt{|\mathcal{U}_{\mathcal{E}}|/T_1}\big)$.

Theorem [7](#page-8-1) states that uniform exploration in phase (i) helps to estimate the ATE, which is natural since UCB-TS explore the exposure action space with a round-robin manner. Specifically, as long as practitioner picks $T_1 = \Omega(T^{\alpha})$, $\alpha \in (0,1)$, then ATE estimation is consistent. After uniformly searching in phase (i), we take phase (ii) to search for the optimal arm, which leads to the convergence of the overall regret.

Theorem 8 (Regret upper bound) Following the condition in Theorem [5.](#page-6-5) With $\delta =$ $\frac{1}{T^2}$ and $T_1 \geq |\mathcal{U}_{\mathcal{E}}|$, the regret of UCB-TSN can be upper bounded as $\mathcal{R}_{\nu}(T,\pi) = \tilde{O}(\sqrt{|\mathcal{U}_{\mathcal{E}}|T} + \mathcal{U}_{\mathcal{E}})$ T_1) .

Theorem [8](#page-8-2) claims the regret could converge as $o(T)$, accommodating with well-selected T_1 , such as $T_1 = \sqrt{|\mathcal{U}_{\mathcal{E}}|T}$ $T_1 = \sqrt{|\mathcal{U}_{\mathcal{E}}|T}$ $T_1 = \sqrt{|\mathcal{U}_{\mathcal{E}}|T}$. Theorem [8](#page-8-2) is consistent with Proposition 1 when we omit phase (i) $(T_1 = 0)$ and reserve phase (ii). By the combination of Theorem [7-](#page-8-1)[8,](#page-8-2) we claim the Pareto-optimality as stated in Section [3](#page-6-0) in our UCB-TS as follows.

Theorem 9 (Trade-off result) Following the condition in Theorem [5.](#page-6-5) Set $T_1 \ge \sqrt{|\mathcal{U}_{\mathcal{E}}|T}$, for all $\nu \in \mathcal{E}_0$, UCB-TSN can guarantee $e_{\nu}(T, \hat{\Delta}) \sqrt{\mathcal{R}_{\nu}(T, \pi)} = \tilde{O}(\sqrt{|\mathcal{U}_{\mathcal{E}}|}).$

Theorem [9](#page-8-3) states that under a stricter but still mild condition upon the uniform exploration process T_1 (since $\sqrt{|U_{\mathcal{E}}|T} \geq |U_{\mathcal{E}}|$ under Condition [1\)](#page-4-5), UCB-TSN could achieve the Paretooptimal property in Theorem [5.](#page-6-5)

Comment on the order of node number N For a supplement, in Theorem [7-](#page-8-1)[9,](#page-8-3) we additionally consider the order of node number N . (i) In Theorem [7,](#page-8-1) we emphasize that if $\forall S' \in \mathcal{U}_{\mathcal{E}}, |\{A : \{S(i, A, \mathbb{H})\}_{i \in [N]} = S' \}| = 1$, namely, there is only one legitimate A which is compatible with each exposure arm S' , then Theorem [7](#page-8-1) could be strengthened as $\mathbb{E} \big[|\hat{\Delta}_T^{(i,j)} - \Delta^{(i,j)}|\big] = \tilde{O}\big(\sqrt{|\mathcal{U}_{\mathcal{E}}|/T_1N}\big)$. For instance, we consider the cluster-wise switchback experiment $(S(i, A, \mathbb{H}) = a_{i,t})$, which is the generalized case of [Jia et al.](#page-14-3) [\(2024\)](#page-14-3). In this case, since $|\mathcal{U}_{\mathcal{E}}| = K^C \ll N$ via manually selecting d_s, C , then we can claim the estimation is consistent when $N \to +\infty^8$ $N \to +\infty^8$. Moreover, in the setting of [Agarwal et al.](#page-12-0) [\(2024\)](#page-12-0), it is equivalent to the case $C = N$ and thus the result in Theorem [7](#page-8-1) is transformed as $\tilde{O}(\sqrt{K^N/T_1N})$. It serves as a supplement of Proposition [1](#page-3-0) , claiming that not only the regret, but also the estimation error is hard to control without exposure mapping. (ii) Analogously, in Theorem [8,](#page-8-2) the result is transformed to $\mathcal{R}_{\nu}(T,\pi) = \tilde{O}(\sqrt{|\mathcal{U}_{\mathcal{E}}|T/N}+T_1)$ under the above one-to-one mapping. (iii) Finally, in Theorem [9,](#page-8-3) the trade-off is transferred to be $\tilde{O}(\sqrt{|\mathcal{U}_{\mathcal{E}}|/N})$ when we slightly modify the condition of T_1 as $T_1 \geq \sqrt{|\mathcal{U}_{\mathcal{E}}|T/N} \vee |\mathcal{U}_{\mathcal{E}}|$. This result is also aligned with the proof of Theorem [5.](#page-6-5)

Comparison with the baseline algorithm To facilitate the fair comparison, we con-sider the degenerated case as in [Simchi-Levi and Wang](#page-15-4) (2024) , where we choose $N =$ $1, |\mathcal{U}_{\mathcal{E}}| = K \geq 2$ in our UCB-TSN. Here each arm corresponds to $\{S_i\}_{i \in [K]}$.

We compare the regret and estimation. (i) For the regret, they proposed their EXP3EG algorithm which guarantees the regret upper bound as $\mathcal{R}_{\nu}(T,\pi) = \tilde{O}(K^5 + T^{1-\alpha})$, where $\alpha \in$ [0, 1]^{[9](#page-9-2)}. Such result is build upon the assumption $\Delta^i := \frac{1}{N} \sum_{i' \in \mathcal{U}} (\tilde{Y}_{i'}(S^*) - \tilde{Y}_{i'}(S_i)) = \Theta(1)$ for all $S_i \neq S^*$. In this single-agent setting with such assumption, it should be pointed out that our regret upper bound in Theorem [8](#page-8-2) could be naturally strengthened to $\tilde O\big(K+T_1\big)$ (refer to our instance dependent regret upper bound in Lemma [11](#page-26-0) in the Appendix), and thus our regret upper bound is strictly stronger than theirs if we force $T_1 = O(T^{1-\alpha})$. (ii) For the estimation error, they state that ATE could be upper bounded by $e_{\nu}(T,\pi) = \tilde{O}(K^2T^{-\frac{1-\alpha}{2}})$. Therefore our estimation error in Theorem [7,](#page-8-1) i.e., $\tilde{O}(\sqrt{|\mathcal{U}_{\mathcal{E}}|/T_1}) = \tilde{O}(\sqrt{K/T_1})$ is strictly stronger than theirs since it is legitimate to force $T_1 = T^{1-\alpha} \vee |\mathcal{U}_{\mathcal{E}}|$.

Such strict improvement is illustrated in Figure [1.](#page-7-0) It validates the statements under Theorem [6](#page-7-1) that we achieve the Pareto optimality with respect to time period T and additionally, the exposure super arm space $|\mathcal{U}_{\mathcal{E}}|$. Moreover, [Simchi-Levi and Wang](#page-15-4) [\(2024\)](#page-15-4) only focuses on the bounded noisy reward within $[-1, 1]$ while we extend the setting to the more general sub-Gaussian noise for each arm.

5. Extended algorithm for the adversarial setting

The adversarial setting We cover [Simchi-Levi and Wang](#page-15-4) [\(2024\)](#page-15-4)'s adversarial setting when considering trade-offs. We consider

$$
r_{i,t}(A_t) = Y_i(A_t) + f_t + \eta_{i,t},
$$
\n(8)

^{8.} Essentially, it is due to the re-scaling of noise. Under the one-to-one mapping in this paragraph, the result is intuitive since $\sum_{i\in\mathcal{U}} \tilde{r}_i(S)/N$ exhibits a re-scaled Sub-Gaussian noise with variance proxy $1/N$. It degenerates to the offline setting when $N \to +\infty$. Otherwise, we could only ensure $\sum_{i \in \mathcal{U}} \tilde{r}_i(S)/N$ is a Sub-Gaussian noise with variance proxy $(1/N + 1/4)$. We defer the details to Appendix.

^{9.} $\mathcal{R}_{\nu}(T,\pi) = O(\sum_{S \in [K]/\{S^*\}} |\mathcal{U}_{\mathcal{E}}|^4 log(T)/\Delta(S) + \Delta(S)T^{1-\alpha}log(T)) = \tilde{O}(K^5 + T^{1-\alpha}).$

Algorithm 1 UCB-Two Stage-Network (UCB-TSN)

Input: arm set A, time $\{T_1, T\}$, unit number N, exposure super arm set $\mathcal{U}_{\mathcal{E}}$, estimator set $\{\hat{R}_0(S) = 0\}_{S \in \mathcal{U}_{\mathcal{E}}}, \ \{\mathcal{N}_0^S = 0\}_{S \in \mathcal{U}_{\mathcal{E}}}, \ \{\text{UCB}_{0,S} = 0\}_{S \in \mathcal{U}_{\mathcal{E}}}, \ \text{counter } k = 1,$ $\mathcal{N}_S^t = \sum_{t'=1}^t \mathbf{1}\{S_{t'} = S\}.$ for $t = 1 : T_1$ do Select exposure super arm $S_t = S_k$ and implement Sampling(S_t) Set $k = k + 1$ if $k + 1 \leq |\mathcal{U}_{\mathcal{E}}|$, else set $k = 1$ end for For all $S_i, S_j \in \mathcal{U}_{\mathcal{E}}, S_i \neq S_j$, output $\hat{\Delta}_T^{(i,j)} = \hat{R}_{T_1}(S_i) - \hat{R}_{T_1}(S_j)$ for $t = T_1 + 1 : T$ do Select $S_t = \arg \max_{S \in \mathcal{U}_{\mathcal{E}}} \text{UCB}_{t-1,S}$ and implement Sampling(S_t) end for # Parameter 1: $\hat{R}_t(S) = \left[\hat{R}_{t-1}(S)\mathcal{N}_S^{t-1} + \mathbf{1}\{S_t = S\}\frac{1}{N}\right]$ # Parameter 1: $\hat{R}_t(S) = \left[\hat{R}_{t-1}(S) \mathcal{N}_S^{t-1} + \mathbf{1} \{ S_t = S \} \frac{1}{N} \sum_{i \in \mathcal{U}} \tilde{r}_{i,t}(S_t) \right] / \mathcal{N}_S^t$
Parameter 2: UCB_{t,S} = $\hat{R}_t(S) + \sqrt{9 \log(1/\delta) / \mathcal{N}_S^t}$

Algorithm 2 Sampling

Input: S

Derive the set of real supper arm $\{Z_s\}_{s=[l]}$ such that $\{\mathbf{S}(i, Z_s, \mathbb{H})\}_{i\in\mathcal{U}}=S, \forall s\in[l]$ Uniformly sample A from set $\{Z_s\}_{s=1}^l$, pull A, and observe reward $\{r_{i,t}(A_t)\}_{i\in\mathcal{U}}$ Return $\{\tilde{r}_{i,t}(S_t)\}_{i\in\mathcal{U}} := \{r_{i,t}(A_t)\}_{i\in\mathcal{U}}$

where $\eta_{i,t}$ is i.i.d. zero means noise and f_t is an adversarial noise. We suppose $r_{i,t}(A) \in [0,1]$ for all $i \in \mathcal{U}$, $A \in \mathcal{K}^{\mathcal{U}}$ and $t \in [T]$. It is also easy to verify that $\tilde{r}_{i,t}(S) \in [0,1]$ for all $t \in [T]$, $S_i \in \mathcal{U}_{\mathcal{E}}, i \in \mathcal{U}$ and $\mathbb{E}[\tilde{r}_{i,t}(S)] = \tilde{Y}_i(S) + f_t$. In addition to the standard setting in the preliminaries, there is an f_t , a pre-specified function w.r.t. period t. Motivated by the fact that the UCB algorithm discussed in the previous section cannot be applied directly in this context, we provide the advanced EXP3-TSN algorithm for substitution. The pusedo code and details of the EXP3-TSN are provided in the Appendix. We provide the estimation error, regret, and trade-off in Theorem [10.](#page-10-0)

Theorem 10 (Pareto-optimality trade-off in the adversarial setting) Following the condition in Theorem [5,](#page-6-5) let $\mathcal{T}(t) \equiv (2|\mathcal{U}_{\mathcal{E}}| + 1)^2 \log(t|\mathcal{U}_{\mathcal{E}}|^2)/2(e-2)|\mathcal{U}_{\mathcal{E}}|$, then

(i)[ATE estimation] Suppose $T \geq \mathcal{T}(T)$ and $T_1 \geq \mathcal{T}(T_1)$. For any $S_i \neq S_j$, the ATE estimation error of the EXP3-TSN can be upper bounded as in Theorem [7.](#page-8-1)

(ii) [Regret] Moreover, if we only suppose $T \geq \mathcal{T}(T)$, then the regret of EXP3-TSN could be upper bounded as the form of Theorem [8.](#page-8-2)

(iii)[Pareto-optimality] Finally, additionally set $T_1 \geq \mathcal{T}(T_1) \vee \sqrt{|\mathcal{U}_{\mathcal{E}}|T}$. EXP3-TSN can also guarantee the Pareto-optimality trade-off, i.e., $e_{\nu}(T, \hat{\Delta})\sqrt{\mathcal{R}(T, \pi)} = \tilde{O}(\sqrt{|\mathcal{U}_{\mathcal{E}}|}).$

Theorem [10](#page-10-1) states that under additional mild conditions, i.e., $T \geq \mathcal{T}(T)$ and $T_1 \geq \mathcal{T}(T_1)^{10}$, the regret, ATE estimation error and the Pareto-Optimality trade-off could still keep their

^{10.} Since $\mathcal{T}(t) = O(|\mathcal{U}_{\mathcal{E}}| \log(|\mathcal{U}_{\mathcal{E}}|t))$, such conditions are natural to satisfy given that T is sufficiently large.

original form in Theorem [7](#page-8-1)[-8.](#page-8-2) In such adversarial setting, our result can also outperforms [Simchi-Levi and Wang](#page-15-4) [\(2024\)](#page-15-4) with the same argument as in Section [4,](#page-9-3) and the discussion concerning the order of the node number N aligns analogously.

6. Justification, discussion and future work

Justification on exposure mapping It is a well-known concept in causality. From a statistical perspective, it serves as a functional tool for mapping a high-dimensional action space to a low-dimensional manifold; from a machine learning standpoint, it can be interpreted as a specialized input representation layer. However, its utility has not been fully explored in interference-based online learning settings like bandits. Interference-based bandit referred to exposure mapping has only been explored in [Jia et al.](#page-14-3) [\(2024\)](#page-14-3) to our knowledge. [Jia et al.](#page-14-3) [\(2024\)](#page-14-3) additionally assumes the intensity of interference decays with distance. Still, the low-dimensional vectors from their exposure mapping are not involved in the computation of the target regret. In contrast, their regret, directly uses the adversarial setting that "the original super arm must be a vector of the form $k * 1^N, k \in \mathcal{K}$ ", which is limited in realistic compared to our settings, e.g., when the optimal arm takes place when the individuals in network are assigned to different treatments; to tackle this problem, although [Agarwal et al.](#page-12-0) [\(2024\)](#page-12-0) could output the best arm beyond $k * 1^N, k \in \mathcal{K}$, they provide a stronger assumption that each node's rewards come only from its limited first-order neighbors. In sum, our paper first presents a integration of exposure mapping with bandit regret frameworks and demonstrate its generality and applicability.

Justification on condition Condition [1](#page-4-5) states that $\mathcal{U}_{\mathcal{E}} \geq 2$ is not empty. It is already weaker than the previous interference-based bandit setting [\(Jia et al.,](#page-14-3) [2024;](#page-14-3) [Agarwal et al.,](#page-12-0) [2024\)](#page-12-0) whereas could be further relaxed. We consider the generalized metric to describe the distance between $\mathcal{U}_{\mathcal{C}}$ and $\mathcal{U}_{\mathcal{O}}$: $\mathcal{D}(\mathcal{U}_{\mathcal{C}},\mathcal{U}_{\mathcal{O}}) := \min_{a \in \mathcal{U}_{\mathcal{C}}, b \in \mathcal{U}_{\mathcal{O}}} ||a - b||_1$ via Hamming distance, where a, b are N-dimensional vectors. When the number of clusters grows, the action space $|\mathcal{U}_c|$ exponentially expands and their compatibility $\mathcal{D}(\mathcal{U}_c, \mathcal{U}_c)$ also changes. These previous literature and Condition [1](#page-4-5) all satisfy $\mathcal{D}(\mathcal{U}_{\mathcal{C}},\mathcal{U}_{\mathcal{O}})=0$, and the former together with additional network structure [\(Agrawal and Goyal,](#page-12-7) [2012\)](#page-12-7) or interference intensity [\(Jia et al.,](#page-14-3) [2024\)](#page-14-3) assumption as above. In fact, it can also be substituted with a more relaxed assumption $\mathcal{D}(\mathcal{U}_{\mathcal{C}},\mathcal{U}_{\mathcal{O}}) \leq \epsilon$, where $\epsilon > 0$ is a prior constant. Joint with some mild interference decaying assumption like [Jia et al.](#page-14-3) [\(2024\)](#page-14-3), we could transfer the approximation of our exposure arm's reward as some off-the-shelf optimization problems, and our theoretical analysis and algorithm can also be naturally generalized. We defer such extension to the future work.

Conclusion and future work In our paper, we establish the general bandit setting under interference via exposure mapping. We bridge the optimal theoretical balance between the learning efficiency and the statistical power via the Pareto trade-off between the regret and estimation error. Finally, we propose the compatible Pareto-optimal advanced UCB algorithm to achieve such trade-off. In sum, our objective is to bridge the statistics and learning communities by employing network interference as a facilitating mechanism.

Concluding the above, due to the flexibility of exposure-based modeling, the stability of the theoretical optimal balancing guarantee, and the scenario extensibility, our work will be promising in the future to solve the following problems: (i) extension to RL, where states are with complex network topology, such as factorized RL, along with the short-long-term problem; (ii) bandit variants: The fully adversarial bandit problem, also so-called designbased experiments in statistics literature. Moreover, we can also consider the neural bandit problem and the Graph neural network fitting model. (iii) extension to more complex topology structure, such as the unknown or dynamic network interference.

References

- Abhineet Agarwal, Anish Agarwal, Lorenzo Masoero, and Justin Whitehouse. Multi-armed bandits with network interference. arXiv preprint arXiv:2405.18621, 2024.
- Shipra Agrawal and Navin Goyal. Thompson sampling for contextual bandits with linear payoffs. In International Conference on Machine Learning, 2012.
- Venkatachalam Anantharam, Pravin Varaiya, and Jean Walrand. Asymptotically efficient allocation rules for the multiarmed bandit problem with multiple plays-part i: Iid rewards. IEEE Transactions on Automatic Control, 32(11):968–976, 1987.
- Peter M Aronow and Cyrus Samii. Estimating average causal effects under general interference, with application to a social network experiment. The Annals of Applied Statistics, 2017.
- Bruno Arpino and Alessandra Mattei. Assessing the causal effects of financial aids to firms in tuscany allowing for interference. The Annals of Applied Statistics, 2016.
- Peter Auer, Nicolò Cesa-Bianchi, and Paul Fischer. Finite-time analysis of the multiarmed bandit problem. Machine Learning, 47:235–256, 2002.
- Oriana Bandiera, Iwan Barankay, and Imran Rasul. Social connections and incentives in the workplace: Evidence from personnel data. Econometrica, 77(4):1047–1094, 2009.
- Lilian Besson and Emilie Kaufmann. Multi-player bandits revisited. In Algorithmic Learning Theory, pages 56–92. PMLR, 2018.
- Robert M Bond, Christopher J Fariss, Jason J Jones, Adam DI Kramer, Cameron Marlow, Jaime E Settle, and James H Fowler. A 61-million-person experiment in social influence and political mobilization. Nature, 489(7415):295–298, 2012.
- Jing Cai, Alain De Janvry, and Elisabeth Sadoulet. Social networks and the decision to insure. American Economic Journal: Applied Economics, 7:81–108, 2015.
- Nicolo Cesa-Bianchi and Gábor Lugosi. Combinatorial bandits. *Journal of Computer and* System Sciences, 78(5):1404–1422, 2012.
- Shouyuan Chen, Tian Lin, Irwin King, Michael R Lyu, and Wei Chen. Combinatorial pure exploration of multi-armed bandits. Advances in Neural Information Processing Systems, 27, 2014.
- Wei Chen, Yajun Wang, and Yang Yuan. Combinatorial multi-armed bandit: General framework and applications. In International conference on machine learning, pages 151–159. PMLR, 2013.
- Brian Cho, Dominik Meier, Kyra Gan, and Nathan Kallus. Reward maximization for pure exploration: Minimax optimal good arm identification for nonparametric multi-armed bandits. arXiv preprint arXiv:2410.15564, 2024.
- Marco Ciotti, Massimo Ciccozzi, Alessandro Terrinoni, Wen-Can Jiang, Cheng-Bin Wang, and Sergio Bernardini. The covid-19 pandemic. Critical reviews in clinical laboratory sciences, 57(6):365–388, 2020.
- Richard Combes, Mohammad Sadegh Talebi Mazraeh Shahi, Alexandre Proutiere, et al. Combinatorial bandits revisited. Advances in Neural Information Processing Systems, 28, 2015.
- Yash Deshpande, Adel Javanmard, and Mohammad Mehrabi. Online debiasing for adaptively collected high-dimensional data with applications to time series analysis. Journal of the American Statistical Association, 118(542):1126–1139, 2023.
- Maria Dimakopoulou, Zhengyuan Zhou, Susan Athey, and Guido Imbens. Estimation considerations in contextual bandits. arXiv preprint arXiv:1711.07077, 2017.
- Maria Dimakopoulou, Zhengyuan Zhou, Susan Athey, and Guido Imbens. Balanced linear contextual bandits. In Proceedings of the AAAI Conference on Artificial Intelligence, volume 33, pages 3445–3453, 2019.
- Maria Dimakopoulou, Zhimei Ren, and Zhengyuan Zhou. Online multi-armed bandits with adaptive inference. Advances in Neural Information Processing Systems, 34:1939–1951, 2021.
- Congyuan Duan, Wanteng Ma, Jiashuo Jiang, and Dong Xia. Regret minimization and statistical inference in online decision making with high-dimensional covariates. $arXiv$ preprint arXiv:2411.06329, 2024.
- Alexander D'Amour, Peng Ding, Avi Feller, Lihua Lei, and Jasjeet Sekhon. Overlap in observational studies with high-dimensional covariates. Journal of Econometrics, $221(2)$: 644–654, 2021.
- Akram Erraqabi, Alessandro Lazaric, Michal Valko, Emma Brunskill, and Yun-En Liu. Trading off rewards and errors in multi-armed bandits. In Artificial Intelligence and Statistics, pages 709–717. PMLR, 2017.
- Mengsi Gao and Peng Ding. Causal inference in network experiments: regression-based analysis and design-based properties. arXiv preprint arXiv:2309.07476, 2023.
- Vitor Hadad, David A Hirshberg, Ruohan Zhan, Stefan Wager, and Susan Athey. Confidence intervals for policy evaluation in adaptive experiments. Proceedings of the national academy of sciences, 118(15): e2014602118, 2021.
- Qiyu Han, Will Wei Sun, and Yichen Zhang. Online statistical inference for matrix contextual bandit. arXiv preprint arXiv:2212.11385, 2022.
- Jiafan He, Tianhao Wang, Yifei Min, and Quanquan Gu. A simple and provably efficient algorithm for asynchronous federated contextual linear bandits. arXiv preprint arXiv:2207.03106, 2022.
- Eshcar Hillel, Zohar S. Karnin, Tomer Koren, Ronny Lempel, and Oren Somekh. Distributed exploration in multi-armed bandits. In Advances in Neural Information Processing Systems, 2013.
- Guido W Imbens. Causal inference in the social sciences. Annual Review of Statistics and Its Application, 11, 2024.
- Kevin G. Jamieson, Matthew Malloy, Robert D. Nowak, and Sébastien Bubeck. lil' ucb : An optimal exploration algorithm for multi-armed bandits. $arXiv$ preprint $arXiv:1312.7308$, 2013.
- Su Jia, Nishant Oli, Ian Anderson, Paul Duff, Andrew A Li, and Ramamoorthi Ravi. Shortlived high-volume bandits. In International Conference on Machine Learning, pages 14902–14929. PMLR, 2023.
- Su Jia, Peter Frazier, and Nathan Kallus. Multi-armed bandits with interference. $arXiv$ preprint arXiv:2402.01845, 2024.
- Junpei Komiyama, Junya Honda, and Hiroshi Nakagawa. Optimal regret analysis of thompson sampling in stochastic multi-armed bandit problem with multiple plays. In International Conference on Machine Learning, pages 1152–1161. PMLR, 2015.
- Junpei Komiyama, Junya Honda, and Akiko Takeda. Position-based multiple-play bandit problem with unknown position bias. Advances in Neural Information Processing Systems, 30, 2017.
- Branislav Kveton, Zheng Wen, Azin Ashkan, and Csaba Szepesvari. Combinatorial cascading bandits. Advances in Neural Information Processing Systems, 28, 2015.
- Paul Lagrée, Claire Vernade, and Olivier Cappe. Multiple-play bandits in the position-based model. Advances in Neural Information Processing Systems, 29, 2016.
- Tor Lattimore and Csaba Szepesvári. Bandit algorithms. Cambridge University Press, 2020.
- Michael P Leung. Causal inference under approximate neighborhood interference. Econometrica, 90(1):267–293, 2022a.
- Michael P Leung. Rate-optimal cluster-randomized designs for spatial interference. The Annals of Statistics, 50(5):3064–3087, 2022b.
- Michael P Leung. Network cluster-robust inference. Econometrica, 91(2):641–667, 2023.
- Chuanhao Li and Hongning Wang. Communication efficient federated learning for generalized linear bandits. arXiv preprint arXiv:2202.01087, 2022.
- Shuai Li, Baoxiang Wang, Shengyu Zhang, and Wei Chen. Contextual combinatorial cascading bandits. In International conference on machine learning, pages 1245–1253. PMLR, 2016.
- Biyonka Liang and Iavor Bojinov. An experimental design for anytime-valid causal inference on multi-armed bandits. arXiv preprint arXiv:2311.05794, 2023.
- Jonathan Louëdec, Max Chevalier, Josiane Mothe, Aurélien Garivier, and Sébastien Gerchinovitz. A multiple-play bandit algorithm applied to recommender systems. In The Twenty-Eighth International Flairs Conference, 2015.
- Alexander R Luedtke and Mark J Van Der Laan. Statistical inference for the mean outcome under a possibly non-unique optimal treatment strategy. Annals of statistics, $44(2)$:713, 2016.
- Ka Ho Mok, Yeun-Wen Ku, and Tauchid Komara Yuda. Managing the covid-19 pandemic crisis and changing welfare regimes, 2021.
- Evan Munro, Stefan Wager, and Kuang Xu. Treatment effects in market equilibrium. arXiv preprint arXiv:2109.11647, 2021.
- Elizabeth Levy Paluck, Hana Shepherd, and Peter M Aronow. Changing climates of conflict: A social network experiment in 56 schools. Proceedings of the National Academy of Sciences, 113(3):566–571, 2016.
- Lijing Qin, Shouyuan Chen, and Xiaoyan Zhu. Contextual combinatorial bandit and its application on diversified online recommendation. In Proceedings of the 2014 SIAM International Conference on Data Mining, pages 461–469. SIAM, 2014.
- Donald B. Rubin. Randomization analysis of experimental data: The fisher randomization test comment. Journal of the American Statistical Association, 75:591–593, 1980.
- Donald B Rubin. Causal inference using potential outcomes: Design, modeling, decisions. Journal of the American Statistical Association, 100(469):322–331, 2005.
- Aadirupa Saha and Aditya Gopalan. Combinatorial bandits with relative feedback. Advances in Neural Information Processing Systems, 32, 2019.
- David Simchi-Levi and Chonghuan Wang. Multi-armed bandit experimental design: Online decision-making and adaptive inference. Management Science, 2024. doi: 10.1287/mnsc. 2023.00492.
- Balázs Szörényi, Róbert Busa-Fekete, István Hegedüs, Róbert Ormándi, Márk Jelasity, and Balázs Kégl. Gossip-based distributed stochastic bandit algorithms. In *International* Conference on Machine Learning, 2013.
- Taishi Uchiya, Atsuyoshi Nakamura, and Mineichi Kudo. Algorithms for adversarial bandit problems with multiple plays. In International Conference on Algorithmic Learning Theory, pages 375–389. Springer, 2010.
- Davide Viviano, Lihua Lei, Guido Imbens, Brian Karrer, Okke Schrijvers, and Liang Shi. Causal clustering: design of cluster experiments under network interference. arXiv preprint arXiv:2310.14983, 2023.
- Yuanhao Wang, Jiachen Hu, Xiaoyu Chen, and Liwei Wang. Distributed bandit learning: Near-optimal regret with efficient communication. arXiv preprint arxiv: 1904.06309, 2019.
- Qingyun Wu, Huazheng Wang, Quanquan Gu, and Hongning Wang. Contextual bandits in a collaborative environment. Proceedings of the 39th International ACM SIGIR conference on Research and Development in Information Retrieval, 2016.
- Yang Xu, Wenbin Lu, and Rui Song. Linear contextual bandits with interference. $arXiv$ preprint arXiv:2409.15682, 2024.
- Fanny Yang, Aaditya Ramdas, Kevin G Jamieson, and Martin J Wainwright. A framework for multi-a (rmed)/b (andit) testing with online fdr control. Advances in Neural Information Processing Systems, 30, 2017.
- Jiayu Yao, Emma Brunskill, Weiwei Pan, Susan Murphy, and Finale Doshi-Velez. Power constrained bandits. In Machine Learning for Healthcare Conference, pages 209–259. PMLR, 2021.
- Kelly Zhang, Lucas Janson, and Susan Murphy. Inference for batched bandits. Advances in Neural Information Processing Systems, 33:9818–9829, 2020.
- Kelly Zhang, Lucas Janson, and Susan Murphy. Statistical inference with m-estimators on adaptively collected data. Advances in Neural Information Processing Systems, 34: 7460–7471, 2021.
- Yi Zhang and Kosuke Imai. Individualized policy evaluation and learning under clustered network interference. arXiv preprint arXiv:2311.02467, 2023.
- Datong Zhou and Claire Tomlin. Budget-constrained multi-armed bandits with multiple plays. In Proceedings of the AAAI Conference on Artificial Intelligence, volume 32, 2018.

Supplementary Material for "Online Experimental Design With Estimation-Regret Trade-off Under Network Interference"

Appendix [A](#page-17-0) summarize key symbols in the main text for reference.

Appendix [B](#page-18-0) provides the detailed literature review for better comprehension of the background.

Appendix [C](#page-19-0) further analyze the structure the exposure mapping and the re-scaled noise. Appendix [D](#page-20-0) provides the proof the Proposition [1.](#page-3-0)

Appendix [E](#page-21-0)[-F](#page-25-0) contain the proof of Theorem [5](#page-6-5) and Theorem [6,](#page-7-1) respectively.

Appendix [G](#page-25-1) presents the proofs of Theorem [7-](#page-8-1)[9](#page-8-3) in Section [4.](#page-8-0)

Appendix [H](#page-29-0) provides algorithm for Non-stochastic Setting.

Appendix [I](#page-30-0) deliver the proof of Theorem [10.](#page-10-0) Finally, Appendix [J](#page-34-0) includes the auxiliary lemmas.

Appendix A. Notations

Appendix B. Literature review

In this section, we present a literature review on network interference within the causality and bandit communities. Additionally, we discuss relevant variants of bandit problems. Finally, we provide a brief summary of recent advancements in the estimation-regret tradeoff within the context of MAB.

Offline causality estimation under network interference In the current causality literature, interference is a well-known concept. It is a violation of the conventional "SUTVA" setting, representing that one individual's treatment would potentially affects other individual's outcome, which is relevant in practice. Current literature resort to clustering [Zhang](#page-16-1) [and Imai](#page-16-1) [\(2023\)](#page-16-1); [Viviano et al.](#page-16-0) [\(2023\)](#page-16-0) or exposure mapping [Leung](#page-14-0) [\(2022a,](#page-14-0)[b,](#page-14-1) [2023\)](#page-14-2).

Bandit under network interference. Previous attempts are being made to consider the multi-armed bandit problem upon network interference. [Agarwal et al.](#page-12-0) [\(2024\)](#page-12-0) conduct the Fourier analysis to transform the traditional stochastic multi-armed bandit into a sparse linear bandit. However, in order to reduce the exponential action space, they made a strong assumption of sparsity for graph structures, i.e., the number of neighbors of each node is manually upper limited. On the other hand, [Jia et al.](#page-14-3) [\(2024\)](#page-14-3) analyzes the action space at the other extreme that considers an adversarial bandit setting and thus forces each node to a simultaneous equal arm. It does not consider that the optimal arm could differ for each node or subgroup. Moreover, [Xu et al.](#page-16-2) [\(2024\)](#page-16-2) further considers the contextual setting under the specific linear structure between the potential outcome and the interference intensity.

Relevant bandit variants: Multiple-play bandits, multi-agent bandits, combinatorial bandits and multi-tasking bandits. In bandit literature, the problem where a bandit algorithm plays multiple arms in each time period has been a subject of study for a long time. Our work is closely related to the *multi-play bandit* problem, where the algorithm selects multiple arms in each round and observes their corresponding reward feedback $(Anantharam et al., 1987; Uchiya et al., 2010; Komiyama et al., 2015, 2017; Louëdec et al.,$ $(Anantharam et al., 1987; Uchiya et al., 2010; Komiyama et al., 2015, 2017; Louëdec et al.,$ $(Anantharam et al., 1987; Uchiya et al., 2010; Komiyama et al., 2015, 2017; Louëdec et al.,$ $(Anantharam et al., 1987; Uchiya et al., 2010; Komiyama et al., 2015, 2017; Louëdec et al.,$ $(Anantharam et al., 1987; Uchiya et al., 2010; Komiyama et al., 2015, 2017; Louëdec et al.,$ $(Anantharam et al., 1987; Uchiya et al., 2010; Komiyama et al., 2015, 2017; Louëdec et al.,$ $(Anantharam et al., 1987; Uchiya et al., 2010; Komiyama et al., 2015, 2017; Louëdec et al.,$ $(Anantharam et al., 1987; Uchiya et al., 2010; Komiyama et al., 2015, 2017; Louëdec et al.,$ $(Anantharam et al., 1987; Uchiya et al., 2010; Komiyama et al., 2015, 2017; Louëdec et al.,$ $(Anantharam et al., 1987; Uchiya et al., 2010; Komiyama et al., 2015, 2017; Louëdec et al.,$ $(Anantharam et al., 1987; Uchiya et al., 2010; Komiyama et al., 2015, 2017; Louëdec et al.,$ $(Anantharam et al., 1987; Uchiya et al., 2010; Komiyama et al., 2015, 2017; Louëdec et al.,$ $(Anantharam et al., 1987; Uchiya et al., 2010; Komiyama et al., 2015, 2017; Louëdec et al.,$ $(Anantharam et al., 1987; Uchiya et al., 2010; Komiyama et al., 2015, 2017; Louëdec et al.,$ [2015;](#page-15-8) [Lagr´ee et al.,](#page-14-8) [2016;](#page-14-8) [Zhou and Tomlin,](#page-16-3) [2018;](#page-16-3) [Besson and Kaufmann,](#page-12-9) [2018;](#page-12-9) [Jia et al.,](#page-14-9) [2023\)](#page-14-9). Additionally, this is closely related to the multi-agent bandit problem (including distributed and federated bandits), where multiple agents each pull an arm in every time period. By exchanging observation histories through communication, these agents can col-laboratively accelerate the learning process. [\(Hillel et al.,](#page-14-10) [2013;](#page-15-9) Szörényi et al., 2013; [Wu](#page-16-4) [et al.,](#page-16-4) [2016;](#page-16-4) [Wang et al.,](#page-16-5) [2019;](#page-16-5) [Li and Wang,](#page-14-11) [2022;](#page-14-11) [He et al.,](#page-14-12) [2022\)](#page-14-12). Furthermore, our work is also connected to the *combinatorial bandit* problem, where the action set consists of a subset of the vertices of a binary hypercube [\(Cesa-Bianchi and Lugosi,](#page-12-10) [2012;](#page-12-10) [Chen](#page-13-4) [et al.,](#page-13-4) [2013,](#page-13-4) [2014;](#page-12-11) [Combes et al.,](#page-13-5) [2015;](#page-13-5) [Qin et al.,](#page-15-10) [2014;](#page-15-10) [Kveton et al.,](#page-14-13) [2015;](#page-14-13) [Li et al.,](#page-15-11) [2016;](#page-15-11) [Saha and Gopalan,](#page-15-12) [2019\)](#page-15-12). Some of these works account for interference between units, but they typically assume that the interference is either explicitly known to the learning algorithm, or the interference follows a specific pattern. In contrast, our setting makes no such assumptions about the nature or structure of interference between units.

Our paper is closely related to the field of multitasking bandits, where the learning algorithm is designed to achieve multiple objectives simultaneously during the learning process. [Yang et al.](#page-16-6) [\(2017\)](#page-16-6) explore the regulation of the false discovery rate while identifying the best arm. [Yao et al.](#page-16-7) [\(2021\)](#page-16-7) focus on ensuring the ability to detect whether an intervention has an effect, while also leveraging contextual bandits to tailor consumer actions. [Jamieson](#page-14-14) [et al.](#page-14-14) [\(2013\)](#page-14-14); [Cho et al.](#page-13-6) [\(2024\)](#page-13-6) aim to minimize cumulative regret while identifying the best arm with minimal sample complexity. [Erraqabi et al.](#page-13-7) [\(2017\)](#page-13-7) aim to balance the trade-off between regret minimization and estimation error; however, their design can not guarantee optimality.

Trade-off between inference and regret A significant body of research has been dedicated to developing statistical methods for inference in MABs. Numerous studies focus on deriving statistical tests or central limit theorems for MABs while ensuring that the bandit algorithm remains largely unaltered [\(Hadad et al.,](#page-13-8) [2021;](#page-13-8) [Luedtke and Van Der Laan,](#page-15-13) [2016;](#page-15-13) [Deshpande et al.,](#page-13-9) [2023;](#page-13-9) [Zhang et al.,](#page-16-8) [2020,](#page-16-8) [2021;](#page-16-9) [Han et al.,](#page-14-15) [2022;](#page-14-15) [Dimakopoulou et al.,](#page-13-10) [2017,](#page-13-10) [2019,](#page-13-11) [2021\)](#page-13-12), thereby facilitating aggressive regret minimization. However, these works all rely on the SUTVA assumption and fail to account for potential interference between units.

Previous literature upon adaptive inference in multi-armed bandits include [Dimakopoulou](#page-13-12) [et al.](#page-13-12) [\(2021\)](#page-13-12); [Liang and Bojinov](#page-15-3) [\(2023\)](#page-15-3) whereas without strict trade-off analysis. To our best knowledge, the only state-of-the-art trade-off result is primarily constructed by [Simchi-Levi](#page-15-4) [and Wang](#page-15-4) [\(2024\)](#page-15-4) whereas also be cursed by the SUTVA assumption without a network connection. Moreover, [Duan et al.](#page-13-3) [\(2024\)](#page-13-3) argue that such Pareto-optimality could be further improved, i.e., the regret and estimation error could simultaneously achieve their optimality, if additionally assuming the "covariate diversity" of each node without network interference. Stepping forward, when we shift our attention to the network setting, [Jia et al.](#page-14-3) [\(2024\)](#page-14-3) is also intuitively aware of the potential "incompatibility" of decision-making and statistical inference: specifically, [Jia et al.](#page-14-3) [\(2024\)](#page-14-3) emphasizes that the truncated HT estimator directly into the policy learning system is no longer robust because policy learning gives different propensity probabilities to different arms, making the propensity score more extreme.

Appendix C. The discussion of exposure mapping and noise re-scaling

Considering (3) , we take the exposure mapping function's output as d_s cardinality without loss of generalization. We choose $\mathbb{P}(Z | S_t) := \mathbb{P}_{\text{Leung}}(Z | S_t e_i)$ then $\forall S_t e_i = t', \tilde{Y}_{\text{Leung}}(t') =$ $\sum \mathbb{P}_{\text{Leung}}(Z \mid t')Y(Z) = \sum \mathbb{P}(Z \mid S_t)Y(Z) = \tilde{Y}(S_t)$. Hence our exposure-based reward notation is generalized from [Leung](#page-14-0) [\(2022a\)](#page-14-0).

Moreover, we discuss the re-scaling of noise. When $\forall S' \in \mathcal{U}_{\mathcal{E}}, |\{A: \{S(i, A, \mathbb{H})\}_{i \in [N]} =$ S' } = 1, it naturally leads to the variance proxy $1/N$ of the Sub-Gaussian variables $\sum_{i\in\mathcal{U}}\tilde{r}_i(S)/N$. Hence, we mainly consider other cases. Notice that [\(3\)](#page-3-1) defines

$$
[\tilde{Y}_i(S_t), \tilde{r}_i(S_t)]^\top := \sum_{A \in \mathcal{K}^{\mathcal{U}}} [Y_i(A), r_i(A)]^\top \mathbb{P}(A_t = A | S_t),
$$

namely, for each S_t , practitioners select random legitimate $r_i(A)$ to approximate $\tilde{r}_i(S_t)$, each with probability $\mathbb{P}(A_t = A \mid S_t)$. It follows that

$$
\mathbb{E}(\exp(m\frac{1}{N}\sum_{i\in\mathcal{U}}(\tilde{r}_i(S_t) - \tilde{Y}_i(S_t))) | A)
$$
\n
$$
= \mathbb{E}(\exp(m\frac{1}{N}\sum_{i\in\mathcal{U}}(r_i(A) - Y_i(A) + Y_i(A) - \tilde{Y}_i(S_t))))
$$
\n
$$
= \exp(m\frac{1}{N}\sum_{i\in\mathcal{U}}(Y_i(A) - \tilde{Y}_i(S_t))) \mathbb{E}(\exp(m\frac{1}{N}\sum_{i\in\mathcal{U}}(r_i(A) - Y_i(A))))
$$
\n
$$
\leq \exp(m\frac{1}{N}\sum_{i\in\mathcal{U}}(Y_i(A) - \tilde{Y}_i(S_t))) \exp(\frac{m^2}{2N})
$$
\n(9)

Taking expectation upon both sides of [\(9\)](#page-20-1), it leads to

$$
\mathbb{E}(\exp(m\frac{1}{N}\sum_{i\in\mathcal{U}}(\tilde{r}_i(S_t)-\tilde{Y}_i(S_t)))) \leq \exp(\frac{m^2}{2N})\mathbb{E}\exp(m\frac{1}{N}\sum_{i\in\mathcal{U}}(Y_i(A)-\tilde{Y}_i(S_t))).
$$
 (10)

According to the boundary $\frac{1}{N} \sum_{i \in \mathcal{U}} (Y_i(A) - \tilde{Y}_i(S_t)) \in [-1,1]$, it is natural to derive $\mathbb{E} \exp(m\frac{1}{N}\sum_{i\in\mathcal{U}}(Y_i(A)-\tilde{Y}_i(S_t))) \leq \cosh(m/2) \leq \exp(m^2/8)$. Then [\(10\)](#page-20-2) achieves that

$$
(10) \le \exp(\frac{m^2}{2N})\exp(m^2/8) = \exp(\frac{m^2}{2}(\frac{1}{N} + \frac{1}{4})).
$$
\n(11)

Therefore the Sub-Gaussian variables $\sum_{i\in\mathcal{U}} \tilde{r}_i(S)/N$ could achieve the variance proxy at most $1/N + 1/4$. In the following part, we set the variance proxy as 2 without loss of generalization.

Appendix D. Proof of Proposition [1](#page-3-0)

Proof [Proof of Proposition [1\]](#page-3-0) We here define $\mathcal{K}^{\mathcal{U}} := \{A_k\}_{k=1}^{K^N}$ as the set of the super arm. Define a MAB instance $\nu_1 \in \mathcal{E}_0$ that $Y_i(Z) = \Delta \mathbf{1}{Z = A_1}$ for all $i \in \mathcal{U}$ and $Z \in \mathcal{K}^{\mathcal{U}}$, where $\Delta \in [0, 1/2]$ will be defined later. We suppose that the noise of all unit $\eta_{i,t}$ follows a $\mathcal{N}(0, 1)$ Gaussian distribution, and therefore the normalized noise of the super arm $(1/N)\sum_{i=1}^{N} \eta_{i,t}$ follows a $\mathcal{N}(0,1/N)$ Gaussian distribution. Hence, we have $1/N \sum_{i\in\mathcal{U}} Y_i(A_1) = \Delta$ and $1/N \sum_{i \in \mathcal{U}} Y_i(A_k) = 0$ for all $k \in [K^N]/1$. This implies in ν_1 , $A_1 = A^*$ is the best arm with potential outcome Δ and $A \neq A_1$ is the sub-optimal arm with potential outcome 0. Due to

$$
\mathcal{R}_{\nu_1}(T,\pi) = \sum_{k=2}^{K^N} \Delta_k \mathbb{E}_{\nu_1,\pi}[\mathcal{N}_{A_k}^T],
$$
\n(12)

where $\mathcal{N}_{A_k}^T$ denotes the number that supper arm A_k is trigger till T and Δ_k denotes the reward gap between super arm A_1 and A_k (i.e., $\Delta_k = (1/N)(\sum_{i \in \mathcal{U}} Y_i(A_1) - Y_i(A_k))).$ Suppose the super arm A_j , $j = \arg \min_{j \in [K^N]/1} \mathbb{E}_{\nu_1, \pi}[\mathcal{N}_{A_j}^T]$, then

$$
\mathbb{E}_{\nu_1,\pi}[\mathcal{N}_{A_j}^T] \le \frac{T}{K^N - 1}.\tag{13}
$$

Besides, we define another $\mathcal{N}(0,1)$ Gaussian MAB instance $\nu_2 \in \mathcal{E}_0$, where $Y_i'(Z) = Y_i(Z) +$ $2\Delta\mathbf{1}{Z = A_j}$ for all $i \in \mathcal{U}$ and $Z \in \mathcal{K}^{\mathcal{U}}$. In ν_2 , A_j is the best arm with potential outcome 2 Δ . Based on the decomposition of the regret [\(12\)](#page-20-3), we have

$$
\mathcal{R}_{\nu_1}(T,\pi) \ge \mathcal{P}_{\nu_1,\pi}\left(\mathcal{N}_{A_1}^T \le T/2\right)\frac{\Delta T}{2}, \quad \text{and} \quad \mathcal{R}_{\nu_2}(T,\pi) \ge \mathcal{P}_{\nu_2,\pi}\left(\mathcal{N}_{A_1}^T \ge T/2\right)\frac{\Delta T}{2}.\tag{14}
$$

Let $\mathcal{P}_{\nu_1,\pi}$ and $\mathcal{P}_{\nu_2,\pi}$ denote the probability measures on the canonical bandit model induced by the T-round interaction between π and ν_1 , and π and ν_2 , respectively. Finally, we have

$$
\mathcal{R}_{\nu_1}(T,\pi) + \mathcal{R}_{\nu_2}(T,\pi)
$$
\n
$$
\geq \left(\mathcal{P}_{\nu_1,\pi}(T_1 \geq T/2) + \mathcal{P}_{\nu_2,\pi}(T_1 \leq T/2)\right) \frac{\Delta T}{2}
$$
\n
$$
\geq \exp\left(-D(\mathcal{P}_{\nu_1,\pi}, \mathcal{P}_{\nu_2,\pi})\right) \frac{\Delta T}{4}
$$
\n
$$
\geq \exp\left(-\mathbb{E}_{\nu_1,\pi}[\mathcal{N}_{A_j}^T]D\left(\mathcal{N}(0,1/N), \mathcal{N}(2\Delta,1/N)\right)\right) \frac{\Delta T}{4}
$$
\n
$$
\geq \exp\left(-\mathbb{E}_{\nu_1,\pi}[\mathcal{N}_{A_j}^T]2N\Delta^2\right) \frac{\Delta T}{4}
$$
\n
$$
\geq \exp\left(-\frac{2TN\Delta^2}{K^N - 1}\right) \frac{\Delta T}{4},
$$
\n(15)

where the second inequality is owing to the Bretagnolle–Huber inequality, the third inequality is due to the Lemma 15.1 in Lattimore and Szepesvári (2020) , the forth inequality is due to the definition of the noise distribution (i.e., $\mathcal{N}(0, 1/N)$) of the super arm. Finally, select $\Delta = \sqrt{\frac{K^N - 1}{4TN}} \wedge \frac{1}{2}$ $\frac{1}{2}$, based on the above result, we have $(i = 1 \text{ or } 2)$

$$
\mathcal{R}_{\nu_i}(T,\pi) \ge \begin{cases} e^{-1/2} \frac{T}{8\sqrt{N}}, \text{ when } T \le K^N\\ \frac{e^{-1/2}}{4} \sqrt{\frac{(K^N - 1)T}{N}}, \text{ when } T \ge K^N. \end{cases}
$$
(16)

ш

Appendix E. Proof of Theorem [5](#page-6-5)

Proof [Proof of Theorem [5\]](#page-6-5) We consider two kinds of MAB instances for a fixed policy π and a fixed strategy of constructing an ATE estimator. For the first one, we denote it as $r_{i,t}(A_t) = f_i(A_t) + \eta_{i,t}$. Here we let $Y_i(A_t) := f_i(A_t) \in [0,1], r_{i,t}(A_t) \in \{-1,1\}$. It means $r_{i,t}(A_t) = \text{Rad}(\frac{1-f_i(A_t)}{2}, \frac{1+f_i(A_t)}{2})$ $\frac{i(A_t)}{2}$). For each feasible cluster-wise super exposure arm $S, S' \in \mathcal{U}_{\mathcal{E}}$, recall that

$$
\tilde{Y}_i(s) = \sum_{A_t \in \mathcal{K}^{\mathcal{U}}} f_i(A_t) \mathbb{P}_{\pi}(A_t | \mathbf{S}(i, A_t, \mathbb{H}) = s).
$$
\n(17)

The difference of treatment effect of S, S' could be represented by $\Delta_1 := \frac{1}{N} \sum_{i \in \mathcal{U}} (\tilde{Y}_i(S) \tilde{Y}_i(S')$, which is (let $S_t := \{ \mathbf{S}(i, A_t, \mathbb{H}) \}_{i \in [N]}$)

$$
\Delta_1 = \frac{1}{N} \sum_{i \in \mathcal{U}} \sum_{A_t \in \mathcal{K}^{\mathcal{U}}} f_i(A_t) \big(\mathbb{P}_{\pi}(A_t | \mathbf{S}_t = S) - \mathbb{P}_{\pi}(A_t | \mathbf{S}_t = S') \big).
$$
(18)

Without loss of generalization, we select the feasible super arm to set $\Delta_1 \leq 0$. Namely, we choose S' as the best arm. We then construct a new MAB instance and hope to get a different ATE value. We define it as $r'_{i,t}(A_t)$. We establish $(\alpha \in [0,1]$ is arbitrary):

$$
r'_{i}(A_{t}) := \begin{cases} r_{i}(A_{t}) & \forall A_{t} \text{ satisfying } \mathbb{P}_{\pi}(A_{t}|\mathbf{S}_{t} = S) = 0. \\ \text{Rad}(\frac{1 - f_{i}(A_{t}) + \alpha}{2}, \frac{1 + f_{i}(A_{t}) - \alpha}{2}) & \forall A_{t} \text{ satisfying } \mathbb{P}_{\pi}(A_{t}|\mathbf{S}_{t} = S) > 0. \end{cases}
$$
(19)

Remind that following (18) , the ATE between super arm S, S' is

$$
\Delta_2 := \Delta_{2,1} + \Delta_{2,2}, \text{ where}
$$
\n
$$
\Delta_{2,1} = \frac{1}{N} \sum_{i \in \mathcal{U}} \sum_{A_t \in \mathcal{K}^{\mathcal{U}}} (f_i(A_t) - \alpha_t)(\mathbb{P}_{\pi}(A_t | \mathbf{S}_t = S) - \mathbb{P}_{\pi}(A_t | \mathbf{S}_t = S')) \mathbb{1}(\mathbb{P}_{\pi}(A_t | \mathbf{S}_t = S) > 0),
$$
\n
$$
\Delta_{2,2} = \frac{1}{N} \sum_{i \in \mathcal{U}} \sum_{A_t \in \mathcal{K}^{\mathcal{U}}} f_i(A_t)(\mathbb{P}_{\pi}(A_t | \mathbf{S}_t = S) - \mathbb{P}_{\pi}(A_t | \mathbf{S}_t = S')) \mathbb{1}(\mathbb{P}_{\pi}(A_t | \mathbf{S}_t = S) = 0).
$$
\n(20)

Hence, it implies that the ATEs in these two MAB instances, respectively, contain a difference

$$
\Delta_2 - \Delta_1
$$
\n
$$
= \frac{1}{N} \sum_{i \in \mathcal{U}} \sum_{A_t \in \mathcal{K}^{\mathcal{U}}} -\alpha_t (\mathbb{P}_{\pi}(A_t | \mathbf{S}_t = S) - \mathbb{P}_{\pi}(A_t | \mathbf{S}_t = S')) \mathbb{1} (\mathbb{P}_{\pi}(A_t | \mathbf{S}_t = S) > 0)
$$
\n
$$
= \frac{1}{N} \sum_{i \in \mathcal{U}} \sum_{A_t \in \mathcal{K}^{\mathcal{U}}} -\alpha_t \mathbb{P}_{\pi}(A_t | \mathbf{S}_t = S) \mathbb{1} (\mathbb{P}_{\pi}(A_t | \mathbf{S}_t = S) > 0)
$$
\n
$$
= \frac{1}{N} \sum_{i \in \mathcal{U}} \sum_{A_t \in \mathcal{K}^{\mathcal{U}}} -\alpha_t \mathbb{P}_{\pi}(A_t | \mathbf{S}_t = S) = -\alpha_t := 2\phi_{\alpha}(t) < 0.
$$
\n
$$
(21)
$$

Naturally, our setting leads to $0 \geq \Delta_1 \geq \Delta_2$ when $f_i(A_t) \geq 0$. The second equality is because $\mathbb{P}_{\pi}(A_t|\mathbf{S}_t=S)\mathbb{P}_{\pi}(A_t|\mathbf{S}_t=S')=0$ when $S \neq S'$.

In this sense, we consider a given estimate strategy, which is summarized by $\{\hat{\Delta}_t\}_{t\in[T]}$. We define a minimum test $\psi(\hat{\Delta}_t) = \arg \min_{i=1,2} |\hat{\Delta}_t - \Delta_i|$. Naturally, it implies that $\psi(\hat{\Delta}_t) \neq$ $i, i \in \{1, 2\}$ is a sufficient condition of $|\hat{\Delta}_t - \hat{\Delta}_i| \ge \phi_\alpha(t)$. As a consequence,

$$
\inf_{\hat{\Delta}_t} \max_{\nu \in \mathcal{E}_0} \mathbb{P}_{\nu} \left(|\hat{\Delta}_t - \Delta_{\nu}| \ge \phi_{\alpha}(t) \right) \ge \inf_{\hat{\Delta}_t} \max_{i \in \{1,2\}} \mathbb{P}_{\nu_i} \left(|\hat{\Delta}_t - \Delta_i| \ge \phi_{\alpha}(t) \right) \n\ge \inf_{\hat{\Delta}_t} \max_{i \in \{1,2\}} \mathbb{P}_{\nu_i} \left(\psi(\hat{\Delta}_t) \ne i \right) \n\ge \inf_{\psi} \max_{i \in \{1,2\}} \mathbb{P}_{\nu_i} (\psi \ne i).
$$
\n(22)

Zhang∗ Wang∗

Here, the probability space is constructed on the exposure arm $\{S(i, A, \mathbb{H})\}_{i\in\mathcal{U}}$ in each time period t , and the observed exposure reward. We use the technique in min-max bound. Notice that the original feasible region of MAB instances as \mathcal{E}_0 ;

We get

RHS of (22)
$$
\geq \inf_{\psi} \max_{i \in \{1,2\}} \mathbb{P}_{\nu_i}(\psi \neq i)
$$

\n
$$
\geq \frac{1}{2} \inf_{\psi} (\mathbb{P}_{\nu_1}(\psi = 2) + \mathbb{P}_{\nu_2}(\psi = 1))
$$
\n
$$
= \frac{1}{2} (1 - TV(\mathbb{P}_{\nu_1}, \mathbb{P}_{\nu_2}))
$$
\n
$$
\geq \frac{1}{2} \left[1 - \sqrt{\frac{1}{2}KL(\mathbb{P}_{\nu_2}, \mathbb{P}_{\nu_1})} \right].
$$
\n(23)

We aim to provide an upper bound of KL divergence $KL(\mathbb{P}_{\nu_2}, \mathbb{P}_{\nu_1})$, inspired by the divergence decomposition:

$$
KL(\mathbb{P}_{\nu_2}, \mathbb{P}_{\nu_1}) = \mathbb{E}_{\nu_2} \left[\log \left(\frac{d \mathbb{P}_{\nu_2}}{d \mathbb{P}_{\nu_1}} \right) \right]. \tag{24}
$$

For any instance, ν , the density function of the series is denoted as (we denote X_t as the observed exposure reward)

$$
p_{\nu}(S_1, X_1, \dots, S_T, X_T) = \prod_{t=1}^T \pi_t(S_t \mid S_1, X_N, \dots, S_{t-1}, X_{t-1}) p_{\nu, S_t}(X_t).
$$
 (25)

Hence [\(24\)](#page-23-0) can be transformed as

KL(
$$
\mathbb{P}_{\nu_2}, \mathbb{P}_{\nu_1}
$$
) = $\sum_{t \in [T]} \mathbb{E}_{\nu_2} log\left(\frac{p_{\nu_2, S_t}(X_t)}{p_{\nu_1, S_t}(X_t)}\right)$
\n= $\sum_{t \in [T]} \mathbb{E}_{\nu_2} \left[\mathbb{E}_{\nu_2} log\left(\frac{p_{\nu_2, S_t}(X_t)}{p_{\nu_1, S_t}(X_t)}\right) | S_t\right]$
\n= $\sum_{t \in [T]} \mathbb{E}_{\nu_2} \left[\text{KL}(\mathbb{P}_{\nu_2}(S_t), \mathbb{P}_{\nu_1}(S_t))\right]$
\n= $\mathbb{E}_{\nu_2} [T(S)] \text{KL}(\mathbb{P}_{\nu_2}(S), \mathbb{P}_{\nu_1}(S))$
\n= $\mathbb{E}_{\nu_2} [T(S)] \text{KL}(\mathbb{P}_{\nu_2}(S), \mathbb{P}_{\nu_1}(S))$.

The last equation is derived from the construction in [\(19\)](#page-22-2). We aim to compute $KL(\mathbb{P}_{\nu_2}(S), \mathbb{P}_{\nu_1}(S))$:

$$
KL(\mathbb{P}_{\nu_2}(S), \mathbb{P}_{\nu_1}(S)) = \int_X p_{\nu_2, S}(X) \log \left(\frac{p_{\nu_2, S}(X)}{p_{\nu_1, S}(X)} \right) dX \le qN\alpha_t^2.
$$
 (27)

Here q is a constant. As a consequence, it implies that (we let the S be the best sub-optimal arm)

$$
KL(\mathbb{P}_{\nu_2}, \mathbb{P}_{\nu_1}) \le qN\alpha_t^2 \mathbb{E}_{\nu_2}[T(S)] \le qN\alpha_t^2 \frac{\mathbb{E}\mathcal{R}_{\nu_2}(T,\pi)}{|\Delta_2|}.
$$
 (28)

The last inequality is due to the definition of regret and the fact that S' is a better supper arm than S . Combined with (22) , (23) , (28) , it achieves that

$$
\inf_{\hat{\Delta}_t} \max_{\nu \in \mathcal{E}_0} \mathbb{P}_{\nu} \left(|\hat{\Delta}_t - \Delta_\nu| \ge \phi_\alpha(t) \right) \ge \frac{1}{2} \left[1 - \sqrt{\frac{1}{2} q N \alpha_t^2 \frac{\mathcal{R}_{\nu_2}(t, \pi)}{|\Delta_2|}} \right]. \tag{29}
$$

Such a conclusion could be naturally extended to the case where $d_s^C \geq 2$. Namely, the number of super arms is more extensive than 2 when α_t approaches to 0:

$$
\inf_{\hat{\Delta}_t} \max_{\nu \in \mathcal{E}_0} \mathbb{P}_{\nu} \left(\max_{i,j \in \mathcal{U}_{\mathcal{E}}} |\hat{\Delta}_t^{(i,j)} - \Delta_{\nu}^{(i,j)}| \ge \phi_\alpha(t) \right) \ge \frac{1}{2} \left[1 - \sqrt{\frac{1}{2} q N \alpha_t^2 \frac{\mathcal{R}_{\nu_2, S}(t, \pi)}{|\mathcal{U}_{\mathcal{E}}||\Delta_{2, S}|}} \right].
$$
 (30)

In this process, we use $\hat{\Delta}^{(i,j)} := \{ \hat{\Delta}_t^{(i,j)} \}$ $\{\hat{\Delta}^{(i,j)}\}_{t\geq 1}, \hat{\Delta} := \{\hat{\Delta}^{(i,j)}\}_{S_i,S_j\in\mathcal{U}_{\mathcal{E}}}$. Here v_2 could represent any instance in the class of construction in [\(19\)](#page-22-2) with the choice of the suboptimal arm S, and the above inequality corresponds to the specific selection of $\alpha \in [0,1]$. On this basis, we derive the final trade-off as follows:

$$
\inf_{\hat{\Delta}_t} \max_{\nu \in \mathcal{E}_0} \mathbb{E}_{\nu} \left(\max_{i,j \in \mathcal{U}_{\mathcal{E}}} |\hat{\Delta}_t^{(i,j)} - \Delta_{\nu}^{(i,j)}| \ge \phi_{\alpha}(t) \right)
$$
\n
$$
\ge \phi_{\alpha}(t) \inf_{\hat{\Delta}_t} \max_{\nu \in \mathcal{E}_0} \mathbb{P}_{\nu} \left(\max_{i,j \in \mathcal{U}_{\mathcal{E}}} |\hat{\Delta}_t^{(i,j)} - \Delta_{\nu}^{(i,j)}| \right)
$$
\n
$$
\ge \frac{\phi_{\alpha}(t)}{2} \left[1 - \alpha_t \sqrt{\frac{1}{2} q N \frac{\mathcal{R}_{\nu_2, S}(t, \pi)}{|\mathcal{U}_{\mathcal{E}}||\Delta_{2, S}|}} \right].
$$
\n(31)

As a consequence,

$$
\inf_{\hat{\Delta}_t} \max_{\nu \in \mathcal{E}_0} \mathbb{E}_{\nu} \left(\max_{i,j \in \mathcal{U}_{\mathcal{E}}} |\hat{\Delta}_t^{(i,j)} - \Delta_{\nu}^{(i,j)}| \ge \phi_\alpha(t) \right) \sqrt{\mathcal{R}_{\nu}(t,\pi)}
$$
\n
$$
\ge \inf_{\hat{\Delta}_t} \max_{\nu \in \mathcal{E}_0} \frac{\phi_\alpha(t)}{2} \left[1 - \sqrt{\frac{1}{2} q \alpha_t^2 N \frac{\mathcal{R}_{\nu_2,S}(t,\pi)}{|\mathcal{U}_{\mathcal{E}}||\Delta_{2,S}|}} \right] \sqrt{\mathcal{R}_{\nu_2,S}(t,\pi)}.
$$
\n(32)

Due to the sqrt-term spans $[0, +\infty]$ with $\alpha \in [0, 1]$, hence we could set $q\alpha_t^2 N \frac{\mathcal{R}_{\nu_2, S}(t, \pi)}{|\mathcal{U}_{\mathcal{E}}||\Delta_{2, S}|} =$ 1 $\frac{1}{2}, \alpha = \alpha_t$, then,

• when $T \geq |\mathcal{U}_{\mathcal{E}}|$, it leads to

$$
(32) = \inf_{\hat{\Delta}_t} \max_{\nu \in \mathcal{E}_0} \frac{\phi_{\alpha_t}(t)}{4} \sqrt{\frac{|\mathcal{U}_{\mathcal{E}}| |\Delta_{2,S}|}{-2Nq\alpha_t^2}} = \Omega_{T,N}(\sqrt{\frac{|\mathcal{U}_{\mathcal{E}}|}{N}}) = \Omega(\sqrt{|\mathcal{U}_{\mathcal{E}}|}).
$$
(33)

• when $T \leq |\mathcal{U}_{\mathcal{E}}|$, notice that $\mathcal{R}_{\nu_2,S}(t,\pi) = O(T) = O(|\mathcal{U}_{\mathcal{E}}|)$, it leads to $\alpha_t = \Omega(\frac{1}{\sqrt{2}})$ $\frac{1}{\overline{N}}),$ then

(32) =
$$
\inf_{\Delta_t} \max_{\nu \in \mathcal{E}_0} \frac{\phi_{\alpha_t}(t)}{4} \sqrt{\frac{T}{\sqrt{N}}} = \Omega_{T,N}(\frac{1}{\sqrt{N}}\sqrt{\frac{T}{\sqrt{N}}}) = \Omega(\sqrt{T}).
$$
 (34)

 \blacksquare

Theorem [6](#page-7-1) also follows. Q.E.D.

Appendix F. Proof of Theorem [6](#page-7-1)

Proof [Proof of Theorem [6\]](#page-7-1) We prove it via contradiction. On the one hand, suppose that the MAB pair $\{\pi, \hat{\Delta}\}\$ satisfies $\max_{\nu \in \mathcal{E}_0} \left(\sqrt{\mathcal{R}_{\nu}(T,\pi)} e_{\nu}(T,\hat{\Delta})\right) = \tilde{O}(\sqrt{|\mathcal{U}_{\mathcal{E}}|})$. If it is not Pareto-optimal, it is equivalent to claim that there is another pair $\{\pi', \hat{\Delta'}\}$ to dominate $\{\pi, \hat{\Delta}\}\$. In this sense, according to Theorem [5,](#page-6-5) there exists an instance ν' such that $\sqrt{\mathcal{R}_{\nu'}(T,\pi')}e_{\nu'}(T,\hat{\Delta}') = \Omega(\sqrt{|\mathcal{U}_{\mathcal{E}}|})$. Moreover, according to the definition of Paretodominance, there further exists another instance ν'' , such that $\forall \otimes \in \{K, T\}, \sqrt{|\mathcal{U}_{\mathcal{E}}|} \prec_{\otimes}$ $\sqrt{\mathcal{R}_{\nu''(T,\pi)}}e_{\nu''(T,\hat{\Delta})}$. It is a contradiction.

Appendix G. Proof of Theorems in Section [4](#page-8-0)

G.1. Proof of Theorem [7](#page-8-1)

Proof [Proof of Theorem [7\]](#page-8-1) Based on the design of the Alg [1,](#page-10-2) in the first phase, we have $\mathcal{N}_S^{T_1} \geq \lfloor \frac{T_1}{|\mathcal{U}_{\mathcal{E}}|} \rfloor \geq 1$ for all $S \in \mathcal{U}_{\mathcal{E}}$. Define the good event as $\mathcal{E}_{T_1} := \left\{\hat{R}_{T_1}(S) - \hat{R}_{T_1}(S)\right\}$ 1 $\frac{1}{N}\sum_{i\in\mathcal{U}}\tilde{Y}_i(S)\leq \sqrt{4\log(T_1|\mathcal{U}_{\mathcal{E}}|)/\mathcal{N}_{S}^{T_1}}$, $\forall S\in\mathcal{U}_{\mathcal{E}}\}$ and its complement as $\mathcal{E}_{T_1}^c$. Based on the previous discussion, the sub Gaussian parameter of any exposure super arm's reward distribution is at most 2, then based on the Hoffeding inequality (Lemma [16\)](#page-34-1), we have for a exposure super arm $S \in \mathcal{U}_{\mathcal{E}}$:

$$
\mathcal{P}\left(\hat{R}_t(S) - \frac{1}{N} \sum_{i \in \mathcal{U}} \tilde{Y}_i(S) > a\right) \le e^{-\frac{N_S^t a^2}{4}},\tag{35}
$$

 \blacksquare

substituting $t = T_1$ and $a = \sqrt{\frac{9 \log(T_1|\mathcal{U}_{\mathcal{E}}|)}{n^{\mathcal{F}_1}}}$ $\mathcal{N}^{T_1}_S$ into [\(35\)](#page-25-2) and we can derive

$$
\mathcal{P}\left(\hat{R}_{T_1}(S) - \frac{1}{N} \sum_{i \in \mathcal{U}} \tilde{Y}_i(S) > \sqrt{\frac{4\log\left(T_1|\mathcal{U}_{\mathcal{E}}|\right)}{\mathcal{N}_S^{T_1}}}\right) \le \frac{1}{T_1|\mathcal{U}_{\mathcal{E}}|}.\tag{36}
$$

Utilize the union bound, there is

$$
\mathcal{P}(\mathcal{E}_{T_1}^c) \leq \sum_{S \in \mathcal{U}_{\mathcal{E}}} \mathcal{P}\left(\left\{\hat{R}_{T_1}(S) - \frac{1}{N} \sum_{i \in \mathcal{U}} \tilde{Y}_i(S) > \sqrt{\frac{4\log\left(T_1|\mathcal{U}_{\mathcal{E}}|\right)}{\mathcal{N}_{S}^t}}\right\}\right)
$$
\n
$$
\leq \sum_{S \in \mathcal{U}_{\mathcal{E}}} \frac{1}{T_1|\mathcal{U}_{\mathcal{E}}|} \leq \frac{1}{T_1},\tag{37}
$$

and $\mathcal{P}(\mathcal{E}_{T_1}) \geq 1 - \frac{1}{T_1}$ $\frac{1}{T_1}$. Therefore, for all $S_i, S_j \in \mathcal{U}_{\mathcal{E}}$, we have:

$$
\mathbb{E}\left[\left|\Delta^{(i,j)}-\hat{\Delta}^{(i,j)}_{T}\right|\right] \n\leq \mathcal{P}(\mathcal{E}_{T_1})\mathbb{E}\left[\left|\Delta^{(i,j)}-\hat{\Delta}^{(i,j)}_{T}\right|\Big|\mathcal{E}_{T_1}\right] + \mathcal{P}(\mathcal{E}_{T_1}^c)\mathbb{E}\left[\left|\Delta^{(i,j)}-\hat{\Delta}^{(i,j)}_{T}\right|\Big|\mathcal{E}_{T_1}\right] \n\leq \mathcal{P}(\mathcal{E}_{T_1})\mathbb{E}\left[\left|\hat{R}_t(S)-\frac{1}{N}\sum_{s\in\mathcal{U}}\tilde{Y}_s(S_i)\right|+\left|\hat{R}_t(S)-\frac{1}{N}\sum_{s\in\mathcal{U}}\tilde{Y}_s(S_j)\right|\Big|\mathcal{E}_{T_1}\right] + \frac{1}{T_1} \n\leq 2\sqrt{\frac{4\log(10|\mathcal{U}_{\mathcal{E}}|)}{|\frac{T_1}{|\mathcal{U}_{\mathcal{E}}|}} + \frac{1}{T_1}
$$
\n
$$
= \tilde{O}\left(\sqrt{\frac{|\mathcal{U}_{\mathcal{E}}|}{T_1}}\right),
$$
\n(38)

where the second inequality is owing to the triangle inequality and $\Delta^{(i,j)}$ and $\hat{\Delta}^{(i,j)}_T \in [0,1],$ and the last inequality is owing to $\mathcal{N}_S^{T_1} \geq \lfloor \frac{T_1}{|\mathcal{U}_{\mathcal{E}}|} \rfloor$. Here we finish the proof of Theorem [7.](#page-8-1)

G.2. Proof of Theorem [8](#page-8-2)

In this section, we will first provide an instance dependent regret upper bound (in the following Lemma [11\)](#page-26-0), then, we will provide an instance-independent regret upper bound based on the instance-dependent one.

Lemma 11 (Instance-dependent regret) Given any instance that satisfies Condition 1. The regret of the UCB-TS can be upper bounded as follows

$$
\mathcal{R}(T,\pi) = O\left(\sum_{S_i \neq S^*,\Delta^i > 0} \frac{\log(T)}{\Delta^i} + T_1\right).
$$
\n(39)

Proof [Proof of Lemma [11\]](#page-26-0) Define $\mathcal{N}_S^{(t,T)} = \sum_{t=t}^T \mathbf{1}\{S_t = S\}$. We first need to decompose and bound the regret as

$$
\mathcal{R}(T,\pi) = \frac{T}{N} \sum_{i \in \mathcal{U}} \tilde{Y}_i(S^*) - \mathbb{E}_{\pi} \Big[\sum_{t=1}^T \sum_{i \in \mathcal{U}} \tilde{r}_{i,t}(S_t) \Big],
$$
\n
$$
\leq \sum_{\substack{S_i \neq S^*, \Delta^i > 0}} \Delta^i \mathbb{E}_{\pi} \Big[\mathcal{N}_{S_i}^{(T_1+1,T)} \Big] + \Big[\frac{T_1}{\mathcal{U}_{\mathcal{E}}} \Big] \sum_{S_i \neq S^*} \Delta^i
$$
\nregret in second phase
\n
$$
= \sum_{S_i \neq S^*, \Delta^i > 0} \Big(\Delta^i \mathbb{E}_{\pi} \Big[\mathcal{N}_{S_i}^{(T_1+1,T)} \Big| \mathcal{E}_i \Big] + \Delta^i \mathbb{E}_{\pi} \Big[\mathcal{N}_{S_i}^{(T_1+1,T)} \Big| \mathcal{E}_i \Big] \Big) + \Big[\frac{T_1}{\mathcal{U}_{\mathcal{E}}} \Big] \sum_{S_i \neq S^*} \Delta^i
$$
\n
$$
\leq \sum_{S_i \neq S^*, \Delta^i > 0} \Delta^i \mathbb{E}_{\pi} \Big[\mathcal{N}_{S_i}^{(T_1+1,T)} \Big| \mathcal{E}_i \Big] + T^2 \delta + \Big[\frac{T_1}{\mathcal{U}_{\mathcal{E}}} \Big] \sum_{S_i \neq S^*} \Delta^i.
$$
\n(40)

Besides, we want to show that under the event \mathcal{E}_i , we have $\mathcal{N}_{S_i}^{(T_1+1,T)}$ $S_i^{(1+1,1)} \leq \mathcal{T}_i$. If $T_1 = T$, then this inequality trivially holds. If $T_1 < T$, suppose $\mathcal{N}_{S_i}^{(T_1+1,T)}$ $\mathcal{T}_{S_i}^{(1+1,1)} > \mathcal{T}_i$, then, there exists a time $t_i \in [T_1 + 1, T]$, such that $S_{t_i} = S_i$ (S_i is pulled in round t_i), and $\mathcal{N}_{S_i}^{(t_i, T)}$ $S_i^{(i_i,1)} = \mathcal{T}_i + 1$. Based on the exploration strategy in Algorithm [1,](#page-10-2) we have $\text{UCB}_{t_i-1,S_i} \geq \text{UCB}_{t_i-1,S^*}$. However, based on the definition of the event \mathcal{E}_i , we have

$$
\begin{aligned} \text{UCB}_{t_i-1,S^*} &\geq \frac{1}{N} \sum_{i' \in \mathcal{U}} \tilde{Y}_{i'}(S^*) \\ &> \hat{R}_{\mathcal{T}_i,S_i} + \sqrt{\frac{18 \log(1/\delta)}{\mathcal{T}_i}} \\ &= \hat{R}_{t_i-1}(S_i) + \sqrt{\frac{18 \log(1/\delta)}{\mathcal{N}_{S_i}^{t_i-1}}} \\ &= \text{UCB}_{t_i-1,S_i}, \end{aligned}
$$

which contradicts to the previous assumption. Therefore, under the event \mathcal{E}_i , we have $\mathcal{N}_{S_k}^T \leq \mathcal{T}_k$. Substituting this result and $\delta = 1/T^2$ into [\(40\)](#page-26-1), we have

$$
\mathcal{R}(T,\pi) \leq \sum_{S_i \neq S^*,\Delta^i>0} \Delta^i \mathbb{E}_{\pi} \Big[\mathcal{N}_{S_i}^{(T_1+1,T)} \Big| \mathcal{E}_i \Big] + T^2 \delta + \Big[\frac{T_1}{\mathcal{U}_{\mathcal{E}}} \Big] \sum_{S_i \neq S^*} \Delta^i
$$

\n
$$
\leq \sum_{S_i \neq S^*,\Delta^i>0} \Delta^i \mathcal{T}_i + 1 + \Big[\frac{T_1}{\mathcal{U}_{\mathcal{E}}} \Big] \sum_{S_i \neq S^*} \Delta^i
$$

\n
$$
\leq \sum_{S_i \neq S^*,\Delta^i>0} \frac{144 \log(T)}{\Delta^i} + 1 + \Big[\frac{T_1}{\mathcal{U}_{\mathcal{E}}} \Big] \sum_{S_i \neq S^*} \Delta^i
$$

\n
$$
= O\Big(\sum_{S_i \neq S^*,\Delta^i>0} \frac{\log(T)}{\Delta^i} + \Big[\frac{T_1}{\mathcal{U}_{\mathcal{E}}} \Big] \sum_{S_i \neq S^*} \Delta^i \Big).
$$

\n(41)

 \blacksquare

Here we finish the proof of Lemma [11.](#page-26-0)

Lemma 12 For all i satisfies $S_i \neq S^*$ and $\Delta^i > 0$, define the good event as:

$$
\mathcal{E}_i = \bigg\{\frac{1}{N}\sum_{i'\in\mathcal{U}}\tilde{Y}_{i'}(S^*) \leq \textit{UCB}_{t,S^*}, \ \forall t\in[T_1+1,T]\bigg\} \cap \bigg\{\hat{R}_{\mathcal{T}_i,S_i} + \sqrt{\frac{18\log\left(\frac{1}{\delta}\right)}{\mathcal{T}_i}} \leq \frac{1}{N}\sum_{i'\in\mathcal{U}}\tilde{Y}_{i'}(S^*)\bigg\},
$$

where $\mathcal{T}_i = \frac{72 \log(1/\delta)}{(\Delta i)^2}$ $\frac{\log(1/\delta)}{(\Delta^i)^2}$ and we utilize $\hat{R}_{\mathcal{T}_i,S_i}$ to represent $\hat{R}_t(S_i)$ when $\mathcal{N}^t_{S_i} = \mathcal{T}_i$. We have $\mathbb{P}(\mathcal{E}_i) \geq 1 - (T - T_1 + 1)\delta.$

Proof [Proof of Lemma [12\]](#page-27-0) Define the complement of \mathcal{E}_i as

$$
\mathcal{E}_{i}^{c} = \left\{ \frac{1}{N} \sum_{i' \in \mathcal{U}} \tilde{Y}_{i'}(S^*) > \mathrm{UCB}_{t}^*, \ \exists t \in [T_1 + 1, T] \right\} \cup \left\{ \hat{R}_{\mathcal{T}_{i}, S_{i}} + \sqrt{\frac{18 \log\left(\frac{1}{\delta}\right)}{\mathcal{T}_{i}}} > \frac{1}{N} \sum_{i' \in \mathcal{U}} \tilde{Y}_{i'}(S^*) \right\}.
$$

Based on the union bound, we have

$$
\mathcal{P}(\mathcal{E}_{i}^{c}) \leq \mathcal{P}\left(\left\{\frac{1}{N}\sum_{i'\in\mathcal{U}}\tilde{Y}_{i'}(S^{*})\geq \text{UCB}_{t,S^{*}},\ \exists t\in[T_{1}+1,T]\right\}\right) \n+ \mathcal{P}\left(\left\{\hat{R}_{\mathcal{T}_{i},S_{i}}+\sqrt{\frac{18\log\left(\frac{1}{\delta}\right)}{\mathcal{T}_{i}}}\geq \frac{1}{N}\sum_{i'\in\mathcal{U}}\tilde{Y}_{i'}(S^{*})\right\}\right) \n\leq \sum_{t=T_{1}+1}^{T} \mathcal{P}\left(\left\{\frac{1}{N}\sum_{i'\in\mathcal{U}}\tilde{Y}_{i'}(S^{*})\geq \text{UCB}_{t,S^{*}}\right\}\right) \n+ \mathcal{P}\left(\left\{\hat{R}_{\mathcal{T}_{i},S_{i}}+\sqrt{\frac{18\log\left(\frac{1}{\delta}\right)}{\mathcal{T}_{i}}}\geq \frac{1}{N}\sum_{i'\in\mathcal{U}}\tilde{Y}_{i'}(S^{*})\right\}\right).
$$
\n(42)

Based on the Hoeffding's inequality, we can bound the first term in [\(42\)](#page-28-0) by:

$$
\sum_{t=T_1+1}^{T} \mathcal{P}\left(\left\{\frac{1}{N}\sum_{i'\in\mathcal{U}}\tilde{Y}_{i'}(S^*)\geq\mathrm{UCB}_{t,S^*}\right\}\right)\leq(T-T_1)\delta.
$$
\n(43)

Besides, we can bound the second term in [\(42\)](#page-28-0) by:

$$
\mathcal{P}\left(\left\{\hat{R}_{\mathcal{T}_i,S_i} + \sqrt{\frac{18\log\left(\frac{1}{\delta}\right)}{\mathcal{T}_i}} \ge \frac{1}{N} \sum_{i' \in \mathcal{U}} \tilde{Y}_{i'}(S^*)\right\}\right)
$$
\n
$$
= \mathcal{P}\left(\left\{\hat{R}_{\mathcal{T}_i,S_i} - \frac{1}{N} \sum_{i' \in \mathcal{U}} \tilde{Y}_{i'}(S_i) \ge \Delta^i - \sqrt{\frac{18\log\left(\frac{1}{\delta}\right)}{\mathcal{T}_i}}\right\}\right)
$$
\n
$$
\le \mathcal{P}\left(\left\{\hat{R}_{\mathcal{T}_i,S_i} - \frac{1}{N} \sum_{i' \in \mathcal{U}} \tilde{Y}_{i'}(S_i) \ge \frac{1}{2}\Delta^i\right\}\right)
$$
\n
$$
\le \exp\left(-\frac{\mathcal{T}_i(\Delta^i)^2}{16}\right)
$$
\n
$$
\le \delta,
$$
\n(44)

where the first and last inequality is owing to the definition of \mathcal{T}_i , and the second inequality is owing to the Hoeffding's inequality. Based on [\(43\)](#page-28-1) and [\(44\)](#page-28-2), we have $P(\mathcal{E}_i) \geq 1-(T-T_1+1)\delta$ for all S_i satisfies $S_i \neq S^*$ and $\Delta^i > 0$. Here we finish the proof of Lemma [12.](#page-27-0) \blacksquare

Now we can prove Theorem [8.](#page-8-2)

Proof [Proof of Theorem [8\]](#page-8-2) In the Proof of Lemma [11,](#page-26-0) we shows that for all $S_i \neq S^*$, Δ^i 0, we have

$$
\mathbb{E}_{\pi} \left[\mathcal{N}_{S_i}^{(T_1+1,T)} \right] \le \frac{144 \log(T)}{\left(\Delta^i\right)^2} + 1. \tag{45}
$$

Algorithm 3 EXP3-Two Stage (EXP3-TS)

Input: arm set \mathcal{A} , unit number N, exposure super arm set $\mathcal{U}_{\mathcal{E}}$, estimator set $\{\hat{R}_0(S) =$ $0\}_{S\in\mathcal{U}_{\mathcal{C}}}$, active super exposure arm set $\mathcal{A}_0 = \mathcal{U}_{\mathcal{E}}$, T_1 , $\alpha = (e-2)(1+2|\mathcal{U}_{\mathcal{E}}|)e^2 \log(2/\delta)$, $\epsilon = \sqrt{\frac{\log(|\mathcal{U}_{\mathcal{E}}|)}{|\mathcal{U}_{\mathcal{E}}|T}}$ $|\mathcal{U}_{\mathcal{E}}|T$ for $t = 1 : T_1$ do $\forall S \in \mathcal{U}_{\mathcal{E}} : \pi_t(S) = \frac{1}{|\mathcal{U}_{\mathcal{E}}|}$ and sample S_t based on π_t Sample S_t based on π_t , implement Sampling(S_t) end for Output $\hat{\Delta}^{(i,j)} = \frac{1}{T}$ $\frac{1}{T_1}\hat{R}_{T_1}(S_i) - \frac{1}{T_1}$ $\frac{1}{T_1}\hat{R}_{T_1}(S_j)$ for any $S_i, S_j \in \mathcal{U}_{\mathcal{E}}, S_i \neq S_j$ $\forall S \in \mathcal{U}_{\mathcal{E}} : \text{set } \hat{R}_{T_1}(S) = 0$ for $t = T_1 + 1 : T$ do $\forall S \in \mathcal{U}_{\mathcal{E}}$: $\pi_t(S) = \frac{\exp(\epsilon \hat{R}_{t-1}(S))}{\sum_{S \in \mathcal{S}_t} \exp(\epsilon \hat{R}_{t-1}(S))}$ Sample S_t based on π_t , implement Sampling(S_t) $\forall S \in \mathcal{U}_{\mathcal{E}}$: set $\hat{R}_t(S) = \hat{R}_{t-1}(S) + 1 - \frac{\mathbf{1}\{S_t = S\}\left(1 - \frac{1}{N}\sum_{i \in \mathcal{U}} \tilde{r}_{i,t}(S_i)\right)}{\pi_t(S)}$ $\pi_t(S)$ end for

Define $\Lambda = 6\sqrt{\frac{|\mathcal{U}_{\mathcal{E}}| \log(T)}{T}}$ $\frac{\log(1)}{T}$, we can decompose the regret as

$$
\mathcal{R}(T,\pi) \leq \sum_{S_i \neq S^*,\Delta^i < \Lambda} \Delta^i \mathbb{E}_{\pi} \left[\mathcal{N}_{S_i}^{(T_1+1,T)} \right] + \sum_{S_i \neq S^*,\Delta^i \geq \Lambda} \Delta^i \mathbb{E}_{\pi} \left[\mathcal{N}_{S_i}^{(T_1+1,T)} \right] + \left[\frac{T_1}{\mathcal{U}_{\mathcal{E}}} \right] \sum_{S_i \neq S^*} \Delta^i
$$
\n
$$
\leq T\Lambda + \sum_{S_i \neq S^*,\Delta^i \geq \Lambda} \left(\frac{144 \log(T)}{\Delta^i} + \Delta^i \right) + \left[\frac{T_1}{\mathcal{U}_{\mathcal{E}}} \right] \sum_{S_i \neq S^*} \Delta^i,
$$
\n
$$
\leq T\Lambda + \frac{144|\mathcal{U}_{\mathcal{E}}| \log(T)}{\Lambda} + \left(1 + \left[\frac{T_1}{\mathcal{U}_{\mathcal{E}}} \right] \right) \sum_{S_i \neq S^*} \Delta^i
$$
\n
$$
\leq 30\sqrt{|\mathcal{U}_{\mathcal{E}}|T \log(T)} + \left(1 + \left[\frac{T_1}{\mathcal{U}_{\mathcal{E}}} \right] \right) \sum_{S_i \neq S^*} \Delta^i
$$
\n
$$
= \tilde{O} \left(\sqrt{|\mathcal{U}_{\mathcal{E}}|T} + \frac{T_1}{|\mathcal{U}_{\mathcal{E}}|} \sum_{S_i \neq S^*} \Delta^i \right).
$$
\n(46)

Here we finish the proof of Theorem [8.](#page-8-2)

Finally, Theorem [9](#page-8-3) naturally follows.

Appendix H. Algorithm for Non-stochastic Setting in [Simchi-Levi and](#page-15-4) [Wang](#page-15-4) [\(2024\)](#page-15-4)

ш

This section introduces our algorithm, EXP3-TS, which operates in two distinct phases. In the first phase, the algorithm uniformly samples exposure super arms from the set $\mathcal{U}_{\mathcal{E}}$. Upon receiving reward feedback, it leverages this data to build unbiased inverse probability weighting (IPW) estimators to estimate the potential outcomes for the super arms. In the second phase, the algorithm applies the EXP3 strategy to minimize regret effectively.

Unbiased estimators for exposure mapping We construct unbiased inverse probability weighting (IPW) estimators to estimate the potential outcome of each *exposure super* arm, i.e.,

$$
\hat{R}_t(S) = \hat{R}_{t-1}(S) + 1 - \frac{\mathbf{1}\{S_t = S\} \left(1 - \frac{1}{N} \sum_{i \in \mathcal{U}} \tilde{r}_{i,t}(S_t)\right)}{\pi_t(S)}.
$$
\n(47)

It is easy to verify that for all $S \in \mathcal{U}_{\mathcal{E}}$, for all $t \in [1, T]$:

$$
\mathbb{E}\bigg[1 - \frac{\mathbf{1}\{S_t = S\}\big(1 - \frac{1}{N}\sum_{i \in \mathcal{U}} \tilde{r}_{i,t}(S_t)\big)}{\pi_t(S)}\bigg|\mathcal{H}_{t-1}\bigg] = \frac{1}{N}\sum_{i \in \mathcal{U}} \tilde{Y}_i(S) + f_t.
$$
 (48)

Using our unbiased estimator $\hat{R}_t(S)$, we can accurately estimate the ATE (which is demon-strated in Theorem [13\)](#page-30-1). We define the martingale sequence as $(M_{t'}^{(i,j)})$ $\{t^{(i,j)}_{t'}\}_{S_i \neq S_j} \}_{t'=1}^t$, where $M_t^{(i,j)} = \hat{R}_t(S_i) - \hat{R}_t(S_j) - \Delta^{(i,j)}$, and it is easy to verify that $\mathbb{E}[M_t^{(i,j)}]$ $t^{(i,j)}_{t}$ $|\mathcal{H}_{t-1}| = 0.$

Appendix I. Proof of Theorem [10](#page-10-0)

Theorem [10](#page-10-0) could be equivalently separated as the following Theorem [13](#page-30-1) and Theorem [14.](#page-31-0)

I.1. Proof of Theorem [13](#page-30-1)

Theorem 13 (Bounding the ATE estimation) Given any instance that satisfy $T \geq$ $\mathcal{T}(T)$ and $|\mathcal{U}_{\mathcal{E}}| \geq 2$. Set $T \geq T_1 \geq \mathcal{T}(T_1)$. For any $S_i \neq S_j$, the ATE estimation error of the EXP3-TS can be upper bounded as follows: $\mathbb{E} \left[|\hat{\Delta}_T^{(i,j)} - \Delta^{(i,j)}| \right] = \tilde{O} \left(\sqrt{\frac{|\mathcal{U}_{\mathcal{E}}|}{T_1}} \right)$ T_1 .

Proof [Proof of Theorem [13\]](#page-30-1) The proof of this lemma is based on the Bernstein Inequality. To utilize it, we first need to upper bound $|M_t^{(i,j)} - M_{t-1}^{(i,j)}|$ $(t^{(i,j)}_{t-1}$, $\forall t \in [T_1]$. It can be expressed as:

$$
\begin{split} & \left| M_t^{(i,j)} - M_{t-1}^{(i,j)} \right| \\ &= \left| \frac{\mathbf{1}\{S_t = S_i\} \left(1 - \frac{1}{N} \sum_{i' \in \mathcal{U}} \tilde{r}_{i',t}(S_t) \right)}{\pi_t(S_i)} - \frac{\mathbf{1}\{S_t = S_j\} \left(1 - \frac{1}{N} \sum_{i' \in \mathcal{U}} \tilde{r}_{i',t}(S_t) \right)}{\pi_t(S_j)} - \Delta^{(j,i)} \right| \\ &\leq \frac{1}{\pi_t(S_i)} + \frac{1}{\pi_t(S_j)} + 1 \\ &= 2|\mathcal{U}_{\mathcal{E}}| + 1, \end{split}
$$

where the first inequality is owing to the $\tilde{r}_{i,t}(\cdot) \in [0,1]$ and $\Delta^{(j,i)} \in [-1,1]$, and the second equality is due to the definition of $\pi_t(S)$ in the first phase. We also need to upper bound the variance of the martingale in the first phase, denoted as $V_t^{(i,j)}$ $\tilde{t}^{(i,j)}$, i.e.,

$$
V_t^{(i,j)} = \sum_{t=1}^{T_1} \mathbb{E}\Bigg[\Bigg(\frac{\mathbf{1}\{S_t = S_j\} \big(1 - \frac{1}{N} \sum_{i' \in \mathcal{U}} \tilde{r}_{i',t}(S_t)\big)}{\pi_t(S_i)} - \frac{\mathbf{1}\{S_t = S_i\} \big(1 - \frac{1}{N} \sum_{i' \in \mathcal{U}} \tilde{r}_{i',t}(S_t)\big)}{\pi_t(S_j)} - \Delta^{(i,j)} \Bigg)^2 \Big| \mathcal{H}_{t-1} \Bigg] \le \sum_{t=1}^{T_1} \Bigg(\frac{1}{\pi_t(S_i)} + \frac{1}{\pi_t(S_j)} \Bigg)
$$

$$
\le 2T_1 |\mathcal{U}_{\mathcal{E}}|.
$$

Based on this fact that $T_1 \geq \frac{(2|\mathcal{U}_{\mathcal{E}}|+1)^2 \log(2T_1|\mathcal{U}_{\mathcal{E}}|^2)}{2(e-2)|\mathcal{U}_{\mathcal{E}}|}$ $\frac{2(e-2)|\mathcal{U}_{\mathcal{E}}|}{2(e-2)|\mathcal{U}_{\mathcal{E}}|}$, we have

$$
\sqrt{\frac{\log(2T_1|\mathcal{U}_{\mathcal{E}}|^2)}{2(e-2)|\mathcal{U}_{\mathcal{E}}|T_1}} \le \frac{1}{2|\mathcal{U}_{\mathcal{E}}|+1},
$$

which implies we can utilize the Bernstein Inequality. By the Bernstein inequality, we have: $\forall t \in [T_1]$, with probability at least $1 - \frac{1}{T_1! \mu}$ $\frac{1}{T_1|\mathcal{U}_{\mathcal{E}}|^2}$, there is

$$
|M_t^{(i,j)}| \le 2\sqrt{2(e-2)|\mathcal{U}_{\mathcal{E}}|T_1\log(2T_1|\mathcal{U}_{\mathcal{E}}|^2)}.
$$

Dividing both sides by T_1 , based on the definition of the martingale $M_t^{(i,j)}$ $t^{(i,j)}$ and the ATE estimator $\hat{\Delta}^{(i,j)}$, we have:

$$
\left|\Delta^{(i,j)} - \hat{\Delta}_T^{(i,j)}\right| \le 2\sqrt{\frac{4(e-2)|\mathcal{U}_{\mathcal{E}}|\log\left(2T_1|\mathcal{U}_{\mathcal{E}}|\right)}{T_1}}.\tag{49}
$$

Define the good event as $\mathcal{E}_{T_1} := \Bigg\{ \big| \Delta^{(i,j)} - \hat{\Delta}_T^{(i,j)} \big|$ $\left| \frac{\langle i,j\rangle}{T} \right| \leq 2 \sqrt{\frac{4(e-2)|\mathcal{U}_{\mathcal{E}}|\log(2T_1|\mathcal{U}_{\mathcal{E}}|)}{T_1}}$ $\frac{|\log(2T_1|\mathcal{U}_{\mathcal{E}}|)}{T_1}$, $\forall S_i \neq S_j$. By applying the union bound, it is easy to know that

$$
\mathcal{P}(\mathcal{E}_{T_1}) \ge 1 - \frac{1}{T_1}.\tag{50}
$$

 \blacksquare

Based on the above result, for any $S_i \neq S_j$, we have

$$
\mathbb{E}\left[\left|\hat{\Delta}_{T}^{(i,j)} - \Delta^{(i,j)}\right|\right] \leq \mathcal{P}(\mathcal{E}_{T_1})\mathbb{E}\left[\left|\Delta^{(i,j)} - \hat{\Delta}_{T}^{(i,j)}\right|\Big|\mathcal{E}_{T_1}\right] + \mathcal{P}(\mathcal{E}_{T_1}^c)\mathbb{E}\left[\left|\Delta^{(i,j)} - \hat{\Delta}_{T}^{(i,j)}\right|\Big|\mathcal{E}_{T_1}\right]
$$
\n
$$
\leq 2\sqrt{\frac{4(e-2)|\mathcal{U}_{\mathcal{E}}|\log(2T_1|\mathcal{U}_{\mathcal{E}}|)}{T_1}} + \frac{1}{T_1}
$$
\n
$$
= \tilde{O}\left(\sqrt{\frac{|\mathcal{U}_{\mathcal{E}}|}{T_1}}\right).
$$
\n(51)

Here we finish the proof of Theorem [13.](#page-30-1)

Theorem 14 (Regret upper bound) Given any instance that satisfy $T \geq \mathcal{T}(T)$ and $|\mathcal{U}_{\mathcal{E}}| \geq 2$. The regret of EXP3-TS can be upper bounded by $\mathcal{R}(T,\pi) = \tilde{O}(\sqrt{|\mathcal{U}_{\mathcal{E}}|T} + T_1)$.

I.2. Proof of Theorem [14](#page-31-0)

Proof [Proof of Theorem [14\]](#page-31-0) Define $R(t, j) = \frac{1}{N} \sum_{i' \in \mathcal{U}} (\tilde{Y}_{i'}(S_j) + f_t)$ as the potential outcome of exposure super arm S_j in round t. For all $S_i \in \mathcal{U}_{\mathcal{E}}$, we define

$$
\mathcal{R}(T,\pi,i) = \sum_{t=1}^{T} R(t,i) - \mathbb{E}_{\pi} \left[\frac{1}{N} \sum_{t=1}^{T} \sum_{i' \in \mathcal{U}} \tilde{r}_{i',t}(S_t) \right]
$$
(52)

as the expected "regret" if the exposure super arm S_i is the best arm. If we can upper bound $\mathcal{R}(T,\pi,i)$ for all $S_i \in \mathcal{U}_{\mathcal{E}}$, then we can upper bound $\mathcal{R}(T,\pi)$. Based on the unbiased property of the IPW estimator, for all $t \in [T_1 + 1, T]$, we have

$$
\mathbb{E}_{\pi}[\hat{R}_T(S'_i)] = \sum_{t=T_1+1}^T R(t, i') \text{ and}
$$

$$
\mathbb{E}_{\pi}\Big[\frac{1}{N}\sum_{t=1}^T \sum_{i'\in\mathcal{U}} \tilde{r}_{i',t}(S_t) \Big| \mathcal{H}_{t-1}\Big] = \sum_{S_{i'}\in\mathcal{U}_{\mathcal{E}}} \pi_t(S_{i'})R(t, i') = \sum_{S_{i'}\in\mathcal{U}_{\mathcal{E}}} \pi_t(S_{i'})\mathbb{E}_{\pi}\Big[\hat{R}_t(S_{i'}) - \hat{R}_{t-1}(S_{i'}) \Big| \mathcal{H}_{t-1}\Big].
$$
\n(53)

Based on (53) and (52) can be rewritten as

$$
\mathcal{R}(T,\pi,i) \leq \mathbb{E}_{\pi}[\hat{R}_{T}(S_{i})] - \mathbb{E}_{\pi} \left[\frac{1}{N} \sum_{t=T_{1}+1}^{T} \sum_{i' \in \mathcal{U}} \tilde{r}_{i',t}(S_{t}) \right] + T_{1}
$$
\n
$$
= \mathbb{E}_{\pi}[\hat{R}_{T}(S_{i})] - \mathbb{E}_{\pi} \left[\mathbb{E}_{\pi} \left[\frac{1}{N} \sum_{t=T_{1}+1}^{T} \sum_{i' \in \mathcal{U}} \tilde{r}_{i',t}(S_{t}) \Big| \mathcal{H}_{t-1} \right] \right] + T_{1}
$$
\n
$$
= \mathbb{E}_{\pi}[\hat{R}_{T}(S_{i})] - \mathbb{E}_{\pi} \left[\sum_{t=T_{1}+1}^{T} \sum_{S_{i'} \in \mathcal{U}_{\mathcal{E}}} \pi_{t}(S_{i'}) \mathbb{E}_{\pi} \left[\left(\hat{R}_{t}(S_{i'}) - \hat{R}_{t-1}(S_{i'}) \right) \Big| \mathcal{H}_{t-1} \right] \right] + T_{1}
$$
\n
$$
= \mathbb{E}_{\pi} \left[\hat{R}_{T}(S_{i}) - \sum_{t=T_{1}+1}^{T} \sum_{S_{i'} \in \mathcal{U}_{\mathcal{E}}} \pi_{t}(S_{i'}) \left(\hat{R}_{t}(S_{i'}) - \hat{R}_{t-1}(S_{i'}) \right) \right] + T_{1}
$$
\n
$$
= \mathbb{E}_{\pi} \left[\hat{R}_{T}(S_{i}) - \hat{R}_{T} \right] + T_{1}, \tag{54}
$$

where the first, second and third equality is owing to the tower rule that $\mathbb{E}[\mathbb{E}[\cdot|\mathcal{H}_{t-1}]]$ = $\mathbb{E}[\cdot]$, and the last equality is owing to we define $\hat{R}_T = \sum_{t=T_1+1}^T \sum_{S_{i'} \in \mathcal{U}_{\mathcal{E}}} \pi_t(S_{i'}) \left(\hat{R}_t(S_{i'}) - \right)$ $\hat{R}_{t-1}(S_{i'})\big).$

Define $W_T = \sum_{S_{i'} \in \mathcal{U}_{\mathcal{E}}} \exp(\epsilon \hat{R}_T(S_{i'})),$ we have

$$
W_{T} = W_{T_{1}} \frac{W_{T_{1}}}{W_{T_{1}}} \cdots \frac{W_{T}}{W_{T-1}}
$$
\n
$$
= |U_{\varepsilon}| \prod_{t=T_{1}+1}^{T} \left(\sum_{S_{i'} \in U_{\varepsilon}} \frac{\exp(\epsilon \hat{R}_{t-1}(S_{i'}))}{W_{t-1}} \exp(\epsilon (\hat{R}_{t}(S_{i'})-\hat{R}_{t-1}(S_{i'}))) \right)
$$
\n
$$
= |U_{\varepsilon}| \prod_{t=T_{1}+1}^{T} \left(\sum_{S_{i'} \in U_{\varepsilon}} \pi_{t}(S_{i'}) \exp(\epsilon (\hat{R}_{t}(S_{i'})-\hat{R}_{t-1}(S_{i'}))) \right)
$$
\n
$$
\leq |U_{\varepsilon}| \prod_{t=T_{1}+1}^{T} \left(1 + \epsilon \sum_{S_{i'} \in U_{\varepsilon}} \pi_{t}(S_{i'}) (\hat{R}_{t}(S_{i'}) - \hat{R}_{t-1}(S_{i'})) \right)
$$
\n
$$
+ \epsilon^{2} \sum_{S_{i'} \in U_{\varepsilon}} \pi_{t}(S_{i'}) (\hat{R}_{t}(S_{i'}) - \hat{R}_{t-1}(S_{i'}))^{2}
$$
\n
$$
\leq |U_{\varepsilon}| \prod_{t=T_{1}+1}^{T} \exp(\epsilon \sum_{S_{i'} \in U_{\varepsilon}} \pi_{t}(S_{i'}) (\hat{R}_{t}(S_{i'}) - \hat{R}_{t-1}(S_{i'}))
$$
\n
$$
+ \epsilon^{2} \sum_{S_{i'} \in U_{\varepsilon}} \pi_{t}(S_{i'}) (\hat{R}_{t}(S_{i'}) - \hat{R}_{t-1}(S_{i'}))^{2}
$$
\n
$$
+ \epsilon^{2} \sum_{S_{i'} \in U_{\varepsilon}} \pi_{t}(S_{i'}) (\hat{R}_{t}(S_{i'}) - \hat{R}_{t-1}(S_{i'}))^{2}
$$
\n
$$
= |U_{\varepsilon}| \exp(\epsilon \hat{R}_{T} + \epsilon^{2} \sum_{t=1}^{t} \sum_{S_{i'} \in U_{\varepsilon}} \pi_{t}(S_{i'}) (\hat{R}_{t}(S_{i'}) - \hat{R}_{t-1}(S_{i'}))^{2}),
$$

where the fourth inequality is owing to the definition of $\pi_t(S)$, the first inequality is owing to $\exp(x) \leq 1 + x + x^2$ for all $x \leq 1$ and $\hat{R}_t(S) - \hat{R}_{t-1}(S) \leq 1$ for all exposure super arm S, the last inequality is owing to $1 + x \leq \exp(x)$ for all x, and the last equality is owing to the definition of \hat{R}_T . Based on the last term of [\(55\)](#page-33-0), we can derive

$$
\hat{R}_T(S_i) - \hat{R}_T \le \frac{\log(|\mathcal{U}_{\mathcal{E}}|)}{\epsilon} + \epsilon \sum_{t=T_1+1}^T \sum_{S_{i'} \in \mathcal{U}_{\mathcal{E}}} \pi_t(S_{i'}) \left(\hat{R}_t(S_{i'}) - \hat{R}_{t-1}(S_{i'}) \right)^2, \tag{56}
$$

and $\mathcal{R}(T,\pi,i)$ can be bounded by

$$
\mathcal{R}(T,\pi,i) \leq \mathbb{E}_{\pi} \left[\hat{R}_T(S_i) - \hat{R}_T \right] + T_1
$$

$$
\leq \frac{\log(|\mathcal{U}_{\mathcal{E}}|)}{\epsilon} + \mathbb{E}_{\pi} \left[\epsilon \sum_{t=T_1+1}^T \sum_{S_{i'} \in \mathcal{U}_{\mathcal{E}}} \pi_t(S_{i'}) \left(\hat{R}_t(S_{i'}) - \hat{R}_{t-1}(S_{i'}) \right)^2 \right] + T_1.
$$
 (57)

We then try to bound $\mathbb{E}_{\pi} \Big[\epsilon \sum_{t=T_1+1}^{T} \sum_{S_{i'} \in \mathcal{U}_{\mathcal{E}}} \pi_t(S_{i'}) \big(\hat{R}_t(S_{i'}) - \hat{R}_{t-1}(S_{i'}) \big)^2 \Big],$ define $\tilde{R}(t, j) =$ $1-\frac{1}{N}$ $\frac{1}{N} \sum_{i' \in \mathcal{U}} \tilde{r}_{i',t}(S_j)$ as the reward outcome if the algorithm pulls S_j in round t, there is

$$
\mathbb{E}_{\pi} \left[\epsilon \sum_{t=T_{1}+1}^{T} \sum_{S_{i'} \in \mathcal{U}_{\mathcal{E}}} \pi_{t}(S_{i'}) \left(\hat{R}_{t}(S_{i'}) - \hat{R}_{t-1}(S_{i'}) \right)^{2} \right]
$$
\n
$$
= \mathbb{E}_{\pi} \left[\epsilon \sum_{t=T_{1}+1}^{T} \sum_{S_{i'} \in \mathcal{U}_{\mathcal{E}}} \pi_{t}(S_{i'}) \left(1 - \frac{\mathbf{1} \{ S_{t} = S_{i'} \} \tilde{R}(t, i')}{\pi_{t}(S_{i'})} \right)^{2} \right]
$$
\n
$$
= \mathbb{E}_{\pi} \left[\epsilon \sum_{t=T_{1}+1}^{T} \sum_{S_{i'} \in \mathcal{U}_{\mathcal{E}}} \pi_{t}(S_{i'}) \left(1 - \frac{2 \times \mathbf{1} \{ S_{t} = S_{i'} \} \tilde{R}(t, i')}{\pi_{t}(S_{i'})} + \frac{\mathbf{1} \{ S_{t} = S_{i'} \} (\tilde{R}(t, i'))^{2}}{\pi_{t}(S_{i'})^{2}} \right) \right]
$$
\n
$$
= \mathbb{E}_{\pi} \left[\epsilon \sum_{t=T_{1}+1}^{T} \left(\frac{2}{N} \sum_{i' \in \mathcal{U}} \tilde{r}_{i',t}(S_{t}) - 1 \right) + \mathbb{E}_{\pi} \left[\epsilon \sum_{t=T_{1}+1}^{T} \sum_{S_{i'} \in \mathcal{U}_{\mathcal{E}}} \pi_{t}(S_{i'}) \left(\frac{\mathbf{1} \{ S_{t} = S_{i'} \} (\tilde{R}_{t,i'})^{2}}{\pi_{t}(S_{i'})^{2}} \right) \right| \mathcal{H}_{t-1} \right]
$$
\n
$$
= \mathbb{E}_{\pi} \left[\epsilon \sum_{t=T_{1}+1}^{T} \left(\frac{2}{N} \sum_{i' \in \mathcal{U}} \tilde{r}_{i',t}(S_{t}) - 1 \right) + \epsilon \sum_{t=T_{1}+1}^{T} \sum_{S_{i'} \in \mathcal{U}_{\mathcal{E}}} (\tilde{R}_{t,i'})^{2} \right]
$$
\n
$$
\leq |\mathcal{U}_{\mathcal{E}}|T\
$$

Based on the definition of ϵ , we can finally bound $\mathcal{R}(T,\pi,i)$ by $\sqrt{|\mathcal{U}_{\mathcal{E}}|T \log(|\mathcal{U}_{\mathcal{E}}|)} + T_1$. Here we finish the proof of Theorem [14.](#page-31-0)

Appendix J. Auxiliary Lemmas

Lemma 15 (Sub-Gaussian) A random variable X is said to be **sub-Gaussian** if there exists a constant $\sigma > 0$ such that for all $t \in \mathbb{R}$, the moment generating function of X satisfies:

$$
\mathbb{E}\left[e^{tX}\right]\leq e^{\frac{\sigma^2t^2}{2}}.
$$

The smallest such σ is known as the sub-Gaussian parameter of X.

Lemma 16 (Hoeffding's Inequality) Let X_1, X_2, \dots, X_n i.i.d. drawn from a σ -sub-Gaussian distribution, $\overline{X} = \frac{1}{n}$ $\frac{1}{n} \sum_{i=1}^{n} X_i$ and $\mathbb{E}[X]$ be the mean, then we have

$$
\mathbb{P}\left(\overline{X} - \mathbb{E}[X] \ge a\right) \le e^{-na^2/2\sigma^2} \quad and \quad \mathbb{P}\left(\overline{X} - \mathbb{E}[X] \le -a\right) \le e^{-na^2/2\sigma^2}.
$$

Lemma 17 (Bernstein's Inequality) Let X_1, X_2, \ldots, X_n be a martingale difference sequence, where each X_t satisfies $|X_t| \leq \alpha_t$ almost surely for a non-decreasing deterministic sequence $\alpha_1, \alpha_2, \ldots, \alpha_n$. Define $M_t := \sum_{\tau=1}^t X_{\tau}$ as the cumulative sum up to time t, forming a martingale. Let $\overline{V}_1, \overline{V}_2, \ldots, \overline{V}_n$ be deterministic upper bounds on the variance $V_t := \sum_{\tau=1}^t \mathbb{E}[X_\tau^2 | X_1,\ldots,X_{\tau-1}]$ of the martingale M_t , and suppose \overline{V}_t satisfies the condition

$$
\sqrt{\frac{\ln\left(\frac{2}{\delta}\right)}{(e-2)\overline{V}_t}} \le \frac{1}{\alpha_t}.
$$

Then, with probability at least $1 - \delta$ for all t:

$$
|M_t| \le 2\sqrt{(e-2)\overline{V}_t \ln \frac{2}{\delta}}.
$$