Representational Transfer Learning for Matrix Completion

By Yong He

Institute for Financial Studies, Shandong University, China. heyong@sdu.edu.cn

Zeyu Li

School of Management, Fudan University, China. zeyuli21@m.fudan.edu.cn

Dong Liu

School of Physical & Mathematical Sciences, Nanyang Technological University, Singapore.

KANGXIANG QIN

Institute for Financial Studies, Shandong University, China.

and Jiahui Xie

Department of Statistics and Data Science, National University of Singapore, Singapore.

SUMMARY

We propose to transfer representational knowledge from multiple sources to a target noisy matrix completion task by aggregating singular subspaces information. Under our representational similarity framework, we first integrate linear representation information by solving a two-way principal component analysis problem based on a properly debiased matrix-valued dataset. After acquiring better column and row representation estimators from the sources, the original high-dimensional target matrix completion problem is then transformed into a low-dimensional linear regression, of which the statistical efficiency is guaranteed. A variety of extensional arguments, including post-transfer statistical inference and robustness against negative transfer, are also discussed alongside. Finally, extensive simulation results and a number of real data cases are reported to support our claims.

Some key words: Low-rank trace regression; two-way principal component analysis; representation learning.

1. INTRODUCTION

The basic idea of transfer leaning, also known as knowledge transfer, is to leverage information from related sources to improve the statistical performance of the target study of interest (Torrey and Shavlik, 2010; Zhuang et al., 2020). In high-dimensional statistical settings, a flourish of transfer learning methods have been proposed with various types of similarity assumptions. For example, when the differences between the target and source parameters, also known as contrast vectors, are sufficiently sparse, Bastani (2021); Li et al. (2022); Tian and Feng (2022); Qiao

et al. (2023) propose to use a two-step procedure, i.e., pooling and debiasing, to better estimate the target parameter. Li et al. (2023) further suggest joint estimation of the target parameters and the contrast vectors, so as to relax the homogeneous Hessian matrices condition, see also Li et al. (2024b) for a joint estimation method by a non-convex penalty. Please refer to Cai and Wei (2021); Reeve et al. (2021); Yan and Chen (2024) for transfer learning in other statistical problems including non-parametric classification and causal inference.

In this work, the target task of interest is a matrix completion problem contaminated by noises. To be more specific, let $\Theta_0^* \in \mathbb{R}^{p \times q}$ be the unknown target matrix, for $i \in [n_0] := \{1, \ldots, n_0\}$, we have i.i.d. observations of the form

$$y_{0,i} = \left(\Theta_0^*\right)_{a_{0,i},b_{0,i}} + (pq)^{-1/2}\xi_{0,i},\tag{1}$$

where $\xi_{0,i}$ has zero mean and variance σ_0^2 , and $(a_{0,i}, b_{0,i})$ are randomly chosen indices. The rescaling factor $(pq)^{-1/2}$ originates from Negahban and Wainwright (2012), to ensure a constant signal-to-noise ratio when Θ_0^* has a constant Frobenius norm regardless of the matrix dimensions. Alternatively, we have an equivalent formulation of (1) by defining $X_{0,i} = e_{a_{0,i}} e_{b_{0,i}}^{\mathsf{T}}$ where both $e_{a_{0,i}}$ and $e_{b_{0,i}}$ are taken from the natural basis of \mathbb{R}^p and \mathbb{R}^q , respectively. The observation model then becomes

$$y_{0,i} = \left\langle \Theta_0^*, X_{0,i} \right\rangle + (pq)^{-1/2} \xi_{0,i}, \quad i \in [n_0].$$
⁽²⁾

The trace regression formulation (2) is insightful enough to offer a way to estimate Θ_0^* , that is, by minimizing the mean square error. However, it is statistically impossible to retrieve the $p \times q$ parameters using merely n_0 observations when $n_0 \ll pq$, unless additional low-rank assumptions are made on Θ_0^* . Candes and Recht (2012) relax the low-rank constraint of a matrix using the nuclear norm of the matrix $\|\cdot\|_N$, which has also spawned a variety of penalized least squares methods of the nuclear norm (Candes and Plan, 2010; Candès and Tao, 2010; Negahban and Wainwright, 2011, 2012; Cai and Zhang, 2015; Cai and Zhou, 2016). These computationally tractable convex relaxed methods are known to be statistically optimal under mild conditions. In parallel, another stream of work focuses on non-convex approaches including matrix factorization. For example, Keshavan et al. (2009) propose a method based on singular value decomposition (SVD); see also Zhao et al. (2015); Wang et al. (2017); Ma et al. (2018); Chen et al. (2020).

In the context of knowledge transfer, we have *K* additional source studies with underlying true matrices $\Theta_k^* \in \mathbb{R}^{p \times q}$ for $k \in [K]$. In some cases, these Θ_k^* are fully observed, probably only contaminated by random noises E_k . That is, we can directly observe $\widetilde{\Theta}_k = \Theta_k^* + E_k$. However, in the main body of this work we consider a more challenging setting where these Θ_k^* are only partially observed as well, leaving the fully observed cases to the extensional arguments in the supplementary material. Specifically, we set $X_{k,i} = e_{a_{k,i}} e_{b_{k,i}}^{\top}$, and

$$y_{k,i} = \left\langle \Theta_k^*, X_{k,i} \right\rangle + (pq)^{-1/2} \xi_{k,i}, \quad i \in [n_k],$$

where $\xi_{k,i}$ has zero mean and variance σ_k^2 . Following Xia and Yuan (2021), we independently and uniformly sample the random matrices $X_{k,i}$ from the canonical orthogonal basis $\mathcal{E} := \{e_a e_b^\top : a \in [p], b \in [q]\}$ for $k \in \{0\} \cup [K]$. We shall always assume that $p \ge q$ without loss of generality.

1.1. Similarity metrics

The characterization of the similarity metric between the target and source studies is essential before tailoring any knowledge transfer algorithms. The similarity metric pins down the shareable features between these statistical tasks, and we design the corresponding algorithm to fully exploit the shared common information, so as to enhance the statistical performance of the target studies.

For the sake of brevity in presentation, we shall first assume that all sources are informative, i.e., close to the target, under certain sense of similarity.

A commonly used and easy-to-analyze form of similarity is the distance similarity. In the context of matrix completion, distance similarity shall require $\|\Theta_0^* - \Theta_k^*\|_N \le h_d$ for $k \in [K]$, where $\|\cdot\|_N$ is the matrix nuclear norm and characterizes the low-rankness of contrast matrices $\Theta_0^* - \Theta_k^*$. Distance similarity often leads to the classical pooling and debiasing methods, where in the first step all source samples are gathered for a joint estimation, and in the second step the pooling estimator is debiased using only the target samples (Li et al., 2022; Tian and Feng, 2022; Qiao et al., 2023). However, in many practical cases, the distance similarity is clearly too ideal to be realistic, as we in essence assume the parameter matrices to be almost element-wise alike with the difference matrix being quite sparse or low-rank.

In the following, we give a few conceptual counter-examples of the distance similarity in empirical applications, where a more suitable similarity metric ought to be considered. First, most knowledge transfer methods in the literature require the dimension of the target parameter to be the same as the source parameters. In many real-world applications, however, we might encounter dimension mismatch due to the difference of measurement or storage between target and the source datasets. That is, the shape of the target matrix Θ_0^* might not be the same as the source matrices Θ_k^* for $k \in [K]$. For example, in the COVID-19 computed tomography (CT) example used in this work, the sizes of chest scan images range from $p \in [115, 1671]$ and $q \in [61, 1225]$, in terms of the number of pixels in rows and columns. Though we may reshape these the matrices into the same size via upsampling, subsampling, or cropping, the distance similarity could be quite sensitive to these operations. Second, in some other cases, even if the target and source matrices are naturally the same size, the similarity would be more reasonable and inherent in the spectral sense, rather than in the distance way, for example the applications on multiple networks and multiple-input multiple-output (MIMO) radars (Zheng and Tang, 2022; Sun et al., 2015).

1.2. Representational similarity

In this work, we adopt the representational similarity (or spectral similarity). First, write the singular value decomposition (SVD) of the rank r_0 matrix $\Theta_0^* = U_0^* \Lambda_0^* (V_0^*)^\top$, where $(U_0^*)^\top U_0^* = (V_0^*)^\top V_0^* = I_{r_0}$ and Λ_0^* is diagonal. Although Θ_k^* might be far away from Θ_0^* in the distance sense such that $\|\Theta_k^* - \Theta_0^*\|_N \gg h_d$, it could still contain valuable information on U_0^* and V_0^* . To better illustrate our motivation, now suppose we are able to exactly recover U_0^* and V_0^* with the help of the auxiliary sources, the task of estimating Θ_0^* then changes

from
$$\underset{\Theta_0 \in \mathbb{R}^{p \times q}, \operatorname{rank}(\Theta_0) = r_0}{\operatorname{arg\,min}} \mathbb{E} \left[y_{0,i} - \operatorname{tr} \left(X_{0,i}^{\top} \Theta_0 \right) \right]^2 \quad \text{to} \quad \underset{\Lambda_0 \in \mathbb{R}^{r_0 \times r_0}}{\operatorname{arg\,min}} \mathbb{E} \left[y_{0,i} - \operatorname{tr} \left(Z_{0,i}^{\top} \Lambda_0 \right) \right]^2, \quad (3)$$

where $Z_{0,i} := (U_0^*)^\top X_{0,i} V_0^*$ of size $r_0 \times r_0$ is the "extracted feature matrix" after acquiring knowledge about the low-dimensional linear representations U_0^* and V_0^* . The original high-dimensional trace regression problem of dimension $p \times q$ is thus turned into a low-dimensional linear regression problem with at most $r_0 \times r_0$ parameters, whose statistical efficiency is guaranteed by classical linear regression theory, avoiding the curse of dimensionality when p and $q \to \infty$. To some extent, the debiasing step under distance similarity solves a relatively easier highdimensional statistical task, so the gain of knowledge transfer for the classical two-step methods is from high-dimensions to high-dimensions (Li et al., 2022; Tian and Feng, 2022; Qiao et al., 2023). On the contrary, the gain via representational transfer could be from high-dimensions to low-dimensions, which seems to be more promising in principle.

We now present our knowledge transfer framework. For brevity, we shall assume first that all source datasets are informative, and we leave the extensions against potentially harmful sources to Section 4. Now for I := [K] and $k \in \{0\} \cup I$, let Θ_k^* be of rank r_k with the singular value decomposition:

$$\underbrace{\Theta_k^*}_{p \times q} = \underbrace{U_k^*}_{p \times r_k} \times \underbrace{\Lambda_k^*}_{r_k \times r_k} \times \underbrace{(V_k^*)^\top}_{r_k \times q}, \tag{4}$$

where $(U_k^*)^{\top}U_k^* = (V_k^*)^{\top}V_k^* = I_{r_k}$ and Λ_k^* is diagonal. We allow r_k to differ across different studies. Before we characterize the similarity between the linear representations U_k^* and V_k^* , note that (4) naturally inherits the identifiability problem such that U_0^* could be replaced by $U_0^*H_k$ for any $r_k \times r_k$ orthogonal matrix H_k while changing Λ_k^* to $H_k^{\top}\Lambda_k^*$ correspondingly. However, the subspaces span (U_k^*) and span (V_k^*) are still identifiable and unique, so it is more natural to impose the representation similarity in the subspace sense.

Due to symmetry, we first focus on $\operatorname{span}(U_k^*)$. Although $\operatorname{span}(U_k^*)$ might in general be quite different from $\operatorname{span}(U_0^*)$ for $k \in I$, we assume that $\operatorname{span}(U_0^*)$ lies in a larger subspace of dimensions p_0 of \mathbb{R}^p , denoted as $\operatorname{span}(U)$, which also approximately contains all $\operatorname{span}(U_k^*)$ for $k \in I$, so that $p_0 \ge \max_{k \in I} (r_k)$. To mathematically quantify such "approximately contains", let U_{\perp} be the orthogonal complement of U, for some small h > 0, we assume that

$$\operatorname{span}(U_0^*) \subseteq \operatorname{span}(U), \quad \left\| U_{\perp}^{\top} U_k^* \right\|_F \le h, \quad k \in \mathcal{I}.$$
(5)

Geometrically, the principal angles between span (U_{\perp}) and span (U_{k}^{*}) are $\{\cos^{-1}(\sigma_{k,l})\}_{l=1}^{r_{k}}$ where $\sigma_{k,l}$ are non-trivial singular values of $U_{\perp}^{\top}U_{k}^{*}$. Hence, small $||U_{\perp}^{\top}U_{k}^{*}||_{F}$ means that span (U_{k}^{*}) and span (U_{\perp}) are almost orthogonal, so that span (U_{k}^{*}) is almost within span(U). Similar arguments could be made with respect to span (V_{k}^{*}) , where we assume that there exists some q_{0} dimensional span(V) with $q_{0} \ge \max_{k \in I} (r_{k})$, such that for its orthogonal complement V_{\perp} we assume

$$\operatorname{span}(V_0^*) \subseteq \operatorname{span}(V), \quad \left\| V_{\perp}^\top V_k^* \right\|_F \le h, \quad k \in \mathcal{I}.$$
(6)

Clearly, $\operatorname{span}(U) = \operatorname{span}(V) = \mathbb{R}^p$ is a trivial case with h = 0, where, however, we cannot achieve dimension reduction and hence achieve no gain of knowledge transfer as depicted by (3). It is foreseeable that h gets larger when we seek smaller p_0 and q_0 , that is, a stronger dimension reduction. Basically, when p_0 and q_0 become larger, the estimated linear representations are more capable of capturing the target matrix structure of interest with a smaller bias h. However, enlarging p_0 and q_0 at the same time increases the statistical difficulty in estimating the postrepresentation target coefficients, since the number of parameters to be estimated by this linear regression is p_0q_0 . Therefore, there is essentially a trade-off when choosing the cut-off dimensions p_0 and q_0 here. Throughout this work, we shall assume a sufficiently small h given finite $\max(p_0, q_0) < \infty$. Similar linear representational conditions have also been assumed in Tian et al. (2023), where the authors add a subspace penalty to enforce similar representations when learning all tasks by aggregating the data. Meanwhile, in He et al. (2024), a non-linear representation function is assumed to be shared across various tasks and is estimated in a joint way.

1.3. Contributions and notations

The contributions of this work lie in the following aspects. First, as an addition to the highdimensional knowledge transfer literature, by introducing two-way representational similarity into the matrix completion problem, we manage to decompose the original high-dimensional statistical task into two parts. In the first part, we carefully extract the useful source information via unsupervised subspace integration methods. After the representations are recovered, the second part for the target dataset is inherently low-dimensional and statistically efficient. It is two-step methods, the debiasing step often involves a relatively easier but still high-dimensional statistical task, for example, estimating a even sparser high-dimensional contrast vector (Li et al., 2022; Tian and Feng, 2022; Qiao et al., 2023). Detailed theoretical discussions and extensive numerical results support our claims above. Second, as one can always stack the target and K source matrices into a tensor of size $(K + 1) \times p \times q$, this work can also be viewed as an extension to the well-developed field of low-rank tensor completion; see, for example, Yuan and Zhang (2016, 2017); Xia et al. (2021). In contrast to the existing tensor completion methods, we assume only the low-rankness in the latter two modes. Meanwhile, after acquiring the representations, our target estimation step shows a great computational advantage. It is particularly useful for streaming data, where the target samples arrive sequentially, as it makes little sense to complete a large tensor immediately each time a new matrix arrives. In the end, we carefully tailor our algorithm to avoid the inclusion of potentially harmful source datasets. As validated by our experiments, it might cause severe negative transfer if one blindly applies tensor completion methods to the stacked tensor.

To end this section, we introduce some notations used throughout the paper. For a real matrix A, let $\{\lambda_i(A)\}\$ be its non-increasing singular values and $d_i(A) = \lambda_i(A) - \lambda_{i+1}(A)$ be the *i*-th singular value gap. The operator norm of the matrix A is denoted by $||A||_{op} = \lambda_1(A)$, while its Frobenius norm is written as $||A||_F$. For a random variable $X \in \mathbb{R}$, we define $||X||_{\psi_2} = \sup_{p\geq 1} p^{-1/2} (\mathbb{E}|X|^p)^{1/p}$ and $||X||_{\psi_1} = \sup_{p\geq 1} p^{-1} (\mathbb{E}|X|^p)^{1/p}$. Please, see Vershynin (2018) for details of the sub-Gaussian and sub-exponential norms. Moreover, o_p in this work is for convergence to zero in probability and O_p means stochastic boundedness. We write $x \leq y$ if $x \leq Cy$ for some C > 0, $x \geq y$ if $x \geq cy$ for some c > 0, and $x \prec y$ if both $x \leq y$ and $x \geq y$ hold. The constants may not be identical across different lines.

ORACLE TRANSFER LEARNING PROCEDURE 2.

We present an oracle three-step procedure designed specifically for the representation similarity between the target and source matrix completion studies, assuming that all available sources are informative. Generally speaking, in the first step, we acquire debiased estimators of Θ_k^* for $k \in \mathcal{I} := [K]$, where \mathcal{I} represents informative sources. We denote the debiased estimators by Θ_k and eventually construct an unbiased matrix-valued dataset $\mathcal{D}_I := \{\widetilde{\Theta}_k, k \in I\}$. As these $\widetilde{\Theta}_k$ shall share linear representation information within our framework, retrieving subspace population information from $\mathcal{D}_{\mathcal{T}}$ then turns into a standard two-way principal component analysis problem (Zhang and Zhou, 2005; Wang et al., 2019; Chen and Fan, 2021). That is to say, in the second step we could take an unsupervised learning approach to integrate the subspace information across the unbiased $\widetilde{\Theta}_k$, to acquire the $p \times p_0$ column orthogonal matrix \widehat{U} and the $q \times q_0$ column orthogonal matrix \hat{V} , which are also called linear representations. In the third step, we turn the original high-dimensional target low-rank trace regression problem to a low-dimensional linear regression with the better estimated linear representations as alluded in (3), to achieve an efficiency gain in the target performance. To be more specific, after acquiring \hat{U} and \hat{V} , we go back to the target task and calculate the projected extracted feature matrices $\hat{Z}_{0,i} = \hat{U}^{\top} X_{0,i} \hat{V}$ of shape $p_0 \times q_0$. We perform a linear regression on the projected dataset $\{(\widehat{Z}_{0,i}, y_{0,i})\}_{i=1}^{n_0}$, to acquire $\widehat{\Gamma}_0$. In the end, we retrieve our target matrix completion estimator as $\widehat{\Theta}_0 = \widehat{U}\widehat{\Gamma}_0 \widehat{V}^{\top}$.

In the main body of this work, source information is treated as externally given for the target task, which is a common practice for transfer learning. Hence, we do not include a debiased Θ_0 in the first step, but this is totally feasible. Meanwhile, the construction details of the unbiased

dataset for partially observed sources in the first step and the choice of the two-way principal component analysis method in the second step are still unclear. Though in principle these two steps are totally flexible and could be tailored according to each specific problem at hand, we present our default implementation procedure as follows.

2.1. Default implementation procedure

First, the unbiasedness of $\overline{\Theta}_k$ in the first step is essential to establish the theoretical properties of any integrated subspace estimator in the second step. When the sources are partially observed, most existing matrix completion estimators, if not all, are inherently biased (Candes and Plan, 2010; Cai and Zhang, 2015; Wang et al., 2017; Chen et al., 2020). Hence, it is important to first debias any crude estimators we acquire using these existing methods. The debiasing technique is important for the statistical inference of sparse linear regression problems (Javanmard and Montanari, 2014; Van de Geer et al., 2014). We may also refer to Carpentier and Kim (2018); Carpentier et al. (2018); Xia (2019) for low-rank matrix trace regression and to Chen et al. (2019); Xia and Yuan (2021) for noisy matrix completion problems.

We adopt the estimation and then debiasing procedure from Xia and Yuan (2021) via Jfold sample splitting. For notational brevity, without loss of generality, we assume that n_k/J is an integer for all $k \in I$. Then we split the indices of the k-th dataset $D_k := [n_k]$ into J nonoverlapping sub-indices D_k^j for $j \in J$, each of length n_k/J . We also write D_k^{-j} as the sub-indices of D_k without D_k^j , i.e., $D_k^{-j} = D_k \setminus D_k^j$. We denote D_k^j and D_k^{-j} as the corresponding sub-samples of the k-th dataset without causing confusions. Then, for each $j \in J$, we first acquire a crude matrix completion estimator $\dot{\Theta}_k^{-j}$ by a certain reliable method (generally biased) using D_k^{-j} . Then, we debias $\dot{\Theta}_k^{-j}$ using D_k^j according to

$$\widetilde{\Theta}_{k}^{j} := \dot{\Theta}_{k}^{-j} + \frac{Jpq}{n_{k}} \sum_{i \in D_{k}^{j}} \left(y_{k,i} - \left\langle \dot{\Theta}_{k}^{-j}, X_{k,i} \right\rangle \right) X_{k,i}.$$

$$\tag{7}$$

Finally, we let $\widetilde{\Theta}_k := \sum_{j \in [J]} \widetilde{\Theta}_k^j / J$. That is, by the debiasing procedure, we now have an unbiased matrix-valued dataset $\mathcal{D}_I =$ $\{\overline{\Theta}_k\}_{k\in I}$ that includes K matrices. Then it becomes a two-way principal component analysis problem that aims to retrieve the population column and row subspaces of the matrices in \mathcal{D}_{I} . For this problem, we also have a rich toolbox of methods, for example, those introduced in (Zhang and Zhou, 2005; Wang et al., 2019; Chen and Fan, 2021; Yu et al., 2022; Li et al., 2024a). As a simple illustration, by the benchmark method $(2D)^2$ -principal component analysis (PCA) in Zhang and Zhou (2005), we can estimate span(U) by extracting the leading p_0 eigenvectors of the matrix $\sum_{k \in I} n_k \widetilde{\Theta}_k^j (\widetilde{\Theta}_k^j)^\top / N$, where $N = \sum_{k \in I} n_k$. In this paper, we suggest using the one-round Grassmannian barycenter method from Li et al. (2024a), due to its robustness against outliers and communication efficiency. For each matrix-valued data Θ_k , we first take its leading r_k left and right singular vectors, that is, those corresponding to the largest r_k singular values, and stack them into $p \times r_k$ and $q \times r_k$ column orthogonal matrices \widetilde{U}_k and \widetilde{V}_k . We then calculate the orthogonal projection matrices corresponding to the subspaces spanned by these eigenvectors as $P_k := U_k(U_k)^{\top}$ and $Q_k := V_k(V_k)^{\top}$. In the end, we integrate the subspace information by extracting the leading p_0 and q_0 eigenvectors of the weighted Euclidean mean of the projection matrices

$$\widetilde{\Sigma}_U := \frac{1}{N} \sum_{k \in \mathcal{I}} n_k \widetilde{P}_k, \quad \widetilde{\Sigma}_V := \frac{1}{N} \sum_{k \in \mathcal{I}} n_k \widetilde{Q}_k, \tag{8}$$

denoted as \widehat{U} and \widehat{V} respectively.

Algorithm 1. Default implementation procedure under partially observed sources.

Require:

 $(X_{k,i}, y_{k,i})$ for $k \in \mathcal{I} = [K]$; cut-off dimensions $\{r_k\}_{k \in \mathcal{I}}$ and p_0, q_0 ; number of folds J; **Ensure:**

1. debiased dataset: for each $k \in I$, first split the dataset D_k into J folds. For each $j \in [J]$, first acquire a crude estimator $\dot{\Theta}_k^{-j}$ using D_k^{-j} , debias $\dot{\Theta}_k^{-j}$ using D_k^j according to (7), and then acquire the unbiased matrix $\tilde{\Theta}_k = \sum_{j \in [J]} \tilde{\Theta}_k^{-j}/J$, so as to construct the matrix-valued dataset $\mathcal{D}_I = \{\tilde{\Theta}_k, k \in I\}$; 2. subspace integration: acquire \hat{U} and \hat{V} by taking the leading p_0 and q_0 eigenvectors of $\tilde{\Sigma}_U$ and $\tilde{\Sigma}_V$ given in (8); 3. target estimation: apply linear regression on $\{(\hat{Z}_{0,i}, y_{0,i})\}$ with $\hat{Z}_{0,i} = \hat{U}^{\top} X_{0,i} \hat{V}$ to obtain

3. target estimation: apply linear regression on $\{(Z_{0,i}, y_{0,i})\}$ with $Z_{0,i} = U^\top X_{0,i} V$ to obtain the $p_0 \times q_0$ parameter matrix $\widehat{\Gamma}_0$; **return** $\widehat{\Theta}_0 = \widehat{U}\widehat{\Gamma}_0\widehat{V}^\top$.

The default implementation procedure under partially observed sources is summarized in Algorithm 1. Apparently, the performance of our knowledge transfer method depends on the statistical precision of the crude estimators $\{\dot{\Theta}_k^{-j}\}_{k\in I}^{j\in [J]}$. Fortunately, as pointed out in Xia and Yuan (2021) and shown in the following section, such a dependence is fairly weak as long as the estimation errors of the crude estimators are small in terms of the vectorized ℓ_{∞} norm, which is denoted by $\|\cdot\|_{\infty}$ in this article. Recall that σ_k^2 is the variance of $\xi_{k,i}$, we adopt the following assumption directly from Assumption 1 of Xia and Yuan (2021).

Assumption 1. For $j \in [J]$ and $k \in [K]$, as $n_k, p, q \to \infty$, the crude estimators satisfy

$$\left\|\dot{\Theta}_{k}^{-j} - \Theta_{k}^{*}\right\|_{\infty} = o_{p}\left[(pq)^{-1/2}\sigma_{k}\right].$$
(9)

Estimation error bounds similar to (9) can also be found in Ma et al. (2018); Chen et al. (2019). For concreteness, we resort to the non-sample-splitting version of a rotation calibrated Grassmannian gradient descent algorithm given by Xia and Yuan (2021). It serves as our default choice for the matrix completion method in this work. A sample-splitting version of this algorithm is capable of producing crude estimators that satisfies Assumption 1 under some mild incoherence and noise conditions in Xia and Yuan (2021). Meanwhile, as shown by extensive numerical experiments, the default implementation procedures stated in Algorithm 1 perform quite satisfactorily.

The debiasing strategy in Algorithm 1 originates from Chernozhukov et al. (2018) and is used in Xia and Yuan (2021) with J = 2. This particular form of debiasing takes advantage of the fact that $\mathbb{E}[\operatorname{vec}(X_{k,i})\operatorname{vec}(X_{k,i})^{\top}] = (pq)^{-1}I_{pq}$, and shall be calibrated accordingly if the entries are not sampled uniformly. The J-fold sample-splitting technique avoids the loss of statistical efficiency associated with the sample splitting. Throughout this work, we consider J as a finite integer. In the end, the choice of the debiasing method is clearly flexible as well; see also Chen et al. (2019) for a similar debiased estimator under uniform sampling observations.

Finally, we briefly remark on the advantages of the selected one-round Grassmannian barycenter approach for the subspace integration step. The first advantage is its robustness against individual outliers that have extremely large eigenvalues, as the Grassmannian barycenter discards all eigenvalue information and only integrates the directional subspace information (Li et al., 2024a). Robustness is extremely important in the current knowledge transfer context, so as to

prevent negative transfer when accidentally including non-informative sources. Second, when multiple source datasets are distributed across different machines, the Grassmannian barycenter is not only communication-efficient but also privacy-protected as it only requires transmitting the local subspace estimators, namely \tilde{U}_k^j and \tilde{V}_k^j , once, rather than transmitting the column and row covariance matrices or even the whole datasets. This advantage is also discussed in detail for distributed principal component analysis by Fan et al. (2019).

3. Oracle Theory

In this section, we provide theoretical justification for the default implementation in Algorithm 1. We first make some technical assumptions.

Assumption 2. For $k \in \{0\} \cup [K]$, the noise $\xi_{k,i}$ is a centered sub-Gaussian random variable independent from the uniformly sampling $X_{k,i}$, satisfying $\|\xi_{k,i}\|_{\psi_2} \leq \sigma_k \leq C$.

Assumption 3. For $k \in \{0\} \cup [K]$, Θ_k^* is of rank $r_k \leq r \leq \min(p_0, q_0) \leq \max(p_0, q_0) < \infty$, with non-trivial singular values $0 < c \leq \lambda_{r_k}(\Theta_k^*) \leq \cdots \leq \lambda_1(\Theta_k^*) \leq C$.

Assumption 4. Assume that there exists some sufficiently small $h \ge 0$ such that both (5) and (6) hold for $k \in I$. Meanwhile, for $P_k^* = U_k^* (U_k^*)^\top$ and $Q_k^* = V_k^* (V_k^*)^\top$, assume there exists some g > h that for any $u \in \text{span}(U)$ and $v \in \text{span}(V)$,

$$\frac{1}{N}\sum_{k\in \mathcal{I}}n_k\left\langle u, P_k^*u\right\rangle \geq g^2, \quad \frac{1}{N}\sum_{k\in \mathcal{I}}n_k\left\langle v, Q_k^*v\right\rangle \geq g^2.$$

Assumptions 2 and 3 ensure a well-conditioned noise and signal, which are standard in the literature (Xia and Yuan, 2021). Meanwhile, Assumption 4 is related to the identifiability of the population subspaces span(U) and span(V) using the Grassmannian barycenter method. If $\sum_{k=0}^{K} n_k \langle u, P_k^* u \rangle / N = 0$ for some $u \in \mathbb{R}^p$, it essentially means that u is orthogonal to all span (U_k^*) and shall be identified as a vector in span (U_\perp) rather than span(U). The same argument applies to span(V). One may refer to Li et al. (2024a) for detailed discussions on a similar identifiability condition. We present our main theoretical claim as follows.

THEOREM 1 (REPRESENTATION TRANSFER LEARNING). Under Assumptions 1 to 4, for $k \in I$, assume that $n_k \gtrsim p \log^{\tau} p$ for some $\tau \geq 3$ and $K \leq (N/p \log p)^{1/2}$ as $n_0, n_k, p, q \to \infty$, we have

$$\left\|\widehat{\Theta}_{0} - \Theta_{0}^{*}\right\|_{F}^{2} = O_{p}\left(\underbrace{\frac{rp\log p}{N} + h^{2}}_{representation} + \underbrace{\frac{p_{0}q_{0}}{n_{0}}}_{target}\right).$$
(10)

We end this section with a few remarks. First, a typical rate for matrix completion methods that use only the target dataset should be $rp \log p/n_0$, while the information theoretical lower bound is of order rp/n_0 (Negahban and Wainwright, 2012). The first term of (10) essentially matches the nearly information theoretical optimal rate with the dimensional factor log p given the pooled sample size $N = \sum_{k \in I} n_k$, which means that integrating the representation information alone is adequate for efficient and almost optimal knowledge transfer. The second term h^2 is standard and vanishes if all span $(U_k^*) \subseteq$ span(U) and span $(V_k^*) \subseteq$ span(V). Finally, the third term comes from the low-dimensional ordinary least squares after acquiring the low-dimensional representations using the target dataset. As alluded in the Introduction, as p_0 , q_0 grows, we shall have smaller h in principle. For example, if $p_0 = p$ and $q_0 = q$, then h = 0 naturally. Representation learning thus requires a trade-off between h^2 in the representation error and the target estimation error p_0q_0/n_0 . We conclude that representational transfer learning outperforms target estimation if $p_0q_0/n_0 + h^2 \ll rp \log p/n_0$ and $N \gg n_0$, which is mild as relatively small p_0 and q_0 would guarantee small h in practice. In the end, we additionally require that $K \leq (N/p \log p)^{1/2}$. This is due to the fact that the Grassmannian barycenter method is inherently biased up to a high-order term. We restrict the size of the useful sources K so that the high-order bias term could be absorbed into the variance term $p \log p/N$ for notational brevity. It still allows K to diverge as long as $N \gg p \log p$, which is almost always the case.

After acquiring the convergence rate of $\widehat{\Theta}_0 - \Theta_0^*$ in Theorem 1, we now discuss post-transfer inference given sufficiently reliable sources. We are interested in the asymptotic distribution of the bilinear form $\langle u, (\widehat{\Theta}_0 - \Theta_0^*)v \rangle$. A motivating example would be $u = e_i$ and $v = e_j$, which is particularly useful since we can perform statistical inference and construct a confidence interval for the (i, j)-th element of Θ_0^* . We claim the following corollary of Theorem 1, while emphasizeing that the left hand side of (11) as a whole could be directly calculated with observations.

COROLLARY 1 (ASYMPTOTIC NORMALITY). Under the assumptions of Theorem 1, for some constant $\sigma_0 > 0$, if we further assume that $\sigma_0^2 \min(\|U^{\top}u\|_2^2, \|V^{\top}v\|_2^2)/n_0 \gg rp \log p/N + h^2$ as $n_0, n_k, p, q \to \infty$, then

$$\frac{\sqrt{n_0}}{\widehat{\sigma}_L} \left\langle u, (\widehat{\Theta}_0 - \Theta_0^*) v \right\rangle \to \mathcal{N}(0, 1) \text{ in distribution, where}$$
(11)
$$\widehat{\sigma}_L^2 = \frac{pq}{n_0} \sum_{i=1}^{n_0} \left[y_{0,i} - \operatorname{tr} \left(X_{0,i}^\top \widehat{\Theta}_0 \right) \right]^2 \left\| \widehat{U}^\top u \right\|_2^2 \left\| \widehat{V}^\top v \right\|_2^2.$$

4. Non-Oracle Transfer Learning Procedure

The preceding discussions on the oracle transfer learning procedure depend heavily on the representational similarity conditions, i.e., (5) and (6). Otherwise, knowledge transfer estimators might have a much poorer performance than single-task learning using the target dataset alone. This is known as *negative transfer* in the literature (Torrey and Shavlik, 2010). In this section, our aim is to provide solutions to avoid negative representational transfer. It naturally falls into two sub-problems, as (5) and (6) can be violated in the following two different ways.

First, for some shared representations U and V, there could exist some $\Theta_k^* = U_k^* \Lambda_k^* (V_k^*)^\top$ such that $||U_{\perp}^\top U_k^*||_F \gg h$ or/and $||V_{\perp}^\top V_k^*||_F \gg h$. Hence, blindly including all source datasets to estimate shared representations might cause problems. Thus, the first task is to acquire a reliable estimate of the shared representations given potentially harmful source datasets. In principle, there shall be informative sources for U, denoted as $I_U \subseteq [K]$ and informative sources for V, denoted as $I_V \subseteq [K]$, and I_U does not necessarily equal to I_V . Therefore, in the rest of this section, we separately discuss I_U and I_V , instead of a joint informative set I as in the former sections.

Second, in (5) and (6), it is assumed that the column and row subspaces of the target matrix Θ_0^* are in span(U) and span(V), respectively. However, if this is not the case and, say, span (U_0^*) is actually far away from span(U), then the target estimation step in Algorithm 1 would probably result in negative transfer. Hence, we also aim to provide a positive transfer warranty for the target task even if the shared representations are of no benefit to the target study.

In the following assume that we already acquire the unbiased matrix-valued dataset $\mathcal{D}_{[K]} := \{\widetilde{\Theta}_k, k \in [K]\}$ and their corresponding left and right singular subspaces, denoted as \widetilde{P}_k and \widetilde{Q}_k , respectively. We address these two sub-problems mentioned above accordingly as follows.

4.1. Selective subspace integration

For the first problem, we reliably retrieve the shared representations by simultaneously selecting those informative sources. We focus on span(U) here because of symmetry. For $k \in I_U$, the similarity condition $||U_{\perp}^{\top}U_k^*||_F \le h$ is equivalent to

$$d_k := r_k - \operatorname{tr}(P_k^* P_U), \quad \text{such that} \quad 0 \le d_k \le h^2, \tag{12}$$

where $P_k^* = U_k^*(U_k^*)^{\top}$. That is, if $\operatorname{span}(U_k^*)$ is sufficiently close to $\operatorname{span}(U)$, then d_k is small, implying a larger $\operatorname{tr}(P_k^*P_U)$ from (12). Meanwhile, for the oracle case such that I_U is known, we acquire the shared linear representations $P_{\widehat{U}} = \widehat{U}\widehat{U}^{\top}$ from (8), and

$$P_{\widehat{U}} = \operatorname*{arg\,max}_{P \in \mathcal{G}(p,p_0)} \operatorname{tr}(\widetilde{\Sigma}_U P) = \operatorname*{arg\,max}_{P \in \mathcal{G}(p,p_0)} \frac{1}{N_U} \sum_{k \in I_U} n_k \operatorname{tr}(\widetilde{P}_k P), \tag{13}$$

where $N_U := \sum_{k \in I_U} n_k$ and $\mathcal{G}(p, p_0)$ is defined as the set of p_0 -dimensional linear subspaces of \mathbb{R}^p . Inspired by both (12) and (13), we follow Li et al. (2024c) and focus on the following rectified problem that is capable of selecting useful datasets and estimating the shared representation simultaneously:

$$P_{\widehat{U}_{\tau}} = \underset{P \in \mathcal{G}(p,p_0)}{\operatorname{arg\,max}} \frac{1}{N_{[K]}} \sum_{k \in [K]} n_k \max\left\{ \operatorname{tr}(\widetilde{P}_k P), r_k - \tau_U \right\},\tag{14}$$

for $\tau_U \in [0, p_0]$, $P_{\widehat{U}_{\tau}} := \widehat{U}_{\tau} \widehat{U}_{\tau}^{\top}$ and $N_{[K]} = \sum_{k \in [K]} n_k$. Clearly, if $\tau_U = 0$, then (14) is an optimization over a constant and no source information is included. Meanwhile, if $\tau_U = p_0$, then (14) degenerates to the Grassmannian barycenter method such that all sources are included blindly. Ideally, we expect some suitable $\tau_U \in (0, p_0)$ that can separate these informative sources from harmful ones.

To numerically solve (14), we resort to the rectified Grassmannian K-means procedure from Li et al. (2024c). Given any initialization $P_0 \in \mathcal{G}(p, p_0)$, in the *t*-th iteration step we have P_{t-1} from the previous step for $t \ge 1$. Then, we select the informative sources according to $I_U^t = \{k \in [K] \mid \text{tr}[\tilde{P}_k P_{t-1}] \ge r_k - \tau_U\}$. We perform the Grassmannian barycenter method for $k \in I_U^t$, updating P_{t-1} to P_t . We proceed with the iteration until we arrive at convergence. Similarly, for span(V), we could acquire $P_{\hat{V}_{\tau}} := \hat{V}_{\tau} \hat{V}_{\tau}^{\top}$ given some $\tau_V \in [0, q_0]$.

We give a brief remark on the dataset selection capability of the rectified problem (14). We show that the oracle estimator from (13) is also a local maximum of (14) with high probability under certain separability conditions. We only discuss on span(U) here as that on span(V) is basically identical.

Assumption 5 (Separable non-informative sources). For $d_k = r_k - \operatorname{tr}(P_k^* P_U)$ with respect to $k \in \mathcal{I}_U^c := [K] \setminus \mathcal{I}_U$, assume that $d_k \ge d_\tau$ for some $d_\tau > 0$.

COROLLARY 2 (LOCAL MAXIMUM). Under the assumptions of Theorem 1 (replacing I by I_U whenever needed) and Assumption 5, if $h + (rp \log p/N_U)^{1/2} + \max_{k \in I_U^c} \{(rp \log p/n_k)^{1/2}\} = o(d_{\tau})$ as $n_k, p, q \to \infty$, choose any $\tau_U \in [(1-c)d_{\tau}, cd_{\tau}]$ for some $c \in (0.5, 1)$, then $P_{\widehat{U}}$ from (13) is a local maximum of (14) with probability tending to 1.

4.2. Optional knowledge transfer

For the second problem, the new-arrived target matrix may not be well represented by the jointly estimated \hat{U}_{τ} and \hat{V}_{τ} . Thus, further emphasis lies on whether \hat{U}_{τ} and \hat{V}_{τ} can be utilized to enhance the performance of the target task. Motivated by (12) and the corresponding rectified

problem above, we first acquire a matrix completion estimator $\dot{\Theta}_0$ using only the target dataset. The leading r_0 -dimensional left and right singular subspaces of $\dot{\Theta}_0$ are defined as span (\dot{U}_0) and span (\dot{V}_0) , respectively. By comparing the similarity of span (\dot{U}_0) and span (\dot{V}_0) with span (\hat{U}_τ) and span (\hat{V}_τ) respectively before the target estimation step, we judge whether transferring the representational knowledge to the target matrix is helpful. Specifically, let $P_{\dot{U}_0} := \dot{U}_0 \dot{U}_0^{\top}$ and $P_{\dot{V}_0} := \dot{V}_0 \dot{V}_0^{\top}$, for $\delta_U \in [0, r_0]$ and $\delta_V \in [0, r_0]$, let

$$\widehat{U}_{\tau}^{\delta} = \begin{cases} \widehat{U}_{\tau}, & \text{if } \operatorname{tr}(P_{\dot{U}_{0}}P_{\hat{U}_{\tau}}) \ge r_{0} - \delta_{U}, \\ \dot{U}_{0}, & \text{if } \operatorname{tr}(P_{\dot{U}_{0}}P_{\hat{U}_{\tau}}) < r_{0} - \delta_{U}, \end{cases} \quad \widehat{V}_{\tau}^{\delta} = \begin{cases} \widehat{V}_{\tau}, & \text{if } \operatorname{tr}(P_{\dot{V}_{0}}P_{\hat{V}_{\tau}}) \ge r_{0} - \delta_{V}, \\ \dot{V}_{0}, & \text{if } \operatorname{tr}(P_{\dot{V}_{0}}P_{\hat{V}_{\tau}}) < r_{0} - \delta_{V}. \end{cases}$$
(15)

Algorithm 2. The pseudo algorithm for non-oracle representational transfer.

Require:

 $(X_{k,i}, y_{k,i})$ for $k \in \mathcal{I} = [K]$; cut-off dimensions p_0, q_0 ; tuning parameters $\tau_U, \tau_V, \delta_U, \delta_V$; **Ensure:**

1. unbiased dataset: for $k \in I$, acquire an unbiased estimator $\widetilde{\Theta}_k$ of Θ_k^* , construct the unbiased matrix-valued dataset $\mathcal{D}_I := \{\widetilde{\Theta}_k, k \in I\};$

2. selective and optional transfer: acquire the selective and optional linear representations $\widehat{U}_{\tau}^{\delta}$ and $\widehat{V}_{\tau}^{\delta}$ following the procedures of this section; 3. target estimation: for $\widehat{Z}_{0,i}^{\tau,\delta} := (\widehat{U}_{\tau}^{\delta})^{\top} X_{0,i} \widehat{V}_{\tau}^{\delta}$, apply ordinary least squares to the projected

3. target estimation: for $Z_{0,i}^{\tau,\delta} := (U_{\tau}^{\delta})^{\top} X_{0,i} V_{\tau}^{\delta}$, apply ordinary least squares to the projected dataset $\{(\widehat{Z}_{0,i}^{\tau,\delta}, y_{0,i})\}_{i=1}^{n_0}$, so as to obtain the $p_0 \times q_0$ parameter matrix $\widehat{\Gamma}_0^{\tau,\delta}$; **return** $\widehat{\Theta}_0^{\tau,\delta} = \widehat{U}_{\tau}^{\delta} \widehat{\Gamma}_0^{\tau,\delta} (\widehat{V}_{\tau}^{\delta})^{\top}$.

Finally, we plug in $\widehat{U}_{\tau}^{\delta}$ and $\widehat{V}_{\tau}^{\delta}$ into the target estimation step. The Non-ORAcle (Nora) representational transfer procedures are summarized in the pseudo Algorithm 2. We end this section with a few remarks. First, if P_{U_0} is estimated using our default matrix completion method (Xia and Yuan, 2021), it shall be mathematically equivalent to the estimator acquired by plugging both \dot{U}_0 and \dot{V}_0 into the target estimation step by construction. That is to say, if we choose the most conservative $\delta_U = \delta_V = 0$ so that $\widehat{U}_{\tau}^{\delta} = \dot{U}_0$ and $\widehat{V}_{\tau}^{\delta} = \dot{V}_0$, the resulting estimator from Algorithm 2 is equivalent to the target matrix completion estimator. Meanwhile, analogously to the claims in Corollary 2, if $h + (rp \log p/N_U)^{1/2} + (rp \log p/n_0)^{1/2} = o(\delta_U)$ for some $\delta_U > 0$, the probability that we correctly identify and include the oracle $P_{\widehat{U}}$ into target estimation tends to 1 as $n_0, n_k, p, q \to \infty$. Almost identical arguments hold for span(V). In short, Algorithm 2 is capable of simultaneously selecting useful sources and transferring representational information with positive warranty.

5. NUMERICAL SIMULATION

In this section, we perform numerical simulation to validate the usefulness of the proposed methods. We generate the datasets as follows. We first take a p_0 dimensional span(U) uniformly, that is, with respect to the Haar measure, from $\mathcal{G}(p, p_0)$. Similarly, we uniformly sample a q_0 dimensional span(V) from $\mathcal{G}(q, q_0)$. As any subspace can be uniquely represented by the orthogonal projector from \mathbb{R}^p onto itself, we write the corresponding projection matrices as P_U and P_V .

Then, define GOE(p) as the $p \times p$ symmetric random matrix with off-diagonal entries taken independently from N(0, $(2p)^{-1}$) and the diagonal entries taken independently from N(0, $(p)^{-1}$),



Fig. 1. Comparison of various methods under different scenarios, i.e., scenario A, B and C from left to right. The proposed non-oracle knowledge transfer algorithm demonstrates its advantage across the three given settings.

for $\Theta_k^* = U_k^* \Lambda_k^* (V_k^*)^\top$, $k \in \{0\} \cup [K]$, we generate U_k^* and V_k^* in the following four ways: (i) U_k^* and V_k^* are acquired by taking the leading r_k eigenvectors of $P_U + hG_k$ and $P_V + hH_k$ respectively, where G_k is generated independently from GOE(p), while H_k is generated independently from GOE(q); (ii) U_k^* is the leading r_k eigenvectors of $P_U + hG_k$, while V_k^* is sampled uniformly from $\mathcal{G}(q, r_k)$; (iii) U_k^* is sampled uniformly from $\mathcal{G}(p, r_k)$, while V_k^* is the leading r_k eigenvectors of $P_V + hH_k$; (iv) U_k^* and V_k^* are sampled uniformly from $\mathcal{G}(p, r_k)$ and $\mathcal{G}(q, r_k)$, respectively. For all 4 cases, Λ_k^* is generated as a $r_k \times r_k$ diagonal matrix whose diagonal elements are drawn independently from Uniform(1, 2) distribution.

For the sources, that is, for $k \in [K]$, we generate K/2 of Θ_k^* from (i), and K/6 each from (ii), (iii) and (iv), so that not all left and right singular subspaces from the sources are informative. Meanwhile, we take the target matrix Θ_0^* from (i), (ii) and (iv), leading to three scenarios: scenario A where Θ_0^* is taken from (i), and it can take advantage of both column and row representations from the informative sources; scenario B where Θ_0^* is taken from (ii), and only one side of the representational information is useful; scenario C where Θ_0^* is taken from (iv), and the target completion task cannot benefit from the sources and we shall be cautious about the negative transfer. We set p = q = 100, $p_0 = q_0 = 5$, $r_k = 3$ and h = 0.1. For $k \in \{0\} \cup [K]$ where $k \in \{24, 36, 48, 60, 72\}$, we uniformly sample $n_k = 2500$ entries of Θ_k^* contaminated by additive noise with $\sigma_k = 1$.

We compare Algorithm 2 with various methods, where the unbiased matrix-valued dataset $\mathcal{D}_{[K]}$ is generated by the default *J*-fold sample splitting with J = 5. For the competitors, we consider the following. 1. The target matrix completion estimator by applying our default matrix completion method, i.e. the calibrated Grassmannian gradient descent algorithm without sample splitting from Xia and Yuan (2021), on the target dataset; 2. the two-step matrix completion estimator by first using the default matrix completion method on the pooled observed samples and then using the same default matrix completion to estimate the contrast by the target dataset; 3. the first slice of the tensor-Tucker completion estimator using the power iteration method from Xia et al. (2021), treating all observations as if they are from a $(K + 1) \times p \times q$ stacked tensor with missing entries.

In Figure 1, we report the average relative completion error of each estimator of the target matrix, defined as $\|\cdot -\Theta_0^*\|_E^2 / \|\Theta_0^*\|_E^2$, based on 100 replications. We can see that Algorithm 2

Transfer Matrix Completion

shows an advantage over competing methods in all settings. In particular, in both scenario B and scenario C, our selective and optional transfer algorithm performs not worse than the target matrix completion estimator, demonstrating its robustness against useless source information, while the blind tensor-Tucker completion method leads to devastating negative transfer.

6. Real Data Experiment

In this section, we provide empirical evidence on the practical usefulness of the proposed method. To do this, we first take the COVID-19 computed tomography (CT) chest scans dataset from Zhang et al. (2022), which includes 349 gray-scale chest scan images from COVID-19 positive patients. Typically, a gray-scale image is stored as a matrix. The elements of the matrix depict the color depth of the pixels, ranging from 0 to 255. We first resize all the images to the size of 150×150 using the Python package PIL. Then we standardize the pixel values by subtracting all the elements by 255/2 and then dividing them by 255.



Fig. 2. For each panel, from left to right are respectively: (a) the partially observed image; (b) the target completed image using the target dataset only; (c) the two-step completed image by debiasing the Euclidean mean of the sources; (d) the first slice of the tensor-Tucker completion estimator and (e) the representational transferred completed image by utilizing the subspace information from the sources.

For visual illustration, each time we choose one of the three typical CT images to be the target, denoted by Θ_0^* . We uniformly sample $n_0 = 6000$ elements from Θ_0^* with $\sigma_0 = 1$, forming the target dataset $\{(X_{0,i}, y_{0,i})\}_{i=1}^{n_0}$. For each target dataset, we randomly take K = 30 fully observed sources from the dataset, denoted as $\{\Theta_k^*\}_{k=1}^{30}$. We plot the following images in each panel of Figure 2: (a) the partially observed target image; (b) the target completed image using the target dataset only; (c) the two-step completed image by debiasing the Euclidean mean of the sources, namely $\sum_{k=1}^{K} \Theta_k^*/K$; (d) the tensor-Tucker completed image by taking the first slice of the $(K + 1) \times p \times q$ stacked tensor; and (e) the representational transferred completed image integrating the subspace information from the sources by Algorithm 1. To acquire the left and right subspaces, namely \widehat{U} and \widehat{V} , from the sources, we apply the one-round Grassmannian barycenter method with $p_0 = q_0 = 40$ and $r_k = 20$. The cut-off dimensions are determined in a fully unsupervised manner

following Li et al. (2024a). We can see that the target completed image, the two-step completed image, and the tensor-Tucker completed image are all blurry and difficult to interpret. In contrast, the completed image after representational transfer is able to retrieve most of the pathological features of the original image. Figure 2 visually justifies the representational similarity in this analysis of the real dataset.

7. Discussion

For saving space, we delegate extensional arguments on the fully observed sources and the determination of cut-off dimensions to the supplementary material. We also report additional simulation results that validate the statistical error rate in Theorem 1 and the asymptotic normality of the post-transfer bilinear forms estimators. A real data example on functional magnetic resonance imaging (fMRI) of patients with attention deficit hyperactivity disorder (ADHD) at different sites is also provided. All the proofs of our theoretical results can be found in the supplementary material. For further extensions, it is rather straightforward to extend the procedures in this work to higher-order tensors. Meanwhile, it will be intriguing to take advantage of the kernel methods to integrate the non-linear representational information in an unsupervised manner (Couillet and Liao, 2022; He et al., 2024).

References

- Bastani, H. (2021). Predicting with proxies: Transfer learning in high dimension. *Management Science*, 67(5):2964–2984.
- Cai, T. T. and Wei, H. (2021). Transfer learning for nonparametric classification: Minimax rate and adaptive classifier. *The Annals of Statistics*, 49(1).
- Cai, T. T. and Zhang, A. (2015). Rop: Matrix recovery via rank-one projections.
- Cai, T. T. and Zhou, W. X. (2016). Matrix completion via max-norm constrained optimization.
- Candes, E. and Recht, B. (2012). Exact matrix completion via convex optimization. *Communications of the ACM*, 55(6):111–119.
- Candes, E. J. and Plan, Y. (2010). Matrix completion with noise. Proceedings of the IEEE, 98(6):925-936.
- Candès, E. J. and Tao, T. (2010). The power of convex relaxation: Near-optimal matrix completion. *IEEE transactions on information theory*, 56(5):2053–2080.
- Carpentier, A. and Kim, A. K. (2018). An iterative hard thresholding estimator for low rank matrix recovery with explicit limiting distribution. *Statistica Sinica*, 28(3):1371–1393.
- Carpentier, A., Klopp, O., Löffler, M., and Nickl, R. (2018). Adaptive confidence sets for matrix completion.
- Chen, E. Y. and Fan, J. (2021). Statistical inference for high-dimensional matrix-variate factor models. *Journal of the American Statistical Association*, pages 1–18.
- Chen, Y., Chi, Y., Fan, J., Ma, C., and Yan, Y. (2020). Noisy matrix completion: Understanding statistical guarantees for convex relaxation via nonconvex optimization. *SIAM journal on optimization*, 30(4):3098–3121.
- Chen, Y., Fan, J., Ma, C., and Yan, Y. (2019). Inference and uncertainty quantification for noisy matrix completion. Proceedings of the National Academy of Sciences, 116(46):22931–22937.
- Chernozhukov, V., Chetverikov, D., Demirer, M., Duflo, E., Hansen, C., Newey, W., and Robins, J. (2018). Double/debiased machine learning for treatment and structural parameters.
- Couillet, R. and Liao, Z. (2022). Random matrix methods for machine learning. Cambridge University Press.
- Fan, J., Wang, D., Wang, K., and Zhu, Z. (2019). Distributed estimation of principal eigenspaces. Annals of statistics, 47(6):3009.
- He, B., Liu, H., Zhang, X., and Huang, J. (2024). Representation transfer learning for semiparametric regression. *arXiv preprint arXiv:2406.13197*.

Javanmard, A. and Montanari, A. (2014). Confidence intervals and hypothesis testing for high-dimensional regression. *The Journal of Machine Learning Research*, 15(1):2869–2909.

- Keshavan, R., Montanari, A., and Oh, S. (2009). Matrix completion from noisy entries. Advances in neural information processing systems, 22.
- Li, S., Cai, T. T., and Li, H. (2022). Transfer learning for high-dimensional linear regression: Prediction, estimation and minimax optimality. *Journal of the Royal Statistical Society Series B: Statistical Methodology*, 84(1):149–173.
- Li, S., Zhang, L., Cai, T. T., and Li, H. (2023). Estimation and inference for high-dimensional generalized linear models with knowledge transfer. *Journal of the American Statistical Association*, pages 1–12.

- Li, Z., He, Y., Xinbing, K., and Xinsheng, Z. (2024a). Robust two-way dimension reduction by grassmannian barycenter. *Journal of Multivariate Analysis (accepted)*.
- Li, Z., Liu, D., He, Y., and Zhang, X. (2024b). Simultaneous estimation and dataset selection for transfer learning in high dimensions by a non-convex penalty. *arXiv:2306.04182v3*.
- Li, Z., Qin, K., He, Y., Zhou, W., and Zhang, X. (2024c). Knowledge transfer across multiple principal component analysis studies. *arXiv preprint arXiv:2403.07431*.
- Ma, C., Wang, K., Chi, Y., and Chen, Y. (2018). Implicit regularization in nonconvex statistical estimation: Gradient descent converges linearly for phase retrieval and matrix completion. In *International Conference on Machine Learning*, pages 3345–3354. PMLR.
- Negahban, S. and Wainwright, M. J. (2011). Estimation of (near) low-rank matrices with noise and high-dimensional scaling. *The Annals of Statistics*, 39(2):1069–1097.
- Negahban, S. and Wainwright, M. J. (2012). Restricted strong convexity and weighted matrix completion: Optimal bounds with noise. *The Journal of Machine Learning Research*, 13:1665–1697.
- Qiao, S., He, Y., and Zhou, W. (2023). Transfer learning for high-dimensional quantile regression with statistical guarantee. Available upon request.
- Reeve, H. W., Cannings, T. I., and Samworth, R. J. (2021). Adaptive transfer learning. *The Annals of Statistics*, 49(6):3618–3649.
- Sun, S., Bajwa, W. U., and Petropulu, A. P. (2015). Mimo-mc radar: A mimo radar approach based on matrix completion. *IEEE Transactions on Aerospace and Electronic Systems*, 51(3):1839–1852.
- Tian, Y. and Feng, Y. (2022). Transfer learning under high-dimensional generalized linear models. *Journal of the American Statistical Association*, pages 1–14.
- Tian, Y., Gu, Y., and Feng, Y. (2023). Learning from similar linear representations: adaptivity, minimaxity, and robustness. *arXiv preprint arXiv:2303.17765*.
- Torrey, L. and Shavlik, J. (2010). Transfer learning. In Handbook of research on machine learning applications and trends: algorithms, methods, and techniques, pages 242–264. IGI global.
- Van de Geer, S., Bühlmann, P., Ritov, Y., and Dezeure, R. (2014). On asymptotically optimal confidence regions and tests for high-dimensional models.
- Vershynin, R. (2018). High-dimensional probability: An introduction with applications in data science, volume 47. Cambridge university press.
- Wang, D., Liu, X., and Chen, R. (2019). Factor models for matrix-valued high-dimensional time series. *Journal of Econometrics*, 208(1):231–248.
- Wang, L., Zhang, X., and Gu, Q. (2017). A unified computational and statistical framework for nonconvex low-rank matrix estimation. In *Artificial Intelligence and Statistics*, pages 981–990. PMLR.
- Xia, D. (2019). Confidence region of singular subspaces for low-rank matrix regression. *IEEE Transactions on Information Theory*, 65(11):7437–7459.
- Xia, D. and Yuan, M. (2021). Statistical inferences of linear forms for noisy matrix completion. Journal of the Royal Statistical Society Series B: Statistical Methodology, 83(1):58–77.
- Xia, D., Yuan, M., and Zhang, C.-H. (2021). Statistically optimal and computationally efficient low rank tensor completion from noisy entries.

Yan, H. and Chen, S. X. (2024). Transfer learning with general estimating equations. arXiv preprint arXiv:2410.04398.

- Yu, L., He, Y., Kong, X., and Zhang, X. (2022). Projected estimation for large-dimensional matrix factor models. *Journal of Econometrics*, 229(1):201–217.
- Yuan, M. and Zhang, C.-H. (2016). On tensor completion via nuclear norm minimization. Foundations of Computational Mathematics, 16(4):1031–1068.
- Yuan, M. and Zhang, C.-H. (2017). Incoherent tensor norms and their applications in higher order tensor completion. *IEEE Transactions on Information Theory*, 63(10):6753–6766.
- Zhang, D. and Zhou, Z.-H. (2005). (2D)²PCA: Two-directional two-dimensional PCA for efficient face representation and recognition. *Neurocomputing*, 69(1-3):224–231.
- Zhang, Y., Zhang, X., Zhang, H., and Liu, C. (2022). Low-rank latent matrix factor-analysis modeling for generalized linear regression with high-dimensional imaging biomarkers. arXiv preprint arXiv:2205.14454.
- Zhao, T., Wang, Z., and Liu, H. (2015). A nonconvex optimization framework for low rank matrix estimation. Advances in Neural Information Processing Systems, 28.
- Zheng, R. and Tang, M. (2022). Limit results for distributed estimation of invariant subspaces in multiple networks inference and pca. arXiv preprint arXiv:2206.04306.
- Zhuang, F., Qi, Z., Duan, K., Xi, D., Zhu, Y., Zhu, H., Xiong, H., and He, Q. (2020). A comprehensive survey on transfer learning. *Proceedings of the IEEE*, 109(1):43–76.