Seeing the Forest and the Trees: Solving Visual Graph and Tree Based Data Structure Problems Using Large Multimodal Models

Sebastian Gutierrez Temple University Philadelphia, PA, USA guts@temple.edu

Kenneth Angelikas Temple University Philadelphia, PA, USA kenneth.angelikas@temple.edu

James Prather Abilene Christian University Abilene, TX, USA james.prather@acu.edu

ABSTRACT

Recent advancements in generative AI systems have raised concerns about academic integrity among educators. Beyond excelling at solving programming problems and text-based multiple-choice questions, recent research has also found that large multimodal models (LMMs) can solve Parsons problems based only on an image. However, such problems are still inherently text-based and rely on the capabilities of the models to convert the images of code blocks to their corresponding text. In this paper, we further investigate the capabilities of LMMs to solve graph and tree data structure problems based only on images. To achieve this, we computationally construct and evaluate a novel benchmark dataset comprising 9,072 samples of diverse graph and tree data structure tasks to assess the performance of the GPT-40, GPT-4 with Vision (GPT-4V), Gemini 1.5 Pro, Gemini 1.5 Flash, Gemini 1.0 Pro Vision, and Claude 3 model families. GPT-40 and Gemini 1.5 Flash performed best on trees and graphs respectively. GPT-40 achieved 87.6% accuracy on tree samples, while Gemini 1.5 Flash, achieved 56.2% accuracy on graph samples. Our findings highlight the influence of structural and visual variations on model performance. This research not only introduces an LMM benchmark to facilitate replication and further exploration but also underscores the potential of LMMs in solving complex computing problems, with important implications for pedagogy and assessment practices.

CCS CONCEPTS

• Social and professional topics → Computing education.

Irene Hou Temple University Philadelphia, PA, USA irene.hou@temple.edu

Owen Man Temple University Philadelphia, PA, USA owen.man@temple.edu

Paul Denny The University of Auckland Auckland, New Zealand paul@cs.auckland.ac.nz

KEYWORDS

Generative AI, Academic Integrity, Computing Education, Large Multimodal Models, LMMs, Large Language Models, LLMs

Jihye Lee

Temple University Philadelphia, PA, USA

jihye.lee0003@temple.edu

Sophia Mettille

Temple University

Philadelphia, PA, USA

sophia.mettille@temple.edu

Stephen MacNeil

Temple University

Philadelphia, PA, USA

stephen.macneil@temple.edu

ACM Reference Format:

Sebastian Gutierrez, Irene Hou, Jihye Lee, Kenneth Angelikas, Owen Man, Sophia Mettille, James Prather, Paul Denny, and Stephen MacNeil. 2024. Seeing the Forest and the Trees: Solving Visual Graph and Tree Based Data Structure Problems Using Large Multimodal Models. In ,. ACM, New York, NY, USA, 14 pages.

1 INTRODUCTION

Generative AI is increasingly prevalent in computing education, with diverse applications that range from code generation [2, 13, 21, 55, 68] and high-quality code explanations [4, 5, 41, 46, 47, 68] to debugging code [43, 50]. Consequently, many students now report using them as a primary help resource [34, 53, 70]. However, the capabilities of generative AI extend beyond mere coding support; students can also leveraging these technologies to answer multiplechoice questions [59, 61] and solve text-based programming problems [25, 33, 56]. The emergence of multimodal models has further transformed this landscape by enabling the comprehension and generation of visual data, thereby enhancing the models' ability to engage with complex educational tasks. While this advancement presents new opportunities for learning, it simultaneously raises significant concerns among researchers and educators regarding assessment integrity and the potential for misuse in academic settings [40, 44, 52, 53, 70].

To deter unsanctioned use of large language models (LLMs) among students, researchers have proposed solutions such as humanproctored exams [36, 53, 58, 64, 70] and visual-based questions that challenge the text-only modalities of LLMs [15, 22, 50]. However, human-proctored exams come with inherent limitations, including biases in test-taking and scalability challenges that can hinder their effectiveness [17, 20, 32, 69]. Although AI-proctored systems offer a potential solution to scalability issues for online exams, they introduce a range of new concerns, such as breaches

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than the author(s) must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from permissions@acm.org.

ACE 2025,

^{© 2024} Copyright held by the owner/author(s). Publication rights licensed to ACM.

of privacy and autonomy, barriers to accessibility, and the risk of negative biases [11, 16, 28, 30]. While representing programming problems visually—through diagrams or images—has historically limited LLMs' problem-solving capabilities [22, 50], the advent of multimodal models that can process both images and text poses a significant challenge to this approach. Recent studies, such as those by Hou et al., have demonstrated these models' remarkable performance on visual programming problems, including Parsons problems [33]. This development underscores the urgent need for further investigation into the capabilities of multimodal models in visual problem-solving contexts. As these models become increasingly proficient in handling complex computational tasks, the potential for academic dishonesty grows, complicating traditional assessment strategies.

This paper builds upon previous research regarding the vision capabilities of large multimodal models (LMMs) by systematically evaluating the performance of several advanced models, including GPT-40, GPT-4V, Gemini 1.5 Flash, Gemini 1.5 Pro, Gemini 1.0 Pro Vision, and the Claude 3 model family. To mitigate data leakage, we computationally constructed a benchmark dataset comprising 9,072 diverse graph and tree data structure problems, designed to assess how these models handle variations in both *aesthetic features (such as edge width and node color)* and *structural characteristics (including density, layout, and the number of nodes and edges)*. Through this evaluation, we aim to gain insights into the strengths and limitations to inform computing education pedagogy and assessment.

We investigate the following research questions:

- **RQ 1** How well do large multi-modal models perform operational and representational tasks on graph and tree data structures?
- **RQ 2** How do variations in the graph and tree's structural features influence the accuracy of large multimodal models?
- **RQ 3** How do variations in the graph and tree's aesthetic features influence the accuracy of large multimodal models?

Our results indicate that these multimodal models are capable of performing operational and representational tasks on graphs and trees to varying degrees, depending on structural and aesthetic variations. GPT-40 was a top-performer on tree-based problems with 87.6% accuracy, but only 44.7% on graph problems. This study highlights both the challenges that models face and the growing concerns for educators, particularly as LMMs are expected to continue improving. To facilitate replication and further research with new models, we also contribute an open-source repository for generating graph and tree problems. We conclude with a discussion on the implications for pedagogy and assessment practices. We offer the following contributions:

- Empirical evaluation of multimodal models on data structure tasks: We provide a comprehensive analysis of multiple multimodal models' performance on visually represented graph and tree problems, highlighting their varying abilities to handle different structural and aesthetic aspects.
- A benchmark dataset for assessing multimodal model capabilities: We introduce a novel dataset of 9,072 data structures problems that vary across structural and visual attributes.
- An open-source tool for generating graph and tree problems: We contribute a tool to create diverse graph and tree problems,

supporting further research and the development of new

2 RELATED WORK

2.1 Graphs and Trees in Computing Education

benchmarks as multimodal models evolve.

Graph and tree data structures are core components of most computing education curricula [35, 62]. Considered foundational topics in CS2 data structures and algorithm courses, students are expected to be able to represent and operate various tasks on graphs and trees [35]. Common examples of graph and tree tasks focus on traversals, insertions, deletions, and efficiency calculations on derivatives such as binary trees (BT), binary search trees (BST), directed graphs (DG), and undirected graphs (UG) [35]. Previous work emphasizes the value of teaching graph theory concepts to students of all ages [26]; these concepts are often important across multiple domains and industries [57, 67].

While critical to computer science, graph theory can be complex to grasp [18]. Prior research has identified popular student misconceptions and errors, such as assuming binary search trees are balanced by default or performing insertions at the wrong node [37, 71, 71]. Students also struggle with traversing BSTs [49], understanding the distinction between heaps and trees, [19], and implementing error-free recursive code for operations [29]. Students especially need help with algorithmic implementation [48].

Given that graphs and tree problems are notoriously challenging for students, pedagogical strategies and visualization techniques have been devised to support the representation of these concepts. For example, students' understanding can be improved with visualizations, drawing attention to the relationships between nodes, branches, and structure [8, 10, 51, 63, 72].

Based on this difficulty and visual complexity, these problems are an effective benchmark for testing the spatial reasoning capabilities of mulitmodal models in computing education. Prior work demonstrated that these models can solve text-based Parsons problems based only on images, though those tasks required limited spatial reasoning ability [33]. However, graphs can be represented in multiple styles with nodes and links placed in varied ways.

2.2 Generative AI Threats to Assessment

The emergence of LLMs and LMMs has sparked widespread concern among educators regarding effective assessment methods in computing education. Educators are particularly worried about academic integrity and the potential for students to overly rely on generative AI tools, potentially compromising genuine learning [3, 40, 45, 53, 70]. These concerns have only been amplified by recent research on the wide-ranging capabilities of these models in computing contexts such as solving programming problems [13, 25, 33, 55, 56, 68] and performing as well as students on multiple choice quizzes [59, 60].

While some instructors initially leaned towards prohibiting AI models in the classroom, many believe that 'resistance is futile' and that regardless of sanctions, students would use them [40, 70]. Most computing students report being aware of these models and seeking help from them on a regular basis [7, 34]. In response, some practitioners are adopting more structured uses of AI tools in classrooms, allowing students guided access to these models [38, 42], while

others are developing problems to circumvent student usage [22]. Discourse on circumventing LLM usage also includes possibilities of returning to proctored or oral exams [36, 64, 70], despite known challenges and biases [11, 16, 28, 30]. Despite a potential 'arms race' between AI capabilities and instructor interventions, and capabilities continue to improve. More recently, multimodal models have emerged which can process text and image data. A recent paper [33] showed that multimodal models can even solve Parsons problems based only on an image of the problem.

3 METHODOLOGY

Building on previous research that benchmarks the performance of LLMs and LMMs in computing education [12, 33, 56], we evaluated the capabilities of LMMs, such as GPT-4V, in solving visual programming problems.

Recognizing that image-based problems can help mitigate cheating in computing education contexts [22], and noting the limited research on evaluating visual problem-solving skills [33], we investigate the ability of LMMs to solve tree and graph data structures problems. We hypothesize that these problems will present unique challenges due to their reliance on spatial reasoning. Our goal is to uncover insights into the interpretative and spatial reasoning abilities of LMMs, representing a significant advancement in understanding their applications in educational contexts. This section describes the creation of our dataset and our evaluation process.

3.1 Creating the Benchmark Dataset

Data leakage presents significant challenges when evaluating the performance of LLMs and LMMs. These models are typically trained on extensive datasets sourced from the internet, which raises the risk that they may encounter similar problems during both training and testing phases. If the test dataset includes problems that already exist online, the model could leverage its prior knowledge to solve these problems, rather than demonstrating its true problem-solving capabilities. This situation can result in inflated performance metrics, ultimately undermining the validity of the evaluation.

To mitigate this issue, we developed a benchmark dataset comprising graph and tree problems that do not exist on the internet. We created a Python script to programmatically generate these graphs and trees, ensuring diverse yet systematic variations. By guaranteeing that the problems are unique and not previously encountered by the model, we significantly reduce the risk of data leakage and enhance the reliability of our assessments.

In our commitment to advancing the research community, we have made both the generator and the benchmark dataset publicly available on GitHub under an MIT license¹. By providing these resources, we aim to foster collaboration, facilitate replication, and encourage the extension of our findings, thereby establishing a solid foundation for future investigations into the capabilities of large multimodal models in tackling complex programming challenges.

3.1.1 Task Criteria. We establish a rigorous process for obtaining graph and tree data structures vision tasks. We seek to create a standard, repeatable method to ensure consistent and reliable task selection through clear inclusion and exclusion factors.

- Curricular Grounding: Subject areas were sourced from the ACM computer science curriculum guidelines [65] to minimize bias and ensure the selection of relevant topics.
- (2) Alignment with Core Topics and Learning Objectives: Evaluation tasks are selected based on their relevance to the core topics and learning objectives outlined in the curriculum guidelines, ensuring that the tasks are contextually appropriate and aligned with educational goals.
- (3) Adherence to Task Standards: Each task requires multimodal reasoning, including object reasoning, spatial relations, and counting. We designed tasks to (a) maximize open-endedness, (b) minimize unnecessary image prompt details, and (c) reduce dependence on explicit output formats, aligning with best practices for vision-language tasks [1].
- (4) Image Specifications: Images are standardized to a 1:1 aspect ratio and 512x512 resolution, which represents the minimum resolution recommended by the models' API guides at the time of publication. This standardization allows for a systematic assessment of model performance.

This comprehensive approach allows a diverse and robust dataset that enables in-depth analysis of model capabilities on graph and tree data structures vision-language tasks.

3.1.2 Task Selection. The selection of samples is guided based on the Curriculum Guidelines for Undergraduate Degree Programs in Computer Science. Specifically, we focus on the topics classified under 'Core Tier 1' in the 'Fundamental Data Structures and Algorithms' course of the 'Algorithms and Complexity (AL)' domain. We are particularly concerned with the following tasks:

> **Binary search trees:** Common operations on binary search trees such as select min, max, insert, delete, iterate over tree.

> **Graphs and graph algorithms:** Representations of graphs (e.g., adjacency list, adjacency matrix) and traversals (e.g.: breadth- and depth-first).

We also ensure that the tasks are aligned with core curriculum standards and the learning outcomes for data structures courses. We are particularly focused on the eighth learning outcome:

Solve problems using fundamental graph algorithms, including depth-first and breadth-first search. [Usage]

Based on these curricular topics and learning objectives, we are able to justify our epistemic decisions. We adopted four structures: binary tree, binary search tree, undirected graph, and directed graph. We also focused on key tasks, such as traversals. This selection process ensures educational relevance for our work.

3.1.3 Process for Constructing the Benchmark Dataset. To construct our benchmark dataset, we followed the process outlined in Figure 1. Initially, three authors sourced problems from academic textbooks, ensuring alignment with our previously established criteria. This step enabled us to identify key variations in the representation of graphs and trees, including node values, node colors, and edge widths. Leveraging these variations, we programmatically generated our benchmark dataset. We created a Python script that used graph libraries (i.e. *networkx* and *matplotlib*) to systematically create relevant images for the vision-language tasks.

¹https://github.com/gutbash/lmm-graph-vision



Figure 1: Overview of our benchmark dataset creation process, illustrating the transition from dataset construction to model evaluation. The image prompt set I and text prompt set Q are generated as follows: each image I_i has a combination of attributes where s denotes data structure type, n denotes the number of nodes, v denotes variation of node values, e denotes edge width, and c denotes node color. A text prompt Q_i combines attributes, where s denotes data structure type and t denotes the operational task category. The sets of image and text prompts combine to form the dataset D, where they are fed to the model M_i .

As shown in Figure 1, the resulting structured dataset, denoted as D, consists of vision-language task instances designed to assess the capabilities of multimodal systems. Each instance within Dis a tuple $(I_i, Q_i, A_i^{\text{true}})$, where I_i is an image prompt from a set of images I (see Figure 2) depicting a graph or tree, Q_i is a text prompt that asserts an imperative task relevant to I_i from a set of text prompts Q, and A_i^{true} is the accurate solution or answer to Q_i with respect to I_i from a set of ground truth answers A^{true} .

The graph-related tasks form the subset D_G , composed of individual instances ($I_{gi}, Q_{gi}, A_{gi}^{true}$), where each I_{gi} is an image prompt of a graph structure, Q_{gi} the accompanying text prompt, and A_{gi}^{true} the ground truth answer. This subset is further divided into tasks concerning undirected graphs D_{UG} and directed graphs D_{DG} , facilitating an in-depth examination of model performance on each graph type. Tree-related tasks are similarly compiled into subset D_T , with each instance ($I_{ti}, Q_{ti}, A_{ti}^{true}$) representing a tree structure question and its answer. This subset is bifurcated into binary tree tasks D_{BT} and binary search tree tasks D_{BST} , allowing the assessment to account for the nuanced differences in processing and analyzing these particular tree structures.

Each image I_i has a combination of attributes where *s* denotes the type of data structure (BST, BT, UG, DG), *n* denotes the number of nodes (3-9), *v* denotes variation of node values given a data structure, *e* denotes rendered edge width (1.0 or 5.0), and *c* denotes node background fill color (yellow or white). A text prompt Q_i combines attributes, where *s* denotes data structure type and *t* denotes the task (i.e. post order, in order, breadth-first search, etc.).

The dataset is divided equally between graph ($|D_G| = 4536$) and tree ($|D_G| = 4536$) problems, with a further subdivision into tasks for binary tree, binary search tree, directed graph, and undirected graph categories where $|D_{BT}| = 2268$, $|D_{BST}| = 2268$, $|D_{UG}| =$ 2268, and $|D_{DG}| = 2268$. The dataset comprises a set of 9072 tasks where |D| = 9072. These tasks are fed to a given model M_i .

Using our framework and carefully selecting features are deliberate choices that enhance the dataset's utility for future research. We aim to create a resource that serves current educational needs and sets a precedent for creating comprehensive vision-language task datasets that are conducive to advancements in the field.

3.2 Prompt Engineering

We establish a standard prompt method across all tasks as a zeroshot imperative task to the model in reference to the paired image. The schema consists of a user message with the text and base64 image prompts, followed by the model response as a prediction. We do not include a system message as the Gemini models currently do not support it. These base prompts are templates that contain two keys to insert information related to the given image prompt. One key is for the given data structure, such as a binary tree, and the other is a vertex node for graph prompts to instruct a model where to start a search traversal.

These prompts align with our task criteria, where no step-by-step instructions are given to perform the task correctly, remaining openended. The prompts also do not indicate the data structure's content other than the identification of the structure's type, minimizing image details. The only exceptions to this are depth-first search and breadth-first search tasks where a starting vertex was provided. The prompt does not explicitly mention the programming language, but the type annotation is in Python. We specify such a format to allow the prediction to be extracted using regular expressions.Three base text prompts take this described form:

Provide a list[int] of vertices representing the *{pre-order, in-order, post-order traversal}* for the image of the **{structure}**.

Provide a dict[int, list[int]] of vertices and their edges representing the adjacency list for the image of the **{structure}**.

Provide a list[int] of vertices representing the *{depth-first, breadth-first}* search traversal for the image of the **{structure}** starting from vertex **{vertex}**.

Seeing the Forest and the Trees



Figure 2: The complete set of images from the dataset.

Preemptive sample evaluations on Gemini 1.0 Pro Vision show minimal differences in accuracy compared to the six prompts tested, so our premise around how to prompt the model focuses on zeroshot learning. This involves evaluating model performance without examples. This simpler prompting technique is probably more likely among computing students than more advanced techniques. Instructions expect an output format in Python type annotations, though they do not express an explicit language intent. The prompt specifies the existence of an image and its general subject but does not expose any more information unless necessary for the task. These specifications align with our established standards and ensure isolated consistency in predictions across different categories.

3.3 Model Selection

To select models for this study, we aimed to align with established research practices while incorporating diversity and leveraging the most state-of-the-art models. Consequently, we first used OpenAI's GPT-4V model due to its widespread use in LMM benchmarks and popularity among both researchers and consumers (via ChatGPT). Initially, we conducted preliminary tests comparing GPT-4V with Google's Bard (prior to its rebranding as Gemini) to broaden our investigation. During these tests, we observed that Bard demonstrated inferior performance in our evaluations. However, with the subsequent release of Google's Gemini Pro 1.0 and 1.5 models-which officially replaced Bard-we observed performance comparable to GPT-4V in our pilot studies, prompting us to include both GPT-4V and Gemini as primary systems in our research. Just before the first analysis, the Claude 3 model family was released with impressive benchmarks which prompted us to include it. After the first analysis, GPT-40 was also released and we repeated the analysis for that model. Finally, all parameter values were left to default since

not all models shared them, except for temperature. We elected a temperature of 1.0 to be used for the set of models since this was the most common default temperature. This set of models aims to constitute a good representation of current state-of-the-art research and consumer multimodal systems.

A given multimodal model M_i from a set of models M is a function to process a given vision-language task, mapping the input pair of an image and its text prompt to an invoked prediction. Formally, for a task $(I_i, Q_i, A_i^{\text{true}})$, the model function is applied as $A_i^{\text{model}} = M_i(I_i, Q_i)$ where A_i^{model} is the model's predicted answer. The objective of M_i is to return an accurate prediction for (I_i, Q_i) . See Appendix B for a further breakdown of performance.

3.4 Evaluation

The first evaluation took place on April 17, 2024 and included the Claude family of models and GPT-4V. As other models—such as GPT-4o, Gemini 1.5 Flash, and Gemini 1.5 Pro—became available, a second evaluation was completed for those models on June 13th, 2024. OpenAI models had few rate limitations, and the evaluation was completed in around 45 minutes. Gemini 1.5 Pro was the earliest released model in a preview state and, therefore, was slower to complete, at around three days. Gemini 1.0 Pro Vision was completed over two hours. Finally, the Claude 3 family of models completed each task quickly, but due to token rate limitations, it ended up taking around the same time as Gemini 1.0 Pro Vision at around two hours each. Results were saved to CSV files, where cleaning and parsing were done to ensure accurate measurements.

To assess the accuracy of the model responses, we define a performance metric, P, which quantitatively evaluates the correspondence between A_i^{model} and A_i^{true} . The metric P is a function

 $P(A_i^{\text{true}}, A_i^{\text{model}})$ that outputs a binary true or false value representing the correctness of the model-generated answer to the ground truth. In practice, our program uses regular expressions to extract the model's answer to compare with the ground truth. The performance metric for each model is measured in both pass@1 and pass@3 accuracy, which shows if the model answered correctly on the first attempt or within three attempts respectively.

Our analysis requires a systematic comparison across models and task categories. The comparative function is thus articulated to discern the model that exhibits superior performance on the designated tasks. For each category of graph *G* and tree *T* tasks, we compute the mean performance across all relevant instances, delineating specific measures for undirected graphs *UG*, directed graphs *DG*, binary trees *BT*, and binary search trees *BST*. These measures facilitate a nuanced comparison across models, revealing their strengths and weaknesses. Thus, let $M = \{M_1, M_2, \ldots, M_n\}$ be the set of models we compare. We form separate performance matrices for each category and subcategory with graph tasks being $P_G^{model}(type)$, where *type* can be UG or DG, and with tree tasks being $P_T^{model}(type)$ where *type* can be BT or BST. Finally, function *C* takes the performance matrices and compares them to find the best-performing model for each set of tasks:

$$C(M, type) = \arg \max_{M_i \in \mathcal{M}} P_{type}^{M_i}$$
(1)

3.4.1 Feature Importance. To address RQ2 and RQ3, we trained a classification model on evaluation results to examine the influence of specific features on model performance. The feature set included experimentally varied aesthetic aspects (e.g. edge width, node colors, and node value variations) and structural features (e.g. number of nodes, node values, graph density, etc.) to capture the visual diversity of graph and tree representations. Additionally, we used Deep Graph Learning (DGL) to compute augmented features, such as graph density and degree, which may impact accuracy in structurally complex tasks. Finally, the task type, determined by the six prompt categories, was included as a feature to understand how different tasks affect multimodal model performance.

To minimize overfitting and enhance model interpretability, we applied Principal Component Analysis (PCA) to image features captured with EfficientViT (efficientvit_l3.r384_in1k), reducing noise and eliminating less relevant features. Finally, we fit a logistic regression model to the refined feature set for each multimodal model, achieving F1 scores ranging from 0.693 to 0.843, with an average score of 0.791. This high performance suggests that the features are both important and predictive. See Appendix D for details on classification model performances.

4 **RESULTS**

We measure accuracy for undirected and directed graphs in addition to binary and binary search trees via pass@k performance. Our findings indicate GPT-40 performs at a higher overall accuracy than any other model in the selection for trees, followed by Gemini 1.5 Flash for graphs. See Appendix A for a detailed response analysis.

4.1 RQ 1 Overall Performance

4.1.1 Tree Performance. GPT-40 is the top performer on trees with 77.8% pass@1 and 87.6% pass@3 accuracy, which is nearly tied with GPT-4V performance at 77.8% pass@1 and 84.5% pass@3 accuracy. GPT-40 surpasses the average range of performance between models on trees, operating at roughly 20% higher accuracy than the next best after GPT-4V. Additionally, Gemini 1.5 Pro is only more accurate than Gemini 1.5 Flash by a small margin, with scores of 71.1% (+0.8%) pass@3. On the lower end, Claude 3 Haiku, the smallest model out of the family, achieves greater pass@1 performance than its siblings at 41.0%, an average of +3.5% higher than its siblings. However, pass@3 accuracy is surpassed by Claude 3 Opus with 49.4%, an average of +2.0% higher than its siblings.

4.1.2 Graph Performance. The top performer on the set of graphs is split between Gemini 1.5 Flash, which achieves a top pass@3 accuracy of **56.2**%, and Gemini 1.5 Pro, which reaches a top pass@3 accuracy of **53.8**%. GPT-40 is the next best performer, reaching a top pass@3 accuracy of **44.7**%, slightly ahead of GPT-4V's pass@3 accuracy of **40.0**%. For the Claude 3 model family, Sonnet obtains the highest performance across pass@k of **26.5**% pass@1, an average of +6.6% higher than its siblings, and **33.6**% pass@3, an average of +7.7% higher than its siblings.

4.2 RQ 2 Structural Features

The structural features were often the most important features. See Appendix C for feature engineering details.

4.2.1 Number of Edges. The number of edges was the most important feature in terms of model performance. Further analysis of the coefficients suggests a positive influence at a fewer edges and approaches a negative influence as the number of edges increases.

4.2.2 Degree Histograms. The distribution of *in-degree vertices* across all vertices in the graph had a strong influence with a slight positive influence at lower distributions and negative influence at higher distributions. Similarly, the distribution of *out-degree vertices* exhibit less influence than in-degree features, but they generally adhere to a similar trend as the in-degree features.

4.2.3 Number of Nodes and Layout. The number of nodes and layout of a graph or tree exhibited a trend of positive coefficients at a smaller number of nodes and negative coefficients at a higher number of nodes, which aligns with what is observed in Figure 3.

4.2.4 *Density.* The number of edges determines a graph's density compared to the maximum number of edges possible for a given graph. Our analysis suggests a positive influence at lower and a negative influence at higher densities.

4.3 RQ 3 Aesthetic Features

Based on our logistic regression analysis, the aesthetic features were ranked less important than structural features. The *edge width* varied in influence and showed inconsistent impact across width levels. This suggests that models are relatively robust in recognizing the edge connections. The *node color* is represented as three features that form the RGB value as a color channel. Results show that, similar to edge width, there is a limited influence on models.

Table 1: Zero-shot pass@k accuracy (%) by model and data structure: BT denotes binary tree, BST denotes binary search tree, and T denotes their combined set. UG denotes undirected graph, DG denotes directed graph, and G denotes their combined set. Bolded values indicate highest accuracies.

	В	BT BST T (Overall)		 UG		DG		G (Ov	erall)			
Model / pass@k	k = 1	<i>k</i> = 3	k = 1	<i>k</i> = 3	k = 1	<i>k</i> = 3	<i>k</i> = 1	<i>k</i> = 3	k = 1	<i>k</i> = 3	<i>k</i> = 1	k = 3
GPT-40	73.3	82.7	82.3	92.5	77.8	87.6	38.5	49.7	27.5	39.6	33.0	44.7
GPT-4 Vis. Prev.	71.8	78.4	83.7	90.6	77.8	84.5	38.0	50.9	19.0	29.0	28.5	40.0
Gemini 1.5 Pro	65.5	71.3	67.5	70.8	66.5	71.1	52.2	56.3	46.2	51.2	49.2	53.8
Gemini 1.5 Flash	64.0	65.3	72.0	75.3	68.0	70.3	50.7	55.3	53.3	57.1	52.0	56.2
Gemini Pro Vision	56.5	59.5	57.0	59.5	56.8	59.5	32.1	34.5	34.3	35.8	33.2	35.2
Claude 3 Opus	27.0	35.7	50.4	63.1	38.7	49.4	16.3	22.6	20.1	28.8	18.2	25.7
Claude 3 Sonnet	31.6	41.8	41.1	53.4	36.4	47.6	25.4	31.9	27.6	35.3	26.5	33.6
Claude 3 Haiku	23.7	29.8	58.2	64.6	41.0	47.2	19.8	23.3	23.3	29.0	21.6	26.2



Figure 3: Zero-shot accuracy overall (%) by model, number of edges, and structure. Consistent with the feature importance analysis, accuracy decreases as the number of edges increases.

However, signs from the GPT-4V model describe a negative influence of an increased 'node rgb blue channel' value. From the node colors used in the dataset, we surmise that since the white color has a higher value in the blue channel, using white as a node color on a white background may yield worse results than using a contrasting color like yellow on a white background.

4.4 Additional Observations

Models performed best on binary search trees, likely due to their consistent structure. Vision transformers, which process images as patches from the top-left to the bottom-right [66], may help explain this trend. In tree structures, the root vertex consistently appears at the top of the image, aligning with the patch encoding sequence and providing a stable spatial reference. In contrast, graphs feature more arbitrary spatial arrangements, with starting vertices positioned unpredictably across the image. This spatial inconsistency may account for the models' lower performance on graph datasets.

Directed graphs present additional challenges due to their unique structural features, including arrows that models must accurately perceive. Claude 3 Opus outperformed other models on directed graphs, achieving higher accuracy than on undirected graphs. These findings suggest that directed graphs require greater spatial reasoning, making them more challenging for models.

Figure 4 shows examples of model responses which in some cases may shed light on their reasoning processes.

5 DISCUSSION

Recent research has shown that generative AI tools like ChatGPT can tackle a broad range of programming tasks, especially at introductory levels (CS1) [14, 24, 33, 39, 50, 59, 60, 68]. These trends have important implications for pedagogy and assessment. Our study extends this body of work in two key ways: by examining advanced data structures problems and by evaluating the spatial reasoning capabilities of multimodal models (LMMs).

Our findings show that multimodal models consistently solve tree problems across a range of visual presentations, including variations in structure and aesthetics, achieving performance levels sufficient to pass traditional assessments. This raises critical concerns about students' ability to leverage these tools as a shortcut, bypassing the development of conceptual understanding. While ACE 2025,

Gutierrez. et al.



Figure 4: Example model responses to a in-order traversal of a binary search tree. The extracted predictions are highlighted.

graph problems showed lower accuracy rates, the use of a simple zero-shot prompting approach suggests a lower bound. Savy students could refine the prompts or use more advanced prompting techniques. Importantly, minimal prompting can still yield strong results, suggesting students don't need extensive prompt-engineering skills to benefit from these tools [9, 22, 54, 68].

5.1 Transforming Traditional Assessment

Our findings challenge the prevailing reliance on traditional assessment methods in computing education, particularly as generative AI continues to evolve. While recent work has suggested that diagrambased and visual problems could counteract students' over-reliance on text-based AI tools [15, 22, 27], our results suggest that this strategy is unsustainable. Multimodal models already demonstrate significant spatial reasoning capabilities, and their ability to process and solve complex visual problems, such as tree structures, suggests that these stopgap measures will soon lose their efficacy. Even video-based problems, which have been proposed as a more robust alternative [15], are unlikely to hold up as models improve.

In parallel, some educators have turned to AI detection tools in an attempt to identify when students misuse generative AI. These tools rely on statistical methods that compare human and AI writing patterns. However, this approach is flawed. Statistical resemblance alone is not reliable evidence of authorship. Just as writing that mimics the style of a famous author does not constitute plagiarism, content that resembles AI-generated patterns does not necessarily indicate AI authorship. In the context of computing, the prevalence of design patterns, coding conventions, and commonly used libraries only increases the likelihood of false positives. Both of these attempts to counter AI's influence on assessment whether through visual-based problems or detection tools—offer only fleeting solutions. Educators are now, perhaps reluctantly, being forced to adopt what some have long advocated for—innovative assessment models like ungrading [6] or project-based learning that encourage active, meaningful engagement and prioritize mastery over performance. This shift, once considered an ideal, is now becoming a necessity in the face of rapidly evolving AI tools. By reimagining assessment to emphasize curiosity and growth, we can create a more resilient approach to learning driven by purpose. This is not merely a pedagogical shift, but a moral imperative. Preparing the next generation of computing professionals requires assessments that promote critical engagement with AI systems, enabling students to navigate their limitations and biases.

5.2 New Opportunities for Pedagogy

While the focus of this work is on the implications for assessment, LMM capabilities could also provide benefits for computing students and educators. As CS2 topics like data structures are particularly challenging [37, 71] and often contribute to 'weeding out' students who lack prior experience in computer science, disproportionately impacting traditionally underrepresented students [31]. Enhanced AI tools could improve access to complex computing concepts like trees and graphs, potentially offering these students an extra layer of support. As these models advance, they could also facilitate the creation of digital teaching assistants that deliver high-quality scaffolded help [23]. More specifically, future work could investigate the potential for LMMs to produce code based on a graph or tree. This would provide help to students that struggle with graph and tree algorithms [48]. Seeing the Forest and the Trees

6 LIMITATIONS

There are several limitations to our work. First, the tree and graph data structures used do not cover all possible data structures, and the operations evaluated are limited to core topics typically found in fundamental data structures courses. Consequently, these findings may not be generalized to more advanced topics in data structure. Second, the generated data structures may not encompass the full range of relevant attributes for graphs and trees. For instance, exploring additional edge widths and node colors could provide further insights. Therefore, investigating a broader array of structural and aesthetic features is warranted. In addition, while advanced prompting methods-such as self-critique, chainof-thought, prompt chaining, and few-shot learning-can enhance performance in reasoning tasks, our study focused on demonstrating how students might use models with basic zero-shot approaches. This choice reflects the assumption that students may not be familiar with these advanced techniques. The model parameters also remained consistent across the evaluations, representing the default values that can be found when using these models for generalized purposes. It is almost certain that the performance varies greatly depending on the modification of certain parameters such as temperature and sampling coefficients across a matrix of these possible combinations. Finally, the models assessed in this study are continually evolving. To facilitate ongoing evaluation of future models, we have open-sourced our benchmarks and generation tools.

7 CONCLUSION

In this paper, we investigated the capabilities of large multimodal models (LMMs) to solve complex, visually represented data structure problems. Through the development and evaluation of a diverse benchmark dataset of graph and tree structures, we assessed the performance of various LMMs, including the GPT-4 and Gemini models, in tackling spatially and visually challenging tasks. Our results reveal that while certain models, such as GPT-40 and Gemini 1.5 Flash, performed well on tree and graph problems respectively, there remain considerable variations in accuracy that are influenced by structural complexity, such as edge density. These findings underscore the evolving capabilities of LMMs in processing visual and spatially complex problems, which has important implications for computing education. As generative AI continues to advance and reshape computing education, it becomes essential for educators to adapt assessment methods and foster environments that promote intrinsic motivation.

REFERENCES

- Aishwarya Agrawal, Jiasen Lu, Stanislaw Antol, Margaret Mitchell, C. Lawrence Zitnick, Dhruv Batra, and Devi Parikh. 2016. VQA: Visual Question Answering. arXiv:1505.00468 [cs.CL]
- [2] Shraddha Barke, Michael B James, and Nadia Polikarpova. 2022. Grounded Copilot: How Programmers Interact with Code-Generating Models. arXiv preprint arXiv:2206.15000 (2022).
- [3] Brett A Becker, Paul Denny, James Finnie-Ansley, Andrew Luxton-Reilly, James Prather, and Eddie Antonio Santos. 2023. Programming is hard-or at least it used to be: Educational opportunities and challenges of ai code generation. In Proceedings of the 54th ACM Technical Symposium on Computer Science Education.
- [4] Seth Bernstein, Paul Denny, Juho Leinonen, Lauren Kan, Arto Hellas, Matt Littlefield, Sami Sarsa, and Stephen MacNeil. 2024. "Like a Nesting Doll": Analyzing Recursion Analogies Generated by CS Students Using Large Language Models. In Proceedings of the 2024 on Innovation and Technology in Computer Science Education V. 1. 122–128.

- [5] Seth Bernstein, Paul Denny, Juho Leinonen, Matt Littlefield, Arto Hellas, and Stephen MacNeil. 2024. Analyzing Students' Preferences for LLM-Generated Analogies. In Proceedings of the 2024 on Innovation and Technology in Computer Science Education V. 2. 812–812.
- [6] Susan Debra Blum. 2020. Ungrading: Why rating students undermines learning (and what to do instead). West Virginia University Press.
- [7] Ritvik Budhiraja, Ishika Joshi, Jagat Sesh Challa, Harshal D Akolekar, and Dhruv Kumar. 2024. "It's not like Jarvis, but it's pretty close!"-Examining ChatGPT's Usage among Undergraduate Students in Computer Science. In Proceedings of the 26th Australasian Computing Education Conference. 124–133.
- [8] Edy Budiman, Haeruddin Haeruddin, Ummul Hairah, and Faza Alameka. 2018. Mobile Learning: Visualizing Contents Media of Data Structures Course in Mobile Networks. Journal of Telecommunication, Electronic and Computer Engineering (JTEC) 10, 1-9 (Feb. 2018), 81–86. https://jtec.utem.edu.my/jtec/article/view/3877
- [9] Christopher Bull and Ahmed Kharrufa. 2023. Generative AI Assistants in Software Development Education: A vision for integrating Generative AI into educational practice, not instinctively defending against it.
- [10] Michael D Byrne, Richard Catrambone, and John T Stasko. 1999. Evaluating animations as student aids in learning computer algorithms. *Computers & education* 33, 4 (1999), 253–278.
- [11] Michael B. Cahapay. 2021. Problems Encountered by College Students in Online Assessment Amid COVID-19 Crisis: A Case Study. SSRN Electronic Journal (2021).
- [12] Federico Cassano, John Gouwar, Daniel Nguyen, Sydney Nguyen, Luna Phipps-Costin, Donald Pinckney, Ming-Ho Yee, Yangtian Zi, Carolyn Jane Anderson, Molly Q Feldman, et al. 2023. MultiPL-E: a scalable and polyglot approach to benchmarking neural code generation. *IEEE Transactions on Software Engineering* 49, 7 (2023), 3675–3691.
- [13] Mark Chen, Jerry Tworek, Heewoo Jun, Qiming Yuan, Henrique Ponde de Oliveira Pinto, Jared Kaplan, Harri Edwards, Yuri Burda, Nicholas Joseph, Greg Brockman, et al. 2021. Evaluating large language models trained on code. arXiv preprint arXiv:2107.03374 (2021).
- [14] Bruno Pereira Cipriano and Pedro Alves. 2023. GPT-3 vs Object Oriented Programming Assignments: An Experience Report. In Proceedings of the 2023 Conference on Innovation and Technology in Computer Science Education V. 1 (ITiCSE 2023). Association for Computing Machinery. https://doi.org/10.1145/3587102.3588814
- [15] Bruno Pereira Cipriano, Pedro Alves, and Paul Denny. 2024. A Picture Is Worth a Thousand Words: Exploring Diagram and Video-Based OOP Exercises to Counter LLM Over-Reliance. arXiv:2403.08396 [cs.SE]
- [16] Simon Coghlan, Tim Miller, and Jeannie Paterson. 2021. Good Proctor or "Big Brother"? Ethics of Online Exam Supervision Technologies. *Philosophy & Technology* 34, 4 (Aug. 2021), 1581–1606. https://doi.org/10.1007/s13347-021-00476-1
- [17] Rianne Conijn, Ad Kleingeld, Uwe Matzat, and Chris Snijders. 2022. The fear of big brother: The potential negative side-effects of proctored exams. *Journal of Computer Assisted Learning* 38, 6 (2022), 1521–1534.
- [18] Vassilios Dagdilelis and Maria Satratzemi. 1998. DIDAGRAPH: Software for teaching graph theory algorithms. ACM SIGCSE Bulletin 30, 3 (1998), 64–68.
- [19] Holger Danielsiek, Wolfgang Paul, and Jan Vahrenhold. 2012. Detecting and understanding students' misconceptions related to algorithms and data structures. SIGCSE'12 - Proceedings of the 43rd ACM Technical Symposium on Computer Science Education (02 2012). https://doi.org/10.1145/2157136.2157148
- [20] Dwight Davis, J Kevin Dorsey, Ronald D Franks, Paul R Sackett, Cynthia A Searcy, and Xiaohui Zhao. 2013. Do racial and ethnic group differences in performance on the MCAT exam reflect test bias? *Academic Medicine* 88, 5 (2013), 593–602.
- [21] Paul Denny, Viraj Kumar, and Nasser Giacaman. 2023. Conversing with Copilot: Exploring Prompt Engineering for Solving CS1 Problems Using Natural Language. In Proceedings of the 54th ACM Technical Symposium on Computer Science Education V. 1 (SIGCSE 2023).
- [22] Paul Denny, Juho Leinonen, James Prather, Andrew Luxton-Reilly, Thezyrie Amarouche, Brett A. Becker, and Brent N. Reeves. 2023. Promptly: Using Prompt Problems to Teach Learners How to Effectively Utilize AI Code Generators. arXiv:2307.16364 [cs.HC]
- [23] Paul Denny, Stephen MacNeil, Jaromir Savelka, Leo Porter, and Andrew Luxton-Reilly. 2024. Desirable Characteristics for AI Teaching Assistants in Programming Education. In Proceedings of the 2024 on Innovation and Technology in Computer Science Education V. 1 (ITiCSE 2024). ACM, 408–414. https://doi.org/10.1145/ 3649217.3653574
- [24] Zhiyu Fan, Xiang Gao, Martin Mirchev, Abhik Roychoudhury, and Shin Hwei Tan. 2023. Automated repair of programs from large language models. In 2023 IEEE/ACM 45th International Conference on Software Engineering (ICSE). IEEE.
- [25] James Finnie-Ansley, Paul Denny, Andrew Luxton-Reilly, Eddie Antonio Santos, James Prather, and Brett A. Becker. 2023. My AI Wants to Know if This Will Be on the Exam: Testing OpenAl's Codex on CS2 Programming Exercises. In Proceedings of the 25th Australasian Computing Education Conference (ACE '23). Association for Computing Machinery. https://doi.org/10.1145/3576123.3576134
- [26] J. Paul Gibson. 2012. Teaching graph algorithms to children of all ages. In Proceedings of the 17th ACM Annual Conference on Innovation and Technology in Computer Science Education (ITiCSE '12). Association for Computing Machinery.

- [27] Matei A. Golesteanu, Garrett B. Vowinkel, and Ryan E. Dougherty. 2024. Can ChatGPT Pass a Theory of Computing Course? https://arxiv.org/abs/2407.07757
- [28] Carina S González-González, Alfonso Infante-Moro, and Juan C Infante-Moro. 2020. Implementation of e-proctoring in online teaching: A study about motivational factors. *Sustainability* 12, 8 (2020), 3488.
- [29] Scott Grissom, Laurie Murphy, Renée McCauley, and Sue Fitzgerald. 2016. Paper vs. Computer-based Exams: A Study of Errors in Recursive Binary Tree Algorithms. In Proceedings of the 47th ACM Technical Symposium on Computing Science Education (SIGCSE '16). Association for Computing Machinery.
- [30] Sandra Gudiño Paredes, Felipe de Jesús Jasso Peña, and Juana María de La Fuente Alcazar. 2021. Remote proctored exams: Integrity assurance in online education? Distance Education 42, 2 (2021), 200–218.
- [31] Neil Hatfield, Nathanial Brown, and Chad M Topaz. 2022. Do introductory courses disproportionately drive minoritized students out of STEM pathways? *PNAS nexus* 1, 4 (2022), pgac167.
- [32] Jeffrey D Holmes. 2021. The Bad Test-Taker Identity. Teaching of psychology 48, 4 (2021), 293–299.
- [33] Irene Hou, Owen Man, Sophia Mettille, Sebastian Gutierrez, Kenneth Angelikas, and Stephen MacNeil. 2024. More Robots are Coming: Large Multimodal Models (ChatGPT) can Solve Visually Diverse Images of Parsons Problems. In Proceedings of the 26th Australasian Computing Education Conference (ACE '24). Association for Computing Machinery, 29–38. https://doi.org/10.1145/3636243.3636247
- [34] Irene Hou, Sophia Mettille, Owen Man, Zhuo Li, Cynthia Zastudil, and Stephen MacNeil. 2024. The Effects of Generative AI on Introductory Students' Help-Seeking Preferences. In Australasian Computing Education Conference (ACE '24). ACM. https://doi.org/10.1145/3636243.3636248
- [35] Association for Computing Machinery (ACM) Joint Task Force on Computing Curricula and IEEE Computer Society. 2013. Computer Science Curricula 2013: Curriculum Guidelines for Undergraduate Degree Programs in Computer Science. Association for Computing Machinery, New York, NY, USA.
- [36] Ishika Joshi, Ritvik Budhiraja, Harshal Dev, Jahnvi Kadia, Muhammad Osama, Ataullah, Sayan Mitra, and Dhruv Kumar. 2023. ChatGPT and the Future of Undergraduate Computer Science: Challenges, Opportunities and Recommendations. https://api.semanticscholar.org/CorpusID:258741417
- [37] Kuba Karpierz and Steven A. Wolfman. 2014. Misconceptions and concept inventory questions for binary search trees and hash tables. In Proceedings of the 45th ACM Technical Symposium on Computer Science Education (SIGCSE '14). Association for Computing Machinery, 6 pages. https://doi.org/10.1145/2538862.2538902
- [38] Majeed Kazemitabaar, Justin Chow, Carl Ka To Ma, Barbara J. Ericson, David Weintrop, and Tovi Grossman. 2023. Studying the effect of AI Code Generators on Supporting Novice Learners in Introductory Programming. In Proceedings of the 2023 CHI Conference on Human Factors in Computing Systems (CHI '23). Association for Computing Machinery. https://doi.org/10.1145/3544548.3580919
- [39] Charles Koutcheme, Sami Sarsa, Juho Leinonen, Arto Hellas, and Paul Denny. 2023. Automated Program Repair Using Generative Models for Code Infilling. In International Conference on Artificial Intelligence in Education. Springer, 798–803.
- [40] Sam Lau and Philip J. Guo. 2023. From 'Ban It Till We Understand It' to "Resistance is Futile": How University Programming Instructors Plan to Adapt as More Students Use AI Code Generation and Explanation Tools such as ChatGPT and GitHub Copilot. In Proceedings of the 2023 ACM Conference on International Computing Education Research V.1 (ICER '23 V1). ACM.
- [41] Juho Leinonen, Paul Denny, Stephen MacNeil, Sami Sarsa, Seth Bernstein, Joanne Kim, Andrew Tran, and Arto Hellas. 2023. Comparing Code Explanations Created by Students and Large Language Models. arXiv preprint arXiv:2304.03938 (2023).
- [42] Mark Liffiton, Brad Sheese, Jaromir Savelka, and Paul Denny. 2023. CodeHelp: Using Large Language Models with Guardrails for Scalable Support in Programming Classes. arXiv:2308.06921 [cs.CY]
- [43] Stephen MacNeil, Paul Denny, Andrew Tran, Juho Leinonen, Seth Bernstein, Arto Hellas, Sami Sarsa, and Joanne Kim. 2023. Decoding Logic Errors: A Comparative Study on Bug Detection by Students and Large Language Models. arXiv preprint arXiv:2311.16017 (2023).
- [44] Stephen MacNeil, Joanne Kim, Juho Leinonen, Paul Denny, Seth Bernstein, Brett A. Becker, Michel Wermelinger, Arto Hellas, Andrew Tran, Sami Sarsa, James Prather, and Viraj Kumar. 2023. The Implications of Large Language Models for CS Teachers and Students. In Proceedings of the 54th ACM Technical Symposium on Computer Science Education V. 2 (SIGCSE 2023). Association for Computing Machinery, 1255. https://doi.org/10.1145/3545947.3573358
- [45] Stephen MacNeil, Scott Spurlock, and Ian Applebaum. 2024. Imagining Computing Education Assessment after Generative AI. https://arxiv.org/abs/2401.04601
- [46] Stephen MacNeil, Andrew Tran, Arto Hellas, Joanne Kim, Sami Sarsa, Paul Denny, Seth Bernstein, and Juho Leinonen. 2023. Experiences from Using Code Explanations Generated by Large Language Models in a Web Software Development E-Book. In Proc. SIGCSE'23. ACM, 6 pages.
- [47] Stephen MacNeil, Andrew Tran, Dan Mogil, Seth Bernstein, Erin Ross, and Ziheng Huang. 2022. Generating Diverse Code Explanations Using the GPT-3 Large Language Model. In Proc. of the 2022 ACM Conf. on Int. Computing Education Research - Volume 2. ACM, 37–39.

- [48] Janka Medová, Kitti Páleníková, Ľubomír Rybanský, and Zuzana Naštická. 2019. Undergraduate Students' Solutions of Modeling Problems in Algorithmic Graph Theory. *Mathematics* 7, 7 (2019). https://doi.org/10.3390/math7070572
- [49] Laurie Murphy, Sue Fitzgerald, Scott Grissom, and Renée McCauley. 2015. Bug Infestation! A Goal-Plan Analysis of CS2 Students' Recursive Binary Tree Solutions. In Proceedings of the 46th ACM Technical Symposium on Computer Science Education (SIGCSE '15). Association for Computing Machinery.
- [50] Eng Lieh Ouh, Benjamin Kok Siew Gan, Kyong Jin Shim, and Swavek Wlodkowski. 2023. ChatGPT, Can You Generate Solutions for my Coding Exercises? An Evaluation on its Effectiveness in an undergraduate Java Programming Course.. In Proceedings of the 2023 Conference on Innovation and Technology in Computer Science Education V. 1. 54-60.
- [51] Ken Perlin, Zhenyi He, and Karl Rosenberg. 2018. Chalktalk : A Visualization and Communication Language – As a Tool in the Domain of Computer Science Education. arXiv:1809.07166 [cs.HC]
- [52] James Prather, Paul Denny, Juho Leinonen, Brett A Becker, Ibrahim Albluwi, Michael E Caspersen, Michelle Craig, Hieke Keuning, Natalie Kiesler, Tobias Kohn, et al. 2023. Transformed by Transformers: Navigating the AI Coding Revolution for Computing Education: An ITiCSE Working Group Conducted by Humans. In Proceedings of the 2023 Conference on Innovation and Technology in Computer Science Education V. 2, 561–562.
- [53] James Prather, Paul Denny, Juho Leinonen, Brett A Becker, Ibrahim Albluwi, Michelle Craig, Hieke Keuning, Natalie Kiesler, Tobias Kohn, Andrew Luxton-Reilly, et al. 2023. The Robots are Here: Navigating the Generative AI Revolution in Computing Education. arXiv preprint arXiv:2310.00658 (2023).
- [54] James Prather, Brent N Reeves, Juho Leinonen, Stephen MacNeil, Arisoa S Randrianasolo, Brett A Becker, Bailey Kimmel, Jared Wright, and Ben Briggs. 2024. The Widening Gap: The Benefits and Harms of Generative AI for Novice Programmers. In Proceedings of the 2024 ACM Conference on International Computing Education Research-Volume 1. 469–486.
- [55] Ben Puryear and Gina Sprint. 2022. Github copilot in the classroom: learning to code with AI assistance. *Journal of Computing Sciences in Colleges* 38, 1 (2022).
- [56] Brent Reeves, Sami Sarsa, James Prather, Paul Denny, Brett A Becker, Arto Hellas, Bailey Kimmel, Garrett Powell, and Juho Leinonen. 2023. Evaluating the performance of code generation models for solving Parsons problems with small prompt variations. In Proceedings of the 2023 Conference on Innovation and Technology in Computer Science Education V. 1. 299–305.
- [57] Ferozuddin Riaz and Khidir M. Ali. 2011. Applications of Graph Theory in Computer Science. In 2011 Third International Conference on Computational Intelligence, Communication Systems and Networks. 142–145.
- [58] Jürgen Rudolph, Samson Tan, and Shannon Tan. 2023. ChatGPT: Bullshit spewer or the end of traditional assessments in higher education? *Journal of Applied Learning and Teaching* 6, 1 (2023).
- [59] Jaromir Savelka, Arav Agarwal, Marshall An, Chris Bogart, and Majd Sakr. 2023. Thrilled by Your Progress! Large Language Models (GPT-4) No Longer Struggle to Pass Assessments in Higher Education Programming Courses. *The 19th ACM Conference on International Computing Education Research (ICER)* (2023).
- [60] Jaromir Savelka, Arav Agarwal, Christopher Bogart, and Majd Sakr. 2023. Large language models (gpt) struggle to answer multiple-choice questions about code. arXiv preprint arXiv:2303.08033 (2023).
- [61] Jaromir Savelka, Arav Agarwal, Christopher Bogart, Yifan Song, and Majd Sakr. 2023. Can Generative Pre-trained Transformers (GPT) Pass Assessments in Control of Control
- Higher Education Programming Courses? arXiv:2303.09325[62] Robert Sedgewick and Kevin Wayne. 2011. Algorithms. Pearson Education.
- [63] Zarema S. Seidametova. 2021. Some ways of increasing the efficiency of teaching data structures. In CoSinE@ICTERI.
- [64] Teo Susnjak. 2022. ChatGPT: The End of Online Exam Integrity? arXiv:2212.09292[65] The Joint Task Force on Computing Curricula, Association for Computing Ma-
- chinery (ACM), IEEE Computer Society. 2013. Computer Science Curricula 2013: Curriculum Guidelines for Undergraduate Degree Programs in Computer Science. https://www.acm.org/binaries/content/assets/education/cs2013_web_final.pdf
- [66] Hugo Touvron, Matthieu Cord, Alaaeldin El-Nouby, Jakob Verbeek, and Hervé Jégou. 2022. Three things everyone should know about vision transformers. In European Conference on Computer Vision. Springer.
- [67] Maarten Van Steen. 2010. Graph theory and complex networks. An introduction 144 (2010), 1–287.
- [68] Michel Wermelinger. 2023. Using GitHub Copilot to Solve Simple Programming Problems. In Proceedings of the 54th ACM Technical Symposium on Computer Science Education V. 1 (SIGCSE 2023). Association for Computing Machinery, New York, NY, USA, 172–178. https://doi.org/10.1145/3545945.3569830
- [69] Benjamin Xie, Matt J Davidson, Baker Franke, Emily McLeod, Min Li, and Amy J Ko. 2021. Domain Experts' Interpretations of Assessment Bias in a Scaled, Online Computer Science Curriculum. In Proceedings of the Eighth ACM Conference on Learning@ Scale. 77–89.
- [70] Cynthia Zastudil, Magdalena Rogalska, Christine Kapp, Jennifer Vaughn, and Stephen MacNeil. 2023. Generative AI in Computing Education: Perspectives of Students and Instructors. arXiv preprint arXiv:2308.04309 (2023).

- [71] Daniel Zingaro, Cynthia Taylor, Leo Porter, Michael Clancy, Cynthia Lee, Soohyun Liao, and Kevin Webb. 2018. Identifying Student Difficulties with Basic Data Structures. 169–177. https://doi.org/10.1145/3230977.3231005
- [72] Andrea Ševčíková and Eva Milková. 2016. Multimedia applications: Graph algorithms visualization. In 2016 IEEE 17th International Symposium on Computational Intelligence and Informatics (CINTI). 000231–000236.

A EVALUATION RESULTS

In Table 2, we share additional analysis of model evaluations. Across the set of all eight models, they constitute over 72,576 responses in total. The response of each model is unique in length, style, and other characteristics.

B PERFORMANCE DETAILS

The overall performance for graph tasks, $Performance_{M_i}^G$, is calculated as follows:

$$\operatorname{Performance}_{M_{i}}^{G} = \frac{\operatorname{Performance}_{M_{i}}^{UG} \cdot |D_{UG}| + \operatorname{Performance}_{M_{i}}^{DG} \cdot |D_{DG}|}{|D_{UG}| + |D_{DG}|}$$

where $\operatorname{Performance}_{M_i}^{UG}$ and $\operatorname{Performance}_{M_i}^{DG}$ are the respective model performances for undirected graphs and directed graphs defined as:

$$\begin{aligned} \text{Performance}_{M_i}^{UG} &= \frac{1}{|D_{UG}|} \sum P(A_{ugi}^{true}, M_i(I_{ugi}, Q_{ugi})) \\ \text{Performance}_{M_i}^{DG} &= \frac{1}{|D_{DG}|} \sum P(A_{dgi}^{true}, M_i(I_{dgi}, Q_{dgi})) \end{aligned}$$

Similarly, the overall performance for tree tasks, $Performance_{M_i}^T$ are calculated as follows:

$$\operatorname{Performance}_{M_{i}}^{T} = \frac{\operatorname{Performance}_{M_{i}}^{BT} \cdot |D_{BT}| + \operatorname{Performance}_{M_{i}}^{BST} \cdot |D_{BST}|}{|D_{BT}| + |D_{BST}|}$$

where $\operatorname{Performance}_{M_i}^{BT}$ and $\operatorname{Performance}_{M_i}^{BST}$ are the respective model performances for binary trees and binary search trees defined as:

$$\begin{aligned} \text{Performance}_{M_{i}}^{BT} &= \frac{1}{|D_{BT}|} \sum P(A_{bti}^{true}, M_{i}(I_{bti}, Q_{bti})) \\ \text{Performance}_{M_{i}}^{BST} &= \frac{1}{|D_{BST}|} \sum P(A_{bsti}^{true}, M_{i}(I_{bsti}, Q_{bsti})) \end{aligned}$$

C FEATURE ENGINEERING

This section details the process and rationale behind the extraction and preparation of the features used to evaluate the performance of the multimodal models. Each feature is derived from various properties of each vision language task sample. The feature engineering process used in the study involves several techniques that transform the data into a suitable format for classification model training. Below is a detailed breakdown of these techniques.

C.1 Graph Features

Graph features are extracted from the adjacency list of each graph, including the number of nodes and edges, graph density, and degree statistics. These features are one-hot encoded and binned to capture structural nuances in the graph data.

C.1.1 Data Structure Type. Each structure category, *BT*, *BST*, *G*, and *DG* is one-hot encoded into a vector.

C.1.2 Node Value Variation. The variation identifier representing a unique set of node values for a given graph is one-hot encoded into a vector.

C.1.3 Generation. The generation identifier representing a unique spatial graph layout is one-hot encoded into a vector.

C.1.4 Node Count. Each graph's node count is converted into a one-hot encoded vector. The length of this vector is determined by the maximum number of nodes across the set of graphs.

C.1.5 Edge Count. Similar to node count, the number of edges is also one-hot encoded, where each position in the vector indicates the presence of a specific number of edges, up to the maximum found in the dataset.

C.1.6 Graph Density. The density of a graph is calculated as the ratio of the number of edges to the number of possible edges in the graph. Density is calculated differently for directed and undirected graphs. For directed graphs, the formula used is

$$\frac{edges}{edges \cdot (nodes - 1)}$$

and for undirected graphs it is

$$\frac{2 \cdot edges}{edges \cdot (nodes - 1)}.$$

The resulting density measure is binned into predefined categories and one-hot encoded.

C.1.7 Average Node Degree. The average degree of nodes in the graph represents the average number of connections each node has. This is calculated by dividing the total number of edges by the number of nodes. The result is binned into predefined intervals and transformed into a one-hot encoded vector.

C.1.8 In-Degree and Out-Degree Histograms. These histograms represent the distribution of connections that go into and exit nodes, providing information on the directional flow of the graph. Each histogram uses different calculations.

- a. **In-degree** is calculated by counting the incoming edges to each node and categorizing these counts into bins. The counts are then compiled into a histogram.
- b. **Out-degree** similarly counts and categorizes the outgoing edges from each node into a histogram.

Table 2: Analysis of model response on a character, word, and token (cl100k_base) basis.

Model		Characters			Words		Tokens			
	Total	Avg ± SD	Min-Max	Total	Avg ± SD	Min-Max	Total	Avg ± SD	Min-Max	
GPT-40	7 239 477	798 ±364	32-3101	1 258 965	139 ±63	5-487	2 137 607	236 ±108	14-930	
GPT-4 Vis. Prev.	5 068 618	559 ±289	32-2054	907 905	100 ±53	6-360	1 376 664	152 ±79	8-561	
Gemini 1.5 Pro	1 077 074	119 ±183	9-1514	210 505	23 ±32	3-297	432 258	48 ±54	9-486	
Gemini 1.5 Flash	635 233	70 ±35	9-1321	130 953	14 ±7	3-244	297 321	33 ±16	9-421	
Gemini Pro Vision	266 413	29 ±25	10-231	73 249	8 ±6	3-46	218 407	24 ±17	9-104	
Claude 3 Opus	3 590 616	396 ±214	9-1955	647 348	71 ±40	3-369	1 038 594	114 ±64	9-547	
Claude 3 Sonnet	3 957 662	436 ±206	65-1984	700 621	77 ±37	13-343	1 078 054	119 ±64	21-581	
Claude 3 Haiku	1 311 315	145 ±90	21-894	243 972	27 ±16	7-164	421 265	46 ±27	19-259	

C.2 Image Features

Image features are extracted using EfficientViT. The images are resized, normalized, and then processed to obtain average-pooled features. Dimensionality reduction is applied using Principal Component Analysis (PCA), reducing the feature space to the top components that capture the most variance.

C.3 Text Features

Text data from prompts is processed using a TF-IDF vectorizer followed by a Truncated Singular Value Decomposition (SVD) to reduce the dimensionality while capturing latent semantic information. The number of components retained is based on the model's explanatory power on the variance observed in the text data.

C.4 Interaction Features

Interaction terms are created to model the interaction between different types of features, such as the interaction between the number of nodes and the width of the edges. These features are expected to provide insights into how structural properties might influence the overall characteristics of the graphs.

C.5 Edge Width Features

The set of possible edge width parameter values are converted into one-hot encoded vectors.

C.6 Node Color Features

Each channel of a node color's RGB values are split and added as continuous features.

C.7 Encoding and Normalization

Categorical variables such as graph types and task identifiers are one-hot encoded. Continuous features are normalized or standardized to ensure they contribute equally to the model training process.

C.8 Feature Reduction

Post-feature extraction and engineering, features undergo a selection process in which constant features are removed and the remaining features are used for model training. This step ensures that only the most informative features are considered, improving model performance and computational efficiency.

C.9 Matrix Construction

Finally, all engineered features are combined into a single feature matrix, along with target labels for classification tasks. This matrix serves as an input for the subsequent model training phase.

D CLASSIFICATION

The classification framework is trained to predict ground truth values from engineered features derived from text-image paired prompts. The following classification metrics show the performance of the logistic regression models:

Model	Accuracy	Precision	Recall	F1
GPT-40	0.828	0.838	0.849	0.843
GPT-4 Vision Preview	0.845	0.838	0.875	0.856
Gemini 1.5 Pro	0.840	0.808	0.837	0.822
Gemini 1.5 Flash	0.866	0.872	0.903	0.887
Gemini 1.0 Pro Vision	0.845	0.815	0.837	0.826
Claude 3 Opus	0.838	0.781	0.629	0.697
Claude 3 Sonnet	0.823	0.755	0.668	0.709
Claude 3 Haiku	0.814	0.713	0.673	0.693

 Table 3: The classification model performances on each

 LMM's evaluation.



Figure 5: A 3D perspective of the PCA image feature space from the first three components.



Figure 6: The t-SNE feature space from the first two components.