# InstructSeg: Unifying Instructed Visual Segmentation with Multi-modal Large Language Models

Cong Wei<sup>1,2</sup>, Yujie Zhong<sup>2†</sup>, Haoxian Tan<sup>2</sup>, Yingsen Zeng<sup>2</sup>, Yong Liu<sup>1</sup>, Zheng Zhao<sup>2</sup>, and Yujiu Yang<sup>1†</sup> <sup>1</sup>Tsinghua Shenzhen International Graduate School, Tsinghua University <sup>2</sup>Meituan Inc.

weic22@mails.tsinghua.edu.cn, jaszhong@hotmail.com, yang.yujiu@sz.tsinghua.edu.cn



Figure 1. We define Instructed Visual Segmentation (IVS) as the union of four text-guided segmentation tasks across image and video domains: referring expression segmentation (RES), reasoning segmentation (ReasonSeg), referring video object segmentation (R-VOS) and reasoning video object segmentation (ReasonVOS). InstructSeg can handle all the IVS tasks in one model with excellent performance.

#### Abstract

Boosted by Multi-modal Large Language Models (MLLMs), text-guided universal segmentation models for the image and video domains have made rapid progress recently. However, these methods are often developed separately for specific domains, overlooking the similarities in task settings and solutions across these two areas. In this paper, we define the union of referring segmentation and reasoning segmentation at both the image and video levels as Instructed Visual Segmentation (IVS). Correspondingly, we propose InstructSeg, an end-to-end segmentation pipeline equipped with MLLMs for IVS. Specifically, we employ an object-aware video perceiver to extract temporal and object information from reference frames, facilitating comprehensive video understanding. Additionally, we introduce vision-guided multi-granularity text fusion to better integrate global and detailed text information with fine-grained visual guidance. By leveraging multi-task and end-to-end training, InstructSeg demonstrates superior performance across diverse image and video segmentation tasks, surpassing both segmentation specialists and MLLM-based methods with a single model. Our code is available here.

<sup>&</sup>lt;sup>†</sup>Corresponding authors.

Method	End-to-End	DES	Instructed Visual Segmentation					
Segmentation Specialists		KES	Reasonseg	K-V03	Reason VOS			
VLT [11], LAVT [48], ReLA [24], PolyFormer [26] ReferFormer [44], OnlineRefer [43], SOC [29]	√ √	1		$\checkmark$				
MLLM-based Generalists								
LISA [18], PixelLM [35], LaSagnA [41] GSVA [45], GLaMM [34], OMG-LLaVA [51], PSALM [53]	√ √	✓ ✓	$\checkmark$					
VISA [47] InstructSeg (Ours)	$\checkmark$	√ √	√ √	$\checkmark$	$\checkmark$			

Table 1. The comparison of capabilities of different methods. Our InstructSeg can tackles more comprehensive Instructed Visual Segmentation tasks with a simplified end-to-end framework and achieves better performance.

## **1. Introduction**

In recent years, language-instructed segmentation tasks, such as referring expression segmentation (RES) [11, 26, 40, 48] and referring video object segmentation (R-VOS) [13, 43, 44], have attracted significant attention in the field of computer vision. These tasks require models to segment objects in images or videos based on natural language descriptions, offering greater potential for practical applications but also presenting a more substantial challenge compared to traditional class-based segmentation tasks like semantic segmentation, which depend on predefined categories. Multimodal Large Language Models (MLLMs) are distinguished by their ability to handle versatile inputs and their impressive performance in visual-language reasoning, making them a preferred choice for these language-instructed segmentation tasks in both image and video domains. Despite the similarity in task settings and solutions, current research often overlooks the collaborative effect of these tasks in the context of multi-task optimization, treating them separately.

Recent works in the image domain, such as LISA [18], PixelLM [35], and PSALM [53], have demonstrated promising results in universal image segmentation by leveraging MLLMs' embedded reasoning capabilities and inherent world knowledge. However, models designed for static images typically **fail to effectively capture the temporal coherence within videos**, either by naively aggregating video frames or by processing video frames individually, thereby incurring excessive computational costs.

Meanwhile, recent work in the video domain, VISA [47], has sought to address these challenges by leveraging the combination of multiple specialists for text-guided image and video segmentation. Nonetheless, VISA requires the integration of each specialist, necessitating the use of additional pre-trained Video-LLMs and a video object tracker. The complex model and cumbersome pipeline impede the potential for widespread application and **end-to-end collaborative optimization in both image and video domains.**  In this work, we unify referring segmentation and reasoning segmentation within both the image and video domains under the framework of **Instructed Visual Segmentation** (**IVS**). IVS requires models to segment targets from visual inputs based on detailed textual instructions. As shown in Tab. 1, IVS encompasses traditional referring segmentation tasks, such as referring expression segmentation (RES) and referring video object segmentation (R-VOS), as well as more complex reasoning-based segmentation tasks, including reasoning segmentation (ReasonSeg) and reasoning video object segmentation (ReasonVOS).

Accordingly, we introduce an end-to-end pipeline, InstructSeg, along with two meticulous designs: Object-aware Video Perceiver and Vision-guided Multi-granularity Text Fusion. This pipeline enables the implementation of all tasks within IVS using a single MLLM and segmentation decoder.

Specifically, Object-aware Video Perceiver is designed to extract both the temporal and object information from reference frames guided by language instructions referring to or reasoning about the objects of interest. Vision-guided Multi-granularity Text Fusion is proposed to comprehend long text instructions and complex scenarios like "A bride and groom often walk together down the aisle during a wedding ceremony. What object in the picture is the bride most likely holding during this moment?". Instead of averaging or summarizing the embeddings of multiple text tokens, we integrate both global and detailed information of text instructions into the multi-granularity text embeddings, facilitating better comprehension of the intentions behind the text instructions.

Extensive experiments on various Instructed Visual Segmentation benchmarks demonstrate the powerful reasoning and segmentation abilities of our InstructSeg. Our contributions are as follows:

 We integrate referring segmentation and reasoning segmentation across both image and video domains within the framework of Instructed Visual Segmentation (IVS). Introducing InstructSeg, we offer an end-to-end unified pipeline for all IVS tasks, leveraging Multi-modal Large Language Models for language-instructed pixel-level reasoning and classification. This model effectively handles tasks across both image and video domains while maintaining a high level of simplicity.

- We propose Object-aware Video Perceiver and Visionguided Multi-granularity Text Fusion modules to fully exploit temporal and object information, enhancing the understanding of both global and detailed text instructions.
- InstructSeg achieves state-of-the-art results on diverse Instructed Visual Segmentation benchmarks across both image and video domains, demonstrating the effectiveness of our simplified pipeline. Additionally, InstructSeg delivers competitive performance on multiple Multi-modal benchmarks.

## 2. Related Work

Referring segmentation in image and video. The referring expression segmentation (RES) task aims at labeling the pixels of an image that represent an object instance referred to by a linguistic expression. CRIS [40], CGFormer [39], CoupAlign [52] firstly use visual language decoder to propagate text information to pixel-level visual features, and then bring relevant features closer based of contrastive Learning. MCN [28], RefTR [22], and X-Decoder [56] enhance the fusion of textual and visual features and utilize multi-task collaborative learning to strengthen the segmentation performance. The referring video object segmentation (R-VOS) extends the RES task to the domain of videos, where the goal is to track and segment the object corresponding to a given natural language description in a video. The method [4] extracts frames from the video and processes them separately. However, this method disregards the temporal information of the video, making it susceptible to challenges such as object motion and lighting variations. On the other hand, the methods [5, 16, 28, 44] detect and propagate the target masks. Both RES and R-VOS are based on explicit instructions but lack the requirements to reason about complex tasks. Recently proposed ReasonSeg [18] and ReasonVOS [47] tasks aim to address this limitation, which extends short phrases to complex sentences that require reasoning and the inference of world knowledge in conjunction with video content.

**Multi-modal Large Language Models.** Inspired by the remarkable comprehension and reasoning capabilities of large language models, considerable effort have been made within both the open-source community and research institutions to expand these models to encompass various modalities, resulting in the development of MLLMs. For instance, Flamingo [1] incorporates a perceiver resampler to convert visual information and employs a gated cross-attention layer to establish deeper feature fusion between the frozen vi-

sual encoder and the LLM. LLAVA [25], BLIP2 [20] and miniGPT4 [54] primarily use vision encoders to encode images and incorporate modal adaptors to map visual features into the text domain, serving as the input for LLMs. Additionally, Video-Chat [21] and Video-ChatGPT [30] extend image encoders to video encoders, facilitating the understanding of visual content in videos. Models such as PLLaVA [46] and MiniGPT4-video [2] process each frame independently using an image encoder and reduce the number of video visual tokens through temporal dimension pooling. Blip3-video [36] introduces a temporal encoder to map a sequence of tokens from multiple frames into a compact set of visual tokens. Furthermore, LLaMA-VID [23] even represents a frame with only two tokens, making it possible to handle inference on long videos lasting over an hour. However, these methods are primarily designed for tasks that require text output, like VQA, and are not directly applicable to pixel-level understanding tasks like image segmentation and video segmentation.

MLLM-based segmentation model. Several existing works aim to utilize MLLMs to incorporate complex reasoning and world knowledge, as well as enable MLLMs to generate segmentation masks in images. These methods including LISA [18], PerceptionGPT [33], GSVA [45], PixelLM [35], LaSagnA [41], PSALM [53], HyperSeg [42] etc., employ a common approach of introducing a segment token for each sentence related to a different object. Specifically, LISA [18], PerceptionGPT [33] and GSVA [45] employ the segment token from the MLLM as a prompt embedding and further employ the SAM [17] model to generate segmentation predictions. PixelLM [35] generates multi-scale segment tokens from the MLLM and a segmentation codebook, which are subsequently processed by a lightweight decoder to produce weighted masks. Conversely, PSALM [53] follows Mask2Former [7], generating mask proposals first and then classifying them instead of directly generating the final prediction. However, these models are limited to static image predictions and do not effectively leverage temporal information for video segmentation tasks. To address video tasks, VISA [47] employs a frame sampler to selectively choose the most relevant frames to the textual instructions. Then the visual token and text sentences are jointly processed using MLLM to derive reasoning over the video content and generate precision textual outputs. Finally, the video object segment output is obtained by the SAM mask decoder and X-Mem [8] tracker. Although VISA [47] supports segment tasks for both images and videos, it relies on the pre-trained model quality for the frame sampler and tracker. These modules are frozen during training, hindering the synergistic optimization of perception and segmentation. To this end, we propose an end-to-end framework that unifies reasoning and segmentation into a single module, allowing for simultaneous optimization and improved performance.



Figure 2. Framework of InstructSeg. InstructSeg tackles Instructed Visual Segmentation tasks in an end-to-end pipeline. For challenging video analysis tasks, we employ the object-aware video perceiver to effectively extract both temporal and object-specific information from the reference frames. Besides, InstructSeg is capable of executing comprehensive and accurate vision-language perception and understanding through vision-guided multi-granularity text fusion applied to detailed text embeddings. Finally, the mask embeddings and multi-granularity text embeddings are decoded into segmentation masks and scores.

## 3. Method

#### 3.1. Overview of InstructSeg

The architecture of our proposed model, referred to as InstructSeg, is depicted in Fig. 2. This model primarily comprises several key components: a Multi-modal Large Language Model (integrating a CLIP encoder and a Large Language Model), a visual encoder, an object-aware video perceiver (OVP), a vision-guided multi-granularity text fusion module (VMTF), and a segmentation decoder responsible for generating masks and scores. The model processes several inputs: an image or key frame denoted as  $\mathcal{V} \in \mathbb{R}^{H \times W \times 3}$ , a reference video sequence  $\mathcal{V}_r \in \mathbb{R}^{T_r \times H \times W \times 3}$ , comprising  $T_r$  frames for video tasks, and language instructions  $\mathcal{E}$ . The CLIP encoder is tasked with encoding all visual inputs into global image features. Concurrently, the object-aware video perceiver handles the reference frames and text tokens, utilizing learnable queries to condense temporal and object information into fixed-length tokens. The Large Language Model (LLM) processes four distinct types of inputs: visual tokens derived from the image or key frame, text tokens, compressed tokens from the reference frames, and mask tokens. The output embeddings of the LLM, which correspond to detailed text instructions, are blended using the VMTF module under visual guidance. Subsequently, the segmentation decoder produces segmentation masks and scores by decoding the mask embeddings and multi-granularity text embeddings from the VMTF output, alongside fine-grained visual features  $f_{imq}$ . It is important to note that all visual

encoders are frozen, while the remaining components are trained. Specifically, the LLM is fine-tuned using Low-Rank Adaptation (LoRA) to enhance tuning efficiency.

#### 3.2. Object-aware Video Perceiver

Video segmentation poses distinct challenges, primarily due to the need for reasoning across multiple frames while ensuring temporal coherence. Recent models, such as VISA [47], employ pre-trained video specialists to tackle these challenges. However, this approach often results in a heavy dependence on the capabilities of individual components, which can lead to error accumulation throughout the process. In response to these challenges, we introduce the Objectaware Video Perceiver (OVP). The OVP module is designed to extract both temporal and object-specific information from reference frames, guided by language instructions that are expected to identify the objects of interest. This approach aims to enhance the accuracy and coherence of video segmentation by effectively integrating temporal and contextual information.

As shown in Fig. 3, given the  $T_r$  reference frames  $\mathcal{V}_r = \{I_r^t\}_{t=1}^{T_r}$  alongside text tokens  $\mathcal{E}$ , we initially utilize the CLIP encoder, denoted as  $F_{CLIP}$ , to extract frame-level visual features  $f_r^t$ . Subsequently, we employ  $N_1$  perceiver layers to integrate vision-language information into learnable queries Q for each reference frame. Formally,

$$f_r^t = F_{CLIP}(I_r^t),$$
  

$$Q^t = \text{CrossAttn}(Q, Concat[F_p(f_r^t), \mathcal{E}]).$$
(1)



Figure 3. Illustration of Object-aware Video Perceiver (OVP). OVP learns temporal and object information with  $N_1$  perceiver layers through the interactions of text and reference frames along with the learnable queries.

where CrossAttn denotes the Multi-Head Cross-Attention layer in perceiver,  $F_p$  is the projection function to align vision-language space,  $Q^t$  denotes the output reference tokens for the *t*-th reference frame.

Finally, we concat all the reference tokens  $Q^t$  along the time dimension to get the general reference tokens  $Q_r$ . We feed the general reference tokens  $Q_r$  into LLM along with text and visual tokens to tackle complex video reasoning tasks and temporal coherence problems. The implementation details will be elaborated upon in the following sections. Besides, for image segmentation tasks, the image itself serves as the reference for our OVP module, facilitating the bridge of the gap between image and video tasks (demonstrated in Tab. 6).

**Co-Decoding Process of LLM.** We utilize LLM for the collaborative decoding process of multiple functional tokens, including visual tokens and text tokens for common Multimodal comprehension, general reference tokens for video reasoning and understanding, and mask tokens for generating segmentation masks. To be specific, given the image or key frame  $\mathcal{V}$ , general reference tokens  $Q_T$  from OVP module for video tasks, text tokens  $\mathcal{E}$ , and initialized mask tokens M. Large Language Model  $F_{LLM}$  integrates them together and outputs the corresponding embeddings for the following multi-granularity text fusion and mask decoding process. Formally,

$$f_v = F_{CLIP}(\mathcal{V}), E = F_{LLM}(F_p(f_v), Q_r, \mathcal{E}, M).$$
(2)

where  $F_p$  is the projection function and E denotes the output embeddings of LLM. Subsequently, we extract the detailed text embeddings  $E_d$  and mask embeddings  $E_m$  from E according to their respective indexes, which are then fed into the following VMTF module and segmentation decoder for multi-granularity text fusion and mask generation.



Figure 4. The structure of the Vision-guided Multi-granularity Text Fusion (VMTF) module.

#### 3.3. Vision-guided Multi-granularity Text Fusion

In the context of Instructed Visual Segmentation tasks, particularly reasoning-based segmentation, it is critical to infer the truly desired or interesting objects from detailed textual descriptions. Previous methods [18, 47, 53] typically average or summarize the embeddings of multiple text tokens to generate a global embedding as the segmentation mask classifier. They tend to overlook detailed text information, which is crucial for understanding complex scenarios. Therefore, we propose the Vision-guided Multi-granularity Text Fusion (VMTF) module to integrate both global and detailed information of language instructions into the multi-granularity text embeddings as the mask classifier, facilitating better comprehension of the intentions behind the text instructions.

As shown in Fig. 4, given the detailed text embeddings  $E_d$ , we initially employ an adaptive average pooling strategy to obtain global text embeddings  $E_g$ , which consolidate global textual information. Subsequently, both the global and detailed text embeddings are input into  $N_2$  cross-attention and FFN layers along with the concatenation of fine-grained image features  $f_{img}$  and global text embeddings  $E_g$ . The Vision-guided Multi-granularity Text Fusion (VMTF) module is then utilized to integrate global and detailed language instruction information into multi-granularity text embeddings  $E_v$ . This integration enhances the accuracy and robustness of mask classification in both image and video domains.

#### 3.4. Mask Decoding and Training objectives

After the collaborative decoding and comprehension of LLM on multiple functional tokens, the segmentation decoder generates more accurate object masks and scores under the guidance of multi-granularity text embeddings.

**Segmentation decoder.** The segmentation decoder  $F_{decoder}$  predicts the masks m and the corresponding mask scores s based on three inputs: the fine-grained visual features  $f_{img}$  from the frozen visual encoder, multi-granularity text embeddings  $E_v$  from our VMTF module, and the mask embeddings  $E_m$  from the output of LLM, following the similar decoding process [7, 14]. Formally,

$$\{m_j, s_j, \}_{j=1}^N = F_{decoder}(f_{img}, E_v, E_m).$$
 (3)

Table 2. Comparison with the state-of-the-art models on the referring expression segmentation benchmarks (refCOCO/+/g) and reasoning segmentation (ReasonSeg). Our InstructSeg exhibits superior performance, surpassing all other methods significantly including both segmentation specialists and MLLM-based methods.

Tuno	Mathad		refCOC	C	refCOCO+		refCOCOg		ReasonSeg		
Type	Method	val	testA	testB	val	testA	testB	val(U)	test(U)	gIoU	cIoU
	VLT [11]	67.5	70.5	65.2	56.3	61.0	50.1	55.0	57.7	-	-
	CRIS [40]	70.5	73.2	66.1	62.3	68.1	53.7	59.9	60.4	-	-
Segmentation	LAVT [48]	72.7	75.8	68.8	62.1	68.4	55.1	61.2	62.1	-	-
Specialists	ReLA [24]	73.8	76.5	70.2	66.0	71.0	57.7	65.0	66.0	-	-
	PolyFormer [26]	74.8	76.6	71.1	67.6	72.9	59.3	67.8	69.1	-	-
	SEEM [57]	-	-	-	-	-	-	67.7	-	25.5	21.2
	LISA-7B [18]	74.9	79.1	72.3	65.1	70.8	58.1	67.9	70.6	52.9	54.0
	PixelLM-7B [35]	73.0	76.5	68.2	66.3	71.7	58.3	69.3	70.5	-	-
	GSVA-7B [45]	76.4	77.4	72.8	64.5	67.7	58.6	71.1	72.0	-	-
	LaSagnA-7B [41]	76.8	78.7	73.8	66.4	70.6	60.1	70.6	71.9	48.8	47.2
MLLM-based	VISA-7B [47]	72.4	75.5	68.1	59.8	64.8	53.1	65.5	66.4	52.7	57.8
Segmentation Models	OMG-LLaVA [51]	78.0	80.3	74.1	69.1	73.1	63.0	72.9	72.9	-	-
	GroundHog [31]	78.5	79.9	75.7	70.5	75.0	64.9	74.1	74.6	56.2	-
	GLaMM [34]	79.5	83.2	76.9	72.6	78.7	64.6	74.2	74.9	-	-
	PSALM [53]	83.6	84.7	81.6	72.9	75.5	70.1	73.8	74.4	-	-
	InstructSeg	85.8	86.6	84.0	80.1	83.8	75.6	79.3	80.3	61.9	65.2

where  $m_j \in \mathbb{R}^{H \times W}$  is the j-th segmentation mask,  $s_j \in \mathbb{R}$  denotes the mask scores of  $m_j$ , N denotes N mask proposals corresponding to the pre-defined N mask tokens. In practice, the final mask for each language instruction is derived by applying a threshold to the mask scores  $s_j$ .

**Training objectives.** We train InstructSeg in an end-to-end manner on multiple tasks and datasets concurrently, using a unified loss function  $\mathcal{L}$ . Specifically, we employ the text loss  $\mathcal{L}_t$  for text generation, the class loss  $\mathcal{L}_{cls}$  for mask classification, and the mask loss  $\mathcal{L}_{mask}$  for mask supervision. Formally,

$$\mathcal{L} = \mathcal{L}_t + \lambda_{cls} \mathcal{L}_{cls} + \lambda_{mask} \mathcal{L}_{mask}, \mathcal{L}_{mask} = \lambda_b \mathcal{L}_b + \lambda_d \mathcal{L}_d.$$
(4)

Specifically, we use an autoregressive cross-entropy loss for  $\mathcal{L}_t$ , a cross-entropy loss for  $\mathcal{L}_{cls}$ , and a combination of per-pixel binary cross-entropy loss  $\mathcal{L}_b$  and DICE loss  $\mathcal{L}_d$  for  $\mathcal{L}_{mask}$ .  $\lambda$  denotes the weight of each loss component.

## 4. Experiments

**Datasets.** We train InstructSeg in an end-to-end manner across multiple datasets of IVS tasks. For referring segmentation tasks, we use RefCOCO/+/g [32, 49] for image-level perception and Ref-Youtube-VOS [37] for video-level referring segmentation. As for reasoning segmentation tasks, we use ReasonSeg [18] for image reasoning segmentation and ReVOS [47] for video-level reasoning and understanding. Furthermore, we use LLAVA-150k [25] for the vision-language instruction task following [18, 53].

**Evaluation metrics.** We report results in widely used evaluation metrics: cumulative Intersection-over-Union (cIoU) for referring expression segmentation (RES) task, cIoU and the average of all per-image Intersection-over-Unions (gIoU) for image reasoning segmentation task, and region similarity  $\mathcal{J}$ and contour accuracy  $\mathcal{F}$  for all the video-level segmentation tasks.

**Implementation details.** We leverage the pre-trained lightweight Multi-modal Large Language Model Mipha-3B [55] as our base model, Swin-B [27] as our visual encoder and Maks2Former [7] as our segmentation decoder. All the models above are initialized with pre-trained weights. The layer numbers  $N_1$  in OVP module and  $N_2$  in VMTF are set to 3 by default. We train InstructSeg for 80k iterations with a batch size of 32 on 8×A100 GPUs. The total iterations are reduced to 40k in the ablation studies. By default, we set all the hyper-parameters  $\lambda_{cls}$ ,  $\lambda_{mask}$ ,  $\lambda_b$ , and  $\lambda_d$  to 1.0 experimentally.

#### 4.1. Main Results

We evaluate the effectiveness of the proposed Instruct-Seg through the comprehensive comparison with other stateof-the-art methods on various IVS tasks and Multi-modal Question Answering tasks.

**Referring expression segmentation and reasoning segmentation.** We compare InstructSeg with the state-of-theart methods on refCOCO/+/g [32, 49] and ReasonSeg [18] in Tab. 2. All the benchmarks are for image-level referring and reasoning segmentation. Our end-to-end model with proposed modules, InstructSeg, surpasses all the pre-

Table 3. Comparison with the state-of-the-art models on more complex and challenging reasoning video object segmentation benchmark, ReVOS. Our InstructSeg outperforms all the previous VLLM-based models with only 3B parameters.

Mathad	Dealthona	Reasoning			Referring				Overall		
Method	Backbolle	$\mathcal{J}$	$\mathcal{F}$	$\mathcal{J}\&\mathcal{F}$	J	$\mathcal{F}$	$\mathcal{J}\&\mathcal{F}$	J	${\mathcal F}$	$\mathcal{J}\&\mathcal{F}$	
LMPM [13]	Swin-T	13.3	24.3	18.8	29.0	39.1	34.1	21.2	31.7	26.4	
LLaMA-VID+LMPM [23]	Swin-T	12.8	23.7	18.2	29.0	39.1	34.1	20.9	31.4	26.1	
ReferFormer [44]	Video-Swin-B	21.3	25.6	23.4	31.2	34.3	32.7	26.2	29.9	28.1	
LISA [18]	LLaVA-7B	33.8	38.4	36.1	44.3	47.1	45.7	39.1	42.7	40.9	
TrackGPT [38]	LLaVA-7B	36.8	41.2	39.0	46.7	49.7	48.2	41.8	45.5	43.6	
TrackGPT [38]	LLaVA-13B	38.1	42.9	40.5	48.3	50.6	49.5	43.2	46.8	45.0	
VISA [47]	Chat-UniVi-7B	36.7	41.7	39.2	51.1	54.7	52.9	43.9	48.2	46.1	
VISA [47]	Chat-UniVi-13B	38.3	43.5	40.9	52.3	55.8	54.1	45.3	49.7	47.5	
InstructSeg	Mipha-3B	49.2	54.7	51.9	54.8	59.2	57.0	52.0	56.9	54.5	

Table 4. Results of referring video object segmentation benchmarks, including Ref-YouTube-VOS val set and Ref-DAVIS17 val set.

Tuno	Mathad	Paakhana	Ref-Y	'ouTube	-VOS val	Ref-DAVIS17 val		
туре	Method	Dackoone		${\mathcal F}$	$\mathcal{J}\&\mathcal{F}$	$\mathcal{J}$	${\mathcal F}$	$\mathcal{J}\&\mathcal{F}$
	URVOS [37]	ResNet50	45.3	49.2	47.2	47.3	56.0	51.6
	YOFO [19]	ResNet50	47.5	49.7	48.6	48.8	57.8	53.3
	MTTR[5]	Video-Swin-T	54.0	56.6	55.3	-	-	-
Segmentation	ReferFormer [44]	Video-Swin-B	61.3	64.6	62.9	58.1	64.1	61.1
Specialists	VLT [12]	Video-Swin-B	63.8	61.9	65.6	61.6	58.9	64.3
	LMPM[13]	Swin-T	-	-	-	-	-	-
	OnlineRefer [43]	Swin-L	61.6	65.5	63.5	61.6	67.7	64.8
	SgMg [31]	Video-Swin-B	63.9	67.4	65.7	60.6	66.0	63.3
	LISA [18]	LLaVA-7B	53.4	54.3	53.9	62.2	67.3	64.8
	LISA [18]	LLaVA-13B	54.0	54.8	54.4	63.2	68.8	66.0
MITM based	TrackGPT [38]	LLaVA-7B	55.3	57.4	56.4	59.4	67.0	63.2
Segmentation Models	TrackGPT [38]	LLaVA-13B	58.1	60.8	59.5	62.7	70.4	66.5
Segmentation Wodels	VISA [47]	Chat-UniVi-7B	59.8	63.2	61.5	66.3	72.5	69.4
	VISA [47]	Chat-UniVi-13B	61.4	64.7	63.0	67.0	73.8	70.4
	InstructSeg	Mipha-3B	65.4	69.5	67.5	67.3	74.9	71.1

vious works, achieving state-of-the-art performance on all the referring and reasoning datasets. To be specific, Instruct-Seg surpasses the current SOTA by a large margin, reaching 80.1 cIoU on RefCOCO+ val (+7.2 over PSALM), 79.3 cIoU on RefCOCOg val (+5.5 over PSALM) and 61.9 gIoU on ReasonSeg (+9.0 over LISA-7B).

**Reasoning video object segmentation.** We compare our InstructSeg with the state-of-the-art methods on the challenging ReVOS [47] benchmark in Tab. 3. Due to the dedicated and simplistic design, our 3B model beats the current SOTA with fewer parameters, especially in the ReVOS reasoning part, which demonstrates the effectiveness and efficiency of our InstructSeg. Specifically, we achieve  $51.9 \mathcal{J}\&\mathcal{F}$  on reasoning,  $57.0 \mathcal{J}\&\mathcal{F}$  on referring, and  $54.5 \mathcal{J}\&\mathcal{F}$  on overall, which outperform previous SOTA model VISA-13B[47] 11.0, 2.9, and 7.0 respectively. **Referring video object segmentation.** We adopt two standard benchmarks for referring video object segmentation tasks, including Ref-YouTube-VOS and Ref-DAVIS17. The comparisons between InstructSeg with the previous state-ofthe-art R-VOS methods are demonstrated in Tab. 4. Instruct-Seg surpasses all the segmentation specialists and MLLMbased segmentation models on both benchmarks. In challenging Ref-YouTube-VOS, our method achieves the best performance 67.5 on  $\mathcal{J}\&\mathcal{F}$  (+4.5 over VISA), outperforming all the methods by a large margin. Besides, InstructSeg achieves remarkable performance with only 3B parameters among MLLM-based models like TrackGPT-13B and VISA-13B.

**Multi-modal question answering benchmarks.** Our InstructSeg is the unified segmentation model leveraging Multimodal Large Language Models (MLLMs) for referring and reasoning segmentation in image and video domains, which

Table 5. The performance comparison of our InstructSeg on Multi-modal benchmarks. Our InstructSeg presents promising performance compared with previous MLLMs in various question-answering benchmarks.

Method	LLM	VQA <sup>v2</sup>	MMB	GQA	POPE	SQA
BLIP-2 [20]	Vicuna-13B	65.0	-	41.0	85.3	61.0
InstructBLIP [10]	Vicuna-7B	-	36.0	49.2	-	60.5
Shikra [6]	Vicuna-13B	77.4	58.8	-	-	-
Qwen-VL-Chat [3]	Qwen-7B	78.2	60.6	57.5	-	68.2
LLaVA-1.5 [25]	Vicuna-7B	78.5	64.3	62.0	85.9	66.8
MobileVLM [9]	M-LLaMA-2.7B	-	59.6	59.0	84.9	61.0
InstructSeg	Phi-2-2.7B	79.0	68.6	62.3	87.0	69.2

Table 6. Ablation on the core components of InstructSeg. OVP and VMTF denote the proposed Object-aware Video Perceiver and Vision-guided Multi-granularity Text Fusion module.

OVP	VMTE	RefCOCO val	I ReVOS				
Ovr	V IVI I I	cIoU	Reasoning	Referring	Overall		
		83.3	50.2	55.7	52.9		
$\checkmark$		84.6	51.2	56.9	54.0		
	$\checkmark$	84.8	51.3	56.6	53.9		
$\checkmark$	$\checkmark$	85.8	51.9	57.0	54.5		

has powerful reasoning capabilities for detailed text instructions. We also demonstrate its efficacy in addressing visionlanguage understanding tasks. As illustrated in Tab. 5, we evaluate InstructSeg on various Multi-modal benchmarks. Notably, InstructSeg achieves commendable performance with a smaller model size compared to existing MLLMs, such as BLIP-2 [20], Qwen-VL-Chat [3], and LLaVA-1.5 [25]. These results underscore the model's advanced conversational and reasoning capabilities.

#### 4.2. Ablations

**Effectiveness of the proposed components.** We assess the effectiveness of the proposed OVP module and VMTF module. As shown in Tab. 6, with our object-aware video perceiver and vision-guided multi-granularity text fusion, the segmentation accuracy can be promoted significantly on both referring and reasoning tasks, which demonstrates the effectiveness of our distinct design for each module.

**Different reference frames number.** We evaluate the performance of different numbers of reference frames  $T_r$  in our object-aware video perceiver module. As shown in Tab. 7, the performance of our InstructSeg gradually improves as the number  $T_r$  increases. We adopt  $T_r$ =4 for effective and efficient training and inference.

**Different text fusion strategy.** In Tab. 8, we compare our vision-guided multi-granularity text fusion module with various design choices. The comparison of the results shows that our multi-granularity fusion strategy (global + detailed) outperforms the single mode. This highlights the distinct

Table 7. The performance comparison on video segmentation tasks with different number  $T_r$  of reference frames in our object-aware video perceiver module.

T	Re	f-DAV	IS17	ReVOS					
$1_r$	$\mathcal{J}$	${\mathcal F}$	$\mathcal{J}\&\mathcal{F}$	Reasoning	Referring	Overall			
0	66.4	74.0	70.2	50.9	56.4	53.6			
4	67.3	74.9	71.1	51.9	57.0	54.5			
8	67.6	75.0	71.3	52.0	57.2	54.6			

Table 8. Ablation of different text fusion strategy.

Global	Detailed	RefCOCO val		ReVOS		
Global Detailed		cIoU	Reasoning	Referring	Overall	
$\checkmark$		84.2	50.3	56.7	53.5	
	$\checkmark$	83.5	51.6	56.7	54.1	
$\checkmark$	$\checkmark$	85.8	51.9	57.0	54.5	

properties of Instructed Visual Segmentation tasks, where both global and detailed textual information are crucial for comprehensive reasoning and perception.

Comparison between different training data recipes. Our model achieves excellent performance on all IVS tasks with joint training. In Tab. 9, we evaluate the impact of different training data recipes on our model performance. For different visual types, the model trained on images exhibits excellent zero-shot performance on ReasonVOS, demonstrating the generalization and robustness of our InstructSeg. Similarly, the model trained on videos achieves promising performance on RefCOCO, even surpassing non-zero-shot methods like LISA and VISA finetuning on the RefCOCO datasets. For different task types, the model trained exclusively on reasoning datasets delivers promising performance on RefCOCO, surpassing specialist models like ReLA and PolyFormer. This demonstrates that our InstructSeg with powerful reasoning segmentation capabilities can effectively generalize to referring segmentation tasks.

## 5. Conclusion

In this work, we unify the text-guided segmentation tasks across image and video domains under the framework of

Table 9. The performance comparison between different visual types (image and video) and task types (reasoning and referring) of Instructed Visual Segmentation tasks. Training jointly enables InstructSeg to achieve better performance with a single model.

Imaga	Video	Passoning	soning Referring		RefCOCO		RefCOCO+			ReVOS		
mage	video	Reasoning	Kelennig	val	testA	testB	val	testA	testB	Reasoning	Referring	Overall
$\checkmark$		<ul> <li>✓</li> </ul>	<ul> <li>✓</li> </ul>	84.2	86.0	81.7	79.2	83.3	72.9	43.6	53.9	48.7
	$\checkmark$	<ul> <li>✓</li> </ul>	$\checkmark$	78.1	82.1	75.0	70.0	77.6	63.0	50.0	56.7	53.3
$\checkmark$	$\checkmark$	<ul> <li>✓</li> </ul>		74.0	78.0	69.6	65.3	72.6	57.9	51.6	55.9	53.8
$\checkmark$	$\checkmark$		$\checkmark$	85.1	86.6	83.2	80.9	84.2	76.1	37.4	52.2	44.8
$\checkmark$	$\checkmark$	<ul> <li>✓</li> </ul>	<ul> <li>✓</li> </ul>	85.8	86.6	84.0	80.1	83.8	75.6	51.9	57.0	54.5

Instructed Visual Segmentation (IVS) and introduce Instruct-Seg, a universal and simplified segmentation network for IVS tasks. Our approach reduces the complexity and overcomes challenges associated with unifying referring expressions segmentation and reasoning segmentation at both the image and video levels. We present two main designs: an objectaware video perceiver that effectively captures temporal and object-specific information for enhanced video understanding and a vision-guided multi-granularity text fusion module that seamlessly integrates global and detailed language instructions with fine-grained vision guidance. Through multitask and end-to-end training, InstructSeg achieves superior performance in all IVS tasks, surpassing both specialist models and existing MLLM-based methods.

#### References

- Jean-Baptiste Alayrac, Jeff Donahue, Pauline Luc, Antoine Miech, Iain Barr, Yana Hasson, Karel Lenc, Arthur Mensch, Katherine Millican, Malcolm Reynolds, et al. Flamingo: a visual language model for few-shot learning. *Advances in Neural Information Processing Systems*, 35:23716–23736, 2022. 3
- [2] Kirolos Ataallah, Xiaoqian Shen, Eslam Abdelrahman, Essam Sleiman, Deyao Zhu, Jian Ding, and Mohamed Elhoseiny. Minigpt4-video: Advancing multimodal llms for video understanding with interleaved visual-textual tokens. *arXiv preprint arXiv:2404.03413*, 2024. 3
- [3] Jinze Bai, Shuai Bai, Shusheng Yang, Shijie Wang, Sinan Tan, Peng Wang, Junyang Lin, Chang Zhou, and Jingren Zhou. Qwen-vl: A frontier large vision-language model with versatile abilities. arXiv preprint arXiv:2308.12966, 2023. 8
- [4] Miriam Bellver, Carles Ventura, Carina Silberer, Ioannis Kazakos, Jordi Torres, and Xavier Giro-i Nieto. A closer look at referring expressions for video object segmentation. *Multimedia Tools and Applications*, 82(3):4419–4438, 2023.
   3
- [5] Adam Botach, Evgenii Zheltonozhskii, and Chaim Baskin. End-to-end referring video object segmentation with multimodal transformers. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 4985–4995, 2022. 3, 7
- [6] Keqin Chen, Zhao Zhang, Weili Zeng, Richong Zhang, Feng Zhu, and Rui Zhao. Shikra: Unleashing multimodal llm's

referential dialogue magic. *arXiv preprint arXiv:2306.15195*, 2023. 8

- [7] Bowen Cheng, Ishan Misra, Alexander G Schwing, Alexander Kirillov, and Rohit Girdhar. Masked-attention mask transformer for universal image segmentation. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 1290–1299, 2022. 3, 5, 6, 1
- [8] Ho Kei Cheng and Alexander G Schwing. Xmem: Long-term video object segmentation with an atkinson-shiffrin memory model. In *European Conference on Computer Vision*, pages 640–658. Springer, 2022. 3
- [9] Xiangxiang Chu, Limeng Qiao, Xinyang Lin, Shuang Xu, Yang Yang, Yiming Hu, Fei Wei, Xinyu Zhang, Bo Zhang, Xiaolin Wei, et al. Mobilevlm: A fast, reproducible and strong vision language assistant for mobile devices. arXiv preprint arXiv:2312.16886, 2023. 8
- [10] Wenliang Dai, Junnan Li, Dongxu Li, Anthony Meng Huat Tiong, Junqi Zhao, Weisheng Wang, Boyang Li, Pascale Fung, and Steven Hoi. Instructblip: Towards general-purpose visionlanguage models with instruction tuning, 2023. 8
- [11] Henghui Ding, Chang Liu, Suchen Wang, and Xudong Jiang. Vision-language transformer and query generation for referring segmentation. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 16321–16330, 2021. 2, 6
- [12] Henghui Ding, Chang Liu, Suchen Wang, and Xudong Jiang. Vlt: Vision-language transformer and query generation for referring segmentation. *IEEE Transactions on Pattern Analysis* and Machine Intelligence, 45(6):7900–7916, 2022. 7
- [13] Henghui Ding, Chang Liu, Shuting He, Xudong Jiang, and Chen Change Loy. Mevis: A large-scale benchmark for video segmentation with motion expressions. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 2694–2703, 2023. 2, 7
- [14] Xiuye Gu, Yin Cui, Jonathan Huang, Abdullah Rashwan, Xuan Yang, Xingyi Zhou, Golnaz Ghiasi, Weicheng Kuo, Huizhong Chen, Liang-Chieh Chen, et al. Dataseg: Taming a universal multi-dataset multi-task segmentation model. Advances in Neural Information Processing Systems, 36, 2024.
- [15] Mojan Javaheripi, Sébastien Bubeck, Marah Abdin, Jyoti Aneja, Sebastien Bubeck, Caio César Teodoro Mendes, Weizhu Chen, Allie Del Giorno, Ronen Eldan, Sivakanth Gopi, et al. Phi-2: The surprising power of small language models. *Microsoft Research Blog*, 1:3, 2023. 1

- [16] Aishwarya Kamath, Mannat Singh, Yann LeCun, Gabriel Synnaeve, Ishan Misra, and Nicolas Carion. Mdetr-modulated detection for end-to-end multi-modal understanding. In Proceedings of the IEEE/CVF international conference on computer vision, pages 1780–1790, 2021. 3
- [17] Alexander Kirillov, Eric Mintun, Nikhila Ravi, Hanzi Mao, Chloe Rolland, Laura Gustafson, Tete Xiao, Spencer Whitehead, Alexander C Berg, Wan-Yen Lo, et al. Segment anything. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 4015–4026, 2023. 3
- [18] Xin Lai, Zhuotao Tian, Yukang Chen, Yanwei Li, Yuhui Yuan, Shu Liu, and Jiaya Jia. Lisa: Reasoning segmentation via large language model. *ArXiv*, abs/2308.00692, 2023. 2, 3, 5, 6, 7
- [19] Dezhuang Li, Ruoqi Li, Lijun Wang, Yifan Wang, Jinqing Qi, Lu Zhang, Ting Liu, Qingquan Xu, and Huchuan Lu. You only infer once: Cross-modal meta-transfer for referring video object segmentation. In *Proceedings of the AAAI Conference* on Artificial Intelligence, pages 1297–1305, 2022. 7
- [20] Junnan Li, Dongxu Li, Silvio Savarese, and Steven Hoi. Blip-2: Bootstrapping language-image pre-training with frozen image encoders and large language models. *arXiv preprint arXiv:2301.12597*, 2023. 3, 8
- [21] KunChang Li, Yinan He, Yi Wang, Yizhuo Li, Wenhai Wang, Ping Luo, Yali Wang, Limin Wang, and Yu Qiao. Videochat: Chat-centric video understanding. *arXiv preprint arXiv:2305.06355*, 2023. 3
- [22] Muchen Li and Leonid Sigal. Referring transformer: A one-step approach to multi-task visual grounding. Advances in neural information processing systems, 34:19652–19664, 2021. 3
- [23] Yanwei Li, Chengyao Wang, and Jiaya Jia. Llama-vid: An image is worth 2 tokens in large language models. In *European Conference on Computer Vision*, pages 323–340. Springer, 2025. 3, 7
- [24] Chang Liu, Henghui Ding, and Xudong Jiang. Gres: Generalized referring expression segmentation. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, pages 23592–23601, 2023. 2, 6
- [25] Haotian Liu, Chunyuan Li, Qingyang Wu, and Yong Jae Lee. Visual instruction tuning. Advances in neural information processing systems, 36, 2024. 3, 6, 8
- [26] Jiang Liu, Hui Ding, Zhaowei Cai, Yuting Zhang, Ravi Kumar Satzoda, Vijay Mahadevan, and R Manmatha. Polyformer: Referring image segmentation as sequential polygon generation. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, pages 18653–18663, 2023. 2, 6
- [27] Ze Liu, Yutong Lin, Yue Cao, Han Hu, Yixuan Wei, Zheng Zhang, Stephen Lin, and Baining Guo. Swin transformer: Hierarchical vision transformer using shifted windows. In Proceedings of the IEEE/CVF international conference on computer vision, pages 10012–10022, 2021. 6, 1
- [28] Gen Luo, Yiyi Zhou, Xiaoshuai Sun, Liujuan Cao, Chenglin Wu, Cheng Deng, and Rongrong Ji. Multi-task collaborative network for joint referring expression comprehension and segmentation. In *Proceedings of the IEEE/CVF Conference*

on computer vision and pattern recognition, pages 10034–10043, 2020. 3

- [29] Zhuoyan Luo, Yicheng Xiao, Yong Liu, Shuyan Li, Yitong Wang, Yansong Tang, Xiu Li, and Yujiu Yang. Soc: Semanticassisted object cluster for referring video object segmentation. *Advances in Neural Information Processing Systems*, 36, 2024.
- [30] Muhammad Maaz, Hanoona Rasheed, Salman Khan, and Fahad Shahbaz Khan. Video-chatgpt: Towards detailed video understanding via large vision and language models. arXiv preprint arXiv:2306.05424, 2023. 3
- [31] Bo Miao, Mohammed Bennamoun, Yongsheng Gao, and Ajmal Mian. Spectrum-guided multi-granularity referring video object segmentation. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 920– 930, 2023. 6, 7
- [32] Varun K Nagaraja, Vlad I Morariu, and Larry S Davis. Modeling context between objects for referring expression understanding. In *Computer Vision–ECCV 2016: 14th European Conference, Amsterdam, The Netherlands, October 11–14,* 2016, Proceedings, Part IV 14, pages 792–807. Springer, 2016. 6
- [33] Renjie Pi, Lewei Yao, Jiahui Gao, Jipeng Zhang, and Tong Zhang. Perceptiongpt: Effectively fusing visual perception into llm. arXiv preprint arXiv:2311.06612, 2023. 3
- [34] Hanoona Rasheed, Muhammad Maaz, Sahal Shaji, Abdelrahman Shaker, Salman Khan, Hisham Cholakkal, Rao M Anwer, Erix Xing, Ming-Hsuan Yang, and Fahad S Khan. Glamm: Pixel grounding large multimodal model. arXiv preprint arXiv:2311.03356, 2023. 2, 6
- [35] Zhongwei Ren, Zhicheng Huang, Yunchao Wei, Yao Zhao, Dongmei Fu, Jiashi Feng, and Xiaojie Jin. Pixellm: Pixel reasoning with large multimodal model. *ArXiv*, abs/2312.02228, 2023. 2, 3, 6
- [36] Michael S Ryoo, Honglu Zhou, Shrikant Kendre, Can Qin, Le Xue, Manli Shu, Silvio Savarese, Ran Xu, Caiming Xiong, and Juan Carlos Niebles. xgen-mm-vid (blip-3-video): You only need 32 tokens to represent a video even in vlms. arXiv preprint arXiv:2410.16267, 2024. 3
- [37] Seonguk Seo, Joon-Young Lee, and Bohyung Han. Urvos: Unified referring video object segmentation network with a large-scale benchmark. In *Computer Vision–ECCV 2020:* 16th European Conference, Glasgow, UK, August 23–28, 2020, Proceedings, Part XV 16, pages 208–223. Springer, 2020. 6, 7
- [38] Nicholas Stroh. Trackgpt–a generative pre-trained transformer for cross-domain entity trajectory forecasting. arXiv preprint arXiv:2402.00066, 2024. 7
- [39] Jiajin Tang, Ge Zheng, Cheng Shi, and Sibei Yang. Contrastive grouping with transformer for referring image segmentation. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, pages 23570– 23580, 2023. 3
- [40] Zhaoqing Wang, Yu Lu, Qiang Li, Xunqiang Tao, Yandong Guo, Mingming Gong, and Tongliang Liu. Cris: Clipdriven referring image segmentation. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 11686–11695, 2022. 2, 3, 6

- [41] Cong Wei, Haoxian Tan, Yujie Zhong, Yujiu Yang, and Lin Ma. Lasagna: Language-based segmentation assistant for complex queries. *arXiv preprint arXiv:2404.08506*, 2024. 2, 3, 6
- [42] Cong Wei, Yujie Zhong, Haoxian Tan, Yong Liu, Zheng Zhao, Jie Hu, and Yujiu Yang. Hyperseg: Towards universal visual segmentation with large language model. arXiv preprint arXiv:2411.17606, 2024. 3
- [43] Dongming Wu, Tiancai Wang, Yuang Zhang, Xiangyu Zhang, and Jianbing Shen. Onlinerefer: A simple online baseline for referring video object segmentation. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 2761–2770, 2023. 2, 7
- [44] Jiannan Wu, Yi Jiang, Peize Sun, Zehuan Yuan, and Ping Luo. Language as queries for referring video object segmentation. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, pages 4974–4984, 2022. 2, 3, 7
- [45] Zhuofan Xia, Dongchen Han, Yizeng Han, Xuran Pan, Shiji Song, and Gao Huang. Gsva: Generalized segmentation via multimodal large language models. *arXiv preprint* arXiv:2312.10103, 2023. 2, 3, 6
- [46] Lin Xu, Yilin Zhao, Daquan Zhou, Zhijie Lin, See Kiong Ng, and Jiashi Feng. Pllava: Parameter-free llava extension from images to videos for video dense captioning. *arXiv preprint arXiv:2404.16994*, 2024. 3
- [47] Cilin Yan, Haochen Wang, Shilin Yan, Xiaolong Jiang, Yao Hu, Guoliang Kang, Weidi Xie, and Efstratios Gavves. Visa: Reasoning video object segmentation via large language models. arXiv preprint arXiv:2407.11325, 2024. 2, 3, 4, 5, 6, 7
- [48] Zhao Yang, Jiaqi Wang, Yansong Tang, Kai Chen, Hengshuang Zhao, and Philip HS Torr. Lavt: Language-aware vision transformer for referring image segmentation. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, pages 18155–18165, 2022. 2, 6
- [49] Licheng Yu, Patrick Poirson, Shan Yang, Alexander C Berg, and Tamara L Berg. Modeling context in referring expressions. In *Computer Vision–ECCV 2016: 14th European Conference, Amsterdam, The Netherlands, October 11-14,* 2016, Proceedings, Part II 14, pages 69–85. Springer, 2016.
  6
- [50] Xiaohua Zhai, Basil Mustafa, Alexander Kolesnikov, and Lucas Beyer. Sigmoid loss for language image pre-training. In Proceedings of the IEEE/CVF International Conference on Computer Vision, pages 11975–11986, 2023. 1
- [51] Tao Zhang, Xiangtai Li, Hao Fei, Haobo Yuan, Shengqiong Wu, Shunping Ji, Chen Change Loy, and Shuicheng Yan. Omg-llava: Bridging image-level, object-level, pixel-level reasoning and understanding. arXiv preprint arXiv:2406.19389, 2024. 2, 6
- [52] Zicheng Zhang, Yi Zhu, Jianzhuang Liu, Xiaodan Liang, and Wei Ke. Coupalign: Coupling word-pixel with sentence-mask alignments for referring image segmentation. *Advances in Neural Information Processing Systems*, 35:14729–14742, 2022. 3
- [53] Zheng Zhang, Yeyao Ma, Enming Zhang, and Xiang Bai.

Psalm: Pixelwise segmentation with large multi-modal model. *arXiv preprint arXiv:2403.14598*, 2024. 2, 3, 5, 6, 1

- [54] Deyao Zhu, Jun Chen, Xiaoqian Shen, Xiang Li, and Mohamed Elhoseiny. Minigpt-4: Enhancing vision-language understanding with advanced large language models. arXiv preprint arXiv:2304.10592, 2023. 3
- [55] Minjie Zhu, Yichen Zhu, Xin Liu, Ning Liu, Zhiyuan Xu, Chaomin Shen, Yaxin Peng, Zhicai Ou, Feifei Feng, and Jian Tang. A comprehensive overhaul of multimodal assistant with small language models. arXiv preprint arXiv:2403.06199, 2024. 6
- [56] Xueyan Zou, Zi-Yi Dou, Jianwei Yang, Zhe Gan, Linjie Li, Chunyuan Li, Xiyang Dai, Harkirat Behl, Jianfeng Wang, Lu Yuan, et al. Generalized decoding for pixel, image, and language. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, pages 15116–15127, 2023. 3
- [57] Xueyan Zou, Jianwei Yang, Hao Zhang, Feng Li, Linjie Li, Jianfeng Wang, Lijuan Wang, Jianfeng Gao, and Yong Jae Lee. Segment everything everywhere all at once. Advances in Neural Information Processing Systems, 36, 2024. 6

# InstructSeg: Unifying Instructed Visual Segmentation with Multi-modal Large Language Models

# Supplementary Material

## **A. Additional Implementation Details**

We utilize Phi-2 [15] with 2.7B parameters as our Large Language Model, SigLIP [50] as our CLIP Encoder, Swin-B [27] as our Visual Encoder, and pre-trained Maks2Former [7] as our Segmentation Decoder. We keep both CLIP Encoder and Visual Encoder frozen while applying LORA with a rank of 8 to fine-tune the Large Language Model. In contrast, the OVP, VMTF, and Segmentation Decoder components are fully fine-tuned. We use AdamW optimizer with the learning rate and weight decay set to 0.00004 and 0, respectively. In addition, we adopt Cosine Decay for the learning rate schedule, where the warmup steps are set to 1680. The source code for our implementation will be made publicly available in the near future.

## **B. Segmentation Decoder Structure**

We illustrate the architecture of the segmentation decoder module in Fig. 5. Consistent with previous methods [7, 53], our approach integrates both a pixel decoder and a transformer decoder to extract pixel-level visual information and instance-level object information. Distinctively, we compute the similarity between mask embeddings and multi-grained text embeddings to derive mask scores, which are then utilized for the selection of mask proposals.

## C. Task-specific Instructions Design

In this section, we illustrate the text prompt with task-specific instructions for all the Instructed Visual Segmentation tasks. As shown in Tab. 10, we design different instruction templates for all four segmentation tasks along with corresponding text prompts.

## **D.** More Qualitative Results

## D.1. Referring Expression Segmentation (Imagelevel)

Fig. 6 shows the visualization of InstructSeg on referring segmentation task.

## **D.2. Reasoning Segmentation (Image-level)**

Fig. 7 presents the effectiveness of our InstructSeg in understanding the complex question and performing segmentation according to the reasoning process.



Figure 5. The structure of the Segmentation Decoder module. Following [7], we adopt the pixel decoder and transformer decoder to excavate pixel-level visual information and instance-level object information. In contrast, we calculate the similarity between mask embeddings and multi-grained text embeddings as the mask scores for mask proposals' selection.

## D.3. Reasoning and Referring Video Object Segmentation (Video-level)

Fig. 8 shows the effectiveness of InstructSeg in comprehending both the reasoning questions and temporal coherence. InstructSeg is capable of producing segmentation masks that maintain consistency across temporal sequences.

Task	Visual Type	Dataset	Instruction Template	Text Prompt
Referring Expression Segmentation	Image	RefCOCO/+/g	You need to perform Referring Expression Segmentation on the image according to the Text Prompt.	"A baseball catcher with an open mitt"
Reasoning Segmentation	Image	ReasonSeg	You need to perform Reasoning Segmentation on the image according to the Text Prompt.	"The person who appears to have already won in the battle"
Referring Video Object Segmentation	Video	Ref-YouTube-VOS, etc.	You need to perform Referring Video Object Segmentation on the video according to the Text Prompt.	"A duck is held by a person with her both hands"
Reasoning Video Object Segmentation	Video	ReVOS	You need to perform Reasoning Video Object Segmentation on the video according to the Text Prompt.	"Which person is in the leading position?"





Figure 6. Qualitative results of InstructSeg's capability in referring expression segmentation.



Figure 7. Qualitative results of InstructSeg in reasoning segmentation.



Figure 8. Qualitative results of InstructSeg demonstrate its capability in the complex reasoning video object segmentation task and referring video object segmentation task.