# LEARN: A Unified Framework for Multi-Task Domain Adapt Few-Shot Learning

Bharadwaj Ravichandran, Alexander Lynch, Sarah Brockman, Brandon RichardWebster, Dawei Du, Anthony Hoogs, Christopher Funk

{firstname.lastname}@kitware.com

Kitware Inc.

#### Abstract

Both few-shot learning and domain adaptation sub-fields in Computer Vision have seen significant recent progress in terms of the availability of state-of-the-art algorithms and datasets. Frameworks have been developed for each sub-field; however, building a common system or framework that combines both is something that has not been explored. As part of our research, we present the first unified framework that combines domain adaptation for the fewshot learning setting across 3 different tasks - image classification, object detection and video classification. Our framework is highly modular with the capability to support few-shot learning with/without the inclusion of domain adaptation depending on the algorithm. Furthermore, the most important configurable feature of our framework is the on-the-fly setup for incremental n-shot tasks with the optional capability to configure the system to scale to a traditional many-shot task. With more focus on Self-Supervised Learning (SSL) for current few-shot learning approaches, our system also supports multiple SSL pre-training configurations. To test our framework's capabilities, we provide benchmarks on a wide range of algorithms and datasets across different task and problem settings. The code is open source has been made publicly available here: https: //gitlab.kitware.com/darpa learn/learn

# 1. Introduction

Up until 2018, with the advent of metric learning and metalearning, the field of few-shot learning had little innovation with most methods revolving around pre-training and fine-tuning [55]. However, after 2018, there has been an exponential increase in the number of few-shot learning publications with the majority of them coming within the field of computer vision. There have been a number of datasets adapted specifically for the task of few-shot learning such as mini-Imagenet [13], CIFAR-10 [30], and Meta-



Figure 1. The LEARN Framework Concept Figure showing the different components of our Domain Adapt Few-Shot learning workflow. The Few-Shot domain adaptation block shows a sample images from DomainNet [46] ClipArt and Sketch for the class "Aircraft Carrier".

Dataset [59] which either subsample a larger dataset to restrict it to a few-shot setting or combine smaller datasets to increase the number of available classes. There has already been remarkable progress on these datasets with the accuracy on mini-Imagenet being pushed from 46.6% in 2016 with Matching Nets [63] to 95.3% in 2022 with the P>M>F algorithm [20]. While image classification was the first computer vision task to see real attention using the few-shot paradigm, both object detection and video classification have also seen progress as both meta-learning and transfer learning have been applied with success [4, 7, 84].

The domain shift problem in computer vision is crucial when considering building systems around multiple datasets with varying image domains and class labels. Back in 2017, Tzeng *et al.* [60] proposed a simple-yet-efficient adversarial adaption baseline for domain transfer between the digit images of MNIST [35] and USPS [22]. Since then, the number of algorithms and datasets introduced as part of domain adaptation has seen a huge increase. For instance, in adversarial domain adaption, the MADA method [44] introduced a fine-grained alignment using multiple domain discriminators (one for each class). Following this, many more methods like DADA [57], IDDA [33], RADA [70] were introduced to push state-of-the-art performance across different datasets such as Office-31 [51] and Office-Home [62]. Unsupervised and Semi-Supervised Domain Adaption paved the way for a whole set of methods that uses Knowledge Distillation [41, 58, 72, 76, 80], Statistical Domain Alignment [14, 16, 25, 81], Contrastive Learning [1, 21, 67, 71]. In addition to the methods discussed above, a large number of public datasets have been made available for the Domain Adaptation Image Classification task [22, 35, 46, 51, 62]. Out of these, since the VisDA2019 [65] challenge, the DomainNet [46] dataset is considered as a standard to advance state-of-the-art Domain Adaptation algorithms for fine-grained classification.

For object detection and video classification, there are a number of public datasets used in combination for domain adaptation. Cityscape [12], FoggyCityscape [53], Sim10k [26], and KITTI [39] datasets are a group of overhead imagery datasets that are commonly used to train domain adaptation models using any two of the above mentioned datasets as the source and target. [43, 78]. PASCAL VOC is also commonly used as a source dataset which is then adapted to ClipArt1K [24], Watercolor2K [24], and BDD100K [79] for object detection domain adaptation [43]. For video classification, UCF101 [56], HMBD [31], Kinetics [27], and ARID [73] are used interchangeably for adapting from one dataset to another. These datasets are some of the oldest and most commonly used datasets for the video classification domain adaptation problem [74, 75, 77].

Therefore, with the increasing interest in few-shot learning and domain adaptation, there is a greater need for tools that can facilitate running few-shot and domain shift experiments. Existing few-shot learning frameworks like the LibFewShot [37] and *learn2learn* [3] provide a variety of APIs across different components of the framework pipeline, but are focused on only the image classification task. In this paper, we showcase a new framework which is easy to use across multiple computer vision tasks and provides APIs for algorithms to be applied in a domain-adapt few-shot setting.

Furthermore, to provide a single cohesive workflow for training models in a variety of *n*-shot settings, we developed the iterative active learning workflow with an increasing number of label instances budgeted either on a per class basis or in totality as described in Figure 2. This modular training loop includes domain adaptation steps for at least one algorithm per task giving users the option to perform domain adaptation regardless of the task being executed. In order to balance the different algorithm and general framework parameters, we use a customizable configuration protocol in which the user specifies parameters to be used in their experiments either in default or through custom configuration files or as optional command line arguments for every possible parameter.

Based on our knowledge about existing domain-adapt few-shot learning frameworks, we believe our proposed system is the first unified framework to

- support multi-stage domain-adapt incremental *n*-shot learning, where *n* is the number of labels per class;
- support different computer vision tasks image classification, object detection and video classification (with/without self-supervised pre-training based on the algorithm) - for different types of domain-adapt scenarios;
- provide a modular and scalable way to extend to a manyshot task without having to restart a few-shot experiment from scratch.

In order to support these claims, we conducted extensive experiments on the 3 tasks mentioned above across different domain-adapt few-shot settings and have included the corresponding results in Section 6.

## 2. Related Works

Over the last few years, there has been significant development with respect to few-shot learning frameworks. Chada *et al.* [10] created a NLP framework named "FewshotQA" which leverages pre-trained text-to-text models for creating benchmarks for a Q&A chatbot. Wang *et al.* [69] introduced a few-shot framework for 1D data, specifically Signal Modulation classification.

In regard to vision-based few-shot learning frameworks, Lin et al. [40] introduced a unified framework for image classification and object detection that supports episodic learning methods, meta-learning and fine-tuning across multiple source/target datasets and pre-trained models. In addition to this, the authors propose a meta-dropout to improve the generalization capability during the meta-training stage. The benchmarks reported from a wide range of algorithms are primarily on 1, 5-shot tasks on the CUB [66] and mini-ImageNet [64] datasets and 1, 3, 10-shot tasks on the VOC2007 [15] dataset. LibFewShot is a similar framework from Li et al. [37] which contains benchmarks across the different modes of few-shot learning, but focuses only on the image classification task. Furthermore, the framework supports K-way, n-shot task setups with benchmarks from different algorithms reported on the following datasets - mini-ImageNet [64], tieredImageNet [49], Stanford Dogs [28], Stanford Cars [29] and CUB [66]. Arnold et al. [3] introduced the learn2learn library which primarily focuses on Meta-learning few-shot benchmarks. The library consists of APIs to interact with PyTorch models and datasets and also contains high-level wrapper code for a bunch of existing meta-learning algorithms - MAML [17], Meta-SGD [38], MetaOptNet [36] and ProtoNets [83]. In contrast, our proposed framework is expanded to support

Framework features	LEARN	LibFewShot [37]	learn2learn [3]
Customizable Datasets	✓	✓	~
Customizable YAML Configuration file	$\checkmark$	✓	
Domain Adaptation Capability	$\checkmark$	✓	
Iterative k-shot experiments	$\checkmark$		
Few-Shot Image Classification	$\checkmark$	✓	$\checkmark$
Few-Shot Video Classification	$\checkmark$		
Few-Shot Object Detection	√		

Table 1. Summarization of the similarities between our framework and LibFewShot and learn2learn and the features we implemented to expand our framework's functionality and the ease of the user experience.

three computer vision tasks in multi-stage domain-adapt few-shot learning.

Table 1 provides an overview of the functionalities of a couple of existing few-shot learning frameworks in comparison with the LEARN framework.

# **3. The LEARN Framework**

The Label-Efficient Active Resilient Networks framework (LEARN) is a unified framework for multi-task, domainadapt few-shot learning. In the following subsections, we discuss the overall design and the experiment protocol configurations for the tasks and algorithms supported by the framework.

## **3.1. Experiment Protocol**

Our framework is capable of running a variety of experiments for different tasks using different algorithms with a plethora of both general and algorithm specific hyperparameters. In order to give users access to the full breadth of experimental possibilities, the entire set of hyperparameters is exposed to the users to maximize ease of use. The experiment running protocol for the framework is configured with the help of Hydra [23] which provides a customizable way to configure experiment parameters. A sample Hydra command looks for the following parameters to start an experiment - problem.tasks\_to\_run, image\_classifier (or) video\_classifier (or) object\_detector (based on the algorithm). These parameters point to individual JSON files containing the configuration details for the chosen task and algorithm respectively. Furthermore, selecting the source method pre-trained backbone weights is specified by domain\_network\_selector.params.set\_source \_data\_network. One of the most important parameters is the problem.add\_dataset\_to\_whitelist. This provides a list of source datasets to consider during the protocol setup and skips all other datasets to save on processing time.

## 3.1.1 Task Configuration

There are many parameters to select between the task, algorithm, and experiment specific parameters. In order to make it easier for users to specify each of these parameters, the LEARN framework has a built-in interface which focuses on task JSON files that are defined locally. Each file contains the following task parameters:

- 1. name: A unique string identifier for the task.
- 2. **problem\_type:** String value to denote 1 out of the 3 tasks supported by the framework -"image\_classification", "object\_detection" and "video\_classification".
- 3. **stages:** A list of JSON objects (where each object corresponds to one stage) containing the following fields:
  - (a) **name:** Name of the domain-adapt stage "base" or "adapt".
  - (b) **dataset:** Name of the target dataset for the stage.
  - (c) **seed\_budgets:** A list containing the cumulative *n*-shot budgets (*n* labels per class), where each *n*-shot problem corresponds to the  $(n 1)^{th}$  checkpoint during training and inference.
  - (d) **label\_budget:** A list containing the cumulative label budget across all classes (not *n*-shot). These additional labels are used during training after completing the *n*-shot training based off of the seed\_budgets.
- 4. **whitelist:** A list containing the names of the source datasets that may be used for task. The dataset names not mentioned in the whitelist are skipped by the system during source dataset and method setup.
- 5. results\_file: Name of the results files under the default "outputs/<current\_date>/<experiment\_start\_time>" path that contains the predictions for each checkpoint of each stage.

## 3.1.2 Algorithm Setup

As shown in Figure 2, each task has N stages and a "source" & "target" dataset for each stage. Each stage consists of the following four algorithm-related sub-stages below that occur in an iterative manner based on the available label budget for each checkpoint. Furthermore, each of these sub-stages have their own dedicated sub-folders and are configured with default experiment parameters using YAML configuration files:

- 1. **Domain/Network Selection:** Determine the source dataset and source pre-trained backbone based on the closest similarity to the chosen target dataset.
- 2. Algorithm Selection: Choose the algorithm to run based on a specified task and given source & target dataset.
- 3. Active Learning Query Strategy: Iteratively queries the unlabeled data that is most impactful for labeling based on the available label budget level (determined by



Figure 2. Task workflow across the different tasks - IC: Image Classification, **OD**: Object Detection and **VC**: Video Classification from the LEARN framework. In addition to the multitask few-shot learning, the framework supports custom domain adapt scenarios as mentioned in the diagram along with the capability to setup SSL pre-training using unlabeled data.

label\_budget). By default, the querying algorithm does a random shuffle of the unlabeled target dataset and updates the training set based on the additional available label budget.

4. **Few-Shot Domain Adaptation:** Perform the algorithm that creates a classification for the target task. After a particular budget level is reached, the adaptation stage performs an evaluation on the test data.

# 4. Algorithms

In this section, we briefly describe the representative algorithms on three tasks used in our framework. The algorithms discussed below are chosen based on their availability for domain adaption scenarios (Image Classification) and self-supervised pre-training capability (for Object Detection and Video Classification) and thus supported by the LEARN framework.

#### 4.1. Image Classification

**MetaBaseline** [11] is a 2-stage architecture for few-shot image classification. In the first classification stage, a classification model is trained using all the samples from base classes set and the last FC layer is removed to obtain the encoder. Following this, the average feature of per-class support set samples is computed and a given sample from a query set is classified using nearest-centroid with cosine similarity as the distance metric. In the second meta stage, the cosine similarity range is scaled using an additional learnable scalar before applying softmax during Meta-Baseline training. The goal of Meta-Baseline is to verify the efficacy of the meta-learning objective over a whole-classification model.

The benchmarking for Meta-Baseline includes a ResNet-12 [18] backbone trained and evaluated on the miniImageNet [64] and tieredImageNet [49] few-shot classification datasets. In addition to these benchmarks, ResNet-18 and ResNet-50 backbones are trained and evaluated on the ImageNet-800 [11] dataset.

MME (MiniMax Entropy) [52] was proposed to effectively align feature distributions of the source and target domains under a semi-supervised domain adaptation setting. The algorithm uses an adversarial optimization approach by updating the classifier's estimated class prototypes to maximize entropy on the unlabeled target domain and cluster features based on the estimated prototypes by minimizing entropy with respect to the feature extractor. As part of the maximization step, the entropy measured on unlabeled target samples shows the similarity between the estimated prototypes and target features. So, the weight vectors are modified to shift towards the target data by maximizing the entropy of the unlabeled target samples. Following this, as part of the minimization step, the feature extractor is updated to minimize entropy of the unlabeled target samples to enable better clustering around the estimated prototypes.

The proposed model consists of a feature extractor created by removing the last linear layer of an existing pretrained model and adding a *K*-way linear classification layer with random initial weights. The feature extractors experimented by the authors include AlexNet, VGG16 and ResNet34 loaded with ImageNet pretrained weights and adapted for cross domain scenarios using the Domain-Net [46], Office-Home [62] and Office-31 [51] datasets.

**PACMAC** (Probing Attention-Conditioned Masking Consistency) [47] is a selection algorithm proposed for domain adaptation of self-supervised Vision Transformers (ViTs) to unseen domains. First, it performs in-domain self-supervised learning on a combination of source and target data to exploit task-discriminative features. Then, the algorithm selects reliable samples for self-training based on the predictive consistency across a set of attention-conditioned masks applied on a set of the target data.

During the attention-conditioned masking stage, a greedy assignment strategy is employed to select the high attention patches followed by generating its corresponding set of disjoint masks. After this, a consistency-based reliability metric is computed based on the original and masked images for selecting target samples for self-training.

Benchmark comparisons for the PACMAC system report target test set accuracy for three few-shot domain-adapt classification datasets - DomainNet [46], Office-Home [62] and VisDA2017 [45]. The model architecture consists of a ViT-Base model with 16x16 images patches, starting from two different pretrained backbones initialized with imagenet1k [50] weights - MAE [19] and DINO [9].

#### 4.2. Video Classification

**X-Clip** [42] is an expansion of CLIP [48] specifically designed for the task of video recognition. The key contribution is a cross-frame attention mechanism for encoding long range temporal dependencies across frames. This transformer takes in raw frame data and generates frame level embeddings while allowing information to be shared across frames during the embedding process. A second "multiframe integration transformer" [42] is then used to fuse those frame-level embeddings and output a single embedding for the whole video.

The X-Clip algorithm then uses a learned text encoder to augment the raw label text embeddings. This text encoder first uses a multi-head attention layer to create a joint embedding of the encoded raw label text and the cohesive video embedding. This text-video embedding is then fed through a FFN (feed forward network) and outputs a text embedding based on the raw label that is specific to the context of the provided video.

Finally a cosine similarity is calculated between the augmented label text embedding and the full video embedding. The goal of this training is to maximize the cosine similarity between these embeddings.

**TimeSformer** [5] implements a transformer architecture that enables feature learning across the temporal and spatial dimensions. The algorithm takes as input a set of frames and then splits each frame into a set of N non-overlapping

square patches. The patches are then mapped to an embedding vector through a learned embedding matrix, and these embeddings are then fed as inputs into the transformer.

The authors experiment with four different variations of self-attention blocks, but the one that achieves the highest success and the one we focus on is referred to as the "Divided Space-Time Attention (T +S)"[5] block. In this block, temporal attention is calculated first by comparing each patch with the patch at the same location across all the given frames. The encoding from the temporal attention block is then fed back into the spatial attention block which compares all of the patches across a single frame. The encoding given from the spatial attention block is then passed through a final multi-layer perceptron (MLP) module to get the final encoding for a given patch.

**CoMix** (Contrast and Mix) [2] uses contrastive learning by maximizing the similarity between both the same video played at different playback speeds as well as different videos played back at varying playback speeds. Sets of fast (f) and slow (s) clips are used as inputs to a feature encoder which maps them to a set of feature encodings. A temporal graph encoder is then used to create a fully connected graph on top of the clip-level feature embeddings. The graph representation is then fed into a graph convolutional network which produces video classification output with per-class confidences.

Another unique contribution of CoMix is the mixing of background frames in a video. Synthetic videos created by cross-domain background frame mixing has the action semantics of the original video but also consists of frames from a different domain. This allows additional positive examples to be created for any given video to be utilized in the contrastive learning process.

#### 4.3. Self-Supervised Object Detection Pre-training

**DETReg** [4] While most object detection pre-training algorithms focus on just training the backbone in the pretraining step, DETReg [4] pre-trains both the embedding backbone as well as the localization head by carrying out an object localization task as well as an object embedding task. DETReg's object localization pre-training "uses simple region proposal methods for class-agnostic bounding-box supervision" by using the Selective Search [61] method. Selective search uses various visual cues to generate a set of bounding boxes around the predicted objects in the image excluding any class predictions. The object localization task takes a set of boxes output by the selective search unsupervised region proposal network (RPN) and optimizes a loss that minimizes the difference between the boxes output by the detector and the boxes generated from the RPN.

When pre-training the object embedding task, the encoders learn transformation-invariant embeddings so that the detectors trained are robust to variation in image trans-



Figure 3. Overview of the image domains across the 3 image classification datasets used in our benchmarking. A: DomainNet dataset samples for the class "Aircraft Carrier". B: Office-Home dataset samples for the class "Alarm Clock". C: Office-31 dataset samples for the class "Backpack".

formations such as cropping or translation. To accomplish this, a pre-trained SwAV [8] is used to generate a ground truth feature embedding to train the object detection classification head.

**CutLER** (Cut and Learn) [68] is agnostic to the underlying detector being used. It is comprised of two sections that are repeated for multiple rounds. First CutLER uses a novel expansion of the NCut [54] algorithm, referred to as MaskCut, that iteratively runs through the NCut algorithm detecting x objects where x is 3 by default. The MaskCut algorithm produces a series of binary masks for each object detected. After generating the set of binary masks, a loss function called DropLoss is applied. DropLoss is specifically designed to encourage the discovery of the "groundtruth" objects that were not discovered by the initial Mask-Cut algorithm. It accomplishes this by dropping the loss for each predicted region that has an overlap greater than or equal to a set threshold.

By using this coarse mask generation from MaskCut and the DropLoss function that encourages new objects to be detected, multiple rounds of this self-training process is applied to steadily increase the number of "ground-truth samples" obtained from a given image.

#### **5.** Datasets

The datasets discussed below are commonly used public datasets that vary in terms of the granularity of the classes and also provide the domain adaptation scenarios (for Image Classification) that could be used to evaluate our framework's capabilities.

**DomainNet** [46] consists of about 600k images with 345 overlapping categories across 6 different image domains: *Real, Sketch, ClipArt, Quickdraw, Painting*, and *Infograph.* Figure 3(A) shows image samples for the "Aircraft Carrier" class across the different image domains. For our experiments, we consider 3 out of the 6 domains (Real, Sketch, ClipArt) with all classes included.

**Office-Home** [62] consists of about 15.5k images with 65 overlapping categories across 4 domains. Figure 3 (B) contains examples for the "Alarm Clock" class from the differ-



Figure 4. Overview of the Video Classification (A) and Object Detection (B and C) datasets used in our benchmarking comparisons. A: UCF101 with its 5 major categories. B: Pool-And-Car sample images overlayed with pool and car detections. C: XView sample images overlayed with detections of "Small car", "Truck" and "Trailer" classes.

ent image domains. For our benchmark comparisons, we will be using the image samples from the Real, Art and ClipArt domains.

**Office-31** [51] consists of totally 4.1k images with 31 overlapping categories across 3 domains. Figure 3 (C) contains examples for the "Backpack" class from 3 domains - Amazon, DSLR, and Webcam.

**PoolCar** [6] is made up of overhead imagery with 2 classes labeled (Pool and Car). The dataset is split into a training set with 2,998 images and a test set with 750 images. Due to the presence of only two classes, the regression task of predicting the bounding boxes is much more challenging than the classification task of identifying the category of an object.

**xView** [34] contains over 1 million individual object instances labeled as one of 60 classes. The sizes of these labeled object vary highly ranging from objects 10 pixels wide to 10,000 pixels wide. Additionally xView provides a granularity of classes as 80% of the classes are specific sub-classes of a given parent class, *e.g.*, "Pickup Truck", "Utility Truck".

**UCF101** [56] contains over 27 hours of video with over 13k clips annotated as one of 101 classes. These 101 classes can be broken down into 5 major categories that are shown in Figure 4. Released in 2012, it is one of the most bench marked activity classification datasets and contains all public data.

## 6. Evaluation

## 6.1. Framework and Experiment Setup

The LEARN framework is structured as specified in Section 3. Before that, to install the framework, there is a README that goes through a series of python conda and pip installations that sets up the dependencies based on a "requirements.txt" file and installs the general dependencies of the framework. In addition to this, each algorithm folder



Figure 5. Qualitative results for the Few-Shot Domain Adapt Image Classification task using the PACMAC [47] algorithm on the (A) DomainNet Sketch (B) Office-Home Art datasets.



Figure 6. Qualitative results (GT, Detections) for the Self-Supervised Pretraining Object Detection task using the Cut-LER [68] algorithm on the (A) Pool and Car (B) xView datasets. has specific dependencies installed as part of the setup process.

With the help of the configurations discussed in Section 3, we have a straightforward way of setting up the different task and algorithm parameters needed for a specific experiment. Furthermore, using the Hydra command, we can override a wide range of experiment parameters during runtime.

## 6.2. Result Analysis

In our experiments we are able to train successive models in as many few-shot domains as we like, scaling up from training on a single instance of each class in a dataset to training on the full dataset in a single experiment. The ability to run a multitude of n-shot settings in a single experiment as opposed to having a user run each experiment individually is both task and algorithm agnostic. This functionality provides a benefit in both efficiency and scalability to the user as it allows them to have a single run that encapsulates the



UCF101

Figure 7. Qualitative results for Video Classification task using the TimeSformer [5] algorithm on the UCF101 dataset.

full breadth of few-shot experiments that they would want to run.

Table 2 provides an overview of the results across the different tasks, algorithms, and datasets for different incremental label budgets ranging from 1-shot to the full size of the training set. Using our framework we show that it is possible to train effectively in the few-shot setting on a number of different datasets across multiple domains and tasks. In total, we train 8 networks on 6 different datasets. In each of our few-shot experiments we show that the model scores at least 79% of the accuracy that is achieved on the full dataset with certain domains showing even more progress in the few-shot setting. For the Video Classification task, for example, the models trained on 10 samples from each class scores 98% of the accuracy that is achieved on the full dataset. This can be attested to the strength of the algorithms and simplicity of the datasets, but it showcases the high level of accuracy that can be achieved even through training on a small number of examples. Figure 7 contains some sample results for the 1-shot and 4-shot settings using the TimeSformer [5] method on the UCF101 [56] dataset. This example shows that our framework can also handle a custom *n*-shot (4-shot) setting apart from the 1,2,5 and 10shot results discussed in Table 2.

Our object detection models perform quite well in the few-shot setting. DETReg [4] and CutLER [68] are able to achieve a mAP of nearly 0.5 on the PoolCar [6] dataset with only 2 labels per class as shown in Table 2. Qualitative results for the CutLER pre-training algorithm on PoolCar and xView [34] in the 1-shot and 5-shot settings can be seen in Figure 6. Our model is able to detect most of the objects on both datasets with very few training labels. The model

Algorithm	Pretraining Backbone		Dataset		Seed budgets (n-shot)			Label budget (total labels $N$ )					
	Model	Weights	Source	Target_Base	Target_Adapt	1-shot	2-shot	5-shot	10-shot	$\sim 0.1N$	$\sim 0.25N$	$\sim 0.5N$	N
Image Classification													
MetaBaseline [11]	ResNet18	ImageNet1k	ImageNet1k	DomainNet-ClipArt	N/A	0.107	0.155	0.274	0.328	0.328	0.356	0.370	0.379
	ResNet18	ImageNet1k	ImageNet1k	OfficeHome-ClipArt	N/A	0.211	0.323	0.452	0.513	0.513	0.526	0.537	0.545
	ResNet18	ImageNet1k	ImageNet1k	Office31-Webcam	N/A	0.654	0.792	0.874	0.887	N/A	N/A	N/A	0.881
MME [52]	EfficientNet-B2	ImageNet1k	DomainNet-Real	DomainNet-ClipArt	DomainNet-Sketch	0.466	0.478	0.518	0.558	0.559	0.599	0.600	0.598
	EfficientNet-B2	ImageNet1k	OfficeHome-Real	OfficeHome-ClipArt	OfficeHome-Art	0.638	0.650	0.670	0.689	0.673	0.677	0.677	0.666
	EfficientNet-B2	ImageNet1k	Office31-Amazon	Office31-Webcam	Office31-DSLR	0.980	0.950	0.960	1.0	N/A	N/A	N/A	0.990
PACMAC [47]	EfficientNet-B2	ImageNet1k	DomainNet-Real	DomainNet-ClipArt	DomainNet-Sketch	0.488	0.510	0.544	0.566	N/A	N/A	N/A	N/A
	EfficientNet-B2	ImageNet1k	OfficeHome-Real	OfficeHome-ClipArt	OfficeHome-Art	0.494	0.547	0.576	0.609	N/A	N/A	N/A	N/A
	EfficientNet-B2	ImageNet1k	Office31-Amazon	Office31-Webcam	Office31-DSLR	1.0	1.0	1.0	1.0	N/A	N/A	N/A	N/A
Object Detection													
DETReg [4]	Convnext FC-2048	Coco 2014	Coco 2014	Pool and Car	N/A	0.22	0.44	0.63	0.66	0.75	0.75	0.84	0.90
CutLER [68]	Convnext FC-2048	Coco 2014	Coco 2014	Pool and Car	N/A	0.23	0.49	0.64	0.71	0.72	0.77	0.83	0.89
Video Classification													
X-Clip [42]			Kinetics400	ucf101	N/A	0.843	0.889	0.950	0.969	0.964	0.976	0.978	0.977
TimeSformer [5]		Kinetics400	Kinetics400	ucf101	N/A	0.795	0.897	0.957	0.981	0.982	0.990	0.990	0.991
CoMix [2]			Kinetics400	ucf101	N/A	0.609	0.806	0.949	0.968	0.966	0.968	0.964	0.969

Table 2. Benchmarking Results on the three tasks - Image Classification, Object Detection and Video Classification.

does particularly well with the "Small Car" and "Building" detections, which is expected as these are the two most common classes in xView. The model has some false positives on what appear to be shipping containers, which may in fact be missing ground truth (i.e. not actually false positives).

We also showcase our use of domain adaptation for the Image Classification problem. In Table 2, we show benchmarks on MetaBaseline [11], MME [52] and PACMAC [47] methods for the Domain-Net [46] Clipart  $\rightarrow$  Sketch, Office-Home [62] ClipArt  $\rightarrow$  Art and the Office-31 [51] Webcam  $\rightarrow$  DSLR domain-adapt scenarios. Figure 5 shows sample images and predictions for the 1-shot and 5-shot image classification tasks using the PACMAC [47] algorithm. Figure 5(A) shows the top-1 predictions comparison between the 1-shot and 5-shot tasks for the same image sample from the DomainNet Sketch dataset. Figure 5(B) shows a similar comparison for the Office-Home Art dataset.

For the DomainNet [46] dataset, PACMAC [47] has the best accuracy with the accuracy score ranging between 48.8% to 56.6% for 1-shot through 10-shot tasks. PACMAC also achieves perfect accuracy on the Office31 [51] dataset. However, for the Office-Home [62] dataset, MME [52] outperforms the other algorithms on the different *n*-shot tasks. Figure 5(A) shows some interesting misclassified results in 1-shot that are corrected in the 5-shot task. Out of those examples, the "Beach" prediction in the 1-shot task is reasonable since the model would have focused on the water and land elements in the image. Another interesting example in Figure 5(B) is the one that is misclassified in both 1 and 5-shot tasks - "Candles" - where both tasks focus on the illumination in the silhouette image.

# 7. Conclusions and Lessons Learned

**Customizability**. The Hydra config protocol provided the basis for customizing the framework across different tasks, datasets and algorithms with the help of fine-grained parameters. For example, for the zero-shot image classification task, we were able to do a straightforward customiza-

tion of the original image classification task to add a flag to identify if the task is a zero-shot task or not. The framework is thus built with a level of modularity that is scalable to adding new computer vision tasks. When we consider datasets, our framework has the capability to include multiple domain adaptation stages with each stage having an on-the-fly specification of the k-shot task, where k is specified as part of the seed budgets for a particular stage. In addition, there is flexibility in terms of the label budgets to extend the framework from a few-shot system to a manyshot classification/detection system.

**Usability**. An important aspect to any system is that it behaves the same way for each user. In the context of a training system, this means that all of the packages and tools that the system utilizes must be the same across all devices it is running on. The LEARN system accomplishes this by including a general requirements file specifying package and tool versions as well as specific package files for each of the algorithms that require additional dependencies. This delineation allows an end user to create either a single reproducible environment to run multiple algorithms or to create algorithm specific environments. Either way this guarantees the consistent training and use of the LEARN system through consistent dependency specifications.

#### 8. Future Work

The proposed LEARN framework has numerous ways of extending capabilities with respect to the domain-adapt few-shot learning problem. One future feature priority would be the capability to setup thousands of randomly initialized episodic N-way tasks where N is the number of classes. In terms of experiment reliability, it is hard to keep track of all the customizable parameters while setting up the Hydra command and can lead to setting up wrong parameter values or sometimes overriding the same parameter twice. To help with this, building a simple GUI for setting parameters would be very a useful extension for the framework.

## 9. Acknowledgement

This material is based on research sponsored by DARPA under agreement number FA8750-19-1-0504. The U.S. Government is authorized to reproduce and distribute reprints for Governmental purposes notwithstanding any copyright notation thereon.

## References

- [1] Peshal Agarwal, Danda Pani Paudel, Jan-Nico Zaech, and Luc Van Gool. Unsupervised robust domain adaptation without source data. In *WACV*, pages 2009–2018, 2022. 2
- [2] Stephan Alaniz, Marco Federici, and Zeynep Akata. Compositional mixture representations for vision and text. In *CVPRW*, pages 4201–4210, 2022. 5, 8
- [3] Sébastien M. R. Arnold, Praateek Mahajan, Debajyoti Datta, Ian Bunner, and Konstantinos Saitas Zarkias. learn2learn: A library for meta-learning research. *CoRR*, abs/2008.12284, 2020. 2, 3
- [4] Amir Bar, Xin Wang, Vadim Kantorov, Colorado J. Reed, Roei Herzig, Gal Chechik, Anna Rohrbach, Trevor Darrell, and Amir Globerson. Detreg: Unsupervised pretraining with region priors for object detection. In *CVPR*, pages 14585– 14595, 2022. 1, 5, 7, 8
- [5] Gedas Bertasius, Heng Wang, and Lorenzo Torresani. Is space-time attention all you need for video understanding? In *ICML*, pages 813–824, 2021. 5, 7, 8
- [6] KARTIK BHARTIYA. Swimming pool and car detection. https://www.kaggle.com/datasets/ kbhartiya83 / swimming - pool - and - car detection. 6,7
- [7] Kaidi Cao, Jingwei Ji, Zhangjie Cao, Chien-Yi Chang, and Juan Carlos Niebles. Few-shot video classification via temporal alignment. In *CVPR*, pages 10618–10627, 2020. 1
- [8] Mathilde Caron, Ishan Misra, Julien Mairal, Priya Goyal, Piotr Bojanowski, and Armand Joulin. Unsupervised learning of visual features by contrasting cluster assignments. In *NeurIPS*, 2020. 6
- [9] Mathilde Caron, Hugo Touvron, Ishan Misra, Hervé Jégou, Julien Mairal, Piotr Bojanowski, and Armand Joulin. Emerging properties in self-supervised vision transformers. In *ICCV*, pages 9650–9660, 2021. 5
- [10] Rakesh Chada and Pradeep Natarajan. Fewshotqa: A simple framework for few-shot learning of question answering tasks using pre-trained text-to-text models. In *EMNLP*, pages 6081–6090, 2021. 2
- [11] Yinbo Chen, Zhuang Liu, Huijuan Xu, Trevor Darrell, and Xiaolong Wang. Meta-baseline: Exploring simple metalearning for few-shot learning. In *ICCV*, pages 9062–9071, 2021. 4, 8
- [12] Marius Cordts, Mohamed Omran, Sebastian Ramos, Timo Rehfeld, Markus Enzweiler, Rodrigo Benenson, Uwe Franke, Stefan Roth, and Bernt Schiele. The cityscapes dataset for semantic urban scene understanding. In *CVPR*, pages 3213–3223, 2016. 2

- [13] Guneet Singh Dhillon, Pratik Chaudhari, Avinash Ravichandran, and Stefano Soatto. A baseline for few-shot image classification. In *ICLR*, 2020. 1
- [14] Cian Eastwood, Ian Mason, Christopher K. I. Williams, and Bernhard Schölkopf. Source-free adaptation to measurement shift via bottom-up feature restoration. In *ICLR*, 2022. 2
- [15] Mark Everingham, Luc Van Gool, Christopher K. I. Williams, John M. Winn, and Andrew Zisserman. The pascal visual object classes (VOC) challenge. *IJCV*, 88(2):303–338, 2010. 2
- [16] Jiahao Fan, Hangyu Zhu, Xinyu Jiang, Long Meng, Chen Chen, Cong Fu, Huan Yu, Chenyun Dai, and Wei Chen. Unsupervised domain adaptation by statistics alignment for deep sleep staging networks. *TNSRE*, 30:205–216, 2022. 2
- [17] Chelsea Finn, Pieter Abbeel, and Sergey Levine. Modelagnostic meta-learning for fast adaptation of deep networks. In *ICML*, pages 1126–1135, 2017. 2
- [18] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *CVPR*, pages 770–778, 2016. 4
- [19] Kaiming He, Xinlei Chen, Saining Xie, Yanghao Li, Piotr Dollár, and Ross Girshick. Masked autoencoders are scalable vision learners. In *CVPR*, pages 16000–16009, 2022. 5
- [20] Shell Xu Hu, Da Li, Jan Stühmer, Minyoung Kim, and Timothy M. Hospedales. Pushing the limits of simple pipelines for few-shot learning: External data and fine-tuning make a difference. In *CVPR*, pages 9058–9067, 2022. 1
- [21] Jiaxing Huang, Dayan Guan, Aoran Xiao, and Shijian Lu. Model adaptation: Historical contrastive learning for unsupervised domain adaptation without source data. *NeurIPS*, 34:3635–3649, 2021. 2
- [22] Jonathan J. Hull. A database for handwritten text recognition research. *TPAMI*, 16(5):550–554, 1994. 1, 2
- [23] Hydra. Hydra a framework for elegantly configuring complex applications. https://github.com/ facebookresearch/hydra. 3
- [24] Naoto Inoue, Ryosuke Furuta, Toshihiko Yamasaki, and Kiyoharu Aizawa. Cross-domain weakly-supervised object detection through progressive domain adaptation. In *CVPR*, pages 5001–5009, 2018. 2
- [25] Masato Ishii and Masashi Sugiyama. Source-free domain adaptation via distributional alignment by matching batch normalization statistics. *CoRR*, abs/2101.10842, 2021. 2
- [26] Matthew Johnson-Roberson, Charles Barto, Rounak Mehta, Sharath Nittur Sridhar, Karl Rosaen, and Ram Vasudevan. Driving in the matrix: Can virtual worlds replace humangenerated annotations for real world tasks? In *ICRA*, pages 746–753, 2017. 2
- [27] Will Kay, João Carreira, Karen Simonyan, Brian Zhang, Chloe Hillier, Sudheendra Vijayanarasimhan, Fabio Viola, Tim Green, Trevor Back, Paul Natsev, Mustafa Suleyman, and Andrew Zisserman. The kinetics human action video dataset. *CoRR*, abs/1705.06950, 2017. 2
- [28] Aditya Khosla, Nityananda Jayadevaprakash, Bangpeng Yao, and Fei-Fei Li. Novel dataset for fine-grained image categorization: Stanford dogs. In CVPRW, 2011. 2

- [29] Jonathan Krause, Michael Stark, Jia Deng, and Li Fei-Fei. 3d object representations for fine-grained categorization. In *ICCVW*, pages 554–561. IEEE Computer Society, 2013. 2
- [30] Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images, 2009. 1
- [31] Hildegard Kuehne, Hueihan Jhuang, Estíbaliz Garrote, Tomaso A. Poggio, and Thomas Serre. HMDB: A large video database for human motion recognition. In *ICCV*, pages 2556–2563, 2011. 2
- [32] Anil Kunchala, Mélanie Bouroche, and Bianca Schoen-Phelan. Towards a framework for privacy-preserving pedestrian analysis. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision (WACV)*, pages 4370–4380, 2023.
- [33] Vinod Kumar Kurmi and Vinay P Namboodiri. Looking back at labels: A class based domain adaptation technique. In *IJCNN*, pages 1–8, 2019. 2
- [34] Darius Lam, Richard Kuzma, Kevin McGee, Samuel Dooley, Michael Laielli, Matthew Klaric, Yaroslav Bulatov, and Brendan McCord. xview: Objects in context in overhead imagery. *CoRR*, abs/1802.07856, 2018. 6, 7
- [35] Yann LeCun, Léon Bottou, Yoshua Bengio, and Patrick Haffner. Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, 86(11):2278–2324, 1998. 1, 2
- [36] Kwonjoon Lee, Subhransu Maji, Avinash Ravichandran, and Stefano Soatto. Meta-learning with differentiable convex optimization. In *CVPR*, pages 10657–10665, 2019. 2
- [37] Wenbin Li, Chuanqi Dong, Pinzhuo Tian, Tiexin Qin, Xuesong Yang, Ziyi Wang, Jing Huo, Yinghuan Shi, Lei Wang, Yang Gao, and Jiebo Luo. Libfewshot: A comprehensive library for few-shot learning. *CoRR*, abs/2109.04898, 2021. 2, 3
- [38] Zhenguo Li, Fengwei Zhou, Fei Chen, and Hang Li. Metasgd: Learning to learn quickly for few shot learning. *CoRR*, abs/1707.09835, 2017. 2
- [39] Yiyi Liao, Jun Xie, and Andreas Geiger. KITTI-360: A novel dataset and benchmarks for urban scene understanding in 2d and 3d. *TPAMI*, 45(3):3292–3310, 2023. 2
- [40] Shaobo Lin, Xingyu Zeng, and Rui Zhao. A unified framework with meta-dropout for few-shot learning. *CoRR*, abs/2210.06409, 2022. 2
- [41] Xiaobin Liu and Shiliang Zhang. Graph consistency based mean-teaching for unsupervised domain adaptive person reidentification. In *IJCAI*, pages 874–880, 2021. 2
- [42] Bolin Ni, Houwen Peng, Minghao Chen, Songyang Zhang, Gaofeng Meng, Jianlong Fu, Shiming Xiang, and Haibin Ling. Expanding language-image pretrained models for general video recognition, 2022. 5, 8
- [43] Poojan Oza, Vishwanath A. Sindagi, Vibashan VS, and Vishal M. Patel. Unsupervised domain adaptation of object detectors: A survey, 2021. 2
- [44] Zhongyi Pei, Zhangjie Cao, Mingsheng Long, and Jianmin Wang. Multi-adversarial domain adaptation. In AAAI, pages 3934–3941, 2018. 1
- [45] Xingchao Peng, Ben Usman, Neela Kaushik, Judy Hoffman, Dequan Wang, and Kate Saenko. Visda: The visual domain adaptation challenge. *CoRR*, abs/1710.06924, 2017. 5

- [46] Xingchao Peng, Qinxun Bai, Xide Xia, Zijun Huang, Kate Saenko, and Bo Wang. Moment matching for multi-source domain adaptation. In *ICCV*, pages 1406–1415, 2019. 1, 2, 5, 6, 8
- [47] Viraj Uday Prabhu, Sriram Yenamandra, Aaditya Singh, and Judy Hoffman. Adapting self-supervised vision transformers by probing attention-conditioned masking consistency. In *NeurIPS*, 2022. 5, 7, 8
- [48] Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, Gretchen Krueger, and Ilya Sutskever. Learning transferable visual models from natural language supervision. In *ICML*, pages 8748–8763, 2021. 5
- [49] Mengye Ren, Eleni Triantafillou, Sachin Ravi, Jake Snell, Kevin Swersky, Joshua B. Tenenbaum, Hugo Larochelle, and Richard S. Zemel. Meta-learning for semi-supervised fewshot classification. In *ICLR*, 2018. 2, 4
- [50] Olga Russakovsky, Jia Deng, Hao Su, Jonathan Krause, Sanjeev Satheesh, Sean Ma, Zhiheng Huang, Andrej Karpathy, Aditya Khosla, Michael Bernstein, et al. Imagenet large scale visual recognition challenge. *IJCV*, 115:211–252, 2015. 5
- [51] Kate Saenko, Brian Kulis, Mario Fritz, and Trevor Darrell. Adapting visual category models to new domains. In ECCV, pages 213–226, 2010. 2, 5, 6, 8
- [52] Kuniaki Saito, Donghyun Kim, Stan Sclaroff, Trevor Darrell, and Kate Saenko. Semi-supervised domain adaptation via minimax entropy. In *ICCV*, pages 8050–8058, 2019. 4, 8
- [53] Christos Sakaridis, Dengxin Dai, and Luc Van Gool. Semantic foggy scene understanding with synthetic data. *IJCV*, 126 (9):973–992, 2018. 2
- [54] Jianbo Shi and Jitendra Malik. Normalized cuts and image segmentation. *TPAMI*, 22(8):888–905, 2000. 6
- [55] Yisheng Song, Ting Wang, Subrota K. Mondal, and Jyoti Prakash Sahoo. A comprehensive survey of few-shot learning: Evolution, applications, challenges, and opportunities. *CoRR*, abs/2205.06743, 2022. 1
- [56] Khurram Soomro, Amir Roshan Zamir, and Mubarak Shah. UCF101: A dataset of 101 human actions classes from videos in the wild. *CoRR*, abs/1212.0402, 2012. 2, 6, 7
- [57] Hui Tang and Kui Jia. Discriminative adversarial domain adaptation. In AAAI, pages 5940–5947, 2020. 2
- [58] Song Tang, Yuji Shi, Zhiyuan Ma, Jian Li, Jianzhi Lyu, Qingdu Li, and Jianwei Zhang. Model adaptation through hypothesis transfer with gradual knowledge distillation. In *IROS*, pages 5679–5685, 2021. 2
- [59] Eleni Triantafillou, Tyler Zhu, Vincent Dumoulin, Pascal Lamblin, Utku Evci, Kelvin Xu, Ross Goroshin, Carles Gelada, Kevin Swersky, Pierre-Antoine Manzagol, and Hugo Larochelle. Meta-dataset: A dataset of datasets for learning to learn from few examples. In *ICLR*, 2020. 1
- [60] Eric Tzeng, Judy Hoffman, Kate Saenko, and Trevor Darrell. Adversarial discriminative domain adaptation. In *CVPR*, pages 7167–7176, 2017. 1
- [61] Jasper R. R. Uijlings, Koen E. A. van de Sande, Theo Gevers, and Arnold W. M. Smeulders. Selective search for object recognition. *IJCV*, 104(2):154–171, 2013. 5

- [62] Hemanth Venkateswara, Jose Eusebio, Shayok Chakraborty, and Sethuraman Panchanathan. Deep hashing network for unsupervised domain adaptation. In *CVPR*, pages 5018– 5027, 2017. 2, 5, 6, 8
- [63] Oriol Vinyals, Charles Blundell, Tim Lillicrap, Koray Kavukcuoglu, and Daan Wierstra. Matching networks for one shot learning. In *NeurIPS*, pages 3630–3638, 2016.
- [64] Oriol Vinyals, Charles Blundell, Timothy Lillicrap, Daan Wierstra, et al. Matching networks for one shot learning. In *NeurIPS*, 2016. 2, 4
- [65] VisDA2019. Visda2019 visual domain adaptation challenge. https://ai.bu.edu/visda-2019/. 2
- [66] Catherine Wah, Steve Branson, Peter Welinder, Pietro Perona, and Serge J. Belongie. The caltech-ucsd birds-200-2011 dataset, 2011. 2
- [67] Rui Wang, Zuxuan Wu, Zejia Weng, Jingjing Chen, Guo-Jun Qi, and Yu-Gang Jiang. Cross-domain contrastive learning for unsupervised domain adaptation. *TMM*, 2022. 2
- [68] Xudong Wang, Rohit Girdhar, Stella X. Yu, and Ishan Misra. Cut and learn for unsupervised object detection and instance segmentation. *CoRR*, abs/2301.11320, 2023. 6, 7, 8
- [69] Yiran Wang, Jing Bai, Zhu Xiao, Huaji Zhou, and Licheng Jiao. Msmcnet: A modular few-shot learning framework for signal modulation classification. *TSP*, 70:3789–3801, 2022.
  2
- [70] Zeya Wang, Baoyu Jing, Yang Ni, Nanqing Dong, Pengtao Xie, and Eric P. Xing. Adversarial domain adaptation being aware of class relationships. In *ECAI*, pages 1579–1586, 2020. 2
- [71] Haifeng Xia, Handong Zhao, and Zhengming Ding. Adaptive adversarial network for source-free domain adaptation. In *ICCV*, pages 9010–9019, 2021. 2
- [72] Lin Xiong, Mao Ye, Dan Zhang, Yan Gan, Xue Li, and Yingying Zhu. Source data-free domain adaptation of object detector through domain-specific perturbation. *Int. J. Intell. Syst.*, 36(8):3746–3766, 2021. 2
- [73] Yuecong Xu, Jianfei Yang, Haozhi Cao, Kezhi Mao, Jianxiong Yin, and Simon See. ARID: A new dataset for recognizing action in the dark. *CoRR*, abs/2006.03876, 2020. 2
- [74] Yuecong Xu, Haozhi Cao, Zhenghua Chen, Xiaoli Li, Lihua Xie, and Jianfei Yang. Video unsupervised domain adaptation with deep learning: A comprehensive survey. *CoRR*, abs/2211.10412, 2022. 2
- [75] Yuecong Xu, Haozhi Cao, Kezhi Mao, Zhenghua Chen, Lihua Xie, and Jianfei Yang. Aligning correlation information for domain adaptation in action recognition. *TNNLS*, pages 1–12, 2022. 2
- [76] Guanglei Yang, Hao Tang, Zhun Zhong, Mingli Ding, Ling Shao, Nicu Sebe, and Elisa Ricci. Transformer-based sourcefree domain adaptation. *CoRR*, abs/2105.14138, 2021. 2
- [77] Lijin Yang, Yifei Huang, Yusuke Sugano, and Yoichi Sato. Interact before align: Leveraging cross-modal knowledge for domain adaptive action recognition. In *CVPR*, pages 14702– 14712, 2022. 2
- [78] Jayeon Yoo, Inseop Chung, and Nojun Kwak. Unsupervised domain adaptation for one-stage object detector using offsets to bounding box. In *ECCV*, pages 691–708, 2022. 2

- [79] Fisher Yu, Haofeng Chen, Xin Wang, Wenqi Xian, Yingying Chen, Fangchen Liu, Vashisht Madhavan, and Trevor Darrell. BDD100K: A diverse driving dataset for heterogeneous multitask learning. In CVPR, pages 2633–2642, 2020. 2
- [80] Hu Yu, Jie Huang, Yajing Liu, Qi Zhu, Man Zhou, and Feng Zhao. Source-free domain adaptation for real-world image dehazing. In *MM*, pages 6645–6654, 2022. 2
- [81] Dan Zhang, Mao Ye, Lin Xiong, Shuaifeng Li, and Xue Li. Source-style transferred mean teacher for source-data free object detection. In *MMAsia*, pages 4:1–4:8, 2021. 2
- [82] Lingzhi Zhang, Weiyu Du, Shenghao Zhou, Jiancong Wang, and Jianbo Shi. Inpaint2learn: A self-supervised framework for affordance learning. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision* (WACV), pages 2665–2674, 2022.
- [83] Junjie Zhu, Xiaodong Yi, Naiyang Guan, and Hang Cheng. Robust re-weighting prototypical networks for few-shot classification. In *ICRAI*, pages 140–146, 2020. 2
- [84] Zhenxi Zhu, Limin Wang, Sheng Guo, and Gangshan Wu. A closer look at few-shot video classification: A new baseline and benchmark. In *BMVC*, page 237, 2021. 1