Two-in-One: Unified Multi-Person Interactive Motion Generation by Latent Diffusion Transformer

Boyuan Li, Xihua Wang, Ruihua Song and Wenbing Huang

Gaoling School of Artificial Intelligence, Renmin University of China, Beijing 100872, China Email: {liboyuan, xihuaw, rsong}@ruc.edu.cn, hwenbing@126.com

Abstract—Multi-person interactive motion generation, a critical yet under-explored domain in computer character animation, poses significant challenges such as intricate modeling of interhuman interactions beyond individual motions and generating two motions with huge differences from one text condition. Current research often employs separate module branches for individual motions, leading to a loss of interaction information and increased computational demands. To address these challenges, we propose a novel, unified approach that models multi-person motions and their interactions within a single latent space. Our approach streamlines the process by treating interactive motions as an integrated data point, utilizing a Variational AutoEncoder (VAE) for compression into a unified latent space, and performing a diffusion process within this space, guided by the natural language conditions. Experimental results demonstrate our method's superiority over existing approaches in generation quality, performing text condition in particular when motions have significant asymmetry, and accelerating the generation efficiency while preserving high quality.

Index Terms—Latent Diffusion Model, Multi-modalities, Human interaction generation

I. INTRODUCTION

Human motion generation is crucial in computer character animation, with wide applications such as video games, animated films, and virtual reality. The emergence of deep generative models [\[29\]](#page-4-0), [\[34\]](#page-4-1), [\[37\]](#page-4-2), [\[38\]](#page-4-3) has revolutionized conventional motion generation techniques. By conditioning on user-friendly input text, these generative methods can produce lifelike and realistic motion sequences, offering the potential to streamline animation workflows and improve efficiency [\[2\]](#page-4-4), [\[12\]](#page-4-5)–[\[14\]](#page-4-6). Despite significant progress, most existing generative methods are limited to generating singleperson motions, with multi-person scenarios remaining less explored, which is our focus.

Compared to the single-person motion generation [\[2\]](#page-4-4), [\[13\]](#page-4-7), [\[19\]](#page-4-8), [\[28\]](#page-4-9), multi-person interactive motion generation is more challenging because it demands both high-quality individual motion generation and accurate inter-motion communication and interaction. For example, as shown in Figure [1,](#page-1-0) given a text condition "One person bows to the other, who accepts the apology.", the model is expected to accurately assign motions to different persons and ensure that the catch neither precedes the toss nor occurs after the ball has landed.

Previous works for multi-person motion generation usually leverage pre-trained single-person motion generation models,

generating independent single-person motions and then integrating them via a motion-communication module [\[3\]](#page-4-10) or motion space control signals [\[4\]](#page-4-11). Recent studies directly model multi-person motions from scratch, but they still rely on individual generative branches supplemented with a crossattention module to model interactions [\[1\]](#page-4-12), or consider the interaction problem as a sequential generation problem [\[36\]](#page-4-13). These approaches separate multi-person motion modeling into individual motion modeling, potentially leading to a loss of interaction information, such as relative spatial relationships. As shown in Figure [1,](#page-1-0) the state-of-the-art model [\[1\]](#page-4-12) generates the right motion of a person bowing, but it fails to generate another person facing the first person and accepting the apology. In addition, taking the description as a common condition of two individual branches may be another cause of such failures when the motions of two persons has significant asymmetry.

In this paper, we propose a unified framework to model the multi-person interactive motions by latent diffusion transformer.First, to maintain full information of individual motions and inter-human interaction, we propose treating two-person motions as a single data point and then employing a Variational AutoEncoder (VAE) [\[34\]](#page-4-1) to compress each data point into one latent space for better representation. Then we propose learning a single diffusion generative network based on this unified latent space while using input text as condition to guide the entire two-person motions. As shown in Figure [1,](#page-1-0) our proposed "two-in-one" motion modeling can correctly generate one person bows to the other, who accepts the apology. In addition, our method is theoretically more efficient compared to previous two-branch design because the unified latent space can compress the motion sequence into less than a tenth of the original length and a unified diffusion model also does not double the sequence length during generation. Experimental results indicate that our proposed approach outperforms all baselines in R-Precision, FID, and Diversity.

Our contributions can be summarized as follows:

- To our best knowledge, we are the first to utilize VAE to encode multi-person interactive motions into a unified latent space with less information loss and better expressiveness.
- We propose employing one latent diffusion transformer to fit the distribution of multi-person interactive motions and better take advantage of multi-person motion descriptions.
- Extensive experimental results indicate that our method consistently surpasses all baselines in terms of generation

Fig. 1: Left: Our proposed framework, which uses an interaction Variational AutoEncoder (InterVAE) to encode two-person motions into a unified latent space and uses a conditional interaction latent diffusio(InterLDM) generate the latents. Right: InterGen is the state-of-the-art work using two-branch framework with cross-attention interactions to generate motions.

quality and diversity, while accelerating the generation speed by more than 4x while maintaining elevated quality.

II. METHOD

Given a text description $c = \{w^{1:N}\}\$ as input, our goal is to generate a sequence with L frames of pairwise interactive motions $x = \{x_1^{1:L}, x_2^{1:L}\}\$ that matches the description. We employ a non-canonical representation [\[1\]](#page-4-12) for individual motions , which allows us to directly access the joint positions of all individuals in the world frame, facilitating the capture of their relative relation. It also provides abundant data, such as joint rotations and foot-ground contact, which aids the model in learning the motion patterns of individuals.

We propose a unified framework to solve the problem, as shown in Figure [1.](#page-1-0) To efficiently generate paired motion sequences while retaining complete interaction information, we first design an Interaction Variational AutoEncoder (InterVAE) in Section [II-A](#page-1-1) to map the entire multi-person interactive motions into a low-dimensional latent space. Then, given the text description, we propose a conditional Interaction Latent Diffusion Model (InterLDM) in Section [II-B](#page-2-0) to capture the relationship between the text condition and the embedding of interactive motions in our InterVAE latent space. In addition, we provide the training and inference details in Section [II-C.](#page-2-1)

A. Interaction Variational Autoencoder

We propose an interaction Variational AutoEncoder called InterVAE, which consists of a transformer encoder $\mathcal E$ and a transformer decoder D, to encode multi-person interactive motions into one latent space. The interaction encoder $\mathcal E$ takes normalized interactive motions x concatenated with a learnable latent token as inputs. The embedded token output by the encoder is used to re-parameterize the low-dimensional latent variable $z \in \mathbb{R}^{n \times d}$ for x embedded in the latent space Z. Then the interaction decoder D takes the latent variable as the head of the zero interactive motion sequences, performing the reconstruction process and generating the interaction sequence \hat{x} . In our experiments, the latent variable size is about 1/10 of the raw data when achieving the best reconstruction results.

In the objective function, we incorporate not only commonly used losses for VAE training, such as Mean Squared Er-

ror(MSE) and Kullback-Leibler(KL) divergence loss, but also several optimization objectives tailored to the geometric features of the human body, including foot contact, bone length, and joint velocity loss, which ensure that the reconstruction process accurately reflects the dynamic structure of the human skeleton.

$$
L_{\text{VAE}} = L_{mse} + L_{kl} + L_{vel} + L_{bone} + L_{fc}.
$$
 (1)

B. Conditional Interaction Latent Diffusion Model

Based on on the unified interaction latent space constructed by the InterVAE, we propose a conditional interaction latent diffusion model called InterLDM to learn the prior distribution of noise and approximate the real data distribution from sampled noise. As multi-person interaction sequence is a kind of sequential data, we use Diffusion Transformer(DiT) [\[31\]](#page-4-15) as the denoiser ϵ_{θ} , which proves to be effective in generating long sequences of images. Specifically, we first get the embedded interaction latent variable z from the frozen InterVAE Encoder $z_0 = \mathcal{E}(x)$, and then we perform the forward diffusion process [\[29\]](#page-4-0) on the latent variable as:

$$
q(\boldsymbol{z}_t|\boldsymbol{z}_{t-1}) = \mathcal{N}(\sqrt{\alpha}_t \boldsymbol{z}_{t-1}, (1-\alpha_t)I),
$$
 (2)

where the constant α is a hyper-parameter for sampling, z_t is the latent variable representation of the sequence x encoded by the encoder and added with noise ϵ_t at the t-th step.

At t-step in the reverse diffusion process, our denoiser predicts the noise distribution $\epsilon_{\theta}(z_t, t, c)$ conditioned by the text description embedding c using the AdaLN-Zero [\[31\]](#page-4-15) mechanism and then removes this noise from the current latent variable to get the previous one, denoted as follows:

$$
L_{\text{LDM}} = \mathbb{E}_{\epsilon, t, c \sim \mathcal{N}(0, 1)}[||\epsilon - \epsilon_{\theta}(\mathbf{z}_t, t, c)||_2^2]. \tag{3}
$$

Once the reverse process is complete, we can get the predicted noise-free variable \hat{z}_0 for subsequent decoding usage.

Our denoiser uses the classifier-free guidance method [\[30\]](#page-4-16) to learn both conditional and unconditional distributions by randomly masking 10% of the description content. This approach allows us to balance diversity and fidelity by adjusting the classifier-free guidance scale s when inference:

$$
\epsilon_{\theta}(\mathbf{z}_t, t, c) = s\epsilon_{\theta}(\mathbf{z}_t, t, c) + (1 - s)\epsilon_{\theta}(\mathbf{z}_t, t, \emptyset). \tag{4}
$$

C. Training and Inference

We first train the InterVAE on the reconstruction task to obtain a reasonable low-dimensional latent space for highdensity interactive motion representation. The interaction encoder and decoder all consist of 9 layers and 4 heads with skip connections. Furthermore, we employ both a frozen *CLIP-ViT-L-14* [\[40\]](#page-4-17) and a frozen *T5-small* [\[42\]](#page-4-18) text encoder for encoding the conditional description to word-level and sentences-level embeddings like [\[41\]](#page-4-19). With these conditional inputs, we train the denoiser ϵ_{θ} of 12 DiT blocks, starting from the compressed latent variable z_0 and sampling a z_t as [\(2\)](#page-2-2) does for denoiser learning to predict the z_{t-1} on random t-step.

During the inference phase, our InterLDM performs a single diffusion process on a latent variable randomly sampled from Gaussian noise. By employing DPMSolver++ [\[33\]](#page-4-20) as the noise scheduler, after 25 denoising steps, we obtain a noise-free latent variable conditioned by the given description, which is then fed into InterVAE's decoder for reconstructing human interactions, generating full interactive human motion data.

III. EXPERIMENT

A. Experiment Setup

Dataset Our model is trained on a public large-scale human motion capture dataset, InterHuman [\[1\]](#page-4-12), which contains 6,022 instances of two-person interactive motions with strong interaction intensity, with a total duration of 6.56 hours. Each interactive motion instance is accompanied by approximately three human-annotated natural language descriptions.

Evaluation To comprehensively evaluate the performance of the latent diffusion model, we adopt the following metrics widely used in previous works [\[1\]](#page-4-12): 1) **Recognition Precision** evaluates the similarity between text-motion data pairs; 2) FID measures the difference between the distribution of raw motion embeddings and the generated motion embeddings; 3) MM Dist measures the distance between the embeddings of generated motion sequences and text embeddings; 4) Diversity assesses the distance between the generated motion sequences; 5) MModality evaluates the distance between motion sequence embeddings generated under the same text conditions.

Fig. 2: Visualization of generated interactive motions from InterGen [\[1\]](#page-4-12) and Ours.

B. Compare with Baselines

We compare our proposed method with baselines including the single-person methods VAE-based TEMOS [\[15\]](#page-4-14) and T2M [\[28\]](#page-4-9), diffusion-based seperated-branch methods ComMDM [\[3\]](#page-4-10), FreeMotion [\[36\]](#page-4-13), and InterGen [\[1\]](#page-4-12) and present results in Table [I.](#page-2-3) As the results shows, our InterLDM model performs the best in terms of R Precision, FID, MM Dist, and Diversity. This indicates that our model has the capability to generate high-quality and highly-relevant multi-person interactions. The improvements in R Precision and MM Distance are the most significant, indicating our method can significantly improve the ability to follow text conditions or instructions. In addition, we observe that our method's Diversity is closest to groundtruth while its MModality, measuring the diversity under the same text condition, is lower than InterGen and other three baselines. This indicates that for different text instructions, our method can generate the most diverse motions, while given a text condition, our method generate more less diverse motions. However, if the generated motions are not relevant to the text condition, the higher MModality means the worse instructionfollowing ability.

We conduct a case study and show some cases in Figure [2.](#page-3-0) First, we observe that our InterLDM method can generate more accurate motions, which are more like the ground-truth, under the conditional textual descriptions. Second, the two persons in InterGen generated results tend to do the similar actions, e.g., both rises in the first case and both in the third case, which confirms that it is difficult for two separate individual branches with interaction via cross-attention mechanism to generate two persons' motions with huge difference under the same text condition. In contrast, our InterLDM model effectively preserves the asymmetrical interactive information between the two individuals and generates results correctly following the text instruction.

We also compare some methods from three perspectives: the number of parameters (by dot size), FID and average inference time per sentence. The results shown in Figure [3](#page-3-1) indicate that although some small models like TEMOS and T2M are faster,

Fig. 3: Comparison of inference time, FID and quantity of parameter. All tests are performed on the same Tesla A100.

TABLE II: Reconstruction and generation performance with different token length f.

$z \in \mathbb{R}^{f \times 256}$	FID_{Recon}	FID_{Gen}	Average Inference Time(s)
$f = 18$	1.970	7.323	0.424
$f = 24$	1.330	5.619	0.487
$f = 30$	1.892	6.221	0.557
$f = 36$	1.919	8.273	0.584

their generation quality is much worse than InterGen and InterLDM. With similar size, our InterLDM model is about 4x faster than InterGen while achieving better quality.

C. Ablation Study

The unified latent space plays an important role in our framework and thus we explore the reconstruction effects of $z \in \mathcal{R}^{f \times 256}$ on both the InterVAE and the diffusion denoiser. Here, a smaller f implies a higher compression rate and a more compact latent space. Table [II](#page-3-2) shows the model's reconstruction and generation performance for different values of f. We find that higher compression rates lead to faster inference but can degrade reconstruction quality, highlighting a trade-off between inference speed and reconstruction quality. Furthermore, lower compression rates can negatively impact the model's generation performance, indicating that the sparsity of interaction information in the raw data space adversely affects generation results. Therefore when $f = 24$, InterLDM achieves high-quality synthesis results with impressive speed.

IV. CONCLUSION

To generate multi-person interaction motions, we propose an interaction Variational AutoEncoder to effectively preserves the full information to two-person interaction motions, and a conditional latent diffusion model to efficiently generate two-person motions together and ensure consistency with textual description. Extensive experiments demonstrate that our model not only performs the best in generation quality and instruction-following ability, but also achieves a 4x faster inference speed than strong baselines. In the future, we plan to explore more unified framework that can model interactive motion generation for any number of persons.

REFERENCES

- [1] H. Liang, W. Zhang, W. Li, J. Yu, and L. Xu, "Intergen: Diffusionbased multi-human motion generation under complex interactions," *International Journal of Computer Vision*, vol. 132, no. 9, p. 3463–3483, Mar. 2024. [Online]. Available: [http://dx.doi.org/10.1007/](http://dx.doi.org/10.1007/s11263-024-02042-6) [s11263-024-02042-6](http://dx.doi.org/10.1007/s11263-024-02042-6)
- [2] G. Tevet, S. Raab, B. Gordon, Y. Shafir, D. Cohen-Or, and A. H. Bermano, "Human motion diffusion model," 2022. [Online]. Available: <https://arxiv.org/abs/2209.14916>
- [3] Y. Shafir, G. Tevet, R. Kapon, and A. H. Bermano, "Human motion diffusion as a generative prior," 2023. [Online]. Available: <https://arxiv.org/abs/2303.01418>
- [4] Z. Wang, J. Wang, D. Lin, and B. Dai, "Intercontrol: Generate human motion interactions by controlling every joint," *arXiv preprint arXiv:2311.15864*, 2023.
- [5] R. Rombach, A. Blattmann, D. Lorenz, P. Esser, and B. Ommer, "Highresolution image synthesis with latent diffusion models," in *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, 2022, pp. 10 684–10 695.
- [6] P. Dhariwal and A. Nichol, "Diffusion models beat gans on image synthesis," *Advances in neural information processing systems*, vol. 34, pp. 8780–8794, 2021.
- [7] M. Zhang, Z. Cai, L. Pan, F. Hong, X. Guo, L. Yang, and Z. Liu, "Motiondiffuse: Text-driven human motion generation with diffusion model," *arXiv preprint arXiv:2208.15001*, 2022.
- [8] Y. Yuan, J. Song, U. Iqbal, A. Vahdat, and J. Kautz, "Physdiff: Physicsguided human motion diffusion model," in *Proceedings of the IEEE/CVF international conference on computer vision*, 2023, pp. 16 010–16 021.
- [9] W. Zhou, Z. Dou, Z. Cao, Z. Liao, J. Wang, W. Wang, Y. Liu, T. Komura, W. Wang, and L. Liu, "Emdm: Efficient motion diffusion model for fast, high-quality motion generation," *arXiv preprint arXiv:2312.02256*, vol. 2, 2023.
- [10] S. Alexanderson, R. Nagy, J. Beskow, and G. E. Henter, "Listen, denoise, action! audio-driven motion synthesis with diffusion models," *ACM Transactions on Graphics (TOG)*, vol. 42, no. 4, pp. 1–20, 2023.
- [11] X. Chen, B. Jiang, W. Liu, Z. Huang, B. Fu, T. Chen, and G. Yu, "Executing your commands via motion diffusion in latent space," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2023, pp. 18 000–18 010.
- [12] C. Guo, X. Zuo, S. Wang, S. Zou, Q. Sun, A. Deng, M. Gong, and L. Cheng, "Action2motion: Conditioned generation of 3d human motions," in *Proceedings of the 28th ACM International Conference on Multimedia*, 2020, pp. 2021–2029.
- [13] M. Petrovich, M. J. Black, and G. Varol, "Action-conditioned 3d human motion synthesis with transformer vae," in *Proceedings of the IEEE/CVF International Conference on Computer Vision*, 2021, pp. 10 985–10 995.
- [14] H. Ahn, T. Ha, Y. Choi, H. Yoo, and S. Oh, "Text2action: Generative adversarial synthesis from language to action," in *2018 IEEE International Conference on Robotics and Automation (ICRA)*. IEEE, 2018, pp. 5915–5920.
- [15] M. Petrovich, M. J. Black, and G. Varol, "Temos: Generating diverse human motions from textual descriptions," in *European Conference on Computer Vision*. Springer, 2022, pp. 480–497.
- [16] C. Guo, X. Zuo, S. Wang, and L. Cheng, "Tm2t: Stochastic and tokenized modeling for the reciprocal generation of 3d human motions and texts," in *European Conference on Computer Vision*. Springer, 2022, pp. 580–597.
- [17] J. Zhang, Y. Zhang, X. Cun, Y. Zhang, H. Zhao, H. Lu, X. Shen, and Y. Shan, "Generating human motion from textual descriptions with discrete representations," in *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, 2023, pp. 14 730–14 740.
- [18] R. Li, S. Yang, D. A. Ross, and A. Kanazawa, "Ai choreographer: Music conditioned 3d dance generation with aist++," in *Proceedings of the IEEE/CVF International Conference on Computer Vision*, 2021, pp. 13 401–13 412.
- [19] C. Guo, S. Zou, X. Zuo, S. Wang, W. Ji, X. Li, and L. Cheng, "Generating diverse and natural 3d human motions from text," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2022, pp. 5152–5161.
- [20] L. Siyao, W. Yu, T. Gu, C. Lin, O. Wang, C. Qian, C. C. Loy, and Z. Liu, "Bailando: 3d dance generation by actor-critic gpt with choreographic memory," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2022, pp. 11 050–11 059.
- [21] J. Li, D. Kang, W. Pei, X. Zhe, Y. Zhang, Z. He, and L. Bao, "Audio2gestures: Generating diverse gestures from speech audio with conditional variational autoencoders," in *Proceedings of the IEEE/CVF International Conference on Computer Vision*, 2021, pp. 11 293–11 302.
- [22] H. Liu, Z. Zhu, N. Iwamoto, Y. Peng, Z. Li, Y. Zhou, E. Bozkurt, and B. Zheng, "Beat: A large-scale semantic and emotional multi-modal dataset for conversational gestures synthesis," in *European conference on computer vision*. Springer, 2022, pp. 612–630.
- [23] Q. Lu, Y. Zhang, M. Lu, and V. Roychowdhury, "Action-conditioned on-demand motion generation," in *Proceedings of the 30th ACM International Conference on Multimedia*, 2022, pp. 2249–2257.
- [24] T. Lucas, F. Baradel, P. Weinzaepfel, and G. Rogez, "Posegpt: Quantization-based 3d human motion generation and forecasting," in *European Conference on Computer Vision*. Springer, 2022, pp. 417– 435.
- [25] G. Tevet, B. Gordon, A. Hertz, A. H. Bermano, and D. Cohen-Or, "Motionclip: Exposing human motion generation to clip space," in *European Conference on Computer Vision*. Springer, 2022, pp. 358– 374.
- [26] S. Lu, L.-H. Chen, A. Zeng, J. Lin, R. Zhang, L. Zhang, and H.-Y. Shum, "Humantomato: Text-aligned whole-body motion generation," 2023. [Online]. Available:<https://arxiv.org/abs/2310.12978>
- [27] Y. Xie, V. Jampani, L. Zhong, D. Sun, and H. Jiang, "Omnicontrol: Control any joint at any time for human motion generation," 2024. [Online]. Available:<https://arxiv.org/abs/2310.08580>
- [28] K. Lin, C. Agia, T. Migimatsu, M. Pavone, and J. Bohg, "Text2motion: from natural language instructions to feasible plans," *Autonomous Robots*, vol. 47, no. 8, p. 1345–1365, Nov. 2023. [Online]. Available: <http://dx.doi.org/10.1007/s10514-023-10131-7>
- [29] J. Ho, A. Jain, and P. Abbeel, "Denoising diffusion probabilistic models," 2020. [Online]. Available:<https://arxiv.org/abs/2006.11239>
- [30] J. Ho and T. Salimans, "Classifier-free diffusion guidance," *arXiv preprint arXiv:2207.12598*, 2022.
- [31] W. Peebles and S. Xie, "Scalable diffusion models with transformers," 2023. [Online]. Available:<https://arxiv.org/abs/2212.09748>
- [32] T. Hempel, A. A. Abdelrahman, and A. Al-Hamadi, "6d rotation representation for unconstrained head pose estimation," in *2022 IEEE International Conference on Image Processing (ICIP)*. IEEE, Oct. 2022. [Online]. Available:<http://dx.doi.org/10.1109/ICIP46576.2022.9897219>
- [33] C. Lu, Y. Zhou, F. Bao, J. Chen, C. Li, and J. Zhu, "Dpm-solver++: Fast solver for guided sampling of diffusion probabilistic models," *arXiv preprint arXiv:2211.01095*, 2022.
- [34] D. P. Kingma, "Auto-encoding variational bayes," *arXiv preprint arXiv:1312.6114*, 2013.
- [35] J. Song, C. Meng, and S. Ermon, "Denoising diffusion implicit models," 2022. [Online]. Available:<https://arxiv.org/abs/2010.02502>
- [36] K. Fan, J. Tang, W. Cao, R. Yi, M. Li, J. Gong, J. Zhang, Y. Wang, C. Wang, and L. Ma, "Freemotion: A unified framework for number-free text-to-motion synthesis," 2024. [Online]. Available: <https://arxiv.org/abs/2405.15763>
- [37] I. J. Goodfellow, J. Pouget-Abadie, M. Mirza, B. Xu, D. Warde-Farley, S. Ozair, A. Courville, and Y. Bengio, "Generative adversarial networks," 2014. [Online]. Available:<https://arxiv.org/abs/1406.2661>
- [38] D. J. Rezende and S. Mohamed, "Variational inference with normalizing flows," 2016. [Online]. Available:<https://arxiv.org/abs/1505.05770>
- [39] O. Ronneberger, P. Fischer, and T. Brox, "U-net: Convolutional networks for biomedical image segmentation," 2015. [Online]. Available:<https://arxiv.org/abs/1505.04597>
- [40] A. Radford, J. W. Kim, C. Hallacy, A. Ramesh, G. Goh, S. Agarwal, G. Sastry, A. Askell, P. Mishkin, J. Clark, G. Krueger, and I. Sutskever, "Learning transferable visual models from natural language supervision," 2021. [Online]. Available:<https://arxiv.org/abs/2103.00020>
- [41] P. Esser, S. Kulal, A. Blattmann, R. Entezari, J. Müller, H. Saini, Y. Levi, D. Lorenz, A. Sauer, F. Boesel, D. Podell, T. Dockhorn, Z. English, K. Lacey, A. Goodwin, Y. Marek, and R. Rombach, "Scaling rectified flow transformers for high-resolution image synthesis," 2024. [Online]. Available:<https://arxiv.org/abs/2403.03206>
- [42] C. Raffel, N. Shazeer, A. Roberts, K. Lee, S. Narang, M. Matena, Y. Zhou, W. Li, and P. J. Liu, "Exploring the limits of transfer learning with a unified text-to-text transformer," 2023. [Online]. Available: <https://arxiv.org/abs/1910.10683>