Efficient Algorithm Design of Dynamic Spectrum Access by Whittle Index

Keqin Liu*, Yiying Zhang, and Zhi Ding

Abstract—This study addresses the dynamic spectrum access problem in a wireless sub-network that shares channels with a parent network. We approach the sequential channel allocation problem using a restless multi-armed bandits (RMAB) framework. Our objective is to maximize the expected discounted return over an infinite horizon while minimizing interference to the parent network caused by shared channels with the subnetwork. Due to the unavailability of direct observations of the true channel state, we leverage the channel quality indicator (CQI) feedback provided by users. However, the RMAB problem is widely acknowledged as PSPACE-hard even for finite-state models. To overcome this challenge, we propose a closed-form channel index function using an iterative online approximation method to approximate the well-known Whittle index policy, which offers a low-complexity solution for ranking the available channels that has an infinite state space. Through extensive numerical simulation experiments, we demonstrate the superior performance and robustness of our proposed algorithm.

Index Terms—Dynamic spectrum access, limited observations, restless multi-armed bandit, Whittle index.

I. INTRODUCTION

A. Dynamic Spectrum Access

YNAMIC spectrum access (DSA) refers to the process of efficiently allocating radio resources within a subnetwork to ensure optimal performance and quality of service (QoS) for its users. For example, in 4G-HeNB network, a small, low-power cellular base station (like a femtocell) provides localized coverage within a limited area, typically in urban high-density areas, by sharing a set of wireless channels with the main/parent network. Effective sequential resource scheduling involves the coordination and allocation of available channels (temporarily not used by the main network) to multiple user devices connected to the small base station [1]. The main challenge here is that the sub-network cannot perfectly observe the availabilities of chosen channels and the channel availabilities are themselves time-varying. In order to achieve high efficiency in radio resource sharing for future 5G deployment of DSA, the primary objective is to maximize sub-network throughput, minimize interference with the parent network, and enhance overall network performance over long-run [2].

To achieve efficient channel allocation for DSA, various algorithms and techniques are employed in different network structures [3]–[12]. These include channel allocation and interference management. Channel allocation requires that the wireless scheduler assigns appropriate channels to user devices based on factors such as channel quality, interference levels, and user priority. The allocation is dynamic, depending on the network requirements and traffic conditions. Meanwhile, the scheduler also needs to mitigate interference to other networks sharing the same set of channels. Interference coordination techniques are employed to optimize spectral efficiency and minimize cross-network interference.

Overall, DSA plays a crucial role in optimizing resource utilization, managing interference, and providing a satisfactory user experience within the localized coverage area of the subnetwork. It enables efficient and reliable communication for a diverse range of user devices while maintaining network performance objectives. In this paper, we mainly focus on the optimization of channel allocation for maximizing the expected data throughput of the sub-network over long-run.

B. Restless Multi-armed Bandit Problem

In this paper, we will formulate our channel allocation problem as a restless multi-armed bandit process (RMAB). RMAB is a generalization of the classical multi-armed bandit problem (MAB). MAB is a well-known mathematical model that serves as a foundational framework for dynamic resource allocation problems and has been widely used in multiple fields [13]-[15]. In the classical formulation, a player is challenged by the task of selecting a single arm out of N options, subsequently receiving a random reward dependent on the state of the arm. The chosen arm undergoes a state transition according to a Markovian rule while other arms do not change their states. At all time, the states of all arms are perfectly observable. The player's goal is to maximize their cumulative discounted reward over an infinite time interval according to a specific arm selection policy. The inception of the general MAB concept can be traced back to its original exposition in 1933 [16], and despite subsequent research endeavors, it remains partially unresolved. Gittins made noteworthy advancements by addressing the curse of dimensionality of the classical MAB problem, effectively reducing the complexity from an Ndimensional problem to N individual 1-dimensional problems [17], [18].

Whittle further extended the classical MAB formulation and introduced the more comprehensive variant, the restless multi-armed bandit (RMAB) problem [19]. In RMAB, the

The first author is with Department of Financial and Actuarial Mathematics, Xi'an Jiaotong-Liverpool University, Suzhou, China. The first and second authors are with National Center for Applied Mathematics, Nanjing, China. The third author is with Department of Electrical and Computer Engineering, University of California at Davis, USA.

Part of this work was presented at 2023 International Conference on Statistics, Applied Mathematics and Computing Science.

^{*}Corresponding author, kqliu@nju.edu.cn

player is granted to select K arms from the available Narms (where 1 < K < N), and passive (unselected) arms can also alter their states, either of which generalizations made Gittins's approach (called Gittins index) suboptimal. Employing Lagrangian relaxation techniques, Whittle devised an indexing policy that generalizes Gittins index for a much broader spectrum of problems. This policy assigns an index (called Whittle index) to each arm dependent on the state of the arm. At each time, the player selects arms currently with the top K largest indices. Whittle's generalization has exhibited remarkable performance in both theoretical and numerical investigations [20]-[23]. Nonetheless, establishing the essential condition for the existence of the Whittle index, known as indexability, and computing the Whittle index when it does exist pose significant challenges. Researchers have demonstrated that the RMAB problem with a finite state space is classified as PSPACE-HARD problem [24]. In this paper, we formulate the channel allocation problem as an RMAB with an infinite state space and construct an efficient algorithm to compute the Whittle index with arbitrary precision that achieves a near-optimal performance.

C. Related Work

Numerous prior studies have investigated the channel allocation problem in similar network models [3]-[12], [25], [26]. Previous research has shown that the problem can be viewed as an MAB [27]-[29]. Nevertheless, relatively fewer works have applied this framework to heterogeneous networks (HetNets) [27], [28]. In HetNets, one of the common assumptions made before regarding the ability to directly observe the channel states no longer hold true without transparent and continuous coordination between the heterogeneous networks, e.g., macro base station (MBS) and femto base stations (FBSs). Achieving such coordination would require additional processing and consume more bandwidth. Our approach differs from previous studies by not assuming that the sub-network has access to instantaneous channel state information. Instead, our proposed method leverages practical channel quality indicator (CQI) reports as a partial and error-prone observation of the channel state.

Moreover, given that the RMAB problem is classified as a PSPACE-HARD problem and direct computation of the Whittle index is time-consuming or infeasible for infinite-state models, some researchers have also considered computing Whittle index approximately to attain a better performance over the myopic policy. In [30], a very coarse approximation to the Whittle index was numerically studied without a theoretical proof on indexability. In this paper, however, we employ an alternative approximation method to compute the Whittle index with arbitrarily high precision and observe significantly improved performance compared to the previous approach by numerical examples. Sufficient conditions for indexability are also established theoretically.

D. Organization

The rest of the paper is organized as follows. In Section II, we present the system model and the RMAB formulation of



Fig. 1. The system model

the channel allocation problem. In Section III, we introduce the basic concepts of indexability and Whittle index, prove some important properties of value functions that will be useful in the following analysis, and derive sufficient conditions for indexability and the threshold structure of the optimal policy for the decoupled single-arm problem. In Section IV, under the conditions derived in Section III, we propose an iterative method to approximate value functions, provide the approximated Whittle index in a closed form, and finish the construction of the approximated Whittle index policy (AWI). In Section V, results of numerical experiments are provided to demonstrate the effectiveness of our generalized AWI compared with another approximated Whittle index policy proposed in [30]. Finally, Section VI concludes this paper.

II. SYSTEM MODEL AND PROBLEM FORMULATION

A. System Model

The system model comprises a parent network and a subnetwork that shares a certain number of channels with the former. The goal of channel allocation is to optimize the selection of channels of the sub-network so that we can maximize total throughput while minimizing interference to the parent network.

In Fig.1, the larger-sized MBS is a base station of the parent network while a smaller FBS of the sub-network is choosing among a set of channels allowed to be shared with the MBS. Due to resource limits and interference constraints, at each time, the FBS can only choose a portion of the shared channels to assign to the sub-network users for transmitting data. However, the data transmission can be successful only if the assigned channel is in the good state (currently not used by the MBS of the parent network). For each shared channel, we adopt the widely recognized 2-state Markov model, also known as Gilbert-Elliott model as shown in Fig.1. Let $S \in \{0 \text{ (poor)}, 1 \text{ (good)}\}$ represent the current state of a channel. The probabilities p_0 and p_1 indicate the likelihood of a channel being in the poor or good state, respectively. The transition probabilities between the two states 0 and 1are denoted by p_{00} , p_{01} , p_{10} and p_{11} . By employing cognitive capabilities, the FBS of the sub-network can acquire the CQI from a channel it just chose, denoted by $q(t) \in \mathbb{Z}$ at time t. In our study, let K denote the number of CQI levels under

n	index of a specific channel	
N	number of shared channels in consideration	
M	number of channels chosen at each time	
S	state of a channel	
В	throughput of a channel	
p_0, p_1	likelihood of a channel being in the poor or good state	
p_{ij}	transition probability between channel states	
q	observed CQI level of a channel	
K	number of CQI levels	
$p_{i,s}$	probability of observing $q = i$ given $S = s$	
a	action taken for a channel	
ω	belief state of a channel	

TABLE I NOTATIONS

investigation. Consequently, q(t) satisfies the condition that $1 \leq q(t) \leq K$. Note that CQI levels are not channel states but contain information about the current state of a channel. Specifically, there is a known probability of observing a specific CQI level given a channel state as shown in Table I. Our main notations are summarized in Table I.

B. Restless Multi-armed Bandit Formulation

Assume that the sub-network has N shared channels that are available to use. At each time instance, it is required to select M channels $(1 \le M \le N)$ for data transmission. For a given channel n, if it is chosen (active) at time t, we denote the action $a_n(t) = 1$; otherwise $a_n(t) = 0$. This is subject to the constraint that the number of active channels at each time equals M ($\sum_{n=1}^{N} a_n(t) = M$).

Considering the unavailability of real-time channel state information in HetNets, we incorporate the general theory of partially observable Markov decision processes (POMDPs) [31] into our model. Specifically, we employ the belief state vector as the system state for decision-making purposes. The belief state vector, denoted by $\omega(t)$, comprises the instantaneous belief states of the N channels. Specifically, the belief state of channel n at time t is defined as

$$\omega_n(t) = \Pr(S_n(t) = 1 \mid \text{past observations on channel } n).$$
(1)

Following the Bayes' rule, it can be proven that the evolution of belief state itself is a Markov process with an infinite state space. The transition probability of $\omega_n(t)$ can be described as

$$\omega_n(t+1) = \begin{cases} \omega_{n,i}(t), & a_n(t) = 1, \ q_n(t) = i \\ \mathcal{T}_n(\omega_n(t)), & a_n(t) = 0. \end{cases}$$
(2)

where $T_n(\omega)$ is the belief update when passive action is taken on belief state ω , hence no observation of CQI such that

$$\mathcal{T}_n(\omega) = p_{11}^{(n)}\omega + p_{01}^{(n)}(1-\omega).$$
(3)

We can also compute the belief update for successively k passive steps from the initial belief state ω as

$$\mathcal{T}_{n}^{k}(\omega) = \frac{p_{01}^{(n)} - \left(p_{11}^{(n)} - p_{01}^{(n)}\right)^{k} \left(p_{01}^{(n)} - \left(1 + p_{01}^{(n)} - p_{11}^{(n)}\right)\omega\right)}{1 + p_{01}^{(n)} - p_{11}^{(n)}}$$
(4)

Moreover, if we let k tend to infinity, we can get the steady state belief value

$$\omega_{n,s} = \lim_{k \to \infty} \mathcal{T}_n^k(\omega) = \frac{p_{01}^{(n)}}{1 + p_{01}^{(n)} - p_{11}^{(n)}}.$$
 (5)

Alternatively, when the channel is active, the belief update is

$$\omega_{n,i}(t) = \mathcal{T}(\Pr(S_n(t) = 1 \mid q_n(t) = i, \ \omega_n(t)))
= \mathcal{T}\left(\frac{p_{i,1}^{(n)}\omega_n(t)}{p_{i,1}^{(n)}\omega_n(t) + p_{i,0}^{(n)}(1 - \omega_n(t))}\right)
= \frac{p_{11}^{(n)}p_{i,1}^{(n)}\omega_n(t) + p_{01}^{(n)}p_{i,0}^{(n)}(1 - \omega_n(t))}{p_{i,1}^{(n)}\omega_n(t) + p_{i,0}^{(n)}(1 - \omega_n(t))},$$
(6)

where $p_{i,1}^{(n)}, p_{i,0}^{(n)}$ are the probabilities of observing $q_n(t) = i$ when the channel *n* is in the good (S = 1) or poor (S = 0) state, respectively. And it is obvious that $\sum_{i=1}^{K} p_{i,1}^{(n)} = 1$ and $\sum_{i=1}^{K} p_{i,0}^{(n)} = 1$. Moreover, the probability of observing a certain CQI given $\omega_n(t)$ is given by

$$p_i^{(n)}(\omega_n(t)) = \Pr(q_n(t) = i|\omega_n(t)) = p_{i,1}^{(n)}\omega_n(t) + p_{i,0}^{(n)}(1 - \omega_n(t)).$$
(7)

Given the initial belief state vector $\boldsymbol{\omega}(1)$, we can formulate the channel allocation problem as a constrained optimization problem

$$\max_{\pi} \mathbb{E}_{\pi} \left[\sum_{t=1}^{\infty} \beta^{t-1} R_{\pi}(t) \mid \boldsymbol{\omega}(1) \right], \tag{8}$$

subject to
$$\sum_{n=1}^{N} a_n(t) = M,$$
 (9)

where $\beta \in [0, 1]$ is the discount factor to balance the importance of the instantaneous and future rewards. And the reward function is defined as

$$R_{\pi}(t) = \sum_{n=1}^{N} \mathbb{1}_{\{a_n(t)=1\}} S_n(t) B_n, \qquad (10)$$

where B_n is the throughput of channel n.

Introducing the Lagrangian multiplier m and applying the Lagrangian relaxation as Whittle did in [19], we can simplify the N-channel optimization problem to a single-channel scenario:

$$\max_{\pi:\omega_n(t)\to\{0,1\}} \mathbb{E}_{\pi} \left[\sum_{t=1}^{\infty} \beta^{t-1} \tilde{R}_{\pi}^{(n)}(t) \mid \omega_n(1) = \omega \right], \quad (11)$$

where

$$\tilde{R}_{\pi}^{(n)}(t) = \mathbb{1}_{\{a_n(t)=1\}} S_n(t) B_n + m \cdot \mathbb{1}_{\{a_n(t)=0\}}.$$
 (12)

The optimal value of the unconstrained optimization problem (11) is denoted by $V_{\beta,m}^{(n)}(\omega)$, and it is equivalent to

$$V_{\beta,m}^{(n)}(\omega) = \max\{V_{\beta,m}^{(n)}(\omega; a=0), \ V_{\beta,m}^{(n)}(\omega; a=1)\}, \quad (13)$$

where $V_{\beta,m}^{(n)}(\omega; a = 1)$ and $V_{\beta,m}^{(n)}(\omega; a = 0)$ represent the optimal value of (11) when channel *n* is chosen or not chosen at the initial belief state ω , respectively. To simplify the presentation and without loss of generality, we will omit the superscript (n) and subscript *n* and set B = 1, considering a single-armed bandit problem in the following. And we can prove that the value function for passive and active actions satisfy the dynamic equations below

$$V_{\beta,m}(\omega; a = 0) = m + \beta V_{\beta,m}(\mathcal{T}(\omega)), \qquad (14)$$
$$V_{\beta,m}(\omega; a = 1) = \omega + \beta \sum_{i=1}^{K} [p_{i,1}\omega + p_{i,0}(1-\omega)] V_{\beta,m}(\omega_i). \qquad (15)$$

III. INDEXABILITY AND THRESHOLD POLICY

Define passive set P(m) as the collection of all belief states where the optimal action is to be passive (a = 0)

$$P(m) = \{ \omega : V_{\beta,m}(\omega; a = 1) \le V_{\beta,m}(\omega; a = 0) \}.$$
 (16)

The indexability of a restless multi-armed bandit is defined as A restless multi-armed bandit is considered indexable if for each single-armed bandit problem with Lagrangian multiplier m, the passive set P(m) monotonically expands from the empty set to the entire state space as m increases from $-\infty$ to $+\infty$ [22]. According to [28], under indexability, the Whittle index $W(\omega)$ for a particular belief state ω is defined as follows:

$$W(\omega) = \inf\{m : V_{\beta,m}(\omega; a = 1) = V_{\beta,m}(\omega; a = 0)\}.$$
(17)

A. Properties of Value Functions

To prove the indexability of the RMAB problem and derive the threshold structure of the optimal policy for relaxed single-armed bandit problem (11), we need to investigate the properties of value functions $V_{\beta,m}(\omega; a = 1)$, $V_{\beta,m}(\omega; a = 0)$ and $V_{\beta,m}(\omega)$. We divide this process into two steps, following the approach in [32]. First, we examine the properties of value functions in finite horizons. Then, utilizing the uniform convergence theorem, we extend these conclusions to the case of an infinite horizon.

We introduce the *T*-horizon value function $V_{1,T,\beta,m}(\omega)$ as follows:

$$V_{1,T,\beta,m}(\omega) = \max_{\pi} \mathbb{E}_{\pi} \left[\sum_{t=1}^{T} \beta^{t-1} \tilde{R}_{\pi}(t) \mid \omega(1) = \omega \right], \quad (18)$$

where $\pi : \omega(t) \to \{0, 1\}$ is a policy determining whether or not to activate the arm based on its current belief state. Then it is obvious that

$$V_{1,T,\beta,m}(\omega) = \max\{V_{1,T,\beta,m}(\omega; a=0), V_{1,T,\beta,m}(\omega; a=1)\}.$$
 (19)

And finite-horizon action value functions also satisfy the similar dynamic equations as (14) and (15):

$$V_{1,T,\beta,m}(\omega; a=0) = m + \beta V_{1,T-1,\beta,m}(\mathcal{T}(\omega)),$$

$$V_{1,T,\beta,m}(\omega; a=1)$$
(20)

$$= \omega + \beta \sum_{i=1}^{K} [p_{i,1}\omega + p_{i,0}(1-\omega)] V_{1,T-1\beta,m}(\omega_i), \quad (21)$$

where $V_{1,0,\beta,m}(\omega) \equiv 0$. Utilizing the above recursive formulas and mathematical induction, we analyze the properties of $V_{1,T,\beta,m}(\omega)$.

Lemma 1: $V_{1,T,\beta,m}(\omega)$ is piecewise linear and convex in both ω and m for any $T \ge 1$.

Proof: Consider first T = 1. It is clear that

$$V_{1,1,\beta,m}(\omega) = \max\{m,\omega\} = \begin{cases} m, & \omega < m \\ \omega, & \omega \ge m \end{cases}$$

is the maximum of two linear equations and thus piecewise linear and convex in both ω and m. Based on the recursive formulas and the induction hypothesis that $V_{1,T-1,\beta,m}(\omega)$ is piecewise linear in both ω and m, we can prove that $V_{1,T,\beta,m}(\omega; a = 0)$ and $V_{1,T,\beta,m}(\omega; a = 1)$ are still piecewise linear in both ω and m. Note that the recursive equation (21) leads to the following term in the expression of $V_{1,T,\beta,m}(\omega; a = 1)$,

$$[p_{i,1}\omega + p_{i,0}(1-\omega)] V_{1,T-1\beta,m}(\omega_i),$$

which has a coefficient $[p_{i,1}\omega + p_{i,0}(1-\omega)]$ also appeared as the denominator in the expression of ω_i . Finally we obtain that $V_{1,T,\beta,m}(\omega)$ is the maximum of two piecewise linear and convex functions and thus piecewise linear and convex in both ω and m.

Lemma 2: If $p_{11} > p_{01}$, $V_{1,T,\beta,m}(\omega)$ is monotonically increasing with $\omega \in [0, 1]$ for any $T \ge 1$.

Proof: Since the function $V_{1,T,\beta,m}(\omega)$ is piecewise linear, demonstrating the monotonically increasing nature of the continuous function $V_{1,T,\beta,m}(\omega)$ with respect to ω can be achieved by proving

$$V'_{1,T,\beta,m}(\omega) \ge 0, \quad \forall \ \omega \in (0,1), \tag{22}$$

where $V'_{1,T,\beta,m}(\omega)$ represents the right derivative of the function $V_{1,T,\beta,m}(\omega)$ with respect to ω .

In the case of T=1, it is evident that $V_{1,1,\beta,m}(\omega)=$ $\max\{\omega, m\}$ has a non-negative right derivative of either 1 or 0. Now, assuming that (22) holds for T, we analyse the case of T + 1. Let

$$V_{1,T+1,\beta,m}(\omega) = \max\{f_T(\omega), g_T(\omega)\}$$
(23)

with

$$f_T(\omega) = m + \beta V_{1,T,\beta,m}(\mathcal{T}(\omega)), \qquad (24)$$
$$g_T(\omega) = \omega + \beta \sum_{i=1}^K \left[p_{i,1}\omega + p_{i,0}(1-\omega) \right] V_{1,T,\beta,m}(\omega_i) . \qquad (25)$$

Let

$$\omega_i = \mathcal{T}\left(\frac{p_{i,1}\omega}{p_{i,1}\omega + p_{i,0}(1-\omega)}\right) = \mathcal{T}\left(\phi_i(\omega)\right).$$
(26)

Taking the derivatives with respect to ω , we have

$$f'_{T}(\omega) = \beta(p_{11} - p_{01})V'_{1,T,\beta,m}(\mathcal{T}(\omega)), \qquad (27)$$

$$g'_{T}(\omega) = 1 + \beta \sum_{i=1}^{K} (p_{i,1} - p_{i,0})V_{1,T,\beta,m}(\mathcal{T}(\phi_{i}(\omega))) + \beta \sum_{i=1}^{K} V'_{1,T,\beta,m}(\mathcal{T}(\phi_{i}(\omega))) \frac{p_{i,1}p_{i,0}(p_{11} - p_{01})}{p_{i,1}\omega + p_{i,0}(1 - \omega)}. \qquad (28)$$

When $p_{11} > p_{01}$, according to the induction hypothesis and (27), it is straightforward to conclude that $f'_T(\omega) \ge 0$ and thus $f_T(\omega)$ is monotonically increasing. To prove the monotonicity of $g_T(\omega)$, we begin by analyzing the properties of the function ϕ_i . Let P and N denote the sets of CQI signals that satisfy

$$P = \{i: p_{i,1} - p_{i,0} \ge 0\}, \quad N = \{i: p_{i,1} - p_{i,0} < 0\}.$$
(29)

Suppose that $i \in P$ and $j \in N$, then we have

$$\phi_{i}(\omega) - \phi_{j}(\omega) = \frac{(p_{i,1}p_{j,0} - p_{i,0}p_{j,1})\omega(1-\omega)}{[p_{i,1}\omega + p_{i,0}(1-\omega)][p_{j,1}\omega + p_{j,0}(1-\omega)]} \ge 0.$$
(30)

Considering that \mathcal{T} and $V_{1,T,\beta,m}(\omega)$ are both monotonically increasing under the condition $p_{11} > p_{01}$, for any $i \in P$, $j \in N$, we obtain

$$V_{1,T,\beta,m}\left(\mathcal{T}\left(\phi_{i}(\omega)\right)\right) \geq V_{1,T,\beta,m}\left(\mathcal{T}\left(\phi_{j}(\omega)\right)\right).$$
(31)

Thus we have 9

$$\begin{aligned} g_{T}'(\omega) &\geq \beta \sum_{i \in P} (p_{i,1} - p_{i,0}) V_{1,T,\beta,m} \left(\mathcal{T} \left(\phi_{i}(\omega) \right) \right) \\ &+ \beta \sum_{j \in N} (p_{j,1} - p_{j,0}) V_{1,T,\beta,m} \left(\mathcal{T} \left(\phi_{j}(\omega) \right) \right) \\ &\geq \beta [\sum_{i \in P} (p_{i,1} - p_{i,0}) + \sum_{j \in N} (p_{j,1} - p_{j,0})] \\ &\cdot \max_{j \in N} \{ V_{1,T,\beta,m} \left(\mathcal{T} \left(\phi_{j}(\omega) \right) \right) \} \\ &\geq 0. \end{aligned}$$

This establishes the property of $g_T(\omega)$ being monotonically increasing. Consequently, $V_{1,T,\beta,m}(\omega) = \max\{f_T(\omega), g_T(\omega)\}$ is also monotonically increasing, thereby concluding the proof.

Lemma 3: We assume that the discount factor $\beta \in (0,1)$ satisfies

$$\beta < \frac{1}{|p_{11} - p_{01}| \left[1 + 2\sum_{i \in P} (p_{i,1} - p_{i,0})\right]}.$$
 (32)

Then for all $T \ge 1$ and $\omega, \omega' \in [0, 1]$, we have

$$|V_{1,T,\beta,m}(\omega) - V_{1,T,\beta,m}(\omega')| \le C|\omega - \omega'|, \qquad (33)$$

where $C = \frac{1}{1-\beta|p_{11}-p_{01}|[1+2\sum_{i\in P}(p_{i,1}-p_{i,0})]}$. *Proof:* In fact, we prove the conclusion above by directly

proving that

$$|V'_{1,T,\beta,m}(\omega)| \le C, \quad \forall \ T \ge 1, \ \omega \in (0,1).$$
(34)

In the case of T = 1, $|V'_{1,1,\beta,m}(\omega)| \le 1 \le C$. Then under the induction hypothesis that $|V'_{1,T,\beta,m}(\omega)| \le C$, we need to prove $|V'_{1,T+1,\beta,m}(\omega)| \leq C$. Recall the right derivatives $f'_T(\omega)$ and $g'_T(\omega)$ in (27) and (28). It is obvious that

$$|f_T'(\omega)| \le \beta C |p_{11} - p_{01}|. \tag{35}$$

Meanwhile, note that

$$\left|\frac{p_{i,1}p_{i,0}(p_{11}-p_{01})}{p_{i,1}\omega+p_{i,0}(1-\omega)}\right| \le \max\{p_{i,1}, p_{i,0}\}|p_{11}-p_{01}|, \quad (36)$$

$$\left| \sum_{i=1}^{K} \left(p_{i,1} - p_{i,0} \right) V_{1,T,\beta,m} \left(\mathcal{T} \left(\phi_i(\omega) \right) \right) \right| \le C |p_{11} - p_{01}| \sum_{i \in P} (p_{i,1} - p_{i,0}). \quad (37)$$

Thus we obtain the bound on $g'_T(\omega)$

$$|g_T'(\omega) - 1| \le \beta C |p_{11} - p_{01}| \left[1 + 2\sum_{i \in P} (p_{i,1} - p_{i,0}) \right].$$
(38)

From (35) and (38), we conclude that

$$|V'_{1,T+1,\beta,m}(\omega)| \le 1 + \beta C |p_{11} - p_{01}| \left[1 + 2\sum_{i \in P} (p_{i,1} - p_{i,0}) \right] = C.$$

The induction process implies that

$$|V'_{1,T,\beta,m}(\omega)| \le C, \quad \forall \ T \ge 1, \ \omega \in (0,1).$$

Thus the proof is finished.

Lemma 4: Suppose that $p_{11} > p_{01}$ and

$$\beta \le \frac{1}{2(p_{11} - p_{01}) \left[1 + \sum_{i \in P} (p_{i,1} - p_{i,0})\right]}, \qquad (39)$$

then we have

$$V'_{1,T,\beta,m}(\omega; a=1) \ge V'_{1,T,\beta,m}(\omega; a=0),$$
 (40)

where $V'_{1,T,\beta,m}(\omega; a = k)$ denotes the right derivative of $V_{1,T,\beta,m}(\omega; a = k)$ at ω for $k \in \{0,1\}$. The above inequality is also true if $p_{01} > p_{11}$ and

$$\beta \le \frac{1}{(p_{01} - p_{11}) \left[3 + 4\sum_{i \in P} (p_{i,1} - p_{i,0})\right]}.$$
 (41)

Proof: Again, we prove by mathematical induction on the time horizon T. When T = 1, it is clear that

$$V'_{1,1,\beta,m}(\omega; a=1) = 1 > V'_{1,1,\beta,m}(\omega; a=0) = 0.$$

Assume that $V'_{1,T,\beta,m}(\omega;a=1)\geq V'_{1,T,\beta,m}(\omega;a=0).$ If $p_{01}>p_{11}$ and

$$\beta \le \frac{1}{(p_{01} - p_{11}) \left[3 + 4\sum_{i \in P} (p_{i,1} - p_{i,0})\right]}$$

we obtain that

$$\beta C(p_{01} - p_{11}) \le 1 - \beta C(p_{01} - p_{11}) \left[1 + 2 \sum_{i \in P} (p_{i,1} - p_{i,0}) \right]$$

which shows that $f'_T(\omega) \ge g'_T(\omega)$ according to (35) and (38).

On the other hand, if $p_{11} > p_{01}$, $V_{1,T,\beta,m}(\omega)$ is increasing with ω with nonnegative right derivatives by Lemma 2. We can thus obtain tighter bounds on $f'_T(\omega)$ and $g'_T(\omega)$

$$1 \le f'_T(\omega) \le 1 + \beta C(p_{11} - p_{01}) \left[1 + 2 \sum_{i \in P} (p_{i,1} - p_{i,0}) \right],$$
$$0 \le g'_T(\omega) \le \beta C(p_{11} - p_{01}).$$

When we choose

$$\beta \le \frac{1}{2(p_{11} - p_{01}) \left[1 + \sum_{i \in P} (p_{i,1} - p_{i,0})\right]}$$

it is clear that $\beta C(p_{11} - p_{01}) \leq 1$, which shows that $f'_T(\omega) \geq g'_T(\omega)$. The proof is thus complete.

B. Optimality of Threshold Policy

In this section, we demonstrate that the optimal singlearmed policy is a threshold policy, subject to the constraints on the discount factor β outlined in the previous section. We still begin with the finite-horizon case.

For a T-horizon single-armed bandit problem, a threshold policy π_T is defined by a time-dependent real number $\omega_{T,\beta}(m)$ such that

$$a_{T,m}(\omega) = \begin{cases} 1, & \text{if } \omega > \omega_{T,\beta}(m);\\ 0, & \text{if } \omega \le \omega_{T,\beta}(m). \end{cases}$$
(42)

Intuitively, as the value of ω increases, so does the expected immediate reward, which in turn makes activating the arm

more appealing. The following theorem formalizes this intuition under specific conditions.

Theorem 1: Suppose that $p_{11} > p_{01}$ and β satisfies the inequality (39). For any $T \ge 1$, the optimal T-horizon singlearmed policy π_T^* is a threshold policy, which means that there exists $\omega_{T,\beta}^*(m) \in \mathbb{R}$ such that under π_T^* , the optimal action is

$$a_{T,m}^{*}(\omega) = \begin{cases} 1, & \text{if } \omega > \omega_{T,\beta}^{*}(m); \\ 0, & \text{if } \omega \le \omega_{T,\beta}^{*}(m). \end{cases}$$
(43)

Furthermore, at the threshold belief state $\omega_{T,\beta}^*(m)$,

$$V_{1,T,\beta,m}(\omega_{T,\beta}^*(m); a=1) = V_{1,T,\beta,m}(\omega_{T,\beta}^*(m); a=0).$$
(44)

The conclusion is also true for the case that $p_{01} > p_{11}$ and β satisfies the inequality (41).

In the next theorem, we show that the optimal single-armed policy over the infinite horizon is also a threshold policy under the same conditions.

Theorem 2: Fix the Lagrangian multiplier m. The finitehorizon value functions $V_{1,T,\beta,m}(\cdot)$, $V_{1,T,\beta,m}(\cdot; a = 1)$ and $V_{1,T,\beta,m}(\cdot; a = 0)$ uniformly converge to the infinite-horizon value functions $V_{\beta,m}(\cdot)$, $V_{\beta,m}(\cdot; a = 1)$ and $V_{\beta,m}(\cdot; a = 0)$ which consequently possess the same properties established in Lemma 2-3 and Theorem 1.

Utilizing the properties of value functions, the proof of Theorem 1 and 2 are the same as those of Theorem 2.5 and 2.6 in [32], so we omit it here. Thus far we have established the threshold structure of the optimal single-armed policy based on the analysis of $V_{\beta,m}(\omega)$ as a function of the belief state ω with *m* fixed.

C. Indexability

Based on the definition of indexability and the threshold structure of the optimal policy for the relaxed single-armed bandit problem (11), establishing the indexability of our model is equivalent to proving that the threshold $\omega_{\beta}^{*}(m)$ is monotonically increasing with respect to m.

To investigate the sufficient condition for indexability, we now examine the properties of $V_{\beta,m}(\omega)$ as a function of the Lagrangian multiplier m with the initial belief state ω fixed.

Lemma 5: Given the initial belief state ω , value function $V_{\beta,m}(\omega)$ is convex in m. Furthermore, The left and right derivatives of $V_{\beta,m}(\omega)$ with respect to m exist at every point $m_0 \in \mathbb{R}$.

Proof: In fact, for any given values of m_1 , m_2 and $\theta \in (0, 1)$, when we apply the optimal policy $\pi_{\beta}^*(\theta m_1 + (1-\theta)m_2)$ of $V_{\beta,\theta m_1+(1-\theta)m_2}(\omega)$ to the problem with Lagrangian multipliers m_1 and m_2 respectively, it cannot surpass the performance achieved by the optimal policies $\pi_{\beta}^*(m_1)$ and $\pi_{\beta}^*(m_2)$ for $V_{\beta,m_1}(\omega)$ and $V_{\beta,m_2}(\omega)$. To be more explicit, let r_a and $r_p(m)$ represent the expected total discounted reward from active and passive actions under policy $\pi_{\beta}^*(\theta m_1 + (1-\theta)m_2)$

applied to the problem with Lagrangian multipliers m and initial belief state ω , then we have

$$\begin{split} \theta V_{\beta,m_1}(\omega) + &(1-\theta) V_{\beta,m_2}(\omega) \\ \geq &\theta(r_a + r_p(m_1)) + (1-\theta)(r_a + r_p(m_2)) \\ = &r_a + r_p(\theta m_1 + (1-\theta)m_2) \\ = &V_{\beta,\theta m_1 + (1-\theta)m_2}(\omega). \end{split}$$

This shows the convexity of value function $V_{\beta,m}(\omega)$ with respect to m. Since $V_{\beta,m}(\omega)$ is convex in m, it is obvious that its left and right derivatives with m exist at every point $m_0 \in \mathbb{R}$, according to the properties of convex functions.

Lemma 6: Given the initial belief state ω , value function $V_{\beta,m}(\omega)$ is differentiable almost everywhere in m.

Proof: Consider two policies $\pi_{\beta}^{*}(m_{1})$ and $\pi_{\beta}^{*}(m_{2})$ achieving $V_{\beta,m_{1}}(\omega)$ and $V_{\beta,m_{2}}(\omega)$ for any $m_{1}, m_{2} \in \mathbb{R}$, respectively. Utilizing the similar trick as the proof of Lemma 5, let r_{a} be the expected total discounted reward from the active action and $r_{p}(m)$ that from the passive action under $\pi_{\beta}^{*}(m_{1})$ applied to the problem with Lagrangian multiplier m, then

$$V_{\beta,m_1}(\omega) = r_a + r_p(m_1), \quad V_{\beta,m_2}(\omega) \ge r_a + r_p(m_2).$$

Thus we can obtain that

$$V_{\beta,m_1}(\omega) - V_{\beta,m_2}(\omega) \le r_a + r_p(m_1) - r_a - r_p(m_2)$$

= $r_p(m_1 - m_2)$
 $\le \frac{1}{1 - \beta} |m_1 - m_2|.$

Interchanging $V_{\beta,m_1}(\omega)$ and $V_{\beta,m_2}(\omega)$ by the symmetry of the problem, we obtain the conclusion that $V_{\beta,m}(\omega)$ is Lipschitz continuous in m, that is

$$|V_{\beta,m_1}(\omega) - V_{\beta,m_2}(\omega)| \le \frac{1}{1-\beta}|m_1 - m_2|.$$

Consequently, according to Rademacher theorem [33], $V_{\beta,m}(\omega)$ is differentiable almost everywhere in m.

In the following theorem, we formalize the relationship between value function and passive time and provide a sufficient condition for the indexability of our model.

Theorem 3: Let $\Pi_{\beta}^{*}(m)$ denote the set of all optimal singlearmed policies achieving $V_{\beta,m}(\omega)$ with initial belief state ω . Define the passive time as

$$D_{\beta,m}(\omega) = \max_{\pi^*_{\beta}(m) \in \Pi^*_{\beta}(m)} \mathbb{E}_{\pi^*_{\beta}(m)} \left[\sum_{t=1}^{\infty} \beta^{t-1} \mathbb{1}_{\{a(t)=0\}} \mid \omega(1) = \omega \right]$$
(45)

The right derivative of the value function $V_{\beta,m}(\omega)$ with m, denoted by $\frac{dV_{\beta,m}(\omega)}{(dm)^+}$, exists at every value of m and

$$\left. \frac{dV_{\beta,m}(\omega)}{(dm)^+} \right|_{m=m_0} = D_{\beta,m_0}(\omega). \tag{46}$$

Furthermore, the single-armed bandit is indexable if at least one of the following condition is satisfied: 1) for any $m_0 \in [0, 1)$, the optimal policy is a threshold policy with threshold $\omega_{\beta}^*(m_0) \in [0, 1)$ (if the threshold is a closed interval then the right end is selected) and

$$\frac{dV_{\beta,m}\left(\omega_{\beta}^{*}(m_{0}); a=0\right)}{(dm)^{+}}\bigg|_{m=m_{0}} \\ > \frac{dV_{\beta,m}\left(\omega_{\beta}^{*}(m_{0}); a=1\right)}{(dm)^{+}}\bigg|_{m=m_{0}}.$$
 (47)

2) for any $m_0 \in \mathbb{R}$ and $\omega \in P(m_0)$, we have

$$\frac{dV_{\beta,m}\left(\omega;a=0\right)}{(dm)^{+}}\Big|_{m=m_{0}} \geq \frac{dV_{\beta,m}\left(\omega;a=1\right)}{(dm)^{+}}\Big|_{m=m_{0}}.$$
(48)

The proof follows directly from the argument of Theorem 2.7 in [32], with only tiny difference. So we omit it here.

Theorem 3 provides a direct way for checking the indexability of the bandit problem with the help of the passive times. And because of this, we can present the sufficient condition for the indexability of our problem.

Corollary 1: The restless single-armed bandit problem is indexable if the discount factor $\beta \leq 0.5$.

Proof: Similar as the dynamic equations that value functions $V_{\beta,m}(\omega)$ satisfy, the passive time also has its own dynamic equations

$$D_{\beta,m}(\omega; a = 0) = 1 + \beta D_{\beta,m}(\mathcal{T}(\omega)),$$
(49)
$$D_{\beta,m}(\omega; a = 1) = \beta \sum_{i=1}^{K} [p_{i,1}\omega + p_{i,0}(1-\omega)] D_{\beta,m}(\omega_i).$$
(50)

Thus the equation (48) is equivalent to

$$1 + \beta D_{\beta,m}(\mathcal{T}(\omega)) \ge \beta \sum_{i=1}^{K} [p_{i,1}\omega + p_{i,0}(1-\omega)] D_{\beta,m}(\omega_i).$$
(51)

The above inequality clearly holds if $\beta \leq 0.5$ since $D_{\beta,m}(\cdot) \in [0, \frac{1}{1-\beta}]$ for any $m \in \mathbb{R}$.

IV. APPROXIMATED WHITTLE INDEX

According to Theorem 2 and Corollary 1, we assume that the following condition is satisfied such that the optimal policy for the relaxed single-armed bandit problem is a threshold policy and the indexability holds

$$\beta \leq \left\{ \min \left\{ \frac{1}{2|p_d| \left[1 + \sum_{i \in P} (p_{i,1} - p_{i,0})\right]}, 0.5 \right\}, \quad p_{11} > p_{01} \\ \frac{1}{|p_d| \left[3 + 4 \sum_{i \in P} (p_{i,1} - p_{i,0})\right]}, 0.5 \right\}, \quad p_{11} < p_{01} \end{cases},$$
(52)

where $p_d = p_{11} - p_{01}$. Given any belief state ω , to solve for the Whittle index $W(\omega)$ under indexability, we need to find

out the minimum Lagrangian multiplier m that satisfies the system of equations below

$$\begin{cases} V_{\beta,m}(\omega; a = 1) = V_{\beta,m}(\omega; a = 0), \\ V_{\beta,m}(\omega; a = 1) = \omega + \beta \sum_{i=1}^{K} p_i(\omega) V_{\beta,m}(\omega_i), \\ V_{\beta,m}(\omega; a = 0) = m + \beta V_{\beta,m}(\mathcal{T}(\omega)). \end{cases}$$
(53)

Before solving the equations above and deriving the approximated Whittle index utilizing the threhold structure of the optimal policy, we first present the concept of first crossing time. Given two belief state ω and ω' , the first crossing time is defined as

$$L(\omega, \omega') = \min_{0 \le k < \infty} \{k : \mathcal{T}^k(\omega) > \omega'\},\tag{54}$$

where we set $\mathcal{T}^0(\omega) = \omega$ and

$$L(\omega, \omega') = +\infty$$
, if $\mathcal{T}^k(\omega) \le \omega'$ for all $k \ge 0$.

It is evident that $L(\omega, \omega')$ is the minimum time slots required for a belief state ω to remain in the passive set P(m) before the channel is chosen, given a threshold $\omega' \in [0, 1)$.

Consider the nontrivial case p_{01} , $p_{11} \in (0, 1)$ and $p_{01} \neq p_{11}$ where the Markov chain of the internal arm states {S(t)} is aperiodic and irreducible and that the belief update is actiondependent. According to (54), we can figure out that, if $p_{11} > p_{01}$,

$$L(\omega, \omega') = \begin{cases} 0, & \omega > \omega' \\ \left\lfloor \log_{p_d} \frac{p_{01} - \omega'(1 - p_d)}{p_{01} - \omega(1 - p_d)} \right\rfloor + 1, & \omega \le \omega' < \omega_s \\ \infty, & \omega \le \omega', \omega' \ge \omega_s \end{cases}$$
(55)

where steady belief state $\omega_s = p_{01}/(1 + p_{01} - p_{11})$, else if $p_{11} < p_{01}$,

$$L(\omega, \omega') = \begin{cases} 0, & \omega > \omega' \\ 1, & \omega \le \omega' < \mathcal{T}(\omega) \\ \infty, & \omega \le \omega', \mathcal{T}(\omega) \le \omega' \end{cases}$$
(56)

Using the first crossing time, the value function $V_{\beta,m}(\omega)$ can be expanded as

$$V_{\beta,m}(\omega) = b_1(\omega)m + b_2(\omega)\Omega(\omega) + \sum_{i=1}^K b_{3,i}(\omega)V_{\beta,m}(f_i(\omega)),$$
(57)

where

$$\Omega(\omega) = \mathcal{T}^{L(\omega,\omega_{\beta}^{*}(m))}(\omega), \tag{58}$$

$$b_1(\omega) = \frac{1 - \beta^{L(\omega,\omega_\beta^*(m))}}{1 - \beta},$$
(59)

$$b_2(\omega) = \beta^{L(\omega,\omega_\beta^*(m))},\tag{60}$$

$$b_{3,i}(\omega) = \beta^{L\left(\omega,\omega_{\beta}^{*}(m)\right)+1} p_i\left(\mathcal{T}^{L\left(\omega,\omega_{\beta}^{*}(m)\right)}(\omega)\right), \quad (61)$$

and we define the function $f_i(\omega)$ as

$$f_i(\omega) = \mathcal{T}\left(\phi_i\left(\mathcal{T}^{L\left(\omega,\omega_\beta^*(m)\right)}(\omega)\right)\right),\tag{62}$$

while we take the notation that

. . .

$$f_{i_2,i_1}(\omega) = f_{i_2} \circ f_{i_1}(\omega) = f_{i_2}(f_{i_1}(\omega)), \ i_1, i_2 \in \{1, 2, \cdots, K\}.$$
(63)

The summation term within (57) poses difficulties in solving for $V_{\beta,m}(\omega)$ since new belief states are introduced as unknowns. To tackle this difficulty, we approximate $V_{\beta,m}(\omega)$ in an iterative fashion. We compute the expanded form of $V_{\beta,m}(\omega)$, $V_{\beta,m}(f_{i_1}(\omega))$, $V_{\beta,m}(f_{i_2,i_1}(\omega))$, \cdots , $V_{\beta,m}(f_{i_n,\cdots,i_2,i_1}(\omega))$ one by one. In this way, we get the following sequence of equations

$$\begin{split} V_{\beta,m}(\omega) &= b_1(\omega)m + b_2(\omega)\Omega(\omega) + \sum_{i_1=1}^K b_{3,i_1}(\omega)V_{\beta,m}(f_{i_1}(\omega)), \\ V_{\beta,m}(f_{i_1}(\omega)) &= b_1(f_{i_1}(\omega))m + b_2(f_{i_1}(\omega))\Omega(f_{i_1}(\omega)) \\ &+ \sum_{i_2=1}^K b_{3,i_2}(f_{i_1}(\omega))V_{\beta,m}(f_{i_2,i_1}(\omega)), \ i_1 \in \{1, 2, \cdots, K\} \\ V_{\beta,m}(f_{i_2,i_1}(\omega)) &= b_1(f_{i_2,i_1}(\omega))m \\ &+ b_2(f_{i_2,i_1}(\omega))\Omega(f_{i_2,i_1}(\omega)) \\ &+ \sum_{i_3=1}^K b_{3,i_3}(f_{i_2,i_1}(\omega))V_{\beta,m}(f_{i_3,i_2,i_1}(\omega)), \\ &i_1, i_2 \in \{1, 2, \cdots, K\} \end{split}$$

$$V_{\beta,m}(f_{i_{n},\cdots,i_{1}}(\omega)) = b_{1}(f_{i_{n},\cdots,i_{1}}(\omega))m + b_{2}(f_{i_{n},\cdots,i_{1}}(\omega))\Omega(f_{i_{n},\cdots,i_{1}}(\omega)) + \sum_{i_{n+1}=1}^{K} b_{3,i_{n+1}}(f_{i_{n},\cdots,i_{1}}(\omega))V_{\beta,m}(f_{i_{n+1},\cdots,i_{1}}(\omega)), i_{1},\cdots,i_{n} \in \{1,2,\cdots,K\}$$
(64)

For sufficiently large iterative steps n, we can get an estimation of $V_{\beta,m}(\omega)$ with an arbitrarily small error by setting

$$V_{\beta,m}\left(f_{i_{n+1},\cdots,i_{1}}(\omega)\right) = 0, \ \forall \ i_{1},\cdots,i_{n+1} = 1,2,\cdots,K.$$

During the computation of $V_{\beta,m}(f_{i_n,\dots,i_2,i_1}(\omega))$, the error of this estimate is discounted by the factor β . As a result, the backward computation process for $V_{\beta,m}(\omega)$ experiences a geometrically decreasing error propagation. Consequently, we can obtain an approximation of $V_{\beta,m}(\omega)$ with arbitrary precision for any $\omega \in [0, 1]$, denoted as $\hat{V}_{\beta,m,n}(\omega)$, where *n* represents the iteration steps here.

In conclusion, the *n*-iteration Whittle index is based on the solution of the system of equations (53). To be more explicit, for any channel in belief state ω , substituting ω_i and $\mathcal{T}(\omega)$ respectively for ω in the above system of equations (64), we obtain *n*-iteration estimates of $V_{\beta,m}(\omega_i)$ and $V_{\beta,m}(\mathcal{T}(\omega))$. Thus we can use them in system of equations (53) to compute the approximated Whittle index $W(\omega)$ by setting $\omega_{\beta}^*(m) = \omega$ according to the first equation of the system and Theorem 1.

Moreover, in the case of large values of $\beta \in (0, 1)$, where the threshold structure of the optimal policy or indexability may not hold (i.e., condition (52) is not satisfied), we can still utilize the aforementioned process to find out the Lagrangian multiplier m that satisfies (53), if such a solution exists. It is important to note that the approximated value functions $\widehat{V}_{\beta,m}(\omega; a = 1)$ and $\widehat{V}_{\beta,m}(\omega; a = 0)$ are linear in m. The equality of these approximated value functions provides a unique solution for m, if it exists. This obtained m, if it is indeed a solution, can then be employed as the approximated Whittle index $W(\omega)$, without necessitating indexability or the threshold structure of the optimal policy. On the other hand, if it does not exist, we can simply set

$$W(\omega) = \omega B. \tag{65}$$

Before computing the closed form of *n*-iteration approximated Whittle index, we solve for the simplest case of 0iteration, which is referred to as the imperfect Whittle index. Setting $V_{\beta,m}(f_{i_1}(\omega)) = 0$, we can directly solve for $V_{\beta,m}(\omega)$ in closed form and thus obtain the estimates of $V_{\beta,m}(\omega_i)$ and $V_{\beta,m}(\mathcal{T}(\omega))$

$$\widehat{V}_{\beta,m,0}(\omega_i) = b_1(\omega_i)m + b_2(\omega_i)\Omega(\omega_i),$$

$$\widehat{V}_{\beta,m,0}(\mathcal{T}(\omega)) = b_1(\mathcal{T}(\omega))m + b_2(\mathcal{T}(\omega))\Omega(\mathcal{T}(\omega)).$$

Then plugging them into the equations (53), we can get a simple linear equation with respect to m:

 $c_1 m = c_0,$

where

$$c_0 = \omega + \beta \sum_{i=1}^{K} p_i(\omega) \left[b_2(\omega_i) \Omega(\omega_i) - b_2(\mathcal{T}(\omega)) \Omega(\mathcal{T}(\omega)) \right],$$
(66)

$$c_1 = 1 + \beta \sum_{i=1}^{K} p_i(\omega) \left[b_1(\mathcal{T}(\omega)) - b_1(\omega_i) \right].$$
 (67)

If $c_1 \neq 0$, we can obtain the imperfect Whittle index as below

$$\widehat{W}_0(\omega) = \left. \frac{c_0}{c_1} \right|_{\omega^*_{\beta}(m) = \omega}.$$
(68)

A. Closed Form of Approximated Whittle Index

Theorem 4: Given iteration step n, belief state ω and Lagrangian multiplier m, setting $V_{\beta,m}(f_{i_1,\cdots,i_{n+1}}(\omega)) = 0$ for any $i_1, \cdots, i_{n+1} \in \{1, 2, \cdots, K\}$ in equation set (64), we get the n-iteration estimate of $V_{\beta,m}(\omega)$, $\widehat{V}_{\beta,m,n}(\omega)$, for $n \ge 0$ as below

$$\widehat{V}_{\beta,m,n}(\omega) = k_n(\omega)m + a_n(\omega), \qquad (69)$$

where

$$k_{0}(\omega) = b_{1}(\omega),$$

$$k_{n}(\omega) = k_{0}(\omega) + \sum_{i_{1}=1}^{K} b_{3,i_{1}}(\omega)k_{n-1}(f_{i_{1}}(\omega)), n \ge 1$$
(70)

and

$$a_{0}(\omega) = b_{2}(\omega)\Omega(\omega),$$

$$a_{n}(\omega) = a_{0}(\omega) + \sum_{i_{1}=1}^{K} b_{3,i_{1}}(\omega)a_{n-1}(f_{i_{1}}(\omega)), n \ge 1.$$
(71)

Thus approximating value functions in this way, solving the system of equations (53) and letting $\omega_{\beta}^{*}(m) = \omega$, we get the

n-iteration approximated Whittle index, $\widehat{W}_n(\omega)$, as below if $1 + \beta \left(k_{n,0} - \sum_{i=1}^K p_i(\omega) k_{n,i} \right) \neq 0$:

$$\widehat{W}_{n}(\omega) = \left. \frac{\omega + \beta \left(\sum_{i=1}^{K} p_{i}(\omega) a_{n,i} - a_{n,0} \right)}{1 + \beta \left(k_{n,0} - \sum_{i=1}^{K} p_{i}(\omega) k_{n,i} \right)} \right|_{\omega_{\beta}^{*}(m) = \omega} .$$
(72)

where $k_{n,0} = k_n(\mathcal{T}(\omega))$, $a_{n,0} = a_n(\mathcal{T}(\omega))$ and $k_{n,i} = k_n(\omega_i)$, $a_{n,i} = a_n(\omega_i)$ for $i = 1, 2, \cdots, K$.

Proof: We first prove the equation (69) by mathematical induction. We start from the 0-iteration case. Let $V_{\beta,m}(f_{i_1}(\omega)) = 0$ for any $i_1 \in \{1, 2, \dots, K\}$ in the system of equations (64), thus it is easy to compute that

$$\widehat{V}_{\beta,m,0}(\omega) = k_0(\omega)m + a_0(\omega)$$

where

$$k_0(\omega) = \frac{1 - \beta^{L(\omega,\omega_{\beta}^*(m))}}{1 - \beta} = b_1(\omega),$$

$$a_0(\omega) = \beta^{L(\omega,\omega_{\beta}^*(m))} \mathcal{T}^{L(\omega,\omega_{\beta}^*(m))}(\omega) = b_2(\omega)\Omega(\omega)$$

Then in the 1-iteration case, we set $f_{i_2,i_1}(\omega) = 0$ for any $i_1, i_2 \in \{1, 2, \dots, K\}$. Solving the equation set (64), we get

$$\dot{V}_{\beta,m,1}(\omega) = k_1(\omega)m + a_1(\omega)$$

where

$$k_{1}(\omega) = b_{1}(\omega) + \sum_{i_{1}=1}^{K} b_{3,i_{1}}(\omega)b_{1}(f_{i_{1}}(\omega))$$

$$= k_{0}(\omega) + \sum_{i_{1}=1}^{K} b_{3,i_{1}}(\omega)k_{0}(f_{i_{1}}(\omega)),$$

$$a_{1}(\omega) = b_{2}(\omega)\Omega(\omega) + \sum_{i_{1}=1}^{K} b_{3,i_{1}}(\omega)b_{2}(f_{i_{1}}(\omega))\Omega(f_{i_{1}}(\omega))$$

$$= a_{0}(\omega) + \sum_{i_{1}=1}^{K} b_{3,i_{1}}(\omega)a_{0}(f_{i_{1}}(\omega)).$$

By mathematical induction, we assume that $\widehat{V}_{\beta,m,n}(\omega)$ satisfies the conclusion for any belief state ω . Based on this, we compute the (n + 1)-iteration estimate of $V_{\beta,m}(\omega)$. Note that $\widehat{V}_{\beta,m,n+1}(f_{i_1}(\omega))$ is the *n*-iteration estimate of $V_{\beta,m}(f_{i_1}(\omega))$ and is equal to

$$\widehat{V}_{\beta,m,n+1}(f_{i_1}(\omega)) = k_n(f_{i_1}(\omega))m + a_n(f_{i_1}(\omega)).$$

Then we have that

$$\begin{split} \widehat{V}_{\beta,m,n+1}(\omega) \\ = & b_1(\omega)m + b_2(\omega)\Omega(\omega) + \sum_{i_1=1}^K b_{3,i_1}(\omega)\widehat{V}_{\beta,m,n+1}(f_{i_1}(\omega)) \\ = & b_1(\omega)m + b_2(\omega)\Omega(\omega) \\ &+ \sum_{i_1=1}^K b_{3,i_1}(\omega) \left[k_n(f_{i_1}(\omega))m + a_n(f_{i_1}(\omega))\right] \\ = & \left[b_1(\omega) + \sum_{i_1=1}^K b_{3,i_1}(\omega)k_n(f_{i_1}(\omega))\right] m \\ &+ b_2(\omega)\Omega(\omega) + \sum_{i_1=1}^K b_{3,i_1}(\omega)a_n(f_{i_1}(\omega)) \\ = & k_{n+1}(\omega)m + a_{n+1}(\omega). \end{split}$$

Thus the proof of equation (69) is finished.

According to equations (53), we can get a linear equation with respect to m using the n-iteration estimate of $V_{\beta,m,n}(\omega_i)$ and $V_{\beta,m,n}(\mathcal{T}(\omega))$

$$\left[1 + \beta \left(k_{n,0} - \sum_{i=1}^{K} p_i(\omega) k_{n,i}\right)\right] m$$
$$= \omega + \beta \left(\sum_{i=1}^{K} p_i(\omega) a_{n,i} - a_{n,0}\right)$$

Given the belief state ω , setting $\omega_{\beta}^{*}(m) = \omega$, if

$$1 + \beta \left(k_{n,0} - \sum_{i=1}^{K} p_i(\omega) k_{n,i} \right) \neq 0,$$

we get the n-iteration approximated Whittle index as below

$$\widehat{W}_{n}(\omega) = \left. \frac{\omega + \beta \left(\sum_{i=1}^{K} p_{i}(\omega) a_{n,i} - a_{n,0} \right)}{1 + \beta \left(k_{n,0} - \sum_{i=1}^{K} p_{i}(\omega) k_{n,i} \right)} \right|_{\omega_{\beta}^{*}(m) = \omega}$$

Note that when n = 0, the 0-iteration approximated Whittle index is the same as the imperfect Whittle index we computed before (68).

B. Algorithm

We summarize the above solution process into an algorithm called the Approximated Whittle Index (AWI) Policy.

V. SIMULATION RESULTS

In this section, results of numerical experiments are presented to validate the effectiveness and robustness of the proposed Approximated Whittle Index Policy. Moreover, we investigate the proper setting of iteration step size and the significance of conditions on the discount factor β .

Given initial belief states of all channels, the simulation starts by approximating Whittle index for each channel and deciding which of them are chosen to transmit data following one particular policy. After that, we calculate the reward of last choice and generate the CQI observation of those active

Algorithm 1 Approximated Whittle Index Policy

Input: $\beta \in (0,1), T \geq 1, N \geq 2, 1 \leq M < N, K \geq$ $1, n_{iter} \ge 0$ Input: $\omega_n(1), p_{11}^{(n)}, p_{01}^{(n)}, p_{i1}^{(n)}, p_{i0}^{(n)}, B_n (n = 1, 2, \dots, N, i = 1, 2, \dots, N)$ $1, 2, \cdots, K$ for $t = 1, 2, \dots, T$ do for $n = 1, \cdots, N$ do Set the threshold $\omega^*_{\scriptscriptstyle{\beta}}(m) = \omega_n(t)$ and try to compute the approximated Whittle index $\widehat{W}_{n_{iter}}(\omega_n(t))$ if $\widehat{W}_{n_{iter}}(\omega_n(t))$ exists then Set $W(\omega_n(t)) = \widehat{W}_{n_{iter}}(\omega_n(t))$ else Set $W(\omega_n(t)) = \omega_n(t)B_n$ end if end for Choose the top M channels with the largest approximated Whittle Indices $W(\omega_n(t))$ Observe the selected M channels and accrue reward $S_n(t)B_n$ from each active channel for $n = 1, \cdots, N$ do Update the belief state $\omega_n(t)$ according to (2) end for end for

channels following the distributions $\{p_{i,0}: i = 1, 2, \dots, K\}$ and $\{p_{i,1}: i = 1, 2, \dots, K\}$ according to the initial states of channels. At the same time, given transition probabilities p_{01} and p_{11} for each channel, we update channel states according to the provided Gilbert-Elliott channel model. Finally we update the belief states in accordance to (2) for next round of decision-making.

Given a time interval [1, T], we take the average of discounted return over different runs as the metric to measure performance, where the discounted return over a finite horizon is defined as

$$G_{\pi}(T) = \sum_{t=1}^{T} \beta^{t-1} R_{\pi}(t).$$
(73)

Before demonstrating the results of numerical experiments, we clarify the problem setting we investigated. Suppose there are 7 available channels, and we need to choose one from them for the sub-network to transmit data. We assume that the prior probability that a channel is in good state is equal to p_1 . And in the beginning, when we have no other useful information, we just set the initial belief state of each channel as

$$\omega_n(1) = p_1, \ n = 1, 2, \cdots, 7.$$
(74)

In order to simulate the diversity of the actual environment, we conducted experiments based on four channel models, and the transition probabilities of each model is shown in Table II. Moreover, in order to simplify the problem, but without the loss of generality, we divided CQI into two levels, where i = 2 indicates the channel is more likely to be in good state, while i = 1 represents a poor level of CQI.

System-1	${p_{11}^{(n)}}_{n=1}^7$	$\{0.6, 0.4, 0.2, 0.2, 0.4, 0.1, 0.3\}$
	${p_{01}^{(n)}}_{n=1}^7$	$\{0.8, 0.6, 0.4, 0.9, 0.8, 0.6, 0.7\}$
	$\{B_n\}_{n=1}^7$	$\{0.4998, 0.6668, 1.0000, 0.6296, 0.5830, 0.8334, 0.6668\}$
System-2	${p_{11}^{(n)}}_{n=1}^7$	$\{0.8, 0.6, 0.4, 0.9, 0.8, 0.6, 0.7\}$
	${p_{01}^{(n)}}_{n=1}^7$	$\{0.6, 0.4, 0.2, 0.2, 0.4, 0.1, 0.3\}$
	$\{B_n\}_{n=1}^7$	$\{0.4998, 0.6668, 1.0000, 0.6296, 0.5830, 0.8334, 0.6668\}$
System-3	${p_{11}^{(n)}}_{n=1}^7$	$\{0.1, 0.4, 0.3, 0.5, 0.1, 0.3, 0.5\}$
	${p_{01}^{(n)}}_{n=1}^7$	$\{0.3, 0.6, 0.4, 0.7, 0.2, 0.6, 0.8\}$
	$\{B_n\}_{n=1}^7$	$\{0.4998, 0.6668, 1.0000, 0.6296, 0.5830, 0.8334, 0.6668\}$
System-4	${p_{11}^{(n)}}_{n=1}^7$	$\{0.3, 0.6, 0.4, 0.7, 0.2, 0.6, 0.8\}$
	${p_{01}^{(n)}}_{n=1}^7$	$\{0.1, 0.4, 0.3, 0.5, 0.1, 0.3, 0.5\}$
	$\{B_n\}_{n=1}^7$	$\{0.4998, 0.6668, 1.0000, 0.6296, 0.5830, 0.8334, 0.6668\}$

TABLE II CHANNEL MODEL SETTING

A. Comparison for Effectiveness and Robustness

We compared the performance of our policy with myopic policy and another existing approximated Whittle index policy, labeled as AWI0, which uses a relatively rough estimation method of Whittle index [30].

The objective of myopic policy is to maximize the expected current reward without considering the long-term benefit. Consequently this policy only selects those channels with the highest myopic indices, whose definition is as simple as

$$I_{myopic}(\omega) = \omega B. \tag{75}$$

In Fig. 2, it is shown that no matter in which of the four systems, our proposed policy outperforms both myopic and AWI0 policies, even when iteration step size is set to 0. The superior performance is a testament to the effectiveness of the proposed policy, and the superior performance under all four channel models illustrates the robustness of the proposed policy.

B. Choice of Iteration Step Size

We also adjust the iteration step sizes between 0 and 3 when we approximate Whittle index for the proposed AWI policy, and observe the resulting changes in average discounted return. Although the increase in iteration step size obviously improves the performance of the proposed policy, it is sufficient to set the iteration step size to 2 according to Fig. 2. When the iteration step size exceeds 2, the small improvement in performance is no longer attractive enough to make up for the exponential increase in computing time and space.

C. Significance of Conditions on Discount Factor

For system 1 to 4, the largest β that satisfies the condition (52) of discount factor is 0.2304, 0.3968, 0.5 and 0.5 respectively. The data of the four channel models shown in Fig. 2 all come from the experiments where we took the largest β satisfying the condition (52), while during the experiment of Fig. 3, we just set β to 0.9 which does not meet the condition on discount factor for any channel model. According to Theorem 2 and Corollary 1, we have proved that inequality (52) is a sufficient condition under which the optimal policy for the single-armed bandit problem is a threshold policy and the indexability holds, so that the proposed AWI policy shows excellent performance. And now by comparing Fig. 2 and Fig. 3, we can find that for large discount factors, the proposed AWI policy still outperforms other policies but increasing the step size may not necessarily bring about performance improvements.

VI. CONCLUSION

In this work, we employed the RMAB framework to model the DSA problem where CQI can be observed through cognitive capabilities of of the sub-network. We established the indexability of the relaxed single-armed bandit problem and demonstrated the optimality of the threshold policy under certain conditions. Furthermore, we analyzed the value functions with tight approximations to obtain the Whittle Index Policy, a heuristic and low-complexity solution for such complex sequential scheduling problems. Finally, we substantiated the effectiveness and robustness of the proposed algorithm through extensive numerical simulations including the scenario where the conditions for indexability do not hold.

In future research, it is worthwhile to investigate the impact of the iteration step size on the performance of the proposed policy and optimize it according to different problem settings. Additionally, the integration of deep learning and neural networks could be explored to enhance the approximate calculation of the Whittle index. For example, we could train a neural network that produces the approximated Whittle index by leveraging the intrinsic mathematical properties of the value functions. Furthermore, extending the 2-state channel model to arbitrary number of channel states is also an intereting direction.

REFERENCES

- 3GPP, "Security of Home Node B (HNB) / Home evolved Node B (HeNB) (Release 18)," Mar. 2024.
- [2] GTI, "GTI 5G Low-Cost Series Products 5G Femto Technical Requirements White Paper," Sep. 2023.
- [3] D. Anand, M. A. Togou, and G.-M. Muntean, "A Machine Learning Solution for Video Delivery to Mitigate Co-Tier Interference in 5G HetNets," *IEEE Transactions on Multimedia*, vol. 25, pp. 5117–5129, 2023.



Fig. 2. Average discounted return using the myopic, AWI0 policies and our AWI policies in different iteration step sizes under the condition (52) of discount factor β

- [4] M. Lin, N. Bartolini, M. Giallorenzo, and T. F. La Porta, "On Interference Aware Power Adjustment and Scheduling in Femtocell Networks," *IEEE/ACM Transactions on Networking*, vol. 28, no. 2, pp. 736–749, Apr. 2020.
- [5] P. Scopelliti, A. Tropeano, G.-M. Muntean, and G. Araniti, "An Energy-Quality Utility-Based Adaptive Scheduling Solution for Mobile Users in Dense Networks," *IEEE Transactions on Broadcasting*, vol. 66, no. 1, pp. 47–55, Mar. 2020.
- [6] L. Pu, H.-C. Wu, C. Wang, S.-H. Fang, S. Mukhopadhyay, and C. Busch, "Novel Fast User-Placement Ushering Algorithms and Performance Analysis for LTE Femtocell Networks," *IEEE Transactions on Cognitive Communications and Networking*, vol. 6, no. 1, pp. 381–393, Mar. 2020.
- [7] L. Eslami, G. Mirjalily, and T. N. Davidson, "Joint Mode Selection and Resource Allocation for D2D and Femtocell Users in Dense Heterogeneous Networks With Full Frequency Reuse," *IEEE Transactions on Vehicular Technology*, vol. 72, no. 11, pp. 14364–14379, Nov. 2023.
- [8] A. Famili, T. O. Atalay, A. Stavrou, H. Wang, and J.-M. Park, "OFDRA: Optimal Femtocell Deployment for Accurate Indoor Positioning of RIS-Mounted AVs," *IEEE Journal on Selected Areas in Communications*, vol. 41, no. 12, pp. 3783–3798, Dec. 2023.
- [9] H. Sharma, N. Kumar, I. Budhiraja, and A. Barnawi, "Secrecy Rate Maximization in THz-Aided Heterogeneous Networks: A Deep Reinforcement Learning Approach," *IEEE Transactions on Vehicular Technology*, vol. 72, no. 10, pp. 13490–13505, Oct. 2023.
- [10] R. Zhang, K. Xiong, Y. Lu, B. Gao, P. Fan, and K. B. Letaief, "Joint Coordinated Beamforming and Power Splitting Ratio Optimization in MU-MISO SWIPT-Enabled HetNets: A Multi-Agent DDQN-Based Approach," *IEEE Journal on Selected Areas in Communications*, vol. 40, no. 2, pp. 677–693, Feb. 2022.
- [11] Y. Xu, H. Xie, Q. Wu, C. Huang, and C. Yuen, "Robust Max-Min Energy Efficiency for RIS-Aided HetNets With Distortion Noises," *IEEE*

Transactions on Communications, vol. 70, no. 2, pp. 1457–1471, Feb. 2022.

- [12] Z. Li, Z. Li, and Z. Ding, "Distributed Generalized Nash Equilibrium Seeking and Its Application to Femtocell Networks," *IEEE Transactions* on Cybernetics, vol. 52, no. 4, pp. 2505–2517, Apr. 2022.
- [13] O. T. Odeyomi, "Online Learning of Time-Varying Unbalanced Networks in Non-Convex Environments: A Multi-Armed Bandit Approach," *IEEE Access*, vol. 11, pp. 15567–15577, 2023.
- [14] A. Sneh, S. Darak, S. S. Ram, and M. Hanawal, "Radar Enhanced Multi-Armed Bandit for Rapid Beam Selection in Millimeter Wave Communications," *IEEE Communications Letters*, vol. 27, no. 9, pp. 2441–2445, Sep. 2023.
- [15] M. K. C. Shisher, B. Ji, I.-H. Hou, and Y. Sun, "Learning and Communications Co-Design for Remote Inference Systems: Feature Length Selection and Transmission Scheduling," *IEEE Journal on Selected Areas in Information Theory*, vol. 4, pp. 524–538, 2023.
- [16] W. R. Thompson, "On the Likelihood that One Unknown Probability Exceeds Another in View of the Evidence of Two Samples," *Biometrika*, vol. 25, no. 3/4, pp. 285–294, 1933.
- [17] J. C. Gittins, "Bandit Processes and Dynamic Allocation Indices," *Journal of the Royal Statistical Society: Series B (Methodological)*, vol. 41, no. 2, pp. 148–164, 1979.
- [18] J. C. Gittins and D. M. Jones, "A Dynamic Allocation Index for the Discounted Multiarmed Bandit Problem," *Biometrika*, vol. 66, no. 3, pp. 561–565, 1979.
- [19] P. Whittle, "Restless Bandits: Activity Allocation in a Changing World," *Journal of Applied Probability*, vol. 25, pp. 287–298, 1988.
- [20] D. B. Brown and J. E. Smith, "Index Policies and Performance Bounds for Dynamic Selection Problems," *Management Science*, vol. 66, no. 7, pp. 3029–3050, Jul. 2020.



Fig. 3. Average discounted return using the myopic, AWI0 policies and our AWI policies in different iteration step sizes when discount factor $\beta = 0.9$

- [21] M. Chen, K. Wu, and L. Song, "A Whittle Index Approach to Minimizing Age of Multi-Packet Information in IoT Network," *IEEE Access*, vol. 9, pp. 31467–31480, 2021.
- [22] R. R. Weber and G. Weiss, "On an index policy for restless bandits," *Journal of Applied Probability*, vol. 27, no. 3, pp. 637–648, Sep. 1990.
- [23] G. Zayas-Cabán, S. Jasin, and G. Wang, "An asymptotically optimal heuristic for general nonstationary finite-horizon restless multi-armed, multi-action bandits," *Advances in Applied Probability*, vol. 51, no. 3, pp. 745–772, Sep. 2019.
- [24] C. Papadimitriou and J. Tsitsiklis, "The complexity of optimal queueing network control," in *Proceedings of IEEE 9th Annual Conference on Structure in Complexity Theory*, Jun. 1994, pp. 318–322.
- [25] R. Xie, F. R. Yu, and H. Ji, "Spectrum sharing and resource allocation for energy-efficient heterogeneous cognitive radio networks with femtocells," in 2012 IEEE International Conference on Communications (ICC), Jun. 2012, pp. 1661–1665.
- [26] D. Lopez-Perez, X. Chu, A. V. Vasilakos, and H. Claussen, "Power Minimization Based Resource Allocation for Interference Mitigation in OFDMA Femtocell Networks," *IEEE Journal on Selected Areas in Communications*, vol. 32, no. 2, pp. 333–344, Feb. 2014.
- [27] K. Liu and Q. Zhao, "Distributed learning in cognitive radio networks: Multi-armed bandit with distributed multiple players," in 2010 IEEE International Conference on Acoustics, Speech and Signal Processing, Mar. 2010, pp. 3010–3013.
- [28] —, "Indexability of Restless Bandit Problems and Optimality of Whittle Index for Dynamic Multichannel Access," *IEEE Transactions* on Information Theory, vol. 56, no. 11, pp. 5547–5567, Nov. 2010.
- [29] Y. Gai and B. Krishnamachari, "Distributed Stochastic Online Learning Policies for Opportunistic Spectrum Access," *IEEE Transactions on Signal Processing*, vol. 62, no. 23, pp. 6184–6193, Dec. 2014.
- [30] H. M. Elmaghraby, K. Liu, and Z. Ding, "Femtocell Scheduling as a Restless Multiarmed Bandit Problem Using Partial Channel State Ob-

servation," in 2018 IEEE International Conference on Communications (ICC), May 2018, pp. 1-6.

- [31] E. J. Sondik, "The Optimal Control of Partially Observable Markov Processes Over the Infinite Horizon: Discounted Costs," *Operations Research*, vol. 26, no. 2, pp. 282–304, 1978.
- [32] K. Liu, R. Weber, and C. Zhang, "Low-Complexity Algorithm for Restless Bandits with Imperfect Observations," May 2024.
- [33] L. Zajíček, "An elementary proof of the one-dimensional Rademacher theorem," *Mathematica Bohemica*, vol. 117, no. 2, pp. 133–136, 1992.