OCRBench v2: An Improved Benchmark for Evaluating Large Multimodal Models on Visual Text Localization and Reasoning

Ling Fu¹, Biao Yang¹, Zhebin Kuang¹, Jiajun Song¹, Yuzhe Li¹, Linghao Zhu¹, Qidi Luo¹, Xinyu Wang², Hao Lu¹, Mingxin Huang³, Zhang Li¹, Guozhi Tang⁴, Bin Shan⁴, Chunhui Lin⁴, Qi Liu⁴, Binghong Wu⁴, Hao Feng⁴, Hao Liu⁴, Can Huang⁴, Jingqun Tang⁴, Wei Chen¹, Lianwen Jin³,

Yuliang Liu¹, Xiang Bai¹

¹Huazhong University of Science and Technology ²University of Adelaide ³South China University of Technology ⁴ByteDance

Abstract

Scoring the Optical Character Recognition (OCR) capabilities of Large Multimodal Models (LMMs) has witnessed growing interest recently. Existing benchmarks have highlighted the impressive performance of LMMs in text recognition; however, their abilities in certain challenging tasks, such as text localization, handwritten content extraction, and logical reasoning, remain underexplored. To bridge this gap, we introduce **OCRBench v2**, a large-scale bilingual text-centric benchmark with currently the most comprehensive set of tasks ($4 \times$ more tasks than the previous multiscene benchmark OCRBench), the widest coverage of scenarios (31 diverse scenarios including street scene, receipt, formula, diagram, and so on), and thorough evaluation metrics, with a total of 10,000 human-verified questionanswering pairs and a high proportion of difficult samples. After carefully benchmarking state-of-the-art LMMs on OCRBench v2, we find that 36 out of 38 LMMs score below 50 (100 in total) and suffer from five-type limitations, including less frequently encountered text recognition, finegrained perception, layout perception, complex element parsing, and logical reasoning. The benchmark and evaluation scripts are available at https://github.com/Yuliang-Liu/MultimodalOCR.

1. Introduction

The emergence of Large Language Models (LLMs) [1, 8, 101] has greatly improved the understanding and generation of structured text. However, in reality, much of the textual content is unstructured; it appears within images, videos, and other non-textual media in varied positions, orientations, and shapes. The need for processing such unstructured content leads to the study of Large Multimodal Models (LMMs) [5, 53, 139] that extend the text-only LLMs to



Text Localization

additional modalities. By pretraining on multimodal data, LMMs acquire the zero-shot ability to interpret across diverse media such as recognizing and understanding complex visual scene text [59]. Such capability represents a significant advancement over standard Optical Character Recognition (OCR), because LMMs not only spot text but also interpret its semantic relevance to a scene.



Figure 2. Overview of the eight testable text-reading capabilities and associated tasks in OCRBench v2. Each color represents a distinct capability type.

Compared with classic OCR that typically relies on taskspecific models to spot text, the increasing capability of LMMs to process and understand multimodal inputs has opened new potential to redefine the area of OCR. OCR has therefore become an important aspect of recent LMM evaluations. Some text-focused tasks have been included in standard benchmarks to assess the proficiency of LMMs in recognizing and interpreting textual content [26, 121]. Typically, text-based Visual Question Answering (VQA) datasets [7, 93, 107] are repurposed to evaluate OCR by framing generic VQA into questions that require accurate reading of embedded text. However, many of these textcentric datasets are initially created for classic OCR models, which is of limited diversity, depth, and suitability for evaluating LMMs. A common drawback is that, many questions lack sufficient complexity to assess the reasoning abilities of LMMs on scene text, and some can even be answered without visual input [10, 107].

More recently, several preliminary work [42, 46, 50, 58, 103] has attempted to explore the OCR capabilities of LMMs with customized benchmarks. For example, OCRBench [58] consolidates a range of common OCR tasks to evaluate LMM performance across traditional OCR functions. Other datasets, such as ComTQA [132] and ChartX [111], focus on structured text interpretation like table and chart understanding. While such effort represents a leap over standard OCR benchmarks, they remain limited in both data diversity and data quantity (see Table 1), which often leads to rapid performance saturation. For example, recent LMMs such as Qwen2-VL [105] have achieved 96.7%

Benchmark	#Scenario	#Task	#Image	#Instruction
OCRbench [58]	~ 14	5	0.9k	1k
Seed-bench-2-plus [46]	~ 8	1	0.6k	2.3k
CONTEXTUAL [103]	~ 11	1	0.5k	0.5k
Fox [50]	2	9	0.7k	2.2k
TableVQA-Bench [42]	1	3	0.9k	1.5k
MMTab-eval [134]	1	9	23k	49k
ComTQA [132]	1	4	1.6k	9k
ChartY [9]	1	1	6k	6k
ChartX [111]	1	7	6k	6k
MMC [51]	1	9	1.7k	2.9k
OCRBench v2 (Ours)	31	23	9.5k	10k

Table 1. Comparison between the proposed benchmark and existing text-centric datasets.

accuracy on the DocVQA dataset [71], nearly matching human performance at 98.1%, and 87.7% on OCRBench [58]. This raises an important question to the OCR community: *Have OCR tasks truly been solved in the LMM era, or do existing benchmarks fail to capture the broader challenges present in diverse environments?*

To answer the question above, we conducted preliminary tests with several state-of-the-art LMMs, including both open-source models such as Qwen2-VL-8B [105] and Monkey [48], and commercial models like GPT-40 [79]. These tests assessed performance on core OCR tasks, such as text localization, handwritten content extraction, and documentbased logical reasoning. As illustrated in Figure 1, each model can fail on one of text-intensive tasks. These failures reveal a gap in detailed visual perception across different models, which constrains their effectiveness in tasks requiring accurate text localization, recognition, and contextual understanding within images. Such observations suggest that existing OCR benchmarks may be insufficient to assess the capabilities and limitations of LMMs for practical OCR applications due to limited task diversity, contextual complexity, and scale.

To bridge this gap, we propose OCRBench v2, a comprehensive benchmark designed to assess LMMs across a diverse set of OCR tasks. As shown in Figure 2, OCR-Bench v2 assesses eight core text-reading abilities, including text recognition, text referring, text spotting, relation extraction, element parsing, mathematical calculation, visual text understanding, and knowledge reasoning, organized into a total of 23 concrete tasks. This benchmark provides 10,000 high-quality, human-validated instruction-response pairs and also six types of evaluation metrics, which offers a rigorous framework for evaluating LMM performance in complex, practical OCR scenarios. In summary, the contributions of this work are three-fold:

 OCRBench v2: an improved benchmark designed to evaluate the OCR capabilities within the context of LMMs. It assesses eight core OCR competencies and covers 23 tasks across 31 diverse scenarios ranging from scientific documents to natural scenes, which provides a thorough evaluation framework encapsulating fundamental and advanced text-centric challenges.

- We systematically evaluate 38 representative LMMs, ranging from commercial APIs to open-source models, which establishes broad baselines for OCR performance and enables a comparative understanding of model capabilities across varied OCR tasks.
- We provide a detailed analysis to identify factors affecting the OCR capabilities of LMMs and highlight key insights for improvement. The analysis examines performance across various dimensions such as model generalization to diverse text types, model robustness, and the ability to tackle complex visual-textual relation.

2. Related Work

We review work related to OCR-enhanced LMMs and benchmarks for text-centric LMMs.

OCR-Enhanced LMMs. Inspired by the success of LLMs, visual encoders are integrated into LLMs to create LMMs capable of processing both visual and textual information. Early LMMs exhibit strong zero-shot OCR capabilities, which motivates further exploration into textcentric LMMs. One pioneering approach, LLaVAR [131], enhances OCR abilities by training LLaVA [53] on textcentric datasets. mPLUG-DocOwl [118] constructs an instruction-tuning dataset with visual-text understanding to improve the model's performance. However, these early methods are restricted to low-res inputs, limiting their ability to recognize dense and small text. To address this limitation, attention has shifted to increasing the input resolution of LMMs. DocPedia [25] processes high-res images in the frequency domain without increasing the input sequence length. UReader [119] crops an image into multiple sub-images, thereby achieving fine-grained perception of high-res text. On the contrary, LayoutLLM [67] adopts the LayoutLMv3 [33] as the vision encoder to process the high-res images. As the resolution of inputs increases, so do the challenges related to computational efficiency. To tackle this issue, TextMonkey [59] proposes a Token Resampler to compress redundant visual feature tokens, while mPLUG-DocOwl 1.5 [31] introduces an H-Reducer to reduce the number of image tokens. As these models advance, they have achieved remarkable results on established benchmarks. Nevertheless, challenges remain unsolved in certain key areas such as text localization, entity extraction, and logical reasoning.

Benchmarks for Text-Centric LMMs. To evaluate LMMs, developing a comprehensive benchmark is essential. Previous effort has focused on creating scenario-specific benchmarks to assess LMMs in particular con-

texts. For example, DocVQA [71] is designed to evaluate the document comprehension abilities of LMMs, while ChartQA [69] is tailored to chart interpretation skills. Similarly, Infographics VQA [73] is dedicated to assessing the understanding of infographic images. Additionally, TextVQA [93] aims to evaluate text comprehension in realworld scenes. To further investigate the robustness of the model, some methods expand the scope of evaluation scenarios. OCRBench [58] introduces a holistic evaluation framework that covers five core OCR tasks. CONTEX-TUAL [103] is developed with context-sensitive instructions. SEED-Bench-2-Plus [46] encompasses a wide spectrum of text-rich images from various sources, including web content, maps, and charts. To provide a more thorough assessment, some benchmarks design multiple evaluation tasks within a specific scenario. TableVQA-Bench [42] first focuses on VQA tasks in the table domain. MMTab [134] and ComTOA [132] then extend the task scope, including table detection, structure recognition, and table querying. Moreover, ChartY [9], ChartX [111], and MMC [51] evaluate LMMs in chart understanding through tasks such as chart information extraction and reasoning. In this work, we focus on establishing a new benchmark called OCRBench v2, which contains more tasks than previous benchmarks and provides a systematic evaluation framework to reveal the limitations of LMMs in diverse text-rich environments.

3. OCRBench v2 Benchmark

In this section, we introduce *OCRBench v2* from four aspects, including task, annotation, statistics, and evaluation.

3.1. Task Description

To provide a comprehensive evaluation framework for textreading tasks, we categorize OCR capabilities into eight core areas, each encompassing specific sub-tasks that address various aspects of text comprehension and interpretation. Figure 3 demonstrates representative examples for each task, which showcases both visual inputs and corresponding instructions. Detailed descriptions of these core capabilities are as follows.

Text Recognition. This fundamental capability focuses on perceiving textual content. The related tasks include (fine-grained) text recognition and full-page OCR.

Text Referring. Determining the location of texts is necessary for real-world OCR applications. *OCRBench v2* evaluates this ability with text grounding and VQA with position tasks, requiring LMMs to localize text positions accurately.

Text Spotting. Text spotting is a widely studied OCR task that requires models to output both the location and content of text. We consider it a distinct capability due to this unique output format.

Relation Extraction. Given that texts are often densely



Figure 3. Sample visualizations for each task in OCRBench v2. The dataset provides a multilingual evaluation setting, comprising 23 sub-tasks grouped under 8 core OCR capabilities. Tasks marked with $\stackrel{\frown}{\Longrightarrow}$ contain both English and Chinese instructions, while other tasks are either English-only $\stackrel{\frown}{\sqsubseteq}$ or Chinese-only $\stackrel{\frown}{\frown}$ (Zoomed in for better clarity).

arranged in images, the ability to extract and map visual components is essential. This capability is assessed through key information extraction, key information mapping, and handwritten content extraction.

Element Parsing. Apart from text recognition, LMMs face the need of parsing complex elements for downstream applications. This ability is evaluated via table parsing, chart parsing, document parsing, and formula recognition.

Mathematical Calculation. Mathematical calculation abilities are essential for LMMs to address tasks that require numerical reasoning. Hence, text counting is introduced to assess the textual perception ability by counting the number of text instances. Additionally, we enhance the original math QA data by rendering textual questions into images, accompanied by geometric figures.

Visual Text Understanding. To tackle sophisticated tasks involving human interaction, LMMs need to comprehend semantic information of texts, a capability we term visual text understanding. This ability is evaluated by document classification and diagram QA. Additionally, we include basic VQA instructions where answers are located directly within the image, which refers to cognition VQA.

Knowledge Reasoning. Certain tasks require reasoning based on world knowledge and involve complex inference procedures, including science QA, APP agent interactions, ASCII art classification, and text translation. Further, we collect some complicated VQA instructions, where answers are not directly visible in images, termed reasoning VQA.

Due to space limitations, additional details for each subtask can be found in Appendix C.

3.2. Annotation Curation

In this section, we introduce annotation curation in three parts, including dataset collection, instruction formulation, and manual verification.

Dataset Collection. To curate diverse data for *OCRBench* v2, we manually harvest and screen 81 text-rich academic datasets. More details about the data sources can be found



Figure 4. The ratios of each type of tasks in OCRBench v2.

in Appendix B. To ensure diverse scenarios coverage, we also supplement them with additional private data. In all, our dataset comprises 31 typical scenarios¹, and the number of images in each scene is displayed in Table 9.

Instruction Formatting. To convert existing annotations into the LMM-compatible instruction format, we design specific prompts for each task. For complex tasks such as document parsing that require structured output, we include a format example to minimize the impact of instruction-following ability and focus the evaluation on OCR capabilities. Additionally, considering the distinct training strategies for localization tasks in LMMs, we standardize the coordinates by normalizing them with image sizes and by scaling to the range of [0, 1000]. Such a standardization is explicitly specified in the related prompts. For unlabeled data, we manually annotate them according to task requirements.

Manual Verification. To ensure data quality, we manually review all instructions and correct approximately 1% annotation errors.

3.3. Statistics of OCRBench v2

Here we present the statistics of *OCRBench v2*, including the proportion of eight task categories, the OCR-related statistics, and the measurement of prompt quality. More details on statistics can be found in Appendix D.

Capabilities Distribution. The proportion of eight capabilities in *OCRBench v2* is shown in Figure 4. The proportions across different categories are relatively balanced.

OCR-Related Statistics. We further count the distribution



(c) Statistics by Average OCR Lines of Capabilities Figure 5. **OCR-related statistics of OCRBench v2**.



Figure 6. Comparison of average entropy, type-token ratio, and variability index between OCRBench v2 and OCRBench.

of line-level OCR results of 7, 400 English and 2, 600 Chinese images in Figure 5(a) and Figure 5(b), respectively. The average number of line-level OCR results per category is shown in Figure 5(c). These statistics demonstrate that the text information is sufficiently rich in *OCRBench v2*.

Prompt Quality. We also compare the metrics of Average Entropy, Type-Token Ratio, and Average Variability Index of the questions between *OCRBench v2* and OCR-Bench in Figure 6. Compared with OCRBench, *OCRBench v2* shows greater Average Entropy, indicating higher unpredictability and diversity in its questions, which challenges the LMMs to tackle more diverse scenarios. It also exhibits a higher Type-Token Ratio, reflecting greater lexical variety and less redundancy in its question formulation. Additionally, the Average Variability Index of *OCRBench v2* is significantly higher, suggesting a wider range of question types and structures, offering a more thorough performance evaluation of LMMs.

¹The 31 scenarios include schematic diagrams, scientific papers, text image patches, filled tables, charts, receipts, question contexts, mathematical formulas, product labels, phone screenshots, indoor scenes, industry research reports, posters, street scenes, ASCII Art, shop signs, financial reports, chemical formulas, textbooks, magazines, emails, web screenshots, details page, verification code, resumes, illustrations, newspapers, road signs, menus, notify, and questionnaires.

Method	Recognition	Referring	Spotting	Extraction	Parsing	Calculation	Understandir	ng Reasoning	Average
			Ope	n-source LMN	Лs				
Qwen-VL [5]	34.6	7.5	0	18.2	20.0	8.1	57.2	41.1	23.3
Qwen-VL-chat [5]	34.5	4.1	0	25.9	14.0	13.8	55.7	39.5	23.4
Qwen2-VL-8B [105]	72.1	47.9	17.5	<u>82.5</u>	25.5	25.4	<u>78.4</u>	<u>61.5</u>	<u>51.4</u>
InternVL2-8B [13]	49.9	23.1	0.5	65.2	24.8	26.7	73.5	52.9	39.6
InternVL2-26B [13]	63.4	26.1	0	76.8	<u>37.8</u>	32.3	79.4	58.9	46.8
InternVL2.5-8B [12]	59.0	25.0	1.4	77.5	35.1	29.4	75.3	57.2	45.0
InternVL2.5-26B [12]	65.6	26.1	1.6	86.9	36.2	37.4	78.3	62.9	49.4
TextMonkey [59]	39.1	0.7	0	19.0	12.2	19.0	61.1	40.2	23.9
LLaVA-Next-8B [52]	41.3	18.8	0	49.5	21.2	17.3	55.2	48.9	31.5
Monkey [48]	35.2	0	0	16.6	16.3	14.4	59.8	42.3	23.1
XComposer2-4KHD [21]	45.1	21.8	0.1	15.9	11.7	15.7	66.8	45.9	27.9
Molmo-7B [17]	52.4	21.3	0.1	45.5	7.6	28.5	65.3	55.0	34.5
EMU2-chat [95]	42.1	0.2	0	12.5	8.1	11.2	42.7	33.4	18.8
mPLUG-Owl3 [120]	41.6	14.0	0.6	24.4	10.9	11.1	52.2	46.0	25.1
CogVLM-chat [106]	50.9	0	0	0.2	8.4	15.0	58.1	41.7	21.8
Deepseek-VL-7B [62]	37.1	15.4	0	23.5	14.6	20.8	53.3	52.9	27.2
GLM-4V-9B [28]	61.8	22.6	0	71.7	31.6	22.6	72.1	58.4	42.6
MiniCPM-V-2.6 [117]	66.8	6.0	0.8	62.0	28.8	32.4	73.7	52.1	40.3
TextHarmony [133]	25.8	2.5	0	1.8	8.5	10.4	46.1	33.1	16.0
VILA1.5-8B [60]	35.3	15.5	0	21.1	12.7	17.3	46.3	40.3	23.6
LLaVAR [131]	37.3	0	0	1.0	9.9	12.3	34.6	27.0	15.3
DocOwl2 [32]	24.0	9.7	0	13.4	13.5	8.8	53.7	32.0	19.4
UReader [119]	22.4	0.1	0	0	9.2	7.9	41.0	29.1	13.7
Yi-VL-6B [122]	28.9	2.9	0	9.7	12.9	15.8	36.1	32.0	17.3
Janus-1.3B [110]	46.1	0	0	0.2	14.5	13.5	36.0	39.1	18.7
Cambrian-1-8B [100]	45.3	21.5	0	53.6	19.2	19.5	63.5	55.5	34.7
LLaVA-OV-7B [47]	46.0	20.8	0.1	58.3	25.3	23.3	64.4	53.0	36.4
Eagle-X5-7B [92]	34.7	17.8	0	21.7	20.6	21.5	61.0	42.6	27.5
Idefics3-8B [44]	23.8	13.2	0	63.2	23.8	23.0	65.8	44.9	32.2
Ovis1.6-3B [66]	59.2	14.3	0	65.0	32.1	29.0	69.8	56.8	40.8
Pixtral-12B [2]	48.9	21.6	0	66.3	35.5	29.8	66.9	53.7	40.3
			Close	ed-source LM	Ms				
GLM-4V-Plus [28]	60.3	25.2	0	74.7	37.6	26.4	61.4	57.2	42.9
GPT-4V [78]	<u>69.7</u>	26.9	0.3	75.6	36.7	42.9	71.5	57.9	47.7
GPT-4o [1]	61.2	26.7	0	77.5	36.3	<u>43.4</u>	71.1	55.5	46.5
GPT-4o-mini [77]	57.9	23.3	0.6	70.8	31.5	38.8	65.9	55.1	43.0
Gemini-Pro [99]	61.2	<u>39.5</u>	<u>13.5</u>	79.3	39.2	47.7	75.5	59.3	51.9
Claude3.5-sonnet [3]	62.2	28.4	1.3	56.6	<u>37.8</u>	40.8	73.5	60.9	45.2
Step-1V [94]	67.8	31.3	7.2	73.6	37.2	27.8	69.8	58.6	46.7

Table 2. **Evaluation of existing LMMs on English subsets of OCRBench v2**. "Recognition" refers to text recognition, "Referring" to text referring, "Spotting" to text spotting, "Extraction" to relation extraction, "Parsing" to element parsing, "Calculation" to mathematical calculation, "Understanding" to visual text understanding, and "Reasoning" to knowledge reasoning. Higher values indicate better performance. Best performance is in boldface, and the second best is underlined. The notations apply to all subsequent figures.

3.4. Evaluation Criteria

Since *OCRBench v2* contains 23 distinct tasks, a single evaluation metric is inadequate. Therefore, we adopt six types of evaluation metrics tailored to specific task categories. In the following, we present an overview of the evaluation metrics and their applicability to specific tasks. More details can be found in Appendix E.

Parsing Type. To evaluate the element parsing ability of LMMs, we assess their performance in transforming input images into structured formats, including HTML, Markdown, and JSON. TEDS [138] is employed to measure the structural similarity between outputs and the desired format.

Localization Type. For text referring, the IoU score is applied to quantify the distance between the predicted regions and the ground truth.

Method	Recognition	Extraction	Parsing	Understanding	Reasoning	Average
		Open-sc	ource LMMs			
Qwen-VL [5]	7.2	5.3	10.7	11.5	11.2	9.2
Qwen-VL-chat [5]	9.5	8.2	9.3	11.0	21.1	11.8
Qwen2-VL-8B [105]	51.3	51.4	21.6	52.5	37.5	42.9
InternVL2-8B [13]	20.6	45.2	23.2	54.4	38.1	36.3
InternVL2-26B [13]	21.9	46.0	34.8	50.9	34.8	37.7
InternVL2.5-8B [12]	<u>52.8</u>	52.8	28.6	56.4	<u>40.5</u>	46.2
InternVL2.5-26B [12]	32.4	56.1	32.6	<u>56.3</u>	43.6	<u>44.2</u>
TextMonkey [59]	23.5	14.8	8.4	19.9	12.2	15.8
LLaVA-Next-8B [52]	5.7	2.9	12.2	7.5	17.2	9.1
Monkey [48]	4.6	11.2	8.4	21.5	20.0	13.1
XComposer2-4KHD [21]	16.7	18.8	12.1	27.5	2.3	15.5
Molmo-7B [17]	7.1	15.0	9.2	9.0	23.7	12.8
EMU2-chat [95]	2.3	0.5	8.5	1.0	7.3	3.9
mPLUG-Owl3 [120]	6.6	17.9	9.7	6.0	26.1	13.3
CogVLM-chat [106]	5.5	10.0	9.8	1.5	2.5	5.9
Deepseek-VL-7B [62]	8.0	13.3	15.7	5.5	18.5	12.2
GLM-4V-9B [28]	24.4	60.6	20.4	52.8	25.2	36.6
MiniCPM-V-2.6 [117]	51.0	29.9	21.2	34.0	33.6	33.9
TextHarmony [133]	1.8	4.5	8.2	1.5	11.9	5.6
VILA1.5-8B [60]	5.4	8.8	8.5	3.0	15.5	8.2
LLaVAR [131]	2.3	1.7	8.9	0	2.5	3.1
DocOwl2 [32]	4.2	10.3	8.6	4.0	9.6	7.3
UReader [119]	6.8	2.7	8.4	2.5	7.2	5.5
Yi-VL-6B [122]	4.8	4.4	8.5	4.0	25.0	9.4
Janus-1.3B [110]	7.6	8.7	11.4	4.5	10.7	8.6
Cambrian-1-8B [100]	5.3	14.9	12.6	8.5	8.1	9.9
LLaVA-OV-7B [47]	14.8	15.7	13.7	16.0	28.7	17.8
Eagle-X5-7B [92]	7.5	12.0	11.6	5.0	19.2	11.1
Idefics3-8B [44]	7.0	15.5	15.9	9.0	18.1	13.1
Ovis1.6-3B [66]	11.5	23.7	22.8	28.8	18.9	21.1
Pixtral-12B [2]	13.4	10.9	21.0	7.0	20.7	14.6
		Closed-s	ource LMMs			
GLM-4V-Plus [28]	34.5	60.6	23.9	49.8	28.2	39.4
GPT-4V [78]	49.9	52.2	34.6	40.8	22.9	40.1
GPT-40 [1]	21.6	53.0	29.8	38.5	18.2	32.2
GPT-4o-mini [77]	13.1	38.9	27.2	28.8	16.9	25.0
Gemini-Pro [99]	52.5	47.3	30.9	51.5	33.4	43.1
Claude3.5-sonnet [3]	21.0	56.2	<u>35.2</u>	55.0	30.5	39.6
Step-1V [94]	56.7	41.1	37.6	38.3	39.2	42.6

Table 3. Evaluation of existing LMMs on Chinese subsets of OCRBench v2.

Extraction Type. To evaluate relation extraction, we employ the F1 score to assess key information extraction and mapping. Since this evaluation requires structural extraction of information from the output of LMMs, the format is provided in the given prompt.

Long Reading Type. To assess performance on tasks involving long text reading, BLEU [80], METEOR [6], F1 score, and edit distance are used to assess the similarity between predicted text and ground truth.

Counting Type. In text counting, LMMs are required to

count the number of text instances. Thus, we use the L1 distance to measure the absolute difference between predicted and ground truth counts. The final score is then normalized to the range of [0, 1] based on the ground truth.

Basic VQA Type. To evaluate LMMs on general VQA cases, we employ task-specific metrics based on answer length and format. For questions where the original data provide options, we use exact string matching to compute accuracy. In other cases, we follow the approach of OCR-Bench to check whether the ground truth is contained in



Figure 7. Results of eight representative LMMs across the eight ability dimensions defined in OCRBench v2.

the prediction for short answers (fewer than 5 words) and employ ANLS to measure prediction quality for longer answers (5 words or more).

4. Results and Discussions

Here we first benchmark state-of-the-art LMMs on *OCR-Bench v2*, presenting the quantitative analysis of their OCR capabilities. We then investigate several critical factors influencing OCR performance, including the resolution setting of visual encoder, pre-provided OCR information, and the direct integration between OCR information and language models. Further, we summarize key findings of current limitations and challenges for LMMs. All results are presented as percentages.

4.1. Baselines

We evaluate a total of 31 open-source LMMs including InternVL series [12, 13], Qwen-VL series [5, 105], GLM-4v-9B [28], Monkey [48], TextMonkey [59], LLaVA-Next-8B [52], XComposer2-4KHD [21], EMU2-chat [95], mPLUG-Owl3 [120], CogVLM-chat [106], Deepseek-VL-7B [62], Molmo-7B [17], MiniCPM-V-2.6 [117], TextHarmony [133], VILA1.5-8B [60], LLaVAR [131], DocOwl2 [32], UReader [119], Yi-VL-6B [122], Janus-1.3B [110], Cambrian-1-8B [100], LLaVA-OV-7B [47], Eagle-X5-7B [92], Idefics3-8B [44], Ovis1.6-3B [66], and Pixtral-12B [2] with the publicly available checkpoints. Further, some cutting-edge commercial models are also tested, including GPT4V [78], GPT4o [79], GPT4omini [77], Gemini-Pro [99], Claude3.5-sonnet [3], GLM-4V-Plus [28], and Step-1V [94].

4.2. Main Results

The main evaluation results are shown in Table 2, Table 3, and Figure 7. We observe that, while current LMMs perform relatively well on some basic capabilities such as text recognition and visual text understanding, most LMMs achieve low scores in other capabilities, such as text spotting and element parsing, mostly below 50. In particular, some LMMs show significant limitations in text spotting capabilities, failing to precisely locate and recognize the texts. Additionally, LMMs demonstrate inadequate abilities in element parsing and mathematical calculation, which are crucial for complicated tasks like document analysis and mathematical reasoning. Besides, after comparing the performance of LMMs on visual text understanding and knowledge reasoning capabilities, we find that they perform poorly in knowledge reasoning, despite being provided with multiple-choice options. This suggests the deficiency of LMMs in logical reasoning.

4.3. Potential Factors Affecting OCR Capabilities

To provide additional insights, we also conduct experiments to explore the potential factors that may affect the performance of LMMs on *OCRBench v2*.

High-Res Visual Encoders. Since text often appears small in images, the resolution setting of the visual encoder could be a key factor affecting the text perception ability of LMMs [48]. Here we change the input resolution of the LMMs and observe the performance changes. In particular, InternVL2-8B is chosen, and the resolution setting includes 448, 896, and dynamic. Table 4 lists the results. Indeed, when the input resolution increases from 448 to 896, the performance increases by 4.1%.

Pre-provided OCR Information. To study the impact of OCR information, we use PaddleOCR² to pre-extract OCR results and incorporate them with prompts. Table 5 shows the results. We observe that adding OCR information does not help much. This suggests that *OCRBench v2* evaluates LMMs capabilities across multiple dimensions, rather than solely focusing on text recognition abilities.

Connection Between OCR and LLMs. We further explore a direct pipeline by first extracting OCR information and then by feeding it directly into Qwen2.5. Unlike LMMs, this pipeline separates OCR and language modeling into distinct stages. The results shown in Table 5 suggests that Qwen2VL-8B outperforms Qwen2.5 with OCR information, demonstrating LMMs' remarkable ability to incorporate both textual and visual features efficiently.

²https://github.com/PaddlePaddle/PaddleOCR

Method	Resolition	Recognition	Referring	Spotting	Extraction	Parsing	Calculation	Understandi	ng Reasoning	Average
	448	47.3	19.1	<u>0.1</u>	52.8	27.3	25.4	61.1	49.1	35.3
InternVL2-8B [13]	896	<u>48.7</u>	<u>23.0</u>	0.5	66.2	<u>26.2</u>	<u>25.9</u>	<u>73.2</u>	<u>51.9</u>	<u>39.4</u>
	dynamic	49.9	23.1	0.5	<u>65.2</u>	24.8	26.7	73.5	52.9	39.6

Table 4. Evaluation of InternVL2-8B with different resolution setting on the English subsets of OCRBench v2.

Method	Recognition	Referring	Spotting	Extraction	Parsing	Calculation	Understandir	ng Reasoning	Average
Qwen2VL-8B [105]	72.1	<u>47.9</u>	<u>17.5</u>	82.5	<u>25.5</u>	25.4	78.4	61.5	<u>51.4</u>
Qwen2VL-8B+OCR	<u>69.8</u>	50.4	20.1	<u>79.1</u>	29.4	28.0	77.7	<u>60.0</u>	51.8
Qwen2.5-8B+OCR	28.6	13.8	0	45.9	24.2	31.3	61.1	40.5	30.7

Table 5. Evaluation of Qwen2VL-8B and Qwen2.5-8B with pre-provided OCR information on English subsets of OCRBench v2.

4.4. Main Findings

Here we further highlight some interesting findings from the experimental results:

Finding 1. *Limited recognition on less frequently encountered texts.* Despite LMMs achieving high performance on text recognition, they can perform poorly when facing with less frequently encountered texts, such as dot matrix texts and mathematical formulas. This performance gap highlights the continuing challenges LMMs face in real-world text recognition.

Finding 2. Limited fine-grained spatial perception. Given that both closed- and open-source LMMs perform poorly in tasks such as text referring and text spotting in *OCRBench* v2, the current LMMs still lack the capability for accurate text localization.

Finding 3. Insufficient layout perception. While LMMs achieve good performance on basic text recognition, they struggle with complex layouts such as overlapping or rotated texts. For example, GPT-40 fails to detect all characters in overlapping handwritten text and misrecognizes numbers in 90° rotated images, revealing LMMs' limitations in handling texts with complex layouts.

Finding 4. Weak analytics for complex elements. When facing complex visual elements like charts and formulas, LMMs struggle to parse them into structured data formats, hindering their effectiveness in downstream applications such as document digitalization.

Finding 5. *Limited logical reasoning.* While LMMs demonstrate basic multimodal reasoning abilities, they struggle with complex scenarios involving mathematical problems or complicated textual reasoning, highlighting the room for improvement in their reasoning capabilities.

5. Conclusion

In this work, we introduce *OCRBench v2*, an improved benchmark for assessing the OCR capabilities of LMMs.

By studying 38 representative LMMs across 23 OCR tasks, we not only reveal some defects of the current LMMs but also explore factors affecting the OCR performance of LMMs. We hope *OCRBench v2* could facilitate future research on improving the OCR capabilities of LMMs.

Limitations. One challenge we encountered is that LMMs sometimes produce responses that deviate from the given instructions, making it difficult to extract the desired answers. In future work, we plan to develop a more objective assessment framework to address this issue.

Acknowledgements

We thank Max Tyrrell for providing valuable receipt images, which have significantly contributed to the development of *OCRBench v2*.

References

- [1] Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia Leoni Aleman, Diogo Almeida, Janko Altenschmidt, Sam Altman, Shyamal Anadkat, et al. Gpt-4 technical report. *arXiv preprint arXiv:2303.08774*, 2023. 1, 6, 7
- [2] Pravesh Agrawal, Szymon Antoniak, Emma Bou Hanna, Baptiste Bout, Devendra Chaplot, Jessica Chudnovsky, Diogo Costa, Baudouin De Monicault, Saurabh Garg, Theophile Gervet, et al. Pixtral 12b. arXiv preprint arXiv:2410.07073, 2024. 6, 7, 8
- [3] Anthropic. Claude 3.5 Sonnet. https://www. anthropic.com/news/claude-3-5-sonnet, 2024. Accessed: 2024-12-29. 6, 7, 8
- [4] Gilles Baechler, Srinivas Sunkara, Maria Wang, Fedir Zubach, Hassan Mansoor, Vincent Etter, Victor Cărbune, Jason Lin, Jindong Chen, and Abhanshu Sharma. Screenai: A vision-language model for ui and infographics understanding, 2024. 2
- [5] Jinze Bai, Shuai Bai, Shusheng Yang, Shijie Wang, Sinan Tan, Peng Wang, Junyang Lin, Chang Zhou, and Jingren Zhou. Qwen-vl: A frontier large vision-language model with versatile abilities. arXiv preprint arXiv:2308.12966, 2023. 1, 6, 7, 8

- [6] Satanjeev Banerjee and Alon Lavie. METEOR: An automatic metric for mt evaluation with improved correlation with human judgments. In *Proceedings of the ACL Workshop on Intrinsic and Extrinsic Evaluation Measures for Machine Translation and/or Summarization*, pages 65–72, 2005. 7, 5
- [7] Ali Furkan Biten, Ruben Tito, Andres Mafla, Lluis Gomez, Marçal Rusinol, Ernest Valveny, CV Jawahar, and Dimosthenis Karatzas. Scene text visual question answering. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, pages 4291–4301, 2019. 2
- [8] Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. Language models are few-shot learners. Advances in Neural Information Processing Systems, 2020. 1
- [9] Jinyue Chen, Lingyu Kong, Haoran Wei, Chenglong Liu, Zheng Ge, Liang Zhao, Jianjian Sun, Chunrui Han, and Xiangyu Zhang. Onechart: Purify the chart structural extraction via one auxiliary token. In *Proceedings of the ACM International Conference on Multimedia*, pages 147–155, 2024. 2, 3
- [10] Lin Chen, Jinsong Li, Xiaoyi Dong, Pan Zhang, Yuhang Zang, Zehui Chen, Haodong Duan, Jiaqi Wang, Yu Qiao, Dahua Lin, et al. Are We on the Right Way for Evaluating Large Vision-Language Models? arXiv preprint arXiv:2403.20330, 2024. 2
- [11] Xingyu Chen, Zihan Zhao, Lu Chen, Danyang Zhang, Jiabao Ji, Ao Luo, Yuxuan Xiong, and Kai Yu. Websrc: A dataset for web-based structural reading comprehension. arXiv preprint arXiv:2101.09465, 2021. 2
- [12] Zhe Chen, Weiyun Wang, Yue Cao, Yangzhou Liu, Zhangwei Gao, Erfei Cui, Jinguo Zhu, Shenglong Ye, Hao Tian, Zhaoyang Liu, et al. Expanding performance boundaries of open-source multimodal models with model, data, and testtime scaling. *arXiv preprint arXiv:2412.05271*, 2024. 6, 7, 8
- [13] Zhe Chen, Jiannan Wu, Wenhai Wang, Weijie Su, Guo Chen, Sen Xing, Muyan Zhong, Qinglong Zhang, Xizhou Zhu, Lewei Lu, et al. Internvl: Scaling up vision foundation models and aligning for generic visual-linguistic tasks. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 24185–24198, 2024. 6, 7, 8, 9
- [14] Hiuyi Cheng, Peirong Zhang, Sihang Wu, Jiaxin Zhang, Qiyuan Zhu, Zecheng Xie, Jing Li, Kai Ding, and Lianwen Jin. M⁶doc: A large-scale multi-format, multi-type, multilayout, multi-language, multi-annotation category dataset for modern document layout analysis, 2023. 2
- [15] Chee Kheng Ch'ng and Chee Seng Chan. Total-text: A comprehensive dataset for scene text detection and recognition. In *Proceedings of International Conference on Document Analysis and Recognition*, pages 935–942. IEEE, 2017. 1
- [16] Chee Kheng Chng, Yuliang Liu, Yipeng Sun, Chun Chet Ng, Canjie Luo, Zihan Ni, ChuanMing Fang, Shuaitao Zhang, Junyu Han, Errui Ding, et al. Icdar2019 robust read-

ing challenge on arbitrary-shaped text-rrc-art. In *Proceed*ings of International Conference on Document Analysis and *Recognition*, pages 1571–1576. IEEE, 2019. 2

- [17] Matt Deitke, Christopher Clark, Sangho Lee, Rohun Tripathi, Yue Yang, Jae Sung Park, Mohammadreza Salehi, Niklas Muennighoff, Kyle Lo, Luca Soldaini, et al. Molmo and pixmo: Open weights and open data for state-of-theart multimodal models. *arXiv preprint arXiv:2409.17146*, 2024. 6, 7, 8
- [18] Biplab Deka, Zifeng Huang, Chad Franzen, Joshua Hibschman, Daniel Afergan, Yang Li, Jeffrey Nichols, and Ranjitha Kumar. Rico: A mobile app dataset for building data-driven design applications. In *Proceedings of the* 30th annual ACM symposium on user interface software and technology, pages 845–854, 2017. 2
- [19] Markus Diem, Stefan Fiel, Florian Kleber, Robert Sablatnig, Jose M. Saavedra, David Contreras, Juan Manuel Barrios, and Luiz S. Oliveira. Proceedings of ieee international conference on frontiers in handwriting recognition. In 2014 14th International Conference on Frontiers in Handwriting Recognition, pages 779–784, 2014. 1
- [20] Longfei Ding, Mengbiao Zhao, Fei Yin, Shuiling Zeng, and Cheng-Lin Liu. A large-scale database for chemical structure recognition and preliminary evaluation. In *Proceedings of the International Conference on Pattern Recognition*, pages 1464–1470, 2022. 2
- [21] Xiaoyi Dong, Pan Zhang, Yuhang Zang, Yuhang Cao, Bin Wang, Linke Ouyang, Songyang Zhang, Haodong Duan, Wenwei Zhang, Yining Li, et al. Internlm-xcomposer2-4khd: A pioneering large vision-language model handling resolutions from 336 pixels to 4k hd. arXiv preprint arXiv:2404.06512, 2024. 6, 7, 8
- [22] Yongkun Du, Zhineng Chen, Caiyan Jia, Xiaoting Yin, Tianlun Zheng, Chenxia Li, Yuning Du, and Yu-Gang Jiang. SVTR: scene text recognition with a single visual model. In *Proceedings of the International Joint Conference on Artificial Intelligence*, pages 884–890. ijcai.org, 2022. 1
- [23] Shancheng Fang, Hongtao Xie, Yuxin Wang, Zhendong Mao, and Yongdong Zhang. Read like humans: Autonomous, bidirectional and iterative language modeling for scene text recognition. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 7098–7107, 2021. 1
- [24] Hao Feng, Wengang Zhou, Jiajun Deng, Yuechen Wang, and Houqiang Li. Geometric representation learning for document image rectification. In *Proceedings of European Conference on Computer Vision*, pages 475–492. Springer, 2022. 2
- [25] Hao Feng, Qi Liu, Hao Liu, Wengang Zhou, Houqiang Li, and Can Huang. Docpedia: Unleashing the power of large multimodal model in the frequency domain for versatile document understanding. arXiv preprint arXiv:2311.11810, 2023. 3
- [26] Chaoyou Fu, Peixian Chen, Yunhang Shen, Yulei Qin, Mengdan Zhang, Xu Lin, Jinrui Yang, Xiawu Zheng, Ke Li, Xing Sun, et al. MME: A comprehensive evaluation

benchmark for multimodal large language models. *arXiv* preprint arXiv:2306.13394, 2023. 2

- [27] Philippe Gervais, Asya Fadeeva, and Andrii Maksai. Mathwriting: A dataset for handwritten mathematical expression recognition. *CoRR*, abs/2404.10690, 2024. 2
- [28] Team GLM, Aohan Zeng, Bin Xu, Bowen Wang, Chenhui Zhang, Da Yin, Diego Rojas, Guanyu Feng, Hanlin Zhao, Hanyu Lai, et al. ChatGLM: A Family of Large Language Models from GLM-130B to GLM-4 All Tools. arXiv preprint arXiv:2406.12793, 2024. 6, 7, 8
- [29] Adam W Harley, Alex Ufkes, and Konstantinos G Derpanis. Evaluation of deep convolutional nets for document image classification and retrieval. In *Proceedings of International Conference on Document Analysis and Recognition*, 2015. 2
- [30] Mengchao He, Yuliang Liu, Zhibo Yang, Sheng Zhang, Canjie Luo, Feiyu Gao, Qi Zheng, Yongpan Wang, Xin Zhang, and Lianwen Jin. Icpr2018 contest on robust reading for multi-type web images. In *Proceedings of the International Conference on Pattern Recognition*, pages 7–12, 2018. 2
- [31] Anwen Hu, Haiyang Xu, Jiabo Ye, Ming Yan, Liang Zhang, Bo Zhang, Chen Li, Ji Zhang, Qin Jin, Fei Huang, et al. mplug-docowl 1.5: Unified structure learning for ocr-free document understanding. arXiv preprint arXiv:2403.12895, 2024. 3
- [32] Anwen Hu, Haiyang Xu, Liang Zhang, Jiabo Ye, Ming Yan, Ji Zhang, Qin Jin, Fei Huang, and Jingren Zhou. mplug-docowl2: High-resolution compressing for ocrfree multi-page document understanding. arXiv preprint arXiv:2409.03420, 2024. 6, 7, 8
- [33] Yupan Huang, Tengchao Lv, Lei Cui, Yutong Lu, and Furu Wei. Layoutlmv3: Pre-training for document ai with unified text and image masking. In *Proceedings of the ACM International Conference on Multimedia*, pages 4083–4091, 2022. 3
- [34] Zheng Huang, Kai Chen, Jianhua He, Xiang Bai, Dimosthenis Karatzas, Shijian Lu, and CV Jawahar. Icdar2019 competition on scanned receipt ocr and information extraction. In *Proceedings of International Conference on Document Analysis and Recognition*, pages 1516–1520. IEEE, 2019. 2
- [35] Guillaume Jaume, Hazim Kemal Ekenel, and Jean-Philippe Thiran. Funsd: A dataset for form understanding in noisy scanned documents. In *Proceedings of International Conference on Document Analysis and Recognition Workshops*, pages 1–6. IEEE, 2019. 2
- [36] Qi Jia, Xiang Yue, Shanshan Huang, Ziheng Qin, Yizhu Liu, Bill Yuchen Lin, and Yang You. Visual perception in text strings. *arXiv preprint arXiv:2410.01733*, 2024. 2, 3
- [37] Kushal Kafle, Scott Cohen, Brian Price, and Christopher Kanan. Dvqa: Understanding data visualizations via question answering. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, 2018. 2
- [38] Dimosthenis Karatzas, Faisal Shafait, Seiichi Uchida, Masakazu Iwamura, Lluis Gomez i Bigorda, Sergi Robles

Mestre, Joan Mas, David Fernandez Mota, Jon Almazàn Almazàn, and Lluís Pere de las Heras. Icdar 2013 robust reading competition. In *Proceedings of International Conference on Document Analysis and Recognition*, pages 1484–1493, 2013. 1

- [39] Dimosthenis Karatzas, Lluis Gomez-Bigorda, Anguelos Nicolaou, Suman Ghosh, Andrew Bagdanov, Masakazu Iwamura, Jiri Matas, Lukas Neumann, Vijay Ramaseshan Chandrasekhar, Shijian Lu, et al. Icdar 2015 competition on robust reading. In *Proceedings of International Conference* on Document Analysis and Recognition, pages 1156–1160. IEEE, 2015. 1
- [40] Aniruddha Kembhavi, Mike Salvato, Eric Kolve, Minjoon Seo, Hannaneh Hajishirzi, and Ali Farhadi. A diagram is worth a dozen images. In *Proceedings of European Conference on Computer Vision*, pages 235–251. Springer, 2016. 2
- [41] Aniruddha Kembhavi, Minjoon Seo, Dustin Schwenk, Jonghyun Choi, Ali Farhadi, and Hannaneh Hajishirzi. Are you smarter than a sixth grader? textbook question answering for multimodal machine comprehension. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, pages 4999–5007, 2017. 2
- [42] Yoonsik Kim, Moonbin Yim, and Ka Yeon Song. TableVQA-Bench: A visual question answering benchmark on multiple table domains. arXiv preprint arXiv:2404.19205, 2024. 2, 3
- [43] Jianfeng Kuang, Wei Hua, Dingkang Liang, Mingkun Yang, Deqiang Jiang, Bo Ren, and Xiang Bai. Visual information extraction in the wild: practical dataset and endto-end solution. In *Proceedings of International Conference on Document Analysis and Recognition*, pages 36–53. Springer, 2023. 2
- [44] Hugo Laurençon, Andrés Marafioti, Victor Sanh, and Léo Tronchon. Building and better understanding visionlanguage models: insights and future directions. In Workshop on Responsibly Building the Next Generation of Multimodal Foundational Models, 2024. 6, 7, 8
- [45] Sangmin Lee, Bolin Lai, Fiona Ryan, Bikram Boote, and James M Rehg. Modeling multimodal social interactions: New challenges and baselines with densely aligned representations. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, pages 14585– 14595, 2024. 2
- [46] Bohao Li, Yuying Ge, Yi Chen, Yixiao Ge, Ruimao Zhang, and Ying Shan. Seed-bench-2-plus: Benchmarking multimodal large language models with text-rich visual comprehension. arXiv preprint arXiv:2404.16790, 2024. 2, 3
- [47] Bo Li, Yuanhan Zhang, Dong Guo, Renrui Zhang, Feng Li, Hao Zhang, Kaichen Zhang, Yanwei Li, Ziwei Liu, and Chunyuan Li. Llava-onevision: Easy visual task transfer. arXiv preprint arXiv:2408.03326, 2024. 6, 7, 8
- [48] Zhang Li, Biao Yang, Qiang Liu, Zhiyin Ma, Shuo Zhang, Jingxu Yang, Yabo Sun, Yuliang Liu, and Xiang Bai. Monkey: Image resolution and text label are important things for large multi-modal models. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 26763–26773, 2024. 2, 6, 7, 8

- [49] Yupu Liang, Yaping Zhang, Cong Ma, Zhiyang Zhang, Yang Zhao, Lu Xiang, Chengqing Zong, and Yu Zhou. Document image machine translation with dynamic multipre-trained models assembling. In *Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 7077–7088, 2024. 2
- [50] Chenglong Liu, Haoran Wei, Jinyue Chen, Lingyu Kong, Zheng Ge, Zining Zhu, Liang Zhao, Jianjian Sun, Chunrui Han, and Xiangyu Zhang. Focus Anywhere for Fine-grained Multi-page Document Understanding. arXiv preprint arXiv:2405.14295, 2024. 2, 1, 3
- [51] Fuxiao Liu, Xiaoyang Wang, Wenlin Yao, Jianshu Chen, Kaiqiang Song, Sangwoo Cho, Yaser Yacoob, and Dong Yu. MMC: Advancing Multimodal Chart Understanding with Large-scale Instruction Tuning. In Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, pages 1287–1310, 2024. 2, 3
- [52] Haotian Liu, Chunyuan Li, Yuheng Li, Bo Li, Yuanhan Zhang, Sheng Shen, and Yong Jae Lee. Llava-next: Improved reasoning, ocr, and world knowledge, 2024. 6, 7, 8
- [53] Haotian Liu, Chunyuan Li, Qingyang Wu, and Yong Jae Lee. Visual instruction tuning. Advances in Neural Information Processing Systems, 36, 2024. 1, 3
- [54] Xi Liu, Rui Zhang, Yongsheng Zhou, Qianyi Jiang, Qi Song, Nan Li, Kai Zhou, Lei Wang, Dong Wang, Minghui Liao, Mingkun Yang, Xiang Bai, Baoguang Shi, Dimosthenis Karatzas, Shijian Lu, and C. V. Jawahar. Icdar 2019 robust reading challenge on reading chinese text on signboard, 2019. 2
- [55] Yuliang Liu, Lianwen Jin, Shuaitao Zhang, Canjie Luo, and Sheng Zhang. Curved scene text detection via transverse and longitudinal sequence connection. *Pattern Recognition*, 90(C):337–345, 2019. 1
- [56] Yuliang Liu, Hao Chen, Chunhua Shen, Tong He, Lianwen Jin, and Liangwei Wang. Abcnet: Real-time scene text spotting with adaptive bezier-curve network. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, pages 9809–9818, 2020. 1
- [57] Yuliang Liu, Chunhua Shen, Lianwen Jin, Tong He, Peng Chen, Chongyu Liu, and Hao Chen. Abcnet v2: Adaptive bezier-curve network for real-time end-to-end text spotting. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 44(11):8048–8064, 2021. 1
- [58] Yuliang Liu, Zhang Li, Biao Yang, Chunyuan Li, Xucheng Yin, Cheng-lin Liu, Lianwen Jin, and Xiang Bai. On the hidden mystery of ocr in large multimodal models. arXiv preprint arXiv:2305.07895, 2023. 2, 3, 1
- [59] Yuliang Liu, Biao Yang, Qiang Liu, Zhang Li, Zhiyin Ma, Shuo Zhang, and Xiang Bai. Textmonkey: An ocr-free large multimodal model for understanding document. *arXiv* preprint arXiv:2403.04473, 2024. 1, 3, 6, 7, 8
- [60] Zhijian Liu, Ligeng Zhu, Baifeng Shi, Zhuoyang Zhang, Yuming Lou, Shang Yang, Haocheng Xi, Shiyi Cao, Yuxian Gu, Dacheng Li, et al. Nvila: Efficient frontier visual

language models. *arXiv preprint arXiv:2412.04468*, 2024. 6, 7, 8

- [61] Shangbang Long, Siyang Qin, Dmitry Panteleev, Alessandro Bissacco, Yasuhisa Fujii, and Michalis Raptis. Towards end-to-end unified scene text detection and layout analysis. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, pages 1049–1059, 2022. 2
- [62] Haoyu Lu, Wen Liu, Bo Zhang, Bingxuan Wang, Kai Dong, Bo Liu, Jingxiang Sun, Tongzheng Ren, Zhuoshu Li, Hao Yang, et al. Deepseek-vl: towards real-world visionlanguage understanding. *arXiv preprint arXiv:2403.05525*, 2024. 6, 7, 8
- [63] Ning Lu, Wenwen Yu, Xianbiao Qi, Yihao Chen, Ping Gong, Rong Xiao, and Xiang Bai. Master: Multi-aspect non-local network for scene text recognition. *Pattern Recognition*, 117:107980, 2021. 1
- [64] Pan Lu, Swaroop Mishra, Tanglin Xia, Liang Qiu, Kai-Wei Chang, Song-Chun Zhu, Oyvind Tafjord, Peter Clark, and Ashwin Kalyan. Learn to explain: Multimodal reasoning via thought chains for science question answering. *Advances in Neural Information Processing Systems*, 35: 2507–2521, 2022. 2
- [65] Pan Lu, Hritik Bansal, Tony Xia, Jiacheng Liu, Chunyuan Li, Hannaneh Hajishirzi, Hao Cheng, Kai-Wei Chang, Michel Galley, and Jianfeng Gao. Mathvista: Evaluating mathematical reasoning of foundation models in visual contexts. In *Proceedings of the International Conference on Learning Representations*. OpenReview.net, 2024. 2
- [66] Shiyin Lu, Yang Li, Qing-Guo Chen, Zhao Xu, Weihua Luo, Kaifu Zhang, and Han-Jia Ye. Ovis: Structural embedding alignment for multimodal large language model. arXiv preprint arXiv:2405.20797, 2024. 6, 7, 8
- [67] Chuwei Luo, Yufan Shen, Zhaoqing Zhu, Qi Zheng, Zhi Yu, and Cong Yao. LayoutLLM: Layout Instruction Tuning with Large Language Models for Document Understanding. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, pages 15630–15640, 2024. 3
- [68] U-V Marti and Horst Bunke. The iam-database: an english sentence database for offline handwriting recognition. *International Journal on Document Analysis and Recognition*, 5:39–46, 2002. 1
- [69] Ahmed Masry, Do Xuan Long, Jia Qing Tan, Shafiq Joty, and Enamul Hoque. Chartqa: A benchmark for question answering about charts with visual and logical reasoning. arXiv preprint arXiv:2203.10244, 2022. 3, 2
- [70] Minesh Mathew, Viraj Bagal, Rubèn Pérez Tito, Dimosthenis Karatzas, Ernest Valveny, and C. V. Jawahar. Infographicvqa. *CoRR*, abs/2104.12756, 2021. 2
- [71] Minesh Mathew, Dimosthenis Karatzas, and CV Jawahar. Docvqa: A dataset for vqa on document images. In Proceedings of the IEEE Winter Conference on Applications of Computer Vision, pages 2200–2209, 2021. 2, 3
- [72] Minesh Mathew, Dimosthenis Karatzas, and C. V. Jawahar. Docvqa: A dataset for VQA on document images. In *Proceedings of the IEEE Winter Conference on Applications of Computer Vision*, pages 2199–2208. IEEE, 2021. 2

- [73] Minesh Mathew, Viraj Bagal, Rubèn Tito, Dimosthenis Karatzas, Ernest Valveny, and CV Jawahar. Infographicvqa. In Proceedings of the IEEE Winter Conference on Applications of Computer Vision, pages 1697–1706, 2022. 3
- [74] Nitesh Methani, Pritha Ganguly, Mitesh M. Khapra, and Pratyush Kumar. Plotqa: Reasoning over scientific plots. In Proceedings of the IEEE Winter Conference on Applications of Computer Vision, 2020. 2
- [75] A. Mishra, K. Alahari, and C. V. Jawahar. Scene text recognition using higher order language priors. In *British Machine Vision Conference*, 2012. 1
- [76] Anand Mishra, Shashank Shekhar, Ajeet Kumar Singh, and Anirban Chakraborty. Ocr-vqa: Visual question answering by reading text in images. In *Proceedings of International Conference on Document Analysis and Recognition*, pages 947–952. IEEE, 2019. 2
- [77] OpenAI. GPT-40 mini: advancing cost-efficient intelligence. https://openai.com/index/ gpt-40-mini-advancing-cost-efficientintelligence, 2024. Accessed: 2024-12-29. 6, 7, 8
- [78] OpenAI. GPT-4V(ision) system card. https:// openai.com/index/gpt-4v-system-card, 2024. Accessed: 2024-12-29. 6, 7, 8, 1
- [79] OpenAI. Hello GPT-40. https://openai.com/ index/gpt-4v-system-card, 2024. Accessed: 2024-12-29. 2, 8
- [80] Kishore Papineni, Salim Roukos, Todd Ward, and Wei-Jing Zhu. Bleu: a method for automatic evaluation of machine translation. In *Proceedings of Annual Meeting of the Association for Computational Linguistics*, pages 311–318, 2002. 7, 5
- [81] Seunghyun Park, Seung Shin, Bado Lee, Junyeop Lee, Jaeheung Surh, Minjoon Seo, and Hwalsuk Lee. Cord: a consolidated receipt dataset for post-ocr parsing. In Advances in Neural Information Processing Systems Workshop, 2019.
- [82] Panupong Pasupat and Percy Liang. Compositional semantic parsing on semi-structured tables. In *Proceedings of Annual Meeting of the Association for Computational Linguistics*, pages 1470–1480, Beijing, China, 2015. Association for Computational Linguistics. 2
- [83] Trung Quy Phan, Palaiahnakote Shivakumara, Shangxuan Tian, and Chew Lim Tan. Recognizing text with perspective distortion in natural scenes. In *Proceedings of IEEE/CVF International Conference on Computer Vision*, pages 569– 576. IEEE Computer Society, 2013. 1
- [84] Anhar Risnumawan, Palaiahnakote Shivakumara, Chee Seng Chan, and Chew Lim Tan. A robust arbitrary text detection system for natural scene images. *Expert Systems with Applications*, 41:8027–8048, 2014. 1
- [85] Long Rujiao, Wang Wen, Xue Nan, Gao Feiyu, Yang Zhibo, Wang Yongpan, and Xia Gui-Song. Parsing table structures in the wild. In *Proceedings of IEEE/CVF International Conference on Computer Vision*, 2021. 2
- [86] David Saxton, Edward Grefenstette, Felix Hill, and Pushmeet Kohli. Analysing mathematical reasoning abilities of neural models. In *Proceedings of the International Confer-*

ence on Learning Representations. OpenReview.net, 2019.

- [87] Baoguang Shi, Xiang Bai, and Cong Yao. An end-to-end trainable neural network for image-based sequence recognition and its application to scene text recognition. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 39(11):2298–2304, 2016. 1
- [88] Baoguang Shi, Cong Yao, Minghui Liao, Mingkun Yang, Pei Xu, Linyan Cui, Serge Belongie, Shijian Lu, and Xiang Bai. Icdar2017 competition on reading chinese text in the wild (rctw-17). In *Proceedings of International Conference on Document Analysis and Recognition*, pages 1429–1434. IEEE, 2017. 2
- [89] Baoguang Shi, Mingkun Yang, Xinggang Wang, Pengyuan Lyu, Cong Yao, and Xiang Bai. Aster: An attentional scene text recognizer with flexible rectification. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 41(9): 2035–2048, 2018. 1
- [90] Baoguang Shi, Cong Yao, Minghui Liao, Mingkun Yang, Pei Xu, Linyan Cui, Serge Belongie, Shijian Lu, and Xiang Bai. Icdar2017 competition on reading chinese text in the wild (rctw-17), 2018. 2
- [91] Cunzhao Shi, Chunheng Wang, Baihua Xiao, Song Gao, and Jinlong Hu. End-to-end scene text recognition using tree-structured models. *Pattern Recognition*, 47:2853– 2866, 2014. 1
- [92] Min Shi, Fuxiao Liu, Shihao Wang, Shijia Liao, Subhashree Radhakrishnan, De-An Huang, Hongxu Yin, Karan Sapra, Yaser Yacoob, Humphrey Shi, et al. Eagle: Exploring the design space for multimodal llms with mixture of encoders. arXiv preprint arXiv:2408.15998, 2024. 6, 7, 8
- [93] Amanpreet Singh, Vivek Natarajan, Meet Shah, Yu Jiang, Xinlei Chen, Dhruv Batra, Devi Parikh, and Marcus Rohrbach. Towards vqa models that can read. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, pages 8317–8326, 2019. 2, 3
- [94] StepFun. Step-1V. https://www.stepfun.com/ #step1v, 2024. Accessed: 2024-12-29. 6, 7, 8, 1
- [95] Quan Sun, Yufeng Cui, Xiaosong Zhang, Fan Zhang, Qiying Yu, Yueze Wang, Yongming Rao, Jingjing Liu, Tiejun Huang, and Xinlong Wang. Generative multimodal models are in-context learners. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, pages 14398–14409, 2024. 6, 7, 8
- [96] Yipeng Sun, Jiaming Liu, Wei Liu, Junyu Han, Errui Ding, and Jingtuo Liu. Chinese street view text: Large-scale chinese text reading with partially supervised learning, 2020.2
- [97] Ryota Tanaka, Kyosuke Nishida, Kosuke Nishida, Taku Hasegawa, Itsumi Saito, and Kuniko Saito. Slidevqa: A dataset for document visual question answering on multiple images. In *Proceedings of the AAAI Conference on Artificial Intelligence*, 2023. 2
- [98] Jun Tang, Zhibo Yang, Yongpan Wang, Qi Zheng, Yongchao Xu, and Xiang Bai. Seglink++: Detecting dense and arbitrary-shaped scene text by instance-aware component grouping. *Pattern Recognition*, 96:106954, 2019. 2

- [99] Gemini Team, Rohan Anil, Sebastian Borgeaud, Jean-Baptiste Alayrac, Jiahui Yu, Radu Soricut, Johan Schalkwyk, Andrew M Dai, Anja Hauth, Katie Millican, et al. Gemini: a family of highly capable multimodal models. arXiv preprint arXiv:2312.11805, 2023. 6, 7, 8, 1
- [100] Shengbang Tong, Ellis L Brown II, Penghao Wu, Sanghyun Woo, ADITHYA JAIRAM IYER, Sai Charitha Akula, Shusheng Yang, Jihan Yang, Manoj Middepogu, Ziteng Wang, et al. Cambrian-1: A fully open, vision-centric exploration of multimodal llms. In Advances in Neural Information Processing Systems, 2024. 6, 7, 8
- [101] Hugo Touvron, Thibaut Lavril, Gautier Izacard, Xavier Martinet, Marie-Anne Lachaux, Timothée Lacroix, Baptiste Rozière, Naman Goyal, Eric Hambro, Faisal Azhar, et al. Llama: Open and efficient foundation language models. arXiv preprint arXiv:2302.13971, 2023. 1
- [102] Andreas Veit, Tomas Matera, Lukas Neumann, Jiri Matas, and Serge Belongie. Coco-text: Dataset and benchmark for text detection and recognition in natural images. arXiv preprint arXiv:1601.07140, 2016. 1
- [103] Rohan Wadhawan, Hritik Bansal, Kai-Wei Chang, and Nanyun Peng. ConTextual: Evaluating Context-Sensitive Text-Rich Visual Reasoning in Large Multimodal Models. In Proceedings of International Conference on Machine Learning, 2024. 2, 3
- [104] Ke Wang, Junting Pan, Weikang Shi, Zimu Lu, Mingjie Zhan, and Hongsheng Li. Measuring multimodal mathematical reasoning with math-vision dataset. *CoRR*, abs/2402.14804, 2024. 2
- [105] Peng Wang, Shuai Bai, Sinan Tan, Shijie Wang, Zhihao Fan, Jinze Bai, Keqin Chen, Xuejing Liu, Jialin Wang, Wenbin Ge, et al. Qwen2-vl: Enhancing vision-language model's perception of the world at any resolution. arXiv preprint arXiv:2409.12191, 2024. 2, 6, 7, 8, 9, 1
- [106] Weihan Wang, Qingsong Lv, Wenmeng Yu, Wenyi Hong, Ji Qi, Yan Wang, Junhui Ji, Zhuoyi Yang, Lei Zhao, Xixuan Song, et al. Cogvlm: Visual expert for pretrained language models. arXiv preprint arXiv:2311.03079, 2023. 6, 7, 8
- [107] Xinyu Wang, Yuliang Liu, Chunhua Shen, Chun Chet Ng, Canjie Luo, Lianwen Jin, Chee Seng Chan, Anton van den Hengel, and Liangwei Wang. On the general value of evidence, and bilingual scene-text visual question answering. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 10126–10135, 2020. 2
- [108] Yuxin Wang, Hongtao Xie, Shancheng Fang, Jing Wang, Shenggao Zhu, and Yongdong Zhang. From two to one: A new scene text recognizer with visual language modeling network. In *Proceedings of IEEE/CVF International Conference on Computer Vision*, pages 14194–14203, 2021. 1
- [109] Haoran Wei, Chenglong Liu, Jinyue Chen, Jia Wang, Lingyu Kong, Yanming Xu, Zheng Ge, Liang Zhao, Jianjian Sun, Yuang Peng, et al. General ocr theory: Towards ocr-2.0 via a unified end-to-end model. arXiv preprint arXiv:2409.01704, 2024. 1
- [110] Chengyue Wu, Xiaokang Chen, Zhiyu Wu, Yiyang Ma, Xingchao Liu, Zizheng Pan, Wen Liu, Zhenda Xie, Xingkai

Yu, Chong Ruan, et al. Janus: Decoupling visual encoding for unified multimodal understanding and generation. *arXiv preprint arXiv:2410.13848*, 2024. 6, 7, 8

- [111] Renqiu Xia, Bo Zhang, Hancheng Ye, Xiangchao Yan, Qi Liu, Hongbin Zhou, Zijun Chen, Min Dou, Botian Shi, Junchi Yan, et al. Chartx & chartvlm: A versatile benchmark and foundation model for complicated chart reasoning. arXiv preprint arXiv:2402.12185, 2024. 2, 3
- [112] Xudong Xie, Ling Fu, Zhifei Zhang, Zhaowen Wang, and Xiang Bai. Toward understanding wordart: Corner-guided transformer for scene text recognition. In *Proceedings of European Conference on Computer Vision*, pages 303–321, Cham, 2022. Springer Nature Switzerland. 1
- [113] Yiheng Xu, Tengchao Lv, Lei Cui, Guoxin Wang, Yijuan Lu, Dinei Florencio, Cha Zhang, and Furu Wei. XFUND: A benchmark dataset for multilingual visually rich form understanding. In *Proceedings of Annual Meeting of the Association for Computational Linguistics*, pages 3214–3224, Dublin, Ireland, 2022. Association for Computational Linguistics. 2
- [114] Fan Yang, Lei Hu, Xinwu Liu, Shuangping Huang, and Zhenghui Gu. A large-scale dataset for end-to-end table recognition in the wild. *Scientific Data*, 10(1):110, 2023. 2
- [115] Wentao Yang, Zhe Li, Dezhi Peng, Lianwen Jin, Mengchao He, and Cong Yao. Read ten lines at one glance: Lineaware semi-autoregressive transformer for multi-line handwritten mathematical expression recognition. In *Proceedings of the ACM International Conference on Multimedia*, pages 2066–2077. ACM, 2023. 2
- [116] Cong Yao, Xiang Bai, Wenyu Liu, Yi Ma, and Zhuowen Tu. Detecting texts of arbitrary orientations in natural images. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 1083–1090. IEEE, 2012. 2
- [117] Yuan Yao, Tianyu Yu, Ao Zhang, Chongyi Wang, Junbo Cui, Hongji Zhu, Tianchi Cai, Haoyu Li, Weilin Zhao, Zhihui He, et al. Minicpm-v: A gpt-4v level mllm on your phone. arXiv preprint arXiv:2408.01800, 2024. 6, 7, 8
- [118] Jiabo Ye, Anwen Hu, Haiyang Xu, Qinghao Ye, Ming Yan, Yuhao Dan, Chenlin Zhao, Guohai Xu, Chenliang Li, Junfeng Tian, et al. mplug-docowl: Modularized multimodal large language model for document understanding. arXiv preprint arXiv:2307.02499, 2023. 3
- [119] Jiabo Ye, Anwen Hu, Haiyang Xu, Qinghao Ye, Ming Yan, Guohai Xu, Chenliang Li, Junfeng Tian, Qi Qian, Ji Zhang, et al. Ureader: Universal ocr-free visually-situated language understanding with multimodal large language model. *arXiv preprint arXiv:2310.05126*, 2023. 3, 6, 7, 8
- [120] Jiabo Ye, Haiyang Xu, Haowei Liu, Anwen Hu, Ming Yan, Qi Qian, Ji Zhang, Fei Huang, and Jingren Zhou. mplug-owl3: Towards long image-sequence understanding in multi-modal large language models. arXiv preprint arXiv:2408.04840, 2024. 6, 7, 8
- [121] Kaining Ying, Fanqing Meng, Jin Wang, Zhiqian Li, Han Lin, Yue Yang, Hao Zhang, Wenbo Zhang, Yuqi Lin, Shuo Liu, et al. Mmt-bench: A comprehensive multimodal

benchmark for evaluating large vision-language models towards multitask agi. *arXiv preprint arXiv:2404.16006*, 2024. 2

- [122] Alex Young, Bei Chen, Chao Li, Chengen Huang, Ge Zhang, Guanwei Zhang, Heng Li, Jiangcheng Zhu, Jianqun Chen, Jing Chang, et al. Yi: Open foundation models by 01. ai. arXiv preprint arXiv:2403.04652, 2024. 6, 7, 8
- [123] Wenwen Yu, Chengquan Zhang, Haoyu Cao, Wei Hua, Bohan Li, Huang Chen, Mingyu Liu, Mingrui Chen, Jianfeng Kuang, Mengjun Cheng, Yuning Du, Shikun Feng, Xiaoguang Hu, Pengyuan Lyu, Kun Yao, Yuechen Yu, Yuliang Liu, Wanxiang Che, Errui Ding, Cheng-Lin Liu, Jiebo Luo, Shuicheng Yan, Min Zhang, Dimosthenis Karatzas, Xing Sun, Jingdong Wang, and Xiang Bai. Icdar 2023 competition on structured text extraction from visually-rich document images, 2023. 2
- [124] Tai-Ling Yuan, Zhe Zhu, Kun Xu, Cheng-Jun Li, Tai-Jiang Mu, and Shi-Min Hu. A large chinese text dataset in the wild. *Journal of Computer Science and Technology*, 34(3): 509–521, 2019. 2
- [125] Ye Yuan, Xiao Liu, Wondimu Dikubab, Hui Liu, Zhilong Ji, Zhongqin Wu, and Xiang Bai. Syntax-aware network for handwritten mathematical expression recognition. arXiv preprint arXiv:2203.01601, 2022. 2
- [126] Xiang Yue, Tianyu Zheng, Yuansheng Ni, Yubo Wang, Kai Zhang, Shengbang Tong, Yuxuan Sun, Botao Yu, Ge Zhang, Huan Sun, et al. Mmmu-pro: A more robust multidiscipline multimodal understanding benchmark. arXiv preprint arXiv:2409.02813, 2024. 2
- [127] Liu Yuliang, Jin Lianwen, Zhang Shuaitao, and Zhang Sheng. Detecting curve text in the wild: New dataset and new solution. arXiv preprint arXiv:1712.02170, 2017. 1
- [128] Ge Zhang, Xinrun Du, Bei Chen, Yiming Liang, Tongxu Luo, Tianyu Zheng, Kang Zhu, Yuyang Cheng, Chunpu Xu, Shuyue Guo, Haoran Zhang, Xingwei Qu, Junjie Wang, Ruibin Yuan, Yizhi Li, Zekun Wang, Yudong Liu, Yu-Hsuan Tsai, Fengji Zhang, Chenghua Lin, Wenhao Huang, and Jie Fu. Cmmmu: A chinese massive multi-discipline multimodal understanding benchmark, 2024. 2
- [129] Renrui Zhang, Dongzhi Jiang, Yichi Zhang, Haokun Lin, Ziyu Guo, Pengshuo Qiu, Aojun Zhou, Pan Lu, Kai-Wei Chang, Yu Qiao, Peng Gao, and Hongsheng Li. MATH-VERSE: does your multi-modal LLM truly see the diagrams in visual math problems? In *Proceedings of European Conference on Computer Vision*, pages 169–186. Springer, 2024. 2
- [130] Xiang Zhang, Yongwen Su, Subarna Tripathi, and Zhuowen Tu. Text spotting transformers. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 9519–9528, 2022. 1
- [131] Yanzhe Zhang, Ruiyi Zhang, Jiuxiang Gu, Yufan Zhou, Nedim Lipka, Diyi Yang, and Tong Sun. Llavar: Enhanced visual instruction tuning for text-rich image understanding. *arXiv preprint arXiv:2306.17107*, 2023. 3, 6, 7, 8, 2
- [132] Weichao Zhao, Hao Feng, Qi Liu, Jingqun Tang, Shu Wei, Binghong Wu, Lei Liao, Yongjie Ye, Hao Liu, Houqiang Li, et al. TabPedia: Towards Comprehensive Visual Ta-

ble Understanding with Concept Synergy. arXiv preprint arXiv:2406.01326, 2024. 2, 3

- [133] Zhen Zhao, Jingqun Tang, Binghong Wu, Chunhui Lin, Shu Wei, Hao Liu, Xin Tan, Can Huang, Yuan Xie, et al. Harmonizing visual text comprehension and generation. In Advances in Neural Information Processing Systems, 2024. 6, 7, 8
- [134] Mingyu Zheng, Xinwei Feng, Qingyi Si, Qiaoqiao She, Zheng Lin, Wenbin Jiang, and Weiping Wang. Multimodal Table Understanding. In *Proceedings of Annual Meeting of the Association for Computational Linguistics*, pages 9102– 9124. Association for Computational Linguistics, 2024. 2, 3
- [135] Xinyi Zheng, Douglas Burdick, Lucian Popa, Xu Zhong, and Nancy Xin Ru Wang. Global table extractor (GTE): A framework for joint table identification and cell structure recognition using visual context. In *Proceedings of the IEEE Winter Conference on Applications of Computer Vision*, pages 697–706. IEEE, 2021. 2
- [136] Xu Zhong, Elaheh ShafieiBavani, and Antonio Jimeno Yepes. Image-based table recognition: data, model, and evaluation. arXiv preprint arXiv:1911.10683, 2019. 2
- [137] Xu Zhong, Jianbin Tang, and Antonio Jimeno-Yepes. Publaynet: Largest dataset ever for document layout analysis. In Proceedings of International Conference on Document Analysis and Recognition, pages 1015–1022. IEEE, 2019.
 2
- [138] Xu Zhong, Elaheh ShafieiBavani, and Antonio Jimeno Yepes. Image-based table recognition: data, model, and evaluation. In *Proceedings of European Conference on Computer Vision*, pages 564–580. Springer, 2020. 6, 4
- [139] Deyao Zhu, Jun Chen, Xiaoqian Shen, Xiang Li, and Mohamed Elhoseiny. Minigpt-4: Enhancing vision-language understanding with advanced large language models. *Proceedings of the International Conference on Learning Representations*, 2024. 1

Appendix

This appendix mainly contains the following contents:

- Section A: Comparison experiments between LMMs and some text-centric expert models.
- Section B: Data source of OCRBench v2.
- Section C: Task definition of *OCRBench v2*.
- Section D: More statistics of OCRBench v2.
- Section E: Evaluation metrics of OCRBench v2.
- Section F: Visualization samples of task examples.
- Section G: Visualization samples of failure cases.

A. Comparison with LMMs and Expert Models

Comparison with text recognizers. We compare LMMs with several representative scene text recognizers, including CRNN [87], ABINet [23], ASTER [89], MASTER [63], and SVTR [22], on the text recognition task. The weights of these models are loaded from mmocr³. The results are shown in Table 6, where we selected the top three LMMs with the best performance, including Qwen2VL-8B [105], GPT4V [78] and Step-1V [94]. The results demonstrate that LMMs exhibit remarkable text recognition capabilities, validating our motivation to evaluate LMMs on more challenging OCR-related tasks.

Method	Accuracy
CRNN [87]	38.1
ABINet [23]	62.4
ASTER [89]	50.0
MASTER [63]	54.1
SVTR [22]	57.8
Qwen2VL-8B [105]	78.2
GPT4V [78]	79.1
Step-1V [94]	75.4

Table 6. Comparison between LMMs and text recognizers.

Comparison with text spotters. We also compare LMMs with ABCNet series [56, 57] and TESTR [130] on the text spotting task. The weights of the ABCNet series are loaded from mmocr and TESTR is loaded from the official checkpoint⁴ fine-tuned with TotalText [15]. The results are shown in Table 7. We observe that although LMMs demonstrate promising capabilities in text recognition, there remains significant potential for improvement in the text spotting task. **Comparison with GOT.** We noticed a recent work, GOT [109], that can parse the textual elements within im-

Method	F1 score
ABCNet [56]	32.2
ABCNetV2 [57]	44.2
TESTR [130]	51.8
Qwen2VL-8B [105]	17.5
Gemini-Pro [99]	13.5
Step-1V [94]	7.2

Table 7. Comparison between LMMs and text spotters.

Method	Rec	FG-Rec	Full-Rec	Doc-Parse
GOT [109]	64.1	52.9	73.3	53.9
Qwen2VL-8B [105]	78.7	38.5	79.4	34.7
GPT4V [78]	79.5	20.0	80.4	39.2
Step-1V [94]	76.8	24.8	74.8	36.0

Table 8. Comparison between LMMs and GOT [109].

ages. We conduct comparison experiments between GOT and some representative LMMs, and the results are shown in Table 8. We observe that LMM shows advantages in general text recognition, while GOT demonstrates better performance in document parsing task.

B. Data Collection

Text Recognition. The data for text recognition task are sampled from ICDAR2013 [38], SVT [91], IIIT5K [75], ICDAR2015 [39], SCUT-CTW1500 [55], COCO-Text [102], CUTE80 [84], TotalText, SVTP [83], WordArt [112], NonSemanticText [58], IAM [68], ORAND-CAR-2014 [19], HOST [108] and WOST [108]. Meanwhile, CAPTCHA(Completely Automated Public Turing Test to Tell Humans Apart) images used in text recognition are sourced from a CAPTCHA dataset⁵ and a number CAPTCHA dataset⁶. And dot matrix images in the text recognition task are obtained from the web page.

Fine-grained Text Recognition. In the fine-grained text recognition task, the images are sampled from the testset of Fox [50], Totaltext, COCO-Text, CTW1500 [127] and IC-DAR2015. For the Fox dataset, we used the original annotations provided. For the other four datasets, we performed manual annotation.

Full-page OCR. The data sources for full-page OCR task

³https://github.com/open-mmlab/mmocr

⁴https://github.com/mlpc-ucsd/TESTR

⁵https://aistudio.baidu.com/datasetdetail/ 159309

⁶https://www.heywhale.com/mw/dataset/ 5e5e56b6b8dfce002d7ee42c/file

include Fox, HierText [61], CTW [124], RCTW-17 [88], ReCTS [54], LSVT2019 [96], M6Doc [14], and CDLA⁷.

Text Grounding. The images for the text Grounding task are sampled from testset of Totaltext, COCO-Text, CTW1500, and ICDAR2015. QA pairs and bounding boxes annotations are based on their official OCR annotations.

VQA with Position. The images for VQA with position task are sampled from testset of TextVQA [93] and RICO [18]. QA pairs and bounding boxes annotations are based on their official OCR annotations.

Text Spotting. The data sources for text spotting task include Totaltext, COCO-Text, CTW1500, and ICDAR2015.

Key Information Extraction. The data sources for key information extraction task include FUNSD [35], SROIE [34], POIE [43], M6Doc, XFUND [113], ICDAR2023-SVRD [123] and a private receipt photograph dataset.

Key Information Mapping. The data sources for the key information mapping task include FUNSD and POIE.

Handwritten Content Extraction. This task's data is our private data, which contains real exam paper data with student information removed and manually annotated question-answer pairs.

Table Parsing. The images for table parsing task are selected from MMTab [134], WTW [85], TabRecSet [114] and flush table recognition competition⁸.

Chart Parsing. The data sources for the chart parsing task come from OneChart [9] and MMC [51].

Document Parsing. The data sources for document parsing task come from DoTA [49], DocVQA [72], M6Doc and CDLA.

Formula Recognition. The data sources for the formula Recognition task including HME100K [125], IM2LATEX-100K [104], M2E [115], MathWriting [27], MLHME-38K⁹, CASIA-CSDB [20] and some private data.

Math QA. The data sources for the math QA task including MathMatics [86], MathVerse [129], MathVision [104] and MathVista [65].

Text Counting. The data for the text counting task are collected from IIIT5K, SVT, ICDAR2013, HierText, and To-talText.

Cognition VQA. The data sources for the cognition VQA task include EST-VQA [107], OCRVQA [76], ST-VQA [7], TEXTVQA, DIR300 [24], ChartQA [69], DVQA [37], PlotQA [74], InfoVQA [70], WTW, PubTab-Net [136], WTQ [82], CORD [81], LLaVAR [131], Web-

SRC [11], DocVQA, M6Doc, XFUND, Publaynet [137], RVL-CDIP [29], ScreenQA [4], SlideVQA [97], a movie poster collection dataset¹⁰, a website screenshot collection dataset¹¹ and a private receipt photograph dataset.

Diagram QA. The data sources for the diagram QA task include AI2D [40] and TextBookQA [41].

Document Classification. The images for the document classification task are mainly collected from RVL-CDIP.

Reasoning VQA. The reasoning VQA task shares some common data sources with the cognition VQA task. Additionally, portions of the reasoning VQA dataset are drawn from MMSI [45] and CMMMU [128].

Science QA. The images and annotations of the science QA task are collected from ScienceQA [64] and MMMU-Pro [126]

APP Agent. The data source of the APP agent task is RICO.

ASCII Art Classification. The data sources for the ASCII art classification task is ASCIIEval [36].

Text Translation. The datasets collected for text translation task includes memes¹², MSRA-TD500 [116], MTWI2018 [30], M6Doc, ICDAR2023-SVRD, EST-VQA, RCTW17 [90], DAST1500 [98], XFUND, ArT2019 [16], ChartQA, CDLA, ICDAR2015, SlideVQA, Fintabnet [135], ScienceQA, InfoVQA, COMICS-Dialogue¹³ and ExpressExpense SRD¹⁴.

C. Task Definition

In this section, we introduce the definition of each task, and the visualizations for each task can be found in Section F. **Text Recognition.** Text recognition refers to the fundamental OCR ability on text image patches, which asks LMMs to read the text content. To comprehensively evaluate LMMs' text recognition ability across diverse scenarios, our collection incorporates various text types, including regular text, irregular text, artistic text, handwriting text, digit string text, non-semantic text, occluded text, doc matrix text, and CAPTCHA text.

Fine-grained Text Recognition. This task requires LLMs to read and comprehend textual content within the given region. It evaluates LLMs' fine-grained perception capabilities in understanding text in natural scenes and documents.

¹¹https://huggingface.co/datasets/Zexanima/ website_screenshots_image_dataset/tree/main

⁷https://github.com/buptlihang/CDLA

⁸https://github.com/10jqka-aicubes/tablerecognition

⁹https://ai.100tal.com/icdar

¹⁰https://www.kaggle.com/datasets/neha1703/
movie-genre-from-its-poster

¹²https://www.kaggle.com/datasets/dvishal485/
meme-challenge?resource=download

¹³https://huggingface.co/datasets/lmms-lab/M4-Instruct-Data

¹⁴https://expressexpense.com/blog/free-receiptimages-ocr-machine-learning-dataset/

Full-page OCR. Full-page OCR [50] task requires LMMs to extract and recognize all text content from the given images. Converting text into digital format facilitates subsequent processing and analysis of text images.

Text grounding. In this task, users would provide a text string and require LMMs to locate its specific location, evaluating LMMs' fine-grained perception capabilities.

VQA with Position. For VQA with position task, LMMs need to not only respond to the question but also provide the exact position coordinates that directly correspond to the answer. We ask LMMs to output both information in JSON format for convenient evaluation, and the coordinates are required to be normalized with image sizes and scaled to the range of [0, 1000].

Text Spotting. Text spotting task needs LMMs to output the localization and content of all appeared text simultaneously. Due to the interference of background elements and the large number of text instances, this task demands high fine-grained perception capabilities from the model. Besides, the coordinates are required to be normalized with image sizes and scaled to the range of [0, 1000].

Key Information Extraction. The key information extraction task is to extract the necessary information from densely arranged text. In this task, we provide some desired entities as keys and demand LMMs to output the corresponding values to form the output JSON string.

Key Information Mapping. In this task, we provide a set of entity keys and their corresponding values in the prompt. The LMMs are then asked to match and pair these keys with their respective values into groups.

Handwritten Content Extraction. To investigate the information extraction capabilities of LMMs in educational scenarios, we collect some Chinese examination papers, containing both printed question text and handwritten student responses. There are four types of questions in these examination papers, including single-choice, multiple-choice, true or false, and brief response questions. The prompts require LMMs to extract the handwritten content for specific questions.

Table Parsing. Table parsing task requires LMMs to parse the given table into structured text, including Markdown and HTML format.

Chart Parsing. Apart from tables, charts can also be converted to structured information. In this task, LLMs are required to transform visual charts into JSON format.

Document Parsing. In the document parsing task, both text and the complex elements, including chart, table, and formula, are required to parse.

Formula Recognition. This task asks LMMs to recognize the given formula in the latex format. The collection includes mathematical and chemical formulas.

Math QA. Math QA task evaluates the LMMs' mathematical calculation ability. In particular, we render the mathematical problem description and related figures into images and ask LMMs to answer the questions within the images.

Text Counting. Text counting task is built to evaluate the quantity property perceiving ability of LMMs, including the character frequency in words and the word counting in the given image.

Cognition VQA. In *OCRBench v2*, we split text-centric VQA instructions into cognition VQA and Reasoning VQA based on whether the answers can be directly found in the images. Cognition VQA task refers to the instructions where answers are explicitly present in the given image. This task evaluates the fundamental text-centric question-answering ability based on visual content.

Diagram QA. In the diagram QA task, LMMs need to respond to the question about the given diagrams, reflecting LMMs' ability to understand the relationship between the visual elements.

Document Classification. Document classification task asks LMMs to classify the category of the given document image. The included categories are letters, forms, emails, handwritten documents, advertisements, scientific reports, scientific publications, specifications, file folders, news articles, budgets, invoices, presentations, questionnaires, resumes, and memos.

Reasoning VQA. In reasoning VQA tasks, the answers often do not directly appear in the image. This forces LMMs to perform logical reasoning to respond to questions based on visual information.

Science QA. In the Science QA task, LMMs are required to respond to the scientific problem. We use PaddleOCR¹⁵ to extract text from the collected images and filter out those with fewer than four OCR results. Additionally, when extra subject-related knowledge is provided by the source, we incorporate them by rendering them into the images.

APP Agent. For the APP agent task, LMMs need to understand the relationship between textual content, icons, and world knowledge to respond to the question from the user, simulating the real-world application scene.

ASCII Art Classification. We incorporate a recent image classification task that uses images composed purely of ASCII characters [36]. This task is included in *OCR-Bench v2* to evaluate LMMs' ability to assess LMMs' pattern recognition and visual abstraction abilities.

Text Translation. In the text translation task, LMMs need to execute translation between Chinese and English texts, evaluating LMMs' semantic understanding abilities.

¹⁵ https://github.com/PaddlePaddle/PaddleOCR

Scene	Number	Scene	Number	Scene	Number
Schematic diagram	1238	Scientific paper	799	Word	728
Table(filled)	705	Chart	620	Receipts	609
Questions	581	Mathematical formula	475	Product labels	434
Phone screenshot	431	Indoor scenes	395	Industry research reports	343
Poster	264	Street scene	224	ASCII Art	199
Shop sign	189	Financial reports	153	Chemical formula	149
Textbook	148	Magazine	146	Email	111
Web screenshot	99	Details page	95	Verification code	87
Resumes	67	Illustration	61	Newspaper	52
Road signs	43	Menus	31	Notify	30
Questionnaire	29				

Table 9. The number of images included in each scene category.



Figure 8. The quantity distribution of English tasks.



Figure 9. The quantity distribution of Chinese tasks.

D. More Statistics of OCRBench v2

D.1. Scene Coverage

Our dataset can be divided into 31 classic scenes according to the scene of the image. The specific scenes and the corresponding number of pictures are shown in Table 9.

D.2. Statistics of each task

The distribution of 23 tasks in *OCRBench* v2 is displayed in Figure 8 and Figure 9. Additionally, we calculate and present the average number of OCR text lines per task in Figure 10 and Figure 11. As illustrated in these figures, the task distribution is well-balanced, with each task containing adequate textual information for analysis.

E. Evaluation Metrics

Parsing Type. We use Tree-Edit-Distance-based Similarity (TEDS) [138] to evaluate parsing tasks, which require LMMs to transform the images to structured formats. Tree Edit Distance (TED) refers to the minimum number of edits to transform one tree into another. TEDS is based on TED to calculate the similarity of two trees. Assuming T_1 and T_2 are two different trees, $TED(T_1, T_2)$ refer to their TED,



Figure 10. The OCR lines distribution of English tasks.



Figure 11. The OCR lines distribution of Chinese tasks.

the TEDS is defined as:

$$TEDS(T_1, T_2) = 1 - \frac{TED(T_1, T_2)}{\max(|T_1|, |T_2|)},$$
 (1)

where $|T_1|$ and $|T_2|$ is the number of nodes of trees, $TED(T_1, T_2)$ can be calculated by dynamic programming algorithm. If T_1 and T_2 are identical, then their TEDS equals to 1. As the structural difference between two trees increases, their TED value becomes larger, resulting in the TEDS approaching 0.

Localization Type. In the text referring and spotting tasks, LMMs are required to provide regression bounding boxes of target objects. IoU score is adopted to measure the distance between the predicted regions and the ground truth.

$$IoU(B_1, B_2) = \frac{Intersect(B_1, B_2)}{Union(B_1, B_2)},$$
 (2)

where $Intersect(B_1, B_2)$ refers to the overlap area of bounding box B_1 and B_2 , while $Union(B_1, B_2)$ refers to their union area.

Extraction Type. The F1 score is used to evaluate LMMs' relation extraction capability. Given the predicted and

ground truth Key-Value pairs, the F1 score is formulated as follows:

$$Precision = \frac{N_3}{N_2},\tag{3}$$

$$Recall = \frac{N_3}{N_1},\tag{4}$$

$$Fmean = \frac{2 * Precision * Recall}{Precision + Recall},$$
(5)

where N_1 , N_2 , and N_3 denote the number of ground-truth Key-Value pairs, predicted Key-Value pairs, and correctly matched Key-Value pairs, respectively.

Long Reading Type. To evaluate LMMs' ability to recognize text across entire paragraphs or pages, BLEU [80], METEOR [6], F1 score and normalized edit distance are employed. And the final score is the average value of these metrics.

BLEU evaluates prediction quality by comparing n-gram match rates between prediction and ground truth sequences. For each n-gram type, precision is calculated as the ratio of matching n-grams to total prediction n-grams. The final BLEU score is the geometric mean of these precision values multiplied by a penalty *BP*, which is defined as:

$$BLEU = BP * exp(\sum_{n=1}^{N} w_n \log p_n), \tag{6}$$

$$BP = \begin{cases} 1 & L_p \ge L_g \\ e^{(1 - \frac{L_p}{L_g})} & L_p < L_g \end{cases},$$
 (7)

where p_n represents the precision of n-grams, L_p represents the length of prediction sequence, L_g represents the length of ground truth sequence, w_n is weight factor, usually evenly distributed ($w_n = \frac{1}{N}$). Typically, N is set to 4.

METEOR employs a semantic-aware matching strategy with four levels. 1) Exact Match: words in prediction that are identical to ground truth. 2) Stem match: matching words that have the same word stem. 3) Synonym Match: matching words based on synonymous relationships. 4) Paraphrase Match: Matching similar phrases at the phrase level. These matches are combined to calculate precision and recall, from which a weighted harmonic mean F1 score is derived as:

$$P_{meteor} = \frac{N_{match}}{N_{pred}},\tag{8}$$

$$R_{meteor} = \frac{N_{match}}{N_{at}},\tag{9}$$

$$F_{meteor} = \frac{10 * P_{meteor} * R_{meteor}}{P_{meteor} + 9 * R_{meteor}},$$
(10)

where N_{match} , N_{pred} , and N_{gt} represent the number of matched items, words in prediction, and words in ground truth, respectively. The final METEOR score is obtained by multiplying the F_{meteor} by the penalty adjustment factor. The calculation is formulated as follows:

$$METEOR = F_{meteor} * (1 - BP_{meteor}), \qquad (11)$$

$$BP_{meteor} = 0.5 * \frac{N_{chunk}}{N_{match}},$$
(12)

where N_{chunk} refers to the number of contiguous matching phrases. More chunks indicate greater word order differences, resulting in a heavier penalty.

The calculation method of the F1 score in long reading metrics follows the same approach as discussed in extraction metrics, as shown in Equations 3, 4, 5.

Normalized Edit Distance (NED) measures string similarity by computing the minimum number of operations needed to transform one string into another. And then NED is normalized by the length of the longer string. The calculation is formulated as follows:

$$NED(S_1, S_2) = \frac{ED(S_1, S_2)}{\max(len(S_1), len(S_2))}$$
(13)

where $ED(S_1, S_2)$ represents the edit distance between the prediction string S_1 and the ground truth S_2 . The *NED* value of 0 indicates identical strings, while 1 indicates completely different strings.

Counting Type. In *OCRBench v2*, character frequency counting and word counting tasks are included. For character frequency, we use exact match evaluation since the answers are typically single-digit integers. For word counting, we evaluate using the L1 distance between predicted and ground truth counts, normalized to [0, 1] based on the ground truth. This can be formulated as follows:

$$score = \begin{cases} 0 & C_{pred} \le 0\\ 1 - \frac{|C_{pred} - C_{gt}|}{C_{gt}}) & 0 < C_{pred} < 2 * C_{gt} \\ 0 & C_{pred} \ge 2 * C_{gt} \end{cases}$$
(14)

where C_{pred} and C_{gt} denote the predicted count and ground truth count, respectively.

Basic VQA Type. The remaining tasks in *OCRBench v2* are basic VQA types, and we employ different evaluation metrics based on question types. For multiple-choice questions, we use exact match between predictions and answer options. In other cases, we check whether the ground truth is contained in the prediction for answers shorter than 5 words, and use ANLS for longer answers.

F. Samples for Each Task

As show in Figure 12 to Figure 20, there are 23 OCR tasks included in OCRBench v2. Among them, Figure 12 to Figure 18 present examples of English tasks, including text recognition, diagram QA, text counting, formula recognition, math QA, VQA with position, ASCII art classification, reasoning VQA, text translation, APP agent, table parsing, cognition VQA, document classification, science QA, chart parsing, key information extraction, full-page OCR, text spotting, fine-grained text recognition, text grounding, key information mapping, and document parsing. These figures show corresponding images and QA pairs for each of the 22 tasks. Figure 19 to Figure 20 provide examples of Chinese tasks, including key information extraction, text translation, formula recognition, reasoning VQA, cognition VQA, handwritten content extraction, document parsing, full-page OCR, and table parsing, along with their associated images and QA pairs.

G. Samples for LMMs' Limitations

Figure 21 to Figure 23 provide examples corresponding to the findings discussed in Section 4.4 of the main text, which show error results of GPT-40 [1], Monkey [48], and Qwen2VL-8B on various tasks in *OCRBench v2*. These examples highlight the current limitations of LLMs on OCR tasks. For instance, LLMs exhibit poor recognition of less frequently encountered texts, struggle to accurately locate text in tasks involving text and coordinates, and demonstrate insufficient perception of text in complex layouts such as rotated texts. Additionally, their logical reasoning abilities are limited when addressing mathematical problems, and their analysis of complex elements in charts remains weak. These are the capabilities of LLMs in OCR tasks that require further improvement.



Figure 12. Samples for each tasks.

APP Agent What's the name of the chef who received four and a half stars on the recipe? ChefSandrine sberenter Table Parsing Fiscal years ended July 31, Recognize the table in the presented picture and 2019 2018 Change represent it in the markdown-format. (\$) (%) Amount Amount (In thousands, except percentages Interest income \$30,182 \$13,281 16,901 127 \$(17,334) \$(6,442) (10,892) 169 Interest expense \$(1,867) \$509 (2,376) (467) Other income (expense), net $\begin{array}{l} Fiscal years ended July 31, | | | |n| --- |---|---|---|n| \\ | 2019 | 2018 | Change | |n| | Amount | Amount | ($) | (%) \\ |n| | | (In thousands, except percentages) | | |n| Interest \\ income | $30,182 | $13,281 | 6,901 | 127 |n| Interest \\ \end{array}$ expense | (17,334) | (6,442) | (10,892) | 169 |n| Other income (expense), net | (1,867) | (509) | (2,376) | (467) | Cognition VQA What car should I look at that has a fuel economy of 30 MPG in highway? 2021 Toyota GR Supra 3.0 Premium Auto (Natl)

Figure 13. Samples for each tasks.



Figure 14. Samples for each tasks.



Figure 15. Samples for each tasks.

Full Page OCR Read all the text in the image. Directly output the content and split the texts with space. SURREALISM, ABSTRACTION\n& THE UNCONSCIOUS\nIn the 1920s, while a student at Yale, Rothko took\nphilosophy and psychology classes that led to his\ninterest in the unconscious and eventually to Sigmund\nFreud's The Interpretation of Dreams. Then, in the '40s,\nlike many American artists, he came under the influence\nof European Surrealist artists and writers living in New\nYork. Many artists also found inspiration in the Museum\nof Modern Art's influential 1936 exhibition, Fantastic Art,\nDada and Surrealism.\nBy the mid-1940s, Rothko loosened up his technique,\ninspired by the Surrealist method of automatism\n(\"automatic\" drawing or writing). Unlike some\nSurrealist artists, such as Salvador Dali, who \"pictured\"\nunconscious dreams in paintings, Surrealists using\nautomatism tried to access the unconscious by letting\nthe brush meander freely without planning or control.\nRothko experimented with the fluidity of watercolor and\nsoon realized he could achieve similar luminous effects/nin oil paint by diluting the pigment and applying color in\nthin washes, one on top of another. Rothko's imagery also\nchanged. Many works suggest paleontology and geology\nand evoke a vision of primordial life. Water seems to be\na primal element in which biomorphic shapes proliferate.\nSome compositions include stacked horizontal zones that\nmay stand for layers of the unconscious. **Text Spotting** Spotting all the text in the image with word-level. Output the normalized coordinates of the left-top and right-bottom corners of the bounding box and the text content. The coordinates should be normalized ranging from 0 to 1000 by the image width and height.\nYour answer should be in the following format: [(x1, y1, x2, y2, text content), (x1, y1, x2, y2, text content)...] # The normalized coordinates and the content of the text in the YELLOWSTONE image. , - ^--- ; 543, 770, 589, 794, 49-0223A, 545, 731, 580, 760, 502, 309, 594, 666, 641, YELLOWSTONE, 417, 160, 554, 198, TOUR

Figure 16. Samples for each tasks.

Fine-graine	d Text Recognition
DOLO ONE RAYOR DOLO ON REAL PROVINCIAL DOLO ON REAL PR	Recognize the text within the [192, 223, 332, 346] of the image. The coordinates have been normalized ranging from 0 to 1000 by the image width and height.
	DIOS LE ABRE CAMINO\\n AL HOMBRE\\n QUE SABE A DONDE VA
Text	Grounding
8	Where is the region of the text 'COMNAM'? Output the normalized coordinates of the left-top and right-bottom corners of the bounding box. The coordinates should be normalized ranging from 0 to 1000 by the image width and height. Your answer should be in the following format: (x1, y1, x2, y2) # x1, y1, x2, y2 are the normalized coordinates of the bounding box.
	[126,537,248,624]
Key]	Information Mapping
NUTRITION INFORMATION Servings per package: 5 Serving size: 200ml (1 cup) Per Serving Per 100ml Energy 98 kcal 49 kcal Protein 10.0 g 5.0 g Total Fat 1.6 g 0.8 g - Saturated Fat 1.0 g 0.5 g - Trans Fat 0.0 g 0.0 g	According to the information in the image, please pair the corresponding keys and values below: Keys that need to be paired are 'Serving Size', 'Calories/Energy per 100g/ml', 'Carbohydrate per serving', Protein per 100g/ml', 'Total Fat per serving', 'Carbohydrate per 100g/ml', 'Total Fat per 100g/ml', 'Protein per serving'. Values that need to be paired are '0.8 g', '11.0 g', '200ml (1 cup)', '10.0 g', '1.6 g', '49 kcal(206 kJ)', '5.0 g', '5.5 g'.
Carbohydrate 0 mg 3 mg Carbohydrate 11.0 g 5.5 g - Total Sugar 9.0 g 4.5 g - Added Sugar 0.0 g 0.0 g - Lactose 2.2 g 1.1 g Dietary Fibre 0.0 g 0.0 g Sodium 164 mg 82 mg Calcium 400.0 mg 200.0 mg Vitamin A 372.0 mcg 186.0 mcg Thiamine (Vitamin B1) 1.0 mg 0.5 mg Niacin (Vitamin B3) 11.0 mg 5.5 mg Pantothenic Acid (Vitamin B5) 7.0 mg 3.5 mg Pyridoxine (Vitamin B6) 1.8 mg 0.9 mg Vitamin C 24.0 mg 12.0 mg Vitamin D3 2.4 mcg 12 mcg Vitamin K1 27.0 mcg 13.5 mcg	{"Calories/Energy per 100g/ml": "49 kcal(206 kJ)" "Protein per serving": "10.0 g" "Protein per 100g/ml": "5.0 g" "Total Fat per serving": "1.6 g" "Total Fat per 100g/ml": "0.8 g" "Carbohydrate per serving": "11.0 g" "Carbohydrate per 100g/ml": "5.5 g" "Serving Size": "200ml (1 cup)"}

Figure 17. Samples for each tasks.

Document Parsing

We describe a winning strategy for Alice with $\Delta(G)$ colours in the [B, A]-edge We describe a writing statisty on rates was a provide the state of th

- If Bob colours the matching edge of the pending object O_j, then, if this was the first such area only the edge zz is still uncoloured, Alter colours zz work the mane colour (If possible, et a are colour startwrske); otherwise, there colours a start edge of the pending why CO_j, ran are the same colour, if possible. If it is not possible, she uses a new colour for software starts are starts are starts are starts and the start edge.
- If Bob colours the first star edge of the pending object O_j and there is still a pending object with only uncoloured star edges, then Alice colours the matching edge of the pending object $O_{j-1} \mod k_i$ with the same colour. If the matching edge is already coloured, then Alice misses her turn.
- If Bob colours the first star edge of the pending object O_j and there is no pending object with only uncoloured star edges left, then Alice colours vz with a new colour (if vz is still uncoloured) or misses her turn (if ez is already coloured).
- If Bob colours the edge vz, an edge vz_j or the second star edge of the pending object (a triangle) O_j, then Alice misses her turn. If Bob colours an edge zu_i, then Alice colours vz (if vz is still uncoloured) or misses her turn (otherwise).
- This strategy has the same properties as the strategy for the single galaxy the proof of Lemma 67, and, in addition, it guarantees that the edge vz is loured before it is in danger to be infeasible for any colour.

5.4 Permitted for game [A, A]

Definition 69 (full tree). Let $n, m_1, m_2 \in \mathbb{N}$. An (n, m_1, m_2) -full tree is based on a path P_3 , where there are main (respectively, n, m_2) leafs attached its three vertices, i.e., the graph has the vertex set

 $\{w_1, v, w_2\} \cup \{x_i \mid 1 \leq i \leq m_1\} \cup \{y_j \mid 1 \leq j \leq n\} \cup \{z_i \mid 1 \leq i \leq m_2\}$ and the edge set

 $\{w_1v, vw_2\} \cup \{w_1x_i \mid 1 \le i \le m_1\} \cup \{vy_j \mid 1 \le j \le n\} \cup \{w_2z_i \mid 1 \le i \le m_2\}$ A full tree is an (n, m_1, m_2) -full tree for some $n, m_1, m_2 \in \mathbb{N}$.

29

Convert the privided document into markdown format.

We describe a winning strategy for Alice with $\backslash (\langle B \rangle)$ colours in the $\([B,A]\)$ -edge colouring game played on $\backslash\!\backslash (G \backslash\!\backslash). \ n \ n \ the only unsafe edges are the star edges of pending$ objects and the edge (vz). Alice may arbitrarily number the pending objects $(O_{1}, O_{2}, (lots, O_{k+(l)}))$ and performs basically the same pairing strategy as in the proof of Lemma 67 with only small extensions, as described in the following.\n\n* If Bob colours the matching edge of the pending object $\backslash (O_{j})$, then, if this was the first such move and the edge (vz) is still uncoloured, Alice colours (vz) with the same colour (if possible, or a new colour otherwise); otherwise, Alice colours a star edge of the pending object $(O_{j+1} \otimes \{k+\|e\|\})$ with the same colour, if possible. If it is not possible, she uses a new colour for such a star edge.\n* If Bob colours the first star edge of the pending object \\(O {j}\\\) and there is still a pending object with only uncoloured star edges, then Alice colours the matching edge of the pending object $(O {j-1} \ k+\))$ with the same colour. If the matching edge is already coloured, then Alice misses her turn.\n* If Bob colours the first star edge of the pending object $\backslash\!\backslash (O_{j})$ and there is no pending object with only uncoloured star edges left, then Alice colours (vz) with a new colour (if (vz)) is still uncoloured) or misses her turn (if $\(vz\)$ is already coloured). \n* If Bob colours the edge $\backslash\!\backslash\!(vz\!\wedge\!),$ an edge $\backslash\!\backslash\!(vx_{j})\!\rangle$ or the second star edge of the pending object (a triangle) (O_{j}) , then Alice misses her turn.\n* If Bob colours an edge $((zu_{i}))$, then Alice colours (vz) (if (vz)) is still uncoloured) or misses her turn (otherwise).\n\nThis strategy has the same properties as the strategy for the single galaxy in the proof of Lemma 67, and, in addition, it guarantees that the edge \\(vz\\) is coloured before it is in danger to be infeasible for any colour. \n\n### Permitted for game \\([A,a]\\)\n\n**Definition 69** (full tree).: Let $(n,m_{1},m_{2}) \in \{N\}$. An $((n,m_{1},m_{2})))$ -full tree is based on a path $(P_{3}))$, where there are (m_{1}) (respectively, (n), $(m_{2}))$ leafs attached its three vertices, i.e., the graph has the vertex $m_{1}\\ (y_{j}\ n \in 1)\ (z_{i}\ n \in 1)\ (z_{$ 1\\leq i\\leq m_{2}\\}\\]\n\nand the edge $\label{eq:liked_m_12} $$ root_1, roo$ $\label{eq:linear} n \ (w_{2}z_{i}) \ n \ (h) \ n \ (h) \ ($ tree_ is an $\((n,m_{1},m_{2})\))-full tree for some$

 $\label{eq:started_lim} $$ (n,m_{1},m_{2}) \in \mathbb{N} $$..., n_{1}, m_{2} \in \mathbb{N} $$..., n_{2} \in \mathbb{N} $$..., n_{2}$

Figure 18. Samples for each tasks.



Figure 19. Samples for each tasks.



Figure 20. Samples for each tasks.





Figure 21. Samples for LMM'S Limitations. The portion of LLM's response marked in red is incorrect content, and the content in the red dashed box is missing information.



Limited logical reasoning



Figure 22. Samples for LMM'S Limitations. The portion of LLM's response marked in red is incorrect content, and the content in the red dashed box is missing information.



Figure 23. **Samples for LMM'S Limitations**. The portion of LLM's response marked in red is incorrect content, and the content in the red dashed box is missing information.