Beyond Words: AuralLLM and SignMST-C for Precise Sign Language Production and Bidirectional Accessibility

Yulong Li^{*1}, Yuxuan Zhang^{*2}, Feilong Tang³, Mian Zhou⁴, Zhixiang Lu⁵, Haochen Xue⁶, Yifang Wang⁷ Kang Dangot^{8†}, Jionglong Su^{9†},

> ^{1,2,4,5,6,7,8,9}School of Artificial Intelligence and Advanced Computing, Xi'an Jiaotong-Liverpool University, Suzhou, 215123, China ³Monash University, Melbourne, Australia

> > {Kang.Dang, Jionglong.Su}@xjtlu.edu.cn

Abstract

Although sign language recognition aids non-hearingimpaired understanding, many hearing-impaired individuals still rely on sign language alone due to limited literacy, underscoring the need for advanced sign language production and translation (SLP and SLT) systems. In the field of sign language production, the lack of adequate models and datasets restricts practical applications. Existing models face challenges in production accuracy and pose control, making it difficult to provide fluent sign language expressions across diverse scenarios. Additionally, data resources are scarce, particularly high-quality datasets with complete sign vocabulary and pose annotations. To address these issues, we introduce CNText2Sign and CNSign, comprehensive datasets to benchmark SLP and SLT, respectively, with CNText2Sign covering gloss and landmark mappings for SLP, and CNSign providing extensive video-to-text data for SLT. To improve the accuracy and applicability of sign language systems, we propose the AuraLLM and SignMST-C models. AuraLLM, incorporating LoRA and RAG techniques, achieves a BLEU-4 score of 50.41 on the *CNText2Sign dataset, enabling precise control over gesture* semantics and motion. SignMST-C employs self-supervised rapid motion video pretraining, achieving a BLEU-4 score of 31.03/32.08 on the PHOENIX2014-T benchmark, setting a new state-of-the-art. These models establish robust baselines for the datasets released for their respective tasks.

1. Introduction

Approximately 72 million individuals worldwide with hearing impairments rely on sign language for daily com-



Figure 1. BeyondWords: Enabling Barrier-Free Communication Between Hearing and Hearing-Impaired Individuals.

munication [35, 49]. Recent advancements in sign language recognition technology primarily assist non-hearingimpaired individuals in understanding sign language content, thus reducing language barriers in communication. However, these recognition technologies often fail to meet the communication needs of hearing-impaired individuals. Due to limited educational and resource access, their reading proficiency is often constrained, making written text less intuitive [23, 26]. In contrast, sign language production (SLP) technology can directly convert spoken language into sign language videos, thereby better fulfilling their commu-

Access the download link from our GitHub repository upon release.

nication needs [37, 53, 56].

The goal of SLP is to convert text input into human-like sign language expressions. Current deep learning-based SLP methods typically involve multiple steps: transforming text to gloss, converting gloss to poses, and rendering these poses into sign language videos [21, 42, 43, 46, 47, 52, 57]. However, due to the complexity of this process, these methods require large, high-quality datasets, which exposes three major limitations in existing datasets and back-translation evaluations for SLP [7, 18, 19, 29, 59]. First, the absence of a foundational lexicon and corresponding videos results in a lack of consistent intermediate representations, making it challenging to maintain semantic coherence. Second, limited scene coverage in current datasets restricts model performance when generating expressions for out-ofvocabulary terms. Third, back-translation evaluation, which relies solely on sentence-level comparisons, cannot accurately assess the precision of individual gestures or poses, often masking errors in sign pose accuracy.

To address the limitations of current SLP datasets, we introduce CNText2Sign, a new large-scale Chinese natural language-to-sign gloss mapping dataset. CNText2Sign comprises 15,000 annotated mappings from natural language to sign glosses, curated by professional sign language experts, and includes 8,643 officially defined core Chinese sign vocabulary items, each accompanied by corresponding video data. By utilizing OpenPose [6] for skeleton keypoint extraction, we generate complete temporal pose sequences, establishing a consistent intermediate representation that enhances semantic coherence in SLP models. This lexicon and annotation structure allows for fine-grained control over semantic and emotional expression, addressing the consistency issues stemming from the limited vocabulary in previous datasets. Additionally, we introduce CN-Sign, a dataset that bridges the data scarcity gap in Chinese sign language translation (SLT). CNSign consists of 10,943 video-to-text mappings, with video durations ranging from 5 to 32 seconds, sourced primarily from real-world news scenarios and incorporating complex sentence structures suitable for a wide range of practical applications. Together, these datasets provide comprehensive gloss and pose data for SLP tasks, addressing the critical limitations of previous resources and ensuring model adaptability across diverse real-world scenarios, including daily conversations, news broadcasts, and public services, thereby enabling effective sign language production and translation across multiple contexts.

Bidirectional sign language translation systems, encompassing sign-to-text (SLT) and text-to-sign (SLP) tasks, face several critical challenges. First, existing SLT methods struggle with aligning dynamic visual gestures and linguistic semantics, leading to difficulties in capturing finegrained motion details and producing grammatically correct, semantically coherent text [3]. Second, SLP systems often generate videos that lack natural motion fluency and fail to convey complex semantics and emotional nuances effectively [15]. Third, SLT and SLP are typically studied as independent tasks, lacking an integrated design that addresses the interconnections required for real-world applications [15].

To address these challenges, we propose AuraLLM and SignMST-C as part of a unified framework for bidirectional sign language translation. SignMST-C leverages selfsupervised pretraining on rapid motion videos and multimodal feature fusion to enhance SLT performance, ensuring precise semantic alignment and dynamic motion comprehension. AuraLLM incorporates LoRA fine-tuning and RAG-based retrieval to achieve accurate text-to-sign mapping, generating natural and fluent sign language videos through the SL-ControlNet module. As illustrated in Figure 1, our approach systematically integrates SLT and SLP into a complete bidirectional translation pipeline, bridging the gap between sign language and natural language while providing a unified framework to support diverse application scenarios effectively.

The key contributions of this paper are three-fold:

1) We propose the first high-precision sign language production model, AuraLLM, which supports production across all daily scenarios. Through strong supervision, AuraLLM achieves fine control over hand poses, ensuring the accuracy and naturalness of the sign language video gestures. In the text-to-gloss task, serving as a baseline, AuraLLM achieves a BLEU-4 score of 50.41%.

2) We introduce a self-supervised pretraining method focused on rapid motion video, specifically designed for SLT tasks. This method incorporates a self-supervised pretraining strategy with weighted perturbation processing based on landmark data, enhancing feature learning in dynamic areas and significantly improving model performance. We achieved a 2.37/3.13 increase on the BLEU-4 metric, establishing a new SOTA.

3) We also collect and release the largest dataset to date specifically for Chinese sign language production, CN-Text2Sign, along with a Chinese sign language translation dataset, CNSign. The CNText2Sign dataset includes an extensive vocabulary and corresponding landmark data, providing accurate vocabulary-to-pose mappings that enable the model to generate sign language videos with high semantic consistency and pose precision.

2. Related Work

Sign Language Datasets

In recent years, research on SLP [13, 24, 30, 31, 50] has gradually shifted from traditional animation synthesis methods to data-driven approaches based on deep learning. However, its development is limited by the lack of high-quality sign language datasets, particularly in non-

English sign languages. Existing datasets are mostly focused on a few languages, such as American Sign Language (ASL) and German Sign Language (GSL), and often restricted to specific topics, such as weather and daily phrases, which limits their applicability to a broader range of contexts [22, 41, 44, 45, 47]. Most datasets provide videos of isolated vocabulary or short phrases, lacking complex syntax and diverse contexts, making it challenging for generative models to produce natural and coherent sign language expressions in more varied situations [14]. Moreover, the commonly used back-translation method to evaluate sign language production has its limitations, as it struggles to capture the nuanced semantics and grammatical features of sign language [2, 5, 12, 25]. This issue is particularly pronounced in the domain of Chinese Sign Language (CSL), where existing datasets mostly consist of isolated words or basic phrases, lacking support for complex sentences and diverse scenes [15]. Our work introduces the CNText2Sign dataset, which fills these gaps by offering multi-modal annotations, a large vocabulary, and broad contextual coverage. It supports more comprehensive sign language production across various scenarios.

Large Language Model in SLP

Large Language Model have demonstrated significant potential in SLP tasks due to their powerful natural language processing capabilities [4, 11, 51, 54, 55]. However, sign language, as a visual language, exhibits structural characteristics that differ significantly from the textual information processed by language models, presenting challenges in applying LLMs to the SLP domain. Current research typically applies LLMs by converting visual features of sign language, such as keypoints or skeletal poses, into sequential data for text-based pose generation, resembling a language modeling approach [27, 38, 40, 40]. Since the vocabulary of sign language is much smaller than that of natural languages, LLMs often simplify details and lose information during the generation process, particularly in terms of emotions, intonation, and complex syntax, which lack direct counterparts in sign language. Some studies have attempted to combine LLMs with multimodal models by incorporating pose keypoints or gloss vocabulary as intermediate layers. However, the generation results still heavily depend on the LLM, and the design of prompts greatly impacts the output quality [4, 11, 39]. Furthermore, sentences generated by LLMs often retain the syntax of natural language, which is not suitable for the concise expression style of sign language. To address these challenges, we introduce a multi-level Retrieval-Augmented Generation (RAG) technique that dynamically retrieves and generates multimodal information suitable for sign language, enabling the model to accurately express details and emotions from natural language.

SLT and Advances in Gloss-Free Approaches

In recent years, to improve the effectiveness of SLT, many studies adopted sign gloss as an intermediate representation layer. SLRT [5] first introduced a Transformerbased encoder-decoder structure combined with Connectionist Temporal Classification (CTC) loss to align sign language representations with gloss sequences, significantly enhancing translation performance. However, the process of obtaining gloss annotations is complex and costly. To address this, STMC-T [61] proposed multi-stream learning, using both single-stream and cross-stream CTC losses to model sequence information more accurately, although this method has limited performance when dealing with complex syntax. SignBack [60] introduced back-translation techniques to improve the linguistic expressiveness of SLT, but back-translation struggles to ensure word-level precision, particularly in nuanced semantic expressions. Chen et al. [9, 10] explored the application of Large Language Models (LLMs) in SLT, leveraging the powerful generative capabilities of LLMs to enhance translation accuracy. However, LLMs still face challenges in aligning visual and linguistic modalities. Recently, gloss-free SLT has emerged as a new approach, with NSLT [12] utilizing a CNN+RNN architecture for end-to-end SLT. Despite its advancements, it still faces limitations in semantic and motion alignment due to the absence of intermediate representations. TSPNet [28] introduced a cross-scale attention mechanism to strengthen the capture of visual features, while CSGCR [58] improved SLT accuracy and fluency through a multi-module design. Nevertheless, challenges in cross-modal alignment remain unresolved. To address these issues, we propose an end-toend SLT model combining self-supervised pretraining.

3. Dataset Benchmark

Chinese Natural Language to Sign Language Gloss Mapping Dataset (CNText2Sign) The CNText2Sign dataset is an innovative resource for SLP tasks, featuring 15,000 mappings from Chinese natural language to sign language gloss, each annotated by professionals to ensure accuracy and consistency. It also includes 8,643 basic Chinese sign language vocabulary items with corresponding videos, processed through MediaPipe [6] to standardize skeleton keypoints and create complete sign language pose sequences. This multimodal data provides an end-to-end, standardized training pipeline that enables precise semantic control in video generation. CNText2Sign was created by collecting extensive video materials from public platforms and supplementing missing vocabulary based on the official Chinese sign language guide, with trained experts contributing annotations. MediaPipe [6] processing extracts 3D skeletal keypoints, further converted to JSON and H5 formats, ensuring data efficiency and usability, thus providing essential gesture information for SLP models.

Name	Language	Vocab.	Duration	Avg Length	Transcription	Gloss	Video Pose	Gloss Pose	Depth
SIGNUM [1]	GSL	450	55	25	×	\checkmark	\checkmark	×	×
RWTH-Phoenix-2014T [12]	GSL	3k	11	9	×	\checkmark	\checkmark	\checkmark	×
Public DGS Corpus [17]	GSL	-	50	327	×	\checkmark	\checkmark	\checkmark	×
BSL Corpus [48]	BSL	5k	_	249	×	\checkmark	\checkmark	\checkmark	\checkmark
NCSLGR [36]	ASL	1.8k	5.3	4	×	\checkmark	\checkmark	×	×
How2Sign	ASL	16k	79	11	×	\checkmark	\checkmark	\checkmark	\checkmark
Prompt2Sign [15]	Multilingual	40k	200	40	\checkmark	\checkmark	\checkmark	×	\checkmark
Video-Based CSL [20]	CSL	178	100	50	×	\checkmark	×	\checkmark	×
CNSign (ours)	CSL	34k	41.7	13.7	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark

Table 1. Comparison of Sign Language Datasets

Dataset Gap Filling

CNText2Sign is the largest Chinese natural language to sign language gloss mapping dataset currently available, covering all officially defined Chinese sign language vocabulary, as given in Table 1. It supports rich semantic expressions in SLP models. The dataset is suitable for fullscenario sign language production tasks, covering various real-world application scenarios, including daily conversations, news reports, public services, etc. Providing standardized data simplifies the sign language production process and helps improve the model's generation quality and adaptability in complex situations.

Chinese Sign Language to Natural Language Dataset (CNSign)

To address the scarcity of Chinese SLT data, we have released a dataset with 10,943 entries translating Chinese sign language videos into natural language, bridging the gap in video-to-text translation. The dataset's video samples, primarily sourced from the Chinese news program "Focus On", feature realistic contexts and complex syntax, with video durations ranging from 5 to 32 seconds to support diverse sentence structures and enhance model adaptability. Due to the typical 5-10 second translation lag, alignment between video and text was manually performed by seven trained experts to ensure high accuracy and coherence, providing reliable annotated data for model training, validation, and evaluation.

Dataset Gap Filling

This dataset plays a crucial role in Chinese sign language to natural language translation tasks, filling the gap for SLT data in diverse real-world scenarios. With rich contextual information and complex syntactical structures, this dataset is suitable for training SLT models in various scenarios. It is particularly valuable in improving the accuracy and semantic understanding of models in complex expressions, such as news reporting.

4. Methodology

SLP Framework

AuraLLM consists of the ZRSL module (Natural Language to Sign Language Conversion Module) and the SL-ControlNet module, designed to generate highly accurate

sign language videos, as seen in Figure 2. The ZRSL module includes a LoRA fine-tuning combined with a RAG retrieval enhancement module (LoRA+RAG), which relies on a proprietary sign language vocabulary and landmark data to ensure the accuracy of sign symbol generation. LoRA fine-tuning enhances the model's ability to generate synonymous expressions aligned with sign language vocabulary, while RAG retrieval selects the most semantically consistent symbols from the sign vocabulary to ensure translation precision and semantic consistency. The landmark data within the sign vocabulary details the key poses associated with each sign symbol, serving as a foundational element for precise sign language video generation. The ZRSL module produces a symbol sequence that aligns with sign language expression and maps these symbols to 3D skeletal poses. The SL-ControlNet module then receives this skeletal pose sequence and transforms it into a natural, smooth video output, ensuring that each sign language gesture transitions seamlessly and cohesively within the video, thereby achieving high-quality sign language video output from natural language input.

Accurate Sign Language Symbols and Smooth Video Generation

To enable efficient sign symbol generation under multimodal input conditions, we apply LoRA fine-tuning based on a large language model. LoRA fine-tuning introduces low-rank matrices into the model's weight matrix, allowing the model to quickly adapt. This approach offers two major advantages: it retains the core capabilities of the pretrained model and enhances the model's ability to generate synonyms within the sign language vocabulary, particularly for words without direct matches.

In the multimodal input process, when certain words in text or audio lack a direct corresponding symbol in the sign language vocabulary, the system leverages the LoRA finetuned model to generate a set of potential synonym candidates. The system then applies RAG technology, using embeddings to match these candidates with vocabulary entries in the sign language lexicon, ensuring that the closest sign language expression is selected. For instance, the embedding representation of an unmatched word q is matched against the sign vocabulary embeddings to identify the most



Figure 2. AuraLLM: Combines ZRSL and SL-ControlNet to convert natural language input into high-quality sign language videos.

semantically similar option. For example, the unmatched word q is represented by its embedding e(q), and a candidate word w_i in the sign language vocabulary is represented by its embedding $e(w_i)$. The semantic similarity between them is calculated using cosine similarity:

similarity
$$(q, w_i) = \frac{e(q) \cdot e(w_i)}{\|e(q)\| \|e(w_i)\|}.$$
 (1)

By selecting the symbol with the highest similarity, the system effectively compensates for any missing entries in the sign language vocabulary, generating semantically consistent substitute symbols that align with sign language expressions. This process integrates LoRA fine-tuning with RAG technology, ensuring translation accuracy for unmatched inputs.

After the ZRSL module generates the sequence of sign language symbols, the SL-ControlNet module is responsible for converting these symbols into smooth sign language video output. SL-ControlNet generates a 3D skeletal keypoint representation for each sign language symbol to simulate the dynamics of sign language gestures. Assuming each symbol s_i in the sequence corresponds to an action frame Pose_{t,i}, the complete skeletal sequence is represented as:

Pose_Sequence = {Pose_{t,i} |
$$t = 1, 2, ..., T$$
}. (2)

SL-ControlNet generates corresponding video frames based on this skeletal sequence, ensuring smooth transitions between actions and natural gesture representation. This module not only creates the 3D poses corresponding to each sign language symbol but also achieves the complete expression of natural language to sign language through skeletal-to-video mapping. During video generation, SL-ControlNet incorporates smoothing processes to ensure that the sequence of symbols forms coherent and natural sign language actions in the video. The final output video frames exhibit realistic dynamic features in both time and space, and SL-ControlNet also supports the generation of 3D virtual avatars.

SLT Framework

We propose a SignMST-C (Sign Model Self-Translation with Correction) framework based on multimodal fusion, as seen in Figure 3, which combines self-supervised pretraining for rapid motion video semantic reconstruction, multimodal feature fusion of video and landmark data, end-toend video-to-text translation, and a text correction network. The framework aims to improve the accuracy and timeliness of translating sign language videos into natural language text. Below are detailed descriptions and formula definitions for each model.



Figure 3. An overview of SignMST-C, starts with video frames and landmarks processed through 3D ResNet18 and 1D convolution for spatial-temporal and geometric features.

Self-Supervised Pretraining for Rapid Motion Video Semantic Reconstruction To enhance the model's attention to dynamic regions in sign language videos, we design a self-supervised pretraining method. By introducing various perturbations to generate noisy input frames and using a weighted perturbation strategy based on landmark recognition, the model is guided to focus on the dynamic features of fast-moving regions during the reconstruction process. In this process, we use a ResNet18-3D convolutional network to extract features and a low-parameter decoder to restore video content, ensuring that the model focuses on the most critical features.

In the self-supervised input generation phase, various perturbations are applied to the video frames v_t to enhance the model's focus on areas of rapid motion. These perturbations include Pixel Shuffling, which randomly reorders pixel positions within a frame to disrupt the static spatial structure of the image; Random Pixel Replacement, which replaces a specified proportion of pixels with random values to simulate blurring; Block Occlusion, which generates random blocks in the image with pixel values set to zero to simulate information loss; Local Gaussian Noise, which adds noise sampled from a Gaussian distribution to random regions to mimic capture interference; and finally, Temporal Sequence Shuffling, which randomly reorders video frames to disrupt the original temporal sequence.

In the process of constructing self-supervised input, we use landmark recognition to identify fast-moving regions in video frames, applying higher perturbation weights to these areas. The detailed process is as follows:

Identify fast-moving regions by calculating the movement speed between consecutive frames at landmark points. For each landmark point (x_i, y_i) :

$$S_i = \sqrt{(x_i - x_{i-1})^2 + (y_i - y_{i-1})^2}.$$
 (3)

When $S_i > \theta$, this landmark point is defined as a fastmoving region, and the surrounding area with a radius of r is expanded, defined as:

$$M_{t} = \{(x, y) \mid \sqrt{(x - x_{i})^{2} + (y - y_{i})^{2}} \le r, \\ \forall (x_{i}, y_{i}) \in L_{t}, S_{i} > \theta \}.$$
(4)

For pixels in the fast-moving regions (including landmarks and surrounding areas), a large perturbation weight w_{large} is used. For other regions, a small perturbation weight w_{small} is applied. The weighted perturbed input is defined as:

$$v'_{t} = w_{\text{large}} f_{\text{large}}(v_{t}, M_{t}) + w_{\text{small}} f_{\text{small}}(v_{t}, M'_{t}), \quad (5)$$

where f_{large} and f_{small} represent large and small perturbation operations, $|| \cdot ||_2$ denotes the L2 norm, and T represents the time step. Additionally, $w_{\text{large}} + w_{\text{small}} = 1$.

We define the reconstruction loss function L_{recon} as the average pixel-wise error between the original video sequence and the reconstructed video sequence, ensuring that the reconstructed output retains the visual content of the original video as closely as possible:

$$L_{\text{recon}} = \frac{1}{T} \sum_{t=1}^{T} \|v_t - \hat{v}_t\|_2^2, \qquad (6)$$

where v_t is the pixel value matrix of the original video frame, \hat{v}_t is the pixel value matrix of the reconstructed video frame generated by the model.

Multimodal Module for SLT

In the multimodal module of the SLT framework, we concatenate and fuse video and landmark features to enhance the model's ability to capture spatiotemporal geometric information in sign language videos. To ensure temporal consistency across different modal features and align the 3D convolutional features with the semantic requirements of the target text, we designed three distillation losses and a cross-entropy loss to guide model learning.

Video frames are processed through a ResNet18 3D network to extract Conv_Feature, capturing the spatiotemporal dynamics of the sign language video. The landmark information in the sign language video is processed through a 1D convolutional layer, generating 1D Conv Feature, which captures the geometric positional changes of sign language actions, providing supplementary support for spatiotemporal dynamics.

The video and landmark features are then concatenated and fed into a Transformer, where a multi-layer selfattention mechanism enables feature interaction and fusion. This process generates the multimodal fused feature representation, Tran_Feature. The self-attention mechanism effectively combines the spatial information from the video and the structural information from the landmark, equipping the model with a robust capacity for dynamic understanding.

In the process of multimodal fusion, the video and landmark features are derived from different networks. To maintain temporal consistency between these features, we introduce three distillation losses to ensure that the temporal structures of the features are aligned before and after fusion, thus avoiding information distortion or conflict. These losses measure the similarity between feature distributions using Kullback-Leibler (KL) Divergence:

$$L_{\text{self-KL}} = \frac{1}{T} \sum_{t=1}^{T} \text{KL} \left(P_{3D}(t) \parallel P_{\text{T}}(t) \right), \quad (7)$$

where $P_{3D}(t)$ is the feature distribution of the 3D convolution, and $P_{\rm T}(t)$ is the fused feature distribution from the Transformer

 $L_{\rm LM-T-KL}$ loss ensures that the fused features of the landmarks and video remain consistent across time steps, allowing the model to effectively capture the dynamic information in sign language videos:

$$L_{\text{LM-T-KL}} = \frac{1}{T} \sum_{t=1}^{T} \text{KL}(P_{\text{LT}}(t) \parallel P_{\text{VT}}(t)), \qquad (8)$$

where $P_{\text{LT}}(t)$ represents the feature distribution from the landmark transformer and $P_{\text{VT}}(t)$ represents the feature distribution from the video transformer.

The final total loss function L_{total} for the multimodal module combines the three distillation losses described

above with the cross-entropy loss to optimize feature alignment and semantic representation:

$$L_{\text{total}} = L_{\text{self-KL}} + L_{\text{LM-Video-KL}} + L_{\text{LM-T-KL}} + L_{\text{CE}}.$$
 (9)

Text Correction Network

The Text Correction Network is designed to enhance the model's capability to identify and correct errors in preliminary translations, including issues with word order, missing words, redundancies, and other inaccuracies. To achieve this, we generate training data by introducing artificial errors into correct text, simulating typical error patterns often made by student networks, as part of the pretraining process.

During pretraining, we employ an error-injection strategy that introduces noise into correct sentences through random shuffling, deletion, substitution, or insertion of words. This approach allows the model to learn how to reconstruct accurate sentence structures from noisy inputs, improving its robustness across various error scenarios. By combining noisy data with authentic text, the model not only maintains semantic comprehension but also progressively strengthens its sensitivity to grammatical structures, leading to more efficient and precise error correction.

5. Experiment

Metric In this study, we utilize BLEU (Bilingual Evaluation Understudy), CER (Character Error Rate), and ROUGE (Recall-Oriented Understudy for Gisting Evaluation) as the primary evaluation metrics for the SLP and SLT tasks. The detailed experimental settings (train details) and dataset partitioning can be found in the supplementary materials.

Benchmark Result In this study, we released a new dataset containing tasks for SLP and SLT, along with baseline methods based on this dataset as Table 2. Our SLP task differs from previous studies in that it no longer relies on back-translation for evaluation. With the provision of a comprehensive sign language vocabulary and corresponding landmark data, the model only needs to achieve precise conversion from natural language to sign language symbols to generate pose-accurate sign language videos. This approach ensures a high level of consistency in the pose information for each sign language symbol, significantly enhancing the accuracy and coherence of the generated sign language videos. This design not only makes the SLP task evaluation more direct and reliable but also provides an efficient benchmark for sign language production, offering an important reference for future research.

Ablation Studies

Sign Language Production Task The following ablation studies were conducted on the test set of the CNText2Sign dataset, with the baseline model for the second ablation experiment being Glm-4-0520.

	Phoenix2014-T dataset [33] (Dev/Test)				
Model	ROUGE	BLEU-1	BLEU-2	BLEU-3	BLEU-4
SL-Luong [12]	31.80/31.80	31.87/32.24	19.11/19.03	13.16/12.83	9.94/9.58
TSPNet [16]	-/34.96	-/36.10	-/12.88	-/16.83	-/13.41
Joint-SLRT [6]	-/-	47.26/46.61	34.40/37.73	27.05/26.19	22.38/21.32
STMC-T [34]	48.24/46.65	47.60/46.98	36.43/36.09	29.18/28.70	24.09/23.65
SignBT [32]	50.29/49.54	51.11/50.80	37.90/37.75	29.80/29.72	24.45/24.32
MMTLB [8]	53.10/52.65	53.95/53.97	41.12/41.75	33.14/33.84	27.61/28.39
TwoStream-SLT [15]	54.08/53.48	54.32/54.90	41.99/42.43	34.15/34.46	28.66/28.95
SignMST-C (Ours)	57.73/56.13	58.03/57.63	43.96/45.32	36.87/37.21	31.03/32.08

Table 2. Comparison of State-of-the-Art Methods on the Phoenix2014-T Dataset for the Sign-to-Text Task. Results better than the SOTAs are in bold.

CNText2Sign Sign Language Production Results (Dev/Test)						
Model	BLEU-1	BLEU-2	BLEU-3	BLEU-4	CER (%)	
Qwen2.5-3b-instruct-lora-rag	58.32/57.13	50.6/49.91	41.68/40.32	35.17/34.26	46.61/45.23	
Qwen2.5-32b-instruct-lora-rag	66.16/64.94	58.7/56.52	50.2/49.22	43.5/42.34	40.5/38.92	
Glm-4-9b-lora-rag	62.58/61.37	54.15/53.14	45.13/44.59	38.16/36.38	46.2/45.14	
Glm-4-0520-lora-rag	69.54/68.31	62.03/61.24	53.31/51.25	50.41/49.23	34.95/33.86	
CNSign SLT Results (Dev/Test)						
Model	BLEU-1	BLEU-2	BLEU-3	BLEU-4	ROUGE	
SignMST	35.47/33.98	23.13/22.21	17.42/16.23	13.94/11.45	34.80/32.86	
SignMST-C	44.37/42.73	33.21/31.84	26.81/24.63	22.43/20.74	44.98/42.36	

Table 3. CNText2Sign Sign Language Production Results (Dev/Test) and CNSign SLT Results (Dev/Test). The best results are in bold.

Direct Application of Large Model to ZRSL As given in Table 4, it is evident that directly using the large model to translate natural language into sign language yields extremely poor results. This is because the sign language vocabulary is significantly smaller than the natural language vocabulary, leading to a limited expressive capability.

Model	BLEU-1	BLEU-2	BLEU-3	BLEU-4
GPT-40	32.47	28.79	24.43	19.87
Glm-4-0520	29.13	24.59	20.11	15.64
Qwen2.5-32-instruct	23.51	19.91	15.83	11.27
Glm-4-520-lora-rag	69.54	62.03	53.31	34.95

Table 4. Performance Comparison of LLMs on the Text-to-Gloss Task. The best results are in bold.

Effectiveness of RAG, LoRA, and Embedding We explore the effectiveness of RAG, LoRA, and Embedding. Embedding represents the process of embedding vocabulary and non-retrieved words, followed by cosine similarity matching. The absence of Embedding indicates direct retrieval without this processing. As shown in Table 5, using LoRA significantly improves results, indicating that it can increase the success rate of RAG. Additionally, Embedding provides a noticeable improvement in the results.

RAG	LoRA	RAG-embedding	CER (%)
\checkmark	×	×	41.83
\checkmark	\checkmark	×	45.83
\checkmark	×	\checkmark	38.64
×	\checkmark	×	56.73
\checkmark	\checkmark	\checkmark	34.95

Table 5. Effect of RAG, LoRA, and RAG-embedding on CER (%). The best results are in bold.

SLT Task To evaluate the effectiveness of our SignMST-C, we compare it with other methods on the Phoenix-2014T benchmark in the field of SLT. All other ablation experiments are conducted on the test set of CNSign.

Our SignMST-C method achieved state-of-the-art results on the Sign-to-Text task in the Phoenix2014-T dataset, as shown in Table 3, demonstrating the effectiveness of our model architecture.

Impact on self-supervised learning in fast-motion regions, multimodal fusion, and the text correction network Results in Table 6 indicate that the text correction network provides the most significant improvement, especially when the base model achieves higher accuracy, showing that the network's enhancements become more pronounced as overall model precision increases.

Pretrain	Landmark	Text Correction Network	ROUGE
\checkmark	×	×	30.13
\checkmark	\checkmark	×	32.86
\checkmark	×	\checkmark	37.53
×	\checkmark	×	27.41
×	×	\checkmark	31.13
×	\checkmark	\checkmark	32.54
\checkmark	\checkmark	\checkmark	42.36

Table 6. ROUGE Scores with Different Configurations. The best result is bold.

6. Conclusion

We introduced high-precision models for sign language production (SLP) and translation (SLT), AuraLLM and SignMST-C, along with two new Chinese sign language datasets, CNText2Sign and CNSign, addressing the critical shortage of Chinese sign language resources. AuraLLM leverages LoRA fine-tuning and RAG retrieval to enable efficient text-to-sign conversion, while SignMST-C establishes a new SLT benchmark on the Phoenix2014-T dataset through self-supervised pretraining and multimodal feature fusion. To support further advancements in sign language technology and foster inclusive communication, we will publicly release all data and code.

References

- Uwe Von Agris and Klaus F. Kraiss. Signum database: Video corpus for signer-independent continuous sign language recognition. In *Workshop on Representation and Processing of Sign Languages*, pages 243–246, 2010. 4
- [2] M. Bohacek and M. Hrúz. Sign pose-based transformer for word-level sign language recognition. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision (WACV) Workshops*, pages 182–191, 2022. 3
- [3] D. Bragg, O. Koller, M. Bellard, L. Berke, M. Saenz, and R. Kushalnagar. Sign language recognition, generation, and translation: An interdisciplinary perspective. In *Proceedings* of the 21st International ACM SIGACCESS Conference on Computers and Accessibility (ASSETS), 2019. 2
- [4] T.B. Brown, B. Mann, N. Ryder, M. Subbiah, J. Kaplan, P. Dhariwal, A. Neelakantan, P. Shyam, G. Sastry, A. Askell, S. Agarwal, A. Herbert-Voss, G. Krueger, T. Henighan, R. Child, A. Ramesh, D.M. Ziegler, J. Wu, C. Winter, C. Hesse, M. Chen, E. Sigler, M. Litwin, S. Gray, B. Chess, J. Clark, C. Berner, S. McCandlish, A. Radford, I. Sutskever, and D. Amodei. Language models are few-shot learners. In Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020 (NeurIPS 2020), pages 1877–1901. Curran Associates, Inc., 2020. 3
- [5] Necati Cihan Camgoz, Oscar Koller, Simon Hadfield, and Richard Bowden. Sign language transformers: Joint end-toend sign language recognition and translation. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR), pages 10023–10033, 2020. 3
- [6] Z. Cao, G. Hidalgo, T. Simon, S.E. Wei, and Y. Sheikh. Openpose: Realtime multi-person 2d pose estimation using

part affinity fields. In *Proceedings of the IEEE Conference* on Computer Vision and Pattern Recognition (CVPR), 2017. 2, 3, 8

- [7] J. Carreira and A. Zisserman. Quo vadis, action recognition? a new model and the kinetics dataset. In *Proceedings* of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR), 2017. 2
- [8] C. Chan, S. Ginosar, T. Zhou, and A.A. Efros. Everybody dance now. In *Proceedings of the IEEE International Conference on Computer Vision (CVPR)*, 2019. 8
- [9] Yutong Chen, Fangyun Wei, Xiao Sun, Zhirong Wu, and Stephen Lin. A simple multi-modality transfer learning baseline for sign language translation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 5120–5130, 2022. 3
- [10] Yutong Chen, Ronglai Zuo, Fangyun Wei, Yu Wu, Shujie Liu, and Brian Mak. Two-stream network for sign language recognition and translation. In Advances in Neural Information Processing Systems (NeurIPS), 2022. Proceedings of NeurIPS 2022. 3
- [11] A. Chowdhery, S. Narang, J. Devlin, M. Bosma, G. Mishra, A. Roberts, P. Barham, H.W. Chung, C. Sutton, S. Gehrmann, P. Schuh, K. Shi, S. Tsvyashchenko, J. Maynez, A. Rao, P. Barnes, Y. Tay, N. Shazeer, V. Prabhakaran, E. Reif, N. Du, B. Hutchinson, R. Pope, J. Bradbury, J. Austin, M. Isard, G. Gur-Ari, P. Yin, T. Duke, A. Levskaya, S. Ghemawat, S. Dev, H. Michalewski, X. Garcia, V. Misra, K. Robinson, L. Fedus, D. Zhou, D. Ippolito, D. Luan, H. Lim, B. Zoph, A. Spiridonov, R. Sepassi, D. Dohan, S. Agrawal, M. Omernick, A.M. Dai, T.S. Pillai, M. Pellat, A. Lewkowycz, E. Moreira, R. Child, O. Polozov, K. Lee, Z. Zhou, X. Wang, B. Saeta, M. Diaz, O. Firat, M. Catasta, J. Wei, K. Meier-Hellstern, D. Eck, J. Dean, S. Petrov, and N. Fiedel. Palm: Scaling language modeling with pathways. *CoRR*, abs/2204.02311, 2022. 3
- [12] N. Cihan Camgoz, S. Hadfield, O. Koller, H. Ney, and R. Bowden. Neural sign language translation. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 7784–7793, 2018. 3, 4, 8
- [13] S. Cox, M. Lincoln, J. Tryggvason, M. Nakisa, M. Wells, M. Tutt, and S. Abbott. Tessa, a system to aid communication with deaf people. In *Proceedings of the ACM International Conference on Assistive Technologies*, 2002. 2
- [14] A. Duarte, S. Palaskar, L. Ventura, D. Ghadiyaram, K. De-Haan, F. Metze, J. Torres, and X. Giro i Nieto. How2sign: A large-scale multimodal dataset for continuous american sign language. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2021. 3
- [15] Sen Fang, Lei Wang, Ce Zheng, Yapeng Tian, and Chen Chen. Signllm: Sign languages production large language models, 2024. 2, 3, 4, 8
- [16] S. Ham, K. Park, Y. Jang, Y. Oh, S. Yun, S. Yoon, C.J. Kim, H.M. Park, and I.S. Kweon. Ksl-guide: A large-scale korean sign language dataset including interrogative sentences for guiding the deaf and hard-of-hearing. In *IEEE International Conference on Automatic Face and Gesture Recognition*, 2021. 8
- [17] Tobias Hanke, Michael Schulder, Roland Konrad, and Elias Jahn. Extending the public dgs corpus in size and depth. In

LREC2020 - Workshop on the Representation and Processing of Sign Languages, pages 75–82, 2020. 4

- [18] Ming Hu, Kun Yuan, Yaling Shen, Feilong Tang, Xiaohao Xu, Lin Zhou, Wei Li, Ying Chen, Zhongxing Xu, Zelin Peng, et al. Ophclip: Hierarchical retrieval-augmented learning for ophthalmic surgical video-language pretraining. arXiv preprint arXiv:2411.15421, 2024. 2
- [19] Ming Hu, Peng Xia, Lin Wang, Siyuan Yan, Feilong Tang, Zhongxing Xu, Yimin Luo, Kaimin Song, Jurgen Leitner, Xuelian Cheng, et al. Ophnet: A large-scale video benchmark for ophthalmic surgical workflow understanding. In *ECCV*, 2025. 2
- [20] J. Huang, W. Zhou, Q. Zhang, H. Li, and W. Li. Videobased sign language recognition without temporal segmentation. In *Proceedings of the AAAI Conference on Artificial Intelligence*, 2018. 4
- [21] W. Huang, W. Pan, Z. Zhao, and Q. Tian. Towards fast and high-quality sign language production. In *Proceedings of the* 29th ACM International Conference on Multimedia (ACM MM). ACM, 2021. 2
- [22] W. Huang, W. Pan, Z. Zhao, and Q. Tian. Towards fast and high-quality sign language production. In *Proceedings of the 29th ACM International Conference on Multimedia*, New York, NY, USA, 2021. ACM. 3
- [23] Y. Kang and et al. Natural language processing (nlp) in management research: A literature review. *Journal of Management Analytics*, 7(2):139–172, 2020. 1
- [24] K. Karpouzis, G. Caridakis, S.E. Fotinea, and E. Efthimiou. Educational resources and implementation of a greek sign language synthesis architecture. *Computers & Education*, 48(1):35–52, 2007. 2
- [25] S.K. Ko, C.J. Kim, H. Jung, and C. Cho. Neural sign language translation based on human keypoint estimation. *Applied Sciences*, 9(20):4307, 2019. 3
- [26] Karolina Kozik. Without sign language, deaf people are not equal: Governments should ensure equal access to information and services, 2019. Published on September 23, 2019, Disability Rights Division, Available in English and Français. 1
- [27] J. Kreutzer, J. Bastings, and S. Riezler. Joey nmt: A minimalist nmt toolkit for novices. In *Proceedings of the Conference on Empirical Methods in Natural Language Processing* (*EMNLP*), 2019. 3
- [28] Dongxu Li, Chenchen Xu, Xin Yu, Kaihao Zhang, Benjamin Swift, Hanna Suominen, and Hongdong Li. Tspnet: Hierarchical feature learning via temporal semantic pyramid for sign language translation. In Advances in Neural Information Processing Systems (NeurIPS), pages 12034–12045, 2020. 3
- [29] C. Lugaresi, J. Tang, H. Nash, C. McClanahan, E. Uboweja, M. Hays, F. Zhang, C.L. Chang, M.G. Yong, J. Lee, and et al. Mediapipe: A framework for building perception pipelines. *arXiv preprint arXiv:1906.08172*, 2019. 2
- [30] S. Mazumder, R. Mukhopadhyay, V.P. Namboodiri, and C.V. Jawahar. Translating sign language videos to talking faces. In Proceedings of the Twelfth Indian Conference on Computer Vision, Graphics and Image Processing (ICVGIP '21), New York, NY, USA, 2021. Association for Computing Machinery. 2

- [31] J. McDonald, R. Wolfe, J. Schnepp, J. Hochgesang, D.G. Jamrozik, M. Stumbo, L. Berke, M. Bialek, and F. Thomas. Automated technique for real-time production of lifelike animations of american sign language. *Universal Access in the Information Society (UAIS)*, 15(4):755–769, 2016. 2
- [32] Y. Men, Y. Mao, Y. Jiang, W.Y. Ma, and Z. Lian. Controllable person image synthesis with attribute-decomposed gan. In Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR), 2020. 8
- [33] Yuecong Min, Aiming Hao, Xiujuan Chai, and Xilin Chen. Visual alignment constraint for continuous sign language recognition. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 11542–11551, 2021. 8
- [34] M. Müller, M. Alikhani, E. Avramidis, R. Bowden, A. Braffort, N. Cihan Camgöz, S. Ebling, C. España-Bonet, A. Göhring, R. Grundkiewicz, M. Inan, Z. Jiang, O. Koller, A. Moryossef, A. Rios, D. Shterionov, S. Sidler-Miserez, K. Tissi, and D. Van Landuyt. Findings of the second wmt shared task on sign language translation (wmt-slt23). In *Proceedings of the Eighth Conference on Machine Translation*, pages 68–94, Singapore, 2023. Association for Computational Linguistics. 8
- [35] United Nations. International day of sign languages, 2023. Accessed: 2024-11-14. 1
- [36] C. Neidle and C. Vogler. A new web interface to facilitate access to corpora: Development of the asllrp data access interface (dai). In Proceedings of the 5th Workshop on the Representation and Processing of Sign Languages: Interactions between Corpus and Lexicon. LREC, 2012. 4
- [37] Ilias Papastratis, Christos Chatzikonstantinou, Dimitrios Konstantinidis, Kosmas Dimitropoulos, and Petros Daras. Artificial intelligence technologies for sign language. Sensors, 21(17):5843, 2021. Submission received: 30 July 2021 / Revised: 22 August 2021 / Accepted: 26 August 2021 / Published: 30 August 2021. 2
- [38] A. Paszke, S. Gross, S. Chintala, G. Chanan, E. Yang, Z. De-Vito, Z. Lin, A. Desmaison, L. Antiga, and A. Lerer. Automatic differentiation in pytorch. In *NIPS Autodiff Workshop*, 2017. 3
- [39] A. Radford, J. Wu, R. Child, D. Luan, D. Amodei, I. Sutskever, and et al. Language models are unsupervised multitask learners. OpenAI blog, 2019. p. 9. 3
- [40] C. Raffel, N. Shazeer, A. Roberts, K. Lee, S. Narang, M. Matena, Y. Zhou, W. Li, and P. J. Liu. Exploring the limits of transfer learning with a unified text-to-text transformer. *The Journal of Machine Learning Research*, 21(1):5485–5551, 2020. 3
- [41] B. Saunders, N.C. Camgöz, and R. Bowden. Progressive transformers for end-to-end sign language production. In *Proceedings of the European Conference on Computer Vision (ECCV)*, Cham, 2020. Springer. 3
- [42] B. Saunders, N.C. Camgöz, and R. Bowden. Progressive transformers for end-to-end sign language production. In *Proceedings of the European Conference on Computer Vi*sion (ECCV), 2020. 2
- [43] B. Saunders, N.C. Camgöz, and R. Bowden. Continuous 3d multi-channel sign language production via progressive

transformers and mixture density networks. International Journal of Computer Vision (IJCV), 2021. 2

- [44] B. Saunders, N.C. Camgöz, and R. Bowden. Continuous 3d multi-channel sign language production via progressive transformers and mixture density networks. *International Journal of Computer Vision (IJCV)*, 129(3):859–877, 2021.
 3
- [45] B. Saunders, N.C. Camgöz, and R. Bowden. Mixed signals: Sign language production via a mixture of motion primitives. In *Proceedings of the International Conference on Computer Vision (ICCV)*, Montreal, Canada, 2021. IEEE. 3
- [46] B. Saunders, N.C. Camgöz, and R. Bowden. Mixed signals: Sign language production via a mixture of motion primitives. In *Proceedings of the International Conference on Computer Vision (ICCV)*, 2021. 2
- [47] B. Saunders, N.C. Camgöz, and R. Bowden. Skeletal graph self-attention: Embedding a skeleton inductive bias into sign language production. *arXiv preprint arXiv:2112.05277*, 2021. 2, 3
- [48] A. Schembri, J. Fenlon, R. Rentelis, S. Reynolds, and K. Cormier. Building the british sign language corpus. *Language Documentation & Conservation*, 7:136–154, 2013. 4
- [49] United Nations Secretariat. 2009 report of the united nations secretariat, 2009. United Nations, New York. 1
- [50] J. Segouat. A study of sign language coarticulation. ACM SIGACCESS Accessibility and Computing, 94:41–46, 2009.
 2
- [51] M. Shanahan. Talking about large language models. CoRR, abs/2212.03551, 2022. 3
- [52] Feilong Tang, Zhongxing Xu, Qiming Huang, Jinfeng Wang, Xianxu Hou, Jionglong Su, and Jingxin Liu. Dual: Dualaggregation transformer network for medical image segmentation. In *PRCV*, 2023. 2
- [53] Feilong Tang, Zhongxing Xu, Zhaojun Qu, Wei Feng, Xingjian Jiang, and Zongyuan Ge. Hunting attributes: Context prototype-aware learning for weakly supervised semantic segmentation. In CVPR, 2024. 2
- [54] R. Taylor, M. Kardas, G. Cucurull, T. Scialom, A. Hartshorn, E. Saravia, A. Poulton, V. Kerkez, and R. Stojnic. Galactica: A large language model for science. *CoRR*, abs/2211.09085, 2022. 3
- [55] H. Touvron, T. Lavril, G. Izacard, X. Martinet, M. Lachaux, T. Lacroix, B. Rozière, N. Goyal, E. Hambro, F. Azhar, A. Rodriguez, A. Joulin, E. Grave, and G. Lample. Llama: Open and efficient foundation language models. *CoRR*, abs/2302.13971, 2023. 3
- [56] Jinfeng Wang, Qiming Huang, Feilong Tang, Jia Meng, Jionglong Su, and Sifan Song. Stepwise feature fusion: Local guides global. In *MICCAI*. Springer, 2022. 2
- [57] Zhongxing Xu, Feilong Tang, Zhe Chen, Zheng Zhou, Weishan Wu, Yuyao Yang, Yu Liang, Jiyu Jiang, Xuyue Cai, and Jionglong Su. Polyp-mamba: Polyp segmentation with visual mamba. In *MICCAI*. Springer, 2024. 2
- [58] Jian Zhao, Weizhen Qi, Wengang Zhou, Nan Duan, Ming Zhou, and Houqiang Li. Conditional sentence generation and cross-modal reranking for sign language translation. *IEEE Transactions on Multimedia*, 24:2662–2672, 2021. 3

- [59] Xinqiao Zhao, Feilong Tang, Xiaoyang Wang, and Jimin Xiao. Sfc: Shared feature calibration in weakly supervised semantic segmentation. In AAAI, 2024. 2
- [60] Hao Zhou, Wengang Zhou, Weizhen Qi, Junfu Pu, and Houqiang Li. Improving sign language translation with monolingual data by sign back-translation. In *Proceedings* of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR), pages 1316–1325, 2021. 3
- [61] Hao Zhou, Wengang Zhou, Yun Zhou, and Houqiang Li. Spatial-temporal multi-cue network for sign language recognition and translation. *IEEE Transactions on Multimedia*, 24:768–779, 2021. 3