# Fresh-CL: Feature Realignment through Experts on Hypersphere in Continual Learning

Zhongyi Zhou<sup>1</sup>, Yaxin Peng<sup>2</sup>, Pin Yi<sup>2</sup>, Minjie Zhu<sup>1</sup>, Chaomin Shen <sup>1</sup>

<sup>1</sup>School of Computer Science, East China Normal University, Shanghai, China <sup>2</sup>Department of Mathematics, Shanghai University, Shanghai, China

Abstract-Continual Learning enables models to learn and adapt to new tasks while retaining prior knowledge. Introducing new tasks, however, can naturally lead to feature entanglement across tasks, limiting the model's capability to distinguish between new domain data. In this work, we propose a method called Feature Realignment through Experts on hyperSpHere in Continual Learning (Fresh-CL). By leveraging predefined and fixed simplex equiangular tight frame (ETF) classifiers on a hypersphere, our model improves feature separation both intra and inter tasks. However, the projection to a simplex ETF shifts with new tasks, disrupting structured feature representation of previous tasks and degrading performance. Therefore, we propose a dynamic extension of ETF through mixture of experts, enabling adaptive projections onto diverse subspaces to enhance feature representation. Experiments on 11 datasets demonstrate a 2% improvement in accuracy compared to the strongest baseline, particularly in fine-grained datasets, confirming the efficacy of combining ETF and MoE to improve feature distinction in continual learning scenarios.

Index Terms—Continual Learning, Neural Collapse, Mixture of Experts

## I. INTRODUCTION

Humans are capable of achieving ongoing learning capacity and preservation of learned information. Similarly, deep learning models are expected to preserve past knowledge while continuously inferring new information. This domain, known as Continual Learning (CL), has gained significant attention in recent years. Existing works in CL continue to face a major challenge known as catastrophic forgetting, where the feature representations of previously learned data are overwritten by updates from newly introduced tasks. Despite numerous efforts, including changes in neural architecture (e.g., L2P [1], DualPrompt [2]) and feature distillation (e.g., GFR [3], FA [4] and DSR [5]), the problem in representation shift remains unresolved. One important observation that has been made for the catastrophic forgetting is that, deep learning models typically fail to disentangle feature representations across different classes, as the number of classes from diverse domains incrementally added into the model. This especially happens in fine-grained datasets and can lead to feature overlap and representation confusion, as is shown in Fig. 1.

To address this challenge, recent works have turned to neural collapse (NC), a phenomenon in which classifier vectors and



Fig. 1. t-SNE visualization of Aircraft dataset features. (a) Features extracted by MOA tend to blend together, making them recognizable as a single "aircraft" class. (b) Our method improves feature separation, enabling distinct class recognition.

activations for all classes converge into a simplex equiangular tight frame (ETF) [6]–[9]. In this structure, all classes are represented as maximally separated points, effectively reducing the overlap between class features. While NC improves feature separation in intra-domain tasks [10]–[12], its performance diminishes in inter-domain tasks. As new tasks with significant domain differences are introduced, the projection onto the ETF degrades, disrupting the structure learned from earlier tasks and causing performance drop across domains.

In this paper, we propose a neural collapse inspired mixture of experts model, termed as Feature Realignment through Experts on hyperSpHere in Continual Learning (Fresh-CL). By using predefined equiangular vectors as targets for each class feature, features across different classes can be distinguished effectively. However, we found that the model's ability to maintain projection onto the ETF may gradually diminish when only a single ETF is used. To address this, we propose a mixture-of-experts approach that leverages multiple ETFs to improve the classification of feature representations across different classes.

Our contribution can be summarized as follows:

• We introduce an optimal pre-assigned alignment structure, inspired by neural collapse, as fixed targets, aiming to distinguish feature representations from each other in

This work is supported by the Sci-Tech Innovation Initiative by the Science and Technology Commission of Shanghai Municipality (24ZR1419000), and the National Science Foundation of China (12471501).



Fig. 2. Overall framework of Fresh-CL. When training **Task** t, each input image  $x_k$  is fed into a frozen backbone, and then processed through a dynamic routing mechanism, which select the top-k (e.g. top-2) appropriate experts i and j using gating weights  $G_i^t$  and  $G_j^t$ . These experts project the normalized features  $\hat{\mu}_k^i$  and  $\hat{\mu}_k^j$  into distinct hyperspheres, aligning each of them with their corresponding predefined "pseudo targets"  $w_a^i$  and  $w_a^j$  on the relevant hypersphere. The subscripts a, b, c represent arbitrary labels from the label space  $C^t$ . These pseudo targets are predefined as equiangular vectors  $\hat{W}_{ETF}^i$  and  $\hat{W}_{ETF}^j$  for each class of all tasks. By using the DR loss, we force these features close to their corresponding targets, therefore achieve max separation on each appropriate hypersphere selected by the MoE module.

multi-domain tasks.

- We propose an extensible framework which employs experts to provide multiple projections to different hyperspheres, inducing neural collapse in various subspaces.
- Experiments on 11 datasets illustrate that our method achieves 2% and 1.1% over a recent strong baseline under full-shot and few-shot multi-task incremental learning settings.

#### **II. PRELIMINARIES**

# A. Problem Statement of Continual Learning

Existing continual learning (CL) methods are typically categorized into Class Incremental Learning (CIL) [13]–[15], which learns new classes within a single domain, and Task Incremental Learning (TIL) [16]–[18], which addresses tasks across different domains. Specifically, each CL method trains a model incrementally on a sequence of training datasets  $\{\mathcal{D}^{(0)}, \mathcal{D}^{(1)}, \dots, \mathcal{D}^{(T)}\}$ , where  $\mathcal{D}^{(t)} = \{(\boldsymbol{x}_i, y_i)\}_{i=1}^{|\mathcal{D}^{(t)}|}$  for task  $t \in [0, T]$ , with  $\boldsymbol{x}_i$  representing the input image and  $y_i$  representing the corresponding label. The label space  $\mathcal{C}^{(t)}$  of task t has no overlap with any other task t', i.e.  $\mathcal{C}^{(t)} \cap \mathcal{C}^{(t')} = \emptyset$ , for all  $t' \neq t \in [0, T]$ . When learning task t, data of previous tasks remains inaccessible. Only the current dataset  $\mathcal{D}^{(t)}$  can be accessed.

## B. Neural Collapse

Previous studies [8] observed that the last layer feature and its corresponding classifier weights form an optimal structure at the terminal phase of training. This phenomenon is called neural collapse.

When neural collapse happens, the collection of K classifier vectors  $w_1, w_2, \dots, w_K$  form a simplex equiangular tight frame (ETF)  $W_{ETF} = [w_1, w_2, \dots, w_K]$ , which satisfies

$$\boldsymbol{w}_i^T \boldsymbol{w}_j = \frac{K}{K-1} \delta_{i,j} - \frac{1}{K-1}, \quad \forall i, j \in [1, K].$$
(1)

where  $\delta_{i,j} = 1$  when i = j, and 0 otherwise.

This implies that all column vectors in  $W_{ETF}$  have the same  $l_2$  norm and each pair has the same inner product.

### III. METHODOLOGY

In this paper, we propose Fresh-CL, an extensible training framework designed to enhance feature separation across various continual learning settings. The overall architecture of our proposed framework is illustrated in Fig. 2. In Section III-A, we first present our fixed simplex equiangular tight frame (ETF) classifier, which is inspired by the neural collapse phenomenon. Beyond the standard projection which maps onto the same hypersphere, we introduce a series of specialized experts. These experts are coupled with a gating mechanism

Method	Aircraft*	Caltech101 [26]	CIFAR100 [27]	DTD [28]	EuroSAT [29]	Flowers*	Food* [23]	MNIST [30]	OxfordPet* [24]	StanfordCars*	su <sub>[31]</sub>	Average
Continual-FT	31.0	89.3	65.8	67.3	88.9	71.1	85.6	99.6	92.9	77.3	81.1	77.3
LwF	26.3	87.5	71.9	66.6	79.9	66.9	83.8	99.6	92.1	66.1	80.4	74.6
iCaRL	35.8	93.0	77.0	70.2	83.3	88.5	90.4	86.7	93.2	81.2	81.9	80.1
LwF-VR	20.5	89.8	72.3	67.6	85.5	73.8	85.7	99.6	93.1	73.3	80.9	76.6
WiSE-FT	27.2	90.8	68.0	68.9	86.9	74.0	87.6	99.6	92.6	77.8	81.3	77.7
ZSCL	40.6	92.2	81.3	70.5	94.8	90.5	91.9	98.7	93.9	85.3	80.2	83.6
MOA	49.8	92.2	86.1	78.1	95.7	94.3	89.5	98.1	89.9	81.6	80.0	85.0
Fresh-CL(1k)	51.6	94.9	83.6	77.9	95.3	97.0	92.1	98.8	94.1	86.2	80.3	86.5(+1.5)
Fresh-CL(3k)	52.4	95.4	83.5	78.2	96.9	97.1	92.7	98.8	93.8	86.5	81.2	87.0(+2.0)

 TABLE I

 Last accuracy score under full-shot MTIL setting.

\* represent fine-grained datasets.

that dynamically adjusts the projection pathways. This design ensures task-specific alignment between features and their respective hypersphere targets, as elaborated in Section III-B.

# A. Inducing Neural Collapse for Continual Learning

While the common models incrementally introduce new tasks or classes, class separation may gradually decreases and feature overlap may occur, leading to performance degradation.

Considering about the optimal alignment provided by ETF structure, which ensures that classes are maximally separated in the feature space, we are motivated to induce neural collapse in a CL process.

Specifically, we employ a fixed ETF  $\hat{W}_{ETF} \in \mathbb{R}^{d \times K}$  as a "pseudo target" on the hypersphere, where d is the dimension of the feature space and K is the number of ETF vectors. The pre-defined pseudo targets are generated by the ETF structure. Although these targets do not directly correspond to specific class features, they serve as idealized reference points. These targets maintain maximum separation on the hypersphere. As a result, they provide a stable reference point, which helps prevent feature interference when learning new classes. This is particularly important in CL, where newly introduced tasks may interfere with previously learned class representations.

In particular, when incrementally training new data from novel classes or tasks, the extracted feature is guided by Dot-Regression Loss ( $\mathcal{L}_{DR}$ ). This loss function aligns the feature with the pseudo target vector on the hypersphere, which is indexed by the class-encoded numerical value, i.e.

$$\mathcal{L}_{DR}\left(\hat{\boldsymbol{\mu}}_{i},\hat{\boldsymbol{W}}_{ETF}\right) = \frac{1}{2}\left(\hat{\boldsymbol{w}}_{y_{i}}^{T}\hat{\boldsymbol{\mu}}_{i}-1\right)^{2},$$
(2)

where  $y_i \in \mathbb{R}^+$  is the class label of data  $x_i$ ,  $\hat{w}_{y_i}$  is the  $y_i$ -th vector of  $\hat{W}_{ETF}$ , and  $\hat{\mu}_i = \mu_i / ||\mu_i||$  is the normalized feature of  $x_i$  extracted by the backbone f.

A key consideration is the dimension of  $\hat{W}_{ETF} \in \mathbb{R}^{d \times K}$ . Unlike previous works that pre-counted the total number of classes for all tasks to specify a fixed K, we do not assume a known total class number. Instead, we set K equal to the feature dimension d, since the total number of classes is unknown and will increase in real CL scenarios.

# B. Incremental Mixture of ETF Classifiers

Although a single ETF can effectively distinguish features across different classes, when the differences between task domains are significant, the way the model projects onto the ETF may gradually be forgotten. In other words, while the new domain can be accommodated through adaptive projection, this often comes at the cost of disrupting the ETF properties learned from earlier tasks. As a result, the model's performance on previous domains may degrade. To achieve the goal of domain-specific adaption, we introduce Mixture of Experts (MoE) [19], [20] into our framework. By dynamically selecting experts tailored to each task, MoE enables different projections for tasks across different domains, ensuring that each task is mapped to the appropriate subspace.

**ETF classifier as Expert.** MoE is designed to improve model performance by dynamically selecting specialized subnetworks, named "experts", based on the input data. Each expert is a fully functional neural network, trained to perform well on specific subsets of the input space. As previously mentioned, a predefined ETF is employed as a pseudo target, enabling the projection layer to realign features with this target, thereby promoting effective feature separation.

Building upon this approach, each expert in our framework is designed as a specialized projection layer associated with a dedicated ETF. The ETF classifier expert ensures the maximal class separation by aligning features with predefined equiangular targets on the hypersphere, thus effectively addressing taskspecific feature representation needs. This design ensures that each task is mapped onto a distinct hyperspherical subspace, allowing for task-specific feature representations.

**Incremental Router for Expert Selection.** Regular setting in MoE uses one router to decide the probability of using certain expert. Under continual learning setting, we introduce a task-specific router  $\mathbf{R}^t$  for each task t, which dynamically computes the probability  $\mathbf{G}^t$  for selecting the most appropriate experts. The router ensures that each task is assigned to the experts best equipped to address its distinct requirements. Therefore, for each data  $\mathbf{x}_k$ , the overall loss function can be written as

$$\mathcal{L}_{k}^{t} = \sum_{i=1}^{N_{E}} G_{i}^{t} \mathcal{L}_{DR} \left( \hat{\boldsymbol{\mu}}_{i}, \boldsymbol{W}_{ETF}^{i} \right), \qquad (3)$$

TABLE II LAST ACCURACY SCORE UNDER FEW-SHOT MTIL SETTING

Method	Aircraft* [21]	Caltech101 [26]	CIFAR100 [27]	DTD [28]	EuroSAT [29]	Flowers*	Food* [23]	MNIST [30]	OxfordPet* [24]	StanfordCars*	SUN397 [31]	Average
Continual-FT	27.8	86.9	60.1	58.4	56.6	75.7	73.8	93.1	82.5	57.0	66.8	67.1
LwF	22.1	58.2	17.9	32.1	28.1	66.7	46.0	84.3	64.1	31.5	60.1	46.5
LwF-VR	22.9	89.8	59.3	57.1	57.6	79.2	78.3	77.7	83.6	60.1	69.8	66.9
WiSE-FT	30.8	88.9	59.6	60.3	80.9	81.7	77.1	94.9	83.2	62.8	70.0	71.9
ZSCL	26.8	88.5	63.7	55.7	60.2	82.1	82.6	58.6	85.9	66.7	70.4	67.4
MOA	30.1	89.0	68.9	63.7	82.2	88.7	84.9	89.1	87.8	69.6	72.3	75.1
Fresh-CL	31.8	90.4	69.5	62.5	81.7	94.2	86.8	88.6	89.2	70.1	72.9	76.2(+1.1)

\* represent fine-grained datasets.

where  $G_i^t$  is the *i*-th column of  $G^t$ , representing the gating weights of experts and can be computed as

$$\boldsymbol{G}^{t} = \text{Softmax}(\text{Topk}(\boldsymbol{R}^{t}(\hat{\boldsymbol{\mu}}_{i}))). \tag{4}$$

The Topk() method selects the k most relevant experts, and Softmax() normalizes the resulting values into a probability distribution over the selected experts. The gating network is trained to assign tasks to the appropriate experts, ensuring that task-relevant features are enhanced while reducing interference from other tasks.

After completing each training task t, we freeze the top k most frequently utilized experts to retain their domain-specific knowledge and specialized projection methods. These frozen experts provide stable feature representations for subsequent tasks, enhancing robustness. Despite being frozen, these experts remain selectable in future tasks, allowing the model to leverage their learned representations without additional updates.

## **IV. EXPERIMENTS**

# A. Experimental Setting

We evaluate Fresh-CL on 11 datasets under the Multitask Incremental Learning (MTIL) [18] setting. These datasets include fine-grained datasets (e.g. Aircraft [21], Flowers [22], Food [23], OxfordPet [24], StanfordCars [25]), and coarsegrained datasets (e.g. Caltech101 [26], CIFAR100 [27], DTD [28], EuroSAT [29], MNIST [30], SUN397 [31]).

To evaluate our method in mitigating the forgetting of previous knowledge, we use the last accuracy  $(A_{last})$  to measure the accuracy at the end of training across all tasks. We follow the training order proposed in [18].

**Implementation Details** We use the CLIP encoder with ViT-B/16 [32] as the backbone to extract image feature and set the total number of experts  $N_E = 22$ . The router is a single MLP that activates the experts with the top-2 gating scores. Following [33], we train an auto-task identifier using the pretrained AlexNet incrementally, therefore obtain the pseudo task id when performing inference on id-agnostic tasks. We train our method for 1k iterations per task under both full-shot and few-shot settings, using AdamW as our optimizer.

## B. Comparison with State-of-the-art Methods

We compare our Fresh-CL with various CL methods, including LwF [34], iCaRL [38], LwF-VR [35], WiSE-FT [36], ZSCL [37] and MOA [33]. **Full shot MTIL.** Tab. I displays the performance between Fresh-CL and other methods under the full shot MTIL setting. All the datasets in Tab. I are trained and tested following the left to right order. Fresh-CL outperforms the challenging baseline MOA by 1.5% in average, especially performs well in fine-grained datasets. By increasing the training iterations to 3k, our method (labeled "Fresh-CL(3k)") achieves further improvement of 2%.

**Few shot MTIL.** Tab. II shows our results under the fewshot MTIL setting, where the model is trained with 5 samples per class. Our Fresh-CL outperforms the second-best approach by an average of 1.1%, demonstrating its robustness in this challenging scenario.

**Computation Cost.** Thanks to the sparse property of MoE, our model only has trainable parameters of 56.22MB.

	TABLE III	
ABLATION STUDY	ON INCREMENTAL ETF CLASSIFIERS	

Mathad	Parar	Average		
Methou	Expert Number	Router Number	Average	
Continual-FT	/	/	77.3	
Fixed ETF w/o MoE	/	/	53.5	
Fixed ETF	2	1	58.24	
Fixed ETF	2	11	62.9	
Fixed ETF	4	11	71.3	
Fixed ETF	8	11	73.3	
Fixed ETF	11	11	84.4	

## C. Ablation Study

We conduct an ablation study as shown in Tab. III. All of these methods are built upon the same framework. To ensure fairness in scenarios with a limited number of experts, a probability of number of experts/11 is applied to freeze experts after the training stage for each task. Tab. III indicates that the degree of feature forgetting is progressively reduced as the number of experts increases, effectively mitigating the representation shift.

### V. CONCLUSION

We have introduced Fresh-CL, an NC-inspired model to mitigate feature interference in continual learning. By utilizing fixed simplex ETF as pseudo targets and incorporating a dynamic MoE, our approach has enhanced feature separation across tasks, ensuring distinct representations and mitigating the forgetting problem. Extensive experiments has shown that Fresh-CL outperforms state-of-the-art methods in both fullshot and few-shot settings, demonstrating its effectiveness in continual learning scenarios.

#### REFERENCES

- [1] Zifeng Wang, Zizhao Zhang, Chen-Yu Lee, Han Zhang, Ruoxi Sun, Xiaoqi Ren, Guolong Su, Vincent Perot, Jennifer Dy, and Tomas Pfister. Learning to prompt for continual learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 139-149, 2022.
- [2] Zifeng Wang, Zizhao Zhang, Sayna Ebrahimi, Ruoxi Sun, Han Zhang, Chen-YuLee, Xiaoqi Ren, Guolong Su, Vincent Perot, Jennifer Dy, et al. Dualprompt: Complementary prompting for rehearsal-free continual learning. In *European Conference on Computer Vision*, pages 631-648, 2022.
- [3] Xialei Liu, Chenshen Wu, Mikel Menta, Luis Herranz, Bogdan Raducanu, Andrew DBagdanov, Shangling Jui, and Joost van de Weijer. Generative feature replay for class-incremental learning. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition Workshops, pages 226-227, 2020.
- [4] Ahmet Iscen, Jeffrey Zhang, Svetlana Lazebnik, and Cordelia Schmid. Memory-efficient incremental learning through feature adaptation. In *Computer Vision–ECCV 2020: 16th European Conference, Glasgow, UK, August 23–28, 2020, Proceedings, Part XVI 16*, pages 699-715, 2020.
- [5] Kai Zhu, Wei Zhai, Yang Cao, Jiebo Luo, and Zheng-Jun Zha. Selfsustaining representation expansion for non-exemplar class-incremental learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 9296-9305, 2022.
- [6] Wenlong Ji, Yiping Lu, Yiliang Zhang, Zhun Deng, and Weijie Su. An unconstrained layer-peeled perspective on neural collapse. In *International Conference on Learning Representations*, 2021.
- [7] Akshay Rangamani and Andrzej Banburski-Fahey. Neural collapse in deep homogeneous classifiers and the role of weight decay. In *International Conference on Acoustics, Speech, and Signal Processing*. pages 4243-4247, 2022.
- [8] Vardan Papyan, XY Han, and David L Donoho. Prevalence of neural collapse during the terminal phase of deep learning training. *Proceed*ings of the National Academy of Sciences, 117(40):24652-24663, 2020.
- [9] Aleix M Martinez and Avinash C Kak. PCA versus LDA. IEEE Transactions on Pattern Analysis and Machine Intelligence, 23(2):228-233, 2001.
- [10] Ahmed N, Kukleva A, Schiele B. OrCo: Towards better generalization via orthogonality and contrast for few-shot class-incremental learning. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, pages 28762-28771, 2024.
- [11] Y Yang, H Yuan, X Li, Z Lin, P Torr, and D Tao. Neural collapse inspired feature-classifier alignment for few-shot class incremental learning. arXiv preprint arXiv:2302.03004, 2023.
- [12] Minhyuk Seo, Hyunseo Koh, Wonje Jeung, Minjae Lee, San Kim, Hankook Lee, Sungjun Cho, Sungik Choi, Hyunwoo Kim, and Jonghyun Choi. Learning equi-angular representations for online continual learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision* and Pattern Recognition, pages 23933-23942, 2024.
- [13] Shipeng Yan, Jiangwei Xie, and Xuming He. DER: Dynamically expandable representation for class incremental learning. In *Proceed*ings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, pages 3014-3023, 2021.
- [14] Eden Belouadah and Adrian Popescu. II2m: Class incremental learning with dual memory. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 583-592, 2019.
- [15] Quentin Jodelet, Xin Liu, Yin Jun Phua, and Tsuyoshi Murata. Classincremental learning using diffusion model for distillation and replay. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 3425-3433, 2023.
- [16] Arun Mallya and Svetlana Lazebnik. PackNet: Adding multiple tasks to a single network by iterative pruning. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 7765-7773, 2018.
- [17] Guy Oren and Lior Wolf. In defense of the learning without forgetting for task incremental learning. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 2209-2218, 2021.
- [18] Zangwei Zheng, Mingyuan Ma, Kai Wang, Ziheng Qin, Xiangyu Yue, and Yang You. Preventing zero-shot transfer degradation in continual learning of vision-language models. arXiv preprint arXiv:2303.06628, 2023.

- [19] Robert A Jacbs, Michael I Jordan, Steven J Nowlan, and Geoffrey E Hinton. Adaptive mixtures of local experts. *Neural Computation*, 3(1):79-87, 1991.
- [20] Noam Shazeer, Azalia Mirhoseini, Krzysztof Maziarz, Andy Davis, Quoc Le, Geoffrey Hinton, and Jeff Dean. Outrageously large neural networks: The sparsely-gated mixture-of-experts layer. arXiv preprint arXiv:1701.06538, 2017.
- [21] S Maji, E Rahtu, J Kannal, Blaschko M, Vedaldi A. Fine-grained visual classification of aircraft. arXiv preprint arXiv:1306.5151. 2013.
- [22] M-E Nilsback, A Zisserman. Automated flower classification over a large number of classes. In 2008 Sixth Indian Conference on Computer Vision, Graphics & Image Processing, pages 722-729, 2018.
- [23] L. Bossard, M. Guillaumin, L Van Gool. Food-101 Mining discriminative components with random forests. In *European Conference on Computer Vision*, pages 446-461, 2014.
- [24] OM Parkhi, A. Vedaldi, A. Zisserman, CV Jawahar. Cats and dogs. In IEEE Conference on Computer Vision and Pattern Recognition, pages 3498-3505, 2012.
- [25] J. Krause, M. Stark, J Deng J, L. Fei-Fei. 3D object representations for fine-grained categorization. In 4th IEEE Workshop on 3D Representation and Recognition, at ICCV 2013 (3DRR-13), 2013.
- [26] L. Fei-Fei, R. Fergus, P. Perona. Learning generative visual models from few training examples: an incremental Bayesian approach tested on 101 object categories. In *Computer Vision and Pattern Recognition Workshop*, 2004.
- [27] Arthur Douillard, Alexandre Ramé, Guillaume Couairon, and Matthieu Cord. Dytox: Transformers for continual learning with dynamic token expansion. In *Proceedings of the IEEE/CVF Conference on Computer* vision and Pattern Recognition, pages 9285-9295, 2022.
- [28] M. Cimpoi, S. Maji, I. Kokkinos, S. Mohamed, A. Vedaldi. Describing textures in the wild. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 3606-3613, 2014.
- [29] P. Helber, B. Bischke, A. Dengel, D. Borth. EuroSAT: A novel dataset and deep learning benchmark for land use and land cover classification. *arXiv preprint arXiv:1709.00029.* 2017.
- [30] Y. LeCun, C. Cortes, C. Burges. MNIST handwritten digit database. ATT Labs[Online]. Available from: http://yann.lecun.com/exdb/mnist. 2010.
- [31] J. Xiao, J. Hays, KA Ehinger, A. Oliva, A. Torralba. SUN database: Large-scale scene recognition from abbey to zoo. In 2010 IEEE Computer Society Conference on Computer Vision and Pattern Recognition, pages 3485-3492, 2010.
- [32] Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, et al. An image is worth 16x16 words: Transformers for image recognition at scale. arXiv preprint arXiv:2010.11929, 2020.
- [33] J. Yu, Y. Zhuge, L. Zhang, P. Hu, D. Wang, H. Lu, Y. He. Boosting continual learning of vision-language models via mixture-of-experts adapters. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 23219-23230, 2024.
- [34] Sang-Woo Lee, Jin-Hwa Kim, Jaehyun Jun, Jung-Woo Ha, and Byoung-Tak Zhang. Overcoming catastrophic forgetting by incremental moment matching. In Advances in Neural Information Processing Systems, pages 4655-4665, 2017.
- [35] Yuxuan Ding, Lingqiao Liu, Chunna Tian, Jingyuan Yang, and Haoxuan Ding. Don't stop learning: Towards continual learning for the CLIP model. arXiv preprint arXiv:2207.09248, 2022.
- [36] Mitchell Wortsman, Gabriel Ilharco, Jong Wook Kim, Mike Li, Simon Kornblith, Rebecca Roelofs Raphael Gontijo Lopes, Hannaneh Hajishirzi, Ali Farhadi, Hongseok Namkoong, et al. Robust fine-tuning of zero-shot models. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 7959-7971, 2022.
- [37] Zangwei Zheng, Mingyuan Ma, Kai Wang, Ziheng Qin, Xiangyu Yue, and Yang You. Preventing zero-shot transfer degradation in continual learning of vision-language models. arXiv preprint arXiv:2303.06628, 2023.
- [38] Sylvestre-Alvise Rebuffi, Alexander Kolesnikov, Georg Sperl, and Christoph H Lampert. iCaRL: Incremental classifier and representation learning. In *Proceedings of the IEEE conference on Computer Vision* and Pattern Recognition, pages 2001-2010, 2017.
- [39] Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, et al. Learning transferable visual models from natural language supervision. In *International Conference on Machine Learning*, pages 8748-8763, 2021.