Visual Large Language Models for Generalized and Specialized Applications

Yifan Li¹, Zhixin Lai², Wentao Bao¹, Zhen Tan³, Anh Dao¹, Kewei Sui⁴,

Jiayi Shen⁵, Dong Liu⁶, Huan Liu³, Yu Kong¹

¹Michigan State University, {liyifal1, baowenta, anhdao, yukong}@msu.edu

²Cornell University, z1768@cornell.edu

³Arizona State University, {ztan36, huanliu}@asu.edu

⁴University of California, Berkeley, ksui2@berkeley.edu

⁵University of Texas at Austin, sjyiya@gmail.com

⁶Yale University, pikeliu.misys@gmail.com

Abstract-Visual-language models (VLM) have emerged as a powerful tool for learning a unified embedding space for vision and language. Inspired by large language models, which have demonstrated strong reasoning and multi-task capabilities, visual large language models (VLLMs) are gaining increasing attention for building general-purpose VLMs. Despite the significant progress made in VLLMs, the related literature remains limited, particularly from a comprehensive application perspective, encompassing generalized and specialized applications across vision (image, video, depth), action, and language modalities. In this survey, we focus on the diverse applications of VLLMs, examining their using scenarios, identifying ethics consideration and challenges, and discussing future directions for their development. By synthesizing these contents, we aim to provide a comprehensive guide that will pave the way for future innovations and broader applications of VLLMs. The paper list repository is available: https://github.com/JackYFL/awesome-VLLMs.

Index Terms—Vision large language model (VLLM), Large Language Model (LLM), vision language model (VLM), applications, multi-modal learning

I. INTRODUCTION

Computer vision tasks are challenging and diverse, requiring machines to possess a range of capabilities such as object perception [1], [2], spatial understanding [3], temporal action interpretation [4], [5], interaction with humans [6], and the ability to handle various domains and data transformations, among others. Numerous vision-language models (VLMs) [5], [7] have been developed to enhance the generalization and reasoning abilities of vision models by leveraging large-scale vision-language data, thereby improving their capacity to address these diverse challenges.

Conventional VLMs (before 2018, fig. 1) are designed to handle limited vision tasks, such as captioning and retrieval, primarily through encoder-decoder architectures. These approaches rely on convolutional neural networks (CNNs) to extract visual representations [8], [9] or hand-crafted visual features, and generate sentences using recurrent neural networks (RNNs) [10], long short-term memory (LSTM) [11] or conditional random field (CRF) [12]-based decoder. However, constrained by the limited scale of pretrained datasets and the



Fig. 1. The evolution of VLMs includes three phases: conventional VLMs (before 2018), emerging VLMs (2018-2022), and VLLMs (2022 onward).

simplicity of their architectures, these models are only capable of addressing specific tasks with moderate performance.

With the advancement of deep learning techniques such as Transformer [13], research on Vision-Language Models (VLMs) gained emergence from 2018 to 2022 (see fig. 1). Inspired by breakthroughs in natural language processing, these VLMs typically follow the Pre-training, Fine-tuning, and Prediction paradigm across various tasks, leveraging foundation models like BERT [14] and CLIP [15] that are pretrained on large-scale language or vision-language datasets. These foundation models encapsulate rich prior knowledge, enabling robust zero-shot and transfer learning performance across diverse tasks. Based on language foundation models like BERT, numerous approaches [16]-[18] have been developed by integrating a visual extractor with the language foundation model, replacing earlier recurrent architectures. By leveraging the prior knowledge embedded in large-scale language corpora, these methods achieve significantly better performance compared to conventional models. Building on VLM foundation models such as CLIP, many studies aim to transfer this prior knowledge to downstream tasks through techniques like prompt tuning [19], [20], visual adaptation [21], and knowledge distillation [22], [23]. Despite these advancements, most of these methods are discriminativebased, which inherently lack multi-task capabilities and strong reasoning abilities. This limitation hinders the further devel-



Fig. 2. The architectures of three VLLM application categories: (a) vision-to-text, (b) vision-to-action, (c) text-to-vision.

opment and broader applications of VLMs.

With the rise of language generative models [24], [25], researchers focus on leveraging the prior knowledge embedded in Large Language Models (LLMs) to develop general-purpose and highly reasoning VLMs. Leveraging instruction-tuning techniques [26] in LLMs, current Visual Large Language Models (VLLMs) [27] can process versatile instructions and generate responses that align with human preferences. Specifically, these VLLMs (as shown in fig. 2) employ a vision encoder to patchy vision data, use a connector to project visual tokens into the language space, and rely on an LLM as a decoder to produce instruction-following answers. These VLLMs can be applied to generalized and specialized applications, leveraging the prior knowledge and the sequence-tosequence architecture of LLMs. Furthermore, they also inherit the reasoning capabilities of LLMs, enabling them to tackle more complex vision tasks.

Previous related surveys have primarily focused on general VLMs [7], [28]–[30], or specific aspects of multi-modal large language models (MLLMs), such as methodologies [31], [32], reasoning capabilities [33], interpretability [34], evaluation benchmarks [35], development trends [36]–[39], and hallucination issues [40]. With the advancement of VLLMs across various tasks, their applications have become increasingly diverse, covering both generalized and specialized scenarios. However, these surveys lack a comprehensive overview of the applications, limitations, and future directions of the vision modality in MLLMs.

In contrast, our survey provides a holistic perspective on VLLM applications, categorizing them into three main aspects: *vision-to-text, vision-to-action,* and *text-to-vision*. Each category is further broken down into detailed subtasks, with an in-depth analysis. Additionally, we explore the social impact of VLLMs, and the challenges they face in different scenarios. Finally, based on the ethical concerns, we propose some promising directions for future development, like security & privacy, efficiency, interpretability & explaninability, complex reasoning, *etc.* We hope our survey will provide a fresh perspective on VLLM applications and serve as a continuous source of inspiration for others.

II. TEXONOMY

A. Image-to-text

Image-to-text tasks are fundamentally designed for models to extract image features and translate them into human language. Traditionally, methods such as CNNs combined with RNNs are the dominant solution for this task. These models primarily focus on leveraging the spatial information of images to generate corresponding textual descriptions. However, such methods demonstrate limitations in handling the complexity and variability of real-world images. Recently, with the rise of LLMs, numerous studies have explored leveraging the power of these advanced models for image understanding tasks. In particular, when combined with a robust pretrained vision encoder, such as CLIP-based or CNN-based architectures, these models have significantly enhanced the ability to accurately and contextually interpret and describe visual content. These advancements have enabled a wide range of applications, including general domain tasks such as image captioning, visual question answering (VQA), visual dialogue, referring expression comprehension (REC), referring expression segmentation (RES), and optical character recognition (OCR), as well as applications in specific domains.

1) General domain application: In the category of general domain applications, image-to-text models are designed to address multiple visual understanding tasks, rather than focusing on any specific domain. Traditionally, most computer vision models were developed to solve single, discrete tasks such as classification, detection, or segmentation. However, these models were limited in providing generalist solutions capable of handling multiple vision tasks simultaneously. Recently, in the field of natural language processing, the instructiontuning paradigm introduced in some large language models (LLMs) [24], [247] has proven to be a game-changer, ushering in a new era where LLMs can manage a diverse range of text-based tasks. This paradigm shift has also influenced the vision domain, leading to the development of instruction-tuned visual LLMs capable of effectively interpreting and describing visual content across various tasks, such as image captioning and VQA. Numerous studies [42], [44]-[46], [248], [249] have pioneered the use of visual instruction tuning, achieving superior performance on these tasks and demonstrating its potential to enable more versatile and generalizable visual understanding models.

General Ability. Image captioning, VQA and visual dialogue are fundamental capabilities of most vision-language image-to-text models. Captioning involves generating descriptive textual explanations for visual data, while VQA focuses on answering specific questions. Visual dialogue further extends VQA by enabling multi-turn conversations about the visual content. Currently, nearly all visual LLMs employ multiple training stages to develop these capabilities.

The first stage, known as pretraining, involves training models on extensive datasets of image-text pairs, such as COCO [250], Visual Genome [251], CC3M [252], Conceptual Captions [253], and LAION400M [254], *etc.* The primary objective during this phase is feature alignment, which unifies image and text into a single embedding space. This alignment process ensures that the model can understand and process visual and textual information cohesively.

During pretraining, connectors between the vision encoder and LLMs are trained to synchronize visual and language representations. These connectors include linear projectors [42],



Fig. 3. VLLM application texonomy. REC (Referring Expression Comprehension), RES (Referring Expression Segmentation), OCR (Optical Character Recognition).

[45], MLPs [62], [248], Q-formers [44], [51], and Resamplers [46], [55], *etc.* These connectors serve as bridges aligning the visual and language spaces, working in conjunction with the pretraining objective of the image captioning task. This alignment enhances the models' efficiency and effectiveness, enabling them to excel in generating coherent textual descriptions from visual inputs.

In the subsequent training stage, referred as supervised finetuning, models are trained on high-quality image-text pair datasets curated from high-capacity closed-source resources like GPT-4V [255], or Gemini [256]. Examples include LLaVA-Instruct-158K [42], GRIT [85], ShareGPT4V [257], and LVIS-Instruct4V [258]. Additionally, some studies [259] integrate high-quality text-only dialogue datasets, including ShareGPT-80K [260], SlimOrca [261], the Alpaca dataset [262], and the Vicuna dataset [263]. These datasets help to preserve the model's ability to handle multi-turn human dialogues. This fine-tuning stage equips models with the



Fig. 4. An illustration of image-to-text general domain applications.

ability to effectively follow user instructions and enhances their multimodal conversation capabilities, thereby improving their performance in visual dialogue tasks.

During fine-tuning, some models [42], [55], [56] opt to freeze the vision encoder to preserve the prior knowledge of visual representations. In contrast, others [58], [259] train both the vision encoder and LLMs to enhance the model's robustness in handling complex visual input. Furthermore, additional training stages are integrated into the training pipeline of certain models. For example, MiniGPT-v2 [45], Qwen-VL [55], and DeepSeek-VL [62] incorporate extra training stages to strengthen their conversational capabilities.

Referring Expression Segmentation (RES). Object segmentation is a fundamental task in computer vision, involving the localization of objects at the pixel level. Traditional methods have addressed this task by targeting a predefined set of objects. Recently, the open vocabulary approach has gained prominence, leveraging LLMs to segment objects based on natural language descriptions, known as *referring expressions*.

LISA [67] introduces the novel task of *Reasoning Segmentation*, where models generate segmentation masks guided by complex and implicit query text instructions. This architecture integrates a VLLM with an additional vision backbone, specifically the Segment Anything Model (SAM) [264], to extract visual embeddings. Leveraging an embedding-as-mask paradigm, the model decodes the last-layer embedding of the <SEG> token from the VLLM into a segmentation mask, thereby enhancing its ability to address intricate reasoning and leverage world knowledge effectively.

GSVA [74] builds on LISA by introducing multiple <SEG> tokens to handle multiple targets and <REJ> tokens to reject empty targets, effectively addressing the challenges of Generalized Referring Expression Segmentation (GRES). Several other works, such as Osprey [79], VisionLLMv2 [78], GLaMM [76], and GROUNDHOG [68], integrate mask or region extractors to enhance the model's ability to capture fine-grained details. This strategy significantly improves RES accuracy, highlighting the effectiveness of incorporating specialized extractors for managing complex visual details. Unlike LISA and other approaches that use SAM [264] as a supporting segmentation model, VistaLLM [70] and LLaFS [75] directly generate segmentation coordinates from the LLM decoders. These models simplify the segmentation process by leveraging the LLMs to directly generate precise segmentation coordinates, eliminating the need for an intermediate segmentation model.

Referring Expression Comprehension (REC). REC is a critical computer vision task that involves identifying and localizing objects in an image based on natural language descriptions. Early works like Shikra [86] and Kosmos-2 [85] build on the architectures of LLaVA [42] and Kosmos-1 [41], using instruction-tuning datasets for grounding and referring tasks. These models represent location coordinates as text tokens, which are generated by LLMs.

Similarly, VisionLLM [77], Pink [90], ChatSpot [87], InfM-LLM [93], and ASMv2 [265] aim to enhance training datasets by incorporating more region-level, fine-grained information. Models such as Ferret [91], GPT4RoI [88], Ferret-v2 [92], and Lion [94] modify their architectures to better capture detailed features from input images. Specifically, Ferret and GPT4RoI leverage Spatial-Aware Visual Sampler and Region Feature Extractor modules, allowing these models to focus on and extract critical image regions, thereby improving grounding accuracy.

Sphinx [95] leverages multiple image encoders, including CLIP-ViT [15], CLIP-ConvNeXt [266], and DINOv2 [267], and introduces a novel joint mixing strategy to integrate model weights. This approach enhances multi-modal understanding and delivers superior performance in fine-grained visual tasks.

An alternative approach leverages external modules for precise object localization instead of directly generating bounding boxes from LLMs. For instance, DetGPT [84] extracts all objects using the GroundingDINO [268] model for the grounding task. BuboGPT [89] introduces a pipeline that combines the Recognize Anything Model (RAM) [269], GroundingDINO, and the SAM [264] to align bounding boxes with objects in the output sequence.

Further, Lenna [100] and VisionLLMv2 utilize hidden fea-

tures of the <DET> token as input for the detection module, following GroundingDINO's architecture. LLaVA-Grounding [99] employs OpenSeeD [270] as its grounding model, using the <REG> token to enhance detection processes.

Recently, OMG-LLaVA [80] introduces a new architecture that includes a universal perception module combined with an LLM. This enables unified image-level, object-level, and pixel-level reasoning and understanding tasks, achieving state-of-the-art performance on datasets such as refCOCO, refCOCO+, refCOCOg [271], and GranD [76].

Optical Character Recognition (OCR). OCR is a crucial application within image-to-text tasks, aiming to convert various types of documents—such as scanned paper documents, PDFs, or images captured by digital cameras—into editable and searchable data. With the advent of LLMs, particularly VLLMs, users can now interact more effectively with textrich documents. Models like LLaVAR [103], mPLUG-DocOwl [46], UniDoc [105], and TGDoc [107] are pioneering in this direction. These models build on the robust architectures and training procedures of LLaVA [42], mPLUG-Owl [46], MiniGPT-4 [44], and Shikra [86], respectively, and have been further trained using instruction-tuning datasets comprising a diverse range of text-rich images, including posters, book covers, and infographics.

One of the key techniques that enhance a model's capability in OCR-related tasks is the ability to handle high-resolution data. Many of the previous models typically leverage pretrained CLIP [15] as the vision encoder, which has limited input resolutions of 224 or 336 pixels. To overcome this limitation, UReader [106] employs a shape-adaptive cropping module that segments high-resolution images into smaller regions, enabling effective use of low-resolution vision encoders. Conversely, DocPedia [108] takes a novel approach by direcly handling high-resolution inputs in the frequency domain, capturing richer visual and textual information while requiring fewer visual tokens.

TextMonkey [109] leverages the Shifted Window Attention mechanism in the Swin Transformer [272] to preserve cross-window connectivity and employs a token resampler to filter relevant tokens, enhancing performance across various text-centric tasks. DocKylin [116] introduces Adaptive Pixel Slimming (APS), which leverages gradient information to eliminate redundant visual content, and Dynamic Token Slimming (DTS) modules to filter out irrelevant visual tokens, thereby improving the efficiency and effectiveness of visual document understanding. LayoutLLM [111] integrates layout instruction tuning by combining layout-aware pre-training with supervised fine-tuning, enabling it to effectively capture and utilize document layout information.

Similarly, Fox [115] focuses on fine-grained, multi-page document understanding by employing flexible, position-aware prompts and hybrid data synthesis, efficiently leveraging multiple vision vocabularies. HRVDA [110] employs content filtering and instruction filtering modules to eliminate contentagnostic and instruction-agnostic visual tokens, optimizing model training and inference for high-resolution images. More recently, InternLM-XComposer2-4KHD [117] has pushed the boundaries by handling resolutions up to 4K HD. It employs dynamic resolution and automatic patch configuration to accommodate varying resolutions and aspect ratios, achieving state-of-the-art performance across OCR benchmarks such as DocVQA, ChartQA, InfoVQA, and TextVQA.

Retrieval. Retrieval tasks in VLLMs focus on selecting and retrieving relevant images or textual data based on a given query, which can be either visual or textual in nature. These tasks are fundamental to the effectiveness of imageto-text models, enabling accurate and context-aware outputs by bridging the gap between visual and textual modalities. Recent advancements in retrieval-based approaches can be categorized into two main groups: single-stage retrieval models and hierarchical retrieval-augmented models.

- Single-Stage Retrieval Models are characterized by their capability to perform direct retrieval operations by mapping visual and textual data into a unified embedding space. These models typically employ a straightforward retrieval process, where the model selects the most relevant image or text based on learned embeddings. For instance, FROMAGe [119] pioneered this approach by integrating vision and language through the use of a specialized retrieval token ([RET]), which enhances the model's ability to accurately retrieve images and generate text. UNIMUR [120] further refines this concept by introducing a unified multimodal embedding training paradigm, addressing modality bias and ensuring more consistent and coherent retrieval results across both visual and textual domains.
- Muli-Stage Retrieval Models are designed to enhance retrieval tasks by incorporating multiple layers of retrieval processes, often leveraging external knowledge sources to enrich the contextual relevance of the outputs. These models typically involve a two-step retrieval process, where the most relevant documents or passages are first identified and then used to generate more accurate and contextually rich responses. For example, Wiki-LLaVA [121] employs a hierarchical retrieval process. It first locates relevant documents using visual and textual encoders, then extracts pertinent passages within those documents. This approach enriches the input context, particularly for tasks requiring external knowledge, such as visual question answering. EchoSight [122] extends this approach by integrating multimodal inputs, combining visual perception with acoustic signals, to retrieve and synthesize information across multiple modalities, thereby enhancing the model's ability to handle complex, multimodal queries.

2) Specific Domain Application: The advancement of VLLM also paves a new way for image-to-text applications across various specialized domains. Unlike VLLMs designed for general applications as discussed in the previous section, these domain-specific models need extensive training on specialized datasets or receive unique structural modifications to improve performance. By aligning the models with the intricate demands of each domain, they demonstrate significant performance improvements, outperforming general models in specific tasks. This high level of contextual relevance and



Fig. 5. An illustration of image-to-text specific domain applications.

model performance are essential for addressing the unique challenge of many domains, which include:

Remote Sensing (RS). The inherent differences between natural and RS images, including variations in color distributions, image resolutions, image context, and object scales, present significant challenges for using general VLLMs in tasks within the RS domain. These tasks include RS captioning [123], [273], [125], [274], [275], [276], RS visual grounding [277], [278], [276], [125], [274], [275], RS-VQA [123], [277], [276], [125], [274], [275], RS-vQA [123], [277], [276], [125], [274], [275], RS image retrieval [273]. To address these challenges, numerous studies concentrate on fine-tuning VLLMs for RS tasks by developing specialized RS datasets.

RS-LLaVA [123] constructs a tailored RS-instruction dataset by integrating data from public datasets on the RS captioning and RS-VQA domains. GeoChat [275] incorporates its dataset by incorporating public datasets on different tasks, including RS visual grounding and landcover classification, and proposes a dataset specifically for flood detection. RSGPT [124] manually annotates a high-quality RS captioning dataset enriched with detailed scene descriptions and comprehensive object information. SkyEyeGPT [274] aims at unifying diverse RS image-to-text tasks, encompassing both single-task and multi-task conversational instructions, with manual verification to ensure dataset quality. EarthGPT [125] overcomes the limitation of existing models, which mainly train on optical RS images by incorporating multiple types of RS images, such as synthetic aperture radar (SAR) and infrared images, into their dataset. This integration enhances the model's performance across various RS tasks. Similarly, LHRS-Bot [276] further enriches the instruction dataset by utilizing extensive volunteered geographic information (VGI) and globally available RS images from Google Earth, improving model performance across most of the RS tasks. H²RSVLM [277] includes a range of unanswerable questions into their RS-VQA dataset, which is then used to fine-tunes LLaVA [42] to successfully mitigate hallucination issue.

Beyond general RS tasks, some researchers create special-

ized datasets to tackle specific RS challenges. For example, Silva *et al.* [273] utilize various RS image captioning datasets and train linear layers to apply contrastive learning between RS images and special tokens to address RS image retrieval tasks. Popeye [278] focuses on ship detection by constructing a dataset that merges data from four existing ship detection datasets effectively targeting this specific issue.

Medical. The integration of VLLMs into the medical domain represents a substantial advancement in diagnostics and treatment planning. These models leverage VQA to interpret complex medical images [126], [279], [280], [127], [281], and generate comprehensive and precise medical reports [282], [283], [284], [128].

In the medical field, Medical Visual Question Answering (Med-VQA) is a fundamental task to enhance diagnostic capabilities by analyzing various types of medical images such as CT scans, radiographs, and dermoscopy images using VLLMs. Med-VQA involves practitioners interacting with VLLMs to extract specific details from medical images, facilitating interactive diagnostic support. For example, Med-Versa [126] demonstrates proficiency in handling multifaceted medical image interpretation by leveraging multimodal inputs and dynamic task specifications. PMC-VQA [127] introduces a large-scale Med-VOA dataset encompassing diverse image modalities such as X-ray, MRI, and Computed Tomography, along with a broad spectrum of diseases. This model employs visual instruction tuning on this comprehensive dataset to enhance its capability to address a wide range of medical questions effectively. LLaVA-Med [279] leverages a two-step fine-tuning process based on LLaVA [42]: first, biomedical vocabulary training using image-caption pairs, followed by medical instruction training utilizing GPT-4 [255] generated instruction-following data. Remarkably, this approach requires only one day of training with eight A100 GPUs to achieve state-of-the-art performance in Med-VQA benchmarks [285], [286], [287]. Med-Flamingo [280] also demonstrates the effectiveness of few-shot learning in generating accurate responses to complex medical queries. Furthermore, Zhou et al. [281] propose a two-stage fine-tuning strategy incorporating instruction tuning and reinforcement learning that allows the model to focus more effectively on abnormal regions in medical images, outperforming other open-source models on the abnormality recognition task.

Building on the advancements in Med-VQA, the task of Medical Report Generation (MRG) further streamlines the diagnostic workflow by automating the creation of comprehensive medical reports. While Med-VQA leverages VLLMs to extract specific details and provide immediate diagnostic support through interactions, MRG augments this by generating detailed, structured reports highlighting anomalies and suggesting potential diagnoses using VLLMs. For example, PeFoMed [282] introduces a novel parameter-efficient finetuning framework for MRG tasks, showing significant improvements in generating clinically useful reports. XrayGPT [283] enhances the quality and usability of automated radiology reports by training on high-quality visual and textual synthetic summaries from free-text radiology reports as training data. Ranjit et al. [284] employ the Retrieval Augmented Generation (RAG), integrating domain-specific retrievals with general language models to generate accurate and clinically relevant radiology reports, while reducing hallucinations and irrelevant content. RaDialog [128] achieves state-of-the-art results in generating and interactively modifying radiology reports, facilitating expert collaboration and enhanced diagnostic support.

Science and Mathematics. Beyond applications in Medical and RS domains, researchers also integrate VLLMs into the science domain to enhance understanding of diagrams and graphs in academic settings. Science VQA [288], [129], [289] is a prevalent evaluation task in these integrations. Specifically, Lu et al. [288] introduce a large-scale science VQA dataset, ScienceQA, encompassing diverse topics such as natural science, social science, and language science. T-SciQ [129] develops a pipeline for generating high-quality Chainof-Thought (CoT) prompts to fine-tune VLLMs, achieving state-of-the-art performance on the ScienceQA benchmark. mPLUG-PaperOwl [289] fine-tunes mPLUG-DocOwl [290] on a scientific diagram analysis dataset derived from 48,000 high-quality arXiv papers on Machine Learning (ML), addressing both Science VOA and science image captioning tasks. FigurA11y [291] further explores the science image captioning task by designing a system, based on GPT-4 [255] and LLaVA [42] to generate high-quality alternative text for scientific figures. This system aims to provide more detailed image descriptions, making scientific content more accessible to blind and low-vision readers.

Within the broader field of science, visual mathematics has emerged as a distinct domain, with many advancements significantly enhancing the ability of VLLMs to address complex mathematical problems and introduce new evaluation metrics. G-LLaVA [130] introduces the Geo170K dataset [130], containing 170,000 geometry image-caption and question-answer pairs, to fine-tune LLaVA [42], outperforming GPT-4V [255] in geometric mathematics VQA task. Similarly, Math-LLaVA [292] fine-tunes LLaVA 1.5 [42] with the MathV360K dataset [292], which includes 40,000 diagrams and 360,000 questionanswer pairs, achieving performance on par with GPT-4V in mathematical reasoning tasks. MAVIS [131] selects MAmmoTH2 model [293] as the base model and fine-tunes it over the MAVIS-Instruct 834K dataset [131], containing diagram, question-answer pairs, and rationale, achieving state-of-theart results. MAmmoTH-VL [294] Beyond model improvements, significant progress has been made in creating new benchmarks to evaluate the performance of VLLMs in solving visual mathematics problems. The MathVista benchmark [295] consolidates over 6,000 examples from 31 datasets, providing a comprehensive evaluation of the mathematical VQA task. GeoEval [296] focuses on geometry mathematics questions, encompassing basic shapes, three-dimensional objects, and analytic geometry. CMMaTH [297] establishes the largest Chinese multimodal mathematical benchmark, specifically for K12 math questions. Additionally, MathVerse [298] and WE-MATH [299] introduce benchmarks that include crucial reasoning steps to evaluate the quality of CoT reasoning by VLLMs.

Graphic Design and UI Understanding. In our progressively digital world, graphical designs play a crucial role across a range of digital devices. Several studies successfully utilize VLLMs in graphics-related tasks, encompassing graphic design and UI understanding. For graphic design tasks, Graphist [132] is the first layout generation VLLM, that constructs graphic compositions from unordered sets of design elements formatted as a JSON draft protocol. This protocol details the coordinates, size, and sequence of each component. For user interface (UI) understanding, general VLLMs may fall short because UI images typically contain smaller objects of interest, such as icons and text, which differ significantly from those in natural images. To address this challenge, CogAgent [133] employs low and high-resolution image encoders to accurately recognize small page elements and text. Similarly, Ferret-UI [134] divides the image into two sub-images and encodes them separately before feeding them into VLLMs, enhancing the model's ability to process intricate UI details.

Financial Analysis. Researchers also explore how VLLMs can be used in financial analysis to interpret financial charts and deliver valuable insights. FinVis-GPT [135] develops a financial dataset featuring candlestick and line charts of Chinese A-shares, which is then used to fine-tune VLLMs for financial analysis. FinTral [136] adopts a similar approach, using stock price data from Fortune 500 companies to facilitate financial analysis in English contexts. FinTral achieves state-of-the-art performance in the Stock Movement Prediction task, outperforming other general VLLMs such as GPT-4V [255], Gemini-Pro [300], and LLaVA-NEXT [301].

B. Video-to-text

Video-to-text tasks deal with advanced video content understanding problems such as video captioning, video question answering, video conversation, *etc*. The input videos could be either short within a few seconds, or a couple of hours long. They are accessed from historically cached databases or real-time streaming platforms. Compared to image-to-text



Fig. 6. An illustration of video-to-text applications.

tasks, video-to-text tasks are significantly more challenging because of the big semantic gap between sparse video content and abstract language information. In the spirit of LLMs, how to embed sparse causal information from long videos, *e.g.*, temporal activity evolution, and physical motion dynamics, into a dense and tokenizable space for learning a video LLM is an open-ended research problem. According to the application goals, we categorize existing literature in the following parts.

1) General-purpose Video Understanding: In the era of LLMs, textual language is becoming a unified interface for modeling various video understanding problems. Such a trend leads to many existing general-purpose video LLMs. The basic idea of building a general-purpose model is to perform large-scale model pre-training on billions or trillions of visual-text data. The pre-training stage brings generalizable knowledge for downstream video understanding tasks. For example, early work such as VideoBERT [137] stands on top of the pre-trained BERT [302] to pre-train on large-scale video datasets by masked language modeling (MLM), which is found critical to both video generation and classification tasks. Instead of MLM, recent LLMs [138]–[142], [303] that adopt autoregressive modeling (ARM) show much better capability, which aims to predict the next token in language space.

The "next-token prediction" has inspired recent generalpurpose video LLMs. For example, LaViLa [138] treats video data as a condition and adopts GPT2 [304] and T5-large [305] as video narrator and rephrase, to fine-tune LLMs for applications including activity recognition, event retrieval, and video question answering. Vid2Seq [139] leverages largescale narrated videos and time tokens in pre-training, leading to a generalizable model for multiple video captioning benchmarks. VideoLLaMA [140] leverages video Q-former and ImageBind to handle visual temporal change and the modality correspondence between modalities of audio, video, and text. Following similar model architecture, recent video LLMs such as LLaMA-VID [141], MiniGPT4-Video [142], ST-LLM [143], LLaVA-Next-Video [303], LLaVA-OV [306], and Aria [307] have been introduced rapidly.

Long-form video LLMs. The common idea of existing video LLM is to use a pre-trained LLM as the decoder to generate text responses. This raises a major challenge of how to effectively encode long-form videos into visual tokens and project them into text token space for LLM to decode. Recently, LLaMA-VID [141] uses two tokens including the context token and content token to encode each frame, enabling hourly-long video understanding. LVChat [150] dynamically

adjusts the number of video tokens by considering the duration of input videos. MA-LMM [308] stores the features of historical video tokens in a memory bank such that the model can process hourly-long videos in an online manner. Different from previous methods, recent LongVU [144] adopts temporal frame selection and spatial token selection to significantly reduce redundant tokens in video LLMs. Until today, how to efficiently encode long video-text context into a unified token space for video conversation is still challenging and being actively studied in research communities.

2) Video Conversation: Instead of building foundational video-to-text models for general purposes, video conversation raises a great interest because the language model serves as a conversational agent of humans. However, this scenario naturally requires multiple rounds of reasoning steps to understand the complex video content, as well as humans' ambiguous intent in a long dialog context. This leads to the recent trend of studying video-language chat applications. ChatGPT is generally regarded as a breakthrough that successfully makes LLMs such as GPT-4 [309] applicable for complex reasoning tasks. Recently, its multi-modality version GPT-4(V) [310] takes images and video into account in conversation. These agents are commercial products without public code and models released. Since LLaVA [42] is a representative visual assistant for image-to-text agent applications. Thanks to its simplicity, plenty of video assistants are developed recently, such as the Video-LLaVA [145], VideoChat [146], VideoChat2 [147], VideoChatGPT [148], Valley [149], BT-Adapter-LLaVA [151]. Note that most existing general-purpose video LLMs are technically feasible for video conversation, though they are not optimized from engineering aspects for improving the conversation experience.

3) Egocentric Understanding: For video understanding tasks, most applications focus on the third-person view. However, understanding egocentric human activities is essential for plenty of real-world applications. For example, a headset with an egocentric camera sensing system could assist a worker in finishing complex mechanical repair jobs, when the system can understand the humans' egocentric visual world and interact with humans with plain language. Prior research such as [311]–[316] primarily resort to vision-language models such as CLIP [317] to achieve egocentric video understanding, which are too small (less than 1 billion parameters) to handle complicated video tasks. Powered by advances in LLMs, the recent GPT4Ego [152] leverages ChatGPT and chain-of-thought to generate text prompts for egocentric videos,



Fig. 7. An illustration of vision-to-action applications.

achieving remarkable zero-shot egocentric action recognition performance. By leveraging LLMs to generate video narrations, LAVILA [318] achieves large performance gains on both egocentric and third-person video understanding tasks. Following prompt tuning strategy, PALM [153] treats the past video events and visual tokens to fine-tune LLM for egocentric long-term action anticipation. Different from PALM, recent AntGPT [154] takes advantage of LLMs at the bottom-up next-token prediction and top-down task goal planning for egocentric long-term action anticipation. To unify the egocentric visual memory and robotic control, recent LLM-Brain [156] treats LLM such as BLIPv2 as the central brain of the model to handle users' instructions for multiple embodied AI tasks. To bridge the gap between LLMs and egocentric video content, Wang et al [155] formulates a natural language query (NLQ) benchmark for egocentric video understanding, and introduce a video captioning module before applying LLMs. Recently, action programming has been an important application of egocentric video understanding, which requires complex visual reasoning capability of models over an egocentric view. The LEAP [157] employs LLMs to generate executable action programs from egocentric videos, which is critical for robot manipulation, planning, and navigation.

C. Vision-to-action

Vision-to-action tasks based on VLLMs mainly take visual modalities such as images/videos/depth/3D as the visual input conditioned with language instructions, and the VLLM will generate actions to control behaviors of vehicles, robots or software (*e.g.*, APIs), *etc.* We divide such tasks into three main streams according to the application scenarios: autonomous driving (AD), embodied AI and tool management. These VLLM agents [319] will be more intelligent and general when making decisions by equipping with LLM's strong contextualizing, reasoning, and generalization ability.

1) Autonomous Driving: Recent AD systems transit from rule-based to data-driven ones [320]–[322], and many of these methods resort to LLMs for better perception, planning and

prediction ability. The vision input for LLMs in AD can be various and adaptive, like multi-view images [166], video [172], bird's eye view (BEV) map [159] and LiDAR [162], [171], which is easy to be extended to various driving tasks.

Perception. As mentioned in Sec. II-A, VLLMs have shown strong reasoning and zero-shot abilities in understanding tasks. This characteristic can also be extended to the AD system to improve the generalization capability in complex driving environments [323]. NuScences-QA [158] proposes a VQAbased benchmark for the AD scenario, including both images and point clouds modalities as input and the question answering pairs on the existence, counting, status, types, and relationships of the objects. DriveLM [160] introduces a graphstructured reasoning task to model the logical dependencies during the AD question and answering process. Talk2BEV [159] proposes to utilize the BEV map to perform scene understanding, visual reasoning, and free-form conversation tasks. HiLM-D [161] proposes an efficient method to localize risk objects, predict intentions, and provide suggestions. Specifically, HiLM-D designs two branches for high-resolution perception and low-resolution reasoning, respectively. Built upon OpenFlamingo [324], Dolphins [164] can process data integrating video/images, instructions, and historical control signals, and generate the understanding results of the driving scenario. Specifically, a new CoT process (Grounded Chainof-Thought, GCoT) is proposed to enhance the reasoning ability of Dolphins by providing the spatial information of the objects. LiDAR-LLM [162] takes 3D LiDAR data as input and performs outdoor scene understanding like description, grounding and VQA based on a frozen LLM.

Planning. VLLMs can perceive complex driving scenarios and generate driving maneuvers or control signals for drivers based on current visual features. ADriver-I [169] introduces the interleaved vision-action pair as the inputs for autoregressively predicting the control signals of the current frame. It then employs a diffusion model to forecast future frames based on historical vision-action pairs, facilitating future action prediction. DriveVLM [166] capitalizes VLLMs for scene understanding and planning by containing a Chain-of-Thought (CoT) process, including scene description, scene analysis and hierarchical planning. DriveVLM can generate three kinds of driving plans, which are meta-actions for a short-term decision, decision description for articulating the more fine-grained driving strategy, and trajectory waypoints for depicting the vehicle's path. DiLu [168] improves the planning capability of AD by combining a reasoning and reflection module based on past driving knowledge. Specifically, a memory module is employed to store the past driving experience like decision prompts, reasoning processes, etc., which can be utilized to enhance the reasoning and planning capabilities of the LLMs. DriveGPT4 [172] can predict the low-level control signals by tuning an end-to-end VLLM based on the BDD-X dataset [325] annotated by ChatGPT. Specifically, DriveGPT4 can analyze video frames by a pretrained vision encoder, and is also trained for two stages like LLaVA [42]. SurrealDriver [170] proposes a driver agent simulation framework for urban scenarios, which can provide driving maneuvers based on real world driver experience. LMDrive [171] introduces an end-toend driving framework, which can perceive multi-view multimodal sensor data (camera and LiDAR) and generate control signals according to the navigation instructions based on an LLM decoder.

Prediction. VLLMs can also be utilized to predict the trajectories and actions of vehicles and pedestrians to assist in navigation. In NuPrompt [173], Wu *et al.* formulate a new task by prompting to predict the described object trajectory across frames. They also propose a method PromptTrack to predict the 3D bounding box of the prompt-referred objects. BEV-InMLLM [174] integrates BEV features and multi-view video into the LLM for perception, prediction and planning tasks. Such a method can forecast the actions of the surrounding entities and predict the potential dangers.

2) Embodied AI: Embodied AI refers to the artificial intelligence systems designed to control physical embodiments and interact with the environments [326]. These systems possess the abilities in cognition, decision-making, and control [327], [328], which are commonly applied in the field of robotics. Since conventional robot agents mainly concentrate on some constricted tasks and lack common sense knowledge, there exists a growing number of works based on LLMs for learning versatile downstream task policies. Among these methods, VLLM-based agents constitute a significant portion and can be categorized into four streams [329], *i.e.*, perception, manipulation, planning, and navigation.

Perception. VLLM-based robots can extract semantic knowledge and understand environments from visual signals such as RGB or LiDAR. OpenEQA [175] introduces a new benchmark on embodied question answering perception tasks, such as object recognition, attribute recognition, object localization, *etc.* This benchmark presents two types of problems: the episodic-memory task for understanding the environment through the episodic memory, and the active one by requiring only navigation actions. AffordanceLLM, 3DVG, 3D-LLM, and PaLM-E utilize 3D data to enhance perception. In AffordanceLLM [176], the authors propose detecting the interaction point of an object (affordance grounding) via VLLM, introducing depth information to better capture object geometry

and improve grounding performance. 3DVG [177] enhances object detection and classification by introducing a languageobject correlation (LOC) module that fuses 3D point cloud geometry with 2D image details via VLLM. This multi-modal fusion improves fine-grained object perception and extends the model's capacity for open-vocabulary scenarios. 3D-LLM [178] proposes a framework that integrates 3D spatial information into an LLM, enabling it to process 3D point clouds and perform tasks such as 3D question answering, captioning, and navigation. Similarly, PaLM-E [183] improves embodied perception by integrating visual inputs, such as images and 3D scene representations, into the language model's embedding space using ViT and object-centric encoders. Other works utilize additional modules or agents for perception. The paper [179] introduces a multi-agent VLLM framework with specialized agents to reduce errors in object identification and coordinate refinement. REPLAN [180] employs a VLM Perceiver, enabling robots to ground actions in visual data, allowing object detection and obstacle identification.

Manipulation. To create a universal robot capable of handling various downstream tasks, a key skill is the ability to manipulate objects in its environment based on the specific requirements of each task [330]. This ability can be greatly enhanced by using VLLMs. PaLM-E [183] incorporates continuous inputs like images, states and language from an agent into a pretrained LLM (PaLM [331]) for manipulation planning. RT-X [182] introduces a large and diverse manipulation dataset "Open X-Embodiment" which includes 527 skills and 1M+ real robot trajectories enabling generalized policy learning. Instruct2Act [184] proposes a training-free method by calling the APIs of existing foundation models using the LLM. Based on the expertise of foundation models and the reasoning ability of LLM, InstructAct can understand complex instructions for manipulation tasks. Roboflamingo [185] is based on an off-theshelf VLLM, which learns the sequential historical information with a policy head and is finetuned by imitation learning on manipulation datasets. Such a decomposition design makes Roboflamingo flexible and efficient when deploying in the real world. VoxPoser [3] proposes synthesizing robot trajectories for manipulation tasks based on open-set instructions and objects. Specifically, a training-free method is proposed by utilizing the code-writing abilities of LLM, which can generate 3D value maps by calling the vision-language model. Niu et al. introduces an instruction-tuning-based method, LLARVA [186], which leverages structured prompts for various robotic learning tasks. They also demonstrate that visual traces, formed by intermediate 2D representations, are beneficial for aligning vision and action spaces. ManipLLM [187] targets at predicting the contact point of the object given the text prompt, RGB image and depth map by tuning a VLLM. Kim et. al. presents an efficient tuning VLLM OpenVLA [188] by training on a large-scale real-world manipulation dataset.

Planning. In embodied AI, task planning involves decomposing high-level objectives into atomic subtasks while accounting for real-world dynamics. NLMap [189] enables agents to construct open-vocabulary queryable scene representations by integrating VLMs and LLMs. It allows robots to identify relevant objects within the environment, and generate context-aware plans, thereby enhancing their ability to execute complex tasks in real-world settings. ELLM [190] assists agents in formulating and pursuing intermediate objectives, facilitating effective exploration of the environment. By prompting LLMs with descriptions of the agent's current state, ELLM generates contextually relevant goals, guiding agents toward diverse behaviors aligned with commonsense knowledge. LLaRP [191] integrates text instructions and egocentric observations to directly output actions in a dynamic environment. This approach enhances the agent's ability to execute complex tasks by learning a reinforcement learning policy. LL3DA [192] directly processes 3D point cloud data by leveraging textual and visual prompts from human interactions. Equipped with visual prompts, LL3DA can enhance the agent's ability to understand, reason and plan within complex 3D environments, facilitating more effective task execution and decision-making. ConceptGraphs [196] introduces a semantically rich 3D scene graph of the environment by leveraging 2D foundation models and the priors in LLMs. This approach enhances navigation by enabling agents to inperpret complex spatial and semantic relationships within a scene, facilitating efficient decision-making during path planning and task execution. Finally, RILA [197] utilizes multi-modal models to process sensory data, and directs an LLM-based planner to actively explore the environment, dynamically evaluating and discarding inaccurate perceptual descriptions during navigation.

Navigation. In the field of embodied navigation, current VLLMs combine multiple modalities to improve navigation efficiency in dynamic environments. These models integrate multi-modal data, leveraging the reasoning capabilities of LLMs to process complex instructions and accurately navigate obstacles in real-world settings [332]. LM-Nav [193] combines an LLM (GPT3), a pretrained VLM (CLIP [15]), and a visual navigation model (ViNG [333]) to handle complex, real-world navigation. This approach enables agents to interpret natural language instructions and execute long-horizon navigation tasks without fine-tuning in challenging outdoor environments. MultiPLY [194] introduces a model enabling active interaction with 3D environment, using multisensory inputs like visual, auditory, tactile, and thermal data. By building correlations among words, actions, and perceptions, this approach can perform context-aware actions within intricate 3D settings. EMMA [195] learns to navigate visual environments by imitating the behavior of an LLM operating in a parallel textual world. By aligning visual observations with textual descriptions, EMMA effectively translates high-level navigation strategies from textual to visual contexts, significantly enhancing its ability to plan and execute navigation tasks in complex, real-world scenarios.

3) Automated Tool Management: The goal of automated tool management is to leverage well-established models to autonomously perform complex tasks that traditionally require human intelligence and decision making. Early efforts in automated tool management predominantly utilized pure textbased models. These models excelled in interpreting and generating textual content for various applications including programming assistance, solving mathematical problems, and executing simple logical tasks. We direct readers to a survey [334] for an exhaust review. However, as the complexity of tasks increases, in this survey, we aim to encompass inputs with not only text but also visual signals and interactions with physical environments [335].

The integration of VLLMs with tool management represents a significant advancement in the field of AI. To systematically understand this integration, a taxonomy is proposed that categorizes these developments based on their system architecture, mode of integration, and application areas. This taxonomy not only organizes the existing methodologies but also provides insights into their functionalities and potential applications.

Actions as Tool APIs. In the context of VLLMs, tools are often conceptualized and implemented as APIs. This approach allows for modular, flexible, and scalable solutions where different functionalities can be called as needed.

Common tools managed by VLLM planners include:

- Pure Vision Models: These models, typically including CNN-based models and ViT-based models, help transform input or intermediate visual signals into vectors for further processing.
- Visual Language Models: Those models, including both generative models such as VQA models, image captioning models, other VLLMs, and discriminative models such as CLIP [15], are the core tools for understanding and responding to queries about visual content, facillitating the planner to support applications in customer service, interactive education, and more.
- *Web Searching APIs*: Integrating VLLMs with web search APIs (*e.g.*, google search) enhances the ability to retrieve and synthesize information from vast internet resources, making the management of information retrieval tasks more efficient.
- *Library Calls:* VLLMs can automate the usage of software tools and libraries, facilitating tasks like code generation, software testing, and even complex design tasks in engineering and graphics.

System Architecture. System architecture in VLLMs planners describes how various components like language models, visual processing units, and tool management systems are structured within the AI systems. This category helps in understanding the foundational setup of VLLMs and their operational efficiency.

- *Integrated Systems*: These systems exemplify a tightly coupled framework where components are seamlessly integrated to perform tasks. For instance, MM-REACT [198] integrates textual and visual inputs to enhance multimodal reasoning and action. Similarly, AVIS [199] combines a dynamic tool management system with planning and reasoning components to handle complex visual queries effectively.
- *Modular Systems*: Characterized by their flexibility, these systems use distinct, interchangeable modules that can be tailored for specific tasks. Mind's Eye [210] integrates a physics simulation engine with a language model to ground linguistic processing in physical reality, while Chameleon [208] employs a sequence of plug-and-play

modules for complex reasoning across multiple modalities and domains.

- Self-Instructing Systems: These systems are designed to adapt and learn how to use tools autonomously through methods like self-instruction [336] and feedback loops [215], [337], [338]. GPT4Tools [205] and Confucius [211] are examples where models instruct themselves to enhance their tool-using capabilities, with Confucius employing a curriculum-based learning approach to manage increasingly complex tools.
- Trajactory Synthesize and Self-exploration: A recently rising pipeline utilizes the strong autonomy power of large VLLMs to explore the given physical environments, such as Visual-WebAreana [335], Windows-WebAreana [339], OSWorld [340], and τ-Bench [341], etc. Such exploration are usually guided by search algorithms, such as MCTS [216], DFS & BFS [217], reinforcement learning [342], bandits [343] or trajactory sampling [218]. Typical work includes Open-WebVoyager [344], Agent-S [212], AgentStore [213], OS-ATLAS [214], and ICAL [345]. Those synthsized tracjories are either used as knowledg-based for retrival as in-context examples, *i.e.*, Retrieval-Augmented Generation (RAG) for large VLLM backbones, or distilled into smaller VLLMs for faster response [218].

Mode of Integration. The mode of integration deals with how tools are incorporated and utilized within VLLMs, reflecting the operational strategies and interaction levels of these models with external resources.

- Direct Tool Invocation: This straightforward approach allows models to directly call tools within their outputs. ToolkenGPT [207], for example, embeds tools as tokens directly within the language model's output, simplifying tool usage. CRAFT [206] retrieves and executes specialized code snippets directly, enabling efficient task execution. TroVE [209], HuggingGPT [201] and ViperGPT [204] also share similar strategies to this.
- Indirect Tool Utilization: In this approach, models use tools through intermediary steps or additional processing layers, allowing for more nuanced interactions and deeper contextual understanding. MLLM-Tool [200] and CLOVA [202] exemplify this method, with CLOVA enhancing tool effectiveness through iterative updates based on reflective learning.

D. Text-to-vision

The boundary between reality and artificiality is increasingly blurred with the rise of generative applications of VLLMs. These models signify a major shift from merely interpreting data to creatively producing new visual content. This section transitions to VLLMs' innovative visual generative applications in generating images, 3D models, and videos.

1) Text-to-image: This section focuses on how VLLMs transform text prompts into images seamlessly. Text-to-image applications include image generation, image editing, image synthesis, and visual story generation.

Image Generation. The core of image generation is crafting visuals from text prompts to closely reflect the prompt's intention, ensuring both visual coherence and realism. VLLMs effectively bridge the linguistic and visual realms.

Optimizing image generation prompts is crucial for synchronizing the visual and textual elements of VLLMs. GILL [219] enhances the handling of longer and more complex textual inputs for image generation by instructing LLMs to predict fixed-size visual embeddings aligned with CLIP space, thus controlling Stable Diffusion for image generation. Instead of relying on LLMs to predict fixed-size embeddings, [220] and [221] utilize LLMs to generate more detailed prompts, resulting in more accurate and rich content.

In addition to textual refinements, some research enhances the visual embedding capabilities of VLLMs. SEED [222] and LaVIT [223] introduce sophisticated visual tokenizers that translate non-linguistic images into sequences of discrete tokens, akin to a foreign language that LLMs can interpret. These visual tokenizers enable LLMs to simultaneously see and draw. VL-GPT [225] proposes an innovative image tokenizer-detokenizer framework, which, alongside traditional text tokenization methods, allows VL-GPT to handle interleaved image-text data seamlessly.

Beyond textual or visual refinements, some research improves image generation by focusing on multimodal fusion. MiniGPT-5 [226] boosts multimodal generation through "generative vokens" as pivotal elements, bridging LLMs with Stable Diffusion for more cohesive and context-aware visionand-language interactions. Emu [224] processes multimodal inputs through an autoregressive training process. Kosmos-G [227] aligns the output space of MLLM with CLIP using the textual modality as an anchor. CoDi-2 [228] aligns modalities with language for both encoding and generation. [229] presents the Joint Autoregressive Mixture (JAM) framework to fuse existing text and image generation models into a single, robust model capable of generating seamless multimodal outputs. CM3Leon [230] is a retrieval-augmented, token-based, decoder-only single multi-modal language model capable of generating and infilling both text and images, with notably fewer training computes compared to existing methods.

Rather than only translating prompts into embeddings, DiffusionGPT [231] utilizes LLMs for image generation model selection by constructing domain-specific Trees for various generative models and them to guide the selection of an appropriate image generation model.

Image Editing. The task of image editing involves modifying images based on language descriptions, such as object removal, color adjustment, and adding text. The primary challenge is accurately interpreting nuanced instructions while maintaining the original image's context and aesthetics.

The models in the section of Image Generation, inherently equipped for image generation, seamlessly adapt to image editing tasks when provided with image inputs. This integration leverages the rich, instruction-based datasets from InstructPix2Pix, enabling more precise and contextually accurate modifications to existing images. For example, Kosmos-G [227] and CoDi-2 [228] both improve image editing capability by leveraging the data constructed by InstructPix2Pix [346].



Fig. 8. An illustration of text-to-vision applications.

Image Synthesis. Image blending or synthesis involves combining elements from multiple images or generating new images from a combination of visual and textual inputs to create cohesive, novel visuals. The main challenge is achieving a seamless blend of different images while ensuring that the synthesized images are contextually relevant to the textual or visual inputs. LaVIT [223] excels in image synthesis due to its ability to autoregressively generate visual tokens from discrete tokens and reconstruct these tokens into a feature map reflecting high-level semantics. Kosmos-G's [227] alignment of the output space with CLIP and compositional instruction tuning enables zero-shot subject-driven image generation with interleaved multi-image and text inputs, advancing the field of image synthesis.

Visual Stories Generation. The task involves creating image sequences that narrate a story or follow text prompts, capturing the narrative visually. The main challenge is generating coherent and contextually relevant sequences that accurately reflect the text prompts' narrative progression. [232] introduces a visual SEED tokenizer that produces discrete visual tokens carrying high-level semantics and aligns them with text, demonstrating remarkable abilities across a wide range of multimodal tasks, especially multimodal dialogue.

2) Text-to-3D: Text-to-3D generation, driven by VLLMs, converts textual descriptions into detailed 3D models and environments, enhancing creativity and efficiency in architecture, game design, and VR. Despite challenges in spatial relationships and volumetric transformations, VLLMs excel in 3D scene generation, editing, and mesh generation.

3D Scene Generation and Editing. The task involves generating and modifying 3D layout to achieve desired aesthetics or functionalities, with the challenge lying in maintaining spatial coherence and realistic interactions among complex elements within dynamic scenes.

VLLMs leverage LLMs to interpret textual instructions, provide generative feedback, conceptualize scene layouts, discretize shapes, and generate and modify interactive 3D scenes. For instance, LI3D [233] integrates LLMs as 3D layout interpreters into off-the-shelf layout-to-3D generative models, incorporating LLaVA for visual feedback to enhance the visual quality of generated content. Similarly, 3D-GPT [234] decomposes complex modeling tasks into smaller components, using LLMs to interpret textual instructions into specific procedural generation tasks, enabling efficient 3D content creation with-

out requiring direct 3D modeling by users. ShapeGPT [235] adopts a "word-sentence-paragraph" framework to discretize continuous shapes into shape words, assembles these words into shape sentences, and integrates shape with instructional text for multi-modal paragraphs. GPT4Point [239] utilizes LLMs to interpret textual instructions and align them with point cloud data.

Additionally, some models incorporate additional tools or assets, such as Objaverse [236] or the Unity game engine [237], to enhance their capabilities in scene understanding, task planning, self-debugging, and memory management. GPT4Point [239] introduces Pyramid-XL, an automated dataset annotation engine for generating a large-scale database of 3D object-text pairs, essential for improving its performance in understanding and generating 3D content.

Mesh Generation. Mesh generation translates geometric shapes into discrete vertex and edge networks for 3D modeling, facing challenges in fidelity, efficiency, and detail preservation. MeshGPT [238] uses a decoder-only transformer model to generate triangle meshes. By learning a vocabulary of latent quantized embeddings, MeshGPT enables the autoregressive generation of compact and detailed meshes, bypassing traditional dense methods.

3) Text-to-video: Text-to-video generation, powered by VLLMs, transforms written narratives into engaging video sequences with high visual quality and consistency. Challenges include ensuring seamless continuity, engaging storytelling, and technical proficiency.

Video Generation and Editing. Video generation and editing have advanced with diffusion-based models, overcoming GAN limitations. Leveraging VLLMs, recent progress enables autonomous generation of realistic scenes and special effects, reshaping content creation.

Some researchers share a common approach of utilizing Large Language Models (LLMs) to interpret textual inputs and generate detailed scene layouts or comprehensive multiscene scripts. LVD [347] first interprets textual inputs into detailed scene layouts, and then using these layouts to inform a diffusion model's video creation, significantly improving the fidelity and motion accuracy of generated videos. VideoDrafter [240] also transforms input prompts into comprehensive multiscene scripts via LLMs, identifying common entities across scenes to maintain visual consistency through reference images generated by a text-to-image model. [241] leverages LLMs for semantic prompt generation and Latent Diffusion Models (LDMs) for frame animation, aiming at producing semantically coherent, high-quality videos from textual descriptions. [242] utilizes the LLM to create a comprehensive video plan from a single text prompt, detailing scene descriptions, entity layouts, and backgrounds, and maintaining consistency across scenes. Mora [243] proposes an LLM-driven multiagent framework for generalist video generation and editing designed to mimic the capabilities of OpenAI's large-scale model, Sora.

The other researches share a focus on enhancing the alignment between visual tokenization and the learning process of LLMs to improve video generation. MAGVITv2 [245] proposes a concise and expressive image and video tokenizer, which demonstrates that LLMs can outperform diffusion models in standard video generation benchmarks. VideoPoet [246] synthesizes high-quality videos, specifically high fidelity motions, using a decoder-only autoregressive transformer architecture that processes multimodal inputs, including images, videos, text, and audio. SVD [244] also identifies and evaluates three different stages for successful training of video generation: text-to-image pretraining, video pretraining, and high-quality video fine-tuning.

III. ETHICS CONSIDERATION, CHALLENGES, AND FUTURE WORK

A. Ethics Consideration

1) Impact on Labor Markets: The application of VLLMs automates tasks across various industries. Sectors like creative design, customer service, and medical diagnostics may experience reduced demand for human labor, as VLLMs generate images, interpret visual data, and perform tasks traditionally requiring human expertise. This shift could displace jobs in areas such as graphic design, video editing, and medical imaging.

However, VLLMs also create new opportunities in AI oversight, ethical deployment, and AI-human collaboration. Creative professionals and medical experts may transition to supervisory roles, ensuring VLLM outputs meet brand, ethical, or medical standards. Policymakers and industries must prioritize reskilling programs to mitigate job displacement risks, promoting a balanced transition as VLLMs advance. Moreover, industries relying on manual labor face accelerated digitalization, heightening the need for responsible adoption of AI to complement, rather than replace, human workers.

2) Bias: VLLMs, trained on large-scale visual and textual datasets, are prone to inheriting and amplifying various biases, including sampling bias, gender/racial bias, and lingual bias. This raises ethical concerns, particularly in tasks where biased outputs can reinforce stereotypes or lead to discriminatory outcomes [376], [377]. Addressing these biases is critical for ensuring fairness and ethical use of VLLMs across diverse domains.

Sampling Bias. Sampling bias in VLLMs occurs when training data is not representative of the global population. Overrepresentation of certain regions, social classes, or cultures can lead to models performing better for those groups

Gender and Racial Bias. Gender and racial biases in VLLMs often originate from training datasets that underrepresent specific demographic groups or perpetuate harmful stereotypes. These biases manifest in biased outputs for image generation and content interpretation, as evidenced by several studies that have highlighted disparities across models and languages [378], [379]. Such biases are particularly concerning in high-stakes domains, including hiring, law enforcement, and healthcare, where VLLMs are increasingly relied upon for analyzing visual data. The presence of bias in these systems can result in skewed outcomes, perpetuating societal inequalities and unfair treatment. To address these issues, ongoing research is focused on developing mitigation strategies to ensure fairness in model outputs [380].

Lingual Bias. Lingual bias in VLLMs arises when training data disproportionately favors dominant languages, like English, leading to better performance in those languages while underperforming in others. This bias can result in lowerquality outputs for underrepresented languages, reinforcing linguistic inequalities and limiting accessibility in applications such as multilingual visual analysis.

B. Challenges

1) Efficiency: The efficiency of VLLMs becomes a critical challenge due to their widespread deployment and the substantial computational demands they impose. The efficiency of VLLMs encompasses two key aspects: training and inference.

Training Efficiency. For instance, training an efficient VLLM model DeepSeek-V3 [62] from scratch costs approximately 5.6M dollars for 180,000 H800 GPU hours, consuming around 54,000 kWh energy and producing 25.65 metric tons of CO_2 . As a result, the training efficiency of VLLMs has a profound impact on economic costs, energy consumption and environment sustainability.

Inference Efficiency. Not only problems faced during the training phase, but inference efficiency of VLLMs is also essential, especially for real-time deployment scenarios, such as Chatbots, autonomous systems, and so on. Furthermore, inference efficiency is key to enabling deployment on edge devices with limited computational power, such as smartphones and internet-of-things devices.

2) Interpretability and Explainability: According to the definitions provided in the literature [381], [382], *interpretability* refers to the internal property, such as its parameters or structure, which does not rely on external explanations. In contrast, *explainability* refers to the extrinsic ability to provide post-hoc explanations for the behavior of the models using tools or methods.

The scalability and complexity of VLLMs for addressing diverse downstream tasks present a considerable challenge in interpretability and explainability, particularly when building transparent, trustworthy, and fair models [34]. Specifically, the intricate decision-making process, massive number of parameters, and extensive training data make VLLMs difficult to interpret and explain effectively.

Datasets	Year	Scale	Modal	Task
SBU Captions [348]	2011	1M	image-text	caption
Flickr30k [349]	2014	145K	image-text	caption
COCO [250]	2014	567K	image-text	caption, vqa, rec, res
Visual Genome [251]	2017	5.4M	image-text	vqa, grounding
LAION-5B [350]	2022	5.9B	image-text	caption
CC3M [253]	2018	3.3M	image-text	caption
CC12M [252]	2021	12.4M	image-text	caption
COYO [351]	2022	747M	image-text	caption
Multimodal C4(MMC4) [352]	2023	101.2M	image-text	caption
Obelics [353]	2023	141M	image-text	caption
GRIT [85]	2023	115M	image-text	caption, grounding
DataComp [354]	2023	1.4B	image-text	caption
MedInterp [126]	2024	13M	image-text	med-vqa, mrg
MTB [280]	2024	800K image	image-text	med-vqa
PMC-vqa [127]	2023	227K	image-text	med-vqa
HqDC-1.4M [277]	2024	1.4M	image-text	classification, vqa, grounding
MMShip [278]	2024	81K	image-text	grounding
LHRS-Align [276]	2024	1.15M	image-text	classification, vqa, grounding
MMRS-1M [125]	2024	1M	image-text	classification, caption, vqa, grounding
RSICap [124]	2023	2.6K	image-text	caption, vqa
M-Paper [289]	2024	49K	image-text	caption, science-vqa
ScienceQA [288]	2022	21K	image-text	science-vqa
MAVIS-Caption [131]	2024	558K	image-text	caption, math-vqa
MathV360K [292]	2024	360K	image-text	math-vqa
GeoEval [296]	2024	2K	image-text	math-vqa
CMMaTH [297]	2024	23K	image-text	math-vqa
MathVerse [298]	2024	2.6K	image-text	math-vqa
WE-MATH [299]	2024	6.5K	image-text	math-vqa
Geo170K [130]	2023	170K	image-text	math-vqa
MathVista [295]	2023	6K	image-text	math-vqa
TextOCR [355]	2021	903K	image-text	ocr
HierText [356]	2022	1.2M	image-text	ocr, layout
TextVQA [357]	2019	45K	image-text	vqa
VIST [358]	2016	72K	image-text	Visual Storytelling
VisDial [359]	2017	123K	image-text	Visual Dialogue, Image Grounded Dialogue
VizWiz [360]	2018	31K	image-text	Caption, VQA
A-OKVQA [361]	2022	24K	image-text	VQA
MSR-VTT [362]	2016	10K video clips	video-text	video caption, video generation
WebVid-10M [363]	2021	10M video clips	video-Text	video caption, video generation
HD-VG-130M [364]	2023	130M video clips	video-text	video caption, video generation
ActivityNet Captions [365]	2017	100K video clips	video-text	video caption, video generation
HD-Vila-100M [366]	2022	103M video clips	video-text	video caption, video generation
InternVid [367]	2023	234M video clips	video-text	video caption, video generation
HowTo100M [368]	2019	136M video clips	video-text	video caption, video generation
LSMDC [369]	2017	128K video clips	video-text	video caption, video generation
VATEX [370]	2019	41.3K video clips	video-text	video caption, video generation
Open X-Embodiment [182]	2023	1M+ trajectories	image-action	embodied manipulation
OpenEQA [175]	2024	1600 questions	video-action	embodied perception
Talk2car [371]	2019	850	video-action	autonomous driving
nuScenes [158]	2019	40K	vision (2D, 3D)-action	autonomous driving
HAD [372]	2019	5.7K	video-action	autonomous driving
ShapeNet [373]	2015	3M 3D models	3D-text	3D generation, 3D shape retrieval
Text2Shape [374]	2019	23K 3D models	3D-text	3D Generation, 3D shape retrieval
Objaverse [375]	2023	818K 3D models	3D-text	3D generation, 3D shape retrieval

 TABLE I

 AN OVERVIEW OF REPRESENTATIVE VLLM DATASETS.

3) Hallucination: Hallucination in VLLMs refers to the generation of outputs that are semantically plausible but factually incorrect or irrelevant to the visual input [383]. Hallucination in VLLMs arises due to several key factors. First, misinterpretation by vision encoders often leads to errors in recognizing spatial relationships, orientations, or subtle visual cues within images. Additionally, complex or ambiguous visual inputs—like overlapping objects, intricate backgrounds, or subtle differences in shapes and colors—can confuse the model, resulting in the generation of incorrect details. Biases

in training data and insufficiently diverse examples further contribute to these errors, as the model may rely on learned patterns that do not accurately reflect the given visual context. Moreover, adversarial inputs specifically designed to exploit weaknesses in the model can exacerbate hallucinations. Lastly, inadequate training on datasets that address these challenges leaves models more prone to hallucinations [384], [385].

The dissemination of misinformation through hallucination poses significant risks, especially in sensitive applications like medical diagnostics, autonomous driving, and security systems. Erroneous outputs can lead to misinformed decisions, safety hazards, and erosion of user trust in AI systems. Furthermore, in social contexts, the propagation of misinformation can have broader societal implications, influencing public opinion and potentially causing harm.

Addressing hallucination in VLLMs requires a multifaceted approach. Enhancing the quality and diversity of training datasets is crucial to mitigate biases and ensure balanced representation. Advanced model architectures that improve cross-modal attention mechanisms can strengthen the alignment between visual inputs and textual outputs. Techniques such as constrained decoding and incorporation of factual verification steps during generation have shown promise in reducing hallucinated content. [384], [386]

4) Spatial Understanding: Recent work [387] highlights that current VLLMs face significant challenges in spatial understanding, particularly when dealing with egocentric visual data. Spatial understanding requires that VLLMs possess the relational reasoning ability to identify spatial relationships between objects based on distance and direction. Moreover, it also requires the ability to perform egocentric-allocentric view (environment-centered) transformations. Addressing this challenge will greatly benefit the development of embodied agents and AD systems.

C. Future Work

1) Security & Pravacy: The increasing integration of VLLMs into diverse applications, particularly those involving sensitive visual data, necessitates a focused exploration of their security and privacy implications. Given their capabilities in image recognition, generation, and analysis, VLLMs present unique challenges and opportunities for ensuring secure and private deployments.

Data Privacy and Confidentiality. VLLMs often handle large quantities of visual data that can include personal identifiers, such as faces or license plates [388], [389]. Ensuring the confidentiality of such data is paramount. Future research should explore advanced data anonymization techniques tailored for images and videos, such as k-anonymity visual models [390], [391], where individual faces or objects are obscured but the utility for training remains intact. Additionally, leveraging encryption methods that allow VLLMs to process encrypted images without decryption (homomorphic encryption) could prevent data exposure even if security breaches occur [392], [393].

Robustness Against Adversarial Attacks. The visual nature of the data processed by VLLMs can make them particularly vulnerable to adversarial attacks that manipulate image pixels in a way that is intended to deceive the model [394], [395]. Enhanced adversarial training that includes a wider array of manipulated visual inputs can improve model robustness [396], [397]. Development of real-time detection systems for adversarial inputs in security-critical applications, like surveillance or authentication systems, is also crucial [398]. These systems could utilize auxiliary networks trained specifically to detect anomalies in input images that may indicate adversarial tampering. **Regulation and Compliance.** Compliance with privacy regulations is critical, especially as VLLMs are deployed across geographic boundaries. Research into VLLM-specific regulatory frameworks that address the unique aspects of visual data is needed. These frameworks should guide the collection, use, and storage of visual data, as well as dictate the transparency requirements for model decisions. Future work could also explore the development of standardized privacy impact assessments for VLLMs to ensure compliance before deployment.

Secure Model Deployment. Post-deployment security of VLLMs involves protecting the model from unauthorized access and ensuring that the model's operations remain secure against ongoing threats [399]. Future research should investigate the use of trusted execution environments for VLLMs that can securely handle sensitive visual data on shared infrastructure. In addition, techniques such as continuous learning, in which the model updates its parameters in response to new security threats without compromising privacy, could be crucial [400], [401].

Enhanced focus on these areas will not only fortify the security and privacy framework around VLLMs but will also facilitate their ethical and safe application in critical sectors, promoting wider acceptance and trust in these powerful technologies of users.

2) *Efficiency:* As VLLMs continue to scale, computation and deployment resources become increasingly critical. Efficiency challenges emerge during both the training and inference stages, driving more academic interest in optimizing these processes.

Training Efficiency

- Token Reduction. Visual data often contains redundant information that can be further minimized. Recent methods aim to reduce computational costs in VLLMs by pruning less important visual tokens. The objective is to preserve critical tokens while discarding or merging others with minimal performance degradation. For instance, early work such as MiniGPT-V2 [402] concatenates and merges neighboring visual tokens. More recent approaches, like FastV [403], leverage cross-modal guidance and attention scores to guide token reduction. LLaVolta [404] proposes to average pool the visual tokens after a specific LLM transformer layer, and introduces a new training paradigm that prunes different tokens at different layers during training. However, designing an automatic tuning scheme to reduce visual tokens without adding extra hyperparameters or compromising performance across different tasks remains a significant challenge.
- Data Distillation. VLLMs require a large amount of training data to achieve remarkable performance, as dictated by the scaling law. Consequently, the training efficiency can be significantly improved if the training data is distilled. Early research has explored methods for distilling training data for CNNs [405]–[407], ViTs [408], [409], diffusion models [410]–[412] and text-only LLMs [413]. However, efforts on distilling the

dataset for VLLMs remain limited, making it a promising direction for further exploration.

• Parameter-Efficient Fine-Tuning. Parameter-efficient fine-tuning (PEFT) allows for efficient adaptation of pretrained models to downstream tasks without fine-tuning the entire model. Techniques like Low-Rank Adaptation (LoRA) [414] reparameterize weight matrices, reducing the number of trainable parameters and optimizing memory usage. LoRA's variant, ReLoRA [415], periodically updates pre-trained weight matrices with low-rank adaptors during training, further improving memory efficiency during fine-tuning. Nonetheless, current PEFT methods are mainly for LLMs, designing specific PEFT methods for VLLMs is a promising direction to explore.

Inference Efficiency

- Token Reduction. It is also promising to reduce visual tokens during the inference phase without tuning VLLMs. LLaVA-PruMerge [416] merges similar visual tokens based on the CLS token scores obtained from the visual encoder before the LLM decoder. However, it lacks the ability to dynamically adjust tokens based on specific instructions. Achieving effective token reduction without significant performance loss is notably more challenging than approaches that involve tuning.
- **KV Cache Optimization.** Key-value (KV) caching accelerates LLM inference by storing key and value states from previous tokens. However, efficient cache management for visual data is particularly critical for VLLMs based on the visual token redundancy fact. FastV [403] addresses this challenge by dynamically pruning unnecessary visual tokens after specific layers. Despite its effectiveness, this approach requires maintaining the KV cache for the initial predictions, resulting in memory overhead for pruned tokens. To further improve the inference efficiency of VLLMs, particularly for tasks requiring long visual contexts, optimizing the KV cache management strategy of vision tokens during the inference phase remains a valuable area of study.

3) Interpretability & Explainability: In order to address the challenges of interpretability, explainability and hallucinations in VLLMs, greater attention should be focused toward analyzing the interpretability and explainability of VLLMs. As highlighted in [34], related literature can be categorized into three perspectives, *i.e.*, data, model, and training & inference.

Data. Interpretability and explainability in VLLMs involve understanding how input data attributes to the models' decision-making process, and analyzing the output data of the models. Early research primarily focuses on analyzing the relationship between input visual data and class labels by visualizing the specific region of interest [417] or attention maps [418]. Additionally, causal inference methods [419], [420] have proven to be powerful tools for exploring the connections between visual and language modalities. The advent of diffusion models has further inspired new approaches for interpretability, including generating attribution maps [421] and leveraging information-theoretic metrics [422], [423].

Model. The architecture of VLLMs, including tokens, em-

beddings, neurons, and layers, provides valuable insights into understanding these models. Token-based methods can be classified based on token types into visual tokens [424], [425] and visual-textual ones [426]-[430]. These methods play a crucial role in reducing visual redundancy and mitigating hallucination issues. In contrast to specific tokens, embeddingbased methods focus on coarse-grained analyses of multimodal embeddings in VLLMs, which can also be divided into visual embeddings and visual-textual embeddings. Visual embeddings [431], [432] are good representations for understanding how VLLMs process visual information. Visual-textual embeddings [433]-[435] provide insights into the semantic space shared by visual data and human instructions. Neurons, the fundamental computing units in VLLMs, play a key role in understanding specific concepts or domains, which have two types: individual neurons and grouped neurons. Individual neurons [436], [436], [437] are associated with distinct concepts or functions. while the grouped ones [438], [439] are connected to specific tasks. Additionally, layer-based analyses focus on examining the layer architectures, such as attention heads or MLP layers from components [440]–[442] or workflow [443], [444] perspectives.

Training & Inference. The training strategies and inference methods are also critical aspects for understanding VLLMs. During the training process, analyzing pretraining [445], [446] is fundamental to understanding the subsequent instruction alignment stage. Following pretraining, interpreting the alignment stage [447]–[449] is a key focus for mitigating hallucination issues and enhancing the reliability of VLLMs. Additionally, approaches such as gradient analysis [450], [451] and incorporating regularization terms [452], [453] have shown promise in reducing hallucination during training. In the inference stage, promising directions include leveraging and explaining techniques such as Chain-of-Thought (CoT) reasoning [454]–[457] and In-Context Learning (ICL) [458], [459], which provide insights into the reasoning processes and decision-making capabilities of VLLMs.

4) Complex Reasoning: Although VLLMs have demonstrated reasoning capabilities, most current open-sourced VLLMs struggle with complex, systematic, and structured reasoning, often leading to hallucination or spatial understanding issues. To enhance their complex reasoning abilities, future research can explore techniques such as Chain-of-Thought (CoT) [460], Tree-of-Thought (ToT) [461], visual prompting [462], tree search [463], etc. Recent advancements, such as LLaVA-o1 [464], inspired by GPT-o1 [465], propose a multi-stage reasoning approach where each stage serves a distinct purpose in the reasoning process. To further improve inference efficiency, LLaVA-o1 incorporates stage-level beam search, generating multiple candidate results at each stage and selecting the optimal one. Investigation on using reward models to guide the planning process [342], or utilizing the multi-VLLM system for judgement [466] can be promising directions.

5) Other Applications: VLLMs can also be applied to other domains, such as face, anomaly detection, or gaming, where the integration of specialized data collection and prior domain knowledge is crucial for achieving high performance. In

these tasks, VLLMs can benefit from understanding nuanced patterns and context, enabling more precise detection and classification tailored to the specific characteristics of the data.

Face. Privacy concerns and the scarcity of instructionbased datasets present significant challenges in acquiring high-quality, domain-specific data. As an initial effort, EmoLA [467] leverages VLLMs with a customized instruction-following dataset facial affective behavior analysis with instructions (FABA-Instruct) and tailored efficient tuning algorithms to address FABA tasks. Similarly, [468] utilizes Gemini to generate instruction data for facial expression recognition (FER) and develops a facial-prior-informed MLLM, EMO-LLaMA, to model human facial information. To further harness the language reasoning capabilities of LLMs, [469] designs ExpLLM, incorporating accurate chain-of-thought (CoT) prompts for FER. [470] explores the social perception of human faces with the assistance of modern VLLMs, while [471] focuses on modeling, understanding, and responding to complex human emotions using additional video-text data and specialized MLLM models. [472] introduces a practical pipeline for constructing image-text datasets with fine-grained descriptions of human faces. Building on this dataset, they propose Face-MLLM, an MLLM designed for face perception.

Anomaly Detection. Data distribution bias and interpretability pose significant challenges for anomaly detection, which remain difficult for VLLMs to effectively address. In [473], the authors propose Hawk as an interactive tool to interpret video anomalies precisely. [474] designs a method tackling video anomaly detection (VAD) in a novel, trainingfree paradigm, exploiting the capabilities of pre-trained LLMs and existing vision-language models (VLMs), through VLMbased captioning to generate the text description and customized prompting to assist the reasoning. From a different research angle of data generation and evaluation, [475] presents a comprehensive benchmark for causation understanding of video anomaly, and an evaluation metric designed to better align with human preferences.

Gaming. VLLMs have demonstrated significant potential in addressing gaming-related challenges by leveraging their ability to comprehend both visual and textual descriptions of gameplay. In the experiments conducted with Atari-GPT [476], VLMs were employed as low-level policies in Atari games. These models exhibited advanced capabilities in processing complex visual scenes and generating strategic responses. Another application of VLMs in action role-playing games (ARPGs), such as Black Myth: Wukong, highlights their ability to operate with vision-only inputs. The proposed framework, VARP [477], successfully handled basic and mediumlevel combat scenarios by integrating an action-planning module with a human-guided trajectory system.

In open-world games like Minecraft, frameworks such as JARVIS-1 [478], MineDreamer [479], Adam [480], STEVE [481], STEVE-EYE [482], and MP5 [483] utilize VLMs to execute task instructions, plan actions, and perform complex, long-horizon tasks. These systems combine visual and language-based planning to handle tasks ranging from resource gathering to crafting tools. Additionally, CRADLE [484] explores the potential of VLMs in AAA games like Red Dead

Redemption 2 (RDR2). CRADLE utilizes input screenshots for planning and translates these into precise keyboard and mouse controls, enabling the model to follow the storyline and successfully complete 40-minute-long missions.

IV. CONCLUSION

Visual large language models (VLLMs) represent a promising frontier in the integration of vision and language, combining the strengths of both modalities into a unified framework and advancing numerous vision language applications. Despite the significant strides made in their development, the literature survey surrounding VLLMs remains limited, particularly with respect to their comprehensive application across diverse fields. In this paper, we have highlighted key application scenarios, the challenges that remain in advancing these VLLMs models, and the potential directions for future research. As VLLMs continue to evolve, addressing the existing limitations in scalability, interpretability, and cross-modal understanding will be crucial to unlocking their full potential. Ultimately, a deeper exploration of VLLMs will not only advance our ability to bridge vision and language but also open up new opportunities for multi-modal systems across a wide range of industries, from autonomous systems to healthcare and beyond. We hope this survey serves as a valuable resource for guiding future research and inspiring further innovation in the field of VLLMs.

REFERENCES

- X. Wang, A. Shrivastava, and A. Gupta, "A-fast-rcnn: Hard positive generation via adversary for object detection," in *CVPR*, 2017, pp. 2606–2615.
- [2] K. He, X. Zhang, S. Ren, and J. Sun, "Deep residual learning for image recognition," in CVPR, 2016, pp. 770–778. 1
- [3] W. Huang, C. Wang, R. Zhang, Y. Li, J. Wu, and L. Fei-Fei, "Voxposer: Composable 3d value maps for robotic manipulation with language models," in *CoRL*, 2023, pp. 540–562. 1, 3, 10
- [4] C. Feichtenhofer, A. Pinz, and R. P. Wildes, "Spatiotemporal multiplier networks for video action recognition," in *CVPR*, 2017, pp. 4768–4777.
- [5] G. Ding, F. Sener, and A. Yao, "Temporal action segmentation: An analysis of modern techniques," *IEEE TPAMI*, 2023. 1
- [6] S. Antol, A. Agrawal, J. Lu, M. Mitchell, D. Batra, C. L. Zitnick, and D. Parikh, "Vqa: Visual question answering," in *ICCV*, 2015, pp. 2425–2433. 1
- [7] J. Zhang, J. Huang, S. Jin, and S. Lu, "Vision-language models for vision tasks: A survey," *IEEE TPAMI*, 2024. 1, 2
- [8] H. Fang, S. Gupta, F. Iandola, R. K. Srivastava, L. Deng, P. Dollár, J. Gao, X. He, M. Mitchell, J. C. Platt *et al.*, "From captions to visual concepts and back," in *CVPR*, 2015, pp. 1473–1482. 1
- [9] O. Vinyals, A. Toshev, S. Bengio, and D. Erhan, "Show and tell: A neural image caption generator," in CVPR, 2015, pp. 3156–3164. 1
- [10] A. Karpathy and L. Fei-Fei, "Deep visual-semantic alignments for generating image descriptions," in CVPR, 2015, pp. 3128–3137. 1
- [11] X. Jia, E. Gavves, B. Fernando, and T. Tuytelaars, "Guiding the longshort term memory model for image caption generation," in *ICCV*, 2015, pp. 2407–2415. 1
- [12] G. Kulkarni, V. Premraj, V. Ordonez, S. Dhar, S. Li, Y. Choi, A. C. Berg, and T. L. Berg, "Babytalk: Understanding and generating simple image descriptions," *IEEE TPAMI*, vol. 35, no. 12, pp. 2891–2903, 2013. 1
- [13] A. Vaswani, N. M. Shazeer, N. Parmar, J. Uszkoreit, L. Jones, A. N. Gomez, L. Kaiser, and I. Polosukhin, "Attention is all you need," in *Adv. Neural Inform. Process. Syst.*, 2017. [Online]. Available: https://api.semanticscholar.org/CorpusID:13756489 1

- [14] J. Devlin, M.-W. Chang, K. Lee, and K. Toutanova, "Bert: Pre-training of deep bidirectional transformers for language understanding," in ACL, 2019. [Online]. Available: https://api.semanticscholar.org/CorpusID: 52967399 1
- [15] A. Radford, J. W. Kim, C. Hallacy, A. Ramesh, G. Goh, S. Agarwal, G. Sastry, A. Askell, P. Mishkin, J. Clark *et al.*, "Learning transferable visual models from natural language supervision," in *ICML*. PMLR, 2021, pp. 8748–8763. 1, 4, 5, 11
- [16] L. H. Li, M. Yatskar, D. Yin, C.-J. Hsieh, and K.-W. Chang, "Visualbert: A simple and performant baseline for vision and language," arXiv preprint arXiv:1908.03557, 2019. 1
- [17] J. Lu, D. Batra, D. Parikh, and S. Lee, "Vilbert: Pretraining taskagnostic visiolinguistic representations for vision-and-language tasks," in Adv. Neural Inform. Process. Syst., vol. 32, 2019. 1
- [18] Y. Sun, Y. Zheng, C. Hao, and H. Qiu, "Nsp-bert: A prompt-based few-shot learner through an original pre-training task——next sentence prediction," in ACL, 2022, pp. 3233–3250. 1
- [19] K. Zhou, J. Yang, C. C. Loy, and Z. Liu, "Learning to prompt for vision-language models," *IJCV*, vol. 130, no. 9, pp. 2337–2348, 2022.
- [20] —, "Conditional prompt learning for vision-language models," in CVPR, 2022, pp. 16816–16825. 1
- [21] N. Mu, A. Kirillov, D. Wagner, and S. Xie, "Slip: Self-supervision meets language-image pre-training," in ECCV, 2022, pp. 529–544. 1
- [22] J. Ding, N. Xue, G.-S. Xia, and D. Dai, "Decoupling zero-shot semantic segmentation," in CVPR, 2022, pp. 11583–11592. 1
- [23] X. Gu, T.-Y. Lin, W. Kuo, and Y. Cui, "Open-vocabulary object detection via vision and language knowledge distillation," in *ICLR*, 2022. 1
- [24] T. Brown, B. Mann, N. Ryder, M. Subbiah, J. D. Kaplan, P. Dhariwal, A. Neelakantan, P. Shyam, G. Sastry, A. Askell *et al.*, "Language models are few-shot learners," in *Adv. Neural Inform. Process. Syst.*, vol. 33, 2020, pp. 1877–1901. 2
- [25] L. Ouyang, J. Wu, X. Jiang, D. Almeida, C. Wainwright, P. Mishkin, C. Zhang, S. Agarwal, K. Slama, A. Ray *et al.*, "Training language models to follow instructions with human feedback," in *Adv. Neural Inform. Process. Syst.*, vol. 35, 2022, pp. 27730–27744. 2
- [26] S. Zhang, L. Dong, X. Li, S. Zhang, X. Sun, S. Wang, J. Li, R. Hu, T. Zhang, F. Wu *et al.*, "Instruction tuning for large language models: A survey," *arXiv preprint arXiv:2308.10792*, 2023. 2
- [27] J.-B. Alayrac, J. Donahue, P. Luc, A. Miech, I. Barr, Y. Hasson, K. Lenc, A. Mensch, K. Millican, M. Reynolds *et al.*, "Flamingo: a visual language model for few-shot learning," in *Adv. Neural Inform. Process. Syst.*, vol. 35, 2022, pp. 23716–23736. 2, 3
- [28] S. Long, F. Cao, S. C. Han, and H. Yang, "Vision-and-language pretrained models: A survey," arXiv preprint arXiv:2204.07356, 2022.
- [29] X. Zhou, M. Liu, B. L. Zagar, E. Yurtsever, and A. C. Knoll, "Vision language models in autonomous driving and intelligent transportation systems," arXiv preprint arXiv:2310.14414, 2023. 2
- [30] A. Ghosh, A. Acharya, S. Saha, V. Jain, and A. Chadha, "Exploring the frontier of vision-language models: A survey of current methodologies and future directions," arXiv preprint arXiv:2404.07214, 2024. 2
- [31] D. Zhang, Y. Yu, J. Dong, C. Li, D. Su, C. Chu, and D. Yu, "Mm-llms: Recent advances in multimodal large language models," *arXiv preprint* arXiv:2401.13601, 2024. 2
- [32] J. Huang, J. Zhang, K. Jiang, H. Qiu, and S. Lu, "Visual instruction tuning towards general-purpose multimodal model: A survey," arXiv preprint arXiv:2312.16602, 2023. 2
- [33] Y. Wang, W. Chen, X. Han, X. Lin, H. Zhao, Y. Liu, B. Zhai, J. Yuan, Q. You, and H. Yang, "Exploring the reasoning abilities of multimodal large language models (mllms): A comprehensive survey on emerging trends in multimodal reasoning," *arXiv preprint arXiv:2401.06805*, 2024. 2
- [34] Y. Dang, K. Huang, J. Huo, Y. Yan, S. Huang, D. Liu, M. Gao, J. Zhang, C. Qian, K. Wang *et al.*, "Explainable and interpretable multimodal large language models: A comprehensive survey," *arXiv* preprint arXiv:2412.02104, 2024. 2, 14, 17
- [35] C. Fu, Y.-F. Zhang, S. Yin, B. Li, X. Fang, S. Zhao, H. Duan, X. Sun, Z. Liu, L. Wang *et al.*, "Mme-survey: A comprehensive survey on evaluation of multimodal llms," *arXiv preprint arXiv:2411.15296*, 2024. 2
- [36] S. Yin, C. Fu, S. Zhao, K. Li, X. Sun, T. Xu, and E. Chen, "A survey on multimodal large language models," *National Science Review*, p. nwae403, 2024. 2

- [37] J. Wu, W. Gan, Z. Chen, S. Wan, and S. Y. Philip, "Multimodal large language models: A survey," in 2023 IEEE International Conference on Big Data (BigData). IEEE, 2023, pp. 2247–2256. 2
- [38] D. Caffagni, F. Cocchi, L. Barsellotti, N. Moratelli, S. Sarto, L. Baraldi, M. Cornia, and R. Cucchiara, "The (r) evolution of multimodal large language models: A survey," arXiv preprint arXiv:2402.12451, 2024. 2
- [39] C. Li, Z. Gan, Z. Yang, J. Yang, L. Li, L. Wang, J. Gao et al., "Multimodal foundation models: From specialists to general-purpose assistants," *Foundations and Trends*® in *Computer Graphics and Vision*, vol. 16, no. 1-2, pp. 1–214, 2024. 2
- [40] H. Liu, W. Xue, Y. Chen, D. Chen, X. Zhao, K. Wang, L. Hou, R. Li, and W. Peng, "A survey on hallucination in large vision-language models," arXiv preprint arXiv:2402.00253, 2024. 2
- [41] S. Huang, L. Dong, W. Wang, Y. Hao, S. Singhal, S. Ma, T. Lv, L. Cui, O. K. Mohammed, B. Patra *et al.*, "Language is not all you need: Aligning perception with language models," in *Adv. Neural Inform. Process. Syst.*, vol. 36, 2023, pp. 72096–72109. 3, 4
- [42] H. Liu, C. Li, Q. Wu, and Y. J. Lee, "Visual instruction tuning," in Adv. Neural Inform. Process. Syst., vol. 36, 2024. 2, 3, 4, 5, 6, 7, 8, 10
- [43] H. Liu, C. Li, Y. Li, and Y. J. Lee, "Improved baselines with visual instruction tuning," in CVPR, 2024, pp. 26 296–26 306. 3
- [44] D. Zhu, J. Chen, X. Shen, X. Li, and M. Elhoseiny, "Minigpt-4: Enhancing vision-language understanding with advanced large language models," arXiv preprint arXiv:2304.10592, 2023. 2, 3, 5
- [45] J. Chen, D. Zhu, X. Shen, X. Li, Z. Liu, P. Zhang, R. Krishnamoorthi, V. Chandra, Y. Xiong, and M. Elhoseiny, "Minigpt-v2: large language model as a unified interface for vision-language multi-task learning," arXiv preprint arXiv:2310.09478, 2023. 2, 3, 4
- [46] J. Ye, A. Hu, H. Xu, Q. Ye, M. Yan, Y. Dan, C. Zhao, G. Xu, C. Li, J. Tian *et al.*, "mplug-docowl: Modularized multimodal large language model for document understanding," *arXiv preprint arXiv:2307.02499*, 2023. 2, 3, 5
- [47] Q. Ye, H. Xu, J. Ye, M. Yan, A. Hu, H. Liu, Q. Qian, J. Zhang, and F. Huang, "mplug-owl2: Revolutionizing multi-modal large language model with modality collaboration," in *CVPR*, 2024, pp. 13040–13051. 3
- [48] J. Ye, H. Xu, H. Liu, A. Hu, M. Yan, Q. Qian, J. Zhang, F. Huang, and J. Zhou, "mplug-owl3: Towards long image-sequence understanding in multi-modal large language models," *arXiv preprint arXiv:2408.04840*, 2024. 3
- [49] T. Gong, C. Lyu, S. Zhang, Y. Wang, M. Zheng, Q. Zhao, K. Liu, W. Zhang, P. Luo, and K. Chen, "Multimodal-gpt: A vision and language model for dialogue with humans," *arXiv preprint arXiv:2305.04790*, 2023. 3
- [50] B. Li, Y. Zhang, L. Chen, J. Wang, J. Yang, and Z. Liu, "Otter: A multimodal model with in-context instruction tuning. corr abs/2305.03726 (2023)," 2023. 3
- [51] W. Dai, J. Li, D. Li, A. Tiong, J. Zhao, W. Wang, B. Li, P. Fung, and S. Hoi, "Instructblip: Towards general-purpose vision-language models with instruction tuning. arxiv 2023," arXiv preprint arXiv:2305.06500, vol. 2, 2023. 3
- [52] G. Luo, Y. Zhou, T. Ren, S. Chen, X. Sun, and R. Ji, "Cheap and quick: Efficient vision-language instruction tuning for large language models," in *Adv. Neural Inform. Process. Syst.*, vol. 36, 2024. 3
- [53] W. Hu, Y. Xu, Y. Li, W. Li, Z. Chen, and Z. Tu, "Bliva: A simple multimodal llm for better handling of text-rich visual questions," in *AAAI*, vol. 38, no. 3, 2024, pp. 2256–2264. 3
- [54] Y. Li, C. Zhang, G. Yu, Z. Wang, B. Fu, G. Lin, C. Shen, L. Chen, and Y. Wei, "Stablellava: Enhanced visual instruction tuning with synthesized image-dialogue data," *arXiv preprint arXiv:2308.10253*, 2023. 3
- [55] J. Bai, S. Bai, S. Yang, S. Wang, S. Tan, P. Wang, J. Lin, C. Zhou, and J. Zhou, "Qwen-vl: A versatile vision-language model for understanding, localization, text reading, and beyond," *arXiv preprint* arXiv:2308.12966, 2023. 3, 4
- [56] P. Zhang, X. D. B. Wang, Y. Cao, C. Xu, L. Ouyang, Z. Zhao, S. Ding, S. Zhang, H. Duan, H. Yan *et al.*, "Internlm-xcomposer: A vision-language large model for advanced text-image comprehension and composition," *arXiv preprint arXiv:2309.15112*, 2023. 3, 4
- [57] R. Bavishi, E. Elsen, C. Hawthorne, M. Nye, A. Odena, A. Somani, and S. Taşırlar, "Introducing our multimodal models," 2023. [Online]. Available: https://www.adept.ai/blog/fuyu-8b 3
- [58] Z. Li, B. Yang, Q. Liu, Z. Ma, S. Zhang, J. Yang, Y. Sun, Y. Liu, and X. Bai, "Monkey: Image resolution and text label are important things

for large multi-modal models," in CVPR, 2024, pp. 26763–26773. 3, 4

- [59] J. Cha, W. Kang, J. Mun, and B. Roh, "Honeybee: Locality-enhanced projector for multimodal llm," in CVPR, 2024, pp. 13817–13827. 3
- [60] H. Wei, L. Kong, J. Chen, L. Zhao, Z. Ge, J. Yang, J. Sun, C. Han, and X. Zhang, "Vary: Scaling up the vision vocabulary for large visionlanguage models," arXiv preprint arXiv:2312.06109, 2023. 3
- [61] Z. Chen, J. Wu, W. Wang, W. Su, G. Chen, S. Xing, M. Zhong, Q. Zhang, X. Zhu, L. Lu *et al.*, "Internvl: Scaling up vision foundation models and aligning for generic visual-linguistic tasks," in *CVPR*, 2024, pp. 24185–24198. 3
- [62] H. Lu, W. Liu, B. Zhang, B. Wang, K. Dong, B. Liu, J. Sun, T. Ren, Z. Li, Y. Sun *et al.*, "Deepseek-vl: towards real-world vision-language understanding," *arXiv preprint arXiv:2403.05525*, 2024. 3, 4, 14
- [63] Z. Wu, X. Chen, Z. Pan, X. Liu, W. Liu, D. Dai, H. Gao, Y. Ma, C. Wu, B. Wang *et al.*, "Deepseek-vl2: Mixture-of-experts visionlanguage models for advanced multimodal understanding," *arXiv* preprint arXiv:2412.10302, 2024. 3
- [64] B. McKinzie, Z. Gan, J.-P. Fauconnier, S. Dodge, B. Zhang, P. Dufter, D. Shah, X. Du, F. Peng, F. Weers *et al.*, "Mm1: Methods, analysis & insights from multimodal llm pre-training," *arXiv preprint* arXiv:2403.09611, 2024. 3
- [65] Y. Li, Y. Zhang, C. Wang, Z. Zhong, Y. Chen, R. Chu, S. Liu, and J. Jia, "Mini-gemini: Mining the potential of multi-modality vision language models," arXiv preprint arXiv:2403.18814, 2024. 3
- [66] S. Tong, E. Brown, P. Wu, S. Woo, M. Middepogu, S. C. Akula, J. Yang, S. Yang, A. Iyer, X. Pan *et al.*, "Cambrian-1: A fully open, vision-centric exploration of multimodal llms," *arXiv preprint arXiv:2406.16860*, 2024. 3
- [67] X. Lai, Z. Tian, Y. Chen, Y. Li, Y. Yuan, S. Liu, and J. Jia, "Lisa: Reasoning segmentation via large language model," in *CVPR*, 2024, pp. 9579–9589. 3, 4
- [68] Y. Zhang, Z. Ma, X. Gao, S. Shakiah, Q. Gao, and J. Chai, "Groundhog: Grounding large language models to holistic segmentation," in *CVPR*, 2024, pp. 14227–14238. 3, 4
- [69] A. Zhang, L. Zhao, C.-W. Xie, Y. Zheng, W. Ji, and T.-S. Chua, "Nextchat: An lmm for chat, detection and segmentation," arXiv preprint arXiv:2311.04498, 2023. 3
- [70] S. Pramanick, G. Han, R. Hou, S. Nag, S.-N. Lim, N. Ballas, Q. Wang, R. Chellappa, and A. Almahairi, "Jack of all tasks master of many: Designing general-purpose coarse-to-fine vision-language model," in *CVPR*, 2024, pp. 14076–14088. 3, 4
- [71] Y. Zang, W. Li, J. Han, K. Zhou, and C. C. Loy, "Contextual object detection with multimodal large language models," *arXiv preprint* arXiv:2305.18279, 2023. 3
- [72] Z. Ren, Z. Huang, Y. Wei, Y. Zhao, D. Fu, J. Feng, and X. Jin, "Pixellm: Pixel reasoning with large multimodal model," in *CVPR*, 2024, pp. 26 374–26 383. 3
- [73] J. Xu, X. Zhou, S. Yan, X. Gu, A. Arnab, C. Sun, X. Wang, and C. Schmid, "Pixel-aligned language model," in *CVPR*, 2024, pp. 13 030–13 039. 3
- [74] Z. Xia, D. Han, Y. Han, X. Pan, S. Song, and G. Huang, "Gsva: Generalized segmentation via multimodal large language models," in *CVPR*, 2024, pp. 3858–3869. 3, 4
- [75] L. Zhu, T. Chen, D. Ji, J. Ye, and J. Liu, "Llafs: When large language models meet few-shot segmentation," in *CVPR*, 2024, pp. 3065–3075. 3, 4
- [76] H. Rasheed, M. Maaz, S. Shaji, A. Shaker, S. Khan, H. Cholakkal, R. M. Anwer, E. Xing, M.-H. Yang, and F. S. Khan, "Glamm: Pixel grounding large multimodal model," in *CVPR*, 2024, pp. 13009– 13018. 3, 4, 5
- [77] W. Wang, Z. Chen, X. Chen, J. Wu, X. Zhu, G. Zeng, P. Luo, T. Lu, J. Zhou, Y. Qiao *et al.*, "Visionllm: Large language model is also an open-ended decoder for vision-centric tasks," in *Adv. Neural Inform. Process. Syst.*, vol. 36, 2024. 3, 4
- [78] J. Wu, M. Zhong, S. Xing, Z. Lai, Z. Liu, W. Wang, Z. Chen, X. Zhu, L. Lu, T. Lu *et al.*, "Visionllm v2: An end-to-end generalist multimodal large language model for hundreds of vision-language tasks," *arXiv* preprint arXiv:2406.08394, 2024. 3, 4
- [79] Y. Yuan, W. Li, J. Liu, D. Tang, X. Luo, C. Qin, L. Zhang, and J. Zhu, "Osprey: Pixel understanding with visual instruction tuning," in *CVPR*, 2024, pp. 28 202–28 211. 3, 4
- [80] T. Zhang, X. Li, H. Fei, H. Yuan, S. Wu, S. Ji, C. C. Loy, and S. Yan, "Omg-llava: Bridging image-level, object-level, pixel-level reasoning and understanding," *arXiv preprint arXiv:2406.19389*, 2024. 3, 5
- [81] J. Wang and L. Ke, "Llm-seg: Bridging image segmentation and large language model reasoning," in CVPR, 2024, pp. 1765–1774. 3

- [82] Z. Zhang, Y. Ma, E. Zhang, and X. Bai, "Psalm: Pixelwise segmentation with large multi-modal model," *arXiv preprint arXiv:2403.14598*, 2024. 3
- [83] L. Qi, Y.-W. Chen, L. Yang, T. Shen, X. Li, W. Guo, Y. Xu, and M.-H. Yang, "Generalizable entity grounding via assistance of large language model," *arXiv preprint arXiv:2402.02555*, 2024. 3
- [84] R. Pi, J. Gao, S. Diao, R. Pan, H. Dong, J. Zhang, L. Yao, J. Han, H. Xu, L. Kong *et al.*, "Detgpt: Detect what you need via reasoning," *arXiv preprint arXiv:2305.14167*, 2023. 3, 4
- [85] Z. Peng, W. Wang, L. Dong, Y. Hao, S. Huang, S. Ma, and F. Wei, "Kosmos-2: Grounding multimodal large language models to the world," *arXiv preprint arXiv:2306.14824*, 2023. 3, 4, 15
- [86] K. Chen, Z. Zhang, W. Zeng, R. Zhang, F. Zhu, and R. Zhao, "Shikra: Unleashing multimodal llm's referential dialogue magic," arXiv preprint arXiv:2306.15195, 2023. 3, 4, 5
- [87] L. Zhao, E. Yu, Z. Ge, J. Yang, H. Wei, H. Zhou, J. Sun, Y. Peng, R. Dong, C. Han *et al.*, "Chatspot: Bootstrapping multimodal llms via precise referring instruction tuning," *arXiv preprint arXiv:2307.09474*, 2023. 3, 4
- [88] S. Zhang, P. Sun, S. Chen, M. Xiao, W. Shao, W. Zhang, K. Chen, and P. Luo, "Gpt4roi: Instruction tuning large language model on regionof-interest," arXiv preprint arXiv:2307.03601, 2023. 3, 4
- [89] Y. Zhao, Z. Lin, D. Zhou, Z. Huang, J. Feng, and B. Kang, "Bubogpt: Enabling visual grounding in multi-modal llms," *arXiv* preprint arXiv:2307.08581, 2023. 3, 4
- [90] S. Xuan, Q. Guo, M. Yang, and S. Zhang, "Pink: Unveiling the power of referential comprehension for multi-modal llms," in *CVPR*, 2024, pp. 13 838–13 848. 3, 4
- [91] H. You, H. Zhang, Z. Gan, X. Du, B. Zhang, Z. Wang, L. Cao, S.-F. Chang, and Y. Yang, "Ferret: Refer and ground anything anywhere at any granularity," *arXiv preprint arXiv:2310.07704*, 2023. 3, 4
- [92] H. Zhang, H. You, P. Dufter, B. Zhang, C. Chen, H.-Y. Chen, T.-J. Fu, W. Y. Wang, S.-F. Chang, Z. Gan *et al.*, "Ferret-v2: An improved baseline for referring and grounding with large language models," *arXiv* preprint arXiv:2404.07973, 2024. 3, 4
- [93] Q. Zhou, Z. Wang, W. Chu, Y. Xu, H. Li, and Y. Qi, "Infmllm: A unified framework for visual-language tasks," arXiv preprint arXiv:2311.06791, 2023. 3, 4
- [94] G. Chen, L. Shen, R. Shao, X. Deng, and L. Nie, "Lion: Empowering multimodal large language model with dual-level visual knowledge," in CVPR, 2024, pp. 26540–26550. 3, 4
- [95] Z. Lin, C. Liu, R. Zhang, P. Gao, L. Qiu, H. Xiao, H. Qiu, C. Lin, W. Shao, K. Chen *et al.*, "Sphinx: The joint mixing of weights, tasks, and visual embeddings for multi-modal large language models," *arXiv* preprint arXiv:2311.07575, 2023. 3, 4
- [96] A. Zhang, L. Zhao, C.-W. Xie, Y. Zheng, W. Ji, and T.-S. Chua, "Nextchat: An lmm for chat, detection and segmentation," arXiv preprint arXiv:2311.04498, 2023. 3
- [97] Y. Zhan, Y. Zhu, Z. Chen, F. Yang, M. Tang, and J. Wang, "Griffon: Spelling out all object locations at any granularity with large language models," arXiv preprint arXiv:2311.14552, 2023. 3
- [98] W. Wang, Q. Lv, W. Yu, W. Hong, J. Qi, Y. Wang, J. Ji, Z. Yang, L. Zhao, X. Song *et al.*, "Cogvlm: Visual expert for pretrained language models," *arXiv preprint arXiv:2311.03079*, 2023. 3
- [99] H. Zhang, H. Li, F. Li, T. Ren, X. Zou, S. Liu, S. Huang, J. Gao, L. Zhang, C. Li *et al.*, "Llava-grounding: Grounded visual chat with large multimodal models," *arXiv preprint arXiv:2312.02949*, 2023. 3, 5
- [100] F. Wei, X. Zhang, A. Zhang, B. Zhang, and X. Chu, "Lenna: Language enhanced reasoning detection assistant," *arXiv preprint* arXiv:2312.02433, 2023. 3, 4
- [101] Y. Tian, T. Ma, L. Xie, J. Qiu, X. Tang, Y. Zhang, J. Jiao, Q. Tian, and Q. Ye, "Chatterbox: Multi-round multimodal referring and grounding," arXiv preprint arXiv:2401.13307, 2024. 3
- [102] C. Ma, Y. Jiang, J. Wu, Z. Yuan, and X. Qi, "Groma: Localized visual tokenization for grounding multimodal large language models," *arXiv* preprint arXiv:2404.13013, 2024. 3
- [103] Y. Zhang, R. Zhang, J. Gu, Y. Zhou, N. Lipka, D. Yang, and T. Sun, "Llavar: Enhanced visual instruction tuning for text-rich image understanding," arXiv preprint arXiv:2306.17107, 2023. 3, 5
- [104] A. Hu, H. Xu, J. Ye, M. Yan, L. Zhang, B. Zhang, C. Li, J. Zhang, Q. Jin, F. Huang *et al.*, "mplug-docowl 1.5: Unified structure learning for ocr-free document understanding," *arXiv preprint arXiv:2403.12895*, 2024. 3
- [105] H. Feng, Z. Wang, J. Tang, J. Lu, W. Zhou, H. Li, and C. Huang, "Unidoc: A universal large multimodal model for simultaneous"

text detection, recognition, spotting and understanding. corr vol. abs/2308.11592 (2023)." 3, 5

- [106] J. Ye, A. Hu, H. Xu, Q. Ye, M. Yan, G. Xu, C. Li, J. Tian, Q. Qian, J. Zhang *et al.*, "Ureader: Universal ocr-free visually-situated language understanding with multimodal large language model," *arXiv preprint arXiv:2310.05126*, 2023. 3, 5
- [107] Y. Wang, W. Zhou, H. Feng, K. Zhou, and H. Li, "Towards improving document understanding: An exploration on text-grounding via mllms," arXiv preprint arXiv:2311.13194, 2023. 3, 5
- [108] H. Feng, Q. Liu, H. Liu, W. Zhou, H. Li, and C. Huang, "Docpedia: Unleashing the power of large multimodal model in the frequency domain for versatile document understanding," arXiv preprint arXiv:2311.11810, 2023. 3, 5
- [109] Y. Liu, B. Yang, Q. Liu, Z. Li, Z. Ma, S. Zhang, and X. Bai, "Textmonkey: An ocr-free large multimodal model for understanding document," arXiv preprint arXiv:2403.04473, 2024. 3, 5
- [110] C. Liu, K. Yin, H. Cao, X. Jiang, X. Li, Y. Liu, D. Jiang, X. Sun, and L. Xu, "Hrvda: High-resolution visual document assistant," in *CVPR*, 2024, pp. 15534–15545. 3, 5
- [111] C. Luo, Y. Shen, Z. Zhu, Q. Zheng, Z. Yu, and C. Yao, "Layoutlm: Layout instruction tuning with large language models for document understanding," in *CVPR*, 2024, pp. 15630–15640. 3, 5
- [112] X. Li, Y. Wu, X. Jiang, Z. Guo, M. Gong, H. Cao, Y. Liu, D. Jiang, and X. Sun, "Enhancing visual document understanding with contrastive learning in large visual-language models," in *CVPR*, 2024, pp. 15546– 15555. 3
- [113] Z. Mao, H. Bai, L. Hou, J. Wei, X. Jiang, Q. Liu, and K.-F. Wong, "Visually guided generative text-layout pre-training for document intelligence," arXiv preprint arXiv:2403.16516, 2024. 3
- [114] P. Lyu, Y. Li, H. Zhou, W. Ma, X. Wan, Q. Xie, L. Wu, C. Zhang, K. Yao, E. Ding *et al.*, "Structextv3: An efficient vision-language model for text-rich image perception, comprehension, and beyond," *arXiv* preprint arXiv:2405.21013, 2024. 3
- [115] C. Liu, H. Wei, J. Chen, L. Kong, Z. Ge, Z. Zhu, L. Zhao, J. Sun, C. Han, and X. Zhang, "Focus anywhere for fine-grained multi-page document understanding," *arXiv preprint arXiv:2405.14295*, 2024. 3, 5
- [116] J. Zhang, W. Yang, S. Lai, Z. Xie, and L. Jin, "Dockylin: A large multimodal model for visual document understanding with efficient visual slimming," arXiv preprint arXiv:2406.19101, 2024. 3, 5
- [117] X. Dong, P. Zhang, Y. Zang, Y. Cao, B. Wang, L. Ouyang, X. Wei, S. Zhang, H. Duan, M. Cao *et al.*, "Internlm-xcomposer2: Mastering free-form text-image composition and comprehension in visionlanguage large model," *arXiv preprint arXiv:2401.16420*, 2024. 3, 5
- [118] Y.-Q. Yu, M. Liao, J. Wu, Y. Liao, X. Zheng, and W. Zeng, "Texthawk: Exploring efficient fine-grained perception of multimodal large language models," *arXiv preprint arXiv:2404.09204*, 2024. 3
- [119] J. Y. Koh, R. Salakhutdinov, and D. Fried, "Grounding language models to images for multimodal inputs and outputs," in *ICML*. PMLR, 2023, pp. 17283–17300. 3, 5
- [120] Z. Wang, H. Elfardy, M. Dreyer, K. Small, and M. Bansal, "Unified embeddings for multimodal retrieval via frozen llms," in ACL, 2024, pp. 1537–1547. 3, 5
- [121] D. Caffagni, F. Cocchi, N. Moratelli, S. Sarto, M. Cornia, L. Baraldi, and R. Cucchiara, "Wiki-Ilava: Hierarchical retrieval-augmented generation for multimodal llms," in *CVPR*, 2024, pp. 1818–1826. 3, 5
- [122] Y. Yan and W. Xie, "Echosight: Advancing visual-language models with wiki knowledge," arXiv preprint arXiv:2407.12735, 2024. 3, 5
- [123] Y. Bazi, L. Bashmal, M. M. Al Rahhal, R. Ricci, and F. Melgani, "Rsllava: A large vision-language model for joint captioning and question answering in remote sensing imagery," *Remote Sensing*, vol. 16, no. 9, p. 1477, 2024. 3, 6
- [124] Y. Hu, J. Yuan, C. Wen, X. Lu, and X. Li, "Rsgpt: A remote sensing vision language model and benchmark," arXiv preprint arXiv:2307.15266, 2023. 3, 6, 15
- [125] W. Zhang, M. Cai, T. Zhang, Y. Zhuang, and X. Mao, "Earthgpt: A universal multi-modal large language model for multi-sensor image comprehension in remote sensing domain," *IEEE Transactions on Geoscience and Remote Sensing*, 2024. 3, 6, 15
- [126] H.-Y. Zhou, S. Adithan, J. N. Acosta, E. J. Topol, and P. Rajpurkar, "A generalist learner for multifaceted medical image interpretation," *arXiv* preprint arXiv:2405.07988, 2024. 3, 6, 15
- [127] X. Zhang, C. Wu, Z. Zhao, W. Lin, Y. Zhang, Y. Wang, and W. Xie, "Pmc-vqa: Visual instruction tuning for medical visual question answering," arXiv preprint arXiv:2305.10415, 2023. 3, 6, 15

- [128] C. Pellegrini, E. Özsoy, B. Busam, N. Navab, and M. Keicher, "Radialog: A large vision-language model for radiology report generation and conversational assistance," *arXiv preprint arXiv:2311.18681*, 2023. 3, 6, 7
- [129] L. Wang, Y. Hu, J. He, X. Xu, N. Liu, H. Liu, and H. T. Shen, "T-sciq: Teaching multimodal chain-of-thought reasoning via large language model signals for science question answering," in AAAI, vol. 38, no. 17, 2024, pp. 19162–19170. 3, 7
- [130] J. Gao, R. Pi, J. Zhang, J. Ye, W. Zhong, Y. Wang, L. Hong, J. Han, H. Xu, Z. Li *et al.*, "G-llava: Solving geometric problem with multimodal large language model," *arXiv preprint arXiv:2312.11370*, 2023. 3, 7, 15
- [131] R. Zhang, X. Wei, D. Jiang, Y. Zhang, Z. Guo, C. Tong, J. Liu, A. Zhou, B. Wei, S. Zhang *et al.*, "Mavis: Mathematical visual instruction tuning," *CoRR*, 2024. 3, 7, 15
- [132] Y. Cheng, Z. Zhang, M. Yang, H. Nie, C. Li, X. Wu, and J. Shao, "Graphic design with large multimodal model," *arXiv preprint arXiv:2404.14368*, 2024. 3, 7
- [133] W. Hong, W. Wang, Q. Lv, J. Xu, W. Yu, J. Ji, Y. Wang, Z. Wang, Y. Dong, M. Ding *et al.*, "Cogagent: A visual language model for gui agents," in *CVPR*, 2024, pp. 14281–14290. 3, 7
- [134] K. You, H. Zhang, E. Schoop, F. Weers, A. Swearngin, J. Nichols, Y. Yang, and Z. Gan, "Ferret-ui: Grounded mobile ui understanding with multimodal llms," in *ECCV*, 2025, pp. 240–255. 3, 7
- [135] Z. Wang, Y. Li, J. Wu, J. Soon, and X. Zhang, "Finvis-gpt: A multimodal large language model for financial chart analysis," arXiv preprint arXiv:2308.01430, 2023. 3, 7
- [136] G. Bhatia, E. M. B. Nagoudi, H. Cavusoglu, and M. Abdul-Mageed, "Fintral: A family of gpt-4 level multimodal financial large language models," *arXiv preprint arXiv:2402.10986*, 2024. 3, 7
- [137] C. Sun, A. Myers, C. Vondrick, K. Murphy, and C. Schmid, "Videobert: A joint model for video and language representation learning," in *ICCV*, 2019, pp. 7464–7473. 3, 8
- [138] Y. Zhao, I. Misra, P. Krähenbühl, and R. Girdhar, "Learning video representations from large language models," in *CVPR*, 2023, pp. 6586– 6597. 3, 8
- [139] A. Yang, A. Nagrani, P. H. Seo, A. Miech, J. Pont-Tuset, I. Laptev, J. Sivic, and C. Schmid, "Vid2seq: Large-scale pretraining of a visual language model for dense video captioning," in *CVPR*, 2023, pp. 10714–10726. 3, 8
- [140] H. Zhang, X. Li, and L. Bing, "Video-Ilama: An instruction-tuned audio-visual language model for video understanding," arXiv preprint arXiv:2306.02858, 2023. 3, 8
- [141] Y. Li, C. Wang, and J. Jia, "Llama-vid: An image is worth 2 tokens in large language models," arXiv preprint arXiv:2311.17043, 2023. 3, 8
- [142] K. Ataallah, X. Shen, E. Abdelrahman, E. Sleiman, D. Zhu, J. Ding, and M. Elhoseiny, "Minigpt4-video: Advancing multimodal llms for video understanding with interleaved visual-textual tokens," *arXiv preprint arXiv:2404.03413*, 2024. 3, 8
- [143] R. Liu, C. Li, H. Tang, Y. Ge, Y. Shan, and G. Li, "St-Ilm: Large language models are effective temporal learners," arXiv preprint arXiv:2404.00308, 2024. 3, 8
- [144] X. Shen, Y. Xiong, C. Zhao, L. Wu, J. Chen, C. Zhu, Z. Liu, F. Xiao, B. Varadarajan, F. Bordes *et al.*, "Longvu: Spatiotemporal adaptive compression for long video-language understanding," *arXiv preprint arXiv:2410.17434*, 2024. 3, 8
- [145] B. Lin, B. Zhu, Y. Ye, M. Ning, P. Jin, and L. Yuan, "Video-Ilava: Learning united visual representation by alignment before projection," *arXiv preprint arXiv*:2311.10122, 2023. 3, 8
- [146] K. Li, Y. He, Y. Wang, Y. Li, W. Wang, P. Luo, Y. Wang, L. Wang, and Y. Qiao, "Videochat: Chat-centric video understanding," *arXiv preprint* arXiv:2305.06355, 2023. 3, 8
- [147] K. Li, Y. Wang, Y. He, Y. Li, Y. Wang, Y. Liu, Z. Wang, J. Xu, G. Chen, P. Luo *et al.*, "Mvbench: A comprehensive multi-modal video understanding benchmark," *arXiv preprint arXiv:2311.17005*, 2023. 3, 8
- [148] M. Maaz, H. Rasheed, S. Khan, and F. S. Khan, "Video-chatgpt: Towards detailed video understanding via large vision and language models," arXiv preprint arXiv:2306.05424, 2023. 3, 8
- [149] R. Luo, Z. Zhao, M. Yang, J. Dong, M. Qiu, P. Lu, T. Wang, and Z. Wei, "Valley: Video assistant with large language model enhanced ability," arXiv preprint arXiv:2306.07207, 2023. 3, 8
- [150] Y. Wang, Z. Zhang, J. McAuley, and Z. He, "Lvchat: Facilitating long video comprehension," arXiv preprint arXiv:2402.12079, 2024. 3, 8
- [151] R. Liu, C. Li, Y. Ge, Y. Shan, T. H. Li, and G. Li, "One for all: Video conversation is feasible without video instruction tuning," *arXiv* preprint arXiv:2309.15785, 2023. 3, 8

- [152] G. Dai, X. Shu, and W. Wu, "Gpt4ego: Unleashing the potential of pre-trained models for zero-shot egocentric action recognition," *arXiv* preprint arXiv:2401.10039, 2024. 3, 8
- [153] S. Kim, D. Huang, Y. Xian, O. Hilliges, L. Van Gool, and X. Wang, "Palm: Predicting actions through language models," in *ECCV*. Springer, 2025, pp. 140–158. 3, 9
- [154] Q. Zhao, S. Wang, C. Zhang, C. Fu, M. Q. Do, N. Agarwal, K. Lee, and C. Sun, "Antgpt: Can large language models help long-term action anticipation from videos?" *arXiv preprint arXiv:2307.16368*, 2023. 3, 9
- [155] Y. Wang, D. Sun, R. Chen, Y. Yang, and M. Ren, "Egocentric video comprehension via large language model inner speech," in 3rd International Ego4D Workshop, 2023. 3, 9
- [156] J. Mai, J. Chen, G. Qian, M. Elhoseiny, B. Ghanem *et al.*, "Llm as a robotic brain: Unifying egocentric memory and control," *arXiv preprint arXiv:2304.09349v2*, 2023. 3, 9
- [157] E. Dessalene, M. Maynord, C. Fermüller, and Y. Aloimonos, "Leap: Llm-generation of egocentric action programs," *arXiv preprint arXiv:2312.00055*, 2023. 3, 9
- [158] T. Qian, J. Chen, L. Zhuo, Y. Jiao, and Y.-G. Jiang, "Nuscenes-qa: A multi-modal visual question answering benchmark for autonomous driving scenario," in AAAI, vol. 38, no. 5, 2024, pp. 4542–4550. 3, 9, 15
- [159] V. Dewangan, T. Choudhary, S. Chandhok, S. Priyadarshan, A. Jain, A. K. Singh, S. Srivastava, K. M. Jatavallabhula, and K. M. Krishna, "Talk2bev: Language-enhanced bird's-eye view maps for autonomous driving," arXiv preprint arXiv:2310.02251, 2023. 3, 9
- [160] C. Sima, K. Renz, K. Chitta, L. Chen, H. Zhang, C. Xie, P. Luo, A. Geiger, and H. Li, "Drivelm: Driving with graph visual question answering," arXiv preprint arXiv:2312.14150, 2023. 3, 9
- [161] X. Ding, J. Han, H. Xu, W. Zhang, and X. Li, "Hilm-d: Towards high-resolution understanding in multimodal large language models for autonomous driving," *arXiv preprint arXiv:2309.05186*, 2023. 3, 9
- [162] S. Yang, J. Liu, R. Zhang, M. Pan, Z. Guo, X. Li, Z. Chen, P. Gao, Y. Guo, and S. Zhang, "Lidar-Ilm: Exploring the potential of large language models for 3d lidar understanding," *CoRR*, 2023. 3, 9
- [163] W. Wang, J. Xie, C. Hu, H. Zou, J. Fan, W. Tong, Y. Wen, S. Wu, H. Deng, Z. Li *et al.*, "Drivemlm: Aligning multi-modal large language models with behavioral planning states for autonomous driving," *arXiv* preprint arXiv:2312.09245, 2023. 3
- [164] Y. Ma, Y. Cao, J. Sun, M. Pavone, and C. Xiao, "Dolphins: Multimodal language model for driving," *arXiv preprint arXiv:2312.00438*, 2023. 3, 9
- [165] H. Sha, Y. Mu, Y. Jiang, L. Chen, C. Xu, P. Luo, S. E. Li, M. Tomizuka, W. Zhan, and M. Ding, "Languagempc: Large language models as decision makers for autonomous driving," *arXiv preprint arXiv:2310.03026*, 2023. 3
- [166] X. Tian, J. Gu, B. Li, Y. Liu, C. Hu, Y. Wang, K. Zhan, P. Jia, X. Lang, and H. Zhao, "Drivevlm: The convergence of autonomous driving and large vision-language models," *arXiv preprint arXiv:2402.12289*, 2024. 3, 9
- [167] J. Mao, Y. Qian, H. Zhao, and Y. Wang, "Gpt-driver: Learning to drive with gpt," arXiv preprint arXiv:2310.01415, 2023. 3
- [168] L. Wen, D. Fu, X. Li, X. Cai, T. Ma, P. Cai, M. Dou, B. Shi, L. He, and Y. Qiao, "Dilu: A knowledge-driven approach to autonomous driving with large language models," in *ICLR*, 2024. 3, 10
- [169] F. Jia, W. Mao, Y. Liu, Y. Zhao, Y. Wen, C. Zhang, X. Zhang, and T. Wang, "Adriver-i: A general world model for autonomous driving," arXiv preprint arXiv:2311.13549, 2023. 3, 9
- [170] Y. Jin, X. Shen, H. Peng, X. Liu, J. Qin, J. Li, J. Xie, P. Gao, G. Zhou, and J. Gong, "Surrealdriver: Designing generative driver agent simulation framework in urban contexts based on large language model," arXiv preprint arXiv:2309.13193, 2023. 3, 10
- [171] H. Shao, Y. Hu, L. Wang, S. L. Waslander, Y. Liu, and H. Li, "Lmdrive: Closed-loop end-to-end driving with large language models," *arXiv* preprint arXiv:2312.07488, 2023. 3, 9, 10
- [172] Z. Xu, Y. Zhang, E. Xie, Z. Zhao, Y. Guo, K. K. Wong, Z. Li, and H. Zhao, "Drivegpt4: Interpretable end-to-end autonomous driving via large language model," *arXiv preprint arXiv:2310.01412*, 2023. 3, 9, 10
- [173] D. Wu, W. Han, T. Wang, Y. Liu, X. Zhang, and J. Shen, "Language prompt for autonomous driving," arXiv preprint arXiv:2309.04379, 2023. 3, 10
- [174] X. Ding, J. Han, H. Xu, X. Liang, W. Zhang, and X. Li, "Holistic autonomous driving understanding by bird's-eye-view injected multimodal large models," in CVPR, 2024, pp. 13668–13677. 3, 10

- [175] A. Majumdar, A. Ajay, X. Zhang, P. Putta, S. Yenamandra, M. Henaff, S. Silwal, P. Mcvay, O. Maksymets, S. Arnaud *et al.*, "Openeqa: Embodied question answering in the era of foundation models," in *CVPR*, 2024, pp. 16488–16498. 3, 10, 15
- [176] S. Qian, W. Chen, M. Bai, X. Zhou, Z. Tu, and L. E. Li, "Affordancellm: Grounding affordance from vision language models," in *CVPR*, 2024, pp. 7587–7597. 3, 10
- [177] Z. Yuan, J. Ren, C.-M. Feng, H. Zhao, S. Cui, and Z. Li, "Visual programming for zero-shot open-vocabulary 3d visual grounding," in *CVPR*, 2024, pp. 20623–20633. 3, 10
- [178] Y. Hong, H. Zhen, P. Chen, S. Zheng, Y. Du, Z. Chen, and C. Gan, "3d-llm: Injecting the 3d world into large language models," in Adv. Neural Inform. Process. Syst., vol. 36, 2023, pp. 20482–20494. 3, 10
- [179] Z. Wang, R. Shen, and B. Stadie, "Solving robotics problems in zeroshot with vision-language models," arXiv preprint arXiv:2407.19094, 2024. 3, 10
- [180] M. Skreta, Z. Zhou, J. L. Yuan, K. Darvish, A. Aspuru-Guzik, and A. Garg, "Replan: Robotic replanning with perception and language models," *arXiv preprint arXiv:2401.04157*, 2024. 3, 10
- [181] B. Zitkovich, T. Yu, S. Xu, P. Xu, T. Xiao, F. Xia, J. Wu, P. Wohlhart, S. Welker, A. Wahid *et al.*, "Rt-2: Vision-language-action models transfer web knowledge to robotic control," in *Conference on Robot Learning*. PMLR, 2023, pp. 2165–2183. 3
- [182] O. X.-E. Collaboration, A. O'Neill, A. Rehman, A. Maddukuri, A. Gupta, A. Padalkar, A. Lee, A. Pooley, A. Gupta, A. Mandlekar, A. Jain, A. Tung, A. Bewley, A. Herzog, A. Irpan, A. Khazatsky, A. Rai, A. Gupta, A. Wang, A. Kolobov, A. Singh, A. Garg, A. Kembhavi, A. Xie, A. Brohan, A. Raffin, A. Sharma, A. Yavary, A. Jain, A. Balakrishna, A. Wahid, B. Burgess-Limerick, B. Kim, B. Schölkopf, B. Wulfe, B. Ichter, C. Lu, C. Xu, C. Le, C. Finn, C. Wang, C. Xu, C. Chi, C. Huang, C. Chan, C. Agia, C. Pan, C. Fu, C. Devin, D. Xu, D. Morton, D. Driess, D. Chen, D. Pathak, D. Shah, D. Büchler, D. Jayaraman, D. Kalashnikov, D. Sadigh, E. Johns, E. Foster, F. Liu, F. Ceola, F. Xia, F. Zhao, F. V. Frujeri, F. Stulp, G. Zhou, G. S. Sukhatme, G. Salhotra, G. Yan, G. Feng, G. Schiavi, G. Berseth, G. Kahn, G. Yang, G. Wang, H. Su, H.-S. Fang, H. Shi, H. Bao, H. B. Amor, H. I. Christensen, H. Furuta, H. Walke, H. Fang, H. Ha, I. Mordatch, I. Radosavovic, I. Leal, J. Liang, J. Abou-Chakra, J. Kim, J. Drake, J. Peters, J. Schneider, J. Hsu, J. Bohg, J. Bingham, J. Wu, J. Gao, J. Hu, J. Wu, J. Wu, J. Sun, J. Luo, J. Gu, J. Tan, J. Oh, J. Wu, J. Lu, J. Yang, J. Malik, J. Silvério, J. Hejna, J. Booher, J. Tompson, J. Yang, J. Salvador, J. J. Lim, J. Han, K. Wang, K. Rao, K. Pertsch, K. Hausman, K. Go, K. Gopalakrishnan, K. Goldberg, K. Byrne, K. Oslund, K. Kawaharazuka, K. Black, K. Lin, K. Zhang, K. Ehsani, K. Lekkala, K. Ellis, K. Rana, K. Srinivasan, K. Fang, K. P. Singh, K.-H. Zeng, K. Hatch, K. Hsu, L. Itti, L. Y. Chen, L. Pinto, L. Fei-Fei, L. Tan, L. J. Fan, L. Ott, L. Lee, L. Weihs, M. Chen, M. Lepert, M. Memmel, M. Tomizuka, M. Itkina, M. G. Castro, M. Spero, M. Du, M. Ahn, M. C. Yip, M. Zhang, M. Ding, M. Heo, M. K. Srirama, M. Sharma, M. J. Kim, N. Kanazawa, N. Hansen, N. Heess, N. J. Joshi, N. Suenderhauf, N. Liu, N. D. Palo, N. M. M. Shafiullah, O. Mees, O. Kroemer, O. Bastani, P. R. Sanketi, P. T. Miller, P. Yin, P. Wohlhart, P. Xu, P. D. Fagan, P. Mitrano, P. Sermanet, P. Abbeel, P. Sundaresan, Q. Chen, Q. Vuong, R. Rafailov, R. Tian, R. Doshi, R. Mart'in-Mart'in, R. Baijal, R. Scalise, R. Hendrix, R. Lin, R. Qian, R. Zhang, R. Mendonca, R. Shah, R. Hoque, R. Julian, S. Bustamante, S. Kirmani, S. Levine, S. Lin, S. Moore, S. Bahl, S. Dass, S. Sonawani, S. Song, S. Xu, S. Haldar, S. Karamcheti, S. Adebola, S. Guist, S. Nasiriany, S. Schaal, S. Welker, S. Tian, S. Ramamoorthy, S. Dasari, S. Belkhale, S. Park, S. Nair, S. Mirchandani, T. Osa, T. Gupta, T. Harada, T. Matsushima, T. Xiao, T. Kollar, T. Yu, T. Ding, T. Davchev, T. Z. Zhao, T. Armstrong, T. Darrell, T. Chung, V. Jain, V. Vanhoucke, W. Zhan, W. Zhou, W. Burgard, X. Chen, X. Chen, X. Wang, X. Zhu, X. Geng, X. Liu, X. Liangwei, X. Li, Y. Pang, Y. Lu, Y. J. Ma, Y. Kim, Y. Chebotar, Y. Zhou, Y. Zhu, Y. Wu, Y. Xu, Y. Wang, Y. Bisk, Y. Dou, Y. Cho, Y. Lee, Y. Cui, Y. Cao, Y.-H. Wu, Y. Tang, Y. Zhu, Y. Zhang, Y. Jiang, Y. Li, Y. Li, Y. Iwasawa, Y. Matsuo, Z. Ma, Z. Xu, Z. J. Cui, Z. Zhang, Z. Fu, and Z. Lin, "Open X-Embodiment: Robotic learning datasets and RT-X models," https://arxiv.org/abs/2310.08864, 2023. 3, 10.15
- [183] D. Driess, F. Xia, M. S. Sajjadi, C. Lynch, A. Chowdhery, B. Ichter, A. Wahid, J. Tompson, Q. Vuong, T. Yu *et al.*, "Palm-e: an embodied multimodal language model," in *ICML*, 2023, pp. 8469–8488. 3, 10
- [184] S. Huang, Z. Jiang, H. Dong, Y. Qiao, P. Gao, and H. Li, "Instruct2act: Mapping multi-modality instructions to robotic actions with large language model," arXiv preprint arXiv:2305.11176, 2023. 3, 10

- [185] X. Li, M. Liu, H. Zhang, C. Yu, J. Xu, H. Wu, C. Cheang, Y. Jing, W. Zhang, H. Liu *et al.*, "Vision-language foundation models as effective robot imitators," in *ICLR*, 2024. 3, 10
- [186] D. Niu, Y. Sharma, G. Biamby, J. Quenum, Y. Bai, B. Shi, T. Darrell, and R. Herzig, "Llarva: Vision-action instruction tuning enhances robot learning," *arXiv preprint arXiv:2406.11815*, 2024. 3, 10
- [187] X. Li, M. Zhang, Y. Geng, H. Geng, Y. Long, Y. Shen, R. Zhang, J. Liu, and H. Dong, "ManipIlm: Embodied multimodal large language model for object-centric robotic manipulation," in *CVPR*, 2024, pp. 18061– 18070. 3, 10
- [188] M. J. Kim, K. Pertsch, S. Karamcheti, T. Xiao, A. Balakrishna, S. Nair, R. Rafailov, E. Foster, G. Lam, P. Sanketi *et al.*, "Openvla: An open-source vision-language-action model," *arXiv preprint arXiv:2406.09246*, 2024. 3, 10
- [189] B. Chen, F. Xia, B. Ichter, K. Rao, K. Gopalakrishnan, M. S. Ryoo, A. Stone, and D. Kappler, "Open-vocabulary queryable scene representations for real world planning," in *ICRA*, 2023, pp. 11509–11522. 3, 10
- [190] Y. Du, O. Watkins, Z. Wang, C. Colas, T. Darrell, P. Abbeel, A. Gupta, and J. Andreas, "Guiding pretraining in reinforcement learning with large language models," in *ICML*, 2023, pp. 8657–8677. 3, 11
- [191] A. Szot, M. Schwarzer, H. Agrawal, B. Mazoure, R. Metcalf, W. Talbott, N. Mackraz, R. D. Hjelm, and A. T. Toshev, "Large language models as generalizable policies for embodied tasks," in *ICLR*, 2024. 3, 11
- [192] S. Chen, X. Chen, C. Zhang, M. Li, G. Yu, H. Fei, H. Zhu, J. Fan, and T. Chen, "Ll3da: Visual interactive instruction tuning for omni-3d understanding reasoning and planning," in *CVPR*, 2024, pp. 26428– 26438. 3, 11
- [193] D. Shah et al., "Lm-nav: Robotic navigation with large pretrained models of language, vision, and action," arXiv preprint arXiv:2204.04102, 2022. 3, 11
- [194] Y. Hong, Z. Zheng, P. Chen, Y. Wang, J. Li, and C. Gan, "Multiply: A multisensory object-centric embodied large language model in 3d world," in *CVPR*, 2024, pp. 26406–26416. 3, 11
- [195] Y. Yang, T. Zhou, K. Li, D. Tao, L. Li, L. Shen, X. He, J. Jiang, and Y. Shi, "Embodied multi-modal agent trained by an llm from a parallel textworld," in *CVPR*, 2024, pp. 26275–26285. 3, 11
- [196] Q. Gu, A. Kuwajerwala, S. Morin, K. M. Jatavallabhula, B. Sen, A. Agarwal, C. Rivera, W. Paul, K. Ellis, R. Chellappa *et al.*, "Conceptgraphs: Open-vocabulary 3d scene graphs for perception and planning," *arXiv preprint arXiv:2309.16650*, 2023. 3, 11
- [197] Z. Yang, J. Liu, P. Chen, A. Cherian, T. K. Marks, J. Le Roux, and C. Gan, "Rila: Reflective and imaginative language agent for zero-shot semantic audio-visual navigation," in *CVPR*, 2024, pp. 16251–16261. 3, 11
- [198] Z. Yang, L. Li, J. Wang, K. Lin, E. Azarnasab, F. Ahmed, Z. Liu, C. Liu, M. Zeng, and L. Wang, "Mm-react: Prompting chatgpt for multimodal reasoning and action," *arXiv preprint arXiv:2303.11381*, 2023. 3, 11
- [199] Z. Hu, A. Iscen, C. Sun, K.-W. Chang, Y. Sun, D. Ross, C. Schmid, and A. Fathi, "Avis: Autonomous visual information seeking with large language model agent," *Adv. Neural Inform. Process. Syst.*, vol. 36, 2024. 3, 11
- [200] C. Wang, W. Luo, Q. Chen, H. Mai, J. Guo, S. Dong, Z. Li, L. Ma, S. Gao et al., "Tool-Imm: A large multi-modal model for tool agent learning," arXiv preprint arXiv:2401.10727, 2024. 3, 12
- [201] Y. Shen, K. Song, X. Tan, D. Li, W. Lu, and Y. Zhuang, "Hugginggpt: Solving ai tasks with chatgpt and its friends in hugging face," Adv. Neural Inform. Process. Syst., vol. 36, 2024. 3, 12
- [202] Z. Gao, Y. Du, X. Zhang, X. Ma, W. Han, S.-C. Zhu, and Q. Li, "Clova: A closed-loop visual assistant with tool usage and update," in *CVPR*, 2024, pp. 13 258–13 268. 3, 12
- [203] Y. Liang, C. Wu, T. Song, W. Wu, Y. Xia, Y. Liu, Y. Ou, S. Lu, L. Ji, S. Mao *et al.*, "Taskmatrix. ai: Completing tasks by connecting foundation models with millions of apis," *Intelligent Computing*, vol. 3, p. 0063, 2024. 3
- [204] D. Surís, S. Menon, and C. Vondrick, "Vipergpt: Visual inference via python execution for reasoning," in *ICCV*, 2023, pp. 11888–11898. 3, 12
- [205] R. Yang, L. Song, Y. Li, S. Zhao, Y. Ge, X. Li, and Y. Shan, "Gpt4tools: Teaching large language model to use tools via self-instruction," Adv. Neural Inform. Process. Syst., vol. 36, 2024. 3, 12
- [206] L. Yuan, Y. Chen, X. Wang, Y. R. Fung, H. Peng, and H. Ji, "Craft: Customizing llms by creating and retrieving from specialized toolsets," *arXiv preprint arXiv:2309.17428*, 2023. 3, 12

- [207] S. Hao, T. Liu, Z. Wang, and Z. Hu, "Toolkengpt: Augmenting frozen language models with massive tools via tool embeddings," *Adv. Neural Inform. Process. Syst.*, vol. 36, 2024. 3, 12
- [208] P. Lu, B. Peng, H. Cheng, M. Galley, K.-W. Chang, Y. N. Wu, S.-C. Zhu, and J. Gao, "Chameleon: Plug-and-play compositional reasoning with large language models," *Adv. Neural Inform. Process. Syst.*, vol. 36, 2024. 3, 11
- [209] Z. Wang, D. Fried, and G. Neubig, "Trove: Inducing verifiable and efficient toolboxes for solving programmatic tasks," *arXiv preprint* arXiv:2401.12869, 2024. 3, 12
- [210] R. Liu, J. Wei, S. S. Gu, T.-Y. Wu, S. Vosoughi, C. Cui, D. Zhou, and A. M. Dai, "Mind's eye: Grounded language model reasoning through simulation," *arXiv preprint arXiv:2210.05359*, 2022. 3, 11
- [211] S. Gao, Z. Shi, M. Zhu, B. Fang, X. Xin, P. Ren, Z. Chen, J. Ma, and Z. Ren, "Confucius: Iterative tool learning from introspection feedback by easy-to-difficult curriculum," in *AAAI*, vol. 38, no. 16, 2024, pp. 18 030–18 038. 3, 12
- [212] S. Agashe, J. Han, S. Gan, J. Yang, A. Li, and X. E. Wang, "Agent s: An open agentic framework that uses computers like a human," *arXiv* preprint arXiv:2410.08164, 2024. 3, 12
- [213] C. Jia, M. Luo, Z. Dang, Q. Sun, F. Xu, J. Hu, T. Xie, and Z. Wu, "Agentstore: Scalable integration of heterogeneous agents as specialized generalist computer assistant," *arXiv preprint arXiv:2410.18603*, 2024. 3, 12
- [214] Z. Wu, Z. Wu, F. Xu, Y. Wang, Q. Sun, C. Jia, K. Cheng, Z. Ding, L. Chen, P. P. Liang *et al.*, "Os-atlas: A foundation action model for generalist gui agents," *arXiv preprint arXiv:2410.23218*, 2024. 3, 12
- [215] Y. Zhang, Y. Cao, X. Xu, and W. Shen, "Logicode: an Ilm-driven framework for logical anomaly detection," arXiv preprint arXiv:2406.04687, 2024. 3, 12
- [216] X. Yu, B. Peng, V. Vajipey, H. Cheng, M. Galley, J. Gao, and Z. Yu, "Exact: Teaching ai agents to explore with reflective-mcts and exploratory learning," *arXiv preprint arXiv:2410.02052*, 2024. 3, 12
- [217] K. Yang, Y. Liu, S. Chaudhary, R. Fakoor, P. Chaudhari, G. Karypis, and H. Rangwala, "Agentoccam: A simple yet strong baseline for Ilmbased web agents," arXiv preprint arXiv:2410.13825, 2024. 3, 12
- [218] Anonymous, "Learn-by-interact: A data-centric framework for selfadaptive agents in realistic environments," in Submitted to The Thirteenth International Conference on Learning Representations, 2024, under review. [Online]. Available: https://openreview.net/forum? id=3UKOzGWCVY 3, 12
- [219] J. Y. Koh, D. Fried, and R. R. Salakhutdinov, "Generating images with multimodal language models," *Advances in Neural Information Processing Systems*, vol. 36, 2024. 3, 12
- [220] B. Xia, S. Wang, Y. Tao, Y. Wang, and J. Jia, "Llmga: Multimodal large language model based generation assistant," arXiv preprint arXiv:2311.16500, 2023. 3, 12
- [221] L. Lian, B. Li, A. Yala, and T. Darrell, "Llm-grounded diffusion: Enhancing prompt understanding of text-to-image diffusion models with large language models," in *TMLR*, 2024. 3, 12
- [222] Y. Ge, S. Zhao, Z. Zeng, Y. Ge, C. Li, X. Wang, and Y. Shan, "Planting a seed of vision in large language model," in *The Twelfth International Conference on Learning Representations*, 2023. 3, 12
- [223] Y. Jin, K. Xu, L. Chen, C. Liao, J. Tan, Q. Huang, C. Bin, C. Song, D. ZHANG, W. Ou *et al.*, "Unified language-vision pretraining in llm with dynamic discrete visual tokenization," in *The Twelfth International Conference on Learning Representations*, 2023. 3, 12, 13
- [224] Q. Sun, Q. Yu, Y. Cui, F. Zhang, X. Zhang, Y. Wang, H. Gao, J. Liu, T. Huang, and X. Wang, "Generative pretraining in multimodality," in *ICLR*, 2024. 3, 12
- [225] J. Zhu, X. Ding, Y. Ge, Y. Ge, S. Zhao, H. Zhao, X. Wang, and Y. Shan, "Vl-gpt: A generative pre-trained transformer for vision and language understanding and generation," *arXiv preprint arXiv:2312.09251*, 2023. 3, 12
- [226] K. Zheng, X. He, and X. E. Wang, "Minigpt-5: Interleaved visionand-language generation via generative vokens," arXiv preprint arXiv:2310.02239, 2023. 3, 12
- [227] X. Pan, L. Dong, S. Huang, Z. Peng, W. Chen, and F. Wei, "Kosmos-g: Generating images in context with multimodal large language models," arXiv preprint arXiv:2310.02992, 2023. 3, 12, 13
- [228] Z. Tang, Z. Yang, M. Khademi, Y. Liu, C. Zhu, and M. Bansal, "Codi-2: In-context, interleaved, and interactive any-to-any generation," *arXiv* preprint arXiv:2311.18775, 2023. 3, 12
- [229] E. Aiello, L. YU, Y. Nie, A. Aghajanyan, and B. Oguz, "Jointly training large autoregressive multimodal models," in *The Twelfth International Conference on Learning Representations*, 2023. 3, 12

- [230] L. Yu, B. Shi, R. Pasunuru, B. Muller, O. Golovneva, T. Wang, A. Babu, B. Tang, B. Karrer, S. Sheynin *et al.*, "Scaling autoregressive multi-modal models: Pretraining and instruction tuning," *arXiv preprint arXiv:2309.02591*, vol. 2, no. 3, 2023. 3, 12
- [231] J. Qin, J. Wu, W. Chen, Y. Ren, H. Li, H. Wu, X. Xiao, R. Wang, and S. Wen, "Diffusiongpt: Llm-driven text-to-image generation system," arXiv preprint arXiv:2401.10061, 2024. 3, 12
- [232] Y. Ge, S. Zhao, Z. Zeng, Y. Ge, C. Li, X. Wang, and Y. Shan, "Making llama see and draw with seed tokenizer," *arXiv preprint* arXiv:2310.01218, 2023. 3, 13
- [233] Y. Lin, H. Wu, R. Wang, H. Lu, X. Lin, H. Xiong, and L. Wang, "Towards language-guided interactive 3d generation: Llms as layout interpreter with generative feedback," *arXiv preprint arXiv:2305.15808*, 2023. 3, 13
- [234] C. Sun, J. Han, W. Deng, X. Wang, Z. Qin, and S. Gould, "3d-gpt: Procedural 3d modeling with large language models," *arXiv preprint* arXiv:2310.12945, 2023. 3, 13
- [235] F. Yin, X. Chen, C. Zhang, B. Jiang, Z. Zhao, J. Fan, G. Yu, T. Li, and T. Chen, "Shapegpt: 3d shape generation with a unified multi-modal language model," arXiv preprint arXiv:2311.17618, 2023. 3, 13
- [236] Y. Yang, F.-Y. Sun, L. Weihs, E. VanderBilt, A. Herrasti, W. Han, J. Wu, N. Haber, R. Krishna, L. Liu *et al.*, "Holodeck: Language guided generation of 3d embodied ai environments," in *The IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR 2024)*, vol. 30. IEEE/CVF, 2024, pp. 20–25. 3, 13
- [237] F. De La Torre, C. M. Fang, H. Huang, A. Banburski-Fahey, J. A. Fernandez, and J. Lanier, "Llmr: Real-time prompting of interactive worlds using large language models," *arXiv preprint arXiv:2309.12276*, 2023. 3, 13
- [238] Y. Siddiqui, A. Alliegro, A. Artemov, T. Tommasi, D. Sirigatti, V. Rosov, A. Dai, and M. Nießner, "Meshgpt: Generating triangle meshes with decoder-only transformers," *arXiv preprint arXiv:2311.15475*, 2023. 3, 13
- [239] Z. Qi, Y. Fang, Z. Sun, X. Wu, T. Wu, J. Wang, D. Lin, and H. Zhao, "Gpt4point: A unified framework for point-language understanding and generation," in *CVPR*, 2024. 3, 13
- [240] F. Long, Z. Qiu, T. Yao, and T. Mei, "Videodrafter: Contentconsistent multi-scene video generation with llm," *arXiv preprint arXiv:2401.01256*, 2024. 3, 13
- [241] H. Huang, Y. Feng, C. Shi, L. Xu, J. Yu, and S. Yang, "Free-bloom: Zero-shot text-to-video generator with llm director and ldm animator," in *Thirty-seventh Conference on Neural Information Processing Sys*tems, 2023. 3, 13
- [242] H. Lin, A. Zala, J. Cho, and M. Bansal, "Videodirectorgpt: Consistent multi-scene video generation via llm-guided planning," arXiv preprint arXiv:2309.15091, 2023. 3, 14
- [243] Z. Yuan, R. Chen, Z. Li, H. Jia, L. He, C. Wang, and L. Sun, "Mora: Enabling generalist video generation via a multi-agent framework," *arXiv preprint arXiv:2403.13248*, 2024. 3, 14
- [244] A. Blattmann, T. Dockhorn, S. Kulal, D. Mendelevitch, M. Kilian, D. Lorenz, Y. Levi, Z. English, V. Voleti, A. Letts *et al.*, "Stable video diffusion: Scaling latent video diffusion models to large datasets," *arXiv* preprint arXiv:2311.15127, 2023. 3, 14
- [245] L. Yu, J. Lezama, N. B. Gundavarapu, L. Versari, K. Sohn, D. Minnen, Y. Cheng, A. Gupta, X. Gu, A. G. Hauptmann *et al.*, "Language model beats diffusion-tokenizer is key to visual generation," in *The Twelfth International Conference on Learning Representations*, 2023. 3, 14
- [246] D. Kondratyuk, L. Yu, X. Gu, J. Lezama, J. Huang, R. Hornung, H. Adam, H. Akbari, Y. Alon, V. Birodkar *et al.*, "Videopoet: A large language model for zero-shot video generation," *arXiv preprint arXiv:2312.14125*, 2023. 3, 14
- [247] C. Raffel, N. Shazeer, A. Roberts, K. Lee, S. Narang, M. Matena, Y. Zhou, W. Li, and P. J. Liu, "Exploring the limits of transfer learning with a unified text-to-text transformer," *Journal of machine learning research*, vol. 21, no. 140, pp. 1–67, 2020. 2
- [248] H. Liu, C. Li, Y. Li, and Y. J. Lee, "Improved baselines with visual instruction tuning," arXiv preprint arXiv:2310.03744, 2023. 2, 3
- [249] W. Dai, J. Li, D. Li, A. M. H. Tiong, J. Zhao, W. Wang, B. Li, P. N. Fung, and S. Hoi, "Instructblip: Towards general-purpose visionlanguage models with instruction tuning," in *Adv. Neural Inform. Process. Syst.*, vol. 36, 2024. 2
- [250] T.-Y. Lin, M. Maire, S. Belongie, J. Hays, P. Perona, D. Ramanan, P. Dollár, and C. L. Zitnick, "Microsoft coco: Common objects in context," in *ECCV*, 2014, pp. 740–755. 2, 15
- [251] R. Krishna, Y. Zhu, O. Groth, J. Johnson, K. Hata, J. Kravitz, S. Chen, Y. Kalantidis, L.-J. Li, D. A. Shamma *et al.*, "Visual genome: Connect-

ing language and vision using crowdsourced dense image annotations," *IJCV*, vol. 123, pp. 32–73, 2017. 2, 15

- [252] S. Changpinyo, P. Sharma, N. Ding, and R. Soricut, "Conceptual 12m: Pushing web-scale image-text pre-training to recognize long-tail visual concepts," in *CVPR*, 2021, pp. 3558–3568. 2, 15
- [253] P. Sharma, N. Ding, S. Goodman, and R. Soricut, "Conceptual captions: A cleaned, hypernymed, image alt-text dataset for automatic image captioning," in ACL, 2018, pp. 2556–2565. 2, 15
- [254] C. Schuhmann, R. Vencu, R. Beaumont, R. Kaczmarczyk, C. Mullis, A. Katta, T. Coombes, J. Jitsev, and A. Komatsuzaki, "Laion-400m: Open dataset of clip-filtered 400 million image-text pairs," *arXiv* preprint arXiv:2111.02114, 2021. 2
- [255] J. Achiam, S. Adler, S. Agarwal, L. Ahmad, I. Akkaya, F. L. Aleman, D. Almeida, J. Altenschmidt, S. Altman, S. Anadkat *et al.*, "Gpt-4 technical report," *arXiv preprint arXiv:2303.08774*, 2023. 3, 6, 7
- [256] G. Team, R. Anil, S. Borgeaud, J.-B. Alayrac, J. Yu, R. Soricut, J. Schalkwyk, A. M. Dai, A. Hauth, K. Millican *et al.*, "Gemini: a family of highly capable multimodal models," *arXiv preprint arXiv:2312.11805*, 2023. 3
- [257] L. Chen, J. Li, X. Dong, P. Zhang, C. He, J. Wang, F. Zhao, and D. Lin, "Sharegpt4v: Improving large multi-modal models with better captions," arXiv preprint arXiv:2311.12793, 2023. 3
- [258] J. Wang, L. Meng, Z. Weng, B. He, Z. Wu, and Y.-G. Jiang, "To see is to believe: Prompting gpt-4v for better visual instruction tuning," *arXiv preprint arXiv:2311.07574*, 2023. 3
- [259] Q. Ye, H. Xu, J. Ye, M. Yan, H. Liu, Q. Qian, J. Zhang, F. Huang, and J. Zhou, "mplug-owl2: Revolutionizing multi-modal large language model with modality collaboration," *arXiv preprint arXiv:2311.04257*, 2023. 3, 4
- [260] W.-L. Chiang, Z. Li, Z. Lin, Y. Sheng, Z. Wu, H. Zhang, L. Zheng, S. Zhuang, Y. Zhuang, J. E. Gonzalez *et al.*, "Vicuna: An opensource chatbot impressing gpt-4 with 90%* chatgpt quality," *See https://vicuna. lmsys. org (accessed 14 April 2023)*, vol. 2, no. 3, p. 6, 2023. 3
- [261] W. Lian, G. Wang, B. Goodson, E. Pentland, A. Cook, C. Vong, and "Teknium", "Slimorca: An open dataset of gpt-4 augmented flan reasoning traces, with verification," 2023. [Online]. Available: https://https://huggingface.co/Open-Orca/SlimOrca 3
- [262] R. Taori, I. Gulrajani, T. Zhang, Y. Dubois, X. Li, C. Guestrin, P. Liang, and T. B. Hashimoto, "Stanford alpaca: An instruction-following llama model," https://github.com/tatsu-lab/stanford_alpaca, 2023. 3
- [263] W.-L. Chiang, Z. Li, Z. Lin, Y. Sheng, Z. Wu, H. Zhang, L. Zheng, S. Zhuang, Y. Zhuang, J. E. Gonzalez, I. Stoica, and E. P. Xing, "Vicuna: An open-source chatbot impressing gpt-4 with 90%* chatgpt quality," March 2023. [Online]. Available: https://lmsys.org/blog/2023-03-30-vicuna/ 3
- [264] A. Kirillov, E. Mintun, N. Ravi, H. Mao, C. Rolland, L. Gustafson, T. Xiao, S. Whitehead, A. C. Berg, W.-Y. Lo *et al.*, "Segment anything," in *ICCV*, 2023, pp. 4015–4026. 4
- [265] W. Wang, Y. Ren, H. Luo, T. Li, C. Yan, Z. Chen, W. Wang, Q. Li, L. Lu, X. Zhu *et al.*, "The all-seeing project v2: Towards general relation comprehension of the open world," *arXiv preprint arXiv:2402.19474*, 2024. 4
- [266] Z. Liu, H. Mao, C.-Y. Wu, C. Feichtenhofer, T. Darrell, and S. Xie, "A convnet for the 2020s," CVPR, 2022. 4
- [267] M. Oquab, T. Darcet, T. Moutakanni, H. Vo, M. Szafraniec, V. Khalidov, P. Fernandez, D. Haziza, F. Massa, A. El-Nouby *et al.*, "Dinov2: Learning robust visual features without supervision," *arXiv preprint arXiv:2304.07193*, 2023. 4
- [268] S. Liu, Z. Zeng, T. Ren, F. Li, H. Zhang, J. Yang, C. Li, J. Yang, H. Su, J. Zhu *et al.*, "Grounding dino: Marrying dino with grounded pre-training for open-set object detection," *arXiv preprint* arXiv:2303.05499, 2023. 4
- [269] Y. Zhang, X. Huang, J. Ma, Z. Li, Z. Luo, Y. Xie, Y. Qin, T. Luo, Y. Li, S. Liu *et al.*, "Recognize anything: A strong image tagging model," in *CVPR*, 2024, pp. 1724–1732. 4
- [270] H. Zhang, F. Li, X. Zou, S. Liu, C. Li, J. Yang, and L. Zhang, "A simple framework for open-vocabulary segmentation and detection," in *ICCV*, 2023, pp. 1020–1031. 5
- [271] J. Mao, J. Huang, A. Toshev, O. Camburu, A. L. Yuille, and K. Murphy, "Generation and comprehension of unambiguous object descriptions," in CVPR, 2016, pp. 11–20. 5
- [272] Z. Liu, Y. Lin, Y. Cao, H. Hu, Y. Wei, Z. Zhang, S. Lin, and B. Guo, "Swin transformer: Hierarchical vision transformer using shifted windows," in *ICCV*, 2021, pp. 10012–10022. 5

- [273] J. D. Silva, J. Magalhães, D. Tuia, and B. Martins, "Large language models for captioning and retrieving remote sensing images," *arXiv* preprint arXiv:2402.06475, 2024. 6
- [274] Y. Zhan, Z. Xiong, and Y. Yuan, "Skyeyegpt: Unifying remote sensing vision-language tasks via instruction tuning with large language model," arXiv preprint arXiv:2401.09712, 2024. 6
- [275] K. Kuckreja, M. S. Danish, M. Naseer, A. Das, S. Khan, and F. S. Khan, "Geochat: Grounded large vision-language model for remote sensing," in *CVPR*, 2024, pp. 27831–27840. 6
- [276] D. Muhtar, Z. Li, F. Gu, X. Zhang, and P. Xiao, "Lhrs-bot: Empowering remote sensing with vgi-enhanced large multimodal language model," arXiv preprint arXiv:2402.02544, 2024. 6, 15
- [277] C. Pang, J. Wu, J. Li, Y. Liu, J. Sun, W. Li, X. Weng, S. Wang, L. Feng, G.-S. Xia *et al.*, "H2rsvlm: Towards helpful and honest remote sensing large vision language model," *arXiv preprint arXiv:2403.20213*, 2024. 6, 15
- [278] W. Zhang, M. Cai, T. Zhang, G. Lei, Y. Zhuang, and X. Mao, "Popeye: A unified visual-language model for multi-source ship detection from remote sensing imagery," *arXiv preprint arXiv:2403.03790*, 2024. 6, 15
- [279] C. Li, C. Wong, S. Zhang, N. Usuyama, H. Liu, J. Yang, T. Naumann, H. Poon, and J. Gao, "Llava-med: Training a large language-and-vision assistant for biomedicine in one day," in *Adv. Neural Inform. Process. Syst.*, vol. 36, 2024. 6
- [280] M. Moor, Q. Huang, S. Wu, M. Yasunaga, Y. Dalmia, J. Leskovec, C. Zakka, E. P. Reis, and P. Rajpurkar, "Med-flamingo: a multimodal medical few-shot learner," in *Machine Learning for Health (ML4H)*. PMLR, 2023, pp. 353–367. 6, 15
- [281] Y. Zhou, L. Song, and J. Shen, "Training medical large visionlanguage models with abnormal-aware feedback," arXiv preprint arXiv:2501.01377, 2025. 6
- [282] J. He, P. Li, G. Liu, Z. Zhao, and S. Zhong, "Pefomed: Parameter efficient fine-tuning on multimodal large language models for medical visual question answering," arXiv preprint arXiv:2401.02797, 2024. 6, 7
- [283] O. Thawkar, A. Shaker, S. S. Mullappilly, H. Cholakkal, R. M. Anwer, S. Khan, J. Laaksonen, and F. S. Khan, "Xraygpt: Chest radiographs summarization using medical vision-language models," *arXiv preprint arXiv:2306.07971*, 2023. 6, 7
- [284] M. Ranjit, G. Ganapathy, R. Manuel, and T. Ganu, "Retrieval augmented chest x-ray report generation using openai gpt models," in *Machine Learning for Healthcare Conference*. PMLR, 2023, pp. 650– 666. 6, 7
- [285] B. Liu, L.-M. Zhan, L. Xu, L. Ma, Y. Yang, and X.-M. Wu, "Slake: A semantically-labeled knowledge-enhanced dataset for medical visual question answering," in *International Symposium on Biomedical Imaging (ISBI)*, 2021, pp. 1650–1654. 6
- [286] X. He, Y. Zhang, L. Mou, E. Xing, and P. Xie, "Pathvqa: 30000+ questions for medical visual question answering," arXiv preprint arXiv:2003.10286, 2020. 6
- [287] J. J. Lau, S. Gayen, A. Ben Abacha, and D. Demner-Fushman, "A dataset of clinically generated visual questions and answers about radiology images," *Scientific data*, vol. 5, no. 1, pp. 1–10, 2018. 6
- [288] P. Lu, S. Mishra, T. Xia, L. Qiu, K.-W. Chang, S.-C. Zhu, O. Tafjord, P. Clark, and A. Kalyan, "Learn to explain: Multimodal reasoning via thought chains for science question answering," Adv. Neural Inform. Process. Syst., vol. 35, pp. 2507–2521, 2022. 7, 15
- [289] A. Hu, Y. Shi, H. Xu, J. Ye, Q. Ye, M. Yan, C. Li, Q. Qian, J. Zhang, and F. Huang, "mplug-paperowl: Scientific diagram analysis with the multimodal large language model," in ACM MM, 2024, pp. 6929–6938. 7, 15
- [290] J. Ye, A. Hu, H. Xu, Q. Ye, M. Yan, Y. Dan, C. Zhao, G. Xu, C. Li, J. Tian *et al.*, "mplug-docowl: Modularized multimodal large language model for document understanding," *arXiv preprint arXiv:2307.02499*, 2023. 7
- [291] N. Singh, L. L. Wang, and J. Bragg, "Figura11y: Ai assistance for writing scientific alt text," in *Proceedings of the 29th International Conference on Intelligent User Interfaces*, 2024, pp. 886–906. 7
- [292] W. Shi, Z. Hu, Y. Bin, J. Liu, Y. Yang, S.-K. Ng, L. Bing, and R. K.-W. Lee, "Math-Ilava: Bootstrapping mathematical reasoning for multimodal large language models," *arXiv preprint arXiv:2406.17294*, 2024. 7, 15
- [293] X. Yue, T. Zheng, G. Zhang, and W. Chen, "Mammoth2: Scaling instructions from the web," *arXiv preprint arXiv:2405.03548*, 2024.
- [294] J. Guo, T. Zheng, Y. Bai, B. Li, Y. Wang, K. Zhu, Y. Li, G. Neubig, W. Chen, and X. Yue, "Mammoth-vl: Eliciting multimodal reasoning

with instruction tuning at scale," *arXiv preprint arXiv:2412.05237*, 2024. 7

- [295] P. Lu, H. Bansal, T. Xia, J. Liu, C. Li, H. Hajishirzi, H. Cheng, K.-W. Chang, M. Galley, and J. Gao, "Mathvista: Evaluating mathematical reasoning of foundation models in visual contexts," *arXiv preprint arXiv:2310.02255*, 2023. 7, 15
- [296] J. Zhang, Z. Li, M. Zhang, F. Yin, C. Liu, and Y. Moshfeghi, "Geoeval: benchmark for evaluating llms and multi-modal models on geometry problem-solving," arXiv preprint arXiv:2402.10104, 2024. 7, 15
- [297] Z.-Z. Li, M.-L. Zhang, F. Yin, Z.-L. Ji, J.-F. Bai, Z.-R. Pan, F.-H. Zeng, J. Xu, J.-X. Zhang, and C.-L. Liu, "Cmmath: A chinese multi-modal math skill evaluation benchmark for foundation models," *arXiv preprint arXiv:2407.12023*, 2024. 7, 15
- [298] R. Zhang, D. Jiang, Y. Zhang, H. Lin, Z. Guo, P. Qiu, A. Zhou, P. Lu, K.-W. Chang, Y. Qiao *et al.*, "Mathverse: Does your multi-modal llm truly see the diagrams in visual math problems?" in *ECCV*, 2025, pp. 169–186. 7, 15
- [299] R. Qiao, Q. Tan, G. Dong, M. Wu, C. Sun, X. Song, Z. GongQue, S. Lei, Z. Wei, M. Zhang *et al.*, "We-math: Does your large multimodal model achieve human-like mathematical reasoning?" *arXiv preprint arXiv:2407.01284*, 2024. 7, 15
- [300] G. Team, P. Georgiev, V. I. Lei, R. Burnell, L. Bai, A. Gulati, G. Tanzer, D. Vincent, Z. Pan, S. Wang *et al.*, "Gemini 1.5: Unlocking multimodal understanding across millions of tokens of context," *arXiv preprint arXiv:2403.05530*, 2024. 7
- [301] H. Liu, C. Li, Y. Li, B. Li, Y. Zhang, S. Shen, and Y. J. Lee, "Llavanext: Improved reasoning, ocr, and world knowledge," 2024. 7
- [302] J. Devlin, M.-W. Chang, K. Lee, and K. Toutanova, "Bert: Pre-training of deep bidirectional transformers for language understanding," arXiv preprint arXiv:1810.04805, 2018. 8
- [303] Y. Zhang, B. Li, h. Liu, Y. j. Lee, L. Gui, D. Fu, J. Feng, Z. Liu, and C. Li, "Llava-next: A strong zero-shot video understanding model," April 2024. [Online]. Available: https: //llava-vl.github.io/blog/2024-04-30-llava-next-video/ 8
- [304] A. Radford, J. Wu, R. Child, D. Luan, D. Amodei, I. Sutskever *et al.*, "Language models are unsupervised multitask learners," *OpenAI blog*, vol. 1, no. 8, p. 9, 2019. 8
- [305] C. Raffel, N. Shazeer, A. Roberts, K. Lee, S. Narang, M. Matena, Y. Zhou, W. Li, and P. J. Liu, "Exploring the limits of transfer learning with a unified text-to-text transformer," *Journal of machine learning research*, vol. 21, no. 140, pp. 1–67, 2020. 8
- [306] B. Li, Y. Zhang, D. Guo, R. Zhang, F. Li, H. Zhang, K. Zhang, P. Zhang, Y. Li, Z. Liu *et al.*, "Llava-onevision: Easy visual task transfer," *arXiv preprint arXiv:2408.03326*, 2024. 8
- [307] D. Li, Y. Liu, H. Wu, Y. Wang, Z. Shen, B. Qu, X. Niu, G. Wang, B. Chen, and J. Li, "Aria: An open multimodal native mixture-ofexperts model," *arXiv preprint arXiv:2410.05993*, 2024. 8
- [308] B. He, H. Li, Y. K. Jang, M. Jia, X. Cao, A. Shah, A. Shrivastava, and S.-N. Lim, "Ma-Imm: Memory-augmented large multimodal model for long-term video understanding," *arXiv preprint arXiv:2404.05726*, 2024. 8
- [309] R. OpenAI, "Gpt-4 technical report. arxiv 2303.08774," View in Article, vol. 2, p. 13, 2023. 8
- [310] OpenAI, "Gpt-4v(ision) system card," 2023. 8
- [311] K. Q. Lin, J. Wang, M. Soldan, M. Wray, R. Yan, E. Z. Xu, D. Gao, R.-C. Tu, W. Zhao, W. Kong *et al.*, "Egocentric video-language pretraining," *Adv. Neural Inform. Process. Syst.*, vol. 35, pp. 7575– 7586, 2022. 8
- [312] S. Pramanick, Y. Song, S. Nag, K. Q. Lin, H. Shah, M. Z. Shou, R. Chellappa, and P. Zhang, "Egovlpv2: Egocentric video-language pre-training with fusion in the backbone," in *ICCV*, 2023, pp. 5285– 5297. 8
- [313] B. Pei, G. Chen, J. Xu, Y. He, Y. Liu, K. Pan, Y. Huang, Y. Wang, T. Lu, L. Wang *et al.*, "Egovideo: Exploring egocentric foundation model and downstream adaptation," *arXiv preprint arXiv:2406.18070*, 2024. 8
- [314] D. Chatterjee, F. Sener, S. Ma, and A. Yao, "Opening the vocabulary of egocentric actions," Adv. Neural Inform. Process. Syst., vol. 36, 2024. 8
- [315] Y. Shen, H. Wang, X. Yang, M. Feiszli, E. Elhamifar, L. Torresani, and E. Mavroudi, "Learning to segment referred objects from narrated egocentric videos," in CVPR, June 2024, pp. 14510–14520. 8
- [316] B. Xu, Z. Wang, Y. Du, S. Zheng, Z. Song, and Q. Jin, "Egonce++: Do egocentric video-language models really understand hand-object interactions?" arXiv preprint arXiv:2405.17719, 2024. 8

- [317] H. Xue, Y. Sun, B. Liu, J. Fu, R. Song, H. Li, and J. Luo, "Clip-vip: Adapting pre-trained image-text model to video-language representation alignment," arXiv preprint arXiv:2209.06430, 2022. 8
- [318] Y. Zhao, I. Misra, P. Krähenbühl, and R. Girdhar, "Learning video representations from large language models," in *CVPR*, June 2023, pp. 6586–6597. 9
- [319] J. Xie, Z. Chen, R. Zhang, X. Wan, and G. Li, "Large multimodal agents: A survey," arXiv preprint arXiv:2402.15116, 2024. 9
- [320] Z. Yang, X. Jia, H. Li, and J. Yan, "Llm4drive: A survey of large language models for autonomous driving," arXiv e-prints, pp. arXiv-2311, 2023. 9
- [321] C. Cui, Y. Ma, X. Cao, W. Ye, Y. Zhou, K. Liang, J. Chen, J. Lu, Z. Yang, K.-D. Liao *et al.*, "A survey on multimodal large language models for autonomous driving," in *Wint. Appl. Comput. Vis.*, 2024, pp. 958–979. 9
- [322] S.-M. Park and Y.-G. Kim, "Visual language navigation: A survey and open challenges," *Artificial Intelligence Review*, vol. 56, no. 1, pp. 365– 427, 2023. 9
- [323] M. Bojarski, D. Del Testa, D. Dworakowski, B. Firner, B. Flepp, P. Goyal, L. D. Jackel, M. Monfort, U. Muller, J. Zhang *et al.*, "End to end learning for self-driving cars," *arXiv preprint arXiv:1604.07316*, 2016. 9
- [324] A. Awadalla, I. Gao, J. Gardner, J. Hessel, Y. Hanafy, W. Zhu, K. Marathe, Y. Bitton, S. Gadre, S. Sagawa *et al.*, "Openflamingo: An open-source framework for training large autoregressive visionlanguage models," *arXiv preprint arXiv:2308.01390*, 2023. 9
- [325] J. Kim, A. Rohrbach, T. Darrell, J. Canny, and Z. Akata, "Textual explanations for self-driving vehicles," in ECCV, 2018, pp. 563–578. 10
- [326] Y. Ma, Z. Song, Y. Zhuang, J. Hao, and I. King, "A survey on vision-language-action models for embodied ai," *arXiv preprint* arXiv:2405.14093, 2024. 10
- [327] R. Firoozi, J. Tucker, S. Tian, A. Majumdar, J. Sun, W. Liu, Y. Zhu, S. Song, A. Kapoor, K. Hausman *et al.*, "Foundation models in robotics: Applications, challenges, and the future," *arXiv preprint arXiv:2312.07843*, 2023. 10
- [328] Y. Hu, Q. Xie, V. Jain, J. Francis, J. Patrikar, N. Keetha, S. Kim, Y. Xie, T. Zhang, Z. Zhao *et al.*, "Toward general-purpose robots via foundation models: A survey and meta-analysis," *arXiv preprint arXiv:2312.08782*, 2023. 10
- [329] K. Kawaharazuka, T. Matsushima, A. Gambardella, J. Guo, C. Paxton, and A. Zeng, "Real-world robot applications of foundation models: A review," arXiv preprint arXiv:2402.05741, 2024. 10
- [330] D. Li, Y. Jin, H. Yu, J. Shi, X. Hao, P. Hao, H. Liu, F. Sun, B. Fang et al., "What foundation models can bring for robot learning in manipulation: A survey," arXiv preprint arXiv:2404.18201, 2024. 10
- [331] A. Chowdhery, S. Narang, J. Devlin, M. Bosma, G. Mishra, A. Roberts, P. Barham, H. W. Chung, C. Sutton, S. Gehrmann *et al.*, "Palm: Scaling language modeling with pathways," *Journal of Machine Learning Research*, vol. 24, no. 240, pp. 1–113, 2023. 10
- [332] M. Deitke *et al.*, "Pixavoxels: Integrating pixels, language, and voxel-based models for multimodal navigation," *arXiv preprint arXiv:2302.02172*, 2023. 11
- [333] D. Shah, B. Eysenbach, G. Kahn, N. Rhinehart, and S. Levine, "Ving: Learning open-world navigation with visual goals," in *ICRA*, 2021, pp. 13215–13222. 11
- [334] C. Qu, S. Dai, X. Wei, H. Cai, S. Wang, D. Yin, J. Xu, and J.-R. Wen, "Tool learning with large language models: A survey," arXiv preprint arXiv:2405.17935, 2024. 11
- [335] J. Y. Koh, R. Lo, L. Jang, V. Duvvur, M. C. Lim, P.-Y. Huang, G. Neubig, S. Zhou, R. Salakhutdinov, and D. Fried, "Visualwebarena: Evaluating multimodal agents on realistic visual web tasks," in *ICLR* Workshop on Large Language Model (*LLM*) Agents, 2024. 11, 12
- [336] Y. Wang, Y. Kordi, S. Mishra, A. Liu, N. A. Smith, D. Khashabi, and H. Hajishirzi, "Self-instruct: Aligning language models with selfgenerated instructions," arXiv preprint arXiv:2212.10560, 2022. 12
- [337] J. Huang, S. S. Gu, L. Hou, Y. Wu, X. Wang, H. Yu, and J. Han, "Large language models can self-improve," arXiv preprint arXiv:2210.11610, 2022. 12
- [338] T. Ferdinan, J. Kocoń, and P. Kazienko, "Into the unknown: Selflearning large language models," arXiv preprint arXiv:2402.09147, 2024. 12
- [339] R. Bonatti, D. Zhao, F. Bonacci, D. Dupont, S. Abdali, Y. Li, Y. Lu, J. Wagle, K. Koishida, A. Bucker *et al.*, "Windows agent arena: Evaluating multi-modal os agents at scale," *arXiv preprint arXiv:2409.08264*, 2024. 12

- [340] T. Xie, D. Zhang, J. Chen, X. Li, S. Zhao, R. Cao, T. J. Hua, Z. Cheng, D. Shin, F. Lei *et al.*, "Osworld: Benchmarking multimodal agents for open-ended tasks in real computer environments," *arXiv preprint arXiv:2404.07972*, 2024. 12
- [341] S. Yao, N. Shinn, P. Razavi, and K. Narasimhan, "tau-bench: A benchmark for tool-agent-user interaction in real-world domains," *arXiv* preprint arXiv:2406.12045, 2024. 12
- [342] T. Q. Luong, X. Zhang, Z. Jie, P. Sun, X. Jin, and H. Li, "Reft: Reasoning with reinforced fine-tuning," arXiv preprint arXiv:2401.08967, 2024. 12, 17
- [343] D. Bouneffouf and R. Féraud, "A tutorial on multi-armed bandit applications for large language models," in *Proceedings of the 30th* ACM SIGKDD Conference on Knowledge Discovery and Data Mining, 2024, pp. 6412–6413. 12
- [344] H. He, W. Yao, K. Ma, W. Yu, H. Zhang, T. Fang, Z. Lan, and D. Yu, "Openwebvoyager: Building multimodal web agents via iterative real-world exploration, feedback and optimization," 2024. [Online]. Available: https://arxiv.org/abs/2410.19609 12
- [345] G. H. Sarch, L. Jang, M. J. Tarr, W. W. Cohen, K. Marino, and K. Fragkiadaki, "Vlm agents generate their own memories: Distilling experience into embodied programs of thought," in *Adv. Neural Inform. Process. Syst.*, 2024. 12
- [346] T. Brooks, A. Holynski, and A. A. Efros, "Instructpix2pix: Learning to follow image editing instructions," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2023, pp. 18 392–18 402. 12
- [347] L. Lian, B. Shi, A. Yala, T. Darrell, and B. Li, "Llm-grounded video diffusion models," in *The Twelfth International Conference on Learning Representations*, 2023. 13
- [348] V. Ordonez, G. Kulkarni, and T. Berg, "Im2text: Describing images using 1 million captioned photographs," in Adv. Neural Inform. Process. Syst., vol. 24, 2011. 15
- [349] P. Young, A. Lai, M. Hodosh, and J. Hockenmaier, "From image descriptions to visual denotations: New similarity metrics for semantic inference over event descriptions," in ACL, vol. 2, 2014, pp. 67–78. 15
- [350] C. Schuhmann, R. Beaumont, R. Vencu, C. Gordon, R. Wightman, M. Cherti, T. Coombes, A. Katta, C. Mullis, M. Wortsman *et al.*, "Laion-5b: An open large-scale dataset for training next generation image-text models," in *Adv. Neural Inform. Process. Syst.*, vol. 35, 2022, pp. 25 278–25 294. 15
- [351] M. Byeon, B. Park, H. Kim, S. Lee, W. Baek, and S. Kim, "Coyo-700m: Image-text pair dataset," https://github.com/kakaobrain/coyo-dataset, 2022. 15
- [352] W. Zhu, J. Hessel, A. Awadalla, S. Y. Gadre, J. Dodge, A. Fang, Y. Yu, L. Schmidt, W. Y. Wang, and Y. Choi, "Multimodal c4: An open, billion-scale corpus of images interleaved with text," in *Adv. Neural Inform. Process. Syst.*, vol. 36, 2024. 15
- [353] H. Laurençon, L. Saulnier, L. Tronchon, S. Bekman, A. Singh, A. Lozhkov, T. Wang, S. Karamcheti, A. Rush, D. Kiela *et al.*, "Obelics: An open web-scale filtered dataset of interleaved image-text documents," in *Adv. Neural Inform. Process. Syst.*, vol. 36, 2024. 15
- [354] S. Y. Gadre, G. Ilharco, A. Fang, J. Hayase, G. Smyrnis, T. Nguyen, R. Marten, M. Wortsman, D. Ghosh, J. Zhang *et al.*, "Datacomp: In search of the next generation of multimodal datasets," in *Adv. Neural Inform. Process. Syst.*, vol. 36, 2024. 15
- [355] A. Singh, G. Pang, M. Toh, J. Huang, W. Galuba, and T. Hassner, "Textocr: Towards large-scale end-to-end reasoning for arbitrary-shaped scene text," in CVPR, 2021, pp. 8802–8812. 15
- [356] S. Long, S. Qin, D. Panteleev, A. Bissacco, Y. Fujii, and M. Raptis, "Towards end-to-end unified scene text detection and layout analysis," in *CVPR*, 2022, pp. 1049–1059. 15
- [357] A. Singh, V. Natarajan, M. Shah, Y. Jiang, X. Chen, D. Batra, D. Parikh, and M. Rohrbach, "Towards vqa models that can read," in *CVPR*, 2019, pp. 8317–8326. 15
- [358] T.-H. Huang, F. Ferraro, N. Mostafazadeh, I. Misra, A. Agrawal, J. Devlin, R. Girshick, X. He, P. Kohli, D. Batra et al., "Visual storytelling," in Proceedings of the 2016 conference of the North American chapter of the association for computational linguistics: Human language technologies, 2016, pp. 1233–1239. 15
- [359] A. Das, S. Kottur, K. Gupta, A. Singh, D. Yadav, J. M. F. Moura, D. Parikh, and D. Batra, "Visual dialog," in *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, July 2017. 15
- [360] D. Gurari, Q. Li, A. J. Stangl, A. Guo, C. Lin, K. Grauman, J. Luo, and J. P. Bigham, "Vizwiz grand challenge: Answering visual questions from blind people," in *Proceedings of the IEEE conference on computer* vision and pattern recognition, 2018, pp. 3608–3617. 15

- [361] D. Schwenk, A. Khandelwal, C. Clark, K. Marino, and R. Mottaghi, "A-okvqa: A benchmark for visual question answering using world knowledge," in *European conference on computer vision*. Springer, 2022, pp. 146–162. 15
- [362] J. Xu, T. Mei, T. Yao, and Y. Rui, "Msr-vtt: A large video description dataset for bridging video and language," in *Proceedings of the IEEE* conference on computer vision and pattern recognition, 2016, pp. 5288–5296. 15
- [363] M. Bain, A. Nagrani, G. Varol, and A. Zisserman, "Frozen in time: A joint video and image encoder for end-to-end retrieval," in *Proceedings* of the IEEE/CVF international conference on computer vision, 2021, pp. 1728–1738. 15
- [364] W. Wang, H. Yang, Z. Tuo, H. He, J. Zhu, J. Fu, and J. Liu, "Videofactory: Swap attention in spatiotemporal diffusions for textto-video generation," arXiv preprint arXiv:2305.10874, 2023. 15
- [365] R. Krishna, K. Hata, F. Ren, L. Fei-Fei, and J. Carlos Niebles, "Densecaptioning events in videos," in *Proceedings of the IEEE International Conference on Computer Vision (ICCV)*, Oct 2017. 15
- [366] H. Xue, T. Hang, Y. Zeng, Y. Sun, B. Liu, H. Yang, J. Fu, and B. Guo, "Advancing high-resolution video-language representation with large-scale video transcriptions," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2022, pp. 5036–5045. 15
- [367] Y. Wang, Y. He, Y. Li, K. Li, J. Yu, X. Ma, X. Li, G. Chen, X. Chen, Y. Wang *et al.*, "Internvid: A large-scale video-text dataset for multimodal understanding and generation," *arXiv preprint arXiv:2307.06942*, 2023. 15
- [368] A. Miech, D. Zhukov, J.-B. Alayrac, M. Tapaswi, I. Laptev, and J. Sivic, "Howto100m: Learning a text-video embedding by watching hundred million narrated video clips," in *Proceedings of the IEEE/CVF international conference on computer vision*, 2019, pp. 2630–2640. 15
- [369] A. Rohrbach, A. Torabi, M. Rohrbach, N. Tandon, C. Pal, H. Larochelle, A. Courville, and B. Schiele, "Movie description," *International Journal of Computer Vision*, vol. 123, pp. 94–120, 2017. 15
- [370] X. Wang, J. Wu, J. Chen, L. Li, Y.-F. Wang, and W. Y. Wang, "Vatex: A large-scale, high-quality multilingual dataset for video-and-language research," in *Proceedings of the IEEE/CVF international conference* on computer vision, 2019, pp. 4581–4591. 15
- [371] T. Deruyttere, S. Vandenhende, D. Grujicic, L. Van Gool, and M. F. Moens, "Talk2car: Taking control of your self-driving car," in *EMNLP*, 2019, pp. 2088–2098. 15
- [372] J. Kim, T. Misu, Y.-T. Chen, A. Tawari, and J. Canny, "Grounding human-to-vehicle advice for self-driving vehicles," in *CVPR*, 2019, pp. 10591–10599. 15
- [373] A. X. Chang, T. Funkhouser, L. Guibas, P. Hanrahan, Q. Huang, Z. Li, S. Savarese, M. Savva, S. Song, H. Su *et al.*, "Shapenet: An information-rich 3d model repository," *arXiv preprint arXiv:1512.03012*, 2015. 15
- [374] K. Chen, C. B. Choy, M. Savva, A. X. Chang, T. Funkhouser, and S. Savarese, "Text2shape: Generating shapes from natural language by learning joint embeddings," in *Computer Vision–ACCV 2018: 14th Asian Conference on Computer Vision, Perth, Australia, December 2– 6, 2018, Revised Selected Papers, Part III 14.* Springer, 2019, pp. 100–116. 15
- [375] M. Deitke, D. Schwenk, J. Salvador, L. Weihs, O. Michel, E. Vander-Bilt, L. Schmidt, K. Ehsani, A. Kembhavi, and A. Farhadi, "Objaverse: A universe of annotated 3d objects," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2023, pp. 13 142–13 153. 15
- [376] G. Ruggeri and D. Nozza, "A multi-dimensional study on bias in vision-language models," in *Findings of the Association for Computational Linguistics: ACL 2023*, A. Rogers, J. Boyd-Graber, and N. Okazaki, Eds. Toronto, Canada: Association for Computational Linguistics, Jul. 2023, pp. 6445–6455. [Online]. Available: https: //aclanthology.org/2023.findings-acl.403 14
- [377] N. Lee, Y. Bang, H. Lovenia, S. Cahyawijaya, W. Dai, and P. Fung, "Survey of social bias in vision-language models," *arXiv preprint* arXiv:2309.14381, 2023. 14
- [378] K. C. Fraser and S. Kiritchenko, "Examining gender and racial bias in large vision-language models using a novel dataset of parallel images," *arXiv preprint arXiv:2402.05779*, 2024. 14
- [379] J. Zhao, Y. Ding, C. Jia, Y. Wang, and Z. Qian, "Gender bias in large language models across multiple languages," *arXiv preprint* arXiv:2403.00277, 2024. 14

- [380] L. Aggarwal and S. Bhargava, "Fairness in ai systems: Mitigating gender bias from language-vision models," arXiv preprint arXiv:2305.01888, 2023. 14
- [381] M. Nauta, J. Trienes, S. Pathak, E. Nguyen, M. Peters, Y. Schmitt, J. Schlötterer, M. Van Keulen, and C. Seifert, "From anecdotal evidence to quantitative evaluation methods: A systematic review on evaluating explainable ai," ACM Computing Surveys, vol. 55, no. 13s, pp. 1–42, 2023. 14
- [382] Z. C. Lipton, "The mythos of model interpretability: In machine learning, the concept of interpretability is both important and slippery." *Queue*, vol. 16, no. 3, pp. 31–57, 2018. 14
- [383] A. Rohrbach, L. A. Hendricks, K. Burns, T. Darrell, and K. Saenko, "Object hallucination in image captioning," arXiv preprint arXiv:1809.02156, 2018. 15
- [384] W. Huang, H. Liu, M. Guo, and N. Z. Gong, "Visual hallucinations of multi-modal large language models," arXiv preprint arXiv:2402.14683, 2024. 15, 16
- [385] Z. Xu, S. Jain, and M. Kankanhalli, "Hallucination is inevitable: An innate limitation of large language models," arXiv preprint arXiv:2401.11817, 2024. 15
- [386] Z. Tan, J. Peng, T. Chen, and H. Liu, "Tuning-free accountable intervention for llm deployment–a metacognitive approach," arXiv preprint arXiv:2403.05636, 2024. 16
- [387] J. Yang, S. Yang, A. W. Gupta, R. Han, L. Fei-Fei, and S. Xie, "Thinking in space: How multimodal large language models see, remember, and recall spaces," *arXiv preprint arXiv:2412.14171*, 2024. 16
- [388] H. Tu, C. Cui, Z. Wang, Y. Zhou, B. Zhao, J. Han, W. Zhou, H. Yao, and C. Xie, "How many unicorns are in this image? a safety evaluation benchmark for vision llms," *arXiv preprint arXiv:2311.16101*, 2023. 16
- [389] Z. Liu, H. Liang, W. Xiong, Q. Yu, C. He, B. Cui, and W. Zhang, "Synthvlm: High-efficiency and high-quality synthetic data for vision language models," *arXiv preprint arXiv:2407.20756*, 2024. 16
- [390] L. Sweeney, "k-anonymity: A model for protecting privacy," *International journal of uncertainty, fuzziness and knowledge-based systems*, vol. 10, no. 05, pp. 557–570, 2002. 16
- [391] B. Meden, Ž. Emeršič, V. Štruc, and P. Peer, "k-same-net: k-anonymity with generative deep neural networks for face deidentification," *Entropy*, vol. 20, no. 1, p. 60, 2018. 16
- [392] B. B. Gupta, A. Gaurav, V. Arya, W. Alhalabi, D. Alsalman, and P. Vijayakumar, "Enhancing user prompt confidentiality in large language models through advanced differential encryption," *Computers* and Electrical Engineering, vol. 116, p. 109215, 2024. 16
- [393] S. Li, R. Zhao, Q. Guan, J. Chen, and Y. Zhang, "A 3d model encryption method supporting adaptive visual effects after decryption," *Advanced Engineering Informatics*, vol. 59, p. 102319, 2024. 16
- [394] E. Bagdasaryan, T.-Y. Hsieh, B. Nassi, and V. Shmatikov, "(ab) using images and sounds for indirect instruction injection in multi-modal llms," arXiv preprint arXiv:2307.10490, 2023. 16
- [395] Z. Tan, C. Zhao, R. Moraffah, Y. Li, Y. Kong, T. Chen, and H. Liu, "The wolf within: Covert injection of malice into mllm societies via an mllm operative," *arXiv preprint arXiv:2402.14859*, 2024. 16
- [396] K. Gao, Y. Bai, J. Bai, Y. Yang, and S.-T. Xia, "Adversarial robustness for visual grounding of multimodal large language models," *arXiv* preprint arXiv:2405.09981, 2024. 16
- [397] C. Schlarmann and M. Hein, "On the adversarial robustness of multimodal foundation models," in *ICCV*, 2023, pp. 3677–3685. 16
- [398] S. Fares, K. Ziu, T. Aremu, N. Durasov, M. Takáč, P. Fua, K. Nandakumar, and I. Laptev, "Mirrorcheck: Efficient adversarial defense for vision-language models," *arXiv preprint arXiv:2406.09250*, 2024. 16
- [399] J. Li, K. Gao, Y. Bai, J. Zhang, and S.-T. Xia, "Video watermarking: Safeguarding your video from (unauthorized) annotations by videobased llms," arXiv preprint arXiv:2407.02411, 2024. 16
- [400] H. Khan, P. M. Shah, S. F. A. Zaidi, Q. Zia et al., "Susceptibility of continual learning against adversarial attacks," arXiv preprint arXiv:2207.05225, 2022. 16
- [401] T. Nguyen, A. Tran, and N. Ho, "Backdoor attack in prompt-based continual learning," 2024. 16
- [402] J. Chen, D. Zhu, X. Shen, X. Li, Z. Liu, P. Zhang, R. Krishnamoorthi, V. Chandra, Y. Xiong, and M. Elhoseiny, "Minigpt-v2: large language model as a unified interface for vision-language multi-task learning," *arXiv preprint arXiv:2310.09478*, 2023. 16
- [403] X. Liu *et al.*, "Fastv: Dynamic visual token pruning for efficient visual language models," *ECCV*, 2024. 16, 17
- [404] J. Chen, L. Ye, J. He, Z.-Y. Wang, D. Khashabi, and A. Yuille, "Efficient large multi-modal models via visual context compression," in Adv. Neural Inform. Process. Syst., 2024. 16

- [405] B. Zhao, K. R. Mopuri, and H. Bilen, "Dataset condensation with gradient matching," in *ICLR*, 2021. 16
- [406] J.-H. Kim, J. Kim, S. J. Oh, S. Yun, H. Song, J. Jeong, J.-W. Ha, and H. O. Song, "Dataset condensation via efficient synthetic-data parameterization," in *ICML*, 2022, pp. 11102–11118. 16
- [407] Y. Liu, J. Gu, K. Wang, Z. Zhu, W. Jiang, and Y. You, "Dream: Efficient dataset distillation by representative matching," in *ICCV*, 2023, pp. 17314–17324. 16
- [408] Y. Zhang, D. Zhou, B. Hooi, K. Wang, and J. Feng, "Expanding small-scale datasets with guided imagination," in Adv. Neural Inform. Process. Syst., vol. 36, 2023, pp. 76558–76618. 16
- [409] D. Zhou, K. Wang, J. Gu, X. Peng, D. Lian, Y. Zhang, Y. You, and J. Feng, "Dataset quantization," in *ICCV*, 2023, pp. 17205–17216. 16
- [410] J. Gu, S. Vahidian, V. Kungurtsev, H. Wang, W. Jiang, Y. You, and Y. Chen, "Efficient dataset distillation via minimax diffusion," in *CVPR*, 2024, pp. 15793–15803. 16
- [411] X. Zhong, S. Sun, X. Gu, Z. Xu, Y. Wang, J. Wu, and B. Chen, "Efficient dataset distillation via diffusion-driven patch selection for improved generalization," arXiv preprint arXiv:2412.09959, 2024. 16
- [412] D. Su, J. Hou, G. Li, R. Togo, R. Song, T. Ogawa, and M. Haseyama, "Generative dataset distillation based on diffusion model," *arXiv* preprint arXiv:2408.08610, 2024. 16
- [413] Z. Tan, D. Li, S. Wang, A. Beigi, B. Jiang, A. Bhattacharjee, M. Karami, J. Li, L. Cheng, and H. Liu, "Large language models for data annotation and synthesis: A survey," in *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, 2024, pp. 930–957. 16
- [414] E. J. Hu et al., "Lora: Low-rank adaptation of large language models," arXiv preprint arXiv:2106.09685, 2021. 17
- [415] R. He et al., "Relora: Periodic low-rank adaptation of pretrained models for efficient fine-tuning," arXiv preprint arXiv:2206.11702, 2022. 17
- [416] W. Zhang *et al.*, "Llavaprumerge: Efficient token reduction for visual language models in visual question answering," *arXiv preprint arXiv:2401.03456*, 2024. 17
- [417] L. M. Zintgraf, T. S. Cohen, T. Adel, and M. Welling, "Visualizing deep neural network decisions: Prediction difference analysis," in *ICLR*, 2017. 17
- [418] D. H. Park, L. A. Hendricks, Z. Akata, A. Rohrbach, B. Schiele, T. Darrell, and M. Rohrbach, "Multimodal explanations: Justifying decisions and pointing to the evidence," in *CVPR*, 2018, pp. 8779– 8788. 17
- [419] H. Morioka and A. Hyvarinen, "Connectivity-contrastive learning: Combining causal discovery and representation learning for multimodal data," in *International conference on artificial intelligence and statistics.* PMLR, 2023, pp. 3399–3426. 17
- [420] E. Walker, J. A. Actor, C. Martinez, and N. Trask, "Causal disentanglement of multimodal data," *arXiv preprint arXiv:2310.18471*, 2023. 17
- [421] R. Tang, L. Liu, A. Pandey, Z. Jiang, G. Yang, K. Kumar, P. Stenetorp, J. Lin, and F. Ture, "What the daam: Interpreting stable diffusion using cross attention," arXiv preprint arXiv:2210.04885, 2022. 17
- [422] P. P. Liang, Y. Lyu, X. Fan, J. Tsaw, Y. Liu, S. Mo, D. Yogatama, L.-P. Morency, and R. Salakhutdinov, "High-modality multimodal transformer: Quantifying modality & interaction heterogeneity for highmodality representation learning," *arXiv preprint arXiv:2203.01311*, 2022. 17
- [423] X. Kong, O. Liu, H. Li, D. Yogatama, and G. Ver Steeg, "Interpretable diffusion via information decomposition," in *ICLR*, 2024. 17
- [424] C. Neo, L. Ong, P. Torr, M. Geva, D. Krueger, and F. Barez, "Towards interpreting visual information processing in vision-language models," arXiv preprint arXiv:2410.07149, 2024. 17
- [425] X. Zhang, C. Shen, X. Yuan, S. Yan, L. Xie, W. Wang, C. Gu, H. Tang, and J. Ye, "From redundancy to relevance: Enhancing explainability in multimodal large language models," *arXiv preprint arXiv:2406.06579*, 2024. 17
- [426] Y. Gandelsman, A. A. Efros, and J. Steinhardt, "Interpreting clip's image representation via text-based decomposition," in *ICLR*, 2024. 17
- [427] Q. Zhao, M. Xu, K. Gupta, A. Asthana, L. Zheng, and S. Gould, "The first to know: How token distributions reveal hidden knowledge in large vision-language models?" in *ECCV*, 2024, pp. 127–142. 17
- [428] Y. Li, Y. Wang, Y. Fu, D. Ru, Z. Zhang, and T. He, "Unified lexical representation for interpretable visual-language alignment," *arXiv* preprint arXiv:2407.17827, 2024. 17
- [429] J. Wei and X. Zhang, "Dopra: Decoding over-accumulation penalization and re-allocation in specific weighting layer," in ACM MM, 2024, pp. 7065–7074. 17

- [430] R. Chen, S. Liang, J. Li, S. Liu, M. Li, Z. Huang, H. Zhang, and X. Cao, "Interpreting object-level foundation models via visual precision search," arXiv preprint arXiv:2411.16198, 2024. 17
- [431] G. Verma, M. Choi, K. Sharma, J. Watson-Daniels, S. Oh, and S. Kumar, "Cross-modal projection in multimodal llms doesn't really project visual attributes to textual space," in ACL, 2024, pp. 657–664. 17
- [432] M. Shi, F. Liu, S. Wang, S. Liao, S. Radhakrishnan, D.-A. Huang, H. Yin, K. Sapra, Y. Yacoob, H. Shi *et al.*, "Eagle: Exploring the design space for multimodal llms with mixture of encoders," *arXiv* preprint arXiv:2408.15998, 2024. 17
- [433] G. Dominici, P. Barbiero, L. C. Magister, P. Liò, and N. Simidjievski, "Shares: Shared concept space for explainable multimodal learning," arXiv preprint arXiv:2307.00316, 2023. 17
- [434] Z. Wang, Z. Zhang, X. Cheng, R. Huang, L. Liu, Z. Ye, H. Huang, Y. Zhao, T. Jin, P. Gao *et al.*, "Freebind: Free lunch in unified multimodal space via knowledge fusion," in *ICML*, 2024. 17
- [435] J. Parekh, P. Khayatan, M. Shukor, A. Newson, and M. Cord, "A concept-based explainability framework for large multimodal models," *arXiv preprint arXiv:2406.08074*, 2024. 17
- [436] A. Dravid, Y. Gandelsman, A. A. Efros, and A. Shocher, "Rosetta neurons: Mining the common units in a model zoo," in *ICCV*, 2023, pp. 1934–1943. 17
- [437] Z. Liu, R. Feng, K. Zhu, Y. Zhang, K. Zheng, Y. Liu, D. Zhao, J. Zhou, and Y. Cao, "Cones: concept neurons in diffusion models for customized generation," in *ICML*, 2023, pp. 21 548–21 566. 17
- [438] S. Schwettmann, N. Chowdhury, S. Klein, D. Bau, and A. Torralba, "Multimodal neurons in pretrained text-only transformers," in *ICCV*, 2023, pp. 2862–2867. 17
- [439] T. Kojima, I. Okimura, Y. Iwasawa, H. Yanaka, and Y. Matsuo, "On the multilingual ability of decoder-based pre-trained language models: Finding and controlling language-specific neurons," *arXiv preprint arXiv:2404.02431*, 2024. 17
- [440] M. Geva, R. Schuster, J. Berant, and O. Levy, "Transformer feedforward layers are key-value memories," in *EMNLP*, 2021. 17
- [441] P. Michel, O. Levy, and G. Neubig, "Are sixteen heads really better than one?" in Adv. Neural Inform. Process. Syst., vol. 32, 2019. 17
- [442] E. Voita, D. Talbot, F. Moiseev, R. Sennrich, and I. Titov, "Analyzing multi-head self-attention: Specialized heads do the heavy lifting, the rest can be pruned," in ACL, 2019, pp. 5797–5808. 17
- [443] M. Kowal, R. P. Wildes, and K. G. Derpanis, "Visual concept connectome (vcc): Open world concept discovery and their interlayer connections in deep models," in *CVPR*, 2024, pp. 10895–10905. 17
- [444] V. Palit, R. Pandey, A. Arora, and P. P. Liang, "Towards vision-language mechanistic interpretability: A causal tracing tool for blip," in *ICCV*, 2023, pp. 2856–2861. 17
- [445] E. Salin, B. Farah, S. Ayache, and B. Favre, "Are vision-language transformers learning multimodal representations? a probing perspective," in AAAI, vol. 36, no. 10, 2022, pp. 11248–11257. 17
- [446] C. Zhou, P. Liu, P. Xu, S. Iyer, J. Sun, Y. Mao, X. Ma, A. Efrat, P. Yu, L. Yu et al., "Lima: Less is more for alignment," in Adv. Neural Inform. Process. Syst., vol. 36, 2024. 17
- [447] Z. Sun, S. Shen, S. Cao, H. Liu, C. Li, Y. Shen, C. Gan, L.-Y. Gui, Y.-X. Wang, Y. Yang *et al.*, "Aligning large multimodal models with factually augmented rlhf," *arXiv preprint arXiv:2309.14525*, 2023. 17
- [448] S. Yan, M. Bai, W. Chen, X. Zhou, Q. Huang, and L. E. Li, "Vigor: Improving visual grounding of large vision language models with finegrained reward modeling," in ECCV, 2024, pp. 37–53. 17
- [449] T. Yu, Y. Yao, H. Zhang, T. He, Y. Han, G. Cui, J. Hu, Z. Liu, H.-T. Zheng, M. Sun *et al.*, "Rlhf-v: Towards trustworthy mllms via behavior alignment from fine-grained correctional human feedback," in *CVPR*, 2024, pp. 13 807–13 816. 17
- [450] R. Mallick, J. Benois-Pineau, and A. Zemmari, "Ifi: Interpreting for improving: A multimodal transformer with an interpretability technique for recognition of risk events," in *International Conference on Multimedia Modeling*, 2024, pp. 117–131. 17
- [451] D. Smilkov, N. Thorat, B. Kim, F. Viégas, and M. Wattenberg, "Smoothgrad: removing noise by adding noise," arXiv preprint arXiv:1706.03825, 2017. 17
- [452] W. Dai, Z. Liu, Z. Ji, D. Su, and P. Fung, "Plausible may not be faithful: Probing object hallucination in vision-language pre-training," *arXiv preprint arXiv:2210.07688*, 2022. 17
- [453] Q. Huang, X. Dong, P. Zhang, B. Wang, C. He, J. Wang, D. Lin, W. Zhang, and N. Yu, "Opera: Alleviating hallucination in multimodal large language models via over-trust penalty and retrospectionallocation," in CVPR, 2024, pp. 13418–13427. 17

- [454] Z. Zhang, A. Zhang, M. Li, H. Zhao, G. Karypis, and A. Smola, "Multimodal chain-of-thought reasoning in language models," *arXiv* preprint arXiv:2302.00923, 2023. 17
- [455] J. Ge, H. Luo, S. Qian, Y. Gan, J. Fu, and S. Zhang, "Chain of thought prompt tuning in vision language models," *arXiv preprint* arXiv:2304.07919, 2023. 17
- [456] H. Shao, S. Qian, H. Xiao, G. Song, Z. Zong, L. Wang, Y. Liu, and H. Li, "Visual cot: Unleashing chain-of-thought reasoning in multimodal language models," *arXiv preprint arXiv:2403.16999*, 2024. 17
- [457] D. Mondal, S. Modi, S. Panda, R. Singh, and G. S. Rao, "Kamcot: Knowledge augmented multimodal chain-of-thoughts reasoning," in AAAI, vol. 38, no. 17, 2024, pp. 18798–18806. 17
- [458] H. Bansal, K. Gopalakrishnan, S. Dingliwal, S. Bodapati, K. Kirchhoff, and D. Roth, "Rethinking the role of scale for in-context learning: An interpretability-based case study at 66 billion scale," in ACL, 2023, pp. 11 833–11 856. 17
- [459] Y. Miyanishi and M. L. Nguyen, "Multimodal contrastive in-context learning," arXiv preprint arXiv:2408.12959, 2024. 17
- [460] J. Wei, X. Wang, D. Schuurmans, M. Bosma, F. Xia, E. Chi, Q. V. Le, D. Zhou *et al.*, "Chain-of-thought prompting elicits reasoning in large language models," in *Adv. Neural Inform. Process. Syst.*, vol. 35, 2022, pp. 24 824–24 837. 17
- [461] S. Yao, D. Yu, J. Zhao, I. Shafran, T. Griffiths, Y. Cao, and K. Narasimhan, "Tree of thoughts: Deliberate problem solving with large language models," in *Adv. Neural Inform. Process. Syst.*, vol. 36, 2024. 17
- [462] Y. Wu, Y. Wang, S. Tang, W. Wu, T. He, W. Ouyang, P. Torr, and J. Wu, "Dettoolchain: A new prompting paradigm to unleash detection ability of mllm," in *ECCV*, 2024, pp. 164–182. 17
- [463] Y. Xie, A. Goyal, W. Zheng, M.-Y. Kan, T. P. Lillicrap, K. Kawaguchi, and M. Shieh, "Monte carlo tree search boosts reasoning via iterative preference learning," arXiv preprint arXiv:2405.00451, 2024. 17
- [464] G. Xu, P. Jin, L. Hao, Y. Song, L. Sun, and L. Yuan, "Llavao1: Let vision language models reason step-by-step," arXiv preprint arXiv:2411.10440, 2024. 17
- [465] T. Zhong, Z. Liu, Y. Pan, Y. Zhang, Y. Zhou, S. Liang, Z. Wu, Y. Lyu, P. Shu, X. Yu *et al.*, "Evaluation of openai o1: Opportunities and challenges of agi," *arXiv preprint arXiv:2409.18486*, 2024. 17
- [466] D. Li, B. Jiang, L. Huang, A. Beigi, C. Zhao, Z. Tan, A. Bhattacharjee, Y. Jiang, C. Chen, T. Wu *et al.*, "From generation to judgment: Opportunities and challenges of llm-as-a-judge," *arXiv preprint arXiv:2411.16594*, 2024. 17
- [467] Y. Li, A. Dao, W. Bao, Z. Tan, T. Chen, H. Liu, and Y. Kong, "Facial affective behavior analysis with instruction tuning," *arXiv preprint* arXiv:2404.05052, 2024. 18
- [468] B. Xing, Z. Yu, X. Liu, K. Yuan, Q. Ye, W. Xie, H. Yue, J. Yang, and H. Kälviäinen, "Emo-llama: Enhancing facial emotion understanding with instruction tuning," *arXiv preprint arXiv:2408.11424*, 2024. 18
- [469] X. Lan, J. Xue, J. Qi, D. Jiang, K. Lu, and T.-S. Chua, "ExplIm: Towards chain of thought for facial expression recognition," *arXiv* preprint arXiv:2409.02828, 2024. 18
- [470] C. I. Hausladen, M. Knott, C. F. Camerer, and P. Perona, "Social perception of faces in a vision-language model," arXiv preprint arXiv:2408.14435, 2024. 18
- [471] Q. Yang, M. Ye, and B. Du, "Emollm: Multimodal emotional understanding meets large language models," arXiv preprint arXiv:2406.16442, 2024. 18
- [472] H. Sun, M. He, T. Lian, H. Han, and S. Shan, "Face-mllm: A large face perception model," arXiv preprint arXiv:2410.20717, 2024. 18
- [473] J. Tang, H. Lu, R. Wu, X. Xu, K. Ma, C. Fang, B. Guo, J. Lu, Q. Chen, and Y.-C. Chen, "Hawk: Learning to understand open-world video anomalies," arXiv preprint arXiv:2405.16886, 2024. 18
- [474] L. Zanella, W. Menapace, M. Mancini, Y. Wang, and E. Ricci, "Harnessing large language models for training-free video anomaly detection," in *CVPR*, 2024, pp. 18 527–18 536. 18
- [475] H. Du, S. Zhang, B. Xie, G. Nan, J. Zhang, J. Xu, H. Liu, S. Leng, J. Liu, H. Fan *et al.*, "Uncovering what why and how: A comprehensive benchmark for causation understanding of video anomaly," in *CVPR*, 2024, pp. 18793–18803. 18
- [476] N. R. Waytowich, D. White, M. Sunbeam, and V. G. Goecks, "Atarigpt: Investigating the capabilities of multimodal large language models as low-level policies for atari games," *arXiv preprint arXiv:2408.15950*, 2024. 18
- [477] P. Chen, P. Bu, J. Song, Y. Gao, and B. Zheng, "Can vlms play action role-playing games? take black myth wukong as a study case," *arXiv* preprint arXiv:2409.12889, 2024. 18

- [478] Z. Wang, S. Cai, A. Liu, Y. Jin, J. Hou, B. Zhang, H. Lin, Z. He, Z. Zheng, Y. Yang *et al.*, "Jarvis-1: Open-world multi-task agents with memory-augmented multimodal language models," *IEEE TPAMI*, 2024. 18
- [479] E. Zhou, Y. Qin, Z. Yin, Y. Huang, R. Zhang, L. Sheng, Y. Qiao, and J. Shao, "Minedreamer: Learning to follow instructions via chain-of-imagination for simulated-world control," *arXiv preprint* arXiv:2403.12037, 2024. 18
- [480] S. Yu and C. Lu, "Adam: An embodied causal agent in open-world environments," arXiv preprint arXiv:2410.22194, 2024. 18
- [481] Z. Zhao, W. Chai, X. Wang, B. Li, S. Hao, S. Cao, T. Ye, and G. Wang, "See and think: Embodied agent in virtual environment," in *ECCV*. Springer, 2025, pp. 187–204. 18
- [482] S. Zheng, J. Liu, Y. Feng, and Z. Lu, "Steve-eye: Equipping llm-based embodied agents with visual perception in open worlds," arXiv preprint arXiv:2310.13255, 2023. 18
- [483] Y. Qin, E. Zhou, Q. Liu, Z. Yin, L. Sheng, R. Zhang, Y. Qiao, and J. Shao, "Mp5: A multi-modal open-ended embodied system in minecraft via active perception," in *CVPR*, 2024, pp. 16307–16316. 18
- [484] W. Tan, W. Zhang, X. Xu, H. Xia, G. Ding, B. Li, B. Zhou, J. Yue, J. Jiang, Y. Li et al., "Cradle: Empowering foundation agents towards general computer control," in *NeurIPS 2024 Workshop on Open-World Agents*, 2024. 18