Rate-My-LoRA: EFFICIENT AND ADAPTIVE FEDERATED MODEL TUNING FOR CARDIAC MRI SEGMENTATION

Xiaoxiao He¹, Haizhou Shi¹, Ligong Han^{1*}, Chaowei Tan¹, Bo Liu^{2*}, Zihao Xu¹, Meng Ye¹, Leon Axel³, Kang Li¹, Dimitris Metaxas¹

> ¹Department of Computer Science, Rutgers University, USA ²Walmart Global Tech, USA ³New York University School of Medicine, USA

ABSTRACT

Cardiovascular disease (CVD) and cardiac dyssynchrony are major public health problems in the United States. Precise cardiac image segmentation is crucial for extracting quantitative measures that help categorize cardiac dyssynchrony. However, achieving high accuracy often depends on centralizing large datasets from different hospitals, which can be challenging due to privacy concerns. To solve this problem, Federated Learning (FL) is proposed to enable decentralized model training on such data without exchanging sensitive information. However, bandwidth limitations and data heterogeneity remain as significant challenges in conventional FL algorithms. In this paper, we propose a novel efficient and adaptive federate learning method for cardiac segmentation that improves model performance while reducing the bandwidth requirement. Our method leverages the low-rank adaptation (LoRA) to regularize model weight update and reduce communication overhead. We also propose a Rate-My-LoRA aggregation technique to address data heterogeneity among clients. This technique adaptively penalizes the aggregated weights from different clients by comparing the validation accuracy in each client, allowing better generalization performance and fast local adaptation. In-client and cross-client evaluations on public cardiac MR datasets demonstrate the superiority of our method over other LoRA-based federate learning approaches. Code can be accessed here.

Index Terms— Federated Learning, Fine-tuning, Low-rank, Cardiac Segmentation, Magnetic Resonance Imaging

1. INTRODUCTION

Cardiac dyssynchrony, where the heart's ventricles beat out of sync, worsens heart failure prognosis, with up to 60% of patients dying within four years [1]. Advances in diagnostic tools like cardiac MRI (cMRI) are crucial in addressing this issue [2]. Accurate segmentation of the left ventricle cavity (LVC), myocardium (LVM), and right ventricle cavity (RVC)



Fig. 1. A demonstration of our FL scenario. it shows a scenario where the bandwidth limits the transfer of the model with full weights. Additionally, the dataset exhibits size imbalance; one hospital has half the patients compared to others.

in cMRI is essential for analyzing cardiac dyssynchrony, particularly in measuring LVM wall displacement [3]. Deep learning has significantly improved automated segmentation [4, 5, 6, 7], aiding in this analysis. However, centralized learning methods, which require data sharing across hospitals, raise privacy concerns [8]. Federated learning (FL) [9, 10, 11, 12] addresses these by allowing model training across sites without direct data sharing. While FL protects patient privacy and leverages diverse data, it faces challenges such as data heterogeneity across hospitals [13]. Differences in equipment, protocols, and patient populations result in non-IID data, which can hinder model performance. Limited bandwidth in resource-constrained hospitals also complicates participation in FL, potentially excluding valuable data and amplifying biases [14], as demonstrated in Fig. 1,2.

Researchers have made efforts to address the challenges of highly heterogeneous data, but the issues remain. Stripelis et al. [15] introduced a federated learning framework where clients' weights are determined by the validation performance of models from other clients. While effective, this method is resource-intensive, requiring each client to validate all other

^{*} Corresponding Author



Fig. 2. Demonstration of the highly non-IID data on federated learning. Due to different imaging equipment, the style of the images across clients differs, as in the red box.

models. Xu et al. [16] proposed evaluating clients' models on a server using an additional dataset, assigning weights based on performance. However, this may reduce generalization by favoring models that excel on the server's validation set.

Furthermore, previous works that attempted to address the convergence of highly heterogeneous data [15, 16] usually overlooked communication efficiency between clients. To tackle this issue, Low-rank adaptation (LoRA) [17] has emerged as an effective method for fine-tuning large-scale models in federated learning. Unlike traditional fine-tuning, which updates all model parameters, LoRA introduces trainable low-rank matrices within the model's weight matrices. This reduces the computational load on clients with limited hardware and significantly cuts communication overhead by transmitting only the compact LoRA parameters instead of full model weights. LoRA's rank constraints also provide regularization, improving generalization in few-shot scenarios where full-rank fine-tuning may overfit [18, 19, 20, 21]. Fed-PETuning [22] combines LoRA with FedAvg [9] to achieve similar performance with reduced communication costs, but it fails to account for data heterogeneity, leading to performance loss after merging.

To address this limitation, we introduce Rate-My-LoRA, a novel method designed to enhance the extraction of generalizable features in federated learning and enable efficient local adaptation with minimal training. Our approach begins by evaluating each client's LoRA adapters on their validation sets, followed by applying an adaptive penalization term when merged LoRAs show performance declines. This process mirrors the iterative refinement seen in diffusion models, which have proven effective in solving inverse problems and editing [23, 24, 25]. This encourages the learning of generalizable knowledge, improving model robustness across diverse data. The method also dynamically adjusts the size of LoRA adapters based on local training set size to prevent overfitting. Our contributions are: (i) Rate-My-LoRA enhances both inclient and cross-client accuracy in LoRA-based FL, (ii) extensive evaluations show superior performance over other methods, and (iii) it reduces bandwidth usage by up to 94% per communication round.

2. METHODS

Fig. 3 provides a visual representation of our proposed LoRAbased federated learning approach. In essence, we fine-tune a low-rank adapter within each client using local datasets and subsequently merge these adapters using our novel Rate-My-LoRA aggregation method.

Problem formulation. We consider a scenario with |C| clients, where each client c possesses a local dataset D^c . The goal is to find a global model \mathcal{M}^* that satisfies the following condition: Denote C is the set of all clients, $\mathcal{M}^* = \operatorname{argmin}_{\{\mathcal{M}^c\}} \sum_{c \in C} f(\mathcal{M}^c, \mathcal{D}^c)$. In general, the local objectives measure the local empirical risk over the local dataset \mathcal{D}^c is defined as $f(\mathcal{M}^c) := \frac{1}{|\mathcal{D}_c|} \sum_{x \in \mathcal{D}^c} f(\mathcal{M}^c; x)$, $\mathcal{M}^c = \mathcal{M}_0 + \sum_{k \in C, k \neq c} \mathcal{A}^k + \mathcal{A}_{T+1}^c$ where \mathcal{M}_0 is the pretrained model, T is the communication rounds, \mathcal{A} is the learned low-rank adapter.

Federated learning framework with LoRA aggregation. In order to allow more hospitals to participate in training and remove the barrier of communication constraint, we integrate the federated learning framework with Low-Rank Adaptation. With federated learning, no personally-identifiable patient data will be transferred in any part of the training process. The core idea of LoRA is to constrain the weight update on the model by a low rank decomposition: $W = W_0 + \mathcal{A} = W_0 + BA$, where $W_0 \in \mathbb{R}^{d \times k}$ and $B \in \mathbb{R}^{d \times r}, A \in \mathbb{R}^{r \times k}$ and $r \ll \min(d, k)$. By using low-rank decomposition, the number of parameters requiring fine-tuning and transmission between client and server is drastically reduced compared to full-weight fine-tuning. This not only alleviates communication bottlenecks but also acts as a form of regularization, limiting the model's capacity to memorize local datasets. Consequently, the generalizability of the aggregated model is enhanced, particularly in few-shot scenarios where overfitting is a concern [18, 20, 26, 27], as utlined in Alg. 1.

The proposed Rate-My-LoRA method. With conventional methods for merging LoRA adapters, includes average weighting $\mathcal{M} = \mathcal{M}_0 + \frac{1}{|C|} \sum_{c \in C} \mathcal{A}^c$ or weighting by dataset size $\mathcal{M} = \mathcal{M}_0 + \frac{1}{\sum_{c \in C} |\mathcal{D}^c|} \sum_{c \in C} |\mathcal{D}^c| \mathcal{A}^c$ (FedPETuning), it is common to see a drastic accuracy drop after merging the adapters. In average weighting, the aggregated model often becomes biased towards clients with shared features, as their models converge in similar directions during training. This can lead to an overemphasis on common features, reducing the model's ability to generalize to unique client data. With FedPETuning, where merging weights are based on dataset size, the model risks overfitting to the client with the most data. This dominant client's model can overshadow others, resulting in a model that performs well on their data but poorly on others, limiting overall generalization.

Both conventional methods compromise the generalizability of the collaborative model in different ways. To overcome this and improve the robustness of the aggregated



Fig. 3. Overview of our efficient and adaptive FL method: the server contains a pretrained model and each client has a local adapter. The red, green and blue label in the MR image represents LVC, LVM, and RVC, respectively. In each FL round, only the adapters in each client are updated.



Fig. 4. Our Rate-My-LoRA method that utilizes on-client data for evaluating the performance gains/losses of the aggregated model and adaptive adjust the aggregation weight of each adapter to achieve overall performance.

Alg	orithm 1 The proposed Rate-My-LoRA method						
Ce	ntral server do:						
1:	Load pretrained network \mathcal{M} .						
2:	Inject and initialize LoRA adapters $\forall c \in C, B_0^c, A_0^c$ to						
	\mathcal{M} .						
3:	Distribute $\mathcal{M}, B_0^c, A_0^c$ to clients.						
4:	for each communication round $t \in 1,, T$ do						
5:	for all each client $c \in C$ do in parallel						
6:	$B_t^c A_t^c \leftarrow \text{TrainLocal}(\mathcal{M} + \sum_{k \in C} B_{t-1}^k A_{t-1}^k) \triangleright$						
	Collect adapter from client c						
7:	end for						
8:	for all each client $c \in C$ do in parallel						
9:	$P_c^t \leftarrow \text{Evaluate } \mathcal{M}_t^A \text{ on client } c \text{ and return the}$						
	evaluation metric						
10:	end for						
11:	Update B_{t+1}^c with Rate-My-LoRA adaptive learning						
	weight $w_t(c)$, indicated in Eqn. 1						
12:	Distribute B_{t+1}^c, A_{t+1}^c						
13:	$\lambda = \lambda \times 0.95$ > Update lambda						
1.4	end for						

model, we propose a novel approach. After client-side traing, each client uploads its learned LoRA adapter weights to e server, which then redistributes them to all clients. Each ent evaluates the aggregated model on its local validation and reports the accuracy back to the server. This accucy score indicates how well each adapter captures common atures across clients. By comparing the current accuracy to e previous round, we can penalize adapters that reduce genalizability by introducing a penalty term. The weight for ch LoRA adapter is determined using the hyperparameter defined as follows:

$$w_t(c) = \begin{cases} 1 - \lambda & \exists i \in \mathcal{C} \text{ s.t. } P_t^i < P_{t-1}^i \text{ and } P_t^c > P_{t-1}^c \\ 1 & \text{otherwise} \end{cases}$$
(1)

where P_t^c is the client c validation accuracy at time t. Note at $w_t(c) = 1 - \lambda$ only happens when there exists a client at has drop in accuracy. Then for each of the weight matrix $^{c}A_{t}^{c}$, the aggregation becomes

$$W_t = W_{t-1} + \frac{1}{\sum_{c \in \mathcal{C}} |\mathcal{D}^c|} \sum_{c \in \mathcal{C}} w_t(c) |\mathcal{D}^c| B_t^c A_t^c \qquad (2)$$

Method	\mathcal{C}	DICE	VOE	HD	ASSD
	1	0.818	29.957	89.897	3.769
Local Only	2	0.830	27.503	93.124	4.171
	3	0.887	19.984	56.680	1.047
Average	1	0.834	26.990	12.652	0.994
Weighting [†]	2	0.896	18.650	54.945	1.111
[9]	3	0.834	28.110	74.786	2.884
E. IDET	1	0.840	27.339	8.402	0.815
reare running	2	0.883	19.947	41.096	2.040
[22]	3	0.873	21.913	36.701	0.943
	1	0.889	19.777	14.992	0.544
Our method	2	0.910	16.114	44.217	1.304
	3	0.895	18.596	26.125	0.688
Full Dataset	all	0.904	17.068	37.983	0.830
(Average)					

Table 1. Quantitative results for in-client evaluation. [†]: full weights fine-tuning. Full Dataset utilizes all available data to train and evaluate on testing set for all three clients, providing an upper bound. The rest results are evaluated on the client-side testing set. Local only fine-tunes the model with local data without federated learning. The best results have been highlighted in the chart.

During the FL aggregation phase, the adapters are first aggregated with equal weights and distributed to each client, which then evaluates the model on its local validation set and reports accuracy to the server. The server tracks validation performance over time. Sometimes, due to data heterogeneity between clients, validation accuracy decreases after adapter aggregation, as shown on the left in Fig. 4. The arrows indicate gradient directions post-local training, and the drop in performance is represented by the distance between W_t and W_{t+1} from the blue local optimal point, highlighting conflicts in client gradient descent directions. When such performance drop is reported, the server adaptively penalizes the adapter from other clients, as they fail to generalize. As illustrated on the right of Fig. 4, this reduces the distance between the aggregated model and local optima, improving overall model performance. To ensure convergence, we apply a diminishing schedule to λ , reducing it by 5% each communication round. When $\lambda = 0$, the method reverts to FedAVG, where LoRA adapters are averaged across all clients.

3. EXPERIMENTS

Experimental Settings. This paper uses two publicly available datasets: the Automated Cardiac Diagnosis Challenge (ACDC) [28] and the Multi-Disease, Multi-View & Multi-Center Right Ventricular Segmentation in Cardiac MRI (M&Ms-2) [29, 30]. The ACDC dataset, with 100 patients imaged using a Siemens scanner, is used to train the base model. The M&Ms-2 dataset includes cardiac cine MR images from 160 patients across three hospitals using GE (Client 1), Philips (Client 2), and Siemens (Client 3) scan-

Model	\mathcal{C}	DICE	VOE	HD	ASSD
	1	0.801	30.505	74.569	2.716
Local Only	2	0.848	25.386	49.832	1.579
	3	0.776	33.231	81.534	3.951
Average	1	0.768	35.695	17.628	1.260
Weighting [†]	2	0.843	26.576	27.330	1.126
[9]	3	0.813	30.690	90.586	2.913
EadDETunina	1	0.849	24.917	29.130	1.018
reare running	2	0.865	23.432	20.331	0.747
[22]	3	0.862	23.429	39.445	1.211
	1	0.882	20.411	37.484	1.396
Our Method	2	0.894	18.826	13.139	0.557
	3	0.904	17.187	24.317	0.697

Table 2. Quantitative results for cross-client accuracy. The number in C column indicates that the model is trained on such client and is evaluated on the other two clients. The best results have been highlighted in the chart.



Fig. 5. 3D visualization results of in-client evaluation. (a-d), (e-h), (i-l) are the ground truth, local training, FedPETuning and the Rate-My-LoRA method results from the client 1, 2 and 3, respectively.

ners, creating a visual appearance gap between FL clients. All images are cropped to 224×224 , and intensity is normalized. A train/validation/test split of 8:1:1 is applied. U-net [31] serves as the base model, with LoRA adapters injected into each convolution block. LoRA adapter sizes are 16, 32, 32, based on local dataset size, and λ is set to 0.2. After aggregation, models are fine-tuned on local data for one extra epoch. We evaluate performance using Dice coefficient (DICE), volumetric error (VOE), Hausdorff distance (HD), and average symmetric surface distance (ASSD) between ground truth and segmentation results.

Evaluation of the segmentation quality. In Tab. 1, we present the in-client evaluation, where our method outperforms FedPETuning by up to 4.7% on client 1. The lower performance of FedAVG with full weights, compared to local fine-tuning on client 3, highlights how data heterogeneity causes performance drops in the aggregated model. Across the full-weight and LoRA-based FL methods, we observe a general performance improvement and reduced client inconsistency, suggesting that low-rank regularization enhances the model's generalizability. Our Rate-My-LoRA approach helps each client extract generalizable knowledge, boosting segmentation accuracy and narrowing the performance gap



Fig. 6. Visualization of the in-client evaluation results. (a-d), (e-h), (i-l) are the ground truth, local training, FedPETuning and our method results from client 1,2 and 3,

between clients. In Fig. 6, we show the in-client evaluation results visually. FedPETuning and local training struggle to segment the RVC. Our method successfully segments the RVC, LVC, and LVM regions. Additionally, Fig. 5 shows 3D visualizations, where other methods exhibit varying degrees of oversegmentation or undersegmentation, while our Rate-My-LoRA produces volumes closest to the ground truth.

In Tab. 2, we present cross-client accuracy results. Consistent with Chen et al. [13], non-IID conditions between clients degrade the performance of Full-weight FedAVG, compared to local training. Using low-rank regularization and our adaptive Rate-My-LoRA, we show that knowledge extracted from one client improves other clients' models, enhancing the generalizability of the aggregated model. We want to emphasize that in terms of bandwidth usage, our method saves up to 15.5x compared to full-weight training per epoch, as calculated by the size of LoRA adapters (1.8MB, 3.6MB, 3.6MB on each client respectively) and the full rank weight size (28MB). Although it requires multiple communications, LoRA weights are only uploaded and downloaded once per iteration.

4. CONCLUSION AND DISCUSSION

In this paper, we proposed a FL-based low-rank adaptation method, Rate-My-LoRA, to improve both in-client and crossclient cardiac segmentation accuracy under communication bandwidth constraints. Rate-My-LoRA carefully evaluates the generalizability of LoRA adapters from different clients and enables fast local adaptation. Both in-client and crossclient evaluations show that our method outperforms other LoRA-based FL approaches. This work holds potential for enabling medical institutions in resource-limited settings to train AI models effectively.

5. COMPLIANCE WITH ETHICAL STANDARDS

This research study was conducted retrospectively using human subject data made available in open access by Universitat de Barcelona, Spain and University of Lyon, France. Ethical approval was not required as confirmed by the license attached with the open access data.

6. ACKNOWLEDGMENTS

This research has been partially funded by research grants to D. Metaxas through NSF: IUCRC CARTA 1747778, 2235405, 2212301, 1951890, 2003874, and NIH-5R01HL127661.

7. REFERENCES

- Antonello D'Andrea, Donato Mele, et al., "The prognostic impact of dynamic ventricular dyssynchrony in patients with idiopathic dilated cardiomyopathy and narrow QRS," *European Heart Journal - Cardiovascular Imaging*, vol. 14, no. 2, pp. 183–189, 08 2012.
- [2] Constantin B Marcu, Aernout M Beek, and Albert C Van Rossum, "Clinical applications of cardiovascular magnetic resonance imaging," *Cmaj*, vol. 175, no. 8, pp. 911–917, 2006.
- [3] Xiaoxiao He, Chaowei Tan, Ligong Han, Bo Liu, Leon Axel, Kang Li, and Dimitris N Metaxas, "Dmcvr: Morphology-guided diffusion model for 3d cardiac volume reconstruction," in *International Conference on Medical Image Computing and Computer-Assisted Intervention.* Springer, 2023, pp. 132–142.
- [4] Xiaoxiao He, Chaowei Tan, Yuting Qiao, Virak Tan, Dimitris Metaxas, and Kang Li, "Effective 3d humerus and scapula extraction using low-contrast and highshape-variability mr data," in *Medical Imaging 2019: Biomedical Applications in Molecular, Structural, and Functional Imaging.* SPIE, 2019, vol. 10953, pp. 118– 124.
- [5] Qilong Zhangli, Jingru Yi, Di Liu, Xiaoxiao He, Zhaoyang Xia, Qi Chang, Ligong Han, Yunhe Gao, Song Wen, Haiming Tang, et al., "Region proposal rectification towards robust instance segmentation of biological images," in *Medical Image Computing and Computer Assisted Intervention–MICCAI 2022: 25th International Conference, Singapore, September 18–22, 2022, Proceedings, Part IV.* Springer Nature Switzerland Cham, 2022, pp. 129–139.
- [6] Di Liu, Yunhe Gao, Qilong Zhangli, Ligong Han, Xiaoxiao He, Zhaoyang Xia, Song Wen, Qi Chang, Zhennan Yan, Mu Zhou, et al., "Transfusion: multi-view divergent fusion for medical image segmentation with transformers," in *Medical Image Computing and Computer Assisted Intervention–MICCAI 2022: 25th International Conference, Singapore, September 18–22,* 2022, Proceedings, Part V. Springer Nature Switzerland Cham, 2022, pp. 485–495.

- [7] Xiaoxiao He, Chaowei Tan, Virak Tan, and Kang Li, "Recursive 3d segmentation of shoulder joint with coarse-scanned mr image," *arXiv preprint arXiv:2203.07846*, 2022.
- [8] Chen Chen, Chen Qin, Huaqi Qiu, Giacomo Tarroni, Jinming Duan, Wenjia Bai, et al., "Deep learning for cardiac image segmentation: a review," *Frontiers in Cardiovascular Medicine*, vol. 7, pp. 25, 2020.
- [9] Brendan McMahan, Eider Moore, Daniel Ramage, Seth Hampson, and Blaise Aguera y Arcas, "Communication-efficient learning of deep networks from decentralized data," in *Artificial intelligence and statistics*. PMLR, 2017, pp. 1273–1282.
- [10] Sarthak Pati, Ujjwal Baid, Brandon Edwards, Micah Sheller, Shih-Han Wang, G Anthony Reina, et al., "Federated learning enables big data for rare cancer boundary detection," *Nature communications*, vol. 13, no. 1, pp. 7346, 2022.
- [11] Xiaoxiao He, Chaowei Tan, Bo Liu, Liping Si, Weiwu Yao, Liang Zhao, Di Liu, Qilong Zhangli, Qi Chang, Kang Li, et al., "Dealing with heterogeneous 3d mr knee images: A federated few-shot learning method with dual knowledge distillation," arXiv preprint arXiv:2303.14357, 2023.
- [12] Qi Chang, Zhennan Yan, Mu Zhou, Hui Qu, Xiaoxiao He, Han Zhang, Lohendran Baskaran, Subhi Al'Aref, Hongsheng Li, Shaoting Zhang, et al., "Mining multicenter heterogeneous medical data with distributed synthetic learning," *Nature communications*, vol. 14, no. 1, pp. 5510, 2023.
- [13] Jinyu Chen, Wenchao Xu, Song Guo, Junxiao Wang, Jie Zhang, and Haozhao Wang, "Fedtune: A deep dive into efficient federated fine-tuning with pre-trained transformers," arXiv preprint arXiv:2211.08025, 2022.
- [14] Dianbo Sui, Yubo Chen, Jun Zhao, Yantao Jia, Yuantao Xie, and Weijian Sun, "FedED: Federated learning via ensemble distillation for medical relation extraction," in *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, Online, Nov. 2020, pp. 2118–2128, Association for Computational Linguistics.
- [15] Dimitris Stripelis, Marcin Abram, and Jose Luis Ambite, "Performance Weighting for Robust Federated Learning Against Corrupted Sources," May 2022, arXiv:2205.01184 [cs].
- [16] Xinlei Xu, Saisai Niu, Zhe Wang, Dongdong Li, Hai Yang, and Wenli Du, "Client selection based weighted federated few-shot learning," *Applied Soft Computing*, vol. 128, pp. 109488, Oct. 2022.

- [17] Edward J Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, et al., "Lora: Low-rank adaptation of large language models," *arXiv* preprint arXiv:2106.09685, 2021.
- [18] David Bau, Steven Liu, Tongzhou Wang, Jun-Yan Zhu, and Antonio Torralba, "Rewriting a deep generative model," in *Computer Vision–ECCV 2020: 16th European Conference, Glasgow, UK, August 23–28, 2020, Proceedings, Part I 16.* Springer, 2020, pp. 351–369.
- [19] Yibin Wang, Haizhou Shi, Ligong Han, Dimitris Metaxas, and Hao Wang, "Blob: Bayesian low-rank adaptation by backpropagation for large language models," *arXiv preprint arXiv:2406.11675*, 2024.
- [20] Jiacheng Zhu, Kristjan Greenewald, Kimia Nadjahi, Haitz Sáez de Ocáriz Borde, Rickard Brüel Gabrielsson, Leshem Choshen, et al., "Asymmetry in lowrank adapters of foundation models," *arXiv preprint arXiv:2402.16842*, 2024.
- [21] Haizhou Shi, Yibin Wang, Ligong Han, Huan Zhang, and Hao Wang, "Training-free bayesianization for lowrank adapters of large language models," *arXiv preprint arXiv:2412.05723*, 2024.
- [22] Zhuo Zhang, Yuanhang Yang, Yong Dai, Qifan Wang, Yue Yu, Lizhen Qu, and Zenglin Xu, "Fedpetuning: When federated learning meets the parameter-efficient tuning methods of pre-trained language models," in *Annual Meeting of the Association of Computational Linguistics 2023*. Association for Computational Linguistics (ACL), 2023, pp. 9963–9977.
- [23] Ligong Han, Song Wen, Qi Chen, Zhixing Zhang, Kunpeng Song, Mengwei Ren, Ruijiang Gao, Anastasis Stathopoulos, Xiaoxiao He, Yuxiao Chen, et al., "Proxedit: Improving tuning-free real image editing with proximal guidance," in *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision*, 2024, pp. 4291–4301.
- [24] Xiaoxiao He, Ligong Han, Quan Dao, Song Wen, Minhao Bai, Di Liu, Han Zhang, Martin Renqiang Min, Felix Juefei-Xu, Chaowei Tan, et al., "Dice: Discrete inversion enabling controllable editing for multinomial diffusion and masked generative models," *arXiv* preprint arXiv:2410.08207, 2024.
- [25] Anastasis Stathopoulos, Ligong Han, and Dimitris Metaxas, "Score-guided diffusion for 3d human recovery," in *Proceedings of the IEEE/CVF Conference* on Computer Vision and Pattern Recognition, 2024, pp. 906–915.

- [26] Ligong Han, Yinxiao Li, Han Zhang, Peyman Milanfar, Dimitris Metaxas, and Feng Yang, "Svdiff: Compact parameter space for diffusion fine-tuning," in *Proceedings of the IEEE/CVF International Conference on Computer Vision*, 2023, pp. 7323–7334.
- [27] Xinxi Zhang, Song Wen, Ligong Han, Felix Juefei-Xu, Akash Srivastava, Junzhou Huang, Hao Wang, Molei Tao, and Dimitris N Metaxas, "Spectrum-aware parameter efficient fine-tuning for diffusion models," arXiv preprint arXiv:2405.21050, 2024.
- [28] Olivier Bernard, Alain Lalande, et al., "Deep learning techniques for automatic mri cardiac multi-structures segmentation and diagnosis: is the problem solved?," *IEEE transactions on medical imaging*, vol. 37, no. 11, pp. 2514–2525, 2018.
- [29] Victor M Campello, Polyxeni Gkontra, Cristian Izquierdo, Carlos Martin-Isla, Alireza Sojoudi, Peter M Full, et al., "Multi-centre, multi-vendor and multidisease cardiac segmentation: the m&ms challenge," *IEEE Transactions on Medical Imaging*, vol. 40, no. 12, pp. 3543–3554, 2021.
- [30] Carlos Martín-Isla, Víctor M Campello, et al., "Deep learning segmentation of the right ventricle in cardiac mri: The m&ms challenge," *IEEE Journal of Biomedical and Health Informatics*, 2023.
- [31] Olaf Ronneberger, Philipp Fischer, and Thomas Brox, "U-net: Convolutional networks for biomedical image segmentation," in *Medical image computing and computer-assisted intervention–MICCAI 2015: 18th international conference, Munich, Germany, October 5-9,* 2015, proceedings, part III 18. Springer, 2015, pp. 234– 241.