# <span id="page-0-0"></span>Text-to-Edit: Controllable End-to-End Video Ad Creation via Multimodal LLMs

Dabing Cheng, Haosen Zhan, Xingchen Zhao, Guisheng Liu, Zemin Li, Jinghui Xie, Zhao Song, Weiguo Feng, Bingyue Peng

ByteDance Inc

**<https://text2edit.github.io>**

#### Abstract

*The exponential growth of short-video content has ignited a surge in the necessity for efficient, automated solutions to video editing, with challenges arising from the need to understand videos and tailor the editing according to user requirements. Addressing this need, we propose an innovative end-to-end foundational framework, ultimately actualizing precise control over the final video content editing. Leveraging the flexibility and generalizability of Multimodal Large Language Models (MLLMs), we defined clear input-output mappings for efficient video creation. To bolster the model's capability in processing and comprehending video content, we introduce a strategic combination of a denser frame rate and a slow-fast processing technique, significantly enhancing the extraction and understanding of both temporal and spatial video information. Furthermore, we introduce a text-to-edit mechanism that allows users to achieve desired video outcomes through textual input, thereby enhancing the quality and controllability of the edited videos. Through comprehensive experimentation, our method has not only showcased significant effectiveness within advertising datasets, but also yields universally applicable conclusions on public datasets.*

#### 1. Introduction

With the rapid rise of short videos online, their role in advertising and marketing has grown significantly, emphasizing the need for smarter, more efficient methods to accelerate high-quality video ad production. Recent advancements in Multimodal Large Language Models (MLLMs) [\[3,](#page-8-0) [25,](#page-8-1) [48,](#page-9-0) [50\]](#page-9-1) show promising potential in commercial advertising, particularly in generating marketing scripts [\[44\]](#page-9-2) and understanding ad images or videos, which substantially improves production efficiency and reduces costs in creating video ads.

However, current MLLM applications in advertising

video creation are limited to specific production stages, lacking an end-to-end framework. We systematically analyze the underlying challenges and summarize them into the following three points: (1) Video creation involves complex processes and material management, including tasks like video clips arrangement, script generation, background music recommendation, and their synchronization with timeline alignment. This demands not only a clear and universally applicable definition of inputs and outputs but also requires significant model flexibility and collaboration. (2) Editing video materials requires a deep understanding of content, focusing on both spatial information and critical temporal dynamics, which are vital for the logic of the video storyline. However, existing models [\[22,](#page-8-2) [28,](#page-9-3) [29,](#page-9-4) [47\]](#page-9-5) for video understanding generally capture overall content but miss crucial temporal variations. (3) The content generated in video production must maintain both diversity and controllability to ensure richness and practical relevance. Imposing rules on model outputs limits diversity, while increasing diversity often produces outputs that fail to meet practical needs, reducing production efficiency.

To address these challenges, we propose a unified video creation solution based on multimodal LLMs for narrative advertising videos. Leveraging the flexibility and generalizability of LLMs, we clearly defined the input and output. Specifically, we input product information, textual user editing requirements, and clips of video materials. The multimodal model understands the input information and completes the video creation task, directly generating a JSONformatted editing draft detailing clips arrangement track, voice-over script track, and decorative-related tags in the video. Finally, we perform simple post-processing and rendering on the draft to complete the video production.

To tackle the video understanding problems, we propose to employ a higher frame density by sampling video frames at up to 2 frames per second (fps), harnessing the self-attention mechanism to enhance sensitivity to temporal

<span id="page-1-1"></span><span id="page-1-0"></span>

Figure 1. Examples of videos generated by our method. Leveraging the Multimodal LLM, we proposed an end-to-end solution for creating advertising narrative videos. This approach directly outputs a draft protocol for video edits by processing inputs including product information, expected requirements (free prompt), and video clips. Importantly, it facilitates precise and controllable video editing that perfectly aligns with user-defined free prompts. For details, refer to the figure where corresponding colors indicate aligned information. See more cases in Appendix [6.7.](#page-11-0)

variations. To facilitate the input of longer videos, we reduce the number of tokens per frame to prevent token overflow. Following token compression, our system can support the input of up to 600 frames of video, a capability rarely seen in other works. Additionally, to avoid losing spatial semantic signals, we balance the need for detailed spatial information and temporal dynamics through a slow-fast strategy [\[13,](#page-8-3) [15\]](#page-8-4). In this approach, the slow pathway processes frames sparsely (e.g., 0.5fps) with more visual tokens per frame (e.g., 16 or 64 tokens) to capture detailed spatial information. Meanwhile, the fast pathway processes frames densely (e.g., 2fps) with fewer tokens (e.g., 1 or 4 tokens), focusing on temporal dynamics to maintain consistency.

Building on LLMs' inherent diversity to enhance video quality and control, we introduce a text-to-edit approach, allowing users to specify desired outputs through text input. We set boundaries for managing free-prompting and use a data enhancement pipeline to simulate user needs. As shown in Fig. [1,](#page-1-0) our framework, trained on high-quality pairwise free-prompt data, closely aligns with user inputs, <span id="page-2-0"></span>ensuring high output quality and extensive control over video editing.

Overall, our core contributions can be summarized as follows:

- We propose a novel video editing framework with a multimodal LLM that clearly defines input-output formats, streamlining production by managing material comprehension and arrangement in one step. To the best of our knowledge, this is the first end-to-end MLLM-based video editing framework.
- We introduce an effective approach employing a denser frame rate and a slow-fast processing strategy, which significantly enhances the model's ability to extract and understand temporal and spatial video information.
- To improve the controllability of the model's output, we develop a text-driven video editing method that ensures the final output aligns precisely with user expectations.
- We conduct comprehensive experiments and exploratory analyses, demonstrating that our proposed video editing framework can optimally perform advertising short-video editing tasks. Moreover, our framework generalizes well to public datasets, achieving applicable results.

#### 2. Related Work

#### 2.1. Multimodal Large Language Models

Recently, a growing focus on MLLMs such as Flamingo [\[3\]](#page-8-0), MiniGPT-4 [\[50\]](#page-9-1), LLaVA [\[25\]](#page-8-1), LLaVA-NeXT series [\[20,](#page-8-5) [24,](#page-8-6) [49\]](#page-9-6), InternLM-XComposer series [\[12,](#page-8-7) [48\]](#page-9-0), InternVL [\[9\]](#page-8-8) and MiniCPMV [\[45\]](#page-9-7) has expanded their potenial. Initial studies mainly centered on the alignment of image and text modalities, with a strong emphasis on image understanding. More recent work has shifted to video understanding [\[15,](#page-8-4) [22,](#page-8-2) [28](#page-9-3)[–30,](#page-9-8) [41,](#page-9-9) [47,](#page-9-5) [49\]](#page-9-6). Early studies, however, were limited by their reliance on basic sparse frame (usually, 8 or 16 frames are extracted from a single video) extraction strategies [\[22,](#page-8-2) [28,](#page-9-3) [29,](#page-9-4) [47\]](#page-9-5) and simplistic temporal feature aggregation modules [\[30,](#page-9-8) [41\]](#page-9-9), which proved inadequate for fine-grained video analysis. Recognizing this limitation, recent studies have demonstrated that utilizing more video frames [\[49\]](#page-9-6) as input or more effective temporal information memory module [\[34\]](#page-9-10) yields substantial improvements. In our video editing task, it is essential to incorporate denser frames and input images with dual frame rates, including both slow and fast [\[13,](#page-8-3) [15\]](#page-8-4), to provide the model with a comprehensive and nuanced representation of the content.

#### 2.2. Video Editing and Composition

Automated video editing and composition has consistently attracted interests from researchers [\[2,](#page-8-9) [11\]](#page-8-10). However, many existing works faces two main limitations. First, they often focus on addressing challenges within specific sub-

processes of editing, such as classifying and organizing materials, retrieving materials based on the script, or supplementing text based on materials. For instance, works like Quickcut [\[38\]](#page-9-11), B-script [\[16\]](#page-8-11), Write-A-Video [\[40\]](#page-9-12), and Transcript-to-Video [\[42\]](#page-9-13) rely heavily on pre-written or rewrtiten scripts to organize or retrieve materials required for editing. Other frameworks, specifically, Argaw *et al.* [\[5\]](#page-8-12) solely facilitate video shots sorting, while Yang *et al.* [\[44\]](#page-9-2) focus on generating advertising oral script for given shots, and ChunkyEdit [\[18\]](#page-8-13) is designed to assist editors in organizing video interview clips. Second, other works are limited by their specific application contexts. For example, Arev*et al.* [\[4\]](#page-8-14) primarily address editing within multi-camera social settings, while Leake *et al.* [\[19\]](#page-8-15) focus on dialogue-driven scenarios. In contrast, while our focus is primarily on short narrative advertising videos, our proposed method is highly adaptable to a broad range of video editing scenarios.

#### 3. Methodolody

#### 3.1. Definition of Task

Our model input comprises three primary aspects: product information, user-specified free prompt and segmented video clips. More specifically, the product information, represented by  $X_p$ , includes the product name, brand, price, and key selling points. For free prompts, the model adheres to user-specified directives such as video storyline, script patterns or decorative elements, encapsulated by  $X_r$ . More importantly, the input video clips are demonstrated as  $C = {\text{clip}_0, \cdots, \text{clip}_i, \cdots, \text{clip}_N}$ . Here, N signifies the quantity of the clips, and  $i$  denotes the clip's index. Moreover, each clip segment can be represented by the extracted frames:  $\text{clip}_{i} = \{\text{fr}_{0}, \cdots, \text{fr}_{l}, \cdots, \text{fr}_{L}\},$  where  $\text{fr}_{l}$ denotes a specific frame within the clip, and L represents the total number of frames in the clip. To closely mimic real scenarios, we incorporated interference clips (denoted by  $\{\text{clip}_i^{\text{neg}}, \dots\}$ ) from other videos as negative examples. This strategy aims to discourage the model from selecting irrelevant clips during editing, thereby enhancing its ability to resist interference. Based on empirical values, we employ a rounded Gaussian distribution ( $numNegativeClip =$  $\max\{0, \text{round}(\mathcal{N}(2.5, 8))\}\)$  to sample interference clips.

Upon processing through our framework, the model directly outputs a simplified JSON draft of the video protocol, represented as  $D_{(R_s, R_v, R_t)}$ , primarily consisting of three tracks: voice-over track  $R_s$ , video nodes track  $R_v$ , and decoration setting  $R_t$ . We define our task as follow:

$$
D_{(R_s, R_v, R_t)} = \mathcal{M}(X_p, X_r, C),\tag{1}
$$

where  $\mathcal{M}(\cdot)$  is our proposed model. After basic postprocessing and converting the generated JSON into an actual video draft, then it can be rendered into a video. Refer to the Appendix [6.2](#page-10-0) for details on the post-processing and conversion of the draft.

<span id="page-3-1"></span><span id="page-3-0"></span>

Figure 2. Illustration of our model architecture. We input product information, free prompt, and video clips into the model, generating a JSON-formatted video editing draft that is transformed into a video through post-processing and rendering. We implement a slow-fast dual-pathway strategy for frame rates: the fast pathway has a higher frame rate with fewer tokens per frame (yellow star), and the slower pathway has a lower frame rate with more tokens per frame (green star). By integrating the free prompt into instructions, we enhance the flexibility and control of the video editing process.

#### 3.2. Denser Slow-fast Strategy

As depicted in the Fig. [2,](#page-3-0) the process begins by obtaining video clips. To increase the model's sensitivity to long-term changes in videos, we employ denser frame sampling frequency (with a maximum rate of 2 fps) and reduce the number of tokens per (to a minimum of 1 token) frame to prevent excessive token overflow. More specifically, We first sample each video  $\text{clip}_{i}$  to extract denser frames  $\tilde{C}_{i}$  as follow:

$$
\tilde{C}_i = \begin{cases} \text{fr}_{L//2}, & \text{if } t_i < \frac{1}{f}, \\ \text{Uniform}(\text{clip}_i, \frac{Lf}{t_i}), & \text{otherwise}, \end{cases}
$$
 (2)

where  $Uniform(\cdot)$  indicates that frames are uniformly sampled at intervals of  $\frac{L \cdot f}{t_i}$ , and  $t_i$  is the duration of clip<sub>i</sub>, L denotes the total number of frames in  $\text{clip}_{i}$ , f represents the expected sampling fps, when  $t_i < \frac{1}{f}$ , we take the middle frame of the clip frames.

Subsequently, each set of acquired clip frames is processed by a vision encoder  $Enc(\cdot)$  and perceive sampler  $PerS(\cdot)$ , transforming the visual frames into a sequence of visual tokens. The perceive sampler can generally be divided into two types: Query based [\[45,](#page-9-7) [48\]](#page-9-0) (e.g. Qformer [\[21\]](#page-8-16)) and Multi-Layer Perceptron (MLP) [\[9,](#page-8-8) [20,](#page-8-5) [24,](#page-8-6) [49\]](#page-9-6) based. Accordingly, for these two different perceive sampler methods, we adopt two distinct strategies for com-

pressing visual tokens. For a Q-former based approach, we control the token count for each frame by squeezing the number of query tokens. For a MLP based approach, we compress the image feature map size after the visual encoder using an average 2D pooling method. This video encoding process can be expressed with the following formula:

$$
\text{PerS}(\tilde{C}_i) = \begin{cases} \text{Query}(\text{Squareze}(q'), \text{Enc}(\tilde{C}_i)),\\ \text{MLP}(\text{Pooling}(\text{Enc}(\tilde{C}_i))), \end{cases} \tag{3}
$$

where  $q' \in \mathbb{R}^{s' \times d}$  and  $s' = s/\alpha$ , s is the number of query tokens initialized by the pre-trained model,  $\alpha$  is squeeze coefficient. During training, we reinitialize  $s'$  query tokens and reload the the pre-trained weights which been squeezed by average pooling with an interval of  $\alpha$ .

Moreover, to simultaneously accommodate long temporal information and spatial semantic signals, we adopt a slow-fast pathway strategy. The encoder operates on two distinct fps pathways and can be rewritten as:

$$
E^{\text{fast}} = \text{PerS}(\tilde{C}^{\text{fast}}),\tag{4}
$$

$$
E^{\text{slow}} = \text{PerS}(\tilde{C}^{\text{slow}}),\tag{5}
$$

where  $E^{\text{fast}}$  and  $E^{\text{slow}}$  represent different pathways visual tokens respectively.

<span id="page-4-4"></span>Slow Pathway Frames: This pathway operates at a lower frame rate where each frame occupies more tokens, effectively capturing abundant spatial semantic information. In the context of the slow pathway, where we designate the frame rate as  $f$  and the duration of a certain  $\text{clip}_{i}$ as  $t_i$ , each frame is encode into  $k$  tokens. Subsequently, we are able to derive that this particular segment yields  $e_i^{\text{slow}}$ tokens:

$$
e_i^{\text{slow}} = f \cdot k \cdot t_i. \tag{6}
$$

Fast Pathway Frames: In contrast, this pathway features a higher frame rate, encoding visual data where each frame occupies fewer tokens, providing a more detailed representation of rapidly changing scenes. Assume that the clip<sub>i</sub> in the fast pathway will be a high frame rate  $\beta \cdot f$ , with the same duration  $t_i$ , each frame will be encoded as  $k/\beta$  tokens, and finally we can get  $e_i^{\text{fast}}$  tokens:

$$
e_i^{\text{fast}} = \beta f \cdot k \cdot t_i / \beta = f \cdot k \cdot t_i. \tag{7}
$$

Thus, from Eq.  $(6)$  and Eq.  $(7)$ , it is evident that the number of tokens encoded per segment correlates directly with the video length. Consequently, this method adeptly handles videos of varying durations, seamlessly integrating extensive information on temporal changes and ample spatial semantics.

Finally, these visual tokens, combined with text tokens derived from product information  $X_p$  and specific requirements  $X_r$ , are encoded by  $\text{Emb}(\cdot)$  and then input into the LLM, which subsequently produces the output video draft.

$$
D_{(R_s, R_v, R_t)} = \text{LLM}(E^{\text{fast}}, E^{\text{slow}}, \text{Emb}(X_p), \text{Emb}(X_r)).
$$
\n(8)

#### <span id="page-4-3"></span>3.3. Text-Driven Controllable Editing

In practical applications, users have specific objectives for advertising videos, such as emphasizing key selling points or adhering to particular editing routines. When models fail to meet these requirements, content may become formulaic and fall short of expectations, diminishing effectiveness. To enhance model output controllability, we propose the use of free-prompt, enabling users to specify their requirements for tailored content. Defining the scope of free-prompt capabilities is essential, therefore, we identify key dimensions, including video duration, visual storyline, target audience, script routine, emphasis on selling points, avatar imagery, Text-to-Speech (TTS) timbre, and music style.

As shown in Fig. [3,](#page-4-2) we follow four key steps to construct high-quality free-prompt training data. Step 1: Deconstruction, we begin with a comprehensive deconstruction of the original video. Initially, Automatic Speech Recognition (ASR) and Optical Character Recognition (OCR) are used to extract the voice-over script and subtitle stickers.

<span id="page-4-2"></span><span id="page-4-0"></span>

Figure 3. Pipeline for generating free-prompt. We produce highquality free-prompt by the four-step process: deconstruction, analysis, generation, and verification. All experiments in this paper utilize the "gpt-4o-2024-08-06" version.

<span id="page-4-1"></span>Then, we utilize TransNet [\[35\]](#page-9-14) to determine the timestamps of the video clips. Sparse frames are extracted to generate video captions using MiniCPMV [\[45\]](#page-9-7). Leveraging the collected data, we utilize GPT-4o [\[1\]](#page-8-17) to recommend appropriate decorative element labels (see Appendix [6.9](#page-13-0) for details) for the original video. Step 2: Analysis, utilizing the deconstructed data along with predefined support dimensions, we employ GPT-4o to analyze and determine specific content for each dimension. For example, as shown in the Fig. [3,](#page-4-2) it is necessary to identify that the visual storyline pertains to a product user experience. Step 3: Generation, following the analysis, a free-prompt is generated to simulate real user requirements. To improve the generalizability, we randomly omit some dimensions during the requirement generation process. Step 4: Verification, since the generated free-prompt may contain inaccuracies, we implement a verification and revision mechanism. This involves reviewing and correcting the free-prompt, resuling in a 50.13% improvement in the free-prompt following (FPF) rate.

#### 4. Experiments

### 4.1. Data Collection

We compiled a dataset of 100K short videos centered around product marketing, predominantly featuring daily small commodities such as beauty products, food and beverages, and electronics, named as VideoAds dataset. Out of these, we designated 2K videos as the testing set and utilized the remaining for training. When constructing the data sample, we synthesize the instruction as shown in Fig. [2.](#page-3-0) Additionally, for the expected draft output, we assemble the video draft by generating the ASR, video clips, and decorative tags deconstructed in Section [3.3.](#page-4-3) Specifically, the ASR

<span id="page-5-1"></span>corresponds to the voice-over track of the draft. However, the text recognized by ASR sometimes contains errors and lacks punctuation, so we use GPT-4o for correction, subsequently restoring it to the voice-over track with timestamp for each sentence. For video clips, we incorporate negative sample clips to shuffle the order and record the correct clip sorting index to construct the video nodes track. Regarding the decorative element labels, we use the deconstructed labels as the content for the decorative settings. For detailed sample construction templates, see the Appendix [6.1.](#page-10-1)

Additionally, we utilized the Shot2story [\[14\]](#page-8-18) dataset to evaluate our method's shot sorting ability and shot caption generation capability on a public dataset, aiming to verify that our approach can be seamlessly applied to other video editing scenarios with minimal modifications.



Figure 4. Depiction of our VideoAds dataset distribution. (a) illustrates the distribution of the number of clips per data sample, encompassing both positive and negative clips, with a mean  $\mu_{\text{numClips}} = 5.88$ . (b) depicts the distribution of clip durations, with a mean  $\mu_{\text{clip}Duration} = 8.03$  seconds.

#### <span id="page-5-0"></span>4.2. Metrics Definition

Since our proposed task is explicitly defined within the video editing domain, employing the LLM metrics (such as BLEU [\[31\]](#page-9-15), ROUGE-L [\[23\]](#page-8-19), METEOR [\[7\]](#page-8-20) and CIDEr [\[39\]](#page-9-16)) commonly used in NLP does not offer significant value (but still report result in the Appendix [6.4\)](#page-10-2). Furthermore, drawing from our extensive practical experience, we define the evaluation indicators for this task as follows:

Clips Rank Accuracy (CRA): Measuring the accuracy of predicted video clip sequences, and it can be written as  $\text{CRA} = \frac{N_{\text{correct}}}{N_{\text{total}}} \times 100\%$ , where  $N_{\text{correct}}$  is the number of samples with all clips in the correct order, and  $N_{total}$  is the total number of samples.

Clips Selection Accuracy (CSA): Assessing the model's accuracy in selecting positive clips, this can be written as CSA =  $\frac{N_{\text{select}}}{N_{\text{total}}} \times 100\%$ , and where  $N_{\text{select}}$  is the number of samples that do not contain any negative clips and  $N_{\text{total}}$  is the total number of samples.

Free Prompt Following (FPF): Evaluating the model's ability to adhere to a free prompt using GPT-4o evaluation and assessed dimensions as section [3.3.](#page-4-3)

Visual Script Relevance (VSR): Assessing the correlation between visual imagery and the spoken script using the EMScore [\[33\]](#page-9-17), a higher score signifies stronger relevance.

Script Quality (SQ): Examining script quality using GPT-4o to evaluate four dimensions: Baisc, Native Language & Tone, Touch the Audience, and Creative Narrative.

Decorative Tags Precision / Recall (DTPR): Measures the precision and recall of recommended decorative element tags, including Avatar, TTS Timbre, and Music. So these can be defined as: Precision  $= \frac{N_{\text{TP}}}{N_{\text{TP}} + N_{\text{FP}}} \times 100\%$ , Recall =  $\frac{N_{\text{TP}}}{N_{\text{TP}}+N_{\text{FN}}} \times 100\%$ , where  $N_{\text{TP}}$ ,  $N_{\text{FP}}$  and  $N_{\text{FN}}$ are the number of tags for correctly, incorrectly and should been recommended but is not, respectively.

See more details for GPT-4o evalutation prompts in Appendix [6.3.](#page-10-3) In the Shot2story dataset, we use CRA and CSA to evaluate shots ranking and selection, and NLP metrics for caption generation.

#### 4.3. Training Details

In this work, we utilized several various multimodal models, including InternLM-XComposer [\[48\]](#page-9-0), InternVL [\[9\]](#page-8-8), LLaVA-NeXT series [\[20,](#page-8-5) [24,](#page-8-6) [49\]](#page-9-6), and MiniCPMV [\[45\]](#page-9-7), coupled with vision encoders such as CLIP [\[32\]](#page-9-18), EVA-CLIP [\[36\]](#page-9-19), SigLIP [\[46\]](#page-9-20), and InternViT-6B [\[9\]](#page-8-8). Base language models included InternLM-7B [\[37\]](#page-9-21), InternLM2- 20B [\[8\]](#page-8-21), and models from the LLaVA-NeXT series such as Vicuna-7B [\[10\]](#page-8-22), Mistral-7B [\[17\]](#page-8-23), along with Qwen variants [\[6,](#page-8-24) [43\]](#page-9-22). Experiments utilized 8 NVIDIA A100 GPUs across 40K iterations with the AdamW optimizer [\[26\]](#page-9-23) and a cosine learning rate decay [\[27\]](#page-9-24), starting at a rate of  $2 \times e^{-5}$ . During Supervised Fine-Tuning (SFT), the vision encoder weights were frozen. Meanwhile, the perceive sampler and the weights of the LLMs were actively fine-tuned to optimize performance.

#### 4.4. Automatic Evaluation Results

As shown in Table [1,](#page-6-0) we use the metrics described in Section [4.2](#page-5-0) to evaluate various models and configurations. Initially, we use GPT-4o as baseline model (detailed in the Appendix  $(6.5)$  $(6.5)$ . Due to the lack of fine-tuning, it exhibits significant disadvantages compared to fine-tuned models. For example, under the same 0.125 fps configuration (64 token setting for LLaVA-NeXT-Vicuna-7B, later simplified as Vicuna), GPT-4o underperforms Vicuna in most metrics, particularly in CRA (-26.70) and CSA (-45.11). However, benefiting from its strong general text generation ability, GPT-4o performs better than Vicuna in SQ (+3.36). Furthermore, we provide results for more multimodal models, which highlight that the InternLM-XComposer model achieves the highest performance in terms of the CRA (44.45) and CSA (89.76) metrics, and Mistral, InternVL, Qwen, and Vicuna perform best in FPF (91.00), VSR (23.62), SQ (78.29), and DTPR (80.54/80.28), respectively.

<span id="page-6-1"></span><span id="page-6-0"></span>

Model	<b>Visual Encoder</b>	Setting(fps/token)	CRA <sup>†</sup>	CSA <sup>†</sup>	FPF↑	VSR <sup>↑</sup>	SQ <sup>↑</sup>	<b>DTPR</b> <sup>↑</sup>
GPT-40		$0.125/-$	10.80	38.03	84.21	23.18	76.93	66.48/75.89
<b>Denser Frame</b>								
LLaVA-NeXT-Vicuna-7B [10]	CLIP $[32]+MLP$	0.125/1	28.37	55.64	$\overline{a}$		$\overline{a}$	
LLaVA-NeXT-Vicuna-7B	CLIP+MLP	2/1	29.24	55.36	89.74	23.23	74.44	78.92/79.72
LLaVA-NeXT-Vicuna-7B	CLIP+MLP	0.125/4	29.13	55.68			$\overline{a}$	
LLaVA-NeXT-Vicuna-7B	CLIP+MLP	2/4	32.07	76.25	90.07	23.53	74.21	80.54/80.28
InternLM-XComposer-7B [48]	EVA-CLIP $[36]+Q$ -former	0.125/1	42.19	89.65			$\overline{\phantom{a}}$	
InternLM-XComposer-7B	EVA-CLIP+O-former	2/1	44.45	89.76	90.88	23.51	76.17	78.26/79.34
InternLM-XComposer-7B	EVA-CLIP+O-former	0.125/4	39.49	87.24	$\overline{a}$	$\overline{a}$	$\overline{a}$	
InternLM-XComposer-7B	EVA-CLIP+O-former	2/4	40.72	80.02	89.90	23.42	75.48	77.88/78.53
LLaVA-NeXT-Mistral-7B [17]	CLIP+MLP	2/1	31.08	61.71	90.14	23.33	76.75	78.25/79.20
LLaVA-NeXT-Mistral-7B	CLIP+MLP	2/4	43.96	88.43	91.00	23.59	77.35	78.92/79.72
LLaVA-NeXT-Qwen-7B [6]	$SigLIP [46]+MLP$	2/1	29.43	58.90	89.97	23.22	78.29	77.69/79.70
LLaVA-NeXT-Owen-7B	SigLIP+MLP	2/9	39.66	85.84	90.72	23.54	78.11	78.12/80.22
Intern $VL-26B$ [9]	Intern $ViT$ [9]+MLP	2/1	41.69	85.22	90.47	23.61	75.85	79.68/80.14
InternVL-26B	InternViT+MLP	2/4	43.58	88.22	90.86	23.62	76.33	79.61/79.92
MiniCPMV2.6-7B [45]	SigLIP+Query	2/1	44.20	79.59	86.42	22.87	72.20	78.17/77.58
MiniCPMV2.6-7B	SigLIP+Ouery	2/4	38.73	73.01	86.77	23.13	70.14	77.40/77.02
<b>Slow-fast Strategy</b>								
LLaVA-NeXT-Vicuna-7B	CLIP+MLP	fast:2/4	32.07	76.25	90.07	23.53	74.21	80.54/80.28
LLaVA-NeXT-Vicuna-7B	CLIP+MLP	slow: 0.5/16	35.33	81.97	89.39	23.53	73.86	80.52/80.30
LLaVA-NeXT-Vicuna-7B	CLIP+MLP	slow:0.125/64	37.50	83.14	89.46	23.61	73.57	80.52/80.27
LLaVA-NeXT-Vicuna-7B	CLIP+MLP	fast: 2/4 slow: 0.5/16	37.01	82.37	90.37	23.61	74.96	80.74/80.72
LLaVA-NeXT-Vicuna-7B	CLIP+MLP	fast: 2/4 slow: 0.125/64	43.94	86.93	89.63	23.97	72.97	80.33/80.26
InternLM-XComposer-7B	EVA-CLIP+Q-former	fast:2/4	40.72	80.02	89.90	23.42	75.48	77.88/78.53
InternLM-XComposer-7B	EVA-CLIP+O-former	slow: 0.5/16	38.76	78.89	89.55	23.41	74.11	78.04/78.82
InternLM-XComposer-7B	EVA-CLIP+Q-former	slow:0.125/64	34.61	70.44	89.44	23.37	73.77	77.87/78.21
InternLM-XComposer-7B	EVA-CLIP+Q-former	fast: 2/4 slow: 0.5/16	43.91	87.77	90.32	23.56	74.87	78.26/79.27
InternLM-XComposer-7B	EVA-CLIP+O-former	fast: 2/4 slow: 0.125/64	45.91	89.53	90.41	23.55	74.94	77.91/79.02

Table 1. Performance analysis of different models using denser frame, and slow-fast strategy. We report the fps and the number of tokens encoded per frame, with the best performance marked in bold.

Verification of the Denser Slow-Fast Strategy. In the context of the Denser Frame strategy, from the results of the Vicuna and InternLM-XComposer, it is evident that the performance (CRA) at 2 fps surpasses that at 0.125 fps, regardless of whether the token setting is 1 or 4. This observation suggests that increasing the fps with a denser frame sampling effectively improves the model's temporal understanding of video sequences. More importantly, in the context of the Slow-fast Strategy, we also experimentally verified the effectiveness of the slow-fast strategy. Both Vicuna and InternLM-XComposer, with two sets of slow-fast experiment settings (fast: 2/4 + slow: 0.5/16 and fast: 2/4 + slow: 0.125/64), use the slow-fast strategy consistently outperforms using only slow or fast pathways separately. For example, for the InternLM-XComposer model, while the fast: 2/4 setting alone reached CRA 40.72 and CSA 80.02, integrating the slow pathway (slow: 0.125/64) elevated performance to CRA 45.91 and CSA 89.53, with improvements of approximately 5.19 and 9.51 points, respectively. This indicates that balancing detailed spatial information from the slow pathway and temporal dynamics from the fast pathway is crucial for optimal performance. From Fig. [5,](#page-7-0) we observe that increasing token numbers per frame from 1 to 64 results in opposing trends for CRA and CSA

7

in InternLM-XComposer (dropping from 42.19 and 89.65 to 34.61 and 70.44, respectively) and LLaVA-NeXT-Vicuna (increasing from 28.37 and 55.64 increasing to 37.50 and 83.14, respectively). This may be due to architectural differences: the MLP of LLaVA-NeXT-Vicuna handles larger token sizes efficiently, whereas the Q-former of InternLM-XComposer struggles with increased computational complexity and information focus.

Free-prompt Following Ability. From Table [1,](#page-6-0) we can see that our model exhibits strong free-prompt following ability, with FPF ranging from 86.42 to 91.00, attributed to our free-prompt construction pipeline. High-quality freeprompt and draft pairs significantly enhance output controllability. As for the specific dimensions, Fig. [6](#page-7-0) shows that LLaVA-NeXT-Mistral and LLaVA-NeXT-Qwen excel in free-prompt following across categories like Visual Storyline, Music, and TTS Timbre, with high scores of 16.47 and 16.40, 9.76 and 9.77, and 9.52 and 9.50, respectively. In contrast, MiniCPMV2.6 performs weaker, particularly in Visual Storyline (15.63) and Duration (9.21).

Script Quality & Decoration Evaluation. Fig. [1](#page-1-0) shows the quality of voice-over script perfectly meets the requirements of advertising narrative videos, with overall SQ scores ranging from 70.14 to 78.29 in Table [1.](#page-6-0) For the

<span id="page-7-0"></span>

Figure 5. Analyzing the impact of token numbers on CRA and CSA metrics  $(fps=0.125)$ .



Figure 6. Evaluating different models performance on free-prompt following (Qwen, fps/token:2/9, others, fps/token:2/4).



Figure 7. Evaluating different models performance on script quality (Qwen, fps/token:2/9, others, fps/token:2/4).

Fig. 7 reveals that LLaVA-NeXT-Qwen	Model	<b>TTS</b> Precisio		
orms well across all categories, including	LLaVA-NeXT-Vicuna	88.98		
iguage & Tone, Touch the Audience, and	LLaVA-NeXT-Mistral LLaVA-NeXT-Owen	89.03 89.16		
e. Table 1 shows the model has high accu-	InternLM-XComposer InternVL	88.26 89.18		
nding tags for decorative elements, with	MiniCPMV2.6	87.46		
rom 77.40/77.02 to 80.54/80.28. Effec- g multiple decorative elements is crucial d our model excels at this (see cases in	Table 2. Details of y (Qwen, fps/token:2/9			
Table 2 shows that model performance	Model	Basic		
omnonents (TTS Timbre Avatar Music)	$GPT-40$ <b>TT - 374 37-37T 37' </b>	3.55 201		

detailed aspects, consistently perfo Basic, Native Lan Creative Narrative racy in recommen DTPR ranging fr tively coordinating in production, and Appendix  $6.7$ ). across different co LLaVA-NeXT-Vicuna excels in most metrics. However, nearly all models have lower precision and recall for avatar, due to the higher complexity of avatar tags.

#### 4.5. Human Evaluation Results.

We have additionally executed human evaluations, categorized into five distinct components: Basic, Visual, Script, Voice (TTS), and Music. Each component is further subdivided into quality evaluation and follow-up ability assessment. The quality evaluation employs a 5-point scale, whereas the follow-up ability assessment utilizes a 3-point scale, with elevated scores signifying superior performance (see detailed criteria in Appendix [6.6\)](#page-11-1). As shown in Table [3,](#page-7-2) our finetuned model surpasses GPT-4o in both quality and follow-up ability, particularly demonstrating improvements in the Basic, Script, and Visual aspects with gains of 0.32, 0.43, and 0.38, respectively, in InternLM-XComposer.

#### 4.6. Transferability of Task in Shot2story.

Table [4](#page-7-3) evaluates the performance of LLaVA-NeXT-Vicuna and InternLM-XComposer on the Shot2story dataset. Through CRA and CSA, we can verify the efficacy of the slow-fast strategy. However, the slow-fast model of InternLM-XComposer performs less effectively than the single fast pathway model in generating shot captions. We attribute this to the large number of visual token inputs, which may negatively impact the text generation ability for this task. However, for the task on this dataset, we visualized the inference result and found that our model can

<span id="page-7-1"></span>Model TTS Timbre Avatar Music Average - Precision Recall Precision Recall Precision Recall Precision Recall Precision Recall Precision Recall LLaVA-NeXT-Vicuna | 88.98 93.65 | 73.65 65.87 | 78.98 81.33 | 80.54 80.28 LLaVA-NeXT-Mistral 89.03 93.36 69.62 66.14 78.1 79.66 78.92 79.72 LLaVA-NeXT-Qwen 89.16 93.07 67.51 68.11 77.69 79.48 78.12 80.22 InternLM-XComposer 88.26 91.29 67.99 65.96 77.4 78.34 77.88 78.53 InternLYL 89.18 92.98 71.24 66.47 78.42 80.3 79.61 79.92<br>
MiniCPMV2.6 87.46 89.16 68.26 64.52 76.47 77.37 77.40 77.02<br>
MiniCPMV2.6 87.46 89.16 68.26 64.52 76.47 77.37 77.40 77.02

various models on decorative tags generation (Qwen, fps/token:2/9, others, fps/token:2/4).

<span id="page-7-2"></span>

Model	Basic	Basic (FU)	Script	Script (FU)	Visual	Visual (FU)	Voice	Voice FU)	Music	Music (FU)
GPT-40	3.55	1.70	3.55	1.53	3.68	1.59	4.40	1.88	4.40	1.81
LLaVA-NeXT-Vicuna	3.81	1.83	3.78	1.64	3.75	1.71	4.59	1.85	4.52	1.82
InternLM-XComposer	3.87	1.76	3.98	1.75	4.06	1.77	4.59	1.89	4.52	1.82

Table 3. Human evaluation of GPT-4o, LLaVA-NeXT-Vicuna, and InternLM-XComposer (fps/token:0.125/64, FU is Follow-up).

<span id="page-7-3"></span>

Table 4. Evaluating performance on Shot2story dataset.

simultaneously and excellently complete shots ranking, selection, and caption generation (see the Appendix [6.8](#page-12-0) for details), validating our method's applicability to other editing scenarios.

### 5. Conclusion

We developed a unified video editing model for advertising marketing, leveraging multimodal Large Language Models. The model requires only product information and specific video requirements to autonomously generate a video editing draft. To handle more information and balance temporal and spatial dimensions, we compress visual token sizes and use a denser slow-fast approach to process frames effectively. Additionally, we implemented a free-prompt strategy, allowing users to specify textual requirements, enhancing output precision for practical business applications. Our model also adapts easily to other editing scenarios with minimal modifications.

#### References

- <span id="page-8-17"></span>[1] Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia Leoni Aleman, Diogo Almeida, Janko Altenschmidt, Sam Altman, Shyamal Anadkat, et al. Gpt-4 technical report. *arXiv preprint arXiv:2303.08774*, 2023. [5,](#page-4-4) [1](#page-0-0)
- <span id="page-8-9"></span>[2] Gulrukh Ahanger and Thomas DC Little. Automatic composition techniques for video production. *IEEE Transactions on Knowledge and Data Engineering*, 10(6):967–987, 1998. [3](#page-2-0)
- <span id="page-8-0"></span>[3] Jean-Baptiste Alayrac, Jeff Donahue, Pauline Luc, Antoine Miech, Iain Barr, Yana Hasson, Karel Lenc, Arthur Mensch, Katherine Millican, Malcolm Reynolds, et al. Flamingo: a visual language model for few-shot learning. *Advances in neural information processing systems*, 35:23716–23736, 2022. [1,](#page-0-0) [3](#page-2-0)
- <span id="page-8-14"></span>[4] Ido Arev, Hyun Soo Park, Yaser Sheikh, Jessica Hodgins, and Ariel Shamir. Automatic editing of footage from multiple social cameras. *ACM Transactions on Graphics (TOG)*, 33(4):1–11, 2014. [3](#page-2-0)
- <span id="page-8-12"></span>[5] Dawit Mureja Argaw, Fabian Caba Heilbron, Joon-Young Lee, Markus Woodson, and In So Kweon. The anatomy of video editing: A dataset and benchmark suite for ai-assisted video editing. In *European Conference on Computer Vision*, pages 201–218. Springer, 2022. [3](#page-2-0)
- <span id="page-8-24"></span>[6] Jinze Bai, Shuai Bai, Yunfei Chu, Zeyu Cui, Kai Dang, Xiaodong Deng, Yang Fan, Wenbin Ge, Yu Han, Fei Huang, et al. Qwen technical report. *arXiv preprint arXiv:2309.16609*, 2023. [6,](#page-5-1) [7](#page-6-1)
- <span id="page-8-20"></span>[7] Satanjeev Banerjee and Alon Lavie. Meteor: An automatic metric for mt evaluation with improved correlation with human judgments. In *Proceedings of the acl workshop on intrinsic and extrinsic evaluation measures for machine translation and/or summarization*, pages 65–72, 2005. [6](#page-5-1)
- <span id="page-8-21"></span>[8] Zheng Cai, Maosong Cao, Haojiong Chen, Kai Chen, Keyu Chen, Xin Chen, Xun Chen, Zehui Chen, Zhi Chen, Pei Chu, et al. Internlm2 technical report. *arXiv preprint arXiv:2403.17297*, 2024. [6](#page-5-1)
- <span id="page-8-8"></span>[9] Zhe Chen, Jiannan Wu, Wenhai Wang, Weijie Su, Guo Chen, Sen Xing, Muyan Zhong, Qinglong Zhang, Xizhou Zhu, Lewei Lu, et al. Internvl: Scaling up vision foundation models and aligning for generic visual-linguistic tasks. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 24185–24198, 2024. [3,](#page-2-0) [4,](#page-3-1) [6,](#page-5-1) [7](#page-6-1)
- <span id="page-8-22"></span>[10] Wei-Lin Chiang, Zhuohan Li, Zi Lin, Ying Sheng, Zhanghao Wu, Hao Zhang, Lianmin Zheng, Siyuan Zhuang, Yonghao Zhuang, Joseph E Gonzalez, et al. Vicuna: An open-source chatbot impressing gpt-4 with 90%\* chatgpt quality. *See https://vicuna. lmsys. org (accessed 14 April 2023)*, 2(3):6, 2023. [6,](#page-5-1) [7](#page-6-1)
- <span id="page-8-10"></span>[11] Tat-Seng Chua and Li-Qun Ruan. A video retrieval and sequencing system. *ACM Transactions on Information Systems (TOIS)*, 13(4):373–407, 1995. [3](#page-2-0)
- <span id="page-8-7"></span>[12] Xiaoyi Dong, Pan Zhang, Yuhang Zang, Yuhang Cao, Bin Wang, Linke Ouyang, Xilin Wei, Songyang Zhang, Haodong Duan, Maosong Cao, Wenwei Zhang, Yining Li, Hang Yan,

Yang Gao, Xinyue Zhang, Wei Li, Jingwen Li, Kai Chen, Conghui He, Xingcheng Zhang, Yu Qiao, Dahua Lin, and Jiaqi Wang. Internlm-xcomposer2: Mastering free-form textimage composition and comprehension in vision-language large model. *arXiv preprint arXiv:2401.16420*, 2024. [3](#page-2-0)

- <span id="page-8-3"></span>[13] Christoph Feichtenhofer, Haoqi Fan, Jitendra Malik, and Kaiming He. Slowfast networks for video recognition. In *Proceedings of the IEEE/CVF international conference on computer vision*, pages 6202–6211, 2019. [2,](#page-1-1) [3](#page-2-0)
- <span id="page-8-18"></span>[14] Mingfei Han, Linjie Yang, Xiaojun Chang, and Heng Wang. Shot2story20k: A new benchmark for comprehensive understanding of multi-shot videos. *arXiv preprint arXiv:2312.10300*, 2023. [6,](#page-5-1) [3](#page-2-0)
- <span id="page-8-4"></span>[15] De-An Huang, Shijia Liao, Subhashree Radhakrishnan, Hongxu Yin, Pavlo Molchanov, Zhiding Yu, and Jan Kautz. Lita: Language instructed temporal-localization assistant. *arXiv preprint arXiv:2403.19046*, 2024. [2,](#page-1-1) [3](#page-2-0)
- <span id="page-8-11"></span>[16] Bernd Huber, Hijung Valentina Shin, Bryan Russell, Oliver Wang, and Gautham J Mysore. B-script: Transcript-based broll video editing with recommendations. In *Proceedings of the 2019 CHI Conference on Human Factors in Computing Systems*, pages 1–11, 2019. [3](#page-2-0)
- <span id="page-8-23"></span>[17] Albert Q Jiang, Alexandre Sablayrolles, Arthur Mensch, Chris Bamford, Devendra Singh Chaplot, Diego de las Casas, Florian Bressand, Gianna Lengyel, Guillaume Lample, Lucile Saulnier, et al. Mistral 7b. *arXiv preprint arXiv:2310.06825*, 2023. [6,](#page-5-1) [7](#page-6-1)
- <span id="page-8-13"></span>[18] Mackenzie Leake and Wilmot Li. Chunkyedit: Text-first video interview editing via chunking. In *Proceedings of the CHI Conference on Human Factors in Computing Systems*, pages 1–16, 2024. [3](#page-2-0)
- <span id="page-8-15"></span>[19] Mackenzie Leake, Abe Davis, Anh Truong, and Maneesh Agrawala. Computational video editing for dialogue-driven scenes. *ACM Trans. Graph.*, 36(4):130–1, 2017. [3](#page-2-0)
- <span id="page-8-5"></span>[20] Feng Li, Renrui Zhang, Hao Zhang, Yuanhan Zhang, Bo Li, Wei Li, Zejun Ma, and Chunyuan Li. Llava-next: Tackling multi-image, video, and 3d in large multimodal models, 2024. [3,](#page-2-0) [4,](#page-3-1) [6,](#page-5-1) [1](#page-0-0)
- <span id="page-8-16"></span>[21] Junnan Li, Dongxu Li, Silvio Savarese, and Steven Hoi. Blip-2: Bootstrapping language-image pre-training with frozen image encoders and large language models. In *International conference on machine learning*, pages 19730– 19742. PMLR, 2023. [4](#page-3-1)
- <span id="page-8-2"></span>[22] Bin Lin, Bin Zhu, Yang Ye, Munan Ning, Peng Jin, and Li Yuan. Video-llava: Learning united visual representation by alignment before projection. *arXiv preprint arXiv:2311.10122*, 2023. [1,](#page-0-0) [3](#page-2-0)
- <span id="page-8-19"></span>[23] Chin-Yew Lin. Rouge: A package for automatic evaluation of summaries. In *Text summarization branches out*, pages 74–81, 2004. [6](#page-5-1)
- <span id="page-8-6"></span>[24] Haotian Liu, Chunyuan Li, Yuheng Li, Bo Li, Yuanhan Zhang, Sheng Shen, and Yong Jae Lee. Llava-next: Improved reasoning, ocr, and world knowledge, 2024. [3,](#page-2-0) [4,](#page-3-1) [6](#page-5-1)
- <span id="page-8-1"></span>[25] Haotian Liu, Chunyuan Li, Qingyang Wu, and Yong Jae Lee. Visual instruction tuning. *Advances in neural information processing systems*, 36, 2024. [1,](#page-0-0) [3](#page-2-0)
- <span id="page-9-23"></span>[26] I Loshchilov. Decoupled weight decay regularization. *arXiv preprint arXiv:1711.05101*, 2017. [6](#page-5-1)
- <span id="page-9-24"></span>[27] Ilya Loshchilov and Frank Hutter. Sgdr: Stochastic gradient descent with warm restarts. *arXiv preprint arXiv:1608.03983*, 2016. [6](#page-5-1)
- <span id="page-9-3"></span>[28] Ruipu Luo, Ziwang Zhao, Min Yang, Junwei Dong, Da Li, Pengcheng Lu, Tao Wang, Linmei Hu, Minghui Qiu, and Zhongyu Wei. Valley: Video assistant with large language model enhanced ability. *arXiv preprint arXiv:2306.07207*, 2023. [1,](#page-0-0) [3](#page-2-0)
- <span id="page-9-4"></span>[29] Muhammad Maaz, Hanoona Rasheed, Salman Khan, and Fahad Shahbaz Khan. Video-chatgpt: Towards detailed video understanding via large vision and language models. *arXiv preprint arXiv:2306.05424*, 2023. [1,](#page-0-0) [3](#page-2-0)
- <span id="page-9-8"></span>[30] Muhammad Maaz, Hanoona Rasheed, Salman Khan, and Fahad Khan. Videogpt+: Integrating image and video encoders for enhanced video understanding. *arXiv preprint arXiv:2406.09418*, 2024. [3](#page-2-0)
- <span id="page-9-15"></span>[31] Kishore Papineni, Salim Roukos, Todd Ward, and Wei-Jing Zhu. Bleu: a method for automatic evaluation of machine translation. In *Proceedings of the 40th annual meeting of the Association for Computational Linguistics*, pages 311–318, 2002. [6](#page-5-1)
- <span id="page-9-18"></span>[32] Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, et al. Learning transferable visual models from natural language supervision. In *International conference on machine learning*, pages 8748–8763. PMLR, 2021. [6,](#page-5-1) [7](#page-6-1)
- <span id="page-9-17"></span>[33] Yaya Shi, Xu Yang, Haiyang Xu, Chunfeng Yuan, Bing Li, Weiming Hu, and Zheng-Jun Zha. Emscore: Evaluating video captioning via coarse-grained and fine-grained embedding matching. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 17929– 17938, 2022. [6](#page-5-1)
- <span id="page-9-10"></span>[34] Enxin Song, Wenhao Chai, Guanhong Wang, Yucheng Zhang, Haoyang Zhou, Feiyang Wu, Haozhe Chi, Xun Guo, Tian Ye, Yanting Zhang, et al. Moviechat: From dense token to sparse memory for long video understanding. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 18221–18232, 2024. [3](#page-2-0)
- <span id="page-9-14"></span>[35] Tomás Soucek and Jakub Lokoc. Transnet v2: An effective deep network architecture for fast shot transition detection. In *Proceedings of the 32nd ACM International Conference on Multimedia*, pages 11218–11221, 2024. [5](#page-4-4)
- <span id="page-9-19"></span>[36] Quan Sun, Yuxin Fang, Ledell Wu, Xinlong Wang, and Yue Cao. Eva-clip: Improved training techniques for clip at scale. *arXiv preprint arXiv:2303.15389*, 2023. [6,](#page-5-1) [7](#page-6-1)
- <span id="page-9-21"></span>[37] InternLM Team. Internlm: A multilingual language model with progressively enhanced capabilities, 2023. [6](#page-5-1)
- <span id="page-9-11"></span>[38] Anh Truong, Floraine Berthouzoz, Wilmot Li, and Maneesh Agrawala. Quickcut: An interactive tool for editing narrated video. In *Proceedings of the 29th Annual Symposium on User Interface Software and Technology*, pages 497–507, 2016. [3](#page-2-0)
- <span id="page-9-16"></span>[39] Ramakrishna Vedantam, C Lawrence Zitnick, and Devi Parikh. Cider: Consensus-based image description evalua-

tion. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 4566–4575, 2015. [6](#page-5-1)

- <span id="page-9-12"></span>[40] Miao Wang, Guo-Wei Yang, Shi-Min Hu, Shing-Tung Yau, Ariel Shamir, et al. Write-a-video: computational video montage from themed text. *ACM Trans. Graph.*, 38(6):177– 1, 2019. [3](#page-2-0)
- <span id="page-9-9"></span>[41] Yi Wang, Kunchang Li, Xinhao Li, Jiashuo Yu, Yinan He, Guo Chen, Baoqi Pei, Rongkun Zheng, Jilan Xu, Zun Wang, et al. Internvideo2: Scaling video foundation models for multimodal video understanding. *arXiv preprint arXiv:2403.15377*, 2024. [3](#page-2-0)
- <span id="page-9-13"></span>[42] Yu Xiong, Fabian Caba Heilbron, and Dahua Lin. Transcript to video: Efficient clip sequencing from texts. In *Proceedings of the 30th ACM International Conference on Multimedia*, pages 5407–5416, 2022. [3](#page-2-0)
- <span id="page-9-22"></span>[43] An Yang, Baosong Yang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Zhou, Chengpeng Li, Chengyuan Li, Dayiheng Liu, Fei Huang, et al. Qwen2 technical report. *arXiv preprint arXiv:2407.10671*, 2024. [6](#page-5-1)
- <span id="page-9-2"></span>[44] Dingyi Yang, Chunru Zhan, Ziheng Wang, Biao Wang, Tiezheng Ge, Bo Zheng, and Qin Jin. Synchronized video storytelling: Generating video narrations with structured storyline. *arXiv preprint arXiv:2405.14040*, 2024. [1,](#page-0-0) [3](#page-2-0)
- <span id="page-9-7"></span>[45] Yuan Yao, Tianyu Yu, Ao Zhang, Chongyi Wang, Junbo Cui, Hongji Zhu, Tianchi Cai, Haoyu Li, Weilin Zhao, Zhihui He, et al. Minicpm-v: A gpt-4v level mllm on your phone. *arXiv preprint arXiv:2408.01800*, 2024. [3,](#page-2-0) [4,](#page-3-1) [5,](#page-4-4) [6,](#page-5-1) [7](#page-6-1)
- <span id="page-9-20"></span>[46] Xiaohua Zhai, Basil Mustafa, Alexander Kolesnikov, and Lucas Beyer. Sigmoid loss for language image pre-training. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 11975–11986, 2023. [6,](#page-5-1) [7](#page-6-1)
- <span id="page-9-5"></span>[47] Hang Zhang, Xin Li, and Lidong Bing. Video-llama: An instruction-tuned audio-visual language model for video understanding. *arXiv preprint arXiv:2306.02858*, 2023. [1,](#page-0-0) [3](#page-2-0)
- <span id="page-9-0"></span>[48] Pan Zhang, Xiaoyi Dong Bin Wang, Yuhang Cao, Chao Xu, Linke Ouyang, Zhiyuan Zhao, Shuangrui Ding, Songyang Zhang, Haodong Duan, Hang Yan, et al. Internlmxcomposer: A vision-language large model for advanced text-image comprehension and composition. *arXiv preprint arXiv:2309.15112*, 2023. [1,](#page-0-0) [3,](#page-2-0) [4,](#page-3-1) [6,](#page-5-1) [7](#page-6-1)
- <span id="page-9-6"></span>[49] Yuanhan Zhang, Bo Li, haotian Liu, Yong jae Lee, Liangke Gui, Di Fu, Jiashi Feng, Ziwei Liu, and Chunyuan Li. Llavanext: A strong zero-shot video understanding model, 2024. [3,](#page-2-0) [4,](#page-3-1) [6](#page-5-1)
- <span id="page-9-1"></span>[50] Deyao Zhu, Jun Chen, Xiaoqian Shen, Xiang Li, and Mohamed Elhoseiny. Minigpt-4: Enhancing vision-language understanding with advanced large language models. *arXiv preprint arXiv:2304.10592*, 2023. [1,](#page-0-0) [3](#page-2-0)

# Text-to-Edit: Controllable End-to-End Video Ad Creation via Multimodal LLMs

Supplementary Material

#### 6. Appendix

#### <span id="page-10-1"></span>6.1. Data Construction Templates

As illustrated in Fig. [9,](#page-11-2) this template is designed for data construction, offering a detailed example of our inputoutput structure. The process involves taking product information, materials (video clips) information, and specific requirements (free prompt) as input. For the details of the video clips, each clip includes its index, duration, and placeholders (like "<image>") for frames corresponding to different frame-rate pathways. Before entering the LLM, these placeholders are replaced with the respective visual tokens. Regarding the output, the model generates a video draft in JSON format, which includes the "voice over track", "video\_nodes\_track", and "decoration\_setting". In the "voice\_over\_track", it specifies the start and end times ("target\_start", "target\_end") for each voice-over sentence appearance in the video. The "video\_nodes\_track" includes the sequence of selected clips, where each clip comprises its index, start and end time of appearance ("target\_start", "target end"), and the start time of playback in the original clip ("source\_start"). Through the above simple formulation, we can clearly define the input and output of the model.

#### <span id="page-10-0"></span>6.2. Post-Processing and Transformation

<span id="page-10-5"></span>

Figure 8. Post-processing and rendering process.

Fig. [8](#page-10-5) depicts the post-processing of the modelgenerated draft and the subsequent rendering process into a final video. Initially, the draft generated by the model is parsed. We use the TTS timbre tags and avatar settings output by the model to match the corresponding voice-over timbre and the avatar's appearance. Simultaneously, the music tags are used to retrieve background music of the appropriate style. Next, we transform the voice-over content into TTS and submit the avatar rendering task to create the avatar narration video. We then adjust the video clips in the video nodes track to ensure alignment with the generated TTS and avatar video timelines. Finally, a new renderable video draft is generated and submitted for final rendering, producing the fully rendered video.

#### <span id="page-10-3"></span>6.3. Prompts for GPT-4o Evaluation

As mentioned in Section [4.2,](#page-5-0) the evaluations for freeprompt following capability and script quality are documented in the files "free\_prompt\_gpt4o\_eval.txt" and "script\_quality\_gpt4o\_eval.txt", respectively. For further details, please refer to the corresponding documents. Specifically, for the free-prompt evaluation, we use a total score of 100 points, distributed across various dimensions: Video Duration (10), Visual Storyline (20), Target Audience (10), Script Routine (10), Selling-points (20), Avatar (10), TTS Timbre (10), and Music (10). Similarly, for the script quality evaluation, the total score is 100 points, divided into the following categories: Basic  $(30)$ , Native Language & Tone (15), Touch the Audience (15), and Creative Narrative (40). Notably, within the script evaluation, we have included both good and bad examples to ensure that GPT-4o comprehends the specific details.

#### <span id="page-10-2"></span>6.4. LLM Metrics for Draft Evaluation

As mentioned in Section [4.2,](#page-5-0) we present the NLP metrics in Table [5.](#page-11-3) Notably, without fine-tuning, GPT-4o [\[1\]](#page-8-17) significantly underperforms compared to LLaVA-NeXT-Vicuna [\[20\]](#page-8-5) and InternLM-XComposer [\[48\]](#page-9-0) at the same fps settings (0.125fps). However, there is not much difference in these indicators in the denser, slow-fast strategy. This is because these indicators are used for machine translation and the draft generation task contains many common structured words, resulting in a relatively low proportion of truly meaningful words. Therefore, using typical NLP metrics for evaluation is not feasible.

#### <span id="page-10-4"></span>6.5. GPT-4o Draft Generation Details

To validate that our proposed method surpasses the GPT after fine-tuning, we developed a draft generation scheme based on GPT-4o, ensuring identical input and output conditions. The prompt used is detailed in the file "gpt4o\_gen\_draft\_prompt.txt". Due to the limitation on the number of input images for GPT-4o, we utilized an input rate of only 0.125 fps. Furthermore, to enhance the consistency of the model's output format, we incorporated fewshot examples as references within the prompt.

<span id="page-11-2"></span>*You are an advertising video editing assistant, and I hope you can help me edit an advertising video based on the information I provide:* 

#### *Product information:*

*{'product\_name': 'Javy Coffee Syrup', 'brand': 'Javy Coffee', 'selling\_points': ['low-carb', 'sugar-free', 'easy to make', 'delicious', 'instant latte', 'variety of flavors', 'no extra calories'], 'price': ''} Material information:* 

*{'clip\_0': {'0.125fps\_frames\_stream': "['<image><image>']", '2fps\_frames\_stream':* 

*"['<image><image><image><image><image><image><image><image><image><image><image><image><image><image><image><image><image><im age><image><image><imag e><image>']", 'duration': 11.8}, 'clip\_1': {'0.125fps\_frames\_stream': "['<image><image>']", '2fps\_frames\_stream':* 

*"['<image><image><image><image><image><image><image><image><image><image><image><image><image><image><image><image><image>']" , 'duration': 9.0}, 'clip\_2': {'0.125fps\_frames\_stream': "['<image>']", '2fps\_frames\_stream':* 

*"['<image><image><image><image><image><image><image><image><image><image><image><image><image><image><image>']", 'duration': 8.5}, 'clip\_3':* 

{'0.125fps\_frames\_stream': "|'<image>'|", '2fps\_frames\_stream': "|'<image><image><image><image>'/", 'duration': 2.8}, 'clip\_4': {'0.125fps\_frames\_stream': "|'<image>'|",<br>'2fps\_frames\_stream': "|'<image><image><image>=>|",

{'0.125fps\_frames\_stream': "['<image>']", '2fps\_frames\_stream': "['<image><image><image><image><image><image><image>'/", 'duration': 3.0}, 'clip\_7': {'0.125fps\_frames\_stream': "['<image><image><image><image><image><image>< *'duration': 7.8}, 'clip\_8': {'0.125fps\_frames\_stream': "['<image>']", '2fps\_frames\_stream': "['<image><image><image><image><image><image><image><image>']", 'duration': 4.0},* 

'clip\_9': {'0.125fps\_frames\_stream': "['<image><image>'|", '2fps\_frames\_stream':<br>"['<image><image><image><image><image><image><image><image><image><image><image><image><image><image><image><image><image><image><image><imag *e><image>']", 'duration': 11.5}}*

*There are also some specific requirements, please be sure to edit according to these requirements:* 

*Craft a 30-sec coffee ad showing a cozy homebrew routine. Highlight Javy's low-sugar syrup. Feature relatable creator enjoying a guilt-free latte. Voice-over: casual, friendly. Chill music. Include 'make it yours' vibe.*

*Please fully understand the above information and complete the video editing task. The output requirements are as this format(JSON format):* 

*{"voice\_over\_track": [{"text": "xxxx", "target\_start": 0, "target\_end": 2.1}, ...], "video\_nodes\_track": [{"clip\_idx": "xxx", "target\_start": 0, "target\_end": 2.3, "source\_start": 1.1}, ...], "decoration\_setting": {…}}*

# *Output:*  $\mathcal{S}% _{M_{1},M_{2}}^{\alpha,\beta}(\varepsilon)$

*{'voice\_over\_track': [{'text': ''Let's make a very cute low-carb sugar-free cookies and cream latte. '', 'target\_start': 0.0, 'target\_end': 3.6}, {'text': 'Start off with your very cute cup and fill*  it with some ice. ", 'target\_start': 3.6, 'target\_end': 7.1}, {'text': "To sweeten it, I'm gonna use a squirt or two of this skinny sauce, then I top everything off with milk.", 'target\_start': 7.1,<br>'target\_end': 12.3}, {' "target\_start': 17.4, "target\_end": 23.5}, {"text': "It's a delicious instant latte, no extra calories but bursting with flavor.", "target\_start': 23.5, "target\_end": 27.4}, {"text': "Enjoy it, link<br>"below!", "target\_start



<span id="page-11-3"></span>

Setting(fps/token)	<b>BLEU</b>	ROUGE-L	<b>CIDEr</b>	<b>METEOR</b>
$0.125/-$	21.24	43.99	8.70	50.27
0.125/1	26.93	48.75	33.40	63.28
2/1	26.91	48.64	32.18	63.43
0.125/4	26.87	48.80	32.97	63.51
2/4	28.01	49.23	32.80	63.55
0.125/1	23.45	46.43	27.47	63.10
2/1	23.60	46.59	29.12	63.35
0.125/4	23.51	46.60	27.55	63.70
2/4	23.15	46.25	27.56	62.86
2/1	27.51	49.25	36.37	63.18
2/4	29.36	50.34	41.32	63.84
2/1	26.55	48.50	32.99	62.11
2/4	28.98	49.58	33.58	62.44
2/1	23.84	47.08	30.17	64.01
2/4	24.02	47.19	31.10	64.09
2/1	26.72	47.46	32.32	60.01
2/4	26.05	46.90	31.55	59.33
fast:2/4	28.01	49.23	32.80	63.55
slow:0.5/16	28.77	49.53	33.29	63.97
slow:0.125/64	28.95	49.72	33.63	63.91
fast: 2/4 slow: 0.5/16	28.71	49.45	34.66	63.79
fast:2/4 slow:0.125/64	26.74	48.38	33.10	61.90
fast:2/4	23.15	46.25	27.56	62.86
slow:0.5/16	23.11	46.32	26.83	63.08
slow:0.125/64	23.51	46.60	27.55	63.69
fast: 2/4 slow: 0.5/16	22.52	45.80	27.81	62.66
fast:2/4 slow:0.125/64	22.52	46.17	28.00	62.85

Table 5. Details of the NLP metrics results.

#### <span id="page-11-1"></span>6.6. Human Evaluation Criteria

For the human evaluation, we recruited three experts from the video advertising production industry to assess generated videos by different models. As seen in Table [3,](#page-7-2) the average score from the three evaluators is used as the manual evaluation result. Additionally, the detailed evaluation criteria is provided in Table [6.](#page-14-0)

#### <span id="page-11-0"></span>6.7. Case Studies for Advertising Videos

In Fig. [10,](#page-12-1) we showcase additional videos generated by our method, demonstrating that our model consistently produces high-quality and controllable outputs. Furthermore, we provide the set of decorative element tags recommended by the model. For example, in case 1, our model recommends a "young female avatar" in a "kitchen setting", which matches the environment in the original video clips. This scene is enhanced by "popular" background music, appealing to the youthful audience targeted by the earbuds being sold. It is clear that the TTS timbre, avatar settings, and background music chosen by the model are seamlessly coordinated and align perfectly with the brand's identity and target audience.

<span id="page-12-1"></span>Case

#### *Product Info*

*Prodcut Name: Wireless Earbuds Brand: JLab Price: \$39. Selling-points: ['compact', 'noi. cancellation', 'touch control', 'crystalclear calls', 'perfect sound', '50% smaller case']* 

*Craft a 15-sec ad that hypes up the JLab JBuds Mini Earbuds' small size but powerful performance. Highlighting key features like noise cancellation. Set it in a relatable kitchen scene with a direct call to action. Keep the vibe upbeat and engaging, aimed at a young, tech-savvy audience.*

*Free prompt*

*Price: \$* 

**Case 2**



*Tired of bulky earbuds cramping your style? Meet the JLab JBuds Mini*—just \$39.99! These compact *powerhouses*  $noise$  *cancellation and touch control noise cancellation and touch control.*



*Experience crystal-clear calls and perfect sound, minus the bulk. Tap below for a 50% smaller case of sound.* 



# **Case 3**

*Prodcut Name: Curling Iron Selling-points: ['transforms curls', 'precision tool', 'creates tight consistent*  'precision tool', 'creates tight consis<br>curls', 'long-lasting', 'home styling',<br>'professional results', 'embrace curl *'professional results', 'embrace curl power']* 

#### *Free prompt*

*Create a 25-second ad with a focus on Wavytalk's precision curling wand. Highlight easy, at-home hair styling for salon-quality curls. Show a user creating tight curls, and include an empowering voice-over. Emphasize comfort and professional results. Keep it light-hearted and aspirational.*

Figure 10. More examples on VideoAds dataset.

*For a professional look, bring the salon home. Don't wait any longer, embrace your curl power.*

*secret weapon for those perfect ringlets.*

*15:7s, Clip\_2*

## <span id="page-12-0"></span>6.8. Case Studies for Shot2story Dataset

As shown in Fig [11,](#page-13-1) we define a new editing scenario on Shot2story [\[14\]](#page-8-18) dataset. The model's task is to identify all the shots that can be combined into a coherent storyline from a series of video shots, correctly sort these shots, and generate a caption for each one. Due to our denser slow-

*Achieve those tight, consistent curls that last, right in the comfort of your home.* 

> fast strategy, the model captures motion within the shots comprehensively. For example, in the caption of shot\_3 in case 2, the model perceives the movement of the camera and naturally transitions from "a man" to "pants". Similarly, in shot\_4 of case 3, it detects the scene switching from "the text on the whiteboard" to "strawberries".

*Tap to shop now and transform your curls!* 

*21:6s*

3

#### *Decorative Tags*

*{'music': {'music\_emotion': 'Happy', 'music\_genre': 'Pop'}, 'tts': {'age': 'Young', 'gender': 'Female', 'accent': 'American'}, 'avatar': {'gender': 'Female', 'age': 'Young', 'clothing\_style': 'Casual', 'scenes': 'Indoor kitchen', 'action\_type': 'Daily Routine'}}*

#### *Decorative Tags*

{'music': {'music motion':<br>'Chill', 'music\_genre': 'Pop'},<br>'tts: {'age': 'Young',<br>'gender': 'Female', 'accent':<br>'American'}, 'avatar':<br>{'gender': 'Female', 'age':<br>'Young', 'clothing\_style':<br>'Casual', 'scenes': 'Indoor *living room'}}*

*Decorative Tags*

*{'music': {'music\_emotion':*  'Happy', 'music\_genre':<br>'Pop'}, 'tas': '('age': 'Young',<br>'gender': 'Female', 'accent':<br>'American'}, 'avatar':<br>!'gender': 'Female', 'age':<br>'Young', 'clothing\_style': 'Long<br>'Casual', 'hair style': 'Long *hair shawl', 'scenes': 'Indo Bedroom'}}*

<span id="page-13-1"></span>

Figure 11. Examples on Shot2story dataset.

#### <span id="page-13-0"></span>6.9. Details of Decoration Tags

Table [7](#page-15-0) presents the labels of decorative elements, which are classed into three main categories: TTS, Avatar, and Music, containing 3, 14, and 2 subcategories respectively, accounting for a total of 98 labels. Notably, the Avatar category, having the highest number of labels, exhibits lower precision and recall as seen in Table [2.](#page-7-1) In practical applications, we enhance and enrich the final video quality and effect by retrieving the corresponding decorative elements based on the tags recommended by the model.

<span id="page-14-0"></span>

Table 6. Details of human evaluation criteria.

<span id="page-15-0"></span>

Table 7. Details of decorative element labels