Final design of Cerberus, a three-headed instrument for the OARPAF telescope

Davide Ricci^{a,*}, Lorenzo Cabona^b, Davide Greggio^a, Matteo Aliverti^b, Luciano Nicastro^c, and Luigi Lessio^a

^aINAF - Osservatorio Astronomico di Padova, Vicolo dell'Osservatorio 5, 35122 Padova, Italy. ^bINAF - Osservatorio Astronomico di Brera, Via E. Bianchi 46, 23807, Merate (LC), Italy. ^cINAF - Osservatorio di Astrofisica e Scienza dello Spazio (Italy).

ABSTRACT

Cerberus will be a new scientific instrument for the alt-az, 1m-class OARPAF telescope in Northern Italy. Currently, the telescope operates with a CCD camera used for imaging and photometry. One of the objectives of the project is to improve this observing mode with a tip-tilt lens for image stabilization up to 10Hz. Moreover, a long-slit spectroscopy at $R \sim 5900$ and an optical fiber échelle spectroscopy at $R \sim 9300$ observing modes will be included. These additional two "heads" of Cerberus will be exclusively selected by moving flat 45° mirrors by means of a linear stage placed in a new custom interface flange. The flange will replace the existing one, recovering the included field flattener lens, to ensure optical correction of the imaging channel. We present the already procured COTS hardware, the opto-mechanical design of the interface flange, the results of the Zemax ray tracing and the design of the web-based instrument control software.

1. INTRODUCTION

The Regional Astronomical Observatory of the Antola Park (OARPAF) is a 80cm, F8 Cassegrain alt-az telescope in the Ligurian Apennine.¹ One of the Nashmyth focal stations, dedicated to scientific observations, is provided by a flange with a field flattener lens for the correction of optical aberrations over a 45' unvignetted Field of View (FoV). Here, a SBIG scientific camera and a related filter wheel are placed. Scientific activities are carried out using this setup, that provides a diagonal FoV of 36', and are mainly focused on exoplanetary transit follow-up programmed by the students of the nearby University of Genoa, under the coordination of INAF researchers.²

Recently, consistent steps in the remotization of the structure have been made, by means of a custom, multi-layered python code that wraps telescope, dome, camera, and switches control software in an integrated web-based ecosystem.³ Latest developments, including a generalization to extend the software adoption in other same-class telescopes, is presented in this conference.⁴

To exploit all the didactic potential and improve the scientific return of the observatory, a new instrument called Cerberus was proposed.⁵ Cerberus aims to replace the current flange to add two new focal stations, orthogonal to the original one. The field flattener is recovered and included in a new flange. In the space between the telescope de-rotator interface and the field flattener, a linear motor supporting two folding mirrors is hosted. In the default position, the mirrors do not intercept the beam, that crosses the field flattener, a SBIG tip-tilt image stabilization system, and finally reaches the current filter wheel + camera setup. This is the first, upgraded, "imaging/photometry head". Otherwise, the linear motor inserts a folding mirror in the optical path. This mirror intercepts the beam before the field flattener, and reflects a $\approx 9.5'$ field towards the second, new "long slit spectroscopy head". A $\approx 4.5'$ fraction of this field, corresponding to the slit lenght (see next Sections), is effectively used. Finally, the linear motor can move forward to insert another folding mirror in the optical path. This mirror reflects a $\approx 9.5'$ field in the opposite direction, towards the third, new "service head" of Cerberus. As default, this last focal station will be equipped with an échelle spectrograph.

This project is thought from the beginning with the aim of embedding, in a single insrument, hardware that has already been procured by INAF and by the University of Genoa during several rounds of financements. Additional hardware has been specifically procured.

^{*}Contact information: davide.ricci@inaf.it

2. HARDWARE

Table 1. Telescope and institument parameters	
Parameter	Value
Transmitted field (towards field flattener)	36' diameter
Reflected field	9.5' diameter
Plate scale (from $0.29''/px$ on the imaging channel)	$3.22''/\mathrm{mm}$
Focal extraction (from mirror center to reflected focal plane)	151mm

Table 1. Telescope and instrument parameters

Here we list following the hardware material that has already been procured by the University of Genoa.

Imaging/photometry head: the following devices compose the "imaging/photometry head" of Cerberus:

• a SBIG STX-16801 4096 × 4096, 9µm pixels array CCD camera with a diagonal 36' FoV at a resolution of 0.29''/px; and a FW7-STX 7 position filter wheel. *UBVRI* standard Johnson-Cousins + $H\alpha$ filters + one position without filters are available. These two devices compose the imaging system currently operating at OARPAF. • a SBIG STX-Guider device as guiding camera, to be placed in front of the filter wheel, and provided with a $0.7 \times$ focal reducer. It is used to calculate tracking offsets for the telescope and to the following tip-tilt lens; • a SBIG AO-X tip-tilt lens, placed in front of the STX-Guider, to correct PSF wobbling at a 10Hz frequency. It is able to be tilted by up to $\pm 2.4^{\circ}$ to displace the field on the main camera up to $\pm 144\mu$ m, corresponding to $\pm 16px$ with an accuracy of 0.14px. Our simulations show that with a 3" seeing, and an exposure time of 0.1s, 50% of the pointings have more than one star brighter than V = 13 to be used as reference for the AO-X.⁵

Long slit spectroscopy head: the following devices compose the long slit channel of Cerberus. This mode requires a flat mirror to direct the light on a slit:

• LHIRES III spectrograph with two gratings available: 2400l/mm and 1200l/mm, that can be replaced by hand. The part of the light passing through the slit falls on a diffraction grating, that can be tilted by a micrometer screw, allowing to select a spectral range of ≈ 138 nm. Then, the light focuses on a CCD camera. We foresee a $R \sim 5800$ resolution in the visible band. LHIRES slit length is 8mm^{*} which covers a 4.5' FoV. • a SBIG STL-11000M camera with 9µm pixels. We estimate a maximum observable magnitude of $m_V \approx 10$, for a signal-to-noise ratio of 100 and 1 hour exposure with a sampling of 0.034nm/px on the above mentioned spectral range.

Service head: the following devices compose the default option for the third head of Cerberus. They are selected by a flat folding mirror:

• a FLECHAS⁶ échelle spectrograph with a 15m, optical fiber head with an effective resolving power $R \sim 9300$, increased to $R \sim 15000$ with an image slicer to suppress scintillation effects. • a ATIK11000M camera with 9µm pixels for the FLECHAS, providing a maximum of efficiency of $\approx 18\%$ at 555nm. The wavelength range of the spectrograph optics on the camera is 350–850nm.

Head selector: to embed this material in the Cerberus concept,

• a 150mm VT-80 62309150 PI linear stage has been provided by INAF. It will be used as the "head selector" motor; • a C-863.12 PI controller for the VT-80 has been specifically procured; • two 50mm right-angle prisms provided by Edmund Optics, alluminated on the long edge[†] together with optical bench material for the mounting, complete the selector.

^{*}https://www.shelyak.com/produit/spectroscope-lhires-iii/?lang=en#specifications-produit

[†]https://www.edmundoptics.eu/f/right-angle-mirrors/12280/

3. OPTICAL DESIGN



Figure 1. Optical quality on the reflected paths. The Field of View is expressed as its radius.

Given that Cerberus is a project aimed at the maximization of already procured hardware, we consider its optical design requirements as a-posteriori.

The first requirement is that the upgrades on the first "imaging photometry head", that introduce an additional backfocus to avoid mechanical overlapping with the field flattener, can be compensated by refocusing with the secondary mirror of the telescope without compromising the optical quality on the diagonal 36' FoV of the SBIG camera. This requirement is verified by Zemax simulations after a reverse-engineering of the field flattener lenses, which specifics are unknown, except from its mechanical footprint in the existing flange.

The second requirement is that the second "long slit spectrograph head" receives an unvignetted, not aberrated beam on all the 8mm slit length, which covers a 4.5′ diameter FOV. The third and final requirement is that the third "service head" allow the largest unvignetted, not aberrated FoV that do not limit the other "heads".

The reflected beams do not pass through the field flattener. The field aberration, quantified as the radius enclosing 90% of the energy, is shown in Fig. 3, and compared with the radius corresponding to a seeing of 1". The maximum reflected FoV is $\approx 9.5'$ (see Table 1), and corresponds to the point in which the telescope aberrations are comparable to a very good seeing conditions at OARPAF. This allows us to fulfill the second and the third requirement.

This $\approx 9.5'$ FoV is way more than sufficient to enlight the 8mm-width slit on the "long slit spectroscopy head", and at the same time gives to the "service head" a RMS spot radius without field flattener of 9.4µm. To fold this FoV, we purchased two off-the-shelf reflective right angle, 50mm short edge prisms with coating on the diagonal surface, in order to simplify the procurement and the alignment on the slit.

These dimensions also let enough stroke to the linear motor to transmit the 36' FoV when none of the mirrors is in the optical path.

4. MECHANICAL DESIGN

An Autodesk Inventor project has been set up to verify mechanical encumbrances. In particular, VT-80 motor has been placed on the "Service head" in order to avoid impacting with the LHIRES III.

The alluminated right-angle prisms intercept a fraction of the beam. This allows the external part of the field to reach the "imaging/photometry head" in any configuration. The can be further used for secondary guiding / calibration purposes.



Figure 2. Mechanical design including the PI stage, the right-angle reflecting prisms, and the three "heads": direct imaging, long slit spectroscopy, and the service head initially provided with a fiber coupler for échelle spectroscopy.

5. SOFTWARE DESIGN

Cerberus software will be an extension of the existing effort for the remotization of OARPAF,³ and that already provides a user friendly, web-based python environment to control the telescope, the dome, and power switches. The current setup also controls the camera + filter wheel, and the same HTTP API provided by SBIG also allows us to control the AO-X and the STX-Guider.

STL software will be developed using SBIG SDK, while for ATIK, Alpaca third-party drivers[‡] can be adapted. Finally, preliminary tests on the VT-80 PI stage using the Python pipython package have been successfully carried out.

While the path of in interfacing with the devices is traced, most of the effort of the software development is put in defining strategies to build robust calibration and observation routines. Given the didatical and scientific goal of the project, students of the University of Genoa will be involved.

6. CONCLUSION

We presented the final design of Cerberus, a new interface flange to embed existing hardware and decectors in an a multi-focal station instrument for OARPAF: a imaging/photometry station with tip-tilt corrector, a long slit spectroscopy station, and a service station initially equipped with an échelle spectrograph.

Optical design allowed us to verify the impact of the aberrations and the feasability, as well as defining the size of the plane mirrors that will fold the beam into the two new "heads". Mechanical design verified the mechanical footprint of the new components in a modular layout, so that the "service head" can be easily adapted to other instruments, and the mirrors on the linear motor do not affect the default "imaging/photometry" mode. The existing control software will be extended to the new components with the inclusion of new modules. All additional material opto-mechanical has been procured, and we are ready to build it!

[‡]https://github.com/msproul/AlpacaPi

ACKNOWLEDGMENTS

DR acknowledges Comitato Interministeriale per la Programmazione Economica (C93C23008400001).

REFERENCES

- Ricci, D., Cabona, L., Righi, C., La Camera, A., Nicolosi, F., and Tosi, S., "Technical and Software Upgrades Completed and Planned at OARPAF," in [*Revista Mexicana de Astronomia y Astrofísica Conference Series*], *Revista Mexicana de Astronomia y Astrofísica Conference Series* 53, 14–17 (Sept. 2021).
- [2] Ricci, D., Tosi, S., Cabona, L., Righi, C., La Camera, A., Marini, A., Domi, A., Santostefano, M., Balbi, E., Nicolosi, F., Ancona, M., Boccacci, P., Bracco, G., Cardinale, R., Dellacasa, A., Landoni, M., Pallavicini, M., Petrolini, A., Schiavi, C., Zappatore, S., and Zerbi, F. M., "Commissioning and improvements of the instrumentation and launch of the scientific exploitation of OARPAF, the Regional Astronomical Observatory of the Antola Park," *Journal of Astronomical Telescopes, Instruments, and Systems* 7, 025003 (Apr. 2021).
- [3] Ricci, D., Cabona, L., Tosi, S., and Zappatore, S., "Toward the remotization and robotization of the OARPAF Telescope," in [Observatory Operations: Strategies, Processes, and Systems IX], Adler, D. S., Seaman, R. L., and Benn, C. R., eds., Society of Photo-Optical Instrumentation Engineers (SPIE) Conference Series 12186, 121860P (Aug. 2022).
- [4] Ricci, D., Cabona, L., Salasnich, B., Nicastro, L., Fini, L., Damonte, A., Tosi, S., and Shibata, T., "Easy remote observations using web interfaces: controlling an italian telescope from japan, and more," in [Observatory Operations: Strategies, Processes, and Systems X], 13098–31, SPIE (June 2024).
- [5] Cabona, L., Ricci, D., Marini, A., Santostefano, M., Aliverti, M., La Camera, A., Righi, C., and Tosi, S., "Cerberus: A three-headed instrument for the OARPAF telescope," in [Ground-based and Airborne Instrumentation for Astronomy VIII], Evans, C. J., Bryant, J. J., and Motohara, K., eds., Society of Photo-Optical Instrumentation Engineers (SPIE) Conference Series 11447, 114475J (Dec. 2020).
- [6] Mugrauer, M., Avila, G., and Guirao, C., "Flechas-a new échelle spectrograph at the university observatory jena," Astronomische Nachrichten 335(4), 417–427 (2014).