PATCHEDSERVE: A Patch Management Framework for SLO-Optimized Hybrid Resolution Diffusion Serving

Desen Sun¹, Zepeng Zhao², and Yuke Wang³

¹University of Waterloo ²Carnegie Mellon University ³Rice University

Abstract

The Text-to-Image (T2I) diffusion model is one of the most popular models in the world. However, serving diffusion models at the entire image level faces several problems, especially when there are multiple candidate resolutions. First, image based serving system prevents requests with different resolutions from batching together. On the other hand, requests with hybrid resolutions also indicate diverse locality features, which makes it hard to apply the same cache policy to all of them.

To this end, we propose PATCHEDSERVE, A Patch Management Framework for SLO-Optimized Hybrid Resolution Diffusion Serving that provides a patch-level management strategy to gather hybrid resolution requests into batches. Specifically, PATCHEDSERVE incorporates a novel patch-based processing workflow, significantly enhancing throughput for hybrid resolution inputs. Furthermore, PATCHEDSERVE designs a patch-level cache reuse policy to fully exploit the redundancy in diffusion. In addition, PATCHEDSERVE features an SLO-aware scheduling algorithm with lightweight online latency prediction, achieving higher SLO satisfaction rates. We show that PATCHEDSERVE can achieve 30.1 % higher SLO satisfaction compared to SOTA diffusion serving system while not hurt the image quality.

1 Introduction

Over recent years, Text-to-Image (T2I) generation tasks have become increasingly popular and have been instrumental for many companies, including Google Imagen [40], Adobe Firefly [1], and OpenAI DALL·E [31]. Behind these successful applications, diffusion models have emerged as the dominant paradigm for image generation [8], primarily due to their ability to generate images with superior quality. T2I diffusion models synthesize images from Gaussian noises by iteratively denoising, leveraging both ResNet [13] and Transformer [43] architectures to create photorealistic images.

Despite their remarkable success, serving such models in real-world settings entails significant computational overhead due to several unique characteristics. First, unlike traditional CNN models (e.g., ResNet [14] and VGG [41]) with millisecond-scale latency or modern vision language models (e.g., LLaVA [23]) that achieve hundreds of frames per second, mainstream diffusion models typically require several seconds to generate a single image. For instance, it generally takes 3 to 4 seconds for the popular SDXL model [36] to generate one 512×512 image on a powerful NVIDIA H100 GPU). Second, real-world serving scenarios often involve simultaneous requests with varying image resolutions [31, 36], each with different latency requirements. For example, if a new request arrives when another request with a different resolution is being processed on the same GPU, the new request must wait until the previous one completes due to resolution mismatches. This results in prolonged execution times and inefficient GPU utilization.

Existing system optimizations for diffusion models primarily consider the simplified uni-resolution input settings and can be broadly categorized into two main approaches. One approach focuses on exploiting the computational parallelism of diffusion models, such as leveraging multiple GPUs or partitioning images into patches [20] for patch-level parallelism within a single request. However, these methods are limited to handling batches of images with identical resolutions and cannot exploit the opportunity to improve GPU utilization by batching images with misaligned shapes. Another line of research emphasizes harnessing the locality benefits of diffusion models. For instance, block caching [47] reduces computational complexity by caching intermediate states at each step. However, they can only profile the state change pattern at the granularity of entire images, overlooking the locality benefits at the finer granularity of image patches.

With the above insights, we propose a novel approach to optimize diffusion model systems by *reorganizing the input at the patch-level granularity*, enabling more flexible cache reuse and simplifying mixed-resolution batching. Our key observation is that most of the operations (e.g., Linear and Cross Attention) in diffusion models focus on "local" (small image patches) rather than "global" (entire image) in-



Figure 1: Multiple Requests Infer. (a) Serving system without patched inference. It fails to combine them into a single batch due to the diverse resolution. (b) The system that processes requests in patch granularity. Even with three requests in different shapes, it can split them to the same size of patches and better leverage GPU capacity, achieving higher throughput.

formation. These operations, originally designed for entire images, can be decomposed into mini-operations targeting small image patches. These small patches have the same shape thus we can easily batch them together. Based on this insight, we can reorganize images with different resolutions into patches with uniform shapes, derived from the common factors of their original dimensions, and then batch all patches together to process and schedule them more efficiently. For a simple illustration (Figure 1), there are three diffusion requests with different resolutions. If we serve these three requests directly, we have to process them sequentially due to misaligned input resolutions (Figure 1(a)). In such cases, GPUs are more likely to be underutilized since only one one resolution can be processed at a time. Alternatively, if we segment the requests into fine-grained image patches with the same shape, they can be processed in a batched mannar (Figure 1(b)). Once processed, the interrelated patches can be concatenated to reconstruct the complete images. With patching, the diffusion serving can exploit abundant locality and parallelism benefits across different levels of compute and memory hierarchies, including inter-patch computational parallelism and intra-patch data locality, to reducing the overall execution latency.

Despite such potential performance gains from patching, there are still several challenges preventing us from harvesting them. **First**, dividing an image into patches can lead to the loss of contextual information between them. For example, GroupNorm operations in U-Net-based diffusion models will calculate the mean and variance values of the entire image. Although it is easy to calculate these metrics for individual patches, it is difficult to calculate them for the whole image due to the extensive exchange of partial results across patches. **Second**, frequent caching operations can introduce severe overhead. To effectively reuse the patch-level cache while

preserving image quality, the system must identify which patch outputs are sufficiently similar to cached results from the previous computation. These decisions must be made online before processing each block, and this process is repeated hundreds of times during generation. Even worse, cache management operations (such as insert, delete, query, and re-organize) are not computationally light, demanding sophisticated design and optimization. Third, diverse SLO requirements add complexity to scheduling. In the real world, the SLO requirement is often $1-5 \times$ of the model execution latency [22], meaning the SLO requirements will always be different when the model latency changes. For instance, if a task with a higher resolution arrives earlier than one with a lower resolution, it is permissible for the larger task to be started later. The more candidate resolutions there are, the more diverse the SLO requirements will be. Such diversity will enlarge the scheduling searching space significantly, makes us hard to find the optimal solution.

To address these problems, we propose PATCHEDSERVE, A Patch Management Framework for SLO-Optimized Hybrid Resolution Diffusion Serving (Figure 10). The core idea of PATCHEDSERVE is to split images into smaller patches, leveraging the advantages of batching while managing the entire generation process at the patch level. First, PATCHED-SERVEensures accurate mapping of each patch to its original request and resolution, which is critical for efficient information completion. To achieve this, we design a customized format for patch management and introduce a patch edge stitching mechanism to mitigate the significant memory overhead associated with patch information exchange (Section 4). Secondly, to reduce computational costs, PATCHEDSERVE employs a patch-aware cache reuse strategy. While individual cache operations are expensive, batching multiple queries significantly improves overall efficiency. We implement a batchbased cache management system to minimize the overhead of frequent cache operations (Section 5). Finally, we observe that the latency for processing a batch of mixed-resolution requests is predictable due to its iterative-based execution pattern. PATCHEDSERVE incorporates an SLO-aware scheduling algorithm guided by the predicted latency to maximize the satisfaction across requests (Section 6).

To sum up, we make the following contributions:

- We propose a novel patch-based batching strategy to effectively handle mixed-resolution diffusion requests. It not only promotes processing parallelism and device utilization but also retains the context information.
- We introduce a patch-tailored online cache management policy to control caches more efficiently and exploit the abundant patch-level cache reuse opportunities.
- We implement a patch-aware scheduling algorithm with agile online latency prediction and dynamic batching to achieve higher SLO satisfaction and throughput.



Figure 2: Latent Diffusion Model. One diffusion model consists of multiple denoising steps. For each step, it processes the same basic model. There are two choices of backbones: U-Net and Diffusion Transformer (DiT).

• Evaluation reveals that PATCHEDSERVE can achieve an average 30.1% higher SLO satisfaction rates with minimum quality loss compared to the state-of-the-art solutions.

2 Background

2.1 Diffusion Models

Text-to-Image (T2I) diffusion model [9, 36] is a probabilistic model of unsupervised learning. Its training procedure consists of a forward Markov process that gradually blurs the information in the input image, followed by a backward process that attempts to remove such blurred noise, producing high-quality images from meaningless noises.

Figure 2 illustrates the workflow of T2I diffusion model. It takes one prompt and one Gaussian noise as input. The Prompt Encoder converts the given prompt to embeddings, which are used during every denoising step (some specific models may update the embeddings). The denoising step uses such embeddings to guide the noise prediction. For each step, the model predicts the potential noise in the original Gaussian noise and eliminates it from the input noise. The input noise will finally be a high-quality image after multiple denoising steps. Within the denoising component, two primary model architectures are commonly used, U-Net [31, 36, 38, 49] and Diffusion Transformer (DiT) [9,21,32,35]. U-Net is a popular model in vision tasks. It downsamples the given image and then upsamples it, which presents a "U" like structure in terms of hidden feature map size. In T2I diffusion models, U-Net comprises two major building blocks - the ResNet block and the Transformer block. The ResNet block hadles the downsampling and upsampling of noise, while the transformer block is to build the connection between the noise and the prompt. As for DiT, it only has transformer blocks. It first converts each pixel, or several pixels to tokens, then applies Self-Attention and Cross-attention operations to help guide noise prediction. After all of the denoising steps, a decoder helps scale up the current image to a larger resolution.



Figure 3: Two T2I diffusion optimization techniques. (a) Distrifusion [20] splits the image into multiple patches and dispatches them to different GPUs to process a single generation in parallel. (b) Block Caching [47] leverages the locality to save computations. It reuses output from the last step and starts the next block without processing the corresponding block in the current block.

T2I diffusion model suffers from heavy computation workload and iterative processing. For mixed resolution serving system, the performance turns worse because mismatched input (given Gaussian noise) and output (final image) shape prevent larger batch processing. It is critical to propose a technique to solve this problem.

2.2 System Optimizations for GenAI

To alleviate the heavy workload in T2I diffusion model, researchers have proposed many techniques. We first introduce them and demonstrate why these techniques don't work for the mixed-resolution scenario.

Acceleration for Transformer-based Model. Some previous works attempt to combine batch flexibly for transformerbased models [11,50]. ORCA [50] schedules requests at the iteration level which enables the system to tune batch at each iteration. Turbotransformer [11] simply pads requests with shorter sequence length. However, in T2I diffusion model, some key operators need to process different shapes of input when serving requests with different resolutions, which makes it hard to gain the benefits from batching with ORCA. Moreover, Turbotransformer requires to pad when serving two resolutions, which results in more overhead than benefits.

Parallelism Exploration with Patching. One innovative method is to split the whole image into several patches and combine these patches together to form a larger batch size. But current works [10, 20] fail to organize a larger batch. Figure 3(a) demonstrates how Distribusion [20] (the stateof-the-art patching technique) works. Distrifusion first splits the whole image into two patches and dispatches them to two GPUs. These two GPUs process the patches in parallel. To avoid the waiting time brought by synchronizing, Distrifusion processes AllGather operation asynchronously, and then scatter the state to each GPU. When operations are in demand of other patches' context, Distrifusion uses the saved state from the last step (the darker part) instead of the current one. By employing this approach, Distrifusion overlaps the communication overhead and computation, achieving better parallelism. However, this technique is not effective for mixed-resolution image generation for two reasons. First, it restricts the number of patches per request, distributing each request evenly across all GPUs, thereby preserving resolution differences even after splitting. Second, it lacks the capability to share context between patches within the same batch.

Locality Exploration with Caching Another technique is caching. Some researchers find that the blocks' outputs change gradually, which means that the output from the last step can be reused for the next step directly [27, 28, 47]. Figure 3(b) depicts the key idea of this kind of cache. For each block, block caching [47] saves their output. Consider that the model reaches Block-0 in Step-1. It is important to note that Block Caching has already stored the output of Block-0 from Step-0 as a cache. Therefore, Block Caching can either reprocess Block-0 or directly reuse the cached output. The decision to reuse the cache is determined through offline profiling. If the output of Block-0 in Step-0 consistently exhibits a high degree of similarity to the output of Block-0 in Step-1, Block Caching chooses to reuse the cached data. This approach results in a fixed, optimized model in which specific blocks are pre-determined to be skipped based on the profiling results.

3 Challenges and Motivations

Unlike Distrifusion [20], which utilizes patches to enhance parallelism, we propose aggregating multiple patches to maximize GPU resource utilization while employing Block Caching [47] to reduce computational overhead. However, several challenges must be addressed: *Inefficient patch index*, *mismatched skipped blocks*, and *explosive combination*.

Inefficient Patch Index: After splitting the whole image into patches, we need some extra indices to help us identify the patches from the same request or the same resolution. In T2I diffusion models, there are two kinds of operations that need extra context from other patches: *Convolution* and *Self-Attention*. Convolution requires other patches' boundaries to help maintain the current patch boundary's quality, while Self-Attention needs to calculate the interactive relation with all

the other patches from the same request (Figure 7). We want efficient patch management to record the patch indices so that we can process Convolution and Self-Attention in an accurate and efficient manner. Take Self-Attention as an example, a naive implementation is to simply note the first patch index and the last patch index for every request, and traverse the list to find the next request (Figure 6(b)). However, this implementation has two drawbacks: First, it has redundant memory access. To get the other patch indices from the same request or image, the system has to visit two arrays, and different patch access different location of these arrays, even if they are from the same request. Second, such discontinuous order in resolution prevents us from leveraging benefits from batching when processing some operations that has to be processed with the full image.

Mismatched Skipped Blocks: Some researchers propose an idea that uses the cache method to eliminate the redundant computation in T2I diffusion model [27, 47]. They usually provide a custom model that appoints some blocks that can use the results of the same block but from the last step. This kind of caching method is fixed and can't be modified with resolution or step changes, which is not flexible for a mixedresolution serving system. We hold an experiment to prove our insight. According to Block Caching [47], T2I diffusion model skips block whose result shows little difference from the result from the last step. They used a threshold σ to help identify whether the difference is small enough. In our evaluation, we use mean squared error (MSE), which is the most popular metric in machine learning, to get the difference and set the threshold as 0.1. We then select three resolutions, 512, 768, and 1024, and execute each of the resolutions for 1k times with different seeds. We then count how many blocks the request can skip and get the average value. Figure 4 illustrates the difference between different resolutions. As resolution changes, T2I diffusion model skips diverse blocks. Therefore, it is hard to give one custom model for multiple resolutions while maintaining the quality.

Explosive Combination To schedule requests while satisfying their SLO demand, the predicted latency for each request is critical. In other works, the researchers tend to profile the execution latency offline with different batch sizes and use these data online [3, 5, 39]. However, this technique does not work for mixed-resolution serving due to the explosive combination. We evaluate the difference among different combinations with the same batch size (We use the technique mentioned in Section 4 to support mix resolution batching). For 3 different resolutions, there are 8 combinations. We then compute the average latency of each of these combinations. Figure 5 demonstrates the diversity of the execution latency. Here, "SML" represents there is 1 request with a Small resolution, 1 request with a Medium resolution, and 1 request with a Large resolution. According to this figure, we can see that the latency can be very different even if the batch size is the same. The latency of 3 requests with large resolution is 68 % slower



Figure 4: Average savings from skipped computations.

Figure 5: Latency with same batch size but the

different combination.



Figure 6: Patch management policy. (a) Four input requests with different resolutions. Each resolution may have a different number of requests. (b) Record latent information for all patches. (c) Reorder and consider the patches as sparse arrays. (d) Use resolution offset and Request offset to help manage patches.

than small resolution. Thus, we have to profile the latency of all the combinations. Assuming that one GPU can contain at most M requests, and there are N choices of resolutions, then we need to hold $\sum_{i=1}^{M} C_{N-1}^{i+N-1}$ different choices. The number of combinations grows quickly with the maximum batch size and the kinds of resolution increasing. It is critical to get the latency without that much preparation for experiments.

However, we observe certain patterns in the system's latency behavior. First, latency is directly influenced by the number of pixels processed. As the T2I diffusion model generates more pixels, its processing speed decreases. Second, latency is also affected by the number of resolutions involved. We find that although "SML" computes fewer pixels than "MML", it may take longer time owing to an additional resolution "S". Therefore, it's necessary to build an ML-based predictor to help us predict the model latency.

4 Patched Inference with Batching

In this section, we first introduce how we manage the patches from different requests. Then we present how we address the missing context during the inference. To reduce the overhead of exchanging, we design a fused kernel to overlap data movement with other computations.

4.1 Offset Based Compression Format

After splitting images, there should be a batch of patches. Although most of the operators can be processed directly, some of them need context information to maintain high quality. These operators usually need information from other patches in the same image (e.g., Convolution and Self-Attention). However, if we record the position for each patch, we have to traverse the whole position list to collect other patches from the same image. On GPU, that means every thread accesses the whole list before start the real calculation, which brings much waste of the resource.

Compressed Sparse Row (CSR) in the sparse matrix for a

diverse range of irregular data structures (e.g., graphs), we design a novel Offset Based Compression (OBC) to manage the image patches efficiently (Figure 6). Assume there are 4 requests in waiting list sorted by their arrival time (Figure 6(a)). If we simply record the latent information for every patch (Figure 6(b)), not only do we waste memory space, but also miss the opportunity to gather all requests with the same resolution for some operators (like Self-Attention in Section 4.2.1). Therefore, we first reorder the requests by resolution and then treat them as sparse arrays (Figure 6(c)). For each sparse array, non-zero patches are always at the left-top position, therefore we don't need to log the location in images for patches but only record the request and resolution information. After compressing the batch of sparse images to a list of patches, we first note the offset of the first patch in every image (Figure 6(d)). We also write down the resolution offset for Self-Attention (We will discuss it in Section 4.2.1). Each thread holds the *index* of request offset which helps them identify the request the thread is processing. When one operator needs the context information, GPU can fetch other patches by simply traversing *RequestOffset[index]* to *RequestOffset*[*index* + 1].

4.2 Patch-Tailored Diffusion Operators

Most operators in diffusion models, such as Linear, FeedForward, and Cross Attention, are unaware of the global context from the whole image, thus we can call them "pixel-wise" operators. However, some other operators need to adjust for patched processing, otherwise we will get a dissected image.

4.2.1 Patch Information Completion

There are essentially two major operators in T2I diffusion model require extra information outside the current patch: *Self-Attention* and *Convolution*.

Patch-based Self-Attention: Self-Attention enables each pixel to gather associated information from all pixels in the same image. Self-Attention operates on three inputs: query,



Figure 7: Patch based operators in T2I diffusion model. A) Naive Self-Attention operator, which calculates the result with all other patches. B) Naive Convolution operator. Gather the boundaries from other patches and stitch them to the current patch. C) Boundary Stitcher that enables to stitch boundaries with GroupNorm.

key, and value, where each pixel or a fixed group of pixels represents a token. It first computes the dot product between the query (current token) and all keys (all tokens in the same image), applies a Softmax function to derive attention scores, and then computes another dot product with the values. For unpatched images, this process is straightforward. However, it becomes significantly more complex for patched images. As illustrated in Figure 7 A), accurate Self-Attention for patched requests requires each patch to consider all other patches from the same image in the computation. This Cartesian product relationship is challenging to incorporate into highly optimized kernels. Consequently, achieving precise results prompts reconstructing the full image from patches before performing Self-Attention. A larger batch size is always helpful even for a single operator. Therefore we propose to recover all the requests with the same resolution to enlarge batch size. By leveraging a Resolution Offset technique, all requests with the same resolution are easy to locate and recover, improving efficiency compared to processing each request individually.

Patch-based Convolution: Convolution operator takes a smaller kernel, called Filter, to help gather the adjacent pixels' features. The Filter size may range from 1 to 3 in T2I diffusion models [30, 36, 38]. If the filter size is larger than 1, the computation requires neighboring pixels. Figure 7 B) illustrates the differences between unpatched and patched convolution. In unpatched convolution, the filter traverses the entire image seamlessly. However, in patched convolution, challenges arise at patch boundaries. For instance, when the filter processes the bottom-right corner of P_1 , it requires boundary pixels from P_2 and P_3 . Similarly, P_1 also provides its boundary pixels to P_2 and P_3 . Implementing such boundary stitching is complex due to two types of diversity: (a) Direction Diversity. each patch must stitch both row and column boundaries. Since memory is row-major, stitching column boundaries results in discontinuous memory access. (b) Position Diversity. Different patches require stitching boundaries from distinct positions. For example, P_1 stitches boundaries

from the right and bottom, while P_4 stitches P_3 's boundary to its left and P_2 's boundary to its top. This diversity makes batch processing of stitch operations infeasible. To address this problem, we log the adjacency relationships during patch splitting. For each patch, we record the indices of its adjacent patches on the left, right, top, and bottom. During stitching, we process all patches uniformly.

4.2.2 Boundary Stitcher

We have discussed how we tune operators to maintain quality with patches. However, for convolution operators, simply stitching the edges with patches brings unacceptable overhead due to fragmented kernels (stitching both column and row from arbitrary other patches) and heavy pixel fetch cost.

To address this problem, we propose an boundary stitcher to reduce memory footprint with only one kernel. Our key observation is that convolution operations typically follow behind group normalization operations in U-Net-based T2I diffusion models [30,36,38]. Therefore, we suggest fusing the stitching kernels with GroupNorm operator rather than running them individually. As shown in Figure 7 C), we implement a novel write-back strategy to eliminate repetitive memory load and relocate the edge pixel to the expected location.

Assume that one input can be split into four patches P_1 - P_4 . Each thread block on GPU is in charge of one group's normalization of a single patch (Figure 7 C) (a)). After normalizing each pixel, the thread block will check if this pixel is at the boundary and if other patches require this pixel in the following convolution operation. We count this information when splitting the image, so we don't need to repeat this when stitching. If it is required, then the thread block first puts it to shared memory (Figure 7 C) (b)). After completing the current normalization, the thread block can stitch the edge pixels on shared memory to correspond patch's boundary no matter whether the patch completes its normalization (Figure 7 C) (c)). When processing follows convolution, we can



Figure 8: Patch-level cache reuse system overview.

start computing without padding.

5 Exploiting Patch-Level Locality

To maintain image quality and reduce computational overhead, we propose a patch-level cache reuse strategy. We make the decision whether to reuse the cache dynamically before each block. We only perform computation for patches exhibiting significant differences from the cached data. To minimize the overhead from cache operations, we employ a batch-based cache management system.

5.1 Patch-aware Caching Strategy

Figure 8 describes how patch-level cache works. This procedure occurs before every blocks in T2I diffusion models. When a new input comes, Cache Reuse Predictor (Later discussed in Section 7) compares input and cache from the last step (1). The predictor generates a mask indicating which patches can directly reuse the cache and which require recomputation of their output. (2). The input and generated mask are subsequently passed to T2I diffusion (3). For pixel-wise operators, processing unmasked patches alone is sufficient. However, as we mentioned in Section 4.2, certain operations require features from adjacent patches to preserve quality. Without additional processing, using masked patch values as input for these operations may result in mismatched shapes (U-Net-based T2I diffusion) or significant errors. Fortunately, Distrifusion [20] mentions that the outputs of operators from adjacent steps are sufficiently similar, allowing us to reuse the results from the previous step to fill the masked patches effectively. After processing the model, the system gets an output which part of it is imprecise due to the masked processing pattern. Therefore, we use the mask again to replace the masked patches with cache, which is generated from the last step (4). Finally, the system saves the input and output of this block for the next step.

5.2 Batching Patches in Cache

Since we should access cache every single operation to load or save data, it is obvious that cache management affects how many benefits we can receive from this patch-level caching system. In SD3 [9], it takes 40 to 50 ms to process one step with 24 blocks, which means we have to use less than 2 ms to complete all the cache operations, otherwise we cannot gain any profits even if all of the blocks can be skipped. To manage the cache system, we need to implement at least three operators: query, delete, and update/insert.

To efficiently manage the cache system, we implement a batching strategy to reduce the overhead associated with cache operations. For patch-level caching, a map structure is employed to store cache data, where each patch is assigned a unique identifier, and each block maintains its own cache system. Figure 9 illustrates our design. When a block needs to generate a mask or compute its masked output, it sends indices --- comprising each patch's unique ID and intermediate results ---- to the cache system as input. By comparing the input indices with the keys stored in the cache, the system identifies three distinct sets ((1)): The Common Set: is the set of IDs that exist in both the cache system and input indices. When new data comes, our cache system will check whether the input needs completion. Patches can be reused only when their indices are in this common set. If there is a patch that is masked and its index is not in the Common Set, we will through an error. The New Set is a set of IDs that are only in input indices, which will be inserted into the cache. After completing the input, the cache system should update all of the masked data and add all indices in New Set. The Expired Set is the set of IDs that only exist in the cache system. Since preemption is not allowed in PATCHEDSERVE, each patch will stay on GPU until it finishes. Once the cache system detects IDs that are only in the cache system, it can consider that the corresponding patch has exited. The data in the Common Set fills the masked position of input data (2). All of the unmasked parts need to be updated in the cache system. Cache system may lack some indices, and indices in New Set help complete that (3). Finally, the cache system deletes the expired cache in Expried Set ((4)).

6 PATCHEDSERVE Design

6.1 Overview

6.1.1 PATCHEDSERVE Work Flow

With the above techniques, we further implement **PATCHED**-**SERVE**, A Patch Management Framework for SLO-Optimized Hybrid Resolution Diffusion Serving. As shown in Figure 10, PATCHEDSERVEconsists of two main components: a *Scheduler* and a *Worker*. Specifically, the Scheduler consists of two main components: one *Schedule Predictor* and one *Schedule Decider*. When PATCHEDSERVE receives a new request, it will add the request to waiting queue first. The scheduler will recurrently get requests from the waiting queue as candidates. The Schedule Predictor (Section 6.1.2) can predict the possible throughput if the candidate request runs with the requests in active queue (1), which is the queue that holds all ongoing requests. The results will then be sent to the Schedule Decider. If the decider thinks PATCHEDSERVE can gain benefits from adding a new request, then it will be sent to the active queue, otherwise, the candidate request will back to the waiting queue until the next scheduled period (2).

In the worker, there is an Image Splitter that partitions all the requested images in the active queue into patches for better parallelism (3). This operation happens before every step in diffusion. Image splitter can split an image to arbitrary patch size. However, changing the patch size frequently would make the cache from the last step unusable due to different cache shapes and IDs, so we keep the patch size unchanged during the process. Before handling these patches, Mask Generator will generate a mask to find the patches that cannot reuse cache with the help of Cache Manager (4). The generated mask will also help Cache Manager maintain its cache by only updating and filling masked patches' data. If all patches are masked, then PATCHEDSERVE can skip one block directly and reuse the whole cache. If all patches are unmasked, where none of these patches can reuse the cache, PATCHED-SERVE process the T2I diffusion model without cache. But it still updates the cache for reuse in the next step. After all these preparations, the patch, mask, and cache will collectively guide the cache reuse process during denoising(**6**). Finally, an output with the same quality will be generated.

6.1.2 Mixed-Resolution Schedule Predictor

There are several key factors that affect schedule decisions: *task SLOs, resource utilization*, and *throughput trend*. For example, when the Schedule Decider attempts to add a new task to the active queue, this new task incurs additional overhead. While this may increase throughput, it also increases the latency for processing the batch, potentially causing some tasks in the batch to violate their SLO. On the other hand, if the active queue contains only a few requests, adding new ones would likely enhance throughput. However, if the number of requests in the active queue has already reached the GPU's capacity limit, further enlarging the queue becomes useless and may even hurt the performance.

To make more reasonable decisions, PATCHEDSERVE incorporates a component called *Schedule Predictor*, which forecasts the future latency of the potential active queue. If the analyzer predicts that adding a candidate request improves system throughput, the new task will be added to the active queue. Otherwise, the unscheduled tasks will wait until the next scheduling period. Typically, the time cost of a model, profiled offline, is often responsible for online estimation [3, 5, 39], as such scenarios involve relatively stable task components, where batch size is the primary variable. However, in our mixed-resolution T2I diffusion serving system, task resolution becomes an additional factor that must be considered. The vast number of potential task combinations makes it challenging to profile all possible scenarios offline. Since PATCHEDSERVE combines requests into a single batch to enhance GPU resource utilization and locality, the latencies of these tasks are generally less than the sum of their execution latencies in the order of resolution. Overestimating latency reduces the likelihood of incorporating new tasks, leading to lower throughput.

According to the above consideration, Schedule Predictor adopts Support Vector Regression (SVR) for time prediction. In this SVR model, we use the following features: the task number of each candidate resolution, the number of types of resolutions that exists, and the patch number. We create 300 diverse resolution combinations randomly and note their latencies as the dataset. Then we set 80 % of the dataset as the train set and 20 % as the test set. We find that the SVR model predicts the latency quite accurate (less than 5 in MSE metric) with negligible overhead.

6.2 Patch-based Scheduling Algorithm

An effective scheduling algorithm is critical for developing an efficient serving system. For mixed-resolution settings, each request has unique resolution and SLO requirements, and the system's ability to divide requests into arbitrary patch sizes further complicates the identification of an optimal scheduling strategy. Assume that there are M different kinds of resolution, and each resolution has N_i , $i \in M$ requests in waiting queue. For every resolution combination, PATCHEDSERVE can split it to arbitrary size of patches, and we suppose it has P_i choices. It is a large search space that the algorithm complexity will reach O(MNP). For each combination, we have to use Schedule Predictor to get their possible throughput, which is also time costly. It is really challenging to complete this schedule selection within a single schedule period.

To address this problem, we propose a heuristic schedule algorithm to optimize the scheduling time to an ideal level while maintaining high SLO satisfaction rates (Algorithm 1). First, we define the slack score for request i as:

$$Slack_i = \frac{DDL_i - C_i - P_i}{STANDALONE_i}$$

where DDL and STANDALONE represent the deadline time to meet SLO and model latency of request *i*, respectively. C_i is the time cost since task i arrived, and P_i means the predicted time of the remaining stages. The slack score describes the urgency of a request, with more urgent requests prioritized for earlier processing. Therefore, we sort all requests in waiting queue by slack score. This scheduling can be executed in parallel with denoising computation.



Figure 9: Batching Patches in Cache.

During scheduling, the scheduler the scheduler repeatedly accesses the waiting queue, selecting the most urgent request as the candidate. Then scheduler will use the predicted throughput from Schedule Predictor to make a decision. We define the benefits of adding a candidate requests i as:

$$Benefit_{i} = \frac{Throu_{.Cur.} \times Throu_{.Candidate}}{Throu_{.New} \times (Throu_{.Cur.} + Throu_{.Candidate})}$$
(1)

If the benefit is larger than a fixed threshold, then Schedule Decider adds the request to the active queue and finds the next candidate, otherwise, Schedule Decider puts the request back and stops scheduling. A threshold, which is a hyper-parameter, is based on the error range of the Schedule Predictor. As a predictor, the Schedule Predictor can't give a precise result, thus we use this threshold to put up such an error. If the candidate cannot catch its deadline even if our system starts processing it at once, then we just discard it without mercy, just like some other works did [22,45]. Additionally, if adding a new task to the active queue risks causing a timeout for any current task, the enqueue operation is halted (lines 9-11).

7 Implementation

We implement PATCHEDSERVE with 12.5K line of codes in Python and C++/CUDA based on PyTorch [33] framework. We implement the system's process in reference to vLLM [17]. We also port Stable Diffusion [44] to our framework and divide the whole model into three stages: Preparation stage, Denoising stage, and Postprocessing stage. This kind of decoupling enables us to schedule these three stages in different ways, such as using ORCA [50] batching strategy for denoising stage, and fcfs strategy for preparation and postprocessing since they are not iterative modules. Inside the T2I diffusion model, we package every module to control the data flow of splitted input. We further re-organize the common components of the sampler (Scheduler in Stable Diffusion) for allowing to denoise a batch of requests with various timesteps. We also apply xformers [18] on SDXL [36] and PATCHED-SERVE. We use Scikit-learn [34] to train the SVR predictor



Figure 10: Overview of PATCHEDSERVE.

Algorithm 1: PATCHEDSERVE schedule algorithm					
Input: wait_queue,active_queue					
Output: <i>active_queue</i>					
1 while True do					
$2 cur_task \leftarrow get_least_slack_task(wait_queue)$					
3 $act_task \leftarrow get_least_slack_task(active_queue)$					
4 /*Prefer tasks which can bring more throughput when					
queue is slack*/					
5 $pred_fut_iter_time \leftarrow$					
predictor(cur_task,active_queue)					
6 if <i>time_out</i> (<i>cur_task</i> , <i>pred_fut_iter_time</i>) then					
7 discards(cur_task)					
8 continue					
9 end					
10 /*Schedulability test*/					
11 if <i>time_out</i> (<i>act_task</i> , <i>pred_fut_iter_time</i>) then					
12 break					
13 end					
14 else if <i>speedup</i> (<i>pred_fut_iter_time</i>) then					
15 active_queue.enqueue(cur_task)					
16 end					
17 else					
18 break					
19 end					
20 end					

efficiently and cuML [37] for the cache predictor. For cache predictor, we use Random Forest Classifier on GPU to achieve both performance and accuracy. We collect the input and output similarities in MSE of all blocks in all timesteps for 1k inference requests. Then we train a classifier to help identify whether the patch can reuse the cache.

8 Experiment

In this section, we present how efficiently PATCHED-SERVE performs by the following evaluations.

Environment: We conduct experiments on a single server node with one H100 80GB HBM3 GPU and AMD EPYC 9534 64-Core CPU. The system on server is a docker image with Ubuntu 18.04 with CUDA 12.3. All experiments are based on Pytorch 2.2.2.

Models: We choose stable diffusion 3 [9] and stable diffusion-xl [36] as our text-to-image diffusion models. We set 50 denoising steps for both these two models as default. We use three the most common resolution choices, 512 [38,51], 768 [2,51], and 1024 [4,29], as our basic settings. For each model, we provide three options for users and use Small, Medium, and Large resolutions to help identify the relative resolutions. Float16 is the default data type in this paper unless specified.

Baseline: We compare PATCHEDSERVE with the following T2I diffusion research works or variants:(1) NIRVANA [2]: The state-of-the-art text to image diffusion serving system. Instead of reusing the previous cache as mentioned in NIR-VANA, we use fewer denoising steps to simulate the performance of NIRVANA, as derived from the data of their work. We also apply ORCA [50] method to help NIRVANA achieve higher batch size. (2) **Distrifusion** [20] is the start-of-the-art patch method for T2I diffusion model. It works on multiple GPUs and overlap the communication and computation to reduce model latency. Since it claims it will separate batches and process them one by one, we simply use the FCFS schedule method to serve requests. (3) PatchedCache: A variant of our method that applies both Patched Batching Inference and Patch-Level Cache. It uses an FCFS-like schedule method processes all the requests in the waiting list unless it reaches the limit of batch size. All of these schedule methods have a maximum batch size of 16.

Workload: We set COCO [6] and diffusiondb [46] as the dataset to check whether our method hurts the quality of generated images. We sample these two datasets into two subsets, each of which contains 5k text-image pairs to help get the quality metrics. We generate a data flow that satisfies Poisson distribution as previous research [12]. We assume that all resolutions contribute equally to the whole workload. According to Clockwork [12], the SLO requirement is often $1 - 5 \times$ of the model execution latency, thus we set our SLO requirement as $5 \times$ of each setting.

Metrics: We use SLO satisfaction, the ratio of requests that receive their results before the expected time, as the fundamental metric to show our performance. We will display how much PATCHEDSERVE outperforms compared to SOTA diffusion serving system and patch-based diffusion inference framework.

8.1 End-to-End Performance

In this section, we show the end-to-end performance of PATCHEDSERVE in default environment settings.

Performance: We first evaluate the performance of PATCHEDSERVE with various QPS (Query Per Second) for both two models. Since T2I Diffusion inference shows little performance change among different datasets, we only set diffusiondb [46] as the default database in performance



Figure 11: End-to-End SLO satisfaction ratio.

Table 1: CLIP Score (\uparrow)

SDXL [<mark>36</mark>]		SD3 [9]		
COCO	diffusiondb	COCO	diffusiondb	
[<mark>6</mark>]	[46]	[<mark>6</mark>]	[46]	
14.92	16.24	14.79	16.65	
15.43	16.62	15.13	17.06	
	SD COCO [6] 14.92 15.43	SDXL [36] COCO diffusiondb [6] [46] 14.92 16.24 15.43 16.62	SDXL [36] S. COCO diffusiondb COCO [6] [46] [6] 14.92 16.24 14.79 15.43 16.62 15.13	

evaluation.

Figure 11 displays the end-to-end performance in SLO satisfaction. We find that compared to the state-of-the-art cache serving system in diffusion models (NIRVANA), we can achieve 30.1 % higher SLO satisfaction on average while more than 99 % of requests receive their results in time. With the QPS increasing, PATCHEDSERVE indicates better performance than Mixed-Patch, proving our schedule algorithm's efficiency. PATCHEDSERVE achieve much better performance on SDXL than on SD3 due to more benefits from batch. We will show our analysis in Section 8.2 the difference between SDXL and SD3 when batch size increases. Therefore, the SLO drops quickly when QPS increases on SD3 but maintains almost the same on SDXL. Our schedule policy helps preserve higher SLO satisfaction on SDXL compared to Patched-Cache. This is because the difference in model latency among different resolutions is larger. For example, to generate one 1024×1024 image, SDXL takes $1.3 \times$ more time than generating one 512 \times 512. But for SD3, it will take more than 2.4 \times time. Such huge differences provide us with less potential to leverage the schedule sequence to satisfy more requests' requirements. To achieve 99 % [22, 45], 95 % [7, 19, 48], and 90 % [52] of the requests satisfying their SLO, PATCHED-SERVE supports $1.5 \times$, $1.12 \times$, $1.1 \times$ tighter workload on average.

We extend our experiments to multiple GPUs, utilizing 2, 4, and 8 H100 GPUs within a single node to measure the performance of our technique in larger-scale settings. Data parallelism is employed for all methods except Distrifusion to improve load balancing. Every time a new request comes, our scheduler selects the GPU with the least pixel generation ongoing and dispatches the request accordingly. Figure 12 and Figure 13 demonstrate how much our method



Figure 12: SDXL End-to-End SLO change with different number of GPUs.



Figure 13: SD3 End-to-End SLO change with different number of GPUs.

Table 2: FID [15] Score (\downarrow)

Method	SDXL [<mark>36</mark>]		SD3 [<mark>9</mark>]	
	COCO	diffusiondb	COCO	diffusiondb
	[6]	[46]	[<mark>6</mark>]	[<mark>46</mark>]
Original	31.92	35.56	28.94	32.38
PATCHEDSERVE	28.85	33.42	26.56	38.01

outperform than other methods. For all of these experiments, PATCHEDSERVE reaches the highest SLO satisfaction. In contrast, NIRVANA and Distrifusion exhibit opposing patterns – NIRVANA performs better under heavy workloads, while Distrifusion achieves high SLO satisfaction only with lighter workloads. NIRVANA, utilizing ORCA to construct batches, tends to keep requests with large resolutions on the GPU longer, allowing more time to insert new requests. This results in stable SLO satisfaction under heavy workloads. Distrifusion can only process requests one by one, making other requests wait for a long time, breaking their SLO.

8.2 **Optimization Analysis**

Quality: Table 1 summarizes the CLIP score of PATCHED-SERVE and the original model on COCO [6] and diffusiondb [46] datasets. CLIP score reflects the relativity between the



Figure 14: Latency Overhead from the extra operation in PATCHEDSERVE.

generated image and the provided prompts. The higher score is, the more relations the image shows with prompts. Table 2 presents the Fréchet Inception Distance [15] (FID) score between the generated images and the real images. Larger FID score indicates a worse generation since the distance is far away from the real images. The results show that PATCHED-SERVE can achieve similar FID and CLIP scores with the original one, which proves that PATCHEDSERVE only brings negligible accuracy loss.

Figure 14 illustrates the overhead of extra operations brought by PATCHEDSERVE. To implement PATCHEDSERVE, there are three kinds of additional operations: Split, Cache



Figure 15: Computation savings from patched and full image.

management, and Schedule. For the schedule, we have already overlapped it with model execution, thus we don't count its overhead. We then hold an experiment that counts the latency of the baseline, the PATCHEDSERVE, and another variant of PATCHEDSERVE - Patched Batching, which processes multiple requests in patch granularity without cache. We use the same three resolutions - 512, 768, and 1024. In Figure 14, the x-axis represents the batch size and the y-axis shows the latency. Here, when we comment that batch size is 3, we mean that there is 1 request for each of the 3 resolutions. For baseline, it can't gain benefits from multiple requests with blended resolutions. Therefore, if there are 12 requests waiting to be processed (4 requests for each resolution), it processes the corresponding model three times in sequence. Patched Batching depicts an average 13 % reduction in latency compared to the baseline. The overhead from splitting is tiny, especially in SD3 because it processes a sequence of tokens rather than two-dimension image-like latent state, which makes it easier to divide evenly. SDXL also indicates higher improvement owing to a smaller proportion of Attention operations, which makes it harder to gain benefits from batching than Convolution and Linear operations. With batch size increasing, benefits from patched batching decline because T2I diffusion model can also fully utilize GPU resources without our method. As for the patched cache method, SDXL displays higher performance. We will show that SDXL is more likely to skip blocks than SD3. Besides, it takes more time to process one block in SDXL than in SD3, which means we can achieve more time savings by reusing one patch in SDXL. We also find that SD3 spends more time in cache management due to more blocks per denoising step (24) than SDXL (7). However, we can find that the overhead is multiplying with batch size increase, indicating that our batching processing in cache works.

We conduct an experiment to compare the number of patches saved using patch-level caching versus whole image caching. These two methods correspond to two configurations: (1) each patch can skip the next block if it is similar to the cache, and (2) a block can only be skipped if all patches in the current batch are similar to the cache, as the previous method does not support patch-level cache reuse. They can only skip blocks when all these patches satisfy the constrain. The batch size used is the maximum capacity of our GPU. We measured the average latency of each request and the computational savings, defined as $(\frac{total_skiped_patches}{patch_num \times blocks_per_step_xstep_num})$. Figure 15 indicates that patch-level cache reuse outperforms whole-image caching for both models. While patch-level cache reuse saves more computations for resolution 512 than for resolution 1024 in SDXL, the latter achieves greater time savings due to the increased computational complexity of Self-Attention. SD3 shows less time savings than SDXL owing to less computation savings. Note that the computation savings in Figure 15 is a little different from in Figure 4 because the data in Figure 4 doesn't consider the cumulative error and only considers whether the current result is similar enough with the previous one. In practice, we limit the maximum reuse steps for each block, which means one single patch cannot skip the same block for N consecutive steps.

9 Related Works

Diffusion Optimizations. Besides splitting the request and caching the block outputs, there are also some other works that help improve the performance. NIRVANA [2] and Flex-Cache [42] propose approximate caching techniques to reuse the intermediate states across requests. DPM [24] DPM++ [25] and LCM [26] apply highly efficient sampling strategy to generate an image with fewer steps. These works target reducing expected denoising steps, while the cache method in PATCHEDSERVE aims to reduce computation while maintaining the same steps. All of these works focus on reducing denoising steps, which are orthogonal to PATCHEDSERVE. It's easy to integrate these advanced techniques into PATCHED-SERVE to further improve performance.

Similarity-driven Data Reuse. Similarity broadly exists in T2I diffusion models, inspiring various optimizing techniques. Beyond the caching methods discussed earlier, Cambricon-D [16] finds this similarity and only calculates the residual in an extremely low bit. FISEdit [51] transfers the multi-turn image generation task to the image editing task, introducing sparsity to reduce computations. We believe that there will be breakthroughs in the use of similarity in the future.

10 Conclusion

This paper proposes PATCHEDSERVE, A Patch Management Framework for SLO-Optimized Hybrid Resolution Diffusion Serving. With the help of patch-based mixed-resolution inference and patch-level cache reuse strategy, PATCHED-SERVE succeeds in combining batches of larger size regardless of resolutions, achieving better performance. In addition, PATCHEDSERVE presents an SLO-aware schedule algorithm to help meet more requests' SLO requirements. Our evaluation shows that PATCHEDSERVE achieve an average 30.1% higher SLO satisfaction than the state-of-the-art T2I diffusion serving system while more than 99 % of requests receive their results in time. In addition, we further prove that our system is easy to scale up to a larger distributed environment and still outperforms the most advanced patch-based diffusion research.

References

- [1] Adobe. Create with adobe firefly generative AI. https: //www.adobe.com/products/firefly.html, 2023.
- [2] Shubham Agarwal, Subrata Mitra, Sarthak Chakraborty, Srikrishna Karanam, Koyel Mukherjee, and Shiv Kumar Saini. Approximate caching for efficiently serving Text-to-Image diffusion models. In <u>21st</u> <u>USENIX Symposium on Networked Systems Design</u> <u>and Implementation (NSDI 24)</u>, pages 1173–1189, Santa Clara, CA, April 2024. USENIX Association.
- [3] Sohaib Ahmad, Hui Guan, Brian D. Friedman, Thomas Williams, Ramesh K. Sitaraman, and Thomas Woo. Proteus: A high-throughput inference-serving system with accuracy scaling. In <u>Proceedings of the</u> 29th ACM International Conference on Architectural <u>Support for Programming Languages and Operating</u> <u>Systems, Volume 1</u>, ASPLOS '24, pages 318–334, New York, NY, USA, 2024. Association for Computing Machinery.
- [4] Shekoofeh Azizi, Simon Kornblith, Chitwan Saharia, Mohammad Norouzi, and David J. Fleet. Synthetic data from diffusion models improves imagenet classification, 2023.
- [5] Jinyu Chen, Wenchao Xu, Zicong Hong, Song Guo, Haozhao Wang, Jie Zhang, and Deze Zeng. Otas: An elastic transformer serving system via token adaptation, 2024.
- [6] Xinlei Chen, Hao Fang, Tsung-Yi Lin, Ramakrishna Vedantam, Saurabh Gupta, Piotr Dollar, and C. Lawrence Zitnick. Microsoft coco captions: Data collection and evaluation server, 2015.
- [7] Ke Cheng, Zhi Wang, Wen Hu, Tiannuo Yang, Jianguo Li, and Sheng Zhang. Towards slo-optimized llm serving via automatic inference engine tuning, 2024.
- [8] Prafulla Dhariwal and Alexander Nichol. Diffusion models beat gans on image synthesis. In M. Ranzato, A. Beygelzimer, Y. Dauphin, P.S. Liang, and J. Wortman Vaughan, editors, <u>Advances in Neural Information</u> <u>Processing Systems</u>, volume 34, pages 8780–8794. Curran Associates, Inc., 2021.

- [9] Patrick Esser, Sumith Kulal, Andreas Blattmann, Rahim Entezari, Jonas Müller, Harry Saini, Yam Levi, Dominik Lorenz, Axel Sauer, Frederic Boesel, Dustin Podell, Tim Dockhorn, Zion English, Kyle Lacey, Alex Goodwin, Yannik Marek, and Robin Rombach. Scaling rectified flow transformers for high-resolution image synthesis, 2024.
- [10] Jiarui Fang, Jinzhe Pan, Xibo Sun, Aoyu Li, and Jiannan Wang. xdit: an inference engine for diffusion transformers (dits) with massive parallelism, 2024.
- [11] Jiarui Fang, Yang Yu, Chengduo Zhao, and Jie Zhou. Turbotransformers: an efficient gpu serving system for transformer models. In <u>Proceedings of the 26th ACM</u> <u>SIGPLAN Symposium on Principles and Practice of</u> <u>Parallel Programming</u>, PPoPP '21, pages 389–402, New York, NY, USA, 2021. Association for Computing Machinery.
- [12] Arpan Gujarati, Reza Karimi, Safya Alzayat, Wei Hao, Antoine Kaufmann, Ymir Vigfusson, and Jonathan Mace. Serving DNNs like clockwork: Performance predictability from the bottom up. In <u>14th USENIX Symposium on Operating Systems</u> <u>Design and Implementation (OSDI 20)</u>, pages 443–462. USENIX Association, November 2020.
- [13] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In Proceedings of the IEEE conference on computer vision and pattern recognition, pages 770–778, 2016.
- [14] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In <u>Proceedings of the IEEE Conference on Computer</u> <u>Vision and Pattern Recognition (CVPR)</u>, June 2016.
- [15] Martin Heusel, Hubert Ramsauer, Thomas Unterthiner, Bernhard Nessler, and Sepp Hochreiter. Gans trained by a two time-scale update rule converge to a local nash equilibrium. In I. Guyon, U. Von Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett, editors, <u>Advances in Neural Information Processing</u> Systems, volume 30. Curran Associates, Inc., 2017.
- [16] Weihao Kong, Yifan Hao, Qi Guo, Yongwei Zhao, Xinkai Song, Xiaqing Li, Mo Zou, Zidong Du, Rui Zhang, Chang Liu, Yuanbo Wen, Pengwei Jin, Xing Hu, Wei Li, Zhiwei Xu, and Tianshi Chen. Cambricond: Full-network differential acceleration for diffusion models. In <u>2024 ACM/IEEE 51st Annual International Symposium on Computer Architecture (ISCA)</u>, pages 903–914, 2024.
- [17] Woosuk Kwon, Zhuohan Li, Siyuan Zhuang, Ying Sheng, Lianmin Zheng, Cody Hao Yu, Joseph Gon-

zalez, Hao Zhang, and Ion Stoica. Efficient memory management for large language model serving with pagedattention. In <u>Proceedings of the 29th</u> <u>Symposium on Operating Systems Principles</u>, SOSP '23, page 611–626, New York, NY, USA, 2023. Association for Computing Machinery.

- [18] Benjamin Lefaudeux, Francisco Massa, Diana Liskovich, Wenhan Xiong, Vittorio Caggiano, Sean Naren, Min Xu, Jieru Hu, Marta Tintore, Susan Zhang, Patrick Labatut, Daniel Haziza, Luca Wehrstedt, Jeremy Reizenstein, and Grigory Sizov. xformers: A modular and hackable transformer modelling library. https: //github.com/facebookresearch/xformers, 2022.
- [19] Baolin Li, Siddharth Samsi, Vijay Gadepally, and Devesh Tiwari. Clover: Toward sustainable ai with carbon-aware machine learning inference service. In Proceedings of the International Conference for High Performance Computing, Networking, Storage and Analysis, SC '23, New York, NY, USA, 2023. Association for Computing Machinery.
- [20] Muyang Li, Tianle Cai, Jiaxin Cao, Qinsheng Zhang, Han Cai, Junjie Bai, Yangqing Jia, Ming-Yu Liu, Kai Li, and Song Han. Distrifusion: Distributed parallel inference for high-resolution diffusion models. In <u>Proceedings of the IEEE/CVF Conference</u> on Computer Vision and Pattern Recognition (CVPR), 2024.
- [21] Zhimin Li, Jianwei Zhang, Qin Lin, Jiangfeng Xiong, Yanxin Long, Xinchi Deng, Yingfang Zhang, Xingchao Liu, Minbin Huang, Zedong Xiao, Dayou Chen, Jiajun He, Jiahao Li, Wenyue Li, Chen Zhang, Rongwei Quan, Jianxiang Lu, Jiabin Huang, Xiaoyan Yuan, Xiaoxiao Zheng, Yixuan Li, Jihong Zhang, Chao Zhang, Meng Chen, Jie Liu, Zheng Fang, Weiyan Wang, Jinbao Xue, Yangyu Tao, Jianchen Zhu, Kai Liu, Sihuan Lin, Yifu Sun, Yun Li, Dongdong Wang, Mingtao Chen, Zhichao Hu, Xiao Xiao, Yan Chen, Yuhong Liu, Wei Liu, Di Wang, Yong Yang, Jie Jiang, and Qinglin Lu. Hunyuan-dit: A powerful multi-resolution diffusion transformer with fine-grained chinese understanding, 2024.
- [22] Zhuohan Li, Lianmin Zheng, Yinmin Zhong, Vincent Liu, Ying Sheng, Xin Jin, Yanping Huang, Zhifeng Chen, Hao Zhang, Joseph E. Gonzalez, and Ion Stoica. AlpaServe: Statistical multiplexing with model parallelism for deep learning serving. In <u>17th USENIX Symposium</u> on Operating Systems Design and Implementation (OSDI 23), pages 663–679, Boston, MA, July 2023. USENIX Association.

- [23] Haotian Liu, Chunyuan Li, Qingyang Wu, and Yong Jae Lee. Visual instruction tuning. <u>Advances in neural</u> information processing systems, 36, 2024.
- [24] Cheng Lu, Yuhao Zhou, Fan Bao, Jianfei Chen, Chongxuan LI, and Jun Zhu. Dpm-solver: A fast ode solver for diffusion probabilistic model sampling in around 10 steps. In S. Koyejo, S. Mohamed, A. Agarwal, D. Belgrave, K. Cho, and A. Oh, editors, <u>Advances in Neural Information Processing Systems</u>, volume 35, pages 5775–5787. Curran Associates, Inc., 2022.
- [25] Cheng Lu, Yuhao Zhou, Fan Bao, Jianfei Chen, Chongxuan Li, and Jun Zhu. Dpm-solver++: Fast solver for guided sampling of diffusion probabilistic models, 2023.
- [26] Simian Luo, Yiqin Tan, Longbo Huang, Jian Li, and Hang Zhao. Latent consistency models: Synthesizing high-resolution images with few-step inference, 2024.
- [27] Xinyin Ma, Gongfan Fang, Michael Bi Mi, and Xinchao Wang. Learning-to-cache: Accelerating diffusion transformer via layer caching. In <u>The Thirty-eighth Annual</u> <u>Conference on Neural Information Processing Systems</u>, 2024.
- [28] Xinyin Ma, Gongfan Fang, and Xinchao Wang. Deepcache: Accelerating diffusion models for free. In 2024 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR), pages 15762–15772, 2024.
- [29] Midjourney. midjourney. https://www.midjourney. com, 2023.
- [30] Alexander Quinn Nichol, Prafulla Dhariwal, Aditya Ramesh, Pranav Shyam, Pamela Mishkin, Bob Mcgrew, Ilya Sutskever, and Mark Chen. GLIDE: Towards photorealistic image generation and editing with textguided diffusion models. In Kamalika Chaudhuri, Stefanie Jegelka, Le Song, Csaba Szepesvari, Gang Niu, and Sivan Sabato, editors, <u>Proceedings of the 39th</u> <u>International Conference on Machine Learning</u>, volume 162 of <u>Proceedings of Machine Learning Research</u>, pages 16784–16804. PMLR, 17–23 Jul 2022.
- [31] OpenAI. Dalle 3 system card. https://cdn.openai. com/papers/DALL_E_3_System_Card.pdf, 2023.
- [32] OpenAI. Video generation models as world simulators. https://openai.com/index/ video-generation-models-as-world-simulators, 2024.
- [33] Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, Alban Desmaison, Andreas Kopf, Edward Yang, Zachary

DeVito, Martin Raison, Alykhan Tejani, Sasank Chilamkurthy, Benoit Steiner, Lu Fang, Junjie Bai, and Soumith Chintala. Pytorch: An imperative style, highperformance deep learning library. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett, editors, <u>Advances in Neural Information</u> <u>Processing Systems</u>, volume 32. Curran Associates, Inc., 2019.

- [34] Fabian Pedregosa, Gaël Varoquaux, Alexandre Gramfort, Vincent Michel, Bertrand Thirion, Olivier Grisel, Mathieu Blondel, Peter Prettenhofer, Ron Weiss, Vincent Dubourg, Jake Vanderplas, Alexandre Passos, David Cournapeau, Matthieu Brucher, Matthieu Perrot, and Édouard Duchesnay. Scikit-learn: Machine learning in python. J. Mach. Learn. Res., 12:2825–2830, nov 2011.
- [35] William Peebles and Saining Xie. Scalable diffusion models with transformers. In <u>2023 IEEE/CVF</u> <u>International Conference on Computer Vision (ICCV)</u>, pages 4172–4182, 2023.
- [36] Dustin Podell, Zion English, Kyle Lacey, Andreas Blattmann, Tim Dockhorn, Jonas Müller, Joe Penna, and Robin Rombach. Sdxl: Improving latent diffusion models for high-resolution image synthesis, 2023.
- [37] Sebastian Raschka, Joshua Patterson, and Corey Nolet. Machine learning in python: Main developments and technology trends in data science, machine learning, and artificial intelligence. <u>arXiv preprint arXiv:2002.04803</u>, 2020.
- [38] Robin Rombach, Andreas Blattmann, Dominik Lorenz, Patrick Esser, and Björn Ommer. High-resolution image synthesis with latent diffusion models. In <u>2022 IEEE/CVF Conference on Computer Vision</u> <u>and Pattern Recognition (CVPR)</u>, pages 10674–10685, 2022.
- [39] Francisco Romero, Qian Li, Neeraja J. Yadwadkar, and Christos Kozyrakis. INFaaS: Automated modelless inference serving. In <u>2021 USENIX Annual</u> <u>Technical Conference (USENIX ATC 21)</u>, pages 397– 411. USENIX Association, July 2021.
- [40] Chitwan Saharia, William Chan, Saurabh Saxena, Lala Li, Jay Whang, Emily L Denton, Kamyar Ghasemipour, Raphael Gontijo Lopes, Burcu Karagol Ayan, Tim Salimans, Jonathan Ho, David J Fleet, and Mohammad Norouzi. Photorealistic text-to-image diffusion models with deep language understanding. In S. Koyejo, S. Mohamed, A. Agarwal, D. Belgrave, K. Cho, and A. Oh, editors, <u>Advances in Neural Information Processing</u> <u>Systems</u>, volume 35, pages 36479–36494. Curran Associates, Inc., 2022.

- [41] Karen Simonyan and Andrew Zisserman. Very deep convolutional networks for large-scale image recognition, 2015.
- [42] Desen Sun, Henry Tian, Tim Lu, and Sihang Liu. Flexcache: Flexible approximate cache system for video diffusion, 2024.
- [43] A Vaswani. Attention is all you need. <u>Advances in</u> Neural Information Processing Systems, 2017.
- [44] Patrick von Platen, Suraj Patil, Anton Lozhkov, Pedro Cuenca, Nathan Lambert, Kashif Rasul, Mishig Davaadorj, and Thomas Wolf. Diffusers: State-ofthe-art diffusion models. https://github.com/ huggingface/diffusers, 2022.
- [45] Chunyang Wang, Yuebin Bai, and Desen Sun. Cd-msa: Cooperative and deadline-aware scheduling for efficient multi-tenancy on dnn accelerators. <u>IEEE Transactions</u> on Parallel and Distributed Systems, 34(7):2091–2106, 2023.
- [46] Zijie J. Wang, Evan Montoya, David Munechika, Haoyang Yang, Benjamin Hoover, and Duen Horng Chau. DiffusionDB: A large-scale prompt gallery dataset for text-to-image generative models. In Anna Rogers, Jordan Boyd-Graber, and Naoaki Okazaki, editors, Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), pages 893–911, Toronto, Canada, July 2023. Association for Computational Linguistics.
- [47] Felix Wimbauer, Bichen Wu, Edgar Schoenfeld, Xiaoliang Dai, Ji Hou, Zijian He, Artsiom Sanakoyeu, Peizhao Zhang, Sam Tsai, Jonas Kohler, Christian Rupprecht, Daniel Cremers, Peter Vajda, and Jialiang Wang. Cache me if you can: Accelerating diffusion models through block caching. In 2024 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR), pages 6211–6220, 2024.
- [48] Minghao Xie, Chen Qian, and Heiner Litz. En4s: Enabling slos in serverless storage systems. In <u>Proceedings</u> of the 2024 ACM Symposium on Cloud Computing, SoCC '24, page 160–177, New York, NY, USA, 2024. Association for Computing Machinery.
- [49] Jingyuan Yang, Jiawei Feng, and Hui Huang. Emogen: Emotional image content generation with text-to-image diffusion models. In <u>2024 IEEE/CVF Conference</u> on Computer Vision and Pattern Recognition (CVPR), pages 6358–6368, 2024.
- [50] Gyeong-In Yu, Joo Seong Jeong, Geon-Woo Kim, Soojeong Kim, and Byung-Gon Chun. Orca: A distributed serving system for Transformer-Based generative models. In 16th USENIX Symposium on Operating

Systems Design and Implementation (OSDI 22), pages 521–538, Carlsbad, CA, July 2022. USENIX Association.

- [51] Zihao Yu, Haoyang Li, Fangcheng Fu, Xupeng Miao, and Bin Cui. Accelerating text-to-image editing via cache-enabled sparse diffusion inference. <u>Proceedings</u> of the AAAI Conference on Artificial Intelligence, 38(15):16605–16613, Mar. 2024.
- [52] Yinmin Zhong, Shengyu Liu, Junda Chen, Jianbo Hu, Yibo Zhu, Xuanzhe Liu, Xin Jin, and Hao Zhang. Dist-Serve: Disaggregating prefill and decoding for goodputoptimized large language model serving. In <u>18th</u> <u>USENIX Symposium on Operating Systems Design</u> and Implementation (OSDI 24), pages 193–210, Santa Clara, CA, July 2024. USENIX Association.