# Indefinite causal order strategy nor adaptive strategy does not improve the estimation of group action

Masahito Hayashi<sup>1, 2, 3, \*</sup>

 <sup>1</sup>School of Data Science, The Chinese University of Hong Kong, Shenzhen, Longgang District, Shenzhen, 518172, China
 <sup>2</sup>International Quantum Academy, Futian District, Shenzhen 518048, China
 <sup>3</sup>Graduate School of Mathematics, Nagoya University, Nagoya, 464-8602, Japan

We consider estimation of unknown unitary operation when the set of possible unitary operations is given by a projective unitary representation of a compact group. We show that indefinite causal order strategy nor adaptive strategy does not improve the performance of this estimation when error function satisfies group covariance. That is, the optimal parallel strategy gives the optimal performance even under indefinite causal order strategy and adaptive strategy.

#### I. INTRODUCTION

Recently, indefinite causal order strategies and adaptive strategies have attracted significant attention in quantum information theory [1]. The papers [2-8] investigated the advantages of adaptive strategies for quantum channel discrimination without considering the asymptotic regime. Similarly, the paper [9] explored these advantages using indefinite causal order strategies. However, in the asymptotic setting, the benefit of adaptive strategies becomes less straightforward. The works [10-12] demonstrated that adaptive strategies provide no improvement for the asymmetric scenario of quantum channel discrimination, specifically the Stein-type bound, which extends the classical result from [13] to the quantum domain. Additionally, the paper [14] showed that adaptive strategies do not enhance discrimination performance in the symmetric setting for classical-quantum channels, where the input is classical and the output is quantum, also as an extension of [13]. However, [4, 14, 15] established that adaptive strategies do offer an advantage in the symmetric setting for fully quantum channel discrimination, where both the input and output systems are quantum.

A more practical scenario in this context is channel estimation. In studies using parallel strategies, quantum Fisher information and Cramér-Rao-type bounds simplify the problem to optimizing these quantities based on input state choice, a topic covered extensively in [16-27]. Recently, the papers [28-32] examined the advantages of adaptive and indefinite causal order strategies in terms of Fisher information. However, it is well-known that Fisher information does not fully describe the asymptotic behavior of estimation errors under Heisenberg scaling. To capture this behavior, direct evaluation of estimation errors, bypassing Fisher information and Cramér-Rao-type bounds, is necessary. When the set of unknown unitaries forms a (projective) unitary representation of a group, group representation theory provides a powerful approach [33–41]. This method yields optimal performance without requiring

asymptotic approximations. Although it predicts Heisenberg scaling, the optimal coefficient obtained differs from that predicted by Cramér-Rao methods [18, 39, 42–44]. Recently, [45] highlighted this discrepancy from the perspective of mutual information, underscoring the limited applicability of Cramér-Rao approaches under Heisenberg scaling.

This paper focuses on unitary operation estimation in a general setting, where the model forms a projective unitary representation of a group *G*. We address this problem within a comprehensive framework that includes all indefinite causal order strategies [1]. Surprisingly, even under this broad framework, the conventional parallel strategy remains optimal when the error function satisfies a covariance condition. In other words, the optimal performance achievable by any strategy is also attainable using a parallel strategy.

Our approach is as follows. We define a generalized positive operator-valued measure (GPOVM) for unitary operations associated with a projective unitary representation. Extending the concept of group covariant measurements from [46] and [47, Chapter 4] to GPOVMs, we develop a GPOVM version of the quantum Hunt-Stein theorem [46], [47, Theorem 4.3.1]. This theorem establishes that the optimal performance is achieved by a covariant GPOVM. Finally, we demonstrate that this performance is attainable using a parallel strategy with a detailed symmetric structure as described in [40]. In our analysis, we show that the action of any covariant GPOVM can be simulated using a parallel strategy. This simulation fixes the measurement while adapting the input state according to the chosen covariant GPOVM.

The remainder of this paper is structured as follows. Section II formulates our problem, encompassing both indefinite causal order and adaptive strategies [1, 28]. Section III provides a detailed analysis of the problem's structure. Section IV demonstrates that the optimal performance under the framework described in Section II can be achieved using a parallel strategy.

<sup>\*</sup> hmasahito@cuhk.edu.cn

(6)

## II. FORMULATION

Given a compact group *G* with Haar measure  $\mu$ , we consider *n* projective representations  $f_j$  on the quantum system  $\mathcal{H}_j$  for j = 1, ..., n. We are allowed to employ various strategy including adaptive strategy and indefinite causal strategy. To describe our general strategies, we describe each channel, i.e., each unitary action by  $d_j$  times of its Choi representation, where  $d_j$  is the dimension of the *j*-th system  $\mathcal{H}_j$ . We describe the unitary  $f_j(g)$  by  $|f_j(g)\rangle\rangle\langle\langle f_j(g)|$ . Here, when  $f_j(g)$  is a matrix  $\sum_{k,k'} u_j(g)_{k,k'} |k\rangle\langle k'|$ ,  $|f_j(g)\rangle\rangle$  is defined as

$$|f_j(g)\rangle\rangle := \sum_{k,k'} u_j(g)_{k,k'} |k,k'\rangle.$$
(1)

In this case, we denote the input and output systems by  $\mathcal{H}_{j,I}$  and  $\mathcal{H}_{j,O}$ , respectively. For example, when  $\mathcal{H} = \mathcal{H}_1 \oplus \mathcal{H}_2$ , we have

$$|I_{\mathcal{H}}\rangle\rangle = |I_{\mathcal{H}_1}\rangle\rangle \oplus |I_{\mathcal{H}_2}\rangle\rangle.$$
<sup>(2)</sup>

When  $\mathcal{H} = \mathcal{H}_1 \otimes \mathcal{H}_2$ , we have

$$|I_{\mathcal{H}}\rangle\rangle = |I_{\mathcal{H}_1}\rangle\rangle \otimes |I_{\mathcal{H}_2}\rangle\rangle.$$
(3)

A measurement operator  $T_k$  is given as a positive semidefinite operator over the system  $\otimes_{j=1}^n (\mathcal{H}_{j,I} \otimes \mathcal{H}_{j,O})$ . Here, we discuss what condition a measurement needs to satisfy. That is, for the set  $\{T_k\}$ , the operator  $\sum_k T_k$  needs to satisfy a certain condition. We clarify this condition.

Now, the whole system is  $(\bigotimes_{j=1}^{n} \mathcal{H}_{j,I}) \otimes (\bigotimes_{j=1}^{n} \mathcal{H}_{j,O})$ , the group *G* acts only on the output system  $\mathcal{H} := (\bigotimes_{j=1}^{n} \mathcal{H}_{j,O})$ , and the input system  $\mathcal{K} := (\bigotimes_{j=1}^{n} \mathcal{H}_{j,I})$  can be considered as multiplicity space. We denote the dimension of  $\mathcal{H}$  by *d*. So, dim  $\mathcal{K} = d$ . The application of *g* on  $\mathcal{H}$  is written as  $f(g) := \bigotimes_{j=1}^{n} f_j(g)$  and its state is written as  $|f(g)\rangle\rangle\langle\langle f(g)|$ . The average with respect to the Haar measure  $\mu$  is

$$\rho_{\mu} := \int_{G} |f(g)\rangle \langle \langle f(g)|\mu(dg).$$
(4)

Our strategy is written as a set of measurement operators  $\{M_k\}$ , where a measurement operator  $M_k$  is given as a positive semi-definite operator on  $\mathcal{H} \otimes \mathcal{K}$ . Since the full probability needs to 1 for any element  $g \in G$ , the set of measurement operators  $\{M_k\}$  needs to satisfy the condition

$$\operatorname{Tr}\left(\sum_{k}M_{k}\right)\rho_{\mu}=1.$$
(5)

In fact, indefinite causal order strategy [1, Eqs. (4),(5),(6)] and adaptive strategy [1, Eqs. (2) (3)], [28, Algorithm 1] satisfies at least the condition (5). Therefore, it is natural that any possible strategy needs to satisfy the condition (5).

In the following, we study the optimization of our measurement to estimate the unknown action  $g \in G$  under the condition (5). For this aim, we introduce covariant error function  $w(g, \hat{g})$ , where g is the true action and  $\hat{g}$  is our guess. Since the above case addresses only the case with discrete outcomes, we extend the condition (5) to the case with continuous outcomes. Our measurement is given as a generalized positive operator valued measure (GPOVM) M over the group G, which is formulated as a generalization of positive operator valued measure (POVM) [47] as follows. We denote the set of Borel sets of G by  $\mathcal{B}(G)$ . Then, a GPOVM M is given as a map from  $\mathcal{B}(G)$  to the set of positive semi-definite operators on  $\mathcal{K} \otimes \mathcal{H}$ . It needs to satisfies the conditions

 $M(\emptyset) = 0$ ,  $\operatorname{Tr} M(G) \rho_{\mu} = 1$ .

and

$$M(\cup_{j}B_{j}) = \sum_{j} M(B_{j}) \tag{7}$$

for countable Borel sets  $\{B_j\}_j$  with the condition  $B_j \cap B_{j'} = \emptyset$  with  $j \neq j'$ .

We introduce the covariant measurement, whose POVM version was introduced in [46], [47, Chapter 4]. We say that a GPOVM M is covariant when

$$M(B_g) := f(g)^{\dagger} M(B) f(g) \tag{8}$$

for  $B \in \mathcal{B}(G)$  and

$$B_g := \{gg'\}_{g' \in B}.$$
 (9)

Hence, a covariant GPOVM M is written as

$$M(B) = \int_{B} M_{g} \mu(dg).$$
 (10)

In particular, we have  $M_g = f(g)^{\dagger} M_e f(g)$  so that we have

$$M(B) = \int_{B} f(g)^{\dagger} T f(g) \mu(dg), \qquad (11)$$

where we denote  $M_e$  by T. Then, the condition (6) implies

$$\operatorname{Tr} T \rho_{\mu} = \operatorname{Tr} T \int_{G} f(g) \rho_{\mu} f(g)^{\dagger} \mu(dg)$$
$$= \operatorname{Tr} \int_{G} f(g)^{\dagger} M_{e} f(g) \mu(dg) \rho_{\mu} = \operatorname{Tr} M(G) \rho_{\mu} = 1.$$
(12)

When  $M_e$  is given as a positive semi-definite operator T, the above GPOVM is written as  $M_T$ .

To study the precision of our measurement, we employ the estimation error  $w(g, \hat{g})$  between the true value g and our estimate  $\hat{g}$ . When our measurement is given by as GPOVM M, the average of w with the true g is given as

$$D_{w,g}(M) := \int_{G} w(g, \hat{g}) \operatorname{Tr} M(d\hat{g}) |f(g)\rangle \rangle \langle \langle f(g)|.$$
(13)

The Bayesian average under the Haar measure  $\mu$  is given as

$$D_{w,\mu}(M) := \int_{G} D_{w,g}(M)\mu(dg).$$
(14)

The minimax criterion focuses on the following value

$$D_w(M) := \max_{g \in G} D_{w,g}(M).$$
(15)

Holevo [46, Theorem 2], [47, Theorem 4.3.1] showed the equivalence between the minimax criterion and the Bayeian criterion with Haar measure in the state estimation, which is called the quantum Hunt-Stein theorem (Also, see [48, Theorem 4.1]). As shown below, we establish its extension to the GPOVM version, which shows the equivalence between the minimization of  $D_{w,\mu}(M)$  and the minimization of  $D_w(M)$ .

**Theorem 1.** When the estimation error  $w(g, \hat{g})$  satisfies the condition

$$w(g, \hat{g}) = w(g'g, g'\hat{g}) \tag{16}$$

for  $g, \hat{g}, g' \in G$ , we have

$$\min_{M:GPOVM} D_{w,\mu}(M) = \min_{M:cov. GPOVM} D_{w,\mu}(M)$$
$$= \min_{T:rank T=1,(12)} D_{w,\mu}(M_T)$$
$$= \min_{M:GPOVM} D_w(M) = \min_{M:cov. GPOVM} D_w(M).$$
(17)

*Proof.* Since the set  $\{M_T : \operatorname{rank} T = 1, (12)\}$  forms the set of extremal points of the set of covariant GPOVMs, we have the relation

$$\min_{M:\text{cov. GPOVM}} D_{w,\mu}(M) = \min_{T:\text{rank } T=1,(12)} D_{w,\mu}(M_T).$$
(18)

Next, we have the relations

$$\min_{\substack{M: \text{cov. GPOVM}}} D_w(M)$$

$$\geq \min_{\substack{M: \text{GPOVM}}} D_w(M) \geq \min_{\substack{M: \text{GPOVM}}} D_{w,\mu}(M). \quad (19)$$

and

$$\min_{M:\text{COV. GPOVM}} D_{w,\mu}(M) \ge \min_{M:\text{GPOVM}} D_{w,\mu}(M).$$
(20)

For a GPOVM *M* and an element  $g \in G$ , we define the GPOVM  $M_g$  as

$$M_g(B) := f(g)M(B_g)f(g)^{\dagger}$$
<sup>(21)</sup>

for  $B \in \mathcal{B}(G)$ . Then, we have

$$D_{w,g'}(M_g)$$

$$\stackrel{(a)}{=} \int_G w(g', \hat{g}) \operatorname{Tr} M_g(d\hat{g}) |f(g')\rangle\rangle \langle \langle f(g') |$$

$$\stackrel{(b)}{=} \int_G w(g', g\hat{g}) \operatorname{Tr} f(g) M(d\hat{g}) f(g)^{\dagger} |f(g')\rangle\rangle \langle \langle f(g') |$$

$$\stackrel{(c)}{=} \int_G w(g^{-1}g', \hat{g}) \operatorname{Tr} M(d\hat{g}) |f(g^{-1}g')\rangle\rangle \langle \langle f(g^{-1}g') |$$

$$= D_{w,g^{-1}g'}(M), \qquad (22)$$

where (*a*) follows from the definition (13) of  $D_{w,g'}(M)$  (*b*) follows from the definitions (9) and (21) of  $B_g$  and  $M_g$ , (*c*) follows from the condition (16). Thus,

$$D_{w,\mu}(M_g) \stackrel{(a)}{=} \int_G D_{w,g'}(M_g)\mu(dg')$$

$$\stackrel{(b)}{=} \int_G D_{w,g^{-1}g'}(M)\mu(dg') \stackrel{(c)}{=} D_{w,\mu}(M), \qquad (23)$$

where (*a*) follows from the definition (14) of  $D_{w,\mu}(M)$ , (*b*) follows from (22), and (*c*) follows from the invariance of Haar measure  $\mu$ . The covariant GPOVM  $\overline{M} := \int_G M_g \mu(dg)$  satisfies

$$D_{w,\mu}(\overline{M}) = \int_{G} D_{w,\mu}(M_g)\mu(dg) = D_{w,\mu}(M),$$
(24)

which implies the relation

$$\min_{M: \text{GPOVM}} D_{w,\mu}(M) \ge \min_{M: \text{cov. GPOVM}} D_{w,\mu}(M).$$
(25)

Also, we have

$$D_{w}(M_{g}) \stackrel{(a)}{=} \max_{g' \in G} D_{w,g'}(M_{g}) \stackrel{(b)}{=} \max_{g' \in G} D_{w,g^{-1}g'}(M) = D_{w}(M),$$
(26)

where (*a*) follows from the definition (15) of  $D_w(M)$  and (*b*) follows from (22). The covariant GPOVM  $\overline{M}$  satisfies

$$D_w(\overline{M}) \ge \int_G D_w(M_g)\mu(dg) = D_w(M), \qquad (27)$$

which implies the relation

$$\min_{M: \text{GPOVM}} D_w(M) \ge \min_{M: \text{cov. GPOVM}} D_w(M).$$
(28)

The combination of (18), (19), (20), (25), and (28) implies the desired relations.  $\Box$ 

#### **III. STRUCTURE OF GPOVM**

To study the minimization in Theorem 1, we need to discuss the structure of GPOVM. For this aim, we consider structure of representation space. We denote the representation on the first system  $\mathcal{H}$  as

$$\mathcal{H} = \bigoplus_{\lambda \in \hat{G}_f} \mathcal{U}_\lambda \otimes \mathbb{C}^{n_\lambda},\tag{29}$$

where  $n_{\lambda}$  expresses the multiplicity of the representation space  $\mathcal{U}_{\lambda}$ . Here, we denote the presentation on  $\mathcal{H}_{\lambda}$  by  $f_{\lambda}$ . We denote the set of irreducible representations appearing in *f* by  $\hat{G}_{f}$ . Then, the whose system is written as

$$\mathcal{H} \otimes \mathcal{K} = \left(\bigoplus_{\lambda \in \hat{G}_f} \mathcal{U}_{\lambda} \otimes \mathbb{C}^{n_{\lambda}}\right) \otimes \left(\bigoplus_{\lambda' \in \hat{G}_f} \mathbb{C}^{d_{\lambda'}} \otimes \mathbb{C}^{n_{\lambda'}}\right)$$
(30)

By considering (2) and (3), the application of g is written as

$$\begin{split} |f(g)\rangle\rangle &= f(g)|I_{\mathcal{H}}\rangle\rangle = f(g)\bigoplus_{\lambda\in\hat{G}_{f}}|I_{\lambda}\rangle\rangle\otimes|I_{n_{\lambda}}\rangle\rangle\\ &= \bigoplus_{\lambda\in\hat{G}_{f}}f_{\lambda}(g)|I_{\lambda}\rangle\rangle\otimes|I_{n_{\lambda}}\rangle\rangle = \bigoplus_{\lambda\in\hat{G}_{f}}|f_{\lambda}(g)\rangle\rangle\otimes|I_{n_{\lambda}}\rangle\rangle. \tag{31}$$

The average state  $\rho_{\mu}$  with respect to the Haar measure  $\mu$  is rewritten as

$$\rho_{\mu} = \bigoplus_{\lambda \in \hat{G}_{f}} d_{\lambda}^{-1} I_{\lambda} \otimes I_{\lambda} \otimes |I_{n_{\lambda}}\rangle\rangle\langle\langle I_{n_{\lambda}}|.$$
(32)

The condition (6) is rewritten as

$$\sum_{\lambda \in \hat{G}_{f}} d_{\lambda}^{-1} \operatorname{Tr} M(G) I_{\lambda} \otimes I_{\lambda} \otimes |I_{n_{\lambda}}\rangle \rangle \langle \langle I_{n_{\lambda}}| = 1.$$
(33)

Also, the condition (12) for *T* can be rewritten as

$$\sum_{\lambda \in \hat{G}_{f}} d_{\lambda}^{-1} \mathrm{Tr} T I_{\lambda} \otimes I_{\lambda} \otimes |I_{n_{\lambda}}\rangle\rangle \langle \langle I_{n_{\lambda}}| = 1.$$
(34)

This description is useful for considering the relation with parallel scheme.

#### **IV. PARALLEL SCHEME**

Next, we discuss the parallel scheme [33–41]. The aim of this section is to show that the performance  $\min_{T:\operatorname{rank} T=1,(12)} D_{w,\mu}(M_T)$  can be realized by Parallel scheme.

When a reference system  $\mathbb{C}^l$  is available, we have

$$\mathcal{H} \otimes \mathbb{C}^{l} = \bigoplus_{\lambda \in \hat{G}_{f}} \mathcal{U}_{\lambda} \otimes \mathbb{C}^{ln_{\lambda}}.$$
(35)

However, when the input state is a pure state, the orbit is restricted into the following space by choosing a suitable subspace  $\mathbb{C}^{\min(d_{\lambda}, ln_{\lambda})}$  of  $\mathbb{C}^{ln_{\lambda}}$ . That is, our representation space can be considered as follows.

$$\bigoplus_{\lambda \in \hat{G}_f} \mathcal{U}_{\lambda} \otimes \mathbb{C}^{\min(d_{\lambda}, ln_{\lambda})}.$$
(36)

In the following, we consider the above case. We denote the projection to  $\mathcal{U}_{\lambda} \otimes \mathbb{C}^{\min(d_{\lambda}, ln_{\lambda})}$  by  $P_{\lambda}$ . When  $n \geq d_{\lambda}/n_{\lambda}$  for any  $\lambda \in \hat{G}_{f}$ , our representation is given as

$$\mathcal{H}' := \bigoplus_{\lambda \in \hat{G}_{\ell}} \mathcal{U}_{\lambda} \otimes \mathbb{C}^{d_{\lambda}}.$$
 (37)

A parallel strategy is given as a pair of a choice of an input state  $\rho$  on  $\mathcal{H}'$  and a choice of a POVM  $\Pi$  on  $\mathcal{H}'$ . The error probability is written as

$$D_{w}(\rho,\Pi) := \int_{G} w(g,\hat{g}) \operatorname{Tr}\Pi(d\hat{g}) f(g) \rho f(g)^{\dagger}.$$
(38)

In particular, as stated below, the reference [40, Theorem 1] showed that the optimization of the average of the error *w* satisfying the condition (16) under a parallel strategy can be achieved by the following simple strategy. The input state is a pure state  $|\psi\rangle$  on  $\mathcal{H}'$ . The POVM is fixed the following covariant POVM  $\Pi_{cov}$ ;

$$\Pi_{cov}(B) := \int_{B} f(g)^{\dagger} |F\rangle \langle F| f(g) \mu(dg)$$
(39)

for  $B \in \mathcal{B}(G)$ , where

$$|F\rangle := \bigoplus_{\lambda \in \hat{G}_f} \sqrt{d_\lambda} |I_\lambda\rangle\rangle.$$
(40)

Hence, this parallel strategy is characterized by the input state  $|\psi\rangle$  and is denoted by  $S[|\psi\rangle]$ . The error probability is written as

$$D_{w}(|\psi\rangle) := D_{w}(|\psi\rangle\langle\psi|,\Pi_{cov}).$$
(41)

Then, the preceding result [40, Theorem 1] is stated as follows.

**Proposition 2** ([40, Theorem 1]). Assume the condition (16). Then, we have

$$\min_{\rho,\Pi} D_{w,\mu}(\rho,\Pi) = \min_{|\psi\rangle} D_w(|\psi\rangle).$$
(42)

Our result is to state that the this value  $\min_{|\psi\rangle} D_w(|\psi\rangle)$  gives the optimal value even under much larger choices. To state this result, given a rank-one operator  $T = |X\rangle\langle X|$  on  $\mathcal{H} \otimes \mathcal{K}$  satisfying (12), we choose the pure state  $|\psi[T]\rangle$  as

$$|\psi[T]\rangle := \bigoplus_{\lambda \in \hat{G}_{f}} d_{\lambda}^{-1/2} \langle Y_{\lambda,\lambda} | I_{n_{\lambda}} \rangle \rangle | X_{\lambda,\lambda}^{T} \rangle \rangle, \qquad (43)$$

where  $|X\rangle$  has the following form

$$|X\rangle = \bigoplus_{\lambda \in \hat{G}_{f}} \bigoplus_{\lambda' \in \hat{G}_{f}} |X_{\lambda,\lambda'}\rangle\rangle \otimes |Y_{\lambda,\lambda'}\rangle \tag{44}$$

on the system  $\bigoplus_{\lambda \in \hat{G}_f} \bigoplus_{\lambda' \in \hat{G}_f} \mathcal{U}_{\lambda} \otimes \mathcal{U}_{\lambda'} \otimes \mathbb{C}^{n_{\lambda}} \otimes \mathbb{C}^{n_{\lambda'}}$ . Then, our result is stated as follows.

**Theorem 3.** The condition (34) guarantees the normalizing condition of  $|\psi[T]\rangle$ . Then, the behavior of the strategy  $M_T$  is simulated by the above parallel strategy with the input state  $|\psi[T]\rangle$ . That is, we have

$$\min_{T:\operatorname{rank} T=1,(12)} D_{w,\mu}(M_T) = \min_{|\psi\rangle} D_w(|\psi\rangle).$$
(45)

Since Theorem 1 addresses a much larger class than the parallel scheme, our result, Theorem 3, recovers Proposition (2) as a much stronger result.

Proof. We have

$$\langle X|f(g)|f(e)\rangle\rangle = \sum_{\lambda\in\hat{G}_{f}} \langle \langle X_{\lambda,\lambda}|\otimes \langle Y_{\lambda,\lambda}|f(g)|I_{\lambda}\rangle\rangle\otimes |I_{n_{\lambda}}\rangle\rangle$$

$$= \sum_{\lambda\in\hat{G}_{f}} \langle Y_{\lambda,\lambda}|I_{n_{\lambda}}\rangle\rangle\langle\langle X_{\lambda,\lambda}|f(g)|I_{\lambda}\rangle\rangle$$

$$= \sum_{\lambda\in\hat{G}_{f}} \langle Y_{\lambda,\lambda}|I_{n_{\lambda}}\rangle\rangle\operatorname{Tr}X_{\lambda,\lambda}^{T}f(g)$$

$$= \sum_{\lambda\in\hat{G}_{f}} \langle Y_{\lambda,\lambda}|I_{n_{\lambda}}\rangle\rangle\langle\langle I_{\lambda}|f(g)|X_{\lambda,\lambda}^{T}\rangle\rangle$$

$$= \sum_{\lambda\in\hat{G}_{f}} d_{\lambda}^{1/2}\langle\langle I_{\lambda}|f(g)d_{\lambda}^{-1/2}\langle Y_{\lambda,\lambda}|I_{n_{\lambda}}\rangle\rangle|X_{\lambda,\lambda}^{T}\rangle\rangle$$

$$= \langle F|f(g)|\psi[T]\rangle.$$

$$(46)$$

Then, we have

$$Trf(g)^{\dagger}Tf(g)|f(e)\rangle\langle\langle\langle f(e)|$$

$$=\langle\langle f(e)|f(g)^{\dagger}|X\rangle\langle X|f(g)|f(e)\rangle\rangle$$

$$=\langle F|f(g)|\psi[T]\rangle\langle\psi[T]|f(g)^{\dagger}|F\rangle$$

$$=Trf(g)^{\dagger}|F\rangle\langle F|f(g)|\psi[T]\rangle\langle\psi[T]|.$$
(47)

Replacing g by  $\hat{g}g'$ , we have

$$\operatorname{Tr} f(\hat{g})^{\dagger} T f(\hat{g}) |f(g')\rangle \langle \langle \langle f(g') |$$
  
= 
$$\operatorname{Tr} f(\hat{g})^{\dagger} |F\rangle \langle F|f(\hat{g})f(g')|\psi[T]\rangle \langle \psi[T]|f(g')^{\dagger}.$$
 (48)

Therefore, the behavior of the strategy  $M_T$  with the unknown action g' is simulated by the above parallel strategy with the input state  $|\psi[T]\rangle$  with the unknown action g'. That is, the performance  $\min_{T:\operatorname{rank} T=1,(12)} D_{w,\mu}(M_T)$  can be realized by Parallel scheme.

In the conversion in the above proof, the freedom of the choice of our covariant GPOVM is converted to the choice of our input state in the parallel strategy. Here, the state in the general setting corresponds to the measurement in the parallel strategy.

# V. CONCLUSION

This paper shows that indefinite causal order strategy nor adaptive strategy does not improve the performance of estimation of unknown operation given by a projective unitary representation of a compact group G. Since finite group is a compact group and our error function covers the case with the delta function in this case, our result can be applied to the discrimination of the unitary operations given by a projective unitary representation of a finite group [49]. In fact, the papers [40, 49] already obtained the optimal estimation in various examples under the parallel strategy. These preceding results gives the optimal performance even under a more general setting including indefinite causal order strategy nor adaptive strategy.

However, this paper does not consider the case with noisy channels. It is an interesting open problem to extend the obtained result to the noisy case. Although the generalized Hunt-Stein theorem can be easily extended to the noisy case, the derivation in Section IV highly depends on the noiseless setting. Therefore, we can expect that the noisy case has an advantage of indefinite causal order strategy and/or adaptive strategy over parallel strategy even under the group covariant setting.

The obtained unusefulness of indefinite causal order strategy and adaptive strategy is related to group symmetry. In fact, similar facts have been proved in the contest of secure network coding. The preceding studies show that adaptive modifications of the input information in each attacked edge by the adversary does not improve the information gain by the adversary when all coding operations are given as linear operations for classical secure network coding [50–53] and quantum secure network coding [54–56]. But, the paper [57] shows that this kind of improvement exists when nonlinear network code is applied. Therefore, it is another interesting open problem to clarify why secure network coding and the estimation of group action commonly have the unusefulness of adaptive strategy.

## ACKNOWLEDGEMENT

The author is thankful to Professor Xin Wang, Dr. Yu-Ao Chen, and Mr. Chenghong Zhu for helpful discussions and informing the reference [1]. The author is supported in part by the National Natural Science Foundation of China (Grant No. 62171212).

- J. Bavaresco, M. Murao, and M. T. Quintino, Strict hierarchy between parallel, sequential, and indefinitecausal-order strategies for channel discrimination, Phys. Rev. Lett. **127**, 200504 (2021).
- [2] G. Chiribella and D. Ebler, Quantum speedup in the identification of cause effect relations, Nature Communications 10, 1472 (2019).
- [3] G. Chiribella, G. M. D'Ariano, and P. Perinotti, Memory effects in quantum channel discrimination, Phys. Rev. Lett. 101, 180501 (2008).
- [4] A. W. Harrow, A. Hassidim, D. W. Leung, and J. Watrous, Adaptive versus nonadaptive strategies for quantum channel discrimination, Phys. Rev. A 81, 032339 (2010).
- [5] S. Pirandola, R. Laurenza, C. Lupo, and J. L. Pereira, Fundamental limits to quantum channel discrimination,

npj Quantum Information 5, 50 (2019).

- [6] Q. Zhuang and S. Pirandola, Ultimate limits quantum for multiple channel discrimination, Phys. Rev. Lett. 125, 080505 (2020).
- [7] M. Mancini, Rexiti and S. Discriminatqubit amplitude damping channels. ing Journal of Physics A: Mathematical and Theoretical 54, 165303 (2021) markovian processes, Phys. Rev. Lett. 127, 060501 (2021).
- [8] V. Katariya and M. M. Wilde, Evaluating the advantage of adaptive strategies for quantum channel distinguishability, Phys. Rev. A 104, 052406 (2021).
- [9] G. Chiribella, Perfect discrimination of no-signalling channels via quantum superposition of causal structures, Phys. Rev. A 86, 040301 (2012).
- [10] M. М. Wilde. Hirche, M. Berta, C. and Kaur. channel divergence E. Amortized for asymptotic quantum channel discrimination, Letters in Mathematical Physics 110, 2277 (2020).
- [11] X. Wang and M. M. Wilde, Resource theory of asymmetric distinguishability for quantum channels, Phys. Rev. Res. 1, 033169 (2019).
- [12] K. Fang, O. Fawzi, R. Renner, and D. Sutter, Chain rule for the quantum relative entropy, Phys. Rev. Lett. 124, 100501 (2020).
- [13] M. Hayashi, Discrimination of two channels by adaptive methods and its application to quantum system, IEEE Transactions on Information Theory 55, 3807 (2009).
- [14] F. Salek, M. Hayashi, and A. Winter, Usefulness of adaptive strategies in asymptotic quantum channel discrimination, Phys. Rev. A 105, 022419 (2022).
- [15] R. Ito and R. Mori, Lower bounds on the error probability of multiple quantum channel discrimination by the bures angle and the trace distance, arXiv preprint arXiv:2107.03948 10.48550/arXiv.2107.03948 (2021).
- [16] A. Fuiiwara and H. Imai. Ouantum parameter estimation of a generalized pauli channel. Journal of Physics A: Mathematical and General 36, 8093 (2003).
- [17] A. Fujiwara, Estimation of a generalized amplitude-damping channel, Phys. Rev. A 70, 012317 (2004).
- [18] M. Hayashi, Comparison between the cramer-rao and the mini-max approaches in quantum channel estimation, Communications in Mathematical Physics 304, 689 (2011).
- [19] V. Giovannetti, S. Lloyd, and L. Maccone, Advances in quantum metrology, Nature Photonics 5, 222-229 (2011).
- [20] V. Giovannetti, S. Lloyd, and L. Maccone, Quantum metrology, Phys. Rev. Lett. 96, 010401 (2006).
- [21] V. Giovannetti, S. Lloyd, and L. Maccone, Quantumenhanced measurements: Beating the standard quantum limit, Science 306, 1330 (2004).
- [22] J. A. Jones, S. D. Karlen, J. Fitzsimons, A. Ardavan, S. C. Benjamin, G. A. D. Briggs, and J. J. L. Morton, Magnetic field sensing beyond the standard quantum limit using 10-spin noon states, Science 324, 1166 (2009).
- [23] H. Imai and A. Fujiwara, Geometry of onestimation scheme timal for su(d) channels. Journal of Physics A: Mathematical and Theoretical 40, 4391
- [24] R. Okamoto, H. F. Hofmann, T. Nagata, J. L. O'Brien, K. Sasaki, and S. Takeuchi, Beating the standard quantum limit: phase super-sensitivity of n-photon interferometers, New Journal of Physics 10, 073033 (2008).
- [25] T. Nagata, R. Okamoto, J. L. O'Brien, K. Sasaki, and S. Takeuchi, Beating the standard quantum limit with fourentangled photons, Science 316, 726 (2007).
- [26] N. Thomas-Peter, B. J. Smith, A. Datta, L. Zhang, U. Dorner, and I. A. Walmsley, Real-world quantum sen-

sors: Evaluating resources for precision measurement, Phys. Rev. Lett. 107, 113603 (2011).

- [27] M. Hayashi and Y. Ouyang, Finding the optimal probe state for multiparameter quantum metrology using conic programming, npj Quantum Information 10, 111 (2024).
- [28] A. Altherr and Y. Yang, Quantum metrology for non-
- [29] Q. Liu, Z. Hu, H. Yuan, and Y. Yang, Optimal strategies of quantum metrology with a strict hierarchy, Phys. Rev. Lett. 130, 070803 (2023).
- [30] S. Kurdziałek, W. Górecki, F. Albarelli, and R. Demkowicz-Dobrzański, Using adaptiveness and causal S11perpositions against noise in quantum metrology, Phys. Rev. Lett. 131, 090801 (2023).
- [31] X. Zhao, Y. Yang, and G. Chiribella, Quantum metrology with indefinite causal order, Phys. Rev. Lett. 124, 190503 (2020).
- [32] Q. Liu, Z. Hu, H. Yuan, and Y. Yang, Fully-optimized quantum metrology: Framework, tools, and applications, Advanced Quantum Technologies n/a, 2400094.
- [33] V. Bužek, R. Derka, and S. Massar, Optimal quantum clocks, Phys. Rev. Lett. 82, 2207 (1999).
- [34] A. Luis and J. Peřina, Optimum phase-shift estimation and the quantum description of the phase difference, Phys. Rev. A 54, 4564 (1996).
- [35] E. Bagan, M. Baig, and R. Muñoz Tapia, Quantum reverse engineering and reference-frame alignment without nonlocal correlations, Phys. Rev. A 70, 030301 (2004).
- [36] G. Chiribella, G. M. D'Ariano, P. Perinotti, and M. F. Sacchi, Efficient use of quantum resources for the transmission of a reference frame, Phys. Rev. Lett. 93, 180503 (2004).
- [37] G. Chiribella, G. M. D'Ariano, and M. F. Sacchi, Optimal estimation of group transformations using entanglement, Phys. Rev. A 72, 042338 (2005).
- [38] H. Imai and M. Havashi, Fourier analytic approach to phase estimation in quantum systems, New Journal of Physics 11, 043034 (2009).
- [39] M. Hayashi, Parallel treatment of estimation of su(2) and phase estimation, Physics Letters A 354, 183 (2006).
- [40] M. Hayashi, Fourier analytic approach to quantum estimation of group action, Communications in Mathematical Physics 347, 3 (2016).
- [41] G. Chiribella, Group theoretic structures in the estimation of an unknown unitary transformation, Journal of Physics: Conference Series 284, 012001 (2011).
- [42] M. Hayashi, S. Vinjanampathy, and L. C. Kwek, Resolving unattainable cramer-rao bounds for quantum sensors, Journal of Physics B: Atomic, Molecular and Optical Physics 52, 015503
- [43] M. Hayashi, Z.-W. Liu, and H. Yuan, Global heisenberg scaling in noisy and practical phase estimation, Quantum Science and Technology 7, 025030 (2022).
- [44] W. Górecki, R. Demkowicz-Dobrzański, H. M. Wiseman, and D. W. Berry,  $\pi$ -corrected heisenberg limit, Physical review letters 124, 030501 (2020).
- [45] M. Hayashi, Heisenberg scaling based on DOD-
- coding, preprint (2007). ulation arXiv arXiv:2410.13399 10.48550/arXiv:2410.13399 (2024).
  - [46] A. Holevo, Covariant measurements and uncertainty relations, Reports on Mathematical Physics 16, 385 (1979).
  - A. S. Holevo, Probabilistic and statistical aspects of quantum theory [47] (Edizioni della Normale, 2011).
  - M. Hayashi, A Group Theoretic Approach to Quantum Infor-[48] mation (Springer, 2017).
  - [49] T. Hashimoto, A. Hayashi, M. Hayashi, and M. Horibe, Unitary-process discrimination with error margin,

Phys. Rev. A 81, 062327 (2010).

- [50] M. Hayashi and N. Cai, Asymptotically secure network code for active attacks, IEEE Transactions on Communications **69**, 3245 (2021).
- [51] M. Hayashi, M. Owari, G. Kato, and N. Cai, Reduction theorem for secrecy over linear network code for active attacks, Entropy 22, 10.3390/e22091053 (2020).
- [52] N. Cai and M. Hayashi, Secure network code for adaptive and active attacks with no-randomness in intermediate nodes, IEEE Transactions on Information Theory 66, 1428 (2020).
- [53] M. Hayashi, Secure network coding with adaptive and active attack, in *Festschrift in Memory of Ning Cai Information The*ory and Related Fields (Bielefeld, Germany, 2024) p. In press.
- [54] G. Kato, M. Owari, and M. Hayashi, Single-shot secure quantum network coding for general multiple uni-

cast network with free one-way public communication, IEEE Transactions on Information Theory **67**, 4564 (2021).

- [55] M. Owari, G. Kato, and M. Hayashi, Singleshot secure quantum network coding on butterfly network with free public communication, Quantum Science and Technology 3, 014001 (2017).
- [56] M. Hayashi and S. Song, Quantum state transmission over partially corrupted quantum information network, Phys. Rev. Res. 2, 033079 (2020).
- [57] M. Hayashi and N. Cai, Secure non-linear network code over a one-hop relay network, IEEE Journal on Selected Areas in Information Theory 2, 296 (2021).