RichSpace: Enriching Text-to-Video Prompt Space via Text Embedding Interpolation

Yuefan Cao^{*} Chengyue Gong[†] Xiaoyu Li[‡] Yingyu Liang[§] Zhizhou Sha[¶]

Zhenmei Shi[∥] Zhao Song^{**}

Abstract

Text-to-video generation models have made impressive progress, but they still struggle with generating videos with complex features. This limitation often arises from the inability of the text encoder to produce accurate embeddings, which hinders the video generation model. In this work, we propose a novel approach to overcome this challenge by selecting the optimal text embedding through interpolation in the embedding space. We demonstrate that this method enables the video generation model to produce the desired videos. Additionally, we introduce a simple algorithm using perpendicular foot embeddings and cosine similarity to identify the optimal interpolation embedding. Our findings highlight the importance of accurate text embeddings and offer a pathway for improving text-to-video generation performance.

^{*} ralph1997off@gmail.com. Zhejiang University.

 $^{^\}dagger$ cygong17@utexas.edu. The University of Texas at Austin.

[‡] 7.xiaoyu.li@gmail.com. Independent Researcher.

[§] yingyul@hku.hk. The University of Hong Kong. yliang@cs.wisc.edu. University of Wisconsin-Madison.

[¶] shazz20@mails.tsinghua.edu.cn. Tsinghua University.

zhmeishi@cs.wisc.edu. University of Wisconsin-Madison.

^{**} magic.linuxkde@gmail.com. Simons Institute for the Theory of Computing, University of California, Berkeley.

Contents

1	Introduction	2		
2	Related Work	3		
3	Preliminary	4		
	3.1 Notations	4		
	3.2 Key Concepts	4		
	3.3 Model Formulation	5		
	3.4 Problem Formulation	7		
4	Main Results	8		
	4.1 Word Embedding Space being Insufficient to Represent for All Videos	8		
	4.2 Optimal Interpolation Embedding Finder	9		
5	Experiments			
6	Discussion			
7	Conclusion			
\mathbf{A}	Word Embedding Space being Insufficient to Represent for All Videos			
в	More Examples			
С	Failure Cases			
D) Full Algorithm			

1 Introduction

Text-to-video models have developed rapidly in recent years, driven by the advancement of Transformer architectures [Vas17] and diffusion models [HJA20]. Early attempts at text-to-video generation focused on scaling up Transformers, with notable works such as CogVideo $[HDZ^+22]$ and Phenaki [VBK⁺22], which demonstrated promising results. More recently, the appearance of DiT [PX23], which incorporates Transformers as the backbone of Diffusion Models, has pushed the capabilities of text-to-video generation models to new heights. Models like Sora [Ope24], MovieGen [Met24], CogVideoX [YTZ⁺24], and Veo 2 [Goo24] have further showcased the potential of these approaches. Despite the impressive progress made in recent years, current state-of-the-art text-tovideo generation models still face challenges in effectively following complex instructions in userprovided text prompts. For instance, when users describe unusual real-world scenarios, such as "a tiger with zebra-like stripes walking on the grassland," the text encoder may struggle to fully capture the intended meaning. This results in text embeddings that fail to guide the video generation model toward producing the desired output. This issue is also observed in the text-to-image generation domain, where a notable work, Stable Diffusion V3 $[EKB^+24]$, addresses this challenge by incorporating multiple text encoders to improve understanding. Although their approach, which combines embeddings from different encoders, yields effective results, it comes at a significant computational cost due to the need to compute embeddings from multiple sources.

In this work, we take a different approach by exploring whether we can obtain a powerful text embedding capable of guiding the video generation model through interpolation within the text embedding space. Through empirical experiments, we demonstrate that by selecting the optimal text embedding, the video generation model can successfully generate the desired video. Additionally, we propose an algorithm that leverages perpendicular foot embeddings and cosine similarity to capture both global and local information in order to identify the optimal interpolation text embedding (Fig. 1 and Algorithm 2).



Figure 1: Two kinds of Text Prompts Mixture. Left: Mixture of Two Prompts. We set two prompts, A and B, and apply linear interpolation to two corresponding text embeddings. After that, we use one of the interpolation results to generate a video. To evaluate the effect of video interpolation, we set another prompt C, which describes the generated video to generate a video to compare with the interpolated video. **Right: Mixture of Three Prompts**. We set two prompts A and B and apply linear interpolation to two corresponding text embeddings. We manually choose one text embedding interpolated from A and B, then apply linear interpolation to this text embedding and text embedding C. After that, we use one of the interpolation results to generate a video. To evaluate the effect of video interpolation, we set another prompt D which describes the generated video to generate a video to compare with the interpolated video.

In summary, our main contributions are as follows:

- We demonstrate that selecting the correct text embedding can effectively guide a video generation model to produce the desired video.
- We propose a simple yet effective algorithm to find the optimal text embedding through the use of perpendicular foot embeddings and cosine similarity.

Roadmap. Our paper is organized as follows: In Section 2, we review related literature. Section 3 presents the preliminary of our notations, key concepts of our video algorithm, model formulation, and our definition of optimal interpolation embedding finder. Section 4 introduces our main algorithm for finding the optimal interpolation embedding. Section 5 presents the experiment result of this work. Section 6 provides further insights and potential future directions. In Section 7, we conclude our paper.

2 Related Work

Text-to-Video Generation. Text-to-video generation [SPH⁺22, VJMP22, BRL⁺23], as a form of conditional video generation, focuses on the synthesis of high-quality videos using text descriptions as conditioning inputs. Most recent works on video generation jointly synthesize multiple frames based on diffusion models [SSDK⁺20, HJA20]. Diffusion models implement an iterative refinement process by learning to gradually denoise a sample from a normal distribution, which has been successfully applied to high-quality text-to-video generation. In terms of training strategies, one of the existing approaches uses pre-trained text-to-image models and inserts temporal modules [GNL⁺23, AZY⁺23], such as temporal convolutions and temporal attention mechanisms into the pre-trained models to build up correlations between frames in the video [SPH⁺22, GWZ⁺23, GYR⁺23]. PYoCo [GNL⁺23] proposed a noise prior approach and leveraged a pre-trained eDiff-I [BNH⁺22] as initialization. Conversely, other works [BRL⁺23, ZWY⁺22] build upon Stable Diffusion [RBL⁺22] owing to the accessibility of pre-trained models. This approach aims to leverage the benefits of large-scale pre-trained text-to-image models to accelerate convergence. However, it may lead to unsatisfactory results due to the potential distribution gap between images and videos. Other approaches are training the entire model from scratch on both image and video datasets $[HCS^+22]$. Although this method can yield high-quality results, it demands tremendous computational resources.

Enrich Prompt Space. In the context of conditional tasks, such as text-to-image and text-tovideo models, prompts worked as conditions can have a significant influence on the performance of the models. For text-conditioned tasks, refining the user-provided natural provided natural language prompts into keyword-enriched prompts has gained increasing attention. Several recent works have explored the prompt space by the use of prompt learning, such as CoCoOp [ZYLL22], which uses conditional prompts to improve the model's generalization capabilities. AutoPrompt [SRLI+20] explores tokens with the most significant gradient changes in the label likelihood to automate the prompt generation process. Fusedream [LGW+21] manipulates the CLIP [RKH+21] latent space by using GAN [GPAM+14] optimization to enrich the prompt space. Specialist Diffusion [LTW+23] augments the prompts to define the same image with multiple captions that convey the same meaning to improve the generalization of the image generation network. Another work [LZY+23] proposes to generate random sentences, including source and target domain, in order to calculate a mean difference that will serve as a direction while editing. The iEdit [BGB+24] generates target prompts by changing words in the input caption in order to retrieve pseudo-target images and guide the model. The TokenCompose [WSD+24] and OmniControlNet [WXZ+24] control the image generation in the token-level space. Compared to the prior works, our work takes a different approach by exploring whether we can obtain a powerful text embedding capable of guiding the video generation model through interpolation within the text embedding space.

3 Preliminary

We first introduce some basic notations in Section 3.1. In Section 3.2, we introduce formal definitions of key concepts. Then, we introduce the formal definition of each module in the CogvideoX model in Section 3.3. Section 3.4 introduces the problem formulation.

3.1 Notations

For any $k \in \mathbb{N}$, let [k] denote the set $\{1, 2, \dots, k\}$. For any $n \in \mathbb{N}$, let n denote the length of the input sequence of a model. For any $d \in \mathbb{N}$, let d denote the hidden dimension. For any $c \in \mathbb{N}$, let c denote the channel of a video. For any $n_f \in \mathbb{N}$, we use n_f to denote the video frames. For any $h \in \mathbb{N}$ and $w \in \mathbb{N}$, we use h and w to denote the height and width of a video. For two vectors $x \in \mathbb{R}^n$ and $y \in \mathbb{R}^n$, we use $\langle x, y \rangle$ to denote the inner product between x, y. Namely, $\langle x, y \rangle = \sum_{i=1}^n x_i y_i$. For a vector $x \in \mathbb{R}^n$, we use $||x||_2$ to denote the ℓ_2 norm of the vector x, i.e., $||x||_2 := \sqrt{\sum_{i=1}^n x_i^2}$. Let \mathcal{D} represent a given distribution. The notation $x \sim \mathcal{D}$ indicates that x is a random variable drawn from the distribution \mathcal{D} .

3.2 Key Concepts

We will introduce some essential concepts in this section. We begin with introducing the formal definition of linear interpolation.

Definition 3.1 (Linear Interpolation). If the following conditions hold:

- Let $x, y \in \mathbb{R}^d$ denote two vectors.
- Let $k \in \mathbb{N}$ denote the interpolation step.

For $i \in [k]$, we define the *i*-th interpolation result $z_i \in \mathbb{R}$ as follows:

$$z_i := \frac{i}{k} \cdot x + \frac{k-i}{k} \cdot y$$

Next, we introduce another key concept used in our paper, the simple yet effective cosine similarity calculator.

Definition 3.2 (Cosine Similarity Calculator). If the following conditions hold:

- Let $X, Y \in \mathbb{R}^{n \times d}$ denote two matrices.
- Let $X_i, Y_i \in \mathbb{R}^d$ denote *i*-th row of X, Y, respectively.

Then, we defined the cosine similarity calculator $\phi_{\cos}(X,Y) : \mathbb{R}^{n \times d} \times \mathbb{R}^{n \times d} \to \mathbb{R}$ as follows

$$\phi_{\cos}(X,Y) := \frac{1}{n} \sum_{i=1}^{n} \frac{\langle X_i, Y_i \rangle}{\|X_i\|_2 \|Y_i\|_2}$$

Algorithm 1 Video Interpolation

1: datastructure INTERPOLATION 2: members $n \in \mathbb{N}$: the length of input sequence 3: $n_f \in \mathbb{N}$: the number of frames 4: $h \in \mathbb{N}$: the hight of video 5:6: $w \in \mathbb{N}$: the width of video $d \in \mathbb{N}$: the hidden dimension 7: 8: $c \in \mathbb{N}$: the channel of video $k \in \mathbb{N}$: the interpolation steps 9: 10: $T \in \mathbb{N}$: the number of inference step $E_{\text{opt}} \in \mathbb{R}^{n \times d}$: the optimal interpolation embedding 11: $E_t \in \mathbb{R}^{n \times d}$: the text embedding 12: $f_{\theta}(z, E_t, t) : \mathbb{R}^{n_f \times h \times w \times c} \times \mathbb{R}^{n \times d} \times \mathbb{N} \to \mathbb{R}^{n_f \times h \times w \times c}$: the text-to-video generation model 13:14: end members 15:**procedure** INTERPOLATION $(E_{t_a}, E_{t_b}, E_{t_c} \in \mathbb{R}^{n \times d}, k \in \mathbb{N}, T \in \mathbb{N})$ 16:/* Find optimal interpolation embedding, Algorithm 2. */ 17: 18: $E_{\text{opt}} \leftarrow \text{OPTIMALFINDER}(E_{t_a}, E_{t_b}, E_{t_c})$ /* Prepare initial latents.*/ 19: $z \sim \mathbb{N}(0, I) \in \mathbb{R}^{n_f \times h \times w \times c}$ 20:for $t = T \rightarrow 0$ do 21:/* One denoise step. */.22: $z \leftarrow f_{\theta}(z, E_{\text{opt}}, t)$ 23:end for 24: 25:Return z26: end procedure

Then, we introduce one crucial fact that we used later in this paper.

Fact 3.3 (Volume of a Ball in d-dimension Space). The volume of a ℓ_2 -ball with radius R in dimension \mathbb{R}^d space is

$$\frac{\pi^{d/2}}{(d/2)!}R^d$$

3.3 Model Formulation

In this section, we will introduce the formal definition for the text-to-video generation video we use. We begin with introducing the formal definition of the attention layer as follows:

Definition 3.4 (Attention Layer). If the following conditions hold:

- Let $X \in \mathbb{R}^{n \times d}$ denote the input matrix.
- Let $W_K, W_Q, W_V \in \mathbb{R}^{d \times d}$ denote the weighted matrices.
- Let $Q = XW_Q \in \mathbb{R}^{n \times d}$ and $K = XW_K \in \mathbb{R}^{n \times d}$.
- Let attention matrix $A = QK^{\top}$.

• Let $D := \operatorname{diag}(A\mathbf{1}_n) \in \mathbb{R}^{n \times n}$.

We define attention layer Attn as follows:

 $\operatorname{Attn}(X) := D^{-1}AXW_V.$

Then, we define the convolution layer as follows:

Definition 3.5 (Convolution Layer). If the following conditions hold:

- Let $h \in \mathbb{N}$ denote the height of the input and output feature map.
- Let $w \in \mathbb{N}$ denote the width of the input and output feature map.
- Let $c_{in} \in \mathbb{N}$ denote the number of channels of the input feature map.
- Let $c_{out} \in \mathbb{N}$ denote the number of channels of the output feature map.
- Let $X \in \mathbb{R}^{h \times w \times c_{\text{in}}}$ represent the input feature map.
- For $l \in [c_{out}]$, we use $K^l \in \mathbb{R}^{3 \times 3 \times c_{in}}$ to denote the *l*-th convolution kernel.
- Let p denote the padding of the convolution layer.
- Let s denote the stride of the convolution kernel.
- Let $Y \in \mathbb{R}^{h \times w \times c_{\text{out}}}$ represent the output feature map.

We define the convolution layer as follows: We use $\phi_{\text{conv}}(X, c_{\text{in}}, c_{\text{out}}, p, s) : \mathbb{R}^{h \times w \times c_{\text{in}}} \to \mathbb{R}^{h \times w \times c_{\text{out}}}$ to represent the convolution operation. Let $Y = \phi_{\text{conv}}(X, c_{\text{in}}, c_{\text{out}}, p, s)$. Then, for $i \in [h], j \in [w], l \in [c_{\text{out}}]$, we have

$$Y_{i,j,l} := \sum_{m=1}^{3} \sum_{n=1}^{3} \sum_{c=1}^{c_{\text{in}}} X_{i+m-1,j+n-1,c} \cdot K_{m,n,c}^{l}$$

We introduce the formal definition of linear projection layer as follows:

Definition 3.6 (Linear Projection). If the following conditions hold:

- Let $X \in \mathbb{R}^{n \times d_1}$ denote the input data matrix.
- Let $W \in \mathbb{R}^{d_1 \times d_2}$ denote the weight matrix.

We define the linear projection $\phi_{\text{linear}} : \mathbb{R}^{n \times d_1} \to \mathbb{R}^{n \times d_2}$ as follows:

$$\phi_{\text{linear}}(X) := XW$$

And we define the 3D full attention layer as follows:

Definition 3.7 (3D Attention). If the following conditions hold:

- Let Attn(X) be defined as in Definition 3.4.
- Let $\phi_{\text{conv}}(X, c_{\text{in,out},p,s})$ be defined in Definition 3.5.
- Let $\phi_{\text{linear}}(X)$ be defined as in Definition 3.6.

We define the 3D attention $\phi_{3DAttn}(E_t, E_v)$ containing three components: $\phi_{linear}(X)$, Attn(X), $\phi_{conv}(X, c_{in}, c_{out}, p, s)$. Its details are provided in Algorithm 4.

Finally, we provide the definition of the text-to-video generation model, which consists of a stack of multiple 3D attention layers, as introduced earlier.

Definition 3.8 (Text-to-Video Generation Model). If the following conditions hold:

- Let ϕ_{3DAttn} be defined as Definition 3.7.
- Let $k_{3D} \in \mathbb{N}$ denote the number of 3D attention layers in the text to video generation model.
- Let θ denote the parameter in the text-to-video generation model.
- Let $E_t \in \mathbb{R}^{n \times d}$ denote the text embedding.
- Let $z \sim \mathbb{N}(0, I) \in \mathbb{R}^{n_f \times h \times w \times c}$ denote the initial random Gaussian noise.

Then we defined the text-to-video generation model $f_{\theta}(E_t, z)$ as follows:

$$f_{\theta}(E_t, z) := \underbrace{\phi_{3\text{DAttn}} \circ \cdots \circ \phi_{3\text{DAttn}}}_{k_{3\text{D}} \text{ lavers}} (E_t, z).$$

3.4 **Problem Formulation**

In this section, we introduce the formal definition for finding the optimal interpolation embedding as follows:

Definition 3.9 (Finding Optimal Interpolation Embedding Problem). *If the following conditions hold:*

- Let P_a, P_b, P_c denote three text prompts.
- Our goal is to generate a video that contains features mentioned in P_a and P_b , and P_c is a text description of the feature combination of P_a and P_b .
- Let $E_{t_a}, E_{t_b}, E_{t_c} \in \mathbb{R}^{n \times d}$ denote the text embedding of P_a, P_b, P_c .
- Let $f_{\theta}(E_t, z)$ be defined in Definition 3.8.

We define the "Finding optimal interpolation embedding" problem as: According to $E_{t_a}, E_{t_b}, E_{t_c}$, find the optimal interpolation embedding E_{opt} that can make the text-to-video generation model $f_{\theta}(E_{opt}, z)$ generate video contains features mentioned in P_a and P_b .

Remark 3.10. We would like to refer the readers to Figure 3 as an example of Definition 3.9. In Figure 3, we set prompt P_a to "The tiger, moves gracefully through the forest, its fur flowing in the breeze." and prompt P_b to: "The zebra, moves gracefully through the forest, its fur flowing in the breeze.". Our goal is to generate a video that contains both features of "tiger" and "zebra", where we set prompt P_c to "The tiger, with black and white stripes like zebra, moves gracefully through the forest, its fur flowing in the breeze.", to describe the mixture features of tiger and zebra. However, the text-to-video model fails to generate the expected video. Therefore, it is essential to find the optimal interpolation embedding E_{opt} to make the model generate the expected video. In Figure 3, the E_{opt} is the 14-th interpolation embedding of E_{t_a} and E_{t_b} . Algorithm 2 Find Optimal Interpolation 1: datastructure OptimalInterpFinder 2: members 3: $n \in \mathbb{N}$: the length of input sequence. $n_{\text{ids}} \in \mathbb{N}$: the ids length of input sequence. 4: $d \in \mathbb{R}$: the hidden dimension. 5: $E_{t_a}, E_{t_b}, E_{t_c} \in \mathbb{R}^{n \times d}$: the text embedding. 6: $\phi_{\cos}(X,Y)$: the cosine similarity calculator. \triangleright Definition 3.2 7: 8: end members 9: **procedure** OptimalFinder($E_{t_a}, E_{t_b}, E_{t_c} \in \mathbb{R}^{n \times d}, n_{a_{ids}}, n_{b_{ids}}, n_{c_{ids}} \in \mathbb{N}$) 10:/* Calculate the max ids length. */11: $n_{\text{ids}} \leftarrow \max\{n_{a_{\text{ids}}}, n_{b_{\text{ids}}}, n_{c_{\text{ids}}}\}$ 12:/* Truncated text embeddings. */ 13: $E_{a_{\text{truc}}} \in \mathbb{R}^{n_{\text{ids}} \times d} \leftarrow E_{t_a}[:n_{\text{ids}},:]$ 14: $E_{b_{\text{truc}}} \in \mathbb{R}^{n_{\text{ids}} \times d} \leftarrow E_{t_b}[:n_{\text{ids}},:]$ 15: $E_{c_{\text{truc}}} \in \mathbb{R}^{n_{\text{ids}} \times d} \leftarrow E_{t_c}[:n_{\text{ids}},:]$ 16:17:/* Calculate cosine similarity, Algorithm 3. */ $L_{\text{CosTruc}} \leftarrow \text{COSINESIM}(E_{a_{\text{truc}}}, E_{b_{\text{truc}}}, E_{c_{\text{truc}}})$ 18: $L_{\text{CosFull}} \leftarrow \text{COSINESIM}(E_{t_a}, E_{t_b}, E_{t_c})$ 19:/* Add ConsineTruc and CosineFull. */ 20: $L_{\text{CosAdd}} \leftarrow []$ 21:for $i = 1 \rightarrow k$ do 22: $L_{\text{CosAdd}}[i] \leftarrow L_{\text{CosTruc}}[i] + L_{\text{CosFull}}[i]$ 23:end for 24: /* Find the optimal interpolation index. */ 25: $i_{\text{opt}} \leftarrow \text{maxindex}(L_{\text{CosAdd}})$ 26:/* Calculate optimal interpolation embedding. */ 27: $E_{\text{opt}} \leftarrow \frac{i_{\text{opt}}}{k} \cdot E_{t_c} + \frac{k - i_{\text{opt}}}{k} \cdot E_{t_b}$ 28:Return E_{opt} 29:30: end procedure

4 Main Results

In Section 4.1, we provide our rigorous theoretical analysis showing that word embedding space is not sufficient to represent all videos. In Section 4.2, we present our algorithm for finding the optimal interpolation embedding.

4.1 Word Embedding Space being Insufficient to Represent for All Videos

Since the text-to-video generation model only has a finite vocabulary size, it only has finite wording embedding space. However, the space for all videos is infinite. Thus, word embedding space is insufficient to represent all videos in video space. We formalize this phenomenon to a rigorous math problem and provide our findings in the following theorem.

Theorem 4.1 (Word Embeddings being Insufficient to Represent for All Videos, informal version of Theorem A.4). *If the following conditions hold:*

- Let n, d denote two integers, where n denotes the maximum length of the sentence, and all videos are in \mathbb{R}^d space.
- Let $V \in \mathbb{N}$ denote the vocabulary size.
- Let $\mathcal{U} = \{u_1, u_2, \cdots, u_V\}$ denote the word embedding space, where for $i \in [V]$, the word embedding $u_i \in \mathbb{R}^k$.
- Let $\delta_{\min} = \min_{i,j \in [V], i \neq j} \|u_i u_j\|_2$ denote the minimum ℓ_2 distance of two word embedding.
- Let $f : \mathbb{R}^{nk} \to \mathbb{R}^d$ denote the text-to-video generation model, which is also a mapping from sentence space (discrete space $\{u_1, \ldots, u_V\}^n$) to video space \mathbb{R}^d .
- Let $M := \max_{x} \|f(x)\|_{2}, m := \min_{x} \|f(x)\|_{2}.$
- Let $\epsilon = ((M^d m^d)/V^n)^{1/d}$.

Then, we can show that there exits a video $y \in \mathbb{R}^d$, satisfying $m \leq ||y||_2 \leq M$, such that for any sentence $x \in \{u_1, u_2, \cdots, u_V\}^n$, $||f(x) - y||_2 \geq \epsilon$.

The above theorem indicates that there always exists a video y, where its ℓ_2 distance to all videos can be represented by the wording embeddings is larger than ϵ . Intuitively understanding as shown in Fig. 2, this means that there always exists a video that cannot be accurately generated by using only the word embeddings from the word embedding space.



Figure 2: Points Mapping to a Circular Domain. This figure denotes a point set mapped to a circular domain by a linear function f(x). The field radius of every point in the circular domain is ϵ . We use M to denote the radius of the circular domain.

4.2 Optimal Interpolation Embedding Finder

In this section, we introduce our main algorithm (Algorithm 1 and Algorithm 2), which is also depicted in Fig. 1. The algorithm is designed to identify the optimal interpolation embedding (as defined in Definition 3.9) and generate the corresponding video. The algorithm consists of three key steps:

1. Compute the perpendicular foot embedding (Line 9 in Algorithm 3).

Algorithm 3 Calculate Cosine Similarity

1: datastructure CosineSimilarityCalculator 2: members 3: $n \in \mathbb{N}$: the length of input sequence. $d \in \mathbb{N}$: the hidden dimension. 4: $E_{t_a}, E_{t_b}, E_{t_c} \in \mathbb{R}^{n \times d}$: the text embedding. 5: $\phi_{\cos}(X,Y)$: the cosine similarity calculator. 6: \triangleright Definition 3.2 end members 7: 8: **procedure** PERPENDICULARFOOT $(E_{t_a}, E_{t_b}, E_{t_c} \in \mathbb{R}^{n \times d})$ 9: /* Find perpendicular foot of E_{t_c} on $E_{t_b} - E_{t_b}$. */ 10: $E_{ac} \leftarrow E_{t_c} - E_{t_a}$ 11: $E_{ab} \leftarrow E_{t_b} - E_{t_a}$ 12:/* Calculate the projection length. */ 13: $l_{\text{proj}} \leftarrow \langle E_{ab}, E_{ac} \rangle / \langle E_{ab}, E_{ab} \rangle$ 14:/* Calculate the projection vector. */ 15: $E_{\text{proj}} \leftarrow l_{\text{proj}} \cdot E_{ab}$ 16:/* Calculate the perpendicular foot. */ 17:18: $E_{\text{foot}} \leftarrow E_{t_a} + E_{\text{proj}}$ Return E_{foot} 19:end procedure 20:21: **procedure** COSINESIM $(E_{t_a}, E_{t_b}, E_{t_c} \in \mathbb{R}^{n \times d})$ 22:/* Calculate perpendicular foot. */ 23: $E_{\text{foot}} \leftarrow \text{PerpendicularFoot}(E_{t_a}, E_{t_b}, E_{t_c})$ 24:/* Init cosine similarity list. */ 25: $L_{\text{CosSim}} \leftarrow []$ 26:for $i = 1 \rightarrow k$ do 27:/* Compute interpolation embedding. */ 28: $E_{\text{interp}} \leftarrow \frac{i}{k} \cdot E_{t_1} + \frac{k-i}{k} \cdot E_{t_2}$ /* Calculate and store cosine similarity. */ 29:30: $L_{\text{CosSim}}[i] \leftarrow \phi_{\text{cos}}(E_{\text{interp}}, E_{\text{foot}})$ 31: end for 32: Return L_{CosSim} 33: 34: end procedure

- 2. Calculate the cosine similarity between the interpolation embeddings and the perpendicular foot embedding (Line 22 in Algorithm 3).
- 3. Select the optimal interpolation embedding based on the cosine similarity results (Algorithm 2).

We will now provide a detailed explanation of each part of the algorithm and the underlying intuitions.

Perpendicular Foot Embedding. As outlined in the problem definition (Definition 3.9), our objective is to identify the optimal interpolation embedding that allows the text-to-video generation model to generate a video containing the features described in P_a and P_b . The combination of

these features is represented by P_c , which typically does not lead to the desired video output. Consequently, we seek an interpolation embedding of E_{t_a} and E_{t_b} guided by E_{t_c} . The first step involves finding the perpendicular foot of E_{t_c} onto the vector $E_{t_b} - E_{t_a}$, also known as the projection of E_{t_c} . This perpendicular foot embedding, denoted as E_{foot} , is not the optimal embedding in itself, as the information within E_{t_c} alone does not enable the generation of the expected video. However, $E_{\rm foot}$ serves as a useful anchor, guiding us toward the optimal interpolation embedding. Further details of this approach will be discussed in the subsequent paragraph.





Prompt C: "The tiger, with black and white stripes like zebra, moves gracefully through the forest, its fur flowing in the breeze."

Figure 3: Mixture of ["Tiger"] and ["Zebra"]. Our objective is to mix the features described in Prompt A and Prompt B with the guidance of Prompt C. We set the total number of interpolation steps to 30. Using Algorithm 2, we identify the 14-th interpolation embedding as the optimal embedding and generate the corresponding video. The video generated directly from Prompt C does not exhibit the desired mixed features from Prompts A and B.

Cosine Similarity and Optimal Interpolation Embedding. To assess the similarity of each interpolation embedding to the anchor perpendicular foot embedding $E_{\rm foot}$, we employ the straightforward yet effective metric of cosine similarity (Definition 3.2). It is important to note that the input text prompts are padded to a fixed maximum length, n = 266, before being encoded by the T5 model. However, in real-world scenarios, the actual length of text prompts is typically much shorter than n = 266, which results in a substantial number of padding embeddings being appended to the original text prompt. The inclusion or exclusion of these padding embeddings can lead to significant differences in the perpendicular foot embedding, as their presence introduces a shift in the distribution of the text embeddings. To account for this, we treat text embeddings with and without padding separately. Specifically, we define "full text embeddings"



Figure 4: Mixture of ["Cat"] and ["Rabbit"]. Our objective is to mix the features described in Prompt A and Prompt B with the guidance of Prompt C. We set the total number of interpolation steps to 30. Using Algorithm 2, we identify the 21-th interpolation embedding as the optimal embedding and generate the corresponding video. The video generated directly from Prompt C does not exhibit the desired mixed features from Prompts A and B.

 $E_{a_t}, E_{b_t}, E_{c_t} \in \mathbb{R}^{n \times d}$ to represent the embeddings that include padding, and "truncated text embeddings" $E_{a_{\text{truc}}}, E_{b_{\text{truc}}}, E_{c_{\text{truc}}} \in \mathbb{R}^{n_{\text{ids}} \times d}$ to represent the embeddings without padding (Line 13 in Algorithm 2). The full-text embeddings capture global information, whereas the truncated text embeddings focus on local information. We compute the perpendicular foot and cosine similarity separately for both types of text embeddings (Line 17) and then combine the results by summing the cosine similarities from the full and truncated embeddings. Finally, we select the optimal interpolation embedding based on the aggregated cosine similarity scores (Line 25).

5 Experiments

Experiments Setup. Our experiments are conducted on the CogVideoX-2B [YTZ⁺24]. We investigate the performance of our optimal embedding finder algorithm in the following two scenarios:

Mixture of Features from Two Initial Prompts. As outlined in Definition 3.9, we conduct experiments where the goal is to generate a mixture of features described in two text prompts, P_a and P_b . We construct a third prompt, P_c , to specify the desired features. Following Algorithm 2, we identify the optimal text embedding and use it for the text-to-video generation with our base model. We conducted experiments using a variety of text prompts. In Fig. 3 and 4, we investigate the mixture of features from different animals, demonstrating that a video containing the mixture



Prompt C: "A sweet and delightful strawberry, with a color of dark purple, served in a crystal dish, is placed on the wooden table."

Figure 5: Mixture of ["Strawberry"] and ["Blueberry"]. Our objective is to mix the features described in Prompt A and Prompt B with the guidance of Prompt C. We set the total number of interpolation steps to 30. Using Algorithm 2, we identify the 17-th interpolation embedding as the optimal embedding and generate the corresponding video. The video generated directly from Prompt C does not exhibit the desired mixed features from Prompts A and B.

of tiger and zebra features, as well as the mixture of rabbit and cat features can only be generated using the optimal embedding, not directly from the text prompts. Similarly, in Fig. 5, we show that a video combining features from strawberry and blueberry can only be generated through the optimal embedding, highlighting a similar phenomenon in the context of fruits. Furthermore, in Fig. 6, we observe the same behavior in the domain of plants, specifically with the combination of rose and cactus features.

Mixture of Features from Three Initial Prompts. We will investigate further to see if we can add one additional feature to the video. The high-level approach involves applying our optimal interpolation embedding algorithm (Algorithm 2) twice. Given three text embeddings, E_{t_a} , E_{t_b} , and E_{t_c} , where we aim to blend their features in the generated video, we first apply Algorithm 2 to E_{t_a} and E_{t_b} to obtain the optimal interpolation embedding $E_{\text{opt}_{ab}}$. Next, we apply Algorithm 2 again, this time on $E_{\text{opt}_{ab}}$ and E_{t_c} , resulting in the final optimal interpolation embedding E_{opt} . We then use this embedding in our base model to generate the desired video. Following the method described above, we mix the giraffe feature with the tiger and zebra features, as shown in Fig. 8. Only by using the optimal embedding identified by our algorithm can we enable the video generation model to produce the desired video. Directly generating the video from the text prompt results in the loss of at least one of the intended features. A similar phenomenon is observed in the case of



Figure 6: Mixture of ["Rose"] and ["Cactus"]. Our objective is to mix the features described in Prompt A and Prompt B with the guidance of Prompt C. We set the total number of interpolation steps to 30. Using Algorithm 2, we identify the 17-th interpolation embedding as the optimal embedding and generate the corresponding video. The video generated directly from Prompt C does not exhibit the desired mixed features from Prompts A and B.

mixing strawberry, blueberry, and orange features, as shown in Fig. 7. The video generated directly from the text prompt always renders each object separately, failing to combine the features into a single coherent entity.

6 Discussion

Identifying the Actual Bottleneck of Generative Models. Our work identifies that the primary bottleneck hindering text-to-video generation models from producing the desired videos is the text encoder's inability to generate accurate text embeddings. Through our proposed algorithm, we can guide the video generation model to produce the desired output. This insight helps the community identify the true bottleneck within cutting-edge generative models, allowing for improvements in model performance and capabilities.

Limitations and Future Work. As discussed in Section 5, our algorithm achieves impressive results on various prompts. But there are still some failure cases, which we analyze in Section C. The reason for these failures is that the optimal text embedding may not lie within the linear interpolation space, preventing our algorithm from identifying the correct embedding in such cases. Additionally, leveraging information from E_{t_c} to derive the optimal embedding based on E_{t_a} and E_{t_h} is a non-trivial task. Therefore, we consider this an important direction for future work.



Figure 7: Mixture of ["Strawberry" + "Blueberry"] and ["Orange"]. We first obtain the optimal embedding of "Strawberry" + "Blueberry" used in Figure 5. Then we apply Algorithm 2 to that optimal embedding and Prompt C embedding, with the guidance of Prompt D. We identify 10-th interpolation embedding as the optimal embedding of ["Strawberry" + "Blueberry"] and ["Orange"] and generate the corresponding video. The video generated directly from Prompt D does not exhibit the desired mixed features.

wooden table."

7 Conclusion

In this work, we propose a novel algorithm designed to identify the optimal embedding that enables a video generation model to produce videos containing features specified in the initial prompts, which indicates that the primary bottleneck in text-to-video generation is due to the text encoder's inability to generate accurate text embeddings. These insights can guide future improvements in model performance by identifying and addressing the bottleneck modules.

References

- [AZY⁺23] Jie An, Songyang Zhang, Harry Yang, Sonal Gupta, Jia-Bin Huang, Jiebo Luo, and Xi Yin. Latent-shift: Latent diffusion with temporal shift for efficient text-to-video generation. arXiv preprint arXiv:2304.08477, 2023.
- [BGB⁺24] Rumeysa Bodur, Erhan Gundogdu, Binod Bhattarai, Tae-Kyun Kim, Michael Donoser, and Loris Bazzani. iedit: Localised text-guided image editing with weak supervision. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, pages 7426–7435, 2024.



Prompt D: "The tiger, with black and white strips and a long neck like giraffe, moves gracefully through the forest, its fur flowing in the breeze."

Figure 8: Mixture of ["Tiger" + "Zebra"] and ["Giraffe"]. We first obtain the optimal embedding of "Tiger" + "Zebra" used in Figure 3. Then we apply Algorithm 2 to that optimal embedding and Prompt C embedding, with the guidance of Prompt D. We identify 17-th interpolation embedding as the optimal embedding of ["Tiger" + "Zebra"] and ["Giraffe"] and generate the corresponding video. The video generated directly from Prompt D does not exhibit the desired mixed features.

- [BNH⁺22] Yogesh Balaji, Seungjun Nah, Xun Huang, Arash Vahdat, Jiaming Song, Qinsheng Zhang, Karsten Kreis, Miika Aittala, Timo Aila, Samuli Laine, et al. ediff-i: Textto-image diffusion models with an ensemble of expert denoisers. arXiv preprint arXiv:2211.01324, 2022.
- [BRL⁺23] Andreas Blattmann, Robin Rombach, Huan Ling, Tim Dockhorn, Seung Wook Kim, Sanja Fidler, and Karsten Kreis. Align your latents: High-resolution video synthesis with latent diffusion models. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, pages 22563–22575, 2023.
- [EKB⁺24] Patrick Esser, Sumith Kulal, Andreas Blattmann, Rahim Entezari, Jonas Müller, Harry Saini, Yam Levi, Dominik Lorenz, Axel Sauer, Frederic Boesel, et al. Scaling rectified flow transformers for high-resolution image synthesis. In *Forty-first International Conference on Machine Learning*, 2024.
- [GNL⁺23] Songwei Ge, Seungjun Nah, Guilin Liu, Tyler Poon, Andrew Tao, Bryan Catanzaro, David Jacobs, Jia-Bin Huang, Ming-Yu Liu, and Yogesh Balaji. Preserve your own correlation: A noise prior for video diffusion models. In *Proceedings of the IEEE/CVF* International Conference on Computer Vision, pages 22930–22941, 2023.

[Goo24] Google. Veo 2, 2024.

- [GPAM⁺14] Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial nets. Advances in neural information processing systems, 27, 2014.
 - [GWZ⁺23] Jiaxi Gu, Shicong Wang, Haoyu Zhao, Tianyi Lu, Xing Zhang, Zuxuan Wu, Songcen Xu, Wei Zhang, Yu-Gang Jiang, and Hang Xu. Reuse and diffuse: Iterative denoising for text-to-video generation. arXiv preprint arXiv:2309.03549, 2023.
 - [GYR⁺23] Yuwei Guo, Ceyuan Yang, Anyi Rao, Zhengyang Liang, Yaohui Wang, Yu Qiao, Maneesh Agrawala, Dahua Lin, and Bo Dai. Animatediff: Animate your personalized text-to-image diffusion models without specific tuning. arXiv preprint arXiv:2307.04725, 2023.
 - [HCS⁺22] Jonathan Ho, William Chan, Chitwan Saharia, Jay Whang, Ruiqi Gao, Alexey Gritsenko, Diederik P Kingma, Ben Poole, Mohammad Norouzi, David J Fleet, et al. Imagen video: High definition video generation with diffusion models. arXiv preprint arXiv:2210.02303, 2022.
 - [HDZ⁺22] Wenyi Hong, Ming Ding, Wendi Zheng, Xinghan Liu, and Jie Tang. Cogvideo: Large-scale pretraining for text-to-video generation via transformers. arXiv preprint arXiv:2205.15868, 2022.
 - [HJA20] Jonathan Ho, Ajay Jain, and Pieter Abbeel. Denoising diffusion probabilistic models. Advances in neural information processing systems, 33:6840–6851, 2020.
 - [LGW⁺21] Xingchao Liu, Chengyue Gong, Lemeng Wu, Shujian Zhang, Hao Su, and Qiang Liu. Fusedream: Training-free text-to-image generation with improved clip+ gan space optimization. arXiv preprint arXiv:2112.01573, 2021.
 - [LTW⁺23] Haoming Lu, Hazarapet Tunanyan, Kai Wang, Shant Navasardyan, Zhangyang Wang, and Humphrey Shi. Specialist diffusion: Plug-and-play sample-efficient fine-tuning of text-to-image diffusion models to learn any unseen style. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, pages 14267– 14276, 2023.
 - [LZY⁺23] Yupei Lin, Sen Zhang, Xiaojun Yang, Xiao Wang, and Yukai Shi. Regeneration learning of diffusion models with rich prompts for zero-shot image translation. arXiv preprint arXiv:2305.04651, 2023.
 - [Met24] Meta. Moviegen: Acastofmediafoundationmodels, 2024.
 - [Ope24] OpenAI. Sora, 2024.
 - [PX23] William Peebles and Saining Xie. Scalable diffusion models with transformers. In Proceedings of the IEEE/CVF International Conference on Computer Vision, pages 4195–4205, 2023.
 - [RBL⁺22] Robin Rombach, Andreas Blattmann, Dominik Lorenz, Patrick Esser, and Björn Ommer. High-resolution image synthesis with latent diffusion models. In Proceedings of the IEEE/CVF conference on computer vision and pattern recognition, pages 10684– 10695, 2022.

- [RKH⁺21] Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, et al. Learning transferable visual models from natural language supervision. In *International* conference on machine learning, pages 8748–8763. PMLR, 2021.
- [SPH⁺22] Uriel Singer, Adam Polyak, Thomas Hayes, Xi Yin, Jie An, Songyang Zhang, Qiyuan Hu, Harry Yang, Oron Ashual, Oran Gafni, et al. Make-a-video: Text-to-video generation without text-video data. arXiv preprint arXiv:2209.14792, 2022.
- [SRLI⁺20] Taylor Shin, Yasaman Razeghi, Robert L Logan IV, Eric Wallace, and Sameer Singh. Autoprompt: Eliciting knowledge from language models with automatically generated prompts. arXiv preprint arXiv:2010.15980, 2020.
- [SSDK⁺20] Yang Song, Jascha Sohl-Dickstein, Diederik P Kingma, Abhishek Kumar, Stefano Ermon, and Ben Poole. Score-based generative modeling through stochastic differential equations. arXiv preprint arXiv:2011.13456, 2020.
 - [Vas17] A Vaswani. Attention is all you need. Advances in Neural Information Processing Systems, 2017.
- [VBK⁺22] Ruben Villegas, Mohammad Babaeizadeh, Pieter-Jan Kindermans, Hernan Moraldo, Han Zhang, Mohammad Taghi Saffar, Santiago Castro, Julius Kunze, and Dumitru Erhan. Phenaki: Variable length video generation from open domain textual descriptions. In International Conference on Learning Representations, 2022.
- [VJMP22] Vikram Voleti, Alexia Jolicoeur-Martineau, and Chris Pal. Mcvd-masked conditional video diffusion for prediction, generation, and interpolation. Advances in neural information processing systems, 35:23371–23385, 2022.
- [WSD+24] Zirui Wang, Zhizhou Sha, Zheng Ding, Yilin Wang, and Zhuowen Tu. Tokencompose: Text-to-image diffusion with token-level supervision. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, pages 8553–8564, 2024.
- [WXZ⁺24] Yilin Wang, Haiyang Xu, Xiang Zhang, Zeyuan Chen, Zhizhou Sha, Zirui Wang, and Zhuowen Tu. Omnicontrolnet: Dual-stage integration for conditional image generation. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, pages 7436–7448, 2024.
- [YTZ⁺24] Zhuoyi Yang, Jiayan Teng, Wendi Zheng, Ming Ding, Shiyu Huang, Jiazheng Xu, Yuanming Yang, Wenyi Hong, Xiaohan Zhang, Guanyu Feng, et al. Cogvideox: Text-to-video diffusion models with an expert transformer. arXiv preprint arXiv:2408.06072, 2024.
- [ZWY⁺22] Daquan Zhou, Weimin Wang, Hanshu Yan, Weiwei Lv, Yizhe Zhu, and Jiashi Feng. Magicvideo: Efficient video generation with latent diffusion models. arXiv preprint arXiv:2211.11018, 2022.
- [ZYLL22] Kaiyang Zhou, Jingkang Yang, Chen Change Loy, and Ziwei Liu. Learning to prompt for vision-language models. International Journal of Computer Vision, 130(9):2337– 2348, 2022.

Appendix

Statements	Comment	Call	Called by
Def. 3.1	Define linear interpolation	None	Alg. 3, Alg. 2
Def. 3.2	Define cosine similarity calculator	None	Alg. 3, Alg. 2
Def. 3.4	Define attention layer	None	Alg. 4, Def. 3.7
Def. 3.5	Define convolution layer	None	Alg. 4, Def. 3.7
Def. 3.6	Define linear projection	None	Alg. 4, Def. 3.7
Def. 3.7	Define 3D attention	Def. 3.4, Def. 3.5, Def. 3.6	Alg. 4, Def. 3.8
Def. 3.8	Define text to video generation model	Def. 3.7	Def. 3.9
Def. 3.9	Define optimal interpolation embedding	Def. 3.8	Alg. 1
Alg. 4	3D Attention algorithm	Def. 3.4, Def. 3.5, Def. 3.6, Def. 3.7	None
Alg. 3	Cosine similarity calculator algorithm	Def. 3.1, Def. 3.2	Alg. 2
Alg. 2	Find optimal interpolation algorithm	Def. 3.1, Def. 3.2, Alg. 3	Alg. 1
Alg. 1	Video interpolation algorithm	Alg. 2	None

Table 1: Statement Call Table.

Roadmap. In Section A, we provide detailed proofs for the theorem showing that word embeddings are insufficient to represent all videos. In Section B, we provide more results of our experiments. In Section C, we provide some of our failure cases.

A Word Embedding Space being Insufficient to Represent for All Videos

In this section, we provide detailed proofs for Theorem A.6, showing that word embeddings are insufficient for representing all videos. We begin with a 1 dimensional case, where we assume all weights in function f(x) are integers.

Lemma A.1 (Integer function bound in 1 dimension). If the following conditions hold:

- Let $V \in \mathbb{N}$ denote a positive integer.
- Let $f: [V]^n \to \mathbb{R}$ denote a linear function where weights are all integers.
- Let $x \in [V]^n$ denote the input of function f.
- Let $M := \max_x f(x), m := \min_x f(x)$.
- Let $\epsilon = 0.5$.

Then we can show there exits a scalar $y \in [m, M]$ such that for any $x \in [V]^n$, $|f(x) - y| \ge \epsilon$.

Proof. Since $x \in [V]^n$, all entries of x are integers. Since function f is a linear function where all weights are integers, the output $f(x) \in \mathbb{Z}$ can only be integer.

Therefore, $m, M \in \mathbb{Z}$. We choose y = m + 0.5. Since for all f(x) are integers, then we have $|f(x) - y| \ge 0.5$.

Then, we extend the above Lemma to d dimensional case.

Lemma A.2 (Integer function bound in d dimension). If the following conditions hold:

- Let $V \in \mathbb{N}$ denote a positive integer.
- Let $f: [V]^n \to \mathbb{R}^d$ denote a linear function where weights are all integers.
- Let $x \in [V]^n$ denote the input of function f.
- Let $M := \max_x \|f(x)\|_2, m := \min_x \|f(x)\|_2.$
- Let $\epsilon = 0.5\sqrt{d}$.

Then we can show there exits a vector $y \in \mathbb{R}^d$, satisfying $m \leq ||y||_2 \leq M$, such that for any $x \in [V]^n$, $||f(x) - y||_2 \geq \epsilon$.

Proof. Let $x_{\min} \in [V]^n$ denote the vector which satisfies $f(x_{\min}) = m$. Since all entries in x and f are integers, all entries in $f(x_{\min})$ are all integers.

For $i \in [d]$, let $z_i \in \mathcal{Z}$ denote the *i*-th entry of $f(x_{\min})$. Then, we choose the vector $y \in \mathbb{R}^d$ as

$$y = \begin{bmatrix} z_1 + 0.5 \\ z_2 + 0.5 \\ \vdots \\ z_d + 0.5 \end{bmatrix}$$

Then, since all entries of f(x) are integers, we have $||f(x) - y||_2 \ge 0.5\sqrt{d}$.

Then, we move on to a more complicated case, in which we do not make any assumptions about the function f(x). We still begin by considering the 1 dimensional case.

Lemma A.3 (Any function bound in 1 dimension). If the following conditions hold:

- Let $V \in \mathbb{N}$ denote a positive integer.
- Let $f: [V]^n \to \mathbb{R}$ denote a function.
- Let $x \in [V]^n$ denote the input of function f.
- Let $M := \max_x f(x), m := \min_x f(x).$
- Let $\epsilon = (M m)/(2V^n)$.

Then we can show there exits a scalar $y \in [m, M]$ such that for any $x \in [V]^n$, $|f(x) - y| \ge \epsilon$.

Proof. Assuming for all $y \in [m, M]$, there exists one f(x), such that $|f(x) - y| < (M - m)/(2V^n)$. The overall maximum cover of all V^n points should satisfy

$$2 \cdot V^{n} \cdot |f(x) - y| < (M - m)$$
(1)

where the first step follows from there are total V^n possible choices for f(x), and each choice has a cover with length less than 2|f(x) - y|.

Eq (1) indicates the overall cover of V^n points can not cover all [m, M] range. We use S to denote the union of covers of all possible f(x).

Since the length of S is less than M - m, there exists at least one y lies in $[m, M] \setminus S$ such that $|f(x) - y| \ge (M - m)/(2V^n)$.

Then, we complete our proof.

Here, we introduce an essential fact that stating the volume of a ℓ_2 -ball in d dimensional space. Then, we extend our 1 dimensional result on any function f(x) to d dimensional cases.

Theorem A.4 (Word embeddings are insufficient to represent for all videos, formal version of Theorem 4.1). *If the following conditions hold:*

- Let n, d denote two integers, where n denotes the maximum length of the sentence, and all videos are in \mathbb{R}^d space.
- Let $V \in \mathbb{N}$ denote the vocabulary size.
- Let $\mathcal{U} = \{u_1, u_2, \cdots, u_V\}$ denote the word embedding space, where for $i \in [V]$, the word embedding $u_i \in \mathbb{R}^k$.
- Let $\delta_{\min} = \min_{i,j \in [V], i \neq j} \|u_i u_j\|_2$ denote the minimum ℓ_2 distance of two word embedding.
- Let $f : \mathbb{R}^{nk} \to \mathbb{R}^d$ denote the mapping from sentence space (discrete space $\{u_1, \ldots, u_V\}^n$) to video space \mathbb{R}^d .
- Let $M := \max_{x} \|f(x)\|_{2}, m := \min_{x} \|f(x)\|_{2}.$
- Let $\epsilon = ((M^d m^d)/V^n)^{1/d}$.

Then, we can show that there exits a video $y \in \mathbb{R}^d$, satisfying $m \leq ||y||_2 \leq M$, such that for any sentence $x \in \{u_1, u_2, \cdots, u_V\}^n$, $||f(x) - y||_2 \geq \epsilon$.

Proof. Assuming for all y satisfying $m \leq ||y||_2 \leq M$, there exists one f(x), such that $|f(x) - y| < ((M^d - m^d)/V^n)^{1/d}$.

Then, according to Fact 3.3, for each f(x), the volume of its cover is $\frac{\pi^{d/2}}{(d/2)!}((M^d - m^d)/V^n)$. There are maximum total V^n f(x), so the maximum volume of all covers is

$$V^n \cdot \frac{\pi^{d/2}}{(d/2)!} ((M^d - m^d)/V^n) < \frac{\pi^{d/2}}{(d/2)!} (M^d - m^d)$$

which indicates the cover of all V^n possible points does not cover the entire space for y.

Therefore, there exists a y satisfying $m \leq ||y||_2 \leq M$, such that $||f(x) - y||_2 \geq ((M^d - m^d)/V^n)^{1/d}$.

Then, we complete our proof.

Definition A.5 (Bi-Lipschitzness). We say a function $f : \mathbb{R}^n \to \mathbb{R}^d$ is L-bi-Lipschitz if for all $x, y \in \mathbb{R}^n$, we have

$$L^{-1}||x - y||_2 \le ||f(x) - f(y)||_2 \le L||x - y||_2.$$

Then, we state our main result as follows

Theorem A.6 (Word embeddings are insufficient to represent for all videos, with Bi-Lipschitz condition). *If the following conditions hold:*

- Let n, d denote two integers, where n denotes the maximum length of the sentence, and all videos are in \mathbb{R}^d space.
- Let $V \in \mathbb{N}$ denote the vocabulary size.

- Let $\mathcal{U} = \{u_1, u_2, \cdots, u_V\}$ denote the word embedding space, where for $i \in [V]$, the word embedding $u_i \in \mathbb{R}^k$.
- Let $\delta_{\min} = \min_{i,j \in [V], i \neq j} \|u_i u_j\|_2$ denote the minimum ℓ_2 distance of two word embedding.
- Let $f : \mathbb{R}^{nk} \to \mathbb{R}^d$ denote the text-to-video generation model, which is also a mapping from sentence space (discrete space $\{u_1, \ldots, u_V\}^n$) to video space \mathbb{R}^d .
- Assuming $f : \mathbb{R}^{nk} \to \mathbb{R}^d$ satisfies the L-bi-Lipschitz condition (Definition A.5).
- Let $M := \max_{x} \|f(x)\|_{2}, m := \min_{x} \|f(x)\|_{2}.$
- Let $\epsilon = \max\{\delta_{\min}(2L)^{-1}, ((M^d m^d)/V^n)^{1/d}\}.$

Then, we can show that there exits a video $y \in \mathbb{R}^d$, satisfying $m \leq ||y||_2 \leq M$, such that for any sentence $x \in \{u_1, u_2, \cdots, u_V\}^n$, $||f(x) - y||_2 \geq \epsilon$.

Proof. According to Lemma A.4, we have that $\epsilon \ge ((M^d - m^d)/V^n)^{1/d}$. Then, we only need to prove that $\epsilon = \delta_{\min}(2L)^{-1}$ when $\delta_{\min}(2L)^{-1} > ((M^d - m^d)/V^n)^{1/d}$.

Then, we only need to prove that $\epsilon = \sigma_{\min}(2L)^{-1}$ when $\sigma_{\min}(2L)^{-1} > ((M^2 - m^2)/V^2)^{-1}$. Since we have assume that the function f(x) satisfies that for all $x, y \in \mathbb{R}^{nk}$, such that

$$||f(x) - f(y)||_2 \ge L^{-1} ||x - y||_2.$$
(2)

According to the definition of δ_{\min} , we have for all $i, j \in [V], i \neq j$, such that

$$\|u_i - u_j\|_2 \ge \delta_{\min} \tag{3}$$

Combining Eq. (2) and (3), we have for all $i, j \in [V], i \neq j$

$$||f(u_i) - f(u_j)||_2 \ge \delta_{\min} L^{-1}$$

which indicates that, if we choose $y = \frac{1}{2}(u_i + u_j)$ for any $i, j \in [V], i \neq j$, we have

$$||y - f(u_i)||_2 \ge \delta_{\min}(2L)^{-1}, \forall i \in [V].$$

Therefore, when we have $\delta_{\min}(2L)^{-1} > ((M^d - m^d)/V^n)^{1/d}$ holds, then we must have $\epsilon = \delta_{\min}(2L)^{-1}$.

Considering all conditions we discussed above, we are safe to reach the conclusion that $\epsilon = \max\{\delta_{\min}(2L)^{-1}, ((M^d - m^d)/V^n)^{1/d}\}$

B More Examples

In this section, we will show more experimental results that the video generated directly from the guidance prompt does not exhibit the desired mixed features from the prompts. In Fig. 9, we provide an example of an "age" case. In Fig. 10, we provide an example of an "animal" case. In Fig. 11, we provide an example of a fruit case. In Fig. 12, we provide an example of the "plant" case.

C Failure Cases

In this section, we show our failure cases that the video generated directly from the guidance prompt can exhibit desired mixed features from the prompts. In Fig. 13, 14, 15, and 16, we provide examples on "color" case. In Fig. 17 and 18, we provide example on "plant" case. In Fig. 19, we provide an example for the "landscape" case.





Prompt C: "A middle-aged man, with a serene expression, sits at the water's edge, a steaming cup of tea by his side."

Figure 9: Mixture of ["Young"] and ["Old"]. Our objective is to mix the features described in Prompt A and Prompt B with the guidance of Prompt C. We set the total number of interpolation steps to 30. Using Algorithm 2, we identify the 16-th interpolation embedding as the optimal embedding and generate the corresponding video. The video generated directly from Prompt C does not exhibit the desired mixed features from Prompts A and B.

D Full Algorithm

In this section, we provide the algorithm for 3D attention in Algorithm 4.



Prompt C: "The tiger, which has horse legs and no black strips on its fur, moves gracefully through the forest, its fur flowing in the breeze."

Figure 10: Mixture of ["Tiger"] and ["Horse"]. Our objective is to mix the features described in Prompt A and Prompt B with the guidance of Prompt C. We set the total number of interpolation steps to 30. Using Algorithm 2, we identify the 17-th interpolation embedding as the optimal embedding and generate the corresponding video. The video generated directly from Prompt C does not exhibit the desired mixed features from Prompts A and B.



Prompt B: "The **orange**, freshly washed, served in a dish, is placed on the wooden table."



Prompt C: *"The eggplant, with the color of yellow, freshly washed, served in a dish, is placed on the wooden table."*

Figure 11: Mixture of ["Eggplant"] and ["Orange"]. Our objective is to mix the features described in Prompt A and Prompt B with the guidance of Prompt C. We set the total number of interpolation steps to 30. Using Algorithm 2, we identify the 0-th interpolation embedding as the optimal embedding and generate the corresponding video. The video generated directly from Prompt C does not exhibit the desired mixed features from Prompts A and B.



Prompt D: "The lily, with the color of green and yellow and thin thorns of cactus, petals in the shape of rose petals, standing tall in the garden, its petals glistening with morning dew."

Figure 12: Mixture of ["Rose" + "Cactus"] and ["Lily"]. We first obtain the optimal embedding of "Rose" + "Cactus" used in Figure 6. Then we apply Algorithm 2 to that optimal embedding and Prompt C embedding, with the guidance of Prompt D. We identify 11-th interpolation embedding as the optimal embedding of ["Rose" + "Cactus"] and ["Lily"] and generate the corresponding video. The video generated directly from Prompt D does not exhibit the desired mixed features.



Prompt B: "A man, wearing a **blue** jacket, walks on the street, in the middle of the day."



Prompt C: "A man, wearing a *purple* jacket, walks on the street, in the middle of the day."

Figure 13: Mixture of ["Red"] and ["Blue"]. Our objective is to mix the features described in Prompt A and Prompt B with the guidance of Prompt C. We set the total number of interpolation steps to 30. Using Algorithm 2, we identify the 18-th interpolation embedding as the optimal embedding and generate the corresponding video. The video generated directly from Prompt C can exhibit the desired mixed features from Prompts A and B.



Prompt B: "A man, wearing a **red** jacket, walks on the street, in the middle of the day."



Prompt C: "A man, wearing a **brown** jacket, walks on the street, in the middle of the day."

Figure 14: Mixture of ["Green"] and ["Red"]. Our objective is to mix the features described in Prompt A and Prompt B with the guidance of Prompt C. We set the total number of interpolation steps to 30. Using Algorithm 2, we identify the 14-th interpolation embedding as the optimal embedding and generate the corresponding video. The video generated directly from Prompt C can exhibit the desired mixed features from Prompts A and B.



Prompt B: "A man, wearing a **blue** jacket, walks on the street, in the middle of the day."



Prompt C: "A man, wearing a **deep green** jacket, walks on the street, in the middle of the day."

Figure 15: Mixture of ["Green"] and ["Blue"]. Our objective is to mix the features described in Prompt A and Prompt B with the guidance of Prompt C. We set the total number of interpolation steps to 30. Using Algorithm 2, we identify the 16-th interpolation embedding as the optimal embedding and generate the corresponding video. The video generated directly from Prompt C can exhibit the desired mixed features from Prompts A and B.



Prompt D: "A man, wearing a **orange** jacket, walks on the street, in the middle of the day."

Figure 16: Mixture of ["Red" + "Blue"] and ["Yellow"]. We first obtain the optimal embedding of "Red" + "Blue" used in Figure 13. Then we apply Algorithm 2 to that optimal embedding and Prompt C embedding, with the guidance of Prompt D. We identify 12-th interpolation embedding as the optimal embedding of ["Red" + "Blue"] and ["Yellow"] and generate the corresponding video. The video generated directly from Prompt D can exhibit desired mixed features.



Prompt C: "The rose, with petals in the shape of lily, standing tall in the garden, its petals glistening with morning dew."

Figure 17: Mixture of ["Rose"] and ["Lily"]. Our objective is to mix the features described in Prompt A and Prompt B with the guidance of Prompt C. We set the total number of interpolation steps to 30. Using Algorithm 2, we identify the 16-th interpolation embedding as the optimal embedding and generate the corresponding video. The video generated directly from Prompt C can exhibit the desired mixed features from Prompts A and B.



Prompt D: "The yellow lily, with petals in the shape of rose petals and leaves in the shape of tulip leaves, standing tall in the garden, its petals glistening with morning dew."

Figure 18: Mixture of ["Rose" + "Lily"] and ["Tulip"]. We first obtain the optimal embedding of "Strawberry" + "Blueberry" used in Figure 17. Then we apply Algorithm 2 to that optimal embedding and Prompt C embedding, with the guidance of Prompt D. We identify 9-th interpolation embedding as the optimal embedding of ["Rose" + "Lily"] and ["Tulip"] and generate the corresponding video. The video generated directly from Prompt D can exhibit desired mixed features.



Figure 19: Mixture of ["Mountain"] and ["River"]. Our objective is to mix the features described in Prompt A and Prompt B with the guidance of Prompt C. We set the total number of interpolation steps to 30. Using Algorithm 2, we identify the 18-th interpolation embedding as the optimal embedding and generate the corresponding video. The video generated directly from Prompt C can exhibit the desired mixed features from Prompts A and B.

in the afternoon light."

Algorithm 4 3D Attention

```
1: datastructure 3D ATTENTION
                                                                                                                                          \triangleright Definition 3.7
 2: members
           n \in \mathcal{N}: the length of input sequence
 3:
 4:
           n_f \in \mathcal{N}: the number of frames
           h \in \mathcal{N}: the hight of video
 5:
           w \in \mathcal{N}: the width of video
 6:
           d \in \mathcal{N}: the hidden dimension
 7:
           c \in \mathcal{N}: the channel of video
 8:
           c_{\text{patch}} \in \mathbb{R}^{n \times d}: the channel of patch embedding.
 9:
           E_t \in \mathbb{R}^{n \times d}: the text embedding.
10:
           E_{\text{video}} \in \mathbb{R}^{n_f \times h \times w \times c}: the video embedding.
11:
           E_{\text{patch}} \in \mathbb{R}^{n_f \times h' \times w' \times c_{\text{patch}}}: the patch embedding.
12:
           \phi_{\text{conv}}(X, c_{\text{in}}, c_{\text{out}}, p, s): the convolution layer.
                                                                                                                                          \triangleright Definition 3.5
13:
14:
           Attn(X): the attention block.
                                                                                                                                          \triangleright Definition 3.4
           \phi_{\text{linear}}(X): the linear projection.
                                                                                                                                          \triangleright Definition 3.6
15:
16: end members
17:
     procedure 3D ATTENTION(E_t \in \mathbb{R}^{n \times d}, E_v \in \mathbb{R}^{n_f \times h \times w \times c})
18:
           /* E_{\text{patch}} dimension: [n_f, h, w, c_v] \rightarrow [n_f, h', w', c_{\text{patch}}] */
19:
           E_{\text{patch}} \leftarrow \phi_{\text{conv}}(E_v, c_v, c_{\text{patch}}, p = 2, s = 2)
20:
           /* E_{\text{patch}} dimension: [n_f, h', w', c_{\text{patch}}] \rightarrow [n_f \times h' \times w', c_{\text{patch}}] */
21:
22:
           E_{\text{patch}} \leftarrow \text{reshape}(E_{\text{patch}})
           /* E_{\text{hidden}} dimension: [n + n_f \times h' \times w', c_{\text{patch}}] */
23:
           E_{\text{hidden}} \leftarrow \text{concat}(E_t, E_{\text{patch}})
24:
           /* E_{\text{hidden}} dimension: [n + n_f \times h' \times w', c_{\text{patch}}] */
25:
           E_{\text{hidden}} \leftarrow \text{Attn}(E_{\text{hidden}})
26:
           /* E_t dimension: [n, d] */
27:
            /* E_{\text{patch}} dimension: [n_f \times h' \times w', c_{\text{patch}}] */
28:
           E_t, E_{\text{patch}} \leftarrow \text{split}(E_{\text{hidden}})
29:
           /* E_v dimension: [n_f \times h' \times w', c_{\text{patch}}] \rightarrow [n_f \times h \times w, c_v]*/
30:
31:
           E_v \leftarrow \phi_{\text{linear}}(E_{\text{patch}})
           /* E_v dimension: [n_f \times h \times w, c_v] \rightarrow [n_f, h, w, c_v] */
32:
           E_v \leftarrow \operatorname{reshape}(E_v)
33:
           Return E_v
34:
35: end procedure
```