# Small Decision Trees for MDPs with Deductive Synthesis

Roman Andriushchenko<sup>1</sup>, Milan Češka (⊠)<sup>1</sup>, Sebastian Junges<sup>2</sup>, and Filip Macák<sup>1</sup>

<sup>1</sup> Brno University of Technology, Brno, Czech Republic
<sup>2</sup> Radboud University, Nijmegen, the Netherlands

Abstract. Markov decision processes (MDPs) describe sequential decisionmaking processes; MDP policies return for every state in that process an advised action. Classical algorithms can efficiently compute policies that are optimal with respect to, e.g., reachability probabilities. However, these policies are then given in a tabular format. A longstanding challenge is to represent optimal or almost-optimal policies concisely, e.g., as decision trees. This paper makes two contributions towards this challenge: first, an SMT-based approach to encode a given (optimal) policy as a small decision tree, and second, an abstraction-refinement loop that searches for policies that are optimal within the set of policies that can be represented with a small tree. Technically, the latter combines the SMT encoding with verification approaches for families of Markov chains. The empirical evaluation demonstrates the feasibility of these approaches and shows how they can outperform the state-of-the-art on various benchmarks, yielding up to 20-times smaller trees representing (almost) optimal policies for models with up to 10k states and 19 variables.

### 1 Introduction

Markov decision processes (MDPs) are the ubiquitous model to describe sequential decision making under uncertainty: the outcomes of nondeterministic actions are determined by a probability distribution over the successor states. MDP policies resolve the nondeterminism and describe for each state which action to take. A classical synthesis task in MDPs is to compute a policy that maximises a given objective, such as: Given a set of goal states, find a maximising policy. i.e. a policy ensuring that the goal is reached with the maximal probability. These policies are efficiently computed by probabilistic model checkers such as STORM [22] or Prism [27] or can be approximated using (deep) reinforcement learning techniques [23, 34]. These techniques apply to huge MDPs that are concisely represented, e.g. in the PRISM language. The result is a policy which is represented either in tabular form, mapping states to an action, or as a neural network. While the tabular form is often prohibitively large for further analysis by machines or a human, neural networks are hard to analyse despite the tremendous progress in neural network verification. This observation has motivated the search for concise representations of policies, in particular in the form of programs [8, 36]



Fig. 1: (a) A simple slippery maze. The goal is to lead the robot placed in the lower left corner (the red dot) towards the exit cell while minimising the number of steps. Red arrowheads illustrate the optimal policy that achieves a value of 12.8 (expected steps). Blue arrowheads illustrate a sub-optimal policy that achieves a value of 13.3. (b) The smallest DT implementing the optimal policy has depth 4. (c) The smallest DT implementing the sub-optimal policy has only depth 2.

or decision trees (DTs) [7, 35, 37]. The main contribution of this paper is an approach to synthesise policies which are optimal within a class of small DTs.

Illustrative example. Consider a simple grid-world maze as in Fig. 1. The agent starts at the bottom left and wants to reach the exit marked E. It can move in the four cardinal directions, and each action has a small probability of transitioning into an unintended neighbouring cell. Consequently, every state is reachable under every policy. STORM computes an optimal (in this example, unique) policy that ensures reaching the exit in an expected 12.8 steps (the policy visualised by the red arrowheads). To represent this policy as a DT (using predicates that compare variables to constants) requires a tree of depth at least 4 (see Fig. 1b). Alternatively, we may ask: What is the optimal expected number of steps to reach the exit among all policies that can be represented as a DT of depth 2? The answer is 13.3 realised by the policy visualised by the blue arrowheads. The corresponding DT is shown in Fig. 1c. This policy aims to avoid the 'staircase' in the left upper corner and then takes sub-optimal actions within that staircase.

Problem setup. We call a policy k-(tree-)implementable, if there is a DT of depth k (and with a particular class of predicates) that represents the policy. The first problem, the mapping problem, asks whether a given tabular policy is k-implementable for any fixed k. Solving this problem then allows us to find the smallest DT, measured by depth, that implements this policy. The second problem, the synthesis problem, is to find a policy that is optimal with respect to some objective, such as reaching the goal state, and within the class of k-implementable policies. We want to highlight that the mapping problem assumes one fixed policy. Therefore, the mapping problem cannot find the minimal representation of any optimal policy. In particular, in our experiments, we show that we can find optimal policies that are 2-implementable, whereas the policy that STORM computes is not 5-implementable. The construction of optimal DTs is well-known to be NP-hard for different notions of optimality [20, 28].

State-of-the-art: Policy mapping. Mapping policies into small, but not necessarily the smallest, DTs is prominently supported by the tools DTCONTROL [4] and Uppaal Stratego [5,14]. These tools approach the problem by *learning* small DTs, by recursively splitting the tree based on ideas like information gain. The result is an approximation or exact representation of the original policy, and while the heuristics for splitting are well-developed, they are heuristics that favour scalability over minimality.

Our approach: An SMT-based encoding. Inspired by encodings of DTs in propositional formulas [32] or as mixed integer linear programs (MILP) [37], we encode the set of k-implementable trees in an SMT formula over the bounded integers and with linear inequalities. Using an SMT solver allows us to find small DTs (up to depth 8) for MDPs with up to 6k states. In particular, for the same policies, we find DTs with up to 900 nodes less than the DTs that DTCONTROL finds. On the other hand, the SMT-based approach scales exponentially in the depth of the tree, and if it cannot find a small tree, it often times out in an attempt to find a larger one.

State-of-the-art: The synthesis problem. The tool OMDT builds a monolithic MILP that encodes both the structural constraints on the policy (being k-implementable) and the constraint that the policy achieves the optimal value (using the standard dual formulation of the LP for maximal discounted rewards). It extends LP-based encodings for MDP model checking and encounters the same scalability issues in terms of the MDP size that other MILP-based approaches face, e.g., in [2, 15–17].

Our approach: Abstraction refinement with SMT-based mapping. We present an abstraction-refinement loop to avoid solving the synthesis problem in one shot. The approach considers a set of k-implementable policies and abstracts them to search for an optimal policy in a larger class of policies. If this policy is not improving over the best k-implementable policy found so far, it abandons the search here. Otherwise, by solving the mapping problem, it tests whether this optimal policy is k-implementable. If yes, we can abandon the search here and store the policy as our best policy so far. Otherwise, the policy is spurious, and the search is recursively invoked on smaller subsets of k-implementable policies.

Example 1. We present a conceptual version of our routine on the example given above, see Fig. 1. To find an optimal 2-implementable policy, we would first search for an optimal memoryless policy  $\sigma$ . This policy is better than the previously found policy (we can e.g. initialize this policy as a random tree). Using the mapping problem,  $\sigma$  is spurious. We can now split and independently search for the best k-implementable policy that goes up in the initial state and for the best k-implementable policy that goes right in the initial state. We observe that these sub-classes can be overapproximated by memoryless deterministic policies on two sub-MDPs of the original MDP.

*Effective abstraction refinement.* In Sec. 4, we introduce the abstraction-refinement loop DTPAYNT that analyses the spurious policies to split in an informed way. Compared to an abstraction-refinement loop for finite state controllers in POMDPs [2],

the set of k-implementable policies is highly irregular and a policy can be represented by many different trees. To overcome this problem, we use an unsatisfiable core UC witnessing that the given policy is not k-implementable. We introduce a harmonisation technique that analyses UC and finds two trees that serve as good approximations of the policy and, most importantly, they differ in one parameter that provides a good heuristic on how to construct the subsets of k-implementable policies. The proposed refinement procedure furthermore entails the ability to first learn a k-tree before learning a k+1-tree.

Relation to partially observable MDPs. Finding optimal k-implementable policies can be phrased as finding a colouring of states and for every colour an action. This reformulation clarifies a connection to the synthesis for memoryless observationbased policies POMDPs [2, 26, 29]. Usually, in POMDPs, one cannot pick the colouring of the states, such variations have been investigated in [13, 25]. However, contrary to those settings, in DTs, the state colouring cannot be arbitrary but must be implementable with a DT.

Contributions. We propose DTPAYNT, an abstraction-refinement loop to find small DTs for MDPs. The loop iteratively invokes an SMT-based routine to represent a given policy as a DT. It can find nontrivial, small DTs on reasonably sized MDPs, and therefore, in contrast to DTCONTROL, it can provide good trade-offs between the size and quality of the resulting DTs. Our approach drastically outperforms the state-of-the-art tool OMDT [37] in finding small decision trees, except on very small MDPs. It finds small DTs implementing (almost) optimal policies for models up to 19 variables (with over 10k states), while OMDT sometimes fails to find a DT outperforming a random policy on those models.

### 2 Background and Problem Statement

**Preliminaries** A distribution over a countable set A is a function  $\mu: A \to [0, 1]$ s.t.  $\sum_{a} \mu(a) = 1$ . The set Distr(A) contains all distributions over A.

**Definition 1 (MDP).** A Markov decision process (MDP) is a tuple  $M = (S, s_0, Act, P)$  with a finite set S of states, an initial state  $s_0 \in S$ , a finite set Act of actions, and a partial transition function  $P: S \times Act \Rightarrow Distr(S)$ .

For an MDP M, we define the available actions in  $s \in S$  as  $Act^{M}(s) := \{\alpha \in Act \mid P(s, \alpha) \neq \bot\}$ . We omit M whenever it is clear from the context. We assume there are no deadlocks, i.e.,  $Act(s) \neq \emptyset$  for each  $s \in S$ . We denote  $P(s, \alpha, s') := P(s, \alpha)(s')$ . An MDP with |Act(s)| = 1 for each  $s \in S$  is a Markov chain (MC). We denote MCs as a tuple  $(S, s_0, P)$ . A (deterministic, memoryless) policy is a function  $\sigma: S \to Act$  with  $\sigma(s) \in Act(s)$  for all  $s \in S$ . The set  $\Sigma^{M}$  denotes the policies for MDP M. A policy  $\sigma \in \Sigma^{M}$  induces the MC  $M^{\sigma} = (S, s_0, P^{\sigma})$  where  $P^{\sigma}(s) = P(s, \sigma(s))$ .

*Specifications* We consider indefinite-horizon reachability and expected reward properties as well as discounted (infinite-horizon) total reward objectives [33].

To simplify the exposition, we formalise our approach only for the maximal reachability probability<sup>3</sup>. Formally, let  $M = (S, s_0, P)$  be an MC, and let  $G \subseteq S$  be a set of goal states. Let  $\mathbb{P}[s \models \Diamond G]$  denote the probability of reaching (some state in) G from state  $s \in S$ . Let  $\mathbb{P}[M \models \Diamond G]$  denote  $\mathbb{P}[s_0 \models \Diamond G]$  in M. For MDPs, specifications are taken over the best and worst possible resolution of the non-determinism. Assume MDP  $M = (S, s_0, Act, P)$ . The maximal reachability probability of G from state  $s_0$  in M is  $\mathbb{P}_{\max}[M \models \Diamond G] \coloneqq \sup_{\sigma \in \Sigma^M} \mathbb{P}[M^{\sigma} \models \Diamond G]$ . We denote  $V(\sigma) \coloneqq \mathbb{P}[M^{\sigma} \models \Diamond G]$  as the value of policy  $\sigma$ . We denote  $\sigma_M^*$  the optimal policy maximising the probability. Details are given in [6].

#### 2.1 Representing Policies as Decision Trees

We study the representation of policies as decision trees. This requires some assumptions on the representation of the MDPs.

Representation of MDPs. In order to symbolically represent policies in MDPs, we assume that state space has some structure. Inspired by PRISM language [27], states are identified by a unique valuation of bounded integer variables  $\mathcal{V} = \{v_i\}_{i=1}^m$ , where each  $v \in \mathcal{V}$  attains a value from a finite domain Dom(v). We write s[v] to denote the value associated with variable v in state s.

We want to allow the policy to pick an arbitrary action whenever the chosen action is not crucial to satisfy a specification. This happens if, in some states, only one action is available or, in MDPs where some nondeterminism is spurious, i.e. where all actions in a state yield the same value. In both cases, no decision needs to be synthesised and therefore, to make the action selection unambiguous, we add a new action  $\alpha_{\text{rand}}$  to every state. This action uniformly selects one of the available actions. Formally, we define  $M' = (S, s_0, Act', P')$  with  $P'(s, \alpha_{\text{rand}}, s') = \frac{1}{|Act(s)|} \sum_{\alpha \in Act(s)} P(s, \alpha, s'), Act'(s) = Act(s) \cup \{\alpha_{\text{rand}}\}$ . We assume that MDP M' = M, i.e., that every MDP contains an action  $\alpha_{\text{rand}}$ .

Trees. A (binary) tree is a tuple  $T = (n_r, N, L, l, r)$  with root node  $n_r$ , the set N of inner nodes, the set L of leaf nodes, and functions  $l, r: N \to N \cup L$ defining the left and right successors of the inner nodes, respectively. A path in a tree T is a finite sequence  $\pi = n_0 \dots n_k$  of nodes where  $n_0 = n_r$  and  $\forall 0 < i \leq k : n_i \in \{l(n_{i-1}), r(n_{i-1})\}$ , its length is k. Path  $\pi$  is complete if it ends in a leaf node. We write  $L(\pi)$  to denote this leaf node. The set Path(T) contains the complete paths in T. The depth of a tree T is defined as the length of its longest path.

**Definition 2 (Decision tree).** Assume an MDP  $(S, s_0, Act, P)$  defined over the set V of variables with domains Dom. A decision tree (DT) for M is a tuple  $\mathcal{T} = (T, \gamma, \delta)$  where (i) T is a binary tree, (ii)  $\gamma$  assigns to every inner node of T a predicate in the form  $v_i \leq b_i$  where  $v_i \in V$  and  $b_i \in Dom(v_i)$ , and (iii)  $\delta$ assigns to every leaf node of T an action  $a \in Act$ .

We lift the notions of leaf nodes, inner nodes, paths and depths of trees to DTs. DTs of depth k are further denoted as k-DTs.

<sup>&</sup>lt;sup>3</sup> Our implementation supports all the aforementioned specifications.

**Definition 3 (Path formula).** In a given  $DT \mathcal{T}$ , a path  $\pi = n_0 \dots n_k$  induces a formula  $\varphi^{\mathcal{T}}(\pi) \coloneqq \bigwedge_{i=1}^k (n_i = l(n_{i-1}) \leftrightarrow \gamma(n_{i-1}))$ .  $\varphi^{\mathcal{T}}(\pi, s) \coloneqq \varphi^{\mathcal{T}}(\pi) [v \leftarrow s[v]]_{v \in \mathcal{V}}$  denotes the corresponding state-path formula where every variable  $v \in \mathcal{V}$ is substituted with the state valuation s[v]. A state  $s \in S$  satisfies path  $\pi$  iff  $\varphi^{\mathcal{T}}(\pi, s)$  holds. Let  $States(\pi)$  denote the set of all states that satisfy  $\pi$ .

Note that the set  $\{States(\pi) \mid \pi \in Path(T)\}$  represents a partition of S.

*Example 2.* Consider the DT of depth 2 from Fig. 1c and let  $\pi = n_r n_T l_2$  be a path that takes a true branch followed by a false branch.  $\pi$  is a complete path of length 2 associated with formula  $\varphi^{\mathcal{T}}(\pi) \equiv (n_T = l(n_r) \leftrightarrow x \leq 0) \land (l_2 = l(n_T) \leftrightarrow y \leq 0) \equiv x \leq 0 \land y > 0$ . For state s with valuation x[s] = y[s] = 1, the corresponding state-path formula  $\varphi^{\mathcal{T}}(\pi, s) \equiv 1 \leq 0 \land 1 > 0$  does not hold. There are two states that satisfy  $\pi$ :  $States(\pi) = \{s \in S \mid x[s] = 0, 1 \leq y[s] \leq 2\}$ .

**Definition 4 (Induced policy).** The DT  $\mathcal{T} = (T, \gamma, \delta)$  induces the policy  $\sigma_{\mathcal{T}}: S \to Act \text{ with } \sigma_{\mathcal{T}}(s) = \delta(L(\pi))$  for path  $\pi$  satisfied by s if  $\delta(L(\pi)) \in Act(s)$  and  $\sigma_{\mathcal{T}}(s) = \alpha_{rand}$  otherwise. The value of the tree is  $V(\mathcal{T}) \coloneqq V(\sigma_{\mathcal{T}})$ .

#### 2.2 Problem Statement

We first consider a classical policy mapping problem: given an unstructured policy, find a concise and interpretable representation in the form of a DT enabling an effective deployment of the policy. This problem has been studied in several domains [19, 30, 35]. We focus on tabular policies for MDPs computed by modern probabilistic model checkers such as STORM [22] or Prism [27]. In contrast to [4, 10], we seek the smallest DT presenting the given policy:

**Policy mapping:** Given MDP M and its policy  $\sigma$ , find a DT  $\mathcal{T}$  with the smallest depth k representing  $\sigma$ , i.e.  $\sigma = \sigma_{\mathcal{T}}$ .

In many cases, the DTs representing the optimal policy  $\sigma_M^*$  are prohibitively large, while there exist significantly smaller DTs that achieve values that are close to the optimal value (recall the example in Fig. 1). Inspired by the recent work [37], we further consider a problem that trades the size of DTs (namely their depth) for the value of these trees:

**Fixed-depth synthesis problem:** Given MDP M, a set G of goal states, and bound k, find a DT  $\mathcal{T}$  of the maximal depth k inducing policy  $\sigma_{\mathcal{T}}$  that maximises the reachability probability to G.

We are interested in anytime synthesis: the faster we find a decision tree achieving high probabilities, the better.

### 3 Solving the policy mapping problem

We first define a *tree template*, a DT with parameterised functions  $\gamma$  and  $\delta$ , that allows us to symbolically represent a *family* of trees.

**Definition 5 (Tree template).** Let MDP M be defined over variables  $\mathcal{V} = \{v_i\}_{i=1}^m$ . A tree template is a tuple  $\mathbb{T} = (T, \Gamma, \Delta)$  where (1) T is a binary tree with inner nodes N and leaves L, (2)  $\Gamma(n)$  assigns to every  $n \in N$  the formula  $\bigwedge_{i=1}^m (\mathcal{D}_n = i \to v_i \leq \mathcal{B}_n^i)$  over free parameters  $\mathcal{D}_n, \mathcal{B}_n^i$  with  $Dom(\mathcal{D}_n) = \{i : 1 \leq i \leq m\}$ ,  $Dom(\mathcal{B}_n^i) = Dom(v_i)$ , and (3)  $\Delta(n)$  assigns to every  $l \in L$  a parameter  $\mathcal{A}_l$  with  $Dom(\mathcal{A}_l) = Act$ . Let  $Par^{\mathbb{T}}$  denote the set of all parameters in  $\mathbb{T}$ .

A parameter assignment f maps every parameter  $p \in Par^{\mathbb{T}}$  to a value from its domain:  $f(p) \in Dom(p)$ . A (parameter assignment) family  $\mathcal{F}$  maps every parameter in  $Par^{\mathbb{T}}$  to some sub-domain:  $\mathcal{F}(p) \subseteq Dom(p)$ . Parameter assignment fbelongs to family  $\mathcal{F}$ , denoted  $f \in \mathcal{F}$ , if  $f(p) \in \mathcal{F}(p)$  for every  $p \in Par^{\mathbb{T}}$ . Family  $\mathcal{F}'$ is a sub-family of  $\mathcal{F}$ , denoted  $\mathcal{F}' \subseteq \mathcal{F}$ , if  $\mathcal{F}'(p) \subseteq \mathcal{F}(p)$  for every  $p \in Par^{\mathbb{T}}$ . Let  $\mathcal{F}^{\mathbb{T}}$ denote the largest (by inclusion) family of parameter assignments. The following lemma clarifies that instantiating all parameters in a parametric expression  $\Gamma(n)$ yields a simple inner node condition. The proof is presented in Appendix A.1.

**Lemma 1.**  $\Gamma(n)[p \leftarrow f(p)]_{p \in Par^{\mathsf{T}}}$  is of the form  $v_i \leq f(\mathcal{B}_n^i)$  where  $i = f(\mathcal{D}_n)$ .

**Definition 6 (Template instantiation).** A parameter assignment  $f \in \mathcal{F}^{\mathbb{T}}$ for the tree template  $\mathbb{T}$  induces  $DT \mathbb{T}(f) = (T, \gamma, \delta)$  where for all  $n \in N$ ,  $\gamma(n) = v_i \leq f(\mathcal{B}_n^i), i = f(\mathcal{D}_n)$  and for all  $l \in L$ ,  $\delta(l) = f(\mathcal{A}_l)$ . The value of the assignment is  $V(f) \coloneqq V(\mathbb{T}(f)) = V(\sigma_{\mathbb{T}(f)})$ .

In a tree template  $\mathbb{T} = (T, \Gamma, \Delta)$ , a path  $\pi = n_0 \dots n_k$  induces a formula  $\varphi^{\mathbb{T}}(\pi) \coloneqq \bigwedge_{i=1}^k (n_i = l(n_{i-1}) \leftrightarrow \Gamma(n_{i-1}))$ . As before, let  $\varphi^{\mathbb{T}}(\pi, s) \coloneqq \varphi^{\mathbb{T}}(\pi)[v \leftarrow s[v]]_{v \in \mathcal{V}}$  denote the corresponding state-path formula. The formula  $\varphi^{\mathbb{T}}(\pi, s)$  essentially describes whether state *s* can satisfy path  $\pi$  in some decision tree  $\mathbb{T}(f), f \in \mathcal{F}^{\mathbb{T}}$ .

*Example 3.* Assume the same path  $\pi = n_r n_T l_2$  from Example 2 in a tree template  $\mathbb{T}$  over the same binary tree of depth 2. Then

$$\varphi^{\mathbb{T}}(\pi) \equiv n_T = l(n_r) \leftrightarrow \left[ \left( \mathcal{D}_{n_r} = 1 \to x \leq \mathcal{B}_{n_r}^1 \right) \land \left( \mathcal{D}_{n_r} = 2 \to y \leq \mathcal{B}_{n_r}^2 \right) \right] \land l_2 = l(n_T) \leftrightarrow \left[ \left( \mathcal{D}_{n_T} = 1 \to x \leq \mathcal{B}_{n_T}^1 \right) \land \left( \mathcal{D}_{n_T} = 2 \to y \leq \mathcal{B}_{n_T}^2 \right) \right].$$

#### 3.1 SMT encoding

We introduce an SMT formula for the policy mapping problem: given policy  $\sigma \in \Sigma^M$  and a tree template  $\mathbb{T}$ , is there a parameter assignment  $f \in \mathcal{F}^{\mathbb{T}}$  that instantiates tree  $\mathbb{T}(f)$  inducing this policy  $\sigma$ ? The variables of the SMT formula are precisely the parameters  $Par^{\mathbb{T}}$ , the theory is quantifier-free linear integer arithmetic. The encoding is defined for some subfamily  $\mathcal{F} \subseteq \mathcal{F}^{\mathbb{T}}$  of parameter assignments since it will be used later in the abstraction-refinement scheme.

$$\begin{split} & \text{SMT encoding for the policy mapping problem} \\ & \text{pol}_{\mathbb{T}}(\mathcal{F},\sigma)\coloneqq \text{dom}(\mathcal{F}) \land \bigwedge_{s\in S} \operatorname{act}_{\mathbb{T}}(s,\sigma(s)), \qquad \text{dom}(\mathcal{F})\coloneqq \bigwedge_{p\in Par^{\mathbb{T}}} p\in \mathcal{F}(p), \\ & \text{act}_{\mathbb{T}}(s,\alpha)\coloneqq \bigwedge_{\pi\in Path(T)} \text{path}_{\mathbb{T}}(s,\alpha,\pi), \quad \text{path}_{\mathbb{T}}(s,\alpha,\pi)\coloneqq \varphi^{\mathbb{T}}(\pi,s) \to \mathcal{A}_{L(\pi)} = \alpha \end{split}$$

Essentially,  $\mathsf{path}_{\mathbb{T}}(s, \alpha, \pi)$  is a formula describing that, if state s satisfies path  $\pi$ , then action  $\alpha$  must be selected in the leaf node  $L(\pi)$ .  $\mathsf{act}_{\mathbb{T}}(s, \alpha)$  is a constraint that describes that action  $\alpha$  must be selected in state s via some path  $\pi$ . Finally,  $\mathsf{pol}_{\mathbb{T}}(\mathcal{F}, \sigma)$  constrains the domains of parameters to  $\mathcal{F}$  and asserts that in every state s, an action must be selected according to  $\sigma(s)$ . A parameter assignment f satisfying  $\mathsf{pol}_{\mathbb{T}}(\mathcal{F}, \sigma)$  is denoted as  $f \models \mathsf{pol}_{\mathbb{T}}(\mathcal{F}, \sigma)$ . We drop the subscript  $\mathbb{T}$  from the formulas whenever it is clear from the context.

**Theorem 1.**  $f \models \mathsf{pol}_{\mathbb{T}}(\mathcal{F}, \sigma)$  iff  $f \in \mathcal{F} \land \sigma_{\mathbb{T}(f)} = \sigma$ . The proof is in Appendix A.2.

Assume a fixed template  $\mathbb{T}$  and assume  $\mathcal{F} = \mathcal{F}^{\mathbb{T}}$ . If  $\mathsf{pol}(\mathcal{F}, \sigma)$  is unsatisfiable, we say that the policy  $\sigma$  is not  $\mathbb{T}$ -*implementable*. For further usage, we want to examine why  $\mathsf{pol}(\mathcal{F}, \sigma)$  is unsatisfiable. The conjunction  $\mathsf{pol}(\mathcal{F}, \sigma)$  is essentially a set  $\{p \in \mathcal{F}(p) \mid p \in Par^{\mathbb{T}}\}$  of domain constraints and a set  $\{\mathsf{path}(s, \sigma(s), \pi) \mid s \in$  $S, \pi \in Path(T)\}$  of state-path constraints. An *unsatisfiable core* [9] is a natural way of distinguishing why  $\mathsf{pol}(\mathcal{F}, \sigma)$  cannot be satisfied. The computation of unsatisfiable cores is supported by existing SMT solvers, e.g. by Z3 [31]

**Definition 7 (Unsatisfiable core).** An unsatisfiable core for  $pol(\mathcal{F}, \sigma)$  is a pair UC =  $(Par^{UC}, SP^{UC})$  with  $Par^{UC} \subseteq Par^{\mathbb{T}}, SP^{UC} \subseteq S \times Path(T)$  s.t. formula  $pol^{UC}(\mathcal{F}, \sigma) \coloneqq \bigwedge_{p \in Par^{UC}} p \in \mathcal{F}(p) \land \bigwedge_{s, \pi \in SP^{UC}} path(s, \sigma(s), \pi)$  is unsatisfiable.

An unsatisfiable core UC is simply a subset of parameters and state-path constraints that make  $pol(\mathcal{F}, \sigma)$  unsatisfiable. Note that  $SP^{UC}$  is typically much smaller than  $S \times Path(T)$  and, in fact, it is not uncommon that  $SP^{UC}$  contains only two state-path pairs. An unsatisfiable core speaks of a few states where selecting actions according to  $\sigma$  (via enabling the corresponding paths) cannot be mapped to the tree template  $\mathbb{T}$ .

#### 3.2 Harmonisation via unsatisfiable cores

Having a precise reason why  $\sigma$  is not T-implementable, harmonisation is a technique used to find two template instantiations  $\mathbb{T}(f_1)$  and  $\mathbb{T}(f_2)$ , differing in the assignment of a single parameter  $p_H \in Par^{\mathbb{T}}$ , that both mimic  $\sigma$ . The basic idea is inspired by inconsistent parameters from [12]. We wish to determine whether there exists parameter  $p_H$  such that assigning two distinct values to  $p_H$  at once makes  $\mathsf{pol}^{\mathsf{UC}}(\mathcal{F}, \sigma)$  satisfiable. For this purpose, to each  $p \in Par^{\mathbb{T}}$  we introduce a fresh duplicate parameter p' with the same domain, introduce a fresh

parameter h with domain  $Dom(h) = Par^{\mathbb{T}}$  and solve the following SMT formula

$$\begin{aligned} \mathcal{H}_{\mathbb{T}}(\mathcal{F},\sigma,SP^{\mathsf{UC}}) &\coloneqq \mathsf{dom}(\mathcal{F}) \wedge \mathsf{dom}(\mathcal{F}_{\mathcal{H}_{\mathbb{T}}}) \wedge \bigwedge_{s,\pi \in SP^{\mathsf{UC}}} \mathcal{H}_{\mathbb{T}}(\mathsf{path}(s,\sigma(s),\pi)) \\ \mathsf{dom}(\mathcal{F}_{\mathcal{H}_{\mathbb{T}}}) &\coloneqq h \in Par^{\mathbb{T}} \wedge \bigwedge_{p \in Par^{\mathbb{T}}} p' \in \mathcal{F}(p) \qquad \mathcal{H}_{\mathbb{T}}(\psi) \coloneqq \psi \lor \bigvee_{p \in Par^{\mathbb{T}}} (h = p \wedge \psi[p \leftarrow p']) \end{aligned}$$

where  $\psi[p \leftarrow p']$  denotes the substitution of parameter p with p' in  $\psi$ . Intuitively, we seek for one parameter  $p_H$  such that replacing *some* instances of  $p_H$  in  $\mathsf{pol}^{\mathsf{UC}}(\mathcal{F},\sigma)$  with a fresh copy  $p'_H$  yields a satisfiable formula. We remark that the formula  $\mathcal{H}_{\mathbb{T}}(\mathcal{F},\sigma,SP^{\mathsf{UC}})$  is not guaranteed to be SAT: multiple duplicates might be necessary to achieve satisfiability. Assume, however, that the formula is SAT with parameter assignment  $f_H$  (denoted  $f_H \models \mathsf{pol}^{\mathsf{UC}}(\mathcal{F},\sigma)$ ). We say that  $p_H \coloneqq f_H(h)$ , the parameter duplicated to achieve satisfiability, is the harmonising parameter.

Let  $f_1 \in \mathcal{F}$  be an assignment with  $\forall p \in Par^{\mathbb{T}} : f_1(p) = f_H(p)$ . While  $f_1$ cannot satisfy  $\operatorname{pol}^{\mathsf{UC}}(\mathcal{F}, \sigma)$ , replacing some instances of  $p_H$  with  $f_H(p'_H)$  makes the formula satisfiable. Let  $f_2 \in \mathcal{F}$  be an assignment that differs from  $f_1$  in this parameter:  $\forall p \in Par^{\mathbb{T}} \setminus \{p_H\} : f_2(p) = f_H(p)$  and  $f_2(p_H) = f_H(p'_H)$ . The solution to the formula yields two trees,  $\mathbb{T}(f_1)$  and  $\mathbb{T}(f_2)$ , that both mimic policy  $\sigma$  on a subset  $\{s \in S \mid \exists \pi \in Path(T) : (s, \pi) \in SP^{\mathsf{UC}}\}$  of states.

Remark 1.  $\operatorname{pol}(\mathcal{F}, \sigma)$  can have multiple unsatisfiable cores, each defining a separate subset of states that together cannot execute  $\sigma$  within the tree template T. We will shortly use the harmonising parameter and its two values in the abstraction refinement scheme, where the choice of a good unsatisfiable core has an enormous impact on the performance. The basic idea here is to use unsatisfiable cores that describe states where choosing a correct action has a big impact on the probability of reaching the set of goal states [10]. To obtain such a core, assume that the state space  $S = \{s_i\}_{i=1}^n$  is ordered. Instead of constructing an unsatisfiable core for  $\operatorname{pol}(\mathcal{F}, \sigma)$ , we construct it for  $\operatorname{dom}(\mathcal{F}) \wedge \bigwedge_{i=1}^m \operatorname{act}(s_i, \sigma(s_i))$  where m is the smallest state index that makes the formula unsatisfiable. In our preliminary evaluation, various orderings of the state space were tested, and, in the final implementation, we use a breadth-first search from the initial state.

#### 4 Abstraction Refinement

We now shift our focus to the fixed-tree synthesis problem: given template  $\mathbb{T}$ , we wish to find a parameter assignment  $f \in \mathcal{F}^{\mathbb{T}}$  with the largest value V(f). The definition below defines the abstraction that is used in the abstraction-refinement loop below.

**Definition 8 (Family-MDP).** Assume an MDP  $M = (S, s_0, Act^M, P)$ , a DT template  $\mathbb{T}$  and a family  $\mathcal{F} \subseteq \mathcal{F}^{\mathbb{T}}$ . An  $\mathcal{F}$ -MDP is an MDP  $M(\mathcal{F}) = (S, s_0, Act^{M(\mathcal{F})}, P)$  where  $\alpha \in Act^{M(\mathcal{F})}(s)$  iff  $\exists f \in \mathcal{F} : \sigma_{\mathbb{T}(f)}(s) = \alpha$ .

Algorithm 1: Recursive tree construction

**Input** : MDP M, goal set G, tree template  $\mathbb{T}$ **Output**: DT  $\mathbb{T}(f)$  s.t.  $f \in \arg \max_{f \in \mathcal{F}^{\mathbb{T}}} V(f)$ 1  $\mathfrak{F} \leftarrow \text{STACK}(), \mathfrak{F}.\text{PUSH}(\mathcal{F}^{\mathbb{T}}), f_{best} = \emptyset, V_{best} = -\infty$ 2 while  $\mathfrak{F} \neq \emptyset$  do  $\mathcal{F} \leftarrow \mathfrak{F}.POP()$ 3  $M(\mathcal{F}) \leftarrow \text{BUILDFAMILYMDP}(M, \mathbb{T}, \mathcal{F}) \triangleright \text{ applying Def. 8}$ 4  $\sigma, V(\sigma) \leftarrow \text{MODELCHECK}(\mathbb{P}_{\max}[M(\mathcal{F}) \models \Diamond G])$  $\mathbf{5}$ if  $V(\sigma) \leq V_{best}$  then continue 6 if  $f \models pol(\mathcal{F}, \sigma)$  then  $f_{best} \leftarrow f, V_{best} \leftarrow V(\sigma)$ , continue 7  $Par^{UC}, SP^{UC} \leftarrow \text{UNSATCORE}(\text{pol}(\mathcal{F}, \sigma)) \triangleright \text{ applying Remark 1 and Def. 7}$ 8 if  $f_H \models \mathcal{H}_{\mathbb{T}}(\mathcal{F}, \sigma, SP^{\mathsf{UC}})$  then 9  $p_H, f_1, f_2 \leftarrow \text{HARMONISE}(f_H) \triangleright$  according to Sec. 3.2 10 for  $f \in \{f_1, f_2\}$  do 11 if  $V(f) > V_{best}$  then  $f_{best} \leftarrow f, V_{best} \leftarrow V(f)$ 12  $\mathcal{F}_1, \mathcal{F}_2 \leftarrow \text{SPLITINFORMED}(\mathcal{F}, p_H, f_1, f_2)$ 13 else  $\mathcal{F}_1, \mathcal{F}_2 \leftarrow \text{SPLITARBITRARY}(\mathcal{F}, Par^{\mathsf{UC}})$ 14  $\mathfrak{F}$ .PUSH $(\mathcal{F}_1)$ ,  $\mathfrak{F}$ .PUSH $(\mathcal{F}_2)$ 15 16 return  $\mathbb{T}(f) \triangleright$  applying Def. 6

An  $\mathcal{F}$ -MDP  $M(\mathcal{F})$  is a sub-MDP of M where some actions are disabled: action  $\alpha$  is enabled in state s iff there exists a parameter assignment  $f \in \mathcal{F}$  that corresponds to a decision tree  $\mathbb{T}(f)$  inducing policy  $\sigma_{\mathbb{T}(f)}$  that picks action  $\alpha$  in that state s. We can create this family-MDP by checking  $\mathsf{dom}(\mathcal{F}) \wedge \mathsf{path}(s, \alpha)$  for every state-action pair. We state without proof (that follows directly from Def. 8) the following proposition asserting that the set of policies for  $M(\mathcal{F})$  includes all policies obtained from  $\mathbb{T}$  using assignments from  $\mathcal{F}$ .

**Proposition 1.** Let  $\mathcal{F} \subseteq \mathcal{F}^{\mathbb{T}}$ . Then  $\forall f \in \mathcal{F} : \sigma_{\mathbb{T}(f)} \in \Sigma^{M(\mathcal{F})}$ .

We propose an abstraction-refinement-based approach to synthesise the best tree from a given template. The basic idea is borrowed from [12] where, for a given family  $\mathcal{F}$  (starting from  $\mathcal{F}^{\mathbb{T}}$ ), an abstraction is built (in our case,  $M(\mathcal{F})$ ) that allows to either prune the family from the search space or to split the family into smaller subfamilies that are recursively analysed. In order to prune family  $\mathcal{F}$ , we compute the maximising policy  $\sigma$  for (sub-)MDP  $M(\mathcal{F})$  and either show that no  $f \in \mathcal{F}$  has a better value than the current optimum or that  $\sigma$ is  $\mathbb{T}$ -implementable using SMT encoding from above, updating the optimum. Otherwise, to partition  $\mathcal{F}$ , we use harmonisation from Sec. 3.2.

The approach is summarised in Algorithm 1. On l.1 we start with a stack  $\mathfrak{F}$  of sub-families, initially containing  $\mathcal{F}^{\mathbb{T}}$ , and initialise the running optimum  $f_{best}$  and its value  $V_{best}$ . In every iteration, we pop a family  $\mathcal{F}$  from the stack, build the corresponding  $M(\mathcal{F})$  and compute the policy  $\sigma$  that maximises  $\mathbb{P}[M(\mathcal{F}) \models \Diamond G]$ (ll. 3-5). If its value  $V(\sigma)$  is worse than  $V_{best}$ , then no assignment in  $\mathcal{F}$  induces a tree with a better value, and thus this family is pruned from the search space (l.6). Otherwise, we solve the SMT formula  $\mathsf{pol}(\mathcal{F}, \sigma)$  to check whether  $\sigma$  is  $\mathbb{T}$ -implementable. If  $f \in \mathcal{F}$  is a parameter assignment s.t.  $\sigma_{\mathbb{T}(f)} = \sigma$ , we update the running optimum and prune the family (l.7). Otherwise, on ll.8-14 we split  $\mathcal{F}$  into sub-families  $\mathcal{F}_1, \mathcal{F}_2$  and push these onto the stack  $\mathfrak{F}$  (l.15).

#### Theorem 2. Algorithm 1 is sound and complete. The proof is in Appendix A.3.

Any nontrivial splitting makes Alg. 1 terminate: the number  $|\mathcal{F}^{\mathbb{T}}|$  of possible parameter assignment is finite and, in the worst case, a nontrivial splitting yields a family with a single assignment f, in which case  $M(\{f\})$  is an MC with only one policy  $\sigma_{\mathbb{T}(f)}$  and the SMT formula  $\mathsf{path}(\{f\}, \sigma_{\mathbb{T}(f)})$  is satisfiable with parameter assignment f. However, even for a tree template of small depth, the number of template instantiations is insurmountable and thus a proper splitting strategy should yield sub-families that can be pruned as soon as possible.

To deal with enormous design spaces, the abstraction refinement framework of [12] successfully used the notion of inconsistent parameters (holes), where a split was made on a hole for which the optimising policy wanted to pick multiple values. In our framework, the harmonising parameter  $p_H$  plays the role of this inconsistent hole, and therefore, on l.8, we extract the unsatisfiable core (see Remark 1) and solve the SMT formula  $\mathcal{H}_{\mathbb{T}}(\mathcal{F}, \sigma, SP^{\mathsf{UC}})$ , as described in Sec. 3.2. Assume the formula is SAT with the harmonising parameter  $p_H$  and  $f_1, f_2$  is the corresponding pair of trees that differ in the value of  $p_H$ . We then split  $\mathcal{F}$  into subfamilies  $\mathcal{F}_1, \mathcal{F}_2$ by splitting the domain  $\mathcal{F}(p_H)$  s.t.  $f_1(p_H) \in \mathcal{F}_1(p_H)$  and  $f_2(p_H) \in \mathcal{F}_2(p_H)^4$ . The idea here is to build in subsequent iterations sub-MDPs  $M(\mathcal{F}_1), M(\mathcal{F}_2)$  that do not contain  $\sigma$ , although this cannot always be guaranteed. Otherwise, if the harmonising formula is unsatisfiable, we split the family arbitrarily on some parameter from  $Par^{UC}$ . We remark that during our experiments the harmonising formula was practically always satisfiable. Additionally, on ll.11-12 we update the value of  $V_{best}$  based on the values  $V(f_1), V(f_2)$ . Empirically, this leads to a mildly better performance.

Iterative mode. Even for modest values of k, Algorithm 1 cannot explore all parameter assignments. Finding good assignments early can accelerate abstraction refinement [1,12] as it prunes sub-optimal families faster. Thus, when searching for the optimal k-tree, it can be beneficial to first go through families of 0-, 1-, 2-trees, etc., where good values are easier to find. This idea inspired the *iterative mode* of our abstraction refinement approach that proceeds as follows. We iteratively use Algorithm 1 on templates of trees of depths  $0, 1, \ldots, k_{\max}$ ; in each iteration, we keep the current optimum  $f_{best}$  and its value  $V_{best}$  and use it in subsequent iterations. To ensure that the algorithm reaches depth  $k_{\max}$ , we run Algorithm 1 on lower depths  $0, 1, \ldots, k_{\max}-1$  with a timeout, that we empirically choose to be  $t/(2 \cdot k_{\max})$ , such that at least 50% of the given time is dedicated to the search on depth  $k_{\max}$ .

**Tree hints.** Having (partially) explored a family of (k-1)-trees, we can accelerate the search for the best k-tree even further by first looking at k-trees that mimic a good (k-1)-tree  $\mathcal{T}_{k-1}$ . Our abstraction-refinement approach on families naturally

<sup>&</sup>lt;sup>4</sup> If  $p_H = \mathcal{B}_n^i$ , i.e. it is a parameter for a variable bound, then its domain (initially, an interval) is split into two sub-intervals.

supports this idea: before running Algorithm 1 with a stack containing the whole family  $\mathcal{F}^{\mathbb{T}_k}$  for a tree template  $\mathbb{T}_k$  of depth k, we can first make it look within the family  $\mathcal{F}'$  of assignments that mimic  $\mathcal{T}_{k-1}$ . Intuitively,  $\mathcal{F}' \subset \mathcal{F}^{\mathbb{T}_k}$  describes all k-trees that, in the inner nodes on the first k-1 levels, behave according to  $\mathcal{T}_{k-1}$ , and behave arbitrarily on the last k-th level as well as in the leaves. Putting family  $\mathcal{F}'$  on top of the stack prioritises the search for the best k-tree within this family, increasing the chance of finding good k-trees early.

**Tree post-processing.** Having finished the search for the best tree, we postprocess this tree to remove redundant nodes. We perform two steps. First, we remove every node  $n \in N \cup L$  for which  $States(\pi(n)) = \emptyset$  where  $\pi(n)$  is the unique path from the root to n, that is, no state  $s \in S$  can take a path to n. Second, if for an inner node  $n \in N$  it holds that  $l(n), r(n) \in L$  and  $\delta(l(n)) = \delta(r(n))$ , i.e. the two children of n are leaves selecting the same action, then both children are removed and n becomes a leaf associated with this action.

### 5 Experimental Evaluation

In the experimental evaluation, we investigate the following two synthesis algorithms: (1) DTMAP is an algorithm that solves the policy mapping problem by trying to map  $\sigma$  to templates of increasing depths k using SMT encoding from Sec. 3.1. (2) DTPAYNT is an algorithm that solves the fixed-depth synthesis problem (with an explicit timeout) using abstraction refinement in an iterative mode using tree hints from Sec. 4. The proposed synthesis algorithms are implemented on top of PAYNT [3] and STORM [22], utilising Z3 [31] to solve SMT queries. The implementation and all the considered benchmarks are publicly available<sup>5</sup> Our evaluation focuses on the following three questions:

- Q1: Can DTMAP find DTs representing the optimal policy that are smaller than the DTs learned by DTCONTROL [4]?
- Q2: Does DTPAYNT outperform the OMDT [37] that is based on a MILP formulation? Can DTPAYNT scale to more complex MDPs?
- Q3: Can DTPAYNT find DTs providing a good trade-off between the value and size with respect to the DTs found by DTCONTROL or OMDT?

Setting. The timeout (TO) for all experiments was 20 minutes<sup>6</sup>. All the experiments were run on a machine equipped with AMD EPYC 9124 16-core Processor and 380GB RAM. Each method was run on a single CPU core.

Benchmarks. In order to answer the questions, we consider three types of benchmarks: (1) The 11 models from OMDT [37]<sup>7</sup>. These benchmarks use expected discounted reward. (2) The standard MDP benchmarks from the QComp evaluation [11] with 10 models with state variables defined<sup>8</sup>. We used the original

<sup>&</sup>lt;sup>5</sup> Hidden for the review process.

<sup>&</sup>lt;sup>6</sup> Based on our preliminary experiments as well as the results from [37] that use 5-minute and 2-hour TOs, the 20-minute TO seems to be a good compromise.

 $<sup>^{7}</sup>$  We excluded 2 models: one uses continuous domains, one has multiple initial states.

<sup>&</sup>lt;sup>8</sup> We excluded 2 benchmarks where action labels overlapped.

Table 1: Comparison with DTCONTROL for the policy mapping problem. k and n denote the depth and the number of decision nodes in the resulting tree. Depth >k indicates that DTMAP proved that there is no k-DT representing the given policy. Bold numbers indicate the DT with the smallest n. The runtimes are in seconds. The numbers in brackets report the number of choices.

model	dtMap			dtControl		model	dtMap			dtControl	
model	time	k	n	k	$\overline{n}$	model	time	k	$\overline{n}$	k	$\overline{n}$
lake-12 (576)	4	7	70	12	73	traffic $(722)$	10.6	6	34	12	32
sys-2 $(2.3k)$	43	8	67	8	41	pacman $(3k)$	6	5	<b>23</b>	14	183
firewire (5.5k)	19	5	23	9	69	pnueli (6.5k)	4	6	59	15	857
tictactoe (22k)	ТО	>5	-	14	1170	maze-7 (8.2k)	ТО	$>\!\!6$	-	14	<b>280</b>
consensus (9.2k)	14	5	<b>22</b>	9	51	resource (11k)	<1	3	7	16	248
philos $(11k)$	12	6	<b>41</b>	16	946	rabin $(15k)$	ТО	>5	-	21	154

specification for the comparison with DTCONTROL in Q1. Where possible, we considered a derived discounted-reward specification required by OMDT in Q2 and Q3. (3) A larger fully observable variant of the classical maze [21] problem with a discounted-reward specification. In total, we considered 22 models. Information about the models is reported in Appendix B. We group the benchmarks into two categories: (1) smaller models with the number of choices (upper bounded by  $|S| \cdot |Act|$ ) below 3k and (2) larger models with the number of choices above 3k (mostly from the QComp benchmark set). For the comparison in Q2 and Q3, we equipped all models with action  $\alpha_{rand}$  executed in states where the corresponding path in the decision tree does not define a valid action. Since OMDT requires every action to be enabled in every state, we add to the QComp models (in Q2 and Q3) the missing actions that behave the same as  $\alpha_{rand}$ .

#### Q1: Comparison with dtControl

We consider the policy mapping problem, allowing for a direct comparison between the proposed SMT encoding used in DTMAP (see Sec. 3) and DTCONTROL. Table 1 reports the performance of these methods on 12 selected benchmarks (out of 22) that demonstrate the key observations from this comparison<sup>9</sup>. For all experiments, we used STORM to compute the optimal reference policy.

Runtimes. For 6 out of 22 models, DTMAP was not able to find the DT representing the given (optimal) policy  $\sigma_M^*$  in 20 minutes. In these cases, >k denotes that DTMAP was able to prove that there is no DT of depth k that can represent the given  $\sigma$  and reached the TO when solving the SMT formula for k + 1. We can see that this happens only for some large models and depths over 4, where solving the SMT formula becomes the bottleneck. In the remaining cases, DTMAP found the minimal k-DT representing  $\sigma_M^*$  – in almost all cases, it takes less than 20 seconds. The runtimes for DTCONTROL are less than 2 seconds for all benchmarks.

<sup>&</sup>lt;sup>9</sup> Comparison on the complete benchmark set is reported in Appendix C.1.



Fig. 2: Comparison on the fix-depth synthesis problem. The scatter plot shows the relative normalised values of the best k-DTs found by OMDT and DTPAYNT in the 20-minute timeout. One point represents the results of both methods for a specific model and a specific depth.

Tree sizes. In terms of the tree depth k, DTMAP is able to find significantly smaller trees almost in all cases. In terms of the number of decision nodes (denoted as n), the situation is slightly different. Recall that DTMAP optimises solely for depth k and the number of nodes is reduced during the post-processing step. We can see that for the smaller models (the upper part of the table), both methods find DTs with a similar number of decision nodes with the exception of *sys-2*. On the other hand, for the large models (the lower part of the table), DTMAP finds significantly (sometimes more than 20x) smaller DTs (see *resource* and *philos*).

#### Q2: Comparison with OMDT

We consider the fixed-depth synthesis problem and compare DTPAYNT with OMDT. We performed a comparison including all benchmarks and tree depths up to k = 6. To ensure OMDT is applicable, we now consider discounted rewards for all models<sup>10</sup>. This yields 19 models and 114 fixed-depth synthesis problems.

Results. Figure 2 depicts two scatter plots visualising the values of the best DTs found by DTPAYNT and OMDT (within the timeout) for the particular synthesis problem (one model and one depth)<sup>11</sup>. The axes describe the relative normalised value of the best k-DT found by the two methods. The value is normalized such that 0 corresponds to a uniform random policy and 1 to an optimal MDP policy. Orange triangles correspond to the smaller models (with the number of choices below 3k), while green circles correspond to the larger models (with the number of choices above 3k). The left figure shows the results for the depths  $k \in \{1, 2, 3\}$  and the right figure shows the results for the depths  $k \in \{4, 5, 6\}$ .

On the smaller models, OMDT typically outperforms DTPAYNT: For smaller k, the difference is mostly insignificant. For some models (i.e. *lake-12* and *sys-2*) and larger k, OMDT achieves significantly better values than DTPAYNT.

 $<sup>^{10}</sup>$  We hence exclude the models that do not admit interesting discounted variants.

<sup>&</sup>lt;sup>11</sup> Detailed statistics for the experiments are reported in Appendix C.2.



Fig. 3: Trade-off between tree quality and size. The left part contains models with less than 3k choices. The upper part shows the normalised values of the synthesised DTs (the same normalisation as in Fig. 2 is used; DTCONTROL always maps an optimal policy). The lower part shows the number of decision nodes in the synthesised trees.

On the majority of larger models, DTPAYNT significantly outperforms OMDT. Only for a few models and small values of k, OMDT achieves similar values. In many cases (especially for large k), the difference in the quality is significant (e.g. maze-7 for k = 5, but also pnueli and resource for k = 3). We also observe that, in many cases, OMDT is not able to find any reasonable solution for  $k \ge 3$ . In fact, in these cases, OMDT finds worse DTs compared to those it found for smaller  $k^{12}$ , and sometimes even finds a DT whose value is worse than the uniform random policy (tictactoe for k = 4 and resource for k = 6).

Runtimes. In most cases (larger models and/or larger k), both tools reach the timeout (20 minutes): DTPAYNT is not able to completely explore the family of trees; OMDT is not able to reduce the gap between the lower and upper bound in the underlying MILP below the given precision. We can observe (see Appendix) that for larger models, DTPAYNT can find better DTs significantly faster.

*Conclusion.* These experiments demonstrate that: (1) Monolithic MILP formulation implemented in OMDT provides a better exploration strategy for easier synthesis problems (in terms of number of choices or depth). In these cases, solving one harder MILP program is more efficient than solving many simpler SMT and MDP model-checking queries. (2) For more complicated problems, solving the MILP is not tractable. In contrast, DTPAYNT is able to find high-quality DTs for larger models and depths beyond 3.

#### Q3: Trade-offs between the value and size

Finally, we focus on trade-offs between the value and size of the DTs found DTPAYNT and OMDT with respect to the DTs representing the optimal policy found by DTCONTROL. Fig. 3 reports DTs that provide (practically) the most interesting trade-offs. It reports results for 14 models (out of 19 in Q2) representing the challenging problems including models not solved by DTMAP in Q1<sup>13</sup>.

The lower part of Fig. 3 compares the sizes of the DTs (the number of decision nodes) while the upper part compares the relative values (as in Fig. 2, we plot the relative normalised values). As expected from Q2, for small models, DTPAYNT and OMDT provide similar trade-offs except for sys-2 and lake-12 where DTPAYNT fails to find DTs with better values. The situation for the larger models is diametrically opposite. In the majority of the models, OMDT is not able to find DTs with a reasonable performance. For *pnueli* and *rabin*, the OMDT finds only 0-DT (playing a single action) having the same/similar value as the random policy. On the other hand, DTPAYNT is able to find significantly smaller DTs with much better values for all models except *wlan*. We would like to emphasise that even for models where DTPAYNT fails to map the given optimal policy to a DT, thanks to the abstraction refinement procedure (see Sec. 4), it is able to find DTs with a very good trade-off – see e.g. *csma* and *rabin*.

### 6 Related Work

The related work in learning [4] and MILP-based synthesis [37] of decision trees as well as in deductive controller synthesis [2] is discussed in the introduction.

Learning concise representation of neural policies. With the boom of explainable reinforcement learning, various methods for learning concise representations of neural policies have been proposed. Imitation learning methods such as VIPER [7] extract a DT from a more complex teacher policy using a supervised learning paradigm. As shown in [37], imitating a complex policy using a small DT can lead to poor performance as the limited capacity of the DT is used ineffectively. A different approach for overcoming this limitation has been recently proposed in [35]. The authors introduce a new type of MDP (so-called iterative bounding MDP) where each policy corresponds to a DT policy for the base MDP. Especially for small DTs, this approach significantly outperforms VIPER. A different line of work focuses on learning a programmatic representation of policies using an oracle in the form of neural policy. In the seminal paper [36], the authors showed how to search over programmatic policies that minimise the distance from the oracle. More recently, a fast distillation method that uses regularized oblique trees to produce tree programs that fits neural oracle has been proposed [24].

*Beyond DTs.* Recently, alternative representations of policies in MDPs have been studied. In [8], the authors establish a tight connection between program-level construction of strategies resolving nondeterminism in probabilistic programs and

<sup>&</sup>lt;sup>12</sup> This can, in principle, also happen to DTPAYNT, but it rarely happens.

<sup>&</sup>lt;sup>13</sup> Recall, as in Q2, we consider discounted reward specifications for all models.

finding good policies in (countably infinite) MDPs. This enables a direct construct of programmatic policies. A different line of work introduces templates of decision diagrams using hierarchical control structures with under-specified entities to encapsulate and reuse common decision-making patterns [18]. In contrast to our templates used to effectively reason about sets of DTs, the hierarchical decision diagrams aim at a more concise and explainable representation of the policies.

### 7 Conclusion

This paper presents DTPAYNT, a novel approach to synthesise small DTs providing good trade-offs between the quality and size. Our experiments demonstrate clear advantages wrt. the state-of-the-art. In the future, we will investigate how to exploit counter-examples for DTs and symbiotically combine DTPAYNT with DTCONTROL to handle more complex MDPs.

### References

- Andriushchenko, R., Češka, M., Junges, S., Katoen, J.P.: Inductive synthesis for probabilistic programs reaches new horizons. In: TACAS. LNCS, vol. 12651, pp. 191–209. Springer (2021)
- Andriushchenko, R., Češka, M., Junges, S., Katoen, J.P.: Inductive synthesis of finite-state controllers for POMDPs. In: UAI. vol. 180, pp. 85–95. PMRL (2022)
- Andriushchenko, R., Češka, M., Junges, S., Katoen, J.P., Stupinský, Š.: PAYNT: a tool for inductive synthesis of probabilistic programs. In: CAV. LNCS, vol. 12759, pp. 856–869. Springer (2021)
- Ashok, P., Jackermeier, M., Křetínský, J., Weinhuber, C., Weininger, M., Yadav, M.: dtcontrol 2.0: Explainable strategy representation via decision tree learning steered by experts. In: TACAS. LNCS, vol. 12652, pp. 326–345. Springer (2021)
- Ashok, P., Křetínský, J., Larsen, K.G., Le Coënt, A., Taankvist, J.H., Weininger, M.: SOS: safe, optimal and small strategies for hybrid Markov decision processes. In: QEST. pp. 147–164. Springer (2019)
- Baier, C., de Alfaro, L., Forejt, V., Kwiatkowska, M.: Model checking probabilistic systems. In: Handbook of Model Checking, pp. 963–999. Springer (2018)
- Bastani, O., Pu, Y., Solar-Lezama, A.: Verifiable reinforcement learning via policy extraction. Advances in neural information processing systems **31** (2018)
- Batz, K., Biskup, T.J., Katoen, J.P., Winkler, T.: Programmatic strategy synthesis: Resolving nondeterminism in probabilistic programs. Proceedings of the ACM on Programming Languages 8(POPL), 2792–2820 (2024)
- 9. Biere, A., Heule, M., van Maaren, H.: Handbook of satisfiability, vol. 185. IOS press (2009)
- Brázdil, T., Chatterjee, K., Chmelík, M., Fellner, A., Křetínský, J.: Counterexample explanation by learning small strategies in Markov decision processes. In: CAV. pp. 158–177. Springer (2015)
- Budde, C.E., Hartmanns, A., Klauck, M., Křetínský, J., Parker, D., Quatmann, T., Turrini, A., Zhang, Z.: On correctness, precision, and performance in quantitative verification: QComp 2020 competition report. In: ISoLA. pp. 216–241. Springer (2020)
- Češka, M., Jansen, N., Junges, S., Katoen, J.P.: Shepherding hordes of Markov chains. In: TACAS. LNCS, vol. 11428, pp. 172–190. Springer (2019)
- Chatterjee, K., Chmelik, M., Topcu, U.: Sensor synthesis for pomdps with reachability objectives. In: ICAPS. pp. 47–55. AAAI Press (2018)
- David, A., Jensen, P.G., Larsen, K.G., Mikučionis, M., Taankvist, J.H.: Uppaal stratego. In: TACAS. pp. 206–211. Springer (2015)
- Dehnert, C., Jansen, N., Wimmer, R., Ábrahám, E., Katoen, J.P.: Fast debugging of PRISM models. In: ATVA. LNCS, vol. 8837, pp. 146–162. Springer (2014)
- Delgrange, F., Katoen, J.P., Quatmann, T., Randour, M.: Simple strategies in multi-objective mdps. In: TACAS. pp. 346–364. Springer (2020)
- 17. Drager, K., Forejt, V., Kwiatkowska, M., Parker, D., Ujma, M.: Permissive controller synthesis for probabilistic systems. Logical Methods in Computer Science 11 (2015)
- Dubslaff, C., Klös, V., Päßler, J.: Template decision diagrams for meta control and explainability. In: XAI. pp. 219–242. Springer (2024)
- Gupta, U.D., Talvitie, E., Bowling, M.: Policy tree: Adaptive representation for policy gradient. In: AAAI. vol. 29 (2015)
- Hancock, T., Jiang, T., Li, M., Tromp, J.: Lower bounds on learning decision lists and trees. Information and Computation 126(2), 114–122 (1996)

- Hauskrecht, M.: Incremental methods for computing bounds in partially observable Markov decision processes. In: AAAI/IAAI. pp. 734–739 (1997)
- Hensel, C., Junges, S., Katoen, J., Quatmann, T., Volk, M.: The probabilistic model checker Storm. Int. J. Softw. Tools Technol. Transf. 24(4), 589–610 (2022)
- Junges, S., Jansen, N., Dehnert, C., Topcu, U., Katoen, J.: Safety-constrained reinforcement learning for MDPs. In: TACAS. LNCS, vol. 9636, pp. 130–146. Springer (2016)
- Kohler, H., Delfosse, Q., Akrour, R., Kersting, K., Preux, P.: Interpretable and editable programmatic tree policies for reinforcement learning. Preprint arXiv:2405.14956 (2024)
- Konsta, A.M., Lluch Lafuente, A., Matheja, C.: What should be observed for optimal reward in pomdps? In: CAV. pp. 373–394. Springer (2024)
- Kumar, A., Zilberstein, S.: History-based controller design and optimization for partially observable MDPs. In: ICAPS. pp. 156–164. AAAI Press (2015)
- Kwiatkowska, M., Norman, G., Parker, D.: PRISM 4.0: Verification of probabilistic real-time systems. In: CAV. LNCS, vol. 6806, pp. 585–591. Springer (2011)
- Laurent, H., Rivest, R.L.: Constructing optimal binary decision trees is np-complete. Information processing letters 5(1), 15–17 (1976)
- Li, Y., Yin, B., Xi, H.: Finding optimal memoryless policies of pomdps under the expected average reward criterion. European Journal of Operational Research 211(3), 556–567 (2011)
- Likmeta, A., Metelli, A.M., Tirinzoni, A., Giol, R., Restelli, M., Romano, D.: Combining reinforcement learning with rule-based controllers for transparent and general decision-making in autonomous driving. Robotics and Autonomous Systems 131, 103568 (2020)
- de Moura, L., Bjørner, N.: Z3: An efficient SMT solver. In: TACAS. pp. 337–340. Springer (2008)
- Narodytska, N., Ignatiev, A., Pereira, F., Marques-Silva, J.: Learning optimal decision trees with SAT. In: IJCAI. pp. 1362–1368. AAAI Press (2018)
- Puterman, M.L.: Markov decision processes: discrete stochastic dynamic programming. John Wiley & Sons (2014)
- Sutton, R.S., Barto, A.G.: Reinforcement Learning: An Introduction. MIT Press (2018)
- Topin, N., Milani, S., Fang, F., Veloso, M.: Iterative bounding mdps: Learning interpretable policies via non-interpretable methods. In: AAAI. vol. 35, pp. 9923– 9931 (2021)
- Verma, A., Murali, V., Singh, R., Kohli, P., Chaudhuri, S.: Programmatically interpretable reinforcement learning. In: ICML. vol. 80, pp. 5052–5061. PMLR (2018)
- Vos, D., Verwer, S.: Optimal decision tree policies for Markov decision processes. In: IJCAI. pp. 5457–5465 (2023)

### A Proofs

In the following, assume an MDP M and a tree template  $\mathbb{T} = (T, \Gamma, \Delta)$ .

#### A.1 Proof of Lemma 1

Assume an arbitrary  $n \in N_T$  and  $f \in \mathcal{F}^{\mathbb{T}}$ . Let  $f(\mathcal{D}_n) = i$ . Then

$$\begin{split} \Gamma(n)[p \leftarrow f(p)]_{p \in Par^{\mathbb{T}}} &\equiv \bigwedge_{j} \left( f(\mathcal{D}_{n}) = j \rightarrow v_{j} \leq f(\mathcal{B}_{n}^{j}) \right) \\ &\equiv \left( f(\mathcal{D}_{n}) = i \rightarrow v_{i} \leq f(\mathcal{B}_{n}^{i}) \right) \land \bigwedge_{j \neq i} \left( f(\mathcal{D}_{n}) = j \rightarrow v_{j} \leq f(\mathcal{B}_{n}^{j}) \right) \\ &\equiv \left( i = i \rightarrow v_{i} \leq f(\mathcal{B}_{n}^{i}) \right) \land \bigwedge_{j \neq i} \left( i = j \rightarrow v_{j} \leq f(\mathcal{B}_{n}^{j}) \right) \\ &\equiv v_{i} \leq f(\mathcal{B}_{n}^{i}). \end{split}$$

#### A.2 Proof of Theorem 1

Assume a policy  $\sigma \in \Sigma^M$  and a sub-family  $\mathcal{F} \subseteq \mathcal{F}^{\mathbb{T}}$  of parameter assignments. Lemma 2. Let  $\pi \in Path(T)$ ,  $f \in \mathcal{F}$ . Then  $\varphi^{\mathbb{T}}(\pi)[p \leftarrow f(p)]_{p \in Par^{\mathbb{T}}} \equiv \varphi^{\mathbb{T}(f)}(\pi)$ . *Proof.* From Lemma 1 and Definitions 6 and 3 it follows that

$$\varphi^{\mathbb{T}}(\pi)[p \leftarrow f(p)]_{p \in Par^{\mathbb{T}}} \equiv \bigwedge_{i=1}^{k} \left( n_{i} = l(n_{i-1}) \leftrightarrow \Gamma(n_{i-1})[p \leftarrow f(p)]_{p \in Par^{\mathbb{T}}} \right)$$
$$\equiv \bigwedge_{i=1}^{k} \left( n_{i} = l(n_{i-1}) \leftrightarrow v_{f(\mathcal{D}_{n_{i-1}})} \leq \mathcal{B}_{n_{i-1}}^{f(\mathcal{D}_{n_{i-1}})} \right)$$
$$\equiv \varphi^{\mathbb{T}(f)}(\pi).$$

**Corollary 1.** For arbitrary  $s \in S$ ,  $\varphi^{\mathbb{T}}(\pi, s)[p \leftarrow f(p)]_{p \in Par^{\mathbb{T}}} \equiv \varphi^{\mathbb{T}(f)}(\pi, s)$ .

We now prove Theorem 1. Note that  $f \models \operatorname{dom}(\mathcal{F})$  iff  $f \in \mathcal{F}$  and thus, to prove Theorem 1, it is sufficient show that, under assumption  $f \in \mathcal{F}$ ,  $f \models \bigwedge_{s \in S} \operatorname{act}_{\mathbb{T}}(s, \sigma(s))$  iff  $\sigma_{\mathbb{T}(f)} = \sigma$ .

Assume  $f \models \bigwedge_{s \in S} \operatorname{act}_{\mathbb{T}}(s, \sigma(s))$ . Let  $s \in S$  be an arbitrary state. Then  $f \models \bigwedge_{\pi \in Path(T)} \varphi^{\mathbb{T}}(\pi, s) \to \mathcal{A}_{L(\pi)} = \sigma(s)$ . From Corollary 1 it holds that  $\bigwedge_{\pi \in Path(T)} \varphi^{\mathbb{T}(f)}(\pi, s) \to f(\mathcal{A}_{L(\pi)}) = \sigma(s)$ . Observe the left-hand side of the implication: condition  $\varphi^{\mathbb{T}(f)}(\pi, s)$  can hold for exactly one path  $\pi$  since state ssatisfies exactly one path in  $\mathbb{T}(f)$ . Assume  $\pi$  is such a path, then  $f(\mathcal{A}_{L(\pi)}) = \sigma(s)$ must hold. From Def. 6 it follows that  $\mathbb{T}(f)$  is a DT  $(T, \gamma, \delta)$  with  $\delta(L(\pi)) =$  $f(\mathcal{A}_{L(\pi)}) = \sigma(s)$  and therefore, by Def. 4,  $\sigma_{\mathbb{T}(f)}(s) = \delta(L(\pi)) = \sigma(s)$ .

Note that in the proof above we picked an arbitrary state  $s \in S$  and applied only equivalences and definitions, therefore, from  $\sigma_{\mathbb{T}(f)} = \sigma$  it follows that  $f \models \bigwedge_{s \in S} \operatorname{act}_{\mathbb{T}}(s, \sigma(s)).$ 

#### A.3 Proof of Theorem 2

We reiterate that any nontrivial splitting makes Algorithm 1 terminate since the family  $\mathcal{F}^{\mathbb{T}}$  is finite. Let  $\mathcal{F}_{\max} \coloneqq \arg \max_{f \in \mathcal{F}^{\mathbb{T}}} V(f)$  be a set of optimal assignments, i.e. correct outputs of Algorithm 1. Note that  $\mathcal{F}_{\max} \neq \emptyset$  and thus Algorithm 1 is complete iff it is sound. To show the soundness, it is sufficient to inspect ll.6-7, where a sub-family can be pruned, and show that on these lines we do not discard some  $f^* \in \mathcal{F}_{\max}$ . Assume an arbitrary iteration of the algorithm where sub-family  $\mathcal{F} \subseteq \mathcal{F}^{\mathbb{T}}$  is analysed. Let  $\sigma$  be a maximising policy for  $M(\mathcal{F})$  obtained on l.5. From Proposition. 1 it follows that  $V(\sigma) \geq \max_{f \in \mathcal{F}} V(f)$ . If  $\mathcal{F}$  is pruned on l.6 because  $V(\sigma) \leq V_{best}$ , then  $\max_{f \in \mathcal{F}} V(f) \leq V_{best}$ , i.e. no  $f \in \mathcal{F}$  has better value than  $f_{best}$ . Otherwise, if  $\mathcal{F}$  is pruned on l.7,  $f_{best}$  is updated with assignment f for which  $V(f) = V(\sigma) \geq \max_{f \in \mathcal{F}} V(f)$ . In both cases, no  $f^* \in \mathcal{F}_{\max}$  is discarded unless  $f_{best} \in \mathcal{F}_{\max}$ .

### **B** Benchmarks

This section contains information about all of the 22 considered models. This information is summarised in Table 2. For the models in the bottom part (these are the models from the QComp benchmark set), the number of choices changes for Q2 and Q3 experiments as we consider their discounted variants there. To compute the choices for these variants, you can use the formula  $|S| \cdot |Act|$ . All the benchmarks are available at https://anonymous.4open.science/r/dt-synthesis-benchmarks-tacas25.

model	vars	S	Act	choices	model	vars	S	Act	choices
maze-7	9	2039	4	8156	3d	3	125	6	750
blackjack	3	533	2	1066	lake-4	2	16	4	64
lake-8	2	64	4	256	lake-12	2	144	4	576
inventory	1	101	100	10100	sys-1	8	256	9	2304
sys-2	8	256	9	2304	sys-tree	7	128	8	1024
tictactoe	27	2424	9	21816	traffic	4	361	2	722
consensus	5	6160	13	9232	$\operatorname{csma}$	11	7958	16	7988
firewire	10	4093	13	5515	ij	10	1023	10	5120
pacman	11	2270	10	2951	philos	4	3192	52	10932
pnueli	3	1949	62	6457	rabin	19	10240	16	15388
resource	7	3291	4	10571	wlan	11	3126	33	4189

Table 2: Model info.

## C Complete experimental results

This section provides the experimental results for all of the models considered in our benchmark set.

### C.1 Comparison with dtControl

Table 3 contains the results of all 22 benchmarks we considered for the policy mapping problem.

model			dtMa	Р	dtControl			
	choices	time	depth	nodes	time	depth	nodes	
lake-4	64	<1	4	8	<1	5	10	
lake-8	256	<1	6	38	<1	8	40	
lake-12	576	4.1	7	70	<1	12	73	
traffic	722	10.6	6	34	<1	12	32	
3d	750	<1	3	6	<1	10	68	
sys-tree	1024	2.7	7	35	<1	7	12	
blackjack	1066	<1	4	10	<1	7	8	
sys-1	2304	150.2	8	97	<1	8	76	
sys-2	2304	42.6	8	67	<1	8	41	
pacman	2951	6.2	5	<b>23</b>	<1	14	183	
wlan	4189	ТО	>5	-	<1	11	159	
ij	5120	ТО	>7	-	<1	10	<b>645</b>	
firewire	5515	19.3	5	<b>23</b>	<1	9	69	
pnueli	6457	4.4	6	<b>59</b>	<1	15	857	
$\operatorname{csma}$	7988	ТО	>5	-	<1	9	54	
maze-7	8156	ТО	>6	-	<1	14	280	
consensus	9232	14.0	5	<b>22</b>	<1	9	51	
inventory	10100	1.5	4	<b>14</b>	<1	6	<b>14</b>	
resource	10571	<1	3	7	<1	16	248	
philos	10932	11.8	6	41	<1	16	946	
rabin	15388	ТО	>5	-	<1	21	154	
tictactoe	21816	ТО	>5	-	1.4	14	1170	

Table 3: Complete comparison of DTMAP with DTCONTROL on the full benchmark set. The upper part includes models with less than 3k choices, and the bottom part includes models with more than 3k choices. The depth > k indicates that DTMAP proved that there is no k-DT representing the given policy. Bold numbers indicate the DT with the smallest number of decision nodes found for the given policy.

### C.2 Comparison with OMDT

The complete comparison with OMDT includes 19 models and 6 fixed depths, resulting in 114 different evaluations. As such, we present the resulting table here: https://anonymous.4open.science/r/dt-synthesis-benchmarks-tacas25.