
Survey on Monocular Metric Depth Estimation

Jiuling Zhang

University of Chinese Academy of Sciences
zhangjiuling19@mailsucas.edu.cn

Abstract

Monocular Depth Estimation (MDE) is a cornerstone of computer vision which underpins tasks such as spatial understanding, 3D reconstruction, and autonomous driving. While deep learning-based MDE methods have made it possible to predict relative depth from a single image, the absence of metric scale information often leads to scale inconsistencies, limiting their effectiveness in downstream tasks like visual SLAM, 3D reconstruction, and novel view synthesis. To address these challenges, Monocular Metric Depth Estimation (MMDE) has emerged as a transformative solution, enabling precise scene-scale inference. MMDE not only mitigates consistency issues in depth prediction but also enhances stability in sequential tasks, simplifies integration into downstream applications, and expands the scope of practical implementations. This paper presents a comprehensive review of the evolution of depth estimation technologies, tracing the transition from traditional geometry-based methods to cutting-edge deep learning approaches. It delves into key advancements and breakthroughs in the field, with a particular focus on the role of scale-agnostic methods in enabling zero-shot generalization—a critical foundation for the development of MMDE. Recent progress in zero-shot MMDE research is examined in depth, with attention to challenges such as model generalization and the loss of fine details at scene boundaries. To tackle these issues, the research community has developed innovative strategies, including unlabelled data augmentation, image patching, architectural optimization, and generative techniques. These approaches have driven significant advancements, which are analyzed in detail to showcase their contributions in overcoming existing limitations. Finally, this paper synthesizes the connections between recent developments in zero-shot MMDE, identifies unresolved challenges, and outlines promising avenues for future research. By offering a thorough analysis of the current state of the field and emerging trends, we aim to equip researchers with a clear roadmap and cutting-edge insights, fostering a deeper understanding of MMDE and inspiring novel applications and technological innovations.

1 Introduction

Depth estimation has become a cornerstone technology for extracting scene depth information from images amid rapid advancements in computer vision and artificial intelligence. It plays a pivotal role in enabling key applications such as virtual reality, autonomous driving, and robotic navigation (Szeliski, 2022). Early methods heavily relied on parallax imaging and stereo photography, achieving high accuracy through stereo cameras (Scharstein & Szeliski, 2002). However, the emergence of deep learning has shifted the focus to monocular depth estimation, which predicts scene depth from a single image. This paradigm shift has drastically reduced hardware requirements and system complexity, offering greater flexibility across a wide range of applications (Eigen et al., 2014).

Monocular Metric Depth Estimation (MMDE) has made remarkable strides in the fields of deep learning and computer vision, particularly in practical model deployment building on this foundation (Guizilini et al., 2023). Unlike traditional Monocular Depth Estimation (MDE), which primarily predicts relative depth, MMDE generates depth maps with absolute metric scale, thereby unlocking a broader spectrum of applications (Fu et al., 2018). However, this advancement also brings new challenges, including ensuring model generalization, improving prediction accuracy, preserving fine details, and reliably inferring scale in complex scenes (Miangoleh et al., 2021). These challenges have a direct impact on the performance of downstream tasks such as visual SLAM, 3D reconstruction, and novel view synthesis (Mur-Artal et al., 2015).

Significant progress has been made in addressing these challenges driven by the availability of large-scale datasets, enhanced computational power, and innovative advancements in model architectures (Ranftl et al., 2021). MMDE has achieved notable improvements in zero-shot generalization, accuracy, and fine-detail preservation, making it increasingly reliable and versatile for real-world applications (Xian et al., 2018).

This paper presents a systematic analysis of the core challenges in MMDE. We review the latest advancements and solutions, and highlights emerging trends shaping the field’s future. By providing a comprehensive overview, this work aims to serve as a valuable resource for researchers, offering both a reference guide and a source of inspiration to advance MMDE and its transformative applications (Godard et al., 2019).

2 Depth Estimation

Depth estimation is a fundamental task in computer vision that is dedicated to deriving 3D depth information from 2D images. By predicting the distance of each pixel from the camera and constructing a corresponding depth map, this technology effectively adds a third dimension to visual data. It captures the geometric structure and spatial relationships within a scene, serving as the cornerstone for visual perception and interaction with the environment (Eigen et al., 2014).

The goal of depth estimation is to generate a depth map $D := (\mathbb{R})^{H \times W}$ from a given 2D image $I := (\mathbb{R})^{H \times W \times 3}$, where each depth value $d_{i,j} \in D$ represents the physical distance between a pixel $i_{i,j} \in I$ in the image and the camera (Bhat et al., 2021). However, this task is inherently underdetermined. A 2D image is a projection of the 3D world, which compresses or discards depth information during the imaging process. In monocular depth estimation, the lack of parallax or auxiliary input further exacerbates ambiguity, making the problem significantly more complex (Miangoleh et al., 2021).

Despite these challenges, depth estimation is indispensable across numerous domains (Hedman et al., 2017; Jampani et al., 2021; Khan et al., 2023). By delivering precise depth information, it enables computers to determine the relative positions and distances of objects within a scene, laying the groundwork for advanced scene understanding and analysis. In autonomous driving and robotics, depth estimation enhances obstacle detection, path planning, and environmental awareness, boosting system reliability and safety (Dong et al., 2022). In augmented and virtual reality (AR/VR), depth data enables accurate scene modeling and interaction, elevating user immersion and realism (Ranftl et al., 2021). Additionally, in computational photography and image post-processing, depth estimation supports tasks such as multi-focus imaging, 3D video generation, and background blurring (Laina et al., 2016).

In essence, depth estimation is more than a pivotal research area in computer vision—it is a transformative technology that empowers vision systems to perceive and interact with the 3D world. Its wide-ranging applications hold immense potential to drive innovation, bridging the gap between visual data and real-world understanding.

2.1 Traditional Methods

Prior to the rise of deep learning, depth estimation was predominantly based on geometric principles or the use of specialized hardware sensors. These conventional approaches relied on well-defined physical and mathematical frameworks, often deriving depth information by examining spatial relationships within images or leveraging auxiliary hardware. Although these methods demonstrated strong performance in controlled and predictable settings, they encountered considerable challenges when applied to more complex and dynamic real-world scenarios.

2.1.1 Sensors

Hardware sensors played a pivotal role in the early development of depth estimation technologies. A notable example is the Microsoft Kinect v1, which utilized structured light technology to project specific patterns onto a scene. Depth information was then calculated by analyzing the deformation of these patterns on object surfaces (Wasenmüller & Stricker, 2017; Samir et al., 2015). Another widely adopted approach involves Time-of-Flight (ToF) sensors, which determine distances by measuring the time it takes for a light pulse to travel to an object and return. While these methods deliver high accuracy under controlled conditions, they come with significant limitations. High hardware costs, sensitivity to factors such as ambient light and surface reflectivity, and reduced reliability in dynamic or unstructured scenes often restrict their broader application (Foix et al., 2011). Moreover, the complexity of these devices poses challenges for their integration into portable systems, limiting their versatility in real-world scenarios.

2.1.2 Stereo

Stereo vision is another widely utilized traditional approach for depth estimation which is inspired by the parallax principle in human vision (Hamzah & Ibrahim, 2016). This technique involves capturing a scene from two distinct camera angles and matching corresponding pixels between the two images to compute disparity. The disparity values are then used to infer the depth of the scene. While stereo vision offers a robust method for depth estimation, it relies heavily on precise camera calibration and accurate image correspondence. Challenges arise in scenarios with sparse textures, low-light conditions, or dynamic scenes, where reliable matching becomes difficult (Lazaros et al., 2008). Additionally, the high hardware costs and the complexity of setup and calibration processes further hinder its adoption in many practical applications, particularly in resource-constrained environments.

2.1.3 Geometrical Multi-Frame

Geometry-based methods, such as Structure from Motion (SfM) and Simultaneous Localization and Mapping (SLAM), utilize disparity information across multiple frames to incrementally reconstruct a 3D representation of a scene. These techniques are typically divided into indirect and direct approaches. Indirect methods rely on detecting and matching feature points (Lowe, 2004), optimizing camera poses and 3D point clouds by minimizing reprojection errors. Direct methods, on the other hand, model the image formation process (Engel et al., 2014) and optimize based on photometric errors, capturing finer details such as edges and intensity variations (Szeliski, 2022; Hartley & Zisserman, 2003; Wong et al., 2020). While these methods offer precise geometric reconstruction, their performance is often hindered by challenging lighting conditions and texture characteristics, limiting their reliability in dynamic environments or textureless regions.

Traditional methods were instrumental in the early advancement of depth estimation technology but frequently demanded additional hardware, controlled environmental conditions (Tola et al., 2009), or intensive computational resources (Scaramuzza & Fraundorfer, 2011). These constraints posed significant challenges, particularly in complex dynamic scenes or when deploying low-cost mobile devices. The rise of deep learning has transformed the field by addressing these limitations. Deep learning methods leverage high-dimensional feature learning directly from images, enabling flexible and efficient depth estimation. This paradigm shift not only enhances the robustness and scalability of traditional techniques but also unlocks new opportunities for deployment in lightweight devices and more intricate, real-world environments.

2.2 Deep Learning

With the rapid advancements in deep learning, monocular depth estimation has undergone a paradigm shift, transitioning from traditional geometric approaches to neural network-driven methods. Deep learning has not only revolutionized the technological framework of depth estimation but also broadened its applicability across diverse fields. Unlike traditional techniques that depend on geometric projections and multi-view imaging, deep learning eliminates the need for specialized hardware, such as stereo cameras or LiDAR, as well as stringent calibration requirements (Eigen et al., 2014). Instead, it leverages neural networks to infer depth information directly from a single image, significantly reducing implementation complexity and costs. This innovation has paved the way

for low-cost, flexible depth estimation solutions, making them particularly advantageous for applications such as augmented reality (AR) on mobile devices and navigation for drones (Ranftl et al., 2021).

The key strength of deep learning lies in its ability to extract prior knowledge from large-scale datasets, effectively addressing the inherently ill-posed nature of depth estimation (Laina et al., 2016). Traditional geometric methods struggle with the lack of explicit depth cues in single images, as inferring 3D structures from a 2D pixel array is a highly complex task. Deep learning overcomes this limitation by training neural networks to capture both global and local image features, such as texture, shape, and semantic content (Godard et al., 2019). These networks learn to infer 3D scene properties indirectly, leveraging contextual information to resolve ambiguities. For instance, neural models can recognize that the sky and horizon correspond to greater depths, while ground texture variations indicate depth gradients. This capacity to make context-based inferences allows deep learning models to generate high-quality depth predictions, even without explicit geometric inputs (Zhou et al., 2017).

A critical driver behind the success of monocular depth estimation is the multi-level feature representation enabled by deep learning architectures. Convolutional Neural Networks (CNNs), for example, excel at extracting multi-scale features from images, combining low-level texture details with high-level semantic understanding (Fu et al., 2018). By integrating these features across scales, deep learning models can simultaneously account for local details and global structures, resulting in more accurate and robust depth maps. In architectural scenes, for instance, CNNs can identify fine texture changes on walls while capturing the overall spatial layout. This hierarchical approach to feature analysis far surpasses the pixel-level computations of traditional methods, enhancing both accuracy and reliability (Hu et al., 2019).

Moreover, deep learning-based methods exhibit superior adaptability to complex and dynamic scenes. Neural networks effectively model features in textureless or irregular regions, overcoming the performance constraints of traditional approaches. For example, in autonomous driving, deep learning models can accurately estimate the depth of roads, pedestrians, vehicles, and other elements, enabling robust path planning and obstacle detection. Similarly, in robotic navigation, these methods facilitate the perception of dynamic environments with reduced hardware demands, fostering wider adoption across diverse domains. This adaptability underscores the transformative impact of deep learning on monocular depth estimation, driving innovation and expanding its applications (Garg et al., 2016).

3 Monocular Depth Estimation

Monocular Depth Estimation (MDE) represents a significant application of deep learning in the field of depth estimation. It aims to infer depth information of a scene directly from a single RGB image without requiring multi-view images or complex hardware setups. Compared to traditional multi-frame depth estimation methods, MDE simplifies implementation and reduces costs by leveraging deep learning models to extract and infer depth information from single-image features (Saxena et al., 2008). Early research in this domain primarily focused on supervised learning frameworks, where neural networks were trained using datasets with precise depth annotations (Fu et al., 2018).

In 2014, Eigen et al. introduced a pioneering multi-scale convolutional neural network (CNN) framework for monocular depth estimation, jointly predicting global and local depth information. Their method decomposed the image into a coarse depth map and a detailed local map, significantly improving depth prediction accuracy by integrating multi-level feature information (Eigen et al., 2014). This foundational work laid the groundwork for subsequent advancements in the field. In 2015, Eigen extended this framework by proposing a multi-task learning model that simultaneously predicted depth, surface normals, and semantic labels. By sharing a common feature extraction backbone across tasks, this model not only enhanced depth prediction accuracy but also mitigated overfitting, a common issue in single-task models. This marked a pivotal step forward in multi-task joint learning for MDE (Eigen & Fergus, 2015).

The architecture for MDE shifted towards encoder-decoder frameworks as deep learning techniques evolved particularly with the advancement of CNNs. The encoder captures global contextual features, while the decoder progressively upsamples these features to generate high-resolution depth

maps (Godard et al., 2017). The integration of multi-scale feature fusion methods further enhanced the network’s ability to capture depth at various levels. For example, cross-scale loss functions were introduced to optimize both local and global depth consistency, significantly improving estimation accuracy (Poggi et al., 2018).

To address the inherently ill-posed nature of MDE, some studies incorporated geometric priors, such as perspective cues and object size, as additional constraints. By combining geometric knowledge with the feature learning capabilities of deep learning, these methods improved the plausibility of depth estimates and enhanced model generalization in diverse scenarios (Chen et al., 2016). Integrating such priors allowed models to better understand the 3D structure of scenes, showing increased robustness, particularly in textureless or complex environments (Hu et al., 2019).

While early MDE models demonstrated success within specific domains (e.g., indoor or outdoor scenes), their generalization capabilities across unseen scenes were limited. This issue arose due to their reliance on single datasets, leading to significant biases in cross-domain applications. To address this challenge, researchers developed more universal feature extraction modules and introduced domain-invariant feature constraints during training. These innovations progressively enhanced the models’ adaptability, paving the way for broader applications of MDE across diverse environments. Such advancements have expanded the practical utility and effectiveness of monocular depth estimation, positioning it as a cornerstone technology in computer vision.

4 Zero-shot Monocular Depth Estimation

Zero-shot monocular depth estimation emerged from the pressing need to enhance model generalization. Early depth estimation models typically regressed metric depth values directly. While this approach performed well when the training data closely matched the test scenarios, it was heavily dependent on specific scene scales and camera parameters. This dependence severely limited the model’s ability to transfer across different scenes, often resulting in poor performance in real-world settings, where scenes vary significantly (Saxena et al., 2008). To address this challenge, researchers proposed a new direction: improving the zero-shot capability of models by simplifying the problem (Poggi et al., 2018).

Relative Depth Estimation (RDE) played a pivotal role in achieving breakthroughs in the zero-shot domain. Unlike metric depth estimation, which directly predicts the true depth of pixels, RDE focuses on the relative depth relationships between pixels (Li & Snavely, 2018). By removing the need for absolute scale information, RDE emphasizes the ordering of depths between pixels, greatly enhancing the model’s generalization ability (Chen et al., 2016). This approach introduced scale-agnostic and scale-and-shift-invariant loss functions (Ranftl et al., 2020), enabling the model to train on heterogeneous datasets and adapt to diverse scenes (Ranftl et al., 2020). The ability of RDE to eliminate scale dependencies allows it to perform effectively in zero-shot settings and exhibit high adaptability to new domains.

MiDAS represents a landmark achievement in zero-shot depth estimation, introducing the concept of universally applicable zero-shot depth estimation (Birkl et al., 2023). By training on multiple heterogeneous datasets and using scale-and-shift-invariant loss functions, MiDAS significantly improved cross-domain prediction capabilities (Ranftl et al., 2021). Over time, MiDAS evolved from a convolution-based architecture to a more modern network structure utilizing Vision Transformers (Dosovitskiy et al., 2021; Han et al., 2022). Vision Transformers provide distinct advantages in capturing global information and enabling multi-scale feature fusion, which further enhances MiDAS’s adaptability across a wide range of scenarios. Although MiDAS only predicts relative depth, its innovative architecture and training strategy laid an important technical foundation for subsequent research (Hu et al., 2019).

While RDE improves model transferability by simplifying the problem, this approach comes with trade-offs. Sacrificing absolute scale information turns depth estimation from a complex metric problem into a relatively simpler ranking task. While this simplification boosts the model’s cross-domain adaptability, it also introduces notable limitations. For instance, the absence of absolute depth information renders RDE unsuitable for tasks requiring precise 3D data, such as SLAM, augmented reality (AR), and autonomous driving. Moreover, since RDE lacks a unified scale reference, its application in continuous frame scenarios can lead to jitter, affecting the stability and consistency of the predicted results.

From that, zero-shot depth estimation has opened new avenues of research through innovative approaches, providing valuable insights into addressing core challenges in depth estimation. Current research is actively exploring ways to combine the strengths of both relative and absolute depth estimation, aiming to develop monocular depth estimation methods that achieve cross-domain generalization while also providing scale information. This progress holds the potential to offer new solutions for applications such as SLAM, autonomous driving, and other domains requiring high precision and robustness (Fu et al., 2018).

5 Zero-shot Monocular Metric Depth Estimation

Metric depth estimation has regained significant attention due to the growing demand from downstream applications, positioning it as a crucial direction in deep learning research. Applications such as 3D reconstruction, novel view synthesis, and SLAM systems increasingly require high-precision geometric information, underscoring the importance of this field. Traditional depth estimation methods, which primarily provide relative depth values, often fall short in meeting the demands for frame-to-frame consistency and geometric stability in dynamic environments (Dong et al., 2022). Meanwhile, advancements in model architectures, such as the introduction of Vision Transformers, alongside the expansion of model sizes (scaling from millions to billions of parameters) and the exponential growth of annotated depth datasets (reaching millions of samples), have collectively reignited interest in this domain. Unlike earlier methods constrained to domain-specific applications, the current wave of research emphasizes zero-shot monocular metric depth estimation, which aims to generate consistent metric depth values in unseen scenes without relying on specific camera parameters or depth annotation during training.

Metric depth estimation outputs absolute depth values in physical units, enabling superior adaptability across diverse scenes. This capability ensures robust performance in both indoor and outdoor environments, providing consistent depth information across frames, even in dynamic settings. Such qualities meet the demands of real-world applications by offering both geometric stability and spatial consistency. However, one key challenge in this field lies in achieving generalization to unknown scenes while maintaining geometric accuracy. This balance is critical for deploying metric depth estimation models in real-world, unconstrained environments.

Early metric depth estimation methods often relied on known camera parameters. For instance, Metric3D addressed scale and offset variations across different camera setups by mapping images and depth maps to a canonical space and adjusting depth values based on focal length (Yin et al., 2023). Similarly, ZeroDepth employed a variational framework to learn camera-specific embeddings, improving performance but limiting generalization due to its reliance on precise camera parameters (Saxena et al., 2023). These constraints prompted research into methods capable of operating without predefined camera parameters. For example, some approaches predict camera embeddings through separate networks, while others directly estimate depth in spherical space, bypassing traditional camera parameter requirements.

Another advancements introduced adaptive depth binning strategies, significantly enhancing depth estimation performance. The Adaptive Bins method dynamically adjusted depth bin positions and distributions based on image content, improving performance in scenes with substantial depth variation (Bhat et al., 2021). Building on this, LocalBins divided images into multiple regions, learning depth distributions within each region to refine accuracy in complex scenes (Bhat et al., 2022). Despite their effectiveness, these strategies introduced high computational complexity, increasing inference time. To address this, BinsFormer, leveraging Transformer architecture, combined global and local information in an end-to-end framework (Li et al., 2024b). This approach improved the model’s ability to capture global context while enhancing estimation accuracy. Additionally, NeW CRFs integrated neural networks with Conditional Random Fields (CRFs), providing global optimization mechanisms that ensured pixel-wise consistency and improved handling of uncertainty, further strengthening the global consistency of depth predictions (Yuan et al., 2022).

The introduction of ZoeDepth represents a significant leap in zero-shot metric depth estimation (Bhat et al., 2023). Combining the strengths of MiDAS with adaptive depth binning techniques, ZoeDepth incorporates a lightweight metric bin module and a dynamic adjustment mechanism, enabling more accurate metric depth predictions. Notably, ZoeDepth automatically classifies input images and routes them to appropriate network heads, ensuring strong performance across both indoor

and outdoor environments. Trained upon a diverse collection of datasets with minimal fine-tuning, ZoeDepth excels in cross-domain generalization, performing exceptionally well in zero-shot testing on various indoor and outdoor datasets. Its unified architecture and extensive training data enable ZoeDepth to set new benchmarks in zero-shot metric depth estimation, laying a robust foundation for future advancements in this field.

6 Challenges and Improvements

Zero-shot monocular metric depth estimation has made remarkable progress in recent years, yet several critical challenges remain unresolved. Foremost among these is the limited generalization capability of existing models. Accurately and reliably estimating depth in previously unseen scenes remains a significant research hurdle. Additionally, practical limitations in single-inference scenarios persist. These include issues such as the loss of geometric precision due to edge smoothing, diminished representation of scene-specific details, and suboptimal handling of high-resolution inputs. These shortcomings pose substantial obstacles to the robustness and applicability of these models in real-world environments.

To tackle these challenges, researchers have proposed and implemented a range of innovative improvement strategies, driving notable advancements in the field. This chapter delves into these developments, providing a comprehensive analysis and discussion of their implications and contributions to the evolution of zero-shot monocular metric depth estimation.

6.1 Generalizability

One efforts to enhance the generalizability have predominantly focused on two critical aspects: data augmentation and model refinement. Data augmentation seeks to enhance the model’s ability to handle diverse and complex scenes by incorporating richer, more varied training datasets and optimizing learning strategies. Concurrently, model refinement emphasizes the development of more robust architectures and algorithms, aiming to fundamentally improve cross-domain adaptability and predictive accuracy. These complementary approaches collectively drive advancements in achieving reliable and versatile depth estimation across diverse environments.

6.1.1 Dataset Augmentation

Depth Anything introduced a large-scale data expansion approach based on a semi-supervised self-learning strategy. By generating approximately 62 million self-labeled samples, this method significantly improves the model’s ability to generalize across diverse scenarios (Yang et al., 2024). Combined with optimized training strategies, it enables the model to actively learn additional visual knowledge in complex and varied environments. Additionally, by leveraging an auxiliary supervision mechanism, Depth Anything effectively taps into the rich semantic priors of pre-trained encoders, substantially reducing generalization errors. This approach demonstrates outstanding zero-shot depth estimation performance in both indoor and outdoor settings, underscoring the potential of large-scale self-labeled datasets in developing robust monocular depth estimation foundation models.

6.1.2 Model Improvements

UniDepth marks a advancement in model development, introducing an innovative approach to depth estimation that directly predicts metric 3D point clouds without relying on additional camera parameters or metadata (Piccinelli et al., 2024). Central to its design is a self-prompting camera module, which generates dense camera representations and employs pseudo-spherical outputs to decouple camera properties from depth features. This design enhances the model’s robustness to camera attribute variations. Furthermore, UniDepth incorporates a geometric invariance loss, reinforcing depth feature consistency and improving generalization across diverse scenarios.

The model also utilizes a dual mechanism combining camera bootstrapping with explicit calibration of intrinsic camera parameters, resulting in improved stability and precision in depth estimation. This decoupled learning strategy, which separates the learning of camera parameters from depth features, establishes a robust technical framework for advancing the generalization capabilities of MMDE models.

6.2 Blurriness

Detail loss and edge smoothing are persistent challenges in deep learning models for dense information prediction, particularly in depth estimation, image segmentation, and object detection. These issues often result in the loss of fine details in images, especially along object edges and intricate structures, such as hair or fur. Consequently, the predicted depth maps fail to accurately represent the true geometric features of the scene (Eigen et al., 2014). These limitations become even more pronounced in complex scenarios, such as occlusion boundaries or regions with intricate details, significantly hindering the practical performance of models in high-precision applications (Ranftl et al., 2021). Moreover, effectively handling high-resolution inputs within computational constraints remains a critical obstacle. Depth estimation models often struggle to strike a balance between global consistency and local detail representation in high-resolution scenes. This imbalance leads to depth maps that lack fine-grained details and exacerbates the blurring of occlusion contours and complex boundaries.

To address these challenges, researchers have proposed a variety of solutions. For instance, SharpNet enhances edge sharpness by incorporating normal and occlusion contour constraints, although this method requires additional supervisory signals, thereby increasing the complexity of the training process (Ramamonjisoa & Lepetit, 2019). Similarly, BoostingDepth applies low-resolution networks to image patches for detail refinement. However, this approach lacks global contextual information and relies on a complex multi-step fusion pipeline, which adds both computational cost and implementation complexity (Miangoleh et al., 2021). In response to these issues, the research community has converged on three primary directions to enhance depth estimation precision while maintaining computational efficiency.

6.2.1 Patching

To tackle with detail loss and edge smoothing, researchers have developed various patch-based methods that enhance the resolution and detail representation of depth maps. These methods offer unique advantages for handling complex scenes by integrating local depth estimation with global context.

PatchFusion represents an innovative extension of the BoostingDepth framework, leveraging a content-adaptive multi-resolution fusion strategy to improve monocular depth estimation (Li et al., 2024a). Specifically, PatchFusion segments the input image into multiple patches, performs independent depth estimation for each patch, and then employs a Global-to-Local (G2L) module to integrate global context information for consistent fusion. To address stitching artifacts, it introduces a "Consistency-Aware Training and Inference" (CAT & CAI) strategy, optimizing alignment in stitching regions by ensuring both geometric and color consistency. However, PatchFusion's multi-step process—including downsampling, patchwise depth estimation, and alignment—results in longer inference times. Additionally, the patch-based approach can misinterpret localized features as actual depth, leading to biases in global scene comprehension.

Building upon PatchFusion, PatchRefiner redefines high-resolution depth estimation as a refinement task, introducing the "Detail and Scale Disentangling" (DSD) loss to enhance edge sharpness and ensure accurate depth scaling (Li et al., 2025). It specifically targets the challenges of high-resolution scenes by employing a pseudo-labeling approach based on synthetic data, which facilitates effective knowledge transfer between real-world and synthetic datasets. Compared to PatchFusion, PatchRefiner's modular architecture streamlines the multi-step pipeline, significantly improving inference efficiency while achieving superior detail preservation and global consistency in depth maps.

DepthPro, on the other hand, focuses on balancing inference efficiency with detail preservation for real-world applications (Bochkovskii et al., 2024). It integrates a multi-scale Vision Transformer (ViT) with a joint training protocol for real and synthetic data, enabling fast inference while retaining fine-grained details. DepthPro's innovative slicing method processes overlapping image patches, mitigating the context loss issues observed in PatchFusion and PatchRefiner. Additionally, it supports direct absolute depth inference from a single image without requiring camera parameters, simplifying the overall methodology. However, DepthPro exhibits a slight trade-off in maintaining global scene consistency and long-distance depth estimation, as its design prioritizes depth prediction for nearby objects.

6.2.2 Synthetic Datasets

Real-world depth-supervised datasets often suffer from quality issues such as inaccurate labels, missing data in reflective or transparent areas, mismatched depth values, and poorly defined object boundaries. These limitations, inherent in data collection and annotation, contribute to model detail loss. By contrast, synthetic datasets generated with rendering engines provide pixel-accurate, comprehensive depth labels and handle challenging conditions like reflections and transparency (Bochkovskii et al., 2024).

Depth Anything V2 capitalizes on synthetic datasets to reduce reliance on real-world data, offering finer-grained supervision, scalability, and avoidance of privacy concerns (Yang et al., 2024). However, the distribution gap between synthetic and real-world data, such as differences in color and scene layout, can limit generalization, particularly in unseen scenarios. To address this, Depth Anything V2 uses pseudo-labeling, where a teacher model generates depth labels for real-world data, bridging the distribution gap. Additionally, a gradient-matching loss enhances sharpness and mitigates detail loss, selectively ignoring hard-to-align regions to prevent overfitting.

Despite these advancements, limitations of synthetic datasets persist. The constrained variety of scenes produced by rendering engines may lead to suboptimal performance when the model encounters real-world scenarios beyond the scope of the synthetic training data.

6.2.3 Generative Methods

Generative diffusion models have recently demonstrated exceptional promise in addressing edge smoothing and detail loss in monocular depth estimation. By simulating image degradation and progressively restoring depth information, these models excel at recovering fine details and structural consistency.

Marigold, a pioneer in applying diffusion models to depth estimation, generates depth maps with superior structural consistency and fine detail compared to traditional discriminative models (Ke et al., 2024). Its strength lies in handling challenging regions, such as reflective or transparent areas. However, in complex multi-scene layouts, Marigold’s depth maps may exhibit layout errors due to inherent ambiguities, limiting its reliability in intricate scenarios.

To address these shortcomings, GeoWizard introduces significant advancements. Its novel Decoupler structure separates the learning of distinct scene distributions, mitigating blurring and ambiguity caused by mixed distributions (Fu et al., 2024). By leveraging a one-dimensional scene classification vector (e.g., indoor, outdoor, or object-centric scenes), GeoWizard significantly enhances generalization across diverse environments. This improvement enables reliable depth estimation in complex scenarios, particularly in distinguishing foreground from background and predicting outdoor geometric layouts. Additionally, GeoWizard integrates normal maps with pseudo-metric depth generated via the BiNI algorithm, facilitating surface reconstruction for more realistic 3D geometries.

Pushing the boundaries further, DeepMind’s DMD (Diffusion for Metric Depth) introduces a groundbreaking logarithmic-scale depth parameterization strategy, addressing uneven depth representation between indoor and outdoor scenes (Saxena et al., 2023). By incorporating a field-of-view (FOV) condition, DMD resolves depth scale ambiguities caused by variations in camera intrinsics. During training, it simulates diverse FOVs using cropping and noise-filling techniques, with vertical FOV as a conditional input. This approach significantly improves adaptability and prediction accuracy across varied scenes. Moreover, DMD employs ϵ -parameterization, enabling rapid inference through a single-step denoising process, which dramatically enhances efficiency.

6.3 Comparisons and Drawbacks

Single-pass inference methods dominate the research landscape due to their speed and efficiency. These methods make predictions in a single pass, making them particularly suitable for real-time applications such as interactive view synthesis and navigation. However, they struggle to accurately capture high-frequency details, leading to suboptimal performance for complex structures like hair, architectural textures, and fine limb details. This limitation results in depth maps with reduced detail. Additionally, single-pass methods heavily rely on large-scale, high-quality annotated datasets, and the variability in real-world data annotations constrains their generalization capabilities (Ranftl et al., 2021).

Table 1: The latest advancements in Metric Monocular Depth Estimation (MMDE) have been summarized chronologically, focusing on their methodological characteristics. While most generative model-based approaches produce relative depth outputs, the only implementation capable of generating metric depth, DMD [41], has not been made publicly available. The potential of generative models in MMDE remains largely untapped and warrants further exploration.

Method	Publication	Category	Inference	Dataset	Output	Source
Zoedepth	Arxiv	discriminative	single	real	metric	open
Depth Anything v1	CVPR '24	discriminative	single	real	metric	open
Patch Fusion	CVPR '24	discriminative	multiple	real	metric	open
Unidepth	CVPR '24	discriminative	single	real	metric	open
Marigold	CVPR '24	generative	multiple	synthetic	relative	open
DMD	Arxiv	generative	multiple	real	metric	close
Depth Anything v2	Arxiv	discriminative	single	real+synthetic	metric	open
GeoWizard	ECCV '24	generative	multiple	real+synthetic	relative	open
Patch Refiner	ECCV '24	discriminative	multiple	real+synthetic	metric	open
Depth pro	Arxiv	discriminative	multiple	real+synthetic	metric	open

In contrast, patch-based inference methods divide an input image into smaller segments or patches, estimating depth for each patch individually before merging the results. This strategy enhances detail representation, with resolution and accuracy improving as the number of patches increases. Additionally, patch-based methods allow parallelized inference, making them appealing for high-resolution applications. However, as the number of patches grows, inference time scales linearly, and performance gains diminish. For example, PatchFusion optimizes patch weight fusion for better results, but its slow inference speed remains unsuitable for real-time tasks. Moreover, the multi-step inference process in patch-based methods creates bottlenecks in high-resolution scenes.

Generative diffusion models present a novel approach to mitigating detail loss in depth estimation. These models simulate image degradation and progressively restore depth information, excelling at capturing intrinsic image structures and complex scene geometries. For instance, Marigold demonstrates remarkable capabilities in interpreting geometric relationships in cluttered environments, such as walls, furniture, and décor, producing depth maps with natural and detailed representations. However, the multi-step inference process in diffusion models introduces efficiency challenges. Each step adds randomness, increasing uncertainty in the final results. Furthermore, most research into generative diffusion models has focused on relative depth estimation (RDE), with limited exploration of metric depth estimation (MMDE), reducing their applicability in downstream tasks.

Generative models also reduce dependency on annotated data. Unlike discriminative methods that require extensive labeled datasets, diffusion models can perform effectively even with minimal labeled data. For example, DeepMind’s DMD introduces field-of-view (FOV) conditions and logarithmic scale depth parameterization to enhance depth prediction in zero-shot scenarios. This innovation enables robust performance across diverse scenes without relying on annotated data. However, the complexity of the multi-step inference and denoising processes limits real-time applicability, highlighting the need for further optimization.

Figure 1 compares single-pass inference, patch-based inference, and generative models in terms of inference time and memory usage. The test, conducted on a 400-frame 1080p video with batch size 1 using an NVIDIA RTX 3090, reveals that time costs grow exponentially for generative methods.

Taken together, single-pass inference methods offer unparalleled efficiency and real-time performance but are constrained in capturing fine details. Patch-based methods improve resolution and detail but face significant efficiency challenges as the number of patches increases. Generative diffusion models excel in detail restoration and complex scene understanding, making them highly promising for depth estimation tasks. However, their multi-step inference process creates bottlenecks that limit real-time usability, necessitating further advancements to bridge the gap between accuracy and efficiency.

7 Summary and Outlook

MMDE has made remarkable progress transitioning from traditional single-task optimization to innovative methods that incorporate generative models and emphasize multi-scene generalization. This shift has greatly expanded the applicability of depth estimation techniques, offering transformative potential for 3D scene reconstruction and spatial understanding. Recent advancements, summarized in Table 1, highlight the synergy between model improvements and data resource optimization, which has improved adaptability across diverse scenarios. However, the field still faces challenges such as the loss of high-frequency details, inadequate geometric consistency in complex scenes, and the performance-efficiency trade-off in real-world applications. Addressing these challenges requires innovations in loss function design, data augmentation strategies, and the integration of generative models, all aiming to achieve precise 3D scene restoration.

Loss functions are fundamental to MMDE, and their design has seen significant innovations. Traditional loss functions often prioritize global depth consistency and local smoothness, yet they struggle to preserve high-frequency details, leading to the loss of depth information in regions with complex textures. To overcome this, researchers have developed constraints such as edge-aware loss and gradient-based structural constraints, which enable models to better capture subtle depth variations. These advancements have enhanced adaptability in textured regions, laying a foundation for high-precision depth estimation in real-world applications. Moreover, the adoption of generative models has introduced a novel approach: using the progressively restored details during generation as supervisory signals. This strategy has enriched detail representation and driven further performance improvements in depth estimation.

The quality and diversity of data resources are equally critical to the success of MMDE. A hybrid approach combining synthetic and real-world data has become a key solution to data scarcity. Advances in generating high-quality synthetic data include simulating realistic optical properties and complex scene layouts, creating datasets that closely mimic real-world environments. Simultaneously, methods for capturing accurate real-world depth data, such as LiDAR-based techniques and multi-view fusion, have significantly improved data authenticity. By integrating synthetic data’s diversity with real-world data’s authenticity through data augmentation and domain alignment, researchers have enhanced model generalization across different domains. These efforts not only improve training efficiency but also provide essential support for tackling more complex MMDE tasks.

Generative models, particularly diffusion-based approaches, have introduced a paradigm shift in the field. These methods balance detail preservation and global consistency by simulating image degradation and progressively generating depth maps. For instance, models like Marigold and GeoWizard excel at understanding complex scene geometries, effectively handling reflective and transparent surfaces. Their depth maps are notably more natural and precise than those produced by traditional approaches. Similarly, innovative methods such as DMD, which integrate logarithmic scale depth parameterization and field-of-view (FOV) input, address depth scale ambiguities across various camera parameters while significantly enhancing generalization across diverse scenes. Although the use of diffusion models in MMDE is still in its early stages, continuous improvements in multi-step inference and denoising strategies are helping strike a balance between efficiency and performance, opening new research directions.

The evolution from single-domain to zero-shot depth estimation represents a significant milestone in the field. By leveraging large-scale unlabeled data and enabling multi-domain transfer, MMDE models are becoming increasingly capable of predicting depth in unseen scenarios. For example, methods like ZoeDepth and UniDepth have demonstrated exceptional performance in complex environments, thanks to architectural innovations and improved training strategies. These advancements expand MMDE’s application scope and significantly enhance adaptability in dynamic and high-resolution scenes. Zero-shot methods, in particular, show great promise in enabling universal 3D perception, positioning them as foundational tools in advancing computer vision technologies.

Looking forward, research will focus on improving efficiency, generalization, and data resource optimization. Streamlining multi-step inference processes will be essential for meeting real-time application demands, with a potential breakthrough in combining the efficiency of single-pass inference and the detail-capturing capabilities of generative methods. Enhancing transfer learning and domain alignment techniques will further improve adaptability across diverse scene distributions,

while optimizing geometric consistency constraints will bolster robustness in multi-view and 3D reconstruction tasks. Additionally, ongoing improvements in synthetic data authenticity and real-world data collection efficiency will provide a more comprehensive training foundation. Dynamic balancing strategies between synthetic and real data are also expected to maximize the strengths of both, further boosting model performance.

In conclusion, MMDE is steadily progressing toward becoming more universal, refined, and efficient. By advancing loss function designs, leveraging high-quality data resources, and embracing generative models, researchers are developing depth estimation systems capable of accurately restoring 3D scene geometries. As generalization-enhancing techniques and geometric consistency constraints continue to evolve, zero-shot monocular depth estimation is poised to become a cornerstone of next-generation computer vision and 3D perception technologies.

References

- Bhat, S. F., Alhashim, I., and Wonka, P. Adabins: Depth estimation using adaptive bins. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 4009–4018, 2021.
- Bhat, S. F., Alhashim, I., and Wonka, P. Localbins: Improving depth estimation by learning local distributions. In *European Conference on Computer Vision*, pp. 480–496. Springer, 2022.
- Bhat, S. F., Birkl, R., Wofk, D., Wonka, P., and Müller, M. Zoedepth: Zero-shot transfer by combining relative and metric depth. *arXiv preprint arXiv:2302.12288*, 2023.
- Birkl, R., Wofk, D., and Müller, M. Midas v3. 1—a model zoo for robust monocular relative depth estimation. *arXiv preprint arXiv:2307.14460*, 2023.
- Bochkovskii, A., Delaunoy, A., Germain, H., Santos, M., Zhou, Y., Richter, S. R., and Koltun, V. Depth pro: Sharp monocular metric depth in less than a second. *arXiv preprint arXiv:2410.02073*, 2024.
- Chen, W., Fu, Z., Yang, D., and Deng, J. Single-image depth perception in the wild. *Advances in neural information processing systems*, 29, 2016.
- Dong, X., Garratt, M. A., Anavatti, S. G., and Abbass, H. A. Towards real-time monocular depth estimation for robotics: A survey. *IEEE Transactions on Intelligent Transportation Systems*, 23(10):16940–16961, 2022.
- Dosovitskiy, A., Beyer, L., Kolesnikov, A., Weissenborn, D., Zhai, X., Unterthiner, T., Dehghani, M., Minderer, M., Heigold, G., Gelly, S., Uszkoreit, J., and Houlsby, N. An image is worth 16x16 words: Transformers for image recognition at scale. In *International Conference on Learning Representations*, 2021. URL <https://openreview.net/forum?id=YicbFdNTTy>.
- Eigen, D. and Fergus, R. Predicting depth, surface normals and semantic labels with a common multi-scale convolutional architecture. In *Proceedings of the IEEE international conference on computer vision*, pp. 2650–2658, 2015.
- Eigen, D., Puhrsch, C., and Fergus, R. Depth map prediction from a single image using a multi-scale deep network. *Advances in neural information processing systems*, 27, 2014.
- Engel, J., Schöps, T., and Cremers, D. Lsd-slam: Large-scale direct monocular slam. In *European conference on computer vision*, pp. 834–849. Springer, 2014.
- Foix, S., Alenya, G., and Torras, C. Lock-in time-of-flight (tof) cameras: A survey. *IEEE Sensors Journal*, 11(9):1917–1926, 2011.
- Fu, H., Gong, M., Wang, C., Batmanghelich, K., and Tao, D. Deep ordinal regression network for monocular depth estimation. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 2002–2011, 2018.
- Fu, X., Yin, W., Hu, M., Wang, K., Ma, Y., Tan, P., Shen, S., Lin, D., and Long, X. Geowizard: Unleashing the diffusion priors for 3d geometry estimation from a single image. In *European Conference on Computer Vision*, pp. 241–258. Springer, 2024.

- Garg, R., Bg, V. K., Carneiro, G., and Reid, I. Unsupervised cnn for single view depth estimation: Geometry to the rescue. In *Computer Vision—ECCV 2016: 14th European Conference, Amsterdam, The Netherlands, October 11-14, 2016, Proceedings, Part VIII 14*, pp. 740–756. Springer, 2016.
- Godard, C., Mac Aodha, O., and Brostow, G. J. Unsupervised monocular depth estimation with left-right consistency. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 270–279, 2017.
- Godard, C., Mac Aodha, O., Firman, M., and Brostow, G. J. Digging into self-supervised monocular depth estimation. In *Proceedings of the IEEE/CVF international conference on computer vision*, pp. 3828–3838, 2019.
- Guizilini, V., Vasiljevic, I., Chen, D., Ambrus, R., and Gaidon, A. Towards zero-shot scale-aware monocular depth estimation. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 9233–9243, 2023.
- Hamzah, R. A. and Ibrahim, H. Literature survey on stereo vision disparity map algorithms. *Journal of Sensors*, 2016(1):8742920, 2016.
- Han, K., Wang, Y., Chen, H., Chen, X., Guo, J., Liu, Z., Tang, Y., Xiao, A., Xu, C., Xu, Y., et al. A survey on vision transformer. *IEEE transactions on pattern analysis and machine intelligence*, 45(1):87–110, 2022.
- Hartley, R. and Zisserman, A. *Multiple view geometry in computer vision*. Cambridge university press, 2003.
- Hedman, P., Alsisan, S., Szeliski, R., and Kopf, J. Casual 3d photography. *ACM Transactions on Graphics (TOG)*, 36(6):1–15, 2017.
- Hu, J., Ozay, M., Zhang, Y., and Okatani, T. Revisiting single image depth estimation: Toward higher resolution maps with accurate object boundaries. In *2019 IEEE winter conference on applications of computer vision (WACV)*, pp. 1043–1051. IEEE, 2019.
- Jampani, V., Chang, H., Sargent, K., Kar, A., Tucker, R., Krainin, M., Kaeser, D., Freeman, W. T., Salesin, D., Curless, B., et al. Slide: Single image 3d photography with soft layering and depth-aware inpainting. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 12518–12527, 2021.
- Ke, B., Obukhov, A., Huang, S., Metzger, N., Daut, R. C., and Schindler, K. Repurposing diffusion-based image generators for monocular depth estimation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 9492–9502, 2024.
- Khan, N., Xiao, L., and Lanman, D. Tiled multiplane images for practical 3d photography. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 10454–10464, 2023.
- Laina, I., Rupprecht, C., Belagiannis, V., Tombari, F., and Navab, N. Deeper depth prediction with fully convolutional residual networks. In *2016 Fourth international conference on 3D vision (3DV)*, pp. 239–248. IEEE, 2016.
- Lazaros, N., Sirakoulis, G. C., and Gasteratos, A. Review of stereo vision algorithms: from software to hardware. *International Journal of Optomechatronics*, 2(4):435–462, 2008.
- Li, Z. and Snavely, N. Megadepth: Learning single-view depth prediction from internet photos. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 2041–2050, 2018.
- Li, Z., Bhat, S. F., and Wonka, P. Patchfusion: An end-to-end tile-based framework for high-resolution monocular metric depth estimation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 10016–10025, 2024a.
- Li, Z., Wang, X., Liu, X., and Jiang, J. Binsformer: Revisiting adaptive bins for monocular depth estimation. *IEEE Transactions on Image Processing*, 2024b.

- Li, Z., Bhat, S. F., and Wonka, P. Patchrefiner: Leveraging synthetic data for real-domain high-resolution monocular metric depth estimation. In *European Conference on Computer Vision*, pp. 250–267. Springer, 2025.
- Lowe, D. G. Distinctive image features from scale-invariant keypoints. *International journal of computer vision*, 60:91–110, 2004.
- Miangoleh, S. M. H., Dille, S., Mai, L., Paris, S., and Aksoy, Y. Boosting monocular depth estimation models to high-resolution via content-adaptive multi-resolution merging. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 9685–9694, 2021.
- Mur-Artal, R., Montiel, J. M. M., and Tardos, J. D. Orb-slam: a versatile and accurate monocular slam system. *IEEE transactions on robotics*, 31(5):1147–1163, 2015.
- Piccinelli, L., Yang, Y.-H., Sakaridis, C., Segu, M., Li, S., Van Gool, L., and Yu, F. Unidepth: Universal monocular metric depth estimation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 10106–10116, 2024.
- Poggi, M., Tosi, F., and Mattoccia, S. Learning monocular depth estimation with unsupervised trinocular assumptions. In *2018 International conference on 3d vision (3DV)*, pp. 324–333. IEEE, 2018.
- Ramamonjisoa, M. and Lepetit, V. Sharpnet: Fast and accurate recovery of occluding contours in monocular depth estimation. In *Proceedings of the IEEE/CVF International Conference on Computer Vision Workshops*, pp. 0–0, 2019.
- Ranftl, R., Lasinger, K., Hafner, D., Schindler, K., and Koltun, V. Towards robust monocular depth estimation: Mixing datasets for zero-shot cross-dataset transfer. *IEEE transactions on pattern analysis and machine intelligence*, 44(3):1623–1637, 2020.
- Ranftl, R., Bochkovskiy, A., and Koltun, V. Vision transformers for dense prediction. In *Proceedings of the IEEE/CVF international conference on computer vision*, pp. 12179–12188, 2021.
- Samir, M., Golkar, E., and Rahni, A. A. A. Comparison between the kinect™ v1 and kinect™ v2 for respiratory motion tracking. In *2015 IEEE International Conference on Signal and Image Processing Applications (ICSIPA)*, pp. 150–155. IEEE, 2015.
- Saxena, A., Sun, M., and Ng, A. Y. Make3d: Learning 3d scene structure from a single still image. *IEEE transactions on pattern analysis and machine intelligence*, 31(5):824–840, 2008.
- Saxena, S., Hur, J., Herrmann, C., Sun, D., and Fleet, D. J. Zero-shot metric depth with a field-of-view conditioned diffusion model. *arXiv preprint arXiv:2312.13252*, 2023.
- Scaramuzza, D. and Fraundorfer, F. Visual odometry [tutorial]. *IEEE robotics & automation magazine*, 18(4):80–92, 2011.
- Scharstein, D. and Szeliski, R. A taxonomy and evaluation of dense two-frame stereo correspondence algorithms. *International journal of computer vision*, 47:7–42, 2002.
- Szeliski, R. *Computer vision: algorithms and applications*. Springer Nature, 2022.
- Tola, E., Lepetit, V., and Fua, P. Daisy: An efficient dense descriptor applied to wide-baseline stereo. *IEEE transactions on pattern analysis and machine intelligence*, 32(5):815–830, 2009.
- Wasenmüller, O. and Stricker, D. Comparison of kinect v1 and v2 depth images in terms of accuracy and precision. In *Computer Vision—ACCV 2016 Workshops: ACCV 2016 International Workshops, Taipei, Taiwan, November 20-24, 2016, Revised Selected Papers, Part II 13*, pp. 34–45. Springer, 2017.
- Wong, A., Fei, X., Tsuei, S., and Soatto, S. Unsupervised depth completion from visual inertial odometry. *IEEE Robotics and Automation Letters*, 5(2):1899–1906, 2020.
- Xian, K., Shen, C., Cao, Z., Lu, H., Xiao, Y., Li, R., and Luo, Z. Monocular relative depth perception with web stereo data supervision. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 311–320, 2018.

- Yang, L., Kang, B., Huang, Z., Zhao, Z., Xu, X., Feng, J., and Zhao, H. Depth anything v2. *arXiv preprint arXiv:2406.09414*, 2024.
- Yin, W., Zhang, C., Chen, H., Cai, Z., Yu, G., Wang, K., Chen, X., and Shen, C. Metric3d: Towards zero-shot metric 3d prediction from a single image. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 9043–9053, 2023.
- Yuan, W., Gu, X., Dai, Z., Zhu, S., and Tan, P. New crfs: Neural window fully-connected crfs for monocular depth estimation. arxiv 2022. *arXiv preprint arXiv:2203.01502*, 2022.
- Zhou, T., Brown, M., Snavely, N., and Lowe, D. G. Unsupervised learning of depth and ego-motion from video. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 1851–1858, 2017.