On the "Illusion" of Gender Bias in Face Recognition: Explaining the Fairness Issue Through Non-demographic Attributes

Paul Jonas Kurz, Haiyu Wu, Kevin W. Bowyer, Philipp Terhörst

Abstract—Face recognition systems (FRS) exhibit significant accuracy differences based on the user's gender. Since such a gender gap reduces the trustworthiness of FRS, more recent efforts have tried to find the causes. However, these studies make use of manually selected, correlated, and small-sized sets of facial features to support their claims. In this work, we analyse gender bias in face recognition by successfully extending the search domain to decorrelated combinations of 40 non-demographic facial characteristics. First, we propose a toolchain to effectively decorrelate and aggregate facial attributes to enable a less-biased gender analysis on large-scale data. Second, we introduce two new fairness metrics to measure fairness with and without context. Based on these grounds, we thirdly present a novel unsupervised algorithm able to reliably identify attribute combinations that lead to vanishing bias when used as filter predicates for balanced testing datasets. The experiments show that the gender gap vanishes when images of male and female subjects share specific attributes, clearly indicating that the issue is not a question of biology but of the social definition of appearance. These findings could reshape our understanding of fairness in face biometrics and provide insights into FRS, helping to address gender bias issues.

Index Terms—Face Recognition, Gender Bias, Gender Gap, Non-Demographic Attributes, Fairness, Biometrics, Explaninability.

I. INTRODUCTION

F ACE recognition systems (FRS) have been criticized as "biased", "sexist", or "racist" [1]–[5]. Such criticisms often come in response to research works that report that face recognition accuracy is lower for one demographic group than another [6]–[8]. For instance, it is observed that female faces are much more likely to produce wrong matching results than male faces. This phenomenon is known as the "gender gap" [9]. Since FRS are spreading worldwide, have a growing effect on daily life, and are increasingly used in critical decisionmaking processes, such as in forensics and law enforcement [10], [11], these systems have a strong potential to discriminate against people on a wider scale.

As FRS are based on data-driven deep learning techniques, the initial speculation is the underrepresentation of women in the training set that causes the inequality known as the gender gap¹ [13]. However, [14] have shown that explicitly balancing the training data for number of male and female identities and images does not result in gender-balanced accuracy in the test data. This motivates investigating the effect of nondemographic attributes [10], such as facial hairstyle [15], [16], makeup [17], scalp hairstyle [9], face exposure [18], face morphology [19] as non-demographic attributes are strongly encoded in face representations [20], [21]. Knowing the effect of individual attributes on the gender gap helps to understand the causes of the accuracy disparity between genders. However, potential correlations and combinations of these attributes could strongly affect the interpretation.

In this work, we fill this gap with three main contributions. First, we propose a set of tools to decorrelate and aggregate facial attributes, allowing for more objective reasoning about the gender gap. Second, we introduce two new fairness metrics to measure the achieved gender fairness of facial attributes in different context scenarios. Lastly, we present a novel unsupervised algorithm to reliably identify attribute combinations that minimize the gender gap. Our experiments begin with a set of 40 non-demographic attributes that describe elements of face image appearance, such as hair color, facial hair, or facial expression. A systematic analysis was conducted to investigate the impact of demographic attributes on the difference in male and female face recognition accuracy. The results demonstrated that the gender disparity in face recognition accuracy is effectively eliminated when the test sets are balanced on a small number of relevant non-demographic attributes. This suggests that the observed discrepancy in face recognition accuracy between males and females is more accurately attributed to social norms surrounding male and female appearance, rather than to biological factors or inherent biases in deep neural networks.

In contrast to previous works, the proposed contributions mainly differ in three aspects:

 Large-scale Attribute Analysis - We consider a wide variety of 40 facial characteristics in this work, significantly more than most comparable studies.

Paul Jonas Kurz is with Paderborn University, Paderborn, Germany and Technical University of Darmstadt, Darmstadt, Germany.

Haiyu Wu and Kevin W. Bowyer are with University of Notre Dame, Indiana, USA.

Philipp Terhörst is with Paderborn University, Paderborn, Germany. He also is the corresponding author.

¹"Gender" is defined as "the state of being male or female as it relates to social, cultural or behavioral factors" and "sex" is defined as "the state of being male or female as it relates to biological factors such as DNA, anatomy and physiology" [12]. In everyday discussion, the terms "gender" and "sex" are often used interchangeably. The term "gender bias" is a commonly used to refer to any instance of an algorithm that has different accuracy between male and female persons. Using the term "gender bias" in this study is not intended to convey any judgment on larger social issues of gender identity and expression.

- Attribute Decorrelation Unlike previous works, we propose a facial attribute decorrelation toolchain, meant to increase the expressiveness of our results while mitigating the probability of correlations distorting the outcomes.
- 3) Unsupervised Joint Investigation Framework While previous works analysed only individual attributes seperately, we devise a completely novel approach to jointly investigate the impact of combinations of non-demographic attributes on gender bias.

II. RELATED WORK

Gender bias in face recognition was first reported in the 2002 Face Recognition Vendor Test (FRVT) [22]. Before deep learning algorithms became popular, [23]–[27] already conducted experiments with multiple face recognition algorithms and consistently reported lower accuracy for females than for males. For deep-learning based face recognition, research increasingly focused on investigating and mitigating this bias.

Investigating Gender Bias: In recent years, advances in learning-based face recognition algorithms and datasets have led to remarkable performance, such as >99.8% accuracy on the LFW benchmark [28]. However, the improvement in absolute level of accuracy did not eliminate the accuracy disparity on gender [29]–[31]. Due to the central role of training data in deep learning, an intuitive speculation for the cause of gender bias is the female under-representation in the training data [13]. However, [14] reported that balancing the number of female and male identities and images in the training data does not result in balanced accuracy on the test data. Wu et al. [31] proposed the bias-aware dataset that controls the head pose, image quality, and brightness of the images in a reasonable range. It reduces the effect of the factors that can strongly affect recognition accuracy but are irrelevant to gender. They reported that males have 4.86% higher true positive rate (TPR) than females on this high image quality dataset. Researchers have also investigated the effects of image attributes associated with gender by social custom. For example, [13], [32]-[34] study the effects of makeup, use of which is more commonly associated with females than males, on face recognition accuracy. The typical observation is that makeup difference between images makes it harder for an algorithm to recognize the genuine (sameidentity) image pairs. The role of facial hair, commonly associated only with males, has also been investigated [15], [16], [35]. Results show that, for an image pair, a similar beard area increases the similarity and dissimilar beard area decreases the similarity. This effect is amplified if the facial hair position is at the central face area (moustache) and if the facial hair size gets larger. Researchers [17], [19], [31] also observed that male faces are on average larger than female, and balancing the test data on face morphology decreases the gender bias. Bhatta et al. [9] examined scalp-based hairstyle difference between males and females. After balancing the data on test set, the gender difference for genuine pairs is strongly reduced, but not for impostor pairs. Lastly, Terhörst et al. [10] comprehensively analyzed the performance of two algorithms on 47 attributes individually and found that these

attributes strongly correlate and that many non-demographic attributes strongly affect the recognition performance. While previous works did great efforts in analysing sources of gender bias, they did so by focusing on individual attributes. This ignores potential correlations and combinations between multiple attributes affecting the final interpretation.

Mitigating Gender Bias: The fact that gender bias was reported in a number of investigations motivated research into how to mitigate such bias. A popular strategy to mitigate this is bias is by modifying the training strategy or the network structure without changing the data. Terhörst et al. [36] introduced an unsupervised fairness score normalization, which guides the model to treat "similar" individuals "similarly". Their approach not only reduces the accuracy bias but also increases overall accuracy. Gong et al. [37] presented a debiasing adversarial network (DebFace), which learns how to extract disentangled unbiased features for face recognition and demographic estimation, as a means to mitigate demographic accuracy disparities. Park et al. [38] introduced the Fairness-aware Disentangling Variational Auto-Encoder (FD-VAE), which disentangles the target attribute latent, protected attribute latent, and mutual attribute latent, to mitigate the performance bias on gender and age. Dhar et al. [39] proposed a Distill and De-bias (D&D) structure to force a network to attend to similar face regions, irrespective of the attribute category. This approach is reported to reduce bias based on skintone. Dhar et al. [40] proposed a descriptor-based adversarial de-biasing approach to reduce gender and skintone information in order to reduce the bias while maintaining high performance. In conclusion, these works have the potential to narrow the gender gap. However, they approach the problem of mitigating unequal accuracy across gender without an understanding of the causes of unequal accuracy. With a deeper understanding of the underlying causes, it may be possible to develop more effective solutions.

This Work: This paper is the first to approach the task of identifying the facial characteristics accounting for gender bias in an entirely unsupervised manner. While previous works manually identified probable causes prior to testing their effect on bias, this work takes a different perspective. By focusing on minimising the gender gap as our primary optimization goal, we aim to identify those subsets of a large repository of decorrelated non-demographic attributes responsible for increased fairness as a by-product. By testing face recognition models in this way, we believe that the identified subsets can be linked to the observed gender bias with a high degree of confidence, yet minimal assumptions.

III. METHODOLOGY

This work explores how specific combinations of nondemographic facial attributes, shared across gender in the test data, minimize gender disparity. Our methodology relies on three core concepts. First, a dependable fairness metric is necessary to reliably assess the degree of gender bias in face recognition accuracy results. Such a metric is presented in Section III-A. Next, an efficient solution to forming attribute combinations and the corresponding test datasets is needed. Our solution to this is detailed in Section III-B. Last, we introduce a novel method of decorrelating facial attributes by clustering in Section III-C, enabling more expressive and generalizable results. Combining these techniques, we are able to project gender bias onto the presence or absence of a few facial features.

A. Fairness Metric

Generally, fairness metrics express the equitability of a system w.r.t. specific groups. For this work, we focus on equitable accuracy of face recognition for male and female.

1) iGARBE: We assume the notion of fairness in face biometrics as presented in [41]. A fair FRS yields the same false non-match rate FNMR(τ) at a given false match rate FMR_x(τ) for the considered subject groups. Here, τ corresponds to the decision threshold where FMR is equal to a chosen operational point x (e.g., 10^{-3} as proposed in [42]). Multiple fairness metrics exist that take up on this concept [41], [43], a recently presented one being GARBE [44]. It addresses accuracy and interpretability issues of previously proposed metrics, and is thus the most reliable and precise option known to us.

GARBE is based on an adjusted version of the well-known Gini coefficient G [45]. GARBE and the adjusted version of G are defined as:

$$\begin{aligned} \text{GARBE}(\tau) &= \alpha A(\tau) + (1 - \alpha) B(\tau) & \text{where} \\ A(\tau) &= G_{\text{FMR}_{\tau}} & \text{and} & (1) \\ B(\tau) &= G_{\text{FNMR}_{\tau}} \\ G_x &= \left(\frac{n}{n-1}\right) \left(\frac{\sum_{i=1}^n \sum_{j=1}^n |x_i - x_j|}{2n^2 \bar{x}}\right) & \forall d_i, d_j \in D \end{aligned}$$

respectively.

We adapt the original GARBE to reflect the intuition that a perfectly fair system have a score of 1 and a perfectly unfair system a score of 0. The original GARBE behaves inversely to this. Since it is bounded to $[0,1] \subset \mathbb{R}$, we compute the inverse GARBE (iGARBE) as

$$iGARBE(\tau) = 1 - GARBE(\tau)$$
 (3)

(2)

Accordingly, iGARBE will be used as the fairness metric of choice in all following sections of this work.

2) Contextualized Fairness (CoFair): The iGARBE metric, as well as the Gini coefficient it is based on, are reliable absolute measures of fairness. However, their results provide no information about how much better the fairness scores computed on one set of attributes are relative to the scores computed on another set of attributes. We therefore propose the computation of contextualized fairness, or CoFair in short, as an additional figure of scrutiny. Given an FRS-specific, estimated probability density of iGARBE scores f and an iGARBE score s, CoFair(s) = p simply reflects the cumulative probability p of any other iGARBE score S being smaller than s. This definition is presented in Equation 4 in more rigor.

$$\operatorname{CoFair}(s) = F_S(s) = P(S \le s) = \int_{-\infty}^{s} f_S(t) dt \qquad (4)$$

Put simply, CoFair expresses the expected fraction of iGARBE scores, computed on varying sets of attributes, that are smaller than or equal to the given score (and thus, the given set of attributes) for a fixed FRS. Therefore, the higher the CoFair value of such a score, the better.

B. Forming Fair Attribute Combinations

We define an attribute combination as a nonempty set of labeled non-demographic attributes. Throughout this work, the terms *labeled (non-demographic) attributes* and *assignments* are used interchangeably. We use the MAAD-Face database [46] as a reference for available non-demographic attributes. It comprises 3.3M images of over 9k distinct individuals, with each image being annotated with 7 demographic and 40 non-demographic attributes (related to, e.g., hair or accessories). Accordingly, the accommodating ternary labels are taken from MAAD-Face as well. However, for the combinations, we limit the space of available labels to only positive (1) and negative (-1), omitting unclear (0) labels to increase expressiveness. Positive labels indicate that the given attribute must be present in the corresponding faces. Conversely, negative labels indicate the specific absence of a given attribute.

Forming fair attribute combinations requires measuring combinations' iGARBE scores. To this end, we use a custom created database of comparisons of annotated image templates. The annotated templates are provided by MAAD-Face's annotated version of VGGFace2 [47]. More relevant details are provided in Section IV-A. The comparison database is then filtered for pairs of image templates of same-gender subjects whose annotations conform with the requirements set by the assignment combination in question. Section III-B1 describes this process in-depth. In consideration of the focus of this work, the resulting subset is then further decomposed into male and female subgroups, respectively. To eliminate the chance of sample-size disparities negatively impacting further analyses, the subgroups' sets are further sampled (see Section III-B2 for more details). Throughout this paper, we refer to the process of filtering and sampling given an assignment combination as "equalizing" or "equalization", describing the forced sharing of an attribute subset across genders. We compute the iGARBE scores over those samples to measure the effect of the attribute combinations in question, linking the results directly to the combination. Accordingly, we call an attribute combination fair if its iGARBE score approaches 1 sufficiently closely at a fixed FMR. Similarly, we call it fairness-increasing if its iGARBE score increases relative to a provided baseline at a fixed FMR.

Given these concepts, the question remains how combinations that are at least fairness-increasing and ideally fair can be determined. It might seem trivial to combine those labeled attributes, which are each fairness-increasing or even fair by themselves. However, this assumes that the provided attributes are statistically independent. To investigate this assumption, we compute the Pearson correlation between all pairs of attributes. A relevant excerpt of the results is shown in Figure 1. It depicts all correlations between those attributes that are featured in the 15 highest *absolute* pairwise correlations. As



Fig. 1: Attribute annotation correlations - The correlations are computed using the Pearson coefficient. The depicted attributes are selected such that the 15 highest absolute, i.e., positive or negative, correlations are visible. As can be seen, very strong correlations exist between various attributes, indicating that they are not statistically independent.

can be seen, correlations with absolute values of 0.75 and higher exist. Clearly, the attributes at hand are not statistically independent. Therefore, we have to form and examine combinations as standalones, discarding the individual effects of attributes they comprise.

Under this assumption, however, the search space becomes very large. As previously elaborated, MAAD-Face assigns each image template one of three values for each of 40 non-demographic attributes. While we limit ourselves to only use explicitly positive or negative labels for attributes that we combine, the remaining annotations are left undefined. Thus, we can approximate the magnitude of possible assignment combinations to be around $3^{40} - 1 \approx 1.2 \cdot 10^{19}$. Computing the effects of all these combinations on fairness is practically impossible in limited time.

Hence, a guided approach that allows to effectively yet efficiently navigate the search space is needed. We therefore propose a greedy attribute-combining algorithm similar to breadth-first search. At its heart, it adds the $n \in \mathbb{N}$ most relevant, fairness-increasing assignments to a given node in the search tree, starting with the root node. The relevance of assignments is determined via a custom ranking metric elaborated on in Section III-B3. This process is repeated for each node in the tree at a given depth $d \in \mathbb{N}$ until a pre-defined depth limit $d_{max} \in \mathbb{N}$ is reached. Upon completion, each branch in the tree represents a fairness-increasing assignment combination. The corresponding algorithm is presented in Algorithm 1. In the following, the previously referenced components supporting this approach, namely filtering, sampling,

Algorithm 1 - Assignment Combination Forming

Input: $\mathcal{T}, \mathcal{A}^l, f_0, d_{max}, n$ **Output:** T'1: $\mathcal{T}' \leftarrow \mathcal{T}$ 2: for all $d \in [0, d_{max}] \subset \mathbb{N}$ do $\mathcal{N} \leftarrow \text{NODESATDEPTH}(d, \mathcal{T}')$ 3: for all $\nu \in \mathcal{N}$ do 4: 5: $\mathcal{M}_{\nu} \leftarrow \{\}$ $\mathcal{B} \leftarrow \text{BRANCHTONODE}(\nu, \mathcal{T}')$ 6: for all $A^l \in \mathcal{A}^l$ do 7: $\mathcal{C} \leftarrow \{A^l\} \cup \mathcal{B}$ 8: $m_{A^l} \leftarrow \text{METRICSOFCOMBINATION}(\mathcal{C})$ 9: if FAIRNESS $(m_{A^l}) > f_0$ then 10: $\mathcal{M}_{\nu} \leftarrow \mathcal{M}_{\nu} \cup \left\{ \left(m_{A^{l}}, A^{l} \right) \right\}$ 11: 12: end if end for 13: $\mathcal{A}_{r}^{l} \leftarrow \mathsf{RelevantAssignments}(n, \mathcal{M}_{\nu})$ 14: ADDTONODE($\mathcal{A}_r^l, \nu, \mathcal{T}'$) 15: end for 16: 17: end for 18: return \mathcal{T}'

Algorithm 2 - Comparison Filtering

Input: S, L, COutput: S_f

1: $\mathcal{L}_{f} \leftarrow \text{LABELEDTEMPLATESBYCOMBINATION}(\mathcal{C}, \mathcal{L})$ 2: $\mathcal{S}_{f,1} \leftarrow \mathcal{S} \rtimes_{\mathcal{S}.idx_1 = \mathcal{L}_{f}.idx} \mathcal{L}_{f}$ 3: $\mathcal{S}_{f,2} \leftarrow \mathcal{S} \rtimes_{\mathcal{S}.idx_2 = \mathcal{L}_{f}.idx} \mathcal{L}_{f}$ 4: $\mathcal{S}_{f} \leftarrow \mathcal{S}_{f,1} \cap \mathcal{S}_{f,2}$ 5: **return** \mathcal{S}_{f}

and ranking, are explained in detail.

1) Filtering: In the proposed approach, a crucial step is filtering all available template comparisons for those in which both partners fulfill the requirements regarding the presence or absence of attributes. These requirements, as previously elaborated, are set by the assignment combination in question.

Given our experimental workflow and tools described in Section IV, we approach this problem in three steps. First, filter the labeled individual templates for those of interest, i.e., those annotated with the assignments of the currently inspected combination. Second, semi-join [48] the indices of these filtered templates, in this case the primary keys, on the comparisons dataset. Since each comparison is comprised of two paired templates, this join is executed on the index of each partner, respectively. Last, intersect the results to retrieve only those comparisons in which *both* partners match the given specifications.

A summary of this algorithm is provided in Algorithm 2. Here, S is the dataset containing the comparisons, \mathcal{L} is the database of labeled templates, and C is the assignment combination setting the requirements and, thus, dictating the filter predicate.

2) Sampling: We sample the filtered comparisons to mainly rule out sample size disparities as root causes for bias. Simultaneously, sampling also prevents small-sized outliers to distort

any results. It is therefore crucial to take these two aspects into account to ultimately enhance informational value.

To this end, we present a custom sampling method. We assemble γ sets of comparison samples per subgroup, such that all sets contain the same number of samples. These samples are chosen uniformly at random from the available comparisons, i.e., those resulting from filtering. Additionally, each such set must adhere to a sample ratio $\rho_s = \frac{1}{\beta}$, with β dictating how many imposter comparisons per genuine comparison the set must comprise. λ_q and λ_i are used as lower boundaries, describing the minimum number of genuine and imposter samples that must be contained in each such set. Note that we ensure that for each subgroup, $\bigcap^{\gamma} S_q^{(\cap \emptyset)} = \emptyset$, i.e., that the available genuine samples are uniquely distributed across all γ sets. However, we disregard this requirement for imposter samples. Since we compute the FNMR at a fixed FMR for our results, it is critical to minimize the risk of duplicated outlier genuine comparisons affecting the FNMR. As there are more imposter comparisons at our disposal in the first place, which by their nature are also more noisy, it is not necessary to enforce these rules w.r.t. the FMR.

Ultimately, Algorithm 3 therefore yields γ fixed-sized, bounded sample sets of genuine and imposter comparisons contained in \mathcal{G}_g^s , \mathcal{G}_i^s for all given genuine and imposter comparisons per subgroup provided through \mathcal{G}_g , \mathcal{G}_i .

In this work, we set $\rho_s = \frac{1}{5}$ to balance computational complexity and the number of samples taken into consideration. For the same reasons as well as the advantage of robust computations of means and standard deviations, we choose $\gamma = 3$. Lastly, $\lambda_g = \frac{1}{\text{FMR}}$ is set to consistently ensure an adequate number of samples given the level of scrutiny the system is put under due to the FMR and the corresponding decision thresholds.

3) Ranking: The proposed approach progressively forms fairness-increasing assignment combinations. As previously described, this involves extending the corresponding search tree with the $n \in \mathbb{N}$ most relevant assignments for each node at each level. To determine these relevant assignments, two steps have to performed. First, the assignments need to be ranked. Subsequently, they need to be pruned for the results to reflect the desired top-n characteristics. While pruning is a straightforward process, ranking is more intricate. We will therefore present the corresponding metric devised for this work in the following.

In designing the ranking metric, the goal is to characterize the effects of assignments w.r.t. three core factors. First, the genuine sample retention is considered. Compared to the originally available number of samples, the currently inspected assignment combination should retain as many as possible. Second, we inspect the assignment combination's effect on the verification error. It should not increase the overall system's verification error, while decreases should be rewarded. Consistency should neither be penalized nor rewarded. Third, in line with this work's objective, the assignment combination in question should increase fairness. The bigger the increase, the higher the reward. Decreases are penalized. Consistency is not minded. All of these factors are to be *weighted equally* in the evaluation. Algorithm 3 - Comparison Sampling **Input:** $\mathcal{G}_g, \mathcal{G}_i, \rho_s, \lambda_g, \gamma$ **Output:** \mathcal{G}_q^s , \mathcal{G}_i^s > Determine max count of samples equal across genders 1: $c_g^{(+)} \leftarrow \text{MaxEqualSampleCount}(\mathcal{G}_g)$ 2: $c_i^{(+)} \leftarrow \text{MaxEqualSampleCount}(\mathcal{G}_i)$ 3: $c_g^{(\cap \emptyset)} \leftarrow \left| \frac{c_g^{(+)}}{\gamma} \right|$ 4: $\lambda_i \leftarrow \left\lfloor \frac{\lambda_g}{\rho_s} \right\rfloor^{-1}$ 5: if $\left(c_g^{(\cap \emptyset)} < \lambda_g \right) \lor \left(c_i^{(+)} < \lambda_i \right)$ then 6: return \emptyset, \emptyset 7: end if 8: $c_g, c_i \leftarrow 0$ > Adjust sample sizes to respect sample ratio 9: if $(c_g^{(\cap \emptyset)} \cdot \rho_s) > c_i^{(+)}$ then ▷ Keep all imposter samples $\begin{array}{c} c_g \leftarrow \begin{bmatrix} c_i^{(+)} \cdot \rho_s \end{bmatrix} \\ c_i \leftarrow c_i^{(+)} \end{array}$ 10: 11: 12: else $\begin{array}{l} \triangleright \text{ Keep all genuine samples} \\ c_g \leftarrow c_g^{(\cap \emptyset)} \\ c_i \leftarrow \left\lfloor \frac{c_g^{(\cap \emptyset)}}{\rho_s} \right\rfloor \end{array}$ 13: 14: 15: end if 16: $\mathcal{G}_q^s, \, \mathcal{G}_i^s \leftarrow \{\}, \, \{\}$ 10. $\mathcal{G}_{g}, \mathcal{G}_{i} \in \mathcal{G}_{g}, \mathcal{G}_{i} \in \mathcal{G}_{i}$ do 17: for all $\mathcal{S}_{g} \in \mathcal{G}_{g}, \mathcal{S}_{i} \in \mathcal{G}_{i}$ do 18: $\mathcal{S}_{g}^{(\cap \emptyset)} \leftarrow \text{NDISJOINTSAMPLEGROUPS}(\gamma, c_{g}, \mathcal{S}_{g})$ 19: $\mathcal{S}_{i}^{s} \leftarrow \text{NSAMPLEGROUPS}(\gamma, c_{i}, \mathcal{S}_{i})$ 20: $\mathcal{G}_{g}^{s} \leftarrow \mathcal{G}_{g}^{s} \cup \left\{ \mathcal{S}_{g}^{(\cap \emptyset)} \right\}$ 21: $\mathcal{G}_{i}^{s} \leftarrow \mathcal{G}_{i}^{s} \cup \left\{ \mathcal{S}_{i}^{s} \right\}$ 22: end for 23: return \mathcal{G}_a^s , \mathcal{G}_i^s

For the implementation of these requirements, we use the well-known sigmoid function σ as a baseline, primarily to leverage its [0, 1]-bounded properties. Consequently, we define our ranking metric as shown in Equation 5.

$$R = \frac{1}{3} \left(R_s + R_p + R_f \right) \text{ with } \tag{5}$$

$$R_s(n_i, \text{FMR}) = \sigma((-\text{FMR} \cdot n_i \cdot (\ln(4) - \mu)) - \mu) \qquad (6)$$

$$R_{p}(\text{FNMR}_{i}, \text{FNMR}_{0}) = \sigma(\lambda (\text{FNMR}_{0} - \text{FNMR}_{i})) \quad (7)$$

$$R_f(f_i, f_0) = \sigma(\omega \left(f_i - f_0\right)) \tag{8}$$

Equations 6, 7, and 8 correspond to the previously described core factors: R_s to genuine sample retention, R_p to verification error, and R_f to fairness. They are structured such that the following holds.

$$R_s \left(\frac{1}{\text{FMR}}, \text{FMR}\right) = 0.2$$

$$R_p (\text{FNMR}_0, \text{FNMR}_0) = 0.5$$

$$R_f (f_0, f_0) = 0.5$$

In all formulas, variables indexed with 0 represent baseline values, while those indexed with i represent values resulting

from evaluating the currently inspected assignment combination. The number of retained genuine samples is represented through n, the current iGARBE score through f. The hyperparameters $\mu, \lambda, \omega \in \mathbb{R}_+$ determine the slope, i.e., how quickly higher scores should be awarded. We desire a moderate scoring behaviour to neither reward minor improvements too highly nor penalize lightly deteriorated values too drastically. Moreover, R_s , R_p , and R_f should behave similarly over relative, semantically equivalent ranges of their relevant domain. To estimate generic hyperparameters for this work, we assume there to be at max 10^7 genuine samples, FNMR₀ = 0.1, and $f_0 = 0.9$. A suitable estimation under these constraints is $\mu = 1.3865$ and $\lambda = \omega = 4$.

C. Decorrelating Attribute Annotations

As shown in Figure 1, the attributes used for annotations in MAAD-Face are highly correlated w.r.t. Pearson correlation. For this work, this is problematic as it restricts the exploratory capabilities of the approach presented in Section III-B. This is because of the limited branch depth. Assume the discovery of a fairness-increasing assignment combination made up of only correlating attributes. Then, this combination of attributes relating to similar underlying characteristics occupies one branch of the tree. Uncovering such correlated fairness-increasing assignment combinations undoubtedly is of high interest. However, the focus of this work is to provide as broad of an overview over likely causes of gender bias as possible. Not limiting the effects of these correlations would interfere with this objective by reducing the expressiveness and informational value of the presented method and its results. Therefore, we devise a decorrelation method to create clusters of correlated attributes such that the underlying attributes can be treated as one. It involves two steps. First, clusters themselves must be formed. This process is described in Section III-C1. Second, the clusters need to be harmonized to reduce the overall correlation. Details are provided in Section III-C2.

1) Incremental Clustering: We intend clusters to comprise attributes that significantly correlate with each other w.r.t. Pearson correlation. This implies both positive and negative correlations, as both cases need to be accounted for in further steps. Thus, we incrementally create clusters based on the pairwise absolute Pearson correlation. In the following, clusters may contain an arbitrary number of attributes in the range $[1, |\mathcal{A}|] \subset \mathbb{N}$, i.e., individual attributes are also viewed as clusters. The corresponding algorithm is presented in Algorithm 4.

Given the initial set of attribute annotations \mathcal{A} as provided by MAAD-Face, it merges the two most correlated clusters in each of the $i_{max} \in \mathbb{N}$ iterations, with $0 \leq i_{max} \leq |\mathcal{A}|$. To this end, the pairwise absolute Pearson correlation of all clusters, \mathcal{R} , is determined. If two clusters contain more than one attribute, we calculate the mean pairwise absolute Pearson correlation between all pairs of attributes that are not part of the same cluster. Subsequently, we merge the pair of clusters $\{A_{\perp,1}, A_{\perp,2}\}$ with the maximum out of all gathered absolute Pearson correlations.

Algorithm 4 - Correlated Attribute Clustering

Input: A, i_{max} Output: $A_{\perp\!\!\perp}$ 1: $\mathcal{A}_{\perp\!\perp} \leftarrow \mathcal{A}$ 2: for all $_ \in [0, i_{max} - 1] \subset \mathbb{N}$ do 3: $\mathcal{R} \leftarrow \emptyset$ 4: for all $A_{\perp \perp} \in A_{\perp \perp}$ do $\Delta \mathcal{A}_{\perp\!\!\perp} \leftarrow \mathcal{A}_{\perp\!\!\perp} - \{A_{\perp\!\!\perp}\}$ 5: for all $\Delta A_{\parallel} \in \Delta A_{\parallel}$ do 6: $r \leftarrow | \operatorname{Pearson}(A_{\perp \perp}, \Delta A_{\perp \perp}) |$ 7: $\mathcal{R} \leftarrow \mathcal{R} \cup \{(r, A_{\perp}, \Delta A_{\perp})\}$ 8: end for 9: 10: end for $_, A_{\perp \perp, 1}, A_{\perp \perp, 2} \leftarrow \max_r \mathcal{R}$ 11: $\mathcal{A}_{\perp} \leftarrow ((\mathcal{A}_{\perp} - A_{\perp,1}) - A_{\perp,2}) \cup \{A_{\perp,1}, A_{\perp,2}\}$ 12: 13: end for 14: return \mathcal{A}_{\parallel}

As determining an optimal i_{max} is not generalizable, the required process and corresponding results are detailed in Section V-A.

2) Cluster Harmonization: As stated previously, we intend to use the clusters resulting from the iterative decorrelation methodology as if they were standalone attributes. However, doing so is not straightforward. Since we use the absolute correlation as a baseline metric, we consciously encourage contradicting but correlating attributes to be clustered in particular. This imposes a problem when trying to assign labels to a cluster as is necessary for the presented approach for forming assignment combinations. Assuming inverse underlying semantics of two clustered attributes A_1 and A_2 , assigning $\{A_1, A_2\} = 1$ would simultaneously require the presence and absence of the same facial characteristic. Subsequent filtering for samples that accord with this predicate would yield no results, rendering our clusters unusable. Consequently, we harmonize the clusters.

In the case of this work, harmonizing entails ensuring that clusters only contain positive correlations without adding or removing any attributes. Thereby, the most transparent behaviour is ensured. Assigning positive labels to a cluster reflects the specific presence of the underlying attributes, while assigning negative labels does the inverse. To facilitate these characteristics, first, the two most negatively correlating attributes of a given cluster are determined. If there are no negative correlations, we do not need to harmonize the cluster. Otherwise, one of these two attributes is used as reference. All other attributes in the cluster will then be inverted, if necessary, such that their correlation with the reference attribute will be exclusively positive. Note that this results in exclusively positive *pairwise* correlations between *all attributes* in the given cluster.

To correctly integrate this behaviour with the rest of our work, the inversion of an attribute leads to three actions being taken. First, it is added the prefix "Not" to intuitively reflect the semantics of the change. Second, all samples with a non-zero annotation of the now inverted attribute have to be inverted as well to guarantee uniformity across the given datasets. Third, the correlations must be updated accordingly. By conforming to these steps, clusters can now be assigned labels as if they were mere attributes without any issues.

IV. EXPERIMENTAL SETUP

A. Databases

The goal of this work is to provide an approach to explain gender bias in face recognition via combinations of nondemographic attributes. To facilitate this task, the use of a large-size database with many high quality attribute annotations is required. It ensures unconstrained conditions and thus allows to make expressive and generalizable statements. Based on these specifications, we choose the publicly available MAAD-Face annotation database [46]. It annotates each of the 3.3M images of over 9k distinct individuals of VGGFace2 [47] with 47 ternary attributes. Of those, 7 relate to demographic factors, namely gender, ethnicity, and age. The remaining 40 relate to non-demographic facial features such as hair or accessories. As the focus of this work is gender bias, we desire a acceptably balanced dataset w.r.t. gender to equally represent male and female individuals. In VGGFace2 and, thus, MAAD-Face, about 60% of the images are of male individuals and the remaining approx. 40% of female subjects. Moreover, the images feature a variety of head poses, thereby providing an even broader representation of recognition scenarios. Lastly, MAAD-Face's attribute annotations are proven to have higher quality than comparable face annotation databases [46].

B. Face Recognition Models

For all experiments conducted in this work, we use templates created by two of the most popular face recognition models trained on two widely-used loss functions: ArcFace [49] and FaceNet [50]. Both models were prepared as described in [10]. In short, the pre-trained models for ArcFace² and FaceNet³ are based on ResNet-100 backbones and are trained on the MS1M database [51]. They are then applied to images that, for ArcFace, were pre-processed as described in [52] and, for FaceNet, as described in [53]. The resulting templates are then compared using cosine similarity to enable identity verification.

C. Metrics

We report the results of our investigations in terms of FNMRs at decision thresholds corresponding to fixed FMRs. These error rates are the international standard for biometric verification evaluation [54]. Throughout our analyses, we set FMR = 10^{-3} , conforming to the recommendations of the European Border And Coast Guard Agency Frontex [42]. We measure the resulting FNMRs such that both total and differential verification performance can be inspected. Thereby, effects on overall system performance as well as effects on male and female subgroups are quantified.

To assess fairness, we compute the iGARBE scores based on those metrics, as described in Section III-A1. Doing so allows us to express the differential outcome, as per the definition of Howard *et al.* [55], across an arbitrary number of compared demographic groups in a single [0, 1]-bounded score. Additionally, it enables the simple comparison of results in the context of a single face recognition model. To also facilitate inter-model discussions about fairness, we contextualize these values with their underlying distribution characteristics through computing CoFair as detailed in Section III-A2. Using the conjunction of these metrics provides us with the necessary tooling to approach the desired fairness analyses holistically.

Lastly, we also provide the number of genuine samples that meet the criteria dictated by the respective attribute filter predicate. Although the high baseline quality of all results is programmatically enforced via strict sampling constraints as per Section III-B2, incorporating the size of the underlying genuine dataset aids in better understanding the impact of the findings w.r.t. their magnitude.

D. Investigations

We apply and evaluate the proposed methodology in multiple steps to investigate the combined effect of nondemographic attributes on fairness. First, we assess the impact of progressive decorrelation to determine the most suitable setting for all further analyses. Using the resulting attribute clusters, we then evaluate how ArcFace and FaceNet perform on samples reflecting the presence or absence of one or multiple of those clusters and their underlying attributes. Specifically, we inspect the differences in error rates between male and female-labelled samples to assess the clusters' influence on gender fairness. In this respect, we proceed in two stages. First, we investigate the effect of individual clusters adhering to the filtering constraints we imposed. Then, we subsequently re-perform our investigations once our proposed attribute combination approach was applied to those clusters. In doing so, we emphasize the effectiveness of the second approach, which is the focus of this work.

V. RESULTS

A. Mitigating the Effects of Attribute Correlations

As seen in Figure 1, various attributes provided by MAAD-Face [46] are highly correlated with each other. If these correlations are not taken into account or better yet mitigated, misinterpretations or limited expressiveness of our approach's results may be the consequence. Therefore, we apply the iterative clustering-based decorrelation approach presented in Section III-C to group together highly correlated attributes. To determine the optimal clustering, we define three core criteria in the following.

First, since the overall objective is to retrieve decorrelated clusters, it is desirable to achieve a **low inter-cluster correla**tion. Second, we want an overall **low number of clusters**. Intuitively, when looking at MAAD-Face, a high number of clusters indicates the retention of numerous correlated attributes that were not yet assigned to their "suitable" cluster. Third and last, it is critical to achieve a **high retention of (genuine) samples**. Undoubtedly, the more samples are retained for a specific cluster, the more expressive the results

²https://github.com/deepinsight/insightface

³https://github.com/davidsandberg/facenet



Fig. 2: Evolution of critical clustering metrics over progressing decorrelation - The chosen measurements reflect the efficacy of the devised algorithm in reducing the correlation of MAAD-Face's non-demographic attributes. The iteration range reflects the clustering intensity, ranging from 0 (no clustering) to 39 (all attributes in one cluster). The number of clusters, mean and maximum correlation decrease linearly. For an optimal clustering w.r.t. low inter-cluster correlation and low number of clusters, it is therefore sensible to choose as late of an iteration as possible. To also accommodate the sampling requirements into these criteria, we conceive iteration 13 as optimal, since these requirements cannot be fulfilled thereafter (orange background).

produced by any given analysis executed on the respective cluster are. However, it is not sufficient to solely take into account the global number of retained samples. Since we assess the effects of those attributes on Male and Female subgroups separately, it is critical to ensure that for each subgroup, the sampling requirements as per Section III-B2 are met. This is not trivial since, e.g., beards intuitively correlate more strongly with the male than with the female subgroup for biological reasons. Consequently, we only view a clustering as valid if there is at least one label assignment to each cluster such that there are enough retained samples for each subgroup.

We proceed to evaluating the proposed decorrelation method under the stated criteria. Consider Figure 2 for a visual representation of the key metrics' evolution over the algorithm's iterative progression. As expected, a linear descent of the number of clusters w.r.t. the iterations can be witnessed. This is intuitive since in each iteration, one cluster, which can either be a standalone attribute or a group thereof, is merged with another. Moreover, we observe a steadily decreasing mean and maximum inter-cluster correlation. From that behaviour, we can draw the interim conclusion that regarding the first two criteria, the optimal result seems to converge with progressing iterations. However, we have not yet accounted for the retention of samples and associated sampling requirements, the third criterion. Its evolution over the course of the iterations is indicated through the shading of the background. The value space here is binary as the requirements can either be met (green) or not met (orange). We see that for the first 13 iterations the requirements can be fulfilled, but not anytime thereafter.

Based on those observations, we can infer that the clustering

algorithm should terminate after iteration 13. This conclusion is based on the observation that this iteration is the only one meeting the third criterion and, due to the converging nature of the related metrics, also the other two criteria. This leaves us with 27 clusters having a mean inter-cluster correlation of approx. 0.21 with a standard deviation of about 0.16. The maximum inter-cluster correlation is around 0.67. Making these results more accessible, we name each resulting attributecluster containing more than one attribute. To this end, we aim to find the most suitable description, best representing the semantics of the attributes the respective cluster is comprised of. Our findings are shown in Table I. All attributes originally dictated by MAAD-Face that do not occur in this table were not clustered and thus remain unchanged. They will still be taken into account in all further analyses, in conjunction with the newly found clusters. The decorrelated nature of this newly constructed attribute set contributes to the expressiveness and generalizability of this work's results.

B. Equalizing Individual Attributes

We begin with evaluating the fairness and performance of ArcFace and FaceNet. To this end, we probe them with samples that result from individually equalizing the clusters the decorrelated attribute set comprises. This is the first step towards projecting gender bias in face recognition to the presence or absence of a subset of non-demographic facial attributes. Unbalanced data distributions are accounted for by applying the custom sampling technique as presented in Section III-B2, and can therefore be neglected in all further analyses.

The results of these investigations are presented in Table II. For each attribute, we provide results for ArcFace and FaceNet in terms of iGARBE and overall FNMR, as well as the number of genuine samples. As can be observed, we retain enough samples to inspect both positively (\checkmark) and negatively (\checkmark) labeled assignments for *Bangs*, *Receding Hairline*, *Brown Eyes*, *Fully Visible Forehead*, *Black Hair*, *Wearing Hat*, *Obstructed Forehead*, *Pointy Nose*, *Cheerful*, *Big Lips*, *Shiny Skin*, *Bushy Eyebrows*, *Brown Hair*, and *Square Face*. However, there exist attributes for which only negative but no positive label assignments are analyzed. This is due to the omitted assignments not conforming with the sampling requirements we enforce to maintain high quality, highly expressive results. Hence, we exclude these in our evaluation, retaining a total of 41 results.

For ArcFace, 11 attribute cluster assignments exceed baseline fairness. These correspond to the absence of *Generic Facial Hair* and *Frontal Facial Hair*, not having the *Mouth Closed*, not being *Bald* or *Corpulent*, not having *Gray Hair* or a *Fully Visible Forehead*, not *Wearing Necktie*, having a *Square Face*, and especially not having a *Receding Hairline* as well as having *Brown Hair*. The latter is particularly interesting, leading to an increased iGARBE fairness score of 0.9984 and a decreased FNMR of 0.0585 (corresponding to a system performance improvement of 18%) when probed on ArcFace. With a retained 1.7 million genuine samples, the results are highly significant. In nearly all other cases, an improved system TABLE I: **Clusters resulting from decorrelation** - Reported in conjunction with author-chosen descriptive titles representing the respective cluster semantics. Note that this table only shows results for clustered attributes, i.e., clusters with a size of greater than or equal to two. All non-demographic attributes that are part of MAAD-Face but do not show up here were not clustered and remain unchanged. Clustered and remaining unchanged attributes will be used in all further analyses.

Feminine	Gene	ric Facial Hair	Fro	ntal Facial Hair	Rugged		
Rosy Cheeks Wearing Earrings Wearing Lipstick Heavy Makeup	5 o'C Sidet Not 1	Clock Shadow ourns No Beard	Goa Mu	atee stache	Big Nose Bags Under Eyes		
Attractive Wayy Hair		Cheerful		Eyewear	Corpulent		
Arched Eyebrows		High Cheekbor Smiling	nes	Eyeglasses Not No Eyewear	Chubby Double Chin		

fairness leads to a decreased system performance. Crucially, we mitigate the probability of underlying correlations to be a factor in these outcomes due to the decorrelated nature of the attribute clusters.

Evaluating the results for the samples probed on FaceNet, it can be seen that 21 attribute cluster assignments exceed baseline fairness. The best one of those corresponds to the absence of a Receding Hairline. It leads to an increased iGARBE score of 0.9951 but also to an increased FNMR of 0.4218 (corresponding to an $\approx 19\%$ system performance deterioration). Approximately 4.5 million matching genuine samples are retained. Interestingly, this particular assignment also is the second best performing attribute for ArcFace. Moreover, the corresponding observations made match those asserted with ArcFace as well. Most times, the equalization of individual attribute clusters across genders shows an inverse relationship between system fairness and system performance. The only significant outlier for FaceNet in this respect, showing high iGARBE scores as well as leading to significantly improved system performance, results from probing the system with samples labeled as having Bushy Eyebrows. Doing so yields an iGARBE score of 0.9794 and an FNMR of 0.2957. However, at only 57 thousand retained genuine samples, the expressiveness of these results is reduced compared to those assignments with a genuine sample retention in the millions.

For both FRS, the rest of the results match these findings and show no other interesting features. As can be deduced, by filtering for individual attribute clusters only, we fall short of baseline fairness in the majority of cases. If it is exceeded, then this fairness-increasing characteristic can only be achieved at the expense of system performance (aside for some few outliers). However, even these outliers do not systematically converge to perfect fairness scores of 1. These observations reinforce both the plausibility and the necessity of focusing on an approach that combines multiple attribute clusters to uncover which *combinations* affect gender bias the most, ideally without deteriorating false-negative error rates. In doing so and, thus, by applying this work's proposed methodology, we can therefore be more productive w.r.t. the research objective at hand.

C. Equalizing Attribute Combinations

1) Performance: We proceed to inspect how combinations of attribute cluster assignments affect system fairness and performance. Therefore, we apply the methodology as proposed in Section III-B. To this end, we will search for optimal combinations w.r.t. system fairness separately for ArcFace and FaceNet to account for the varying topology of the optimization problem. Such differences are most likely caused by the different loss functions used in training the FRS. Nonetheless, we will evaluate the corresponding optimal combinations for the respective other system as well. We report our results in Table III.

The results of applying the proposed approach to find optimal results for ArcFace are presented in Table IIIa. All assignment combinations clearly exceed baseline fairness with values ranging from 0.9974 to 0.9987. Considering that a maximum possible iGARBE score of 1 indicates perfect fairness, these high scores are especially noteworthy. Most of the assignments responsible for these results are related to (facial) hair. Receding Hairline, Bushy Eyebrows, Blond Hair, Frontal Facial Hair, Gray Hair, Bangs, Bald, and Black Hair all fall under that category. The second most prominent attribute clusters can be categorized as "occluding accessories", namely Eyewear, Wearing Hat, and Wearing Necktie. Corpulent is the only outlier. Given this observation, it can be inferred that for ArcFace, a lack of facial hair and the absence of certain hair colors but the overall presence of hair, is beneficial for equal recognition performance across gender. Paired with the absence of specific occluding accessories in some cases, we can deduct that the masking of specific facial areas or the lack thereof is an important factor for differential outcome across genders for ArcFace. The sporadic occurrence or absence of Corpulent throughout the results can be related to this inference using the common notion that an equal amount of face representation is paramount for cross-gender fairness, which this cluster allows more control over. Otherwise, there seems to be no clear pattern of which combinations occur regularly, i.e., which attribute clusters are often paired with others or not.

The overall system performance increases for four out of ten

TABLE II: Face recognition fairness and performance on test samples filtered for individual decorrelated attributes -Reported in terms of FNMR for a fixed FMR of 10^{-3} as well as the fairness metric iGARBE. The number of genuine samples indicates the scarcity of samples annotated with the respective attribute-label pair. Pairs for which not enough samples could be retrieved to conform to the sampling requirements were left out. Although some assignments lead to increased fairness (higher iGARBE values), these improvements come at the cost of system performance (higher FNMR) most times. Perfect fairness cannot be achieved by solely inspecting the results of equalizing individual attributes.

		ArcF	ace	Face	Net	
Attribute	Label	iGARBE	FNMR	iGARBE	FNMR	Genuine Samples
	•	0.9592	0.0714	0.9253	0.3682	12257651
Bangs	×	0.9566	0.0656	0.9138	0.3570	7381868
Bangs	1	0.8382	0.0891	0.9345	0.4787	384735
Bald	×	0.9618	0.0725	0.9428	0.3859	12213782
Feminine	×	0.7050	0.0725	0.7975	0.3795	25041
Blond Hair	×	0.9528	0.0703	0.9236	0.3502	4980573
Receding Hairline	×	0.9895	0.0788	0.9951	0.4399	4525040
Receding Hairline	1	0.7875	0.0408	0.8082	0.2593	101650
Brown Eyes	×	0.7970	0.0508	0.8083	0.3686	288447
Brown Eyes	1	0.9355	0.0826	0.9190	0.4154	1508420
Wearing Necktie	X	0.9687	0.0813	0.9593	0.4471	5075688
Corpulent	×	0.9740	0.0738	0.9815	0.4336	6978086
Fully Visible Forehead	×	0.9622	0.0916	0.9843	0.4557	1785040
Fully Visible Forehead	1	0.9205	0.0502	0.8641	0.3159	3741913
Black Hair	×	0.9233	0.0617	0.8884	0.3657	6613258
Black Hair	1	0.9078	0.0911	0.9486	0.4430	961940
Mouth Closed	×	0.9756	0.0714	0.9445	0.4899	814259
Wearing Hat	×	0.9398	0.0632	0.9043	0.3475	10892163
Wearing Hat	1	0.9000	0.1198	0.9724	0.5762	115686
Rugged	×	0.8543	0.0753	0.8913	0.4770	210814
Eyewear	X	0.9154	0.0609	0.9166	0.3370	9194376
Obstructed Forehead	X	0.9246	0.0580	0.8990	0.3569	7822935
Obstructed Forehead	1	0.9020	0.1194	0.9543	0.6195	116882
Pointy Nose	×	0.8917	0.0927	0.9084	0.4069	799108
Pointy Nose	1	0.8641	0.0592	0.8582	0.3830	4163088
Cheerful	×	0.9069	0.0900	0.9159	0.4831	490084
Cheerful	1	0.8891	0.0522	0.7307	0.3439	23270
Frontal Facial Hair	×	0.9697	0.0747	0.9512	0.3992	8838416
Big Lips	×	0.9241	0.0621	0.9342	0.3400	1135456
Big Lips	1	0.9399	0.0769	0.9883	0.4361	2133293
Shiny Skin	×	0.9157	0.0684	0.9562	0.4037	509064
Shiny Skin	1	0.9320	0.0606	0.9083	0.3963	593781
Bushy Eyebrows	×	0.9589	0.0740	0.9641	0.4161	5259417
Bushy Eyebrows	1	0.9207	0.0545	0.9794	0.2957	57087
Generic Facial Hair	×	0.9707	0.0793	0.9874	0.4218	1935348
Gray Hair	X	0.9718	0.0743	0.9490	0.3905	10697373
Brown Hair	X	0.9529	0.0692	0.8720	0.3616	1542963
Brown Hair	1	0.9961	0.0585	0.9632	0.4302	1714373
Round Face	X	0.9195	0.0497	0.8745	0.3136	6461864
Oval Face	X	0.8729	0.0929	0.8928	0.4030	427890
Square Face	X	0.9272	0.0795	0.9807	0.4316	1011924
Square Face	1	0.9826	0.0600	0.9809	0.3148	91328

TABLE III: **Combinations of decorrelated attributes achieving ten highest iGARBE scores** - Reported in terms of FNMR for a fixed FMR of 10^{-3} , the fairness metric iGARBE and the contextualized fairness metric CoFair. Again, the number of genuine samples indicates the scarcity of samples annotated with the given assignment combination. As the combinations found by the proposed unsupervised approach are specific per FRS, we report them separately for ArcFace and FaceNet in Tables IIIa and IIIb. To underline that the resulting combinations also have a positive impact on fairness for the respective other FRS, we report iGARBE and CoFair values for them as well.

(a) Top 10 gender-balanced (fair) attribute combinations based on ArcFace

ceding Hairline	shy Eyebrows	nd Hair	ewear	ontal Facial Hair	ay Hair	ugs	rpulent	aring Hat	aring Necktie	р	ick Hair	FNI	MR - ArcH	Face	iGA	RBE	Col	Fair	
Re	Bu	Blc	Ey	Fre	ß	Ba	C	We	We	Bal	Bl_{∂}	Male	Female	Total	ArcFace	FaceNet	ArcFace	FaceNet	Gen. Samples
٠	•	٠	•	•	•	•	•	•	•	•	•	0.0684	0.0784	0.0714	0.9592	0.9253	0.7266	0.6639	12257651
•	•	×	•	•	×	•	×	•	•	•	×	0.0594	0.0593	0.0590	0.9987	0.9664	0.9975	0.9134	1170030
•	•	•	X	•	•	•	•	•	×	X	•	0.0710	0.0714	0.0715	0.9983	0.9842	0.9968	0.9723	2882629
•	X	X	•	×	X	•	•	•	•	•	•	0.0782	0.0777	0.0781	0.9982	0.9684	0.9968	0.9219	2242832
•	•	X	•	×	•	•	•	•	•	•	X	0.0591	0.0594	0.0585	0.9979	0.9660	0.9962	0.9122	1363650
•	•	X	•	•	•	•	•	×	×	X	•	0.0721	0.0726	0.0724	0.9979	0.9665	0.9962	0.9147	2634757
×	•	•	•	•	X	X	•	•	•	×	•	0.0725	0.0719	0.0724	0.9978	0.9378	0.9955	0.7538	2114894
•	×	•	•	×	X	•	•	•	•	×	•	0.0764	0.0770	0.0775	0.9977	0.9491	0.9955	0.8267	2234224
×	•	×	•	•	•	•	•	•	•	×	•	0.0821	0.0814	0.0816	0.9976	0.9641	0.9955	0.9044	3827023
•	•	•	•	•	•	•	×	×	×	×	•	0.0699	0.0705	0.0705	0.9974	0.9798	0.9948	0.9600	2415037
•	•	٠	٠	×	•	×	×	•	•	×	•	0.0691	0.0697	0.0700	0.9974	0.9628	0.9948	0.8990	2455854

(b) Top 10 gender-balanced (fair) attribute combinations based on FaceNet

taring Hat	rpulent	ay Hair	g Lips	shy Eyebrows	ond Hair	ld	ontal Facial Hair	structed Forehead	ngs	ewear	FNI	MR - Face	eNet	iGA	RBE	Col	Fair	
We	S	Gr	Big	Bu	Ble	\mathbf{Ba}	Fre	qo	Ba	Ey	Male	Female	Total	FaceNet	ArcFace	FaceNet	ArcFace	Gen. Samples
•	•	•	•	•	•	•	•	•	•	•	0.3332	0.4268	0.3682	0.9253	0.9592	0.6639	0.7266	12345855
•	X	X	•	•	•	•	•	X	•	×	0.4092	0.4096	0.4101	0.9997	0.9764	0.9997	0.8997	2652903
X	X	X	•	•	•	•	×	•	•	•	0.4349	0.4335	0.4331	0.9991	0.9771	0.9991	0.9051	2672231
×	×	•	•	•	•	•	•	×	•	×	0.4035	0.4051	0.4049	0.9988	0.9704	0.9988	0.8450	2805567
•	•	•	•	X	•	×	×	•	•	•	0.4308	0.4318	0.4306	0.9986	0.9266	0.9988	0.4298	2892688
•	•	•	•	X	X	×	×	•	•	•	0.4353	0.4374	0.4369	0.9986	0.9782	0.9988	0.9129	2576408
•	•	X	•	X	•	×	•	•	×	•	0.4409	0.4432	0.4415	0.9985	0.9442	0.9985	0.5868	2355399
•	X	•	•	•	•	•	•	X	X	×	0.4092	0.4113	0.4102	0.9984	0.9642	0.9985	0.7822	2723159
X	•	•	X	X	•	×	•	•	•	•	0.3866	0.3889	0.3853	0.9978	0.9858	0.9978	0.9590	927385
•	×	•	•	•	•	×	•	×	•	X	0.4133	0.4098	0.4098	0.9974	0.9768	0.9975	0.9024	2555046
٠	٠	×	٠	×	٠	٠	X	٠	٠	×	0.3997	0.3960	0.3955	0.9972	0.9818	0.9972	0.9379	1522274

assignment combinations. In these cases, the average decrease in FNMR is about 10 %. Assignments involved only in such situations are to *Corpulent* and *Black Hair*. In the remaining instances, the total FNMR increases slightly, on average by about 5.5 %. The recognition errors for Male-labeled and Female-labeled samples are similar. Consequently, the inferences made above also apply for the gender-specific cases. It should only be noted that the relative improvements differ slightly due to a different baseline. The number of retained genuine samples lies within a range of around 1 170 000 and 3 820 000, reinforcing the representativeness of the presented

results.

To reason about the values of CoFair, we first need to elaborate on their calculation. As explained in Section III-A2, the purpose of CoFair is the contextualization of iGARBE fairness scores relative to the underlying distribution characteristics of the respective FRS. Therefore, we need to estimate the probability density of iGARBE scores to calculate the cumulative distribution function. To this end, we perform a kernel density estimation (KDE) with Gaussian kernels for a bandwidth estimated using Scott's rule [56]. We multiply the resulting bandwidth with an additional adjusting factor of



Fig. 3: **Fairness iGARBE distributions for both FRS** - The estimations were performed using a KDE with Gaussian kernels with a bandwidth determined using Scott's rule. These distributions are the basis for CoFair.

0.5 to prevent oversmoothing. For the estimation, we use the samples from Table II. We specifically use only those samples whose FNMR is better than or at max 10% worse than the corresponding baseline FNMR. In doing so, we specifically exclude samples with an unrepresentative performance that would therefore not contribute to an usable, realistic estimation. The resulting probability density is shown in Figure 3.

We now shift the focus on the results of CoFair for each FRS. For ArcFace, results ranging from 0.9948 to 0.9975 at a baseline of 0.7266 can be observed in this respect. Recall that a value of CoFair = 0.9948 indicates that the respective combination achieves an iGARBE fairness score that is higher than that of 99.48% of the single attributes on the same FRS. Therefore, the optimization approach works as expected. At the same time, these results are also to be expected, since the underlying iGARBE scores already approach values resembling nearly perfect fairness (i.e., iGARBE = 1). However, for the given values, results of CoFair = 1 are not reached because of the positive response of ArcFace to people with Brown Hair in terms of fairness. When inspecting the impact of the ArcFace-focussed combinations on the fairness of FaceNet, contextualizing iGARBE scores offers more insight into the effectiveness of the presented approach. The scores themselves range from 0.9378 to 0.9842 at a baseline of 0.9253. Although these improvements might seem minor at first, contextualizing enables a more comprehensive analysis. With a baseline of CoFair = 0.6639, the results range from 0.7538 to 0.9723, with 7 out of 10 values exceeding 0.9. These results underline the capability of the proposed approach in finding facial characteristics positively impacting gender fairness, ubiquitously.

FaceNet-specific results, as shown in Table IIIb, are semantically similar to those of ArcFace. Again, the found attribute cluster assignment combinations exceed the baseline fairness score of 0.9253 by far. They range from 0.9972 to 0.9997, thus approaching the perfect score of 1, as was the case for ArcFace. Most of the clustered attributes associated with these results as part of combinations were already seen and discussed in the ArcFace-focused analysis, namely all but

Big Lips and Obstructed Forehead. Consequences observed and inferences made based on them and their negative label assignments largely parallel those for ArcFace. As for the specific absence of Obstructed Forehead, it can be inferred that accessories or hairstyles occluding the forehead in particular seem to be a dictating factor in affecting recognition error differentials. Negatively labeled Big Lips also seems to play a role in fostering the gender gap. This is likely to be due to its connection to controlling the appearance of the mouthregion of the face, which therefore also appears to be vital for recognition performance. At the same time, since such an assignment only occurs in one of the top ten results, its significance is reduced compared to those to the other attributes. Again, no clear pattern emerges regarding which attributes are combined in which specific scenario. Genuine sample retention is again predominantly in the millions, ranging from about 920 000 to 2 890 000. The total FNMR also increases by approx. 17 % compared to the baseline, thereby decreasing overall recognition performance.

To better understand the iGARBE scores w.r.t. the underlying distribution characteristics, we again compute the contextualized fairness CoFair. For FaceNet, this results in values between 0.9972 and 0.9997. At a baseline of 0.6639, these outcomes reinforce the capabilities of the presented approach. Once more, these values are to be expected since our results approach perfect fairness, i.e., iGARBE scores of 1. The iGARBE scores for ArcFace in the ArcFace-optimized approach are comparable to those for FaceNet in the FaceNetfocused analysis. However, the results of CoFair for the latter are slightly higher regardless. This is due to there not being an as high-scored peak in the probability distribution as was the case for ArcFace due to the impact of Brown Hair, as can be seen in Figure 3. Shifting the attention to the performance of ArcFace on combinations created with a focus on FaceNet, the respective iGARBE scores are in between 0.9266 and 0.9858 at a baseline of 0.9592. The corresponding values of CoFair range from 0.4298 to 0.9590 at a baseline of 0.7266. 5 out of 10 combinations exceed a value of 0.9, again proving the capability of the presented approach w.r.t. unveiling facial characteristics positively affecting gender fairness in face recognition.

2) Combination Correlations: Previously, we have shown the significant advantage of analyzing combinations of decorrelated attributes to reveal the dictating factors of gender bias in face recognition compared to focusing on individual attributes. In the following, we scrutinize the single highestscoring assignment *combination* w.r.t. iGARBE per optimization target model. We focus on correlations between said combination and other attribute assignments. In doing so, new insights can be gained since combining decorrelated attributes leads to new correlations that could not have been considered during clustering. Therefore, the correlations occur based on the assignments combinations, and not directly based on the individual, decorrelated attributes. Consequently, the spectrum of possible reasons for bias can be tightened even more, solidifying this work's results.

The results of this analysis are shown in Figure 4. Assignments will be called "strongly correlated" if, in the label



Fig. 4: Relative frequency of occurrence of attribute-label pairs after filtering for attribute combination achieving highest iGARBE score - The filter-dictating combination is chosen based on Tables IIIa and IIIb for ArcFace and FaceNet, respectively. The shown distributions are computed over those annotated samples in the used database that remain after filtering. Attributes part of the filter-dictating combination are not displayed. The distributions help to understand what gender-fair data might look like.

assignment distribution, a specific label for a given attribute makes up at least 90% of total assignments for that specific attribute. The assignment combination achieving the highest iGARBE score for ArcFace in the ArcFace-optimized analysis consists of negative assignments to Blond Hair, Gray Hair, Corpulent, and Black Hair as is presented in Table IIIa. Figure 4(a) shows strong correlations of this combination with the attributes Bald and Eyeglasses, both with negative assignments. As they are also part of one or more of the remaining top nine assignment combinations⁴, they must carry significance for fairness across genders. A similar observation can also be made for FaceNet and its respective highest performing assignment combination comprising all negative assignments to Corpulent, Gray Hair, Obstructed Forehead and Eyewear as seen in Table IIIb. Said combination strongly correlates with negative assignments to Wearing Hat, Gray Hair, and Bangs. This is observable in Figure 4(b). All of the attributes named above are, again, part of the highest iGARBE scoring combinations, underlining their importance for equitable recognition performance.

VI. LIMITATIONS

This work relies on an extensive set of facial attributes commonly used in face image analysis. However, it is possible that a more refined selection of attributes could lead to a more concise description of the causing factors of gender bias. Within the MAAD-Face dataset, there can be assumed to be an unknown small amount of label noise, but we do not believe that this impacts the results of this study. The analysis presented in this work is primarily aimed at revealing the origins of supposed gender bias in face recognition. It may or may not lead to as high-quality results for investigations on age bias or race bias. It should be noted that, while poorly balanced training sets have been ruled out empirically as sources of gender bias, such imbalances in training data may create other problems.

VII. CONCLUSION

As use of FRS becomes ever more prominent in day-today activities, ensuring that FRS operate fairly is of utmost importance. Understanding the cause(s) of observed differences in accuracy across demographic groups is an essential basis for making judgements about fairness. Consequently, we conducted comprehensive investigations on the origins of the gender gap in face recognition accuracy, and the role of combinations of decorrelated non-demographic attributes in explaining this gap. To this end, several novel methodical components were presented and evaluated. They include (1) a decorrelation-by-clustering toolchain to derive more unbiased statements, (2) two fairness metrics to measure fairness with and without context, and (3) an unsupervised joint investigation framework enabling identification of attribute combinations leading to a vanishing gender gap when adjusting test datasets accordingly. This notion is reflected in the results with high confidence, leading to the following empirical observation:

Once male and female subjects share specific nondemographic attributes, the gender gap in recognition accuracy vanishes.

The above holds for all considered experimental setups using two popular face recognition models. Accordingly, we come to the following **interpretation**:

Gender bias in FRS is likely to originate from nondemographic attributes associated with gender instead of gender itself. The non-demographic attributes in question relate to the same handful of categories throughout all results. Specifically, supposed gender bias seems to depend entirely on the presence or absence of specific characteristics related to (1) *hairstyles*, (2) *facial hair*, and (3) *occluding accessories*. Forcing these attributes to be explicitly shared across gender effectuates a negligibly low error differential between the two subject groups without notably degrading system performance. Acknowledging these outcomes, which encompass a wide range of reliable empirical investigations, leads to the following **conclusion**:

Gender bias in FRS is likely no issue of biology but of the social definition of gender-specific appearance.

Overall, by providing high-confidence explanations, we have performed the groundwork for subsequent evolution of FRS to hopefully overcome this issue. This work's findings therefore illustrate multiple conceivable routes for future work to explore. To tackle the gender bias problem in practice, it may be important to focus on making FRS more robust to non-demographic attributes. If future research wants to further investigate bias mitigation strategies, they need to do so on datasets not only balanced based on gender but also balanced w.r.t. relevant categories of non-demographic attributes.

REFERENCES

- [1] M. Orcutt, "Are face recognition systems accurate? Depends on your race," *MIT Technology Review 2016*, 2016.
- [2] S. Lohr, "Facial recognition is accurate, if you're a white guy," in *Ethics of Data and Analytics*, Auerbach Publications, 2022, pp. 143–147.
- [3] T. Hoggins, "Racist and sexist'facial recognition cameras could lead to false arrests," *The Telegraph*, 2019.
- [4] D. Castelvecchi, "Is facial recognition too biased to be let loose?" *Nature*, Nov. 2020.
- [5] E. Santow, "Emerging from ai utopia," *Science*, vol. 368, no. 6486, pp. 9–9, 2020.
- [6] B. Klare, M. J. Burge, J. C. Klontz, R. W. V. Bruegge, and A. K. Jain, "Face Recognition Performance: Role of Demographic Information," *IEEE Trans. Inf. Forensics Secur.*, vol. 7, no. 6, pp. 1789–1801, 2012.
- [7] P. J. Phillips, F. Jiang, A. Narvekar, J. H. Ayyad, and A. J. O'Toole, "An other-race effect for face recognition algorithms," *ACM Trans. Appl. Percept.*, vol. 8, no. 2, 14:1–14:11, 2011.
- [8] P. Grother, M. Ngan, and K. Hanaoka, *Face Recognition* Vendor Test Part 3: Demographic Effects, 2019.
- [9] A. Bhatta, V. Albiero, K. W. Bowyer, and M. C. King, "The gender gap in face recognition accuracy is a hairy problem," in *IEEE/CVF Winter Conference on Applications of Computer Vision Workshops, WACV* 2023 - Workshops, Waikoloa, HI, USA, January 3-7, 2023, IEEE, 2023, pp. 1–10.

- [10] P. Terhörst, J. N. Kolf, M. Huber, et al., "A Comprehensive Study on Face Recognition Biases Beyond Demographics," *IEEE Transactions on Technology and Society*, vol. 3, no. 1, pp. 16–30, 2022.
- [11] P. Terhörst, M. L. Tran, N. Damer, F. Kirchbuchner, and A. Kuijper, "Comparison-Level Mitigation of Ethnic Bias in Face Recognition," in 8th International Workshop on Biometrics and Forensics, IWBF 2020, Porto, Portugal, April 29-30, 2020, IEEE, 2020, pp. 1–6.
- [12] J. W. M. Campbell, "Demographic bias in biometric systems: Current research and applicable standards," 2017.
- [13] V. Albiero, K. K. S, K. Vangara, K. Zhang, M. C. King, and K. W. Bowyer, "Analysis of Gender Inequality In Face Recognition Accuracy," in *IEEE Winter Applications of Computer Vision Workshops, WACV Workshops* 2020, Snowmass Village, CO, USA, March 1-5, 2020, IEEE, 2020, pp. 81–89.
- [14] V. Albiero, K. Zhang, and K. W. Bowyer, "How Does Gender Balance In Training Data Affect Face Recognition Accuracy?" In 2020 IEEE International Joint Conference on Biometrics, IJCB 2020, Houston, TX, USA, September 28 - October 1, 2020, IEEE, 2020, pp. 1–10.
- [15] H. Wu, G. Bezold, A. Bhatta, and K. W. Bowyer, "Logical consistency and greater descriptive power for facial hair attribute learning," in *CVPR*, IEEE, 2023, pp. 8588–8597.
- [16] H. Wu, S. Tian, A. Bahatta, K. Öztürk, K. Ricanek Jr., and K. W. Bowyer, "Facial Hair area in face recognition across demographics: Small size, big Effect," presented at the Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision Workshops, 2024.
- [17] V. Albiero, K. Zhang, M. C. King, and K. W. Bowyer, "Gendered differences in face recognition accuracy explained by hairstyles, makeup, and facial morphology," *IEEE Trans. Inf. Forensics Secur.*, vol. 17, pp. 127–137, 2022.
- [18] H. Wu, V. Albiero, K. S. Krishnapriya, M. C. King, and K. W. Bowyer, "Face recognition accuracy across demographics: Shining a light into the problem," in *CVPRW*, IEEE, 2023, pp. 1041–1050.
- [19] V. Albiero and K. W. Bowyer, "Is Face Recognition Sexist? No, Gendered Hairstyles and Biology Are," in 31st British Machine Vision Conference 2020, BMVC 2020, Virtual Event, UK, September 7-10, 2020, BMVA Press, 2020.
- [20] P. Terhörst, D. Fährmann, N. Damer, F. Kirchbuchner, and A. Kuijper, "On soft-biometric information stored in biometric face embeddings," *IEEE Trans. Biom. Behav. Identity Sci.*, vol. 3, no. 4, pp. 519–534, 2021.
- [21] P. Terhörst, D. Fährmann, N. Damer, F. Kirchbuchner, and A. Kuijper, "Beyond identity: What information is stored in biometric face templates?" In 2020 IEEE International Joint Conference on Biometrics, IJCB 2020, Houston, TX, USA, September 28 - October 1, 2020, IEEE, 2020, pp. 1–10.

- [22] P. J. Phillips, P. Grother, R. Micheals, D. M. Blackburn, E. Tabassi, and M. Bone, "Face recognition vendor test 2002," in 2003 IEEE International SOI Conference. Proceedings (Cat. No. 03CH37443), IEEE, 2003, p. 44.
- [23] P. J. Phillips, P. J. Flynn, W. T. Scruggs, et al., "Overview of the face recognition grand challenge," in 2005 IEEE Computer Society Conference on Computer Vision and Pattern Recognition (CVPR 2005), 20-26 June 2005, San Diego, CA, USA, IEEE Computer Society, 2005, pp. 947–954.
- [24] J. R. Beveridge, G. H. Givens, P. J. Phillips, and B. A. Draper, "Factors that influence algorithm performance in the face recognition grand challenge," *Comput. Vis. Image Underst.*, vol. 113, no. 6, pp. 750–762, 2009.
- [25] Y. M. Lui, D. Bolme, B. A. Draper, J. R. Beveridge, G. Givens, and P. J. Phillips, "A meta-analysis of face recognition covariates," in 2009 IEEE 3rd International Conference on Biometrics: Theory, Applications, and Systems, IEEE, 2009, pp. 1–8.
- [26] P. J. Grother, P. J. Grother, P. J. Phillips, and G. W. Quinn, *Report on the evaluation of 2D still-image face recognition algorithms*. US Department of Commerce, National Institute of Standards and Technology, 2011.
- [27] B. Klare, M. J. Burge, J. C. Klontz, R. W. V. Bruegge, and A. K. Jain, "Face recognition performance: Role of demographic information," *IEEE Trans. Inf. Forensics Secur.*, vol. 7, no. 6, pp. 1789–1801, 2012.
- [28] G. B. Huang, M. Mattar, T. Berg, and E. Learned-Miller, "Labeled faces in the wild: A database forstudying face recognition in unconstrained environments," in Workshop on faces in'Real-Life'Images: detection, alignment, and recognition, 2008.
- [29] L. Best-Rowden and A. K. Jain, "A longitudinal study of automatic face recognition," in *International Conference on Biometrics, ICB 2015, Phuket, Thailand, 19-22 May, 2015,* IEEE, 2015, pp. 214–221.
- [30] L. Best-Rowden and A. K. Jain, "Longitudinal study of automatic face recognition," *IEEE Trans. Pattern Anal. Mach. Intell.*, vol. 40, no. 1, pp. 148–162, 2018.
- [31] H. Wu and K. W. Bowyer, "What should be balanced in a "balanced" face recognition dataset?" In 34th British Machine Vision Conference 2022, BMVC 2022, Aberdeen, UK, November 20-24, 2023, BMVA Press, 2023, p. 235.
- [32] S. Ueda and T. Koyama, "Influence of make-up on facial recognition," *Perception*, vol. 39, no. 2, pp. 260–264, 2010.
- [33] A. Dantcheva, C. Chen, and A. Ross, "Can facial cosmetics affect the matching accuracy of face recognition systems?" In *IEEE Fifth International Conference on Biometrics: Theory, Applications and Systems, BTAS* 2012, Arlington, VA, USA, September 23-27, 2012, IEEE, 2012, pp. 391–398.
- [34] G. Guo, L. Wen, and S. Yan, "Face authentication with makeup changes," *IEEE Trans. Circuits Syst. Video Technol.*, vol. 24, no. 5, pp. 814–825, 2014.

- [35] K. Ozturk, G. Bezold, A. Bhatta, H. Wu, and K. W. Bowyer, "Beard segmentation and recognition bias," *CoRR*, vol. abs/2308.15740, 2023. arXiv: 2308.15740.
- [36] P. Terhörst, J. N. Kolf, N. Damer, F. Kirchbuchner, and A. Kuijper, "Post-comparison mitigation of demographic bias in face recognition using fair score normalization," *Pattern Recognit. Lett.*, vol. 140, pp. 332–338, 2020.
- [37] S. Gong, X. Liu, and A. K. Jain, "Jointly de-biasing face recognition and demographic attribute estimation," in *Computer Vision - ECCV 2020 - 16th European Conference, Glasgow, UK, August 23-28, 2020, Proceedings, Part XXIX*, A. Vedaldi, H. Bischof, T. Brox, and J. Frahm, Eds., ser. Lecture Notes in Computer Science, vol. 12374, Springer, 2020, pp. 330–347.
- [38] S. Park, S. Hwang, D. Kim, and H. Byun, "Learning disentangled representation for fair facial attribute classification via fairness-aware information alignment," in *Thirty-Fifth AAAI Conference on Artificial Intelligence*, *AAAI 2021, Thirty-Third Conference on Innovative Applications of Artificial Intelligence, IAAI 2021, The Eleventh Symposium on Educational Advances in Artificial Intelligence, EAAI 2021, Virtual Event, February 2-9, 2021*, AAAI Press, 2021, pp. 2403–2411.
- [39] P. Dhar, J. Gleason, A. Roy, C. D. Castillo, P. J. Phillips, and R. Chellappa, "Distill and de-bias: Mitigating bias in face verification using knowledge distillation," *CoRR*, vol. abs/2112.09786, 2021. arXiv: 2112.09786.
- [40] P. Dhar, J. Gleason, A. Roy, C. D. Castillo, and R. Chellappa, "PASS: protected attribute suppression system for mitigating bias in face recognition," in 2021 IEEE/CVF International Conference on Computer Vision, ICCV 2021, Montreal, QC, Canada, October 10-17, 2021, IEEE, 2021, pp. 15067–15076.
- [41] T. de Freitas Pereira and S. Marcel, "Fairness in Biometrics: A Figure of Merit to Assess Biometric Verification Systems," *IEEE Trans. Biom. Behav. Identity Sci.*, vol. 4, no. 1, pp. 19–29, 2022.
- [42] Frontex, Best Practice Technical Guidelines for Automated Border Control (ABC) Systems. Publications Office of the European Union, 2015, ISBN: 978-92-95205-43-7.
- [43] P. J. Grother, "Demographic Differentials in Face Recognition Algorithms," presented at the EAB Virtual Event Series - Demographic Fairness in Biometric Systems, 2021.
- [44] J. J. Howard, E. J. Laird, R. E. Rubin, Y. B. Sirotin, J. L. Tipton, and A. R. Vemury, "Evaluating Proposed Fairness Models for Face Recognition Algorithms," in Pattern Recognition, Computer Vision, and Image Processing. ICPR 2022 International Workshops and Challenges - Montreal, QC, Canada, August 21-25, 2022, Proceedings, Part I, Springer, 2022, pp. 431–447.
- [45] G. Deltas, "The Small-Sample Bias of the Gini Coefficient: Results and Implications for Empirical Research," *The Review of Economics and Statistics*, vol. 85, no. 1, pp. 226–234, 2003.

- [46] P. Terhörst, D. Fährmann, J. N. Kolf, N. Damer, F. Kirchbuchner, and A. Kuijper, "MAAD-Face: A Massively Annotated Attribute Dataset for Face Images," *IEEE Trans. Inf. Forensics Secur.*, vol. 16, pp. 3942– 3957, 2021.
- [47] Q. Cao, L. Shen, W. Xie, O. M. Parkhi, and A. Zisserman, "VGGFace2: A Dataset for Recognising Faces across Pose and Age," in 13th IEEE International Conference on Automatic Face & Gesture Recognition, FG 2018, Xi'an, China, May 15-19, 2018, IEEE Computer Society, 2018, pp. 67–74.
- [48] P. A. Bernstein and D. W. Chiu, "Using Semi-Joins to Solve Relational Queries," J. ACM, vol. 28, no. 1, pp. 25–40, 1981.
- [49] J. Deng, J. Guo, N. Xue, and S. Zafeiriou, "ArcFace: Additive Angular Margin Loss for Deep Face Recognition," in *IEEE Conference on Computer Vision and Pattern Recognition, CVPR 2019, Long Beach, CA, USA, June 16-20, 2019,* Computer Vision Foundation / IEEE, 2019, pp. 4690–4699.
- [50] F. Schroff, D. Kalenichenko, and J. Philbin, "FaceNet: A unified embedding for face recognition and clustering," in *IEEE Conference on Computer Vision and Pattern Recognition, CVPR 2015, Boston, MA, USA, June* 7-12, 2015, IEEE Computer Society, 2015, pp. 815– 823.
- [51] Y. Guo, L. Zhang, Y. Hu, X. He, and J. Gao, "MS-Celeb-1M: A Dataset and Benchmark for Large-Scale Face Recognition," in *Computer Vision ECCV 2016 14th European Conference, Amsterdam, The Netherlands, October 11-14, 2016, Proceedings, Part III,* ser. Lecture Notes in Computer Science, vol. 9907, Springer, 2016, pp. 87–102.
- [52] J. Guo, J. Deng, N. Xue, and S. Zafeiriou, "Stacked Dense U-Nets with Dual Transformers for Robust Face Alignment," in *British Machine Vision Conference* 2018, BMVC 2018, Newcastle, UK, September 3-6, 2018, BMVA Press, 2018, p. 44.
- [53] V. Kazemi and J. Sullivan, "One Millisecond Face Alignment with an Ensemble of Regression Trees," in 2014 IEEE Conference on Computer Vision and Pattern Recognition, CVPR 2014, Columbus, OH, USA, June 23-28, 2014, IEEE Computer Society, 2014, pp. 1867– 1874.
- [54] "Information technology Biometric performance testing and reporting — Part 1: Principles and framework (ISO/IEC 19795-1)," International Organization for Standardization, Standard, 2021.
- [55] J. J. Howard, Y. B. Sirotin, and A. R. Vemury, "The Effect of Broad and Specific Demographic Homogeneity on the Imposter Distributions and False Match Rates in Face Recognition Algorithm Performance," in 10th IEEE International Conference on Biometrics Theory, Applications and Systems, BTAS 2019, Tampa, FL, USA, September 23-26, 2019, IEEE, 2019, pp. 1–8.
- [56] D. W. Scott, Multivariate Density Estimation: Theory, Practice, and Visualization. Wiley, 1992, ISBN: 9780470316849.

Haiyu Wu is a Ph.D. student at the University of Notre Dame. He received his Master degree in Computer Engineering from University of Notre Dame, in 2024. His research interests include improving the ethical responsibility of face recognition algorithms, computer vision, and machine learning. He has received the best paper award from the Vision Dataset Understanding workshop in CVPR. He is the author of several publications in conferences and journals such as CVPR, BMVC, IJCB, IEEE TTS and regularly serve as a reviewer for CVPR, ECCV, WACV, IJCB, PRLETTERS, F&G.

Kevin W. Bowyer is the Schubmehl-Prein Family Professor of Computer Science and Engineering at the University of Notre Dame. He was elected as a Fellow of the American Academy for the Advancement of Science "for distinguished contributions to the field of computer vision and pattern recognition, biometrics, object recognition and data science", a Fellow of the IEEE "for contributions to algorithms for recognizing objects in images", and a Fellow of the IAPR "for contributions to computer vision, pattern recognition and biometrics". He has received a Technical Achievement Award from the IEEE Computer Society, and IEEE Biometrics Council's Meritorious Service Award and Leadership Award. Professor Bowyer has served as Editor-In-Chief of the IEEE Transactions on Biometrics, Behavior, and Identity Science and the IEEE Transactions on Pattern Analysis and Machine Intelligence, and as General Chair or Program Chair of conferences such as Computer Vision and Pattern Recognition, Winter Conference on Applications of Computer Vision, and the International Joint Conference on Biometrics.

Philipp Terhörst is a research group leader at Paderborn University working on "Responsible AI for Biometrics". He received his Ph.D. in computer science in 2021 from the Technical University of Darmstadt for his work on "Mitigating Soft-Biometric Driven Bias and Privacy Concerns in Face Recognition Systems" and worked at the Fraunhofer IGD from 2017 to 2022. He was also an ERCIM fellow at the Norwegian University of Science and Technology funded by the European Research Consortium for Informatics and Mathematics. His interest lies in responsible machine learning algorithms in the context of biometrics. This includes the topics of fairness, privacy, explainability, uncertainty, and confidence. Dr. Terhörst is the author of several publications in conferences and journals such as CVPR and IEEE TIFS and regularly works as a reviewer for e.g. TPAMI, TIP, Nature Medicine, PR, BTAS, ICB. For his scientific work, he received several awards such as from the European Association for Biometrics, Fraunhofer ICT, or the International Joint Conference for Biometrics. He furthermore participated in the 'Software Campus' Program, a management program of the German Federal Ministry of Education and Research (BMBF).