# The regret lower bound for communicating Markov Decision Processes

Victor Boone † victor.boone@inria.fr

Odalric-Ambrym Maillard ‡ odalric.maillard@inria.fr

†Univ. Grenoble Alpes, Inria, CNRS, Grenoble INP, LIG, 38000 Grenoble, France. ‡Univ. Lille, Inria, CNRS, Centrale Lille, UMR 9189 – CRIStAL, F-59000, Lille, France

#### Abstract

This paper is devoted to the extension of the regret lower bound beyond ergodic Markov decision processes (MDPs) in the problem dependent setting. While the regret lower bound for ergodic MDPs is well-known and reached by tractable algorithms, we prove that the regret lower bound becomes significatively more complex in communicating MDPs. Our lower bound revisits the necessary explorative behavior of consistent learning agents and further explains that *all* optimal regions of the environment must be overvisited compared to sub-optimal ones, a phenomenon that we refer to as co-exploration. In tandem, we show that these two explorative and co-explorative behaviors are intertwined with navigation constraints obtained by scrutinizing the navigation structure at logarithmic scale. The resulting lower bound is expressed as the solution of an optimization problem that, in many standard classes of MDPs, can be specialized to recover existing results. From a computational perspective, it is provably  $\Sigma_2^P$ -hard in general and as a matter of fact, even testing the membership to the feasible region is coNP-hard. We further provide an algorithm to approximate the lower bound in a constructive way.

Keywords: Markov Decision Processes, Regret minimization, Lower bounds, Average reward, Instance dependent.

## <span id="page-0-0"></span>1 Introduction

This paper considers the problem of regret minimization in discrete Markov decision processes under the average reward objective with the standard communicating assumption. We more specifically focus on the derivation of the instance dependent regret lower bound, that characterizes the performance frontier of what learning algorithms can achieve within the regret minimization framework.

Regret minimization in MDPs. Indeed, to quantify the learning performance of a learning agent, a popular approach is to compare the amount of reward that the learning agent and an ominous agent that knows everything in advance are able to collect with the same time budget. The di fference between the cumulative rewards that the two gather is known as the regret; the smaller the regret, the more efficient the learner. The challenging task of designing learners with theoretical and practical regret guarantees has a long history, that goes back to multi-armed bandits. In this work, we follow the path of [Lai and Robbins](#page-36-0) [\(1985](#page-36-0)) by focusing on the **model dependent** setting: Given a Markov decision process, what is the best regret that a learner may hope to achieve? It happens that this question is only interesting when the focus is restricted to consistent learners, that, roughly speaking, have an asymptotically small regret for every environment in a given class of Markov decision processes. The seminal paper of [Lai and Robbins](#page-36-0) [\(1985\)](#page-36-0) emerges as the first model dependent regret lower bound

for multi-armed bandits: for M a bandit, A a consistent learner and *T* a number of learning steps, the expected regret of  $A$  when running on M for *T* steps, denoted  $Reg(T; M, A)$ , is lower-bounded as

$$
Reg(T; M, A) \ge K(M) \log(T) + o(\log(T)),
$$
\n(1)

where  $K(M)$  is a known and tractable constant. [Lai and Robbins](#page-36-0) [\(1985\)](#page-36-0) also show that their bound is tight, by providing a family of consistent learners that achieve the above lower bound. Such learners are said asymptotically optimal. In the more general setting of Markov decision processes, the lower bound of [Lai and Robbins](#page-36-0) [\(1985\)](#page-36-0) has been generalized in various directions. However, most of the literature seems to plateau at ergodic environments [Agrawal et al.](#page-34-0) [\(1988b](#page-34-0)); [Burnetas and Katehakis](#page-35-0) [\(1997](#page-35-0)); [Graves and Lai](#page-36-1) [\(1997](#page-36-1)), with very few exceptions such as [Tranos and Proutiere](#page-37-0) [\(2021\)](#page-37-0). Overall, the question of obtaining a tight regret lower bound for general communicating Markov decision processes was left open for decades.

Contribution. This article bridges this gap by deriving the regret lower bound *K*(M) for communicating Markov decision processes. As our first contribution, we unravel the delicate structure of the general regret lower bound by describing it as the solution of an optimization problem that conjugates *three* complementary behaviors: (1) consistent learners have to gather information on suboptimal regions (known as mandatory exploration, or information constraints); (2) they need to saturate the amount of information gathered on *all* optimal regions (mandatory co-exploration); (3) the two previous behaviors must be achieved while preserving a second order structural constraint in the way navigate their environment (second order navigation constraints). Second, we show that the solution of this optimization problem is computationally hard in general by reducing it to a Knapsack problem. Third, we present multiple specification of the lower bound in several illustrative cases of interest, including classical ones and highlighting key simplifications. Lastly, we present a constructive algorithm to approximate these bounds, offering both practical utility and further insight in the lower bound. Because of its delicacy, this paper is entirely dedicated to the lower bound and discusses it exhaustively. The construction of an explicit algorithm that matches our lower bound is deliberately postponed to future work.

Previous work on regret lower bounds. The lower bound for ergodic MDPs can be traced back to [Agrawal et al.](#page-34-0) [\(1988b\)](#page-34-0) that generalize the lower bound and the asymptotically optimal algorithm of [Lai and Robbins](#page-36-0) [\(1985](#page-36-0)) to ergodic MDPs. The approach of [Agrawal et al.](#page-34-0) [\(1988b](#page-34-0)) is policy-wise and every policy is treated as an arm, each explored in turn until regeneration; Thus their approach is heavily relying on the ergodic nature of the environment and is suffering from a tremendous burn-in phase, due to the immensely large number of policies. [Burnetas and Katehakis](#page-35-0) [\(1997\)](#page-35-0) circumvent this issue by decomposing the lower bound relatively to state-action pairs and provide a pair-wisely indexed learning algorithm that is asymptotically optimal. Specifically, instead of playing policies in a round robin fashion like [Agrawal et al.](#page-34-0) [\(1988b\)](#page-34-0), the algorithm of [Burnetas and Katehakis](#page-35-0) [\(1997\)](#page-35-0) associates an index to every playable action and play the actions with the highest index. Their solution was recently improved and mixed to more modern bandit methods, for instance [Pirutinsky](#page-37-1) [\(2020](#page-37-1)) with DMED of [Honda and Takemura](#page-36-2) [\(2010\)](#page-36-2) or [Pesquerel and Maillard](#page-37-2) [\(2022](#page-37-2)) with IMED of [Honda and Takemura](#page-36-3) [\(2015](#page-36-3)). In parallel, [Graves and Lai](#page-36-1) [\(1997\)](#page-36-1) generalize [Lai and Robbins](#page-36-0) [\(1985\)](#page-36-0) to MDPs with compact state-action spaces but stick to the ergodic assumption. We have to wait for [Ok et al.](#page-36-4) [\(2018\)](#page-36-4) to find lower bounds again, generalizing [Burnetas and Katehakis](#page-35-0) [\(1997](#page-35-0)) but still keeping the ergodic assumption. The first paper to ever escape the world of ergodic MDPs is [Tranos and Proutiere](#page-37-0) [\(2021\)](#page-37-0), that provides a regret lower bound for the very specific setting of deterministic transition MDPs together with algorithms that are asymptotically optimal in a few cases. To the best of our knowledge, general communicating Markov decision processes remained unsolved ever since.

Related work on regret minimization. Our paper lives in the neighborhood of a large literature of algorithms with theoretical regret guarantees for average reward Markov decision processes. These works do not aim, however, at specifically matching the instance dependent regret lower bound. In the setting of average-reward regret minimization, model-based methods include optimistic approaches [Auer et al.](#page-35-1) [\(2009\)](#page-35-1); [Bartlett and Tewari](#page-35-2) [\(2012\)](#page-35-2); [Filippi et al.](#page-35-3) [\(2010](#page-35-3)); [Talebi and Maillard](#page-37-3) [\(2018](#page-37-3)); [Fruit et al.](#page-35-4) [\(2018\)](#page-35-4); [Zhang and Ji](#page-38-0) [\(2019\)](#page-38-0); [Bourel et al.](#page-35-5) [\(2020\)](#page-35-5); [Boone and Zhang](#page-35-6) [\(2024\)](#page-35-6), in-spired from the popular Upper Confidence Bound (UCB) strategy [Auer](#page-35-7) [\(2002\)](#page-35-7) and variants Cappé et al. [\(2013](#page-35-8)); Bayesian approaches [Osband et al.](#page-37-4) [\(2013](#page-37-4)); [Ouyang et al.](#page-37-5) [\(2017\)](#page-37-5); [Agrawal and Jia](#page-35-9) [\(2023](#page-35-9)) derived from posterior sampling [Thompson](#page-37-6) [\(1933](#page-37-6)); Information-theoretic methods [Saber et al.](#page-37-7) [\(2024](#page-37-7)); [Pesquerel and Maillard](#page-37-2) [\(2022\)](#page-37-2) derived from [Honda and Takemura](#page-36-3) [\(2015\)](#page-36-3) or [Agrawal and Teneketzis](#page-34-1) [\(1989](#page-34-1)); Regret minimization has also been considered in model-free methods [Zhang and Xie](#page-38-1) [\(2023](#page-38-1)) and references therein, based on Q-learning [Watkins and Dayan](#page-38-2) [\(1992\)](#page-38-2), or extended e.g. to smooth continuous MDPs [Lakshmanan et al.](#page-36-5) [\(2015\)](#page-36-5); [Qian et al.](#page-37-8) [\(2019](#page-37-8)). Quite often, these works actually aim at reaching the celebrated minimax (or model independent) regret lower bound of [Auer et al.](#page-35-1) [\(2009](#page-35-1)) although many of the above mentioned are also provided with model dependent guarantees of order O(log(*T*)) such as [Auer and Ortner](#page-35-10) [\(2006\)](#page-35-10); [Auer et al.](#page-35-1) [\(2009\)](#page-35-1); [Filippi et al.](#page-35-3) [\(2010](#page-35-3)); [Pesquerel and Maillard](#page-37-2) [\(2022](#page-37-2)); [Saber et al.](#page-37-7) [\(2024\)](#page-37-7). Yet, none are proven to be asymptotically optimal in the general setup.

Outline of the paper. The paper begins with the exposition of general background on Markov decision processes, reinforcement learning and regret minimization in [Section 2.](#page-4-0) [Section 3](#page-6-0) serves as an informal and reader-friendly introduction to the main ideas and concepts behind our main result, the regret lower bound of [Theorem 3.](#page-9-0) [Section 4](#page-9-1) is entirely dedicated to proving the lower bound. In [Section 4.1,](#page-10-0) we quantify the necessary explorative behavior of consistent learners, showing that sub-optimal regions are explored logarithmically often. We introduce and detail the concept of coexploration in [Section 4.2,](#page-12-0) where consistent learners are shown to inevitably visit *all* optimal regions of their environment over-logarithmically. In [Section 4.3,](#page-14-0) we describe the navigation structure of how consistent learners may wander in their environment, showing that what matters is found at higher order (i.e.,  $log(T)$ ) rather than first order (i.e., *T*). We rely on the novel notion of **minors**, introduced in [Section 3.2](#page-8-0) and formalized in [Section 4.3.1.](#page-15-0) Everything is combined together in [Section 4.4](#page-18-0) for an intermediate regret lower bound, then adapted in [Section 4.5](#page-18-1) into a simpler and final bound. In [Section 5,](#page-20-0) we prove that the regret lower bound is computationally hard in general. As a matter of fact, even the related information tests are provably NP-hard, see [Section 5.1.](#page-20-1) In [Section 6,](#page-23-0) we discuss many examples while drawing links with the existing literature. Our bound covers multi-armed bandits [\(Section 6.1\)](#page-23-1), ergodic and recurrent Markov decision processes [\(Section 6.2\)](#page-24-0) that are shown to be special instances of the new class of optimally recurrent models [\(Definition 9\)](#page-24-1), bandits with switching costs [\(Section 6.3\)](#page-25-0) as well as fixed kernel spaces [\(Section 6.4\)](#page-26-0) with deterministic kernel spaces as special cases. We make our last stop at a policy-wise decomposition of the regret lower bound in [Section 6.5.](#page-28-0) In our final [Section 7,](#page-29-0) we discuss a special case of MDPs for which the optimality of optimal policies can be broken with only a few local modifications of the original model [\(Section 7.1\)](#page-29-1). In this scenario, which extends constructions of the ergodic setting, the regret lower bound can be approximated using an algorithmic scheme [\(Section 7.2\)](#page-31-0).

## **Contents**







## <span id="page-4-0"></span>2 Preliminaries: Formal setup and notations

**General notations.** For each  $k \in \mathbb{N}$ , [k] denotes the set  $\{1, \ldots, k\}$ . For a topological space  $(S, \mathcal{T})$ ,  $P(S)$  denotes the set of Borel probability measures on S. Provided that S, X are discrete, a kernel  $\mathbf{p}: \mathcal{X} \to \mathcal{P}(\mathcal{S})$  is seen as a stochastic operator acting on functions  $f: \mathcal{S} \to \mathbb{R}$ . Following folklore notations,  $p(s|x)$  denotes the mass of  $p(x)$  at point *s*. We further use operator notation  $p f$  to denote  $x \mapsto (\mathbf{p}f)(x) = \sum_{s \in \mathcal{S}} \mathbf{p}(s|x) f(s)$ . Given a probability distribution  $\mathbf{q} \in \mathcal{P}(\mathcal{S})$ , we denote  $\mathbb{E}_{\mathbf{q}}[f]$  or sometimes  $\langle \mathbf{q}, f \rangle$  the expected value of *f* under **q**. We denote KL(p||p') the Kullback-Laibler divergence between **p** and **p**'. For  $u \in \mathbb{R}_+^n$  a non-negative vector, we write dmin(*u*) := min{*u<sub>i</sub>* : *u<sub>i</sub>* > 0} its definite minimum, which is its smallest positive entry.

For reference and reader-friendliness, an index of notations is provided in Appendix.

#### <span id="page-4-1"></span>2.1 Markov decision processes in average reward

A Markov decision process (MDP)  $M \equiv (S, \mathcal{A}, p, r)$  consists in a four-tuple formed by a finite set of states S, finite sets of actions indexed by states  $\mathcal{A} \equiv (\mathcal{A}(s))_{s \in S}$ , together forming the pair space  $X := \bigcup_{s \in S} \{s\} \times \mathcal{A}(s);$   $\mathbf{p} : X \to \mathcal{P}(S)$  is the transition kernel; and  $\mathbf{r} : X \to \mathcal{P}(\mathbb{R})$  is the reward **function.** We denote  $\mathbf{m} : \mathcal{X} \to \mathbb{R}$  the mean reward vector, i.e.,  $\mathbf{m}(x)$  is the mean of  $\mathbf{r}(x)$  for each  $x \in \mathcal{X}$ .

Managing a Markov decision process M by picking dynamically actions generates a trajectory in discrete time as follows: At time  $t \ge 1$  from the current state  $S_t$ , playing an action  $A_t$  chosen respective to the past of the trajectory makes the system switch to the new state  $S_{t+1} \sim p(S_t, A_t)$  and produce a reward  $R_t \sim \mathbf{r}(S_t, A_t)$  independently of the past. For short,  $X_t \equiv (S_t, A_t)$  denotes the current pair.

In the average reward setting, the controlling agent aims at picking actions to maximize the average of all produced rewards  $R_1, \ldots, R_T$  when *T* goes to infinity.

**Stationary policies.** A **stationary policy**, or **policy**, is a map  $\pi : S \to \mathcal{P}(\mathcal{A})$ . Its set is denoted  $\Pi^{SR}$ . Every policy  $\pi$  induces a Markov reward process on S by acting on M, of which the transition kernel is denoted  $\mathbf{p}_{\pi}(s) := \sum_{a \in \mathcal{A}(s)} \pi(a|s) \mathbf{p}(s, a)$  and the mean reward function  $\mathbf{m}_{\pi}(s) := \sum_{a \in \mathcal{A}(s)} \pi(a|s) \mathbf{m}(s, a)$ . The associated probability and expectation operators induced by iterating  $\pi$  on **M** starting from  $s_0 \in$  $S_0$  are respectively  $\mathbb{P}_{s_0}^{\mathbf{M}, \pi}(-)$  and  $\mathbb{E}_{s_0}^{\mathbf{M}, \pi}(-]$ . It is well-known [\(Puterman](#page-37-9), [2014,](#page-37-9) Chapters 8,9) that every policy  $\pi \in \Pi^{\text{SR}}$  has well-defined **gain** and **bias** functions,  $\mathbf{g}_{\pi}$  and  $\mathbf{b}_{\pi}$ , given by:

$$
\mathbf{g}_{\pi}(s_0; \mathbf{M}) := \lim_{T \to \infty} \frac{1}{T} \mathbb{E}_{s_0}^{\mathbf{M}, \pi} \Bigg[ \sum_{t=1}^T R_t \Bigg] = \lim_{T \to \infty} \Bigg( \frac{1}{T} \sum_{t=1}^T \mathbf{p}_{\pi}^{t-1} \mathbf{m}_{\pi} \Bigg) (s_0);
$$
  

$$
\mathbf{b}_{\pi}(s_0; \mathbf{M}) := \lim_{T \to \infty} \mathbb{E}_{s_0}^{\mathbf{M}, \pi} \Bigg[ \sum_{t=1}^T (R_t - \mathbf{g}_{\pi}(S_t; \mathbf{M})) \Bigg] = \lim_{T \to \infty} \Bigg( \sum_{t=1}^T \mathbf{p}_{\pi}^{t-1} (\mathbf{m}_{\pi} - \mathbf{g}_{\pi}) \Bigg) (s_0)
$$

where Clim denotes the Cesàro-limit. A policy  $\pi$  is said **ergodic, recurrent** or **unichain** if the Markov chain of kernel  $\mathbf{p}_{\pi}$  is respectively ergodic, recurrent or unichain, see [Levin and Peres](#page-36-6) [\(2017](#page-36-6)); [Puterman](#page-37-9) [\(2014](#page-37-9)). A state  $s \in S$  is recurrent under a policy  $\pi$  if it is visited infinitely often starting from itself, i.e.,  $\mathbb{P}_{s}^{\mathbf{M},\pi}$  { $\forall n, \exists m \geq n : S_m = s$ } = 1; or equivalently, if its return time has bounded expectation with  $\mathbb{E}_{s}^{M,\pi}[\inf\{t \geq 2 : S_t = s\}] < \infty$ . Likewise, a pair  $x \equiv (s, a) \in \mathcal{X}$  is said recurrent under  $\pi$  if it satisfies  $\mathbb{P}_{s}^{\mathbf{M}, \pi} \{ \forall n, \exists m \geq n : X_m = x \} = 1$ . We write  $\mathcal{S}_{\pi}^{\star}(\mathbf{M})$  and  $\mathcal{X}_{\pi}^{\star}(\mathbf{M})$  the recurrent states and pairs of a policy.

V. Boone & OA. Maillard 5 January 23, 2025

In the remaining of our work, we make an important structural assumption on MDPs.

#### Assumption 1. All considered MDPs are *communicating*, i.e., every  $M \in \mathcal{M}$  has finite diameter:

$$
D(\mathbf{M}) := \max_{s \neq s'} \min_{\pi \in \Pi} \mathbb{E}_s^{\mathbf{M}, \pi}[\inf\{t \geq 1 : S_t = s'\}] < \infty.
$$
 (2)

Equivalently, a Markov decision process is communicating if every fully supported policy is recurrent, i.e., every policy satisfying  $\pi(a|s) > 0$  for all  $(s, a) \in X$  is recurrent.

Optimal play and Bellman equations. The optimal gain  $g_{\star}(M)$  and bias  $b_{\star}(M)$  of M are given by:

$$
\mathbf{g}_{\star}(s_0;\mathbf{M}) := \max_{\pi \in \Pi^{\text{SR}}} \mathbf{g}_{\pi}(s_0;\mathbf{M}) \quad \text{and} \quad \mathbf{b}_{\star}(s_0;\mathbf{M}) := \max_{\pi \in \Pi^{\star}(\mathbf{M})} \mathbf{b}_{\pi}(s_0;\mathbf{M}),
$$

and every policy achieving the maximum is said **gain optimal**, written  $\pi \in \Pi^*(M)$ . When M is communicating, the optimal gain function does not depend on  $s_0$  and we will sometimes write  $g_*(M)$ instead of  $g_{\star}(s_0; M)$ . A gain optimal policy of which the bias reaches  $b_{\star}(s_0; M)$  from every initial state is further said bias optimal.

At the interplay of gain and bias optimalities stand the famous Bellman optimality equations:

<span id="page-5-1"></span>
$$
\forall s \in \mathcal{S}, \quad \mathbf{g}_{\star}(s; \mathbf{M}) + \mathbf{b}_{\star}(s; \mathbf{M}) = \max_{a \in \mathcal{A}(s)} \{ \mathbf{m}(s, a) + \mathbf{p}(s, a) \mathbf{b}_{\star}(\mathbf{M}) \}
$$
(3)

that can also be written as  $\mathbf{g}_{\star}(\mathbf{M}) + \mathbf{b}_{\star}(\mathbf{M}) = \max_{\pi \in \Pi^{SR}} \{\mathbf{m}_{\pi} + \mathbf{p}_{\pi} \mathbf{b}_{\star}(\mathbf{M})\}$ . Every bias optimal policy satisfies the Bellman equations; Every policy satisfying the Bellman equations is gain optimal; Both reverse statements are wrong in general. We introduce the **Bellman gaps**  $\Delta_{\star}(s, a; \mathbf{M}) := \mathbf{g}_{\star}(s; \mathbf{M}) +$  **The Bellman equations equivalently rewrite as**  $\Delta_{*}(M) \geq 0$ **.** 

#### <span id="page-5-0"></span>2.2 Reinforcement learning and regret

A learning agent, or learner, is formally a measurable map  $A : H \to P(H)$ , associating histories  $H_t \equiv (S_1, A_1, R_1, \ldots, S_t) \in \mathcal{H}$  to probabilities over actions. Given a MDP **M** and an initial state  $s_0$ , a choice of learner completely determines the law of  $A_t \in \mathcal{A}(S_t)$  conditioned on  $H_t$  for all  $t \geq 1$ , hence of  $S_t$  and  $R_t$  as well. We write  $\mathbb{P}^{\mathbf{M},\mathbb{A}}_{s_0}$  $_{s_0}^{\mathbf{M},\mathbb{A}}$ {-} and  $\mathbb{E}_{s_0}^{\mathbf{M},\mathbb{A}}$  $S_{\rm SO}^{\rm M, A}$ [-] the associated probability and expectation operators.

A common benchmark to evaluate the performance of a learning agent is the regret, that compares the amount of reward that the learning agent gathers to the amount of reward that an *ominous* agent, that knows everything in advance and plays accordingly, is able to score within the same time budget. The standard theory of Markov decision processes with average rewards [Puterman](#page-37-9) [\(2014](#page-37-9)) explains that  $R_1 + ... + R_T$  is equal to  $Tg_{\star}(M) + O(1)$  in expectation, when actions are picked optimally with respect to time, the initial state  $s_0 \in S$  and M. Following this observation, the regret compares the optimal score proxy  $T\mathbf{g}_\star(s_0; \mathbf{M})$  to what the learning agent actually collects, i.e.,  $R_1 + \ldots + R_T$ .

Definition 1 (Regret, [Auer et al.](#page-35-1) [\(2009](#page-35-1))). *The expected regret of a learning agent* A *in* M *at horizon T* ∈ *N and from the initial state*  $s_0$  ∈ *S is given by:* 

$$
\operatorname{Reg}(T; \mathbb{A}, \mathbf{M}, s_0) := \mathbb{E}_{s_0}^{\mathbf{M}, \mathbb{A}} \bigg[ T \mathbf{g}_{\star}(\mathbf{M}) - \sum_{t=1}^T R_t \bigg]
$$
(4)

The smaller the regret, the better the learning agent. In particular, there is convergence to optimal play if, and only if the regret grows sublinearly.

The quantity  $T\mathbf{g}_\star(\mathbf{M}) - \sum_{t=1}^T R_t$ , although easy to interpret, is a bit inconvenient because it is subject to various noises over which no learner has any control on. The so-called noise includes the stochasticity on observed rewards (i.e.,  $R_t$  versus  $m(X_t)$ ) as well as the stochasticity on state transitions (i.e.,  $S_{t+1}$  versus  $p(X_t)$ ). Several variants of **pseudo-regret** exist in the literature to circumvent this inconvenience, easing the empirical study and providing finer insight into a learner's quality of play.<sup>[1](#page-6-2)</sup> In this work, we use  $\sum_{t=1}^{T} \Delta_{\star}(X_t)$ , as motivated by [Proposition 1.](#page-6-3)

<span id="page-6-3"></span>**Proposition 1.** *For every communicating model* **M**, *learner* A *and initial state*  $s_0 \in S$ *, we have:* 

$$
\left| \text{Reg}(T; \mathbb{A}, \mathbf{M}, s_0) - \mathbb{E}_{s_0}^{\mathbf{M}, \mathbb{A}} \left[ \sum_{t=1}^T \Delta_{\star}(X_t) \right] \right| \le \text{sp}(\mathbf{b}_{\star}(\mathbf{M})) \tag{5}
$$

*where*  $sp(b_{\star}(M)) = max(b_{\star}(M)) - min(b_{\star}(M))$  *is the span of the optimal bias function.* 

*Proof.* Use that  $\mathbb{E}_{s_0}^{\mathbf{M}, A}$  $\mathbf{g}_{s_0}^{\mathbf{M},\mathbb{A}}[\mathbf{g}_{\star}(\mathbf{M}) - R_t | H_t] = \mathbb{E}_{s_0}^{\mathbf{M},\mathbb{A}}$  ${}_{s_0}^{\mathbf{M},\mathbb{A}}[\mathbf{\Delta}_{\star}(X_t) + \mathbf{b}_{\star}(S_t) - \mathbf{b}_{\star}(S_{t+1})|H_t]$  and sum over  $t \leq T$ .  $\Box$ 

Although the optimal policy depends on  $M$ , a learning agent  $A$  is only properly learning if there is convergence to optimal play *regardless* of M, that remains hidden. Instead, a learning algorithm is tuned to work for a class M of Markov decision processes and therefore is a function of that class. The class  $M$  is viewed as the assumptions that the learning agent makes on the hidden environment. Claiming that the learner eventually converges to optimal play for every  $M \in \mathcal{M}$  is informally referred to as consistency, and can be stated at various degrees of strength. For log(*T*)-rate lower bounds to be even possible, we make the strong consistency assumption of [Lai and Robbins](#page-36-0) [\(1985](#page-36-0)), also known as uniformly fast convergence [Burnetas and Katehakis](#page-35-11) [\(1996](#page-35-11)); [Garivier et al.](#page-36-7) [\(2018](#page-36-7)); [Agrawal et al.](#page-34-0) [\(1988b](#page-34-0)) or even simply consistency Lattimore and Szepesvári [\(2020\)](#page-36-8) in the literature. This assumption can hardly be weakened without degrading the lower bound, see [Salomon et al.](#page-37-10) [\(2013\)](#page-37-10).

<span id="page-6-4"></span>Definition 2 (Consistency). *A learning agent* A *is said consistent on a space of Markov decision processes*  $M$  *if for all*  $\eta > 0$ *, all*  $M \in M$  *and*  $s_0 \in S$ *,*  $Reg(T; A, M, s_0) = o(T^{\eta})$ *.* 

Note that this consistency assumption is more concisely written  $log(Reg(T; A, M, s_0)) = o(log(T))$ .

## <span id="page-6-0"></span>3 Main ideas and concepts behind the lower bound

We start by providing some general intuition on our regret lower bound and what are the main concepts behind our general regret lower bound.

### <span id="page-6-1"></span>3.1 Exploration: Consistent learners must fetch information

Consider running a consistent learning agent A. On both of the environments M and  $M^{\dagger}$  displayed in [Figure 1,](#page-7-0) such a learning algorithm is supposed to converge to optimal play; Specifically, it must eventually discover how to drive and navigate the environment in order to collect as much reward as possible and its efficiency is measured by  $Reg(T; A, M, s_0)$ . Every regret lower bound essentially says that, provided that an algorithm is consistent, it cannot learn too fast. Accordingly, that every of such algorithm has some mandatory behavior.

Looking at M in more detail, it is made of two circles of length five; the outer and the inner circle, scoring 1 and 2 in average respectively. Especially, every consistent learner should quickly discover that the inner circle is the best. However, such a learner can only prioritize playing this inner optimal circle up to a limited extent. To understand why this is exactly the case, we consider the alternative model  $M^{\dagger}$ . On  $M^{\dagger}$ , the inner circle (in red) is a copy of the one of M. In particular, M and

<span id="page-6-2"></span><sup>&</sup>lt;sup>1</sup>There is no universally recognized definition of what a pseudo-regret actually is. In this work, we mean **pseudo-regret** for any quantity of the form  $\sum_{t=1}^{T} C_t$  with  $C_t$  a  $\sigma(H_t, A_t)$ -measurable quantity and  $\mathbb{E}_{s_0}^{\mathbf{M}, A}[\sum_{t=1}^{T} C_t] = \text{Reg}(T; A, \mathbf{M}, s_0) + O(1)$ .



<span id="page-7-0"></span>Figure 1: Two 10 state Markov decision processes M and  $M^{\dagger}$  with deterministic transitions. Every arrow is a choice of action that leads to the same pointed state with probability one and with reward  $N(x, 1)$  where  $x \in \{0, 1, 2\}$  is the label of the arrow.

 $M^{\dagger}$  are indistinguishable if one only observes what happens on the red circle. However, on  $M^{\dagger}$ , the average reward on the outer circle is increased to 2.1, so that the outer circle is actually better than the inner one. This means that on  $M^{\dagger}$ , efficient learners should spend most of their time on the outer circle instead. Yet, if on  $M$  a learner spends too little time on the outer circle, then there are decent chances that when playing on  $M^{\dagger}$ , the empirically observed average reward of the outer circle is close to 1 (because rewards are random), hence this learner is equally likely to mistake  $M^{\dagger}$  for M, and to commit to the red inner circle that is actually suboptimal in  $M^{\dagger}$ . Overall, on M, and because the learner is able to learn  $M^{\dagger}$  correctly, the outer circle cannot be too little explored because the learner must **gather information** in order to reject the plausibility that the actual environment is  $M^{\dagger}$  rather than M.

This idea goes back to [Lai and Robbins](#page-36-0) [\(1985](#page-36-0)) in multi-armed bandits: Consistent learners must, on M, fetch information in order to reject environments such as  $M^{\dagger}$ . Such environments are somehow indistinguishable from M if one only plays optimal actions of M yet optimal actions of M are not guaranteed to be optimal anymore; They are called **confusing models**. More precisely, **M** and  $M^{\dagger}$ are indistinguishable in that they are identical at every pair  $x \in X$  such that there exists an optimal policy  $\pi \in \Pi^*(M)$  under which *x* is recurrent, i.e.,  $x \in \mathcal{X}^*(M)$ . Such pairs are said **optimal**, written  $x \in \mathcal{X}_{\star}(\mathbf{M})$ , and the first requirement for a confusing model is that  $\mathbf{M}^{\dagger}(x) = \mathbf{M}(x)$  for all  $x \in \mathcal{X}_{\star}(\mathbf{M})$ . Following this intuition, pairs are classified as follows.

Definition 3 (Classification of pairs). *The pairs of a Markov decision process* M *are split as follows:*

(*Optimal pairs*) 
$$
X_{\star}(\mathbf{M}) := \bigcup \{X_{\pi}^{\star}(\mathbf{M}) : \pi \in \Pi^{\star}(\mathbf{M})\};
$$
  
\n(*Weakly optimal pairs*)  $X_{\star}(\mathbf{M}) := \{x \in X : \Delta_{\star}(x; \mathbf{M}) = 0\};$   
\n(*Suboptimal pairs*)  $X_{-}(\mathbf{M}) := X \setminus X_{\star}(\mathbf{M})$ .

The key differences between optimal and weakly optimal pairs, and their different roles regarding the description of a consistent learner's behavior, will be discussed when time comes, see [Section 4.2.](#page-12-0) For now, we will stick to the observation that optimal pairs are indeed weakly optimal [\(Lemma 2\)](#page-7-1).

<span id="page-7-1"></span>**Lemma 2.** Assuming **M** is communicating, we have the inclusion  $X_*(\mathbf{M}) \subseteq X_{\mathcal{X}}(\mathbf{M})$ .

*Proof.* Let  $x \equiv (s, a) \in \mathcal{X}_{\star}(\mathbf{M})$ . We have  $x \in \mathcal{X}_{\pi}^{\star}(\mathbf{M})$  for some  $\pi \in \Pi^{\star}(\mathbf{M})$ . Starting from *s* and upon iterating  $\pi$ , *x* is visited infinitely many times, so because the number of states is finite,  $\mathbb{E}_s^{M,\pi}[\sum_{t=1}^T \mathbb{1}(X_t =$  $[x(x)] = \Omega(T)$ . Combined with [Proposition 1,](#page-6-3) we deduce that Reg(*T*;  $\pi$ , **M**,  $s$ ) =  $\Omega(\Delta_{\star}(x; \mathbf{M})T)$ . Since  $\pi \in \Pi^*(M)$ , we have  $\text{Reg}(T; \pi, M, s) = o(T)$  hence necessarily  $\Lambda_\star(x; M) = 0$ , i.e.,  $x \in \mathcal{X}_\star(M)$ .  $\Box$ 

V. Boone & OA. Maillard 8 January 23, 2025

<span id="page-8-1"></span>The second requirement for a confusing model  $M^{\dagger}$  is that  $\Pi^{\star}(M^{\dagger}) \cap \Pi^{\star}(M) = \emptyset$ .

**Definition 4** (Confusing models). *Fix*  $M \in M$ . *The confusing set of*  $M$  *is given by:* 

 $\mathrm{Cnf}_\star(\mathbf{M}) := \left\{ \mathbf{M}^\dagger \in \mathcal{M} : \mathbf{M}^\dagger \gg \mathbf{M} \text{ and } \mathbf{M}^\dagger = \mathbf{M} \text{ on } \mathcal{X}_\star(\mathbf{M}) \text{ and } \Pi^\star(\mathbf{M}^\dagger) \cap \Pi^\star(\mathbf{M}) = \emptyset \right\}.$ 

In [Definition 4](#page-8-1) and in the sequel, we write  $M^{\dagger} \gg M$  to mean that  $p(x) \ll p^{\dagger}(x)$  and  $r(x) \ll r^{\dagger}(x)$ for all  $x \in X$ . This absolute continuity assumption is linked to changes of measures and is crucial to the underlying proof techniques.

#### <span id="page-8-0"></span>3.2 Navigation: The higher order navigational structure

Yet, if fetching information is the first ingredient of our regret lower bound, it is insufficient to obtain a tight one. This makes quite a big difference with multi-armed bandits [Lai and Robbins\(1985\)](#page-36-0) and ergodic Markov decision processes [Agrawal et al.](#page-34-0) [\(1988b\)](#page-34-0); [Burnetas and Katehakis\(1997](#page-35-0)); [Graves and Lai](#page-36-1) [\(1997](#page-36-1)). In general, every MDP has a dynamical structure, so it cannot be explored freely and every learner is confined within the exploration possibilities allowed by the transition kernel. On M in [Figure 1,](#page-7-0) it is rather obvious that the number of times  $s'_4$  is visited should be about equal to the number of times  $s'_3$  is visited. Formally, the **visit vector**  $N_T \in \mathbb{R}^X$  given by  $N_T(x) := \sum_{t=1}^{T-1} \mathbb{1}(X_t = x)$ , mapping state-action pairs to their current number of visits, is nearly a flow of the MDP by satisfying an "entering mass equals outgoing mass" property.

<span id="page-8-2"></span>In this work, we instead talk of invariant measures (see [Definition 5\)](#page-8-2).

**Definition 5.** An **invariant measure**  $\mu \in \text{Inv}(\mathbf{M})$  of a Markov decision process **M** is a measure on X *such that:*

$$
\forall s \in \mathcal{S}, \quad \sum_{x \in \mathcal{X}} \mathbf{p}(s|x) \mu(x) = \sum_{a \in \mathcal{A}(s)} \mu(s, a).
$$

Unfortunately, we are not interested in the first order structure of the visit vector nor of the associated invariant measure, contrasting with the literature on provably approximately correct (PAC) learning, see [Al Marjani et al.](#page-35-12) [\(2021](#page-35-12)); [Tirinzoni et al.](#page-37-11) [\(2022\)](#page-37-11); [Russo and Proutiere](#page-37-12) [\(2024\)](#page-37-12); [Al-Marjani et al.](#page-35-13) [\(2023](#page-35-13)). For every consistent learner, as the regret is growing sublinearly, all the mass of  $N_T$  provably concentrates on optimal pairs and optimal pairs do not account for the regret. Thankfully, this dominant part can be discarded with a structural operation on M that we call **pair space contraction** which is close in spirit to the state aggregation operation of [Ortner](#page-36-9) [\(2013\)](#page-36-9): Every communicating component of  $M|_{X<sub>+</sub>(M)}$  (the original model constrained to optimal pairs) is contracted into a single state, providing a new contracted Markov decision process denoted  $M/X_{\star}(M)$ .

This operation is illustrated in [Figure 2](#page-9-2) and described formally in [Definition 8,](#page-15-2) see [Section 4.3.](#page-14-0)

On [Figure 2,](#page-9-2) the states spawned by  $\mathcal{X}_{\star}(\mathbf{M})$  are merged into a single state. The visit vector  $N_T$ satisfies a near-flow property on  $M/X_{\star}(M)$  as well, but this time all pairs of  $X_{\star}(M)$  are loops; And loops are trivial regarding flows hence are utterly discarded. What remains is the second order structure of  $N_T$ , which is nothing less than a near-flow of  $M/X_{\star}(M)$ . It follows that the second order structure of  $N_T$  converges to an invariant measure of  $M/X_{\star}(M)$  up to rescaling, as formally described by [Corollary 10.](#page-16-0)

A third, slightly more subtile ingredient will come refine what happens regarding exploration. This one, that we refer to as co-exploration, will be discussed more carefully in [Section 4.2.](#page-12-0) Combining all these ideas, we derive that consistent learners must fetch information to "reject" confusing models while preserving the structure of a contracted version of M at second order; These ingredients are enough to derive a complete regret lower bound in [Theorem 3,](#page-9-0) hence they completely describe the mandatory asymptotic behavior of consistent learners.



<span id="page-9-2"></span>Figure 2: The contraction of M by  $\mathcal{X}_\star(\mathbf{M})$ . The states spawning  $\mathcal{X}_\star(\mathbf{M})$  are merged together into a single state, forming a new Markov decision process  $M/X_{\star}(M)$ , where the navigational behavior of a consistent learner is better understood.

## <span id="page-9-1"></span>4 An asymptotic regret lower bound

This section is dedicated to the main contribution of this paper in the form of [Theorem 3.](#page-9-0) We provide an asymptotic lower bound on the cumulative regret of strong consistent learning agents under a communicating assumption.

<span id="page-9-0"></span>**Theorem 3** (Regret lower bound). Let  $M ∈ M$  *communicating. The regret of every consistent learning agent on M satisfies* liminf Reg(*T*; A, **M**)  $log^{-1}(T) \ge K_{\star}(\mathbf{M})$  *where*  $K_{\star}(\mathbf{M}) \in [0, \infty]$  *is:*  $\mathcal{L}(\mathbf{M}) = \mathcal{L}(\mathbf{M})$ *T*→∞

$$
K_{\star}(\mathbf{M}) = \inf \left\{ \sum_{x \in \mathcal{X}} \mu(x) \Delta_{\star}(x) : \mu \in \text{Inv}(\mathbf{M}) \text{ and } \inf_{\mathbf{M}^{\dagger} \in \text{Cnf}_{\star}(\mathbf{M})} \left\{ \sum_{x \in \mathcal{X}} \mu(x) \text{KL}_{x}(\mathbf{M} || \mathbf{M}^{\dagger}) \right\} \ge 1 \right\}.
$$
 (LB)

In the definition of  $K_{\star}(\mathbf{M})$ , we introduced  $KL_x(\mathbf{M}||\mathbf{M}^{\dagger}) := KL(\mathbf{p}(x)||\mathbf{p}^{\dagger}(x)) + KL(\mathbf{r}(x)||\mathbf{r}^{\dagger}(x)).$ 

The measure  $\mu \in \mathbb{R}^{\chi}$  tracks the number of times pairs are being **explored** (in logarithmic scale), and an element  $\mu^*$  that achieves the minimum of [\(LB\)](#page-10-1) can be interpreted as an optimal way to explore the environment and gather information. In that regard, such a  $\mu^*$  will be referred to as an **optimal** exploration measure and indirectly defines a randomized policy given by  $\pi(a|s) \propto \mu^*(s, a)$  that can be used to explore optimally. In light of this terminology, the result of [Theorem 3](#page-9-0) can be read as follows. It claims that (1) any optimal exploration measure  $\mu^*$  must respect the structure of the Markov decision process, with  $\mu^* \in Inv(M)$ ; and (2) any optimal exploration measure must be informative enough, with inf{ $\sum_{x \in \mathcal{X}} \mu(x) \mathbf{KL}_x(\mathbf{M}||\mathbf{M}^+)$ :  $\mathbf{M}^{\dagger} \in \text{Cnf}_\star(\mathbf{M})$ } ≥ 1. The second condition means that, when explorating according to  $\mu^*$ , one visits all the pairs in such a way that the learning agent can assess with sufficiently high confidence that seemingly optimal pairs are indeed optimal.

Outline of the section. The purpose of this section is to prove [Theorem 3.](#page-9-0) We start by following the ideas motivated in [Section 3,](#page-6-0) starting with information constraints in [Section 4.1.](#page-10-0) These information constraints are given relatively to a super-set of the confusing set [\(Definition 4\)](#page-8-1), called the alternative set [\(Definition 6\)](#page-10-2). The resulting information constraints embody the idea that consistent learners must explore, by wandering the suboptimal regions to make sure that they do not miss the optimal policies. In [Section 4.2,](#page-12-0) we show that **every** optimal region should be explored way more than sub-optimal regions, a phenomenon that we refer to as co-exploration. This leads to the simplification of the alternative set to the confusing set. In [Section 4.3,](#page-14-0) we dive into navigation constraints by properly defining minors and showing that the second order structure of the visit vector converges in expectation to an

invariant measure of a well-chosen minor. In [Section 4.4,](#page-18-0) we mix these three ingredients together to provide a first regret lower bound with [Theorem 11,](#page-18-2) given in terms of the confusing set  $\text{Cnf}_{\star}(\mathbf{M})$ and contracted invariant measures Inv( $M/X_{\star}(M)$ ). We finally prove [Theorem 3](#page-9-0) from [Theorem 11](#page-18-2) in [Section 4.5](#page-18-1) by showing that elements of  $Inv(M/X_{\star}(M))$  can be **represented** by elements of  $Inv(M)$ without changing the lower bound. We conclude by showing the importance of navigation constraints in [Section 4.6.](#page-19-0)

### <span id="page-10-0"></span>4.1 Exploration: Fetching information to reject alternative models

In [Sections 4.1](#page-10-0) and [4.2,](#page-12-0) we formalize the informal idea of [Section 3.1:](#page-6-1) that consistent learners must gather information to make sure that they do not miss the optimal policy. This is achieved in a twophase process. We start by proving that consistent learning agent must explore their environments M so that  $\mathbb{E}_{s_0}^{\mathbf{M},\mathbb{A}}$  ${}_{s_0}^{\mathbf{M},\mathbb{A}}[\sum_{x\in \mathcal{X}} N_{T+1}(x)\mathbf{K} L_x(\mathbf{M}||\mathbf{M}^{\dagger})] \geq \log(T)$  for every **alternative** model  $\mathbf{M}^{\dagger} \in \text{Alt}(\mathbf{M})$ . Alterna-tive models [\(Definition 6\)](#page-10-2) are all the environments  $M^{\dagger}$  such that  $\Pi^*(M^{\dagger}) \cap \Pi^*(M) = \emptyset$ , and confusing models [\(Definition 4\)](#page-8-1) are therefore special cases of alternative models. We will show that confusing models can replace alternative ones without degrading the lower bound in [Section 4.2.](#page-12-0)

The purpose of this paragraph is to provide a complete overview of the techniques and intuitions behind the main result of this paragraph, see [Proposition 4](#page-10-3) below.

We motivate the introduction of alternative models to begin with. In [Section 3.1,](#page-6-1) the motivational example makes obvious that any  $M^{\dagger}$  such that " $M^{\dagger} = M$  on  $\chi_{\star}(M)$ " doesn't hold will be trivially rejected by consistent learners. This is properly shown in [Section 4.2](#page-12-0) under mild assumptions, and this behavior is to be distinguished with the fetching of information displayed in this section, usually known as **exploration**. For the time being, the assumption " $M^{\dagger} = M$  on  $\chi_{\star}(M)$ " in the definition of confusing models is dropped, resulting in the broader notion of alternative models, named accordingly to the works of [Marjani and Proutiere](#page-36-10) [\(2021\)](#page-36-10); [Al Marjani et al.](#page-35-12) [\(2021\)](#page-35-12); [Al-Marjani et al.](#page-35-13) [\(2023\)](#page-35-13) in the PAC setting.

<span id="page-10-2"></span>**Definition 6** (Alternative models). *Fix*  $M \in M$ . *The alternative set of*  $M$  *is given by:* 

$$
\mathrm{Alt}(\mathbf{M}):=\Big\{\mathbf{M}^{\dagger}\in\mathcal{M}:\mathbf{M}^{\dagger}\gg\mathbf{M}\ and\ \Pi^{\star}(\mathbf{M}^{\dagger})\cap\Pi^{\star}(\mathbf{M})=\emptyset\Big\}.
$$

<span id="page-10-3"></span>It is obvious that  $\text{Cnf}_{\star}(M) \subseteq \text{Alt}(M)$ . The informal argument of information gathering is formalized by the following result.

Proposition 4 (Information constraint). *Let* M ∈ M *and let* M† ∈ Alt(M)*. Whatever the initial state*  $s_0 \in S$ , every consistent learner  $\mathbb A$  *satisfies:* 

$$
\mathbb{E}_{s_0}^{\mathbf{M},\mathbb{A}}\bigg[\sum_{x\in\mathcal{X}}N_{T+1}(x)\mathrm{KL}_x(\mathbf{M}||\mathbf{M}^\dagger)\bigg]\geq \log(T)+\mathrm{o}(\log(T)).
$$

**Changes of measures.** The core of the proof is to show that a consistent learner  $A$  cannot behave similarly on **M** and  $M^{\dagger}$  if  $M^{\dagger} \in Alt(M)$ . The learner A explores *because* it cannot perform too poorly on  $M^{\dagger}$ , even though there is a positive probability that when navigating  $M^{\dagger}$ , the observed data that resembles M much more than  $M^{\dagger}$ . This informal argument is concretized using log-likelihood ratios to relate the behavior of the learning agent on  $M^{\dagger}$  to its behavior on M. By doing a change of measure, it happens (see [Theorem C.1\)](#page-46-2) that for all  $\sigma(H_T)$ -measurable random variable  $U \ge 0$  and all  $M^{\dagger} \gg M$ , we have:

<span id="page-10-1"></span>
$$
\mathbb{E}_{s_0}^{\mathbf{M}^\dagger,\mathbb{A}}[U] \geq \mathbb{E}_{s_0}^{\mathbf{M},\mathbb{A}} \Bigg[ U \exp \Bigg\{ -\sum_{t=1}^T \log \Bigg( \frac{\mathbf{p}(S_{t+1}|S_t,A_t)}{\mathbf{p}^\dagger(S_{t+1}|S_t,A_t)} \frac{\mathbf{r}(R_t|S_t,A_t)}{\mathbf{r}^\dagger(R_t|S_t,A_t)} \Bigg) \Bigg\} \Bigg]
$$
(6)

with equality when  $M^{\dagger} \ll M$  as well. The quantity  $L(H_T; M, M^{\dagger}) := \sum_{t=1}^{T} \log \left( \frac{p(S_{t+1}|S_t, A_t)}{p^{\dagger}(S_{t+1}|S_t, A_t)} \right)$  $\mathbf{p}^{\dagger}(S_{t+1}|S_{t},A_{t})$  $\frac{\mathbf{r}(R_t|S_t,A_t)}{R_t}$  $\mathbf{r}^{\dagger}(R_t|S_t,A_t)$  is known as the log-likelihood ratio of observations.

If the equation [\(6\)](#page-10-1) can be used as is, like in [Lai and Robbins](#page-36-0) [\(1985](#page-36-0)), it is often transformed [Wald](#page-37-13) [\(1945](#page-37-13)); [Kaufmann](#page-36-11) [\(2014](#page-36-11)); [Maillard](#page-36-12) [\(2019](#page-36-12)) to obtain an inequality that are more easy to work with. The key observation is that the expected log-likelihood ratio takes the simpler form  $\mathbb{E}_{s_0}^{\mathbf{M},\check{\mathbf{A}}}$  $\sum_{s_0}^{\mathbf{M},\mathbb{A}}[L(H_T;\mathbf{M},\mathbf{M}^\dagger)] =$  $\mathbb{E}_{so}^{\mathbf{M},\mathbb{A}}$  $\sum_{x_0}^{M,A} [\sum_{x \in \mathcal{X}} N_T(x)KL_x(M||M^{\dagger})]$ . In tandem with an application of Jensen's inequality in [\(6\)](#page-10-1), we obtain (see [Corollary C.3\)](#page-46-3), for  $U > 0$ ,

<span id="page-11-1"></span>
$$
\mathbb{E}_{s_0}^{\mathbf{M},\mathbb{A}}\bigg[\sum_{x\in\mathcal{X}}N_T(x)\mathrm{KL}_x(\mathbf{M}||\mathbf{M}^\dagger)\bigg]\geq \mathbb{E}_{s_0}^{\mathbf{M},\mathbb{A}}\big[\log(U)\big]-\log\big(\mathbb{E}_{s_0}^{\mathbf{M}^\dagger,\mathbb{A}}[U]\big).
$$
 (7)

Accordingly, we are looking for a  $U > 0$  such that  $\mathbb{E}_{s_0}^{\mathbf{M}, \mathbb{A}}$  $_{\mathcal{S}_0}^{\mathbf{M},\mathbb{A}}[\log(U)]$  is large while  $\log(\mathbb{E}_{\mathcal{S}_0}^{\mathbf{M}^\dagger,\mathbb{A}})$  $\binom{M^+, A}{s_0}$  [*U*]) is small; Or, such that  $\mathbb{E}_{s_0}^{\mathbf{M},\mathbb{A}}$  ${}_{s_0}^{\mathbf{M},\mathbb{A}}$ [log(*U*)] is small while − log( $\mathbb{E}_{s_0}^{\mathbf{M}^\dagger,\mathbb{A}}$  $S_0^{M^{1},A}[U]$  is large. In other words, we are looking for a random variable that discriminate how the learner behaves on M and  $M^{\dagger}$ .

A simple example of discriminating random variable. In a few cases where  $M^{\dagger}$  satisfies more properties than merely  $M^{\dagger} \in Alt(M)$ , the design of a discriminating random variable may be greatly simplified, so that results  $\dot{a}$ -*la* [Proposition 4](#page-10-3) can be derived within a few lines from the change of measure inequality [\(7\)](#page-11-1). One such example is when  $\chi_{\hat{X}}(M^{\dagger}) \cap \chi_{\hat{X}}(M) = \emptyset$ , in which case the set of sub-optimal pairs of  $M^{\dagger}$  is a superset of  $X_{\mathfrak{X}}(M)$ . Following this, letting  $U := 1 + \sum_{x \in X_{\mathfrak{X}}(M)} N_{T+1}(x)$ and rewriting the expected regret as a sum of gaps with [Proposition 1,](#page-6-3) we readily obtain:

$$
\operatorname{Reg}(T; \mathbf{M}, \mathbb{A}, s_0) \le \max(\Delta_{\star}(\mathbf{M})) \mathbb{E}_{s_0}^{\mathbf{M}, \mathbb{A}} [T - U] + O(1);
$$
 and  

$$
\operatorname{Reg}(T; \mathbf{M}^\dagger, \mathbb{A}, s_0) \ge \dim(\Delta_{\star}(\mathbf{M}^\dagger)) \mathbb{E}_{s_0}^{\mathbf{M}, \mathbb{A}} [U] + O(1).
$$

What is important in the above, is to convert the consistency properties that control the expected regret to controlled inequalities on visit counts; The very value of max $(\Delta_{\star}(M))$  and dmin $(\Delta_{\star}(M^{\dagger}))$  have very little importance asymptotically. By consistency, it follows that  $\mathbb{E}_{s_0}^{\mathbf{M},\mathbf{A}}$  $\sum_{s_0}^{\mathbf{M},\mathbb{A}} [T-U] = o(T^{\eta}) \text{ and } \mathbb{E}_{s_0}^{\mathbf{M}^{\dagger},\mathbb{A}}$  $S_0^{\mathbf{M}^{\intercal},\mathbb{A}}[U] =$ o( $T^{\eta}$ ) where  $\eta > 0$  is arbitrarily small. So, by Markov's inequality,  $\mathbb{P}_{s_0}^{M,A}$  $_{S_0}^{M,A}(U \leq T - T^{\eta}) = o(1)$  and  $\mathbb{E}_{so}^{\mathbf{M},\mathbb{A}}$  $\log_{s_0}$  [log(*U*)]  $\geq \log(T) + o(\log(T))$ . Together with [\(7\)](#page-11-1), we obtain:

$$
\mathbb{E}_{s_0}^{\mathbf{M},\mathbb{A}}\bigg[\sum_{x\in\mathcal{X}}N_{T+1}(x)\mathrm{KL}_x(\mathbf{M}||\mathbf{M}^\dagger)\bigg]\geq (1-\eta)\log(T)+\mathrm{o}(\log(T)).
$$

As  $\eta > 0$  can be chosen arbitrarily small, we conclude that [Proposition 4](#page-10-3) holds in particular for  $M^{\dagger} \in \mathcal{M}$  such that  $\mathcal{X}_{\dot{\mathbf{x}}}(\mathbf{M}^{\dagger}) \cap \mathcal{X}_{\dot{\mathbf{x}}}(\mathbf{M}) = \emptyset$ .

A general discriminating random variable. For the general setting, where  $M^{\dagger} \in Alt(M)$  without any additional assumption, the random variable *U* that we choose is provided by [Lemma 5](#page-11-0) below. We track with U how many times the algorithm plays sub-optimal pairs of M that are optimal on  $M^{\dagger}$ . Intuitively,  $\mathbb{E}_{s_0}^{\mathbf{M},\mathbb{A}}$  $_{S_0}^{\mathbf{M},\mathbb{A}}[U]$  is roughly bounded by the regret  $\mathrm{Reg}(T;\mathbf{M},\mathbb{A})$  while  $\mathbb{E}_{S_0}^{\mathbf{M}^\dagger,\mathbb{A}}$  $\binom{M^+,A}{s_0}[U]$  grows at the same rate as  $T - O(Reg(T; M^{\dagger}, A))$ . A fine control of the tails of *U* is however required to properly spawn the  $log(T)$  factor that appears in [Proposition 4.](#page-10-3) This is made possible by the key [Lemma 5](#page-11-0) below.

<span id="page-11-0"></span>**Lemma 5.** *Let*  $M \in \mathcal{M}$ , *pick*  $M^{\dagger} \in Alt(M)$  *and let*  $X_c := \{x \in X_{\star}(M^{\dagger}) : \Delta_{\star}(x; M) > 0\}$ *. There exist constants*  $\varepsilon_c^{\dagger}$ ,  $D_c^{\dagger}$  > 0 *such that, whatever the learning agent* A *and the initial state*  $s_0$ *, we have:* 

$$
\forall u \geq 0, \quad \mathbb{P}_{s_0}^{\mathbf{M}^\dagger, \mathbb{A}} \Bigg( \sum_{x \in X_c} N_{T+1}(x) + D_c^\dagger \sum_{x \in X_{-}(\mathbf{M})} N_{T+1}(x) \leq \varepsilon_c^\dagger T - u \Bigg) \leq \exp \Biggl( -\frac{2u^2}{TD_c^{\dagger 2}} \Biggr).
$$

V. Boone & OA. Maillard 12 January 23, 2025

The proof of [Lemma 5](#page-11-0) is provided in [Appendix B.](#page-42-0) We can now prove the proposition of interest.

*Proof of [Proposition 4.](#page-10-3)* Let  $M \in \mathcal{M}$  and pick  $M^{\dagger} \in Alt(M)$ . Let  $\mathcal{X}_c := \{x \in \mathcal{X}_\star(M^{\dagger}) : \Delta_\star(x; M) > 0\}$ and fix  $U := (1 + \sum_{x \in \mathcal{X}_c} N_{T+1}(x))^{-1}$ . The goal is to invoke [\(7\)](#page-11-1) for *U*.

Fix  $\eta > 0$  arbitrary.

We start by upper-bounding  $\mathbb{E}_{s_0}^{\mathbf{M}^\dagger,\mathbb{A}}$  $S_0^{N^1,A}[U]$ . Let  $\varepsilon_c^T, D_c^T > 0$  the constants provided by [Lemma 5.](#page-11-0) By [Proposition 1,](#page-6-3) we know that for  $\alpha := sp(b_{\star}(M^{\dagger}))$  and for all  $T \ge 1$ , we have:

$$
\alpha + \text{Reg}(T; \mathbf{M}^{\dagger}, \mathbb{A}, s_0) \geq \mathbb{E}_{s_0}^{\mathbf{M}^{\dagger}, \mathbb{A}} \Bigg[ \sum_{x \in \mathcal{X}} N_{T+1}(x) \Delta_{\star}(x; \mathbf{M}^{\dagger}) \Bigg] \geq \dim(\Delta_{\star}(\mathbf{M}^{\dagger})) \mathbb{E}_{s_0}^{\mathbf{M}^{\dagger}, \mathbb{A}} \Bigg[ \sum_{x \in \mathcal{X}_{-}(\mathbf{M}^{\dagger})} N_{T+1}(x) \Bigg].
$$

Observe that with this kind of reasoning, we also show that  $\mathbb{E}_{s_0}^{\mathbf{M},\mathbf{A}}$  $\sum_{s_0}^{\mathbf{M},\mathbb{A}} \left[ \sum_{x \in \mathcal{X}_c} N_{T+1}(x) \right] \leq \frac{\text{Reg}(T; \mathbf{M}, \mathbb{A}, s_0) + \text{sp}(\mathbf{b}_\star(\mathbf{M}))}{\text{dmin}(\mathbf{\Delta}_\star(\mathbf{M}))} =$  $o(T<sup>\eta</sup>)$ . Now, combining [Lemma 5](#page-11-0) with Markov's inequality, we obtain:

$$
\mathbb{P}_{s_0}^{\mathbf{M}^\dagger,\mathbb{A}}\bigg(U \leq \frac{1}{2}\varepsilon_c^\dagger T - u\bigg) \leq \frac{2\mathrm{Reg}(T;\mathbf{M}^\dagger,\mathbb{A},s_0)T^{-1}}{\mathrm{dmin}(\Delta_\star(\mathbf{M}^\dagger))\varepsilon_c^\dagger} + \exp\bigg(-\frac{2u}{TD_c^{\dagger 2}}\bigg) = \mathrm{o}\bigg(T^{\eta-1}\bigg) + \exp\bigg(-\frac{2u}{TD_c^{\dagger 2}}\bigg)
$$

where the equality follows by strong consistency of  $A$  on  $M^{\dagger}$ . So, we get:

$$
\mathbb{E}_{s_0}^{\mathbf{M}^{\dagger},\mathbb{A}}[U] \equiv \mathbb{E}_{s_0}^{\mathbf{M}^{\dagger},\mathbb{A}} \bigg[ \frac{1}{1+\sum_{x \in \mathcal{X}_c} N_{T+1}(x)} \bigg] \leq \inf_{\nu \geq 0} \bigg\{ \frac{1}{1+\nu} + \mathbb{P}_{s_0}^{\mathbf{M}^{\dagger},\mathbb{A}} \bigg( \sum_{x \in \mathcal{X}_c} N_{T+1}(x) \leq \nu \bigg) \bigg\} \leq \inf_{\nu \geq 0} \bigg\{ \frac{1}{1+\nu} + o(T^{\eta-1}) + \exp \bigg( -\frac{2\big(\frac{1}{2}\varepsilon_c^{\dagger}T - \nu\big)^2}{TD_c^{\dagger 2}} \bigg) \bigg\} \bigg\}
$$

$$
\leq \frac{\inf}{1 + \frac{1}{4}\varepsilon_c^{\dagger}T} + o(T^{\eta-1}) + \exp \bigg( -\frac{\varepsilon_c^{\dagger}T}{8D_c^{\dagger 2}} \bigg)
$$

where (†) follows by setting  $v := \frac{1}{4}$  $\frac{1}{4}\varepsilon_c^\dagger T$ . We conclude that  $\log(\mathbb{E}_{s_0}^{{\bf M}^\dagger,\mathbb{A}})$  $S_{S_0}^{M',A}[U]$ ) ≤ (η − 1) log(*T*) + o(log(*T*)). We conclude as follows. By  $(7)$ , we have:

$$
\mathbb{E}_{s_0}^{\mathbf{M},\mathbb{A}} \Biggl[ \sum_{x \in \mathcal{X}} N_{T+1}(x) \text{KL}_{x}(\mathbf{M}||\mathbf{M}^{\dagger}) \Biggr] \geq \mathbb{E}_{s_0}^{\mathbf{M},\mathbb{A}} [\log(U)] - \log \Biggl( \mathbb{E}_{s_0}^{\mathbf{M}^{\dagger},\mathbb{A}}[U] \Biggr)
$$
  
\n
$$
= -\mathbb{E}_{s_0}^{\mathbf{M},\mathbb{A}} \Biggl[ \log \Biggl( 1 + \sum_{x \in \mathcal{X}_c} N_{T+1}(x) \Biggr) \Biggr) - \log \Biggl( \mathbb{E}_{s_0}^{\mathbf{M}^{\dagger},\mathbb{A}} \Biggl[ \frac{1}{1 + \sum_{x \in \mathcal{X}_c} N_{T+1}(x)} \Biggr] \Biggr)
$$
  
\n
$$
\stackrel{(\dagger)}{\geq} - \log \Biggl( 1 + \mathbb{E}_{s_0}^{\mathbf{M},\mathbb{A}} \Biggl[ \sum_{x \in \mathcal{X}_c} N_{T+1}(x) \Biggr] \Biggr) + (1 - \eta) \log(T) + o(\log(T))
$$
  
\n
$$
\stackrel{(\dagger)}{\geq} (1 - 2\eta) \log(T) + o(\log(T)).
$$

where (†) is obtained by applying Jensen's inequality to bound the first term and the previous computation to bound the second and ( $\ddagger$ ) uses that  $\mathbb{E}_{s_0}^{\mathbf{M},\mathbf{A}}$  $\sum_{x \in \mathcal{X}_c} N_{T+1}(x)$  = o(*T*<sup>*n*</sup>). As this holds for arbitrary  $\eta > 0$ , we conclude accordingly.

#### <span id="page-12-0"></span>4.2 Co-exploration: From alternative to confusing sets

[Proposition 4](#page-10-3) provides our strongest result about how much information consistent learners must collect during play, by essentially showing that consistent learners have to reject every alternative

model. In this paragraph, we couple this fact with an orthogonal result, stating that under a mild assumptions, every alternative model  $M^{\dagger}$  that differ from M on optimal pairs is trivially "ruled out" by a consistent learner. If, in fact, Alt(M) was introduced in [Definition 6](#page-10-2) to account for the fact that generic learners are not guaranteed to gather a lot of information of  $\mathcal{X}_{\star}(\mathbf{M})$ , we can actually show that pairs of  $\mathcal{X}_{\star}(\mathbf{M})$  are all visited overlogarithmically by consistent learners. This behavior is to be distinguished from exploration (playing sub-optimal pairs to make sure that they are sub-optimal) because it underlines a need to play optimal (hence zero-cost) pairs in order to gather information on them rather than gathering rewards alone; This is referred to as co-exploration.

<span id="page-13-0"></span>**Proposition 6** (Co-exploration constraint). Let  $M \in \mathcal{M}$  and fix  $x_{\star} \in \mathcal{X}_{\star}(M)$ . Assume that, for all  $\varepsilon > 0$ , there exists  $M' \in M$  such that (1) M' and M only differ with  $r(x_\star) \neq r'(x_\star)$ , (2)  $m(x_\star) < m'(x_\star)$ *and* (3)  $KL(\mathbf{r}(x_{\star})||\mathbf{r}'(x_{\star})) < \varepsilon$ . Then,<sup>[2](#page-13-1)</sup> for every consistent learner A and regardless of the initial state  $s_0 \in \mathcal{S}$ ,

$$
\mathbb{E}_{s_0}^{\mathbf{M},\mathbb{A}}[N_{T+1}(x_{\star})] = \omega(\log(T)).
$$

The proof of [Proposition 6](#page-13-0) is deferred to [Appendix B](#page-42-0) — it again relies on change of measures, but in a quite different way than [Proposition 4.](#page-10-3) In [Proposition 6,](#page-13-0) the three conditions (1-3) imply that there exists models that are arbitrarily close to M for which every gain optimal policy must use  $x_{\star}$  infinitely often. These conditions are for instance automatically satisfied when  $M = \prod_{x \in \mathcal{X}} (\mathcal{P}(S) \otimes \mathcal{P}([0, 1]))$  is the set of all Markov decision processes with pair space X and  $M \in \mathcal{M}$  satisfies max(m) < 1. That scenario is quite similar to the one under which [Lai and Robbins](#page-36-0) [\(1985](#page-36-0)) prove the tightness of their lower bound in the first place. And in that scenario, the information constraints of [Proposition 4](#page-10-3) can be dropped to confusing models instead of alternative ones. Indeed, if  $M^{\dagger} \in Alt(M)$  is such that there exists  $x \in X_{\star}(\mathbf{M})$  with  $KL_x(\mathbf{M}||\mathbf{M}^{\dagger}) > 0$ , then every consistent learner is such that:

$$
\liminf_{T\to\infty}\frac{1}{\log(T)}\mathbb{E}_{s_0}^{\mathbf{M},\mathbb{A}}\left[\sum_{x\in\mathcal{X}}N_{T+1}(x)\mathrm{KL}_x(\mathbf{M}||\mathbf{M}^\dagger)\right]=\infty.
$$

Therefore, the information constraint associated to  $M^{\dagger}$  in [Proposition 4](#page-10-3) is trivially met. Accordingly, the immediate consequence of [Proposition 4,](#page-10-3) [Corollary 7](#page-13-2) below, does not lose any information relatively to [Proposition 4](#page-10-3) when completed with [Proposition 6.](#page-13-0)

<span id="page-13-2"></span>Corollary 7. Let  $M$  ∈  $M$  *and let*  $M^{\dagger}$  ∈ Cnf<sub>\*</sub>(M). Then, every consistent learner  $\mathbb A$  satisfies:

$$
\mathbb{E}_{s_0}^{\mathbf{M},\mathbb{A}}\left[\sum_{x\in\mathcal{X}}N_{T+1}(x)\mathrm{KL}_x(\mathbf{M}||\mathbf{M}^{\dagger})\right]\geq \log(T)+\mathrm{o}(\log(T)).
$$

Beyond optimal pairs. The alternative set can be provably simplified to the confusing set via [Proposition 6,](#page-13-0) because consistent learners are forced to gather much more information on  $\mathcal{X}_{\star}(\mathbf{M})$ than on  $X \setminus X_{\star}(\mathbf{M})$ . However, it is impossible to further simplify Cnf<sub>\*</sub>(M) with more results in the style of [Proposition 6.](#page-13-0) For instance,  $\text{Cnf}_{\star}(M)$  cannot be strengthened to

$$
Cnf_{\dot{\mathbf{X}}}(\mathbf{M}):=\left\{\mathbf{M}^{\dagger}\in\mathcal{M}:\mathbf{M}^{\dagger}\gg\mathbf{M}\text{ and }\mathbf{M}^{\dagger}=\mathbf{M}\text{ on }\mathcal{X}_{\dot{\mathbf{X}}}(\mathbf{M})\text{ and }\Pi^{\star}(\mathbf{M}^{\dagger})\cap\Pi^{\star}(\mathbf{M})=\emptyset\right\}
$$

in [Corollary 7.](#page-13-2) The reason for this is that the amount of time spent outside of  $\mathcal{X}_{\star}(M)$  is proportional to the regret, underlying a key difference between  $\mathcal{X}_{\star}(\mathbf{M})$  and  $\mathcal{X}_{\star}(\mathbf{M})$ , see [Lemma 8](#page-13-3) below, that illustrates the transient nature of  $\mathcal{X}_{\dot{\mathcal{X}}}(\mathbf{M}) \setminus \mathcal{X}_{\dot{\mathcal{X}}}(\mathbf{M}).$ 

<span id="page-13-3"></span>**Lemma 8.** Let  $M \in \mathcal{M}$ . There exist constants  $\alpha, \beta > 0$  such that, for every learner A and  $T \geq 1$ ,

$$
\mathbb{E}_{s_0}^{\mathbf{M},\mathbb{A}}\left[\sum_{t=1}^T \mathbb{1}(X_t \notin \mathcal{X}_{\star}(\mathbf{M}))\right] \leq \alpha \operatorname{Reg}(T; \mathbf{M}, \mathbb{A}, s_0) + \beta.
$$

<span id="page-13-1"></span><sup>2</sup>We recall that  $f(T) = \omega(g(T))$  means that *f* grows strictly faster than *g* as  $T \to \infty$  that is, lim inf $T \to \infty$   $|f(T)/g(T)| = \infty$ .

V. Boone & OA. Maillard 14 January 23, 2025

*Proof.* Consider the revised version  $M_f$  of M with revised reward vector  $f(x) := 1(x \in X_{\star}(M))$ . Let  $\pi$  the policy such that  $\pi(s)$  is the uniform probability distribution over  $\{a \in \mathcal{A}(s) : (s, a) \in \mathcal{X}_{\mathcal{X}}(\mathbf{M})\}.$ This policy is gain-optimal, and we denote  $\mathbf{g}_f$ ,  $\mathbf{b}_f$  and  $\Delta_f$  the gain, bias and gap functions of  $\pi$  under the reward function  $f$ . We have:

$$
\sum_{x \notin X_{\star}(\mathbf{M})} N_{T+1}(x) = T - \sum_{t=1}^{T} f(X_{t}) \stackrel{(\dagger)}{=} T - \sum_{t=1}^{T} \left( \mathbf{g}_{f}(S_{t}) + (\mathbf{e}_{S_{t}} - \mathbf{p}(X_{t})) \mathbf{b}_{f} - \mathbf{\Delta}_{f}(X_{t}) \right)
$$
\n
$$
\stackrel{(\dagger)}{\leq} \text{sp}(\mathbf{b}_{f}) + ||\mathbf{\Delta}_{f}||_{\infty} \sum_{x \notin X_{\star}(\mathbf{M})} N_{T+1}(x)
$$
\n
$$
\leq \text{sp}(\mathbf{b}_{f}) + \frac{||\mathbf{\Delta}_{f}||_{\infty}}{\text{dmin}(\mathbf{\Delta}_{\star}(\mathbf{M}))} \sum_{x \notin X_{\star}(\mathbf{M})} N_{T+1}(x) \mathbf{\Delta}_{\star}(x; \mathbf{M})
$$

where (†) unfolds the definition of  $\Delta_f$ , (‡) uses the remark that since  $\pi$  is gain optimal, it converges to  $\mathcal{X}_{\star}(\mathbf{M})$  so  $\mathbf{g}_f = 1$ ; and that we have  $\Delta_f(x) = 0$  for  $x \notin \mathcal{X}_{\star}(M)$ . Take the expectation.

If the learner cannot spend too much time outside of  $\mathcal{X}_{\star}(\mathbf{M})$  without degrading the regret, it means that it cannot gather a lot of information on any pair outside of  $\mathcal{X}_{\star}(\mathbf{M})$  without increasing the regret. In that aspect, [Proposition 6](#page-13-0) and [Lemma 8](#page-13-3) are the two sides of the same coin: efficient consistent learners will gather enormous amount of information *precisely* on all optimal pairs. In other words,  $\mathcal{X}_{\star}(\mathbf{M})$  and  $\mathcal{X} \setminus \mathcal{X}_{\star}(\mathbf{M})$  are treated differently by such learners.

Regret bounds obtained from information constraints. As a matter of fact, a regret lower bound can immediately be derived from the information constraints described by [Proposition 4.](#page-10-3) By [Proposition 1,](#page-6-3) the expected regret can be written as  $\sum_{x \in \mathcal{X}} \mathbb{E}_{s_0}^{\mathbf{M}, A}$  $N_{s_0}^{M,A}[N_{T+1}(x)]\Delta_{\star}(x; \mathbf{M}) + O(1)$ , while [Proposition 4](#page-10-3) states that  $\sum_{x \in \mathcal{X}} \mathbb{E}^{\mathbf{M}, A}_{s_0}$  ${}_{S_0}^{M,A}[N_{T+1}(x)]KL_x(M||M^{\dagger}) \geq log(T) + o(log(T))$  for every  $M^{\dagger} \in Alt(M)$ . Normalizing by  $log(T)$  and going to the asymptotic, we see that a consistent learner satisfies:

$$
\liminf_{T \to \infty} \frac{\text{Reg}(T; \mathbf{M}, \mathbb{A}, s_0)}{\log(T)} \geq \inf \left\{ \sum_{x \in \mathcal{X}} \mu(x) \Delta_\star(x; \mathbf{M}) : \mu \in [0, \infty]^{\mathcal{X}} \text{ and } \inf_{\mathbf{M}^\dagger \in \text{Alt}(\mathbf{M})} \sum_{x \in \mathcal{X}} \mu(x) \text{KL}_x(\mathbf{M} || \mathbf{M}^\dagger) \geq 1 \right\}.
$$

What [Proposition 6](#page-13-0) states is that in the above and under mild assumptions, Alt(M) can be changed to  $Cnf_{\star}(M)$  without changing the lower bound. The resulting lower bound is of the same kind as [Lai and Robbins](#page-36-0) [\(1985\)](#page-36-0); [Graves and Lai](#page-36-1) [\(1997](#page-36-1)); [Burnetas and Katehakis](#page-35-0) [\(1997](#page-35-0)); [Agrawal et al.](#page-34-0) [\(1988b](#page-34-0)) and can be seen as a generalization of their results to the more general setting of communicating Markov decision processes. It appears clearly that in such bounds however, the structure of  $N_{T+1}/\log(T)$  is disregarded. In the respective settings of these works, it is disregarded because the obtained lower bound is provably reached by a learning agent. This is only possible in their particular settings, and the lower bound that we provide downstream will provide new light into why, and when, the structure of  $N_{T+1}/\log(T)$  can be "ignored", see [Sections 6.1](#page-23-1) and [6.2.](#page-24-0)

In general and as motivated in [Section 3.2,](#page-8-0) the structure of  $N_{T+1}/\log(T)$  is far from arbitrary for communicating Markov decision processes, and has to be taken into account.

### <span id="page-14-0"></span>4.3 Decomposition of the navigation of consistent learners and minors

With [Proposition 4,](#page-10-3) consistent learning agents have been shown to wander their environment in order to implicitely collect enough information so that alternative models are rejected. This environment, in opposition to multi-armed bandits, usually has structure. The critical lack of information on a pair  $x \in \mathcal{X}$  requires the agent to compute an efficient way to reach that pair, hence the visit vector  $N_{T+1}$ is not just any element of  $\mathbb{N}^{\chi}$ . This all has already been discussed in [Section 3.2,](#page-8-0) where we have pinpointed the importance of minors, that we shall formally define now.

### <span id="page-15-0"></span>4.3.1 Formal definition of minors

Minors generalize edge contraction on graphs to Markov decision processes and are close in spirit to the state reduction/aggregation of [Ortner](#page-36-9) [\(2013\)](#page-36-9). They are obtained by contracting subsets of pairs of the initial model/ In opposition to classical graph theory, we won't allow for the contraction of arbitrary subsets of pairs. The contracted subset  $X'$  must be **closed** [\(Definition 7\)](#page-15-3), meaning that (1) one remains in the states spawned by  $X'$  by playing pairs of  $X'$ , and (2) it does not contain transient states. The property (1) implies that **M** can be restricted to  $\chi'$  and the states it spawns, and (2) that the obtained model is a union of disjoint communicating Markov decision processes.

<span id="page-15-3"></span>**Definition 7** (Closed pair subspace of M). A *subset*  $X_0 \subseteq X$  *with corresponding states*  $S(X_0)$  *is a closed set of* M *if it is (1) forward closed meaning*  $p(-|x)$  *is supported in*  $S(X_0)$  *for all*  $x \in X_0$ *, and* (2)  $\bm{backward}$  closed, meaning the model  $\bm{\mathrm{M}}$  constrained to  $X_0{}^3$  $X_0{}^3$  is a union of communicating components *(no transient states).*

A simple, yet illuminating observation, is that a subset  $X_0$  is closed if, and only if it is the set of recurrent pairs under some randomized stationary policy. In this paper, the most important example of closed set is the set of optimal pairs  $\mathcal{X}_\star(\mathbf{M})$ , which is obtained as the recurrent pairs of the policy  $\pi^*$  given by  $\pi^*(s)$  as the uniform distribution on  $\{a \in \mathcal{A}(s) : (s, a) \in \mathcal{X}_{\mathcal{X}}(\mathbf{M})\}.$ 

<span id="page-15-2"></span>**Definition 8** (Minors/Contractions). *Up to re-labeling actions, assume that*  $\mathcal{A}(s) \cap \mathcal{A}(s') = \emptyset$  *for*  $s \neq s'$ . Let  $M \in \mathcal{M}$  *a* model and fix  $X_0 \subseteq X$  *a* closed set of M. The **contraction of** M by  $X_0$  is the *model*  $M/X_0$  *obtained by merging every communicating component of*  $X_0$  *into single states. More formally, letting*  $S_1, \ldots, S_k$  *the communicating components of*  $X_0$ *, we have:* 

- (1) The state space is  $S(M/X_0) := \{S_1, \ldots, S_k\} \cup \{(s\} : s \in S \text{ and } \forall i, s \notin S_i\}$  and contracted states *are denoted* [*s*]*;*
- (2) *The action space is, for*  $[s] \in S(M/X_0)$ ,  $\mathcal{A}(M/X_0)[s] := \bigcup_{s' \in [s]} \mathcal{A}(s')$ ; *Because in* **M**, *the choice of an action uniquely determines a state, the state-action space*  $X(M/X_0)$  *is canonically isomorphic to* X(M)*, by associating* ([*x*], *a*) *to* (*s* ′ , *a*) *where s*′ *is the unique state such that*  $a \in \mathcal{A}(s')$ .
- (3) *The kernel is*  $[p]([s_1] | [s_0], a) := \sum_{s'_1 \in [s_1]} p(s'_1 | s'_0, a)$ ;
- (4) *The reward is*  $[r]([s_0], a) := r(s'_0, a)$ *.*

*We also say that*  $M/X_0$  *is a minor of M.* 

#### <span id="page-15-1"></span>4.3.2 Decomposing executions using invariant measures of minors

Minors provide a descriptive decomposition of how a Markov decision process can be explored, following a general principle. The collection of optimal pairs  $X_{\star}$  is an example of closed set [\(Definition 7\)](#page-15-3), that themselves are recurrent pairs of randomized policies. Independently of the way a planner explores the model, the normalized ratio of visits outside of a closed set converges to an invariant measure of the minor induced by that closed set, provided that the outside is visited at least logarithmically often.

<span id="page-15-5"></span>**Proposition 9.** Let  $\pi$  *a randomized policy and let*  $X_{\pi}$  *its recurrent pairs. Let*  $A$  *any learning agent such that*  $\mathbb{E}_{s_0}^{\mathbf{M},\mathbb{A}}$  $\sum_{s_0}^{M,A}[\sum_{x \notin X_\pi} N_T(x)] = \Omega(\log(T))$ *. The vector given by* 

$$
\mu_t(x) := \frac{\mathbb{E}_{s_0}^{\mathbf{M},\mathbb{A}}[N_t(x)] \mathbb{1}(x \notin \mathcal{X}_\pi)}{\mathbb{E}_{s_0}^{\mathbf{M},\mathbb{A}}\Big[\sum_{x' \notin \mathcal{X}_\pi} N_t(x')\Big]}
$$

*converges to the space of invariant measures of*  $M/X_\pi$ , *i.e., every limit point of*  $(\mu_t)$  *is an invariant measure of*  $M/X_\pi$ *.* 

<span id="page-15-4"></span> $3$ It is well-defined by forward closeness (1).

This result is coupled with a second observation. It can be shown that if the expected visits counts can be written as  $\mathbb{E}^{\mathbb{A}}[N_T(x)] = \alpha(x)T + o(T)$ , then  $X_{\mathbb{A}} := \{x : \alpha(x) > 0\}$  is a closed set that, if the planner is consistent, is a subset of  $\mathcal{X}_\star(\mathbf{M})$ . [Proposition 9](#page-15-5) supports the previously motivated idea that the "sublinear" part of visit counts is easier to understand after contracting the model by  $\mathcal{X}_{\star}(\mathbf{M})$ : Up to normalization, the truncation of the visit vector to  $X \setminus X_*(M)$ , i.e.,  $N_T \mathbb{1}(X_*(M)^c)$ , of a consistent learning agent converges in expectation to a probability invariant measure of  $M/X_{\star}(M)$ .

<span id="page-16-0"></span>Specifically, [Proposition 9](#page-15-5) will be used in the following form.

**Corollary 10** (Navigation constraints). *Consider a consistent algorithm* A *and let*  $M \in M$  *such that*  $Cnf_{\star}(M) \neq \emptyset$ . Then the vector given by

$$
\mu_T(x) := \frac{\mathbb{E}_{s_0}^{\mathbf{M},\mathbb{A}}[N_T(x)] \mathbb{1}(x \notin \mathcal{X}_{\star}(\mathbf{M}))}{\mathbb{E}_{s_0}^{\mathbf{M},\mathbb{A}}\Big[\sum_{x' \notin \mathcal{X}_{\star}(\mathbf{M})} N_T(x')\Big]}
$$

*converges to*  $Inv(M/X_{\star}(M)) \cap \mathcal{P}(X)$  *when*  $T \to \infty$ *.* 

*Proof of [Corollary 10.](#page-16-0)* Since Cnf<sub>\*</sub>(**M**)  $\neq$  0, there exists  $M^{\dagger} \in \text{Cnf}_{\star}(M)$  and  $\max_{x \in \mathcal{X}} KL_x(M||M^{\dagger}) < \infty$ . By [Corollary 7,](#page-13-2) we have

$$
\log(T) \lesssim \mathbb{E}_{s_0}^{\mathbf{M},\mathbb{A}} \Bigg[ \sum_{x \in \mathcal{X}} N_{T+1}(x) \mathrm{KL}_x(\mathbf{M}||\mathbf{M}^{\dagger}) \Bigg] \leq \max_{x \in \mathcal{X}} \Big\{ \mathrm{KL}_x(\mathbf{M}||\mathbf{M}^{\dagger}) \Big\} \mathbb{E}_{s_0}^{\mathbf{M},\mathbb{A}} \Bigg[ \sum_{x \notin \mathcal{X}_{\star}(\mathbf{M})} N_{T+1}(x) \Bigg]
$$

where the second inequality follows from  $M^{\dagger} = M$  on  $\chi_{\star}(M)$ . So  $\mathbb{E}_{s_0}^{M,A}$  $N_{\text{so}}^{\text{M,A}}[\sum_{x \notin \mathcal{X}_{\star}(\text{M})} N_T(x)] = \Omega(\log(T)).$ Moreover, remark that  $X_{\star}(M)$  is closed as the set of recurrent pairs of the policy  $\pi^*$  such that  $\pi^*(-|s)$ is uniform on { $a : (s, a) \in X_{\star}(M)$ } if  $s \in S(X_{\star}(M))$  and uniform on  $\mathcal{A}(s)$  otherwise. Accordingly, we can apply [Proposition 9,](#page-15-5) to see that

$$
\mu'_T(x) := \frac{\mathbb{E}_{s_0}^{\mathbf{M},\mathbb{A}}[N_T(x)] \mathbb{1}(x \notin \mathcal{X}_{\star}(\mathbf{M}))}{\mathbb{E}_{s_0}^{\mathbf{M},\mathbb{A}}\Big[\sum_{x' \notin \mathcal{X}_{\star}(\mathbf{M})} N_T(x')\Big]}
$$

converges to Inv( $M/X_{\star}(M)$ ) as  $T \to \infty$ . The fact that it is a probability vector is obvious.

We now move on to the proof of [Proposition 9.](#page-15-5)

*Proof of [Proposition 9.](#page-15-5)* For conciseness, we write  $\mathbb{E}[-]$  in place of  $\mathbb{E}_{s_0}^{\mathbf{M},\mathbf{A}}$ *M*, <sup>*A*</sup>[−]. Let *f*(*t*) :=  $E[\sum_{x' \notin X_{\pi}} N_t(x')]$ for short. By definition, the states of  $[M] := M/X_\pi$  are subsets of states of the original model M and its pair-space is canonically identical to the one of **M**. Introduce the  $X^c_\pi$ -truncated visit counts:

$$
N_t'(x) := \mathbb{1}(x \notin \mathcal{X}_\pi)N_t(x)
$$

with the induced state-wise visits  $N'_t(s) := \sum_a N'_t(s, a)$ , and in the minor  $N'_t[s] := \sum_{s' \in [s]} N'_t(s')$ . By definition, we have  $\mu_t(s, a) \equiv \mathbb{E}[N_t'(s, a)]f(t)^{-1}$ . Let  $\mu_t(s) := \sum_{a \in \mathcal{A}(s)} \mu_t(s, a) = \mathbb{E}[N_t'(s)]$  and, for  $[s] \in S[M]$  a state of the contraction,  $\mu_t[s] := \sum_{s' \in S} \mu_t(s') = \mathbb{E}[N'_t[s]]$ . Viewing  $N'_t$  as a vector indexed by states of [M], a remarkable property of  $N_t'$  is that it satisfies the quasi-flow property (what goes in is what goes out):

<span id="page-16-1"></span>
$$
N'_{t}[s] = \sum_{s' \in [s]} \sum_{x} N'_{t}(x; s') + \mathbb{1}(S_{0} \in [s]) - \mathbb{1}(X_{t} \in X_{\pi}, S_{t} \in [s]) = \sum_{s' \in [s]} \sum_{a \in \mathcal{A}(s')} N'_{t}(s', a)
$$
(8)

where  $N'_{t+1}(x; s') := 1(x \notin X_{\pi})N_{t+1}(x; s')$ . This is established by induction on  $t \ge 0$ . This is obvious for  $t = 0$ , and for  $t \ge 1$ , we have:

$$
(-) := \sum_{s' \in [s]} \sum_{a \in \mathcal{A}(s')} N'_t(s', a)
$$

V. Boone & OA. Maillard 17 January 23, 2025

$$
\equiv N'_{t}[s] = N'_{t-1}[s] + \mathbb{1}(S_{t} \in [s], X_{t} \notin X_{\pi})
$$
\n
$$
\stackrel{(*)}{=} \mathbb{1}(S_{0} \in [s]) - \mathbb{1}(X_{t-1} \in X_{\pi}, S_{t-1} \in [s]) + \sum_{s' \in [s]} \sum_{x} N'_{t-1}(x; s') + \mathbb{1}(S_{t} \in [s], X_{t} \notin X_{\pi})
$$
\n
$$
= \mathbb{1}(S_{0} \in [s]) + \sum_{s' \in [s]} \sum_{x} N'_{t}(x; s')
$$
\n
$$
- \mathbb{1}(X_{t-1} \in X_{\pi}, S_{t-1} \in [s]) + \mathbb{1}(S_{t} \in [s], X_{t} \notin X_{\pi}) - \mathbb{1}(S_{t} \in [s], X_{t-1} \notin X_{\pi})
$$

where  $(*)$  is obtained by induction. We focus on the RHS:

$$
\alpha = -1(X_{t-1} \in X_{\pi}, S_{t-1} \in [s]) + 1(S_t \in [s], X_t \notin X_{\pi}) - 1(S_t \in [s], X_{t-1} \notin X_{\pi})
$$
  

$$
\stackrel{(\dagger)}{=} -1(X_t \in X_{\pi}, S_t \in [s]).
$$

The equality (†) is shown by distinguishing cases.

- If  $X_{t-1} \in \mathcal{X}_{\pi}$  and  $X_t \in \mathcal{X}_{\pi}$ , then because the states of  $\mathcal{X}_{\pi}$  are closed by playing pairs of  $\mathcal{X}_{\pi}$ , it follows that  $[S_t] = [S_{t-1}]$  correspond to the same recurrent class of  $\pi$ . If  $[S_t] = [S_{t-1}] \neq [s]$ , then we get (†) :  $0 = 0$  and if  $[S_t] = [S_{t-1}] = [s]$ , then (†) :  $-1 = -1$ .
- If  $X_{t-1} \notin \mathcal{X}_{\pi}$  and  $X_t \notin \mathcal{X}_{\pi}$ , then (†) : 0 = 0.
- If  $X_{t-1} \in \mathcal{X}_{\pi}$  and  $X_t \notin \mathcal{X}_{\pi}$ , then similarly  $[S_{t-1}] = [S_t]$ . If equal to [s] then (†) : 0 = 0 and otherwise  $(\dagger)$  :  $0 = 0$ .
- If  $X_{t-1} \notin X_{\pi}$  and  $X_t \in X_{\pi}$ , then  $[S_t]$  and  $[S_{t-1}]$  can be equal or different. If (1)  $[S_t] = [S_{t-1}] = [s]$ , we have (†) : −1 = −1; If (2)  $[S_t] = [S_{t-1}] \neq [s]$ , we have (†) : 0 = 0; If (3)  $[S_t] = [s] \neq [S_{t-1}]$ , we have (†) :  $-1 = -1$ ; And if (4)  $[S_t] \neq [s] = [S_{t-1}]$ , we have (†) :  $0 = 0$ .

So (†) is established the quasi-flow property follows immediately.

Introduce  $\pi'$  the policy of [M] as any state-wise probability distribution with  $\mathbb{E}[N'_t[s]]\pi'_t(a|[s]) =$  $\mathbb{E}[N'_{t}([s], a)]$ , which is uniquely defined when  $\mathbb{E}[N'_{t}[s]] > 0$ . For all  $[s'] \in S[\mathbf{M}]$ , we have:

$$
\sum_{x=(s], a) \in X[M]} \mu_t[s] \pi'_t(x[[s]) p([s']|x) = \sum_{x=(s], a) \in X[M]} \frac{\mathbb{E}[N'_t[s]] \pi'_t(x[[s])}{f(t)} p([s']|x)
$$
\n
$$
= \sum_{x \notin X_{\pi}} \frac{\mathbb{E}[N_t(x)]}{f(t)} p([s']|x)
$$
\n
$$
= \sum_{x \notin X_{\pi}} \sum_{s'' \in [s']} \frac{\mathbb{E}[N_t(x)]}{f(t)} p(s''|x)
$$
\n
$$
= \sum_{x \notin X_{\pi}} \sum_{s'' \in [s']} \frac{\mathbb{E}[N_t(x)[p(s'']x) - \widehat{p}_t(s''|x)] + \mathbb{E}[N_t(x)\widehat{p}_t(s''|x)]}{f(t)}
$$
\n(Lemma A.1) = 
$$
\sum_{x \notin X_{\pi}} \sum_{s'' \in [s']} \frac{\mathbb{E}[N_{t+1}(x; s')]}{f(t)} + o(1 + \frac{\mathbb{E}[N_t(x)]}{f(t)})
$$
\n
$$
= \sum_{x \notin X_{\pi}} \sum_{s'' \in [s']} \frac{\mathbb{E}[N_{t+1}(x; s'')]}{f(t)} + o(1)
$$
\n
$$
= \sum_{x \notin X_{\pi}} \sum_{s'' \in [s']} \frac{\mathbb{E}[N'_{t+1}(x; s'')]}{f(t)} + o(1)
$$
\n(quasi-flow property (8)) = 
$$
\sum_{s'' \in [s']} \frac{\mathbb{E}[N'_{t+1}(s'')]}{f(t)} + o(1) = \mu[s'] + o(1).
$$

V. Boone & OA. Maillard 18 January 23, 2025

We have shown that for all  $[s] \in S[M], \sum_{x} \mu_t(x) p([s]|x) = \mu_t[s] + o(1)$ . Written differently, introducting  $\varphi(\mu) := \max_{[s] \in S[M]} |\mu[s] - \sum_{x} \mu(x) p([s]|x)|$ , we have shown that  $\varphi(\mu_t) \to 0$ . The function  $\varphi$  is continuous,  $P(X)$  is compact and  $\varphi(\mu) = 0$  is equivalent to  $\mu \in Inv(M/X_{\pi})$ . Because Inv( $M/X_{\pi}$ ) is closed in  $P(X)$ , we deduce that  $\varphi(\mu_t) \to 0$  implies that  $\mu_t$  converges to Inv( $\mathbf{M}/X_\pi$ ).

This concludes the proof.  $\Box$ 

## <span id="page-18-0"></span>4.4 A regret lower bound with contracted invariant measures

<span id="page-18-2"></span>We start by proving the following version of the lower bound. In the next section, we will show that it is equivalent to [Theorem 3.](#page-9-0)

**Theorem 11.** Let **M** ∈ *M*. Regardless of the initial state  $s_0$  ∈ *S*, the regret of every consistent *algorithm* A *satisfies* lim  $\inf_{T\to\infty}$  Reg(*T*; A, **M**, *s*<sub>0</sub>)  $\log^{-1}(T) \ge K(M)$  *where*  $K(M) \in [0, ∞]$  *is equal to:* 

$$
\inf \left\{ \sum_{x \in \mathcal{X}} \mu(x) \Delta_{\star}(x) : \mu \in \text{Inv}(\mathbf{M}/\mathcal{X}_{\star}(\mathbf{M})) \text{ and } \inf_{\mathbf{M}^{\dagger} \in \text{Cnf}_{\star}(\mathbf{M})} \left\{ \sum_{x \in \mathcal{X}} \mu(x) \text{KL}_{x}(\mathbf{M} || \mathbf{M}^{\dagger}) \right\} \ge 1 \right\} \tag{LB'_{\star}}
$$

The only difference with [Theorem 3](#page-9-0) is that the condition " $\mu \in Inv(M)$ " of Theorem 3 is changed to the less restrictive " $\mu \in Inv(M/X_{\star}(M))$ " in [Theorem 11.](#page-18-2)

*Proof of [Theorem 11.](#page-18-2)* Consider a consistent algorithm A and pick  $M \in \mathcal{M}$ . Introduce the quantities:

$$
\mu_T(x) := \frac{\mathbf{1}(x \notin \mathcal{X}_\star(\mathbf{M})) \mathbb{E}_{s_0}^{\mathbf{M},\mathbb{A}}[N_{T+1}(x)]}{\mathbb{E}_{s_0}^{\mathbf{M},\mathbb{A}}\Big[\sum_{x' \notin \mathcal{X}_\star(\mathbf{M})} N_{T+1}(x')\Big]} \quad \text{and} \quad \lambda_T := \frac{\mathbb{E}_{s_0}^{\mathbf{M},\mathbb{A}}\Big[\sum_{x \notin \mathcal{X}_\star(\mathbf{M})} N_{T+1}(x)\Big]}{\log(T)}
$$

and further introduce  $\psi(T) := \text{Reg}(T; \mathbf{M}, \mathbb{A}, s_0) \log(T)^{-1}$ . Note that  $\psi(T) = \lambda_T \sum_{x \notin \mathcal{X}_{\star}(\mathbf{M})} \mu_T(x) \Delta_{\star}(x; \mathbf{M})$ .

Let  $L := \liminf_{T \to \infty} \psi(T)$  and let  $(T_n)$  a sequence with  $\lim \psi(T_n) = L$ . Remark that  $\limsup \lambda_{T_n} \le$  $\alpha L$  as a consequence of [Lemma 8,](#page-13-3) where  $\alpha > 0$  is the constant provided by [Lemma 8.](#page-13-3) Up to extracting a subsequence of  $(T_n)$ , we can assume that  $\lambda_{T_n}$  converges to some  $\Lambda \in [0, \alpha L]$ . Similarly, since  $(\mu_T)$ evolves within the compact space  $[0, 1]^X$ , we can assume that  $\mu_{T_n}$  converges to some  $\mu \in [0, 1]^X$  up to extracting a subsequence of  $(T_n)$ . By [Corollary 10,](#page-16-0) every limit point of  $(\mu_T)$  belongs to Inv( $\mathbf{M}/X_{\star}(\mathbf{M})$ ) which is closed, so  $\mu \in Inv(M/X_{\star}(M))$ . By [Proposition 4,](#page-10-3) we further have

<span id="page-18-3"></span>
$$
\forall T \ge 1, \quad \inf_{\mathbf{M}^{\dagger} \in \text{Cnf}_{\star}(\mathbf{M})} \left\{ \lambda_T \sum_{x \in \mathcal{X}} \mu_T(x) \text{KL}_x(\mathbf{M}||\mathbf{M}^{\dagger}) \right\} \ge 1 \tag{9}
$$

so the limit  $\Lambda \mu \in \text{Inv}(\mathbf{M}/X_{\star}(\mathbf{M}))$  must satisfy [\(9\)](#page-18-3) as well. In tandem with  $L = \Lambda \sum_{x \in X} \mu(x) \Delta_{\star}(x; \mathbf{M})$ , we conclude that  $L > K(M)$ .

Remark 1. *The quantity K*(M) *actually depends on* M*. In general,* M *is obvious in the context but whenever it is not, we write*  $K(M;M)$  *to make the dependency clear.* 

### <span id="page-18-1"></span>4.5 A regret lower bound without contracted invariant measures

<span id="page-18-4"></span>To finally prove [Theorem 3,](#page-9-0) we show that the contraction  $\mu \in Inv(M/X_{\star}(M))$  can be dropped to  $\mu \in Inv(M)$  in the lower bound. While minors play a central role in the decomposition of the execution consistent learning agents, they are eventually dropped in the final result, hence slightly simplifying the lower bound. More precisely, by using that  $\Delta_{\star}(x)$  is null for  $x \in \mathcal{X}_{\star}(\mathbf{M})$ , invariant measures of the minor  $M/X_{\star}(M)$  can be **represented** by invariant measures of the initial model M, leading to:

**Proposition 12** (Removing the contraction). *The regret lower bound K(M) is equal to K*<sup> $_{\star}$ </sup>(M):

$$
K(\mathbf{M}) = K_{\star}(\mathbf{M}) = \inf \left\{ \sum_{x \in \mathcal{X}} \mu(x) \Delta_{\star}(x) : \mu \in \text{Inv}(\mathbf{M}) \text{ and } \inf_{\mathbf{M}^{\dagger} \in \text{Cnf}_{\star}(\mathbf{M})} \left\{ \sum_{x \in \mathcal{X}} \mu(x) \text{KL}_{x}(\mathbf{M} || \mathbf{M}^{\dagger}) \right\} \ge 1 \right\}.
$$
 (10)

This is a direct consequence of the following remarkable result.

**Lemma 13.** *Denote*  $u|_{X\setminus X_*(M)}$  *the truncation of*  $u \in \mathbb{R}^X$  *to pairs of*  $X \setminus X_*(M)$  *and extend the notations* to subsets of  $\mathbb{R}^X$ . Then  $\text{Inv}(\mathbf{M})|_{X\setminus X_*(\mathbf{M})} = \text{Inv}(\mathbf{M}/X_*(\mathbf{M}))|_{X\setminus X_*(\mathbf{M})}$ .

*Proof.* Since Inv( $M/X_{\star}(M)$ )  $\supseteq$  Inv(M), one inclusion is obvious and we focus on the other. Up to iterating the process on the communicating components of  $\mathcal{X}_{\star}(\mathbf{M})$ , we assume that  $\mathcal{X}_0 := \mathcal{X}_{\star}(\mathbf{M})$ induces a communicating model  $M|_{X_0}$ . Pick  $[\mu] \in Inv(M/X_0)$ . We show that there  $\mu$  such that  $[\mu](x) = \mu(x)$  for  $x \notin X_0$ . Denote  $S_0 := \{s : \exists a, (s, a) \in X_0\}$  the states in which  $X_0$  is rooted. In [M] :=  $M/X_0$ , we have  $[p]([S_0]|x_0) = 1$  for all  $x_0 \in X_0$  so that we can assume that  $[\mu](x_0) = 0$ without loss of generality. For  $s_0 \in S_0$ , introduce

$$
\alpha(s) := \sum_{a \in \mathcal{A}(s_0)} [\mu](s_0, a) - \sum_{x \in \mathcal{X}} [\mu](x) \mathbf{p}(s_0 | x).
$$
 (11)

Observe that  $\sum_{s_0 \in S_0} \alpha(s_0) = 0$  since [ $\mu$ ] is an invariant measure of [**M**] = **M**/ $X_0$ . It is enough to find  $\mu_0 \in \mathbb{R}^{\mathcal{X}_0}$  such that

<span id="page-19-1"></span>
$$
\mu_0 \ge 0
$$
 and  $\forall s_0 \in S_0$ ,  $\sum_{x_0 \in X_0} \mu_0(x_0) \mathbf{p}(s_0 | x_0) = \sum_{a_0:(s_0,a_0) \in X_0} \mu(s_0, a_0) + \alpha(s_0);$  (12)

then  $\mu \in \mathbb{R}^X$  given by  $\mu(x) = \mu_0(x)$  if  $x \in X_0$  and  $[\mu](x)$  if  $x \notin X_0$  will be solution. Assume that [\(12\)](#page-19-1) has no solution. By Farkas' Lemma, there exists  $v_0 \in \mathbb{R}^{S_0}$  such that:

<span id="page-19-2"></span>
$$
\sum_{s_0 \in S_0} \nu_0(s_0) \alpha(s_0) < 0 \quad \text{and} \quad \forall (s_0, a_0) \in X_0, \ \sum_{s'_0 \in S_0} \nu_0(s_0) (\mathbf{p}(s'_0 | s_0, a_0) - \mathbb{1}(s'_0 = s_0)) \ge 0. \tag{13}
$$

Let  $\pi_0$  the policy picking its actions uniformly in  $X_0$  from  $S_0$ . The second condition can be rewritten as  $\mathbf{p}_{\pi_0}(\mathbf{M}|_{X_0})v_0 \ge v_0$  so by induction,  $\overline{\mathbf{p}}_{\pi_0}(\mathbf{M}|_{X_0})v_0 \ge v_0$  where  $\overline{\mathbf{p}}_{\pi_0} := \lim_{T \to \infty} \frac{1}{T} \sum_{t=1}^T \mathbf{p}_{\pi_0}^{t-1}$ . Because  $X_0$  is communicating,  $\overline{\mathbf{p}}_{\pi_0}(\mathbf{M}|_{X_0})$  has full support and  $v_0 \in \mathbb{R}e$ . But  $\sum_{s_0 \in S_0} \alpha(s_0) = 0$  so  $\sum_{s_0 \in S_0} v_0(s_0) \alpha(s_0) =$ 0, contradicting [\(13\)](#page-19-2).

Combining [Proposition 12](#page-18-4) and [Theorem 11,](#page-18-2) [Theorem 3](#page-9-0) follows immediately.

#### <span id="page-19-0"></span>4.6 Why navigation constraints are mandatory

To conclude this section, we discuss a simple example that illustrates the importance of navigation constraints.

On [Figure 3,](#page-20-2) we present a two-state Markov decision process M with deterministic transitions and Bernoulli rewards.  $X_{\star}(M)$  consists in the loop from  $s_1$  to itself, scoring  $\frac{2}{3}$  in average. The other circle, between  $s_1$  and  $s_2$ , only scores  $\frac{1}{2}$  in average. With navigation constraints, we see that every  $\mu \in Inv(M)$  satisfies  $\mu(s_1 \rightarrow s_2) = \mu(s_2 \rightarrow s_1)$ ; We can numerically evaluate  $K(M)$  and obtain  $\mu^*(s_1 \rightarrow s_2) \approx 7.704$  and  $K(M) \approx 2.6$ . Meanwhile, if one ignores navigation constraints (refer to the last paragraph of [Section 4.2\)](#page-12-0), then the transition  $s_2 \rightarrow s_1$  can be explored arbitrarily more than  $s_1 \to s_2$ , while it is free to pick because it scores  $\frac{2}{3} = \mathbf{g}_\star$ . Therefore, one puts infinitely much mass on  $s_2 \rightarrow s_1$  and has less information to gather on  $s_1 \rightarrow s_2$ , leading to the navigation-less lower bound of  $\approx$  1.4, which is significatively far from *K*(**M**).

V. Boone & OA. Maillard 20 January 23, 2025



<span id="page-20-2"></span>Figure 3: An example of a two-state deterministic Markov decision process with Bernoulli rewards where the navigation constraints are necessary to obtain the right regret lower bound.

## <span id="page-20-0"></span>5 Computational intractability of the regret lower bound

In this section, we discuss the computational difficulties related to the regret lower bound  $K_{\star}(\mathbf{M};\mathcal{M})$ of [Theorem 3,](#page-9-0) given by:

$$
\inf \Biggl\{ \sum_{x \in \mathcal{X}} \mu(x) \Delta_{\star}(x) : \mu \in \text{Inv}(\mathbf{M}) \text{ and } \forall \mathbf{M}^{\dagger} \in \text{Cnf}_{\star}(\mathbf{M}), \sum_{x \in \mathcal{X}} \mu(x) \text{KL}_{x}(\mathbf{M} || \mathbf{M}^{\dagger}) \ge 1 \Biggr\}.
$$

While the objective function is linear, the unknown  $\mu$  must satisfy a continuum of constraints that are non-convex in general. Behind the computation of  $K_{\star}(M;M)$  hides a question that is even simpler: Given an exploration measure  $\mu \in Inv(M)$ , is it informative enough? Does it satisfy the information constraint  $\inf_{\mathbf{M}^{\dagger} \in \text{Cnf}_*(\mathbf{M})} \sum_{x \in \mathcal{X}} \mu(x) \mathbf{KL}_x(\mathbf{M}||\mathbf{M}^{\dagger}) \geq 1$ , i.e., is it a point of the feasible region of [\(LB\)](#page-10-1)? If the constraint  $\mu \in Inv(M)$  oppose no difficulty in general because Inv(M) is a polytope, the second constraint is more troublesome. In the sequel, we show that if  $M$  is discrete, then checking that an exploration measure is informative enough is computationally difficult [\(Section 5.1\)](#page-20-1) and that the estimation of  $K_{\star}(\mathbf{M}; \mathcal{M})$  is even harder [\(Section 5.2\)](#page-22-0).

**Remark 2.** *The lower bound*  $K_{\star}(M; M)$  *depends on the ambient space* M, and the computational *hardness of estimating K*<sub>*x*</sub>(**M**; *M*) *depends both on* **M** *and M*. The regret lower bound  $K_{\star}(\mathbf{M}; \mathcal{M})$ *may actually be easy to estimate if* M *and*/*or* M *have a special structure, see [Section 6.](#page-23-0)*

#### <span id="page-20-1"></span>5.1 CONFUSING-MODEL: Information tests are NP-complete

As motivated earlier, a simple question that arises from  $(LB)$  is, given a measure  $\mu$ , how easy it is to check the condition  $\forall M^{\dagger} \in \text{Cnf}_{\star}(M), \sum_{x} \mu(x)KL_{x}(M||M^{\dagger}) \geq 1$ . In this paragraph, the problem is shown to be coNP difficult, see the problem CONFUSING-MODEL thereafter.

CONFUSING-MODEL: *Given a space of Markov decision processes* M*, a reference model*  $M \in \mathcal{M}$  *and a pair of scalars*  $\alpha, \beta \geq 0$ *, is there a*  $M^{\dagger} \in \mathcal{M}$  *such that:* 

$$
\sum_{x} \mu(x) \text{KL}_{x}(\mathbf{M}||\mathbf{M}^{\dagger}) < \alpha \text{ and } \mathbf{g}_{\star}(\mathbf{M}^{\dagger}) > \beta,\tag{14}
$$

*where* µ *is an invariant probability measure of* M*?*

Out of simplicity and to essentialize the problem, CONFUSING-MODEL does not require that  $M^{\dagger}$  ∈  $Cnf_{\star}(M;M)$ . Imposing that  $M^{\dagger} \in \text{Cnf}_{\star}(M;M)$  does not change the computational hardness of the problem, see [Remark 3.](#page-22-2)

To be formal, the way the space of MDPs may be fed to an algorithm must be specified. If M contains polynomially many models and if every element of it is encoded in polynomial size, then

the enumeration of  $M$  is polysized — In this case, it is clear that CONFUSING-MODEL is polynomial. Therefore, we focus on spaces  $M$  that cannot be enumerated in polynomial time. We assume that  $M$  is given by its state-action space together with polynomially many polynomial constraints on its kernel and reward functions. Then, we have the following result:

#### <span id="page-21-0"></span>Theorem 14. CONFUSING-MODEL *is NP-complete.*

We provide a reduction from the Knapsack Problem (KP), where the choice of  $M^{\dagger}$  modelizes a choice of items,  $g_{\star}(M^{\dagger})$  corresponds to the aggregate value of that choice and  $\sum_{x} \mu(x)$  KL<sub>x</sub>(M||M<sup>†</sup>) accounts for the required capacity to carry the chosen items. We provide a high level overview of the construction and leave the careful tuning of constants to [Appendix D.](#page-47-0)

*Proof sketch of [Theorem 14.](#page-21-0)* Proving that it is NP is immediate, because the optimal gain of a MDP is the solution of a LP [\(Puterman,](#page-37-9) [2014,](#page-37-9) §8.8) hence given  $M^{\dagger}$ , checking  $\sum_{x} \mu(x)KL_{x}(M||M^{\dagger}) < \alpha$ and  $\mathbf{g}_{\star}(\mathbf{M}^{\dagger}) > \beta$  is done in polynomial time. The point is to show the NP-hardness.

To prove that the problem is NP-hard, it is reduced from the Knapsack Problem (KP). Recall that an instance of KP is given by a collection of *n* items of integer values  $\{v_1, \ldots, v_n\}$  and integer weights  $\{w_1, \ldots w_n\}$ , as well as a capacity *W* and a value threshold *V*, both integers. The problem is to determine whether there exists  $\mathcal{K} \subseteq [n]$  such that  $\sum_{k \in \mathcal{K}} w_k \leq W$  and  $\sum_{k \in \mathcal{K}} v_k \geq V$ .

Fix  $\varepsilon$ ,  $\sigma$ ,  $\delta$  > 0 to be tuned later on. Given an instance of KP, consider the Markov decision process <sup>M</sup> whose structure is given by *<sup>n</sup>* (choose *<sup>k</sup>*) 3-state widgets connected in a ring fashion.



Figure 4: The (Choose k) widget, where  $\sigma_k^2$  $\frac{2}{k} := \frac{\sigma^2}{w_k}$  $\frac{\sigma^2}{w_k}$ . The labels N(*x*, *y*)\$ are the (Gaussian) reward distributions.

From the state (Choose *k*) are two actions: The top action that is likely to go to (Pick *k*) that shall be referred to as action Pick, and the bottom action called SKIP. From every over state, there is a single action that denoted  $*$ . A (deterministic) policy of M is analogue to a subset  $\mathcal{K} \subseteq \{1, ..., n\}$ , written  $\pi_{\mathcal{K}}$ , which is given by  $\pi_K$  (PICK|CHOOSE *k*) := 1( $k \in K$ ). We get:

$$
\mathbf{g}(\pi_{\mathcal{K}}) = \frac{1}{2n} \left( \frac{1}{2} \sum_{k=1}^n v_k + \sum_{k \in \mathcal{K}} \left( \left( \frac{1}{2} - \varepsilon \right) v_k + \delta \right) \right) = \frac{||v||_1}{4n} + \frac{1}{2n} \sum_{k \in \mathcal{K}} \left( \left( \frac{1}{2} - \varepsilon \right) v_k + \delta \right).
$$

The key idea is that every policy  $\pi_{\mathcal{K}}$  can equivalently be seen as a single-action Markov decision process  $M_{\mathcal{K}}$ , i.e., the model of a policy over the state-space

 $S := \{$ **(CHOOSE k)**, **(PICK k)**, **(SKIP k)** :  $k = 1, ..., n$ .

The choice of an action is equivalently the choice of a kernel distribution. The set of stationary deterministic policies of M, denoted  $\Pi^{\text{SD}}(\mathcal{M})$ , can therefore be seen as the set of Markov reward processes  $M^{\text{SD}} := \{M_{\mathcal{K}} : \mathcal{K} \subseteq \{1, ..., n\}\}\$ . Provided that the parameters  $\varepsilon, \sigma, \delta$  are polynomial in  $n, v, w$ , this (structured) set of models is described in polynomial size in  $n, v, w$ . Then, carefully choosing  $\varepsilon$ ,  $\sigma$  and  $\delta$  relatively to *V* and *W*, we can make it so that the gain of a model  $M_K$  is directly related to the collected value  $\sum_{k \in \mathcal{K}} v_k$ , while the divergence  $\sum_x \mu(x)KL_x(\mathbf{M}||\mathbf{M}^{\dagger})$  is directly related to

the weight  $\sum_{k \in \mathcal{K}} w_k$ . Designing  $\alpha$  and  $\beta$  relatively to *W* and *V* respectively, we manage to encode the Knapsack instance with

$$
\exists? \mathcal{K} \subseteq [n], \quad \sum_{x} \mu(x) \text{KL}_x(\mathbf{M}||\mathbf{M}_{\mathcal{K}}) \le \alpha \text{ and } \mathbf{g}_\star(\mathbf{M}_{\mathcal{K}}) \ge \beta.
$$

<span id="page-22-2"></span>Details are found in [Appendix D.](#page-47-0)

**Remark 3.** *In* CONFUSING-MODEL,  $M^{\dagger}$  *is not required to belong to* Cnf<sub>★</sub>( $M$ ;  $M$ ). We may consider *the problem* CONFUSING-MODEL\* *that adds the constraint that*  $M^{\dagger} \in \text{Cnf}_{\star}(M; M)$ *. The reduction from* KP provided in the proof of [Theorem 3](#page-9-0) would work similarly, by adding a loop on  $M_{\odot}$  with mean *reward* <sup>β</sup>*. More specifically, pick the state (*Choose <sup>0</sup>*) and add a special action* <sup>∗</sup> *from (*Choose <sup>0</sup>*) with*  $m$ (Choose 0; \*) =  $\beta$  *and*  $p$ (Choose 0|Choose 0, \*) = 1 *to all*  $M_{\mathcal{K}}$ *. Then, all elements*  $M^{\dagger} \in \mathcal{M}$ *coincide to each over on*  $\mathcal{X}_{\star}(\mathbf{M}_{\varnothing}) = \{(\text{Choose } 0, \ast)\}.$ 

### <span id="page-22-0"></span>5.2 REGRET: Checking the regret lower bound is co-NP-hard

The computation of the regret lower bound seems essentially harder than CONFUSING-MODEL. However, the computational hardness of CONFUSING-MODEL does not directly propagate to the estimation of  $K_{\star}(M;M)$ . If  $\mu, \alpha, \beta$  are close to the values corresponding to the solution of regret optimization problem, is the problem still difficult? Then answer remains positive so that the computation of the regret lower bound is computationally hard.

REGRET: *Given a space of MDPs M, a reference model*  $M \in M$  *and a scalar*  $\rho \geq 0$ *, does there exists a*  $\mu \in Inv(\mathbf{M}/X_{\text{+}}(\mathbf{M}))$  *such that* 

$$
\sum_{x \in \mathcal{X}} \mu(x) \Delta_{\star}(x; \mathbf{M}) \le \rho \text{ and } \inf_{\mathbf{M}^{\dagger} \in \mathrm{Cnf}_{\star}(\mathbf{M}; \mathcal{M})} \left\{ \sum_{x \in \mathcal{X}} \mu(x) \mathrm{KL}(\mathbf{M}(x) || \mathbf{M}^{\dagger}(x)) \right\} \ge 1? \tag{15}
$$

<span id="page-22-1"></span>We have the following result.

Theorem 15. *Checking a solution of* REGRET *is co-NP complete.*

We suggest a reduction from the co-knapsack problem that refines the construction of the proof of [Theorem 14.](#page-21-0) Again, we focus here on the construction and leave the details to [Appendix D.](#page-47-0)

*Proof.* We provide a reduction from the co-knapsack problem (co-KP), which is coNP-complete because KP is NP-complete. An instance of co-KP is given by a collection of *n* items of integer values  $\{v_1, \ldots, v_n\}$  and integer weights  $\{w_1, \ldots, w_n\}$ , as well as a capacity and a value threshold *V*, both integers. The problem is to determine if, for all  $K \subseteq [n]$ , we either have  $\sum_{k \in K} w_k \ge W$  or  $\sum_{k \in K} v_k \le V$ .

The reduction is very similar to CONFUSING-MODEL's. Fix  $\varepsilon, \sigma, \delta, \theta$  to be tuned later on and consider an instance of co-KP. Consider the MDP M whose structure is as given by [Figure 5.](#page-23-2)

The change regarding the reduction of CONFUSING-MODEL is the state (0), in between (Choose *n*) and (Choose 1). From (0) you can either loop with the action Loop scoring  $\theta$ , or go to (Choose 1) with the action Cycle scoring 0, hence entering the big cycle. The state (0) is a special state. From the state (Choose  $k$ ) are two actions: The top action that is likely to go to (Pick  $k$ ) that we shall refer to as action PICK, and the bottom action that we shall call SKIP. From every over state, there is a single action that denoted ∗. The special policy looping on (0) is denoted  $\pi^*$  and will model the optimal policy later on. The other (deterministic) policies of M are analogue to a subset  $\mathcal{K} \subseteq \{1, ..., n\}$ , written  $\pi_{\mathcal{K}}$ , and are given  $\pi_K$ (PICK|CHOOSE k) :=  $\mathbb{1}(k \in \mathcal{K})$  with  $\pi$ (CYCLE|0) = 1. We get:

$$
\mathbf{g}(\pi_{\mathcal{K}}) = \frac{1}{2(n+1)} \left( \frac{1}{2} \sum_{k=1}^{n} v_k + \sum_{k \in \mathcal{K}} \left( \left( \frac{1}{2} - \varepsilon \right) v_k + \delta \right) \right) = \frac{\|v\|_1}{4(n+1)} + \frac{1}{2(n+1)} \sum_{k \in \mathcal{K}} \left( \left( \frac{1}{2} - \varepsilon \right) v_k + \delta \right).
$$

V. Boone & OA. Maillard 23 January 23, 2025



<span id="page-23-2"></span>Figure 5: Embedding a knapsack problem in a Markov decision process.

Every policy  $\pi_{\mathcal{K}}$  can equivalently be seen as a single-action Markov decision process  $M_{\mathcal{K}}$ . The choice of an action is equivalently the choice of a kernel distribution. The set of stationary deterministic policies of M, denoted  $\Pi^{\text{SD}}(\mathcal{M})$ , can therefore be seen as the set of Markov reward processes  $M^{\text{SD}} := \{M_K : K \subseteq \{1, \ldots, n\}\}\$ . The Markov decision process of reference is  $M_{\varnothing}$  (where the unique optimal policy is looping at the special state 0) of which every invariant measure is uniform, making the lower bound easier to write. Following that observation, the remaining of the proof is essentially similar to [Theorem 14.](#page-21-0) Details are found in [Appendix D.](#page-47-0)

Discussion. If we focus on convex model classes, the proof of intractability fails. The previous reduction doesn't work anymore, because by taking the convex hull of  $\mathcal{M}^{\text{SD}}$ , we obtain a space that is very close to the space of randomized policies of M instead of deterministic ones, which is essential in the proof. Also, the rational relaxed Knapsack problem is a linear program, so is solvable in polynomial time — but the optimization problem related to  $\mathcal{M}^{SR}$  is not exactly the relaxation of the reduced KP, hence we cannot easily claim that  $K(M; Conv(M^{SD}))$  is tractable. It is only natural to raise the following question.

Open problem. *If* <sup>M</sup> *is convex,*[4](#page-23-3) *does* REGRET *remain computationally di*ffi*cult?*

## <span id="page-23-0"></span>6 Instanciation of the lower bound in classical settings

According to [Theorem 15,](#page-22-1)  $K_{\star}(M;M)$  is computationallly difficult to estimate in general. However, in many scenarios, the environment of interest  $M$  or the considered class of environments  $M$  have special structures that make the regret lower bound easier to describe. Alternative descriptions of  $K_{\star}(\mathbf{M};\mathcal{M})$  can ease the design of asymptotically optimal learning agents.

In this section, we discuss such examples, such as multi-armed bandits, ergodic models, known dynamics problems and beyond. Our bound is compared to existing results in the literature, and we discuss how the optimization problems  $(LB)$  and  $(LB')$  can be decomposed both in their navigation constraint " $\mu \in Inv(M)$ " or " $\mu \in Inv(M/X_{\star}(M))$ " as well as in their information constraint " $\forall M^{\dagger} \in$  $\text{Cnf}_{\star}(\mathbf{M}), \sum_{x} \mu(x) \text{KL}_x(\mathbf{M}||\mathbf{M}^{\dagger}) \ge 1$ ".

## <span id="page-23-1"></span>6.1 Example: Multi-armed bandits

Instances of multi-armed bandits are equivalent to state-less Markov decision processes, i.e., with pair space  $X = \{1\} \times \{1, ..., A\}$ . In this paragraph, we fix  $X = \{1\} \times \{1, ..., A\}$  and let M the space of MDPs with Bernoulli rewards and pair space X, i.e.,  $M \cong \bigcup_{m \in [0,1]^X} \bigotimes_x \text{Ber}(\mathbf{m}_x)$ .

<span id="page-23-3"></span><sup>4</sup> e.g., a polyhedron.

Given  $M \in \mathcal{M}$ , a policy is a choice of action *a* (or **arm**) and its gain **m**(1, *a*), so the gap associated to the pair  $x \equiv (1, a)$  is  $\Delta_{\star}(x) = \max(m) - m(x)$ . We see that Inv(M) =  $\mathbb{R}^{\chi}$  hence multi-armed bandits have trivial navigational structure. Moreover, confusing models  $M^{\dagger} \in \text{Cnf}_{\star}(M)$  are precisely models such that  $\exists x \notin \mathcal{X}_\star(\mathbf{M})$  such that  $\mathbf{m}^\dagger(x) > \max(\mathbf{m}) = \mathbf{g}_\star(\mathbf{M})$ . Combined, [Theorem 3](#page-9-0) can be rewritten as:

$$
K_{\star}(\mathbf{M};\mathcal{M}) = \inf \Biggl\{ \sum_{x \in \mathcal{X}} \mu(x) \Delta_{\star}(x;\mathbf{M}) : \mu \in \mathbb{R}_{+}^{\mathcal{X}} \text{ and } \forall \mathbf{M}^{\dagger} \in \mathrm{Cnf}_{\star}(\mathbf{M}), \sum_{x \in \mathcal{X}} \mu(x) \mathrm{kl}(\mathbf{m}(x)||\mathbf{m}^{\dagger}(x)) \geq 1 \Biggr\}.
$$

Remark that any  $M^{\dagger} \in \text{Cnf}_{\star}(M)$  can be simplified into a  $M^{\ddagger} \in \text{Cnf}_{\star}(M)$  where M and  $M^{\ddagger}$  only differ at one pair x (the suboptimal pair of M that is made optimal in  $M^{\ddagger}$ ), consisting in any pair such that  $\mathbf{m}^{\dagger}(x)$  > max(m). Also, it follows Cnf<sub>\*</sub>(M)  $\neq \emptyset$  if, and only if max(m) < 1 leading to the well-known interior condition "max(**m**) < 1". Using the continuity of the function  $\mathbf{m}^{\dagger}(x) \mapsto k\mathbf{l}(\mathbf{m}(x)||\mathbf{m}^{\dagger}(x))$  on (0, 1), we retrieve the celebrated regret lower bound of [Lai and Robbins](#page-36-0) [\(1985](#page-36-0)).

<span id="page-24-2"></span>Corollary 16 [\(Lai and Robbins](#page-36-0) [\(1985\)](#page-36-0)). *Let* M *the space of MDPs with Bernoulli rewards and pair space x. Let*  $M \in \mathcal{M}$  *such that*  $max(m) < 1$ *. Then:* 

<span id="page-24-3"></span>
$$
K_{\star}(\mathbf{M}; \mathcal{M}) = \sum_{x \in \mathcal{X}} \frac{\Delta_{\star}(x; \mathbf{M})}{\mathrm{kl}(\mathbf{m}(x) || \max(\mathbf{m}))}.
$$
 (16)

Discussion. While [Corollary 16](#page-24-2) is specific to bandits with Bernoulli rewards, it can be straightfully generalized to larger class of bandits (single parameter exponential families or semi-bounded rewards) in which case the denominator  $kl(\mathbf{m}(x)|| \max(\mathbf{m}))$  is changed to  $\inf \{KL(\mathbf{r}(x)||\mathbf{r}^\dagger(x)) : \mathbf{m}^\dagger(x) >$ max(**m**)} where  $\mathbf{r}^{\dagger}(x)$  goes other the possible reward distribution on the pair *x*.

Several observations can be made regarding [\(16\)](#page-24-3).

- (1) The regret lower bound has a closed-form expression that can easily be evaluated.
- (2) Exploration constraints are trivial in multi-armed bandits  $Inv(M) = \mathbb{R}_{+}^{X}$ .
- (3) Information constraints are pair-wisely decoupled (or **indexed**) and are equivalent to | $X$ | linear constraints on  $\mu$ , all of the form  $\mu(x) \geq (kl(m(x)||max(m)))^{-1}$ .

The properties (1-3) are not always satisfied. As a matter fact, (1) and (3) may fail when considering  $K_{\star}(\mathbf{M}; \mathcal{M}')$  for  $\mathcal{M}' \subsetneq \mathcal{M}$  (structured bandit problems). Meanwhile, (2) only depends on **M** rather than M. All together, these properties are arguably what makes multi-armed bandits significatively easier to learn than Markov decision processes. However, multi-armed bandits are not the only classes of model spaces with such properties.

### <span id="page-24-0"></span>6.2 Example: (Optimally) Recurrent models, or navigation-free models

The property (2) in [Section 6.1](#page-23-1) is written as  $Inv(M) = \mathbb{R}^X_+$ , but according to [\(LB\)](#page-10-1) and [\(LB](#page-18-3)'<sub>\*</sub>), we could also see it as  $Inv(M/X_{\star}(M)) = \mathbb{R}_{+}^{X}$ . This property only depends on M and will be referred to as the **navigation-free** property, because the minor  $M/X_{\star}(M)$  is a bandit. When the environment is navigation-free, then one can commute between any pair with zero cost (and conversely). This motivates the definition below.

<span id="page-24-1"></span>Definition 9. *We say that a model* M *is optimally recurrent if there exists a gain optimal policy* π ∗ *whose recurrent states are S; or equivalently, if*  $X_{\star}(M)$  *covers all the states of* M; *or equivalently again, if*  $X_*(M) = X_{\dot{x}}(M)$ .

By definition, M is optimally recurrent if, and only if  $M/X_{\star}$  is state-less. For instance, ergodic models are optimally recurrent. The navigation and information constraints can be heavily simplified when the model is optimally recurrent. Given  $M \in \mathcal{M}$  an optimally recurrent model and  $(s, a) \in$  $X$ <sub>−</sub>(M), denote:

$$
C(\mathbf{M}, s, a) := \inf_{\tilde{\mathbf{r}}_{s,a}, \tilde{\mathbf{p}}_{s,a}} \{ KL(\mathbf{r}_{s,a} || \tilde{\mathbf{r}}_{s,a}) + KL(\mathbf{p}_{s,a} || \tilde{\mathbf{p}}_{s,a}) : \tilde{\mathbf{m}}(s,a) + \tilde{\mathbf{p}}(s,a) \mathbf{b}_{\star} > \mathbf{g}_{\star}(s) + \mathbf{b}_{\star}(s) \}
$$
(17)

<span id="page-25-1"></span>where  $\mathbf{g}_{\star}$  and  $\mathbf{b}_{\star}$  are respectively the optimal gain and bias vectors of M.

Proposition 17 (Lower bound for optimally recurrent models). *Assume that* M *the space of all models with state-action space*  $X$ *. If*  $M \in M$  *is an optimally recurrent model, then* 

$$
K_{\star}(\mathbf{M}) = \sum_{x \notin X_{\star}(\mathbf{M})} \frac{\Delta_{\star}(x)}{C(\mathbf{M}, x)}.
$$
 (18)

*Proof of [Proposition 17.](#page-25-1)* When **M** is optimally recurrent,  $M/X_{\star}(M)$  is a single-state Markov decision process, hence Inv $(M/X_{\star}(M)) = \mathbb{R}^X_+$  meaning that the navigation constraints are trivial. We now simplify the information constraints using a policy improvement argument which is similar to [Burnetas and Katehakis](#page-35-0) [\(1997](#page-35-0)). Let  $\pi^* \in \Pi^*(M)$  with recurrent class S and pick a confusing model  $M^{\dagger} \in \text{Cnf}_{\star}(M)$ . We have  $(s, \pi^{\star}(s)) \in \mathcal{X}_{\star}(M)$  for all  $s \in \mathcal{S}$ , and because M and M<sup>†</sup> coincide on  $\mathcal{X}_{\star}(M)$ , it follows that the gain, bias, reward and kernel of  $\pi^{\star}$  are preserved in  $M^{\dagger}$ . Yet  $\pi^{\star}$  is not gain-optimal in  $M^{\dagger}$ , hence is not Bellman optimal in  $M^{\dagger}$  [\(3\)](#page-5-1). Accordingly, there must exists  $(s, a) \in X$  such that:

$$
\mathbf{m}^{\dagger}(s,a) + \mathbf{p}^{\dagger}(s,a)\mathbf{b}_{\star}(\mathbf{M}) > \mathbf{g}_{\star}(s,\mathbf{M}) + \mathbf{b}_{\star}(s,\mathbf{M}).
$$

Meanwhile, all states are recurrent under  $\pi^*$  which is optimal in **M**, hence (1)  $\chi_*(\mathbf{M}) = \chi_{\hat{\pi}}(\mathbf{M})$  and (2) it is a fixpoint of the Bellman operator of M, in particular  $m(s, a) + p(s, a)b_{\star}(M) \leq g_{\star}(s, M) +$  $\mathbf{b}_{\star}(s, \mathbf{M})$ . By (1), **M** and **M**<sup>†</sup> coincide on  $\mathcal{X}_{\star}(\mathbf{M})$  so invoking (2), we must have  $(s, a) \notin \mathcal{X}_{\star}(\mathbf{M})$ . In the end, we obtain:

$$
K(\mathbf{M}) = \inf \left\{ \sum_{x \in \mathcal{X}} \mu(x) \Delta_{\star}(x) : \mu \in \mathbb{R}_{+}^{\mathcal{X}} \text{ and } \forall (s, a) \in \mathcal{X}_{-}(\mathbf{M}), \ \mu(s, a) C(\mathbf{M}, s, a) \ge 1 \right\},\
$$

of which the solution is obvious.

**Discussion.** In particular, when  $M \in \mathcal{M}$  is an optimally recurrent model, then the navigation constraints become trivial ( $\mu \in \mathbb{R}_+^X$ ) and the information constraints are decoupled along sub-optimal pairs, just like for multi-armed bandits. We recover a regret lower-bound that is in closed form, navigation free and with pair-wisely decoupled information constraints. In other words, the regret lower bound of optimally recurrent models is morally the same than than in multi-armed bandits. The obtain bound is a generalization of the well-known results of [Burnetas and Katehakis](#page-35-0) [\(1997\)](#page-35-0), that provides a lower bound which is similar to [Proposition 17,](#page-25-1) excepted that it only holds for M irreducible (or recurrent), meaning that all the states are recurrent under every policy — which is much stronger than the optimal recurrence assumption of [Definition 9.](#page-24-1)

## <span id="page-25-0"></span>6.3 Example: Bandits with switching costs

We now go back to multi-armed bandits by adding switching costs. Multi-armed bandits with switching costs [Agrawal et al.](#page-34-2) [\(1988a](#page-34-2)); [Jun](#page-36-13) [\(2004\)](#page-36-13); [Brezzi and Lai](#page-35-14) [\(2002\)](#page-35-14); [Ortner](#page-36-14) [\(2010\)](#page-36-14) consist in multiarmed bandits where a cost in induced every time the learning agent changes arm. Formally, a bandit with switching costs can be seen as a Markov decision process M with pair space  $X = S \times S$  where

each state corresponds to an arm, and actions from a state are another choice of state. By choosing *s* from *s*, one remains in *s* and scores according to  $r(s, s')$  of positive mean; And by choosing  $s' \neq s$ from *s*, one goes to *s'* and pays a fixed switching cost  $\lambda > 0$ . That is,

$$
\mathbf{p}(s'|s, s) = s \quad \text{and} \quad \mathbf{m}(s, s') \ge 0,
$$
  

$$
\mathbf{p}(s'|s, s) = s' \quad \text{and} \quad \mathbf{m}(s, s') = -\lambda.
$$

For a fixed switching cost  $\lambda > 0$  and a fixed set of arms S, we let  $\mathcal{M}_{\lambda}$  the collection of all multiarmed bandits with switching cost  $\lambda$  and Bernoulli rewards, consisting in the set of Markov decision processes described above. With a similar rationale than in [Section 6.1,](#page-23-1) we show that the regret lower bound can be put in closed form, meeting the known result of [Agrawal et al.](#page-34-2) [\(1988a\)](#page-34-2).

Indeed, just as for bandits, we can show that any confusing model  $M^{\dagger} \in \text{Cnf}_{\star}(M; \mathcal{M}_\lambda)$  can be simplified into  $M^{\ddagger}$  where  $M$  and  $M^{\ddagger}$  only differ at an optimal pair of  $M^{\dagger}$ . When rewards are Bernoulli, information constraints are therefore decoupled along states and can be written as:

<span id="page-26-1"></span>
$$
\forall s \in \mathcal{S}, \quad \mu(s) \text{kl}(\mathbf{m}(s, s)) \mid \max(\mathbf{m})) \ge 1. \tag{19}
$$

Then, it is easy to see that the structure of bandits with switching cost is such that for all  $\alpha \in \mathbb{R}^{\mathcal{S}}_+$ , there is  $\mu \in Inv(M)$  such that  $\mu(s, s) = \alpha(s)$ . Moreover, just like for multi-armed bandit, the optimal gain is  $g_{\star}(M) = \max(m)$  regardless of the switching cost. Combining it all with [\(19\)](#page-26-1), we obtain [Corollary 18.](#page-26-2)

<span id="page-26-2"></span>**Corollary 18** [\(Agrawal et al.](#page-34-2) [\(1988a](#page-34-2))). *Fix*  $\lambda > 0$  *and let*  $M_{\lambda}$  *the space of all Bernoulli bandits with switching costs*  $\lambda$  *and arms*  $S$ *. Let*  $M \in M_{\lambda}$  *such that*  $max(m) < 1$ *. Then:* 

$$
K_{\star}(\mathbf{M}; \mathcal{M}_{\lambda}) = \sum_{x \in \mathcal{X}} \frac{\Delta_{\star}(x; \mathbf{M})}{k l(\mathbf{m}(x) || \max(\mathbf{m}))}.
$$
 (20)

**Discussion.** Remark that despite the fact that  $Inv(M) \neq \mathbb{R}^X_+$ , the navigation constraints do not appear in that reworked lower bound. This is because the information constraints do not constrain  $\mu$  outside of  $\{(s, s) : s \in S\}$ , hence the optimal exploration measure has zero mass on  $X \setminus \{(s, s) : s \in S\}$  which is indeed where navigation is constrained. This is linked to the surprising fact that  $\lambda$  is absent from  $K_{\star}(\mathbf{M};\mathcal{M}_\lambda)$ , hence that the optimal asymptotic regret does not depend on switching costs. In other words, our main regret lower bound of [Theorem 3](#page-9-0) claims that switching costs are negligible. It is not obvious at first sight that there are strongly consistent agents of which the asymptotic regrets are reaching  $K_{\star}(\mathbf{M};\mathcal{M}_\lambda)$ , or independent of  $\lambda$  at all — we refer the interested reader to [Agrawal et al.](#page-34-2) [\(1988a\)](#page-34-2); [Brezzi and Lai](#page-35-14) [\(2002](#page-35-14)) for more insight on the subject.

## <span id="page-26-0"></span>6.4 Example: Fixed kernel spaces

Beyond optimally recurrent models, the lower bound may be impossible to decouple pair-wisely in general. It may have no closed-form expression and navigation constraints may be non trivial. One setting in which the lower bound cannot be decoupled, and which is slightly simpler than the general setting yet, is when the transition kernel is known or deterministic. This setting is the subject of a few works [Saber et al.](#page-37-7) [\(2024](#page-37-7)); [Ortner](#page-36-14) [\(2010](#page-36-14)); [Tranos and Proutiere](#page-37-0) [\(2021\)](#page-37-0). [Tranos and Proutiere](#page-37-0) [\(2021](#page-37-0)) provides a lower bound for deterministic transition models and while [Saber et al.](#page-37-7) [\(2024](#page-37-7)) provides model dependent regret analysis of their method in the more general setting where only the reward function has to be learned, no lower bound was known in this more general setting.

**Definition 10.** Fix a pair space X. A model space  $M$  ∈  $\mathfrak{M}(X)$  is called a fixed kernel space if *all elements of* M *have the same transition kernel, i.e.,*  $\forall M, M' \in M$ ,  $p = p'$ . We say that it is *deterministic kernel space if, in addition,*  $p(s'|s, a) \in \{0, 1\}$  *for every transition triplet*  $(s, a, s')$ *.* 

We start by relating our results to the lower bound of [Tranos and Proutiere](#page-37-0) [\(2021](#page-37-0)). For deterministic kernel space, [\(Tranos and Proutiere,](#page-37-0) [2021,](#page-37-0) Theorem 1) provided a model dependent lower bound and already make apparent the information and navigation constraints in a form that are similar to [Theorem 3,](#page-9-0) although the objective function is written differently. In our set of notations, their result can be adapted as follows.

**Theorem 19** [\(Tranos and Proutiere](#page-37-0) [\(2021](#page-37-0))). *Let* M *a deterministic kernel space and fix*  $M \in M$ *. The regret of every strongly consistent learning agent satisfies*  $Reg(T; A, M) \ge C(M; M) \log(T)$  *where*  $C(M;M)$  *is:* 

$$
\inf \left\{ \sum_{x \in \mathcal{X}} \mu(x) (\mathbf{g}_{\star} - \mathbf{m}(x)) : \mu \in \text{Inv}(\mathbf{M}) \text{ and } \inf_{\mathbf{M}^{\dagger} \in \text{Cnf}_{\star}(\mathbf{M}; \mathcal{M})} \sum_{x \in \mathcal{X}} \mu(x) \text{KL}(\mathbf{M}(x) || \mathbf{M}^{\dagger}(x)) \ge 1 \right\}.
$$
 (21)

This lower bound is the same as ours, with  $K_{\star}(\mathbf{M};\mathcal{M}) = C(\mathbf{M};\mathcal{M})$ , because

$$
\sum_{x \in X} \mu(x)(\mathbf{g}_{\star} - \mathbf{m}(x)) \stackrel{(*)}{=} \sum_{(s,a) \in X} \mu(s,a)(\Delta_{\star}(s,a) + (\mathbf{p}(s,a) - e_s)\mathbf{b}_{\star})
$$
\n
$$
= \sum_{x \in X} \mu(x)\Delta_{\star}(x) + \sum_{s' \in S} \mathbf{b}_{\star}(s') \sum_{(s,a) \in X} \mu(s,a)\mathbf{p}(s'|s,a) - \sum_{s \in S} \mathbf{b}_{\star}(s) \sum_{a \in \mathcal{A}(s)} \mu(s,a)
$$
\n
$$
\stackrel{(\dagger)}{=} \sum_{x \in X} \mu(x)\Delta_{\star}(x) + \sum_{s' \in S} \mathbf{b}_{\star}(s') \sum_{a \in \mathcal{A}(s')} \mu(s',a) - \sum_{s \in S} \mathbf{b}_{\star}(s) \sum_{a \in \mathcal{A}(s)} \mu(s,a)
$$
\n
$$
= \sum_{x \in X} \mu(x)\Delta_{\star}(x)
$$

where (\*) follows from the Poisson equation and (†) uses that  $\mu \in Inv(M)$ . Therefore and in particular, our results generalizes [Tranos and Proutiere](#page-37-0) [\(2021](#page-37-0)) to fixed kernel spaces.

**Policy decomposition and fixed kernel spaces.** When a model  $M^{\dagger}$  is confusing, it means that there exists a policy which is optimal in  $M^{\dagger}$  and sub-optimal in M. This is also true the other way around: Confusing models can be enumerated according to the sub-optimal policy that they make optimal, encouraging the introduction of confusing models related to a policy, see [Definition 11.](#page-27-0)

<span id="page-27-0"></span>**Definition 11.** Let  $M \in \mathcal{M}$  and  $fix \pi \notin \Pi^*(M)$ . The **beneficial set** related to  $\pi$  is:

$$
Ben(\pi, M; \mathcal{M}) := \left\{ M^{\dagger} \in \mathcal{M} : g_{\pi}(M^{\dagger}) > \sup_{\pi^{\star} \in \Pi^{\star}(M)} g_{\pi^{\star}}(M^{\dagger}) \right\}.
$$
 (22)

*We further denote*  $\text{Ben}_\star(\pi, M; \mathcal{M}) := \text{Ben}(\pi, M; \mathcal{M}) \cap \text{Cnf}_\star(M; \mathcal{M})$ .

This decomposition of the confusing set is present in many works, including [Saber et al.](#page-37-7) [\(2024](#page-37-7)); [Marjani and Proutiere](#page-36-10) [\(2021\)](#page-36-10); [Al Marjani et al.](#page-35-12) [\(2021\)](#page-35-12). Now, fixed kernel spaces are a setting where a classical decomposition of the confusing set is especially pertinent. Indeed when the space M is a convex fixed kernel space, then the set  $\text{Ben}_\star(\pi, M; \mathcal{M})$  of both confusing and beneficial models related to a policy  $\pi$  is a convex set. Further, the infimum of  $\sum_{x \in \mathcal{X}} \mu(x)KL_x(\mathbf{M}||\mathbf{M}^{\dagger})$  over  $\mathbf{M}^{\dagger} \in \text{Ben}_{\star}(\pi, \mathbf{M}; \mathcal{M})$ can be computed numerically as:

$$
\inf \left\{ \sum_{x \in \mathcal{X}} \mu(x) \mathrm{KL}(\mathbf{m}(x) || \mathbf{m}^{\dagger}(x)) : \mathbf{m}_{|\mathcal{X}_{\star}(\mathbf{M})} = \mathbf{m}_{|\mathcal{X}_{\star}(\mathbf{M})}^{\dagger} \text{ and } \mathbf{g}_{\pi}((\mathbf{m}^{\dagger}, \mathbf{p})) > \mathbf{g}_{\star}(\underbrace{(\mathbf{m}, \mathbf{p})}_{\mathbf{M}}) \right\}
$$

This is a convex program with a strongly convex objective function and linear constraints, because  $m^{\dagger} \mapsto g_{\pi}(m^{\dagger}, p)$  is a linear function. So, while in general, the regret lower bound  $K_{\star}(M; M)$  is the

#### V. Boone & OA. Maillard 28 January 23, 2025

solution of an optimization program with a continuum of convex constraints [\(LB\)](#page-10-1), it becomes the solution of an optimization program with exponentially many convex constraints (one per policy) when M is a convex fixed kernel space  $(LB_{\star}^{\pi})$ . As constraints are indexed by policies, good heuristics on politics are crucial to get good estimates of  $K_{\star}(M;M)$ . As a matter of fact, using heuristics to select seemingly critical policies and information constraints is a key component of the algorithm of [Saber et al.](#page-37-7) [\(2024\)](#page-37-7), even though [Saber et al.](#page-37-7) [\(2024\)](#page-37-7) does not try to approach the regret lower bound perfectly.

## <span id="page-28-0"></span>6.5 Policy-wise decompositions of the lower bound

Following [Section 6.4,](#page-26-0) fixed kernel spaces are a setting where a general decomposition of the confusing set is especially pertinent. We provide a few additional remarks about this policy-wise decomposition.

#### <span id="page-28-1"></span>6.5.1 Beneficial sets and fixed kernel spaces

Remark that Ben( $\pi$ , M; M)  $\subseteq$  Alt(M). We leave as an exercise to the reader that Cnf<sub>\*</sub>(M; M) =  $\bigcup_{\pi \notin \Pi^{\star}(\mathbf{M})} \text{Ben}_{\star}(\pi, \mathbf{M}; \mathcal{M})$ . From this fact, it immediately follows that  $K_{\star}(\mathbf{M}; \mathcal{M})$  can be written as:

$$
K_{\star}(\mathbf{M}; \mathcal{M}) = \inf \left\{ \sum_{x \in \mathcal{X}} \mu(x) \Delta_{\star}(x) : \mu \in \text{Inv}(\mathbf{M}), \forall \pi \notin \Pi^{\star}(\mathbf{M}), \mathbb{U}(\pi, \mu, \mathbf{M}) \geq 1 \right\}.
$$
 (LB <sup>$\pi$</sup> <sub>\*</sub>)

Here, we have introduced the **unlikelihood of optimality**  $U(\pi, \mu, M)$  of the policy  $\pi$ , borrowing the terminology from [Pesquerel](#page-37-14) [\(2023\)](#page-37-14), which is formally defined as

<span id="page-28-2"></span>
$$
\mathbb{U}(\pi,\mu,\mathbf{M}) := \inf \left\{ \sum_{x \in \mathcal{X}} \mu(x) \mathbf{KL}_x(\mathbf{M}||\mathbf{M}^\dagger) : \mathbf{M}^\dagger \in \text{Ben}_{\star}(\pi,\mathbf{M};\mathcal{M}) \right\}.
$$
 (23)

For general M and M, Ben<sub>\*</sub>( $\pi$ , M; M) is not necessarily convex and this expression cannot be argued to be simpler or more computationally friendly than the original [\(LB\)](#page-10-1). However, when  $\mathbb{U}(\pi,\mu,\mathbf{M})$  can be computed efficiently for each policy, this rewriting becomes appealing as it involves finitely-many policy-wise constraints rather than a continuum of confusing models.

#### 6.5.2 Policy-wise lower bounds, ergodic environments and [Agrawal et al.](#page-34-0) [\(1988b](#page-34-0))

If the information constraints can be rewritten in a policy-wise fashion, as a last detour, we emphasize on the observation that the whole lower bound of [Theorem 3](#page-9-0) can be rewritten policy-wisely. This is actually how ergodic Markov decision processes have been first approached [Agrawal et al.](#page-34-0) [\(1988b](#page-34-0)); [Graves and Lai](#page-36-1) [\(1997](#page-36-1)). In an ergodic environment, every policy can be played until regeneration, i.e., until coming back to the initial state. Doing so, the expected regret itself can be written in terms of policies, leading to the lower bound of [Agrawal et al.](#page-34-0) [\(1988b\)](#page-34-0) that rewrites, when M is ergodic, as

$$
K(\mathbf{M}) = \inf \left\{ \sum_{\pi \in \Pi} \alpha(\pi) (\mathbf{g}_{\star}(\mathbf{M}) - \mathbf{g}_{\pi}(\mathbf{M})) : \alpha \in \mathcal{P}(\Pi) \text{ and } \sum_{\pi \in \Pi} \alpha(\pi) \mathbb{U}(\pi, \mu_{\pi}, \mathbf{M}) \ge 1 \right\}.
$$

The quantity  $\alpha(\pi)$  accounts for the amount of time (in logarithmic scale) that the algorithm spends playing the policy  $\pi$ . The above coincides with the lower bound of [Burnetas and Katehakis](#page-35-0) [\(1997\)](#page-35-0). However, it is not clear that it can be generalized beyond the scope of ergodic Markov decision processes. Indeed, the expected regret can only be expressed as  $\sum_{\pi \in \Pi} \alpha(\pi)(g_{\star}(M) - g_{\pi}(M))$  if the algorithm plays fixed policies until regeneration, hence heavily relying on the ergodic nature of the environment. Moreover, algorithms play actions rather than policies and algorithms that explore by playing fixed policies for long periods of time are, although common, of a special kind.

V. Boone & OA. Maillard 29 January 23, 2025

## <span id="page-29-0"></span>7 An elementary construction of confusing MDPs

We have seen in the previous section that the constraint on MDPs can be decomposed into constraints on policies, via Cnf<sub>★</sub>(M;  $M$ ) =  $\bigcup_{\pi \notin \Pi^*(M)} \text{Ben}_\star(\pi, M; M)$ . In this section, we aim to building confusing MDPs from an elementary constructive perspective. To this aim, we examine specific scenarios where constraints on policies can be further replaced with constraints on individual state-action pairs. The most specific situation happens when modifying a single pair *x* in a Markov Decision Process (MDP) suffices to construct a confusing instance for a sub-optimal policy  $\pi \notin \Pi^{\star}(\mathbf{M})$ . In this case, this means that the subset of MDPs  $M_1(x, M)$ , resulting from a **single-pair** modification at  $x \notin X_*(M)$ , satisfies  $\text{Ben}_{\star}(\pi, M; \mathcal{M}) \cap \mathcal{M}_1(x, M) \neq \emptyset$ . Consequently, in this specific situation the unlikelihood of optimality of  $\pi$  is controlled as  $\mathbb{U}(\pi, \mu, \mathbf{M}) \leq \mu(x) \inf \{KL_x(\mathbf{M}, \mathbf{M}^{\dagger}) : \mathbf{M}^{\dagger} \in \text{Ben}_{\star}(\pi, \mathbf{M}; \mathcal{M}) \cap \mathcal{M}_1(x, \mathbf{M})\}$ , which, together with the constraint  $\mathbb{U}(\pi, \mu, \mathbf{M}) \geq 1$  yields a pair-wise constraint on  $\mu(x)$ .

To guide the construction of the general case, we need to scrutinize the structure policies and corresponding recurrent sets. To this aim, we introduce the set  $S_+(\pi, \pi^{\dagger}) := \{ s \in S : \pi(s) \neq \pi^{\dagger}(s) \}$ of states where two policies  $\pi$ ,  $\pi^{\dagger}$  differ, then characterize the proximity of policies by the size of this set:

**Definition 12** (*k*-neighborhoods). *For a policy*  $\pi \in \Pi$ , *the k*-neighborhood  $V_{\pi}(k) := {\pi^{\dagger} \in \Pi :}$  $|S_{\neq}(\pi, \pi^{\dagger})| \leq k$  *is defined as the set of policies differing from*  $\pi$  *in at most k states.* 

Of particular interest is the set  $V_*(1) = \{ \pi : \exists \pi^* \in \Pi^*(M), \pi \in V_{\pi^*}(1) \}$ , representing policies that are immediate neighbors of optimal policies. These policies, denoted as  $\pi = \pi_x^*$ , deviate from a specific optimal policy  $\pi^*$  only at the state *x*. Such policies are especially appealing when  $\text{Ben}_{\star}(\pi_{x}^{\star}, \mathbf{M}; \mathcal{M}) \cap \mathcal{M}_{1}(x, \mathbf{M}) \neq \emptyset$ , since *x* is also the pair where to modify the MDP to obtain a confusing one. However, note that this favorable situation may not happen in general, which means *even single-pair modification of an optimal policy may require many pairs modifications* to build a corresponding confusing MDP. Restricting in  $K_{\star}(M)$  the policy-wise constraints to the subset  $V_{\star}(1)$  only may considerably reduce the set of constraints and yield computable approximations of this quantity.

To streamline the discussion, we assume below that the set of permissible rewards and transitions in the MDP is fully unstructured. In other words, no constraints link rewards and transitions across different pairs or within a single pair. This assumption isolates the generic mechanisms at play, free from the added complexity of structural dependencies, which may render some cases more or less challenging depending on the specific constraints. Formally, we assume that the set of rewards and transitions in the MDP can be expressed as a product set,  $\bigotimes_{i} (\mathcal{R}_x \otimes \mathcal{P}_x)$ , where  $\mathcal{R}_x \subset \mathcal{P}(\mathbb{R})$  represents

the set of reward distributions and  $\mathcal{P}_x \subset \mathcal{P}(\mathcal{S})$  denotes the set of transition distributions for each stateaction pair *x*. Under this assumption, the subset of MDPs  $M_1(x, M)$ , resulting from a **single-pair** modification at  $x \notin \mathcal{X}_\star(\mathbf{M})$ , can be represented as  $\mathcal{R}_x \otimes \mathcal{P}_x$ .

## <span id="page-29-1"></span>7.1 Locally modifying an MDP to induce confusion

The construction of a confusing instance for a sub-optimal policy  $\pi$  often involves selectively modifying an MDP M at recurrent state-action pairs under  $\pi$ . The objective is to either increase the rewards or adjust the transitions to amplify the visiting frequency of these pairs, provided the resulting MDP remains within the permissible set  $M$ . While in some cases a single-pair modification suffices, in general, multiple pairs may need to be adjusted.

### <span id="page-30-0"></span>7.1.1 Local modifications of an MDP

Formally, for a configuration set M and a state-action pair  $x = (s, a) \notin X_{\star}(\mathbf{M})$ , we define two key sets:

(Local uncertainty set)  $C(x, M) := \{(\rho, q) \in \mathcal{P}(\mathbb{R}) \times \mathcal{P}(\mathcal{S}) : \exists M \in \mathcal{M}, \mathbf{r}_M(x) = \rho, \mathbf{p}_M(x) = q\},\$  $(\text{Local optimistic set}) \quad C_+(x, \mathcal{M}) := \{(\rho, q) \in C(x, \mathcal{M}) : \mathbb{E}_{\rho}[r] + (q\mathbf{b}_{\pi^*})(s) > \mathbf{m}_{\pi^*}(s) + (\mathbf{p}_{\pi^*}\mathbf{b}_{\pi^*})(s)\}.$ 

The locally modified MDP  $M(x)$  matches M at all pairs except x, where the reward and transition are adjusted as follows:

$$
(\tilde{\mathbf{p}}(x), \tilde{\mathbf{r}}(x)) := \begin{cases} \operatorname{argmin}\{KL(\mathbf{r}(x), \rho) + KL(\mathbf{p}(x), q) : (\rho, q) \in C_+(x, \mathbf{M})\} & \text{if } C_+(x, \mathbf{M}) \neq \emptyset, \\ \operatorname{argmax}\{\mathbb{E}_{\rho}[r] + (q\mathbf{b}_{\pi^*})(s) : (\rho, q) \in C(x, \mathbf{M})\} & \text{otherwise.} \end{cases}
$$

Intuitively, such elementary modifications aim to either increase the reward of this pair, enhancing the gain of a recurrent sub-optimal policy, or alter the transition probabilities to redistribute the invariant measure toward more rewarding pairs—or both. Now to ensure that stringent constraints on  $C(x, M)$ are appropriately handled, if  $C_+(x, M)$  is empty, this procedure selects the admissible modification that maximally increases the pair's contribution to the gain.

#### <span id="page-30-1"></span>7.1.2 Specific Local Modification Sets

Two subsets of  $C_+(x, M)$  merit special attention, each imposing distinct restrictions: The first set  $C<sup>sw</sup>(x, M)$  restricts to transitions that switch the behavior of action *a* into that of an optimal policy  $\pi^*$ , and is reminiscent of [Burnetas and Katehakis](#page-35-0) [\(1997\)](#page-35-0) for ergodic MDPs. The second set  $C^r(x, M)$ forces to keep the transition unchanged, hence only rewards can be modified. Formally,

$$
C^{sw}(x, M) := \{ (\rho, q) \in C(x, M) : q = (1 - \varepsilon) \mathbf{p}_a(s) + \varepsilon \mathbf{p}_{\pi^*}(s), \varepsilon \in (0, 1] \}
$$
  

$$
C^{r}(x, M) := \{ (\rho, q) \in C(x, M) : q = \mathbf{p}_a(s) \},
$$

We define both  $C^{\text{sw}}_+(x, \mathcal{M})$ ,  $C^{\text{r}}_+(x, \mathcal{M})$  and  $\widetilde{\mathbf{M}}^{\text{sw}}(x)$ ,  $\widetilde{\mathbf{M}}^{\text{r}}(x)$  replacing  $C(x, \mathbf{M})$  with  $C^+(x, \mathbf{M})$  accordingly.

**Remark 4** (Switched Markov chain). *In particular, when*  $\tilde{\mathbf{p}}(x) = q = \mathbf{p}_{\pi^*}(s)$ , the Markov chain *induced by playing*  $x = (s, a)$  *in*  $\mathbf{\overline{M}}^{sw}(x)$  *coincides with playing*  $\pi^*$  *in*  $\mathbf{M}$ *, by construction. When considering a switch MDP*  $M^{\dagger}$  *such that*  $q = p_{M^{\dagger}}(x) = p_{\pi^*}(s)$  *(so with*  $\varepsilon = 1$ *), then the condition in the definition of the local optimistic set simplifies into*  $\mathbb{E}_{\rho}[r] > \mathbf{m}_{\pi^{\star}}(s)$ *.* 

#### <span id="page-30-2"></span>7.1.3 Choice of local modifications

We choose either set in the computation of a local modification depending on the corresponding stateaction pair  $x = (s, \pi(s))$ . Note that we locally modify an MDP only when  $S(\pi, M) \cap S_{\neq}(\pi, \pi^*) \neq \emptyset$ , since otherwise we can show that  $\pi \in \Pi^*(M)$ . For the remaining cases, we proceed as follows

• When  $s \in S(\pi, M) \cap S_{\neq}(\pi, \pi^*) \cap S(\pi^*, M)$ , we build  $\widetilde{M}^{sw}(x)$  where  $x = (s, \pi(s))$ .

- When  $s \in S(\pi, M) \cap S_{\neq}(\pi, \pi^{\star}) \setminus S(\pi^{\star}, M)$ , we build  $\widetilde{M}^{r}(x)$  where  $x = (s, \pi(s))$ .
- When  $s \in S(\pi, M) \setminus (S_{\neq}(\pi, \pi^*) \cup S(\pi^*, M))$ , we build  $\widetilde{M}^r(x)$  where  $x = (s, \pi(s))$ .

For convenience, we denote the union of all these states by  $S^{ch}(\pi, M)$ , their corresponding pairs by  $X^{ch}(\pi, M) = \{(s, \pi(s)) : s \in S^{ch}(\pi, M)\}\)$ , and the modified MDP  $\widetilde{M}^{ch}(x)$  (either  $\widetilde{M}^{sw}(x)$  or  $\widetilde{M}^{r}(x)$ ) corresponding to the situation. Now let us recall that a confusing MDP  $M^{\dagger}$  should coincide with M on  $X_{\star}(\mathbf{M})$ . In particular, provided  $\mathbf{M}^{\dagger}$  does not modify the recurrent pairs of any policy in  $\Pi^{\star}(\mathbf{M})$ , then the gain and bias of any optimal policy  $\pi^* \in \Pi^*(M)$  is the same in M and  $M^{\dagger}$ . This is a key property that justifies the local optimist set defines valid confusing instances, and this is the reason why we only modify the transitions of the MDP in pairs where  $\pi$  differs from  $\pi^*$ . More formally:

**Proposition 20.** For each  $M^{\dagger} \in \text{Cnf}_{\star}(M)$ ,  $\pi^{\star} \in \Pi^{\star}(M)$  such that  $X(\pi^{\star}, M) = X(\pi^{\star}, M^{\dagger})$ , then  $\mathbf{g}_{\pi^{\star}}(\cdot, \mathbf{M}) = \mathbf{g}_{\pi^{\star}}(\cdot, \mathbf{M}^{\dagger})$  and  $\mathbf{b}_{\pi^{\star}}(\cdot, \mathbf{M}) = \mathbf{b}_{\pi^{\star}}(\cdot, \mathbf{M}^{\dagger}).$ 

**Remark 5** (Changes outside of  $S_{\neq}(\pi, \pi^*)$ ). *On the states*  $S(\pi, M) \setminus S_{\neq}(\pi, \pi^*)$ , *one has*  $\pi = \pi^*$ . *Hence modifying the transitions of* **M** *at pairs*  $(s, \pi(s)) = (s, \pi^*(s))$  *may actually modify*  $X(\pi^*, M)$ *. This is* why we keep the transition unchanged in this case. Further, when  $s \in S(\pi^\star, \mathbf{M})$  increasing the rewards *also increases the gain of* π ⋆ *in the modified MDP, which is prohibited. This is why we exclude the set*  $S(\pi^*, M)$  and only increasing rewards on  $S(\pi, M) \setminus (S_\neq(\pi, \pi^*) \cup S(\pi^*, M))$ .

When a single pair modification is enough. To give some intuition, let us consider a policy  $\pi$ such that  $S_+(\pi, \pi^*) = \{s\}$ . In particular,  $\pi \in V_*(1)$  and this policy differs only at a single pair  $x = (s, \pi(s))$  from an optimal policy. We say the Switch property holds if  $M_{sw}(x) \in \text{Ben}_\star(\pi, M; \mathcal{M})$ , that is if a single-pair modification is enough to build a confusing MDP for policy  $\pi$ , when built from the local set  $C_{sw}(x, M)$ . The following proposition justifies the choice of building  $\mathbf{M}^{sw}(x)$  when  $s \in \mathcal{S}(\pi, \mathbf{M}) \cap \mathcal{S}(\pi^*, \mathbf{M}).$ 

<span id="page-31-1"></span>**Proposition 21** (Switch property). Let  $x = (s, \pi(s))$  and assume that  $C_{+}^{sw}(x) \neq \emptyset$ .

- (1) If  $\pi^*$  is ergodic in **M**, then Switch holds at x.
- (2) If  $\pi^*$  is unichain in **M**, then Switch holds at x except when  $s \notin S(\pi^*, M)$ .
- (3) If  $\pi^*$  is multichain in **M**, then Switch holds at x when  $s \in S(\pi, M) \cap S(\pi^*, M)$  and does not *hold when*  $s \notin S(\pi^*, \mathbf{M})$ .

In particular, when restricting the policy-wise constraints in  $K_{\star}(M)$  to the subset  $\mathcal{V}_{\star}(1)$ , we obtain the following relaxation expressed with pair-wise constraints:

$$
K_{\star}(\mathbf{M}) \ge \inf \Big\{ \sum_{x \in \mathcal{X}} \mu(x) \Delta_{\star}(x) : \mu \in \text{Inv}(\mathbf{M}), \forall x \in \mathcal{X}, \begin{cases} \mu(x) \text{KL}_{x}(\mathbf{M}, \widetilde{\mathbf{M}}_{\text{sw}}(x)) \ge 1 & \text{if } \text{Switch}(x) \\ \mathbb{U}(\pi_{x}^{\star}, \mu, \mathbf{M}) \ge 1 & \text{otherwise.} \end{cases} \Big\}.
$$

Remark 6 (Prior knowledge). *Let us remark that if prior knowledge is assumed about* p(*x*)*, say we know that*  $p(x) \in \mathcal{P}_x$ , where  $\mathcal{P}_x$  is a strict subset of  $\mathcal{P}(S)$  (meaning all MDP **M** in M must satisfy  $\tilde{\mathbf{p}}(x) \in \mathcal{P}_x$ , then  $C^{sw}_+(x)$  may be empty: This happens e.g. if  $x = (s, a)$  and  $\mathbf{p}(s, \pi^*(s)) \notin \mathcal{P}_{s,a}$ . Hence *the complexity of deriving the lower bound in the agnostic situation when*  $P_x = P(S)$  *is possibly very di*ff*erent than when we have a more informative knowledge.*

Adapting to multi-pair modification. When no MDP can be found that is sufficiently optimistic in a single modification, we need to progressively modify the MDP at other pairs in order to increase the gain of policy  $\pi$  and not only at single place. We suggest using here a simple iterative procedure that successively modifies **M** at well-chosen pairs. We let  $M_0 = M$ , then for each  $i \ge 0$ , we choose  $x_i \in \mathcal{X}^{\text{ch}}(\pi, \mathbf{M}) \setminus \{x_1, \ldots, x_{i-1}\}$  in an appropriate way. Then, we build  $\mathbf{M}_{i+1} = \widetilde{\mathbf{M}}_i^{\text{ch}}(x_i)$ , that is we build a local modification of  $M_i$  at pair  $x_i$ . We stop when  $g_{\pi}(M_{i+1}) \ge g_{\pi^*}(M)$ . An appropriate choice of  $x_i$ is one that minimizes the local contribution of this change to the unlikelihood of optimality, that is

$$
x_i = \operatorname{argmin}\left\{ \mathbb{E}^{\mathbf{M},\mathbb{A}}[N_T(x)]\mathrm{KL}_x(\mathbf{M},\widetilde{\mathbf{M}}_i^{\mathrm{ch}}(x)): x \in \mathcal{X}^{\mathrm{ch}}(\pi,\mathbf{M}) \setminus \{x_1,\ldots,x_{i-1}\}\right\}.
$$

## <span id="page-31-0"></span>7.2 Approaching confusing MDPs by local changes

We are now almost ready to state the algorithm that tries to compute a confusing MDP for a suboptimal policy  $\pi$ . It remains to handle a few special cases that enable to simplify the search procedure.

Special case. When  $S(\pi, M) \cap S_{\neq}(\pi, \pi^*) = \emptyset$ , then  $\pi$  coincides with an optimal policy  $\pi^*$  on  $S(\pi, M)$ . When this policy is unichain, then it must be that  $S(\pi, M) = S(\pi^*, M)$ , and thus the gain of  $\pi$  is optimal in M. In this special case, there is no need to build a confusing instance for  $\pi$ .

Saving computations. When considering a policy  $\pi \in V_{\pi^*}(k)$ , then  $S(\pi, M) \cap S_{\neq}(\pi, \pi^*)$  consists of at most *k* states. On the other hand, the size  $S(\pi, M) \setminus (S_\neq(\pi, \pi^*) \cup S(\pi^*, M))$  might be large, the order of  $|S|$ . Hence, to save computations, one may prioritize to first compute  $\overline{M}_i^{ch}(x)$  for  $x = (s, \pi(s))$ from  $S(\pi, M) \cap S_{\neq}(\pi, \pi^*)$  only, and scan the rest of the states only if  $g_{\pi}(\widetilde{M}_i^{ch}(x)) \ge g_{\pi^*}(M)$  does not hold for these pairs. This "early stopping search" may yield a final MDP having larger KL cost, but possibly save computations.

<span id="page-32-0"></span>**Algorithm 1** Construction of confusing MDP for policy  $\pi$ **Input:** Policy  $\pi$ , optimal policy  $\pi^*$  with gain  $g^*$ , counts  $(\kappa(x))_{x \in \mathcal{X}}$ . 1: Let  $\tilde{X} = \emptyset$  and  $\triangleright \triangleright \triangleright \mathsf{Set}$  where M is modified 2: if  $S_{\neq}(\pi, \pi^{\star}) \cap S(\pi, M) = \emptyset$  then 3: return  $M, X$  and  $\rightarrow \rightarrow \pi$  is actually optimal 4: end if 5: Set  $M_0 = M$ ,  $i = 0$ ,  $X_0 = X^{ch}(\pi, M)$ . 6: **while**  $\mathbf{g}_{\pi}(\mathbf{M}_i) < g^*$  **or**  $X_i \neq \emptyset$  **do** 7: Compute  $X'_i = \{x \in X_i : x = (s, \pi(s)), s \in S(\pi, M) \cap S_{\neq}(\pi, \pi^{\star}), g_{\pi}(\widetilde{M}_i^{ch}(x)) \ge g_{\pi^{\star}}(M)\}\$ 8: **if**  $X'_i \neq \emptyset$  then 9: Compute  $x_i = \operatorname{argmin} \left\{ \kappa(x) \mathbf{KL}_x(\mathbf{M}, \widetilde{\mathbf{M}}_i^{\text{ch}}(x)) : x \in \mathcal{X}'_i \right\}.$ 10: else 11: Compute  $x_i = \operatorname{argmin} \left\{ \kappa(x) \mathbf{KL}_x(\mathbf{M}, \widetilde{\mathbf{M}}_i^{\text{ch}}(x)) : x \in \mathcal{X}_i \right\}.$  $12:$  end if 13: Let  $M_{i+1} = \widetilde{M}_i^{ch}(x_i), X_{i+1} = X_i \setminus \{x_i\}, \widetilde{X} = \widetilde{X} \cup \{x_i\}, i = i+1.$ 14: end while 15: **if**  $X_i = \emptyset$  then<br>16: **return**  $\emptyset, \emptyset$ 16: return  $\emptyset$ ,  $\emptyset$  and  $\emptyset$  suboptimal  $\rightarrow \emptyset$  and  $\rightarrow \emptyset$  are is unconfusingly suboptimal 17: else 18: **return**  $M_i$ ,  $\tilde{X}$ 19: end if

We summarize the procedure to build a confusing MDP in Algorithm [1.](#page-32-0) This algorithm returns the confusing instance M together with the set of pairs  $\tilde{X}$  where the MDP differs from M, and enables to control the unlikelihood of optimality as

$$
\mathbb{U}(\pi,\mu,\mathbf{M})\leqslant \sum_{x\in\tilde{X}}\mu(x)\mathrm{KL}_x(\mathbf{M},\widetilde{\mathbf{M}}).
$$

Provided  $\tilde{X} \neq \emptyset$ , this procedure outputs a confusing MDP, not necessarily the most confusing MDP in the sense of achieving the minimal unlikelihood of optimality due to the considered relaxation. Specifically, since for policies  $\pi \in V_{\star}(k)$ , performing switch modifications of **M** at  $S_{\neq}(\pi, \pi^{\star})$  (of size  $\le k$ ) enables to ensure  $\pi$  induces the same Markov chain than an optimal policy in M<sup>†</sup>, and such modifications are considered by the algorithm, this ensures the construction eventually finds a confusing MDP for such policies. Indeed, since the algorithm proceed by maximizing the policy improvement at each non-final modification, the local modification ensures a gain increase not below that of a single pair exchange between  $\pi$  and  $\pi^*$ , which in turn ensures that procedure eventually stops.

**Complexity.** For each such policy  $\pi$  with  $|S_{\neq}(\pi, \pi^*)| = j$  each construction requires at most  $|S(\pi, M)| \le$ *S* local optimization steps, and possibly less than *j* when  $X'_i \neq \emptyset$ . Since there are  $\binom{S}{j}$  $\int_{i}^{5}$  *A*<sup>*j*</sup> policies that differs from  $\pi^*$  at exactly *j* pairs, computing a confusing MDP for all policies e.g. in  $\mathcal{V}_*(k)$  requires at most  $\sum^k$ *j*=1 *S*  $\binom{3}{i}$  *A*<sup>*j*</sup>*S* local optimization steps, where the factor *S* can be reduced to at most *j*. Of course

V. Boone & OA. Maillard 33 January 23, 2025

when  $k = S$ , the procedure becomes infeasible, since it essentially involves  $A<sup>S</sup>$  many optimization problems. On the other hand, when *k* is small with respect to *S*, say  $k = O(\log(S))$  this yields a fast procedure. This motivates to consider scanning only a subset of all policies  $\mathcal{V}_{\star}(k)$ .

<span id="page-33-1"></span>**Structure of policies.** Another motivation for restricting to  $\mathcal{V}_{\star}(k)$  comes from [Saber et al.](#page-37-7) [\(2024\)](#page-37-7). In this article, the authors consider the following structural assumption

**Property 1** (*k*-Local policy-improvement).  $\forall \pi \notin \Pi^*(\mathbf{M}) \exists \pi' \in \mathcal{V}_{\pi}(k), \mathbf{g}_{\pi'}(s) > \mathbf{g}_{\pi}(s)$ .

Let us recall that in a generic MDP, the classic policy iteration scheme ensures that at each step, there exists a state in which either the gain  $g_{\pi_{k+1}}$  or the bias  $b_{\pi_{k+1}}$  improves. However, there may be in general several consecutive steps before there exists a state in which the gain is improved. Hence this assumption ensures that a policy-improvement step is possible by searching in local neighborhood of any sub-optimal policy. It is a key step in the regret analysis of the IMED-KD strategy from [Saber et al.](#page-37-7) [\(2024\)](#page-37-7) to guarantee its correctness. In such situation, one can indeed scan only  $V_{\star}(k)$ , that is, computing confusing MDPs for such policies only, and ensure a controlled regret. While somewhat different, it provides a complementary perspective on the choice of the set of policies to be considered.

Remark 7 (Easy and Hard MDPs). *Remark that all MDPs necessarily satisfy Property [1](#page-33-1) for k* = *S . Now, intuitively an MDP that satisfies k-Local policy-improvement with small value of k (e.g.* 1, 2*) is easier to solve than an MDP that only satisfies it for large k. That's because for larger k, one needs to search for a policy improvement in a larger neighborhood of a sub-optimal policy. Interestingly, the policy-improvement lemma of [Puterman](#page-37-9) [\(2014\)](#page-37-9) implies that all ergodic MDPs satisfy the* 1*-Local policy-improvement property. Hence, they are in a sense the simplest of all MDPs. On the other hand, it is interesting to note that the MDP built in Section [5](#page-20-0) to prove NP-complete hardness only satisfies k-local policy-improvement property for k* = *S , hence is maximally complex in this sense.*

## <span id="page-33-0"></span>8 Conclusion, future work and conjectures

In this paper, we provide the regret lower bound in the model dependent setting for communicating Markov decision processes. The bound is found as the solution of an optimization problem that combines the mandatory exploration, co-exploration and second order navigational structure that every consistent learner must conform to. In general, the bound is  $\Sigma_2^P$ <sup>P</sup><sub>2</sub>-complete, i.e., merely checking its value is coNP-complete; This is true when the considered class is discrete, and the question of the complexity remains open for convex classes. In many classical classes of Markov decision processes, such as bandits, switching bandits, ergodic classes or deterministic transition classes, our bound coincide with existing ones. Moreover, we have discussed a direction to approximate it in a constructive fashion, by exploiting the idea of local modifications of the underlying environment.

Tightness. One obvious and immediate concern is the tightness of our bound, that we indeed conjecture to be tight. More precisely, we conjecture that there exists a consistent learning agent with theoretical regret guarantees matching the lower bound; Curious readers can already take a look at [\(Boone](#page-35-15), [2024,](#page-35-15) Chapter 10) for a preliminary version. We further conjecture that despite the computational hardness of the lower bound, it is possible to design asymptotically optimal algorithms that run in reasonable time. Once the bound will be proven tight, will raise the classical question of the compatibility of the model dependent setting with the model independent setting. In multiarmed bandits, [Garivier et al.](#page-36-15) [\(2022](#page-36-15)) design KL-UCB-Switch, reaching asymptotically optimal regret  $K(M) \log(T)$  and minimax optimal regret  $\sqrt{|\mathcal{A}|T}$  simultaneously; This is the best-of-both-worlds of

[Bubeck and Slivkins](#page-35-16) [\(2012\)](#page-35-16), that we conjecture to fail at Markov decision processes. In addition to the best-of-both-worlds, there is the question of how asymptotic the bound is. For bandits again, [Garivier et al.](#page-36-7) [\(2018](#page-36-7)) pointed out that simple algorithms such as Thompson Sampling [Thompson](#page-37-6) [\(1933](#page-37-6)) manage to beat the lower bound  $K(M) \log(T)$  even for large time horizons and it is nowadays known [Honda and Takemura](#page-36-3) [\(2015](#page-36-3)); [Garivier et al.](#page-36-7) [\(2018](#page-36-7)) that the second order term is a *negative*  $log log(T)$  when the support of rewards is bounded. We conjecture that even in simple cases, the second order term is a *positive* log log(*T*) for Markov decision processes and that the culprit should be co-exploration [\(Proposition 6\)](#page-13-0). All this is left for future work.

Extensions. Another immediate research direction is the generalization of our result to broader settings. Sticking to finite Markov decision processes, there is the question of dropping the communicating assumption to a weakly communicating assumption or even considering general multi-chain models. We conjecture that the lower bound is essentially the same in the weakly communicating setting. In the multi-chain setting however, the regret actually depends on the initial state and additional elements are required to properly generalize our results there. Beyond finite Markov decision processes, there is the question of countable state spaces such as in Queuing Theory, compact action spaces, compact state-action spaces or even parameterized environments such as linear MDPs or MDPs with function approximation.

Local policy improvement. Last but not least, is the question of the approximation of the lower bound. We find that Property [1](#page-33-1) plays an important role in providing a computationally efficient to approximate the bound. Especially, we remark that for ergodic MDPs, which satisfy a *k*-local policy improvement property with  $k = 1$ , our procedure recovers the lower bounds for the ergodic case, while MDPs causing the NP-hardness only satisfy it with  $k = S$ . This motivates studying and characterizing the MDPs obeying an intermediate *k* in greater depth. Up to our knowledge, very little is known about the intermediate regime of  $1 < k < S$ , and in particular the MDPs with  $k < log(S)$ , which we find of special interest, as the complexity of our procedure directly follows from Property [1.](#page-33-1) Characterizing such classes of MDPs and leveraging such structure is left for future work.

## Acknowledgments

This work has been supported by the French Ministry of Higher Education and Research, the Hautsde-France region, Inria, the MEL, the I-Site ULNE regarding project R-PILOTE-19-004-APPRENF, and the PEPR FOUNDRY. O. Maillard acknowledges the Inria-Kyoto University Associate Team "RELIANT" and the Scool research group for its outstanding working environment.

## References

- <span id="page-34-2"></span>Agrawal, R., Hedge, M., and Teneketzis, D. (1988a). Asymptotically efficient adaptive allocation rules for the multiarmed bandit problem with switching cost. *IEEE Transactions on Automatic Control*, 33(10):899–906. Publisher: IEEE.
- <span id="page-34-1"></span>Agrawal, R. and Teneketzis, D. (1989). Certainty equivalence control with forcing: revisited. *Systems* & *control letters*, 13(5):405–412.
- <span id="page-34-0"></span>Agrawal, R., Teneketzis, D., and Anantharam, V. (1988b). Asymptotically efficient adaptive allocation schemes for controlled Markov chains: finite parameter space. In *Proceedings of the 27th IEEE Conference on Decision and Control*, pages 1198–1203 vol.2.
- <span id="page-35-9"></span>Agrawal, S. and Jia, R. (2023). Optimistic Posterior Sampling for Reinforcement Learning: Worst-Case Regret Bounds. *Mathematics of Operations Research*, 48(1):363–392. Publisher: INFORMS.
- <span id="page-35-12"></span>Al Marjani, A., Garivier, A., and Proutiere, A. (2021). Navigating to the best policy in markov decision processes. *Advances in Neural Information Processing Systems*, 34:25852–25864.
- <span id="page-35-13"></span>Al-Marjani, A., Tirinzoni, A., and Kaufmann, E. (2023). Active coverage for pac reinforcement learning. In *The Thirty Sixth Annual Conference on Learning Theory*, pages 5044–5109. PMLR.
- <span id="page-35-7"></span>Auer, P. (2002). Using Confidence Bounds for Exploitation-Exploration Trade-offs. *J. Mach. Learn. Res.*, 3:397–422.
- <span id="page-35-1"></span>Auer, P., Jaksch, T., and Ortner, R. (2009). Near-optimal Regret Bounds for Reinforcement Learning. In *Advances in Neural Information Processing Systems*, volume 21. Curran Associates, Inc.
- <span id="page-35-10"></span>Auer, P. and Ortner, R. (2006). Logarithmic Online Regret Bounds for Undiscounted Reinforcement Learning. *Proceedings of the 19th International Conference on Neural Information Processing Systems*.
- <span id="page-35-2"></span>Bartlett, P. L. and Tewari, A. (2012). Regal: A regularization based algorithm for reinforcement learning in weakly communicating mdps. *arXiv preprint arXiv:1205.2661*.
- <span id="page-35-15"></span>Boone, V. (2024). Optimal regrets in markov decision processes. PhD thesis, see victorboone.github.io.
- <span id="page-35-6"></span>Boone, V. and Zhang, Z. (2024). Achieving Tractable Minimax Optimal Regret in Average Reward MDPs. eprint: 2406.01234.
- <span id="page-35-5"></span>Bourel, H., Maillard, O., and Talebi, M. S. (2020). Tightening Exploration in Upper Confidence Reinforcement Learning. In III, H. D. and Singh, A., editors, *Proceedings of the 37th International Conference on Machine Learning*, volume 119 of *Proceedings of Machine Learning Research*, pages 1056–1066. PMLR.
- <span id="page-35-14"></span>Brezzi, M. and Lai, T. L. (2002). Optimal learning and experimentation in bandit problems. *Journal of Economic Dynamics and Control*, 27(1):87–108. Publisher: Elsevier.
- <span id="page-35-16"></span>Bubeck, S. and Slivkins, A. (2012). The best of both worlds: stochastic and adversarial bandits. arXiv:1202.4473 [cs].
- <span id="page-35-0"></span>Burnetas, A. and Katehakis, M. (1997). Optimal Adaptive Policies for Markov Decision Processes. *Mathematics of Operations Research - MOR*, 22:222–255.
- <span id="page-35-11"></span>Burnetas, A. N. and Katehakis, M. N. (1996). Optimal adaptive policies for sequential allocation problems. *Advances in Applied Mathematics*, 17(2):122–142. Publisher: Elsevier.
- <span id="page-35-8"></span>Capp´e, O., Garivier, A., Maillard, O.-A., Munos, R., and Stoltz, G. (2013). Kullback-leibler upper confidence bounds for optimal sequential allocation. *The Annals of Statistics*, pages 1516–1541.
- <span id="page-35-3"></span>Filippi, S., Cappé, O., and Garivier, A. (2010). Optimism in Reinforcement Learning and Kullback-Leibler Divergence. *2010 48th Annual Allerton Conference on Communication, Control, and Computing (Allerton)*, pages 115–122. arXiv: 1004.5229.
- <span id="page-35-4"></span>Fruit, R., Pirotta, M., Lazaric, A., and Ortner, R. (2018). Efficient Bias-Span-Constrained Exploration-Exploitation in Reinforcement Learning. *Proceedings of the 35 th International Conference on Machine Learning*.
- V. Boone & OA. Maillard 36 January 23, 2025
- <span id="page-36-15"></span>Garivier, A., Hadiji, H., Ménard, P., and Stoltz, G. (2022). KL-UCB-Switch: Optimal Regret Bounds for Stochastic Bandits from Both a Distribution-Dependent and a Distribution-Free Viewpoints. *Journal of Machine Learning Research*, 23(179):1–66.
- <span id="page-36-7"></span>Garivier, A., Ménard, P., and Stoltz, G. (2018). Explore First, Exploit Next: The True Shape of Regret in Bandit Problems. *Mathematics of Operations Research*, 44(2):377–399.
- <span id="page-36-1"></span>Graves, T. L. and Lai, T. L. (1997). Asymptotically efficient adaptive choice of control laws incontrolled markov chains. *SIAM journal on control and optimization*, 35(3):715–743.
- <span id="page-36-2"></span>Honda, J. and Takemura, A. (2010). An asymptotically optimal bandit algorithm for bounded support models. In *COLT*, pages 67–79. Citeseer.
- <span id="page-36-3"></span>Honda, J. and Takemura, A. (2015). Non-asymptotic analysis of a new bandit algorithm for semibounded rewards. *J. Mach. Learn. Res.*, 16:3721–3756.
- <span id="page-36-13"></span>Jun, T. (2004). A survey on the bandit problem with switching costs. *de Economist*, 152:513–541. Publisher: Springer.
- <span id="page-36-11"></span>Kaufmann, E. (2014). *Analyse de stratégies bayésiennes et fréquentistes pour l'allocation s´equentielle de ressources*. PhD thesis, ENST Paris, France.
- <span id="page-36-16"></span>Kaufmann, E., Cappé, O., and Garivier, A. (2016). On the Complexity of Best-Arm Identification in Multi-Armed Bandit Models. *Journal of Machine Learning Research*, 17(1):1–42.
- <span id="page-36-0"></span>Lai, T. and Robbins, H. (1985). Asymptotically efficient adaptive allocation rules. *Advances in Applied Mathematics*, 6(1):4–22.
- <span id="page-36-5"></span>Lakshmanan, K., Ortner, R., and Ryabko, D. (2015). Improved regret bounds for undiscounted continuous reinforcement learning. In *International conference on machine learning*, pages 524–532. PMLR.
- <span id="page-36-8"></span>Lattimore, T. and Szepesvári, C. (2020). *Bandit algorithms*. Cambridge University Press.
- <span id="page-36-6"></span>Levin, D. A. and Peres, Y. (2017). *Markov chains and mixing times*, volume 107. American Mathematical Soc.
- <span id="page-36-12"></span>Maillard, O.-A. (2019). *Mathematics of statistical sequential decision making*. PhD thesis, Université de Lille, Sciences et Technologies.
- <span id="page-36-10"></span>Marjani, A. A. and Proutiere, A. (2021). Adaptive Sampling for Best Policy Identification in Markov Decision Processes. In *Proceedings of the 38th International Conference on Machine Learning*, pages 7459–7468. PMLR. ISSN: 2640-3498.
- <span id="page-36-4"></span>Ok, J., Proutiere, A., and Tranos, D. (2018). Exploration in Structured Reinforcement Learning. In Bengio, S., Wallach, H., Larochelle, H., Grauman, K., Cesa-Bianchi, N., and Garnett, R., editors, *Advances in Neural Information Processing Systems*, volume 31. Curran Associates, Inc.
- <span id="page-36-14"></span>Ortner, R. (2010). Online regret bounds for Markov decision processes with deterministic transitions. *Theoretical Computer Science*, 411(29):2684–2695.
- <span id="page-36-9"></span>Ortner, R. (2013). Adaptive aggregation for reinforcement learning in average reward markov decision processes. *Annals of Operations Research*, 208:321–336.
- <span id="page-37-4"></span>Osband, I., Russo, D., and Van Roy, B. (2013). (More) Efficient Reinforcement Learning via Posterior Sampling. *arXiv:1306.0940 [cs, stat]*. arXiv: 1306.0940.
- <span id="page-37-5"></span>Ouyang, Y., Gagrani, M., Nayyar, A., and Jain, R. (2017). Learning Unknown Markov Decision Processes: A Thompson Sampling Approach. *arXiv:1709.04570 [cs]*. arXiv: 1709.04570.
- <span id="page-37-14"></span>Pesquerel, F. (2023). *Information per unit of interaction in stochastic sequential decision making*. PhD thesis. Université de Lille.
- <span id="page-37-2"></span>Pesquerel, F. and Maillard, O.-A. (2022). IMED-RL: Regret optimal learning of ergodic Markov decision processes. In Koyejo, S., Mohamed, S., Agarwal, A., Belgrave, D., Cho, K., and Oh, A., editors, *Advances in Neural Information Processing Systems*, volume 35, pages 26363–26374. Curran Associates, Inc.
- <span id="page-37-1"></span>Pirutinsky, D. (2020). *On Asymptotically Optimal Reinforcement Learning*. PhD Thesis, Rutgers The State University of New Jersey, Graduate School-Newark.
- <span id="page-37-9"></span>Puterman, M. L. (2014). *Markov decision processes: discrete stochastic dynamic programming*. John Wiley & Sons.
- <span id="page-37-8"></span>Qian, J., Fruit, R., Pirotta, M., and Lazaric, A. (2019). Exploration bonus for regret minimization in discrete and continuous average reward mdps. *Advances in Neural Information Processing Systems*, 32.
- <span id="page-37-12"></span>Russo, A. and Proutiere, A. (2024). Model-free active exploration in reinforcement learning. *Advances in Neural Information Processing Systems*, 36.
- <span id="page-37-7"></span>Saber, H., Pesquerel, F., Maillard, O.-A., and Talebi, M. S. (2024). Logarithmic regret in communicating MDPs: Leveraging known dynamics with bandits. In Yanıkoğlu, B. and Buntine, W., editors, *Proceedings of the 15th Asian Conference on Machine Learning*, volume 222 of *Proceedings of Machine Learning Research*, pages 1167–1182. PMLR.
- <span id="page-37-10"></span>Salomon, A., Audibert, J.-Y., and El Alaoui, I. (2013). Lower bounds and selectivity of weakconsistent policies in stochastic multi-armed bandit problem. *Journal of Machine Learning Research*, 14(1).
- <span id="page-37-3"></span>Talebi, M. S. and Maillard, O.-A. (2018). Variance-Aware Regret Bounds for Undiscounted Reinforcement Learning in MDPs. *Journal of Machine Learning Research*, pages 1–36. Publisher: Microtome Publishing.
- <span id="page-37-6"></span>Thompson, W. R. (1933). On the Likelihood that One Probability Exceeds Another in View of the Evidence of Two Samples. *Biometrika*, 25(3-4):285–294.
- <span id="page-37-11"></span>Tirinzoni, A., Al Marjani, A., and Kaufmann, E. (2022). Near Instance-Optimal PAC Reinforcement Learning for Deterministic MDPs. In Koyejo, S., Mohamed, S., Agarwal, A., Belgrave, D., Cho, K., and Oh, A., editors, *Advances in Neural Information Processing Systems*, volume 35, pages 8785–8798. Curran Associates, Inc.
- <span id="page-37-0"></span>Tranos, D. and Proutiere, A. (2021). Regret Analysis in Deterministic Reinforcement Learning. *arXiv:2106.14338 [cs, stat]*. arXiv: 2106.14338.
- <span id="page-37-13"></span>Wald, A. (1945). Sequential tests of statistical hypotheses. *The Annals of Mathematical Statistics*, 16(2):117–186.

<span id="page-38-2"></span>Watkins, C. J. and Dayan, P. (1992). Q-learning. *Machine learning*, 8:279–292.

- <span id="page-38-0"></span>Zhang, Z. and Ji, X. (2019). Regret Minimization for Reinforcement Learning by Evaluating the Optimal Bias Function. In Wallach, H., Larochelle, H., Beygelzimer, A., Alché-Buc, F. d., Fox, E., and Garnett, R., editors, *Advances in Neural Information Processing Systems*, volume 32. Curran Associates, Inc.
- <span id="page-38-1"></span>Zhang, Z. and Xie, Q. (2023). Sharper Model-free Reinforcement Learning for Average-reward Markov Decision Processes. In *The Thirty Sixth Annual Conference on Learning Theory*, pages 5476–5477. PMLR.

## List of notations



## <span id="page-40-1"></span><span id="page-40-0"></span>A Supplementary proofs for the regret lower bound

## A.1 On self-normalized expected deviations of the empirical mean

<span id="page-40-3"></span>In this paragraph, we provide a technical lemma for the proof of [Proposition 9.](#page-15-5)

**Lemma A.1.** *Consider*  $X_n \in [0, 1]$  *a family of r.v. with*  $\mathbb{E}[X_n|\mathcal{F}_n] = \mu$ *. Let*  $\widehat{\mu}_n := \frac{1}{n}$  $\frac{1}{n} \sum_{k=1}^{n} X_k$  their *empirical mean. Let N a random variable of support*  $\{0, 1, \ldots, T\}$  *where*  $T \geq 1$  *is a fixed scalar. Then, for all*  $\varepsilon > 0$ *,* 

$$
\mathbb{E}[N(\widehat{\mu}_N - \mu)] \leq \varepsilon (\mathbb{E}[N] + \log(1+T)) + \sqrt{\mathbb{E}\Big[N\log\Bigl(2\vee \tfrac{3\sqrt{1+N}\log(1+T)}{2\varepsilon^3\mathbb{E}[N]}\Bigr)\Big]} + 1.
$$

*Proof.* Let  $\delta > 0$  that shall be tuned later. By Hoeffding's Lemma,  $X_n$  is conditionally  $\sigma$ -subgaussian for  $\sigma = \frac{1}{2}$  $\frac{1}{2}$ . By a time-uniform Azuma-Hoeffding's inequality [\(Bourel et al.,](#page-35-5) [2020,](#page-35-5) Lemma 5), for all  $m \geq 1$ ,

<span id="page-40-4"></span>
$$
\mathbb{P}\left(\exists m \le n \le T, |\widehat{\mu}_n - \mu| \ge 2\sigma \sqrt{\frac{\log(T\sqrt{1+T})}{m}}\right) \le \frac{1}{T}.\tag{A.1}
$$

Setting  $m = m_{\varepsilon} := \left(\frac{2\sigma}{\varepsilon}\right)$  $\frac{d\sigma}{\epsilon}$ )<sup>2</sup> log(*T*  $\sqrt{1+T}$ ), we have  $\mathbb{P}(\exists m_{\epsilon} \leq n \leq T, |\widehat{\mu}_n - \mu| \geq \epsilon) \leq \frac{1}{T}$  $\frac{1}{T}$ . The target expectation is split into two. Denoting  $f(N) := N(\widehat{\mu}_N - \mu)$ , we write:

$$
\mathbb{E}[N(\widehat{\mu}_N - \mu)] = \mathbb{E}[f(N)\mathbb{1}(N \ge m_\varepsilon)] + \mathbb{E}[f(N)\mathbb{1}(N < m_\varepsilon)].
$$
\n(A.2)

We start by controlling  $\mathbb{E}[f(N)\mathbb{1}(N \ge m_{\varepsilon})]$ . By construction of  $m_{\varepsilon}$ , we have:

$$
\mathbb{E}[f(N)\mathbb{1}(N \ge m_{\varepsilon})] \le \mathbb{E}[f(N)\mathbb{1}(N \ge m_{\varepsilon})\mathbb{1}([\widehat{\mu}_N - \mu] < \varepsilon)] + \mathbb{E}[f(N)\mathbb{1}(N \ge m_{\varepsilon})\mathbb{1}([\widehat{\mu}_N - \mu] \ge \varepsilon)]
$$
\n
$$
\le \varepsilon \mathbb{E}[N] + T\mathbb{P}(\exists m \le n \le T, |\widehat{\mu}_n - \mu| \ge \varepsilon)
$$
\n(by (A.1)) \le \varepsilon \mathbb{E}[N] + 1.

We continue with  $\mathbb{E}[f(N)\mathbb{1}(N < m_{\varepsilon})]$ . Denote  $\mathcal{E}_{\delta} := (\forall n \ge 1, n(\widehat{\mu}_n - \mu)^2 \le 4\sigma^2 \log(\sqrt{1 + n}/\delta))$ . By a time problem Agroup Hassel is expected to each problem that the state last 1. S. We time-uniform Azuma-Hoeffding's inequality again, this good event has probability at least  $1 - \delta$ . We obtain:

$$
\mathbb{E}[f(N)\mathbb{1}(N < m_{\varepsilon})] = \mathbb{E}[f(N)\mathbb{1}(N < m_{\varepsilon})\mathbb{1}(\mathcal{E}_{\delta})] + \mathbb{E}[f(N)\mathbb{1}(N < m_{\varepsilon})\mathbb{1}(\mathcal{E}_{\delta}^c)]
$$
\n
$$
\leq 2\sigma \mathbb{E}\left[\sqrt{N\log\left(\frac{\sqrt{1+N}}{\delta}\right)}\right] + \delta m_{\varepsilon}
$$
\n
$$
\leq 2\sigma \sqrt{\mathbb{E}\left[N\log\left(\frac{\sqrt{1+N}}{\delta}\right)\right]} + \delta m_{\varepsilon}
$$
\n
$$
\equiv 2\sigma \sqrt{\mathbb{E}\left[N\log\left(\frac{\sqrt{1+N}}{\delta}\right)\right]} + \delta\left(\frac{2\sigma}{\varepsilon}\right)^2 \log\left(T\sqrt{1+T}\right)
$$

where (\*) follows from Jensen's inequality. Set  $\delta := \frac{\varepsilon^3}{6\sigma^2}$  $6\sigma^2$ E[*N*]  $\frac{\mathbb{E}[N]}{\log(1+T)}$  and plug everything together.  $\Box$ 

Applied to sequential control, where  $N_T$  is the number of triggers up to time *T*, we see that when  $\mathbb{E}[N_T] + \mathbb{E}[\log(N_T)] = \Omega(\log(T))$ , then  $\mathbb{E}[N_T(\widehat{\mu}_{N_T} - \mu)] = o(\mathbb{E}[N])$ .

### <span id="page-40-2"></span>A.2 Comments on less asymptotic regret lower bounds

The techniques used to establish [Theorem 3](#page-9-0) are all very asymptotic. This is no surprise, because the whole theory is built on a very asymptotic notion of consistency [\(Definition 2\)](#page-6-4), that only asks

#### V. Boone & OA. Maillard 41 January 23, 2025

that learners eventually converge to optimal play. The asymptotic speed of that convergence  $o(T<sup>\eta</sup>)$ has nothing to do the possibly arbitrarily long burn-in time before the bound  $T^{\eta}$  starts to barely holds. This allows for algorithms that are asymptotically optimal in theory, but impractical because of their immense burn-in times. This is reproached by [Burnetas and Katehakis](#page-35-0) [\(1997](#page-35-0)) to the solution of [Agrawal et al.](#page-34-0) [\(1988b\)](#page-34-0), until their very solution was itself criticized for its impracticability by [Pesquerel and Maillard](#page-37-2) [\(2022](#page-37-2)) two decades later. The lower bound of [Lai and Robbins](#page-36-0) [\(1985](#page-36-0)) has also been pointed out for its over-asymptotic nature by [Garivier et al.](#page-36-7) [\(2018](#page-36-7)), with Thompson Sampling [Thompson](#page-37-6) [\(1933](#page-37-6)) beating the asymptotic lower bound  $K(M) \log(T)$  even for large time horizons.

This kind of story is common and there have been many attempts at patching the asymptotic inclination of theory: the trend for finite time bounds, second order terms of asymptotic lower bounds, or straight up modifications of the learning framework.

Properly addressing the asymptotic nature of our own [Theorem 3](#page-9-0) goes way beyond the scope of this paper, but we thought important to leave a few elements behind. Following the direction of finite time bounds, we first introduce a notion of consistency that is less asymptotic than [Definition 2.](#page-6-4)

**Definition A.1** (Timely-consistent learner). Let  $\eta : \mathbb{N} \to [0, 1]$  *a function satisfying*  $\eta(t) = o(1)$ . A *learning agent*  $A$  *is said*  $n$ -timely-consistent on M, if for all  $M \in M$ ,

$$
\exists T_{\mathbf{M}} \in \mathbb{N}, \forall T \ge T_{\mathbf{M}}, \sup_{x: \Delta_{\star}(x:\mathbf{M})>0} \mathbb{E}_{s_0}^{\mathbf{M},\mathbb{A}} \bigg[ \frac{N_{T+1}(x)}{T} \bigg] \le \eta(T).
$$

Observe that this definition is expressed in terms of visits rather than of regret. This is done so in order to streamline the argument behind the regret lower bound. Consider an  $\eta$ -timely-consistent learner A and let us mimic the computations done for the simple example of discriminating random variable in [Section 4.1.](#page-10-0) Let  $M^{\dagger}$  such that  $X_{\star}(M^{\dagger}) \cap X_{\star}(M) = \emptyset$  and let  $U := \sum_{x \in X_{\star}(M)} N_{T+1}(x)$ . By assumption and provided that  $T \ge \max\{T_M, T_{M^{\dagger}}\}\)$ , we directly obtain

$$
\mathbb{E}_{s_0}^{\mathbf{M},\mathbb{A}}[N_{T+1}(x)] \ge (1-|\mathcal{X}|\eta(T))T \text{ and } \mathbb{E}_{s_0}^{\mathbf{M}^\dagger,\mathbb{A}}[N_{T+1}(x)] \le |\mathcal{X}|\eta(T)T.
$$

Setting  $\mathcal{E} := (U \leq \frac{1}{2})$  $\frac{1}{2}T$ ), we deduce that  $\mathbb{P}_{s_0}^{\mathbf{M},\mathbb{A}}$  $\lim_{s_0} A(\mathcal{E}) \leq 2|\mathcal{X}|\eta(T)$  and  $\mathbb{P}_{s_0}^{\mathbf{M}^\dagger,\mathcal{A}}$  $S_0^{M^{\dagger},A}(\mathcal{E}) \geq 1 - 2|\mathcal{X}|\eta(T).$  For  $\eta(T) \le \frac{1}{2|X|}$  and invoking [Corollary C.4,](#page-47-2) we conclude that:

$$
\mathbb{E}_{s_0}^{\mathbf{M},\mathbb{A}}\bigg[\sum_{x\in\mathcal{X}}N_{T+1}(x)\mathrm{KL}_x(\mathbf{M}||\mathbf{M}^\dagger)\bigg]\geq \mathrm{kl}\big(2|\mathcal{X}|\eta(T),1-2|\mathcal{X}|\eta(T)\big).
$$

Following the recipe described in [Section 4.2](#page-12-0) to convert the above into a regret lower bound, we normalize by *T* and invoke [Proposition 1](#page-6-3) to obtain the finite time bound below:

**Theorem A.2.** Let  $\mathbb A$  an  $\eta$ -timely-consistent learner. For all  $T \geq T_M$ , then  $\text{Reg}(T; M, \mathbb A, s_0)$  +  $\text{sp}(\mathbf{b}_\star(\mathbf{M}))$  *is lower-bounded by* 

$$
T \inf_{\mu \in \mathbb{R}_+^X} \left\{ \sum_{x \in X} \mu(x) \Delta_\star(x; \mathbf{M}) : \forall \mathbf{M}^\dagger \in \text{Cnf}_{\hat{\tau}_\star}(\mathbf{M}), \sum_{x \in X} \mu(x) \text{KL}_x(\mathbf{M}||\mathbf{M}^\dagger) \ge \mathbb{1} (T_{\mathbf{M}^\dagger} < T) \frac{\text{kl}(2|X|\eta(T), 1 - 2|X|\eta(T))}{T} \right\}
$$

*where*  $\text{Cnf}_{\mathfrak{X}}(\mathbf{M}) := \{ \mathbf{M}^{\dagger} \in \text{Alt}(\mathbf{M}) : \mathcal{X}_{\mathfrak{X}}(\mathbf{M}^{\dagger}) \cap \mathcal{X}_{\mathfrak{X}}(\mathbf{M}) = \emptyset \}.$ 

### <span id="page-41-0"></span>A.3 Supplementary content for the Switch property

In this paragraph, we provide a few proofs of the [Section 7,](#page-29-0) especially by providing a proof of [Proposition 21,](#page-31-1) of which the statement is recalled below.

**[Proposition 21.](#page-31-1)** *Let*  $x = (s, \pi(s))$  *and assume that*  $C_{+}^{sw}(x) \neq \emptyset$ *.* 

- (1) If  $\pi^*$  is ergodic in **M**, then Switch holds at x.
- (2) If  $\pi^*$  is unichain in **M**, then Switch holds at x except when  $s \notin S(\pi^*, M)$ .
- (3) If  $\pi^*$  is multichain in **M**, then Switch holds at x when  $s \in S(\pi, M) \cap S(\pi^*, M)$  and does not *hold when*  $s \notin S(\pi^*, M)$ .

*Proof of [Proposition 21.](#page-31-1)* Let us denote  $\pi = \pi_x^*$ . Before proceeding, with discuss the following few cases:

**Case a.** Assume that  $s \notin S(\pi, M)$ . Let us remind that  $\pi$  coincides with  $\pi^*$  on  $S \setminus \{s\}$ , hence in particular on  $S(\pi, M)$ . This means that on the set of recurrent states  $S(\pi, M)$  of  $\pi$ ,  $\pi$  behaves as  $\pi^*$ . Since  $S(\pi, M)$  is a closed set, this means that it is also a recurrent set according to  $\pi^*$ , which shows  $S(\pi, M) \subset S(\pi^*, M)$ . Now when  $\pi^*$  is unichain,  $S(\pi, M) = S(\pi^*, M)$ . In particular  $s \notin S(\pi^*, M)$ , and since  $\pi$  coincides with  $\pi^*$ , they then have same gain hence  $\pi$  is already optimal in M, which contradicts assumption  $\pi \notin \Pi^*(M)$ .

**Case b.** Now assume instead that  $s \in S(\pi, M)$ . For a switch MDP  $\widetilde{M} \in C_{X}(M)$  to be a confusing instance, the gain of  $\pi$  must be larger than that of  $\pi^*$ , without modifying the MDP on  $\mathcal{X}_\star(\mathbf{M})$ .

**Case b.1** As a result, when  $s \notin S(\pi^*, M)$ , then switching the effect of action *a* in *s* and increasing the reward of this pair cannot modify the gain in  $M^{\dagger}$  beyond the gain of  $\pi^*$ , hence Switch(x) cannot hold in such cases. A special case is when  $S(\pi^*, M)$  is further not reachable from *s* under  $\pi$ . In particular, when  $\pi$  is unichain, this means no state from  $S(\pi, M)$  communicates with  $S(\pi^*, M)$  under  $\pi$ , which means *x* is a bottleneck.

**Case b.2.** It remains to deal with the case when  $s \in S(\pi, M) \cap S(\pi^*, M)$ . In this case, switching the effect of *a* in  $M^{\dagger}$  ensures the gain of the policy is not smaller than that of  $\pi^{\star}$  in M, and increasing the mean reward ensures it becomes larger. Indeed, for  $M^{\dagger} \in C_{X}(M)$ , since the Markov chain induced by  $\pi^{\star}$  in  $M^{\dagger}$  coincides with the Markov chain induced by  $\pi^{\star}$  in M, this means choosing distribution r' with mean  $m' > m(s, \pi^*(s))$  at pair *x* ensures that  $\mathbf{g}_{\pi^*_x}^{\dagger}(s_1) > \mathbf{g}_{\pi^*_x}^{\dagger}(s_1)$  for all  $s_1$ . Hence  $\mathbf{M}^{\dagger} \in$  $\text{Cnf}_{\star}(\mathbf{M}) \cap \mathcal{B}(\pi_{x}^{\star}, \mathbf{M})$  and Switch(*x*) holds.

For the case (1) in [Proposition 21,](#page-31-1) we note that by ergodicity of  $\pi^*$ ,  $S(X_*(M)) = S$ . Now  $s \notin$  $S(\pi, M)$ , would imply  $\pi \notin \Pi^*(M)$  by a) which is excluded by assumption, hence we are in the case **b.2** and Switch(x) holds. Regarding case (2) in [Proposition 21,](#page-31-1) then  $s \notin S(\pi, M)$  is excluded by a) hence we conclude by **b.1** and **b.2**. Regarding the multichain case, the only difference is that  $s \notin S(\pi, M)$  may not contradict that  $\pi$  is sub-optimal. But the conclusion regarding **b.1** and **b.2** still holds. may not contradict that  $\pi$  is sub-optimal. But the conclusion regarding **b.1** and **b.2** still holds.

## <span id="page-42-0"></span>B Inevitable sets and details on informational constraints

This section provides technical details on the proofs of informational constraints, especially [Proposition 4,](#page-10-3) [Proposition 6](#page-13-0) and [Corollary 7.](#page-13-2)

### <span id="page-42-1"></span>B.1 Inevitable sets and the inevitability lemma

A key idea, invoked at several places in the proofs of these statements, is the notion of inevitable set. Inevitable sets are sets of pairs that every policy of a reference set is forced to go through infinitely many times, i.e., linearly often and regardless of the initial state.

**Definition B.1.** A set of pairs  $X_c \subseteq X$  is said **inevitable** relatively to  $\Pi^{\star}(\mathbf{M})$  if, for all  $\pi \in \Pi^{\star}(\mathbf{M})$  and *all initial state*  $s_0 \in S$ *, we have*  $\mathbb{P}_{s_0}^{\mathbf{M}, \pi} \{ \forall n, \exists m \geq n : X_m \in X_c \} = 1$ *.* 

Although inevitable sets could be described to different sets than  $\Pi^{\star}(\mathbf{M})$ , the generalization won't be required, and we will speak of *inevitable sets* rather than *inevitable sets relatively to* Π<sup>\*</sup>(M) in the sequel. By standard Markov chain theory [Levin and Peres](#page-36-6) [\(2017](#page-36-6)), recurrent and positive recurrent are equivalent when the number of states is finite, hence the condition " $\forall s_0 \in S$ ,  $\mathbb{P}_{s_0}^{M,\pi} \{\forall n, \exists m \geq n : S_n \neq \emptyset\}$  $X_m \in \mathcal{X}_c$  = 1" can be changed to " $\forall s_0 \in S$ ,  $\mathbb{E}_{s_0}^{\mathbf{M}, \pi}$  [inf{ $t \geq 2 : X_t \in \mathcal{X}_c$ ] <  $\infty$ " or again to " $\forall s_0 \in S$ ,  $\mathbb{E}_{s_0}^{\mathbf{M}, \pi}[\sum_{t=1}^T \mathbb{1}(X_t \in \mathcal{X}_c)] = \Omega(T)^{\nu}.$ 

Inevitability requires that, for every  $\pi \in \Pi^*(M)$ ,  $\mathcal{X}_c$  is visited linearly often. This point-wise property is converted to a more uniform one via the remarkable result below, actually stating that in probability, the number of visits of an inevitable set  $X_c$  satisfies  $\sum_{x \in X_c} N_{T+1}(x) = \Omega(T - \text{Reg}(T; \mathbf{M}, \mathbb{A}))$ .

<span id="page-43-1"></span>**Lemma B.1** (Inevitability lemma). Let **M** ∈ *M* and assume that  $X_c$  ⊆ X is inevitable. There exist *constants*  $\varepsilon_c$ ,  $D_c$  > 0 *such that, whatever the learning agent* A *and the initial state*  $s_0$ *, we have:* 

$$
\forall u \ge 0, \quad \mathbb{P}_{s_0}^{\mathbf{M},\mathbf{A}} \Biggl( \sum_{x \in \mathcal{X}_c} N_{T+1}(x) + D_c \sum_{x \in \mathcal{X}_-(\mathbf{M})} N_{T+1}(x) \le \varepsilon_c T - u \Biggr) \le \exp \Biggl( - \frac{2u^2}{TD_c^2} \Biggr).
$$

*Moreover,*  $\mathbb{E}_{s_0}^{\mathbf{M},\mathbb{A}}$  $\sum_{x_0}^{M,A} [\sum_{x \in \mathcal{X}_c} N_{T+1}(x)] + D_c \mathbb{E}^{M,A}_{s_0}$  $\sum_{s_0}^{M,A} [\sum_{x \in \mathcal{X}_-(M)} N_{T+1}(x)] \ge \varepsilon_c T - D_c.$ 

*Proof.* The idea is to construct the optimal policy of that visits  $X_c$  as rarely as possible. Consider the reward function  $f(x) := -1(x \in X_c)$  and consider  $M_f|_{X_{\mathfrak{X}}(M)}$ , a copy of M restricted to  $X_{\mathfrak{X}}(M)$ and with reward function *f*. Let  $\pi_f$  a bias optimal policy of  $M_f|_{X_{\mathcal{H}}(M)}$ ; It is also a policy of M since  $S(X_{\hat{X}}(M)) = S$ . Moreover,  $\pi \in \Pi^{\star}(M)$  because  $\pi$  only picks pairs such that  $\Lambda_{\star}(x; M) = 0$ , hence is guaranteed to have optimal gain via [Proposition 1.](#page-6-3) Let  $\mathbf{g}_f$ ,  $\mathbf{b}_f$  and  $\mathbf{\Lambda}_f$  its gain, bias and gap functions on M under the reward function *f*. By construction of  $\pi_f$ , we have  $\Delta_f(x) \ge 0$  for all  $x \in X_{\mathcal{X}}(M)$ . Let  $\varepsilon_c := -\max_{s \in S} g_f(s)$ , and denote  $D_c := \max\{sp(\mathbf{b}_f), \max_{x \in \mathcal{X}} |\Delta_f(x)|\} < \infty$ . Since  $\pi \in \Pi^*(\mathbf{M})$  and  $\mathcal{X}_c$  is inevitable, we have  $\varepsilon_c > 0$ . Now,

$$
\sum_{x \in X_c} N_{T+1}(x) = -\sum_{t=1}^T f(X_t)
$$
\n
$$
\stackrel{(*)}{=} -\sum_{t=1}^T \Big( \mathbf{g}_f(S_t) + (\mathbf{e}_{S_t} - \mathbf{p}(X_t)) \mathbf{b}_f - \mathbf{\Delta}_f(X_t) \Big)
$$
\n
$$
\stackrel{(*)}{\geq} \varepsilon_c T + \sum_{t=1}^T (\mathbf{e}_{S_{t+1}} - \mathbf{p}(X_t)) \mathbf{b}_f - D_c \Bigg( 1 + \sum_{x \in X_{-}(\mathbf{M})} N_{T+1}(x) \Bigg)
$$

where (\*) invokes the Poisson equation  $\mathbf{g}_f(s) + \mathbf{b}_f(s) = f(s, a) + \mathbf{p}(s, a)\mathbf{b}_f + \Delta_f(s, a)$ , and (§) that  $\Delta_f$ (M) ≥ 0 for *x* ∈  $\chi$ <sub>x</sub>(M). By Azuma-Hoeffding's inequality, the MDS term satisfies:

$$
\forall u \geq 0, \quad \mathbb{P}_{s_0}^{\mathbf{M},\mathbb{A}} \Bigg( \sum_{t=1}^T (\mathbf{e}_{S_{t+1}} - \mathbf{p}(X_t)) \mathbf{b}_f \leq -u \Bigg) \leq \exp \Bigg( -\frac{2u^2}{TD_c^2} \cdot \Bigg)
$$

This provides the result in probability. The result in expectation is immediately obtained by using that  $\mathbb{E}_{so}^{\mathbf{M},\mathbb{A}}$  $\sum_{s_0}^{\mathbf{M},\mathbb{A}}[\sum_{t=1}^T(\mathbf{e}_{S_{t+1}} - \mathbf{p}(X_t))\mathbf{b}_f] = 0.$ 

**Discussion.** In [Lemma B.1,](#page-43-1) what is important is that  $\varepsilon_c \neq 0$ . In a few scenarios, for instance when  $X_c = X_{\star}(\mathbf{M})$ , one can check that  $\varepsilon_c = 1$ . This is actually the idea behind [Lemma 8,](#page-13-3) that can be seen as a simplified version of [Lemma B.1](#page-43-1) when  $X_c = X_{\star}(M)$ . Overall, Lemma B.1 is immensely useful in the proofs of [Proposition 4](#page-10-3) and [Proposition 6.](#page-13-0)

#### <span id="page-43-0"></span>B.2 Proof of [Lemma 5](#page-11-0)

We start by providing a proof of [Lemma 5](#page-11-0) which is essential to [Proposition 4.](#page-10-3) We recall its statement below.

V. Boone & OA. Maillard 44 January 23, 2025

**[Lemma 5.](#page-11-0)** *Let*  $M \in \mathcal{M}$ *, pick*  $M^{\dagger}$  ∈ Alt $(M)$  *and let*  $\mathcal{X}_c := \{x \in \mathcal{X}_{\star}(M^{\dagger}) : \Delta_{\star}(x; M) > 0\}$ *. There exist constants*  $\varepsilon_c^{\dagger}$ ,  $D_c^{\dagger}$  > 0 *such that, whatever the learning agent* A *and the initial state*  $s_0$ *, we have:* 

$$
\forall u \geq 0, \quad \mathbb{P}_{s_0}^{\mathbf{M}^\dagger, \mathbb{A}} \Biggl( \sum_{x \in \mathcal{X}_c} N_{T+1}(x) + D_c^\dagger \sum_{x \in \mathcal{X}_-(\mathbf{M})} N_{T+1}(x) \leq \varepsilon_c^\dagger T - u \Biggr) \leq \exp \Biggl( -\frac{2u^2}{TD_c^{\dagger 2}} \Biggr).
$$

*Proof.* We show that  $X_c$  is inevitable in  $M^{\dagger}$ . The conclusion will follow by [Lemma B.1.](#page-43-1) Let  $\pi^{\dagger} \in \Pi^{\star}(\mathbf{M}^{\dagger}).$ 

We say that a state  $s_{\star}$  is *reachable* from *s* in  $\mathbf{M}' \in \{ \mathbf{M}, \mathbf{M}^{\dagger} \}$  if  $\mathbb{P}_{s}^{\mathbf{M}', \pi^{\dagger}} \{ \exists n : S_n = s_{\star} \} > 0$ .

Assume, by contradiction, that there is  $s \in S$  such that  $\mathbb{P}_{s}^{\mathbf{M}^{\dagger}, \pi^{\dagger}} \{ \forall n, \exists m \geq n : X_m \in X_c \} < 1$ ; There must exist  $s^{\dagger} \in S$  reachable from *s* in M<sup>†</sup> such that  $\mathbb{P}^{\mathbf{M}^{\dagger}, \pi^{\dagger}}_{s^{\dagger}}$  $\int_{s^{\dagger}}^{\mathbf{M}^{\dagger}, \pi^{\dagger}} \{ \forall n, \exists m : X_m \in \mathcal{X}_c \} = 0$ . Let  $\mathcal{S}^{\dagger}$  the collection of all states that are reachable from  $s^{\dagger}$  in  $M^{\dagger}$ . Remark that every state of  $S^{\dagger}$  is reachable (under  $\pi^{\dagger}$ ) is reachable from any other of  $S^{\dagger}$  in M<sup>†</sup>. We see that for all  $s \in S^{\dagger}$  and all  $a \in \mathcal{A}(s)$  with  $\pi^{\dagger}(a|s) > 0$ , we have  $\Delta_{\star}(s, a|\mathbf{M}) = 0$ .

From there, we construct  $\pi \in \Pi^*(M^{\dagger}) \cap \Pi^*(M)$ , as the policy given by:

$$
\pi(a|s) := \begin{cases} \pi^{\dagger}(a|s) & \text{if } s \in S^{\dagger}; \\ \frac{1}{|\mathcal{A}(s)|} & \text{if } s \notin S^{\dagger}. \end{cases}
$$

Because it is uniform outside of  $S^{\dagger}$ ,  $S^{\dagger}$  is reachable under  $\pi$  from every state both in **M** and **M**<sup>†</sup>. Now, observe that for all  $s \in S^{\dagger}$  and  $a \in \mathcal{A}(s)$  with  $\pi(a|s) > 0$ , we have supp( $\mathbf{p}^{\dagger}(s, a) \subseteq S^{\dagger}$ . Since  $\mathbf{p} \ll \mathbf{p}^{\dagger}$ , we similarly have  $supp(\mathbf{p}(s, a)) \subseteq \mathcal{S}^{\dagger}$ . It follows that the recurrent states of  $\pi$  satisfy  $\mathcal{S}_{\pi}(\mathbf{M}^{\dagger}) = \mathcal{S}^{\dagger}$  and  $\mathcal{S}_{\pi}(\mathbf{M}) \subseteq \mathcal{S}^{\dagger}$ . In other words, both on **M** and **M**<sup>†</sup>, the iterates of  $\pi$  are eventually confined within  $\mathcal{S}^{\dagger}$ , whatever the initial state. Since  $S_{\pi}(\mathbf{M}^{\dagger}) = S^{\dagger}$  which is a component of recurrent states of  $\pi^{\dagger}$ , and that  $\pi^{\dagger}$  satisfies  $\mathbf{g}_{\pi^{\dagger}}(\mathbf{M}^{\dagger}) = \mathbf{g}_{\star}(\mathbf{M}^{\dagger})$ , it follows that  $\mathbf{g}_{\pi}(\mathbf{M}^{\dagger}) = \mathbf{g}_{\star}(\mathbf{M}^{\dagger})$ . Since  $\mathcal{S}_{\pi}(\mathbf{M}) \subseteq \mathcal{S}^{\dagger}$  and that every pair *x* that  $\pi$  plays on  $S^{\dagger}$  satisfies  $\Delta_{\star}(\pi; M) = 0$ , it follows by [Proposition 1](#page-6-3) that  $g_{\pi}(M) = g_{\star}(M)$ . So  $\pi \in \Pi^{\star}(\mathbf{M}^{\dagger}) \cap \Pi^{\star}(\mathbf{M});$  A contradiction with  $\mathbf{M}^{\dagger} \in \text{Alt}(\mathbf{M})$ .

### <span id="page-44-0"></span>B.3 Proof of [Proposition 6](#page-13-0)

To conclude this section, we provide a proof of [Proposition 6.](#page-13-0)

**[Proposition 6.](#page-13-0)** *Let*  $M \in \mathcal{M}$  *and fix*  $x_{\star} \in \mathcal{X}_{\star}(M)$ *. Assume that, for all*  $\varepsilon > 0$ *, there exists*  $M' \in \mathcal{M}$  *such that (1)*  $\mathbf{M}'$  *and*  $\mathbf{M}$  *only differ with*  $\mathbf{r}(x_{\star}) \neq \mathbf{r}'(x_{\star})$ *, (2)*  $\mathbf{m}(x_{\star}) < \mathbf{m}'(x_{\star})$  *and* (3)  $\text{KL}(\mathbf{r}(x_{\star})||\mathbf{r}'(x_{\star})) < \varepsilon$ *. Then, for every consistent learner* A *and regardless of the initial state*  $s_0 \in S$ *,* 

$$
\mathbb{E}_{s_0}^{\mathbf{M},\mathbb{A}}[N_{T+1}(x_\star)] = \omega(\log(T)).
$$

*Proof.* Let  $\varepsilon > 0$  small enough (to be chosen later) and pick  $M' \in M$  as the above. The idea of the proof is to show that  $X_c := \{x_\star\}$  is an inevitable set in M', i.e., that every optimal policy of M' plays  $x_{\star}$  infinitely often regardless of the initial state. Let  $\delta := \mathbf{m}'(x_{\star}) - \mathbf{m}(x_{\star}) > 0$ . Given a policy  $\pi \in \Pi$ , we denote  $\mu_{\pi}(x|s_0) := \lim_{T \to \infty} \frac{1}{T}$  $\frac{1}{T} \mathbb{E}_{s_0}^{\mathbf{M}, \pi} [\sum_{t=1}^T \mathbb{1}(X_t = x)]$  the asymptotic average number of plays of *x* under  $\pi$  in **M** starting from  $s_0$ . Since **M** and **M**' have the same transition kernel, we obtain:

$$
\mathbf{g}_{\pi}(s_0; \mathbf{M}') = \mathbf{g}_{\pi}(s_0; \mathbf{M}) + \mu_{\pi}(x_{\star}|s_0)\delta.
$$

Provided that  $\delta < \Delta_{\mathbf{g}}(\mathbf{M}) := \min{\{\|\mathbf{g}_{\star}(\mathbf{M}) - \mathbf{g}_{\pi}(\mathbf{M})\|_{\infty} : \pi \notin \Pi^{\star}(\mathbf{M})\}}$ , it follows that optimal policies of M' are necesseraly optimal in M. Then, optimal policies of M' are found as the optimal policies of M that maximize  $\mu_{\pi}(x_{\star}|s_0)$ , i.e., such that  $\mu_{\pi}(x_{\star}|s_0) = \max_{\pi' \in \Pi^*(M)} \mu_{\pi'}(x_{\star}|s_0)$ . Because  $x_{\star} \in \mathcal{X}_{\star}(M)$ , it follows that this maximum is positive and that  $x<sub>λ</sub>$  is visited linearly often under every optimal policy

V. Boone & OA. Maillard 45 January 23, 2025

of M'; Hence, that  $\chi_c$  is inevitable. This all is provided that  $\delta < \Delta_g(M)$ . This assumption is met as soon as  $KL(\mathbf{r}(x_{\star})||\mathbf{r}'(x_{\star})) \to 0$  implies  $\mathbf{m}'(x_{\star}) \to \mathbf{m}(x_{\star})$ , which is true in particular when rewards have support within [0, 1].

So,  $\{x_{\star}\}\$ is inevitable in M'. By [Lemma B.1,](#page-43-1) there exists  $\varepsilon'_{c}$ ,  $D'_{c} > 0$  such that:

$$
\forall u \ge 0, \quad \mathbb{P}_{s_0}^{\mathbf{M}',A} \Bigg( N_{T+1}(x_{\star}) + D_c' \sum_{x \in \mathcal{X} \cup (\mathbf{M})} N_{T+1}(x) \le \varepsilon_c' T - u \Bigg) \le \exp \Bigg( - \frac{2u^2}{T D_c'^2} \Bigg).
$$

The remaining of the proof is essentially similar to the one of [Proposition 4.](#page-10-3) Let  $\alpha := sp(b_{\star}(M'))$ , introduce  $\varphi(T) := \sqrt{\frac{\text{Reg}(T; \mathbf{M}', \mathbb{A}, s_0) + \alpha}{T} \text{ and } \psi(T)} := D'_c \text{dmin}(\mathbf{\Delta}_{\star}(\mathbf{M}'))^{-1} \sqrt{T(\text{Reg}(T; \mathbf{M}', \mathbb{A}, s_0) + \alpha)}}.$ Combining the above inequality with Markov's inequality, we find:

$$
\forall u \ge 0, \quad \mathbb{P}_{s_0}^{\mathbf{M}',\mathbb{A}}(N_{T+1}(x_\star) \le \varepsilon'_c T - \psi(T) - u) \le \varphi(T) + \exp\left(-\frac{2u^2}{TD_c'^2}\right).
$$

To conclude, we aim at invoking [Corollary C.3](#page-46-3) with  $U := \frac{1}{1 + N\epsilon}$  $\frac{1}{1+N_{T+1}(x_{\star})}$ . We start by upper-bounding  $\mathbb{E}_{so}^{\mathbf{M}',\mathbb{A}}$  $\binom{M^r, A}{s_0}$ [*U*]. We have:

$$
\mathbb{E}_{s_0}^{\mathbf{M}',\mathbb{A}}[U] \equiv \mathbb{E}_{s_0}^{\mathbf{M}',\mathbb{A}} \left[ \frac{1}{1 + N_{T+1}(x_\star)} \right] \leq \inf_{\nu \geq 0} \left\{ \frac{1}{1 + \nu} + \mathbb{P}_{s_0}^{\mathbf{M}',\mathbb{A}}(N_{T+1}(x_\star) \leq \nu) \right\}
$$
  
\n
$$
\leq \inf_{\nu \geq 0} \left\{ \frac{1}{1 + \nu} + \varphi(T) + \exp\left(-\frac{2(\varepsilon_c' T - \psi(T) - \nu)^2}{T D_c'^2} \right) \right\}
$$
  
\n
$$
\leq \frac{1}{1 + \frac{1}{2} \varepsilon_c' T} + \varphi(T) + \exp\left(-\frac{2(\frac{1}{2} \varepsilon_c' T - \psi(T))^2}{T D_c'^2}\right)
$$
  
\n
$$
\leq \frac{1}{1 + \frac{1}{2} \varepsilon_c' T} + \varphi(T) + \exp\left(-\frac{\varepsilon_c'^2 T}{2 D_c'^2} + \frac{2\varepsilon_c' \psi(T)}{D_c'^2}\right)
$$

where (†) follows by setting  $v := \frac{1}{2}$  $\frac{1}{2}\varepsilon_c^T$ . By strong consistency,  $\psi(T) = o(T)$  and  $\log \varphi(T) =$  $-\frac{1}{2}$  $\frac{1}{2}$  log(*T*) + o(log(*T*)). We conclude that log( $\mathbb{E}_{s_0}^{\mathbf{M}',A}$  $\int_{S_0}^{M',A} [U] \leq -\frac{1}{2} \log(T) + o(\log(T)).$ 

So, applying [Corollary C.3,](#page-46-3) we obtain:

$$
\varepsilon \mathbb{E}_{s_0}^{\mathbf{M},\mathbb{A}}[N_{T+1}(x_{\star})] \geq \mathbb{E}_{s_0}^{\mathbf{M},\mathbb{A}}[\log(U)] + \log\left(\frac{1}{\mathbb{E}_{s_0}^{\mathbf{M}',\mathbb{A}}[U]}\right)
$$
  
=  $-\mathbb{E}_{s_0}^{\mathbf{M},\mathbb{A}}[\log(1 + N_{T+1}(x_{\star}))] - \log\left(\mathbb{E}_{s_0}^{\mathbf{M}',\mathbb{A}}\left[\frac{1}{1 + N_{T+1}(x_{\star})}\right]\right)$   
 $\stackrel{\text{(t)}}{\geq} - \log\left(\mathbb{E}_{s_0}^{\mathbf{M},\mathbb{A}}[1 + N_{T+1}(x_{\star})]\right) + \frac{1}{2}\log(T) + o(\log(T))$ 

where (†) follows by Jensen's inequality, Since  $log(\mathbb{E}_{s_0}^{M,A})$  $N_{s_0}^{M,A}[1 + N_{T+1}(x_{\star})]$  is negligible in front of  $\mathbb{E}_{so}^{\mathbf{M},\mathbb{A}}$  $N_{s_0}^{M,A}[N_{T+1}(x_{\star})]$ . We conclude that  $\mathbb{E}_{s_0}^{M,A}$  $\binom{M,A}{s_0} [N_{T+1}(x_\star)] \geq \frac{1}{2s}$  $\frac{1}{2\varepsilon}$  log(*T*) + o(log(*T*)). As this holds for  $\varepsilon > 0$ arbitrarily small, we conclude accordingly.  $\square$ 

## <span id="page-45-0"></span>C Background from information theory

In this appendix and for the sake of self-containedness, we provide a proof of [\(6\)](#page-10-1) and [\(7\)](#page-11-1) that are both key to derive the regret lower bound of [Theorem 3.](#page-9-0) The curious reader may also read [Maillard](#page-36-12) [\(2019](#page-36-12)); [Kaufmann](#page-36-11) [\(2014](#page-36-11)); [Kaufmann et al.](#page-36-16) [\(2016\)](#page-36-16).

V. Boone & OA. Maillard  $46$  January 23, 2025

## <span id="page-46-0"></span>C.1 Change of measures and log-likelihood ratios

<span id="page-46-2"></span>We begin with an instance of the celebrated Radon-Nikodym' theorem, specialized for the stochastic process underlying a Markov decision process.

Theorem C.1 (Change of measure). *Let* M ≪ M′ *two Markov decision processes and fix an arbitrary learning agent* A *and*  $s \in S$ . If  $U \ge 0$  *is a*  $\sigma(H_T)$ *-measurable random variable, then:* 

$$
\mathbb{E}_{s}^{\mathbf{M}',\mathbb{A}}[U] \geq \mathbb{E}_{s}^{\mathbf{M},\mathbb{A}}[U\exp\{-L(H_t)\}].
$$

*Proof.* Let  $v_T$ ,  $v'_T$  the distributions of  $H_T$  induced by running A for *T* steps from *s* on **M**, **M**<sup>*'*</sup> respectively. We have  $v_T \ll v'_T$ , so by Radon-Nikodym's theorem, for every  $\sigma(H_T)$ -measurable random variable *V*, we have:

$$
\mathbb{E}_{s}^{\mathbf{M},\mathbb{A}}[V] \equiv \int V(h_T) \, \mathrm{d}v_T(h_T) = \int V(h_T) \, \frac{\mathrm{d}v_T}{\mathrm{d}v'_T}(h_T) \, \, \mathrm{d}v'_T(h_T) \equiv \mathbb{E}_{s}^{\mathbf{M}',\mathbb{A}} \bigg[ V \cdot \frac{\mathrm{d}v_T}{\mathrm{d}v'_T}(H_T) \bigg]
$$

where  $\frac{dv_T}{dv'_T}$  is the Radon Nikodym of  $v_T$  with respect to  $v'_T$ . By Markov's property, the Radon-Nikodym derivative can be written as:

$$
\frac{d\nu_T}{d\nu'_T}(H_T) = \frac{\prod_{t=1}^{T-1} \mathbf{p}(S_{t+1}|S_t, A_t) \mathbf{r}(R_t|S_t, A_t) \mathbb{A}(A_t|S_1, A_1, R_1, \dots, S_t)}{\prod_{t=1}^{T-1} \mathbf{p}'(S_{t+1}|S_t, A_t) \mathbf{r}'(R_t|S_t, A_t) \mathbb{A}(A_t|S_1, A_1, R_1, \dots, S_t)} \\
= \prod_{t=1}^{T-1} \frac{\mathbf{p}(S_{t+1}|S_t, A_t) \mathbf{r}(S_{t+1}|S_t, A_t)}{\mathbf{p}'(S_{t+1}|S_t, A_t) \mathbf{r}'(S_{t+1}|S_t, A_t)} \\
= \exp\left\{\sum_{t=1}^{T-1} \left(\log\left(\frac{\mathbf{p}(S_{t+1}|S_t, A_t)}{\mathbf{p}'(S_{t+1}|S_t, A_t)}\right) + \log\left(\frac{\mathbf{r}(S_{t+1}|S_t, A_t)}{\mathbf{r}'(S_{t+1}|S_t, A_t)}\right)\right)\right\} \\
=: \exp\{L(H_T)\}
$$

with the convention that  $log(0) = -\infty$ . Set  $V := U1(L(H_T) > -\infty)exp{-L(H_T)}$ , with the convention  $0 \cdot \infty = 0$ . We have:

$$
\mathbb{E}_{s}^{\mathbf{M}',\mathbb{A}}[U] \stackrel{(\dagger)}{\geq} \mathbb{E}_{s}^{\mathbf{M}',\mathbb{A}}[V \cdot \exp\{L(H_{T})\}]
$$
  

$$
\stackrel{(\dagger)}{=} \mathbb{E}_{s}^{\mathbf{M},\mathbb{A}}[U \cdot \mathbb{1}(L(H_{T}) > -\infty) \exp\{-L(H_{T})\}] \stackrel{(\S)}{=} \mathbb{E}_{s}^{\mathbf{M},\mathbb{A}}[U]
$$

where (†) uses that  $U \geq V$ , (‡) invokes Radon-Nikodym's theorem and (§) uses that, under M, A, we have  $L(H_T) > -\infty$  almost surely.  $□$ 

<span id="page-46-4"></span>Lemma C.2. *The log-likelihood ratio has expected value:*

$$
\mathbb{E}_{s}^{\mathbf{M},\mathbb{A}}\Bigg[\sum_{t=1}^{T-1}\Bigg(\log\Bigg(\frac{\mathbf{p}(S_{t+1}|S_{t},A_{t})}{\mathbf{p}'(S_{t+1}|S_{t},A_{t})}\Bigg)+\log\Bigg(\frac{\mathbf{r}(S_{t+1}|S_{t},A_{t})}{\mathbf{r}'(S_{t+1}|S_{t},A_{t})}\Bigg)\Bigg]=\mathbb{E}_{s}^{\mathbf{M},\mathbb{A}}\Bigg[\sum_{x\in\mathcal{X}}N_{T}(x)\mathbf{KL}_{x}(\mathbf{M}||\mathbf{M}')\Bigg].
$$

*Proof.* Direct application of the tower property. □

## <span id="page-46-1"></span>C.2 Simpler forms of the change of measure's inequality

<span id="page-46-3"></span>While the inequality of [Theorem C.1](#page-46-2) can be used as is, we provide below a few alternative (weaker) form that are often more easy to work with.

Corollary C.3. *Let* M ≪ M′ *two Markov decision processes and fix an arbitrary learning agent* A *and*  $s \in S$ *. If*  $U \ge 0$  *is a*  $\sigma(H_T)$ *-measurable random variable, then:* 

$$
\log \mathbb{E}_{s}^{\mathbf{M}',\mathbb{A}}[U] + \mathbb{E}_{s}^{\mathbf{M},\mathbb{A}}\Bigg[\sum_{x \in \mathcal{X}} N_T(x) \mathrm{KL}_x(\mathbf{M}||\mathbf{M}')\Bigg] \geq \mathbb{E}_{s}^{\mathbf{M},\mathbb{A}}[\log(U)].
$$

*Proof.* We write:

$$
\mathbb{E}_{s}^{\mathbf{M},\mathbb{A}}[U] \stackrel{(\dagger)}{\geq} \mathbb{E}_{s}^{\mathbf{M},\mathbb{A}}[U \exp\{-L(H_{T})\}]
$$
\n
$$
= \mathbb{E}_{s}^{\mathbf{M},\mathbb{A}}[\exp\{-L(H_{T}) + \log(U)\}]
$$
\n
$$
\stackrel{(\dagger)}{\geq} \exp\{\mathbb{E}_{s}^{\mathbf{M},\mathbb{A}}[-L(H_{T}) + \log(U)]\}
$$
\n
$$
\stackrel{(\underline{\S})}{=} \exp\{-\mathbb{E}_{s}^{\mathbf{M},\mathbb{A}}\Big[\sum_{x \in \mathcal{X}} N_{T}(x)\text{KL}_{x}(\mathbf{M}||\mathbf{M}')\Big] + \mathbb{E}_{s}^{\mathbf{M},\mathbb{A}}[\log(U)]\Big\}
$$

where (†) follows by [Theorem C.1,](#page-46-2) ( $\ddagger$ ) is a use of Jensen's inequality and (§) follows by [Lemma C.2.](#page-46-4)<br>Conclude by taking the log and rearranging terms Conclude by taking the log and rearranging terms.

<span id="page-47-2"></span>Corollary C.4. *Let* M ≪ M′ *two Markov decision processes and fix an arbitrary learning agent* A *and*  $s \in S$ *. If*  $\mathcal{E}$  *is a*  $\sigma(H_T)$ *-measurable event, then:* 

$$
\mathbb{E}_{s}^{\mathbf{M},\mathbb{A}}\left[\sum_{x\in\mathcal{X}}N_{T}(x)\mathrm{KL}_{x}(\mathbf{M}||\mathbf{M}')\right]\geq \mathrm{kl}\left(\mathbb{P}_{s}^{\mathbf{M},\mathbb{A}}(\mathcal{E}),\mathbb{P}_{s}^{\mathbf{M}',\mathbb{A}}(\mathcal{E})\right).
$$

*Proof.* For conciseness, we write  $\mathbb{E}[-], \mathbb{E}'[-]$  rather  $\mathbb{E}_{s}^{\mathbf{M},\mathbb{A}}[-], \mathbb{E}_{s}^{\mathbf{M}',\mathbb{A}}[-]$ , and  $\rho := \mathbb{P}(\mathcal{E})$  and  $\rho' := \mathbb{P}'(\mathcal{E})$ . If  $\rho = \rho'$ , there is nothing to prove. Up to considering  $\mathcal{E}^{\mathbb{C}}$ , we can assume that  $\rho > \rho'$ . We have:

$$
\mathbb{E}\left[\sum_{x\in\mathcal{X}}N_T(x)\text{KL}_x(\mathbf{M}||\mathbf{M}')\right] \ge \sup_{\lambda\ge 0}\left\{\mathbb{E}[\log(\lambda+1(\mathcal{E}))] + \log \mathbb{E}'(\lambda+1(\mathcal{E}))\right\}
$$

$$
= \sup_{\lambda>0}\left\{\rho \log(\lambda+1) + (1-\rho)\log(\lambda) - \log(\lambda+\rho')\right\} =: \sup_{\lambda>0}\varphi(\lambda)
$$

The supremum of  $\varphi$  is reached for  $\lambda := \frac{\rho'(1-\rho)}{\rho - \rho'}$  $\frac{\mu_{\rho-\rho'}}{\rho-\rho'}$ , and with a bit of algebra, we find that sup<sub> $\lambda>0$ </sub>  $\varphi(\lambda) =$  $kl(\rho, \rho')$ . This concludes the proof. ). This concludes the proof.  $\Box$ 

## <span id="page-47-0"></span>D Proofs of complexity results

In this appendix, we provide the complete proofs of [Theorems 14](#page-21-0) and [15.](#page-22-1)

#### <span id="page-47-1"></span>D.1 Proof of [Theorem 14](#page-21-0)

Proving that it is NP is immediate, because the optimal gain of a MDP is the solution of a linear program [Puterman](#page-37-9) [\(2014\)](#page-37-9) hence given  $M^{\dagger}$ , checking that  $\sum_{x} \mu(x)KL_{x}(M||M^{\dagger}) < \alpha$  and  $g_{\star}(M^{\dagger}) > \beta$  is done in polynomial time. The point is to show the NP-hardness.

(STEP 1) To prove that the problem is NP-hard, it is reduced from the Knapsack Problem (KP). Recall that an instance of KP is given by a collection of *n* items of integer values  $\{v_1, \ldots, v_n\}$  and integer weights  $\{w_1, \ldots w_n\}$ , as well as a capacity *W* and a value threshold *V*, both integers. The problem is to determine whether there exists  $\mathcal{K} \subseteq [n]$  such that  $\sum_{k \in \mathcal{K}} w_k \leq W$  and  $\sum_{k \in \mathcal{K}} v_k \geq V$ .



Figure 6: The (Choose k) widget, where  $\sigma_k^2$  $\frac{2}{k} := \frac{\sigma^2}{w_k}$  $\frac{\sigma^2}{w_k}$ .

Fix  $\varepsilon, \sigma, \delta > 0$  to be tuned later on. Given an instance of KP, consider the MDP M whose structure is given by *n* (choose *k*) 3-state widgets connected in a ring fashion.

From the state (Choose *k*) are two actions: The top action that is likely to go to (Pick *k*) that shall be referred to as action Pick, and the bottom action called SKIP. From every over state, there is a single action that denoted  $*$ . A (deterministic) policy of M is analogue to a subset  $\mathcal{K} \subseteq \{1, ..., n\}$ , written  $\pi_{\mathcal{K}}$ , which is given by  $\pi_K$  (PICK|CHOOSE *k*) := 1( $k \in \mathcal{K}$ ). We get:

$$
\mathbf{g}(\pi_{\mathcal{K}}) = \frac{1}{2n} \left( \frac{1}{2} \sum_{k=1}^{n} v_k + \sum_{k \in \mathcal{K}} \left( \left( \frac{1}{2} - \varepsilon \right) v_k + \delta \right) \right) = \frac{\|v\|_1}{4n} + \frac{1}{2n} \sum_{k \in \mathcal{K}} \left( \left( \frac{1}{2} - \varepsilon \right) v_k + \delta \right).
$$
 (D.1)

(STEP 2) Every policy  $\pi_{\mathcal{K}}$  can equivalently be seen as a *single-action* Markov decision process  $M_{\mathcal{K}}$ , i.e., the model of a policy over the state-space

 $S := \{$ **(CHOOSE k)**, **(PICK k)**, **(SKIP k)** :  $k = 1, ..., n$ .

The choice of an action is equivalently the choice of a kernel distribution. The set of stationary deterministic policies of M, denoted  $\Pi^{\text{SD}}(\mathcal{M})$ , can therefore be seen as the set of Markov reward processes  $M^{\text{SD}} := \{ \mathbf{M}_{\mathcal{K}} : \mathcal{K} \subseteq \{1, ..., n\} \}$ . Provided that the parameters  $\varepsilon, \sigma, \delta$  are polynomial in *n*, *v*, *w*, this (structured) set of mdps is described in polynomial size in *n*, *v*, *w*.

Consider  $M_{\varnothing} \in \mathcal{M}^{SD}$ . Because  $\mathcal{M}^{SD}$  is a space of single-action MDPs, we don't make any distinction between a state and a pair of  $M_K \in M^{SD}$ . Now, we see that  $g(M_\emptyset) = \frac{||y||_1}{4n}$  and the invariant measure  $\mu$  of the unique policy of  $M_{\odot}$  is:

$$
\mu
$$
(Choose *k*) =  $\frac{1}{2n}$  and  $\mu$ (PICK *k*) =  $\mu$ (SkIP *k*) =  $\frac{1}{4n}$ .

Moreover, check that for  $\mathcal{K} \subseteq \{1, \ldots, n\}$ , the only states such that  $KL_s(M_\emptyset||M_\mathcal{K}) \neq 0$  are (Choose *k*) states, with:

$$
KL_{(Choose\ k)}(\mathbf{M}_{\emptyset}||\mathbf{M}_{\mathcal{K}}) = \mathbb{1}(k \in \mathcal{K}) \Big( \log \Big( \frac{1}{4\varepsilon(1-\varepsilon)} \Big) + w_k \Big( \frac{\delta}{\sigma} \Big)^2 \Big).
$$

Hence:

$$
\sum_{x} \mu(x) \mathrm{KL}_x(\mathbf{M}_{\emptyset} || \mathbf{M}_{\mathcal{K}}) = \frac{1}{2n} \sum_{k \in \mathcal{K}} \Biggl( \log \Bigl( \frac{1}{4\varepsilon(1-\varepsilon)} \Bigr) + w_k \Bigl( \frac{\delta}{\sigma} \Bigr)^2 \Biggr).
$$

(STEP 3) We want (1) to be able to retrieve the value of  $\sum_{k \in \mathcal{K}} v_k$  from  $g(M_{\mathcal{K}})$ ; (2) to be able to retrieve the value of  $\sum_{k \in \mathcal{K}} w_k$  from  $\sum_x \mu(x) \mathbf{KL}_x(\mathbf{M}_{\emptyset}||\mathbf{M}_k)$ . For simplicity and because it will eventually work with it, fix  $\varepsilon \equiv \frac{1}{4}$  $\frac{1}{4}$ .

The condition (1) holds when  $\delta = \frac{1}{16}$  $\frac{1}{16n}$ . Indeed, then:

$$
\mathbf{g}(\mathbf{M}_{\mathcal{K}}) = \frac{||v||_1}{4n} + \frac{1}{8n} \sum_{k \in \mathcal{K}} (v_k + 4\delta) = \frac{1}{8n} \left( 2||v||_1 + \sum_{k \in \mathcal{K}} v_k \pm \frac{1}{4} \right)
$$

where  $\pm \frac{1}{4}$  $\frac{1}{4}$  denotes an arbitrary quantity in the range of  $\left[-\frac{1}{4}\right]$  $\frac{1}{4}$ ,  $\frac{1}{4}$  $\frac{1}{4}$ ]. Rearranging, we get  $\sum_{k \in \mathcal{K}} v_k$  =  $8n\mathbf{g}(\mathbf{M}_{\mathcal{K}}) - 2||v||_1 \pm \frac{1}{4}$  $\frac{1}{4}$  = [8*n*g(**M**<sub>K</sub>) – 2||v||<sub>1</sub>] where [ $\lambda$ ] denotes the rounding operation (nearest integer).

V. Boone & OA. Maillard 49 January 23, 2025

The condition (2) is satisfied when

$$
\sigma^2 = \frac{\delta^2}{4n \log(\frac{1}{4\epsilon(1-\epsilon)})} \equiv \frac{1}{1024n^3 \log(\frac{4}{3})}.
$$

Indeed, then we have

$$
\sum_{x} \mu(x) \text{KL}_{x}(\mathbf{M}_{\emptyset} || \mathbf{M}_{\mathcal{K}}) = \frac{1}{2n} \sum_{k \in \mathcal{K}} \left( \log \left( \frac{1}{4\varepsilon(1-\varepsilon)} \right) + w_{k} \left( \frac{\delta}{\sigma} \right)^{2} \right)
$$

$$
= \frac{\delta^{2}}{2n\sigma^{2}} \sum_{k \in \mathcal{K}} \left( w_{k} + \frac{1}{4n} \right) = \frac{\delta^{2}}{2n\sigma^{2}} \left( \sum_{k \in \mathcal{K}} w_{k} \pm \frac{1}{4} \right).
$$

Rearranging, we find  $\sum_{k \in \mathcal{K}} w_k = \left[ \frac{2n\sigma^2}{\delta^2} \right]$  $\frac{n\sigma^2}{\delta^2} \sum_x \mu(x) \text{KL}_x(\mathbf{M}_{\emptyset} || \mathbf{M}_{\mathcal{K}})$  where  $\lceil \lambda \rfloor$  also denotes the rounding operation.

(STEP 4) Remark that this choice of  $\varepsilon, \sigma, \delta$  is polynomial in the size of *n*. Following this remark, it should be clear that  $M^{SD}$  can be encoded in polynomial size. Finally set  $\alpha = 2 \log(4/3)(W + \frac{1}{3})$  $\frac{1}{3}$ ) and  $\beta = \frac{1}{8}$  $\frac{1}{8n}(2||v|| + V)$ . Then, we claim that there is  $M^{\dagger} \in \mathcal{M}^{SD}$  such that

<span id="page-49-1"></span>
$$
\sum_{x} \mu(x) \text{KL}_{x}(\mathbf{M}||\mathbf{M}^{\dagger}) \le \alpha, \text{ and } \mathbf{g}_{\star}(\mathbf{M}^{\dagger}) \ge \beta
$$
\n(D.2)

if, and only if the KP instance  $(v, w, V, W)$  has a solution.

This is just a commodity to check using the formulas established so far. If the KP instance has solution  $K$ , then  $M_K$  is by construction a solution of [\(D.2\)](#page-49-1), because

$$
\sum_{x} \mu(x) \text{KL}_{x}(\mathbf{M}||\mathbf{M}^{\dagger}) = \frac{\delta^{2}}{2n\sigma^{2}} \sum_{k \in \mathcal{K}} \left( w_{k} + \frac{1}{4n} \right) \leq 2 \log \left( \frac{4}{3} \right) \left( W + \frac{|\mathcal{K}|}{4n} \right) < \alpha
$$

and

$$
\mathbf{g}(\mathbf{M}_{\mathcal{K}}) = \frac{1}{8n} \left( 2||v||_1 + \sum_{k \in \mathcal{K}} \left( v_k + \frac{1}{4n} \right) \right) > \frac{1}{8n} (2||v||_1 + V) = \beta.
$$

Conversely, if  $M_k$  is a solution of  $(D.2)$ , then we have

$$
\alpha = 2\log\left(\frac{4}{3}\right)\left(W + \frac{1}{3}\right) \ge \frac{\delta^2}{2n\sigma^2} \sum_{k \in \mathcal{K}} \left(w_k + \frac{1}{4n}\right) \ge 2\log\left(\frac{4}{3}\right) \sum_{k \in \mathcal{K}} w_k
$$

hence  $\sum_{k \in \mathcal{K}} w_k \leq W + \frac{1}{3}$  $\frac{1}{3}$ , so  $\sum_{k \in \mathcal{K}} w_k \leq W$ ; and similarly

$$
\beta = \frac{1}{8n}(2||v|| + V) \le \frac{1}{8n}\left(2||v|| + \frac{1}{4} + \sum_{k \in \mathcal{K}} v_k\right)
$$

so  $\sum_{k \in \mathcal{K}} v_k \geq V - \frac{1}{4}$  $\frac{1}{4}$ , so  $\sum_{k \in \mathcal{K}} v_k \geq V$ .

#### <span id="page-49-0"></span>D.2 Proof of [Theorem 15](#page-22-1)

We provide a reduction from the co-knapsack problem (co-KP), which is coNP-complete because KP is NP-complete. An instance of co-KP is given by a collection of *n* items of integer values  $\{v_1, \ldots, v_n\}$ and integer weights  $\{w_1, \ldots, w_n\}$ , as well as a capacity and a value threshold *V*, both integers. The problem is to determine if, for all  $K \subseteq [n]$ , we either have  $\sum_{k \in K} w_k \ge W$  or  $\sum_{k \in K} v_k \le V$ .



<span id="page-50-0"></span>Figure 7: Embedding a knapsack problem in a Markov decision process.

The reduction is very similar to CONFUSING-MODEL's. Fix  $\varepsilon$ ,  $\sigma$ ,  $\delta$ ,  $\theta$  to be tuned later on and consider an instance of co-KP. Consider the MDP M whose structure is as given by [Figure 7.](#page-50-0)

The change regarding the reduction of CONFUSING-MODEL is the state (0), in between (Choose *n*) and (Choose 1). From (0) you can either loop with the action Loop scoring  $\theta$ , or go to (Choose 1) with the action Cycle scoring 0, hence entering the big cycle. The state  $(0)$  is a special state. From the state (Choose  $k$ ) are two actions: The top action that is likely to go to (Pick  $k$ ) that we shall refer to as action Pick, and the bottom action that we shall call Skip. From every over state, there is a single action that denoted  $\ast$ . The special policy looping on (0) is denoted  $\pi^{\star}$  and will model the optimal policy later on. The other (deterministic) policies of M are analogue to a subset  $\mathcal{K} \subseteq \{1, ..., n\}$ , written  $\pi_{\mathcal{K}}$ , and are given  $\pi_K$ (PICK|CHOOSE k) :=  $\mathbb{1}(k \in \mathcal{K})$  with  $\pi$ (CYCLE|0) = 1. We get:

$$
\mathbf{g}(\pi_{\mathcal{K}}) = \frac{1}{2(n+1)} \left( \frac{1}{2} \sum_{k=1}^{n} v_k + \sum_{k \in \mathcal{K}} \left( \left( \frac{1}{2} - \varepsilon \right) v_k + \delta \right) \right) = \frac{||v||_1}{4(n+1)} + \frac{1}{2(n+1)} \sum_{k \in \mathcal{K}} \left( \left( \frac{1}{2} - \varepsilon \right) v_k + \delta \right). \tag{D.3}
$$

Every policy  $\pi_{\mathcal{K}}$  can equivalently be seen as a single-action Markov decision process  $M_{\mathcal{K}}$ . The choice of an action is equivalently the choice of a kernel distribution. The set of stationary deterministic policies of M, denoted  $\Pi^{\text{SD}}(\mathcal{M})$ , can therefore be seen as the set of Markov reward processes  $M^{\text{SD}} := \{ \mathbf{M}_{\mathcal{K}} : \mathcal{K} \subseteq \{1, ..., n\} \}$ . Now, we see that  $\mathbf{g}(\mathbf{M}_{\emptyset}) = \frac{\|\mathbf{v}\|_1}{4(n+1)}$  and the invariant measure  $\mu_{\emptyset}$  of the unique policy of  $M_{\odot}$  is:

$$
\mu_{\emptyset}(0) = \frac{1}{n+1}, \ \mu_{\emptyset}(\text{Choose } k) = \frac{1}{2(n+1)}, \text{ and } \mu_{\emptyset}(\text{Pick } k) = \mu_{\emptyset}(\text{SkIP } k) = \frac{1}{4(n+1)}.
$$

Moreover, check that:

$$
\sum_{x} \mu_{\emptyset}(x) \text{KL}_{x}(\mathbf{M}_{\emptyset} || \mathbf{M}_{\mathcal{K}}) = \frac{1}{2(n+1)} \sum_{k \in \mathcal{K}} \Biggl( \log \Bigl( \frac{1}{4\epsilon(1-\epsilon)} \Bigr) + w_{k} \Bigl( \frac{\delta}{\sigma} \Bigr)^{2} \Biggr).
$$

We find the values:

$$
\varepsilon = \frac{1}{4}
$$
,  $\delta = \frac{1}{16n}$ ,  $\sigma^2 = \frac{\delta^2}{4(n+1)\log(\frac{4}{3})}$ ,  $\theta = \frac{2||v||_1 + V}{8(n+1)}$ , and  $\rho = \frac{V}{16\log(\frac{4}{3})W}$ .

Consider  $M_*^{\text{SD}}$  the copy of  $M^{\text{SD}}$  with each element augmented with the action Loop at 0, scoring  $N(\theta, 0)$  and pick the reference model  $M_{\emptyset} \in \mathcal{M}^{SD}$  (In abuse of notations, we write the elements of  $M^{\text{SD}}$  and  $M^{\text{SD}}_*$  similarly because the two sets are obviously isomorphic, so  $M_{\varnothing}$  contains the policies  $\pi_{\varnothing}$  and  $\pi_*$ ). We show that the initial co-KP problem is reduced to the REGRET instance ( $\mathcal{M}_*^{\text{SD}}$ ,  $\mathbf{M}_{\varnothing}$ ,  $\rho$ ).

First, remark that  $\pi^*$  is the optimal policy of  $M_\varnothing$ . Then, We show that given  $\mu \in Inv(M_\varnothing / X_\star)$ such that  $\sum_{x} \mu(x) \Delta^*(x; \mathbf{M}_{\emptyset}) \le \rho$ , we have

(1)  $\sum_{k \in \mathcal{K}} v_k \leq V$  if, and only if  $\mathbf{g}(\mathbf{M}_{\mathcal{K}}) > \theta$ , i.e.,  $\mathbf{M}_{\mathcal{K}} \in \text{Cnf}_{\star}(\mathbf{M}_{\emptyset}; \mathcal{M}_{*}^{\text{SD}})$ ; and

V. Boone & OA. Maillard 51 January 23, 2025

(2)  $\sum_{k \in \mathcal{K}} w_k \geq W$  if, and only if  $\sum_{x} \mu(x) \text{KL}_x(\mathbf{M}_{\emptyset} || \mathbf{M}_{\mathcal{K}}) \geq 1$ .

We start with (1). If  $\sum_{k \in \mathcal{K}} v_k \leq V$ , then

$$
\mathbf{g}(\pi_{\mathcal{K}}) > \frac{||v||_1}{4(n+1)} + \frac{V}{8(n+1)} = \theta.
$$

Conversely, if  $g(\pi_K) > \theta$ , then

$$
\frac{2||v||_1 + V}{8(n+1)} < \frac{1}{8(n+1)} \left( 2||v||_1 + \sum_{k \in \mathcal{K}} \left( v_k + \frac{1}{4n} \right) \right) \le \frac{2||v||_1 + \frac{1}{4} + \sum_{k \in \mathcal{K}} v_k}{8(n+1)},
$$

so  $\sum_{k \in \mathcal{K}} v_k \geq V - \frac{1}{4}$  $\frac{1}{4}$ , so  $\sum_{k \in \mathcal{K}} v_k \geq V$ .

For (2), first remark that the only positive Bellman-gap of  $M_{\odot}$  is at the state-action pair (0, Cycle) with  $\Delta^{\star}((0, \text{CYCLE}); \mathbf{M}_{\odot}) = \frac{V}{8}$  $\frac{1}{8}$ . Moreover, every element of Inv( $M_{\varnothing}/X_{\star}$ ) is of the form  $c\mu_{\varnothing}$  where  $c > 0$ . So, having  $\sum_{x} \mu(x) \Delta^*(x; \mathbf{M}_{\emptyset}) \le \rho$  means that  $\mu = c\mu_{\emptyset}$  with  $c \le \frac{8\rho}{V}$  $\frac{g_p}{V} = (2 \log(\frac{4}{3})W)^{-1}$ . With this in mind, if  $\sum_{k \in \mathcal{K}} w_k \geq W$ , then

$$
\sum_{x} \mu(x) \mathbf{KL}_x(\mathbf{M}_{\emptyset} || \mathbf{M}_{\mathcal{K}}) = \frac{c\delta^2}{2(n+1)\sigma^2} \sum_{k \in \mathcal{K}} \left( w_k + \frac{1}{4n} \right) \ge \frac{2\log\left(\frac{4}{3}\right)W}{2\log\left(\frac{4}{3}\right)W} \ge 1.
$$

Conversely, if  $\sum_{x} \mu(x) \text{KL}_x(\textbf{M}_{\emptyset} || \textbf{M}_{\mathcal{K}}) \ge 1$ , then

$$
1 \le \frac{c\delta^2}{2(n+1)\sigma^2} \sum_{k \in \mathcal{K}} \left( w_k + \frac{1}{4n} \right) \le \frac{2\log\left(\frac{4}{3}\right) \left( \sum_{k \in \mathcal{K}} w_k + \frac{|\mathcal{K}|}{4n} \right)}{2\log\left(\frac{4}{3}\right)W}
$$

so  $\sum_{k \in \mathcal{K}} w_k \geq W - \frac{1}{4}$  $\frac{1}{4}$ , so  $\sum_{k \in \mathcal{K}} w_k \geq W$ .

We readily obtain that: "every  $\mathcal{K} \subseteq [n]$  satisfies either  $\sum_{k \in \mathcal{K}} w_k \geq W$  or  $\sum_{k \in \mathcal{K}} v_k \leq V$ " is equivalent to  $\mu \equiv (2W \log(\frac{4}{3}))^{-1} \mu_{\emptyset}$  satisfying:

$$
\forall \mathbf{M}^{\dagger} \in \mathrm{Cnf}_{\star}(\mathbf{M}_{\varnothing}; \mathcal{M}_{*}^{\mathrm{SD}}), \ \sum_{x} \mu(x) \mathrm{KL}_{x}(\mathbf{M}_{\varnothing} || \mathbf{M}_{\mathcal{K}}) \geq 1,
$$

and this  $\mu$  is the unique  $\mu \in Inv(\mathbf{M}_{\emptyset}/X_{\star})$  such that  $\sum_{x} \mu(x) \Delta^{\star}(x; \mathbf{M}_{\emptyset}) = \rho$ .