Quantum frequency resampling

Emanuele Tumbiolo ⁽⁰⁾,^{1,2,*} Simone Roncallo ⁽⁰⁾,^{1,2,†} Chiara Macchiavello ⁽⁰⁾,^{1,2,‡} and Lorenzo Maccone ⁽⁰⁾,^{2,§}

¹Dipartimento di Fisica, Università degli Studi di Pavia, Via Agostino Bassi 6, I-27100, Pavia, Italy

²INFN Sezione di Pavia, Via Agostino Bassi 6, I-27100, Pavia, Italy

In signal processing, resampling algorithms can modify the number of resources encoding a collection of data points. Downsampling reduces the cost of storage and communication, while upsampling interpolates new data from limited one, e.g. when resizing a digital image. We present a toolset of quantum algorithms to resample data encoded in the probabilities of a quantum register, using the quantum Fourier transform to adjust the number of high-frequency encoding qubits. We discuss advantage over classical resampling algorithms.

Keywords: Quantum resampling; Quantum downsampling; Quantum upsampling; Quantum interpolation; Quantum signal processing;

I. INTRODUCTION

In signal processing, resampling (or sample-rate conversion) can modify the rate at which continuous processes are discretized into a finite set of data points [1]. It consists in two reciprocal operations: downsampling, which simplifies the signal representation by reducing such rate, and upsampling, which interpolates existing data to increase the resolution and approximate finer details. Classically, these techniques are typically used to improve the compatibility between systems with different data formats. Several protocols perform resampling in the frequency domain by three steps: (i) signal conversion, e.g. using the fast Fourier transform (FFT), (ii) manipulation of the high-frequency components, and (iii) conversion back to the original domain, e.g. using the inverse FFT.

Quantum effects can be employed to tackle signal processing tasks, efficiently manipulating both quantum data and classical information. In quantum image processing [2–6], several compression and interpolation algorithms have been proposed, e.g. based on matrix product state truncation [7], bilinear interpolation [3, 8], quantum variational circuits [9] and Fourier methods [10]. Resampling algorithms have also been investigated in quantum state preparation [11–13]. However, a general framework for quantum signal resampling is still lacking.

In this paper, we address this gap by introducing two protocols that tackle the fundamental resampling operations - downsampling and upsampling - for data encoded in the probabilities of a multiqubit state [14]. These techniques establish a framework for multidimensional resampling in the frequency domain, of which [10] is an application for the downscaling of digital images. Using a combination of Hadamard gates and quantum Fourier transforms (QFTs) [15, 16], we achieve downsampling by discarding the most significant qubits of the register (corresponding to the high-frequency modes), and upsampling by appending new qubits to increase the signal resolution. Both protocols preserve the original information content. We analyze them from both an analytical and numerical point of view, deriving closed-form expressions for their outputs. Detailed calculations are reported in the Appendix. This is a two-fold result, that identifies the classical equivalents of our algorithms as well as their advantages and limitations. We discuss the resource cost of these methods, both in terms of gates and experimental repetitions. For gates, both algorithms achieve an exponential speedup over their classical counterparts. Moreover, we establish the robustness of downsampling against the statistical cost of output retrieval.

II. THE ALGORITHMS

In this section we discuss the operating principles of our quantum resampling algorithms, for a signal encoded in the probabilities of a multiqubit state. We propose two complementary protocols, one for downsampling, i.e. for reducing the number of samples of the signal while preserving its pattern, and one for upsampling, namely for interpolating new information from the existing one. Both algorithms employ a multidimensional quantum Fourier transform (MD-QFT) to process the input in the frequency domain, where we either discard the qubits encoding the highest frequency modes of the signal or add fresh qubits to the register, expanding the signal spectrum with vanishing high-frequency components.

A discrete signal S is a multidimensional array of d indexes (called axes), i.e. a collection of finite values, sampled from an underlying continuous process at a given sampling rate and distributed in a d-dimensional grid. For instance, a digital image can be described as a twodimensional signal, where the samples correspond to the pixel intensities, and the axes define a coordinate system on the image plane. Similarly, a video can be viewed as a three-dimensional array, with two spatial axes and a temporal one that orders the sequence of frames in time. Each axis may have a distinct sampling rate, specifying the average number of samples acquired in the unit in-

^{*} Emanuele Tumbiolo: emanuele.tumbiolo01@ateneopv.it

[†] Simone Roncallo: simone.roncallo01@ateneopv.it

[‡] Chiara Macchiavello: chiara.macchiavello@unipv.it

[§] Lorenzo Maccone: lorenzo.maccone@unipv.it



FIG. 1. Little-endian ordering when encoding a 3D signal S. Classically, S is represented by a $4 \times 4 \times 4$ array, with a total of 64 samples arranged along axes e_0, e_1, e_2 . According to Eq. (1), these values are encoded in the probabilities of a 6 qubits register E, which can be decomposed into 3 subregisters, E_0, E_1, E_2 , arranged, top to bottom, in order of increasing significance.

terval [17]. We limit our discussion to hyper-cubic, i.e. square, arrays, with N_0 entries per axis and thus a total of N_0^d samples, since the extension to different entries per axis is straightforward. We employ an amplitude encoding scheme [14] to upload S onto the state of an *encoding* register E of $n_E = \log_2(N_0^d)$ qubits, as

$$|\Psi\rangle_E = \sum_{\mathbf{e}} \alpha_{\mathbf{e}} \,|\mathbf{e}\rangle_E \ , \tag{1}$$

where $|\mathbf{e}\rangle_{E}$ labels the computational basis elements and

$$\alpha_{\mathbf{e}} = \sqrt{\frac{\mathcal{S}_{\mathbf{e}}}{I_E}} \quad , \tag{2}$$

with $S_{\mathbf{e}}$ the sample values normalized to the total input signal intensity $I_E = \sum_{\mathbf{e}} S_{\mathbf{e}}$. Unless otherwise specified, summations are always taken over all the possible values of their index. The *d*-tuple $\mathbf{e} = (e_0, e_1, \dots, e_{d-1})$, with $e_i \in \{0, N_0 - 1\}$, labels the entries of S along each dimension. Due to the correspondence between sample indexes and computational basis elements, E can be decomposed in *d* subregisters E_i of n_0 qubits, one for each signal axis, such that $n_E = d n_0$. In the computational basis

$$|\mathbf{e}\rangle_E = |e_{d-1}\rangle_{E_{d-1}} \otimes \dots \otimes |e_0\rangle_{E_0} \quad . \tag{3}$$

We call $|\Psi\rangle_E$ quantum signal. In the little-endian ordering, the qubits in E are arranged from top to bottom in order of increasing significance. Hence, the E_{d-1} subregister contains the n_0 most significant qubits, i.e. the entries along the first dimension and so on, as depicted in Fig. 1. We identify each qubit with a pair of indices (s,q), where $0 \le s \le d-1$ labels the subregister, and $0 \le q \le n_0 - 1$ the position within it.

In this representation, we define the MD-QFT \mathcal{F} as the tensor product of d standard, i.e. one-dimensional, quantum Fourier transforms F [15], each acting on a separate subregister. For example, on the encoding register

$$\mathcal{F}_{E} |\mathbf{e}\rangle_{E} = F |e_{d-1}\rangle_{E_{d-1}} \otimes ... \otimes F |e_{0}\rangle_{E_{0}} = N_{0}^{-d/2} \sum_{\mathbf{k}} \exp\{2\pi i \mathbf{k} \cdot \mathbf{e}/N_{0}\} |\mathbf{k}\rangle_{E} , \qquad (4)$$

with $\mathbf{k} = (k_0, k_1, ..., k_{d-1}), k_i \in \{0, ..., N_0 - 1\}$ and $\mathbf{k} \cdot \mathbf{e}$ the usual dot product. Similarly, its inverse is

$$\mathcal{F}_{E}^{\dagger} |\mathbf{e}\rangle_{E} = F^{\dagger} |e_{d-1}\rangle_{E_{d-1}} \otimes \dots \otimes F^{\dagger} |e_{0}\rangle_{E_{0}} = \\ = N_{0}^{-d/2} \sum_{\mathbf{k}} \exp\{-2\pi i \mathbf{k} \cdot \mathbf{e}/N_{0}\} |\mathbf{k}\rangle_{E} \quad .$$
⁽⁵⁾

Quantum downsampling We now focus on the downsampling algorithm, which reduces the size of the encoding register from n_E to $n_D = d n_1$, with $n_1 = n_0 - \tilde{n}$ the number of qubits per axis in the *downsampled register* D. The settable parameter \tilde{n} controls the downsampling ratio

$$\frac{n_E}{n_D} = 1 + \frac{d\tilde{n}}{n_D} \tag{6}$$

of the output signal. In the following, we discuss how this is related to output quality.

The algorithm works as follows. Apply a set of Hadamard gates $H^{\otimes n_E}$ to E - with H the single-qubit Hadamard gate - followed by a MD-QFT, which converts the state of the register into the Fourier domain. For each of the d subregisters, discard (by partial tracing) the \tilde{n} most significant qubits, retaining only those with $0 \leq q \leq (n_0 - \tilde{n}) - 1$ in the downsampled register. This operation amounts to averaging out the high-frequency components of the signal and yields a reduced state of n_D qubits. Consequently, the number of samples in the signal is uniformly reduced along each axis by a factor of $\tilde{N} = 2^{\tilde{n}}$. Take the inverse MD-QFT \mathcal{F}_D^{\dagger} on the reduced register. Finally, apply a set of Hadamard gates $H^{\otimes n_D}$ to the remaining qubits, thus returning to the computational basis. We report the circuital implementation of Alg. 1 in Fig. 2a. The output, now encoded by the density operator ρ_D , has only $N_1 = N_0/\tilde{N}$ samples per axis, and thus a total of N_1^d entries. In terms of sampling rates, this is equivalent to introducing a reduced effective rate $f_i^D = f_i^E/\tilde{N}$, where f_i^E is the input rate for the *i*-th axis. Such samples can be recovered from the probability distribution $p_{\mathbf{m}} = \text{Tr}[\rho_D | \mathbf{m} \rangle_D \langle \mathbf{m} |]$ where $|\mathbf{m} \rangle_D = |m_{d-1} \rangle_{D_{d-1}} \otimes ... \otimes |m_0 \rangle_{D_0}$ is the computational



FIG. 2. Quantum downsampling of a *d*-dimensional signal encoded in the probabilities of a register E, divided in *d* subregisters E_i , of n_0 qubits each. (a) Circuit scheme of the algorithm, which discards $\tilde{n} < n_0$ qubit for each axis, compressing the input into a state of register D, with $n_D = n_E - d\tilde{n}$ qubits (consistently divided into *d* subregisters). (b) Effect on the classical signal. The discarding parameter \tilde{n} determines the output resolution, from N_0^d to $N_0^d/2^{d\tilde{n}}$. The algorithm is equivalent to averaging the original signal on a set of hyper-cubic blocks of side \tilde{N} .

basis element of the downsampled register. These probabilities are related to the input by

$$p_{\mathbf{m}} = \sum_{\tilde{\mathbf{e}}} \frac{S_{\tilde{N}\mathbf{m}+\tilde{\mathbf{e}}}}{I_D} , \qquad (7)$$

where $I_D = \tilde{N}^{-d}/I_E$ is the downsampled signal intensity, $\tilde{\mathbf{e}} = (\tilde{e}_0, \dots, \tilde{e}_{d-1}), \ \tilde{e}_i \in \{0, \tilde{N} - 1\}$, and the sum is to be interpreted as element-wise. See Appendix A for a detailed derivation of Eq. (7).

Algorithm 1 Quantum downsampling	
Input State $ \Psi\rangle_E$	\triangleright Encoding register (n_E qubits)
Parameters	
Integer d	$\triangleright \#$ of signal dimensions
Integer $\tilde{n} < n_0$	▷ Discarding parameter
Protocol	
1: apply $H^{\otimes n_E}$	
2: apply \mathcal{F}_E	
3: for $0 \le s \le d - 1$ do	▷ Discarding rule
4: if $n_0 - \tilde{n} \le q \le n_0 - 1$ then	
5: discard the q th qubit	
6: apply \mathcal{F}_D^{\dagger}	
7: apply $H^{\otimes n_D}$	
Result State ρ_D	\triangleright Downsampled register (n_D qubit)

As we show in Fig. 2b, our protocol corresponds to a *block-wise averaging operation*: it averages the input, first divided in a set of non-overlapping hyper-cubic blocks of side \tilde{N} . This is equivalent to performing a circular discrete convolution between S and a *d*-dimensional rectangular filter whose shape arises due to the combination of the Hadamard gates and the discarding operations. The higher the downsampling ratio of Eq. (6), the higher the loss in output quality, as more information is averaged. Reducing the sampling rate below the Nyquist limit can produce digital distortions, e.g. aliasing, [18], which arises when low and high-frequency Fourier components overlap at the output. As such, our protocol is better suited to processing signals with negligible highfrequency modes in their spectra, such as traditional digital pictures, while its performances are limited for signals experiencing sharp transitions in intensities.

Quantum upsampling Complementary to the downsampling procedure, the upsampling algorithm proceeds in the reciprocal way: it expands the signal by interpolating existing samples with additional encoding resources, called *padding qubits*. In signal processing, padding means expanding an input with new data of no significant content [19]. Similarly, our protocol calls for $n_P = d\tilde{n}$ qubits, i.e. the *padding register* P, to increase the size of the encoding one. Both corresponds to the *upsampled register* U, made of $n_U = dn_1$ qubits, with $n_1 = n_0 + \tilde{n}$. Each padding qubit is identified by the pair (i, p), where $0 \le i \le d - 1$ and $0 \le p \le \tilde{n} - 1$. P can be seen as the composition of d subregisters $\{P_i\}$, one per signal axis, each expanding the corresponding encoding subregister E_i .

The algorithm operates as follows. Initialize P to $|0\rangle_P = |0\rangle^{\otimes n_P}$. Apply a set of Hadamard gates $H^{\otimes n_U}$ to all qubits. A MD-QFT \mathcal{F}_E is taken on E, followed by a *padding operation*: for each axis, \tilde{n} qubits are moved from P to the bottom of the corresponding subregister, i.e. in the most significant position. This operation is equivalent to introducing new zero-valued high-frequency components into the signal, expanding its spectrum. Depending on the circuit layout and its connectivity, the above padding can be actively achieved by a series of subsequent SWAP gates, appropriately shifting the qubits of the various subregisters to directly connect E_i and P_i . Finally, perform an inverse MD-QFT \mathcal{F}_U^{\dagger} on the full ex-



FIG. 3. Quantum upsampling of a *d*-dimensional signal encoded in the probabilities of register E, composed of *d* subregisters E_i , each containing n_0 qubits. (a) Circuit implementation of the protocol: for the *i*-th axes, \tilde{n} additional qubits (the subregister P_i) are appended to E_i . The upsampled state $|\Omega\rangle_U$, encoded in *d* subregisters U_i , consists of $n_0 + \tilde{n}$ qubits. In contrast to downsampling, this protocol is purity-preserving. (b) Effect on the underlying classical signal, expanded from N_0 to $N_0 2^{\tilde{n}}$ samples per axis. The protocol acts as a nearest neighborhood interpolation: if one neglects the normalization, the input values are duplicated along all axes, for a number of times determined by the padding parameter.

panded register U, and apply a set of Hadamard gates $H^{\otimes n_U}$. The circuit representing Alg. 2 is depicted in Fig. 3a.

Algorithm 2 Quantum upsampling		
Input State $ \Psi\rangle_E$	\triangleright Encoding register (n_E qubits)	
Parameters		
Integer d	$\triangleright \#$ of signal dimensions	
Integer \tilde{n}	▷ Padding/axis size	
Protocol		
1: initialize padding reg	gister P to $ 0\rangle_P \triangleright n_P = d\tilde{n}$ qubits	
2: apply $H^{\hat{\otimes}n_U}$		
3: apply \mathcal{F}_E		
4: for $0 \le s \le d - 1$ do	▷ Padding rule	
5: for $0 \le p \le \tilde{n} - 1$	do	
6: append p th qubit to the bottom of E_i		
7: apply $\mathcal{F}_{U}^{\dagger}$		
8: apply $H^{\otimes n_U}$		
Result State $ \Omega\rangle_U$	\triangleright Upsampled register (n_U qubits)	

The upsampled quantum state $|\Omega\rangle_U$ encodes $N_0^d 2^{d\bar{n}}$ entries, with each axes expanded by a factor $2^{\bar{n}}$ and sampling rates $f_i^U = f_i^D \tilde{N}$. In contrast to downsampling, which is a lossy operation, the upsampling scheme is unitary, always yielding pure states at its output and thus fully preserving the amplitude encoding. Once again, output retrieval requires the knowledge of the probabilities $p_{\mathbf{w}}$ of observing $|\mathbf{w}\rangle_U$ at the output of the upsampled register, for all $\mathbf{w} = (w_0, w_1, ..., w_{d-1})$ and $w_i \in \{0, N_1\}$. These are related to the input via

$$p_{\mathbf{w}} = \frac{\mathcal{S}_{\bar{\mathbf{w}}}}{I_U} , \qquad (8)$$

where $\bar{\mathbf{w}} = (w_0 \mod N_0, ..., w_{d-1} \mod N_0)$ and $I_U = I_E N_1^d$ being the output intensity. As shown in

Fig. 3b, Eq. (8) describes a nearest neighbor interpolation scheme, in which each data sample is repeated for \tilde{N} times. The resulting signal is piece-wise constant, making the protocol expecially suited for sharp transitions, which are optimally preserved by this kind of interpolation technique [20]. An explicit derivation of this result is shown in Appendix B.

Alternatively, upsampling can be implemented by substituting Steps 1 and 7 of Alg. 2 with a set of C-NOT gates for each subregister, each controlled on the most significant qubit of E_i and targeting all the padding qubits $p \in P_i$. Although equivalent, Alg. 2 uses fewer entangling gates: it is thus preferable complexity wise. See [12] for a related example.

Combined, Alg. 1 and Alg. 2 allow to approximate multiple sampling rates, without explicitly re-digitizing the source signal. An example of their use for a onedimensional digital signal is shown in Fig. 4. Both resampling schemes combine three key operations: the quantum Fourier transforms, the rectangular filter of the Hadamard gates and the tensor structure imposed by encoding multiple signal axes. Alternative schemes can be developed by modifying each of these elements. By substituting the QFTs, e.g. with the Haar or other wavelets transforms [22], it is possible to resample signals in a different domain (than the frequency one). Similarly, modifying the filter - by replacing the Hadamard gates with other unitaries - can produce outcomes different than block-averaging and nearest-neighbor interpolation, enabling higher-order polynomial interpolation or potentially addressing aliasing. Finally, different encodings can be explored, e.g. the flexible (FRQI) and the novel enhanced (NEQR) quantum representations used for image processing [4, 5].



FIG. 4. Simulation of quantum resampling. A truncated sinc function (shifted by a unit value along the y-axis), is initially sampled over 256 possible values at 256 Hz in [0, 2]s and encoded in a register of 9 qubits (left), whose computational basis indexes are obtained by discretizing and normalizing the x-axis (the sampling interval). The signal is first downsampled to 32 Hz (6 qubits) via Alg. 1(center) and then upsampled to 512 Hz (10 qubits) beyond the original resolution, employing Alg. 2 (right). The insets at [0.56, 0.59]s show the effects of block-averaging and nearest neighbour interpolation. For the latter, upsampled values vary due to artefacts and statistical fluctuations. The simulation is conducted with *Qiskit Aer* [21] and $256^2 \times 2^n$ shots, with n being the number of output qubits.

III. COMPLEXITY

In this section, we compare the resource cost of the quantum resampling algorithms with that of their classical counterparts, i.e. block-averaging and nearest neighbor interpolation. First, consider a signal of N_0^d samples (encoded in $n_E = d n_0$ qubits), downsampled to $N_0^d/2^{d\tilde{n}}$ points $(n_D = d n_1 \text{ qubits, with } n_1 = n_0 - \tilde{n}).$ The gate complexity of our algorithm is dominated by the cost of performing a MD-QFT - i.e. d QFTs - on the encoding register, followed by its inverse on the downsampled one. Their total cost can be upper bounded at $\mathcal{O}(2dn_0^2)$, namely an exponential advantage over classical block-averaging in terms of number of operations only, as the latter is instead linear in the input samples, i.e. $\mathcal{O}(2^{dn_0})$. Advantage holds whenever the cost of state preparation scales at most polynomially with the number of encoding resources. This condition is met in several scenarios, exactly when the input is efficiently and classically integrable [11, 23-25], or approximately, using trainable quantum generator [26–28]. Similarly, preparation schemes leveraging quantum hardware [10, 29] offer efficient implementations by passing state preparation.

The overall complexity of our schemes must account for the cost of output recovery, i.e.: the full knowledge of the probability distribution described by Eq. (7). Assuming that the input intensity I_E can be stored in a classical memory during the encoding, we can estimate the output values as $O_{\mathbf{m}} = I_D p_{\mathbf{m}}$, with I_D being the downsampled intensity and $0 \leq O_{\mathbf{m}} \leq L - 1 \forall \mathbf{m}$. Although easily liftable, this assumption simplifies our analysis. Let Mdenote the total number of shots, i.e. experimental repetitions of the sequence

encoding \rightarrow downsampling \rightarrow measurement,

and let $f_{\mathbf{m}}$ be the observed frequency for the **m**-th outcome. For each outcome, the measurement statistics is effectively modelled by a Bernoulli trial [30]: we either obtain the **m**-th outcome with success probability $p_{\mathbf{m}}$, or

not with failure probability of $1 - p_{\mathbf{m}}$. Under the normal approximation and at 98% confidence level, we can estimate $p_{\mathbf{m}}$ as

$$p_{\mathbf{m}} = f_{\mathbf{m}} \pm 2\sqrt{\frac{f_{\mathbf{m}}(1-f_{\mathbf{m}})}{M}} , \qquad (9)$$

with mean square error (MSE) $\Delta O_{\mathbf{m}}^2 = 4 I_D^2 f_{\mathbf{m}} (1 - f_{\mathbf{m}})/M$. Consider the arithmetic average of the MSE over all sample values, $\delta^2 = 2^{-dn_1} \sum_{\mathbf{m}} \Delta O_{\mathbf{m}}^2$. Similarly, let $\langle O \rangle = 2^{-dn_1} \sum_{\mathbf{m}} O_{\mathbf{m}}$ be the average sample output. Within our assumptions, $\langle O \rangle = 2^{-dn_1} I_D = 2^{-dn_0} I_E$, namely $\langle O \rangle$ is independent of the signal size, and thus a property of the underlying source process. Then, exploiting the HM-GM-AM-QM inequality [31] we find

$$\delta^2 \le \frac{4\langle O \rangle^2}{M} 2^{dn_1} . \tag{10}$$

whose detailed derivation can be found in Appendix C. Thus, the number of shots required by a full output reconstruction with mean uncertainty δ^2 is

$$M = \mathcal{O}\left(4\langle O \rangle^2 \delta^{-2} 2^{dn_1}\right) \ . \tag{11}$$

We further specialize to digital signals, for which samples can take only L possible values: when these are maximal and uniformly distributed, we have $M = \mathcal{O}\left(4L^2\delta^{-2}2^{dn_1}\right)$, i.e. an average of $4L^2$ shots has to be collected per sample. The latter bound is looser than Eq. (11), but it provides a "worst-case scenario" conservative estimation, valid for all outputs.

Alternatively, the reconstruction can be achieved without prior knowledge of the input intensity, by normalizing the output frequencies to the maximum one, i.e. $\max_{\mathbf{m}} f_{\mathbf{m}}$. Nonetheless, the asymptotic scaling of Mremains comparable to Eq. (11), which still provides a more general bound. Both procedures can be optimized by tracking the fluctuations at the output, accumulating statistics until the desired error threshold is reached. Combining the gate and statistical costs of the algorithm (the latter taken in the worst-case scenario), we get its overall complexity, $\mathscr{D}_{q} = \mathcal{O}(8dL^{2}\delta^{-2}n_{0}^{2}2^{dn_{1}})$. An advantage holds whenever $\mathscr{D}_{q} < \mathscr{D}_{c}$, with $\mathscr{D}_{c} = \mathcal{O}(2^{dn_{0}})$ being the classical cost, namely

$$\frac{1}{d} \left[2c + 3 + 2\log_2 n_0 + \log_2 \left(\frac{d}{\delta^2} \right) \right] \le \tilde{n} < n_0 , \quad (12)$$

where the bit depth $c = \log_2 L$ indicates the number of classical bits encoding the output. Here, the upper bound represents the impossibility of discarding more qubits than those initially considered. As shown in Fig. 5, the advantage grows approximately with the exponential of the downsampling ratio, i.e. $\mathcal{O}(n_0^2 2^{n_E/n_D})$, and thus increases with both the input sampling rate and the number of qubits discarded. As an example, Alg. 1 can be employed to enhance the signal-to-noise ratios in oversampled noisy signals, as higher downsampling ratios are achievable without violating the Nyquist limit.

Analogous arguments hold for the upsampling protocol, in which the signal is expanded from N_0^d (n_E qubits) to $N_0^d 2^{d\tilde{n}}$ samples ($n_U = d n_1$ qubits, where now $n_1 = n_0 + \tilde{n}$). Similarly, Alg. 2 has a combined gate and statistical complexity of $\mathscr{U}_q = \mathcal{O}(8dL^2\delta^{-2}n_1^2 2^{dn_1})$, where the cost of padding is dominated by the QFTs and is thus negligible. Conversely, classical nearest neighbour interpolation scales as $\mathscr{U}_c = \mathcal{O}(2^{dn_1})$. Independently of the output size, we get $\mathscr{U}_q > \mathscr{U}_c$, meaning that the quantum upsampling protocol shows no advantage per se.

Both algorithms can work as subroutines in more complex tasks, such as image edge detection [32] or classification - as it is often the case in classical signal processing scenarios - bypassing the cost of output reconstruction and recovering the full computational advantage. Similarly to [12], Alg. 2 can enhance state preparation schemes - especially those lacking in scalability by interpolating few (efficiently prepared) amplitudes to higher-dimensional registers. In this scenario, no reconstruction is required, and the gate overhead added by Alg. 2 scales quadratically in n_1 .

The resource requirement of our algorithms can be reduced through a patch-based approach. Specifically, a N_0^d signal can be split into $\mathcal{B} = N_0/N_b$ smaller, nonoverlapping patches of side N_b , which can be processed independently by Algs. 1 and 2. Such procedure is best suited to slowly varying signals, as it requires qubits to be discarded (appended) for each patch, eventually increasing aliasing. This strategy restricts the size of the QFTs to match that of the register encoding the patch, reducing the circuit size with improved NISQ-compatibility [33].

IV. CONCLUSIONS

In this work, we introduced two reciprocal quantum algorithms for multidimensional signal resampling. Combining amplitude encoding with the QFT, our protocols downsample (or upsample) all the multidimensional signal axes in parallel, modifying the number of most signif-



FIG. 5. Quantum advantage bounds for the downsampling algorithms, as a function of the number of encoding and discarded qubits per signal axis. The dotted red line and the solid black one represent the lower and upper bounds of Eq. (12), respectively. The colormap expresses the ratio $(\mathscr{D}_c/\mathscr{D}_q)$, taken as figure of merit for quantifying advantage. (a) One-dimensional binary signal. (b) Two-dimensional 8-bit signal (e.g. a traditional grey-scale digital image). In both cases, the averaged MSE is set to $\delta^2 = 1/L^2$, i.e. by requiring fluctuations to be no larger than the bit-resolution.

icant encoding qubits. We provided closed formulae and a detailed derivation of their outputs. Both downsampling and upsampling demonstrate exponential speedups over classical methods, in terms of operations only. For the former, an advantage persists despite the overhead introduced by the necessity of repeating the procedure to retrieve the full output. For the latter, the same overhead completely offsets the quantum speedup, attaining the same resource cost of its classical counterpart. Despite this limitation, the unitarity of upsampling provides easier compatibility with subsequent quantum routines, e.g. in state preparation.

Our framework focuses on frequency, but it can be adapted to different forms of quantum (or quantuminspired) resampling, e.g. beyond the frequency domain, introducing higher-order filters (e.g. polynomial or spline interpolations) or different encoding schemes. Indeed, our results pave the way towards a comprehensive quantum library of such methods, whose range of applicability goes beyond signal processing, namely in quantum machine learning [14, 34], e.g. when compressing the parameter space in kernel methods.

CODE AVAILABILITY

The underlying code employed for this study is openly available in GitHub [35].

- A. Oppenheim and R. Schafer, *Discrete-Time Signal Processing* (Pearson Education, 2011).
- [2] S. E. Venegas-Andraca and S. Bose, Storing, processing, and retrieving an image using quantum mechanics, in *Quantum Information and Computation*, Vol. 5105 (SPIE, 2003) pp. 137 – 147.
- [3] F. Yan, A. M. Iliyasu, and S. E. Venegas-Andraca, A survey of quantum image representations, Quantum Inf. Process. 15, 1 (2016).
- [4] Y. Zhang, K. Lu, Y. Gao, and M. Wang, NEQR: a novel enhanced quantum representation of digital images, Quantum Inf. Process. 12, 2833 (2013).
- [5] P. Q. Le, F. Dong, and K. Hirota, A flexible representation of quantum images for polynomial preparation, image compression, and processing operations, Quantum Inf. Process. 10, 63 (2011).
- [6] F. Yan and S. E. Venegas-Andraca, *Quantum Image Processing* (Springer, 2020).
- [7] J. I. Latorre, Image compression and entanglement (2005), arXiv:quant-ph/0510031 [quant-ph].
- [8] R.-G. Zhou, W. Hu, P. Fan, and H. Ian, Quantum realization of the bilinear interpolation method for NEQR, Sci. Rep. 7, 2511 (2017).
- [9] Y. Peng, X. Li, Z. Liang, and Y. Wang, Hybrid quantum downsampling networks (2024), arXiv:2405.16375 [quant-ph].
- [10] S. Roncallo, L. Maccone, and C. Macchiavello, Quantum jpeg, AVS Quantum Sci. 5, 043803 (2023).
- [11] A. Kitaev and W. A. Webb, Wavefunction preparation and resampling using a quantum computer (2009), arXiv:0801.0342 [quant-ph].
- [12] S. Ramos-Calderer, Efficient quantum interpolation of natural data, Phys. Rev. A 106, 062427 (2022).
- [13] C. Stefanski, V. Markov, and C. Gonciulea, Quantum amplitude interpolation (2022), arXiv:2203.08758 [quantph].

ACKNOWLEDGMENTS

E.T. acknowledges support from the PNRR MUR Project PE0000023-NQSTI. S.R. acknowledges support from the PRIN MUR Project 2022RATBS4. L.M. acknowledges support from from the U.S. Department of Energy, Office of Science, National Quantum Information Science Research Centers, Superconducting Quantum Materials and Systems Center (SQMS) under Contract No. DE-AC02-07CH11359. C.M. acknowledges support from the National Research Centre for HPC, Big Data and Quantum Computing, PNRR MUR Project CN0000013-ICSC. E.T. is grateful to G.F. Conte, L. Frau, A.E. Mazzarone, D. Rinaldi and D. Tona for the helpful feedback and discussions.

- [14] M. Schuld and F. Petruccione, *Machine Learning with Quantum Computers* (Springer, 2021).
- [15] M. A. Nielsen and I. L. Chuang, Quantum Computation and Quantum Information: 10th Anniversary Edition (Cambridge University Press, 2010).
- [16] L. Hales and S. Hallgren, An improved quantum Fourier transform algorithm and applications, in *Proceedings 41st Annual Symposium on Foundations of Computer Science* (2000) pp. 515–525.
- [17] T. Moir, Rudiments of Signal Processing and Systems (Springer International Publishing, 2021).
- [18] C. Shannon, Communication in the presence of noise, Proc. IRE 37, 10 (1949).
- [19] J. O. Smith, Mathematics of the discrete Fourier transform (DFT) (Stanford, 2007).
- [20] J. Russ and F. Neal, *The Image Processing Handbook* (CRC Press, 2018).
- [21] A. Javadi-Abhari, M. Treinish, K. Krsulich, C. J. Wood, J. Lishman, J. Gacon, S. Martiel, P. D. Nation, L. S. Bishop, A. W. Cross, B. R. Johnson, and J. M. Gambetta, Quantum computing with Qiskit (2024), arXiv:2405.08810 [quant-ph].
- [22] C. P. Fijany, Amirand Williams, Quantum wavelet transforms: Fast algorithms and complete circuits, in *Quan*tum Computing and Quantum Communications, edited by C. P. Williams (Springer, 1999) pp. 10–33.
- [23] L. Grover and T. Rudolph, Creating superpositions that correspond to efficiently integrable probability distributions (2002), arXiv:quant-ph/0208112 [quant-ph].
- [24] A. N. Soklakov and R. Schack, Efficient state preparation for a register of quantum bits, Phys. Rev. A 73, 012307 (2006).
- [25] D. Ramacciotti, A. I. Lefterovici, and A. F. Rotundo, Simple quantum algorithm to efficiently prepare sparse states, Phys. Rev. A 110, 032609 (2024).
- [26] S. Lloyd and C. Weedbrook, Quantum generative adversarial learning, Phys. Rev. Lett. 121, 040502 (2018).

- [27] S. Daimon and Y.-i. Matsushita, Quantum circuit generation for amplitude encoding using a transformer decoder, Phys. Rev. Appl. 22, L041001 (2024).
- [28] P.-L. Dallaire-Demers and N. Killoran, Quantum generative adversarial networks, Phys. Rev. A 98, 012324 (2018).
- [29] V. Giovannetti, S. Lloyd, and L. Maccone, Quantum random access memory, Phys. Rev. Lett. 100, 160501 (2008).
- [30] A. Rotondi, P. Pedroni, and A. Pievatolo, Probability, Statistics and Simulation: With Application Programs Written in R (Springer, 2022).
- [31] H. Sedrakyan and N. Sedrakyan, The HM-GM-AM-QM inequalities, in *Algebraic Inequalities* (Springer International Publishing, Cham, 2018) pp. 21–43.
- [32] X.-W. Yao, H. Wang, Z. Liao, M.-C. Chen, J. Pan, J. Li, K. Zhang, X. Lin, Z. Wang, Z. Luo, W. Zheng, J. Li,

M. Zhao, X. Peng, and D. Suter, Quantum image processing and its application to edge detection: Theory and experiment, Phys. Rev. X 7, 031041 (2017).

- [33] J. Preskill, Quantum computing in the NISQ era and beyond, Quantum 2, 79 (2018).
- [34] I. Kankeu, S. G. Fritsch, G. Schönhoff, E. Mounzer, P. Lukowicz, and M. Kiefer-Emmanouilidis, Quantuminspired embeddings projection and similarity metrics for representation learning (2025), arXiv:2501.04591 [cs.CL].
- [35] E. Tumbiolo, (2025), https://github.com/GitTumb/ QuFRes.
- [36] J. Tyson, Operator-Schmidt decompositions and the fourier transform, with applications to the operatorschmidt numbers of unitaries, J. Phys. A: Math. Gen. 36, 6813–6819 (2003).
- [37] W. Ledermann, *Complex Numbers* (Dordrecht, 2013).

APPENDIX A: QUANTUM DOWNSAMPLING

In this section, we compute the step-by-step evolution of a signal downsampled via Alg. 1. For simplicity, we consider d = 1, namely a one-dimensional discrete signal $S = (S_0, S_1, ..., S_{N_0-1})$, with N_0 samples that are encoded into a quantum register of $n_E = n_0$ qubits as

$$\left|\Psi\right\rangle_{E} = \sum_{e=0}^{N_{0}-1} \alpha_{e} \left|e\right\rangle , \qquad (A1)$$

where $\alpha_e = \sqrt{S_e/I_E}$, $I_E = \sum_{e=0}^{N_0-1} S_e$ and with *e* labelling both classical sample values and computational basis states. Starting from $|\psi\rangle_E$, our algorithm discards its most \tilde{n} most significant qubits, associated with the highest spatial frequencies, reducing the number of samples in the signal to $N_1 = N_0/\tilde{N}$, where $\tilde{N} = 2^{\tilde{n}}$, $N_1 = 2^{n_1}$ and $n_1 = n - \tilde{n}$. We use pedix \bullet_1 and diacritic $\tilde{\bullet}$ to label indices running from 0 to N_1 and from 0 to \tilde{N} , respectively. Conversely, any unmarked index is intended to assume values from 0 to N_0 , unless otherwise stated. Since for one-dimensional signals $n_E(n_D) = n_0(n_1)$, we suppress the $|\bullet\rangle_E$ notation.

The quantum downsampling protocol begins by applying n_0 Hadamard gates

$$H^{\otimes n_0} |\psi\rangle = \sum_{z} \beta_z |z\rangle , \qquad (A2)$$

where
$$\beta_z = \frac{1}{\sqrt{N_0}} \sum_e \alpha_e (-1)^{e \odot z}$$
, (A3)

and with \odot being the modulo-2 bitwise inner product [15]. This is followed by a quantum Fourier transform F_0 , performed on the full register

$$F_0\left(\sum_{z}\beta_z |z\rangle\right) = \frac{1}{\sqrt{N_0}} \sum_{z,k} \beta_z \omega_{N_0}^{kz} |k\rangle \quad , \tag{A4}$$

where $\omega_N = \exp\{2\pi i/N\}$ denotes the N-th root of the imaginary unity. Then, the \tilde{n} most significant qubits of the register are discarded, i.e. by a partial trace on the subspace $\tilde{\mathcal{H}}$ spanned by such qubits. For simplicity, we postpone this computation, which commutes with any local operation applied to the remaining qubits. We decompose the two subregisters as

$$k = N_1 k + k_1 av{A5}$$

yielding $\omega_{N_0}^{kz} = \omega_{\tilde{N}}^{\tilde{k}z} \cdot \omega_{N_0}^{k_1 z}$, and

$$\frac{1}{\sqrt{N_0}} \sum_{z} \underbrace{\sum_{\tilde{k}} \omega_{\tilde{N}}^{\tilde{k}z} \left| \tilde{k} \right\rangle}_{\left| \tilde{\chi}_z \right\rangle} \bigotimes \beta_z \underbrace{\sum_{k_1} \omega_{N_0}^{k_1 z} \left| k_1 \right\rangle}_{\left| \chi_z^1 \right\rangle} . \tag{A6}$$

Alternatively, the same formula can be recovered from the Schmidt decomposition of the QFT operator [36]. Following Alg. 1, we apply the inverse QFT F_1^{\dagger} to the n_1 -register, yielding

$$\left(\mathbb{1}_{\tilde{n}} \otimes F_{1}^{\dagger}\right) \left(\frac{1}{\sqrt{N_{0}}} \sum_{z} |\tilde{\chi}_{z}\rangle \otimes |\chi_{z}^{1}\rangle\right) = \frac{1}{\sqrt{N_{0}N_{1}}} \sum_{z} |\tilde{\chi}_{z}\rangle \otimes \beta_{z} \sum_{k_{1},t_{1}} \underbrace{\omega_{N_{0}}^{k_{1}z} \omega_{N_{1}}^{-k_{1}t_{1}}}_{\omega_{N_{0}}^{-k_{1}(z-\tilde{N}t_{1})}} |t_{1}\rangle , \qquad (A7)$$

where $\mathbb{1}_{\tilde{n}}$ is the identity operator on the $\tilde{\mathcal{H}}$ subspace. The protocol ends with a final set of Hadamard gates on the n_1 -register, getting

$$|\Phi\rangle = \frac{1}{\sqrt{N_0}N_1} \sum_{z} |\tilde{\chi}_z\rangle \otimes |\lambda_z^1\rangle , \qquad (A8)$$

where
$$|\lambda_z\rangle = \sum_{k_1, t_1, l_1} \beta_z \omega_{N_0}^{k_1(z-\tilde{N}t_1)} (-1)^{t_1 \odot l_1} |l_1\rangle$$
 (A9)

We now explicitly discuss the discarding operation. The density operator associated with the state $|\Phi\rangle$ is

$$|\Phi\rangle\langle\Phi| = \frac{1}{N_0 N_1^2} \sum_{z,z'} |\tilde{\chi}_z\rangle\langle\tilde{\chi}_{z'}| \otimes |\lambda_z^1\rangle\langle\lambda_{z'}^1| , \qquad (A10)$$

Tracing on $\tilde{\mathcal{H}}$ gives

$$\rho_1 = \operatorname{Tr}_{\tilde{\mathcal{H}}}\left[|\Phi\rangle\langle\Phi|\right] = \sum_{z,z'} \sum_{\tilde{k}} \omega_{\tilde{N}}^{\tilde{k}(z-z')} \left|\lambda_z^1\rangle\langle\lambda_z^1\right| \quad .$$
(A11)

Observe that

$$\sum_{\tilde{k}} \omega_{\tilde{N}}^{\tilde{k}(z-z')} = \begin{cases} \tilde{N} & \text{if } z \equiv z' \mod \tilde{N} \\ 0 & \text{otherwise} \end{cases}$$
(A12)

which acts as a modular Kronecker delta between z and z' [37]. Condition A12 implies that we can decompose z, z'into $z = \tilde{N}j_1 + \tilde{r}$ and $z' = \tilde{N}j'_1 + \tilde{r}$, with $j_1(j'_1)$ being the results of the division of z (z') by \tilde{N} and \tilde{r} the common remainder. We thus decompose the summations in z, z' as $\sum_{z} \sum_{z'} \to \sum_{j_1} \sum_{j'_1} \sum_{\tilde{r}}$. Recalling Eq. (A2), together with the definition of the modulo-2 bitwise inner product, gives

$$\beta_{z} = \beta_{\tilde{N}j_{1}+\tilde{r}} = \sum_{e_{1},\tilde{e}} \frac{1}{\sqrt{N_{0}}} \alpha_{e_{1},\tilde{e}} (-1)^{j_{1} \odot e_{1}} (-1)^{\tilde{r} \odot \tilde{e}} , \qquad (A13)$$

and similarly for $\beta_{z'}$. Here, e_1, \tilde{e} and e undergo $e = \tilde{N}e_1 + \tilde{e}$, which parametrizes the integers formed of the n_1 most and \tilde{n} least significant bits of e, respectively. Then

$$\rho_{1} = \frac{1}{N_{1}^{3}N_{0}} \sum_{\substack{k_{1},e_{1}\tilde{e},\tilde{e},\tilde{e}',\tilde{r} \\ k_{1}',e_{1}'}} \sum_{\substack{k_{1},e_{1}\tilde{e},\tilde{e}',\tilde{r} \\ k_{1}',e_{1}'}} \alpha_{e_{1},\tilde{e}} \alpha_{e_{1}',\tilde{e}'}^{*} (-1)^{\tilde{r} \odot(\tilde{e}+\tilde{e}')} \omega_{N_{0}}^{\tilde{r}(k_{1}-k_{1}')} \\
\times \sum_{\substack{j_{1},t_{1} \\ j_{1}',t_{1}'}} \phi(k_{1},e_{1},j_{1},t_{1}) \phi^{*}(k_{1}',e_{1}',j_{1}',t_{1}') \sum_{l_{1},l_{1}'} (-1)^{t_{1} \odot l_{1}} (-1)^{t_{1}' \odot l_{1}'} |l_{1}\rangle \langle l_{1}'| , \qquad (A14)$$

where

$$\phi(k_1, e_1, j_1, t_1) = \omega_{N_1}^{k_1(j_1 - t_1)} (-1)^{(e_1 \odot j_1)} .$$
(A15)

Observe that ϕ is periodic with period N_1 in each of its arguments. Hence, it is invariant under the transformation

$$\begin{cases} j_1 \to t_1 + p_1 \\ j'_1 \to t'_1 + p'_1 \end{cases} \Rightarrow \sum_{t_1=0}^{N_1-1} \sum_{p_1=-t_1}^{N_1-1-t_1} = \sum_{p_1=0}^{N_1-1} \sum_{t_1=0}^{N_1-1} , \qquad (A16)$$

and similarly for t'_1 and p'_1 . We combine this change of variable with the identity

$$\sum_{a}^{N-1} (-1)^{a \odot (c+b)} = N \delta_{c,b} , \qquad (A17)$$

where $\delta_{c,b}$ is the usual Kronecker delta - which follows from the involutivity of the Hadamard operator. Then Eq. (A14) simplifies to

$$\rho_{1} = \frac{1}{\tilde{N}N_{1}^{2}} \sum_{\substack{k_{1},e_{1}\tilde{e},\tilde{e}',\tilde{r}\\k_{1}',e_{1}'}} \alpha_{e_{1},\tilde{e}} \, \alpha_{e_{1}',\tilde{e}'}^{*}(-1)^{\tilde{r} \odot(\tilde{e}+\tilde{e}')} \omega_{N_{0}}^{\tilde{r}(k_{1}-k_{1}')} \sum_{p_{1},p_{1}'} \omega_{N_{1}}^{k_{1}p_{1}}(-1)^{p_{1}\odot e_{1}} \omega_{N_{1}}^{k_{1}'p_{1}'}(-1)^{p_{1}'\odot e_{1}'} |e_{1}\rangle\langle e_{1}'| \quad .$$
(A18)

We recover the downsampled signal from the output probabilities $p(m_1) = \text{Tr} \left[\rho_1 | m_1 \rangle \langle m_1 | \right]$, which in our case read

$$p(m_1) = \frac{1}{\tilde{N}N_1^2} \sum_{k_1,k_1'} \sum_{\tilde{e},\tilde{e}',\tilde{r}} \alpha_{m_1,\tilde{e}} \, \alpha_{m_1,\tilde{e}'}^* (-1)^{\tilde{r} \odot(\tilde{e}+\tilde{e}')} \omega_{N_0}^{\tilde{r}(k_1-k_1')} \sum_{p_1,p_1'} \omega_{N_1}^{k_1p_1} \omega_{N_1}^{k_1'p_1'} (-1)^{m_1 \odot(p_1+p_1')} \,. \tag{A19}$$

Exploiting the periodicity of the sums on p_1 and p'_1 appearing, we set $p_1 \rightarrow p'_1 + h_1$, getting

$$\begin{cases} \omega_{N_1}^{k_1 p_1} \omega_{N_1}^{k'_1 p'_1} \to \omega_{N_1}^{p'_1(k_1 - k'_1)} \omega_{N_1}^{h_1 k_1} \\ (-1)^{m_1 \odot (p_1 + p'_1)} \to (-1)^{m_1 \odot h_1} \end{cases}.$$
(A20)

We complete the computations by observing that: (i) the summations on p'_1 and k_1 give δ_{k_1,k'_1} and $\delta_{h,0}$, respectively; (2) due to Eq. (A17), the summation on \tilde{r} yields $\delta_{\tilde{e},\tilde{e}'}$; ending up with

$$p(m_1) = \tilde{N} \sum_{\tilde{e}} |\alpha_{m_1,\tilde{e}}|^2 = \sum_{\tilde{e}} \frac{\mathcal{S}_{\tilde{N}m_1+\tilde{e}}}{I_D} , \qquad (A21)$$

where $I_D = N/I_E$. Since Alg. 1 processes distinct subregisters in parallel, the extension to the multidimensional case is immediate. This shows that the protocol performs a block-average of the input samples, whose output size depends on the number of qubits discarded from the original register.

APPENDIX B: QUANTUM UPSAMPLING

In this section, we compute the evolution of a signal extended to a bigger support via our quantum upsampling algorithm. Without loss of generality, we consider once again the one-dimensional case, and employ the same conventions discussed in the previous section. The upsampling scheme is a padding of the previously considered state $|\Psi\rangle_E$ in the frequency domain, using a set of \tilde{n} uninitialized qubits, which are added to the register as the new most significant ones. This operation increases the number of qubits from n_0 to $n_1 = n_0 + \tilde{n}$. We refer to the \tilde{n} -register as padding register. Therefore, we consider as input $|0\rangle^{\otimes \tilde{n}} \otimes |\Psi\rangle_E$. First, the algorithm applies a set of Hadamard gates to all the qubits, producing

$$\frac{1}{\sqrt{\tilde{N}}} \sum_{\tilde{p}} |\tilde{p}\rangle \otimes \sum_{z} \beta_{z} |z\rangle , \qquad (B1)$$

where β_z is defined as in Eq. (A2). Then, we perform a QFT on the initial n_0 qubits, while the padding register remains unaltered. Then

$$\frac{1}{\sqrt{\tilde{N}N_0}} \sum_{\tilde{p}} |\tilde{p}\rangle \otimes \sum_{z,k} \beta_z \omega_{N_0}^{kz} |k\rangle .$$
(B2)

The tensor product states $|\tilde{p}\rangle \otimes |k\rangle$ are in a one-to-one correspondence with $|t_1\rangle = |N_0\tilde{p} + k\rangle$. This change of summation variables gives

$$\frac{1}{\sqrt{\tilde{N}N_0}} \sum_z \sum_{t_1} \beta_z \omega_{N_0}^{t_1 z} |t_1\rangle . \tag{B3}$$

The last two steps of the protocol consist of a full inverse QFT, followed by Hadamard gates applied to all qubits

$$\frac{1}{\sqrt{N_1^3}} \sum_{z} \beta_z \sum_{v_1, l_1} \underbrace{\sum_{t_1} \omega_{N_1}^{t_1(\tilde{N}z - v_1)}}_{N_1 \delta_{\tilde{N}z, v_1}} (-1)^{v_1 \odot l_1} |l_1\rangle .$$
(B4)

Inserting the definition of β_z in Eq. (B4), and using the same arguments that lead us to Eq. (A2), we finally get

$$|\Omega\rangle = \frac{1}{\sqrt{N_1}N_0} \sum_{e,l} \sum_{\tilde{l}} \alpha_e \underbrace{\sum_{z} (-1)^{z \odot (e+l)}}_{N_0 \delta_{e,l}} |l\rangle \left|\tilde{l}\right\rangle = \frac{1}{\sqrt{N_1}} \sum_{e} \sum_{\tilde{l}} \alpha_e \left|e\right\rangle \left|\tilde{l}\right\rangle , \tag{B5}$$

where $l_1 = \tilde{N}l + \tilde{l}$. Once again, the output signal is recovered from the probabilities of each outcome in the computational basis. From the Born rule

$$p(w_1) = p(\tilde{N}w + \tilde{w}) = \left| \left(\langle w | \otimes \langle \tilde{w} | \right) | \Phi \rangle_U \right|^2 = \frac{1}{N_1} |\alpha_w|^2 = \mathcal{S}_w / I_U .$$
(B6)

Here $I_U = I_E N_1$. This holds for any w'_1 such that $w'_1 \equiv w_1 \mod \tilde{N}$, meaning that all the samples, with indexes in the same congruence class modulo \tilde{N} , will be identical. The generalization to the multidimensional case is guaranteed by the MD-QFT acting independently on distinct subregisters, leading to Eq. (8). This shows that the protocol actually performs a nearest-neighbor interpolation, whose size depends on the number of padding qubits added to the initial register.

APPENDIX C: STATISTICS OF OUTPUT RECONSTRUCTION

In this section, we discuss the size of the statistical sample, i.e. the number of shots M required to reconstruct the output at a given uncertainty. As stated in the main text, this cost dampens the advantage of our algorithms with respect to their counterparts, imposing a trade-off between efficiency and output quality. Conversely, the theoretical advantage is recovered whenever a full output reconstruction is not needed.

Without loss of generality, we limit our discussion to the downsampling of a one-dimensional signal, from N_0 (n_0 qubits) to $N_1 = N_0/2^{\tilde{n}}$ (n_1 qubits), with output intensity I_D . Let p_m be the probability mass function associated to a computational basis measurement on the output state, with $m \in \{0, N_1 - 1\}$. Due to the probabilistic nature of our encoding, output sample values can be expressed as $O_m = I_D p_m$. Following the main text, their maximum likelihood estimator at a 98% confidence level is

$$O_m = I_D f_m \pm 2I_D \sqrt{\frac{f_m (1 - f_m)}{M}} \tag{C1}$$

where f_m is again the occurrence frequency for the *m*-th output. Let δ^2 be the arithmetic average of the squared standard error over all samples, namely

$$\delta^2 = \frac{1}{N} \sum_{m=0}^{N_1 - 1} \Delta O_m^2 = \frac{4I_D^2}{M} \sum_{m=0}^{N_1 - 1} (f_m - f_m^2) .$$
(C2)

From the QM-AM-GM-HM inequality [31]

$$\sum_{m=0}^{N_1-1} \frac{f_m^2}{N_1} \ge \frac{1}{N_1^2} \left(\sum_m f_m\right)^2 = \frac{1}{N_1^2} , \qquad (C3)$$

leading us to

$$\delta^2 \le \frac{4I_D^2}{M} \left(\frac{N_1 - 1}{N_1^2}\right) \le \frac{4I_D^2}{M} \frac{1}{N_1} , \qquad (C4)$$

where the last inequality holds for sufficiently large signals, i.e. $N_1 \gg 1$. Let $\langle O \rangle = I_D/N_1$ be the average sample value in the output, then

$$M \le 4\langle O \rangle^2 N_1 \delta^{-2} . \tag{C5}$$

Eq. (C5) gives a signal-dependent bound. Conversely a looser, all-purpose bound directly follows when the output samples have the highest possible values, namely $\langle O \rangle = L - 1$.